
pox Documentation

Release 0.3.4

Mike McKerns

Feb 20, 2024

CONTENTS

1	pox module documentation	1
1.1	shutils module	1
1.2	utils module	8
2	pox scripts documentation	17
2.1	pox script	17
3	pox: utilities for filesystem exploration and automated builds	27
3.1	About Pox	27
3.2	Major Features	27
3.3	Current Release	28
3.4	Development Version	28
3.5	Installation	28
3.6	Requirements	28
3.7	Basic Usage	28
3.8	More Information	29
3.9	Citation	30
4	Indices and tables	41
	Python Module Index	43
	Index	45

POX MODULE DOCUMENTATION

1.1 shutils module

shell utilities for user environment and filesystem exploration

```
class Popen(args, bufsize=- 1, executable=None, stdin=None, stdout=None, stderr=None,
             preexec_fn=None, close_fds=True, shell=False, cwd=None, env=None, univer-
             sal_newlines=None, startupinfo=None, creationflags=0, restore_signals=True,
             start_new_session=False, pass_fds=(), *, user=None, group=None, extra_groups=None,
             encoding=None, errors=None, text=None, umask=- 1)
```

Bases: `object`

Execute a child program in a new process.

For a complete description of the arguments see the Python documentation.

Parameters

- **args** – A string, or a sequence of program arguments.
- **bufsize** – supplied as the buffering argument to the `open()` function when creating the `stdin/stdout/stderr` pipe file objects
- **executable** – A replacement program to execute.
- **stdin** – These specify the executed programs' standard input, standard output and standard error file handles, respectively.
- **and stderr** (*stdout*) – These specify the executed programs' standard input, standard output and standard error file handles, respectively.
- **preexec_fn** – (POSIX only) An object to be called in the child process just before the child is executed.
- **close_fds** – Controls closing or inheriting of file descriptors.
- **shell** – If true, the command will be executed through the shell.
- **cwd** – Sets the current directory before the child is executed.
- **env** – Defines the environment variables for the new process.
- **text** – If true, decode `stdin`, `stdout` and `stderr` using the given encoding (if set) or the system default otherwise.
- **universal_newlines** – Alias of `text`, provided for backwards compatibility.
- **and creationflags** (*startupinfo*) –
- **restore_signals** (*POSIX only*) –

- **start_new_session** (*POSIX only*) –
- **group** (*POSIX only*) –
- **extra_groups** (*POSIX only*) –
- **user** (*POSIX only*) –
- **umask** (*POSIX only*) –
- **pass_fds** (*POSIX only*) –
- **and_errors** (*encoding*) – Text mode encoding and error handling to use for file objects `stdin`, `stdout` and `stderr`.

Variables `stdout`, `stderr`, `pid`, `returncode` (`stdin`), –

Create new Popen instance.

```
__class_getitem__ = <bound method GenericAlias of <class 'subprocess.Popen'>>
__del__ (_maxsize=9223372036854775807, _warn=<built-in function warn>)
__enter__ ()
__exit__ (exc_type, value, traceback)
__repr__ ()
    Return repr(self).
_check_timeout (endtime, orig_timeout, stdout_seq, stderr_seq, skip_check_and_raise=False)
    Convenience for checking if a timeout has expired.
_child_created = False
_close_pipe_fds (p2cread, p2cwrite, c2pread, c2pwrite, errread, errwrite)
_communicate (input, endtime, orig_timeout)
_execute_child (args, executable, preexec_fn, close_fds, pass_fds, cwd, env, startupinfo, creationflags, shell, p2cread, p2cwrite, c2pread, c2pwrite, errread, errwrite, restore_signals, gid, gids, uid, umask, start_new_session)
    Execute program (POSIX version)
_get_devnull ()
_get_handles (stdin, stdout, stderr)
    Construct and return tuple with IO objects: p2cread, p2cwrite, c2pread, c2pwrite, errread, errwrite
_handle_exitstatus (sts, waitstatus_to_exitcode=<built-in function waitstatus_to_exitcode>, _WIFSTOPPED=<built-in function WIFSTOPPED>, _WSTOPSIG=<built-in function WSTOPSIG>)
    All callers to this function MUST hold self._waitpid_lock.
_internal_poll (_deadstate=None, _waitpid=<built-in function waitpid>, _WNOHANG=1, _ECHILD=10)
    Check if child process has terminated. Returns returncode attribute.

    This method is called by __del__, so it cannot reference anything outside of the local scope (nor can any methods it calls).
_posix_spawn (args, executable, env, restore_signals, p2cread, p2cwrite, c2pread, c2pwrite, errread, errwrite)
    Execute program using os.posix_spawn().
_remaining_time (endtime)
    Convenience for _communicate when computing timeouts.
```

_save_input (*input*)

_stdin_write (*input*)

_translate_newlines (*data, encoding, errors*)

_try_wait (*wait_flags*)

All callers to this function MUST hold self._waitpid_lock.

_wait (*timeout*)

Internal implementation of wait() on POSIX.

communicate (*input=None, timeout=None*)

Interact with process: Send data to stdin and close it. Read data from stdout and stderr, until end-of-file is reached. Wait for process to terminate.

The optional “input” argument should be data to be sent to the child process, or None, if no data should be sent to the child. communicate() returns a tuple (stdout, stderr).

By default, all communication is in bytes, and therefore any “input” should be bytes, and the (stdout, stderr) will be bytes. If in text mode (indicated by self.text_mode), any “input” should be a string, and (stdout, stderr) will be strings decoded according to locale encoding, or by “encoding” if set. Text mode is triggered by setting any of text, encoding, errors or universal_newlines.

kill ()

Kill the process with SIGKILL

poll ()

Check if child process has terminated. Set and return returncode attribute.

send_signal (*sig*)

Send a signal to the process.

terminate ()

Terminate the process with SIGTERM

property universal_newlines

wait (*timeout=None*)

Wait for child process to terminate; returns self.returncode.

env (*variable, all=True, minimal=False*)

get dict of environment variables of the form {variable:value}

Parameters

- **variable** (*str*) – name or partial name for environment variable.
- **all** (*bool, default=True*) – if False, only return the first match.
- **minimal** (*bool, default=False*) – if True, remove all duplicate paths.

Returns dict of strings of environment variables.

<p>Warning: selecting all=False can lead to unexpected matches of <i>variable</i>.</p>

Examples

```
>>> env('*PATH')
{'PYTHONPATH': '.', 'PATH': '.:usr/bin:/bin:/usr/sbin:/sbin'}
```

find (*patterns*, *root=None*, *recurse=True*, *type=None*, *verbose=False*)
get the path to a file or directory

Parameters

- **patterns** (*str*) – name or partial name of items to search for.
- **root** (*str*, *default=None*) – path of top-level directory to search.
- **recurse** (*bool*, *default=True*) – if True, recurse downward from *root*.
- **type** (*str*, *default=None*) – a search filter.
- **verbose** (*bool*, *default=False*) – if True, be verbose about the search.

Returns a list of string paths.

Notes

on some OS, *recursion* can be specified by recursion depth (*int*), and *patterns* can be specified with basic pattern matching. Also, multiple patterns can be specified by splitting patterns with a `;`. The *type* can be one of {*file*, *dir*, *link*, *socket*, *block*, *char*}.

Examples

```
>>> find('pox*', root='..')
['/Users/foo/pox/pox', '/Users/foo/pox/scripts/pox_launcher.py']
>>>
>>> find('*shutils*;*init*')
['/Users/foo/pox/pox/shutils.py', '/Users/foo/pox/pox/__init__.py']
```

getHOME ()
get the full path of the user's home directory

Parameters **None** –

Returns string path of the directory, or None if home can not be determined.

getROOT ()
get the path corresponding to the root of the current drive

Parameters **None** –

Returns string path of the directory.

getSEP (*type=""*)
get the separator string for the given type of separator

Parameters **type** (*str*, *default=''*) – one of {*sep*, *line*, *path*, *ext*, *alt*}.

Returns separator string.

getSHELL ()
get the name (e.g. *bash*) of the current command shell

Parameters **None** –

Returns string name of the shell, or None if name can not be determined.

getUSER()

get the login name of the current user

Parameters None –

Returns string name of the user.

homedir()

get the full path of the user's home directory

Parameters None –

Returns string path of the directory, or None if home can not be determined.

minpath(*path*, *pathsep=None*)

remove duplicate paths from given set of paths

Parameters

- **path**(*str*) – path string (e.g. '/Users/foo/bin:/bin:/sbin:/usr/bin').
- **pathsep**(*str*, *default=None*) – path separator (e.g. ':').

Returns string composed of one or more paths, with duplicates removed.

Examples

```
>>> minpath(' ../Users/foo/bin: ../Users/foo/bar/bin:/Users/foo/bin')
' ../Users/foo/bin:/Users/foo/bar/bin'
```

mkdir(*path*, *root=None*, *mode=None*)

create a new directory in the root directory

create a directory at *path* and any necessary parents (i.e. `mkdir -p`). Default mode is read/write/execute for 'user' and 'group', and then read/execute otherwise.

Parameters

- **path**(*str*) – string name of the new directory.
- **root**(*str*, *default=None*) – path at which to build the new directory.
- **mode**(*str*, *default=None*) – octal read/write permission [default: 0o775].

Returns string absolute path for new directory.

rmtree(*path*, *self=True*, *ignore_errors=False*, *onerror=None*)

remove directories in the given path

Parameters

- **path**(*str*) – path string of root of directories to delete.
- **self**(*bool*, *default=True*) – if False, delete subdirectories, not path.
- **ignore_errors**(*bool*, *default=False*) – if True, silently ignore errors.
- **onerror**(*function*, *default=None*) – custom error handler.

Returns None

Notes

If `self=False`, the directory indicated by `path` is left in place, and its subdirectories are erased. If `self=True`, `path` is also removed.

If `ignore_errors=True`, errors are ignored. Otherwise, `onerror` is called to handle the error with arguments (`func`, `path`, `exc_info`), where `func` is `os.listdir`, `os.remove`, or `os.rmdir`; `path` is the argument to the function that caused it to fail; and `exc_info` is a tuple returned by `sys.exc_info()`. If `ignore_errors=False` and `onerror=None`, an exception is raised.

rootdir()

get the path corresponding to the root of the current drive

Parameters `None` –

Returns string path of the directory.

sep(*type*=")

get the separator string for the given type of separator

Parameters `type` (`str`, `default=' '`) – one of {`sep`, `line`, `path`, `ext`, `alt`}.

Returns separator string.

shellsub(*command*)

parse the given command to be formatted for remote shell invocation

secure shell (`ssh`) can be used to send and execute commands to remote machines (using `ssh <hostname> <command>`). Additional escape characters are needed to enable the command to be correctly formed and executed remotely. `shellsub` attempts to parse the given command string correctly so that it can be executed remotely with `ssh`.

Parameters `command` (`str`) – the command to be executed remotely.

Returns the parsed command string.

shelltype()

get the name (e.g. `bash`) of the current command shell

Parameters `None` –

Returns string name of the shell, or `None` if name can not be determined.

stripDups(*path*, *pathsep*=None)

remove duplicate paths from given set of paths

Parameters

- **path** (`str`) – path string (e.g. `'/Users/foo/bin:/bin:/sbin:/usr/bin'`).
- **pathsep** (`str`, `default=None`) – path separator (e.g. `:`).

Returns string composed of one or more paths, with duplicates removed.

Examples

```
>>> minpath('..:/Users/foo/bin:..:/Users/foo/bar/bin:/Users/foo/bin')
'..:/Users/foo/bin:/Users/foo/bar/bin'
```

username()

get the login name of the current user

Parameters None –

Returns string name of the user.

walk (*root*, *patterns*='*', *recurse*=True, *folders*=False, *files*=True, *links*=True)

walk directory tree and return a list matching the requested pattern

Parameters

- **root** (*str*) – path of top-level directory to search.
- **patterns** (*str*, *default*='*') – (partial) name of items to search for.
- **recurse** (*bool*, *default*=True) – if True, recurse downward from *root*.
- **folders** (*bool*, *default*=False) – if True, include folders in the results.
- **files** (*bool*, *default*=True) – if True, include files in results.
- **links** (*bool*, *default*=True) – if True, include links in results.

Returns a list of string paths.

Notes

patterns can be specified with basic pattern matching. Additionally, multiple patterns can be specified by splitting patterns with a ;.

Examples

```
>>> walk('..', patterns='pox*')
['/Users/foo/pox/pox', '/Users/foo/pox/scripts/pox_launcher.py']
>>>
>>> walk('.', patterns='*shutils*;*init*')
['/Users/foo/pox/pox/shutils.py', '/Users/foo/pox/pox/__init__.py']
```

where (*name*, *path*, *pathsep*=None)

get the full path for the given name string on the given search path.

Parameters

- **name** (*str*) – name of file, folder, etc to find.
- **path** (*str*) – path string (e.g. '/Users/foo/bin:/bin:/sbin:/usr/bin').
- **pathsep** (*str*, *default*=None) – path separator (e.g. :)

Returns the full path string.

Notes

if pathsep is not provided, the OS default will be used.

whereis (*prog*, *all=False*)

get path to the given program

search the standard binary install locations for the given executable.

Parameters

- **prog** (*str*) – name of an executable to search for (e.g. python).
- **all** (*bool*, *default=True*) – if True, return a list of paths found.

Returns string path of the executable, or list of path strings.

which (*prog*, *allow_links=True*, *ignore_errors=True*, *all=False*)

get the path of the given program

search the user's paths for the given executable.

Parameters

- **prog** (*str*) – name of an executable to search for (e.g. python).
- **allow_links** (*bool*, *default=True*) – if False, replace link with fullpath.
- **ignore_errors** (*bool*, *default=True*) – if True, ignore search errors.
- **all** (*bool*, *default=False*) – if True, get list of paths for executable.

Returns if all=True, get a list of string paths, else return a string path.

1.2 utils module

higher-level shell utilities for user environment and filesystem exploration

convert (*files*, *platform=None*, *pathsep=None*, *verbose=True*)

convert text files to given platform type

Ensure given files use the appropriate `os.linesep` and other formatting.

Parameters

- **files** (*list(str)*) – a list of filenames.
- **platform** (*str*, *default=None*) – platform name as in `os.name`.
- **pathsep** (*str*, *default=None*) – the path separator string.
- **verbose** (*bool*, *default=True*) – if True, print debug statements..

Returns 0 if converted, otherwise return 1.

disk_used (*path*)

get the disk usage for the given directory

Parameters **path** (*str*) – path string.

Returns int corresponding to disk usage in blocks.

expandvars (*string*, *ref*=None, *secondref*={})
 expand shell variables in string

Expand shell variables of form `$var` and `${var}`. Unknown variables are left unchanged. If a reference dictionary (*ref*) is provided, restrict lookups to *ref*. A second reference dictionary (*secondref*) can also be provided for failover searches. If *ref* is not provided, lookup variables are defined by the user's environment variables.

Parameters

- **string** (*str*) – a string with shell variables.
- **ref** (*dict* (*str*), *default*=None) – a dict of lookup variables.
- **secondref** (*dict* (*str*), *default*={}) – a failover reference dict.

Returns string with the selected shell variables substituted.

Examples

```
>>> expandvars('found:: $PYTHONPATH')
'found:: ../Users/foo/lib/python3.4/site-packages'
>>>
>>> expandvars('found:: $PYTHONPATH', ref={})
'found:: $PYTHONPATH'
```

findpackage (*package*, *root*=None, *all*=False, *verbose*=True, *recurse*=True)
 retrieve the path(s) for a package

Parameters

- **package** (*str*) – name of the package to search for.
- **root** (*str*, *default*=None) – path string of top-level directory to search.
- **all** (*bool*, *default*=False) – if True, return everywhere package is found.
- **verbose** (*bool*, *default*=True) – if True, print messages about the search.
- **recurse** (*bool*, *default*=True) – if True, recurse down the root directory.

Returns string path (or list of paths) where package is found.

Notes

On some OS, recursion can be specified by recursion depth (an integer). `findpackage` will do standard pattern matching for package names, attempting to match the head directory of the distribution.

getLines (*sequence*, *start*, *stop*, *step*=1, *sequential*=True, *inclusive*=True)
 slice a list of strings, then join the remaining strings

If *start* is not found in the sequence, slice from the beginning. If *stop* is not found in the sequence, slice to the end.

Parameters

- **sequence** (*list*) – an ordered sequence of elements.
- **start** (*int*) – index for start of the slice.
- **stop** (*int*) – index for stop position in the sequence.
- **step** (*int*, *default*=1) – indices until next member of the slice.

- **sequential** (*bool*, *default=True*) – if *True*, *start* must precede *stop*.
- **inclusive** (*bool*, *default=True*) – if *True*, include *stop* in the slice.

Returns string produced by slicing the given sequence and joining the elements.

getVars (*path*, *ref=None*, *sep=None*)

get a dictionary of all variables defined in path

Extract shell variables of form `$var` and `${var}`. Unknown variables will raise an exception. If a reference dictionary (*ref*) is provided, first try the lookup in *ref*. Failover from *ref* will lookup variables defined in the user's environment variables. Use *sep* to override the path separator (`os.sep`).

Parameters

- **path** (*str*) – a path string with shell variables.
- **ref** (*dict* (*str*), *default=None*) – a dict of lookup variables.
- **sep** (*str*, *default=None*) – the path separator string.

Returns dict of shell variables found in the given path string.

Examples

```
>>> getvars('$HOME/stuff')
{'HOME': '/Users/foo'}
```

getvars (*path*, *ref=None*, *sep=None*)

get a dictionary of all variables defined in path

Extract shell variables of form `$var` and `${var}`. Unknown variables will raise an exception. If a reference dictionary (*ref*) is provided, first try the lookup in *ref*. Failover from *ref* will lookup variables defined in the user's environment variables. Use *sep* to override the path separator (`os.sep`).

Parameters

- **path** (*str*) – a path string with shell variables.
- **ref** (*dict* (*str*), *default=None*) – a dict of lookup variables.
- **sep** (*str*, *default=None*) – the path separator string.

Returns dict of shell variables found in the given path string.

Examples

```
>>> getvars('$HOME/stuff')
{'HOME': '/Users/foo'}
```

index_join (*sequence*, *start*, *stop*, *step=1*, *sequential=True*, *inclusive=True*)

slice a list of strings, then join the remaining strings

If *start* is not found in the sequence, slice from the beginning. If *stop* is not found in the sequence, slice to the end.

Parameters

- **sequence** (*list*) – an ordered sequence of elements.
- **start** (*int*) – index for start of the slice.

- **stop** (*int*) – index for stop position in the sequence.
- **step** (*int*, *default=1*) – indices until next member of the slice.
- **sequential** (*bool*, *default=True*) – if True, *start* must precede *stop*.
- **inclusive** (*bool*, *default=True*) – if True, include *stop* in the slice.

Returns string produced by slicing the given sequence and joining the elements.

index_slice (*sequence*, *start*, *stop*, *step=1*, *sequential=False*, *inclusive=False*)
get the slice for a given sequence

Slice indices are determined by the positions of *start* and *stop*. If *start* is not found in the sequence, slice from the beginning. If *stop* is not found in the sequence, slice to the end.

Parameters

- **sequence** (*list*) – an ordered sequence of elements.
- **start** (*int*) – index for start of the slice.
- **stop** (*int*) – index for stop position in the sequence.
- **step** (*int*, *default=1*) – indices until next member of the slice.
- **sequential** (*bool*, *default=False*) – if True, *start* must precede *stop*.
- **inclusive** (*bool*, *default=False*) – if True, include *stop* in the slice.

Returns slice corresponding to given *start*, *stop*, and *step*.

kbytes (*text*)
convert memory text to the corresponding value in kilobytes

Parameters **text** (*str*) – string corresponding to an abbreviation of size.

Returns int representation of text.

Examples

```
>>> kbytes('10K')
10
>>>
>>> kbytes('10G')
10485760
```

makeTarget (*path*, *host=None*, *user=None*, *loopback=False*)
build string for a remote connection of the form `[[user@]host:]path`

Parameters

- **path** (*str*) – path string for location of target on (remote) filesystem.
- **host** (*str*, *default=None*) – string name/ip address of (remote) host.
- **user** (*str*, *default=None*) – user name on (remote) host.
- **loopback** (*bool*, *default=False*) – if True, ensure *host* is used.

Returns a remote connection string.

Notes

if `loopback=True` and `host=None`, then `host` will be set to `localhost`.

makefilter (*list*=[], *separator*=';')

generate a filter pattern from list of strings

Parameters

- **list** (*list* (*str*), *default*=[]) – a list of filter elements.
- **separator** (*str*, *default*='; ') – the separator string.

Returns a string composed of filter elements joined by the separator.

parseTarget (*path*, *loopback*=False, *login_flag*=False)

parse remote connection string of the form [[user@] host :] path

Parameters

- **path** (*str*) – remote connection string.
- **loopback** (*bool*, *default*=False) – if True, ensure *host* is used.
- **login_flag** (*bool*, *default*=False) – if True, prepend user with -l.

Returns a tuple of the form (*user*, *host*, *path*).

Notes

if `loopback=True` and `host=None`, then `host` will be set to `localhost`.

parse_remote (*path*, *loopback*=False, *login_flag*=False)

parse remote connection string of the form [[user@] host :] path

Parameters

- **path** (*str*) – remote connection string.
- **loopback** (*bool*, *default*=False) – if True, ensure *host* is used.
- **login_flag** (*bool*, *default*=False) – if True, prepend user with -l.

Returns a tuple of the form (*user*, *host*, *path*).

Notes

if `loopback=True` and `host=None`, then `host` will be set to `localhost`.

pattern (*list*=[], *separator*=';')

generate a filter pattern from list of strings

Parameters

- **list** (*list* (*str*), *default*=[]) – a list of filter elements.
- **separator** (*str*, *default*='; ') – the separator string.

Returns a string composed of filter elements joined by the separator.

prunedict (*dict*, *counter*="", *minimum*=False, *all*=True)

return a dict of items with the max (or min) count of the given counter.

Get the items from a dict that have the maximum number of the *counter* (e.g. *counter*='3' counts occurrences of '3') in the values. Use *minimum*=True to search for minimum number of occurrences of *counter*.

Parameters

- **dict** (*dict*) – dict with iterables as values (e.g. lists, strings, etc).
- **counter** (*str*, *default*='') – the item to count.
- **minimum** (*bool*, *default*=*False*) – if True, find min count (else, max).
- **all** (*bool*, *default*=*True*) – if False, only return the first result.

Returns dict of items composed of the entries with the min (or max) count.

Examples

```
>>> z = ['zero', 'one', 'two', 'three', '4', 'five', 'six', 'seven', '8', '9/81']
>>> z = dict(enumerate(z))
>>> selectdict(z, counter='e')
{3: 'three', 7: 'seven'}
>>> selectdict(z, counter='e', minimum=True)
{8: '8', 9: '9/81', 2: 'two', 4: '4', 6: 'six'}
>>>
>>> y = {1: [1,2,3], 2: [4,5,6], 3: [1,3,5]}
>>> selectdict(y, counter=3)
{1: [1, 2, 3], 3: [1, 3, 5]}
>>> selectdict(y, counter=3, minumim=True)
{2: [4, 5, 6]}
```

prunelist (*iterable*, *counter*="", *minimum*=*False*, *reverse*=*False*, *all*=*True*)

find items in iterable with the max (or min) count of the given counter.

Find the items in an iterable that have the maximum number of *counter* (e.g. *counter*='3' counts occurrences of '3'). Use *minimum*=*True* to search for the minimum number of occurrences of the *counter*.

Parameters

- **iterable** (*list*) – an iterable of iterables (e.g. lists, strings, etc).
- **counter** (*str*, *default*='') – the item to count.
- **minimum** (*bool*, *default*=*False*) – if True, find min count (else, max).
- **reverse** (*bool*, *default*=*False*) – if True, reverse order of the results.
- **all** (*bool*, *default*=*True*) – if False, only return the first result.

Returns list of items in the iterable with the min (or max) count.

Examples

```
>>> z = ['zero', 'one', 'two', 'three', '4', 'five', 'six', 'seven', '8', '9/81']
>>> select(z, counter='e')
['three', 'seven']
>>> select(z, counter='e', minimum=True)
['two', '4', 'six', '8', '9/81']
>>>
>>> y = [[1,2,3], [4,5,6], [1,3,5]]
>>> select(y, counter=3)
[[1, 2, 3], [1, 3, 5]]
>>> select(y, counter=3, minumim=True, all=False)
[4, 5, 6]
```

remote (*path*, *host=None*, *user=None*, *loopback=False*)
build string for a remote connection of the form `[[user@]host:]path`

Parameters

- **path** (*str*) – path string for location of target on (remote) filesystem.
- **host** (*str*, *default=None*) – string name/ip address of (remote) host.
- **user** (*str*, *default=None*) – user name on (remote) host.
- **loopback** (*bool*, *default=False*) – if True, ensure *host* is used.

Returns a remote connection string.

Notes

if *loopback=True* and *host=None*, then *host* will be set to *localhost*.

replace (*file*, *sub={}*, *outfile=None*)
make text substitutions given by *sub* in the given file

Parameters

- **file** (*str*) – path to original file.
- **sub** (*dict* (*str*)) – dict of string replacements `{old:new}`.
- **outfile** (*str*, *default=None*) – if given, don't overwrite original file.

Returns None

Notes

replace uses regular expressions, thus a pattern may be used as *old* text. *replace* can fail if order of substitution is important.

replaceText (*file*, *sub={}*, *outfile=None*)
make text substitutions given by *sub* in the given file

Parameters

- **file** (*str*) – path to original file.
- **sub** (*dict* (*str*)) – dict of string replacements `{old:new}`.
- **outfile** (*str*, *default=None*) – if given, don't overwrite original file.

Returns None

Notes

replace uses regular expressions, thus a pattern may be used as *old* text. *replace* can fail if order of substitution is important.

select (*iterable*, *counter="*, *minimum=False*, *reverse=False*, *all=True*)
find items in *iterable* with the max (or min) count of the given *counter*.

Find the items in an *iterable* that have the maximum number of *counter* (e.g. *counter='3'* counts occurrences of '3'). Use *minimum=True* to search for the minimum number of occurrences of the *counter*.

Parameters

- **iterable** (*list*) – an iterable of iterables (e.g. lists, strings, etc).
- **counter** (*str*, *default*='') – the item to count.
- **minimum** (*bool*, *default*=*False*) – if *True*, find min count (else, max).
- **reverse** (*bool*, *default*=*False*) – if *True*, reverse order of the results.
- **all** (*bool*, *default*=*True*) – if *False*, only return the first result.

Returns list of items in the iterable with the min (or max) count.

Examples

```
>>> z = ['zero', 'one', 'two', 'three', '4', 'five', 'six', 'seven', '8', '9/81']
>>> select(z, counter='e')
['three', 'seven']
>>> select(z, counter='e', minimum=True)
['two', '4', 'six', '8', '9/81']
>>>
>>> y = [[1, 2, 3], [4, 5, 6], [1, 3, 5]]
>>> select(y, counter=3)
[[1, 2, 3], [1, 3, 5]]
>>> select(y, counter=3, minimum=True, all=False)
[4, 5, 6]
```

selectdict (*dict*, *counter*="", *minimum*=*False*, *all*=*True*)

return a dict of items with the max (or min) count of the given counter.

Get the items from a dict that have the maximum number of the *counter* (e.g. *counter*='3' counts occurrences of '3') in the values. Use *minimum*=*True* to search for minimum number of occurrences of *counter*.

Parameters

- **dict** (*dict*) – dict with iterables as values (e.g. lists, strings, etc).
- **counter** (*str*, *default*='') – the item to count.
- **minimum** (*bool*, *default*=*False*) – if *True*, find min count (else, max).
- **all** (*bool*, *default*=*True*) – if *False*, only return the first result.

Returns dict of items composed of the entries with the min (or max) count.

Examples

```
>>> z = ['zero', 'one', 'two', 'three', '4', 'five', 'six', 'seven', '8', '9/81']
>>> z = dict(enumerate(z))
>>> selectdict(z, counter='e')
{3: 'three', 7: 'seven'}
>>> selectdict(z, counter='e', minimum=True)
{8: '8', 9: '9/81', 2: 'two', 4: '4', 6: 'six'}
>>>
>>> y = {1: [1, 2, 3], 2: [4, 5, 6], 3: [1, 3, 5]}
>>> selectdict(y, counter=3)
{1: [1, 2, 3], 3: [1, 3, 5]}
>>> selectdict(y, counter=3, minimum=True)
{2: [4, 5, 6]}
```

wait_for (*path*, *sleep*=1, *tries*=150, *ignore_errors*=False)
block execution by waiting for a file to appear at the given path

Parameters

- **path** (*str*) – the path string to watch for the file.
- **sleep** (*float*, *default*=1) – the time between checking results.
- **tries** (*int*, *default*=150) – the number of times to try.
- **ignore_errors** (*bool*, *default*=False) – if True, ignore timeout error.

Returns None

Notes

if the file is not found after the given number of tries, an error will be thrown unless `ignore_error=True`.

using `subproc = Popen(...)` and `subproc.wait()` is usually a better approach. However, when a handle to the subprocess is unavailable, waiting for a file to appear at a given path is a decent last resort.

which_python (*version*=False, *lazy*=False, *fullpath*=True, *ignore_errors*=True)
get the command to launch the selected version of python

`which_python` composes a command string that can be used to launch the desired python executable. The user's path is searched for the executable, unless `lazy=True` and thus only a lazy-evaluating command (e.g. `which python`) is produced.

Parameters

- **version** (*bool*, *default*=False) – if True, include the version of python.
- **lazy** (*bool*, *default*=False) – if True, build a lazy-evaluating command.
- **fullpath** (*bool*, *default*=True) – if True, provide the full path.
- **ignore_errors** (*bool*, *default*=True) – if True, ignore path search errors.

Returns string of the implicit or explicit location of the python executable.

Notes

if version is given as an int or float, include the version number in the command string.

if the executable is not found, an error will be thrown unless `ignore_error=True`.

POX SCRIPTS DOCUMENTATION

2.1 pox script

run any of the pox commands from the command shell prompt

Notes

- To get help, type `$ pox` at a shell terminal prompt.
- For a list of available functions, type `$ pox "help('pox')"`.
- Incorrect function invocation will print the function's documentation.

Examples:

```
$ pox "which('python') "  
/usr/bin/python
```

citation()
print the citation

convert (*files*, *platform=None*, *pathsep=None*, *verbose=True*)
convert text files to given platform type

Ensure given files use the appropriate `os.linesep` and other formatting.

Parameters

- **files** (*list(str)*) – a list of filenames.
- **platform** (*str*, *default=None*) – platform name as in `os.name`.
- **pathsep** (*str*, *default=None*) – the path separator string.
- **verbose** (*bool*, *default=True*) – if True, print debug statements..

Returns 0 if converted, otherwise return 1.

disk_used (*path*)
get the disk usage for the given directory

Parameters **path** (*str*) – path string.

Returns int corresponding to disk usage in blocks.

env (*variable*, *all=True*, *minimal=False*)
get dict of environment variables of the form {*variable:value*}

Parameters

- **variable** (*str*) – name or partial name for environment variable.
- **all** (*bool*, *default=True*) – if False, only return the first match.
- **minimal** (*bool*, *default=False*) – if True, remove all duplicate paths.

Returns dict of strings of environment variables.

Warning: selecting `all=False` can lead to unexpected matches of *variable*.

Examples

```
>>> env('*PATH')
{'PYTHONPATH': '.', 'PATH': '.:usr/bin:/bin:/usr/sbin:/sbin'}
```

expandvars (*string*, *ref=None*, *secondref={}*)
expand shell variables in string

Expand shell variables of form `$var` and `${var}`. Unknown variables are left unchanged. If a reference dictionary (*ref*) is provided, restrict lookups to *ref*. A second reference dictionary (*secondref*) can also be provided for failover searches. If *ref* is not provided, lookup variables are defined by the user's environment variables.

Parameters

- **string** (*str*) – a string with shell variables.
- **ref** (*dict(str)*, *default=None*) – a dict of lookup variables.
- **secondref** (*dict(str)*, *default={}*) – a failover reference dict.

Returns string with the selected shell variables substituted.

Examples

```
>>> expandvars('found:: $PYTHONPATH')
'found:: ./Users/foo/lib/python3.4/site-packages'
>>>
>>> expandvars('found:: $PYTHONPATH', ref={})
'found:: $PYTHONPATH'
```

find (*patterns*, *root=None*, *recurse=True*, *type=None*, *verbose=False*)
get the path to a file or directory

Parameters

- **patterns** (*str*) – name or partial name of items to search for.
- **root** (*str*, *default=None*) – path of top-level directory to search.
- **recurse** (*bool*, *default=True*) – if True, recurse downward from *root*.
- **type** (*str*, *default=None*) – a search filter.
- **verbose** (*bool*, *default=False*) – if True, be verbose about the search.

Returns a list of string paths.

Notes

on some OS, *recursion* can be specified by recursion depth (*int*), and *patterns* can be specified with basic pattern matching. Also, multiple patterns can be specified by splitting patterns with a `;`. The *type* can be one of {*file*, *dir*, *link*, *socket*, *block*, *char*}.

Examples

```
>>> find('pox*', root='..')
['/Users/foo/pox/pox', '/Users/foo/pox/scripts/pox_launcher.py']
>>>
>>> find('*shutils*;*init*')
['/Users/foo/pox/pox/shutils.py', '/Users/foo/pox/pox/__init__.py']
```

findpackage (*package*, *root=None*, *all=False*, *verbose=True*, *recurse=True*)
retrieve the path(s) for a package

Parameters

- **package** (*str*) – name of the package to search for.
- **root** (*str*, *default=None*) – path string of top-level directory to search.
- **all** (*bool*, *default=False*) – if True, return everywhere package is found.
- **verbose** (*bool*, *default=True*) – if True, print messages about the search.
- **recurse** (*bool*, *default=True*) – if True, recurse down the root directory.

Returns string path (or list of paths) where package is found.

Notes

On some OS, recursion can be specified by recursion depth (an integer). `findpackage` will do standard pattern matching for package names, attempting to match the head directory of the distribution.

getvars (*path*, *ref=None*, *sep=None*)
get a dictionary of all variables defined in path

Extract shell variables of form `$var` and `${var}`. Unknown variables will raise an exception. If a reference dictionary (*ref*) is provided, first try the lookup in *ref*. Failover from *ref* will lookup variables defined in the user's environment variables. Use *sep* to override the path separator (`os.sep`).

Parameters

- **path** (*str*) – a path string with shell variables.
- **ref** (*dict(str)*, *default=None*) – a dict of lookup variables.
- **sep** (*str*, *default=None*) – the path separator string.

Returns dict of shell variables found in the given path string.

Examples

```
>>> getvars('$HOME/stuff')
{'HOME': '/Users/foo'}
```

help (*function=None*)

homedir ()

get the full path of the user's home directory

Parameters **None** –

Returns string path of the directory, or None if home can not be determined.

index_join (*sequence, start, stop, step=1, sequential=True, inclusive=True*)

slice a list of strings, then join the remaining strings

If *start* is not found in the sequence, slice from the beginning. If *stop* is not found in the sequence, slice to the end.

Parameters

- **sequence** (*list*) – an ordered sequence of elements.
- **start** (*int*) – index for start of the slice.
- **stop** (*int*) – index for stop position in the sequence.
- **step** (*int, default=1*) – indices until next member of the slice.
- **sequential** (*bool, default=True*) – if True, *start* must precede *stop*.
- **inclusive** (*bool, default=True*) – if True, include *stop* in the slice.

Returns string produced by slicing the given sequence and joining the elements.

index_slice (*sequence, start, stop, step=1, sequential=False, inclusive=False*)

get the slice for a given sequence

Slice indicies are determined by the positions of *start* and *stop*. If *start* is not found in the sequence, slice from the beginning. If *stop* is not found in the sequence, slice to the end.

Parameters

- **sequence** (*list*) – an ordered sequence of elements.
- **start** (*int*) – index for start of the slice.
- **stop** (*int*) – index for stop position in the sequence.
- **step** (*int, default=1*) – indices until next member of the slice.
- **sequential** (*bool, default=False*) – if True, *start* must precede *stop*.
- **inclusive** (*bool, default=False*) – if True, include *stop* in the slice.

Returns slice corresponding to given *start*, *stop*, and *step*.

isfunction (*object*)

Return true if the object is a user-defined function.

Function objects provide these attributes: `__doc__` documentation string `__name__` name with which this function was defined `__code__` code object containing compiled function bytecode `__defaults__` tuple of any default values for arguments `__globals__` global namespace in which this function was defined `__annotations__` dict of parameter annotations `__kwdefaults__` dict of keyword only parameters with defaults

kbytes (*text*)

convert memory text to the corresponding value in kilobytes

Parameters **text** (*str*) – string corresponding to an abbreviation of size.

Returns int representation of text.

Examples

```
>>> kbytes('10K')
10
>>>
>>> kbytes('10G')
10485760
```

license ()

print the license

minpath (*path*, *pathsep=None*)

remove duplicate paths from given set of paths

Parameters

- **path** (*str*) – path string (e.g. `‘/Users/foo/bin:/bin:/sbin:/usr/bin’`).
- **pathsep** (*str*, *default=None*) – path separator (e.g. `‘:’`).

Returns string composed of one or more paths, with duplicates removed.

Examples

```
>>> minpath('.: /Users/foo/bin:./Users/foo/bar/bin:/Users/foo/bin')
'.:/Users/foo/bin:/Users/foo/bar/bin'
```

mkdir (*path*, *root=None*, *mode=None*)

create a new directory in the root directory

create a directory at *path* and any necessary parents (i.e. `mkdir -p`). Default mode is read/write/execute for ‘user’ and ‘group’, and then read/execute otherwise.

Parameters

- **path** (*str*) – string name of the new directory.
- **root** (*str*, *default=None*) – path at which to build the new directory.
- **mode** (*str*, *default=None*) – octal read/write permission [default: `0o775`].

Returns string absolute path for new directory.

parse_remote (*path*, *loopback=False*, *login_flag=False*)

parse remote connection string of the form `[[user@] host :] path`

Parameters

- **path** (*str*) – remote connection string.
- **loopback** (*bool*, *default=False*) – if True, ensure *host* is used.
- **login_flag** (*bool*, *default=False*) – if True, prepend user with `-l`.

Returns a tuple of the form (*user*, *host*, *path*).

Notes

if `loopback=True` and `host=None`, then `host` will be set to `localhost`.

pattern (*list*=[], *separator*=';')

generate a filter pattern from list of strings

Parameters

- **list** (*list* (*str*), *default*=[])*–* a list of filter elements.
- **separator** (*str*, *default*='; ')*–* the separator string.

Returns a string composed of filter elements joined by the separator.

remote (*path*, *host*=None, *user*=None, *loopback*=False)

build string for a remote connection of the form `[[user@]host:]path`

Parameters

- **path** (*str*)*–* path string for location of target on (remote) filesystem.
- **host** (*str*, *default*=None)*–* string name/ip address of (remote) host.
- **user** (*str*, *default*=None)*–* user name on (remote) host.
- **loopback** (*bool*, *default*=False)*–* if True, ensure *host* is used.

Returns a remote connection string.

Notes

if `loopback=True` and `host=None`, then `host` will be set to `localhost`.

replace (*file*, *sub*={}, *outfile*=None)

make text substitutions given by *sub* in the given file

Parameters

- **file** (*str*)*–* path to original file.
- **sub** (*dict* (*str*)*–* dict of string replacements {old:new}.
- **outfile** (*str*, *default*=None)*–* if given, don't overwrite original file.

Returns None

Notes

`replace` uses regular expressions, thus a pattern may be used as *old* text. `replace` can fail if order of substitution is important.

rmtree (*path*, *self*=True, *ignore_errors*=False, *onerror*=None)

remove directories in the given path

Parameters

- **path** (*str*)*–* path string of root of directories to delete.
- **self** (*bool*, *default*=True)*–* if False, delete subdirectories, not path.
- **ignore_errors** (*bool*, *default*=False)*–* if True, silently ignore errors.
- **onerror** (*function*, *default*=None)*–* custom error handler.

Returns None

Notes

If `self=False`, the directory indicated by `path` is left in place, and its subdirectories are erased. If `self=True`, `path` is also removed.

If `ignore_errors=True`, errors are ignored. Otherwise, `onerror` is called to handle the error with arguments (`func`, `path`, `exc_info`), where `func` is `os.listdir`, `os.remove`, or `os.rmdir`; `path` is the argument to the function that caused it to fail; and `exc_info` is a tuple returned by `sys.exc_info()`. If `ignore_errors=False` and `onerror=None`, an exception is raised.

rootdir()

get the path corresponding to the root of the current drive

Parameters None –

Returns string path of the directory.

select (*iterable*, *counter*="", *minimum*=False, *reverse*=False, *all*=True)

find items in iterable with the max (or min) count of the given counter.

Find the items in an iterable that have the maximum number of *counter* (e.g. `counter='3'` counts occurrences of '3'). Use `minimum=True` to search for the minimum number of occurrences of the *counter*.

Parameters

- **iterable** (*list*) – an iterable of iterables (e.g. lists, strings, etc).
- **counter** (*str*, *default*='') – the item to count.
- **minimum** (*bool*, *default*=False) – if True, find min count (else, max).
- **reverse** (*bool*, *default*=False) – if True, reverse order of the results.
- **all** (*bool*, *default*=True) – if False, only return the first result.

Returns list of items in the iterable with the min (or max) count.

Examples

```
>>> z = ['zero', 'one', 'two', 'three', '4', 'five', 'six', 'seven', '8', '9/81']
>>> select(z, counter='e')
['three', 'seven']
>>> select(z, counter='e', minimum=True)
['two', '4', 'six', '8', '9/81']
>>>
>>> y = [[1, 2, 3], [4, 5, 6], [1, 3, 5]]
>>> select(y, counter=3)
[[1, 2, 3], [1, 3, 5]]
>>> select(y, counter=3, minimum=True, all=False)
[4, 5, 6]
```

selectdict (*dict*, *counter*="", *minimum*=False, *all*=True)

return a dict of items with the max (or min) count of the given counter.

Get the items from a dict that have the maximum number of the *counter* (e.g. `counter='3'` counts occurrences of '3') in the values. Use `minimum=True` to search for minimum number of occurrences of *counter*.

Parameters

- **dict** (*dict*) – dict with iterables as values (e.g. lists, strings, etc).
- **counter** (*str*, *default*='') – the item to count.
- **minimum** (*bool*, *default*=False) – if True, find min count (else, max).
- **all** (*bool*, *default*=True) – if False, only return the first result.

Returns dict of items composed of the entries with the min (or max) count.

Examples

```
>>> z = ['zero', 'one', 'two', 'three', '4', 'five', 'six', 'seven', '8', '9/81']
>>> z = dict(enumerate(z))
>>> selectdict(z, counter='e')
{3: 'three', 7: 'seven'}
>>> selectdict(z, counter='e', minimum=True)
{8: '8', 9: '9/81', 2: 'two', 4: '4', 6: 'six'}
>>>
>>> y = {1: [1,2,3], 2: [4,5,6], 3: [1,3,5]}
>>> selectdict(y, counter=3)
{1: [1, 2, 3], 3: [1, 3, 5]}
>>> selectdict(y, counter=3, minumim=True)
{2: [4, 5, 6]}
```

sep (*type*=")

get the separator string for the given type of separator

Parameters **type** (*str*, *default*='') – one of {sep, line, path, ext, alt}.

Returns separator string.

shellsub (*command*)

parse the given command to be formatted for remote shell invocation

secure shell (ssh) can be used to send and execute commands to remote machines (using `ssh <hostname> <command>`). Additional escape characters are needed to enable the command to be correctly formed and executed remotely. *shellsub* attempts to parse the given command string correctly so that it can be executed remotely with ssh.

Parameters **command** (*str*) – the command to be executed remotely.

Returns the parsed command string.

shelltype ()

get the name (e.g. `bash`) of the current command shell

Parameters **None** –

Returns string name of the shell, or None if name can not be determined.

username ()

get the login name of the current user

Parameters **None** –

Returns string name of the user.

wait_for (*path*, *sleep*=1, *tries*=150, *ignore_errors*=False)

block execution by waiting for a file to appear at the given path

Parameters

- **path** (*str*) – the path string to watch for the file.
- **sleep** (*float*, *default=1*) – the time between checking results.
- **tries** (*int*, *default=150*) – the number of times to try.
- **ignore_errors** (*bool*, *default=False*) – if True, ignore timeout error.

Returns None

Notes

if the file is not found after the given number of tries, an error will be thrown unless `ignore_error=True`.

using `subproc = Popen(...)` and `subproc.wait()` is usually a better approach. However, when a handle to the subprocess is unavailable, waiting for a file to appear at a given path is a decent last resort.

walk (*root*, *patterns='*'*, *recurse=True*, *folders=False*, *files=True*, *links=True*)
walk directory tree and return a list matching the requested pattern

Parameters

- **root** (*str*) – path of top-level directory to search.
- **patterns** (*str*, *default='*'*) – (partial) name of items to search for.
- **recurse** (*bool*, *default=True*) – if True, recurse downward from *root*.
- **folders** (*bool*, *default=False*) – if True, include folders in the results.
- **files** (*bool*, *default=True*) – if True, include files in results.
- **links** (*bool*, *default=True*) – if True, include links in results.

Returns a list of string paths.

Notes

patterns can be specified with basic pattern matching. Additionally, multiple patterns can be specified by splitting patterns with a `;`.

Examples

```
>>> walk('.', patterns='pox*')
['/Users/foo/pox/pox', '/Users/foo/pox/scripts/pox_launcher.py']
>>>
>>> walk('.', patterns='*shutils*;*init*')
['/Users/foo/pox/pox/shutils.py', '/Users/foo/pox/pox/__init__.py']
```

where (*name*, *path*, *pathsep=None*)
get the full path for the given name string on the given search path.

Parameters

- **name** (*str*) – name of file, folder, etc to find.
- **path** (*str*) – path string (e.g. `'/Users/foo/bin:/bin:/sbin:/usr/bin'`).
- **pathsep** (*str*, *default=None*) – path separator (e.g. `:`)

Returns the full path string.

Notes

if pathsep is not provided, the OS default will be used.

whereis (*prog*, *all=False*)

get path to the given program

search the standard binary install locations for the given executable.

Parameters

- **prog** (*str*) – name of an executable to search for (e.g. python).
- **all** (*bool*, *default=True*) – if True, return a list of paths found.

Returns string path of the executable, or list of path strings.

which (*prog*, *allow_links=True*, *ignore_errors=True*, *all=False*)

get the path of the given program

search the user's paths for the given executable.

Parameters

- **prog** (*str*) – name of an executable to search for (e.g. python).
- **allow_links** (*bool*, *default=True*) – if False, replace link with fullpath.
- **ignore_errors** (*bool*, *default=True*) – if True, ignore search errors.
- **all** (*bool*, *default=False*) – if True, get list of paths for executable.

Returns if all=True, get a list of string paths, else return a string path.

which_python (*version=False*, *lazy=False*, *fullpath=True*, *ignore_errors=True*)

get the command to launch the selected version of python

`which_python` composes a command string that can be used to launch the desired python executable. The user's path is searched for the executable, unless `lazy=True` and thus only a lazy-evaluating command (e.g. `which python`) is produced.

Parameters

- **version** (*bool*, *default=False*) – if True, include the version of python.
- **lazy** (*bool*, *default=False*) – if True, build a lazy-evaluating command.
- **fullpath** (*bool*, *default=True*) – if True, provide the full path.
- **ignore_errors** (*bool*, *default=True*) – if True, ignore path search errors.

Returns string of the implicit or explicit location of the python executable.

Notes

if version is given as an int or float, include the version number in the command string.

if the executable is not found, an error will be thrown unless `ignore_error=True`.

POX: UTILITIES FOR FILESYSTEM EXPLORATION AND AUTOMATED BUILDS

3.1 About Pox

`pox` provides a collection of utilities for navigating and manipulating filesystems. This module is designed to facilitate some of the low level operating system interactions that are useful when exploring a filesystem on a remote host, where queries such as “*what is the root of the filesystem?*”, “*what is the user’s name?*”, and “*what login shell is preferred?*” become essential in allowing a remote user to function as if they were logged in locally. While `pox` is in the same vein of both the `os` and `shutil` builtin modules, the majority of its functionality is unique and compliments these two modules.

`pox` provides Python equivalents of several unix shell commands such as `which` and `find`. These commands allow automated discovery of what has been installed on an operating system, and where the essential tools are located. This capability is useful not only for exploring remote hosts, but also locally as a helper utility for automated build and installation.

Several high-level operations on files and filesystems are also provided. Examples of which are: finding the location of an installed Python package, determining if and where the source code resides on the filesystem, and determining what version the installed package is.

`pox` also provides utilities to enable the abstraction of commands sent to a remote filesystem. In conjunction with a registry of environment variables and installed utilities, `pox` enables the user to interact with a remote filesystem as if they were logged in locally.

`pox` is part of `pathos`, a Python framework for heterogeneous computing. `pox` is in active development, so any user feedback, bug reports, comments, or suggestions are highly appreciated. A list of issues is located at <https://github.com/uqfoundation/pox/issues>, with a legacy list maintained at <https://uqfoundation.github.io/project/pathos/query>.

3.2 Major Features

`pox` provides utilities for discovering the user’s environment:

- return the user’s name, current shell, and path to user’s home directory
- strip duplicate entries from the user’s `$PATH`
- lookup and expand environment variables from `${VAR}` to `value`

`pox` also provides utilities for filesystem exploration and manipulation:

- discover the path to a file, executable, directory, or symbolic link
- discover the path to an installed package

- parse operating system commands for remote shell invocation
- convert text files to platform-specific formatting

3.3 Current Release

The latest released version of `pox` is available from:

<https://pypi.org/project/pox>

`pox` is distributed under a 3-clause BSD license.

3.4 Development Version

You can get the latest development version with all the shiny new features at:

<https://github.com/uqfoundation>

If you have a new contribution, please submit a pull request.

3.5 Installation

`pox` can be installed with `pip`:

```
$ pip install pox
```

3.6 Requirements

`pox` requires:

- python (or pypy), **>=3.8**
- setuptools, **>=42**

3.7 Basic Usage

`pox` includes some basic utilities to connect to and automate exploration on local and remote filesystems. There are some basic functions to discover important locations:

```
>>> import pox
>>> pox.homedir()
'/Users/mmckerns'
>>> pox.rootdir()
'/'
```

or, you can interact with local and global environment variables:


```
>>> local = {'DEV': '${HOME}/dev', 'FOO_VERSION': '0.1', 'BAR_VERSION': '1.0'}
>>> pox.getvars('${DEV}/lib/foo-${FOO_VERSION}', local)
{'DEV': '${HOME}/dev', 'FOO_VERSION': '0.1'}
>>> pox.expandvars('${DEV}/lib/foo-${FOO_VERSION}', local)
${HOME}/dev/lib/foo-0.1
>>> pox.expandvars('${HOME}/dev/lib/foo-0.1')
/Users/mmckerns/dev/lib/foo-0.1
>>> pox.env('HOME')
{'HOME': '/Users/mmckerns'}
```

and perform some basic search functions:

```
>>> pox.find('python3.9', recurse=5, root='/opt')
['/opt/local/bin/python3.9']
>>> pox.which('python3.9')
'/opt/local/bin/python3.9'
```

pox also has a specialized *which* command just for Python:

```
>>> pox.which_python()
'/opt/local/bin/python3.9'
>>> pox.which_python(lazy=True, version=True)
'which python3.9'
```

Any of the pox functions can be launched from the command line, which facilitates executing commands across parallel and distributed pipes (such as *pathos.connection.Pipe* and *pathos.secure.connection.Pipe*):

```
>>> import pathos
>>> p = pathos.connection.Pipe()
>>> p(command="python -m pox 'which_python()'")
>>> p.launch()
>>> print(p.response())
'/usr/bin/python'
>>> p.kill()
```

The functions in pox that help make interactions with filesystems and environment variables programmatic and abstract become especially relevant when trying to execute complex commands remotely.

3.8 More Information

Probably the best way to get started is to look at the documentation at <http://pox.rtfd.io>. Also see `pox.tests` for a set of scripts that demonstrate how pox can be used to interact with the operating system. You can run the test suite with `python -m pox.tests`. All pox utilities can be launched directly from an operating system terminal, using the pox script (or with `python -m pox`). The source code is also generally well documented, so further questions may be resolved by inspecting the code itself. Please feel free to submit a ticket on github, or ask a question on stackoverflow (@Mike McKerns). If you would like to share how you use pox in your work, please send an email (to mmckerns@uqfoundation.org).

3.9 Citation

If you use `pox` to do research that leads to publication, we ask that you acknowledge use of `pox` by citing the following in your publication:

```
M.M. McKerns, L. Strand, T. Sullivan, A. Fang, M.A.G. Aivazis,  
"Building a framework for predictive science", Proceedings of  
the 10th Python in Science Conference, 2011;  
http://arxiv.org/pdf/1202.1056  
  
Michael McKerns and Michael Aivazis,  
"pathos: a framework for heterogeneous computing", 2010- ;  
https://uqfoundation.github.io/project/pathos
```

Please see <https://uqfoundation.github.io/project/pathos> or <http://arxiv.org/pdf/1202.1056> for further information.

citation()

print the citation

convert (*files*, *platform=None*, *pathsep=None*, *verbose=True*)

convert text files to given platform type

Ensure given files use the appropriate `os.linesep` and other formatting.

Parameters

- **files** (*list(str)*) – a list of filenames.
- **platform** (*str*, *default=None*) – platform name as in `os.name`.
- **pathsep** (*str*, *default=None*) – the path separator string.
- **verbose** (*bool*, *default=True*) – if True, print debug statements..

Returns 0 if converted, otherwise return 1.

disk_used (*path*)

get the disk usage for the given directory

Parameters **path** (*str*) – path string.

Returns int corresponding to disk usage in blocks.

env (*variable*, *all=True*, *minimal=False*)

get dict of environment variables of the form {*variable*:*value*}

Parameters

- **variable** (*str*) – name or partial name for environment variable.
- **all** (*bool*, *default=True*) – if False, only return the first match.
- **minimal** (*bool*, *default=False*) – if True, remove all duplicate paths.

Returns dict of strings of environment variables.

Warning: selecting `all=False` can lead to unexpected matches of *variable*.

Examples

```
>>> env('*PATH')
{'PYTHONPATH': '.', 'PATH': '.:usr/bin:/bin:/usr/sbin:/sbin'}
```

expandvars (*string*, *ref*=None, *secondref*={})

expand shell variables in string

Expand shell variables of form `$var` and `${var}`. Unknown variables are left unchanged. If a reference dictionary (*ref*) is provided, restrict lookups to *ref*. A second reference dictionary (*secondref*) can also be provided for failover searches. If *ref* is not provided, lookup variables are defined by the user's environment variables.

Parameters

- **string** (*str*) – a string with shell variables.
- **ref** (*dict*(*str*), *default*=None) – a dict of lookup variables.
- **secondref** (*dict*(*str*), *default*={}) – a failover reference dict.

Returns string with the selected shell variables substituted.

Examples

```
>>> expandvars('found:: $PYTHONPATH')
'found:: ../Users/foo/lib/python3.4/site-packages'
>>>
>>> expandvars('found:: $PYTHONPATH', ref={})
'found:: $PYTHONPATH'
```

find (*patterns*, *root*=None, *recurse*=True, *type*=None, *verbose*=False)

get the path to a file or directory

Parameters

- **patterns** (*str*) – name or partial name of items to search for.
- **root** (*str*, *default*=None) – path of top-level directory to search.
- **recurse** (*bool*, *default*=True) – if True, recurse downward from *root*.
- **type** (*str*, *default*=None) – a search filter.
- **verbose** (*bool*, *default*=False) – if True, be verbose about the search.

Returns a list of string paths.

Notes

on some OS, *recursion* can be specified by recursion depth (*int*), and *patterns* can be specified with basic pattern matching. Also, multiple patterns can be specified by splitting patterns with a `;`. The *type* can be one of {file, dir, link, socket, block, char}.

Examples

```
>>> find('pox*', root='..')
['/Users/foo/pox/pox', '/Users/foo/pox/scripts/pox_launcher.py']
>>>
>>> find('*shutils*;*init*')
['/Users/foo/pox/pox/shutils.py', '/Users/foo/pox/pox/__init__.py']
```

findpackage (*package*, *root=None*, *all=False*, *verbose=True*, *recurse=True*)
retrieve the path(s) for a package

Parameters

- **package** (*str*) – name of the package to search for.
- **root** (*str*, *default=None*) – path string of top-level directory to search.
- **all** (*bool*, *default=False*) – if True, return everywhere package is found.
- **verbose** (*bool*, *default=True*) – if True, print messages about the search.
- **recurse** (*bool*, *default=True*) – if True, recurse down the root directory.

Returns string path (or list of paths) where package is found.

Notes

On some OS, recursion can be specified by recursion depth (an integer). `findpackage` will do standard pattern matching for package names, attempting to match the head directory of the distribution.

getvars (*path*, *ref=None*, *sep=None*)
get a dictionary of all variables defined in path

Extract shell variables of form `$var` and `${var}`. Unknown variables will raise an exception. If a reference dictionary (*ref*) is provided, first try the lookup in *ref*. Failover from *ref* will lookup variables defined in the user's environment variables. Use *sep* to override the path separator (`os.sep`).

Parameters

- **path** (*str*) – a path string with shell variables.
- **ref** (*dict* (*str*), *default=None*) – a dict of lookup variables.
- **sep** (*str*, *default=None*) – the path separator string.

Returns dict of shell variables found in the given path string.

Examples

```
>>> getvars('$HOME/stuff')
{'HOME': '/Users/foo'}
```

homedir ()
get the full path of the user's home directory

Parameters **None** –

Returns string path of the directory, or None if home can not be determined.

index_join (*sequence*, *start*, *stop*, *step=1*, *sequential=True*, *inclusive=True*)

slice a list of strings, then join the remaining strings

If *start* is not found in the sequence, slice from the beginning. If *stop* is not found in the sequence, slice to the end.

Parameters

- **sequence** (*list*) – an ordered sequence of elements.
- **start** (*int*) – index for start of the slice.
- **stop** (*int*) – index for stop position in the sequence.
- **step** (*int*, *default=1*) – indices until next member of the slice.
- **sequential** (*bool*, *default=True*) – if True, *start* must precede *stop*.
- **inclusive** (*bool*, *default=True*) – if True, include *stop* in the slice.

Returns string produced by slicing the given sequence and joining the elements.

index_slice (*sequence*, *start*, *stop*, *step=1*, *sequential=False*, *inclusive=False*)

get the slice for a given sequence

Slice indicies are determined by the positions of *start* and *stop*. If *start* is not found in the sequence, slice from the beginning. If *stop* is not found in the sequence, slice to the end.

Parameters

- **sequence** (*list*) – an ordered sequence of elements.
- **start** (*int*) – index for start of the slice.
- **stop** (*int*) – index for stop position in the sequence.
- **step** (*int*, *default=1*) – indices until next member of the slice.
- **sequential** (*bool*, *default=False*) – if True, *start* must precede *stop*.
- **inclusive** (*bool*, *default=False*) – if True, include *stop* in the slice.

Returns slice corresponding to given *start*, *stop*, and *step*.

kbytes (*text*)

convert memory text to the corresponding value in kilobytes

Parameters **text** (*str*) – string corresponding to an abbreviation of size.

Returns int representation of text.

Examples

```
>>> kbytes('10K')
10
>>> kbytes('10G')
10485760
```

license ()

print the license

minpath (*path*, *pathsep=None*)

remove duplicate paths from given set of paths

Parameters

- **path** (*str*) – path string (e.g. `‘/Users/foo/bin:/bin:/sbin:/usr/bin’`).
- **pathsep** (*str*, *default=None*) – path separator (e.g. `:`).

Returns string composed of one or more paths, with duplicates removed.

Examples

```
>>> minpath('..:/Users/foo/bin:../Users/foo/bar/bin:/Users/foo/bin')
'..:/Users/foo/bin:/Users/foo/bar/bin'
```

mkdir (*path*, *root=None*, *mode=None*)

create a new directory in the root directory

create a directory at *path* and any necessary parents (i.e. `mkdir -p`). Default mode is read/write/execute for ‘user’ and ‘group’, and then read/execute otherwise.

Parameters

- **path** (*str*) – string name of the new directory.
- **root** (*str*, *default=None*) – path at which to build the new directory.
- **mode** (*str*, *default=None*) – octal read/write permission [default: `0o775`].

Returns string absolute path for new directory.

parse_remote (*path*, *loopback=False*, *login_flag=False*)

parse remote connection string of the form `[[user@]host:]path`

Parameters

- **path** (*str*) – remote connection string.
- **loopback** (*bool*, *default=False*) – if True, ensure *host* is used.
- **login_flag** (*bool*, *default=False*) – if True, prepend user with `-l`.

Returns a tuple of the form (*user*, *host*, *path*).

Notes

if *loopback*=True and *host*=None, then *host* will be set to localhost.

pattern (*list=[]*, *separator=';'*)

generate a filter pattern from list of strings

Parameters

- **list** (*list(str)*, *default=[]*) – a list of filter elements.
- **separator** (*str*, *default=';'*) – the separator string.

Returns a string composed of filter elements joined by the separator.

remote (*path*, *host=None*, *user=None*, *loopback=False*)

build string for a remote connection of the form `[[user@]host:]path`

Parameters

- **path** (*str*) – path string for location of target on (remote) filesystem.

- **host** (*str*, *default=None*) – string name/ip address of (remote) host.
- **user** (*str*, *default=None*) – user name on (remote) host.
- **loopback** (*bool*, *default=False*) – if True, ensure *host* is used.

Returns a remote connection string.

Notes

if loopback=True and host=None, then host will be set to localhost.

replace (*file*, *sub*={}, *outfile=None*)

make text substitutions given by *sub* in the given file

Parameters

- **file** (*str*) – path to original file.
- **sub** (*dict* (*str*)) – dict of string replacements {old:new}.
- **outfile** (*str*, *default=None*) – if given, don't overwrite original file.

Returns None

Notes

replace uses regular expressions, thus a pattern may be used as *old* text. replace can fail if order of substitution is important.

rmtree (*path*, *self=True*, *ignore_errors=False*, *onerror=None*)

remove directories in the given path

Parameters

- **path** (*str*) – path string of root of directories to delete.
- **self** (*bool*, *default=True*) – if False, delete subdirectories, not path.
- **ignore_errors** (*bool*, *default=False*) – if True, silently ignore errors.
- **onerror** (*function*, *default=None*) – custom error handler.

Returns None

Notes

If self=False, the directory indicated by path is left in place, and its subdirectories are erased. If self=True, path is also removed.

If ignore_errors=True, errors are ignored. Otherwise, onerror is called to handle the error with arguments (*func*, *path*, *exc_info*), where *func* is `os.listdir`, `os.remove`, or `os.rmdir`; *path* is the argument to the function that caused it to fail; and *exc_info* is a tuple returned by `sys.exc_info()`. If ignore_errors=False and onerror=None, an exception is raised.

rootdir ()

get the path corresponding to the root of the current drive

Parameters None –

Returns string path of the directory.

select (*iterable*, *counter*="", *minimum*=False, *reverse*=False, *all*=True)
find items in iterable with the max (or min) count of the given counter.

Find the items in an iterable that have the maximum number of *counter* (e.g. *counter*='3' counts occurrences of '3'). Use *minimum*=True to search for the minimum number of occurrences of the *counter*.

Parameters

- **iterable** (*list*) – an iterable of iterables (e.g. lists, strings, etc).
- **counter** (*str*, *default*='') – the item to count.
- **minimum** (*bool*, *default*=False) – if True, find min count (else, max).
- **reverse** (*bool*, *default*=False) – if True, reverse order of the results.
- **all** (*bool*, *default*=True) – if False, only return the first result.

Returns list of items in the iterable with the min (or max) count.

Examples

```
>>> z = ['zero', 'one', 'two', 'three', '4', 'five', 'six', 'seven', '8', '9/81']
>>> select(z, counter='e')
['three', 'seven']
>>> select(z, counter='e', minimum=True)
['two', '4', 'six', '8', '9/81']
>>>
>>> y = [[1, 2, 3], [4, 5, 6], [1, 3, 5]]
>>> select(y, counter=3)
[[1, 2, 3], [1, 3, 5]]
>>> select(y, counter=3, minimum=True, all=False)
[4, 5, 6]
```

selectdict (*dict*, *counter*="", *minimum*=False, *all*=True)
return a dict of items with the max (or min) count of the given counter.

Get the items from a dict that have the maximum number of the *counter* (e.g. *counter*='3' counts occurrences of '3') in the values. Use *minimum*=True to search for minimum number of occurrences of *counter*.

Parameters

- **dict** (*dict*) – dict with iterables as values (e.g. lists, strings, etc).
- **counter** (*str*, *default*='') – the item to count.
- **minimum** (*bool*, *default*=False) – if True, find min count (else, max).
- **all** (*bool*, *default*=True) – if False, only return the first result.

Returns dict of items composed of the entries with the min (or max) count.

Examples

```
>>> z = ['zero', 'one', 'two', 'three', '4', 'five', 'six', 'seven', '8', '9/81']
>>> z = dict(enumerate(z))
>>> selectdict(z, counter='e')
{3: 'three', 7: 'seven'}
>>> selectdict(z, counter='e', minimum=True)
{8: '8', 9: '9/81', 2: 'two', 4: '4', 6: 'six'}
>>>
>>> y = {1: [1,2,3], 2: [4,5,6], 3: [1,3,5]}
>>> selectdict(y, counter=3)
{1: [1, 2, 3], 3: [1, 3, 5]}
>>> selectdict(y, counter=3, minumim=True)
{2: [4, 5, 6]}
```

sep (*type*="")

get the separator string for the given type of separator

Parameters **type** (*str*, *default*='') – one of {sep, line, path, ext, alt}.

Returns separator string.

shellsub (*command*)

parse the given command to be formatted for remote shell invocation

secure shell (ssh) can be used to send and execute commands to remote machines (using `ssh <hostname> <command>`). Additional escape characters are needed to enable the command to be correctly formed and executed remotely. *shellsub* attempts to parse the given command string correctly so that it can be executed remotely with ssh.

Parameters **command** (*str*) – the command to be executed remotely.

Returns the parsed command string.

shelltype ()

get the name (e.g. `bash`) of the current command shell

Parameters **None** –

Returns string name of the shell, or `None` if name can not be determined.

username ()

get the login name of the current user

Parameters **None** –

Returns string name of the user.

wait_for (*path*, *sleep*=1, *tries*=150, *ignore_errors*=False)

block execution by waiting for a file to appear at the given path

Parameters

- **path** (*str*) – the path string to watch for the file.
- **sleep** (*float*, *default*=1) – the time between checking results.
- **tries** (*int*, *default*=150) – the number of times to try.
- **ignore_errors** (*bool*, *default*=False) – if True, ignore timeout error.

Returns None

Notes

if the file is not found after the given number of tries, an error will be thrown unless `ignore_error=True`.

using `subproc = Popen(...)` and `subproc.wait()` is usually a better approach. However, when a handle to the subprocess is unavailable, waiting for a file to appear at a given path is a decent last resort.

walk (*root*, *patterns*='*', *recurse*=True, *folders*=False, *files*=True, *links*=True)
walk directory tree and return a list matching the requested pattern

Parameters

- **root** (*str*) – path of top-level directory to search.
- **patterns** (*str*, *default*='*') – (partial) name of items to search for.
- **recurse** (*bool*, *default*=True) – if True, recurse downward from *root*.
- **folders** (*bool*, *default*=False) – if True, include folders in the results.
- **files** (*bool*, *default*=True) – if True, include files in results.
- **links** (*bool*, *default*=True) – if True, include links in results.

Returns a list of string paths.

Notes

patterns can be specified with basic pattern matching. Additionally, multiple patterns can be specified by splitting patterns with a `;`.

Examples

```
>>> walk('.', patterns='pox*')
['/Users/foo/pox/pox', '/Users/foo/pox/scripts/pox_launcher.py']
>>>
>>> walk('.', patterns='*shutils*;*init*')
['/Users/foo/pox/pox/shutils.py', '/Users/foo/pox/pox/__init__.py']
```

where (*name*, *path*, *pathsep*=None)
get the full path for the given name string on the given search path.

Parameters

- **name** (*str*) – name of file, folder, etc to find.
- **path** (*str*) – path string (e.g. `'/Users/foo/bin:/bin:/sbin:/usr/bin'`).
- **pathsep** (*str*, *default*=None) – path separator (e.g. `:`)

Returns the full path string.

Notes

if pathsep is not provided, the OS default will be used.

whereis (*prog*, *all=False*)

get path to the given program

search the standard binary install locations for the given executable.

Parameters

- **prog** (*str*) – name of an executable to search for (e.g. python).
- **all** (*bool*, *default=True*) – if True, return a list of paths found.

Returns string path of the executable, or list of path strings.

which (*prog*, *allow_links=True*, *ignore_errors=True*, *all=False*)

get the path of the given program

search the user's paths for the given executable.

Parameters

- **prog** (*str*) – name of an executable to search for (e.g. python).
- **allow_links** (*bool*, *default=True*) – if False, replace link with fullpath.
- **ignore_errors** (*bool*, *default=True*) – if True, ignore search errors.
- **all** (*bool*, *default=False*) – if True, get list of paths for executable.

Returns if all=True, get a list of string paths, else return a string path.

which_python (*version=False*, *lazy=False*, *fullpath=True*, *ignore_errors=True*)

get the command to launch the selected version of python

which_python composes a command string that can be used to launch the desired python executable. The user's path is searched for the executable, unless *lazy=True* and thus only a lazy-evaluating command (e.g. `which python`) is produced.

Parameters

- **version** (*bool*, *default=False*) – if True, include the version of python.
- **lazy** (*bool*, *default=False*) – if True, build a lazy-evaluating command.
- **fullpath** (*bool*, *default=True*) – if True, provide the full path.
- **ignore_errors** (*bool*, *default=True*) – if True, ignore path search errors.

Returns string of the implicit or explicit location of the python executable.

Notes

if version is given as an int or float, include the version number in the command string.

if the executable is not found, an error will be thrown unless *ignore_error=True*.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

—
`_pox`, 17

p
`pox`, 26

s
`pox.shutils`, 1

u
`pox.utils`, 8

Symbols

[__class_getitem__ \(Popen attribute\), 2](#)
[__del__ \(\) \(Popen method\), 2](#)
[__enter__ \(\) \(Popen method\), 2](#)
[__exit__ \(\) \(Popen method\), 2](#)
[__repr__ \(\) \(Popen method\), 2](#)
[_check_timeout \(\) \(Popen method\), 2](#)
[_child_created \(Popen attribute\), 2](#)
[_close_pipe_fds \(\) \(Popen method\), 2](#)
[_communicate \(\) \(Popen method\), 2](#)
[_execute_child \(\) \(Popen method\), 2](#)
[_get_devnull \(\) \(Popen method\), 2](#)
[_get_handles \(\) \(Popen method\), 2](#)
[_handle_exitstatus \(\) \(Popen method\), 2](#)
[_internal_poll \(\) \(Popen method\), 2](#)
[_posix_spawn \(\) \(Popen method\), 2](#)
[_pox](#)
 [module, 17](#)
[_remaining_time \(\) \(Popen method\), 2](#)
[_save_input \(\) \(Popen method\), 2](#)
[_stdin_write \(\) \(Popen method\), 3](#)
[_translate_newlines \(\) \(Popen method\), 3](#)
[_try_wait \(\) \(Popen method\), 3](#)
[_wait \(\) \(Popen method\), 3](#)

C

[citation \(\) \(in module _pox\), 17](#)
[citation \(\) \(in module pox\), 30](#)
[communicate \(\) \(Popen method\), 3](#)
[convert \(\) \(in module _pox\), 17](#)
[convert \(\) \(in module pox\), 30](#)
[convert \(\) \(in module pox.utils\), 8](#)

D

[disk_used \(\) \(in module _pox\), 17](#)
[disk_used \(\) \(in module pox\), 30](#)
[disk_used \(\) \(in module pox.utils\), 8](#)

E

[env \(\) \(in module _pox\), 17](#)
[env \(\) \(in module pox\), 30](#)
[env \(\) \(in module pox.shutils\), 3](#)

[expandvars \(\) \(in module _pox\), 18](#)
[expandvars \(\) \(in module pox\), 31](#)
[expandvars \(\) \(in module pox.utils\), 8](#)

F

[find \(\) \(in module _pox\), 18](#)
[find \(\) \(in module pox\), 31](#)
[find \(\) \(in module pox.shutils\), 4](#)
[findpackage \(\) \(in module _pox\), 19](#)
[findpackage \(\) \(in module pox\), 32](#)
[findpackage \(\) \(in module pox.utils\), 9](#)

G

[getHOME \(\) \(in module pox.shutils\), 4](#)
[getLines \(\) \(in module pox.utils\), 9](#)
[getROOT \(\) \(in module pox.shutils\), 4](#)
[getSEP \(\) \(in module pox.shutils\), 4](#)
[getSHELL \(\) \(in module pox.shutils\), 4](#)
[getUser \(\) \(in module pox.shutils\), 5](#)
[getvars \(\) \(in module _pox\), 19](#)
[getvars \(\) \(in module pox\), 32](#)
[getVar \(\) \(in module pox.utils\), 10](#)
[getvars \(\) \(in module pox.utils\), 10](#)

H

[help \(\) \(in module _pox\), 20](#)
[homedir \(\) \(in module _pox\), 20](#)
[homedir \(\) \(in module pox\), 32](#)
[homedir \(\) \(in module pox.shutils\), 5](#)

I

[index_join \(\) \(in module _pox\), 20](#)
[index_join \(\) \(in module pox\), 32](#)
[index_join \(\) \(in module pox.utils\), 10](#)
[index_slice \(\) \(in module _pox\), 20](#)
[index_slice \(\) \(in module pox\), 33](#)
[index_slice \(\) \(in module pox.utils\), 11](#)
[isfunction \(\) \(in module _pox\), 20](#)

K

[kbytes \(\) \(in module _pox\), 20](#)
[kbytes \(\) \(in module pox\), 33](#)

kbytes() (in module *pox.utils*), 11
kill() (*Popen method*), 3

L

license() (in module *_pox*), 21
license() (in module *pox*), 33

M

makefilter() (in module *pox.utils*), 12
makeTarget() (in module *pox.utils*), 11
minpath() (in module *_pox*), 21
minpath() (in module *pox*), 33
minpath() (in module *pox.shutils*), 5
mkdir() (in module *_pox*), 21
mkdir() (in module *pox*), 34
mkdir() (in module *pox.shutils*), 5
module
 _pox, 17
 pox, 26
 pox.shutils, 1
 pox.utils, 8

P

parse_remote() (in module *_pox*), 21
parse_remote() (in module *pox*), 34
parse_remote() (in module *pox.utils*), 12
parseTarget() (in module *pox.utils*), 12
pattern() (in module *_pox*), 22
pattern() (in module *pox*), 34
pattern() (in module *pox.utils*), 12
poll() (*Popen method*), 3
Popen (class in *pox.shutils*), 1
pox
 module, 26
pox.shutils
 module, 1
pox.utils
 module, 8
prunedict() (in module *pox.utils*), 12
prunelist() (in module *pox.utils*), 13

R

remote() (in module *_pox*), 22
remote() (in module *pox*), 34
remote() (in module *pox.utils*), 13
replace() (in module *_pox*), 22
replace() (in module *pox*), 35
replace() (in module *pox.utils*), 14
replaceText() (in module *pox.utils*), 14
rmtree() (in module *_pox*), 22
rmtree() (in module *pox*), 35
rmtree() (in module *pox.shutils*), 5
rootdir() (in module *_pox*), 23
rootdir() (in module *pox*), 35

rootdir() (in module *pox.shutils*), 6

S

select() (in module *_pox*), 23
select() (in module *pox*), 35
select() (in module *pox.utils*), 14
selectdict() (in module *_pox*), 23
selectdict() (in module *pox*), 36
selectdict() (in module *pox.utils*), 15
send_signal() (*Popen method*), 3
sep() (in module *_pox*), 24
sep() (in module *pox*), 37
sep() (in module *pox.shutils*), 6
shellsub() (in module *_pox*), 24
shellsub() (in module *pox*), 37
shellsub() (in module *pox.shutils*), 6
shelltype() (in module *_pox*), 24
shelltype() (in module *pox*), 37
shelltype() (in module *pox.shutils*), 6
stripDups() (in module *pox.shutils*), 6

T

terminate() (*Popen method*), 3

U

universal_newlines() (*Popen property*), 3
username() (in module *_pox*), 24
username() (in module *pox*), 37
username() (in module *pox.shutils*), 7

W

wait() (*Popen method*), 3
wait_for() (in module *_pox*), 24
wait_for() (in module *pox*), 37
wait_for() (in module *pox.utils*), 15
walk() (in module *_pox*), 25
walk() (in module *pox*), 38
walk() (in module *pox.shutils*), 7
where() (in module *_pox*), 25
where() (in module *pox*), 38
where() (in module *pox.shutils*), 7
whereis() (in module *_pox*), 26
whereis() (in module *pox*), 39
whereis() (in module *pox.shutils*), 8
which() (in module *_pox*), 26
which() (in module *pox*), 39
which() (in module *pox.shutils*), 8
which_python() (in module *_pox*), 26
which_python() (in module *pox*), 39
which_python() (in module *pox.utils*), 16