

# LilyPond

---

The music typesetter

## Notation Reference

The LilyPond development team

This manual provides a reference for all notation that can be produced with LilyPond version 2.15.29. It assumes that the reader is familiar with the material in the [Section “Learning Manual”](#) in *Learning Manual*.

For more information about how this manual fits with the other documentation, or to read this manual in other formats, see [Section “Manuals”](#) in *General Information*.

If you are missing any manuals, the complete documentation can be found at <http://www.lilypond.org/>.

Copyright © 1999–2012 by the authors.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with no Invariant Sections. A copy of the license is included in the section entitled “GNU Free Documentation License”.

For LilyPond version 2.15.29

---

# Table of Contents

<b>1</b>	<b>Musical notation</b>	<b>1</b>
1.1	Pitches	1
1.1.1	Writing pitches	1
	Absolute octave entry	1
	Relative octave entry	2
	Accidentals	5
	Note names in other languages	7
1.1.2	Changing multiple pitches	8
	Octave checks	8
	Transpose	9
	Inversion	12
	Retrograde	13
	Modal transformations	13
1.1.3	Displaying pitches	15
	Clef	15
	Key signature	19
	Ottava brackets	20
	Instrument transpositions	21
	Automatic accidentals	22
	Ambitus	29
1.1.4	Note heads	31
	Special note heads	32
	Easy notation note heads	33
	Shape note heads	35
	Improvisation	37
1.2	Rhythms	38
1.2.1	Writing rhythms	38
	Durations	38
	Tuplets	40
	Scaling durations	44
	Ties	46
1.2.2	Writing rests	49
	Rests	49
	Invisible rests	51
	Full measure rests	52
1.2.3	Displaying rhythms	56
	Time signature	56
	Metronome marks	61
	Upbeats	63
	Unmetered music	64
	Polymetric notation	66
	Automatic note splitting	69
	Showing melody rhythms	70
1.2.4	Beams	72
	Automatic beams	72
	Setting automatic beam behavior	74
	Manual beams	82
	Feathered beams	84



1.2.5	Bars.....	85
	Bar lines.....	85
	Bar numbers.....	90
	Bar and bar number checks.....	94
	Rehearsal marks.....	95
1.2.6	Special rhythmic concerns.....	97
	Grace notes.....	97
	Aligning to cadenzas.....	103
	Time administration.....	103
1.3	Expressive marks.....	104
1.3.1	Expressive marks attached to notes.....	105
	Articulations and ornamentations.....	105
	Dynamics.....	107
	New dynamic marks.....	112
1.3.2	Expressive marks as curves.....	114
	Slurs.....	114
	Phrasing slurs.....	117
	Breath marks.....	118
	Falls and doits.....	119
1.3.3	Expressive marks as lines.....	120
	Glissando.....	120
	Arpeggio.....	122
	Trills.....	125
1.4	Repeats.....	127
1.4.1	Long repeats.....	127
	Normal repeats.....	127
	Manual repeat marks.....	133
	Written-out repeats.....	135
1.4.2	Short repeats.....	137
	Percent repeats.....	137
	Tremolo repeats.....	139
1.5	Simultaneous notes.....	141
1.5.1	Single voice.....	141
	Chorded notes.....	142
	Chord repetition.....	143
	Simultaneous expressions.....	144
	Clusters.....	145
1.5.2	Multiple voices.....	146
	Single-staff polyphony.....	146
	Voice styles.....	149
	Collision resolution.....	150
	Automatic part combining.....	154
	Writing music in parallel.....	159
1.6	Staff notation.....	161
1.6.1	Displaying staves.....	162
	Instantiating new staves.....	162
	Grouping staves.....	163
	Nested staff groups.....	166
	Separating systems.....	168
1.6.2	Modifying single staves.....	169
	Staff symbol.....	169
	Ossia staves.....	172
	Hiding staves.....	176
1.6.3	Writing parts.....	179

Instrument names .....	179
Quoting other voices .....	183
Formatting cue notes .....	185
1.7 Editorial annotations .....	191
1.7.1 Inside the staff .....	191
Selecting notation font size .....	191
Fingering instructions .....	192
Hidden notes .....	194
Coloring objects .....	195
Parentheses .....	196
Stems .....	197
1.7.2 Outside the staff .....	198
Balloon help .....	198
Grid lines .....	199
Analysis brackets .....	201
1.8 Text .....	202
1.8.1 Writing text .....	202
Text scripts .....	202
Text spanners .....	203
Text marks .....	205
Separate text .....	209
1.8.2 Formatting text .....	210
Text markup introduction .....	210
Selecting font and font size .....	212
Text alignment .....	214
Graphic notation inside markup .....	217
Music notation inside markup .....	220
Multi-page markup .....	222
1.8.3 Fonts .....	223
Fonts explained .....	223
Single entry fonts .....	225
Entire document fonts .....	225
<b>2 Specialist notation .....</b>	<b>226</b>
2.1 Vocal music .....	226
2.1.1 Common notation for vocal music .....	226
References for vocal music .....	226
Entering lyrics .....	227
Aligning lyrics to a melody .....	228
Automatic syllable durations .....	230
Manual syllable durations .....	232
Multiple syllables to one note .....	234
Multiple notes to one syllable .....	234
Extenders and hyphens .....	238
2.1.2 Techniques specific to lyrics .....	238
Working with lyrics and variables .....	238
Placing lyrics vertically .....	240
Placing syllables horizontally .....	244
Lyrics and repeats .....	246
Divisi lyrics .....	253
2.1.3 Stanzas .....	254
Adding stanza numbers .....	254
Adding dynamics marks to stanzas .....	254
Adding singers' names to stanzas .....	255

Stanzas with different rhythms .....	255
Printing stanzas at the end .....	258
Printing stanzas at the end in multiple columns .....	259
2.1.4 Songs .....	261
References for songs .....	261
Lead sheets .....	261
2.1.5 Choral .....	262
References for choral .....	262
Score layouts for choral .....	263
Divided voices .....	264
2.1.6 Opera and stage musicals .....	265
References for opera and stage musicals .....	265
Character names .....	266
Musical cues .....	268
Spoken music .....	271
Dialogue over music .....	271
2.1.7 Chants psalms and hymns .....	273
References for chants and psalms .....	273
Setting a chant .....	273
Pointing a psalm .....	280
Partial measures in hymn tunes .....	283
2.1.8 Ancient vocal music .....	285
2.2 Keyboard and other multi-staff instruments .....	285
2.2.1 Common notation for keyboards .....	286
References for keyboards .....	286
Changing staff manually .....	286
Changing staff automatically .....	288
Staff-change lines .....	289
Cross-staff stems .....	290
2.2.2 Piano .....	292
Piano pedals .....	292
2.2.3 Accordion .....	293
Discant symbols .....	293
2.2.4 Harp .....	296
References for harps .....	296
Harp pedals .....	297
2.3 Unfretted string instruments .....	297
2.3.1 Common notation for unfretted strings .....	298
References for unfretted strings .....	298
Bowing indications .....	298
Harmonics .....	299
Snap (Bartók) pizzicato .....	300
2.4 Fretted string instruments .....	300
2.4.1 Common notation for fretted strings .....	300
References for fretted strings .....	301
String number indications .....	301
Default tablatures .....	303
Custom tablatures .....	315
Fret diagram markups .....	317
Predefined fret diagrams .....	327
Automatic fret diagrams .....	337
Right-hand fingerings .....	340
2.4.2 Guitar .....	341
Indicating position and barring .....	341

Indicating harmonics and dampened notes .....	342
Indicating power chords .....	343
2.4.3 Banjo .....	345
Banjo tablatures .....	345
2.5 Percussion .....	345
2.5.1 Common notation for percussion .....	345
References for percussion .....	346
Basic percussion notation .....	346
Drum rolls .....	347
Pitched percussion .....	347
Percussion staves .....	348
Custom percussion staves .....	349
Ghost notes .....	353
2.6 Wind instruments .....	354
2.6.1 Common notation for wind instruments .....	354
References for wind instruments .....	354
Fingerings .....	355
2.6.2 Bagpipes .....	357
Bagpipe definitions .....	358
Bagpipe example .....	358
2.6.3 Woodwinds .....	359
2.6.3.1 Woodwind diagrams .....	359
2.7 Chord notation .....	367
2.7.1 Chord mode .....	368
Chord mode overview .....	368
Common chords .....	369
Extended and altered chords .....	370
2.7.2 Displaying chords .....	373
Printing chord names .....	373
Customizing chord names .....	375
2.7.3 Figured bass .....	380
Introduction to figured bass .....	381
Entering figured bass .....	381
Displaying figured bass .....	384
2.8 Contemporary music .....	387
2.8.1 Pitch and harmony in contemporary music .....	387
References for pitch and harmony in contemporary music .....	387
Microtonal notation .....	387
Contemporary key signatures and harmony .....	387
2.8.2 Contemporary approaches to rhythm .....	388
References for contemporary approaches to rhythm .....	388
Tuplets in contemporary music .....	388
Contemporary time signatures .....	388
Extended polymetric notation .....	388
Beams in contemporary music .....	388
Bar lines in contemporary music .....	388
2.8.3 Graphical notation .....	388
2.8.4 Contemporary scoring techniques .....	388
2.8.5 New instrumental techniques .....	388
2.8.6 Further reading and scores of interest .....	388
Books and articles on contemporary musical notation .....	388
Scores and musical examples .....	388
2.9 Ancient notation .....	388
2.9.1 Overview of the supported styles .....	389

2.9.2	Ancient notation—common features	390
	Pre-defined contexts	390
	Ligatures	390
	Custodes	391
	Figured bass support	392
2.9.3	Typesetting mensural music	392
	Mensural contexts	392
	Mensural clefs	393
	Mensural time signatures	394
	Mensural note heads	395
	Mensural flags	396
	Mensural rests	396
	Mensural accidentals and key signatures	397
	Annotational accidentals ( <i>musica ficta</i> )	397
	White mensural ligatures	398
2.9.4	Typesetting Gregorian chant	399
	Gregorian chant contexts	399
	Gregorian clefs	400
	Gregorian accidentals and key signatures	401
	Divisiones	401
	Gregorian articulation signs	402
	Augmentum dots ( <i>morae</i> )	403
	Gregorian square neume ligatures	403
2.9.5	Working with ancient music—scenarios and solutions	410
	Incipits	410
	Mensurstriche layout	410
	Transcribing Gregorian chant	411
	Ancient and modern from one source	414
	Editorial markings	414
2.10	World music	414
2.10.1	Common notation for non-Western music	414
	Extending notation and tuning systems	414
2.10.2	Arabic music	415
	References for Arabic music	416
	Arabic note names	416
	Arabic key signatures	417
	Arabic time signatures	418
	Arabic music example	419
	Further reading for Arabic music	420
2.10.3	Turkish classical music	420
	References for Turkish classical music	420
	Turkish note names	421
<b>3</b>	<b>General input and output</b>	<b>422</b>
3.1	Input structure	422
3.1.1	Structure of a score	422
3.1.2	Multiple scores in a book	423
3.1.3	Multiple output files from one input file	424
3.1.4	Output file names	425
3.1.5	File structure	426
3.2	Titles and headers	428
3.2.1	Creating titles headers and footers	428
	Title blocks explained	428
	Default layout of book and score title blocks	430

Default layout of headers and footers .....	432
3.2.2 Custom headers footers and titles .....	433
Custom text formatting for title blocks .....	433
Custom layout for title blocks .....	434
Custom layout for headers and footers .....	437
3.2.3 Creating footnotes .....	438
Footnotes overview .....	438
Automatic footnotes .....	438
Manual footnotes .....	441
3.2.4 Reference to page numbers .....	444
3.2.5 Table of contents .....	446
3.3 Working with input files .....	448
3.3.1 Including LilyPond files .....	448
3.3.2 Different editions from one source .....	449
Using variables .....	449
Using tags .....	450
Using global settings .....	453
3.3.3 Special characters .....	453
Text encoding .....	453
Unicode .....	454
ASCII aliases .....	455
3.4 Controlling output .....	456
3.4.1 Extracting fragments of music .....	456
3.4.2 Skipping corrected music .....	456
3.4.3 Alternative output formats .....	457
3.4.4 Replacing the notation font .....	457
3.5 MIDI output .....	458
3.5.1 Creating MIDI files .....	458
Instrument names .....	459
3.5.2 MIDI block .....	460
3.5.3 What goes into the MIDI output? .....	461
Supported in MIDI .....	461
Unsupported in MIDI .....	461
3.5.4 Repeats in MIDI .....	462
3.5.5 Controlling MIDI dynamics .....	462
Dynamic marks .....	462
Overall MIDI volume .....	463
Equalizing different instruments (i) .....	464
Equalizing different instruments (ii) .....	465
3.5.6 Percussion in MIDI .....	466
3.5.7 The Articulate script .....	467
3.6 Extracting musical information .....	467
3.6.1 Displaying LilyPond notation .....	467
3.6.2 Displaying scheme music expressions .....	468
3.6.3 Saving music events to a file .....	468

<b>4</b>	<b>Spacing issues</b>	<b>469</b>
4.1	Page layout	469
4.1.1	The <code>\paper</code> block	469
4.1.2	Paper size and automatic scaling	470
	Setting paper size	470
	Automatic scaling to paper size	470
4.1.3	Fixed vertical spacing <code>\paper</code> variables	471
4.1.4	Flexible vertical spacing <code>\paper</code> variables	472
	Structure of flexible vertical spacing alists	472
	List of flexible vertical spacing <code>\paper</code> variables	473
4.1.5	Horizontal spacing <code>\paper</code> variables	474
	<code>\paper</code> variables for widths and margins	474
	<code>\paper</code> variables for two-sided mode	475
	<code>\paper</code> variables for shifts and indents	475
4.1.6	Other <code>\paper</code> variables	476
	<code>\paper</code> variables for line breaking	476
	<code>\paper</code> variables for page breaking	476
	<code>\paper</code> variables for page numbering	477
	Miscellaneous <code>\paper</code> variables	477
4.2	Score layout	478
4.2.1	The <code>\layout</code> block	478
4.2.2	Setting the staff size	479
4.3	Breaks	480
4.3.1	Line breaking	480
4.3.2	Page breaking	482
4.3.3	Optimal page breaking	483
4.3.4	Optimal page turning	483
4.3.5	Minimal page breaking	484
4.3.6	Explicit breaks	484
4.3.7	Using an extra voice for breaks	486
4.4	Vertical spacing	488
4.4.1	Flexible vertical spacing within systems	488
	Within-system spacing properties	488
	Spacing of ungrouped staves	491
	Spacing of grouped staves	492
	Spacing of non-staff lines	493
4.4.2	Explicit staff and system positioning	495
4.4.3	Vertical collision avoidance	502
4.5	Horizontal spacing	503
4.5.1	Horizontal spacing overview	503
4.5.2	New spacing area	505
4.5.3	Changing horizontal spacing	505
4.5.4	Line length	507
4.5.5	Proportional notation	508
4.6	Fitting music onto fewer pages	515
4.6.1	Displaying spacing	515
4.6.2	Changing spacing	516

<b>5</b>	<b>Changing defaults</b>	<b>519</b>
5.1	Interpretation contexts	519
5.1.1	Contexts explained	519
	Score - the master of all contexts	519
	Top-level contexts - staff containers	519
	Intermediate-level contexts - staves	520
	Bottom-level contexts - voices	520
5.1.2	Creating contexts	521
5.1.3	Keeping contexts alive	522
5.1.4	Modifying context plug-ins	524
5.1.5	Changing context default settings	526
5.1.6	Defining new contexts	528
5.1.7	Context layout order	529
5.2	Explaining the Internals Reference	530
5.2.1	Navigating the program reference	531
5.2.2	Layout interfaces	531
5.2.3	Determining the grob property	532
5.2.4	Naming conventions	533
5.3	Modifying properties	534
5.3.1	Overview of modifying properties	534
5.3.2	The <code>\set</code> command	534
5.3.3	The <code>\override</code> command	536
5.3.4	The <code>\tweak</code> command	538
5.3.5	<code>\set</code> vs. <code>\override</code>	539
5.3.6	Modifying alists	540
5.4	Useful concepts and properties	541
5.4.1	Input modes	541
5.4.2	Direction and placement	543
5.4.3	Distances and measurements	544
5.4.4	Staff symbol properties	545
5.4.5	Spanners	545
	Using the <code>spanner-interface</code>	545
	Using the <code>line-spanner-interface</code>	547
5.4.6	Visibility of objects	550
	Removing the stencil	550
	Making objects transparent	550
	Painting objects white	550
	Using break-visibility	551
	Special considerations	553
5.4.7	Line styles	554
5.4.8	Rotating objects	555
	Rotating layout objects	555
	Rotating markup	556
5.5	Advanced tweaks	556
5.5.1	Aligning objects	556
	Setting <code>X-offset</code> and <code>Y-offset</code> directly	557
	Using the <code>side-position-interface</code>	557
	Using the <code>self-alignment-interface</code>	558
	Using the <code>break-alignable-interface</code>	559
5.5.2	Vertical grouping of grobs	561
5.5.3	Modifying stencils	561
5.5.4	Modifying shapes	562
	Modifying ties and slurs	562
5.5.5	Unpure-pure containers	563



5.6	Using music functions .....	564
5.6.1	Substitution function syntax .....	565
5.6.2	Substitution function examples .....	565
<b>Appendix A</b>	<b>Notation manual tables .....</b>	<b>568</b>
A.1	Chord name chart .....	568
A.2	Common chord modifiers .....	569
A.3	Predefined string tunings .....	572
A.4	Predefined fretboard diagrams .....	573
A.5	MIDI instruments .....	586
A.6	List of colors .....	587
A.7	The Feta font .....	589
	Clef glyphs .....	589
	Time Signature glyphs .....	589
	Number glyphs .....	589
	Accidental glyphs .....	590
	Default Notehead glyphs .....	591
	Special Notehead glyphs .....	591
	Shape-note Notehead glyphs .....	592
	Rest glyphs .....	596
	Flag glyphs .....	596
	Dot glyphs .....	597
	Dynamic glyphs .....	597
	Script glyphs .....	597
	Arrowhead glyphs .....	599
	Bracket-tip glyphs .....	600
	Pedal glyphs .....	600
	Accordion glyphs .....	600
	Tie glyphs .....	600
	Vaticana glyphs .....	601
	Medicaea glyphs .....	602
	Hufnagel glyphs .....	602
	Mensural glyphs .....	603
	Neomensural glyphs .....	606
	Petrucchi glyphs .....	607
	Solesmes glyphs .....	608
A.8	Note head styles .....	608
A.9	Text markup commands .....	609
A.9.1	Font .....	609
A.9.2	Align .....	618
A.9.3	Graphic .....	632
A.9.4	Music .....	638
A.9.5	Instrument Specific Markup .....	642
A.9.6	Other .....	645
A.10	Text markup list commands .....	651
A.11	List of special characters .....	652
A.12	List of articulations .....	654
	Articulation scripts .....	654
	Ornament scripts .....	654
	Fermata scripts .....	654
	Instrument-specific scripts .....	655
	Repeat sign scripts .....	655
	Ancient scripts .....	655
A.13	Percussion notes .....	655

A.14	Technical glossary .....	657
	alist .....	657
	callback .....	657
	closure .....	657
	glyph .....	657
	grob .....	657
	immutable .....	658
	interface .....	658
	lexer .....	658
	mutable .....	658
	output-def .....	658
	parser .....	658
	parser variable .....	659
	prob .....	659
	simple closure .....	659
	smob .....	659
	stencil .....	659
A.15	All context properties .....	660
A.16	Layout properties .....	670
A.17	Available music functions .....	688
A.18	Context modification identifiers .....	695
A.19	Predefined type predicates .....	695
	R5RS primary predicates .....	695
	R5RS secondary predicates .....	695
	Guile predicates .....	696
	LilyPond scheme predicates .....	696
	LilyPond exported predicates .....	696
A.20	Scheme functions .....	697
<b>Appendix B</b>	<b>Cheat sheet .....</b>	<b>720</b>
<b>Appendix C</b>	<b>LilyPond grammar .....</b>	<b>723</b>
<b>Appendix D</b>	<b>GNU Free Documentation License .....</b>	<b>748</b>
<b>Appendix E</b>	<b>LilyPond command index .....</b>	<b>755</b>
<b>Appendix F</b>	<b>LilyPond index .....</b>	<b>765</b>

# 1 Musical notation

This chapter explains how to create musical notation.

## 1.1 Pitches



This section discusses how to specify the pitch of notes. There are three steps to this process: input, modification, and output.

### 1.1.1 Writing pitches

This section discusses how to input pitches. There are two different ways to place notes in octaves: absolute and relative mode. In most cases, relative mode will be more convenient.

#### Absolute octave entry

A pitch name is specified using lowercase letters **a** through **g**. The note names **c** to **b** are engraved in the octave below middle C.

```
{
  \clef bass
  c4 d e f
  g4 a b c
  d4 e f g
}
```



Other octaves may be specified with a single quote (') or comma (,) character. Each ' raises the pitch by one octave; each , lowers the pitch by an octave.

```
{
  \clef treble
  c'4 c'' e' g
  d''4 d' d c
}
```

```

\clef bass
c,4 c,, e, g
d,,4 d, d c
}

```



## See also

Music Glossary: [Section “Pitch names” in \*Music Glossary\*](#).

Snippets: [Section “Pitches” in \*Snippets\*](#).

## Relative octave entry

When octaves are specified in absolute mode it is easy to accidentally put a pitch in the wrong octave. Relative octave mode reduces these errors since most of the time it is not necessary to indicate any octaves at all. Furthermore, in absolute mode a single mistake may be difficult to spot, while in relative mode a single error puts the rest of the piece off by one octave.

```
\relative startpitch musicexpr
```

In relative mode, each note is assumed to be as close to the previous note as possible. This means that the octave of each pitch inside *musicexpr* is calculated as follows:

- If no octave changing mark is used on a pitch, its octave is calculated so that the interval with the previous note is less than a fifth. This interval is determined without considering accidentals.
- An octave changing mark ' or , can be added to respectively raise or lower a pitch by an extra octave, relative to the pitch calculated without an octave mark.
- Multiple octave changing marks can be used. For example, '' and ,, will alter the pitch by two octaves.
- The pitch of the first note is relative to *startpitch*. *startpitch* is specified in absolute octave mode, and it is recommended that it be a octave of c.

Here is the relative mode shown in action:

```

\relative c {
  \clef bass
  c d e f
  g a b c
  d e f g
}

```



Octave changing marks are used for intervals greater than a fourth:

```

\relative c'' {
  c g c f,
  c' a, e'' c
}

```

}



A note sequence without a single octave mark can nevertheless span large intervals:

```
\relative c {
  c f b e
  a d g c
}
```




When `\relative` blocks are nested, the innermost `\relative` block applies.

```
\relative c' {
  c d e f
  \relative c'' {
    c d e f
  }
}
```



`\relative` has no effect on `\chordmode` blocks.

```
\new Staff {
  \relative c''' {
    \chordmode { c1 }
  }
  \chordmode { c1 }
}
```



`\relative` is not allowed inside of `\chordmode` blocks.

Music inside a `\transpose` block is absolute unless a `\relative` is included.

```
\relative c' {
  d e
  \transpose f g {
    d e
    \relative c' {
      d e
    }
  }
}
```

}




If the preceding item is a chord, the first note of the chord is used as the reference point for the octave placement of a following note or chord. Inside chords, the next note is always relative to the preceding one. Examine the next example carefully, paying attention to the `c` notes.

```
\relative c' {
  c
  <c e g>
  <c' e g'>
  <c, e, g' '>
}
```



As explained above, the octave of pitches is calculated only with the note names, regardless of any alterations. Therefore, an E-double-sharp following a B will be placed higher, while an F-double-flat will be placed lower. In other words, a double-augmented fourth is considered a smaller interval than a double-diminished fifth, regardless of the number of semitones that each interval contains.

```
\relative c'' {
  c2 fis
  c2 ges
  b2 eisis
  b2 feses
}
```



One consequence of these rules is that the first note inside `\relative f` music is interpreted just the same as if it was written in absolute pitch mode.

## See also

Music Glossary: Section “fifth” in *Music Glossary*, Section “interval” in *Music Glossary*, Section “Pitch names” in *Music Glossary*.

Notation Reference: [Octave checks], page 8.

Snippets: Section “Pitches” in *Snippets*.

Internals Reference: Section “RelativeOctaveMusic” in *Internals Reference*.

If no `startpitch` is specified for `\relative`, then `c'` is assumed. However, this is a deprecated option and may disappear in future versions, so its use is discouraged.

## Accidentals

**Note:** New users are sometimes confused about accidentals and key signatures. In LilyPond, note names are the raw input; key signatures and clefs determine how this raw input is displayed. An unaltered note like `c` means ‘C natural’, regardless of the key signature or clef. For more information, see [Section “Accidentals and key signatures”](#) in *Learning Manual*.

A *sharp* pitch is made by adding `is` to the note name, and a *flat* pitch by adding `es`. As you might expect, a *double sharp* or *double flat* is made by adding `isis` or `eses`. This syntax is derived from Dutch note naming conventions. To use other names for accidentals, see [\[Note names in other languages\]](#), page 7.

```
ais1 aes aisis aeses
```




A natural will cancel the effect of an accidental or key signature. However, naturals are not encoded into the note name syntax with a suffix; a natural pitch is shown as a simple note name:

```
a4 aes a2
```



Quarter tones may be added; the following is a series of Cs with increasing pitches:

```
ceseh1 ces ceh c cih cis cisih
```



Normally accidentals are printed automatically, but you may also print them manually. A reminder accidental can be forced by adding an exclamation mark `!` after the pitch. A cautionary accidental (i.e., an accidental within parentheses) can be obtained by adding the question mark `?` after the pitch. These extra accidentals can also be used to produce natural signs.


```
cis cis cis! cis? c c c! c?
```



Accidentals on tied notes are only printed at the beginning of a new system:

```
cis1~ cis~  
\break  
cis
```





## Selected Snippets

*Hiding accidentals on tied notes at the beginning of a new system*

This shows how to hide accidentals on tied notes at the beginning of a new system.

```
\relative c'' {
  \override Accidental #'hide-tied-accidental-after-break = ##t
  cis1~ cis~
  \break
  cis
}
```



*Preventing extra naturals from being automatically added*

In accordance with standard typesetting rules, a natural sign is printed before a sharp or flat if a previous accidental on the same note needs to be canceled. To change this behavior, set the `extraNatural` property to `f` in the `Staff` context.

```
\relative c'' {
  aeses4 aes ais a
  \set Staff.extraNatural = ##f
  aeses4 aes ais a
}
```



## See also

Music Glossary: Section “sharp” in *Music Glossary*, Section “flat” in *Music Glossary*, Section “double sharp” in *Music Glossary*, Section “double flat” in *Music Glossary*, Section “Pitch names” in *Music Glossary*, Section “quarter tone” in *Music Glossary*.

Learning Manual: Section “Accidentals and key signatures” in *Learning Manual*.

Notation Reference: [Automatic accidentals], page 22, [Annotational accidentals (musica ficta)], page 397, [Note names in other languages], page 7.

Snippets: Section “Pitches” in *Snippets*.

Internals Reference: Section “Accidental-engraver” in *Internals Reference*, Section “Accidental” in *Internals Reference*, Section “AccidentalCautionary” in *Internals Reference*, Section “accidental-interface” in *Internals Reference*.



## Known issues and warnings

There are no generally accepted standards for denoting quarter-tone accidentals, so LilyPond's symbol does not conform to any standard.

## Note names in other languages

There are predefined sets of note and accidental names for various other languages. Selecting the note name language is usually done at the beginning of the file; the following example is written using Italian note names:

```
\language "italiano"
```

```
\relative do' {  
  do re mi sib  
}
```



The available languages and the note names they define are:

Language	Note Names
nederlands	c d e f g a bes b
catalan	do re mi fa sol la sib si
deutsch	c d e f g a b h
english	c d e f g a bf b
espanol	do re mi fa sol la sib si
italiano	do re mi fa sol la sib si
norsk	c d e f g a b h
portugues	do re mi fa sol la sib si
suomi	c d e f g a b h
svenska	c d e f g a b h
vlaams	do re mi fa sol la sib si

In addition to note names, accidental suffixes may also vary depending on the language:

Language	sharp	flat	double sharp	double flat
nederlands	-is	-es	-isis	-eses
catalan	-d/-s	-b	-dd/-ss	-bb
deutsch	-is	-es	-isis	-eses
english	-s/-sharp	-f/-flat	-ss/-x/-sharpsharp	-ff/-flatflat
espanol	-s	-b	-ss/-x	-bb
italiano	-d	-b	-dd	-bb
norsk	-iss/-is	-ess/-es	-ississ/-isis	-essess/-eses
portugues	-s	-b	-ss	-bb
suomi	-is	-es	-isis	-eses
svenska	-iss	-ess	-ississ	-essess
vlaams	-k	-b	-kk	-bb

In Dutch, **aes** is contracted to **as**, but both forms are accepted in LilyPond. Similarly, both **es** and **ees** are accepted. This also applies to **aeses** / **ases** and **eeses** / **eses**. Sometimes only these contracted names are defined in the corresponding language files.

a2 as e es a ases e eses



Some music uses microtones whose alterations are fractions of a ‘normal’ sharp or flat. The following table lists note names for quarter-tone accidentals in various languages; here the prefixes *semi-* and *sesqui-* respectively mean ‘half’ and ‘one and a half’. Languages that do not appear in this table do not provide special note names yet.

Language	semi-sharp	semi-flat	sesqui-sharp	sesqui-flat
nederlands	-ih	-eh	-isih	-eseh
deutsch	-ih	-eh	-isih	-eseh
english	-qs	-qf	-tqs	-tqf
espanol	-cs	-cb	-tcs	-tcb
italiano	-sd	-sb	-dsd	-bsb
portugues	-sqt	-bqt	-stqt	-btqt

Most languages presented here are commonly associated with Western classical music, also referred to as *Common Practice Period*. However, alternate pitches and tuning systems are also supported: see [Section 2.10.1 \[Common notation for non-Western music\]](#), page 414.

## See also

Music Glossary: [Section “Pitch names” in \*Music Glossary\*](#), [Section “Common Practice Period” in \*Music Glossary\*](#).

Notation Reference: [Section 2.10.1 \[Common notation for non-Western music\]](#), page 414.

Installed Files: ‘`scm/define-note-names.scm`’.

Snippets: [Section “Pitches” in \*Snippets\*](#).

## 1.1.2 Changing multiple pitches

This section discusses how to modify pitches.

### Octave checks

In relative mode, it is easy to forget an octave changing mark. Octave checks make such errors easier to find by displaying a warning and correcting the octave if a note is found in an unexpected octave.

To check the octave of a note, specify the absolute octave after the = symbol. This example will generate a warning (and change the pitch) because the second note is the absolute octave d'' instead of d' as indicated by the octave correction.

```
\relative c'' {
  c2 d='4 d
  e2 f
}
```



The octave of notes may also be checked with the `\octaveCheck controlpitch` command. `controlpitch` is specified in absolute mode. This checks that the interval between the previous

note and the *controlpitch* is within a fourth (i.e., the normal calculation of relative mode). If this check fails, a warning is printed, but the previous note is not changed. Future notes are relative to the *controlpitch*.

```
\relative c' {
  c2 d
  \octaveCheck c'
  e2 f
}
```



Compare the two bars below. The first and third `\octaveCheck` checks fail, but the second one does not fail.

```
\relative c' {
  c4 f g f

  c4
  \octaveCheck c'
  f
  \octaveCheck c'
  g
  \octaveCheck c'
  f
}
```



## See also

Snippets: [Section “Pitches” in \*Snippets\*](#).

Internals Reference: [Section “RelativeOctaveCheck” in \*Internals Reference\*](#).

## Transpose

A music expression can be transposed with `\transpose`. The syntax is

```
\transpose frompitch topitch musicexpr
```

This means that *musicexpr* is transposed by the interval between the pitches *frompitch* and *topitch*: any note with pitch *frompitch* is changed to *topitch* and any other note is transposed by the same interval. Both pitches are entered in absolute mode.

**Note:** Music inside a `\transpose` block is absolute unless a `\relative` is included in the block.

Consider a piece written in the key of D-major. It can be transposed up to E-major; note that the key signature is automatically transposed as well.

```
\transpose d e {
  \relative c' {
```

```

\key d \major
d4 fis a d
}
}

```



If a part written in C (normal *concert pitch*) is to be played on the A clarinet (for which an A is notated as a C and thus sounds a minor third lower than notated), the appropriate part will be produced with:

```

\transpose a c' {
  \relative c' {
    \key c \major
    c4 d e g
  }
}

```



Note that we specify `\key c \major` explicitly. If we do not specify a key signature, the notes will be transposed but no key signature will be printed.

`\transpose` distinguishes between enharmonic pitches: both `\transpose c cis` or `\transpose c des` will transpose up a semitone. The first version will print sharps and the notes will remain on the same scale step, the second version will print flats on the scale step above.

```

music = \relative c' { c d e f }
\new Staff {
  \transpose c cis { \music }
  \transpose c des { \music }
}

```



`\transpose` may also be used in a different way, to input written notes for a transposing instrument. The previous examples show how to enter pitches in C (or *concert pitch*) and typeset them for a transposing instrument, but the opposite is also possible if you for example have a set of instrumental parts and want to print a conductor's score. For example, when entering music for a B-flat trumpet that begins on a notated E (concert D), one would write:

```

musicInBflat = { e4 ... }
\transpose c bes, \musicInBflat

```

To print this music in F (e.g., rearranging to a French horn) you could wrap the existing music with another `\transpose`:

```

musicInBflat = { e4 ... }
\transpose f c' { \transpose c bes, \musicInBflat }

```

For more information about transposing instruments, see [\[Instrument transpositions\]](#), page 21.

## Selected Snippets

*Transposing pitches with minimum accidentals ("Smart" transpose)*

This example uses some Scheme code to enforce enharmonic modifications for notes in order to have the minimum number of accidentals. In this case, the following rules apply:

Double accidentals should be removed

B sharp -> C

E sharp -> F

C flat -> B

F flat -> E

In this manner, the most natural enharmonic notes are chosen.

```
#(define (naturalize-pitch p)
  (let ((o (ly:pitch-octave p))
        (a (* 4 (ly:pitch-alteration p)))
        ;; alteration, a, in quarter tone steps,
        ;; for historical reasons
        (n (ly:pitch-notename p)))
    (cond
      ((and (> a 1) (or (eq? n 6) (eq? n 2))))
      (set! a (- a 2))
      (set! n (+ n 1)))
    ((and (< a -1) (or (eq? n 0) (eq? n 3))))
    (set! a (+ a 2))
    (set! n (- n 1))))
  (cond
    ((> a 2) (set! a (- a 4)) (set! n (+ n 1)))
    ((< a -2) (set! a (+ a 4)) (set! n (- n 1))))
    (if (< n 0) (begin (set! o (- o 1)) (set! n (+ n 7))))
    (if (> n 6) (begin (set! o (+ o 1)) (set! n (- n 7))))
    (ly:make-pitch o n (/ a 4))))
```

```
#(define (naturalize music)
  (let ((es (ly:music-property music 'elements))
        (e (ly:music-property music 'element))
        (p (ly:music-property music 'pitch)))
    (if (pair? es)
        (ly:music-set-property!
         music 'elements
         (map (lambda (x) (naturalize x)) es)))
        (if (ly:music? e)
            (ly:music-set-property!
             music 'element
             (naturalize e)))
            (if (ly:pitch? p)
                (begin
                 (set! p (naturalize-pitch p))
                 (ly:music-set-property! music 'pitch p)))
                music)))
```

naturalizeMusic =

```
#(define-music-function (parser location m)
```

```

(ly:music?)
(naturalize m))

music = \relative c' { c4 d e g }

\score {
  \new Staff {
    \transpose c ais { \music }
    \naturalizeMusic \transpose c ais { \music }
    \transpose c deses { \music }
    \naturalizeMusic \transpose c deses { \music }
  }
  \layout { }
}

```



## See also

Notation Reference: [\[Instrument transpositions\]](#), page 21, [\[Inversion\]](#), page 12, [\[Modal transformations\]](#), page 13, [\[Relative octave entry\]](#), page 2, [\[Retrograde\]](#), page 13.

Snippets: [Section “Pitches” in \*Snippets\*](#).

Internals Reference: [Section “TransposedMusic” in \*Internals Reference\*](#).

## Known issues and warnings

The relative conversion will not affect `\transpose`, `\chordmode` or `\relative` sections in its argument. To use relative mode within transposed music, an additional `\relative` must be placed inside `\transpose`.

Triple accidentals will not be printed if using `\transpose`. An ‘enharmonically equivalent’ pitch will be used instead (e.g. d-flat rather than e-triple-flat).

## Inversion

A music expression can be inverted with:

```
\inversion from-pitch to-pitch musicexpr
```

The *musicexpr* is inverted interval-by-interval, and then transposed so that *from-pitch* is mapped to *to-pitch*.

```

music = \relative c' { c d e f }
\new Staff {
  \music
  \inversion d' d' \music
  \inversion d' ees' \music
}

```



## See also

Notation Reference: [\[Modal transformations\]](#), page 13, [\[Retrograde\]](#), page 13, [\[Transpose\]](#), page 9.

## Retrograde

A music expression can be reversed to produce its retrograde:

```
music = \relative c' { c8. ees16( fis8. a16 b8.) gis16 f8. d16 }

\new Staff {
  \music
  \retrograde \music
}
```



## Known issues and warnings

Manual ties inside `\retrograde` will be broken and generate warnings. Some ties can be generated automatically by enabling [\[Automatic note splitting\]](#), page 69.

## See also

Notation Reference: [\[Inversion\]](#), page 12, [\[Modal transformations\]](#), page 13, [\[Transpose\]](#), page 9.

## Modal transformations

In a musical composition that is based on a scale, a motif is frequently transformed in various ways. It may be *transposed* to start at different places in the scale or it may be *inverted* around a pivot point in the scale. It may also be reversed to produce its *retrograde*, see [\[Retrograde\]](#), page 13.

**Note:** Any note that does not lie within the given scale will be left untransformed.

## Modal transposition

A motif can be transposed within a given scale with:

```
\modalTranspose from-pitch to-pitch scale motif
```

The notes of *motif* are shifted within the *scale* by the number of scale degrees given by the interval between *to-pitch* and *from-pitch*:

```
diatonicScale = \relative c' { c d e f g a b }
motif = \relative c' { c8 d e f g a b c }

\new Staff {
  \motif
  \modalTranspose c f \diatonicScale \motif
  \modalTranspose c b, \diatonicScale \motif
}
```



An ascending scale of any length and with any intervals may be specified:

```
pentatonicScale = \relative c' { ges aes bes des ees }
motif = \relative c' { ees8 des ges,4 <ges' bes,> <ges bes,> }
```

```
\new Staff {
  \motif
  \modalTranspose ges ees' \pentatonicScale \motif
}
```



When used with a chromatic scale `\modalTranspose` has a similar effect to `\transpose`, but with the ability to specify the names of the notes to be used:

```
chromaticScale = \relative c' { c cis d dis e f fis g gis a ais b }
motif = \relative c' { c8 d e f g a b c }
```

```
\new Staff {
  \motif
  \transpose c f \motif
  \modalTranspose c f \chromaticScale \motif
}
```



## Modal inversion

A motif can be inverted within a given scale around a given pivot note and transposed in a single operation with:

```
\modalInversion around-pitch to-pitch scale motif
```

The notes of *motif* are placed the same number of scale degrees from the *around-pitch* note within the *scale*, but in the opposite direction, and the result is then shifted within the *scale* by the number of scale degrees given by the interval between *to-pitch* and *around-pitch*.

So to simply invert around a note in the scale use the same value for *around-pitch* and *to-pitch*:

```
octatonicScale = \relative c' { ees f fis gis a b c d }
motif = \relative c' { c8. ees16 fis8. a16 b8. gis16 f8. d16 }
```

```
\new Staff {
  \motif
  \modalInversion fis' fis' \octatonicScale \motif
}
```





To invert around a pivot between two notes in the scale, invert around one of the notes and then transpose by one scale degree. The two notes specified can be interpreted as bracketing the pivot point:

```
scale = \relative c' { c g' }
motive = \relative c' { c c g' c, }

\new Staff {
  \motive
  \modalInversion c' g' \scale \motive
}
```



The combined operation of inversion and retrograde produce the retrograde-inversion:

```
octatonicScale = \relative c' { ees f fis gis a b c d }
motif = \relative c' { c8. ees16 fis8. a16 b8. gis16 f8. d16 }

\new Staff {
  \motif
  \retrograde \modalInversion c' c' \octatonicScale \motif
}
```



## See also

Notation Reference: [\[Inversion\]](#), page 12, [\[Retrograde\]](#), page 13, [\[Transpose\]](#), page 9.


### 1.1.3 Displaying pitches

This section discusses how to alter the output of pitches.

#### Clef

The clef may be altered. Middle C is shown in every example. The following clef names can (but do not need to) be enclosed in quotes.

```
\clef treble
c2 c
\clef alto
c2 c
\clef tenor
c2 c
\clef bass
c2 c
```



Other clefs include:

```

\clef french
c2 c
\clef soprano
c2 c
\clef mezzosoprano
c2 c
\clef baritone
c2 c

\break

\clef varbaritone
c2 c
\clef subbass
c2 c
\clef percussion
c2 c

\break

\clef G    % synonym for treble
c2 c
\clef F    % synonym for bass
c2 c
\clef C    % synonym for alto
c2 c

```



By adding `_8` or `^8` to the clef name, the clef is transposed one octave down or up respectively, and `_15` and `^15` transpose by two octaves. Other integers can be used if required. Clef names containing non-alphabetic characters must be enclosed in quotes

```

\clef treble
c2 c
\clef "treble_8"
c2 c
\clef "bass^15"
c2 c
\clef "alto_2"
c2 c
\clef "G_8"

```

```
c2 c
\clef "F^5"
c2 c
```



Some special purpose clefs are described in [\[Mensural clefs\]](#), page 393, [\[Gregorian clefs\]](#), page 400, [\[Default tablatures\]](#), page 303, and [\[Custom tablatures\]](#), page 315. For mixing different clefs when using cue notes within a score, see the `\cueClef` and `\cueDuringWithClef` functions in [\[Formatting cue notes\]](#), page 185.

## Selected Snippets

### *Tweaking clef properties*

The command `\clef "treble_8"` is equivalent to setting `clefGlyph`, `clefPosition` (which controls the vertical position of the clef), `middleCPosition` and `clefOctavation`. A clef is printed when any of the properties except `middleCPosition` are changed.

Note that changing the glyph, the position of the clef, or the octavation does not in itself change the position of subsequent notes on the staff: the position of middle C must also be specified to do this. The positional parameters are relative to the staff center line, positive numbers displacing upwards, counting one for each line and space. The `clefOctavation` value would normally be set to 7, -7, 15 or -15, but other values are valid.

When a clef change takes place at a line break the new clef symbol is printed at both the end of the previous line and the beginning of the new line by default. If the warning clef at the end of the previous line is not required it can be suppressed by setting the `Staff` property `explicitClefVisibility` to the value `end-of-line-invisible`. The default behavior can be recovered with `\unset Staff.explicitClefVisibility`.

The following examples show the possibilities when setting these properties manually. On the first line, the manual changes preserve the standard relative positioning of clefs and notes, whereas on the second line, they do not.

```
\layout { ragged-right = ##t }

{
  % The default treble clef
  c'1
  % The standard bass clef
  \set Staff.clefGlyph = #"clefs.F"
  \set Staff.clefPosition = #2
  \set Staff.middleCPosition = #6
  c'1
  % The baritone clef
  \set Staff.clefGlyph = #"clefs.C"
  \set Staff.clefPosition = #4
  \set Staff.middleCPosition = #4
  c'1
  % The standard choral tenor clef
  \set Staff.clefGlyph = #"clefs.G"
  \set Staff.clefPosition = #-2
  \set Staff.clefOctavation = #-7
  \set Staff.middleCPosition = #1
```

```

c'1
% A non-standard clef
\set Staff.clefPosition = #0
\set Staff.clefOctavation = #0
\set Staff.middleCPosition = #-4
c'1 \break

% The following clef changes do not preserve
% the normal relationship between notes and clefs:

\set Staff.clefGlyph = #"clefs.F"
\set Staff.clefPosition = #2
c'1
\set Staff.clefGlyph = #"clefs.G"
c'1
\set Staff.clefGlyph = #"clefs.C"
c'1
\set Staff.clefOctavation = #7
c'1
\set Staff.clefOctavation = #0
\set Staff.clefPosition = #0
c'1

% Return to the normal clef:

\set Staff.middleCPosition = #0
c'1
}

```



## See also

Notation Reference: [Mensural clefs], page 393, [Gregorian clefs], page 400, [Default tablatures], page 303, [Custom tablatures], page 315, [Formatting cue notes], page 185.

Snippets: Section “Pitches” in *Snippets*.

Internals Reference: Section “Clef\_engraver” in *Internals Reference*, Section “Clef” in *Internals Reference*, Section “OctavateEight” in *Internals Reference*, Section “clef-interface” in *Internals Reference*.

## Key signature

**Note:** New users are sometimes confused about accidentals and key signatures. In LilyPond, note names are the raw input; key signatures and clefs determine how this raw input is displayed. An unaltered note like `c` means ‘C natural’, regardless of the key signature or clef. For more information, see [Section “Accidentals and key signatures”](#) in *Learning Manual*.

The key signature indicates the tonality in which a piece is played. It is denoted by a set of alterations (flats or sharps) at the start of the staff. The key signature may be altered:

```
\key pitch mode
```

Here, *mode* should be `\major` or `\minor` to get a key signature of *pitch*-major or *pitch*-minor, respectively. You may also use the standard mode names, also called *church modes*: `\ionian`, `\dorian`, `\phrygian`, `\lydian`, `\mixolydian`, `\aeolian`, and `\locrian`.

```
\key g \major
fis1
f
fis
```



## Selected Snippets

*Preventing natural signs from being printed when the key signature changes*

When the key signature changes, natural signs are automatically printed to cancel any accidentals from previous key signatures. This may be prevented by setting to `f` the `printKeyCancellation` property in the **Staff** context.

```
\relative c' {
  \key d \major
  a4 b cis d
  \key g \minor
  a4 bes c d
  \set Staff.printKeyCancellation = ##f
  \key d \major
  a4 b cis d
  \key g \minor
  a4 bes c d
}
```



*Non-traditional key signatures*

The commonly used `\key` command sets the `keySignature` property, in the **Staff** context.

To create non-standard key signatures, set this property directly. The format of this command is a list:

`\set Staff.keySignature = #`(((octave . step) . alter) ((octave . step) . alter) ...)` where, for each element in the list, `octave` specifies the octave (0 being the octave from middle C to the B above), `step` specifies the note within the octave (0 means C and 6 means B), and `alter` is `,SHARP` `,FLAT` `,DOUBLE-SHARP` etc. (Note the leading comma.)

Alternatively, for each item in the list, using the more concise format `(step . alter)` specifies that the same alteration should hold in all octaves.

Here is an example of a possible key signature for generating a whole-tone scale:

```
\relative c' {
  \set Staff.keySignature = #`(((0 . 6) . ,FLAT)
                                ((0 . 5) . ,FLAT)
                                ((0 . 3) . ,SHARP))

  c4 d e fis
  aes4 bes c2
}
```



## See also

Music Glossary: [Section “church mode”](#) in *Music Glossary*, [Section “scordatura”](#) in *Music Glossary*.

Learning Manual: [Section “Accidentals and key signatures”](#) in *Learning Manual*.


Snippets: [Section “Pitches”](#) in *Snippets*.

Internals Reference: [Section “KeyChangeEvent”](#) in *Internals Reference*, [Section “Key\\_engraver”](#) in *Internals Reference*, [Section “Key\\_performer”](#) in *Internals Reference*, [Section “KeyCancellation”](#) in *Internals Reference*, [Section “KeySignature”](#) in *Internals Reference*, [Section “key-cancellation-interface”](#) in *Internals Reference*, [Section “key-signature-interface”](#) in *Internals Reference*.

## Ottava brackets

*Ottava brackets* introduce an extra transposition of an octave for the staff:

```
a2 b
\ottava #-2
a2 b
\ottava #-1
a2 b
\ottava #0
a2 b
\ottava #1
a2 b
\ottava #2
a2 b
```



## Selected Snippets

### *Ottava text*

Internally, `\ottava` sets the properties `ottavation` (for example, to `8va` or `8vb`) and `middleCPosition`. To override the text of the bracket, set `ottavation` after invoking `\ottava`.

```
{
  \ottava #1
  \set Staff.ottavation = #"8"
  c''1
  \ottava #0
  c'1
  \ottava #1
  \set Staff.ottavation = #"Text"
  c''1
}
```



## See also

Music Glossary: [Section “octavation” in \*Music Glossary\*](#).

Snippets: [Section “Pitches” in \*Snippets\*](#).

Internals Reference: [Section “Ottava-spanner\\_engraver” in \*Internals Reference\*](#), [Section “OttavaBracket” in \*Internals Reference\*](#), [Section “ottava-bracket-interface” in \*Internals Reference\*](#).

## Instrument transpositions

When typesetting scores that involve transposing instruments, some parts can be typeset in a different pitch than the *concert pitch*. In these cases, the key of the *transposing instrument* should be specified; otherwise the MIDI output and cues in other parts will produce incorrect pitches. For more information about quotations, see [\[Quoting other voices\]](#), page 183.

### `\transposition pitch`

The pitch to use for `\transposition` should correspond to the real sound heard when a `c'` written on the staff is played by the transposing instrument. This pitch is entered in absolute mode, so an instrument that produces a real sound which is one tone higher than the printed music should use `\transposition d'`. `\transposition` should *only* be used if the pitches are *not* being entered in concert pitch.

Here are a few notes for violin and B-flat clarinet where the parts have been entered using the notes and key as they appear in each part of the conductor’s score. The two instruments are playing in unison.

```
\new GrandStaff <<
  \new Staff = "violin" {
    \relative c'' {
      \set Staff.instrumentName = #"Vln"
      \set Staff.midiInstrument = #"violin"
      % not strictly necessary, but a good reminder
      \transposition c'

      \key c \major
```

```

      g4( c8) r c r c4
    }
  }
  \new Staff = "clarinet" {
    \relative c'' {
      \set Staff.instrumentName = \markup { Cl (B\flat) }
      \set Staff.midiInstrument = #"clarinet"
      \transposition bes

      \key d \major
      a4( d8) r d r d4
    }
  }
  >>

```




The `\transposition` may be changed during a piece. For example, a clarinetist may switch from an A clarinet to a B-flat clarinet.

```

\set Staff.instrumentName = #"Cl (A)"
\key a \major
\transposition a
c d e f
\textLengthOn
s1*0~\markup { Switch to B\flat clarinet }
R1

\key bes \major
\transposition bes
c2 g

```



## See also

Music Glossary: [Section “concert pitch” in \*Music Glossary\*](#), [Section “transposing instrument” in \*Music Glossary\*](#).

Notation Reference: [\[Quoting other voices\]](#), page 183, [\[Transpose\]](#), page 9.

Snippets: [Section “Pitches” in \*Snippets\*](#).

## Automatic accidentals

There are many different conventions on how to typeset accidentals. LilyPond provides a function to specify which accidental style to use. This function is called as follows:



```

\new Staff <<
  \accidentalStyle "voice"
  { ... }
>>

```

The accidental style applies to the current **Staff** by default (with the exception of the styles **piano** and **piano-cautionary**, which are explained below). Optionally, the function can take a second argument that determines in which scope the style should be changed. For example, to use the same style in all staves of the current **StaffGroup**, use:

```

\accidentalStyle #'StaffGroup "voice"

```

The following accidental styles are supported. To demonstrate each style, we use the following example:

```

musicA = {
  <<
    \relative c' {
      cis'8 fis, bes4 <a cis>8 f bis4 |
      cis2. <c, g'>4 |
    }
    \\
    \relative c' {
      ais'2 cis, |
      fis8 b a4 cis2 |
    }
  >>
}

musicB = {
  \clef bass
  \new Voice {
    \voiceTwo \relative c' {
      <fis, a cis>8 <fis a cis>
      \change Staff = up
      cis' cis
      \change Staff = down
      <fis, a> <fis a>
      \showStaffSwitch
      \change Staff = up
      dis'4 |
      \change Staff = down
      <fis, a cis>4 gis <f a d>2 |
    }
  }
}


\new PianoStaff {
  <<
    \context Staff = "up" {
      \accidentalStyle "default"
      \musicA
    }
    \context Staff = "down" {
      \accidentalStyle "default"

```

```

        \musicB
    }
  >>
}

```



Note that the last lines of this example can be replaced by the following, as long as the same accidental style should be used in both staves.

```

\new PianoStaff {
  <<
    \context Staff = "up" {
      %% change the next line as desired:
      \accidentalStyle #'Score "default"
      \musicA
    }
    \context Staff = "down" {
      \musicB
    }
  >>
}

```

**default**


This is the default typesetting behavior. It corresponds to eighteenth-century common practice: accidentals are remembered to the end of the measure in which they occur and only in their own octave. Thus, in the example below, no natural signs are printed before the **b** in the second measure or the last **c**:




**voice**

The normal behavior is to remember the accidentals at **Staff-level**. In this style, however, accidentals are typeset individually for each voice. Apart from that, the rule is similar to **default**.


As a result, accidentals from one voice do not get canceled in other voices, which is often an unwanted result: in the following example, it is hard to determine whether the second **a** should be played natural or sharp. The **voice** option should therefore be used only if the voices are to be read solely by individual musicians. If the staff is to be used by one musician (e.g., a conductor or in a piano score) then **modern** or **modern-cautionary** should be used instead.

**modern**


This rule corresponds to the common practice in the twentieth century. It omits some extra natural signs, which were traditionally prefixed to a sharp following a double sharp, or a flat following a double flat. The **modern** rule prints the same accidentals as **default**, with two additions that serve to avoid ambiguity: after temporary accidentals, cancellation marks are printed also in the following measure (for notes in the same octave) and, in the same measure, for notes in other octaves. Hence the naturals before the **b** and the **c** in the second measure of the upper staff:

**modern-cautionary**


This rule is similar to **modern**, but the ‘extra’ accidentals (the ones not typeset by **default**) are typeset as cautionary accidentals. They are by default printed with parentheses, but they can also be printed in reduced size by defining the **cautionary-style** property of **AccidentalSuggestion**.

**modern-voice**


This rule is used for multivoice accidentals to be read both by musicians playing one voice and musicians playing all voices. Accidentals are typeset for each voice, but they *are* canceled across voices in the same **Staff**. Hence, the **a** in the last measure is canceled because the previous cancellation was in a different voice, and the **d** in the lower staff is canceled because of the accidental in a different voice in the previous measure:

**modern-voice-cautionary**


This rule is the same as **modern-voice**, but with the extra accidentals (the ones not typeset by **voice**) typeset as cautionaries. Even though all accidentals typeset by **default** *are* typeset with this rule, some of them are typeset as cautionaries.

**piano**


This rule reflects twentieth-century practice for piano notation. Its behavior is very similar to `modern` style, but here accidentals also get canceled across the staves in the same `GrandStaff` or `PianoStaff`, hence all the cancellations of the final notes. This accidental style applies to the current `GrandStaff` or `PianoStaff` by default.

**piano-cautionary**


This is the same as `piano` but with the extra accidentals typeset as cautionaries.

**neo-modern**

This rule reproduces a common practice in contemporary music: accidentals are printed like with `modern`, but they are printed again if the same note appears later in the same measure – except if the note is immediately repeated.


**neo-modern-cautionary**

This rule is similar to `neo-modern`, but the extra accidentals are printed as cautionary accidentals.




**neo-modern-voice**


This rule is used for multivoice accidentals to be read both by musicians playing one voice and musicians playing all voices. Accidentals are typeset for each voice as with `neo-modern`, but they are canceled across voices in the same `Staff`.

**neo-modern-voice-cautionary**

This rule is similar to `neo-modern-voice`, but the extra accidentals are printed as cautionary accidentals.

**dodecaphonic**


This rule reflects a practice introduced by composers at the beginning of the 20th century, in an attempt to abolish the hierarchy between natural and non-natural notes. With this style, *every* note gets an accidental sign, including natural signs.

**teaching**

This rule is intended for students, and makes it easy to create scale sheets with automatically created cautionary accidentals. Accidentals are printed like with `modern`, but cautionary accidentals are added for all sharp or flat tones specified by the key signature, except if the note is immediately repeated.


**no-reset**

This is the same as `default` but with accidentals lasting ‘forever’ and not only within the same measure:



forget

This is the opposite of `no-reset`: Accidentals are not remembered at all – and hence all accidentals are typeset relative to the key signature, regardless of what came before in the music.



See also


Snippets: [Section “Pitches” in \*Snippets\*](#).

Internals Reference: [Section “Accidental” in \*Internals Reference\*](#), [Section “Accidental-engraver” in \*Internals Reference\*](#), [Section “GrandStaff” in \*Internals Reference\*](#), [Section “PianoStaff” in \*Internals Reference\*](#), [Section “Staff” in \*Internals Reference\*](#), [Section “AccidentalSuggestion” in \*Internals Reference\*](#), [Section “AccidentalPlacement” in \*Internals Reference\*](#), [Section “accidental-suggestion-interface” in \*Internals Reference\*](#).

## Known issues and warnings

Simultaneous notes are not considered in the automatic determination of accidentals; only previous notes and the key signature are considered. Forcing accidentals with `!` or `?` may be required when the same note name occurs simultaneously with different alterations, as in `<f! fis!>`.

Cautionary cancellation of accidentals is done by looking at previous measure. However, in the `\alternative` block following a `\repeat volta N` section, one would expect the cancellation being calculated using the previous *played* measure, not previous *printed* measure. In the following example, the natural `c` in the second alternative does not need a natural sign:




The following work-around can be used: define a function that locally changes the accidental style to `forget`:

```
forget = #(define-music-function (parser location music) (ly:music?) #{
  \accidentalStyle "forget"
  $music
  \accidentalStyle "modern"
#})
{
  \accidentalStyle "modern"
  \time 2/4
  \repeat volta 2 {
    c'2
```

```

    }
    \alternative {
      cis'
      \forget c'
    }
  }
}

```



## Ambitus

The term *ambitus* (pl. *ambitus*) denotes a range of pitches for a given voice in a part of music. It may also denote the pitch range that a musical instrument is capable of playing. Ambitus are printed on vocal parts so that performers can easily determine if it matches their capabilities.

Ambitus are denoted at the beginning of a piece near the initial clef. The range is graphically specified by two note heads that represent the lowest and highest pitches. Accidentals are only printed if they are not part of the key signature.

```

\layout {
  \context {
    \Voice
    \consists "Ambitus_engraver"
  }
}

\relative c'' {
  aes c e2
  cis,1
}

```



## Selected Snippets

### *Adding ambitus per voice*

Ambitus can be added per voice. In this case, the ambitus must be moved manually to prevent collisions.

```

\new Staff <<
  \new Voice \with {
    \consists "Ambitus_engraver"
  } \relative c'' {
    \override Ambitus #'X-offset = #2.0
    \voiceOne
    c4 a d e
    f1
  }
  \new Voice \with {
    \consists "Ambitus_engraver"
  }

```

```

    } \relative c' {
      \voiceTwo
      es4 f g as
      b1
    }
  >>

```



### *Ambitus with multiple voices*

Adding the `Ambitus_engraver` to the `Staff` context creates a single ambitus per staff, even in the case of staves with multiple voices.

```

\new Staff \with {
  \consists "Ambitus_engraver"
}
<<
  \new Voice \relative c'' {
    \voiceOne
    c4 a d e
    f1
  }
  \new Voice \relative c' {
    \voiceTwo
    es4 f g as
    b1
  }
}
>>

```



### *Changing the ambitus gap*

It is possible to change the default gap setting for ambitus.

```

\layout {
  \context {
    \Voice
    \consists "Ambitus_engraver"
  }
}

\new Staff {
  \time 2/4
  % Default setting
  c'4 g''
}

```



```

}

\new Staff {
  \time 2/4
  \override AmbitusLine #'gap = #0
  c'4 g''
}

\new Staff {
  \time 2/4
  \override AmbitusLine #'gap = #1
  c'4 g''
}

\new Staff {
  \time 2/4
  \override AmbitusLine #'gap = #1.5
  c'4 g''
}

```



## See also

Music Glossary: Section “ambitus” in *Music Glossary*.

Snippets: Section “Pitches” in *Snippets*.

Internals Reference: Section “Ambitus\_engraver” in *Internals Reference*, Section “Voice” in *Internals Reference*, Section “Staff” in *Internals Reference*, Section “Ambitus” in *Internals Reference*, Section “AmbitusAccidental” in *Internals Reference*, Section “AmbitusLine” in *Internals Reference*, Section “AmbitusNoteHead” in *Internals Reference*, Section “ambitus-interface” in *Internals Reference*.

## Known issues and warnings

There is no collision handling in the case of multiple per-voice ambitus.

### 1.1.4 Note heads

This section suggests ways of altering note heads.

## Special note heads

The appearance of note heads may be altered:


```
c4 b
\override NoteHead #'style = #'cross
c4 b
\revert NoteHead #'style
a b
\override NoteHead #'style = #'harmonic
a b
\revert NoteHead #'style
c4 d e f
```



To see all note head styles, see [Section A.8 \[Note head styles\]](#), page 608.

The `cross` style is used to represent a variety of musical intentions. The following generic predefined commands modify the note head in both staff and tablature contexts and can be used to represent any musical meaning:

```
c4 b
\xNotesOn
a b c4 b
\xNotesOff
c4 d
```



The music function form of this predefined command may be used inside and outside chords to generate crossed note heads in both staff and tablature contexts:

```
c4 b
\xNote { e f }
c b < g \xNote c f > b
```



As synonyms for `\xNote`, `\xNotesOn` and `\xNotesOff`, `\deadNote`, `\deadNotesOn` and `\deadNotesOff` can be used. The term *dead note* is commonly used by guitarists.

There is also a shorthand for diamond shapes which can be used only inside chords:

```
<c f\harmonic>2 <d a'\harmonic>4 <c g'\harmonic>
```



## Predefined commands

`\harmonic`, `\xNotesOn`, `\xNotesOff`, `\xNote`.

## See also

Snippets: [Section “Pitches” in \*Snippets\*](#).


Notation Reference: [Section A.8 \[Note head styles\]](#), page 608, [\[Chorded notes\]](#), page 142, [\[Indicating harmonics and dampened notes\]](#), page 342.

Internals Reference: [Section “note-event” in \*Internals Reference\*](#), [Section “Note\\_heads\\_engraver” in \*Internals Reference\*](#), [Section “Ledger\\_line\\_engraver” in \*Internals Reference\*](#), [Section “NoteHead” in \*Internals Reference\*](#), [Section “LedgerLineSpanner” in \*Internals Reference\*](#), [Section “note-head-interface” in \*Internals Reference\*](#), [Section “ledger-line-spanner-interface” in \*Internals Reference\*](#).

## Easy notation note heads

The ‘easy play’ note head includes a note name inside the head. It is used in music for beginners. To make the letters readable, it should be printed in a large font size. To print with a larger font, see [Section 4.2.2 \[Setting the staff size\]](#), page 479.

```
#(set-global-staff-size 26)
\relative c' {
  \easyHeadsOn
  c2 e4 f
  g1
  \easyHeadsOff
  c,1
}
```



## Predefined commands

`\easyHeadsOn`, `\easyHeadsOff`.

## Selected Snippets

*Numbers as easy note heads*

Easy notation note heads use the `note-names` property of the `NoteHead` object to determine what appears inside the note head. By overriding this property, it is possible to print numbers representing the scale-degree.

A simple engraver can be created to do this for every note head object it sees.

```
#(define Ez_numbers_engraver
  (list
    (cons 'acknowledgers
      (list
        (cons 'note-head-interface
          (lambda (engraver grob source-engraver)
            (let* ((context (ly:translator-context engraver))
                  (tonic-pitch (ly:context-property context 'tonic))
                  (tonic-name (ly:pitch-notename tonic-pitch))
                  (grob-pitch
                    (ly:event-property (event-cause grob) 'pitch))
                  (grob-name (ly:pitch-notename grob-pitch)))
```

```

(delta (modulo (- grob-name tonic-name) 7))
(note-names
 (make-vector 7 (number->string (1+ delta))))
(ly:grob-set-property! grob 'note-names note-names))))))

#(set-global-staff-size 26)


\layout {
  ragged-right = ##t
  \context {
    \Voice
    \consists \Ez_numbers_engraver
  }
}

\relative c' {
  \easyHeadsOn
  c4 d e f
  g4 a b c \break

  \key a \major
  a,4 b cis d
  e4 fis gis a \break

  \key d \dorian
  d,4 e f g
  a4 b c d
}

```



## See also

Notation Reference: [Section 4.2.2 \[Setting the staff size\]](#), page 479.

Snippets: [Section “Pitches” in \*Snippets\*](#).

Internals Reference: [Section “note-event” in \*Internals Reference\*](#), [Section “Note\\_heads\\_engraver” in \*Internals Reference\*](#), [Section “NoteHead” in \*Internals Reference\*](#), [Section “note-head-interface” in \*Internals Reference\*](#).

## Shape note heads

In shape note head notation, the shape of the note head corresponds to the harmonic function of a note in the scale. This notation was popular in nineteenth-century American song books. Shape note heads can be produced in Sacred Harp, Southern Harmony, Funk (Harmonica Sacra), Walker, and Aiken (Christian Harmony) styles:

```
\aikenHeads
c, d e f g2 a b1 c \break
\sacredHarpHeads
c,4 d e f g2 a b1 c \break
\southernHarmonyHeads
c,4 d e f g2 a b1 c \break
\funkHeads
c,4 d e f g2 a b1 c \break
\walkerHeads
c,4 d e f g2 a b1 c \break
```



Shapes are typeset according to the step in the scale, where the base of the scale is determined by the `\key` command. When writing in a minor key, the scale step can be determined from the relative major:

```
\key a \minor
\aikenHeads
a b c d e2 f g1 a \break
\aikenHeadsMinor
a,4 b c d e2 f g1 a \break
\sacredHarpHeadsMinor
a,2 b c d \break
\southernHarmonyHeadsMinor
a2 b c d \break
\funkHeadsMinor
```

```
a2 b c d \break
\walkerHeadsMinor
a2 b c d \break
```



## Predefined commands

```
\aikenHeads, \aikenHeadsMinor, \funkHeads, \funkHeadsMinor, \sacredHarpHeads,
\sacredHarpHeadsMinor, \southernHarmonyHeads, \southernHarmonyHeadsMinor,
\walkerHeads, \walkerHeadsMinor.
```

## Selected Snippets

*Applying note head styles depending on the step of the scale*

The `shapeNoteStyles` property can be used to define various note head styles for each step of the scale (as set by the key signature or the `tonic` property). This property requires a set of symbols, which can be purely arbitrary (geometrical expressions such as `triangle`, `cross`, and `xcircle` are allowed) or based on old American engraving tradition (some latin note names are also allowed).

That said, to imitate old American song books, there are several predefined note head styles available through shortcut commands such as `\aikenHeads` or `\sacredHarpHeads`.

This example shows different ways to obtain shape note heads, and demonstrates the ability to transpose a melody without losing the correspondence between harmonic functions and note head styles.

```

fragment = {
  \key c \major
  c2 d
  e2 f
  g2 a
  b2 c
}

\new Staff {
  \transpose c d
  \relative c' {
    \set shapeNoteStyles = #'#(do re mi fa
                          #f la ti)


    \fragment
  }

  \break

  \relative c' {
    \set shapeNoteStyles = #'#(cross triangle fa #f
                          mensural xcircle diamond)

    \fragment
  }
}

```



To see all note head styles, see [Section A.8 \[Note head styles\]](#), page 608.

## See also

Snippets: [Section “Pitches” in \*Snippets\*](#).

Notation Reference: [Section A.8 \[Note head styles\]](#), page 608.

Internals Reference: [Section “note-event” in \*Internals Reference\*](#), [Section “Note\\_heads\\_engraver” in \*Internals Reference\*](#), [Section “NoteHead” in \*Internals Reference\*](#), [Section “note-head-interface” in \*Internals Reference\*](#).

## Improvisation

Improvisation is sometimes denoted with slashed note heads, where the performer may choose any pitch but should play the specified rhythm. Such note heads can be created:

```

\new Voice \with {
  \consists "Pitch_squash_engraver"
} {
  e8 e g a a16( bes) a8 g
  \improvisationOn
}

```

```

e8 ~
e2 ~ e8 f4 f8 ~
f2
\improvisationOff
a16( bes) a8 g e
}

```



## Predefined commands

`\improvisationOn`, `\improvisationOff`.

## See also

Snippets: [Section “Pitches” in \*Snippets\*](#).

Internals Reference: [Section “Pitch\\_squash\\_engraver” in \*Internals Reference\*](#), [Section “Voice” in \*Internals Reference\*](#), [Section “RhythmicStaff” in \*Internals Reference\*](#).

## 1.2 Rhythms

This section discusses rhythms, rests, durations, beaming and bars.

### 1.2.1 Writing rhythms

#### Durations

Durations are designated by numbers and dots. Durations are entered as their reciprocal values. For example, a quarter note is entered using a 4 (since it is a 1/4 note), and a half note is entered using a 2 (since it is a 1/2 note). For notes longer than a whole you must use the `\longa` (a double breve) and `\breve` commands. Durations as short as 128th notes may be specified. Shorter values are possible, but only as beamed notes.

```

\time 8/1
c\longa c\breve c1 c2
c4 c8 c16 c32 c64 c128 c128

```





Here are the same durations with automatic beaming turned off.

```
\time 8/1
\autoBeamOff
c\longa c\breve c1 c2
c4 c8 c16 c32 c64 c128 c128
```



A note with the duration of a quadruple breve may be entered with `\maxima`, but this is supported only within ancient music notation. For details, see [Section 2.9 \[Ancient notation\]](#), [page 388](#).

If the duration is omitted, it is set to the previously entered duration. The default for the first note is a quarter note.

a a a2 a a4 a a1 a



To obtain dotted note lengths, place a dot (.) after the duration. Double-dotted notes are specified by appending two dots, and so on.

a4 b c4. b8 a4. b4... c8.



Some durations cannot be represented with just binary durations and dots; they can be represented only by tying two or more notes together. For details, see [Ties], page 46.

For ways of specifying durations for the syllables of lyrics and ways of aligning lyrics to notes, see [Section 2.1 \[Vocal music\]](#), page 226.

Optionally, notes can be spaced strictly proportionately to their duration. For details of this and other settings which control proportional notation, see [Section 4.5.5 \[Proportional notation\]](#), page 508.

Dots are normally moved up to avoid staff lines, except in polyphonic situations. Dots may be manually placed above or below the staff; see [Section 5.4.2 \[Direction and placement\]](#), page 543.

## Predefined commands

\autoBeamOn, \autoBeamOff, \dotsUp, \dotsDown, \dotsNeutral.

## Selected Snippets

Alternative breve notehead with double vertical lines

This code demonstrates how to use the alternative breve note with two vertical lines on each side of the notehead instead of one line.

```
\relative c'' {
  \time 4/2
  \override Staff.NoteHead #'style = #'altdefault
  c\breve | b\breve
}
```



### *Changing the number of augmentation dots per note*

This code demonstrates how to change the number of augmentation dots on a single note.

```
\relative c' {
  c4.. a16 r2 |
  \override Dots #'dot-count = #4
  c4.. a16 r2 |
  \override Dots #'dot-count = #0
  c4.. a16 r2 |
  \revert Dots #'dot-count
  c4.. a16 r2 |
}
```



## See also

Music Glossary: Section “breve” in *Music Glossary*, Section “longa” in *Music Glossary*, Section “maxima” in *Music Glossary*, Section “note value” in *Music Glossary*, Section “Duration names notes and rests” in *Music Glossary*.

Notation Reference: [Automatic beams], page 72, [Ties], page 46, [Stems], page 197, Section 1.2.1 [Writing rhythms], page 38, Section 1.2.2 [Writing rests], page 49, Section 2.1 [Vocal music], page 226, Section 2.9 [Ancient notation], page 388, Section 4.5.5 [Proportional notation], page 508.

Snippets: Section “Rhythms” in *Snippets*.

Internals Reference: Section “Dots” in *Internals Reference*, Section “DotColumn” in *Internals Reference*.

## Known issues and warnings

There is no fundamental limit to rest durations (both in terms of longest and shortest), but the number of glyphs is limited: rests from 128th to maxima (8 x whole) may be printed.

## Tuplets

Tuplets are made from a music expression by multiplying all the durations with a fraction:

```
\times fraction { music }
```

The duration of *music* will be multiplied by the fraction. The fraction’s denominator will be printed over or under the notes, optionally with a bracket. The most common triplet is the triplet in which 3 notes have the duration of 2, so the notes are 2/3 of their written length.

```
a2 \times 2/3 { b4 b b }
c4 c \times 2/3 { b4 a g }
```



Tuplet brackets may be manually placed above or below the staff; see [Section 5.4.2 \[Direction and placement\]](#), page 543.

Tuplets may be nested:

```
\autoBeamOff
c4 \times 4/5 { f8 e f \times 2/3 { e[ f g] } } f4
```



Modifying nested tuplets which begin at the same musical moment must be done with `\tweak`.

To modify the duration of notes without printing a tuplet bracket, see [\[Scaling durations\]](#), page 44.

## Predefined commands

`\tupletUp`, `\tupletDown`, `\tupletNeutral`.

## Selected Snippets

*Entering several tuplets using only one `\times` command*

The property `tupletSpannerDuration` sets how long each of the tuplets contained within the brackets after `\times` should last. Many consecutive tuplets can then be placed within a single `\times` expression, thus saving typing.

In the example, two triplets are shown, while `\times` was entered only once.

Read the relevant sections of the Notation Reference for more information about `ly:make-moment`.

```
\relative c' {
  \time 2/4
  \set tupletSpannerDuration = #(ly:make-moment 1 4)
  \times 2/3 { c8 c c c c c }
}
```



*Changing the tuplet number*

By default, only the numerator of the tuplet number is printed over the tuplet bracket, i.e., the denominator of the argument to the `\times` command. Alternatively, `num:den` of the tuplet number may be printed, or the tuplet number may be suppressed altogether.

```

\relative c'' {
  \times 2/3 { c8 c c }
  \times 2/3 { c8 c c }
  \override TupletNumber #'text = #tuplet-number::calc-fraction-text
  \times 2/3 { c8 c c }
  \override TupletNumber #'stencil = ##f
  \times 2/3 { c8 c c }
}

```



### *Non-default tuplet numbers*

LilyPond also provides formatting functions to print tuplet numbers different than the actual fraction, as well as to append a note value to the tuplet number or tuplet fraction.

```

\relative c'' {
  \once \override TupletNumber #'text =
    #(tuplet-number::non-default-tuplet-denominator-text 7)
  \times 2/3 { c4. c4. c4. c4. }
  \once \override TupletNumber #'text =
    #(tuplet-number::non-default-tuplet-fraction-text 12 7)
  \times 2/3 { c4. c4. c4. c4. }
  \once \override TupletNumber #'text =
    #(tuplet-number::append-note-wrapper
      (tuplet-number::non-default-tuplet-fraction-text 12 7) "8")
  \times 2/3 { c4. c4. c4. c4. }

  \once \override TupletNumber #'text =
    #(tuplet-number::append-note-wrapper
      tuplet-number::calc-denominator-text "4")
  \times 2/3 { c8 c8 c8 c8 c8 c8 }
  \once \override TupletNumber #'text =
    #(tuplet-number::append-note-wrapper
      tuplet-number::calc-fraction-text "4")
  \times 2/3 { c8 c8 c8 c8 c8 c8 }

  \once \override TupletNumber #'text =
    #(tuplet-number::fraction-with-notes "4." "8")
  \times 2/3 { c4. c4. c4. c4. }
  \once \override TupletNumber #'text =
    #(tuplet-number::non-default-fraction-with-notes 12 "8" 4 "4")
  \times 2/3 { c4. c4. c4. c4. }
}

```





### *Controlling tuplet bracket visibility*

The default behavior of tuplet-bracket visibility is to print a bracket unless there is a beam of the same length as the tuplet. To control the visibility of tuplet brackets, set the property `'bracket-visibility` to either `#t` (always print a bracket), `#f` (never print a bracket) or `#'if-no-beam` (only print a bracket if there is no beam).

```
music = \relative c' {
  \times 2/3 { c16[ d e ] f8]
  \times 2/3 { c8 d e }
  \times 2/3 { c4 d e }
}

\new Voice {
  \relative c' {
    << \music s4^"default" >>
    \override TupletBracket #'bracket-visibility = #'if-no-beam
    << \music s4^"'if-no-beam" >>
    \override TupletBracket #'bracket-visibility = ##t
    << \music s4^"#t" >>
    \override TupletBracket #'bracket-visibility = ##f
    << \music s4^"#f" >>
  }
}
```



### *Permitting line breaks within beamed tuplets*

This artificial example shows how both manual and automatic line breaks may be permitted to within a beamed tuplet. Note that such off-beat tuplets have to be beamed manually.

```

\layout {
  \context {
    \Voice
    % Permit line breaks within triplets
    \remove "Forbid_line_break_engraver"
    % Allow beams to be broken at line breaks
    \override Beam #'breakable = ##t
  }
}
\relative c'' {
  a8
  \repeat unfold 5 { \times 2/3 { c[ b a] } }
  % Insert a manual line break within a triplet
  \times 2/3 { c[ b \bar "" \break a] }
  \repeat unfold 5 { \times 2/3 { c[ b a] } }
  c8
}

```



## See also

Music Glossary: [Section “triplet”](#) in *Music Glossary*, [Section “tuplet”](#) in *Music Glossary*, [Section “polymetric”](#) in *Music Glossary*.

Learning Manual: [Section “Tweaking methods”](#) in *Learning Manual*.

Notation Reference: [\[Time administration\]](#), page 103, [\[Scaling durations\]](#), page 44, [Section 5.3.4 \[The tweak command\]](#), page 538, [\[Polymetric notation\]](#), page 66.

Snippets: [Section “Rhythms”](#) in *Snippets*.

Internals Reference: [Section “TupletBracket”](#) in *Internals Reference*, [Section “TupletNumber”](#) in *Internals Reference*, [Section “TimeScaledMusic”](#) in *Internals Reference*.

## Known issues and warnings

Grace notes may be placed within tuplet brackets, *except* when a staff begins with a grace note followed by a tuplet. In this particular case, the grace note must be placed before the `\times` command to avoid errors.

When using a tuplet at the beginning of a piece with a `\tempo` mark, the music must be explicitly entered in a `\new Voice` block, as discussed in [Section “Voices contain music”](#) in *Learning Manual*.

## Scaling durations

You can alter the duration of single notes, rests or chords by a fraction  $N/M$  by appending `*N/M` (or `*N` if  $M$  is 1) to the duration. This will not affect the appearance of the notes or rests produced, but the altered duration will be used in calculating the position within the measure

In the following example, the first three notes take up exactly two beats, but no triplet bracket is printed.

Longer stretches of music may be compressed by a fraction in the same way, as if every note, chord or rest had the fraction as a multiplier. This leaves the appearance of the music unchanged but the internal duration of the notes will be multiplied by the fraction  $num/den$ . The spaces around the dot are required. Here is an example showing how music can be compressed and expanded:

Snippets: Section “Rhythms” in *Snippets*.

## Ties

A tie connects two adjacent note heads of the same pitch. The tie in effect extends the duration of a note.

**Note:** Ties should not be confused with *slurs*, which indicate articulation, or *phrasing slurs*, which indicate musical phrasing. A tie is just a way of extending a note duration, similar to the augmentation dot.

A tie is entered using the tilde symbol (~).

a2 ~ a



Ties are used either when the note crosses a bar line, or when dots cannot be used to denote the rhythm. Ties should also be used when note values cross larger subdivisions of the measure:


```
\relative c' {
  r8 c8 ~ c2 r4 |
  r8^"not" c2 ~ c8 r4
}
```



If you need to tie many notes across bar lines, it may be easier to use automatic note splitting, see [\[Automatic note splitting\]](#), page 69. This mechanism automatically splits long notes, and ties them across bar lines.


When a tie is applied to a chord, all note heads whose pitches match are connected. When no note heads match, no ties will be created. Chords may be partially tied by placing the tie inside the chord.

```
<c e g> ~ <c e g>
<c~ e g~ b> <c e g b>
```



When a second alternative of a repeat starts with a tied note, you have to specify the repeated tie as follows:


```
\repeat volta 2 { c g <c e>2 ~ }
\alternative {
  % First alternative: following note is tied normally
  { <c e>2. r4 }
  % Second alternative: following note has a repeated tie
  { <c e>2\repeatTie d4 c } }
```





*L.v. ties* (*laissez vibrer*) indicate that notes must not be damped at the end. It is used in notation for piano, harp and other string and percussion instruments. They can be entered as follows:

```
<c f g>1\laissezVibrer
```



Ties may be manually placed above or below the staff; see [Section 5.4.2 \[Direction and placement\]](#), page 543.

Ties may be made dashed, dotted, or a combination of solid and dashed.

```
\tieDotted
c2 ~ c
\tieDashed
c2 ~ c
\tieHalfDashed
c2 ~ c
\tieHalfSolid
c2 ~ c
\tieSolid
c2 ~ c
```



Custom dash patterns can be specified:

```
\tieDashPattern #0.3 #0.75
c2 ~ c
\tieDashPattern #0.7 #1.5
c2 ~ c
\tieSolid
c2 ~ c
```



Dash pattern definitions for ties have the same structure as dash pattern definitions for slurs. For more information about complex dash patterns, see [\[Slurs\]](#), page 114.

Override *whiteout* and *layer* layout properties for ties that collide with other objects in a staff.

```
\override Tie #'layer = #-2
\override Staff.TimeSignature #'layer = #-1
\override Staff.KeySignature #'layer = #-1
\override Staff.TimeSignature #'whiteout = ##t
\override Staff.KeySignature #'whiteout = ##t
b2 b~
\time 3/4
```

```
\key a \major
b r4
```



## Predefined commands

`\tieUp`, `\tieDown`, `\tieNeutral`, `\tieDotted`, `\tieDashed`, `\tieDashPattern`, `\tieHalfDashed`, `\tieHalfSolid`, `\tieSolid`.

## Selected Snippets

### *Using ties with arpeggios*

Ties are sometimes used to write out arpeggios. In this case, two tied notes need not be consecutive. This can be achieved by setting the `tieWaitForNote` property to `#t`. The same feature is also useful, for example, to tie a tremolo to a chord, but in principle, it can also be used for ordinary consecutive notes.

```
\relative c' {
  \set tieWaitForNote = ##t
  \grace { c16[ ~ e ~ g] ~ } <c, e g>2
  \repeat tremolo 8 { c32 ~ c' ~ } <c c,>1
  e8 ~ c ~ a ~ f ~ <e' c a f>2
  \tieUp
  c8 ~ a
  \tieDown
  \tieDotted
  g8 ~ c g2
}
```



### *Engraving ties manually*

Ties may be engraved manually by changing the `tie-configuration` property of the `TieColumn` object. The first number indicates the distance from the center of the staff in half staff-spaces, and the second number indicates the direction (1 = up, -1 = down).

```
\relative c' {
  <c e g>2~ <c e g>
  \override TieColumn #'tie-configuration =
    #'((0.0 . 1) (-2.0 . 1) (-4.0 . 1))
  <c e g>2~ <c e g>
}
```



## See also

Music Glossary: [Section “tie”](#) in *Music Glossary*, [Section “laissez vibrer”](#) in *Music Glossary*.

Notation Reference: [\[Slurs\]](#), page 114, [\[Automatic note splitting\]](#), page 69.

Snippets: [Section “Expressive marks”](#) in *Snippets*, [Section “Rhythms”](#) in *Snippets*.

Internals Reference: [Section “LaissezVibrerTie”](#) in *Internals Reference*, [Section “LaissezVibrerTieColumn”](#) in *Internals Reference*, [Section “TieColumn”](#) in *Internals Reference*, [Section “Tie”](#) in *Internals Reference*.

## Known issues and warnings

Switching staves when a tie is active will not produce a slanted tie.

Changing clefs or ottavations during a tie is not really well-defined. In these cases, a slur may be preferable.


### 1.2.2 Writing rests

Rests are entered as part of the music in music expressions.

#### Rests

Rests are entered like notes with the note name `r`. Durations longer than a whole rest use the following predefined commands:

```
\new Staff {
  % These two lines are just to prettify this example
  \time 16/1
  \override Staff.TimeSignature #'stencil = ##f
  % Print a maxima rest, equal to four breves
  r\maxima
  % Print a longa rest, equal to two breves
  r\longa
  % Print a breve rest
  r\breve
  r1 r2 r4 r8 r16 r32 r64 r128
}
```



Whole measure rests, centered in the middle of the measure, must be entered as multi-measure rests. They can be used for a single measure as well as many measures and are discussed in [\[Full measure rests\]](#), page 52.

To explicitly specify a rest’s vertical position, write a note followed by `\rest`. A rest of the duration of the note will be placed at the staff position where the note would appear. This allows for precise manual formatting of polyphonic music, since the automatic rest collision formatter will not move these rests.

```
a4\rest d4\rest
```



## Selected Snippets

### *Rest styles*

Rests may be used in various styles.


```
\layout {
  indent = 0
  \context {
    \Staff
    \remove "Time_signature_engraver"
  }
}

\new Staff \relative c {
  \cadenzaOn
  \override Staff.Rest #'style = #'mensural
  r\maxima^\markup \typewriter { mensural }
  r\longa r\breve r1 r2 r4 r8 r16 s32 s64 s128 s128
  \bar ""

  \override Staff.Rest #'style = #'neomensural
  r\maxima^\markup \typewriter { neomensural }
  r\longa r\breve r1 r2 r4 r8 r16 s32 s64 s128 s128
  \bar ""

  \override Staff.Rest #'style = #'classical
  r\maxima^\markup \typewriter { classical }
  r\longa r\breve r1 r2 r4 r8 r16 r32 r64 r128 s128
  \bar ""

  \override Staff.Rest #'style = #'default
  r\maxima^\markup \typewriter { default }
  r\longa r\breve r1 r2 r4 r8 r16 r32 r64 r128 s128
}
```



## See also

Music Glossary: [Section “breve”](#) in *Music Glossary*, [Section “longa”](#) in *Music Glossary*, [Section “maxima”](#) in *Music Glossary*.

Notation Reference: [\[Full measure rests\]](#), page 52.

Snippets: [Section “Rhythms”](#) in *Snippets*.

Internals Reference: [Section “Rest”](#) in *Internals Reference*.

## Known issues and warnings

There is no fundamental limit to rest durations (both in terms of longest and shortest), but the number of glyphs is limited: there are rests from 128th to maxima (8 x whole).

## Invisible rests

An invisible rest (also called a ‘spacer rest’) can be entered like a note with the note name `s`:

```
c4 c s c
s2 c
```




Spacer rests are available only in note mode and chord mode. In other situations, for example, when entering lyrics, the command `\skip` is used to skip a musical moment. `\skip` requires an explicit duration, but this is ignored if the lyrics derive their durations from the notes in an associated melody through `\addlyrics` or `\lyricsto`.

```
<<
{
  a2 \skip2 a2 a2
}
\new Lyrics {
  \lyricmode {
    foo2 \skip 1 bla2
  }
}
>>
```



Because `\skip` is a command, it does not affect the default durations of following notes, unlike `s`.

```
<<
{
  \repeat unfold 8 { a4 }
}
{
  a4 \skip 2 a |
  s2 a
}
>>
```



A spacer rest implicitly causes **Staff** and **Voice** contexts to be created if none exist, just like notes and rests do:

```
s1 s s
```



`\skip` simply skips musical time; it creates no output of any kind.

```
% This is valid input, but does nothing
\skip 1 \skip1 \skip 1
```

## See also

Learning Manual: [Section “Visibility and color of objects”](#) in *Learning Manual*.

Notation Reference: [\[Hidden notes\]](#), page 194, [Section 5.4.6 \[Visibility of objects\]](#), page 550.


Snippets: [Section “Rhythms”](#) in *Snippets*.

Internals Reference: [Section “SkipMusic”](#) in *Internals Reference*.

## Full measure rests

Rests for one or more full measures are entered like notes with the note name uppercase R:

```
% Rest measures contracted to single measure
\compressFullBarRests
R1*4
R1*24
R1*4
b2^"Tutti" b4 a4
```



The duration of full-measure rests is identical to the duration notation used for notes. The duration in a multi-measure rest must always be an integral number of measure-lengths, so augmentation dots or fractions must often be used:

```
\compressFullBarRests
\time 2/4
R1 | R2 |
\time 3/4
R2. | R2.*2 |
\time 13/8
R1*13/8 | R1*13/8*12 |
\time 10/8
R4*5*4 |
```




A full-measure rest is printed as either a whole or breve rest, centered in the measure, depending on the time signature.

```
\time 4/4
R1 |
\time 6/4
R1*3/2 |
\time 8/4
R1*2 |
```



By default a multi-measure rest is expanded in the printed score to show all the rest measures explicitly. Alternatively, a multi-measure rest can be shown as a single measure containing a multi-measure rest symbol, with the number of measures of rest printed above the measure:

```
% Default behavior
\time 3/4 r2. | R2.*2 |
\time 2/4 R2 |
\time 4/4
% Rest measures contracted to single measure
\compressFullBarRests
r1 | R1*17 | R1*4 |
% Rest measures expanded
\expandFullBarRests
\time 3/4
R2.*2 |
```



Markups can be added to multi-measure rests. The predefined command `\fermataMarkup` is provided for adding fermatas.

```
\compressFullBarRests
\time 3/4
R2.*10^\markup { \italic "ad lib." }
R2.^ \fermataMarkup
```




**Note:** Markups attached to a multi-measure rest are objects of type `MultiMeasureRestText`, not `TextScript`. Overrides must be directed to the correct object, or they will be ignored. See the following example:

```
% This fails, as the wrong object name is specified
\override TextScript #'padding = #5
R1^"wrong"
```

```
% This is the correct object name to be specified
\override MultiMeasureRestText #'padding = #5
R1^"right"
```

right



When a multi-measure rest immediately follows a `\partial` setting, resulting bar-check warnings may not be displayed.

## Predefined commands


```
\textLengthOn,      \textLengthOff,      \fermataMarkup,      \compressFullBarRests,
\expandFullBarRests.
```

## Selected Snippets

### *Changing form of multi-measure rests*

If there are ten or fewer measures of rests, a series of longa and breve rests (called in German “Kirchenpausen” - church rests) is printed within the staff; otherwise a simple line is shown. This default number of ten may be changed by overriding the `expand-limit` property.

```
\relative c'' {
  \compressFullBarRests
  R1*2 | R1*5 | R1*9
  \override MultiMeasureRest #'expand-limit = #3
  R1*2 | R1*5 | R1*9
}
```



### *Positioning multi-measure rests*

Unlike ordinary rests, there is no predefined command to change the staff position of a multi-measure rest symbol of either form by attaching it to a note. However, in polyphonic music multi-measure rests in odd-numbered and even-numbered voices are vertically separated. The positioning of multi-measure rests can be controlled as follows:

```
\relative c'' {
  % Multi-measure rests by default are set under the fourth line
  R1
  % They can be moved using an override
  \override MultiMeasureRest #'staff-position = #-2
  R1
  \override MultiMeasureRest #'staff-position = #0
  R1
  \override MultiMeasureRest #'staff-position = #2
  R1
  \override MultiMeasureRest #'staff-position = #3
  R1
  \override MultiMeasureRest #'staff-position = #6
```



```


R1
\revert MultiMeasureRest #'staff-position
\break

% In two Voices, odd-numbered voices are under the top line
<< { R1 } \\ { a1 } >>
% Even-numbered voices are under the bottom line
<< { a1 } \\ { R1 } >>
% Multi-measure rests in both voices remain separate
<< { R1 } \\ { R1 } >>

% Separating multi-measure rests in more than two voices
% requires an override
<< { R1 } \\ { R1 } \\
  \once \override MultiMeasureRest #'staff-position = #0
  { R1 }
>>

% Using compressed bars in multiple voices requires another override
% in all voices to avoid multiple instances being printed
\compressFullBarRests
<<
  \revert MultiMeasureRest #'staff-position
  { R1*3 }
  \\
  \revert MultiMeasureRest #'staff-position
  { R1*3 }
>>
}

```



### *Multi-measure rest markup*

Markups attached to a multi-measure rest will be centered above or below it. Long markups attached to multi-measure rests do not cause the measure to expand. To expand a multi-measure rest to fit the markup, use a spacer rest with an attached markup before the multi-measure rest.


Note that the spacer rest causes a bar line to be inserted. Text attached to a spacer rest in this way is left-aligned to the position where the note would be placed in the measure, but if the measure length is determined by the length of the text, the text will appear to be centered.

```

\relative c' {
  \compressFullBarRests
  \textLengthOn
  s1*0^\markup { [MAJOR GENERAL] }
  R1*19
  s1*0_\markup { \italic { Cue: ... it is yours } }
}

```

```
s1*0^\markup { A }
R1*30^\markup { [MABEL] }
\textLengthOff
c4^\markup { CHORUS } d f c
}
```



## See also

Music Glossary: [Section “multi-measure rest” in \*Music Glossary\*](#).

Notation Reference: [\[Durations\]](#), page 38, [Section 1.8 \[Text\]](#), page 202, [Section 1.8.2 \[Formatting text\]](#), page 210, [\[Text scripts\]](#), page 202.

Snippets: [Section “Rhythms” in \*Snippets\*](#).

Internals Reference: [Section “MultiMeasureRest” in \*Internals Reference\*](#), [Section “MultiMeasureRestNumber” in \*Internals Reference\*](#), [Section “MultiMeasureRestText” in \*Internals Reference\*](#).

## Known issues and warnings

Fingerings over multi-measure rests (e.g. `R1*10-4`) may result in the fingering numeral colliding with the bar counter numeral.

There is no way to automatically condense multiple ordinary rests into a single multi-measure rest.

Multi-measure rests do not take part in rest collisions.

### 1.2.3 Displaying rhythms

#### Time signature

The time signature is set as follows:

```
\time 2/4 c2
\time 3/4 c2.
```



Time signatures are printed at the beginning of a piece and whenever the time signature changes. If a change takes place at the end of a line a warning time signature sign is printed there. This default behavior may be changed, see [Section 5.4.6 \[Visibility of objects\]](#), page 550.

```
\time 2/4
c2 c
\break
c c
\break
\time 4/4
c c c c
```



The time signature symbol that is used in 2/2 and 4/4 time can be changed to a numeric style:

```
% Default style
\time 4/4 c1
\time 2/2 c1
% Change to numeric style
\numericTimeSignature
\time 4/4 c1
\time 2/2 c1
% Revert to default style
\defaultTimeSignature
\time 4/4 c1
\time 2/2 c1
```



Mensural time signatures are covered in [\[Mensural time signatures\]](#), page 394.

In addition to setting the printed time signature, the `\time` command also sets time-signature-based default values for the properties `baseMoment`, `beatStructure`, and `beamExceptions`. The predefined default values for these properties can be found in `'scm/time-signature-settings.scm'`. The existing default values can be changed, or new default values can be added:

```
\score {
  \new Staff {
    \relative c' {
      \overrideTimeSignatureSettings
        #'(4 . 4) % timeSignatureFraction
        #'(1 . 4) % baseMomentFraction
        #'(3 1)   % beatStructure
        #'()      % beamExceptions
      \time 4/4
      \repeat unfold 8 { c8 } |
    }
  }
}
```



`\overrideTimeSignatureSettings` takes four arguments:

1. *timeSignatureFraction*, a Scheme pair describing the time signature.
2. *baseMomentFraction*, a Scheme pair containing the numerator and denominator of the basic timing unit for the time signature.
3. *beatStructure*, a Scheme list indicating the structure of the beats in the measure, in units of the base moment.
4. *beamExceptions*, an alist containing any beaming rules for the time signature that go beyond ending at every beat, as described in [\[Setting automatic beam behavior\]](#), page 74.

The context containing `\overrideTimeSignatureSettings` must be instantiated before the `\overrideTimeSignatureSettings` call is executed. That means it must either be explicitly instantiated or there must be music in the context before the `\overrideTimeSignatureSettings` call:

```
\score {
  \relative c' {
    % This call will fail because the context isn't yet instantiated
    \overrideTimeSignatureSettings
      #'(4 . 4) % timeSignatureFraction
      #'(1 . 4) % baseMomentFraction
      #'(3 1)   % beatStructure
      #'()      % beamExceptions
    \time 4/4
    c8^\markup {"Beamed (2 2)"}
    \repeat unfold 7 { c8 } |
    % This call will succeed
    \overrideTimeSignatureSettings
      #'(4 . 4) % timeSignatureFraction
      #'(1 . 4) % baseMomentFraction
      #'(3 1)   % beatStructure
      #'()      % beamExceptions
    \time 4/4
    c8^\markup {"Beamed (3 1)"}
    \repeat unfold 7 { c8 } |
  }
}
```



Changed values of default time signature properties can be restored to the original values:

```
\score{
  \relative c' {
    \repeat unfold 8 { c8 } |
    \overrideTimeSignatureSettings
      #'(4 . 4) % timeSignatureFraction
      #'(1 . 4) % baseMomentFraction
      #'(3 1)   % beatStructure
      #'()      % beamExceptions
    \time 4/4
    \repeat unfold 8 { c8 } |
    \revertTimeSignatureSettings #'(4 . 4)
  }
```

```

\time 4/4
\repeat unfold 8 { c8 } |
}
}

```




Different values of default time signature properties can be established for different staves by moving the `Timing_translator` and the `Default_bar_line_engraver` from the `Score` context to the `Staff` context.

```

\score {
  \new StaffGroup <<
    \new Staff {
      \overrideTimeSignatureSettings
        #'(4 . 4) % timeSignatureFraction
        #'(1 . 4) % baseMomentFraction
        #'(3 1)   % beatStructure
        #'()      % beamExceptions
      \time 4/4
      \repeat unfold 8 {c''8}
    }
    \new Staff {
      \overrideTimeSignatureSettings
        #'(4 . 4) % timeSignatureFraction
        #'(1 . 4) % baseMomentFraction
        #'(1 3)   % beatStructure
        #'()      % beamExceptions
      \time 4/4
      \repeat unfold 8 {c''8}
    }
  >>
  \layout {
    \context {
      \Score
      \remove "Timing_translator"
      \remove "Default_bar_line_engraver"
    }
    \context {
      \Staff
      \consists "Timing_translator"
      \consists "Default_bar_line_engraver"
    }
  }
}

```



## Predefined commands

`\numericTimeSignature`, `\defaultTimeSignature`.

## Selected Snippets

*Time signature printing only the numerator as a number (instead of the fraction)*

Sometimes, a time signature should not print the whole fraction (e.g. 7/4), but only the numerator (7 in this case). This can be easily done by using `\override Staff.TimeSignature #'style = #'single-digit` to change the style permanently. By using `\revert Staff.TimeSignature #'style`, this setting can be reversed. To apply the single-digit style to only one time signature, use the `\override` command and prefix it with a `\once`.

```
\relative c'' {
  \time 3/4
  c4 c c
  % Change the style permanently
  \override Staff.TimeSignature #'style = #'single-digit
  \time 2/4
  c4 c
  \time 3/4
  c4 c c
  % Revert to default style:
  \revert Staff.TimeSignature #'style
  \time 2/4
  c4 c
  % single-digit style only for the next time signature
  \once \override Staff.TimeSignature #'style = #'single-digit
  \time 5/4
  c4 c c c c
  \time 2/4
  c4 c
}
```



## See also

Music Glossary: [Section “time signature” in \*Music Glossary\*](#)

Notation Reference: [\[Mensural time signatures\]](#), page 394, [\[Time administration\]](#), page 103.

Snippets: [Section “Rhythms” in \*Snippets\*](#).

Internals Reference: [Section “TimeSignature” in \*Internals Reference\*](#), [Section “Timing\\_translator” in \*Internals Reference\*](#).

## Metronome marks

A basic metronome mark is simple to write:

```
\tempo 4 = 120
c2 d
e4. d8 c2
```



Metronome marks may also be printed as a range of two numbers:

```
\tempo 4 = 40 ~ 46
c4. e8 a4 g
b,2 d4 r
```



Tempo indications with text can be used instead:

```
\tempo "Allegretto"
c4 e d c
b4. a16 b c4 r4
```



Combining a metronome mark and text will automatically place the metronome mark within parentheses:

```
\tempo "Allegro" 4 = 160
g4 c d e
d4 b g2
```



In general, the text can be any markup object:

```
\tempo \markup { \italic Faster } 4 = 132
a8-. r8 b-. r gis-. r a-. r
```



A parenthesized metronome mark with no textual indication may be written by including an empty string in the input:

```
\tempo "" 8 = 96
d4 g e c
```



## Selected Snippets


### *Printing metronome and rehearsal marks below the staff*

By default, metronome and rehearsal marks are printed above the staff. To place them below the staff simply set the `direction` property of `MetronomeMark` or `RehearsalMark` appropriately.

```
\layout { ragged-right = ##f }

{
  % Metronome marks below the staff
  \override Score.MetronomeMark #'direction = #DOWN
  \tempo 8. = 120
  c''1

  % Rehearsal marks below the staff
  \override Score.RehearsalMark #'direction = #DOWN
  \mark \default
  c''1
}
```



### *Changing the tempo without a metronome mark*

To change the tempo in MIDI output without printing anything, make the metronome mark invisible.

```
\score {
  \new Staff \relative c' {
    \tempo 4 = 160
    c4 e g b
    c4 b d c
    \set Score.tempohideNote = ##t
    \tempo 4 = 96
    d,4 fis a cis
    d4 cis e d
  }
  \layout { }
  \midi { }
}
```





### *Creating metronome marks in markup mode*

New metronome marks can be created in markup mode, but they will not change the tempo in MIDI output.

```
\relative c' {
  \tempo \markup {
    \concat {
      (
        \smaller \general-align #Y #DOWN \note #"16." #1
        " = "
        \smaller \general-align #Y #DOWN \note #"8" #1
      )
    }
  }
  c1
  c4 c' c,2
}
```



For more details, see [Section 1.8.2 \[Formatting text\]](#), page 210.

### See also

Music Glossary: [Section “metronome”](#) in *Music Glossary*, [Section “metronomic indication”](#) in *Music Glossary*, [Section “tempo indication”](#) in *Music Glossary*, [Section “metronome mark”](#) in *Music Glossary*.

Notation Reference: [Section 1.8.2 \[Formatting text\]](#), page 210, [Section 3.5 \[MIDI output\]](#), page 458.

Snippets: [Section “Staff notation”](#) in *Snippets*.

Internals Reference: [Section “MetronomeMark”](#) in *Internals Reference*.

### Upbeats

Partial or pick-up measures, such as an *anacrusis* or an *upbeat*, are entered using the `\partial` command,

```
\partial duration
```

where *duration* is the *remaining* length of the partial measure *before* the start of the next full measure.

```
\time 3/4
\partial 8
e8 | a4 c8 b c4 |
```



The *duration* can be any value less than a full measure:

```
\time 3/4
\partial 4.
r4 e8 | a4 c8 b c4 |
```



The `\partial` *duration* can also be written as;

```
\set Timing.measurePosition -duration
```

So `\partial 8` becomes:

```
\time 3/4
\set Timing.measurePosition = #(ly:make-moment -1 8)
e8 | a4 c8 b c4 |
```



The property `measurePosition` contains a rational number indicating how much of the measure has passed at this point. Note that this is set to a negative number by the `\partial` command: i.e., `\partial 4` is internally translated to `-4`, meaning “there is a quarter note left in the measure.”

## See also

Music Glossary: [Section “anacrusis” in \*Music Glossary\*](#).

Notation Reference: [\[Grace notes\]](#), page 97.

Snippets: [Section “Rhythms” in \*Snippets\*](#).

Internal Reference: [Section “Timing\\_translator” in \*Internals Reference\*](#).

## Known issues and warnings

The `\partial` command should be used only at the beginning of a piece. If you use it after the beginning, warnings or problems may occur, so use `\set Timing.measurePosition` instead.

```
\time 6/8
\partial 8
e8 | a4 c8 b[ c b] |
\set Timing.measurePosition = #(ly:make-moment -1 4)
r8 e,8 | a4 c8 b[ c b] |
```



## Unmetered music

Bar lines and bar numbers are calculated automatically. For unmetered music (some cadenzas, for example), this is not desirable. To turn off automatic calculation of bar lines and bar numbers, use the command `\cadenzaOn`, and use `\cadenzaOff` to turn them on again.

```
c4 d e d
\cadenzaOn
c4 c d8[ d d] f4 g4.
```

```
\cadenzaOff
\bar "|"
d4 e d c
```



Bar numbering is resumed at the end of the cadenza as if the cadenza were not there:

```
% Show all bar numbers
\override Score.BarNumber #'break-visibility = #all-visible
c4 d e d
\cadenzaOn
c4 c d8[ d d] f4 g4.
\cadenzaOff
\bar "|"
d4 e d c
```



Automatic beaming is disabled by `\cadenzaOn` and enabled by `\cadenzaOff`. Therefore, all beaming in cadenzas must be entered manually ([\[Manual beams\]](#), page 82).

```
\repeat unfold 8 { c8 }
\cadenzaOn
\repeat unfold 5 { c8 }
\bar"|"
\cadenzaOff
\repeat unfold 8 { c8 }
```



Note that these predefined commands affect all staves in the score, even when they are placed in just one `Voice` context. To change this, move the `Timing_translator` from the `Score` context to the `Staff` context, as shown in [\[Polymetric notation\]](#), page 66.

## Predefined commands

`\cadenzaOn`, `\cadenzaOff`.

## See also

Music Glossary: [Section “cadenza”](#) in *Music Glossary*.

Notation Reference: [Section 5.4.6 \[Visibility of objects\]](#), page 550, [\[Polymetric notation\]](#), page 66, [\[Manual beams\]](#), page 82.

Snippets: [Section “Rhythms”](#) in *Snippets*.

## Known issues and warnings

LilyPond will insert line breaks and page breaks only at a bar line. Unless the unmeasured music ends before the end of the staff line, you will need to insert invisible bar lines with

```
\bar ""
```

to indicate where breaks can occur.

You should explicitly create a `Voice` context when starting a piece with `\cadenzaOn`, otherwise strange errors may occur.

```
\new Voice {
  \relative c' {
    \cadenzaOn
    c16["Solo Free Time" d e f] g2.
    \bar "||"
    \cadenzaOff
  }
}
```

## Polymetric notation

Polymetric notation is supported explicitly or by manually modifying the visible time signature symbol and/or scaling note durations.


### Different time signatures with equal-length measures

Set a common time signature for each staff, and set the `timeSignatureFraction` to the desired fraction. Then use the `\scaleDurations` function to scale the durations of the notes in each staff to the common time signature.

In the following example, music with the time signatures of  $3/4$ ,  $9/8$  and  $10/8$  are used in parallel. In the second staff, shown durations are multiplied by  $2/3$  (because  $2/3 * 9/8 = 3/4$ ) and in the third staff, the shown durations are multiplied by  $3/5$  (because  $3/5 * 10/8 = 3/4$ ). It may be necessary to insert beams manually, as the duration scaling will affect the autobeaming rules.

```
\relative c' <<
  \new Staff {
    \time 3/4
    c4 c c |
    c4 c c |
  }
  \new Staff {
    \time 3/4
    \set Staff.timeSignatureFraction = #'(9 . 8)
    \scaleDurations #'(2 . 3)
    \repeat unfold 6 { c8[ c c] }
  }
  \new Staff {
    \time 3/4
    \set Staff.timeSignatureFraction = #'(10 . 8)
    \scaleDurations #'(3 . 5) {
      \repeat unfold 2 { c8[ c c] }
      \repeat unfold 2 { c8[ c] } |
      c4. c \times 2/3 { c8[ c c] } c4
    }
  }
}
```

&gt;&gt;



### Different time signatures with unequal-length measures


Each staff can be given its own independent time signature by moving the `Timing_translator` and the `Default_bar_line_engraver` to the `Staff` context.

```
\layout {
  \context {
    \Score
    \remove "Timing_translator"
    \remove "Default_bar_line_engraver"
  }
  \context {
    \Staff
    \consists "Timing_translator"
    \consists "Default_bar_line_engraver"
  }
}

% Now each staff has its own time signature.

\relative c' <<
  \new Staff {
    \time 3/4
    c4 c c |
    c4 c c |
  }
  \new Staff {
    \time 2/4
    c4 c |
    c4 c |
    c4 c |
  }
  \new Staff {
    \time 3/8
    c4. |
    c8 c c |
    c4. |
    c8 c c |
  }
}
```

&gt;&gt;



## Compound time signatures

These are created using the `\compoundMeter` function. The syntax for this is:

```
\compoundMeter #'(list of lists)
```

The simplest construction is a single list, where the *last* number indicates the bottom number of the time signature and those that come before it, the top numbers.

```
\relative c' {
  \compoundMeter #'((2 2 2 8))
  \repeat unfold 6 c8 \repeat unfold 12 c16
}
```



More complex meters can be constructed using additional lists. Also, automatic beaming settings will be adjusted depending on the values.

```
\relative c' {
  \compoundMeter #'((1 4) (3 8))
  \repeat unfold 5 c8 \repeat unfold 10 c16
}
```

```
\relative c' {
  \compoundMeter #'((1 2 3 8) (3 4))
  \repeat unfold 12 c8
}
```



## See also

Music Glossary: [Section “polymetric” in \*Music Glossary\*](#), [Section “polymetric time signature” in \*Music Glossary\*](#), [Section “meter” in \*Music Glossary\*](#).

Notation Reference: [\[Automatic beams\]](#), page 72, [\[Manual beams\]](#), page 82, [\[Time signature\]](#), page 56, [\[Scaling durations\]](#), page 44.

Snippets: [Section “Rhythms” in \*Snippets\*](#).

Internals Reference: [Section “TimeSignature” in \*Internals Reference\*](#), [Section “Timing-translator” in \*Internals Reference\*](#), [Section “Default\\_bar\\_line-engraver” in \*Internals Reference\*](#), [Section “Staff” in \*Internals Reference\*](#).

## Known issues and warnings

When using different time signatures in parallel, notes at the same moment will be placed at the same horizontal location. However, the bar lines in the different staves will cause the note spacing to be less regular in each of the individual staves than would be normal without the different time signatures.

## Automatic note splitting

Long notes which overrun bar lines can be converted automatically to tied notes. This is done by replacing the `Note_heads_engraver` with the `Completion_heads_engraver`. Similarly, long rests which overrun bar lines are split automatically by replacing the `Rest_engraver` with the `Completion_rest_engraver`. In the following example, notes and rests crossing the bar lines are split, notes are also tied.

```
\new Voice \with {
  \remove "Note_heads_engraver"
  \consists "Completion_heads_engraver"
  \remove "Rest_engraver"
  \consists "Completion_rest_engraver"
}

{ c2. c8 d4 e f g a b c8 c2 b4 a g16 f4 e d c8. c2 r1*2 }
```



These engravers split all running notes and rests at the bar line, and inserts ties for notes. One of its uses is to debug complex scores: if the measures are not entirely filled, then the ties show exactly how much each measure is off.

## See also

Music Glossary: [Section “tie” in \*Music Glossary\*](#)

Learning Manual: [Section “Engravers explained” in \*Learning Manual\*](#), [Section “Adding and removing engravers” in \*Learning Manual\*](#).

Snippets: [Section “Rhythms” in \*Snippets\*](#).

Internals Reference: [Section “Note\\_heads\\_engraver” in \*Internals Reference\*](#), [Section “Completion\\_heads\\_engraver” in \*Internals Reference\*](#), [Section “Rest\\_engraver” in \*Internals Reference\*](#), [Section “Completion\\_rest\\_engraver” in \*Internals Reference\*](#), [Section “Forbid\\_line\\_break\\_engraver” in \*Internals Reference\*](#).

## Known issues and warnings


Not all durations (especially those containing tuplets) can be represented exactly with normal notes and dots, but the `Completion_heads_engraver` will not insert tuplets.

The `Completion_heads_engraver` only affects notes; it does not split rests.

## Showing melody rhythms


Sometimes you might want to show only the rhythm of a melody. This can be done with the rhythmic staff. All pitches of notes on such a staff are squashed, and the staff itself has a single line

```
<<
  \new RhythmicStaff {
    \new Voice = "myRhythm" {
      \time 4/4
      c4 e8 f g2
      r4 g g f
      g1
    }
  }
  \new Lyrics {
    \lyricsto "myRhythm" {
      This is my song
      I like to sing
    }
  }
>>
```



Guitar chord charts often show the strumming rhythms. This can be done with the `Pitch_squash_engraver` and `\improvisationOn`.

```
<<
  \new ChordNames {
    \chordmode {
      c1 f g c
    }
  }
  \new Voice \with {
    \consists Pitch_squash_engraver
  } \relative c'' {
    \improvisationOn
    c4 c8 c c4 c8 c
    f4 f8 f f4 f8 f
    g4 g8 g g4 g8 g
    c4 c8 c c4 c8 c
  }
>>
```



## Predefined commands

`\improvisationOn`, `\improvisationOff`.



## Selected Snippets

### *Guitar strum rhythms*

For guitar music, it is possible to show strum rhythms, along with melody notes, chord names and fret diagrams.

```
\include "predefined-guitar-fretboards.ly"
<<
  \new ChordNames {
    \chordmode {
      c1 | f | g | c
    }
  }
  \new FretBoards {
    \chordmode {
      c1 | f | g | c
    }
  }
  \new Voice \with {
    \consists "Pitch_squash_engraver"
  } {
    \relative c'' {
      \improvisationOn
      c4 c8 c c4 c8 c
      f4 f8 f f4 f8 f
      g4 g8 g g4 g8 g
      c4 c8 c c4 c8 c
    }
  }
  \new Voice = "melody" {
    \relative c'' {
      c2 e4 e4
      f2. r4
      g2. a4
      e4 c2.
    }
  }
  \new Lyrics {
    \lyricsto "melody" {
      This is my song.
      I like to sing.
    }
  }
>>
```

The image shows two systems of musical notation. The first system consists of two staves. Above the first staff are three guitar chord diagrams: C (with fret numbers 3, 2, 1), F (with fret numbers 1, 3, 4, 2, 1, 1), and G (with fret numbers 2, 1, 3). The first staff has a treble clef and a common time signature 'C'. It contains a series of eighth notes with beams. The second staff has a treble clef and a common time signature 'C'. It contains a series of eighth notes with beams. Below the staves are the lyrics: "This is my song. I like".

The second system also consists of two staves. Above the first staff is a guitar chord diagram: C (with fret numbers 3, 2, 1). The first staff has a treble clef and a common time signature 'C'. It contains a series of eighth notes with beams. The second staff has a treble clef and a common time signature 'C'. It contains a series of eighth notes with beams. Below the staves are the lyrics: "to sing."

## See also

Snippets: [Section “Rhythms” in \*Snippets\*](#).

Internals Reference: [Section “RhythmicStaff” in \*Internals Reference\*](#), [Section “Pitch\\_squash\\_engraver” in \*Internals Reference\*](#).

## 1.2.4 Beams

### Automatic beams

By default, beams are inserted automatically:

```
\time 2/4 c8 c c c
\time 6/8 c8 c c c8. c16 c8
```

The image shows a musical staff with a treble clef. The first measure has a 2/4 time signature and contains four eighth notes beamed together. The second measure has a 6/8 time signature and contains a quarter note, two eighth notes, and a quarter note, all beamed together.

If these automatic decisions are not satisfactory, beaming can be entered explicitly; see [\[Manual beams\]](#), page 82. Beams *must* be entered manually if beams are to be extended over rests.

If automatic beaming is not required, it may be turned off with `\autoBeamOff` and on with `\autoBeamOn`:

```
c4 c8 c8. c16 c8. c16 c8
\autoBeamOff
c4 c8 c8. c16 c8.
\autoBeamOn
c16 c8
```

The image shows a musical staff with a treble clef and a common time signature 'C'. It contains a series of eighth notes with beams, some of which are explicitly beamed together.

**Note:** If beams are used to indicate melismata in songs, then automatic beaming should be switched off with `\autoBeamOff` and the beams indicated manually. Using `\partcombine` with `\autoBeamOff` can produce unintended results. See the snippets for more information.

Beaming patterns that differ from the automatic defaults can be created; see [\[Setting automatic beam behavior\]](#), page 74.

## Predefined commands

`\autoBeamOff`, `\autoBeamOn`.

## Selected Snippets

### *Beams across line breaks*

Line breaks are normally forbidden when beams cross bar lines. This behavior can be changed as shown:

```
\relative c'' {
  \override Beam #'breakable = ##t
  c8 c[ c] c[ c] c[ c] c[ \break
  c8] c[ c] c[ c] c[ c] c
}
```



### *Changing beam knee gap*

Kneed beams are inserted automatically when a large gap is detected between the note heads. This behavior can be tuned through the `auto-knee-gap` property. A kneed beam is drawn if the gap is larger than the value of `auto-knee-gap` plus the width of the beam object (which depends on the duration of the notes and the slope of the beam). By default `auto-knee-gap` is set to 5.5 staff spaces.

```
{
  f8 f''8 f8 f''8
  \override Beam #'auto-knee-gap = #6
  f8 f''8 f8 f''8
}
```



### *Partcombine and autoBeamOff*

The function of `\autoBeamOff` when used with `\partcombine` can be difficult to understand. It may be preferable to use

```
\set Staff.autoBeaming = ##f
```

instead, to ensure that autobeaming will be turned off for the entire staff.

`\partcombine` apparently works with 3 voices – stem up single, stem down single, stem up combined.

An `\autoBeamOff` call in the first argument to `partcombine` will apply to the voice that is active at the time the call is processed, either stem up single or stem up combined. An `\autoBeamOff` call in the second argument will apply to the voice that is stem down single.

In order to use `\autoBeamOff` to stop all autobeaming when used with `\partcombine`, it will be necessary to use three calls to `\autoBeamOff`.

```
{
  \% \set Staff.autoBeaming = ##f % turns off all autobeaming
  \partcombine
  {
    \autoBeamOff % applies to split up stems
    \repeat unfold 4 a'16
    \% \autoBeamOff % applies to combined up stems
    \repeat unfold 4 a'8
    \repeat unfold 4 a'16
  }
  {
    \autoBeamOff % applies to down stems
    \repeat unfold 4 f'8
    \repeat unfold 8 f'16 |
  }
}
```



## See also

Notation Reference: [\[Manual beams\]](#), page 82, [\[Setting automatic beam behavior\]](#), page 74.

Installed Files: ‘`scm/auto-beam.scm`’.

Snippets: [Section “Rhythms” in \*Snippets\*](#).

Internals Reference: [Section “Auto\\_beam-engraver” in \*Internals Reference\*](#), [Section “Beam-engraver” in \*Internals Reference\*](#), [Section “Beam” in \*Internals Reference\*](#), [Section “BeamEvent” in \*Internals Reference\*](#), [Section “BeamForbidEvent” in \*Internals Reference\*](#), [Section “beam-interface” in \*Internals Reference\*](#), [Section “unbreakable-spanner-interface” in \*Internals Reference\*](#).

## Known issues and warnings

The properties of a beam are determined at the *start* of its construction and any additional beam-property changes that occur before the beam has been completed will not take effect until the *next*, new beam starts.

## Setting automatic beam behavior

In most instances, automatic beams will end at the end of a beat. The ending points for beats are determined by the context properties `baseMoment` and `beatStructure`. `beatStructure` is a scheme list that defines the length of each beat in the measure in units of `baseMoment`. By

default, `baseMoment` is the one over numerator of the time signature. By default, each unit of length `baseMoment` is a single beat.

```
\time 5/16
c16^"default" c c c c |
\set Timing.beatStructure = #'(2 3)
c16^(2+3)" c c c c |
\set Timing.beatStructure = #'(3 2)
c16^(3+2)" c c c c |
```



Beam setting changes can be limited to specific contexts. If no setting is included in a lower-level context, the setting of the enclosing context will apply.

```
\new Staff {
  \time 7/8
  \set Staff.beatStructure = #'(2 3 2)
  <<
    \new Voice = one {
      \relative c'' {
        a8 a a a a a a
      }
    }
    \new Voice = two {
      \relative c' {
        \voiceTwo
        \set Voice.beatStructure = #'(1 3 3)
        f8 f f f f f f
      }
    }
  >>
}
```



When multiple voices are used the `Staff` context must be specified if the beaming is to be applied to all voices in the staff:

```
\time 7/8
% rhythm 3-1-1-2
% Change applied to Voice by default -- does not work correctly
% Because of autogenerated voices, all beaming will
% be at baseMoment (1 . 8)
\set beatStructure = #'(3 1 1 2)
<< {a8 a a a16 a a a a8 a} \\ {f4. f8 f f f} >>

% Works correctly with context Staff specified
\set Staff.beatStructure = #'(3 1 1 2)
<< {a8 a a a16 a a a a8 a} \\ {f4. f8 f f f} >>
```



The value of `baseMoment` can be adjusted to change the beaming behavior, if desired. When this is done, the value of `beatStructure` must be set to be compatible with the new value of `baseMoment`.

```
\time 5/8
\set Timing.baseMoment = #(ly:make-moment 1 16)
\set Timing.beatStructure = #'(7 3)
\repeat unfold 10 { a16 }
```



`baseMoment` is a *moment*; a unit of musical duration. A quantity of type *moment* is created by the scheme function `ly:make-moment`. For more information about this function, see [\[Time administration\]](#), page 103.

By default `baseMoment` is set to one over the denominator of the time signature. Any exceptions to this default can be found in ‘`scheme/time-signature-settings.scm`’.

Special autobeaming rules (other than ending a beam on a beat) are defined in the `beamExceptions` property.

```
\time 3/16
\set Timing.beatStructure = #'(2 1)
\set Timing.beamExceptions =
  #'(
    (end . ;start of alist
      ( ;entry for end of beams
        ( ;start of alist of end points
          ((1 . 32) . (2 2 2)) ;rule for 1/32 beams -- end each 1/16
        ))
      )
    )
  %close all entries
c16 c c |
\repeat unfold 6 { c32 } |
```



`beamExceptions` is an alist with a key of rule-type and a value of beaming-rules.

At this time the only available value of rule-type is ‘`end`’ for beam ending.

Beaming-rules is a scheme alist (or list of pairs) that indicates the beam type and the grouping to be applied to beams containing notes with a shortest duration of that beam type.

```
#'((beam-type1 . grouping-1)
   (beam-type2 . grouping-2)
   (beam-type3 . grouping-3))
```

Beam type is a scheme pair indicating the duration of the beam, e.g., `(1 . 16)`.

Grouping is a scheme list indicating the grouping to be applied to the beam. The grouping is in units of the beam type.

**Note:** A `beamExceptions` value must be *complete* exceptions list. That is, every exception that should be applied must be included in the setting. It is not possible to add, remove, or change only one of the exceptions. While this may seem cumbersome, it means that the current beaming settings need not be known in order to specify a new beaming pattern.

When the time signature is changed, default values of `Timing.baseMoment`, `Timing.beatStructure`, and `Timing.beamExceptions` are set. Setting the time signature will reset the automatic beaming settings for the `Timing` context to the default behavior.

```
\time 6/8
\repeat unfold 6 { a8 }
% group (4 + 2)
\set Timing.beatStructure = #'(4 2)
\repeat unfold 6 { a8 }
% go back to default behavior
\time 6/8
\repeat unfold 6 { a8 }
```



The default automatic beaming settings for a time signature are determined in `'scm/time-signature-settings.scm'`. Changing the default automatic beaming settings for a time signature is described in [\[Time signature\]](#), page 56.

Many automatic beaming settings for a time signature contain an entry for `beamExceptions`. For example, 4/4 time tries to beam the measure in two if there are only eighth notes. The `beamExceptions` rule can override the `beatStructure` setting if `beamExceptions` is not reset.

```
\time 4/4
\set Timing.baseMoment = #(ly:make-moment 1 8)
\set Timing.beatStructure = #'(3 3 2)
% This won't beam (3 3 2) because of beamExceptions
\repeat unfold 8 {c8} |
% This will beam (3 3 2) because we clear beamExceptions
\set Timing.beamExceptions = #'()
\repeat unfold 8 {c8}
```



In a similar fashion, eighth notes in 3/4 time are beamed as a full measure by default. To beam eighth notes in 3/4 time on the beat, reset `beamExceptions`.

```
\time 3/4
% by default we beam in (3) due to beamExceptions
\repeat unfold 6 {a8} |
% This will beam (1 1 1) due to beatLength
\set Timing.beamExceptions = #'()
\repeat unfold 6 {a8}
```



### How automatic beaming works

When automatic beaming is enabled, the placement of automatic beams is determined by the context properties `baseMoment`, `beatStructure`, and `beamExceptions`.

The following rules, in order of priority, apply when determining the appearance of beams:

- If a manual beam is specified with `[.]` set the beam as specified, otherwise
- if a beam-ending rule is defined in `beamExceptions` for the beam-type, use it to determine the valid places where beams may end, otherwise
- if a beam-ending rule is defined in `beamExceptions` for a longer beam-type, use it to determine the valid places where beams may end, otherwise
- use the values of `baseMoment` and `beatStructure` to determine the ends of the beats in the measure, and end beams at the end of beats.

In the rules above, the *beam-type* is the duration of the shortest note in the beamed group.

The default beaming rules can be found in `'scm/time-signature-settings.scm'`.

## Selected Snippets

### *Subdividing beams*

The beams of consecutive 16th (or shorter) notes are, by default, not subdivided. That is, the three (or more) beams stretch unbroken over entire groups of notes. This behavior can be modified to subdivide the beams into sub-groups by setting the property `subdivideBeams`. When set, multiple beams will be subdivided at intervals defined by the current value of `baseMoment` by reducing the multiple beams to just one beam between the sub-groups. Note that `baseMoment` defaults to one over the denominator of the current time signature if not set explicitly. It must be set to a fraction giving the duration of the beam sub-group using the `ly:make-moment` function, as shown in this snippet. Also, when `baseMoment` is changed, `beatStructure` should also be changed to match the new `baseMoment`:

```
\relative c'' {
  c32[ c c c c c c c]
  \set subdivideBeams = ##t
  c32[ c c c c c c c]

  % Set beam sub-group length to an eighth note
  \set baseMoment = #(ly:make-moment 1 8)
  \set beatStructure = #'(2 2 2 2)
  c32[ c c c c c c c]

  % Set beam sub-group length to a sixteenth note
  \set baseMoment = #(ly:make-moment 1 16)
  \set beatStructure = #'(4 4 4 4)
  c32[ c c c c c c c]
}
```



### *Strict beat beaming*

Beamlets can be set to point in the direction of the beat to which they belong. The first beam avoids sticking out flags (the default); the second beam strictly follows the beat.



```

\relative c'' {
  \time 6/8
  a8. a16 a a
  \set strictBeatBeaming = ##t
  a8. a16 a a
}

```



### *Conducting signs measure grouping signs*

Beat grouping within a measure is controlled by the context property `beatStructure`. Values of `beatStructure` are established for many time signatures in ‘`scm/time-signature-settings.scm`’. Values of `beatStructure` can be changed or set with `\set`. Alternatively, `\time` can be used to both set the time signature and establish the beat structure. For this, you specify the internal grouping of beats in a measure as a list of numbers (in Scheme syntax) before the time signature.


`\time` applies to the `Timing` context, so it will not reset values of `beatStructure` or `baseMoment` that are set in other lower-level contexts, such as `Voice`.

If the `Measure_grouping_engraver` is included in one of the display contexts, measure grouping signs will be created. Such signs ease reading rhythmically complex modern music. In the example, the 9/8 measure is grouped in two different patterns using the two different methods, while the 5/8 measure is grouped according to the default setting in ‘`scm/time-signature-settings.scm`’:

```

\score {
  \new Voice \relative c'' {
    \time 9/8
    g8 g d d g g a( bes g) |
    \set Timing.beatStructure = #'(2 2 2 3)
    g8 g d d g g a( bes g) |
    \time #'(4 5) 9/8
    g8 g d d g g a( bes g) |
    \time 5/8
    a4. g4 |
  }
  \layout {
    \context {
      \Staff
      \consists "Measure_grouping_engraver"
    }
  }
}

```






### *Beam endings in Score context*

Beat structure rules specified in the **Score** context apply to all staves, but can be modified at both **Staff** and **Voice** levels:

```
\relative c'' {
  \time 5/4
  % Set default beaming for all staves
  \set Score.baseMoment = #(ly:make-moment 1 8)
  \set Score.beatStructure = #'(3 4 3)
  <<
    \new Staff {
      c8 c c c c c c c c c
    }
    \new Staff {
      % Modify beaming for just this staff
      \set Staff.beatStructure = #'(6 4)
      c8 c c c c c c c c c
    }
    \new Staff {
      % Inherit beaming from Score context
      <<
        {
          \voiceOne
          c8 c c c c c c c c c
        }
        % Modify beaming for this voice only
        \new Voice {
          \voiceTwo
          \set Voice.beatStructure = #'(6 4)
          a8 a a a a a a a a a
        }
      >>
    }
  >>
}
```



See also

Installed Files: 'scm/beam-settings.scm'.

Snippets: [Section “Rhythms” in \*Snippets\*](#).


Internals Reference: [Section “Auto\\_beam\\_engraver” in \*Internals Reference\*](#), [Section “Beam” in \*Internals Reference\*](#), [Section “BeamForbidEvent” in \*Internals Reference\*](#), [Section “beam-interface” in \*Internals Reference\*](#).

## Known issues and warnings

If a score ends while an automatic beam has not been ended and is still accepting notes, this last beam will not be typeset at all. The same holds for polyphonic voices, entered with `<< ... \\ ... >>`. If a polyphonic voice ends while an automatic beam is still accepting notes, it is not typeset. The workaround for these problems is to manually beam the last beam in the voice or score.

By default, the `Timing` translator is aliased to the `Score` context. This means that setting the time signature in one staff will affect the beaming of the other staves as well. Thus, a time signature setting in a later staff will reset custom beaming that was set in an earlier staff. One way to avoid this problem is to set the time signature in only one staff.


```
<<
  \new Staff {
    \time 3/4
    \set Timing.baseMoment = #(ly:make-moment 1 8)
    \set Timing.beatStructure = #'(1 5)
    \repeat unfold 6 { a8 }
  }
  \new Staff {
    \repeat unfold 6 { a8 }
  }
>>
```



The default beam settings for the time signature can also be changed, so that the desired beaming will always be used. Changes in automatic beaming settings for a time signature are described in [\[Time signature\]](#), [page 56](#).

```
<<
  \new Staff {
    \overrideTimeSignatureSettings
      #'(3 . 4)          % timeSignatureFraction
      #'(1 . 8)          % baseMomentFraction
      #'(1 5)           % beatStructure
      #'()              % beamExceptions
    \time 3/4
    \repeat unfold 6 { a8 }
  }
  \new Staff {
    \time 3/4
    \repeat unfold 6 { a8 }
  }
>>
```

&gt;&gt;



## Manual beams

In some cases it may be necessary to override the automatic beaming algorithm. For example, the autobeamer will not put beams over rests or bar lines, and in choral scores the beaming is often set to follow the meter of the lyrics rather than the notes. Such beams can be specified manually by marking the begin and end point with [ and ].

```
r4 r8[ g' a r] r g[ | a] r
```



Beaming direction can be set manually using direction indicators:

```
c8^[ d e] c,[ d e f g]
```




Individual notes may be marked with `\noBeam` to prevent them from being beamed:

```
\time 2/4
c8 c\noBeam c c
```



Grace note beams and normal note beams can occur simultaneously. Unbeamed grace notes are not put into normal note beams.

```
c4 d8[
\grace { e32[ d c d] }
e8] e[ e
\grace { f16 }
e8 e]
```



Even more strict manual control with the beams can be achieved by setting the properties `stemLeftBeamCount` and `stemRightBeamCount`. They specify the number of beams to draw on the left and right side, respectively, of the next note. If either property is set, its value will be used only once, and then it is erased. In this example, the last `f` is printed with only one beam on the left side, i.e., the eighth-note beam of the group as a whole.

```

a8[ r16 f g a]
a8[ r16
\set stemLeftBeamCount = #2
\set stemRightBeamCount = #1
f16
\set stemLeftBeamCount = #1
g16 a]

```



## Predefined commands

`\noBeam.`

## Selected Snippets

### *Flat flags and beam nubs*

Flat flags on lone notes and beam nubs at the ends of beamed figures are both possible with a combination of `stemLeftBeamCount`, `stemRightBeamCount` and paired `[]` beam indicators.

For right-pointing flat flags on lone notes, use paired `[]` beam indicators and set `stemLeftBeamCount` to zero (see Example 1).

For left-pointing flat flags, set `stemRightBeamCount` instead (Example 2).

For right-pointing nubs at the end of a run of beamed notes, set `stemRightBeamCount` to a positive value. And for left-pointing nubs at the start of a run of beamed notes, set `stemLeftBeamCount` instead (Example 3).

Sometimes it may make sense for a lone note surrounded by rests to carry both a left- and right-pointing flat flag. Do this with paired `[]` beam indicators alone (Example 4).

(Note that `\set stemLeftBeamCount` is always equivalent to `\once \set`. In other words, the beam count settings are not “sticky”, so the pair of flat flags attached to the lone `c'16[]` in the last example have nothing to do with the `\set` two notes prior.)

```


\score {
  <<
    % Example 1
    \new RhythmicStaff {
      \set stemLeftBeamCount = #0
      c16[]
      r8.
    }
    % Example 2
    \new RhythmicStaff {
      r8.
      \set stemRightBeamCount = #0
      c16[]
    }
    % Example 3
    \new RhythmicStaff {
      c16 c
      \set stemRightBeamCount = #2
      c16 r r
    }
  }
}

```

```

    \set stemLeftBeamCount = #2
    c16 c c
  }
  % Example 4
  \new RhythmicStaff {
    c16 c
    \set stemRightBeamCount = #2
    c16 r
    c16[]
    r16
    \set stemLeftBeamCount = #2
    c16 c
  }
  >>
}

```



## See also

Notation Reference: [Section 5.4.2 \[Direction and placement\]](#), page 543, [\[Grace notes\]](#), page 97.

Snippets: [Section “Rhythms” in \*Snippets\*](#).

Internals Reference: [Section “Beam” in \*Internals Reference\*](#), [Section “BeamEvent” in \*Internals Reference\*](#), [Section “Beam\\_engraver” in \*Internals Reference\*](#), [Section “beam-interface” in \*Internals Reference\*](#), [Section “Stem\\_engraver” in \*Internals Reference\*](#).

## Feathered beams

Feathered beams are used to indicate that a small group of notes should be played at an increasing (or decreasing) tempo, without changing the overall tempo of the piece. The extent of the feathered beam must be indicated manually using [ and ], and the beam feathering is turned on by specifying a direction to the **Beam** property **grow-direction**.

If the placement of the notes and the sound in the MIDI output is to reflect the *ritardando* or *accelerando* indicated by the feathered beam the notes must be grouped as a music expression delimited by braces and preceded by a **featherDurations** command which specifies the ratio between the durations of the first and last notes in the group.

The square brackets show the extent of the beam and the braces show which notes are to have their durations modified. Normally these would delimit the same group of notes, but this is not required: the two commands are independent.

In the following example the eight 16th notes occupy exactly the same time as a half note, but the first note is one half as long as the last one, with the intermediate notes gradually lengthening. The first four 32nd notes gradually speed up, while the last four 32nd notes are at a constant tempo.

```
\override Beam #'grow-direction = #LEFT
\featherDurations #(ly:make-moment 2 1)
{ c16[ c c c c c c c c] }
\override Beam #'grow-direction = #RIGHT
\featherDurations #(ly:make-moment 2 3)
{ c32[ d e f] }
% revert to non-feathered beams
\override Beam #'grow-direction = #'()
{ g32[ a b c] }
```



The spacing in the printed output represents the note durations only approximately, but the MIDI output is exact.

## Predefined commands

`\featherDurations`.

## See also

Snippets: [Section “Rhythms” in \*Snippets\*](#).

## Known issues and warnings

The `\featherDurations` command only works with very short music snippets, and when numbers in the fraction are small.

### 1.2.5 Bars

#### Bar lines

Bar lines delimit measures, and are also used to indicate repeats. Normally, simple bar lines are automatically inserted into the printed output at places based on the current time signature.

The simple bar lines inserted automatically can be changed to other types with the `\bar` command. For example, a closing double bar line is usually placed at the end of a piece:

```
e4 d c2 \bar "|."
```



It is not invalid if the final note in a measure does not end on the automatically entered bar line: the note is assumed to carry over into the next measure. But if a long sequence of such carry-over measures appears the music can appear compressed or even flowing off the page. This is because automatic line breaks happen only at the end of complete measures, i.e., where all notes end before the end of a measure.

**Note:** An incorrect duration can cause line breaks to be inhibited, leading to a line of highly compressed music or music which flows off the page.

Line breaks are also permitted at manually inserted bar lines even within incomplete measures. To allow a line break without printing a bar line, use the following:

```
\bar ""
```

This will insert an invisible bar line and allow (but not force) a line break to occur at this point. The bar number counter is not increased. To force a line break see [Section 4.3.1 \[Line breaking\]](#), page 480.

This and other special bar lines may be inserted manually at any point. When they coincide with the end of a measure they replace the simple bar line which would have been inserted there automatically. When they do not coincide with the end of a measure the specified bar line is inserted at that point in the printed output.

Note that manual bar lines are purely visual. They do not affect any of the properties that a normal bar line would affect, such as measure numbers, accidentals, line breaks, etc. They do not affect the calculation and placement of subsequent automatic bar lines. When a manual bar line is placed where a normal bar line already exists, the effects of the original bar line are not altered.


Two types of simple bar lines and five types of double bar lines are available for manual insertion:

```
f1 \bar "|"
f1 \bar "."
g1 \bar "||"
a1 \bar ".|"
b1 \bar ".|."
c1 \bar "|.|"
d1 \bar "|.|"
e1
```



together with dotted and dashed bar lines:


```
f1 \bar ":"
g1 \bar "dashed"
a1
```



and five types of repeat bar line:

```
f1 \bar "|:"
g1 \bar "||:"
a1 \bar "||.|"
b1 \bar "||.|"
c1 \bar "||.|"
e1
```





Additionally, a bar line can be printed as a simple tick:

```
f1 \bar "'
```



However, as such ticks are typically used in Gregorian chant, it is preferable to use `\divisioMinima` there instead, described in the section [\[Divisiones\]](#), [page 401](#) in Gregorian chant.

For in-line segno signs, there are three types of bar lines which differ in their behavior at line breaks:

```
c4 c c c
\bar "S"
c4 c c c \break
\bar "S"
c4 c c c
\bar "|S"
c4 c c c \break
\bar "|S"
c4 c c c
\bar "S|"
c4 c c c \break
\bar "S|"
c1
```




Although the bar line types signifying repeats may be inserted manually they do not in themselves cause LilyPond to recognize a repeated section. Such repeated sections are better entered using the various repeat commands (see [Section 1.4 \[Repeats\]](#), [page 127](#)), which automatically print the appropriate bar lines.

In addition, you can specify `"|:|:"`, which is equivalent to `"|:"` except at line breaks, where it gives a double bar line at the end of the line and a start repeat at the beginning of the next line.

```

c4 c c c
\bar "||:"
c4 c c c \break
\bar "||:"
c4 c c c

```



For combinations of repeats with the segno sign, there are six different variations:

```

c4 c c c
\bar " :|S"
c4 c c c \break
\bar " :|S"
c4 c c c
\bar " :|S."
c4 c c c \break
\bar " :|S."
c4 c c c
\bar "S|:"
c4 c c c \break
\bar "S|:"
c4 c c c
\bar ".S|:"
c4 c c c \break
\bar ".S|:"
c4 c c c
\bar " :|S|:"
c4 c c c \break
\bar " :|S|:"
c4 c c c
\bar " :|S.|:"
c4 c c c \break
\bar " :|S.|:"
c1

```





In scores with many staves, a `\bar` command in one staff is automatically applied to all staves. The resulting bar lines are connected between different staves of a `StaffGroup`, `PianoStaff`, or `GrandStaff`.

```
<<
  \new StaffGroup <<
    \new Staff {
      e4 d
      \bar "||"
      f4 e
    }
    \new Staff { \clef bass c4 g e g }
  >>
  \new Staff { \clef bass c2 c2 }
>>
```



## Selected Snippets

The command `'\bar bartype'` is a shortcut for `'\set Timing.whichBar = bartype'`. A bar line is created whenever the `whichBar` property is set.

The default bar type used for automatically inserted bar lines is `"|"`. This may be changed at any time with `'\set Timing.defaultBarType = bartype'`.

## See also

Notation Reference: [Section 4.3.1 \[Line breaking\]](#), page 480, [Section 1.4 \[Repeats\]](#), page 127, [\[Grouping staves\]](#), page 163.


Snippets: [Section “Rhythms” in \*Snippets\*](#).

Internals Reference: [Section “BarLine” in \*Internals Reference\*](#) (created at **Staff** level), [Section “SpanBar” in \*Internals Reference\*](#) (across staves), [Section “Timing-translator” in \*Internals Reference\*](#) (for Timing properties).

## Bar numbers


Bar numbers are typeset by default at the start of every line except the first line. The number itself is stored in the `currentBarNumber` property, which is normally updated automatically for every measure. It may also be set manually:

```
c1 c c c
\break
\set Score.currentBarNumber = #50
c1 c c c
```



Bar numbers can be typeset at regular intervals instead of just at the beginning of every line. To do this the default behavior must be overridden to permit bar numbers to be printed at places other than the start of a line. This is controlled by the `break-visibility` property of `BarNumber`. This takes three values which may be set to `#t` or `#f` to specify whether the corresponding bar number is visible or not. The order of the three values is `end of line visible`, `middle of line visible`, `beginning of line visible`. In the following example bar numbers are printed at all possible places:

```
\override Score.BarNumber #'break-visibility = #'(#t #t #t)
\set Score.currentBarNumber = #11
% Permit first bar number to be printed
\bar ""
c1 | c | c | c
\break
c1 | c | c | c
```




## Selected Snippets

### *Printing the bar number for the first measure*

By default, the first bar number in a score is suppressed if it is less than or equal to ‘1’. By setting `barNumberVisibility` to `all-bar-numbers-visible`, any bar number can be printed for the first measure and all subsequent measures. Note that an empty bar line must be inserted before the first note for this to work.


```
\relative c' {
  \set Score.barNumberVisibility = #all-bar-numbers-visible
  \bar ""
  c1 | d | e | f \break
  g1 | e | d | c
}
```



### *Printing bar numbers at regular intervals*

Bar numbers can be printed at regular intervals by setting the property `barNumberVisibility`. Here the bar numbers are printed every two measures except at the end of the line.

```
\relative c' {
  \override Score.BarNumber #'break-visibility = #end-of-line-invisible
  \set Score.currentBarNumber = #11
  % Permit first bar number to be printed
  \bar ""
  % Print a bar number every second measure
  \set Score.barNumberVisibility = #(every-nth-bar-number-visible 2)
  c1 | c | c | c | c
  \break
  c1 | c | c | c | c
}
```



### *Printing bar numbers inside boxes or circles*

Bar numbers can also be printed inside boxes or circles.

```


\relative c' {
  % Prevent bar numbers at the end of a line and permit them elsewhere
  \override Score.BarNumber #'break-visibility = #end-of-line-invisible
  \set Score.barNumberVisibility = #(every-nth-bar-number-visible 4)

  % Increase the size of the bar number by 2
  \override Score.BarNumber #'font-size = #2

  % Draw a box round the following bar number(s)
  \override Score.BarNumber #'stencil
    = #(make-stencil-boxer 0.1 0.25 ly:text-interface::print)
  \repeat unfold 5 { c1 }

  % Draw a circle round the following bar number(s)
  \override Score.BarNumber #'stencil
    = #(make-stencil-circler 0.1 0.25 ly:text-interface::print)
  \repeat unfold 4 { c1 } \bar "|"
}

```



### *Alternative bar numbering*

Two alternative methods for bar numbering can be set, especially for when using repeated music.

```

\relative c'{
  \set Score.alternativeNumberingStyle = #'numbers
  \repeat volta 3 { c4 d e f | }
  \alternative {
    { c4 d e f | c2 d \break }
    { f4 g a b | f4 g a b | f2 a | \break }
    { c4 d e f | c2 d }
  }
  c1 \break
  \set Score.alternativeNumberingStyle = #'numbers-with-letters
  \repeat volta 3 { c,4 d e f | }
  \alternative {
    { c4 d e f | c2 d \break }
    { f4 g a b | f4 g a b | f2 a | \break }
    { c4 d e f | c2 d }
  }
  c1
}

```

The image shows six musical staves, each with a treble clef and a common time signature (C). The staves are labeled 1, 2, 3, 5, 6b, and 6c. Each staff contains a sequence of notes and rests. The first ending (staff 1) is marked with a bracket and the number 1. The second ending (staff 2) is marked with a bracket and the number 2. The third ending (staff 3) is marked with a bracket and the number 3. The fourth ending (staff 5) is marked with a bracket and the number 1. The fifth ending (staff 6b) is marked with a bracket and the number 2. The sixth ending (staff 6c) is marked with a bracket and the number 3.

### Aligning bar numbers

Bar numbers by default are right-aligned to their parent object. This is usually the left edge of a line or, if numbers are printed within a line, the left hand side of a bar line. The numbers may also be positioned directly over the bar line or left-aligned to the bar line.

```
\relative c' {
  \set Score.currentBarNumber = #111
  \override Score.BarNumber #'break-visibility = #all-visible
  % Increase the size of the bar number by 2
  \override Score.BarNumber #'font-size = #2
  % Print a bar number every second measure
  \set Score.barNumberVisibility = #(every-nth-bar-number-visible 2)
  c1 | c1
  % Center-align bar numbers
  \override Score.BarNumber #'self-alignment-X = #CENTER
  c1 | c1
  % Left-align bar numbers
  \override Score.BarNumber #'self-alignment-X = #LEFT
  c1 | c1
}
```

The image shows a musical staff with a treble clef and a common time signature (C). The staff contains six measures, each with a whole note. The bar numbers 112, 114, and 116 are centered over the bar lines.

*Removing bar numbers from a score*

Bar numbers can be removed entirely by removing the `Bar_number_engraver` from the `Score` context.

```
\layout {
  \context {
    \Score
    \remove "Bar_number_engraver"
  }
}

\relative c'' {
  c4 c c c \break
  c4 c c c
}
```

**See also**

Snippets: [Section “Rhythms” in \*Snippets\*](#).

Internals Reference: [Section “BarNumber” in \*Internals Reference\*](#), [Section “Bar\\_number\\_engraver” in \*Internals Reference\*](#).

**Known issues and warnings**

Bar numbers may collide with the top of the `StaffGroup` bracket, if there is one. To solve this, the `padding` property of `BarNumber` can be used to position the number correctly. See [Section “StaffGroup” in \*Internals Reference\*](#) and [Section “BarNumber” in \*Internals Reference\*](#) for more.

**Bar and bar number checks**

Bar checks help detect errors in the entered durations. A bar check may be entered using the bar symbol, `|`, at any place where a bar line is expected to fall. If bar check lines are encountered at other places, a list of warnings is printed in the log file, showing the line numbers and lines in which the bar checks failed. In the next example, the second bar check will signal an error.

```
\time 3/4 c2 e4 | g2 |
```

Bar checks can also be used in lyrics:

```
\lyricmode {
  \time 2/4
  Twin -- kle | Twin -- kle |
}
```

An incorrect duration can result in a completely garbled score, especially if the score is polyphonic, so a good place to start correcting input is by scanning for failed bar checks and incorrect durations.



If successive bar checks are off by the same musical interval, only the first warning message is displayed. This allows the warning to focus on the source of the timing error.

It is also possible to redefine the action taken when a bar check or pipe symbol, |, is encountered in the input, so that it does something other than a bar check. This is done by assigning a music expression to `pipeSymbol`. In the following example | is set to insert a double bar line wherever it appears in the input, rather than checking for end of bar.

```
pipeSymbol = \bar "||"
{
  c'2 c' |
  c'2 c'
  c'2 | c'
  c'2 c'
}
```



When copying large pieces of music, it can be helpful to check that the LilyPond bar number corresponds to the original that you are entering from. This can be checked with `\barNumberCheck`, for example,

```
\barNumberCheck #123
```

will print a warning if the `currentBarNumber` is not 123 when it is processed.


## See also

Snippets: [Section “Rhythms” in \*Snippets\*](#).

## Rehearsal marks


To print a rehearsal mark, use the `\mark` command.

```
c1 \mark \default
c1 \mark \default
c1 \mark \default
c1 \mark \default
```




The mark is incremented automatically if you use `\mark \default`, but you can also use an integer argument to set the mark manually. The value to use is stored in the property `rehearsalMark`.

```
c1 \mark \default
c1 \mark \default
c1 \mark #8
c1 \mark \default
c1 \mark \default
```




The letter ‘I’ is skipped in accordance with engraving traditions. If you wish to include the letter ‘I’, then use one of the following commands, depending on which style of rehearsal mark you want (letters only, letters in a hollow box, or letters in a hollow circle).

```
\set Score.markFormatter = #format-mark-alphabet
\set Score.markFormatter = #format-mark-box-alphabet
\set Score.markFormatter = #format-mark-circle-alphabet
\set Score.markFormatter = #format-mark-box-alphabet
c1 \mark \default
c1 \mark \default
c1 \mark #8
c1 \mark \default
c1 \mark \default
```



The style is defined by the property `markFormatter`. It is a function taking the current mark (an integer) and the current context as argument. It should return a markup object. In the following example, `markFormatter` is set to a pre-defined procedure. After a few measures, it is set to a procedure that produces a boxed number.

```
\set Score.markFormatter = #format-mark-numbers
c1 \mark \default
c1 \mark \default
\set Score.markFormatter = #format-mark-box-numbers
c1 \mark \default
\set Score.markFormatter = #format-mark-circle-numbers
c1 \mark \default
\set Score.markFormatter = #format-mark-circle-letters
c1
```



The file ‘`scm/translation-functions.scm`’ contains the definitions of `format-mark-numbers` (the default format), `format-mark-box-numbers`, `format-mark-letters` and `format-mark-box-letters`. These can be used as inspiration for other formatting functions.

You may use `format-mark-barnumbers`, `format-mark-box-barnumbers`, and `format-mark-circle-barnumbers` to get bar numbers instead of incremented numbers or letters.

Other styles of rehearsal mark can be specified manually:


```
\mark "A1"
```

Note that `Score.markFormatter` does not affect marks specified in this manner. However, it is possible to apply a `\markup` to the string.

```
\mark \markup{ \box A1 }
```

Music glyphs (such as the segno sign) may be printed inside a `\mark`

```
c1 \mark \markup { \musicglyph #"scripts.segno" }
c1 \mark \markup { \musicglyph #"scripts.coda" }
c1 \mark \markup { \musicglyph #"scripts.ufermata" }
c1
```



See [Section A.7 \[The Feta font\]](#), page 589, for a list of symbols which may be printed with `\musicglyph`.

For common tweaks to the positioning of rehearsal marks, see [Section 1.8.2 \[Formatting text\]](#), page 210. For more precise control, see `break-alignable-interface` in [Section 5.5.1 \[Aligning objects\]](#), page 556.

## See also

Notation Reference: [Section A.7 \[The Feta font\]](#), page 589, [Section 1.8.2 \[Formatting text\]](#), page 210, [Section 5.5.1 \[Aligning objects\]](#), page 556.

Installed Files: ‘`scm/translation-functions.scm`’ contains the definitions of `format-mark-numbers` and `format-mark-letters`. They can be used as inspiration for other formatting functions.

Snippets: [Section “Rhythms” in \*Snippets\*](#).

Internals Reference: [Section “MarkEvent” in \*Internals Reference\*](#), [Section “Mark\\_engraver” in \*Internals Reference\*](#), [Section “RehearsalMark” in \*Internals Reference\*](#).

## 1.2.6 Special rhythmic concerns

### Grace notes

Grace notes are musical ornaments, printed in a smaller font, that take up no additional logical time in a measure.

```
c4 \grace b16 a4(
\grace { b16[ c16] } a2)
```



There are three other types of grace notes possible; the *acciaccatura* – an unmeasured grace note indicated by a slurred note with a slashed stem – and the *appoggiatura*, which takes a fixed fraction of the main note it is attached to and prints without the slash. It is also possible to write a grace note with a slashed stem, like the *acciaccatura* but without the slur, so as to place it between notes that are slurred themselves, using the `\slashedGrace` function.

```
\acciaccatura d8 c4
\appoggiatura e8 d4
\acciaccatura { g16[ f] } e2
\slashedGrace a,8 g4
\slashedGrace b16 a4(
\slashedGrace b8 a2)
```




The placement of grace notes is synchronized between different staves. In the following example, there are two sixteenth grace notes for every eighth grace note

```
<<
  \new Staff { e2 \grace { c16[ d e f] } e2 }
  \new Staff { c2 \grace { g8[ b] } c2 }
>>
```



If you want to end a note with a grace, use the `\afterGrace` command. It takes two arguments: the main note, and the grace notes following the main note.

```
c1 \afterGrace d1 { c16[ d] } c1
```



This will put the grace notes after a space lasting  $3/4$  of the length of the main note. The default fraction  $3/4$  can be changed by setting `afterGraceFraction`. The following example shows the results from setting the space at the default, at  $15/16$ , and finally at  $1/2$  of the main note.

```
<<
  \new Staff {
    c1 \afterGrace d1 { c16[ d] } c1
  }
  \new Staff {
    #(define afterGraceFraction (cons 15 16))
    c1 \afterGrace d1 { c16[ d] } c1
  }
  \new Staff {
    #(define afterGraceFraction (cons 1 2))
    c1 \afterGrace d1 { c16[ d] } c1
  }
>>
```



The space between the main note and the grace note may also be specified using spacers. The following example places the grace note after a space lasting 7/8 of the main note.

```
\new Voice {
  <<
  { d1^\trill_( }
  { s2 s4. \grace { c16[ d] } }
  >>
  c1)
}
```



A `\grace` music expression will introduce special typesetting settings, for example, to produce smaller type, and set directions. Hence, when introducing layout tweaks to override the special settings, they should be placed inside the grace expression. The overrides should also be reverted inside the grace expression. Here, the grace note's default stem direction is overridden and then reverted.

```
\new Voice {
  \acciaccatura {
    \stemDown
    f16->
    \stemNeutral
  }
  g4 e c2
}
```



## Selected Snippets

*Using grace note slashes with normal heads*

The slash through the stem found in acciaccaturas can be applied in other situations.

```
\relative c'' {
  \override Flag #'stroke-style = #"grace"
  c8( d2) e8( f4)
}
```



*Tweaking grace layout within music*

The layout of grace expressions can be changed throughout the music using the functions `add-grace-property` and `remove-grace-property`. The following example undefines the `Stem` direction for this grace, so that stems do not always point up, and changes the default note heads to crosses.

```

\relative c'' {
  \new Staff {
    $(remove-grace-property 'Voice 'Stem 'direction)
    $(add-grace-property 'Voice 'NoteHead 'style 'cross)
    \new Voice {
      \acciaccatura { f16 } g4
      \grace { d16[ e] } f4
      \appoggiatura { f,32[ g a] } e2
    }
  }
}

```



### *Redefining grace note global defaults*

The global defaults for grace notes are stored in the identifiers `startGraceMusic`, `stopGraceMusic`, `startAcciaccaturaMusic`, `stopAcciaccaturaMusic`, `startAppoggiaturaMusic` and `stopAppoggiaturaMusic`, which are defined in the file `ly/grace-init.ly`. By redefining them other effects may be obtained.

```

startAcciaccaturaMusic = {
  s1*0(
    \override Flag #'stroke-style = #"grace"
    \slurDashed
  }

stopAcciaccaturaMusic = {
  \revert Flag #'stroke-style
  \slurSolid
  s1*0)
}

\relative c'' {
  \acciaccatura d8 c1
}

```



### *Positioning grace notes with floating space*

Setting the property `'strict-grace-spacing` makes the musical columns for grace notes 'floating', i.e., decoupled from the non-grace notes: first the normal notes are spaced, then the (musical columns of the) graces are put left of the musical columns for the main notes.

```


\relative c'' {
  <<
    \override Score.SpacingSpanner #'strict-grace-spacing = ##t
    \new Staff \new Voice {
      \afterGrace c4 { c16[ c8 c16] }
      c8[ \grace { b16[ d] } c8]
    }
  >>
}

```

```

        c4 r
      }
    \new Staff {
      c16 c c c c c c c c4 r
    }
  >>
}

```



## See also

Music Glossary: Section “grace notes” in *Music Glossary*, Section “acciaccatura” in *Music Glossary*, Section “appoggiatura” in *Music Glossary*.

Notation Reference: [Manual beams], page 82.

Installed Files: ‘ly/grace-init.ly’.

Snippets: Section “Rhythms” in *Snippets*.

Internals Reference: Section “GraceMusic” in *Internals Reference*, Section “Grace.beam engraver” in *Internals Reference*, Section “Grace engraver” in *Internals Reference*, Section “Grace.spacing engraver” in *Internals Reference*.

## Known issues and warnings

A multi-note beamed *acciaccatura* is printed without a slash, and looks exactly the same as a multi-note beamed *appoggiatura*.

Grace note synchronization can also lead to surprises. Staff notation, such as key signatures, bar lines, etc., are also synchronized. Take care when you mix staves with grace notes and staves without, for example,

```

<<
  \new Staff { e4 \bar "|:" \grace c16 d2. }
  \new Staff { c4 \bar "|:" d2. }
>>

```



This can be remedied by inserting grace skips of the corresponding durations in the other staves. For the above example

```

<<
  \new Staff { e4 \bar "|:" \grace c16 d2. }
  \new Staff { c4 \bar "|:" \grace s16 d2. }

```

&gt;&gt;



The use of grace notes within voice contexts confuses the way the voice is typeset. This can be overcome by inserting a rest or note between the voice command and the grace note.

```
accMusic = {
  \acciaccatura { f8 } e8 r8 \acciaccatura { f8 } e8 r4
}

\new Staff {
  <<
    \new Voice {
      \relative c'' {
        r8 r8 \voiceOne \accMusic \oneVoice r8 |
        r8 \voiceOne r8 \accMusic \oneVoice r8 |
      }
    }
    \new Voice {
      \relative c' {
        s8 s8 \voiceTwo \accMusic \oneVoice s8 |
        s8 \voiceTwo r8 \accMusic \oneVoice s8 |
      }
    }
  >>
}
```



Grace sections should only be used within sequential music expressions. Nesting or juxtaposing grace sections is not supported, and might produce crashes or other errors.

Each grace note in MIDI output has a length of 1/4 of its actual duration. If the combined length of the grace notes is greater than the length of the preceding note a “Going back in MIDI time” error will be generated. Either make the grace notes shorter in duration, for example:

```
\acciaccatura { c'8[ d' e' f' g'] }
```

becomes:

```
\acciaccatura { c'16[ d' e' f' g'] }
```

Or explicitly change the musical duration:

```
\acciaccatura { \scaleDurations #' (1 . 2) { c'8[ d' e' f' g'] } }
```

See [\[Scaling durations\]](#), page 44.




## Aligning to cadenzas

In an orchestral context, cadenzas present a special problem: when constructing a score that includes a measured cadenza or other solo passage, all other instruments should skip just as many notes as the length of the cadenza, otherwise they will start too soon or too late.

One solution to this problem is to use the functions `mmrest-of-length` and `skip-of-length`. These Scheme functions take a defined piece of music as an argument and generate a multi-measure rest or `\skip` exactly as long as the piece.

```
MyCadenza = \relative c' {
  c4 d8 e f g g4
  f2 g4 g
}

\new GrandStaff <<
  \new Staff {
    \MyCadenza c'1
    \MyCadenza c'1
  }
  \new Staff {
    $(mmrest-of-length MyCadenza)
    c'1
    $(skip-of-length MyCadenza)
    c'1
  }
>>
```



## See also

Music Glossary: [Section “cadenza” in \*Music Glossary\*](#).

Snippets: [Section “Rhythms” in \*Snippets\*](#).

## Time administration

Time is administered by the `Timing_translator`, which by default is to be found in the `Score` context. An alias, `Timing`, is added to the context in which the `Timing_translator` is placed. To ensure that the `Timing` alias is available, you may need to explicitly instantiate the containing context (such as `Voice` or `Staff`).

The following properties of `Timing` are used to keep track of timing within the score.

### `currentBarNumber`

The current measure number. For an example showing the use of this property see [\[Bar numbers\]](#), page 90.

### `measureLength`

The length of the measures in the current time signature. For a 4/4 time this is 1, and for 6/8 it is 3/4. Its value determines when bar lines are inserted and how automatic beams should be generated.

measurePosition

The point within the measure where we currently are. This quantity is reset by subtracting `measureLength` whenever `measureLength` is reached or exceeded. When that happens, `currentBarNumber` is incremented.

**timing** If set to true, the above variables are updated for every time step. When set to false, the engraver stays in the current measure indefinitely.

Timing can be changed by setting any of these variables explicitly. In the next example, the default 4/4 time signature is printed, but `measureLength` is set to 5/4. At 4/8 through the third measure, the `measurePosition` is advanced by 1/8 to 5/8, shortening that bar by 1/8. The next bar line then falls at 9/8 rather than 5/4.

```
\new Voice \relative c' {
  \set Timing.measureLength = #(ly:make-moment 5 4)
  c1 c4 |
  c1 c4 |
  c4 c
  \set Timing.measurePosition = #(ly:make-moment 5 8)
  b4 b b8 |
  c4 c1 |
}
```



As the example illustrates, `ly:make-moment n m` constructs a duration of  $n/m$  of a whole note. For example, `ly:make-moment 1 8` is an eighth note duration and `ly:make-moment 7 16` is the duration of seven sixteenths notes.

See also

Notation Reference: [Bar numbers], page 90, [Unmetered music], page 64.

Snippets: Section “Rhythms” in *Snippets*.

Internals Reference: Section “Timing\_translator” in *Internals Reference*, Section “Score” in *Internals Reference*.

### 1.3 Expressive marks



This section lists various expressive marks that can be created in a score.

### 1.3.1 Expressive marks attached to notes

This section explains how to create expressive marks that are attached to notes: articulations, ornamentations, and dynamics. Methods to create new dynamic markings are also discussed.

#### Articulations and ornamentations

A variety of symbols that denote articulations, ornamentations, and other performance indications can be attached to a note using this syntax:

```
note \name
```

The possible values for *name* are listed in [Section A.12 \[List of articulations\]](#), page 654. For example:

```
c4 \staccato c \mordent b2 \turn
c1 \fermata
```



Some of these articulations have shorthands for easier entry. Shorthands are appended to the note name, and their syntax consists of a dash – followed by a symbol signifying the articulation. Predefined shorthands exist for *marcato*, *stopped*, *tenuto*, *staccatissimo*, *accent*, *staccato*, and *portato*. Their corresponding output appears as follows:

```
c4-^ c-+ c-- c-|
c4-> c-. c2- _
```



The rules for the default placement of articulations are defined in ‘`scm/script.scm`’. Articulations and ornamentations may be manually placed above or below the staff; see [Section 5.4.2 \[Direction and placement\]](#), page 543.

Articulations are `Script` objects. Their properties are described more fully in [Section “Script” in Internals Reference](#).

Articulations can be attached to rests as well as notes but they cannot be attached to multi-measure rests. A special predefined command, `\fermataMarkup`, is available for attaching a fermata to a multi-measure rest (and only a multi-measure rest). This creates a `MultiMeasureRestText` object.

```
\override Script #'color = #red
\override MultiMeasureRestText #'color = #blue
a2 \fermata r \fermata
R1 \fermataMarkup
```



In addition to articulations, text and markups can be attached to notes. See [\[Text scripts\]](#), page 202.

For more information about the ordering of `Scripts` and `TextScripts` that are attached to the notes, see [Section “Placement of objects” in Learning Manual](#).

## Selected Snippets

### *Modifying default values for articulation shorthand notation*

The shorthands are defined in ‘ly/script-init.ly’, where the variables `dashHat`, `dashPlus`, `dashDash`, `dashBar`, `dashLarger`, `dashDot`, and `dashUnderscore` are assigned default values. The default values for the shorthands can be modified. For example, to associate the `++` (`dashPlus`) shorthand with the trill symbol instead of the default `+` symbol, assign the value `trill` to the variable `dashPlus`:

```
\relative c'' { c1-+ }

dashPlus = "trill"

\relative c'' { c1-+ }
```



### *Controlling the vertical ordering of scripts*

The vertical ordering of scripts is controlled with the '`script-priority`' property. The lower this number, the closer it will be put to the note. In this example, the `TextScript` (the sharp symbol) first has the lowest priority, so it is put lowest in the first example. In the second, the prall trill (the `Script`) has the lowest, so it is on the inside. When two objects have the same priority, the order in which they are entered determines which one comes first.

```
\relative c''' {
  \once \override TextScript #'script-priority = #-100
  a2^\prall^\markup { \sharp }

  \once \override Script #'script-priority = #-100
  a2^\prall^\markup { \sharp }
}
```



### *Creating a delayed turn*

Creating a delayed turn, where the lower note of the turn uses the accidental, requires several overrides. The `outside-staff-priority` property must be set to `#f`, as otherwise this would take precedence over the `avoid-slur` property. The value of `halign` is used to position the turn horizontally.

```
\relative c'' {
  \once \override TextScript #'avoid-slur = #'inside
  \once \override TextScript #'outside-staff-priority = ##f
```

```

c2(\markup \tiny \override #'(baseline-skip . 1) {
  \halign #-4
  \center-column {
    \sharp
    \musicglyph #"scripts.turn"
  }
}
d4.) c8
}

```



## See also

Music Glossary: [Section “tenuto” in \*Music Glossary\*](#), [Section “accent” in \*Music Glossary\*](#), [Section “staccato” in \*Music Glossary\*](#), [Section “portato” in \*Music Glossary\*](#).

Learning Manual: [Section “Placement of objects” in \*Learning Manual\*](#).

Notation Reference: [\[Text scripts\]](#), page 202, [Section 5.4.2 \[Direction and placement\]](#), page 543, [Section A.12 \[List of articulations\]](#), page 654, [\[Trills\]](#), page 125.

Installed Files: ‘`scm/script.scm`’.

Snippets: [Section “Expressive marks” in \*Snippets\*](#).

Internals Reference: [Section “Script” in \*Internals Reference\*](#), [Section “TextScript” in \*Internals Reference\*](#).

## Dynamics

Absolute dynamic marks are specified using a command after a note, such as `c4\ff`. The available dynamic marks are `\ppppp`, `\pppp`, `\ppp`, `\pp`, `\p`, `\mp`, `\mf`, `\f`, `\ff`, `\fff`, `\ffff`, `\fffff`, `\fp`, `\sf`, `\sff`, `\sp`, `\spp`, `\sfz`, and `\rfz`. Dynamic marks may be manually placed above or below the staff; see [Section 5.4.2 \[Direction and placement\]](#), page 543.

```

c2\ppp c\mp
c2\rfz c^\mf
c2_\spp c^\ff

```




A *crescendo* mark is started with `\<` and terminated with `\!`, an absolute dynamic, or an additional crescendo or decrescendo mark. A *decrescendo* mark is started with `\>` and is also terminated with `\!`, an absolute dynamic, or another crescendo or decrescendo mark. `\cr` and `\decr` may be used instead of `\<` and `\>`. *Hairpins* are engraved by default using this notation.

```

c2\< c\!
d2\< d\f
e2\< e\>
f2\> f\!
e2\> e\mp

```

```
d2\> d\>
c1\!
```



A hairpin that is terminated with `\!` will end at the right edge of the note that has the `\!` assigned to it. In the case where it is terminated with the start of another *crescendo* or *decrescendo* mark, it will end at the centre of the note that has the next `<` or `>` assigned to it. The next hairpin will then start at the right edge of the same note instead of the usual left edge had it been terminated with `\!` before.

```
c1\< | c4 a c\< a | c4 a c\! a\< | c4 a c a\!
```



Hairpins that are terminated with absolute dynamic marks instead of `\!` will also be engraved in a similar way. However, the length of the absolute dynamic itself can alter where the preceding hairpin ends.

```
c1\< | c4 a c\mf a | c1\< | c4 a c\ffff a
```



Spacer rests are needed to engrave multiple marks on one note. This is particularly useful when adding a *crescendo* and *decrescendo* to the same note:

```
c4\< c\! d\> e\!
<< f1 { s4 s4\< s4\> s4\! } >>
```



The `\espressivo` command can be used to indicate a crescendo and decrescendo on the same note. However, be warned that this is implemented as an articulation, not a dynamic.

```
c2 b4 a
g1\espressivo
```



Textual crescendo marks begin with `\cresc`. Textual decrescendos begin with `\decresc` or `\dim`. Extender lines are engraved as required.

```
g8\cresc a b c b c d e\mf |
f8\decresc e d c e\> d c b |
a1\dim ~ |
a2. r4\! |
```



Textual marks for dynamic changes can also replace hairpins:

```
\crescTextCresc
c4\< d e f\! |
\dimTextDecresc
g4\> e d c\! |
\dimTextDecr
e4\> d c b\! |
\dimTextDim
d4\> c b a\! |
\crescHairpin
\dimHairpin
c4\< d\! e\> d\! |
```




To create new absolute dynamic marks or text that should be aligned with dynamics, see [\[New dynamic marks\]](#), page 112.

Vertical positioning of dynamics is handled by [Section “DynamicLineSpanner”](#) in *Internals Reference*.

A `Dynamics` context is available to engrave dynamics on their own horizontal line. Use spacer rests to indicate timing. (Notes in a `Dynamics` context will also take up musical time, but will not be engraved.) The `Dynamics` context can usefully contain some other items such as text scripts, text spanners, and piano pedal marks.

```
<<
\new Staff \relative c' {
  c2 d4 e |
  c4 e e,2 |
  g'4 a g a |
  c1 |
}
\new Dynamics {
  s1\< |
  s1\f |
  s2\dim s2-"rit." |
  s1\p |
}
>>
```



## Predefined commands


`\dynamicUp, \dynamicDown, \dynamicNeutral, \crescTextCresc, \dimTextDim,`  
`\dimTextDecr, \dimTextDecresc, \crescHairpin, \dimHairpin.`

## Selected Snippets

### Setting hairpin behavior at bar lines

If the note which ends a hairpin falls on a downbeat, the hairpin stops at the bar line immediately preceding. This behavior can be controlled by overriding the `'to-barline` property.

```
\relative c' {
  e4\< e2.
  e1\!
  \override Hairpin #'to-barline = ##f
  e4\< e2.
  e1\!
}
```



### Setting the minimum length of hairpins

If hairpins are too short, they can be lengthened by modifying the `minimum-length` property of the `Hairpin` object.

```
\relative c'' {
  c4\< c\! d\> e\!
  \override Hairpin #'minimum-length = #5
  << f1 { s4 s\< s\> s\! } >>
}
```



### Printing hairpins using *al niente* notation

Hairpin dynamics may be printed with a circled tip (“al niente” notation) by setting the `circled-tip` property of the `Hairpin` object to `#t`.

```
\relative c'' {
  \override Hairpin #'circled-tip = ##t
  c2\< c\!
  c4\> c\< c2\!
}
```





*Vertically aligned dynamics and textscripts*

By setting the 'Y-extent' property to a suitable value, all `DynamicLineSpanner` objects (hairpins and dynamic texts) can be aligned to a common reference point, regardless of their actual extent. This way, every element will be vertically aligned, thus producing a more pleasing output.

The same idea is used to align the text scripts along their baseline.


```
music = \relative c' {
  a'2\p b\f
  e4\p f\f\> g, b\p
  c2^\markup { \huge gorgeous } c^\markup { \huge fantastic }
}

{
  \music
  \break
  \override DynamicLineSpanner #'staff-padding = #2.0
  \override DynamicLineSpanner #'Y-extent = #'(-1.5 . 1.5)
  \override TextScript #'Y-extent = #'(-1.5 . 1.5)
  \music
}
```

*Hiding the extender line for text dynamics*

Text style dynamic changes (such as *cresc.* and *dim.*) are printed with a dashed line showing their extent. This line can be suppressed in the following way:

```
\relative c'' {
  \override DynamicTextSpanner #'style = #'none
  \crescTextCresc
  c1\< | d | b | c\!
}
```



*Changing text and spanner styles for text dynamics*

The text used for crescendos and decrescendos can be changed by modifying the context properties `crescendoText` and `decrescendoText`.

The style of the spanner line can be changed by modifying the `'style` property of `DynamicTextSpanner`. The default value is `'dashed-line`, and other possible values include `'line`, `'dotted-line` and `'none`.

```
\relative c' {
  \set crescendoText = \markup { \italic { cresc. poco } }
  \set crescendoSpanner = #'text
  \override DynamicTextSpanner #'style = #'dotted-line
  a2\< a
  a2 a
  a2 a
  a2 a\mf
}
```

**See also**

Music Glossary: [Section “al niente” in \*Music Glossary\*](#), [Section “crescendo” in \*Music Glossary\*](#), [Section “decrescendo” in \*Music Glossary\*](#), [Section “hairpin” in \*Music Glossary\*](#).

Learning Manual: [Section “Articulation and dynamics” in \*Learning Manual\*](#).

Notation Reference: [Section 5.4.2 \[Direction and placement\]](#), page 543, [\[New dynamic marks\]](#), page 112, [Section 3.5.3 \[What goes into the MIDI output?\]](#), page 461, [Section 3.5.5 \[Controlling MIDI dynamics\]](#), page 462.

Snippets: [Section “Expressive marks” in \*Snippets\*](#).

Internals Reference: [Section “DynamicText” in \*Internals Reference\*](#), [Section “Hairpin” in \*Internals Reference\*](#), [Section “DynamicLineSpanner” in \*Internals Reference\*](#), [Section “Dynamics” in \*Internals Reference\*](#).

**New dynamic marks**

The easiest way to create dynamic indications is to use `\markup` objects.

```
moltoF = \markup { molto \dynamic f }
```

```
\relative c' {
  <d e>16_\moltoF <d e>
  <d e>2..
}
```



In markup mode, editorial dynamics (within parentheses or square brackets) can be created. The syntax for markup mode is described in [Section 1.8.2 \[Formatting text\]](#), page 210.

```

roundF = \markup {
  \center-align \concat { \bold { \italic ( }
    \dynamic f \bold { \italic ) } } }
boxF = \markup { \bracket { \dynamic f } }
\relative c' {
  c1_\roundF
  c1_\boxF
}

```



Simple, centered dynamic marks are easily created with the `make-dynamic-script` function.

```

sfzp = #(make-dynamic-script "sfzp")
\relative c' {
  c4 c c\sfpz c
}

```




In general, `make-dynamic-script` takes any markup object as its argument. The dynamic font only contains the characters `f`, `m`, `p`, `r`, `s` and `z`, so if a dynamic mark that includes plain text or punctuation symbols is desired, markup commands that reverts font family and font encoding to normal text should be used, for example `\normal-text`. The interest of using `make-dynamic-script` instead of an ordinary markup is ensuring the vertical alignment of markup objects and hairpins that are attached to the same note head.

```

roundF = \markup { \center-align \concat {
  \normal-text { \bold { \italic ( } }
  \dynamic f
  \normal-text { \bold { \italic ) } } } }
boxF = \markup { \bracket { \dynamic f } }
mfEspress = \markup { \center-align \line {
  \hspace #3.7 mf \normal-text \italic espress. } }
roundFdynamic = #(make-dynamic-script roundF)
boxFdynamic = #(make-dynamic-script boxF)
mfEspressDynamic = #(make-dynamic-script mfEspress)
\relative c' {
  c4_\roundFdynamic\< d e f
  g,1~_\boxFdynamic\>
  g1
  g'1~\mfEspressDynamic
  g1
}


```



The Scheme form of markup mode may be used instead. Its syntax is explained in [Section “Markup construction in Scheme” in \*Extending\*](#).

```
moltoF = #(make-dynamic-script
            (markup #:normal-text "molto"
                    #:dynamic "f"))

\relative c' {
  <d e>16 <d e>
  <d e>2..\moltoF
}
```



Font settings in markup mode are described in [\[Selecting font and font size\]](#), page 212.

## See also

Notation Reference: [Section 1.8.2 \[Formatting text\]](#), page 210, [\[Selecting font and font size\]](#), page 212, [Section 3.5.3 \[What goes into the MIDI output?\]](#), page 461, [Section 3.5.5 \[Controlling MIDI dynamics\]](#), page 462.

Snippets: [Section “Expressive marks” in \*Snippets\*](#).

Extend: [Section “Markup construction in Scheme” in \*Extending\*](#).

## 1.3.2 Expressive marks as curves

This section explains how to create various expressive marks that are curved: normal slurs, phrasing slurs, breath marks, falls, and doits.

### Slurs

*Slurs* are entered using parentheses:

**Note:** In polyphonic music, a slur must be terminated in the same voice it began.

```
f4( g a) a8 b(
a4 g2 f4)
<c e>2( <b d>2)
```



Slurs may be manually placed above or below the staff; see [Section 5.4.2 \[Direction and placement\]](#), page 543.

Simultaneous or overlapping slurs are not permitted, but a phrasing slur can overlap a slur. This permits two slurs to be printed at once. For details, see [\[Phrasing slurs\]](#), page 117.

Slurs can be solid, dotted, or dashed. Solid is the default slur style:

```

c4( e g2)
\slurDashed
g4( e c2)
\slurDotted
c4( e g2)
\slurSolid
g4( e c2)

```



Slurs can also be made half-dashed (the first half dashed, the second half solid) or half-solid (the first half solid, the second half dashed):

```

c4( e g2)
\slurHalfDashed
g4( e c2)
\slurHalfSolid
c4( e g2)
\slurSolid
g4( e c2)

```



Custom dash patterns for slurs can be defined:

```

c4( e g2)
\slurDashPattern #0.7 #0.75
g4( e c2)
\slurDashPattern #0.5 #2.0
c4( e g2)
\slurSolid
g4( e c2)

```



## Predefined commands

`\slurUp`, `\slurDown`, `\slurNeutral`, `\slurDashed`, `\slurDotted`, `\slurHalfDashed`, `\slurHalfSolid`, `\slurDashPattern`, `\slurSolid`.

## Selected Snippets

*Using double slurs for legato chords*

Some composers write two slurs when they want legato chords. This can be achieved by setting `doubleSlurs`.

```
\relative c' {
  \set doubleSlurs = ##t
  <c e>4( <d f> <c e> <d f>)
}
```



### *Positioning text markups inside slurs*

Text markups need to have the `outside-staff-priority` property set to false in order to be printed inside slurs.

```
\relative c'' {
  \override TextScript #'avoid-slur = #'inside
  \override TextScript #'outside-staff-priority = ##f
  c2(~\markup { \halign #-10 \natural } d4.) c8
}
```



### *Making slurs with complex dash structure*

Slurs can be made with complex dash patterns by defining the `dash-definition` property. `dash-definition` is a list of `dash-elements`. A `dash-element` is a list of parameters defining the dash behavior for a segment of the slur.

The slur is defined in terms of the bezier parameter `t` which ranges from 0 at the left end of the slur to 1 at the right end of the slur. `dash-element` is a list (`start-t stop-t dash-fraction dash-period`). The region of the slur from `start-t` to `stop-t` will have a fraction `dash-fraction` of each `dash-period` black. `dash-period` is defined in terms of staff spaces. `dash-fraction` is set to 1 for a solid slur.

```
\relative c' {
  \once \override
    Slur #'dash-definition = #'((0 0.3 0.1 0.75)
                                (0.3 0.6 1 1)
                                (0.65 1.0 0.4 0.75))

  c4( d e f)
  \once \override
    Slur #'dash-definition = #'((0 0.25 1 1)
                                (0.3 0.7 0.4 0.75)
                                (0.75 1.0 1 1))

  c4( d e f)
}
```



## See also

Music Glossary: [Section “slur” in \*Music Glossary\*](#).

Learning Manual: [Section “On the un-nestedness of brackets and ties” in \*Learning Manual\*](#).

Notation Reference: [Section 5.4.2 \[Direction and placement\]](#), page 543, [\[Phrasing slurs\]](#), page 117.

Snippets: [Section “Expressive marks” in \*Snippets\*](#).

Internals Reference: [Section “Slur” in \*Internals Reference\*](#).

## Phrasing slurs

*Phrasing slurs* (or phrasing marks) that indicate a musical sentence are written using the commands `\(` and `\)` respectively:

```
c4\( d( e) f(
e2) d\)
```



Typographically, a phrasing slur behaves almost exactly like a normal slur. However, they are treated as different objects; a `\slurUp` will have no effect on a phrasing slur. Phrasing may be manually placed above or below the staff; see [Section 5.4.2 \[Direction and placement\]](#), page 543.

Simultaneous or overlapping phrasing slurs are not permitted.

Phrasing slurs can be solid, dotted, or dashed. Solid is the default style for phrasing slurs:

```
c4\( e g2\)
\phrasingSlurDashed
g4\( e c2\)
\phrasingSlurDotted
c4\( e g2\)
\phrasingSlurSolid
g4\( e c2\)
```



Phrasing slurs can also be made half-dashed (the first half dashed, the second half solid) or half-solid (the first half solid, the second half dashed):

```
c4\( e g2\)
\phrasingSlurHalfDashed
g4\( e c2\)
\phrasingSlurHalfSolid
c4\( e g2\)
\phrasingSlurSolid
g4\( e c2\)
```



Custom dash patterns for phrasing slurs can be defined:

```

c4\ ( e g2\ )
\phrasingSlurDashPattern #0.7 #0.75
g4\ ( e c2\ )
\phrasingSlurDashPattern #0.5 #2.0
c4\ ( e g2\ )
\phrasingSlurSolid
g4\ ( e c2\ )

```



Dash pattern definitions for phrasing slurs have the same structure as dash pattern definitions for slurs. For more information about complex dash patterns, see the snippets under [\[Slurs\]](#), [page 114](#).

## Predefined commands

```

\phrasingSlurUp, \phrasingSlurDown, \phrasingSlurNeutral, \phrasingSlurDashed,
\phrasingSlurDotted, \phrasingSlurHalfDashed, \phrasingSlurHalfSolid,
\phrasingSlurDashPattern, \phrasingSlurSolid.

```

## See also

Learning Manual: [Section “On the un-nestedness of brackets and ties”](#) in *Learning Manual*.

Notation Reference: [Section 5.4.2 \[Direction and placement\]](#), [page 543](#), [\[Slurs\]](#), [page 114](#).

Snippets: [Section “Expressive marks”](#) in *Snippets*.

Internals Reference: [Section “PhrasingSlur”](#) in *Internals Reference*.

## Breath marks

Breath marks are entered using `\breathe`:

```
c2. \breathe d4
```



A breath mark will end an automatic beam; to override this behavior, see [\[Manual beams\]](#), [page 82](#).

```
c8 \breathe d e f g2
```



Musical indicators for breath marks in ancient notation, *divisiones*, are supported. For details, see [\[Divisiones\]](#), [page 401](#).



## Selected Snippets

### *Changing the breath mark symbol*

The glyph of the breath mark can be tuned by overriding the `text` property of the `BreathingSign` layout object with any markup text.

```
\relative c'' {
  c2
  \override BreathingSign #'text = \markup { \musicglyph #"scripts.rvarcomma" }
  \breathe
  d2
}
```



### *Inserting a caesura*

Caesura marks can be created by overriding the `text` property of the `BreathingSign` object. A curved caesura mark is also available.

```
\relative c'' {
  \override BreathingSign #'text = \markup {
    \musicglyph #"scripts.caesura.straight"
  }
  c8 e4. \breathe g8. e16 c4

  \override BreathingSign #'text = \markup {
    \musicglyph #"scripts.caesura.curved"
  }
  g8 e'4. \breathe g8. e16 c4
}
```



## See also

Music Glossary: [Section “caesura” in \*Music Glossary\*](#).

Notation Reference: [\[Divisiones\]](#), page 401.

Snippets: [Section “Expressive marks” in \*Snippets\*](#).

Internals Reference: [Section “BreathingEvent” in \*Internals Reference\*](#), [Section “BreathingSign” in \*Internals Reference\*](#), [Section “Breathing-sign-engraver” in \*Internals Reference\*](#).

## Falls and doits

*Falls* and *doits* can be added to notes using the `\bendAfter` command. The direction of the fall or doit is indicated with a plus or minus (up or down). The number indicates the pitch interval that the fall or doit will extend *beyond* the main note.

```
c2-\bendAfter #+4
c2-\bendAfter #-4
c2-\bendAfter #+6.5
c2-\bendAfter #-6.5
```

```
c2-\bendAfter #+8
c2-\bendAfter #-8
```



The dash - immediately preceding the `\bendAfter` command is *required* when writing falls and doits.

## Selected Snippets

*Adjusting the shape of falls and doits*

The `shortest-duration-space` property may have to be tweaked to adjust the shape of falls and doits.

```
\relative c' {
  \override Score.SpacingSpanner #'shortest-duration-space = #4.0
  c2-\bendAfter #5
  c2-\bendAfter #-4.75
  c2-\bendAfter #8.5
  c2-\bendAfter #-6
}
```



## See also

Music Glossary: [Section “fall” in Music Glossary](#), [Section “doit” in Music Glossary](#).

Snippets: [Section “Expressive marks” in Snippets](#).

### 1.3.3 Expressive marks as lines

This section explains how to create various expressive marks that follow a linear path: glissandos, arpeggios, and trills.

#### Glissando

A *glissando* is created by attaching `\glissando` to a note:

```
g2\glissando g'
c2\glissando c,
```



Different styles of glissandi can be created. For details, see [Section 5.4.7 \[Line styles\]](#), [page 554](#).

## Selected Snippets

NoteColumn grobs can be skipped over by glissandi.

```
% DO NOT EDIT this file manually; it is automatically
% generated from Documentation/snippets/new
% Make any changes in Documentation/snippets/new/
% and then run scripts/auxiliar/makelsr.py
%
% This file is in the public domain.
%% Note: this file works from version 2.15.12
\version "2.15.12"

\header {
%% Translation of GIT committish: 3b125956b08d27ef39cd48bfa3a2f1e1bb2ae8b4
texidocfr = "
Un glissando peut sauter un objet @code{NoteColumn}.

"
doctitlefr = "Glissando par dessus un objet graphique"

lsrtags = "expressive marks, staff-notation, tweaks-and-overrides"
texidoc = "@code{NoteColumn} grobs can be skipped over by glissandi."
}

\relative c' {
a2 \glissando
\once \override NoteColumn #'glissando-skip = ##t
f''4 d,
}
```



### *Contemporary glissando*

A contemporary glissando without a final note can be typeset using a hidden note and cadenza timing.

```
\relative c'' {
\time 3/4
\override Glissando #'style = #'zigzag
c4 c
\cadenzaOn
c4\glissando
\hideNotes
c,,4
\unHideNotes
\cadenzaOff
\bar "|"
}
```



## See also

Music Glossary: [Section “glissando” in \*Music Glossary\*](#).

Notation Reference: [Section 5.4.7 \[Line styles\], page 554](#).

Snippets: [Section “Expressive marks” in \*Snippets\*](#).

Internals Reference: [Section “Glissando” in \*Internals Reference\*](#).

## Known issues and warnings

Printing text over the line (such as *gliss.*) is not supported.

## Arpeggio

An *arpeggio* on a chord (also known as a broken chord) is denoted by appending `\arpeggio` to the chord construct:

```
<c e g c>1\arpeggio
```



Different types of arpeggios may be written. `\arpeggioNormal` reverts to a normal arpeggio:

```
<c e g c>2\arpeggio
```

```
\arpeggioArrowUp
```

```
<c e g c>2\arpeggio
```

```
\arpeggioArrowDown
```

```
<c e g c>2\arpeggio
```

```
\arpeggioNormal
```

```
<c e g c>2\arpeggio
```



Special *bracketed* arpeggio symbols can be created:

```
<c e g c>2
```

```
\arpeggioBracket
```

```
<c e g c>2\arpeggio
```

```
\arpeggioParenthesis
```

```
<c e g c>2\arpeggio
```

```
\arpeggioParenthesisDashed
```

```
<c e g c>2\arpeggio
```

```
\arpeggioNormal
```

```
<c e g c>2\arpeggio
```



The dash properties of the parenthesis arpeggio are controlled with the 'dash-details' property, which is described at [\[Slurs\]](#), page 114.

Arpeggios can be explicitly written out with ties. For more information, see [\[Ties\]](#), page 46.

## Predefined commands


`\arpeggio`, `\arpeggioArrowUp`, `\arpeggioArrowDown`, `\arpeggioNormal`, `\arpeggioBracket`, `\arpeggioParenthesis` `\arpeggioParenthesisDashed`.

## Selected Snippets

### *Creating cross-staff arpeggios in a piano staff*

In a `PianoStaff`, it is possible to let an arpeggio cross between the staves by setting the property `PianoStaff.connectArpeggios`.

```
\new PianoStaff \relative c' <<
  \set PianoStaff.connectArpeggios = ##t
  \new Staff {
    <c e g c>4\arpeggio
    <g c e g>4\arpeggio
    <e g c e>4\arpeggio
    <c e g c>4\arpeggio
  }
  \new Staff {
    \clef bass
    \repeat unfold 4 {
      <c,, e g c>4\arpeggio
    }
  }
>>
```



### *Creating cross-staff arpeggios in other contexts*


Cross-staff arpeggios can be created in contexts other than `GrandStaff`, `PianoStaff` and `StaffGroup` if the `Span_arpeggio_engraver` is included in the `Score` context.

```
\score {
  \new ChoirStaff {
    \set Score.connectArpeggios = ##t
    <<
      \new Voice \relative c' {
```

```

        <c e>2\arpeggio
        <d f>2\arpeggio
        <c e>1\arpeggio
    }
    \new Voice \relative c {
        \clef bass
        <c g'>2\arpeggio
        <b g'>2\arpeggio
        <c g'>1\arpeggio
    }
    >>
}
\layout {
    \context {
        \Score
        \consists "Span_arpeggio_engraver"
    }
}
}

```



### *Creating arpeggios across notes in different voices*

An arpeggio can be drawn across notes in different voices on the same staff if the `Span_arpeggio_engraver` is added to the `Staff` context:

```

\new Staff \with {
    \consists "Span_arpeggio_engraver"
}
\relative c' {
    \set Staff.connectArpeggios = ##t
    <<
        { <e' g>4\arpeggio <d f> <d f>2 }
        \\\
        { <d, f>2\arpeggio <g b>2 }
    >>
}

```



## See also

Music Glossary: [Section “arpeggio” in Music Glossary](#).

Notation Reference: [\[Slurs\]](#), page 114, [\[Ties\]](#), page 46.

Snippets: [Section “Expressive marks” in Snippets](#).

Internals Reference: [Section “Arpeggio” in Internals Reference](#), [Section “Slur” in Internals Reference](#), [Section “PianoStaff” in Internals Reference](#).

## Known issues and warnings

It is not possible to mix connected arpeggios and unconnected arpeggios in one `PianoStaff` at the same point in time.


The parenthesis-style arpeggio brackets do not work for cross-staff arpeggios.

## Trills

Short trills without an extender line are printed with `\trill`; see [\[Articulations and ornaments\]](#), page 105.

Longer trills with an extender line are made with `\startTrillSpan` and `\stopTrillSpan`:

```
d1\startTrillSpan
d1
c2\stopTrillSpan
r2
```




A trill spanner crossing a line break will restart exactly above the first note on the new line.

```
d1\startTrillSpan
\break
d1
c2\stopTrillSpan
r2
```



Consecutive trill spans will work without explicit `\stopTrillSpan` commands, since successive trill spanners will automatically become the right bound of the previous trill.

```
d1\startTrillSpan
d1
b1\startTrillSpan
d2\stopTrillSpan
r2
```



Trills can also be combined with grace notes. The syntax of this construct and the method to precisely position the grace notes are described in [\[Grace notes\]](#), page 97.

```
d1~\afterGrace
d1\startTrillSpan { c32[ d]\stopTrillSpan }
c2 r2
```



Trills that require an auxiliary note with an explicit pitch can be typeset with the `\pitchedTrill` command. The first argument is the main note, and the second is the *trilled* note, printed as a stemless note head in parentheses.

```
\pitchedTrill
d2\startTrillSpan fis
d2
c2\stopTrillSpan
r2
```



Subsequent accidentals of the same note in the same measure will need to be added manually. Only the accidental of the first pitched trill in a measure is printed.

```
\pitchedTrill
eis4\startTrillSpan fis
eis4\stopTrillSpan
\pitchedTrill
eis4\startTrillSpan cis
eis4\stopTrillSpan
\pitchedTrill
eis4\startTrillSpan fis
eis4\stopTrillSpan
\pitchedTrill
eis4\startTrillSpan fis!
eis4\stopTrillSpan
```



## Predefined commands

`\startTrillSpan`, `\stopTrillSpan`.



## See also

Music Glossary: [Section “trill” in Music Glossary](#).

Notation Reference: [\[Articulations and ornamentations\]](#), page 105, [\[Grace notes\]](#), page 97.

Snippets: [Section “Expressive marks” in Snippets](#).

Internals Reference: [Section “TrillSpanner” in Internals Reference](#).

## 1.4 Repeats



Repetition is a central concept in music, and multiple notations exist for repetitions. LilyPond supports the following kinds of repeats:

- volta**      The repeated music is not written out but enclosed between repeat bar lines. If the repeat is at the beginning of a piece, a repeat bar line is only printed at the end of the repeat. Alternative endings (volte) are printed left to right with brackets. This is the standard notation for repeats with alternatives.
- unfold**     The repeated music is fully written out, as many times as specified by *repeatcount*. This is useful when entering repetitious music.
- percent**    These are beat or measure repeats. They look like single slashes or percent signs.
- tremolo**    This is used to write tremolo beams.

### 1.4.1 Long repeats

This section discusses how to input long (usually multi-measure) repeats. The repeats can take two forms: repeats enclosed between repeat signs; or written-out repeats, used to input repetitious music. Repeat signs can also be controlled manually.

#### Normal repeats

The syntax for a normal repeat is

```
\repeat volta repeatcount musicexpr
```

where *musicexpr* is a music expression.

A single repeat without an alternate ending:

```
\repeat volta 2 { c4 d e f }
c2 d
\repeat volta 2 { d4 e f g }
```



Alternative endings can be produced using `\alternative`. Each group of alternatives must be themselves, enclosed in a set of braces.

```
\repeat volta repeatcount musicexpr
\alternative {
  { musicexpr }
}
```

where *musicexpr* is a music expression.

If there are more repeats than there are alternate endings, the earliest repeats are given the first alternative.

A single repeat with one alternate ending:

```
\repeat volta 2 { c4 d e f | }
\alternative {
  { c2 e | }
  { f2 g | }
}
c1
```




A single repeat with more than one alternate ending:

```
\repeat volta 4 { c4 d e f | }
\alternative {
  { c2 e | }
  { f2 g | }
}
c1
```



Multiple repeats with more than one alternate ending:

```
\repeat volta 3 { c4 d e f | }
\alternative {
  { c2 e | }
  { f2 g | }
  { a2 g | }
}
c1
```



**Note:** If there are two or more alternatives, nothing should appear between the closing brace of one and the opening brace of the next in an `\alternative` block, otherwise you will not get the expected number of endings.

**Note:** If you include `\relative` inside a `\repeat` without explicitly instantiating the `Voice` context, extra (unwanted) staves will appear. See [Section “An extra staff appears”](#) in *Application Usage*.

If a repeat starts in the middle of a measure and has no alternate endings, normally the end of the repeat will also fall in the middle of a measure, so that the two ends add up to one complete measure. In such cases, the repeat signs do not constitute true bar lines. Do not use `\partial` commands or bar checks where these repeat signs are printed:

```
% no \partial here
c4 e g % no bar check here
% no \partial here
\repeat volta 4 {
  e4 |
  c2 e |
  % no \partial here
  g4 g g % no bar check here
}
% no \partial here
g4 |
a2 a |
g1 |
```



Similarly, if a repeat begins with the initial partial measure of a score and has no alternate endings, the same conditions apply as in the above example, except that in this case the `\partial` command is required at the beginning of the score:

```
\partial 4 % required
\repeat volta 4 {
  e4 |
  c2 e |
  % no \partial here
  g4 g g % no bar check here
}
% no \partial here
g4 |
a2 a |
g1 |
```



When alternate endings are added to a repeat that begins with an incomplete measure, it becomes necessary to set the `Timing.measureLength` context property manually, in the following specific places:

- at the start of any incomplete measures in the `\alternative` block, which normally occur at the end of each alternative, except (in most cases) the last.
- at the start of each alternative, except the first.

```

\partial 4
\repeat volta 2 { e4 | c2 e | }
\alternative {
  {
    f2 d |
    \set Timing.measureLength = #(ly:make-moment 3 4)
    g4 g g % optional bar check is allowed here
  }
  {
    \set Timing.measureLength = #(ly:make-moment 4 4)
    a2 a |
  }
}
g1 |

```




The `measureLength` property is described in [\[Time administration\]](#), page 103.

Ties may be added to a second ending:

```

c1
\repeat volta 2 { c4 d e f~ }
\alternative {
  { f2 d }
  { f2\repeatTie f, }
}

```



## Selected Snippets

### *Shortening volta brackets*

By default, the volta brackets will be drawn over all of the alternative music, but it is possible to shorten them by setting `voltaSpannerDuration`. In the next example, the bracket only lasts one measure, which is a duration of  $3/4$ .

```

\relative c'' {
  \time 3/4
  c4 c c
  \set Score.voltaSpannerDuration = #(ly:make-moment 3 4)
  \repeat volta 5 { d4 d d }
  \alternative {
    {
      e4 e e
    }
  }
}

```

```

        f4 f f
      }
    { g4 g g }
  }
}

```



#### *Adding volta brackets to additional staves*

The `Volta_engraver` by default resides in the `Score` context, and brackets for the repeat are thus normally only printed over the topmost staff. This can be adjusted by adding the `Volta_engraver` to the `Staff` context where the brackets should appear; see also the “Volta multi staff” snippet.

```

<<
  \new Staff { \repeat volta 2 { c'1 } \alternative { c' } }
  \new Staff { \repeat volta 2 { c'1 } \alternative { c' } }
  \new Staff \with { \consists "Volta_engraver" } { c'2 g' e' a' }
  \new Staff { \repeat volta 2 { c'1 } \alternative { c' } }
>>

```




#### *Setting the double repeat default for volte*

There are three different styles of double repeats for volte, that can be set using `doubleRepeatType`.

```

\relative c'' {
  \repeat volta 1 { c1 }
  \set Score.doubleRepeatType = #":|:"
  \repeat volta 1 { c1 }
  \set Score.doubleRepeatType = #":|.|:"
  \repeat volta 1 { c1 }
  \set Score.doubleRepeatType = #":|.:"
  \repeat volta 1 { c1 }
}

```



### Alternative bar numbering

Two alternative methods for bar numbering can be set, especially for when using repeated music.

```
\relative c'{
  \set Score.alternativeNumberingStyle = #'numbers
  \repeat volta 3 { c4 d e f | }
  \alternative {
    { c4 d e f | c2 d \break }
    { f4 g a b | f4 g a b | f2 a | \break }
    { c4 d e f | c2 d }
  }
  c1 \break
  \set Score.alternativeNumberingStyle = #'numbers-with-letters
  \repeat volta 3 { c,4 d e f | }
  \alternative {
    { c4 d e f | c2 d \break }
    { f4 g a b | f4 g a b | f2 a | \break }
    { c4 d e f | c2 d }
  }
  c1
}
```

## See also

Music Glossary: [Section “repeat” in Music Glossary](#), [Section “volta” in Music Glossary](#).

Notation Reference: [\[Bar lines\]](#), page 85, [Section 5.1.4 \[Modifying context plug-ins\]](#), page 524, [\[Time administration\]](#), page 103.

Snippets: [Section “Repeats” in Snippets](#).

Internals Reference: [Section “VoltaBracket” in Internals Reference](#), [Section “RepeatedMusic” in Internals Reference](#), [Section “VoltaRepeatedMusic” in Internals Reference](#), [Section “UnfoldedRepeatedMusic” in Internals Reference](#).

## Known issues and warnings

Slurs that span from a `\repeat` block into an `\alternative` block will only work for the first alternate ending. Also, slurs cannot wrap around from the end of one alternative back to the beginning of the repeat.

If a repeat that begins with an incomplete measure has an `\alternative` block that contains modifications to the `measureLength` property, using `\unfoldRepeats` will result in wrongly-placed bar lines and bar check warnings.

A nested repeat like

```
\repeat ...
\repeat ...
\alternative
```

is ambiguous, since it is not clear to which `\repeat` the `\alternative` belongs. This ambiguity is resolved by always having the `\alternative` belong to the inner `\repeat`. For clarity, it is advisable to use braces in such situations.

## Manual repeat marks

**Note:** These methods are only used for displaying unusual repeat constructs, and may produce unexpected behavior. In most cases, repeats should be created using the standard `\repeat` command or by printing the relevant bar lines. For more information, see [\[Bar lines\]](#), page 85.

The property `repeatCommands` can be used to control the layout of repeats. Its value is a Scheme list of repeat commands.

### start-repeat

Print a |: bar line.

```
c1
\set Score.repeatCommands = #'(start-repeat)
d4 e f g
c1
```



As per standard engraving practice, repeat signs are not printed at the beginning of a piece.

### end-repeat

Print a :| bar line:

```

c1
d4 e f g
\set Score.repeatCommands = #'(end-repeat)
c1

```



(volta number) ... (volta #f)

Create a new volta with the specified number. The volta bracket must be explicitly terminated, or it will not be printed.

```

f4 g a b
\set Score.repeatCommands = #'((volta "2"))
g4 a g a
\set Score.repeatCommands = #'((volta #f))
c1

```




Multiple repeat commands may occur at the same point:

```

f4 g a b
\set Score.repeatCommands = #'((volta "2, 5") end-repeat)
g4 a g a
c1
\set Score.repeatCommands = #'((volta #f) (volta "95") end-repeat)
b1
\set Score.repeatCommands = #'((volta #f))

```



Text can be included with the volta bracket. The text can be a number or numbers or markup text, see [Section 1.8.2 \[Formatting text\]](#), page 210. The simplest way to use markup text is to define the markup first, then include the markup in a Scheme list.

```

voltaAdLib = \markup { 1. 2. 3... \text \italic { ad lib. } }
\relative c'' {
  c1
  \set Score.repeatCommands = #(list(list 'volta voltaAdLib) 'start-repeat)
  c4 b d e
  \set Score.repeatCommands = #'((volta #f) (volta "4.") end-repeat)
  f1
  \set Score.repeatCommands = #'((volta #f))
}

```






## Selected Snippets

*Printing a repeat sign at the beginning of a piece*

A |: bar line can be printed at the beginning of a piece, by overriding the relevant property:

```
\relative c'' {
  \once \override Score.BreakAlignment #'break-align-orders =
    #(make-vector 3 '(instrument-name
                      left-edge
                      ambitus
                      breathing-sign
                      clef
                      key-signature
                      time-signature
                      staff-bar
                      custos))
  \once \override Staff.TimeSignature #'space-alist =
    #'((first-note . (fixed-space . 2.0))
       (right-edge . (extra-space . 0.5))
       ;; free up some space between time signature
       ;; and repeat bar line
       (staff-bar . (extra-space . 1)))
  \bar "||:"
  c1
  d1
  d4 e f g
}
```



## See also

Notation Reference: [Bar lines], page 85, Section 1.8.2 [Formatting text], page 210.

Snippets: Section “Repeats” in *Snippets*.

Internals Reference: Section “VoltaBracket” in *Internals Reference*, Section “RepeatedMusic” in *Internals Reference*, Section “VoltaRepeatedMusic” in *Internals Reference*.

## Written-out repeats

By using the `unfold` command, repeats can be used to simplify the writing out of repetitious music. The syntax is

```
\repeat unfold repeatcount musicexpr
```

where *musicexpr* is a music expression and *repeatcount* is the number of times *musicexpr* is repeated.

```
\repeat unfold 2 { c4 d e f }
c1
```



In some cases, especially in a `\relative` context, the `\repeat unfold` function is not the same as writing out the music expression multiple times. E.g.,

```
\repeat unfold 2 { a'4 b c }
```

is not equivalent to

```
a'4 b c | a'4 b c
```

Unfold repeats can be made with alternate endings.

```
\repeat unfold 2 { c4 d e f }
\alternative {
  { c2 g' }
  { c,2 b }
}
c1
```



If there are more repeats than there are alternate endings, the first alternative is applied multiple times until the remaining alternatives make up the total number of repeats.

```
\repeat unfold 4 { c4 d e f }
\alternative {
  { c2 g' }
  { c,2 b }
  { e2 d }
}
c1
```



If there are more alternate endings than repeats then only the first alternatives are applied. The remaining alternatives will be ignored and not printed.

```
\repeat unfold 2 { c4 d e f }
\alternative {
  { c2 g' }
  { c,2 b }
  { e2 d }
}
c1
```



It is also possible to nest multiple `unfold` functions (with or without alternate endings).

```

\repeat unfold 2 {
  \repeat unfold 2 { c4 d e f }
  \alternative {
    { c2 g' }
    { c,2 b }
  }
}
c1

```



Chord constructs can be repeated by the chord repetition symbol `q`. See [\[Chord repetition\]](#), page 143.

**Note:** If you include `\relative` inside a `\repeat` without explicitly instantiating the `Voice` context, extra (unwanted) staves will appear. See [Section “An extra staff appears”](#) in *Application Usage*.

## See also

Notation Reference: [\[Chord repetition\]](#), page 143.

Snippets: [Section “Repeats”](#) in *Snippets*.

Internals Reference: [Section “RepeatedMusic”](#) in *Internals Reference*, [Section “UnfoldedRepeatedMusic”](#) in *Internals Reference*.

### 1.4.2 Short repeats

This section discusses how to input short repeats. Short repeats can take two forms: slashes or percent signs to represent repeats of a single note, a single measure or two measures, and tremolos otherwise.

#### Percent repeats

Repeated short patterns are printed once, and the repeated pattern is replaced with a special sign.

The syntax is

```
\repeat percent number musicexpr
```


where *musicexpr* is a music expression.

Patterns that are shorter than one measure are replaced by slashes.

```

\repeat percent 4 { c128 d e f }
\repeat percent 4 { c64 d e f }
\repeat percent 5 { c32 d e f }
\repeat percent 4 { c16 d e f }
\repeat percent 4 { c8 d }
\repeat percent 4 { c4 }
\repeat percent 2 { c2 }

```



Patterns of one or two measures are replaced by percent-like symbols.

```
\repeat percent 2 { c4 d e f }
\repeat percent 2 { c2 d }
\repeat percent 2 { c1 }
```




```
\repeat percent 3 { c4 d e f | c2 g' }
```



Patterns that are shorter than one measure but contain mixed durations use a double-percent symbol.

```
\repeat percent 4 { c8. <d f>16 }
\repeat percent 2 { \times 2/3 { r8 c d } e4 }
```



## Selected Snippets

### *Percent repeat counter*

Measure repeats of more than two repeats can get a counter when the convenient property is switched, as shown in this example:

```
\relative c'' {
  \set countPercentRepeats = ##t
  \repeat percent 4 { c1 }
}
```




### *Percent repeat count visibility*

Percent repeat counters can be shown at regular intervals by setting the context property `repeatCountVisibility`.

```

\relative c'' {
  \set countPercentRepeats = ##t
  \set repeatCountVisibility = #(every-nth-repeat-count-visible 5)
  \repeat percent 10 { c1 } \break
  \set repeatCountVisibility = #(every-nth-repeat-count-visible 2)
  \repeat percent 6 { c1 d1 }
}

```



### Isolated percent repeats

Isolated percents can also be printed.

```

makePercent =
#(define-music-function (parser location note) (ly:music?)
  "Make a percent repeat the same length as NOTE."
  (make-music 'PercentEvent
    'length (ly:music-length note)))

\relative c'' {
  \makePercent s1
}

```



### See also

Music Glossary: [Section “percent repeat”](#) in *Music Glossary*, [Section “simile”](#) in *Music Glossary*.

Snippets: [Section “Repeats”](#) in *Snippets*.

Internals Reference: [Section “RepeatSlash”](#) in *Internals Reference*, [Section “RepeatSlashEvent”](#) in *Internals Reference*, [Section “DoubleRepeatSlash”](#) in *Internals Reference*, [Section “PercentRepeat”](#) in *Internals Reference*, [Section “PercentRepeatCounter”](#) in *Internals Reference*, [Section “PercentRepeatedMusic”](#) in *Internals Reference*, [Section “Percent\\_repeat\\_engraver”](#) in *Internals Reference*, [Section “DoublePercentEvent”](#) in *Internals Reference*, [Section “DoublePercentRepeat”](#) in *Internals Reference*, [Section “DoublePercentRepeatCounter”](#) in *Internals Reference*, [Section “Double\\_percent\\_repeat\\_engraver”](#) in *Internals Reference*, [Section “Slash\\_repeat\\_engraver”](#) in *Internals Reference*.

### Tremolo repeats

Tremolos can take two forms: alternation between two chords or two notes, and rapid repetition of a single note or chord. Tremolos consisting of an alternation are indicated by adding beams

between the notes or chords being alternated, while tremolos consisting of the rapid repetition of a single note are indicated by adding beams or slashes to a single note.

To place tremolo marks between notes, use `\repeat` with tremolo style:

```
\repeat tremolo 8 { c16 d }
\repeat tremolo 6 { c16 d }
\repeat tremolo 2 { c16 d }
```



The `\repeat tremolo` syntax expects exactly two notes within the braces, and the number of repetitions must correspond to a note value that can be expressed with plain or dotted notes. Thus, `\repeat tremolo 7` is valid and produces a double dotted note, but `\repeat tremolo 9` is not.

The duration of the tremolo equals the duration of the braced expression multiplied by the number of repeats: `\repeat tremolo 8 { c16 d16 }` gives a whole note tremolo, notated as two whole notes joined by tremolo beams.

There are two ways to put tremolo marks on a single note. The `\repeat tremolo` syntax is also used here, in which case the note should not be surrounded by braces:

```
\repeat tremolo 4 c'16
```



The same output can be obtained by adding `:N` after the note, where  $N$  indicates the duration of the subdivision (it must be at least 8). If  $N$  is 8, one beam is added to the note's stem. If  $N$  is omitted, the last value (stored in `tremoloFlags`) is used:

```
c2:8 c:32
c: c:
```



## Selected Snippets

### *Cross-staff tremolos*

Since `\repeat tremolo` expects exactly two musical arguments for chord tremolos, the note or chord which changes staff within a cross-staff tremolo should be placed inside curly braces together with its `\change Staff` command.

```
\new PianoStaff <<
  \new Staff = "up" \relative c'' {
    \key a \major
    \time 3/8
    s4.
  }
  \new Staff = "down" \relative c'' {
    \key a \major
    \time 3/8
```

```

\voiceOne
\repeat tremolo 6 {
  <a e'>32
  {
    \change Staff = "up"
    \voiceTwo
    <cis a' dis>32
  }
}
}
>>

```



See also

Snippets: [Section “Repeats” in Snippets](#).

## 1.5 Simultaneous notes

Polyphony in music refers to having more than one voice occurring in a piece of music. Polyphony in LilyPond refers to having more than one voice on the same staff.


### 1.5.1 Single voice

This section discusses simultaneous notes inside the same voice.

## Chorded notes


A chord is formed by enclosing a set of pitches between < and >. A chord may be followed by a duration just like simple notes.

```
<a c e>1 <a c e>2 <f a c e>4 <a c>8. <g c e>16
```




Chords may also be followed by articulations, again just like simple notes.

```
<a c e>1\fermata <a c e>2-> <f a c e>4\prall <a c>8.^| <g c e>16-.
```




The notes within the chord themselves can also be followed by articulation and ornamentation.

```
<a c\prall e>1 <a-> c-^ e>2 <f-. a c-. e-.>4 <a-+ c-->8. <g\fermata c e\turn>16
```




However some notation, such as dynamics, hairpins and slurs must be attached to the chord, rather than notes within the chord, otherwise they will not print.

```
<a\f c( e>1 <a c) e>\f <a\< c e>( <a\! c e>) <a c e>\< <a c e> <a c e>\!
```



Relative mode can be used for pitches in chords. The first note of each chord is always relative to the first note of the chord that came before it, or in the case where no preceding chord exists, the pitch of the last note that came before the chord. All remaining notes in the chord are relative to the note that came before it *within the same chord*.

```
<a c e>1 <f a c> <a c e> <f' a c> <b, e b,>
```



For more information about chords, see [Section 2.7 \[Chord notation\]](#), page 367.

## See also

Music Glossary: [Section “chord” in Music Glossary](#).

Learning Manual: [Section “Combining notes into chords” in Learning Manual](#).

Notation Reference: [Section 2.7 \[Chord notation\]](#), page 367, [\[Articulations and ornamentations\]](#), page 105, [\[Relative octave entry\]](#), page 2, [Section 1.5.2 \[Multiple voices\]](#), page 146.

Snippets: [Section “Simultaneous notes” in Snippets](#).



## Known issues and warnings


Chords containing more than two pitches within a staff space, such as ‘<e f! fis!>’, create overlapping noteheads. Depending on the situation, better representations might involve

- temporary use of [Section 1.5.2 \[Multiple voices\]](#), [page 146](#), ‘<< f! \\ <e fis!> >>’,
- enharmonic transcription of one or more pitches, ‘<e f ges>’, or
- [\[Clusters\]](#), [page 145](#).

## Chord repetition


In order to save typing, a shortcut can be used to repeat the preceding chord. The chord repetition symbol is q:

```
<a c e>1 q <f a c>2 q
```




As with regular chords, the chord repetition symbol can be used with durations, articulations, markups, slurs, beams, etc. as only the pitches of the previous chord are duplicated.

```
<a c e>1\p^"text" q2\<( q8)[-| q8.]\! q16-1-2-3 q8\prall
```



The chord repetition symbol always remembers the last instance of a chord so it is possible to repeat the most recent chord even if other non-chorded notes or rests have been added since.

```
<a c e>1 c'4 q2 r8 q8 |
q2 c, |
```



However, the chord repetition symbol does not retain any dynamics, articulation or ornamentation within, or attached to, the previous chord.

```
<a-. c\prall e>1\sفز c'4 q2 r8 q8 |
q2 c, |
```




To have some of them retained, the `\chordRepeats` function can be called explicitly with an extra argument specifying a list of *event types* to keep unless events of that type are already present on the q chord itself.

```

\relative c'' {
  \chordRepeats #'(articulation-event)
  { <a-. c\prall e>1\s fz c'4 q2 r8 q8-. } |
  q2 c, |
}

```




Here using `\chordRepeats` inside of a `\relative` construction produces unexpected results: once chord events have been expanded, they are indistinguishable from having been entered as regular chords, making `\relative` assign an octave based on their current context.

Since nested instances of `\relative` don't affect one another, another `\relative` inside of `\chordRepeats` can be used for establishing the octave relations before expanding the repeat chords. In that case, the whole content of the inner `\relative` does not affect the outer one; hence the different octave entry of the final note in this example.

```

\new Voice
\relative c'' {
  \chordRepeats #'(articulation-event)
  \relative c''
  { <a-. c\prall e>1\s fz c'4 q2 r8 q8-. } |
  q2 c |
}

```



Interactions with `\relative` occur only with explicit calls of `\chordRepeats`: the implicit expansion at the start of typesetting is done at a time where all instances of `\relative` have already been processed.

## See also

Notation Reference: [Section 2.7 \[Chord notation\]](#), page 367, [\[Articulations and ornamentations\]](#), page 105.

Installed Files: `'ly/chord-repetition-init.ly'`.

## Simultaneous expressions

One or more music expressions enclosed in double angle brackets are taken to be simultaneous. If the first expression begins with a single note or if the whole simultaneous expression appears explicitly within a single voice, the whole expression is placed on a single staff; otherwise the elements of the simultaneous expression are placed on separate staves.

The following examples show simultaneous expressions on one staff:

```

\new Voice { % explicit single voice
  << { a4 b g2 } { d4 g c,2 } >>
}

```



```
% single first note
a << { a4 b g } { d4 g c, } >>
```



This can be useful if the simultaneous sections have identical rhythms, but attempts to attach notes with different durations to the same stem will cause errors.

The following example shows how simultaneous expressions can generate multiple staves implicitly:

```
% no single first note
<< { a4 b g2 } { d4 g2 c,4 } >>
```



Here different rhythms cause no problems.

## Known issues and warnings

If notes from two or more voices, with stems in the same direction, are placed at the same position on the staff and have no shift (or have the same shift specified), the message:

```
warning: ignoring too many clashing note columns
```

will appear during compilation. This message can be suppressed by:


```
\override NoteColumn #'ignore-collision = ##t
```

However, this not only suppresses the warning but will prevent any collision resolution whatsoever and may have other unintended effects (also see *Known Issues* in [\[Collision resolution\]](#), page 150).

## Clusters

A cluster indicates a continuous range of pitches to be played. They can be denoted as the envelope of a set of notes. They are entered by applying the function `\makeClusters` to a sequence of chords, e.g.,

```
\makeClusters { <g b>2 <c g'> }
```



Ordinary notes and clusters can be put together in the same staff, even simultaneously. In such a case no attempt is made to automatically avoid collisions between ordinary notes and clusters.

## See also

Music Glossary: [Section “cluster” in \*Music Glossary\*](#).

Snippets: [Section “Simultaneous notes” in \*Snippets\*](#).

Internals Reference: [Section “ClusterSpanner” in \*Internals Reference\*](#), [Section “ClusterSpannerBeacon” in \*Internals Reference\*](#), [Section “Cluster\\_spanner\\_engraver” in \*Internals Reference\*](#).

## Known issues and warnings

Clusters look good only if they span at least two chords; otherwise they appear too narrow.

Clusters do not have a stem and cannot indicate durations by themselves, but the length of the printed cluster is determined by the durations of the defining chords. Separate clusters need a separating rest between them.

Clusters do not produce MIDI output.

### 1.5.2 Multiple voices

This section discusses simultaneous notes in multiple voices or multiple staves.

#### Single-staff polyphony

*Explicitly instantiating voices*

The basic structure needed to achieve multiple independent voices in a single staff is illustrated in the following example:

```
\new Staff <<
  \new Voice = "first"
    { \voiceOne r8 r16 g e8. f16 g8[ c,] f e16 d }
  \new Voice= "second"
    { \voiceTwo d16 c d8~ d16 b c8~ c16 b c8~ c16 b8. }
>>
```



Here, voices are instantiated explicitly and are given names. The `\voiceOne ... \voiceFour` commands set up the voices so that first and third voices get stems up, second and fourth voices get stems down, third and fourth voice note heads are horizontally shifted, and rests in the respective voices are automatically moved to avoid collisions. The `\oneVoice` command returns all the voice settings to the neutral default directions.

*Temporary polyphonic passages*

A temporary polyphonic passage can be created with the following construct:

```
<< { \voiceOne ... }
  \new Voice { \voiceTwo ... }
>> \oneVoice
```

Here, the first expression within a temporary polyphonic passage is placed into the `Voice` context which was in use immediately before the polyphonic passage, and that same `Voice` context continues after the temporary section. Other expressions within the angle brackets are assigned to distinct temporary voices. This allows lyrics to be assigned to one continuing voice before, during and after a polyphonic section:

```
<<
  \new Voice = "melody" {
```

```

a4
<<
{
  \voiceOne
  g f
}
  \new Voice {
    \voiceTwo
    d2
  }
>>
\oneVoice
e4
}
\new Lyrics \lyricsto "melody" {
This is my song.
}
>>

```



Here, the `\voiceOne` and `\voiceTwo` commands are required to define the settings of each voice.

#### *The double backslash construct*

The `<< {...} \ \ {...} >>` construct, where the two (or more) expressions are separated by double backslashes, behaves differently to the similar construct without the double backslashes: *all* the expressions within this construct are assigned to new **Voice** contexts. These new **Voice** contexts are created implicitly and are given the fixed names "1", "2", etc.

The first example could be typeset as follows:

```

<<
{ r8 r16 g e8. f16 g8[ c,] f e16 d }
\ \
{ d16 c d8~ d16 b c8~ c16 b c8~ c16 b8. }
>>

```



This syntax can be used where it does not matter that temporary voices are created and then discarded. These implicitly created voices are given the settings equivalent to the effect of the `\voiceOne ... \voiceFour` commands, in the order in which they appear in the code.

In the following example, the intermediate voice has stems up, therefore we enter it in the third place, so it becomes voice three, which has the stems up as desired. Spacer rests are used to avoid printing doubled rests.

```

<<
{ r8 g g g g f16 ees f8 d }
\ \

```

```
{ ees,8 r ees r d r d r }
\\
{ d'8 s c s bes s a s }
>>
```



In all but the simplest works it is advisable to create explicit **Voice** contexts as explained in [Section “Contexts and engravers”](#) in *Learning Manual* and [Section “Explicitly instantiating voices”](#) in *Learning Manual*.

#### *Voice order*

When entering multiple voices in the input file, use the following order:

```
Voice 1: highest
Voice 2: lowest
Voice 3: second highest
Voice 4: second lowest
Voice 5: third highest
Voice 6: third lowest
etc.
```

Though this may seem counterintuitive, it simplifies the automatic layout process. Note that the odd-numbered voices are given upstems, and the even-numbered voices are given downstems:

```
\new Staff <<
  \time 2/4
  { f''2 } % 1: highest
  \\
  { c'2 } % 2: lowest
  \\
  { d''2 } % 3: second-highest
  \\
  { e'2 } % 4: second-lowest
  \\
  { b'2 } % 5: third-highest
  \\
  { g'2 } % 6: third-lowest
>>
```



**Note:** Lyrics, spanners (such as slurs, ties, hairpins etc.) cannot be created ‘across’ voices.

#### *Identical rhythms*

In the special case that we want to typeset parallel pieces of music that have the same rhythm, we can combine them into a single **Voice** context, thus forming chords. To achieve this, enclose them in a simple simultaneous music construct within an explicit voice:

```
\new Voice <<
  { e4 f8 d e16 f g8 d4 }
  { c4 d8 b c16 d e8 b4 }
>>
```



This method leads to strange beamings and warnings if the pieces of music do not have the same rhythm.

## Predefined commands

`\voiceOne`, `\voiceTwo`, `\voiceThree`, `\voiceFour`, `\oneVoice`.

Snippets: [Section “Simultaneous notes” in \*Snippets\*](#).

## See also


Learning Manual: [Section “Voices contain music” in \*Learning Manual\*](#), [Section “Explicitly instantiating voices” in \*Learning Manual\*](#).

Notation Reference: [\[Percussion staves\]](#), page 348, [\[Invisible rests\]](#), page 51, [\[Stems\]](#), page 197.

## Voice styles

Voices may be given distinct colors and shapes, allowing them to be easily identified:

```
<<
  { \voiceOneStyle d4 c2 b4 }
  \\\
  { \voiceTwoStyle e,2 e }
  \\\
  { \voiceThreeStyle b2. c4 }
  \\\
  { \voiceFourStyle g'2 g }
>>
```



The `\voiceNeutralStyle` command is used to revert to the standard presentation.

## Predefined commands

`\voiceOneStyle`, `\voiceTwoStyle`, `\voiceThreeStyle`, `\voiceFourStyle`, `\voiceNeutralStyle`.

## See also

Learning Manual: [Section “I’m hearing Voices” in \*Learning Manual\*](#), [Section “Other sources of information” in \*Learning Manual\*](#).

Snippets: [Section “Simultaneous notes” in \*Snippets\*](#).

## Collision resolution

The note heads of notes in different voices with the same pitch, same note head and opposite stem direction are automatically merged, but notes with different note heads or the same stem direction are not. Rests opposite a stem in a different voice are shifted vertically. The following example shows three different circumstances, on beats 1 and 3 in bar 1 and beat 1 in bar 2, where the automatic merging fails.

```
<<
{
  c8 d e d c d c4
  g'2 fis
} \\ {
  c2 c8. b16 c4
  e,2 r
} \\ {
  \oneVoice
  s1
  e8 a b c d2
}
>>
```



Notes with different note heads may be merged, with the exception of half-note heads and quarter-note heads, as shown below. Here the note heads on beat 1 of bar 1 are now merged:

```
<<
{
  \mergeDifferentlyHeadedOn
  c8 d e d c d c4
  g'2 fis
} \\ {
  c2 c8. b16 c4
  e,2 r
} \\ {
  \oneVoice
  s1
  e8 a b c d2
}
>>
```



Note heads with different dots as shown in beat 3 of bar 1 may be also be merged:

```
<<
{
  \mergeDifferentlyHeadedOn
  \mergeDifferentlyDottedOn
```



```

      c8 d e d c d c4
      g'2 fis
} \ {
      c2 c8. b16 c4
      e,2 r
} \ {
      \oneVoice
      s1
      e8 a b c d2
}
>>

```



The half note and eighth note at the start of the second measure are incorrectly merged because the automatic merge cannot successfully complete the merge when three or more notes line up in the same note column, and in this case the merged note head is incorrect. To allow the merge to select the correct note head a `\shift` must be applied to the note that should not be merged. Here, `\shiftOn` is applied to move the top *g* out of the column, and `\mergeDifferentlyHeadedOn` then works properly.

```

<<
{
  \mergeDifferentlyHeadedOn
  \mergeDifferentlyDottedOn
  c8 d e d c d c4
  \shiftOn
  g'2 fis
} \ {
  c2 c8. b16 c4
  e,2 r
} \ {
  \oneVoice
  s1
  e8 a b c d2
}
>>

```



The `\shiftOn` command allows (but does not force) the notes in a voice to be shifted. When `\shiftOn` is applied to a voice, a note or chord in that voice is shifted only if its stem would otherwise collide with a stem from another voice, and only if the colliding stems point in the same direction. The `\shiftOff` command prevents this type of shifting from occurring.

By default, the outer voices (normally voices one and two) have `\shiftOff` specified, while the inner voices (three and above) have `\shiftOn` specified. When a shift is applied, voices with upstems (odd-numbered voices) are shifted to the right, and voices with downstems (even-numbered voices) are shifted to the left.

Here is an example to help you visualize how an abbreviated polyphonic expression would be expanded internally.

**Note:** Note that with three or more voices, the vertical order of voices in your input file should not be the same as the vertical order of voices on the staff!

```
\new Staff \relative c'' {
  %% abbreviated entry
  <<
    { f2 } % 1: highest
    \\\
    { g,2 } % 2: lowest
    \\\
    { d'2 } % 3: upper middle
    \\\
    { b2 } % 4: lower middle
  >>
  %% internal expansion of the above
  <<
    \new Voice = "1" { \voiceOne \shiftOff f'2 }
    \new Voice = "2" { \voiceTwo \shiftOff g,2 }
    \new Voice = "3" { \voiceThree \shiftOn d'2 } % shifts right
    \new Voice = "4" { \voiceFour \shiftOn b2 } % shifts left
  >>
}
```



Two additional commands, `\shiftOnn` and `\shiftOnnn` provide further shift levels which may be specified temporarily to resolve collisions in complex situations – see [Section “Real music example” in \*Learning Manual\*](#).

Notes are only merged if they have opposing stem directions (as they have, for example, in voices one and two by default or when the stems are explicitly set in opposite directions).

## Predefined commands

```
\mergeDifferentlyDottedOn, \mergeDifferentlyDottedOff, \mergeDifferentlyHeadedOn,
\mergeDifferentlyHeadedOff.
```

```
\shiftOn, \shiftOnn, \shiftOnnn, \shiftOff.
```

## Selected Snippets

*Additional voices to avoid collisions*

In some instances of complex polyphonic music, additional voices are necessary to prevent collisions between notes. If more than four parallel voices are needed, additional voices can be added by defining a variable using the Scheme function `context-spec-music`.

```
voiceFive = #(context-spec-music (make-voice-props-set 4) 'Voice)
```

```
\relative c'' {
```

```

\time 3/4
\key d \minor
\partial 2
<<
{
  \voiceOne
  a4. a8
  e'4 e4. e8
  f4 d4. c8
}
\\
{
  \voiceThree
  f,2
  bes4 a2
  a4 s2
}
\\
{
  \voiceFive
  s2
  g4 g2
  f4 f2
}
\\
\bar "||" {
  \voiceTwo
  d2
  d4 cis2
  d4 bes2
}
>>
}

```



### *Forcing horizontal shift of notes*

When the typesetting engine cannot cope, the following syntax can be used to override typesetting decisions. The units of measure used here are staff spaces.

```

\relative c' <<
{
  <d g>2 <d g>
}
\\
{
  <b f'>2
  \once \override NoteColumn #'force-hshift = #1.7
}

```

```

    <b f'>2
  }
>>

```



## See also

Music Glossary: [Section “polyphony”](#) in *Music Glossary*.

Learning Manual: [Section “Multiple notes at once”](#) in *Learning Manual*, [Section “Voices contain music”](#) in *Learning Manual*, [Section “Real music example”](#) in *Learning Manual*.

Snippets: [Section “Simultaneous notes”](#) in *Snippets*.

Internals Reference: [Section “NoteColumn”](#) in *Internals Reference*, [Section “NoteCollision”](#) in *Internals Reference*, [Section “RestCollision”](#) in *Internals Reference*.


## Known issues and warnings

Using `\override NoteColumn #'ignore-collision = ##t` will cause differently headed notes in different voices to merge incorrectly.

```

\mergeDifferentlyHeadedOn
<< { c16 a' b a } \ { c,2 } >>
\override NoteColumn #'ignore-collision = ##t
<< { c16 a' b a } \ { c,2 } >>

```



## Automatic part combining

Automatic part combining is used to merge two separate parts of music onto a single staff. This can be especially helpful when typesetting orchestral scores. A single **Voice** is printed while the two parts of music are the same, but in places where they differ, a second **Voice** is printed. Stem directions are set up & down accordingly while Solo and a *due* parts are also identified and marked appropriately.

The syntax for automatic part combining is:

```
\partcombine musicexpr1 musicexpr2
```

The following example demonstrates the basic functionality, putting parts on a single staff as polyphony and setting stem directions accordingly. The same variables are used for the independent parts and the combined staff.

```

instrumentOne = \relative c' {
  c4 d e f |
  R1 |
  d'4 c b a |
  b4 g2 f4 |
  e1 |
}


```

```

instrumentTwo = \relative g' {
  R1 |
  g4 a b c |
  d4 c b a |
  g4 f( e) d |
  e1 |
}

<<
  \new Staff \instrumentOne
  \new Staff \instrumentTwo
  \new Staff \partcombine \instrumentOne \instrumentTwo
>>

```



Both parts have identical notes in the third measure, so only one instance of the notes is printed. Stem, slur, and tie directions are set automatically, depending on whether the parts are playing solo or in unison. When needed in polyphony situations, the first part (with context called *one*) gets “up” stems, while the second (called *two*) always gets “down” stems. In solo situations, the first and second parts get marked with “Solo” and “Solo II”, respectively. The unison (*a due*) parts are marked with the text “a2”.

Both arguments to `\partcombine` will be interpreted as separate *Voice* contexts, so if the music is being specified in relative mode then *both* parts must contain a `\relative` function, i.e.,

```

\partcombine
  \relative ... musicexpr1
  \relative ... musicexpr2

```

A `\relative` section that encloses a `\partcombine` has no effect on the pitches of *musicexpr1* or *musicexpr2*.

In professional scores, voices are often kept apart from each other for long passages of music even if some of the notes are the same in both voices, and could just as easily be printed as unison. Combining notes into a chord, or showing one voice as solo is, therefore, not ideal as the `\partcombine` function considers each note separately. In this case the `\partcombine` function can be overridden with the following commands:

Commands ending in `...Once` apply only to the next note in the music expression.

- `\partcombineApart` and `\partcombineApartOnce` keep the notes as two separate voices, even if they can be combined into a chord or unison.
- `\partcombineChords` and `\partcombineChordsOnce` combine the notes into a chord.
- `\partcombineUnisono` and `\partcombineUnisonoOnce` combine both voices as “unison”.

- `\partcombineSoloI` and `\partcombineSoloIOnce` print only voice one, and mark it as a “Solo”.
- `\partcombineSoloII` or `\partcombineSoloIIOnce` print only voice two and mark it as a “Solo”.
- `\partcombineAutomatic` and `\partcombineAutomaticOnce` end the functions of the commands above, and revert back to the standard `\partcombine` functionality.

```

instrumentOne = \relative c' {
  \partcombineApart c2^"apart" e |
  \partcombineAutomatic e2^"auto" e |
  \partcombineChords e'2^"chord" e |
  \partcombineAutomatic c2^"auto" c |
  \partcombineApart c2^"apart" \partcombineChordsOnce e^"chord once" |
  c2 c |
}
instrumentTwo = \relative c' {
  c2 c |
  e2 e |
  a,2 c |
  c2 c' |
  c2 c |
  c2 c |
}

<<
  \new Staff { \instrumentOne }
  \new Staff { \instrumentTwo }
  \new Staff { \partcombine \instrumentOne \instrumentTwo }
>>

```

The musical score consists of three staves. The top staff has notes with labels 'apart', 'auto', 'chord', 'auto', 'apart', and 'chord once' above them. The middle staff has notes with labels 'apart', 'a2', 'chord', 'auto', 'a2', and 'apart' above them. The bottom staff has notes with labels 'apart', 'a2', 'chord', 'auto', 'a2', and 'apart' above them. The notes are in treble clef with a common time signature 'C'.

## Selected Snippets

### *Combining two parts on the same staff*

The part combiner tool (`\partcombine` command) allows the combination of several different parts on the same staff. Text directions such as “solo” or “a2” are added by default; to remove them, simply set the property `printPartCombineTexts` to `f`. For vocal scores (hymns), there is no need to add “solo/a2” texts, so they should be switched off. However, it might be better not to use it if there are any solos, as they won’t be indicated. In such cases, standard polyphonic notation may be preferable.

This snippet presents the three ways two parts can be printed on a same staff: standard polyphony, `\partcombine` without texts, and `\partcombine` with texts.

```

musicUp = \relative c'' {
  \time 4/4
  a4 c4.( g8) a4 |
  g4 e' g,( a8 b) |
  c b a2.
}

musicDown = \relative c'' {
  g4 e4.( d8) c4 |
  r2 g'4( f8 e) |
  d2 \stemDown a
}

\score {
  <<
  <<
  \new Staff {
    \set Staff.instrumentName = #"Standard polyphony"
    << \musicUp \\\musicDown >>
  }
  \new Staff \with { printPartCombineTexts = ##f } {
    \set Staff.instrumentName = #"PartCombine without texts"
    \partcombine \musicUp \musicDown
  }
  \new Staff {
    \set Staff.instrumentName = #"PartCombine with texts"
    \partcombine \musicUp \musicDown
  }
  >>
  >>
  \layout {
    indent = 6.0\cm
    \context {
      \Score
      \override SystemStartBar #'collapse-height = #30
    }
  }
}

```

Standard polyphony

PartCombine without texts

PartCombine with texts

### Changing partcombine texts

When using the automatic part combining feature, the printed text for the solo and unison sections may be changed:

```
\new Staff <<
  \set Staff.soloText = #"girl"
  \set Staff.soloIIText = #"boy"
  \set Staff.aDueText = #"together"
  \partcombine
  \relative c'' {
    g4 g r r
    a2 g
  }
  \relative c'' {
    r4 r a( b)
    a2 g
  }
}>>
```

### See also

Music Glossary: [Section “a due” in Music Glossary](#), [Section “part” in Music Glossary](#).

Notation Reference: [Section 1.6.3 \[Writing parts\]](#), page 179.

Snippets: [Section “Simultaneous notes” in Snippets](#).

Internals Reference: [Section “PartCombineMusic” in Internals Reference](#), [Section “Voice” in Internals Reference](#).



## Known issues and warnings

All `\partcombine...` functions can only accept two voices and are not designed to work with lyrics; such that when one of the voices is explicitly named in order to attach lyrics to it, the partcombiner will stop working.

`\partcombine...` functions cannot be placed inside a `\times` or `\relative` block.

If `printPartCombineTexts` is set and the two voices play the same notes “on and off”, in the same measure, the part combiner may typeset `a2` more than once in that measure.

`\partcombine` only knows when a note starts in a `Voice`; it cannot, for example, remember if a note in one `Voice` has already started when combining notes that have just started in the other `Voice`. This can lead to a number of unexpected issues including “Solo” or “Unison” marks being printed incorrectly.

`\partcombine` keeps all spanners (slurs, ties, hairpins etc.) in the same `Voice` so that if any such spanners start or end in a different `Voice`, they may not be printed properly or at all.

If the `\partcombine` function cannot combine both music expressions (i.e. when both voices have different durations), it will give the voices, internally, its own custom names: `one` and `two` respectively. This means if there is any “switch” to a differently named `Voice` context, the events in that differently named `Voice` will be ignored.

Refer also to *Known issues and warnings* when using `\partcombine` with tablature in [\[Default tablatures\]](#), page 303 and the *Note* in [\[Automatic beams\]](#), page 72 when using automatic beam-  
ing.

## Writing music in parallel


Music for multiple parts can be interleaved in input code. The function `\parallelMusic` accepts a list with the names of a number of variables to be created, and a musical expression. The content of alternate measures from the expression become the value of the respective variables, so you can use them afterwards to print the music.

**Note:** Bar checks | must be used, and the measures must be of the same length.

```
\parallelMusic #'(voiceA voiceB voiceC) {
  % Bar 1
  r8 g'16 c'' e'' g' c'' e'' r8 g'16 c'' e'' g' c'' e'' |
  r16 e'8.~ e'4 r16 e'8.~ e'4 |
  c'2 c'2 |

  % Bar 2
  r8 a'16 d'' f'' a' d'' f'' r8 a'16 d'' f'' a' d'' f'' |
  r16 d'8.~ d'4 r16 d'8.~ d'4 |
  c'2 c'2 |

}
\new StaffGroup <<
  \new Staff << \voiceA \\\voiceB >>
  \new Staff { \clef bass \voiceC }
>>
```




Relative mode may be used. Note that the `\relative` command is not used inside `\parallelMusic` itself. The notes are relative to the preceding note in the voice, not to the previous note in the input – in other words, relative notes for `voiceA` ignore the notes in `voiceB`.

```
\parallelMusic #'(voiceA voiceB voiceC) {
  % Bar 1
  r8 g16 c e g, c e r8 g,16 c e g, c e |
  r16 e8.~ e4          r16 e8.~ e4          |
  c2                  c                    |

  % Bar 2
  r8 a,16 d f a, d f r8 a,16 d f a, d f |
  r16 d8.~ d4          r16 d8.~ d4          |
  c2                  c                    |

}
\new StaffGroup <<
  \new Staff << \relative c' \voiceA \\\relative c' \voiceB >>
  \new Staff \relative c' { \clef bass \voiceC }
>>
```



This works quite well for piano music. This example maps four consecutive measures to four variables:

```
global = {
  \key g \major
  \time 2/4
}

\parallelMusic #'(voiceA voiceB voiceC voiceD) {
  % Bar 1
  a8    b    c    d    |
  d4          e    |
  c16 d e fis d e fis g |
  a4          a    |

  % Bar 2
  e8    fis g    a    |
  fis4          g    |
  e16 fis g a fis g a b |
  a4          a    |
```

```

% Bar 3 ...
}

\score {
  \new PianoStaff <<
    \new Staff {
      \global
      <<
        \relative c'' \voiceA
        \\
        \relative c' \voiceB
      >>
    }
    \new Staff {
      \global \clef bass
      <<
        \relative c \voiceC
        \\
        \relative c \voiceD
      >>
    }
  >>
}

```



## See also

Learning Manual: [Section “Organizing pieces with variables”](#) in *Learning Manual*.

Snippets: [Section “Simultaneous notes”](#) in *Snippets*.

## 1.6 Staff notation

This section explains how to influence the appearance of staves, how to print scores with more than one staff, and how to add tempo indications and cue notes to staves.

### 1.6.1 Displaying staves

This section describes the different methods of creating and grouping staves.

#### Instantiating new staves

*Staves* (singular: *staff*) are created with the `\new` or `\context` commands. For details, see [Section 5.1.2 \[Creating contexts\]](#), page 521.


The basic staff context is `Staff`:

```
\new Staff { c4 d e f }
```



The `DrumStaff` context creates a five-line staff set up for a typical drum set. Each instrument is shown with a different symbol. The instruments are entered in drum mode following a `\drummode` command, with each instrument specified by name. For details, see [\[Percussion staves\]](#), page 348.

```
\new DrumStaff {
  \drummode { cymc hh ss tomh }
}
```




`RhythmicStaff` creates a single-line staff that only displays the rhythmic values of the input. Real durations are preserved. For details, see [\[Showing melody rhythms\]](#), page 70.

```
\new RhythmicStaff { c4 d e f }
```



`TabStaff` creates a tablature with six strings in standard guitar tuning. For details, see [\[Default tablatures\]](#), page 303.

```
\new TabStaff { c4 d e f }
```



There are two staff contexts specific for the notation of ancient music: `MensuralStaff` and `VaticanaStaff`. They are described in [\[Pre-defined contexts\]](#), page 390.

The `GregorianTranscriptionStaff` context creates a staff to notate modern Gregorian chant. It does not show bar lines.

```
\new GregorianTranscriptionStaff { c4 d e f e d }
```



New single staff contexts may be defined. For details, see [Section 5.1.6 \[Defining new contexts\]](#), page 528.

## See also

Music Glossary: Section “staff” in *Music Glossary*, Section “staves” in *Music Glossary*.

Notation Reference: Section 5.1.2 [Creating contexts], page 521, [Percussion staves], page 348, [Showing melody rhythms], page 70, [Default tablatures], page 303, [Pre-defined contexts], page 390, [Staff symbol], page 169, [Gregorian chant contexts], page 399, [Mensural contexts], page 392, Section 5.1.6 [Defining new contexts], page 528.

Snippets: Section “Staff notation” in *Snippets*.


Internals Reference: Section “Staff” in *Internals Reference*, Section “DrumStaff” in *Internals Reference*, Section “GregorianTranscriptionStaff” in *Internals Reference*, Section “RhythmicStaff” in *Internals Reference*, Section “TabStaff” in *Internals Reference*, Section “MensuralStaff” in *Internals Reference*, Section “VaticanaStaff” in *Internals Reference*, Section “StaffSymbol” in *Internals Reference*.

## Grouping staves

Various contexts exist to group single staves together in order to form multi-stave systems. Each grouping context sets the style of the system start delimiter and the behavior of bar lines.


If no context is specified, the default properties will be used: the group is started with a vertical line, and the bar lines are not connected.

```
<<
  \new Staff { c1 c }
  \new Staff { c1 c }
>>
```




In the `StaffGroup` context, the group is started with a bracket and bar lines are drawn through all the staves.

```
\new StaffGroup <<
  \new Staff { c1 c }
  \new Staff { c1 c }
>>
```




In a `ChoirStaff`, the group starts with a bracket, but bar lines are not connected.

```
\new ChoirStaff <<
  \new Staff { c1 c }
  \new Staff { c1 c }
>>
```




In a `GrandStaff`, the group begins with a brace, and bar lines are connected between the staves.

```
\new GrandStaff <<
  \new Staff { c1 c }
  \new Staff { c1 c }
>>
```



The `PianoStaff` is identical to a `GrandStaff`, except that it supports printing the instrument name directly. For details, see [\[Instrument names\]](#), page 179.

```
\new PianoStaff <<
  \set PianoStaff.instrumentName = #"Piano"
  \new Staff { c1 c }
  \new Staff { c1 c }
>>
```



Each staff group context sets the property `systemStartDelimiter` to one of the following values: `SystemStartBar`, `SystemStartBrace`, or `SystemStartBracket`. A fourth delimiter, `SystemStartSquare`, is also available, but it must be explicitly specified.


New staff group contexts may be defined. For details, see [Section 5.1.6 \[Defining new contexts\]](#), page 528.

## Selected Snippets

*Use square bracket at the start of a staff group*

The system start delimiter `SystemStartSquare` can be used by setting it explicitly in a `StaffGroup` or `ChoirStaff` context.

```
\score {
  \new StaffGroup { <<
    \set StaffGroup.systemStartDelimiter = #'SystemStartSquare
    \new Staff { c'4 d' e' f' }
    \new Staff { c'4 d' e' f' }
  >> }
}
```




*Display bracket with only one staff in a system*

If there is only one staff in one of the staff types `ChoirStaff` or `StaffGroup`, the bracket and the starting bar line will not be displayed as standard behavior. This can be changed by overriding the relevant properties.

Note that in contexts such as `PianoStaff` and `GrandStaff` where the systems begin with a brace instead of a bracket, another property has to be set, as shown on the second system in the example.


```
\markup \left-column {
  \score {
    \new StaffGroup <<
      % Must be lower than the actual number of staff lines
      \override StaffGroup.SystemStartBracket #'collapse-height = #1
      \override Score.SystemStartBar #'collapse-height = #1
      \new Staff {
        c'1
      }
    >>
    \layout { }
  }
  \null
  \score {
    \new PianoStaff <<
      \override PianoStaff.SystemStartBrace #'collapse-height = #1
      \override Score.SystemStartBar #'collapse-height = #1
      \new Staff {
        c'1
      }
    >>
    \layout { }
  }
}
```



*Mensurstriche layout (bar lines between the staves)*

The mensurstriche-layout where the bar lines do not show on the staves but between staves can be achieved with a `StaffGroup` instead of a `ChoirStaff`. The bar line on staves is blanked out by setting the `transparent` property.

```
global = {
  \override Staff.BarLine #'transparent = ##t
  s1 s
  % the final bar line is not interrupted
  \revert Staff.BarLine #'transparent
  \bar "|."
}
\new StaffGroup \relative c'' {
  <<
    \new Staff { << \global { c1 c } >> }
    \new Staff { << \global { c c } >> }
  >>
}
```



## See also

Music Glossary: [Section “brace” in Music Glossary](#), [Section “bracket” in Music Glossary](#), [Section “grand staff” in Music Glossary](#).

Notation Reference: [\[Instrument names\]](#), page 179, [Section 5.1.6 \[Defining new contexts\]](#), page 528.

Snippets: [Section “Staff notation” in Snippets](#).

Internals Reference: [Section “Staff” in Internals Reference](#), [Section “StaffGroup” in Internals Reference](#), [Section “ChoirStaff” in Internals Reference](#), [Section “GrandStaff” in Internals Reference](#), [Section “PianoStaff” in Internals Reference](#), [Section “SystemStartBar” in Internals Reference](#), [Section “SystemStartBrace” in Internals Reference](#), [Section “SystemStartBracket” in Internals Reference](#), [Section “SystemStartSquare” in Internals Reference](#).

## Known issues and warnings

`PianoStaff` does not, by default, accept `ChordNames`.

## Nested staff groups

Staff-group contexts can be nested to arbitrary depths. In this case, each child context creates a new bracket adjacent to the bracket of its parent group.

```
\new StaffGroup <<
  \new Staff { c2 c | c2 c }
  \new StaffGroup <<
    \new Staff { g2 g | g2 g }
    \new StaffGroup \with {
      systemStartDelimiter = #'SystemStartSquare
```



```

    }
  <<
    \new Staff { e2 e | e2 e }
    \new Staff { c2 c | c2 c }
  >>
>>
>>

```



New nested staff group contexts can be defined. For details, see [Section 5.1.6 \[Defining new contexts\]](#), page 528.

## Selected Snippets

### *Nesting staves*


The property `systemStartDelimiterHierarchy` can be used to make more complex nested staff groups. The command `\set StaffGroup.systemStartDelimiterHierarchy` takes an alphabetical list of the number of staves produced. Before each staff a system start delimiter can be given. It has to be enclosed in brackets and takes as much staves as the brackets enclose. Elements in the list can be omitted, but the first bracket takes always the complete number of staves. The possibilities are `SystemStartBar`, `SystemStartBracket`, `SystemStartBrace`, and `SystemStartSquare`.

```

\new StaffGroup
\relative c'' <<
  \set StaffGroup.systemStartDelimiterHierarchy
    = #'(SystemStartSquare (SystemStartBrace (SystemStartBracket a
                                              (SystemStartSquare b) ) c ) d)

  \new Staff { c1 }
  \new Staff { c1 }
  \new Staff { c1 }
  \new Staff { c1 }
  \new Staff { c1 }
>>

```



## See also

Notation Reference: [Grouping staves], page 163, [Instrument names], page 179, Section 5.1.6 [Defining new contexts], page 528.

Snippets: Section “Staff notation” in *Snippets*.

Internals Reference: Section “StaffGroup” in *Internals Reference*, Section “ChoirStaff” in *Internals Reference*, Section “SystemStartBar” in *Internals Reference*, Section “SystemStartBrace” in *Internals Reference*, Section “SystemStartBracket” in *Internals Reference*, Section “SystemStartSquare” in *Internals Reference*.

## Separating systems


If the number of systems per page changes from page to page it is customary to separate the systems by placing a system separator mark between them. By default the system separator is blank, but can be turned on with a `\paper` option.

```
\book {
  \score {
    \new StaffGroup <<
      \new Staff {
        \relative c'' {
          c4 c c c
          \break
          c4 c c c
        }
      }
      \new Staff {
        \relative c'' {
          c4 c c c
          \break
          c4 c c c
        }
      }
    >>
  }
  \paper {
    system-separator-markup = \slashSeparator
    % following commands are needed only to format this documentation
```

```

    paper-width = 100\mm
    paper-height = 100\mm
    tagline = ##f
  }
}

```



## See also

Notation Reference: [Section 4.1 \[Page layout\]](#), page 469.

Snippets: [Section “Staff notation” in Snippets](#).

## 1.6.2 Modifying single staves

This section explains how to change specific attributes of one staff: for example, modifying the number of staff lines or the staff size. Methods to start and stop staves and set ossia sections are also described.

### Staff symbol

The `\stopStaff` and `\startStaff` commands can be used to stop or (re)start the staff lines respectively, from being printed at any point within a score.

```

\stopStaff f4 d \startStaff g, e
f'4 d \stopStaff g, e
f'4 d \startStaff g, e

```



## Predefined commands

`\startStaff`, `\stopStaff`.

The lines of a staff belong to the `StaffSymbol` grob (including ledger lines) can be modified using `StaffSymbol` properties, but these modifications must be made before the staff is (re)started.

The number of staff lines can be altered,

```
f4 d \stopStaff
\override Staff.StaffSymbol #'line-count = #2
\startStaff g, e |
```

```
f'4 d \stopStaff
\revert Staff.StaffSymbol #'line-count
\startStaff g, e |
```



The position of each the staff lines can also be altered. The values used are *half* staff line spaces and the new position is relative to the normal center line. A single staff line is printed for every value entered so that the number of staff lines, as well as their position in the staff, can be changed with a single override.

```
f4 d \stopStaff
\override Staff.StaffSymbol #'line-positions = #'(1 3 5 -1 -3)
\startStaff g, e |
f'4 d \stopStaff
\override Staff.StaffSymbol #'line-positions = #'(8 6.5 -6 -8 -0.5)
\startStaff g, e
```



The clef position and the position of middle C may need to be adjusted accordingly to fit the new lines. See [\[Clef\]](#), page 15.

Staff line thickness can be altered. Ledger lines and note stems, by default, are also affected.

```
\new Staff \with {
  \override StaffSymbol #'thickness = #3
}
{ f4 d g, e }
```




However, it is possible to set ledger line thickness independently of staff lines. The two values required multiply the staff line thickness with the staff line spacing and are then added together to give the ledger line thickness.

```
\new Staff \with {
  \override StaffSymbol #'thickness = #2
  \override StaffSymbol #'ledger-line-thickness = #'(0.5 . 0.4)
}
{ f'4 a, a,, f }
```



The vertical positions of ledger lines can be altered,

```
\new Staff \with {
  \override StaffSymbol #'ledger-positions = #'(-3 -2 -1 2 5 6)
}
{ f'4 a, a,, f }
```



Additional ledger lines can be made to appear above or below note heads depending on the current position relative to other note heads that also have their own ledger lines.

```
\new Staff \with {
  \override StaffSymbol #'ledger-extra = #4
}
{ f'4 a, d, f, }
```



Ledger lines can also be made to appear inside the staff where custom staff lines are required. The example shows the default position of ledger lines when the explicit `ledger-position` is and is not set. The `stopStaff` is needed in the example to revert the `\override` for the whole `StaffSymbol`.



The distance between staff lines can be altered. This affects ledger line spacing as well.

```
\new Staff \with {
  \override StaffSymbol #'staff-space = #1.5
}
{ f'4 d, g, e, }
```



## Selected Snippets

*Making some staff lines thicker than the others*

For pedagogical purposes, a staff line can be thickened (e.g., the middle line, or to emphasize the line of the G clef). This can be achieved by adding extra lines very close to the line that should be emphasized, using the `line-positions` property of the `StaffSymbol` object.

```
{
  \override Staff.StaffSymbol #'line-positions = #'(-4 -2 -0.2 0 0.2 2 4)
  d'4 e' f' g'
}
```



## See also

Music Glossary: [Section “line” in \*Music Glossary\*](#), [Section “ledger line” in \*Music Glossary\*](#), [Section “staff” in \*Music Glossary\*](#).

Notation Reference: [\[Clef\]](#), page 15.

Snippets: [Section “Staff notation” in \*Snippets\*](#).

Internals Reference: [Section “StaffSymbol” in \*Internals Reference\*](#), [Section “staff-symbol-interface” in \*Internals Reference\*](#).

## Ossia staves

Ossia staves can be set by creating a new simultaneous staff in the appropriate location:

```
\new Staff \relative c'' {
  c4 b d c
  <<
  { c4 b d c }
  \new Staff { e4 d f e }
  >>
  c4 b c2
}
```



However, the above example is not what is usually desired. To create ossia staves that are above the original staff, have no time signature or clef, and have a smaller font size, tweaks must be used. The Learning Manual describes a specific technique to achieve this goal, beginning with [Section “Nesting music expressions” in \*Learning Manual\*](#).

The following example uses the `alignAboveContext` property to align the ossia staff. This method is most appropriate when only a few ossia staves are needed.

```

\new Staff = main \relative c' {
  c4 b d c
  <<
    { c4 b d c }

    \new Staff \with {
      \remove "Time_signature_engraver"
      alignAboveContext = #"main"
      fontSize = #-3
      \override StaffSymbol #'staff-space = #(magstep -3)
      \override StaffSymbol #'thickness = #(magstep -3)
      firstClef = ##f
    }
    { e4 d f e }
  >>
  c4 b c2
}

```



If many isolated ossia staves are needed, creating an empty **Staff** context with a specific *context id* may be more appropriate; the ossia staves may then be created by *calling* this context and using `\startStaff` and `\stopStaff` at the desired locations. The benefits of this method are more apparent if the piece is longer than the following example.

```

<<
  \new Staff = ossia \with {
    \remove "Time_signature_engraver"
    \override Clef #'transparent = ##t
    fontSize = #-3
    \override StaffSymbol #'staff-space = #(magstep -3)
    \override StaffSymbol #'thickness = #(magstep -3)
  }
  { \stopStaff s1*6 }

  \new Staff \relative c' {
    c4 b c2
    <<
      { e4 f e2 }
      \context Staff = ossia {
        \startStaff e4 g8 f e2 \stopStaff
      }
    >>
    g4 a g2 \break
    c4 b c2
    <<
      { g4 a g2 }
      \context Staff = ossia {

```

```

        \startStaff g4 e8 f g2 \stopStaff
    }
    >>
    e4 d c2
}
>>

```



4



Using the `\Staff \RemoveEmptyStaves` command to create ossia staves may be used as an alternative. This method is most convenient when ossia staves occur immediately following a line break. For more information about `\Staff \RemoveEmptyStaves`, see [\[Hiding staves\]](#), page 176.

```

<<
  \new Staff = ossia \with {
    \remove "Time_signature_engraver"
    \override Clef #'transparent = ##t
    fontSize = #-3
    \override StaffSymbol #'staff-space = #(magstep -3)
    \override StaffSymbol #'thickness = #(magstep -3)
  } \relative c'' {
    R1*3
    c4 e8 d c2
  }
  \new Staff \relative c' {
    c4 b c2
    e4 f e2
    g4 a g2 \break
    c4 b c2
    g4 a g2
    e4 d c2
  }
>>

\layout {
  \context {
    \Staff \RemoveEmptyStaves
    \override VerticalAxisGroup #'remove-first = ##t
  }
}

```





## Selected Snippets

*Vertically aligning ossias and lyrics*

This snippet demonstrates the use of the context properties `alignBelowContext` and `alignAboveContext` to control the positioning of lyrics and ossias.

```
\paper {
  ragged-right = ##t
}

\relative c' <<
  \new Staff = "1" { c4 c s2 }
  \new Staff = "2" { c4 c s2 }
  \new Staff = "3" { c4 c s2 }
  { \skip 2
    <<
      \lyrics {
        \set alignBelowContext = #"1"
        lyrics4 below
      }
      \new Staff \with {
        alignAboveContext = #"3"
        fontSize = #-2
        \override StaffSymbol #'staff-space = #(magstep -2)
        \remove "Time_signature_engraver"
      } {
        \times 4/6 {
          \override TextScript #'padding = #3
          c8["ossia above" d e d e f]
        }
      }
    }
  }
  >>
}
>>
```



## See also

Music Glossary: [Section “ossia” in \*Music Glossary\*](#), [Section “staff” in \*Music Glossary\*](#), [Section “Frenched staff” in \*Music Glossary\*](#).

Learning Manual: [Section “Nesting music expressions” in \*Learning Manual\*](#), [Section “Size of objects” in \*Learning Manual\*](#), [Section “Length and thickness of objects” in \*Learning Manual\*](#).

Notation Reference: [\[Hiding staves\]](#), page 176.

Snippets: [Section “Staff notation” in \*Snippets\*](#).

Internals Reference: [Section “StaffSymbol” in \*Internals Reference\*](#).

## Hiding staves

Staff lines can be hidden by removing the `Staff_symbol_engraver` from the `Staff` context. As an alternative, `\stopStaff` may be used.

```
\new Staff \with {
  \remove "Staff_symbol_engraver"
}
\relative c''' { a8 f e16 d c b a2 }
```



Empty staves can be hidden by setting the `\Staff \RemoveEmptyStaves` command in the `\layout` block. In orchestral scores, this style is known as ‘Frenched Score’. By default, this command hides and removes all empty staves in a score except for those in the first system.

**Note:** A staff is considered empty when it contains only multi-measure rests, rests, skips, spacer rests, or a combination of these elements.


```
\layout {
  \context {
    \Staff \RemoveEmptyStaves
  }
}
```

```
\relative c' <<
  \new Staff {
    e4 f g a \break
    b1 \break
```

```

    a4 b c2
  }
  \new Staff {
    c,4 d e f \break
    R1 \break
    f4 g c,2
  }
>>

```



`\Staff \RemoveEmptyStaves` can also be used to create ossia sections for a staff. For details, see [\[Ossia staves\]](#), page 172.

The `\VaticanaStaff \RemoveEmptyStaves` command may be used to hide empty staves in ancient music contexts. Similarly, `\RhythmicStaff \RemoveEmptyStaves` may be used to hide empty `RhythmicStaff` contexts.

## Predefined commands

`\Staff \RemoveEmptyStaves`, `\VaticanaStaff \RemoveEmptyStaves`, `\RhythmicStaff \RemoveEmptyStaves`.

## Selected Snippets

### *Removing the first empty line*

The first empty staff can also be removed from the score by setting the `VerticalAxisGroup` property `remove-first`. This can be done globally inside the `\layout` block, or locally inside the specific staff that should be removed. In the latter case, you have to specify the context (`Staff` applies only to the current staff) in front of the property.

The lower staff of the second staff group is not removed, because the setting applies only to the specific staff inside of which it is written.

```





\layout {
  \context {
    \Staff \RemoveEmptyStaves
    % To use the setting globally, uncomment the following line:

```

```

    % \override VerticalAxisGroup #'remove-first = ##t
  }
}
\new StaffGroup <<
  \new Staff \relative c' {
    e4 f g a \break
    c1
  }
  \new Staff {
    % To use the setting globally, comment this line,
    % uncomment the line in the \layout block above
    \override Staff.VerticalAxisGroup #'remove-first = ##t
    R1 \break
    R
  }
}
>>
\new StaffGroup <<
  \new Staff \relative c' {
    e4 f g a \break
    c1
  }
  \new Staff {
    R1 \break
    R
  }
}
>>

```



## See also

Music Glossary: [Section “Frenched staff”](#) in *Music Glossary*.

Learning Manual: [Section “Visibility and color of objects”](#) in *Learning Manual*.

Notation Reference: [Section 5.1.5 \[Changing context default settings\]](#), page 526, [\[Staff symbol\]](#), page 169, [\[Ossia staves\]](#), page 172, [\[Hidden notes\]](#), page 194, [\[Invisible rests\]](#), page 51, [Section 5.4.6 \[Visibility of objects\]](#), page 550.

Snippets: [Section “Staff notation”](#) in *Snippets*.

Internals Reference: [Section “ChordNames”](#) in *Internals Reference*, [Section “FiguredBass”](#) in *Internals Reference*, [Section “Lyrics”](#) in *Internals Reference*, [Section “Staff”](#) in *Internals Reference*, [Section “VerticalAxisGroup”](#) in *Internals Reference*, [Section “Staff\\_symbol\\_engraver”](#) in *Internals Reference*.

## Known issues and warnings

Removing `Staff_symbol_engraver` also hides bar lines. If bar line visibility is forced, formatting errors may occur. In this case, use the following overrides instead of removing the engraver:

```
\override StaffSymbol #'stencil = ##f
\override NoteHead #'no-ledgers = ##t
```

For the Known issues and warnings associated with `\Staff \RemoveEmptyStaves` see [Section 5.1.5 \[Changing context default settings\]](#), page 526.

### 1.6.3 Writing parts

This section explains how to insert tempo indications and instrument names into a score. Methods to quote other voices and format cue notes are also described.

#### Instrument names

Instrument names can be printed on the left side of staves in the `Staff`, `PianoStaff`, `StaffGroup`, `GrandStaff` and `ChoirStaff` contexts. The value of `instrumentName` is used for the first staff, and the value of `shortInstrumentName` is used for all succeeding staves.

```
\new Staff \with {
  instrumentName = #"Violin "
  shortInstrumentName = #"Vln. "
}
{ c4.. g'16 c4.. g'16 \break | c1 }
```



`\markup` can be used to create more complex instrument names:

```
\new Staff \with {
  instrumentName = \markup {
    \column { "Clarinetti"
      \line { "in B" \smaller \flat }
    }
  }
}
```

```
}
{ c4 c,16 d e f g2 }
```



When two or more staff contexts are grouped together, the instrument names and short instrument names are centered by default. To center multi-line instrument names, `\center-column` must be used:

```
<<
  \new Staff \with {
    instrumentName = #"Flute"
  }
  { f2 g4 f }
  \new Staff \with {
    instrumentName = \markup {
      \center-column { "Clarinet" }
      \line { "in B" \smaller \flat }
    }
  }
  { c4 b c2 }
>>
```



However, if the instrument names are longer, the instrument names in a staff group may not be centered unless the `indent` and `short-indent` settings are increased. For details about these settings, see [\[\paper variables for shifts and indents\]](#), page 475.

```
\relative c'' {
  <<
    \new Staff \with {
      instrumentName = #"Alto Flute in G"
      shortInstrumentName = #"Flt."
    }
    {
      f2 g4 f \break
      g4 f g2
    }
    \new Staff \with {
      instrumentName = #"Clarinet"
      shortInstrumentName = #"Clar."
    }
    {
      c,4 b c2 \break
      c2 b4 c
    }
  >>
}
```

```

    }
  >>
}

\layout {
  indent = 3.0\cm
  short-indent = 1.5\cm
}


```

Alto Flute in G



Clarinet

Flt.



Clar.

To add instrument names to other contexts (such as `ChordNames` or `FiguredBass`), `Instrument_name_engraver` must be added to that context. For details, see [Section 5.1.4 \[Modifying context plug-ins\]](#), page 524.


The `shortInstrumentName` may be changed in the middle of a piece. However, only the first instance of `instrumentName` will be printed and subsequent changes will be ignored:

```


\new Staff \with {
  instrumentName = #"Flute"
  shortInstrumentName = #"Flt."
}
{
  c1 c c c \break
  c1 c c c \break
  \set Staff.instrumentName = #"Clarinet"
  \set Staff.shortInstrumentName = #"Clt."
  c1 c c c \break
  c1 c c c \break
}


```

Flute



Flt.





If an instrument *switch* is needed, `\addInstrumentDefinition` may be used in combination with `\instrumentSwitch` to create a detailed list of the necessary changes for the switch. The `\addInstrumentDefinition` command has two arguments: an identifying string, and an association list of context properties and values to be used for the instrument. It must be placed in the toplevel scope. `\instrumentSwitch` is used in the music expression to declare the instrument switch:

```
\addInstrumentDefinition #"contrabassoon"
  #`((instrumentTransposition . ,(ly:make-pitch -1 0 0))
    (shortInstrumentName . "Cbsn.")
    (clefGlyph . "clefs.F")
    (middleCPosition . 6)
    (clefPosition . 2)
    (instrumentCueName . ,(make-bold-markup "cbsn.))
    (midiInstrument . "bassoon"))

\new Staff \with {
  instrumentName = #"Bassoon"
}
\relative c' {
  \clef tenor
  \compressFullBarRests
  c2 g'
  R1*16
  \instrumentSwitch "contrabassoon"
  c,,2 g \break
  c,1 ~ | c1
}
```



## See also

Notation Reference: [\[\paper variables for shifts and indents\]](#), page 475, Section 5.1.4 [\[Modifying context plug-ins\]](#), page 524.

Snippets: [Section “Staff notation” in Snippets.](#)

Internals Reference: [Section “InstrumentName” in Internals Reference](#), [Section “PianoStaff” in Internals Reference](#), [Section “Staff” in Internals Reference.](#)



## Quoting other voices

It is very common for one voice to use the same notes as those from another voice. For example, first and second violins playing the same phrase during a particular passage of the music. This is done by letting one voice *quote* the other, without having to re-enter the music all over again for the second voice.

The `\addQuote` command, used in the top level scope, defines a stream of music from which fragments can be quoted.

The `\quoteDuring` command is used to indicate the point where the quotation begins. It is followed by two arguments: the name of the quoted voice, as defined with `\addQuote`, and a music expression for the duration of the quote.

```
fluteNotes = \relative c'' {
  a4 gis g gis | b4~"quoted" r8 ais\p a4( f)
}

oboeNotes = \relative c'' {
  c4 cis c b \quoteDuring #"flute" { s1 }
}

\addQuote "flute" { \fluteNotes }

\score {
  <<
    \new Staff \with { instrumentName = "Flute" } \fluteNotes
    \new Staff \with { instrumentName = "Oboe" } \oboeNotes
  >>
}
```



If the music expression used in `\quoteDuring` contains notes instead of spacer or multimeasure rests then the quote will appear as polyphony and may produce unexpected results.

```
fluteNotes = \relative c'' {
  a4 gis g gis | b4~"quoted" r8 ais\p a4( f)
}

oboeNotes = \relative c'' {
  c4 cis c b \quoteDuring #"flute" { e4 r8 ais b4 a }
}

\addQuote "flute" { \fluteNotes }

\score {
  <<
    \new Staff \with { instrumentName = "Flute" } \fluteNotes
```

```

    \new Staff \with { instrumentName = "Oboe" } \oboeNotes
  >>
}

```

The `\quoteDuring` command uses the `\transposition` settings of both quoted and quoting parts to produce notes for the quoting part that have the same sounding pitch as those in the quoted part.

```

clarinetNotes = \relative c'' {
  \transposition bes
  \key d \major
  b4 ais a ais | cis4~"quoted" r8 bis\p b4( f)
}

oboeNotes = \relative c'' {
  c4 cis c b \quoteDuring #"clarinet" { s1 }
}

\addQuote "clarinet" { \clarinetNotes }

\score {
  <<
    \new Staff \with { instrumentName = "Clarinet" } \clarinetNotes
    \new Staff \with { instrumentName = "Oboe" } \oboeNotes
  >>
}

```

By default quoted music will include all articulations, dynamics, markups, etc., in the quoted expression. It is possible to choose which of these objects from the quoted music are displayed by using the `quotedEventTypes` context property.

```

fluteNotes = \relative c'' {
  a2 g2 |
  b4\<~"quoted" r8 ais a4\f( c->)
}

```

```


}

oboeNotes = \relative c'' {
  c2. b4 |
  \quoteDuring #"flute" { s1 }
}

\addQuote "flute" { \fluteNotes }

\score {
  <<
    \set Score.quotedEventTypes = #'(note-event articulation-event
                                   crescendo-event rest-event
                                   slur-event dynamic-event)
    \new Staff \with { instrumentName = "Flute" } \fluteNotes
    \new Staff \with { instrumentName = "Oboe" } \oboeNotes
  >>
}

```



Quotes can also be tagged, see [\[Using tags\]](#), page 450.

## See also

Notation Reference: [\[Instrument transpositions\]](#), page 21, [\[Using tags\]](#), page 450.

Snippets: [Section “Staff notation” in \*Snippets\*](#).

Internals Reference: [Section “Music classes” in \*Internals Reference\*](#), [Section “QuoteMusic” in \*Internals Reference\*](#), [Section “Voice” in \*Internals Reference\*](#).

Installed Files: ‘`scm/define-event-classes.scm`’.

## Known issues and warnings

Only the contents of the first `Voice` occurring in an `\addQuote` command will be considered for quotation, so if the music expression contains `\new` or `\context Voice` statements, their contents will not be quoted. Quoting grace notes is unsupported and may cause LilyPond to crash whereas quoting nested triplets may result in poor notation.

## Formatting cue notes

The simplest way to format cue notes is to explicitly create a `CueVoice` context within the part.

R1

```

<<
{ e2\rest r4. e8 }
\new CueVoice {
  \stemUp d'8^"flute" c d e fis2
}

```

```

}
>>
d,,4 r a r

```



The `\cueClef` command can also be used with an explicit `CueVoice` context if a change of clef is required and will print an appropriately sized clef for the cue notes. The `\cueClefUnset` command can then be used to switch back to the original clef, again with an appropriately sized clef.

```

\clef "bass"
R1
<<
{ e2\rest r4. \cueClefUnset e,8 }
\new CueVoice {
  \cueClef "treble" \stemUp d''8~"flute" c d e fis2
}
>>
d,,4 r a r

```



The `\cueClef` and `\cueClefUnset` command can also be used without a `CueVoice` if required.

```

\clef "bass"
R1
\cueClef "treble"
d'8~"flute" c d e fis2
\cueClefUnset
d,,4 r a r

```



For more complex cue note placement, e.g including transposition, or inserting cue notes from multiple music sources the `\cueDuring` or `\cueDuringWithClef` commands can be used. These are more specialized form of `\quoteDuring`, see [\[Quoting other voices\]](#), page 183 in the previous section.

The syntax is:

```

\cueDuring #quotename #direction #music
and
\cueDuringWithClef #quotename #direction #clef #music

```


The music from the corresponding measures of the *quote name* is added as a `CueVoice` context and occurs simultaneously with the *music*, which then creates a polyphonic situation. The *direction* takes the argument UP or DOWN, and corresponds to the first and second voices respectively, determining how the cue notes are printed in relation to the other voice.

```
fluteNotes = \relative c'' {
  r2. c4 | d8 c d e fis2 | g2 d |
}
```

```
oboeNotes = \relative c'' {
  R1
  s1*0^\markup { \tiny "flute" }
  \cueDuring #"flute" #UP { R1 }
  g2 c,
}
```

```
\addQuote "flute" { \fluteNotes }
```

```
\new Staff {
  \oboeNotes
}
```



It is possible to adjust which aspects of the music are quoted with `\cueDuring` by setting the `quotedCueEventTypes` property. Its default value is `'(note-event rest-event tie-event beam-event tuplet-span-event)`, which means that only notes, rests, ties, beams and tuplets are quoted, but not articulations, dynamic marks, markup etc.

**Note:** When a `Voice` starts with `\cueDuring`, as in the following example, the `Voice` context must be explicitly declared, or else the entire music expression would belong to the `CueVoice` context.

```
oboeNotes = \relative c'' {
  r2 r8 d16(\f f e g f a)
  g8 g16 g g2.
}
\addQuote "oboe" { \oboeNotes }

\new Voice \relative c'' {
  \set Score.quotedCueEventTypes = #'(note-event rest-event tie-event
                                     beam-event tuplet-span-event
                                     dynamic-event slur-event)

  \cueDuring #"oboe" #UP { R1 }
  g2 c,
}
```



Markup can be used to show the name of the quoted instrument. Also, if the cue notes require a change in clef, this can be done manually but the original clef should also be restored manually at the end of the cue notes.

```


fluteNotes = \relative c'' {
  r2. c4 d8 c d e fis2 g2 d2
}

bassoonNotes = \relative c {
  \clef bass
  R1
  \clef treble
  s1*0^\markup { \tiny "flute" }
  \cueDuring #"flute" #UP { R1 }
  \clef bass
  g4. b8 d2
}

\addQuote "flute" { \fluteNotes }

\new Staff {
  \bassoonNotes
}

```



Alternatively, the `\cueDuringWithClef` function can be used instead. This command takes an extra argument to specify the change of clef that needs to be printed for the cue notes but will automatically print the original clef once the cue notes have finished.

```


fluteNotes = \relative c'' {
  r2. c4 d8 c d e fis2 g2 d2
}

bassoonNotes = \relative c {
  \clef bass
  R1
  s1*0^\markup { \tiny "flute" }
  \cueDuringWithClef #"flute" #UP #"treble" { R1 }
  g4. b8 d2
}

\addQuote "flute" { \fluteNotes }

\new Staff {
  \bassoonNotes
}

```



Like `\quoteDuring`, `\cueDuring` takes instrument transpositions into account. Cue notes are produced at the pitches that would be written for the instrument receiving the cue to produce the sounding pitches of the source instrument.

To transpose cue notes differently, use `\transposedCueDuring`. This command takes an extra argument to specify (in absolute mode) the printed pitch that you want to represent the sound of a concert middle C. This is useful for taking cues from an instrument in a completely different register.

```
piccoloNotes = \relative c''' {
  \clef "treble^8"
  R1
  c8 c c e g2
  c4 g g2
}

bassClarinetNotes = \relative c' {
  \key d \major
  \transposition bes,
  d4 r a r
  \transposedCueDuring #"piccolo" #UP d { R1 }
  d4 r a r
}

\addQuote "piccolo" { \piccoloNotes }

<<
  \new Staff \piccoloNotes
  \new Staff \bassClarinetNotes
>>
```



The `\killCues` command removes cue notes from a music expression, so the same music expression can be used to produce the instrument part with cues and the score. The `\killCues` command removes only the notes and events that were quoted by `\cueDuring`. Other markup associated with cues, such as clef changes and a label identifying the source instrument, can be tagged for selective inclusion in the score; see [\[Using tags\]](#), page 450.

```
fluteNotes = \relative c'' {
  r2. c4 d8 c d e fis2 g2 d2
}

bassoonNotes = \relative c {
  \clef bass
  R1
  \tag #'part {
    \clef treble
    s1*0^\markup { \tiny "flute" }
  }
  \cueDuring #"flute" #UP { R1 }
  \tag #'part \clef bass
```

```



    g4. b8 d2
  }

\addQuote "flute" { \fluteNotes }

\new Staff {
  \bassoonNotes
}

\new StaffGroup <<
  \new Staff {
    \fluteNotes
  }
  \new Staff {
    \removeWithTag #'part { \killCues { \bassoonNotes } }
  }
>>

```



Alternatively, Clef changes and instrument labels can be collected into an instrument definition for repeated use, using `\addInstrumentDefinition` described in [\[Instrument names\]](#), [page 179](#).

## See also

Notation Reference: [\[Quoting other voices\]](#), [page 183](#), [\[Instrument transpositions\]](#), [page 21](#), [\[Instrument names\]](#), [page 179](#), [\[Clef\]](#), [page 15](#), [\[Musical cues\]](#), [page 268](#), [\[Using tags\]](#), [page 450](#).

Snippets: [Section “Staff notation” in \*Snippets\*](#).


Internals Reference: [Section “CueVoice” in \*Internals Reference\*](#), [Section “Voice” in \*Internals Reference\*](#).

## Known issues and warnings

Collisions can occur with rests, when using `\cueDuring`, between `Voice` and `CueVoice` contexts. When using `\cueDuringWithClef` or `\transposedCueDuring` the extra argument required for each case must come after the quote and the direction.



## 1.7 Editorial annotations



This section discusses the various ways to change the appearance of notes and add analysis or educational emphasis.

### 1.7.1 Inside the staff

This section discusses how to add emphasis to elements that are inside the staff.

## Selecting notation font size

The font size of notation elements may be altered. It does not change the size of variable symbols, such as beams or slurs.

**Note:** For font sizes of text, see [Selecting font and font size], page 212.

```
\huge
c4.-> d8---3
\large
c4.-> d8---3
\normalsize
c4.-> d8---3
\small
c4.-> d8---3
\tiny
c4.-> d8---3
\teeny
c4.-> d8---3
```



Internally, this sets the `fontSize` property. This in turn causes the `font-size` property to be set in all layout objects. The value of `font-size` is a number indicating the size relative to the standard size for the current staff height. Each step up is an increase of approximately 12% of the font size. Six steps is exactly a factor of two. The Scheme function `magstep` converts a `font-size` number to a scaling factor. The `font-size` property can also be set directly, so that only certain layout objects are affected.

```
\set fontSize = #3
c4.-> d8---3
\override NoteHead #'font-size = #-4
c4.-> d8---3
\override Script #'font-size = #2
c4.-> d8---3
```

```
\override Stem #'font-size = #-5
c4.-> d8---3
```



Font size changes are achieved by scaling the design size that is closest to the desired size. The standard font size (for `font-size = #0`) depends on the standard staff height. For a 20pt staff, a 10pt font is selected.

The `font-size` property can only be set on layout objects that use fonts. These are the ones supporting the `font-interface` layout interface.

## Predefined commands

`\teeny`, `\tiny`, `\small`, `\normalsize`, `\large`, `\huge`.

## See also

Snippets: [Section “Editorial annotations” in \*Snippets\*](#).

Internals Reference: [Section “font-interface” in \*Internals Reference\*](#).

## Fingering instructions

Fingering instructions can be entered using `'note-digit'`:

```
c4-1 d-2 f-4 e-3
```



Markup texts may be used for finger changes.

```
c4-1 d-2 f-4 c^\markup { \finger "2 - 3" }
```



A thumb-script can be added (e.g. cello music) to indicate that a note should be played with the thumb.

```
<a_\thumb a'-3>2 <b_\thumb b'-3>
```



Fingerings for chords can also be added to individual notes by adding them after the pitches.

```
<c-1 e-2 g-3 b-5>2 <d-1 f-2 a-3 c-5>
```




Fingering instructions may be manually placed above or below the staff, see [Section 5.4.2 \[Direction and placement\]](#), page 543.

## Selected Snippets

### *Controlling the placement of chord fingerings*

The placement of fingering numbers can be controlled precisely. For fingering orientation to apply, you must use a chord construct `<>` even if it is a single note.


```
\relative c' {
  \set fingeringOrientations = #'(left)
  <c-1 e-3 a-5>4
  \set fingeringOrientations = #'(down)
  <c-1 e-3 a-5>4
  \set fingeringOrientations = #'(down right up)
  <c-1 e-3 a-5>4
  \set fingeringOrientations = #'(up)
  <c-1 e-3 a-5>4
  \set fingeringOrientations = #'(left)
  <c-1>2
  \set fingeringOrientations = #'(down)
  <e-3>2
}
```



### *Allowing fingerings to be printed inside the staff*

By default, vertically oriented fingerings are positioned outside the staff. However, this behavior can be canceled. Note: you must use a chord construct `<>`, even if it is only a single note.

```
\relative c' {
  <c-1 e-2 g-3 b-5>2
  \override Fingering #'staff-padding = #'()
  <c-1 e-2 g-3 b-5>4 <g'-0>
}
```



### *Avoiding collisions with chord fingerings*

Fingerings and string numbers applied to individual notes will automatically avoid beams and stems, but this is not true by default for fingerings and string numbers applied to the individual notes of chords. The following example shows how this default behavior can be overridden.

```

\relative c' {
  \set fingeringOrientations = #'(up)
  \set stringNumberOrientations = #'(up)
  \set strokeFingerOrientations = #'(up)

  % Default behavior
  r8
  <f c'-5>8
  <f c'\5>8
  <f c'-\rightHandFinger #2 >8

  % Corrected to avoid collisions
  r8
  \override Fingering #'add-stem-support = ##t
  <f c'-5>8
  \override StringNumber #'add-stem-support = ##t
  <f c'\5>8
  \override StrokeFinger #'add-stem-support = ##t
  <f c'-\rightHandFinger #2 >8
}

```



## See also

Notation Reference: [Section 5.4.2 \[Direction and placement\]](#), page 543.

Snippets: [Section “Editorial annotations” in \*Snippets\*](#).

Internals Reference: [Section “FingeringEvent” in \*Internals Reference\*](#), [Section “fingering-event” in \*Internals Reference\*](#), [Section “Fingering-engraver” in \*Internals Reference\*](#), [Section “New\\_fingering-engraver” in \*Internals Reference\*](#), [Section “Fingering” in \*Internals Reference\*](#).

## Known issues and warnings

By default, numbers greater than 9 are not supported using ‘*note-digit*’.


## Hidden notes

Hidden (or invisible or transparent) notes can be useful in preparing theory or composition exercises.

```

c4 d
\hideNotes
e4 f
\unHideNotes
g a
\hideNotes
b
\unHideNotes
c

```



Notation objects which are attached to invisible notes are still visible.

```
c4( d)
\hideNotes
e4(\p f)--
```



## Predefined commands

`\hideNotes`, `\unHideNotes`.

## See also

Learning Manual: [Section “Visibility and color of objects”](#) in *Learning Manual*.

Notation Reference: [\[Invisible rests\]](#), page 51, [Section 5.4.6 \[Visibility of objects\]](#), page 550, [\[Hiding staves\]](#), page 176.

Snippets: [Section “Editorial annotations”](#) in *Snippets*.

Internals Reference: [Section “Note\\_spacing\\_engraver”](#) in *Internals Reference*, [Section “NoteSpacing”](#) in *Internals Reference*.

## Coloring objects

Individual objects may be assigned colors. Valid color names are listed in the [Section A.6 \[List of colors\]](#), page 587.

```
\override NoteHead #'color = #red
c4 c
\override NoteHead #'color = #(x11-color 'LimeGreen)
d
\override Stem #'color = #blue
e
```



The full range of colors defined for X11 can be accessed by using the Scheme function `x11-color`. The function takes one argument; this can be a symbol in the form `'FooBar` or a string in the form `"FooBar"`. The first form is quicker to write and is more efficient. However, using the second form it is possible to access X11 colors by the multi-word form of its name.

If `x11-color` cannot make sense of the parameter then the color returned defaults to black.

```
\override Staff.StaffSymbol #'color = #(x11-color 'SlateBlue2)
\set Staff.instrumentName = \markup {
  \with-color #(x11-color 'navy) "Clarinet"
}
```

```
gis8 a
\override Beam #'color = #(x11-color "medium turquoise")
gis a
```

```
\override Accidental #'color = #(x11-color 'DarkRed)
gis a
\override NoteHead #'color = #(x11-color "LimeGreen")
gis a
% this is deliberate nonsense; note that the stems remain black
\override Stem #'color = #(x11-color 'Boggle)
b2 cis
```



Exact RGB colors can be specified using the Scheme function `rgb-color`.

```
\override Staff.StaffSymbol #'color = #(x11-color 'SlateBlue2)
\set Staff.instrumentName = \markup {
  \with-color #(x11-color 'navy) "Clarinet"
}
```

```
\override Stem #'color = #(rgb-color 0 0 0)
gis8 a
\override Stem #'color = #(rgb-color 1 1 1)
gis8 a
\override Stem #'color = #(rgb-color 0 0 0.5)
gis4 a
```



See also

Notation Reference: Section A.6 [List of colors], page 587, Section 5.3.4 [The tweak command], page 538.

Snippets: Section “Editorial annotations” in *Snippets*.

## Known issues and warnings

An X11 color is not necessarily exactly the same shade as a similarly named normal color.

Not all X11 colors are distinguishable in a web browser, i.e., a web browser might not display a difference between `LimeGreen` and `ForestGreen`. For web use normal colors are recommended (i.e., `blue`, `green`, `red`).

Notes in a chord cannot be colored with `\override`; use `\tweak` instead, see [Section 5.3.4 \[The tweak command\]](#), page 538.

## Parentheses

Objects may be parenthesized by prefixing `\parenthesize` to the music event. When prefixed to a chord, it parenthesizes every note. Individual notes inside a chord may also be parenthesized.

```
c2 \parenthesize d
c2 \parenthesize <c e g>
c2 <c \parenthesize e g>
```



Non-note objects may be parenthesized as well. For articulations, a hyphen is needed before the `\parenthesize` command.

```
c2-\parenthesize -. d
c2 \parenthesize r
```



## See also

Snippets: [Section “Editorial annotations” in \*Snippets\*](#).

Internals Reference: [Section “Parenthesis\\_engraver” in \*Internals Reference\*](#), [Section “ParenthesesItem” in \*Internals Reference\*](#), [Section “parentheses-interface” in \*Internals Reference\*](#).

## Known issues and warnings

Parenthesizing a chord prints parentheses around each individual note, instead of a single large parenthesis around the entire chord.

## Stems

Whenever a note is found, a `Stem` object is created automatically. For whole notes and rests, they are also created but made invisible.

Stems may be manually placed to point up or down; see [Section 5.4.2 \[Direction and placement\]](#), page 543.

## Predefined commands

```
\stemUp, \stemDown, \stemNeutral.
```

## Selected Snippets

*Default direction of stems on the center line of the staff*

The default direction of stems on the center line of the staff is set by the `Stem` property `neutral-direction`.

```
\relative c' {
  a4 b c b
  \override Stem #'neutral-direction = #up
  a4 b c b
  \override Stem #'neutral-direction = #down
  a4 b c b
}
```



## See also

Notation Reference: [Section 5.4.2 \[Direction and placement\]](#), page 543.

Snippets: [Section “Editorial annotations” in \*Snippets\*](#).

Internals Reference: [Section “Stem\\_engraver” in \*Internals Reference\*](#), [Section “Stem” in \*Internals Reference\*](#), [Section “stem-interface” in \*Internals Reference\*](#).

### 1.7.2 Outside the staff

This section discusses how to add emphasis to elements in the staff from outside of the staff.

#### Balloon help

Elements of notation can be marked and named with the help of a square balloon. The primary purpose of this feature is to explain notation.


```
\new Voice \with { \consists "Balloon_engraver" }
{
  \balloonGrobText #'Stem #'(3 . 4) \markup { "I'm a Stem" }
  a8
  \balloonGrobText #'Rest #'(-4 . -4) \markup { "I'm a rest" }
  r
  <c, g'-\balloonText #'(-2 . -2) \markup { "I'm a note head" } c>2.
}
```



There are two music functions, `balloonGrobText` and `balloonText`; the former is used like `\once \override` to attach text to any grob, and the latter is used like `\tweak`, typically within chords, to attach text to an individual note.

Balloon text normally influences note spacing, but this can be altered:

```
\new Voice \with { \consists "Balloon_engraver" }
{
  \balloonLengthOff
  \balloonGrobText #'Stem #'(3 . 4) \markup { "I'm a Stem" }
  a8
  \balloonGrobText #'Rest #'(-4 . -4) \markup { "I'm a rest" }
  r
  \balloonLengthOn
  <c, g'-\balloonText #'(-2 . -2) \markup { "I'm a note head" } c>2.
}
```



#### Predefined commands

`\balloonLengthOn`, `\balloonLengthOff`.

#### See also

Snippets: [Section “Editorial annotations” in \*Snippets\*](#).

Internals Reference: [Section “Balloon\\_engraver” in \*Internals Reference\*](#), [Section “Balloon-TextItem” in \*Internals Reference\*](#), [Section “balloon-interface” in \*Internals Reference\*](#).



## Grid lines

Vertical lines can be drawn between staves synchronized with the notes.

The `Grid_point_engraver` must be used to create the end points of the lines, while the `Grid_line_span_engraver` must be used to actually draw the lines. By default this centers grid lines horizontally below and to the left side of each note head. Grid lines extend from the middle lines of each staff. The `gridInterval` must specify the duration between the grid lines.

```
\layout {
  \context {
    \Staff
    \consists "Grid_point_engraver"
    gridInterval = #(ly:make-moment 1 4)
  }
  \context {
    \Score
    \consists "Grid_line_span_engraver"
  }
}

\score {
  \new ChoirStaff <<
    \new Staff \relative c'' {
      \stemUp
      c4. d8 e8 f g4
    }
    \new Staff \relative c {
      \clef bass
      \stemDown
      c4 g' f e
    }
  >>
}
```



## Selected Snippets

*Grid lines: changing their appearance*

The appearance of grid lines can be changed by overriding some of their properties.

```
\score {
  \new ChoirStaff <<
    \new Staff {
      \relative c'' {
        \stemUp
        c'4. d8 e8 f g4
      }
    }
  >>
}
```

```

}
\new Staff {
  \relative c {
    % this moves them up one staff space from the default position
    \override Score.GridLine #'extra-offset = #'(0.0 . 1.0)
    \stemDown
    \clef bass
    \once \override Score.GridLine #'thickness = #5.0
    c4
    \once \override Score.GridLine #'thickness = #1.0
    g'4
    \once \override Score.GridLine #'thickness = #3.0
    f4
    \once \override Score.GridLine #'thickness = #5.0
    e4
  }
}
>>
\layout {
  \context {
    \Staff
    % set up grids
    \consists "Grid_point_engraver"
    % set the grid interval to one quarter note
    gridInterval = #(ly:make-moment 1 4)
  }
  \context {
    \Score
    \consists "Grid_line_span_engraver"
    % this moves them to the right half a staff space
    \override NoteColumn #'X-offset = #-0.5
  }
}
}

```



## See also

Snippets: [Section “Editorial annotations” in \*Snippets\*](#).

Internals Reference: [Section “Grid\\_line\\_span\\_engraver” in \*Internals Reference\*](#), [Section “Grid\\_point\\_engraver” in \*Internals Reference\*](#), [Section “GridLine” in \*Internals Reference\*](#), [Section “GridPoint” in \*Internals Reference\*](#), [Section “grid-line-interface” in \*Internals Reference\*](#), [Section “grid-point-interface” in \*Internals Reference\*](#).

## Analysis brackets

Brackets are used in musical analysis to indicate structure in musical pieces. Simple horizontal brackets are supported.

```
\layout {
  \context {
    \Voice
    \consists "Horizontal_bracket_engraver"
  }
}
\relative c'' {
  c2\startGroup
  d\stopGroup
}
```



Analysis brackets may be nested.

```
\layout {
  \context {
    \Voice
    \consists "Horizontal_bracket_engraver"
  }
}
\relative c'' {
  c4\startGroup\startGroup
  d4\stopGroup
  e4\startGroup
  d4\stopGroup\stopGroup
}
```



## See also

Snippets: [Section “Editorial annotations” in \*Snippets\*](#).

Internals Reference: [Section “Horizontal\\_bracket\\_engraver” in \*Internals Reference\*](#), [Section “HorizontalBracket” in \*Internals Reference\*](#), [Section “horizontal-bracket-interface” in \*Internals Reference\*](#), [Section “Staff” in \*Internals Reference\*](#).

## 1.8 Text

This section explains how to include text (with various formatting) in music scores.

Some text elements that are not dealt with here are discussed in other specific sections: [Section 2.1 \[Vocal music\]](#), page 226, [Section 3.2 \[Titles and headers\]](#), page 428.

### 1.8.1 Writing text

This section introduces different ways of adding text to a score.

**Note:** To write accented and special text (such as characters from other languages), simply insert the characters directly into the LilyPond file. The file must be saved as UTF-8. For more information, see [\[Text encoding\]](#), page 453.

### Text scripts

Simple “quoted text” indications may be added to a score, as demonstrated in the following example. Such indications may be manually placed above or below the staff, using the syntax described in [Section 5.4.2 \[Direction and placement\]](#), page 543.

```
a8~"pizz." g f e a4-"scherz." f
```

This syntax is actually a shorthand; more complex text formatting may be added to a note by explicitly using a `\markup` block, as described in [Section 1.8.2 \[Formatting text\]](#), page 210.

```
a8~\markup { \italic pizz. } g f e
a4_\markup { \tiny scherz. \bold molto } f
```

By default, text indications do not influence the note spacing. However, their widths can be taken into account: in the following example, the first text string does not affect spacing, whereas the second one does.

```
a8~"pizz." g f e
\textLengthOn
a4_"scherzando" f
```



In addition to text scripts, articulations can be attached to notes. For more information, see [\[Articulations and ornamentations\]](#), page 105.

For more information about the relative ordering of text scripts and articulations, see [Section “Placement of objects”](#) in *Learning Manual*.

## Predefined commands

```
\textLengthOn, \textLengthOff.
```

## See also

Learning Manual: [Section “Placement of objects”](#) in *Learning Manual*.

Notation Reference: [Section 1.8.2 \[Formatting text\]](#), page 210, [Section 5.4.2 \[Direction and placement\]](#), page 543, [\[Articulations and ornamentations\]](#), page 105.

Snippets: [Section “Text”](#) in *Snippets*.

Internals Reference: [Section “TextScript”](#) in *Internals Reference*.

## Known issues and warnings


Checking to make sure that text scripts and lyrics are within the margins requires additional calculations. In cases where slightly faster performance is desired, use

```
\override Score.PaperColumn #'keep-inside-line = ##f
```

## Text spanners

Some performance indications, e.g., *rallentando* or *accelerando*, are written as text and are extended over multiple notes with dotted lines. Such objects, called “spanners”, may be created from one note to another using the following syntax:


```
\override TextSpanner #'(bound-details left text) = "rit."
b1\startTextSpan
e,\stopTextSpan
```



The string to be printed is set through object properties. By default it is printed in italic characters, but different formatting can be obtained using `\markup` blocks, as described in [Section 1.8.2 \[Formatting text\]](#), page 210.

```
\override TextSpanner #'(bound-details left text) =
  \markup { \upright "rit." }
b1\startTextSpan c
```

e,\stopTextSpan



The line style, as well as the text string, can be defined as an object property. This syntax is described in [Section 5.4.7 \[Line styles\]](#), page 554.

## Predefined commands

\textSpannerUp, \textSpannerDown, \textSpannerNeutral.

## Known issues and warnings

LilyPond is only able to handle one text spanner per voice.

## Selected Snippets

### *Dynamics text spanner postfix*

Custom text spanners can be defined and used with hairpin and text crescendos. \< and \> produce hairpins by default, \cresc etc. produce text spanners by default.

% Some sample text dynamic spanners, to be used as postfix operators

```
crpoco =
#(make-music 'CrescendoEvent
  'span-direction START
  'span-type 'text
  'span-text "cresc. poco a poco")
```

```
\relative c' {
  c4\cresc d4 e4 f4 |
  g4 a4\! b4\crpoco c4 |
  c4 d4 e4 f4 |
  g4 a4\! b4\< c4 |
  g4\dim a4 b4\decreasc c4\!
}
```



### *Dynamics custom text spanner postfix*

Postfix functions for custom crescendo text spanners. The spanners should start on the first note of the measure. One has to use -\mycresc, otherwise the spanner start will rather be assigned to the next note.

% Two functions for (de)crescendo spanners where you can explicitly give the  
% spanner text.


```
mycresc =
#(define-music-function (parser location mymarkup) (markup?)
  (make-music 'CrescendoEvent
    'span-direction START
    'span-type 'text
```

```

        'span-text mymarkup))
mydecresc =
#(define-music-function (parser location mymarkup) (markup?)
  (make-music 'DecrescendoEvent
    'span-direction START
    'span-type 'text
    'span-text mymarkup))

\relative c' {
  c4-\mycresc "custom cresc" c4 c4 c4 |
  c4 c4 c4 c4 |
  c4-\mydecresc "custom decresc" c4 c4 c4 |
  c4 c4\! c4 c4
}

```



## See also

Notation Reference: [Section 5.4.7 \[Line styles\]](#), page 554, [\[Dynamics\]](#), page 107, [Section 1.8.2 \[Formatting text\]](#), page 210.

Snippets: [Section “Text” in \*Snippets\*](#), [Section “Expressive marks” in \*Snippets\*](#).

Internals Reference: [Section “TextSpanner” in \*Internals Reference\*](#).

## Text marks

Various text elements may be added to a score using the syntax described in [\[Rehearsal marks\]](#), [page 95](#):

```

c4
\mark "Allegro"
c c c

```



This syntax makes it possible to put any text on a bar line; more complex text formatting may be added using a `\markup` block, as described in [Section 1.8.2 \[Formatting text\]](#), page 210:

```

<c e>1
\mark \markup { \italic { colla parte } }
<d f>2 <e g>
<c f aes>1

```



This syntax also allows to print special signs, like coda, segno or fermata, by specifying the appropriate symbol name as explained in [\[Music notation inside markup\]](#), page 220:

```
<bes f>2 <aes d>
\mark \markup { \musicglyph #"scripts.ufermata" }
<e g>1
```



Such objects are only typeset above the top staff of the score; depending on whether they are specified at the end or the middle of a bar, they can be placed above the bar line or between notes. When specified at a line break, the mark will be printed at the beginning of the next line.

```
\mark "Allegro"
c1 c
\mark "assai" \break
c c
```

**Allegro**



**assai**



## Selected Snippets

*Printing marks at the end of a line*

Marks can be printed at the end of the current line, instead of the beginning of the following line. In such cases, it might be preferable to align the right end of the mark with the bar line.

```
\relative c' ' {
  g2 c
  d,2 a'
  \once \override Score.RehearsalMark #'break-visibility = #end-of-line-visible
  \once \override Score.RehearsalMark #'self-alignment-X = #RIGHT
  \mark "D.C. al Fine"
  \break
  g2 b,
  c1 \bar "||"
}
```







### *Aligning marks with various notation objects*

If specified, text marks may be aligned with notation objects other than bar lines. These objects include `ambitus`, `breathing-sign`, `clef`, `custos`, `staff-bar`, `left-edge`, `key-cancellation`, `key-signature`, and `time-signature`.

In such cases, text marks will be horizontally centered above the object. However this can be changed, as demonstrated on the second line of this example (in a score with multiple staves, this setting should be done for all the staves).

```
\relative c' {
  e1

  % the RehearsalMark will be centered above the Clef
  \override Score.RehearsalMark #'break-align-symbols = #'(clef)
  \key a \major
  \clef treble
  \mark ""
  e1

  % the RehearsalMark will be centered above the TimeSignature
  \override Score.RehearsalMark #'break-align-symbols = #'(time-signature)
  \key a \major
  \clef treble
  \time 3/4
  \mark \markup { \char ##x2193 }
  e2.

  % the RehearsalMark will be centered above the KeySignature
  \override Score.RehearsalMark #'break-align-symbols = #'(key-signature)
  \key a \major
  \clef treble
  \time 4/4
  \mark \markup { \char ##x2193 }
  e1

  \break
  e1

  % the RehearsalMark will be aligned with the left edge of the KeySignature
  \once \override Score.KeySignature #'break-align-anchor-alignment = #LEFT
  \mark \markup { \char ##x2193 }
  \key a \major
  e1


  % the RehearsalMark will be aligned with the right edge of the KeySignature
  \once \override Score.KeySignature #'break-align-anchor-alignment = #RIGHT
  \key a \major
  \mark \markup { \char ##x2193 }
  e1

  % the RehearsalMark will be aligned with the left edge of the KeySignature
  % and then shifted right by one unit.
```

```

\once \override Score.KeySignature #'break-align-anchor = #1
\key a \major
\mark \markup { \char ##x2193 }
e1
}

```




*Printing marks on every staff*

Although text marks are normally only printed above the topmost staff, they may also be printed on every staff.

```

\score {
  <<
    \new Staff { c''1 \mark "molto" c'' }
    \new Staff { c'1 \mark "molto" c' }
  >>
  \layout {
    \context {
      \Score
      \remove "Mark_engraver"
      \remove "Staff_collecting_engraver"
    }
    \context {
      \Staff
      \consists "Mark_engraver"
      \consists "Staff_collecting_engraver"
    }
  }
}

```



## See also

Notation Reference: [Rehearsal marks], page 95, Section 1.8.2 [Formatting text], page 210, [Music notation inside markup], page 220, Section A.7 [The Feta font], page 589.

Snippets: Section “Text” in *Snippets*.

Internals Reference: [Section “MarkEvent” in \*Internals Reference\*](#), [Section “Mark\\_engraver” in \*Internals Reference\*](#), [Section “RehearsalMark” in \*Internals Reference\*](#).

## Separate text

A `\markup` block can exist by itself, outside of any `\score` block, as a “top-level expression”. This syntax is described in [Section 3.1.5 \[File structure\]](#), [page 426](#).

```
\markup {
  Tomorrow, and tomorrow, and tomorrow...
}
```

Tomorrow, and tomorrow, and tomorrow...

This allows printing text separately from the music, which is particularly useful when the input file contains several music pieces, as described in [Section 3.1.2 \[Multiple scores in a book\]](#), [page 423](#).

```
\score {
  c'1
}
\markup {
  Tomorrow, and tomorrow, and tomorrow...
}
\score {
  c'1
}
```



Tomorrow, and tomorrow, and tomorrow...



Separate text blocks can be spread over multiple pages, making it possible to print text documents or books entirely within LilyPond. This feature, and the specific syntax it requires, are described in [\[Multi-page markup\]](#), [page 222](#).

## Predefined commands

`\markup`, `\markuplist`.

## Selected Snippets

*Stand-alone two-column markup*

Stand-alone text may be arranged in several columns using `\markup` commands:

```
\markup {
  \fill-line {
    \hspace #1
    \column {
      \line { 0 sacrum convivium }
```

```

\line { in quo Christus sumitur, }
\line { recolitur memoria passionis ejus, }
\line { mens impletur gratia, }
\line { futurae gloriae nobis pignus datur. }
\line { Amen. }
}
\hspace #2
\column {
\line { \italic { O sacred feast } }
\line { \italic { in which Christ is received, } }
\line { \italic { the memory of His Passion is renewed, } }
\line { \italic { the mind is filled with grace, } }
\line { \italic { and a pledge of future glory is given to us. } }
\line { \italic { Amen. } }
}
\hspace #1
}
}

```

O sacrum convivium	<i>O sacred feast</i>
in quo Christus sumitur,	<i>in which Christ is received,</i>
recolitur memoria passionis ejus,	<i>the memory of His Passion is renewed,</i>
mens impletur gratia,	<i>the mind is filled with grace,</i>
futurae gloriae nobis pignus datur.	<i>and a pledge of future glory is given to us.</i>
Amen.	<i>Amen.</i>

## See also

Notation Reference: [Section 1.8.2 \[Formatting text\]](#), page 210, [Section 3.1.5 \[File structure\]](#), page 426, [Section 3.1.2 \[Multiple scores in a book\]](#), page 423, [\[Multi-page markup\]](#), page 222.

Snippets: [Section “Text” in Snippets](#).

Internals Reference: [Section “TextScript” in Internals Reference](#).

## 1.8.2 Formatting text

This section presents basic and advanced text formatting, using the `\markup` mode specific syntax.

### Text markup introduction

A `\markup` block is used to typeset text with an extensible syntax called “markup mode”.

The markup syntax is similar to LilyPond’s usual syntax: a `\markup` expression is enclosed in curly braces `{...}`. A single word is regarded as a minimal expression, and therefore does not need to be enclosed with braces.

Unlike simple “quoted text” indications, `\markup` blocks may contain nested expressions or markup commands, entered using the backslash `\` character. Such commands only affect the first following expression.

```

a1-\markup intenso
a2^\markup { poco \italic più forte }
c e1
d2_\markup { \italic "string. assai" }
e


```

```
b1^\markup { \bold { molto \italic agitato } }
c
```




A `\markup` block may also contain quoted text strings. Such strings are treated as minimal text expressions, and therefore any markup command or special character (such as `\` and `#`) will be printed verbatim without affecting the formatting of the text. Double quotation marks themselves may be printed by preceding them with backslashes.

```
a1^\italic markup..."
a_\markup { \italic "... prints \"italic\" letters!" }
a a
```



To be treated as a distinct expression, a list of words needs to be enclosed with double quotes or preceded by a command. The way markup expressions are defined affects how these expressions will be stacked, centered and aligned; in the following example, the second `\markup` expression is treated the same as the first one:

```
c1^\markup { \center-column { a bbb c } }
c1^\markup { \center-column { a { bbb c } } }
c1^\markup { \center-column { a \line { bbb c } } }
c1^\markup { \center-column { a "bbb c" } }
```



Markups can be stored in variables. Such variables may be directly attached to notes:

```
allegro = \markup { \bold \large Allegro }
```

```
{
d''8.^allegro
d'16 d'4 r2
}
```



An exhaustive list of `\markup`-specific commands can be found in [Section A.9 \[Text markup commands\]](#), page 609.

## See also

Notation Reference: [Section A.9 \[Text markup commands\]](#), page 609.

Snippets: [Section “Text” in \*Snippets\*](#).

Installed Files: ‘scm/markup.scm’.

## Known issues and warnings

Syntax errors for markup mode can be confusing.

## Selecting font and font size

Basic font switching is supported in markup mode:

```
d1^\markup {
  \bold { Più mosso }
  \italic { non troppo \underline Vivo }
}
r2 r4 r8
d,_\markup { \italic quasi \smallCaps Tromba }
f1 d2 r
```



The size of the characters can also be altered in different ways:

- the font size can be set to predefined standard sizes,
- the font size can be set to an absolute value,
- the font size can also be changed relatively to its previous value.

The following example demonstrates these three methods:

```
f1_\markup {
  \tiny espressivo
  \large e
  \normalsize intenso
}
a^\markup {
  \fontsize #5 Sinfonia
  \fontsize #2 da
  \fontsize #3 camera
}
bes^\markup { (con
  \larger grande
  \smaller emozione
  \magnify #0.6 { e sentimento } )
}
d c2 r8 c bes a g1
```



Text may be printed as subscript or superscript. By default these are printed in a smaller size, but a normal size can be used as well:

```
\markup {
  \column {
    \line { 1 \super st movement }
    \line { 1 \normal-size-super st movement }
    \sub { (part two) } }
}
```

1<sup>st</sup> movement  
1<sup>st</sup> movement  
(part two)

The markup mode provides an easy way to select alternate font families. The default serif font, of roman type, is automatically selected unless specified otherwise; on the last line of the following example, there is no difference between the first and the second word.

```
\markup {
  \column {
    \line { Act \number 1 }
    \line { \sans { Scene I. } }
    \line { \typewriter { Verona. An open place. } }
    \line { Enter \roman Valentine and Proteus. }
  }
}
```

Act **1**  
Scene I.  
Verona. An open place.  
Enter Valentine and Proteus.

Some of these font families, used for specific items such as numbers or dynamics, do not provide all characters, as mentioned in [\[New dynamic marks\]](#), page 112 and [\[Manual repeat marks\]](#), page 133.

When used inside a word, some font-switching or formatting commands may produce an unwanted blank space. This can easily be solved by concatenating the text elements together:

```
\markup {
  \column {
    \line {
      \concat { 1 \super st }
      movement
    }
    \line {
      \concat { \dynamic p , }
      \italic { con dolce espressione }
    }
  }
}
```

1<sup>st</sup> movement  
***p***, con dolce espressione

An exhaustive list of font switching commands and custom font usage commands can be found in [Section A.9.1 \[Font\]](#), page 609.

Defining custom font sets is also possible, as explained in [Section 1.8.3 \[Fonts\]](#), page 223.

## Predefined commands

`\teeny`, `\tiny`, `\small`, `\normalsize`, `\large`, `\huge`, `\smaller`, `\larger`.

## See also

Notation Reference: [Section A.9.1 \[Font\]](#), page 609, [\[New dynamic marks\]](#), page 112, [\[Manual repeat marks\]](#), page 133, [Section 1.8.3 \[Fonts\]](#), page 223.

Snippets: [Section “Text” in \*Snippets\*](#).

Internals Reference: [Section “TextScript” in \*Internals Reference\*](#).

Installed Files: ‘`scm/define-markup-commands.scm`’.

## Known issues and warnings

Using the font sizing commands `\teeny`, `\tiny`, `\small`, `\normalsize`, `\large`, and `\huge` will lead to inconsistent line spacing compared to using `\fontsize`.

## Text alignment

This subsection discusses how to place text in markup mode. Markup objects can also be moved as a whole, using the syntax described in [Section “Moving objects” in \*Learning Manual\*](#).


Markup objects may be aligned in different ways. By default, a text indication is aligned on its left edge: in the following example, there is no difference between the first and the second markup.

```
d1-\markup { poco }
f
d-\markup { \left-align poco }
f
d-\markup { \center-align { poco } }
f
d-\markup { \right-align poco }
```



Horizontal alignment may be fine-tuned using a numeric value:

```
a1-\markup { \halign #-1 poco }
e'
a,-\markup { \halign #0 poco }
e'
a,-\markup { \halign #0.5 poco }
e'
a,-\markup { \halign #2 poco }
```





Some objects may have alignment procedures of their own, and therefore are not affected by these commands. It is possible to move such markup objects as a whole, as shown for instance in [Text marks], page 205.

Vertical alignment is a bit more complex. As stated above, markup objects can be moved as a whole; however, it is also possible to move specific elements inside a markup block. In this case, the element to be moved needs to be preceded with an *anchor point*, that can be another markup element or an invisible object. The following example demonstrates these two possibilities; the last markup in this example has no anchor point, and therefore is not moved.

```
d2^\markup {
  Acte I
  \raise #2 { Scène 1 }
}
a'
g_\markup {
  \null
  \lower #4 \bold { Très modéré }
}
a
d,^\markup {
  \raise #4 \italic { Une forêt. }
}
a'4 a g2 a
```



**Très modéré**

Some commands can affect both the horizontal and vertical alignment of text objects in markup mode. Any object affected by these commands must be preceded with an anchor point:

```
d2^\markup {
  Acte I
  \translate #'(-1 . 2) "Scène 1"
}
a'
g_\markup {
  \null
  \general-align #Y #3.2 \bold "Très modéré"
}
a
d,^\markup {
  \null
  \translate-scaled #'(-1 . 2) \teeny "Une forêt."
}
a'4 a g2 a
```

**Très modéré**

A markup object may include several lines of text. In the following example, each element or expression is placed on its own line, either left-aligned or centered:

```
\markup {
  \column {
    a
    "b c"
    \line { d e f }
  }
  \hspace #10
  \center-column {
    a
    "b c"
    \line { d e f }
  }
}
```

a	a
b c	b c
d e f	d e f

Similarly, a list of elements or expressions may be spread to fill the entire horizontal line width (if there is only one element, it will be centered on the page). These expressions can, in turn, include multi-line text or any other markup expression:

```
\markup {
  \fill-line {
    \line { William S. Gilbert }
    \center-column {
      \huge \smallCaps "The Mikado"
      or
      \smallCaps "The Town of Titipu"
    }
    \line { Sir Arthur Sullivan }
  }
}
\markup {
  \fill-line { 1885 }
}
```

William S. Gilbert

**THE MIKADO**  
or  
**THE TOWN OF TITIPU**

Sir Arthur Sullivan

1885

Long text indications can also be automatically wrapped accordingly to the given line width. These will be either left-aligned or justified, as shown in the following example.

```

\markup {
  \column {
    \line \smallCaps { La vida breve }
    \line \bold { Acto I }
    \wordwrap \italic {
      (La escena representa el corral de una casa de
        gitanos en el Albaicín de Granada. Al fondo una
        puerta por la que se ve el negro interior de
        una Fragua, iluminado por los rojos resplandores
        del fuego.)
    }
    \hspace #0

    \line \bold { Acto II }
    \override #'(line-width . 50)
    \justify \italic {
      (Calle de Granada. Fachada de la casa de Carmela
        y su hermano Manuel con grandes ventanas abiertas
        a través de las que se ve el patio
        donde se celebra una alegre fiesta)
    }
  }
}

```

LA VIDA BREVE

### Acto I

*(La escena representa el corral de una casa de gitanos en el Albaicín de Granada. Al fondo una puerta por la que se ve el negro interior de una Fragua, iluminado por los rojos resplandores del fuego.)*

### Acto II

*(Calle de Granada. Fachada de la casa de Carmela y su hermano Manuel con grandes ventanas abiertas a través de las que se ve el patio donde se celebra una alegre fiesta)*

An exhaustive list of text alignment commands can be found in [Section A.9.2 \[Align\]](#), [page 618](#).

### See also

Learning Manual: [Section “Moving objects” in \*Learning Manual\*](#).

Notation Reference: [Section A.9.2 \[Align\]](#), [page 618](#), [\[Text marks\]](#), [page 205](#).

Snippets: [Section “Text” in \*Snippets\*](#).

Internals Reference: [Section “TextScript” in \*Internals Reference\*](#).

Installed Files: ‘`scm/define-markup-commands.scm`’.

## Graphic notation inside markup


Various graphic objects may be added to a score, using markup commands.

Some markup commands allow decoration of text elements with graphics, as demonstrated in the following example.

```

\markup \fill-line {
  \center-column {
    \circle Jack
    \box "in the box"
    \null
    \line {
      Erik Satie
      \hspace #3
      \bracket "1866 - 1925"
    }
    \null
    \rounded-box \bold Prelude
  }
}

```



Erik Satie [1866 - 1925]

**Prelude**

Some commands may require an increase in the padding around the text; this is achieved with some markup commands exhaustively described in [Section A.9.2 \[Align\]](#), page 618.

```

\markup \fill-line {
  \center-column {
    \box "Charles Ives (1874 - 1954)"
    \null
    \box \pad-markup #2 "THE UNANSWERED QUESTION"
    \box \pad-x #8 "A Cosmic Landscape"
    \null
  }
}
\markup \column {
  \line {
    \hspace #10
    \box \pad-to-box #'(-5 . 20) #'(0 . 5)
    \bold "Largo to Presto"
  }
  \pad-around #3
  "String quartet keeps very even time,
  Flute quartet keeps very uneven time."
}

```

Charles Ives (1874 - 1954)

THE UNANSWERED QUESTION

A Cosmic Landscape

**Largo to Presto**

String quartet keeps very even time, Flute quartet keeps very uneven time.

Other graphic elements or symbols may be printed without requiring any text. As with any markup expression, such objects can be combined.

```
\markup {
  \combine
    \draw-circle #4 #0.4 ##f
    \filled-box #'(-4 . 4) #'(-0.5 . 0.5) #1
  \hspace #5


  \center-column {
    \triangle ##t
    \combine
      \draw-line #'(0 . 4)
      \arrow-head #Y #DOWN ##f
  }
}
```



Advanced graphic features include the ability to include external image files converted to the Encapsulated PostScript format (*eps*), or to directly embed graphics into the input file, using native PostScript code. In such a case, it may be useful to explicitly specify the size of the drawing, as demonstrated below:

```
c1^\markup {
  \combine
    \epsfile #X #10 #"./context-example.eps"
    \with-dimensions #'(0 . 6) #'(0 . 10)
    \postscript #"
      -2 3 translate
      2.7 2 scale
      newpath
      2 -1 moveto
      4 -2 4 1 1 arct
      4 2 3 3 1 arct
      0 4 0 3 1 arct
      0 0 1 -1 1 arct
      closepath
      stroke"
}
```

c



An exhaustive list of graphics-specific commands can be found in [Section A.9.3 \[Graphic\]](#), [page 632](#).

See also

Notation Reference: Section A.9.3 [Graphic], page 632, Section 1.7 [Editorial annotations], page 191, Section A.9.2 [Align], page 618.

Snippets: Section “Text” in *Snippets*.

Internals Reference: [Section “TextScript” in \*Internals Reference\*](#).

Installed Files: 'scm/define-markup-commands.scm', 'scm/stencil.scm'.

## Music notation inside markup

Various musical notation elements may be added to a score, inside a markup object.

Notes and accidentals can be entered using markup commands:

```
a2 a^\markup {
  \note #"4" #1
=
  \note-by-number #1 #1 #1.5
}
b1_\markup {
  \natural \semiflat \flat
  \sesquiflat \doubleflat
}
\glissando
a1_\markup {
  \natural \semisharp \sharp
  \sesquisharp \doublesharp
}
\glissando b
```



Other notation objects may also be printed in markup mode:


```
g1 bes
ees-\markup {
  \finger 4
  \tied-lyric #"~"
  \finger 1
}
fis_\markup { \dynamic rf }
bes^\markup {
  \beam #8 #0.1 #0.5
}
cis
d-\markup {
  \markalphabet #8
  \markletter #8
}
```

}



More generally, any available musical symbol may be included separately in a markup object, as demonstrated below; an exhaustive list of these symbols and their names can be found in [Section A.7 \[The Feta font\]](#), page 589.


```
c2
c'\markup { \musicglyph #"eight" }
c,4
c,8._\markup { \musicglyph #"clefs.G_change" }
c16
c2^\markup { \musicglyph #"timesig.neomensural94" }
```



Another way of printing non-text glyphs is described in [\[Fonts explained\]](#), page 223. This is useful for printing braces of various sizes.

The markup mode also supports diagrams for specific instruments:

```
c1^\markup {
  \fret-diagram-terse #"x;x;o;2;3;2;"
}
c^\markup {
  \harp-pedal #"^~v|--ov^"
}
c
c^\markup {
  \combine
  \musicglyph #"accordion.discant"
  \combine
  \raise #0.5 \musicglyph #"accordion.dot"
  \raise #1.5 \musicglyph #"accordion.dot"
}
```




Such diagrams are documented in [Section A.9.5 \[Instrument Specific Markup\]](#), page 642.

A whole score can even be nested inside a markup object. In such a case, the nested `\score` block must contain a `\layout` block, as demonstrated here:

```

c4 d^\markup {
  \score {
    \relative c' { c4 d e f }
    \layout { }
  }
}
e f |
c d e f

```



An exhaustive list of music notation related commands can be found in [Section A.9.4 \[Music\]](#), page 638.

## See also

Notation Reference: [Section A.9.4 \[Music\]](#), page 638, [Section A.7 \[The Feta font\]](#), page 589, [\[Fonts explained\]](#), page 223.

Snippets: [Section “Text” in \*Snippets\*](#).

Internals Reference: [Section “TextScript” in \*Internals Reference\*](#).

Installed Files: ‘scm/define-markup-commands.scm’, ‘scm/fret-diagrams.scm’, ‘scm/harp-pedals.scm’.

## Multi-page markup

Although standard markup objects are not breakable, a specific syntax makes it possible to enter lines of text that can spread over multiple pages:

```

\markuplist {
  \justified-lines {
    A very long text of justified lines.
    ...
  }
  \wordwrap-lines {
    Another very long paragraph.
    ...
  }
  ...
}

```

A very long text of justified lines. ...

Another very long paragraph. ...

...

This syntax accepts a list of markups, that can be

- the result of a markup list command,



- a list of markups,
- a list of markup lists.

An exhaustive list of markup list commands can be found in [Section A.10 \[Text markup list commands\]](#), page 651.

## See also

Notation Reference: [Section A.10 \[Text markup list commands\]](#), page 651,

Snippets: [Section “Text” in \*Snippets\*](#).

Extending: [Section “New markup list command definition” in \*Extending\*](#).

Internals Reference: [Section “TextScript” in \*Internals Reference\*](#).

Installed Files: ‘`scm/define-markup-commands.scm`’.

## Predefined commands

`\markuplist`.

### 1.8.3 Fonts


This section presents the way fonts are handled, and how they may be changed in scores.

## Fonts explained

Fonts are handled through several libraries. `FontConfig` is used to detect available fonts on the system; the selected fonts are rendered using `Pango`.

Music notation fonts can be described as a set of specific glyphs, ordered in several families. The following syntax allows various LilyPond `feta` non-text fonts to be used directly in markup mode:

```
a1^\markup {
  \vcenter {
    \override #'(font-encoding . fetaBraces)
    \lookup #"brace120"
    \override #'(font-encoding . fetaText)
    \column { 1 3 sf }
    \override #'(font-encoding . fetaMusic)
    \lookup #"noteheads.s0petrucci"
  }
}
```



However, all these glyphs except the braces of various sizes contained in `fetaBraces` are available using the simpler syntax described in [\[Music notation inside markup\]](#), page 220.

When using the glyphs contained in `fetaBraces`, the size of the brace is specified by the numerical part of the glyph name, in arbitrary units. Any integer from 0 to 575 inclusive may be specified, 0 giving the smallest brace. The optimum value must be determined by trial and error. These glyphs are all left braces; right braces may be obtained by rotation, see [Section 5.4.8 \[Rotating objects\]](#), page 555.

Three families of text fonts are made available: the *roman* (serif) font, that defaults to New Century Schoolbook, the *sans* font and the monospaced *typewriter* font – these last two families are determined by the Pango installation.

Each family may include different shapes and series. The following example demonstrates the ability to select alternate families, shapes, series and sizes. The value supplied to **font-size** is the required change from the default size.

```
\override Score.RehearsalMark #'font-family = #'typewriter
\mark \markup "Ouverture"
\override Voice.TextScript #'font-shape = #'italic
\override Voice.TextScript #'font-series = #'bold
d2.^ \markup "Allegro"
\override Voice.TextScript #'font-size = #-3
c4^smaller
```



A similar syntax may be used in markup mode; however in this case it is preferable to use the simpler syntax explained in [\[Selecting font and font size\], page 212](#):

```
\markup {
  \column {
    \line {
      \override #'(font-shape . italic)
      \override #'(font-size . 4)
      Idomeneo,
    }
    \line {
      \override #'(font-family . typewriter)
      {
        \override #'(font-series . bold)
        re
        di
      }
      \override #'(font-family . sans)
      Creta
    }
  }
}
```

*Idomeneo,*  
re di Creta

Although it is easy to switch between preconfigured fonts, it is also possible to use other fonts, as explained in the following sections: [\[Single entry fonts\], page 225](#) and [\[Entire document fonts\], page 225](#).

## See also

Notation Reference: [Section A.7 \[The Feta font\], page 589](#), [\[Music notation inside markup\], page 220](#), [Section 5.4.8 \[Rotating objects\], page 555](#), [\[Selecting font and font size\], page 212](#), [Section A.9.1 \[Font\], page 609](#).

## Single entry fonts

Any font that is installed on the operating system and recognized by FontConfig may be used in a score, using the following syntax:

```
\override Staff.TimeSignature #'font-name = #"Bitstream Charter"
\override Staff.TimeSignature #'font-size = #2
\time 3/4
```

```
a1_\markup {
  \override #'(font-name . "Vera Bold")
  { Vera Bold }
}
```



The following command displays a list of all available fonts on the operating system:

```
lilypond -dshow-available-fonts x
```

## See also

Notation Reference: [\[Fonts explained\]](#), page 223, [\[Entire document fonts\]](#), page 225.


Snippets: [Section “Text” in \*Snippets\*](#).

## Entire document fonts

It is possible to change the fonts to be used as the default fonts in the *roman*, *sans* and *typewriter* font families by specifying them, in that order, as shown in the example below. For an explanation of fonts, see [\[Fonts explained\]](#), page 223.

```
\paper {
  myStaffSize = #20
  #(define fonts
    (make-pango-font-tree "Times New Roman"
      "Nimbus Sans"
      "Luxi Mono"
      (/ myStaffSize 20)))
}
```

```
\relative c'{
  c1-\markup {
    roman,
    \sans sans,
    \typewriter typewriter. }
}
```



## See also

Notation Reference: [\[Fonts explained\]](#), page 223, [\[Single entry fonts\]](#), page 225, [\[Selecting font and font size\]](#), page 212, [Section A.9.1 \[Font\]](#), page 609.

## 2 Specialist notation

This chapter explains how to create musical notation for specific types of instrument or in specific styles.

### 2.1 Vocal music

The image shows three staves of musical notation for a vocal piece. The first staff is labeled '216' and 'Recitativo Baritono'. It contains the lyrics 'O Freun - - de, nicht die - se Tö-ne! Sondern laßt uns'. The second staff is labeled '226' and contains the lyrics 'an - - ge - nehmere an-stimmen, und freu - -'. The third staff is labeled '233' and contains the lyrics '- - - - denvollere!'. The notation includes various musical symbols such as notes, rests, and dynamic markings.

This section explains how to typeset vocal music, and make sure that the lyrics will be aligned with the notes of their melody.

#### 2.1.1 Common notation for vocal music

This section discusses issues common to most types of vocal music.

#### References for vocal music

This section indicates where to find details of notation issues that may arise in any type of vocal music.

- Most styles of vocal music use written text as lyrics. An introduction to this notation is to be found in [Section “Setting simple songs” in \*Learning Manual\*](#).
- Vocal music is likely to require the use of `markup` mode, either for lyrics or for other text elements (characters’ names, etc.) This syntax is described in [\[Text markup introduction\]](#), [page 210](#).
- *Ambitus* may be added at the beginning of vocal staves, as explained in [\[Ambitus\]](#), [page 29](#).
- Dynamic markings by default are placed below the staff, but in choral music they are usually placed above the staff in order to avoid the lyrics, as explained in [\[Score layouts for choral\]](#), [page 263](#).

#### See also

Music Glossary: [Section “ambitus” in \*Music Glossary\*](#).

Learning Manual: [Section “Setting simple songs” in \*Learning Manual\*](#).

Notation Reference: [\[Text markup introduction\]](#), [page 210](#), [\[Ambitus\]](#), [page 29](#), [\[Score layouts for choral\]](#), [page 263](#).

Snippets: [Section “Vocal music” in \*Snippets\*](#).

## Entering lyrics

Lyrics are entered in a special input mode, which can be introduced by the keyword `\lyricmode`, or by using `\addlyrics` or `\lyricsto`. In this special input mode, the input `d` is not parsed as the pitch *D*, but rather as a one-letter syllable of text. In other words, syllables are entered like notes but with pitches replaced by text.

For example:

```
\lyricmode { Three4 blind mice,2 three4 blind mice2 }
```

There are two main methods for specifying the horizontal placement of the syllables, either by specifying the duration of each syllable explicitly, as in the example above, or by leaving the lyrics to be aligned automatically to a melody or other voice of music, using `\addlyrics` or `\lyricsto`. The former method is described below in [\[Manual syllable durations\]](#), page 232. The latter method is described in [\[Automatic syllable durations\]](#), page 230.

A word or syllable of lyrics begins with an alphabetic character (plus some other characters, see below) and is terminated by any white space or a digit. Later characters in the syllable can be any character that is not a digit or white space.

Because any character that is not a digit or white space is regarded as part of the syllable, a word is valid even if it ends with `}`, which often leads to the following mistake:

```
\lyricmode { lah lah lah}
```

In this example, the `}` is included in the final syllable, so the opening brace is not balanced and the input file will probably not compile. Instead, braces should always be surrounded with white space:

```
\lyricmode { lah lah lah }
```

Similarly, in lyric mode, a period will be included in the alphabetic sequence that it follows. As a consequence, spaces must be inserted around the period in `\override` commands. Do *not* write

```
\override Score.LyricText #'font-shape = #'italic
```

but instead use

```
\override Score . LyricText #'font-shape = #'italic
```

Punctuation, lyrics with accented characters, characters from non-English languages, or special characters (such as the heart symbol or slanted quotes), may simply be inserted directly into the input file, providing it is saved with UTF-8 encoding. For more information, see [Section 3.3.3 \[Special characters\]](#), page 453.

```
\relative c' { d8 c16 a bes8 f e' d c4 }
```

```
\addlyrics { „Schad’ um das schö -- ne grü -- ne Band, }
```



Normal quotes may be used in lyrics, but they have to be preceded with a backslash character and the whole syllable has to be enclosed between additional quotes. For example,

```
\relative c' { \time 3/4 e4 e4. e8 d4 e d c2. }
```

```
\addlyrics { "\"I" am so lone -- "ly,\"" said she }
```



The full definition of a word start in lyrics mode is somewhat more complex. A word in lyrics mode is one that begins with an alphabetic character, `_`, `?`, `!`, `:`, `'`, the control characters `^A` through `^F`, `^Q` through `^W`, `^Y`, `^^`, any 8-bit character with an ASCII code over 127, or a two-character combination of a backslash followed by one of ```, `'`, `"`, or `^`.

Great control over the appearance of lyrics comes from using `\markup` inside the lyrics themselves. For explanation of many options, see [Section 1.8.2 \[Formatting text\]](#), page 210.


## Selected Snippets

### *Formatting lyrics syllables*

Markup mode may be used to format individual syllables in lyrics.

```
mel = \relative c'' { c4 c c c }
lyr = \lyricmode {
  Lyrics \markup { \italic can } \markup { \with-color #red contain }
  \markup { \fontsize #8 \bold Markup! }
}

<<
  \new Voice = melody \mel
  \new Lyrics \lyricsto melody \lyr
>>
```



## See also

Learning Manual: [Section “Songs” in \*Learning Manual\*](#).

Notation Reference: [\[Automatic syllable durations\]](#), page 230, [Section 1.8.3 \[Fonts\]](#), page 223, [Section 1.8.2 \[Formatting text\]](#), page 210, [Section 5.4.1 \[Input modes\]](#), page 541, [\[Manual syllable durations\]](#), page 232, [Section 3.3.3 \[Special characters\]](#), page 453.

Internals Reference: [Section “LyricText” in \*Internals Reference\*](#).

Snippets: [Section “Text” in \*Snippets\*](#)

## Aligning lyrics to a melody

Lyrics are printed by interpreting them in the context called `Lyrics`, see [Section 5.1.1 \[Contexts explained\]](#), page 519.

```
\new Lyrics \lyricmode { ... }
```

Lyrics can be aligned with melodies in two main ways:

- Lyrics can be aligned automatically, with the durations of the syllables being taken from another voice of music or (in special circumstances) an associated melody, using `\addlyrics`, `\lyricsto`, or by setting the `associatedVoice` property. For more details, see [\[Automatic syllable durations\]](#), page 230.

```
<<
  \new Staff <<
    \time 2/4
    \new Voice = "one" \relative c'' {
      \voiceOne
```


```

    c4 b8. a16 g4. r8 a4 ( b ) c2
  }
  \new Voice = "two" \relative c' {
    \voiceTwo
    s2 s4. f8 e4 d c2
  }
>>

% takes durations and alignment from notes in "one"
\new Lyrics \lyricsto "one" {
  Life is __ _ love, live __ life.
}

% takes durations and alignment from notes in "one" initially
% then switches to "two"
\new Lyrics \lyricsto "one" {
  No more let
  \set associatedVoice = "two" % must be set one syllable early
  sins and sor -- rows grow.
}
>>

```



The first stanza shows the normal way of entering lyrics.

The second stanza shows how the voice from which the lyric durations are taken can be changed. This is useful if the words to different stanzas fit the notes in different ways and all the durations are available in Voice contexts. For more details, see [Section 2.1.3 \[Stanzas\]](#), [page 254](#).

- Lyrics can be aligned independently of the duration of any notes if the durations of the syllables are specified explicitly, and entered with `\lyricmode`.

```

<<
  \new Voice = "one" \relative c'' {
    \time 2/4
    c4 b8. a16 g4. f8 e4 d c2
  }

% uses previous explicit duration of 2;
\new Lyrics \lyricmode {
  Joy to the earth!
}

% explicit durations, set to a different rhythm
\new Lyrics \lyricmode {
  Life4 is love,2. live4 life.2
}
>>

```



The first stanza is not aligned with the notes because the durations were not specified, and the previous value of 2 is used for each word.

The second stanza shows how the words can be aligned quite independently from the notes. This is useful if the words to different stanzas fit the notes in different ways and the required durations are not available in a music context. For more details see [\[Manual syllable durations\]](#), page 232. This technique is also useful when setting dialogue over music; for examples showing this, see [\[Dialogue over music\]](#), page 271.

When entered in this way the words are left-aligned to the notes by default, but may be center-aligned to the notes of a melody by specifying an associated voice, if one exists. For details, see [\[Manual syllable durations\]](#), page 232.

## See also

Learning Manual: [Section “Aligning lyrics to a melody”](#) in *Learning Manual*.

Notation Reference: [Section 5.1.1 \[Contexts explained\]](#), page 519, [\[Automatic syllable durations\]](#), page 230. [Section 2.1.3 \[Stanzas\]](#), page 254, [\[Manual syllable durations\]](#), page 232, [\[Dialogue over music\]](#), page 271, [\[Manual syllable durations\]](#), page 232.

Internals Reference: [Section “Lyrics”](#) in *Internals Reference*.

## Automatic syllable durations

Lyrics can be automatically aligned to the notes of a melody in three ways:

- by specifying the named Voice context containing the melody with `\lyricsto`,
- by introducing the lyrics with `\addlyrics` and placing them immediately after the Voice context containing the melody,
- by setting the `associatedVoice` property, the alignment of the lyrics may be switched to a different named Voice context at any musical moment.

In all three methods hyphens can be drawn between the syllables of a word and extender lines can be drawn beyond the end of a word. For details, see [\[Extenders and hyphens\]](#), page 238.

The Voice context containing the melody to which the lyrics are being aligned must not have “died”, or the lyrics after that point will be lost. This can happen if there are periods when that voice has nothing to do. For methods of keeping contexts alive, see [Section 5.1.3 \[Keeping contexts alive\]](#), page 522.

## Using `\lyricsto`

Lyrics can be aligned under a melody automatically by specifying the named Voice context containing the melody with `\lyricsto`:

```
<<
  \new Voice = "melody" {
    a4 a a a
  }
  \new Lyrics \lyricsto "melody" {
    These are the words
  }
>>
```





This aligns the lyrics to the notes of the named **Voice** context, which must already exist. Therefore normally the **Voice** context is specified first, followed by the **Lyrics** context. The lyrics themselves follow the `\lyricsto` command. The `\lyricsto` command invokes lyric mode automatically, so the `\lyricmode` keyword may be omitted. By default, the lyrics are placed underneath the notes. For other placements, see [\[Placing lyrics vertically\], page 240](#).

## Using `\addlyrics`

The `\addlyrics` command is just a convenient shortcut that can sometimes be used instead of having to set up the lyrics through a more complicated LilyPond structure.

```
{ MUSIC }
\addlyrics { LYRICS }
```

is the same as

```
\new Voice = "blah" { MUSIC }
\new Lyrics \lyricsto "blah" { LYRICS }
```

Here is an example,

```
{
  \time 3/4
  \relative c' { c2 e4 g2. }
  \addlyrics { play the game }
}
```



More stanzas can be added by adding more `\addlyrics` sections:

```
{
  \time 3/4
  \relative c' { c2 e4 g2. }
  \addlyrics { play the game }
  \addlyrics { speel het spel }
  \addlyrics { joue le jeu }
}
```



The command `\addlyrics` cannot handle polyphonic settings. For these cases one should use `\lyricsto`.

## Using associatedVoice

The melody to which the lyrics are being aligned can be changed by setting the `associatedVoice` property,

```
\set associatedVoice = #"lala"
```

The value of the property (here: "lala") should be the name of a `Voice` context. For technical reasons, the `\set` command must be placed one syllable before the one to which the change in voice is to apply.

Here is an example demonstrating its use:

```
<<
\new Staff <<
  \time 2/4
  \new Voice = "one" \relative c'' {
    \voiceOne
    c4 b8. a16 g4. r8 a4 ( b ) c2
  }
  \new Voice = "two" \relative c' {
    \voiceTwo
    s2 s4. f8 e8 d4. c2
  }
  }
>>
% takes durations and alignment from notes in "one" initially
% then switches to "two"
\new Lyrics \lyricsto "one" {
  No more let
  \set associatedVoice = "two" % must be set one syllable early
  sins and sor -- rows grow.
}
>>
```



## See also

Notation Reference: [\[Extenders and hyphens\]](#), page 238, [Section 5.1.3 \[Keeping contexts alive\]](#), page 522, [\[Placing lyrics vertically\]](#), page 240.

## Manual syllable durations

In some complex vocal music, it may be desirable to place lyrics completely independently of notes. In this case do not use `\lyricsto` or `\addlyrics` and do not set `associatedVoice`. Syllables are entered like notes – but with pitches replaced by text – and the duration of each syllable is entered explicitly after the syllable.

By default, syllables will be left-aligned to the corresponding musical moment. Hyphenated lines may be drawn between syllables as usual, but extender lines cannot be drawn when there is no associated voice.

Here are two examples:

```
<<
  \new Voice = "melody" {
    \time 3/4
    c2 e4 g2 f
  }
  \new Lyrics \lyricmode {
    play1 the4 game4
  }
>>
```



```
<<
  \new Staff {
    \relative c'' {
      c2 c2
      d1
    }
  }
  \new Lyrics {
    \lyricmode {
      I2 like4. my8 cat!1
    }
  }
  \new Staff {
    \relative c' {
      c8 c c c c c c c
      c8 c c c c c c c
    }
  }
>>
```



This technique is useful when writing dialogue over music, see [\[Dialogue over music\]](#), page 271.

To center-align syllables on the notes at the corresponding musical moments, set `associatedVoice` to the name of the Voice context containing those notes. When `associatedVoice` is set, both double hyphens and double underscores can be used to draw hyphenated lines and extenders under melismata correctly.

```
<<
  \new Voice = "melody" {
    \time 3/4
    c2 e4 g f g
  }
>>
```

```
\new Lyrics \lyricmode {
  \set associatedVoice = #"melody"
  play2 the4 game2. --
}
>>
```



## See also


Notation Reference: [\[Dialogue over music\]](#), page 271.

Internals Reference: [Section “Lyrics” in \*Internals Reference\*](#), [Section “Voice” in \*Internals Reference\*](#).

## Multiple syllables to one note

In order to assign more than one syllable to a single note with spaces between the syllables, you can surround the phrase with quotes or use a \_ character. Alternatively, you can use the tilde symbol (~) to get a lyric tie.

```
{
  \relative c'' { \autoBeamOff
    r8 b c fis, fis c' b e, }
  \addlyrics { Che_in ques -- ta_e_in quel -- l'al -- tr'on -- da }
  \addlyrics { "Che in" ques -- "ta e in" quel -- l'al -- tr'on -- da }
  \addlyrics { Che~in ques -- ta~e~in quel -- l'al -- tr'on -- da }
}
```



## See also

Internals Reference: [Section “LyricCombineMusic” in \*Internals Reference\*](#).

## Multiple notes to one syllable

Sometimes, particularly in Medieval music, several notes are to be sung on one syllable; such vocalises are called melismata, or [Section “melisma” in \*Music Glossarys\*](#). The syllable to a melisma is usually left-aligned with the first note of the melisma.

When a melisma occurs on a syllable other than the last one in a word, that syllable is usually joined to the following one with a hyphenated line. This is indicated by placing a double hyphen, --, immediately after the syllable.

Alternatively, when a melisma occurs on the last or only syllable in a word an extender line is usually drawn from the end of the syllable to the last note of the melisma. This is indicated by placing a double underscore, \_\_, immediately after the word.

There are five ways in which melismata can be indicated:

- Melismata are created automatically over notes which are tied together:

```
<<
  \new Voice = "melody" {
    \time 3/4
    f4 g2 ~ |
    g4 e2 ~ |
    e8
  }
  \new Lyrics \lyricsto "melody" {
    Ky -- ri -- e --
  }
>>
```



- Melismata can be created automatically from the music by placing slurs over the notes of each melisma. This is the usual way of entering lyrics:

```
<<
  \new Voice = "melody" {
    \time 3/4
    f4 g8 ( f e f )
    e8 ( d e2 )
  }
  \new Lyrics \lyricsto "melody" {
    Ky -- ri -- e --
  }
>>
```



- Notes are considered a melisma if they are manually beamed, providing automatic beaming is switched off. See [\[Setting automatic beam behavior\]](#), page 74.

```
<<
  \new Voice = "melody" {
    \time 3/4
    \autoBeamOff
    f4 g8[ f e f]
    e2.
  }
  \new Lyrics \lyricsto "melody" {
    Ky -- ri -- e
  }
>>
```



Clearly this is not suited to melismata over notes which are longer than eighth notes.

- An unslurred group of notes will be treated as a melisma if they are bracketed between `\melisma` and `\melismaEnd`.

```
<<
  \new Voice = "melody" {
    \time 3/4
    f4 g8
    \melisma
    f e f
    \melismaEnd
    e2.
  }
  \new Lyrics \lyricsto "melody" {
    Ky -- ri -- e
  }
>>
```



Note that this method cannot be used to indicate two melismata if the first one is immediately followed by another.

- A melisma can be defined entirely in the lyrics by entering a single underscore character, `_`, for every extra note that has to be added to the melisma.

```
<<
  \new Voice = "melody" {
    \time 3/4
    f4 g8 f e f
    e8 d e2
  }
  \new Lyrics \lyricsto "melody" {
    Ky -- ri -- _ _ _ e _ _ _
  }
>>
```



It is possible to have ties, slurs and manual beams in the melody without their indicating melismata. To do this, set `melismaBusyProperties`:

```
<<
  \new Voice = "melody" {
    \time 3/4
    \set melismaBusyProperties = #'()
    c4 d ( e )
    g8 [ f ] f4 ~ f
  }
>>
```

```

}
\new Lyrics \lyricsto "melody" {
  Ky -- ri -- e e -- le -- i -- son
}
>>

```



Other settings for `melismaBusyProperties` can be used to selectively include or exclude ties, slurs, and beams from the automatic detection of melismata; see `melismaBusyProperties` in [Section “Tunable context properties” in \*Internals Reference\*](#).


Alternatively, if all melismata indications are to be ignored, `ignoreMelismata` may be set true; see [\[Stanzas with different rhythms\]](#), page 255.

If a melisma is required during a passage in which `melismaBusyProperties` is active, it may be indicated by placing a single underscore in the lyrics for each note which should be included in the melisma:

```

<<
\new Voice = "melody" {
  \time 3/4
  \set melismaBusyProperties = #'()
  c4 d ( e )
  g8 [ f ] ~ f4 ~ f
}
\new Lyrics \lyricsto "melody" {
  Ky -- ri -- _ e -- - - -
}
>>

```



## Predefined commands

`\autoBeamOff`, `\autoBeamOn`, `\melisma`, `\melismaEnd`.

## See also

Musical Glossary: [Section “melisma” in \*Music Glossary\*](#).

Learning Manual: [Section “Aligning lyrics to a melody” in \*Learning Manual\*](#).

Notation Reference: [\[Aligning lyrics to a melody\]](#), page 228, [\[Automatic syllable durations\]](#), page 230, [\[Setting automatic beam behavior\]](#), page 74, [\[Stanzas with different rhythms\]](#), page 255.

Internals Reference: [Section “Tunable context properties” in \*Internals Reference\*](#).

## Known issues and warnings

Extender lines under melismata are not created automatically; they must be inserted manually with a double underscore.

## Extenders and hyphens

In the last syllable of a word, melismata are sometimes indicated with a long horizontal line starting in the melisma syllable, and ending in the next one. Such a line is called an extender line, and it is entered as ‘`--`’ (note the spaces before and after the two underscore characters).

**Note:** Melismata are indicated in the score with extender lines, which are entered as one double underscore; but short melismata can also be entered by skipping individual notes, which are entered as single underscore characters; these do not make an extender line to be typeset by default.

Centered hyphens are entered as ‘`--`’ between syllables of a same word (note the spaces before and after the two hyphen characters). The hyphen will be centered between the syllables, and its length will be adjusted depending on the space between the syllables.

In tightly engraved music, hyphens can be removed. Whether this happens can be controlled with the `minimum-distance` (minimum distance between two syllables) and the `minimum-length` (threshold below which hyphens are removed) properties of `LyricHyphen`.

### See also

Internals Reference: [Section “LyricExtender” in \*Internals Reference\*](#), [Section “LyricHyphen” in \*Internals Reference\*](#).

## 2.1.2 Techniques specific to lyrics

### Working with lyrics and variables

Variables containing lyrics can be created, but the lyrics must be entered in lyric mode:

```
musicOne = \relative c'' {
  c4 b8. a16 g4. f8 e4 d c2
}
verseOne = \lyricmode {
  Joy to the world, the Lord is come.
}
\score {
  <<
    \new Voice = "one" {
      \time 2/4
      \musicOne
    }
    \new Lyrics \lyricsto "one" {
      \verseOne
    }
  >>
}
```



Durations do not need to be added if the variable is to be invoked with `\addlyrics` or `\lyricsto`.



For different or more complex orderings, the best way is to define the music and lyric variables first, then set up the hierarchy of staves and lyrics, omitting the lyrics themselves, and then add the lyrics using `\context` underneath. This ensures that the voices referenced by `\lyricsto` have always been defined earlier. For example:

```
sopranoMusic = \relative c'' { c4 c c c }
contraltoMusic = \relative c'' { a4 a a a }
sopranoWords = \lyricmode { Sop -- ra -- no words }
contraltoWords = \lyricmode { Con -- tral -- to words }

\score {
  \new ChoirStaff <<
    \new Staff {
      \new Voice = "sopranos" {
        \sopranoMusic
      }
    }
    \new Lyrics = "sopranos"
    \new Lyrics = "contraltos"
    \new Staff {
      \new Voice = "contraltos" {
        \contraltoMusic
      }
    }
    \context Lyrics = "sopranos" {
      \lyricsto "sopranos" {
        \sopranoWords
      }
    }
    \context Lyrics = "contraltos" {
      \lyricsto "contraltos" {
        \contraltoWords
      }
    }
  }
  >>
}
```



## See also

Notation Reference: [\[Placing lyrics vertically\]](#), page 240.

Internals Reference: [Section “LyricCombineMusic”](#) in *Internals Reference*, [Section “Lyrics”](#) in *Internals Reference*.

## Placing lyrics vertically


Depending on the type of music, lyrics may be positioned above the staff, below the staff, or between staves. Placing lyrics below the associated staff is the easiest, and can be achieved by simply defining the Lyrics context below the Staff context:

```
\score {
  <<
    \new Staff {
      \new Voice = "melody" {
        \relative c'' { c4 c c c }
      }
    }
    \new Lyrics {
      \lyricsto "melody" {
        Here are the words
      }
    }
  >>
}
```



Lyrics may be positioned above the staff using one of two methods. The simplest (and preferred) method is to use the same syntax as above and explicitly specify the position of the lyrics:

```
\score {
  <<
    \new Staff = "staff" {
      \new Voice = "melody" {
        \relative c'' { c4 c c c }
      }
    }
    \new Lyrics \with { alignAboveContext = "staff" } {
      \lyricsto "melody" {
        Here are the words
      }
    }
  >>
}
```




Alternatively, a two-step process may be used. First the Lyrics context is declared (without any content) before the Staff and Voice contexts, then the `\lyricsto` command is placed after the Voice declaration it references by using `\context`, as follows:

```
\score {
  <<
```

```

\new Lyrics = "lyrics" \with {
  % lyrics above a staff should have this override
  \override VerticalAxisGroup #'staff-affinity = #DOWN
}
\new Staff {
  \new Voice = "melody" {
    \relative c'' { c4 c c c }
  }
}
\context Lyrics = "lyrics" {
  \lyricsto "melody" {
    Here are the words
  }
}
>>
}

```



When there are two voices on separate staves the lyrics may be placed between the staves using either of these methods. Here is an example of the second method:

```

\score {
  \new ChoirStaff <<
    \new Staff {
      \new Voice = "sopranos" {
        \relative c'' { c4 c c c }
      }
    }
    \new Lyrics = "sopranos"
    \new Lyrics = "contraltos" \with {
      % lyrics above a staff should have this override
      \override VerticalAxisGroup #'staff-affinity = #DOWN
    }
    \new Staff {
      \new Voice = "contraltos" {
        \relative c'' { a4 a a a }
      }
    }
    \context Lyrics = "sopranos" {
      \lyricsto "sopranos" {
        Sop -- ra -- no words
      }
    }
    \context Lyrics = "contraltos" {
      \lyricsto "contraltos" {
        Con -- tral -- to words
      }
    }
  }
  >>
}

```



Other combinations of lyrics and staves may be generated by elaborating these examples, or by examining the [Section “Vocal ensembles”](#) in *Learning Manual* templates in the Learning Manual.

## Selected Snippets

### *Obtaining 2.12 lyrics spacing in newer versions*

The vertical spacing engine changed for version 2.14. This can cause lyrics to be spaced differently. It is possible to set properties for **Lyric** and **Staff** contexts to get the spacing engine to behave as it did in version 2.12.

```
global = {
  \key d \major
  \time 3/4
}

sopMusic = \relative c' {
  % VERSE ONE
  fis4 fis fis | \break
  fis4. e8 e4
}

altoMusic = \relative c' {
  % VERSE ONE
  d4 d d |
  d4. b8 b4 |
}

tenorMusic = \relative c' {
  a4 a a |
  b4. g8 g4 |
}

bassMusic = \relative c {
  d4 d d |
  g,4. g8 g4 |
}

words = \lyricmode {
  Great is Thy faith- ful- ness,
}

\score {
  \new ChoirStaff <<
    \new Lyrics = sopranos
    \new Staff = women <<
      \new Voice = "sopranos" {
```

```

        \voiceOne
        \global \sopMusic
    }
    \new Voice = "altos" {
        \voiceTwo
        \global \altoMusic
    }
>>
\new Lyrics = "altos"
\new Lyrics = "tenors"
\new Staff = men <<
    \clef bass
    \new Voice = "tenors" {
        \voiceOne
        \global \tenorMusic
    }
    \new Voice = "basses" {
        \voiceTwo \global \bassMusic
    }
>>
\new Lyrics = basses
\context Lyrics = sopranos \lyricsto sopranos \words
\context Lyrics = altos \lyricsto altos \words
\context Lyrics = tenors \lyricsto tenors \words
\context Lyrics = basses \lyricsto basses \words
>>
\layout {
    \context {
        \Lyrics
        \override VerticalAxisGroup #'staff-affinity = ##f
        \override VerticalAxisGroup #'staff-staff-spacing =
            #'((basic-distance . 0)
              (minimum-distance . 2)
              (padding . 2))
    }
    \context {
        \Staff
        \override VerticalAxisGroup #'staff-staff-spacing =
            #'((basic-distance . 0)
              (minimum-distance . 2)
              (padding . 2))
    }
}
}

```

[illegible]

See also

Learning Manual: **Section** “Vocal ensembles” in *Learning Manual*.

Notation Reference: Section 5.1.7 [Context layout order], page 529, Section 5.1.2 [Creating contexts], page 521.

## Placing syllables horizontally

To increase the spacing between lyrics, set the `minimum-distance` property of `LyricSpace`.

```
{
  c c c c
  \override Lyrics.LyricSpace #'minimum-distance = #1.0
  c c c c
}

\addlyrics {
  longtext longtext longtext longtext
  longtext longtext longtext longtext
}
```





To make this change for all lyrics in the score, set the property in the `\layout` block.

```
\score {
  \relative c' {
    c c c c
    c c c c
  }
  \addlyrics {
    longtext longtext longtext longtext
    longtext longtext longtext longtext
  }
  \layout {
    \context {
      \Lyrics
      \override LyricSpace #'minimum-distance = #1.0
    }
  }
}
```




## Selected Snippets

### *Lyrics alignment*

Horizontal alignment for lyrics can be set by overriding the `self-alignment-X` property of the `LyricText` object. `#-1` is left, `#0` is center and `#1` is right; however, you can use `#LEFT`, `#CENTER` and `#RIGHT` as well.

```
\layout { ragged-right = ##f }
\relative c' {
  c1
  c1
  c1
}
\addlyrics {
  \once \override LyricText #'self-alignment-X = #LEFT
  "This is left-aligned"
  \once \override LyricText #'self-alignment-X = #CENTER
  "This is centered"
  \once \override LyricText #'self-alignment-X = #1
  "This is right-aligned"
}
```



Checking to make sure that text scripts and lyrics are within the margins requires additional calculations. To speed up processing slightly, this feature can be disabled:

```
\override Score.PaperColumn #'keep-inside-line = ##f
```

To make lyrics avoid bar lines as well, use

```
\layout {
  \context {
    \Lyrics
    \consists "Bar_engraver"
    \consists "Separating_line_group_engraver"
    \override BarLine #'transparent = ##t
  }
}
```

## Lyrics and repeats

### Simple repeats

Repeats in *music* are fully described elsewhere; see [Section 1.4 \[Repeats\]](#), page 127. This section explains how to add lyrics to repeated sections of music.

Lyrics to a section of music that is repeated should be surrounded by exactly the same repeat construct as the music, if the words are unchanged.

```
\score {
  <<
    \new Staff {
      \new Voice = "melody" {
        \relative c'' {
          a4 a a a
          \repeat volta 2 { b4 b b b }
        }
      }
    }
    \new Lyrics {
      \lyricsto "melody" {
        Not re -- peat -- ed.
        \repeat volta 2 { Re -- peat -- ed twice. }
      }
    }
  >>
}
```



The words will then be correctly expanded if the repeats are unfolded.

```
\score {
  \unfoldRepeats {
    <<
      \new Staff {
```



```

\new Voice = "melody" {
  \relative c'' {
    a4 a a a
    \repeat volta 2 { b4 b b b }
  }
}
\new Lyrics {
  \lyricsto "melody" {
    Not re -- peat -- ed.
    \repeat volta 2 { Re -- peat -- ed twice. }
  }
}
>>
}

```



If the repeated section is to be unfolded and has different words, simply enter all the words:

```

\score {
  <<
    \new Staff {
      \new Voice = "melody" {
        \relative c'' {
          a4 a a a
          \repeat unfold 2 { b4 b b b }
        }
      }
    }
  \new Lyrics {
    \lyricsto "melody" {
      Not re -- peat -- ed.
      The first time words.
      Sec -- ond time words.
    }
  }
  >>
}

```



When the words to a repeated volta section are different, the words to each repeat must be entered in separate Lyrics contexts, correctly nested in parallel sections:

```

\score {
  <<

```

```

\new Staff {
  \new Voice = "melody" {
    \relative c'' {
      a4 a a a
      \repeat volta 2 { b4 b b b }
    }
  }
}
\new Lyrics \lyricsto "melody" {
  Not re -- peat -- ed.
  <<
    { The first time words. }
    \new Lyrics {
      \set associatedVoice = "melody"
      Sec -- ond time words.
    }
  >>
}
>>
}

```



More verses may be added in a similar way:

```


\score {
  <<
    \new Staff {
      \new Voice = "singleVoice" {
        \relative c'' {
          a4 a a a
          \repeat volta 3 { b4 b b b }
          c4 c c c
        }
      }
    }
  >>
  \new Lyrics \lyricsto "singleVoice" {
    Not re -- peat -- ed.
    <<
      { The first time words. }
      \new Lyrics {
        \set associatedVoice = "singleVoice"
        Sec -- ond time words.
      }
      \new Lyrics {
        \set associatedVoice = "singleVoice"
        The third time words.
      }
    >>
  }
}

```

```

    The end sec -- tion.
  }
  >>
}

```



## Repeats with alternative endings

If the words of the repeated section are the same, exactly the same structure can be used for both the lyrics and music.

```

\score {
  <<
    \new Staff {
      \time 2/4
      \new Voice = "melody" {
        \relative c'' {
          a4 a a a
          \repeat volta 2 { b4 b }
          \alternative { { b b } { b c } }
        }
      }
    }
    \new Lyrics {
      \lyricsto "melody" {
        Not re -- peat -- ed.
        \repeat volta 2 { Re -- peat -- }
        \alternative { { ed twice. } { ed twice. } }
      }
    }
  >>
}

```




But when the repeated section has different words, a repeat construct cannot be used around the words and `\skip` commands have to be inserted manually to skip over the notes in the alternative sections which do not apply.

Note: do not use an underscore, `_`, to skip notes – an underscore indicates a melisma, causing the preceding syllable to be left-aligned.

**Note:** The `\skip` command must be followed by a number, but this number is ignored in lyrics which derive their durations from the notes in an associated melody through `\addlyrics` or `\lyricsto`. Each `\skip` skips a single note of any value, irrespective of the value of the following number.

```
\score {
  <<
    \new Staff {
      \time 2/4
      \new Voice = "melody" {
        \relative c'' {
          \repeat volta 2 { b4 b }
          \alternative { { b b } { b c } }
          c4 c
        }
      }
    }
    \new Lyrics {
      \lyricsto "melody" {
        The first time words.
        \repeat unfold 2 { \skip 1 }
        End here.
      }
    }
    \new Lyrics {
      \lyricsto "melody" {
        Sec -- ond
        \repeat unfold 2 { \skip 1 }
        time words.
      }
    }
  >>
}
```



When a note is tied over into two or more alternative endings a tie is used to carry the note into the first alternative ending and a `\repeatTie` is used in the second and subsequent endings. This structure causes difficult alignment problems when lyrics are involved and increasing the length of the alternative sections so the tied notes are contained wholly within them may give a more acceptable result.

The tie creates a melisma into the first alternative, but not into the second and subsequent alternatives, so to align the lyrics correctly it is necessary to disable the automatic creation of melismata over the volta section and insert manual skips.

```
\score {
  <<
    \new Staff {
      \time 2/4
      \new Voice = "melody" {
```

```

\relative c'' {
  \set melismaBusyProperties = #'()
  \repeat volta 2 { b4 b ~}
  \alternative { { b b } { b \repeatTie c } }
  \unset melismaBusyProperties
  c4 c
}
}
}
\new Lyrics {
  \lyricsto "melody" {
    \repeat volta 2 { Here's a __ }
    \alternative {
      { \skip 1 verse }
      { \skip 1 sec }
    }
    ond one.
  }
}
>>
}

```



Note that if `\unfoldRepeats` is used around a section containing `\repeatTie`, the `\repeatTie` should be removed to avoid both types of tie being printed.

When the repeated section has different words a `\repeat` cannot be used around the lyrics and `\skip` commands need to be inserted manually, as before.

```


\score {
  <<
    \new Staff {
      \time 2/4
      \new Voice = "melody" {
        \relative c'' {
          \repeat volta 2 { b4 b ~}
          \alternative { { b b } { b \repeatTie c } }
          c4 c
        }
      }
    }
  }
  \new Lyrics {
    \lyricsto "melody" {
      Here's a __ verse.
      \repeat unfold 2 { \skip 1 }
    }
  }
  \new Lyrics {
    \lyricsto "melody" {

```

```

Here's one
\repeat unfold 2 { \skip 1 }
more to sing.
}
}
>>
}

```



If you wish to show extenders and hyphens into and out of alternative sections these must be inserted manually.

```

\score {
  <<
    \new Staff {
      \time 2/4
      \new Voice = "melody" {
        \relative c'' {
          \repeat volta 2 { b4 b ~}
          \alternative { { b b } { b \repeatTie c } }
          c4 c
        }
      }
    }
    \new Lyrics {
      \lyricsto "melody" {
        Here's a __ verse.
        \repeat unfold 2 { \skip 1 }
      }
    }
    \new Lyrics {
      \lyricsto "melody" {
        Here's "a_"
        \skip 1
        "_" sec -- ond one.
      }
    }
  >>
}

```



## See also

Notation Reference: [Section 5.1.3 \[Keeping contexts alive\]](#), page 522, [Section 1.4 \[Repeats\]](#), page 127.

## Divisi lyrics

When just the words and rhythms of the two parts differ with the pitches remaining the same, temporarily turning off the automatic detection of melismata and indicating the melisma in the lyrics may be the appropriate method to use:

```
\score {
  <<
    \new Voice = "melody" {
      \relative c' {
        \set melismaBusyProperties = #'()
        \slurDown
        \slurDashed
        e4 e8 ( e ) c4 c |
        \unset melismaBusyProperties
        c
      }
    }
    \new Lyrics \lyricsto "melody" {
      They shall not o -- ver -- come
    }
    \new Lyrics \lyricsto "melody" {
      We will _
    }
  >>
}
```



When both music and words differ it may be better to display the differing music and lyrics by naming voice contexts and attaching lyrics to those specific contexts:

```
\score {
  <<
    \new Voice = "melody" {
      \relative c' {
        <<
          {
            \voiceOne
            e4 e8 e
          }
          \new Voice = "splitpart" {
            \voiceTwo
            c4 c
          }
        >>
      }
    }
  >>
}
```

```

\oneVoice
c4 c |
c
}
}
\new Lyrics \lyricsto "melody" {
  They shall not o -- ver -- come
}
\new Lyrics \lyricsto "splitpart" {
  We will
}
}
>>
}

```



### 2.1.3 Stanzas


#### Adding stanza numbers

Stanza numbers can be added by setting `stanza`, e.g.,

```

\new Voice {
  \time 3/4 g2 e4 a2 f4 g2.
} \addlyrics {
  \set stanza = #"1. "
  Hi, my name is Bert.
} \addlyrics {
  \set stanza = #"2. "
  Oh, ché -- ri, je t'aime
}

```



These numbers are put just before the start of the first syllable.

#### Adding dynamics marks to stanzas

Stanzas differing in loudness may be indicated by putting a dynamics mark before each stanza. In LilyPond, everything coming in front of a stanza goes into the `StanzaNumber` object; dynamics marks are no different. For technical reasons, you have to set the stanza outside `\lyricmode`:

```

text = {
  \set stanza = \markup { \dynamic "ff" "1. " }
  \lyricmode {
    Big bang
  }
}

```



```

}

<<
  \new Voice = "tune" {
    \time 3/4
    g'4 c'2
  }
\new Lyrics \lyricsto "tune" \text
>>

```




### Adding singers' names to stanzas

Names of singers can also be added. They are printed at the start of the line, just like instrument names. They are created by setting `vocalName`. A short version may be entered as `shortVocalName`.

```

\new Voice {
  \time 3/4 g2 e4 a2 f4 g2.
} \addlyrics {
  \set vocalName = #"Bert "
  Hi, my name is Bert.
} \addlyrics {
  \set vocalName = #"Ernie "
  Oh, ché -- ri, je t'aime
}

```



### Stanzas with different rhythms

Often, different stanzas of one song are put to one melody in slightly differing ways. Such variations can still be captured with `\lyricsto`.

### Ignoring melismata

One possibility is that the text has a melisma in one stanza, but multiple syllables in another. One solution is to make the faster voice ignore the melisma. This is done by setting `ignoreMelismata` in the Lyrics context.

```


<<
  \relative c' \new Voice = "lahlah" {
    \set Staff.autoBeaming = ##f
    c4
    \slurDotted
    f8.[( g16)]
    a4
  }

```

```

\new Lyrics \lyricsto "lahlah" {
  more slow -- ly
}
\new Lyrics \lyricsto "lahlah" {
  go
  \set ignoreMelismata = ##t
  fas -- ter
  \unset ignoreMelismata
  still
}
>>

```



## Known issues and warnings

Unlike most `\set` commands, `\set ignoreMelismata` does not work if prefixed with `\once`. It is necessary to use `\set` and `\unset` to bracket the lyrics where melismata are to be ignored.

## Adding syllables to grace notes

By default, grace notes (e.g. via `\grace`) do not get assigned syllables when using `\lyricsto`, but this behavior can be changed:

```

<<
\new Voice = melody \relative c' {
  f4 \appoggiatura a32 b4
  \grace { f16[ a16] } b2
  \afterGrace b2 { f16[ a16] }
  \appoggiatura a32 b4
  \acciaccatura a8 b4
}
\new Lyrics
\lyricsto melody {
  normal
  \set includeGraceNotes = ##t
  case,
  gra -- ce case,
  after -- grace case,
  \set ignoreMelismata = ##t
  app. case,
  acc. case.
}
>>

```



## Known issues and warnings

Like `associatedVoice`, `includeGraceNotes` needs to be set at latest one syllable before the one which is to be put under a grace note. For the case of a grace note at the very beginning of a piece of music, consider using a `\with` or `\context` block:

```
<<
  \new Voice = melody \relative c' {
    \grace { c16[( d e f] }
    g1) f
  }
  \new Lyrics \with { includeGraceNotes = ##t }
  \lyricsto melody {
    Ah __ fa
  }
>>
```



## Switching to an alternative melody


More complex variations in setting lyrics to music are possible. The melody to which the lyrics are being set can be changed from within the lyrics by setting the `associatedVoice` property:

```
<<
  \relative c' \new Voice = "lahlah" {
    \set Staff.autoBeaming = ##f
    c4
    <<
      \new Voice = "alternative" {
        \voiceOne
        \times 2/3 {
          % show associations clearly.
          \override NoteColumn #'force-hshift = #-3
          f8 f g
        }
      }
    }
    {
      \voiceTwo
      f8.[ g16]
      \oneVoice
    } >>
    a8( b) c
  }
  \new Lyrics \lyricsto "lahlah" {
    Ju -- ras -- sic Park
  }
  \new Lyrics \lyricsto "lahlah" {
    % Tricky: need to set associatedVoice
    % one syllable too soon!
    \set associatedVoice = "alternative" % applies to "ran"
    Ty --
```

```

ran --
no --
\set associatedVoice = "lahlah" % applies to "rus"
sau -- rus Rex
} >>

```



The text for the first stanza is set to the melody called ‘lahlah’ in the usual way, but the second stanza is set initially to the **lahlah** context and is then switched to the **alternative** melody for the syllables ‘ran’ to ‘sau’ by the lines:

```

\set associatedVoice = "alternative" % applies to "ran"
Ty --
ran --
no --
\set associatedVoice = "lahlah" % applies to "rus"
sau -- rus Rex

```

Here, **alternative** is the name of the Voice context containing the triplet.

Note the placement of the `\set associatedVoice` command – it appears to be one syllable too early, but this is correct.

**Note:** The `\set associatedVoice` command must be placed one syllable *before* the one at which the switch to the new voice is to occur. In other words, changing the associated Voice happens one syllable later than expected. This is for technical reasons, and it is not a bug.

## Printing stanzas at the end

Sometimes it is appropriate to have one stanza set to the music, and the rest added in verse form at the end of the piece. This can be accomplished by adding the extra verses into a `\markup` section outside of the main score block. Notice that there are two different ways to force linebreaks when using `\markup`.

```

melody = \relative c' {
e d c d | e e e e |
d d e d | c1 |
}

text = \lyricmode {
\set stanza = #"1." Ma- ry had a lit- tle lamb,
its fleece was white as snow.
}

\score{ <<
  \new Voice = "one" { \melody }
  \new Lyrics \lyricsto "one" \text
>>
  \layout { }
}

```


```

\markup { \column{
  \line{ Verse 2. }
  \line{ All the children laughed and played }
  \line{ To see a lamb at school. }
}
}
\markup{
  \wordwrap-string #"
  Verse 3.

  Mary took it home again,

  It was against the rule."
}

```



Verse 2.  
All the children laughed and played  
To see a lamb at school.

Verse 3.  
Mary took it home again,  
It was against the rule.

## Printing stanzas at the end in multiple columns

When a piece of music has many verses, they are often printed in multiple columns across the page. An outdented verse number often introduces each verse. The following example shows how to produce such output in LilyPond.

```

melody = \relative c' {
  c c c c | d d d d
}

text = \lyricmode {
  \set stanza = #"1." This is verse one.
  It has two lines.
}

\score {
  <<
    \new Voice = "one" { \melody }
    \new Lyrics \lyricsto "one" \text
  >>
  \layout { }
}

\markup {

```

```

\fill-line {
  \hspace #0.1 % moves the column off the left margin;
  % can be removed if space on the page is tight
  \column {
    \line { \bold "2."
    \column {
      "This is verse two."
      "It has two lines."
    }
  }
  \hspace #0.1 % adds vertical spacing between verses
  \line { \bold "3."
  \column {
    "This is verse three."
    "It has two lines."
  }
}
\hspace #0.1 % adds horizontal spacing between columns;
% if they are still too close, add more " " pairs
% until the result looks good
\column {
  \line { \bold "4."
  \column {
    "This is verse four."
    "It has two lines."
  }
}
\hspace #0.1 % adds vertical spacing between verses
\line { \bold "5."
\column {
  "This is verse five."
  "It has two lines."
}
}
\hspace #0.1 % gives some extra space on the right margin;
% can be removed if page space is tight
}
}

```



**2.** This is verse two.

It has two lines.

**3.** This is verse three.

It has two lines.

**4.** This is verse four.

It has two lines.

**5.** This is verse five.

It has two lines.

## See also

Internals Reference: [Section “LyricText” in \*Internals Reference\*](#), [Section “StanzaNumber” in \*Internals Reference\*](#).

## 2.1.4 Songs

### References for songs

Songs are usually written on three staves with the melody for the singer on the top staff and two staves of piano accompaniment at the bottom. The lyrics of the first stanza are printed immediately underneath the top staff. If there are just a small number of further stanzas these can be printed immediately under the first one, but if there are more stanzas than can be easily accommodated there the second and subsequent stanzas are printed after the music as stand-alone text.

All the notational elements needed to write songs are fully described elsewhere:

- For constructing the staff layout, see [Section 1.6.1 \[Displaying staves\]](#), page 162.
- For writing piano music, see [Section 2.2 \[Keyboard and other multi-staff instruments\]](#), page 285.
- For writing the lyrics to a melody line, see [Section 2.1.1 \[Common notation for vocal music\]](#), page 226.
- For placing the lyrics, see [\[Placing lyrics vertically\]](#), page 240.
- For entering stanzas, see [Section 2.1.3 \[Stanzas\]](#), page 254.
- Songs are frequently printed with the chording indicated by chord names above the staves. This is described in [Section 2.7.2 \[Displaying chords\]](#), page 373.
- To print fret diagrams of the chords for guitar accompaniment or accompaniment by other fretted instruments, see “Fret diagram markups” in [Section 2.4.1 \[Common notation for fretted strings\]](#), page 300.

## See also

Learning Manual: [Section “Songs” in \*Learning Manual\*](#).

Notation Reference: [Section 2.1.1 \[Common notation for vocal music\]](#), page 226, [Section 2.7.2 \[Displaying chords\]](#), page 373, [Section 1.6.1 \[Displaying staves\]](#), page 162, [Section 2.2 \[Keyboard and other multi-staff instruments\]](#), page 285, [\[Placing lyrics vertically\]](#), page 240, [Section 2.1.3 \[Stanzas\]](#), page 254.

Snippets: [Section “Vocal music” in \*Snippets\*](#).

## Lead sheets

Lead sheets may be printed by combining vocal parts and ‘chord mode’; this syntax is explained in [Section 2.7 \[Chord notation\]](#), page 367.


## Selected Snippets

*Simple lead sheet*

When put together, chord names, a melody, and lyrics form a lead sheet:

```
<<
\chords { c2 g:sus4 f e }
\relative c'' {
  a4 e c8 e r4
  b2 c4( d)
}
```

```
\addlyrics { One day this shall be free __ }
>>
```



## See also

Notation Reference: [Section 2.7 \[Chord notation\]](#), page 367.

### 2.1.5 Choral

This section discusses notation issues that relate most directly to choral music. This includes anthems, part songs, oratorio, etc.

## References for choral

Choral music is usually notated on two, three or four staves within a **ChoirStaff** group. Accompaniment, if required, is placed beneath in a **PianoStaff** group, which is usually reduced in size for *a capella* choral works. The notes for each vocal part are placed in a **Voice** context, with each staff being given either a single vocal part (i.e., one **Voice**) or a pair of vocal parts (i.e., two **Voices**).

Words are placed in **Lyrics** contexts, either underneath each corresponding music staff, or one above and one below the music staff if this contains the music for two parts.

Several common topics in choral music are described fully elsewhere:

- An introduction to creating an SATB vocal score can be found in the Learning Manual, see [Section “Four-part SATB vocal score” in \*Learning Manual\*](#).
- Several templates suitable for various styles of choral music can also be found in the Learning Manual, see [Section “Vocal ensembles” in \*Learning Manual\*](#).
- For information about **ChoirStaff** and **PianoStaff** see [\[Grouping staves\]](#), page 163.
- Shape note heads, as used in Sacred Harp and similar notation, are described in [\[Shape note heads\]](#), page 35.
- When two vocal parts share a staff the stems, ties, slurs, etc., of the higher part will be directed up and those of the lower part down. To do this, use `\voiceOne` and `\voiceTwo`. See [\[Single-staff polyphony\]](#), page 146.

## Predefined commands

`\oneVoice`, `\voiceOne`, `\voiceTwo`.

## See also

Learning Manual: [Section “Four-part SATB vocal score” in \*Learning Manual\*](#), [Section “Vocal ensembles” in \*Learning Manual\*](#).

Notation Reference: [Section 5.1.7 \[Context layout order\]](#), page 529, [\[Grouping staves\]](#), page 163, [\[Shape note heads\]](#), page 35, [\[Single-staff polyphony\]](#), page 146.

Snippets: [Section “Vocal music” in \*Snippets\*](#).

Internals Reference: [Section “ChoirStaff” in \*Internals Reference\*](#), [Section “Lyrics” in \*Internals Reference\*](#), [Section “PianoStaff” in \*Internals Reference\*](#).




## Score layouts for choral

Choral music containing four staves, with or without piano accompaniment, is usually laid out with two systems per page. Depending on the page size, achieving this may require changes to several default settings. The following settings should be considered:

- The global staff size can be modified to change the overall size of the elements of the score. See [Section 4.2.2 \[Setting the staff size\]](#), page 479.
- The distances between the systems, the staves and the lyrics can all be adjusted independently. See [Section 4.4 \[Vertical spacing\]](#), page 488.
- The dimensions of the vertical layout variables can be displayed as an aid to adjusting the vertical spacing. This and other possibilities for fitting the music onto fewer pages are described in [Section 4.6 \[Fitting music onto fewer pages\]](#), page 515.
- If the number of systems per page changes from one to two it is customary to indicate this with a system separator mark between the two systems. See [\[Separating systems\]](#), page 168.
- For details of other page formatting properties, see [Section 4.1 \[Page layout\]](#), page 469.

Dynamic markings by default are placed below the staff, but in choral music they are usually placed above the staff in order to avoid the lyrics. The predefined command `\dynamicUp` does this for the dynamic markings in a single `Voice` context. If there are many `Voice` contexts this predefined command would have to be placed in every one. Alternatively its expanded form can be used to place all dynamic markings in the entire score above their respective staves, as shown here:

```
\score {
  \new ChoirStaff <<
    \new Staff {
      \new Voice {
        \relative c'' { g4\ff g g g }
      }
    }
    \new Staff {
      \new Voice {
        \relative c' { d4 d d\p d }
      }
    }
  >>
  \layout {
    \context {
      \Score
      \override DynamicText #'direction = #UP
      \override DynamicLineSpanner #'direction = #UP
    }
  }
}
```



## Predefined commands

`\dynamicUp`, `\dynamicDown`, `\dynamicNeutral`.

## See also

Notation Reference: Section 4.6.2 [Changing spacing], page 516, Section 4.6.1 [Displaying spacing], page 515, Section 4.6 [Fitting music onto fewer pages], page 515, Section 4.1 [Page layout], page 469, Section 4.2 [Score layout], page 478, [Separating systems], page 168, Section 4.2.2 [Setting the staff size], page 479, Section 4.3.7 [Using an extra voice for breaks], page 486, Section 4.4 [Vertical spacing], page 488.

Internals Reference: Section “VerticalAxisGroup” in *Internals Reference*, Section “StaffGrouper” in *Internals Reference*.


## Divided voices

*Using arpeggioBracket to make divisi more visible*

The `arpeggioBracket` can be used to indicate the division of voices where there are no stems to provide the information. This is often seen in choral music.

```
\include "english.ly"
```

```
\score {
  \relative c'' {
    \key a \major
    \time 2/2
    <<
      \new Voice = "upper"
      <<
        { \voiceOne \arpeggioBracket
          a2( b2
            <b d>1\arpeggio)
            <cs e>\arpeggio ~
            <cs e>4
          }
          \addlyrics { \lyricmode { A -- men. } }
        >>
      \new Voice = "lower"
      { \voiceTwo
        a1 ~
        a
        a ~
        a4 \bar "|"
      }
    >>
  }
  \layout { ragged-right = ##t }
}
```



## See also

Notation Reference: [Section 1.3.3 \[Expressive marks as lines\]](#), page 120.

### 2.1.6 Opera and stage musicals

The music, lyrics and dialogue to opera and stage musicals are usually set out in one or more of the following forms:

- A *Conductors' Score* containing the full orchestral and vocal parts, together with libretto cues if there are spoken passages.
- *Orchestral Parts* containing the music for the individual instruments of the orchestra or band.
- A *Vocal Score* containing all vocal parts with piano accompaniment. The accompaniment is usually an orchestral reduction, and if so the name of the original orchestral instrument is often indicated. Vocal scores sometimes includes stage directions and libretto cues.
- A *Vocal Book* containing just the vocal parts (no accompaniment), sometimes combined with the libretto.
- A *Libretto* containing the extended passages of spoken dialogue usually found in musicals, together with the words to the sung parts. Stage directions are usually included. LilyPond can be used to typeset libretti but as they contain no music alternative methods may be preferable.

The sections in the LilyPond documentation which cover the topics needed to create scores in the styles commonly found in opera and musicals are indicated in the References below. This is followed by sections covering those techniques which are peculiar to typesetting opera and musical scores.

## References for opera and stage musicals

- A conductors' score contains many grouped staves and lyrics. Ways of grouping staves is shown in [\[Grouping staves\]](#), page 163. To nest groups of staves see [\[Nested staff groups\]](#), page 166.
- The printing of empty staves in conductors' scores and vocal scores is often suppressed. To create such a "Frenched score" see [\[Hiding staves\]](#), page 176.
- Writing orchestral parts is covered in [Section 1.6.3 \[Writing parts\]](#), page 179. Other sections in the Specialist notation chapter may be relevant, depending on the orchestration used. Many instruments are transposing instruments, see [\[Instrument transpositions\]](#), page 21.
- If the number of systems per page changes from page to page it is customary to separate the systems with a system separator mark. See [\[Separating systems\]](#), page 168.
- For details of other page formatting properties, see [Section 4.1 \[Page layout\]](#), page 469.
- Dialogue cues, stage directions and footnotes can be inserted, see [Section 3.2.3 \[Creating footnotes\]](#), page 438 and [Section 1.8 \[Text\]](#), page 202. Extensive stage directions can also be added with a section of stand-alone markups between two `\score` blocks, see [\[Separate text\]](#), page 209.

## See also

Musical Glossary: [Section "Frenched score" in \*Music Glossary\*](#), [Section "Frenched staves" in \*Music Glossary\*](#), [Section "transposing instrument" in \*Music Glossary\*](#).

Notation Reference: [Section 3.2.3 \[Creating footnotes\]](#), page 438, [\[Grouping staves\]](#), page 163, [\[Hiding staves\]](#), page 176, [\[Instrument transpositions\]](#), page 21, [\[Nested staff groups\]](#), page 166, [Section 4.1 \[Page layout\]](#), page 469, [\[Separating systems\]](#), page 168, [\[Transpose\]](#), page 9, [Section 1.6.3 \[Writing parts\]](#), page 179, [Section 1.8.1 \[Writing text\]](#), page 202.

Snippets: [Section "Vocal music" in \*Snippets\*](#).

## Character names

Character names are usually shown to the left of the staff when the staff is dedicated to that character alone:

```
\score {
  <<
    \new Staff {
      \set Staff.vocalName = \markup \smallCaps Kaspar
      \set Staff.shortVocalName = \markup \smallCaps Kas.
      \relative c' {
        \clef "G_8"
        c4 c c c
        \break
        c4 c c c
      }
    }
    \new Staff {
      \set Staff.vocalName = \markup \smallCaps Melchior
      \set Staff.shortVocalName = \markup \smallCaps Mel
      \clef "bass"
      \relative c' {
        a4 a a a
        a4 a a a
      }
    }
  >>
}
```



When two or more characters share a staff the character's name is usually printed above the staff at the start of every section applying to that character. This can be done with markup. Often a specific font is used for this purpose.

```
\clef "G_8"
c4^\markup \fontsize #1 \smallCaps Kaspar
c c c
\clef "bass"
a4^\markup \fontsize #1 \smallCaps Melchior
a a a
\clef "G_8"
```

```
c4^\markup \fontsize #1 \smallCaps Kaspar
c c c
```



Alternatively, if there are many character changes, it may be easier to set up “instrument” definitions for each character at the top level so that `\instrumentSwitch` can be used to indicate each change.

```
\addInstrumentDefinition #"kaspar"
#`((instrumentTransposition . ,(ly:make-pitch -1 0 0))
  (shortInstrumentName . "Kas.")
  (clefGlyph . "clefs.G")
  (clefOctavation . -7)
  (middleCPosition . 1)
  (clefPosition . -2)
  (instrumentCueName . ,(markup #:fontsize 1 #:smallCaps "Kaspar"))
  (midiInstrument . "voice oohs"))

\addInstrumentDefinition #"melchior"
#`((instrumentTransposition . ,(ly:make-pitch 0 0 0))
  (shortInstrumentName . "Mel.")
  (clefGlyph . "clefs.F")
  (clefOctavation . 0)
  (middleCPosition . 6)
  (clefPosition . 2)
  (instrumentCueName . ,(markup #:fontsize 1 #:smallCaps "Melchior"))
  (midiInstrument . "voice aahs"))

\relative c' {
  \instrumentSwitch "kaspar"
  c4 c c c
  \instrumentSwitch "melchior"
  a4 a a a
  \instrumentSwitch "kaspar"
  c4 c c c
}
```



## See also

Notation Reference: [\[Instrument names\]](#), page 179, [Section A.20 \[Scheme functions\]](#), page 697, [Section 1.8 \[Text\]](#), page 202, [Section A.9 \[Text markup commands\]](#), page 609.

Extending LilyPond: [Section “Markup construction in Scheme” in \*Extending\*](#).

## Musical cues


Musical cues can be inserted in Vocal Scores, Vocal Books and Orchestral Parts to indicate what music in another part immediately precedes an entry. Also, cues are often inserted in the piano reduction in Vocal Scores to indicate what each orchestral instrument is playing. This aids the conductor when a full Conductors' Score is not available.

The basic mechanism for inserting cues is fully explained in the main text, see [\[Quoting other voices\]](#), page 183 and [\[Formatting cue notes\]](#), page 185. But when many cues have to be inserted, for example, as an aid to a conductor in a vocal score, the instrument name must be positioned carefully just before and close to the start of the cue notes. The following example shows how this is done.

```
flute = \relative c'' {
  s4 s4 e g
}
\addQuote "flute" { \flute }

pianoRH = \relative c'' {
  c4. g8
  % position name of cue-ing instrument just before the cue notes,
  % and above the staff
  s1*0^\markup { \right-align { \tiny "Flute" } }
  \cueDuring "flute" #UP { g4 bes4 }
}
pianoLH = \relative c { c4 <c' e> e, <g c> }

\score {
  \new PianoStaff <<
    \new Staff {
      \pianoRH
    }
    \new Staff {
      \clef "bass"
      \pianoLH
    }
  >>
}
```



If a transposing instrument is being quoted the instrument part should specify its key so the conversion of its cue notes will be done automatically. The example below shows this transposition for a B-flat clarinet. The notes in this example are low on the staff so `DOWN` is specified in `\cueDuring` (so the stems are down) and the instrument name is positioned below the staff. Note also that the piano right-hand voice is explicitly declared. This is because the cue notes in this example begin at the start of the first bar and this would otherwise cause the entire piano right-hand notes to be placed in a `CueVoice` context.

```
clarinet = \relative c' {
```

```

\transposition bes
fis4 d d c
}
\addQuote "clarinet" { \clarinet }

pianoRH = \relative c'' {
  \transposition c'
  % position name of cue-ing instrument below the staff
  s1*0_\markup { \right-align { \tiny "Clar." } }
  \cueDuring "clarinet" #DOWN { c4. g8 }
  g4 bes4
}
pianoLH = \relative c { c4 <c' e> e, <g c> }

\score {
  <<
    \new PianoStaff <<
      \new Staff {
        \new Voice {
          \pianoRH
        }
      }
      \new Staff {
        \clef "bass"
        \pianoLH
      }
    >>
  >>
}

```



From these two examples it is clear that inserting many cues in a Vocal Score would be tedious, and the notes of the piano part would become obscured. However, as the following snippet shows, it is possible to define a music function to reduce the amount of typing and to make the piano notes clearer.

## Selected Snippets

### *Adding orchestral cues to a vocal score*

This shows one approach to simplify adding many orchestral cues to the piano reduction in a vocal score. The music function `\cueWhile` takes four arguments: the music from which the cue is to be taken, as defined by `\addQuote`, the name to be inserted before the cue notes, then either `#UP` or `#DOWN` to specify either `\voiceOne` with the name above the staff or `\voiceTwo` with the name below the staff, and finally the piano music in parallel with which the cue notes are to appear. The name of the cued instrument is positioned to the left of the cued notes. Many passages can be cued, but they cannot overlap each other in time.

```

cueWhile =
#(define-music-function
  (parser location instrument name dir music)
  (string? string? ly:dir? ly:music?)
  #{
    \cueDuring $instrument #dir {
      \once \override TextScript #'self-alignment-X = #RIGHT
      \once \override TextScript #'direction = $dir
      s1*0-\markup { \tiny #name }
      $music
    }
  })

flute = \relative c'' {
  \transposition c'
  s4 s4 e g
}
\addQuote "flute" { \flute }

clarinet = \relative c' {
  \transposition bes
  fis4 d d c
}
\addQuote "clarinet" { \clarinet }

singer = \relative c'' { c4. g8 g4 bes4 }
words = \lyricmode { here's the lyr -- ics }

pianoRH = \relative c'' {
  \transposition c'
  \cueWhile "clarinet" "Clar." #DOWN { c4. g8 }
  \cueWhile "flute" "Flute" #UP { g4 bes4 }
}
pianoLH = \relative c { c4 <c' e> e, <g c> }

\score {
  <<
    \new Staff {
      \new Voice = "singer" {
        \singer
      }
    }
    \new Lyrics {
      \lyricsto "singer"
      \words
    }
    \new PianoStaff <<
      \new Staff {
        \new Voice {
          \pianoRH
        }
      }
    }
  }
}

```



```

\new Staff {
  \clef "bass"
  \pianoLH
}
>>
>>
}

```



## See also

Musical Glossary: [Section “cue-notes” in \*Music Glossary\*](#).

Notation Reference: [Section 5.5.1 \[Aligning objects\]](#), page 556, [Section 5.4.2 \[Direction and placement\]](#), page 543, [\[Formatting cue notes\]](#), page 185, [\[Quoting other voices\]](#), page 183, [Section 5.6 \[Using music functions\]](#), page 564.

Snippets: [Section “Vocal music” in \*Snippets\*](#).

Internals Reference: [Section “InstrumentSwitch” in \*Internals Reference\*](#), [Section “CueVoice” in \*Internals Reference\*](#).

## Known issues and warnings

`\cueDuring` automatically inserts a `CueVoice` context and all cue notes are placed in that context. This means it is not possible to have two overlapping sequences of cue notes by this technique. Overlapping sequences could be entered by explicitly declaring separate `CueVoice` contexts and using `\quoteDuring` to extract and insert the cue notes.

## Spoken music

Such effects as ‘parlato’ or ‘Sprechgesang’ require performers to speak without pitch but still with rhythm; these are notated by cross note heads, as demonstrated in [\[Special note heads\]](#), page 32.

## Dialogue over music

Dialogue over music is usually printed over the staves in an italic font, with the start of each phrase keyed in to a particular music moment.

For short interjections a simple markup suffices.

```

a4^\markup { \smallCaps { Alex - } \italic { He's gone } } a a a
a4 a a^\markup { \smallCaps { Bethan - } \italic Where? } a
a4 a a a

```



For longer phrases it may be necessary to expand the music to make the words fit neatly. There is no provision in LilyPond to do this fully automatically, and some manual intervention to layout the page will be necessary.

For long phrases or for passages with a lot of closely packed dialogue, using a Lyrics context will give better results. The Lyrics context should not be associated with a music Voice; instead each section of dialogue should be given an explicit duration. If there is a gap in the dialogue, the final word should be separated from the rest and the duration split between them so that the underlying music spaces out smoothly.


If the dialogue extends for more than one line it will be necessary to manually insert `\breaks` and adjust the placing of the dialogue to avoid running into the right margin. The final word of the last measure on a line should also be separated out, as above.

Here is an example illustrating how this might be done.

```
music = \relative c'' {
  \repeat unfold 3 { a4 a a a }
}

dialogue = \lyricmode {
  \markup {
    \fontsize #1 \upright \smallCaps Abe:
    "Say this over measures one and"
  }4*7
  "two"4 |
  \break
  "and this over measure"4*3
  "three"4 |
}

\score {
  <<
    \new Lyrics \with {
      \override LyricText #'font-shape = #'italic
      \override LyricText #'self-alignment-X = #LEFT
    }
    { \dialogue }
    \new Staff {
      \new Voice { \music }
    }
  >>
}
```



## See also

Notation Reference: [Manual syllable durations], page 232, Section 1.8 [Text], page 202.

Internal Reference: Section “LyricText” in *Internals Reference*.

### 2.1.7 Chants psalms and hymns

The music and words for chants, psalms and hymns usually follow a well-established format in any particular church. Although the formats may differ from church to church the type-setting problems which arise are broadly similar, and are covered in this section.

## References for chants and psalms

Typesetting Gregorian chant in various styles of ancient notation is described in Section 2.9 [Ancient notation], page 388.

## See also

Notation reference: Section 2.9 [Ancient notation], page 388.

Snippets: Section “Vocal music” in *Snippets*.

## Setting a chant

Modern chant settings use modern notation with varying numbers of elements taken from ancient notation. Some of the elements and methods to consider are shown here.

Chants often use quarter notes without stems to indicate the pitch, with the rhythm being taken from the spoken rhythm of the words.

```
stemOff = { \override Staff.Stem #'transparent = ##t }
```

```
\relative c' {
  \stemOff
  a'4 b c2 |
}
```



Chants often omit the bar lines or use shortened or dotted bar lines to indicate pauses in the music. To omit all bar lines from all staves remove the bar line engraver completely:

```
\score {
  \new StaffGroup <<
    \new Staff {
      \relative c'' {
        a4 b c2 |
        a4 b c2 |
        a4 b c2 |
      }
    }
  \new Staff {
    \relative c'' {
      a4 b c2 |
      a4 b c2 |
      a4 b c2 |
    }
  }
}
```

```

    }
  }
  >>
  \layout {
    \context {
      \Staff
      \remove Bar_engraver
    }
  }
}

```



Bar lines can also be removed on a staff-by-staff basis:

```

\score {
  \new ChoirStaff <<
    \new Staff
    \with { \remove Bar_engraver } {
      \relative c'' {
        a4 b c2 |
        a4 b c2 |
        a4 b c2 |
      }
    }
  \new Staff {
    \relative c'' {
      a4 b c2 |
      a4 b c2 |
      a4 b c2 |
    }
  }
}
>>
}

```



To remove bar lines from just a section of music treat it as a cadenza. If the section is long you may need to insert dummy bar lines with `\bar ""` to show where the line should break.

```

a4 b c2 |
\cadenzaOn
a4 b c2

```

```

a4 b c2
\bar ""
a4 b c2
a4 b c2
\cadenzaOff
a4 b c2 |
a4 b c2 |

```



Rests or pauses in chants can be indicated by modified bar lines.

```

a4
\cadenzaOn
b c2
a4 b c2
\bar "'"
a4 b c2
a4 b c2
\bar ":"
a4 b c2
\bar "dashed"
a4 b c2
\bar "||"

```



Alternatively, the notation used in Gregorian chant for pauses or rests is sometimes used even though the rest of the notation is modern. This uses a modified `\breathe` mark:

```

divisioMinima = {
  \once \override BreathingSign #'stencil = #ly:breathing-sign::divisio-minima
  \once \override BreathingSign #'Y-offset = #0
  \breathe
}
divisioMaior = {
  \once \override BreathingSign #'stencil = #ly:breathing-sign::divisio-maior
  \once \override BreathingSign #'Y-offset = #0
  \breathe
}
divisioMaxima = {
  \once \override BreathingSign #'stencil = #ly:breathing-sign::divisio-maxima
  \once \override BreathingSign #'Y-offset = #0
  \breathe
}
finalis = {
  \once \override BreathingSign #'stencil = #ly:breathing-sign::finalis
  \once \override BreathingSign #'Y-offset = #0
  \breathe
}

```

```
\score {
  \new Staff {
    \relative c'' {
      a4 b c2 |
      a4 b c2 |
      a4 b c2 |
    }
  }
}

\layout {
  \context {
    \Staff
    \remove Bar_engraver
    \remove Time_signature_engraver
    \remove Clef_engraver
  }
}
```



Chants for psalms in the Anglican tradition are usually either *single*, with 7 bars of music, or *double*, with two lots of 7 bars. Each group of 7 bars is divided into two halves, corresponding to the two halves of each verse, usually separated by a double bar line. Only whole and half notes are used. The 1st bar in each half always contains a single chord of whole notes. This is the “reciting note”. Chants are usually centered on the page.

```

SopranoMusic = \relative g' {
  g1 | c2 b | a1 | \bar "||"
  a1 | d2 c | c b | c1 | \bar "||"
}

AltoMusic = \relative c' {
  e1 | g2 g | f1 |
  f1 | f2 e | d d | e1 |
}

TenorMusic = \relative a {
  c1 | c2 c | c1 |
  d1 | g,2 g | g g | g1 |
}

BassMusic = \relative c {
  c1 | e2 e | f1 |
  d1 | b2 c | g' g | c,1 |
}

global = {
  \time 2/2
}


% Use markup to center the chant on the page
\markup {
  \fill-line {
    \score { % centered
      <<
        \new ChoirStaff <<
          \new Staff <<
            \global
            \clef "treble"
            \new Voice = "Soprano" <<
              \voiceOne
              \SopranoMusic
            >>
            \new Voice = "Alto" <<
              \voiceTwo
              \AltoMusic
            >>
          >>
        \new Staff <<
          \clef "bass"
          \global
          \new Voice = "Tenor" <<
            \voiceOne
            \TenorMusic
          >>
          \new Voice = "Bass" <<
            \voiceTwo
            \BassMusic
          >>
        >>
      >>
    }
  }
}

```

```

>>
>>
>>
>>
\layout {
  \context {
    \Score
    \override SpacingSpanner
      #'base-shortest-duration = #(ly:make-moment 1 2)
  }
  \context {
    \Staff
    \remove "Time_signature_engraver"
  }
}
} % End score
} % End markup

```



Some other approaches to setting such a chant are shown in the first of the following snippets.

## Selected Snippets

### *Chant or psalms notation*

This form of notation is used for the chant of the Psalms, where verses aren't always the same length.


```

stemOn = { \revert Staff.Stem #'transparent \revert Staff.Flag #'transparent }
stemOff = { \override Staff.Stem #'transparent = ##t \override Staff.Flag #'transparent = ##f }

\score {
  \new Staff \with { \remove "Time_signature_engraver" }
  {
    \key g \minor
    \cadenzaOn
    \stemOff a'\breve bes'4 g'4
    \stemOn a'2 \bar "||"
    \stemOff a'\breve g'4 a'4
    \stemOn f'2 \bar "||"
    \stemOff a'\breve^\markup { \italic flexe }
    \stemOn g'2 \bar "||"
  }
}

```





Canticles and other liturgical texts may be set more freely, and may use notational elements from ancient music. Often the words are shown underneath and aligned with the notes. If so, the notes are spaced in accordance with the syllables rather than the notes' durations.

*Ancient notation template – modern transcription of gregorian music*

This example demonstrates how to do modern transcription of Gregorian music. Gregorian music has no measure, no stems; it uses only half and quarter note heads, and special marks, indicating rests of different length.

```
\include "gregorian.ly"

chant = \relative c' {
  \set Score.timing = ##f
  f4 a2 \divisioMinima
  g4 b a2 f2 \divisioMaior
  g4( f) f( g) a2 \finalis
}

verba = \lyricmode {
  Lo -- rem ip -- sum do -- lor sit a -- met
}

\score {
  \new Staff <<
    \new Voice = "melody" \chant
    \new Lyrics = "one" \lyricsto melody \verba
  >>
  \layout {
    \context {
      \Staff
      \remove "Time_signature_engraver"
      \remove "Bar_engraver"
      \override Stem #'transparent = ##t
      \override Flag #'transparent = ##t
    }
    \context {
      \Voice
      \override Stem #'length = #0
    }
    \context {
      \Score
      barAlways = ##t
    }
  }
}
```



## See also

Learning Manual: [Section “Visibility and color of objects” in \*Learning Manual\*](#), [Section “Vocal ensembles” in \*Learning Manual\*](#).

Notation Reference: [Section 2.9 \[Ancient notation\]](#), page 388, [\[Bar lines\]](#), page 85, [Section 5.1.4 \[Modifying context plug-ins\]](#), page 524, [Section 2.9.4 \[Typesetting Gregorian chant\]](#), page 399, [\[Unmetered music\]](#), page 64, [Section 5.4.6 \[Visibility of objects\]](#), page 550.

## Pointing a psalm

The words to an Anglican psalm are usually printed in separate verses centered underneath the chant.

Single chants (with 7 bars) are repeated for every verse. Double chants (with 14 bars) are repeated for every pair of verses. Marks are inserted in the words to show how they should be fitted to the chant. Each verse is divided into two halves. A colon is usually used to indicate this division. This corresponds to the double bar line in the music. The words before the colon are sung to the first three bars of music; the words after the colon are sung to the last four bars.

Single bar lines (or in some psalters an inverted comma or similar symbol) are inserted between words to indicate where the bar lines in the music fall. In markup mode a single bar line can be entered with the bar check symbol, |.

```
\markup {
  \fill-line {
    \column {
      \left-align {
        \line { 0 come let us sing | unto the | Lord : let }
        \line { us heartily rejoice in the | strength of | our }
        \line { sal- | -vation. }
      }
    }
  }
}
```

O come let us sing | unto the | Lord : let  
us heartily rejoice in the | strength of | our  
sal- | -vation.

Other symbols may require glyphs from the `fetaMusic` fonts. For details, see [Section 1.8.3 \[Fonts\]](#), page 223.

```
tick = \markup {
  \raise #1 \fontsize #-5 \musicglyph #"scripts.rvarcomma"
}
\markup {
  \fill-line {
    \column {
      \left-align {
        \line { 0 come let us sing \tick unto the \tick Lord : let }
        \line {
          us heartily rejoice in the \tick strength of \tick our
        }
        \line { sal \tick vation. }
      }
    }
  }
}
```

```
}
}
```

O come let us sing' unto the' Lord : let  
us heartily rejoice in the' strength of' our  
sal' vation.

Where there is one whole note in a bar all the words corresponding to that bar are recited on that one note in speech rhythm. Where there are two notes in a bar there will usually be only one or two corresponding syllables. If there are more than two syllables a dot is usually inserted to indicate where the change in note occurs.

```
dot = \markup {
  \raise #0.7 \musicglyph #"dots.dot"
}
tick = \markup {
  \raise #1 \fontsize #-5 \musicglyph #"scripts.rvarcomma"
}
\markup {
  \fill-line {
    \column {
      \left-align {
        \line {
          O come let us sing \tick unto \dot the \tick Lord : let
        }
        \line {
          us heartily rejoice in the \tick strength of \tick our
        }
        \line { sal \tick vation. }
      }
    }
  }
}
```

O come let us sing' unto • the' Lord : let  
us heartily rejoice in the' strength of' our  
sal' vation.

In some psalters an asterisk is used to indicate a break in a recited section instead of a comma, and stressed or slightly lengthened syllables are indicated in bold text.

```
dot = \markup {
  \raise #0.7 \musicglyph #"dots.dot"
}
tick = \markup {
  \raise #1 \fontsize #-5 \musicglyph #"scripts.rvarcomma"
}
\markup {
  \fill-line {
    \column {
      \left-align {
        \line { Today if ye will hear his voice * }
        \line {

```

```

\concat { \bold hard en }
| not your | hearts : as in the pro-
}
\line { vocation * and as in the \bold day of tempt- | }
\line { -ation | in the | wilderness. }
}
}
}
}
}

```

Today if ye will hear his voice \*  
**harden** | not your | hearts : as in the pro-  
vocation \* and as in the **day** of tempt- |  
-ation | in the | wilderness.

In other psalters an accent is placed over the syllable to indicate stress.

```

tick = \markup {
  \raise #2 \fontsize #-5 \musicglyph #"scripts.rvarcomma"
}
\markup {
  \fill-line {
    \column {
      \left-align {
        \line {
          O come let us \concat {
            si \combine \tick ng
          }
          | unto the | Lord : let
        }
        \line {
          us heartily \concat {
            rejo \combine \tick ice
          }
          in the | strength of | our
        }
        \line { sal- | -vation. }
      }
    }
  }
}
}
}
}

```

O come let us <sup>ˈ</sup>sing | unto the | Lord : let  
us heartily re<sup>ˈ</sup>joice in the | strength of | our  
sal- | -vation.

The use of markup to center text, and arrange lines in columns is described in [Section 1.8.2 \[Formatting text\]](#), page 210.

Most of these elements are shown in one or other of the two verses in the template, see “Psalms” in [Section “Vocal ensembles” in Learning Manual](#).

## See also

Learning Manual: [Section “Vocal ensembles” in \*Learning Manual\*](#).

Notation Reference: [Section 1.8.3 \[Fonts\]](#), page 223, [Section 1.8.2 \[Formatting text\]](#), page 210.

## Partial measures in hymn tunes

Hymn tunes frequently start and end every line of music with partial measures so that each line of music corresponds exactly with a line of text. This requires a `\partial` command at the start of the music and `\bar "|"` or `\bar "||"` commands at the end of each line.

### *Hymn template*

This code shows one way of setting out a hymn tune when each line starts and ends with a partial measure. It also shows how to add the verses as stand-alone text under the music.

```
Timeline = {
  \time 4/4
  \tempo 4=96
  \partial 2
  s2 | s1 | s2 \breathe s2 | s1 | s2 \bar "||" \break
  s2 | s1 | s2 \breathe s2 | s1 | s2 \bar "||"
}

SopranoMusic = \relative g' {
  g4 g | g g g g | g g g g | g g g g | g2
  g4 g | g g g g | g g g g | g g g g | g2
}

AltoMusic = \relative c' {
  d4 d | d d d d | d d d d | d d d d | d2
  d4 d | d d d d | d d d d | d d d d | d2
}

TenorMusic = \relative a {
  b4 b | b b b b | b b b b | b b b b | b2
  b4 b | b b b b | b b b b | b b b b | b2
}

BassMusic = \relative g {
  g4 g | g g g g | g g g g | g g g g | g2
  g4 g | g g g g | g g g g | g g g g | g2
}

global = {
  \key g \major
}

\score { % Start score
  <<
    \new PianoStaff << % Start pianostaff
      \new Staff << % Start Staff = RH
        \global
        \clef "treble"
        \new Voice = "Soprano" << % Start Voice = "Soprano"
          \Timeline
```


```

        \voiceOne
        \SopranoMusic
    >> % End Voice = "Soprano"
    \new Voice = "Alto" << % Start Voice = "Alto"
        \Timeline
        \voiceTwo
        \AltoMusic
    >> % End Voice = "Alto"
    >> % End Staff = RH
    \new Staff << % Start Staff = LH
        \global
        \clef "bass"
        \new Voice = "Tenor" << % Start Voice = "Tenor"
            \Timeline
            \voiceOne
            \TenorMusic
        >> % End Voice = "Tenor"
        \new Voice = "Bass" << % Start Voice = "Bass"
            \Timeline
            \voiceTwo
            \BassMusic
        >> % End Voice = "Bass"
    >> % End Staff = LH
    >> % End pianostaff
>>
} % End score

\markup {
  \fill-line {
    ""
    {
      \column {
        \left-align {
          "This is line one of the first verse"
          "This is line two of the same"
          "And here's line three of the first verse"
          "And the last line of the same"
        }
      }
    }
  }
}

\paper { % Start paper block
  indent = 0 % don't indent first system
  line-width = 130 % shorten line length to suit music
} % End paper block

```



This is line one of the first verse  
 This is line two of the same  
 And here's line three of the first verse  
 And the last line of the same

### 2.1.8 Ancient vocal music

Ancient vocal music is supported, as explained in [Section 2.9 \[Ancient notation\]](#), page 388.

See also

Notation Reference: [Section 2.9 \[Ancient notation\]](#), page 388.

## 2.2 Keyboard and other multi-staff instruments

This section discusses several aspects of music notation that are unique to keyboard instruments and other instruments notated on many staves, such as harps and vibraphones. For the purposes of this section this entire group of multi-staff instruments is called “keyboards” for short, even though some of them do not have a keyboard.

### 2.2.1 Common notation for keyboards

This section discusses notation issues that may arise for most keyboard instruments.

#### References for keyboards

Keyboard instruments are usually notated with Piano staves. These are two or more normal staves coupled with a brace. The same notation is also used for other keyed instruments. Organ music is normally written with two staves inside a `PianoStaff` group and third, normal staff for the pedals.

The staves in keyboard music are largely independent, but sometimes voices can cross between the two staves. This section discusses notation techniques particular to keyboard music.

Several common issues in keyboard music are covered elsewhere:

- Keyboard music usually contains multiple voices and the number of voices may change regularly; this is described in [\[Collision resolution\]](#), page 150.
- Keyboard music can be written in parallel, as described in [\[Writing music in parallel\]](#), page 159.
- Dynamics may be placed in a `Dynamics` context, between the two `Staff` contexts to align the dynamic marks on a horizontal line centered between the staves; see [\[Dynamics\]](#), page 107.
- Fingerings are indicated with [\[Fingering instructions\]](#), page 192.
- Organ pedal indications are inserted as articulations, see [Section A.12 \[List of articulations\]](#), page 654.
- Vertical grid lines can be shown with [\[Grid lines\]](#), page 199.
- Keyboard music often contains *Laissez vibrer* ties as well as ties on arpeggios and tremolos, described in [\[Ties\]](#), page 46.
- Placing arpeggios across multiple voices and staves is covered in [\[Arpeggio\]](#), page 122.
- Tremolo marks are described in [\[Tremolo repeats\]](#), page 139.
- Several of the tweaks that can occur in keyboard music are demonstrated in [Section “Real music example” in \*Learning Manual\*](#).
- Hidden notes can be used to produce ties that cross voices, as shown in [Section “Other uses for tweaks” in \*Learning Manual\*](#).

#### See also

Learning Manual: [Section “Real music example” in \*Learning Manual\*](#), [Section “Other uses for tweaks” in \*Learning Manual\*](#).

Notation Reference: [\[Grouping staves\]](#), page 163, [\[Instrument names\]](#), page 179, [\[Collision resolution\]](#), page 150, [\[Writing music in parallel\]](#), page 159, [\[Fingering instructions\]](#), page 192, [Section A.12 \[List of articulations\]](#), page 654, [\[Grid lines\]](#), page 199, [\[Ties\]](#), page 46, [\[Arpeggio\]](#), page 122, [\[Tremolo repeats\]](#), page 139.

Internals Reference: [Section “PianoStaff” in \*Internals Reference\*](#).

Snippets: [Section “Keyboards” in \*Snippets\*](#).

#### Changing staff manually

Voices can be switched between staves manually, using the command

```
\change Staff = staffname
```


The string *staffname* is the name of the staff. It switches the current voice from its current staff to the staff called *staffname*. Typical values for *staffname* are "up" and "down", or "RH" and "LH".



The staff to which the voice is being switched must exist at the time of the switch. If necessary, staves should be “kept alive”, see [Section 5.1.3 \[Keeping contexts alive\]](#), page 522.

Cross-staff notes are beamed automatically:


```
\new PianoStaff <<
  \new Staff = "up" {
    <e' c'>8
    \change Staff = "down"
    g8 fis g
    \change Staff = "up"
    <g'' c''>8
    \change Staff = "down"
    e8 dis e
    \change Staff = "up"
  }
  \new Staff = "down" {
    \clef bass
    % keep staff alive
    s1
  }
>>
```



If the beaming needs to be tweaked, make any changes to the stem directions first. The beam positions are then measured from the center of the staff that is closest to the beam. For a simple example of beam tweaking, see [Section “Fixing overlapping notation” in \*Learning Manual\*](#).

Overlapping notation can result when voices cross staves:

```
\new PianoStaff <<
  \new Staff = "up" {
    \voiceOne
    % Make space for fingering in the cross-staff voice
    \once\override DynamicLineSpanner #'staff-padding = #3.4
    e''2\p\< d''\> s1*0\!
  }
  \new Staff = "down" <<
  {
    \clef bass
    s4. e,8\rest g,2\rest
  } \ {
    c8\ ( g c'
    \change Staff = "up"
    e' g' b'-3 a' g'\ )
  }
>>
>>
```



The stem and slur overlap the intervening line of dynamics because automatic collision resolution is suspended for beams, slurs and other spanners that connect notes on different staves, as well as for stems and articulations if their placement is affected by a cross-staff spanner. The resulting collisions must be resolved manually, where necessary, using the methods in [Section “Fixing overlapping notation”](#) in *Learning Manual*.

## See also

Learning Manual: [Section “Fixing overlapping notation”](#) in *Learning Manual*.

Notation Reference: [\[Stems\]](#), page 197, [\[Automatic beams\]](#), page 72, [Section 5.1.3 \[Keeping contexts alive\]](#), page 522.

Snippets: [Section “Keyboards”](#) in *Snippets*.

Internals Reference: [Section “Beam”](#) in *Internals Reference*, [Section “ContextChange”](#) in *Internals Reference*.

## Known issues and warnings

Beam collision avoidance does not work for automatic beams that end right before a change in staff. In this case use manual beams.

## Changing staff automatically

Voices can be made to switch automatically between the top and the bottom staff. The syntax for this is

```
\autochange ...music...
```

This will create two staves inside the current staff group (usually a `PianoStaff`), called "up" and "down". The lower staff will be in the bass clef by default. The autochanger switches on the basis of the pitch (middle C is the turning point), and it looks ahead skipping over rests to switch in advance.

```
\new PianoStaff {
  \autochange {
    g4 a b c'
    d'4 r a g
  }
}
```




A `\relative` section that is outside of `\autochange` has no effect on the pitches of the music, so if necessary, put `\relative` inside `\autochange`.

If additional control is needed over the individual staves, they can be created manually with the names "up" and "down". The `\autochange` command will then switch its voice between the existing staves.

**Note:** If staves are created manually, they *must* be named "up" and "down".

For example, staves must be created manually in order to place a key signature in the lower staff:

```
\new PianoStaff <<
  \new Staff = "up" {
    \new Voice = "melOne" {
      \key g \major
      \autochange \relative c' {
        g8 b a c b d c e
        d8 r fis, g a2
      }
    }
  }
  \new Staff = "down" {
    \key g \major
    \clef bass
  }
>>
```



## See also

Notation Reference: [\[Changing staff manually\]](#), page 286.

Snippets: [Section “Keyboards”](#) in *Snippets*.

Internals Reference: [Section “AutoChangeMusic”](#) in *Internals Reference*.

## Known issues and warnings

The staff switches may not end up in optimal places. For high quality output, staff switches should be specified manually.


Chords will not be split across the staves; they will be assigned to a staff based on the first note named in the chord construct.

## Staff-change lines

Whenever a voice switches to another staff, a line connecting the notes can be printed automatically:

```
\new PianoStaff <<
  \new Staff = "one" {
    \showStaffSwitch
    c1
    \change Staff = "two"
    b2 a
  }
  \new Staff = "two" {
    \clef bass
    s1*2
  }
>>
```

```
}
>>
```



## Predefined commands

`\showStaffSwitch`, `\hideStaffSwitch`.

## See also

Snippets: [Section “Keyboards” in \*Snippets\*](#).

Internals Reference: [Section “Note\\_head\\_line\\_engraver” in \*Internals Reference\*](#), [Section “VoiceFollower” in \*Internals Reference\*](#).

## Cross-staff stems

Chords that cross staves may be produced:

```
\new PianoStaff <<
  \new Staff {
    \relative c' {
      f8 e4 d8 d f e4
    }
  }
  \new Staff {
    \relative c' {
      << {
        \clef bass
        % stems may overlap the other staff
        \override Stem #'cross-staff = ##t
        % extend the stems to reach the other staff
        \override Stem #'length = #12
        % do not print extra flags
        \override Flag #'style = #'no-flag
        % prevent beaming as needed
        a8 g4 f8 f bes\noBeam g4
      }
      \\
      {
        f,2 bes4 c
      }
    } >>
  }
>>
```




## Selected Snippets

*Indicating cross-staff chords with arpeggio bracket*

An arpeggio bracket can indicate that notes on two different staves are to be played with the same hand. In order to do this, the `PianoStaff` must be set to accept cross-staff arpeggios and the arpeggios must be set to the bracket shape in the `PianoStaff` context.

(Debussy, Les collines d'Anacapri, m. 65)

```
\new PianoStaff <<
  \set PianoStaff.connectArpeggios = ##t
  \override PianoStaff.Arpeggio #'stencil = #ly:arpeggio::brew-chord-bracket
  \new Staff {
    \relative c' {
      \key b \major
      \time 6/8
      b8-.(\arpeggio fis'-.\> cis-. e-. gis-. b-.)\!\fermata^\laissezVibrer
      \bar "||"
    }
  }
  \new Staff {
    \relative c' {
      \clef bass
      \key b \major
      <<
        {
          <a e cis>2.\arpeggio
        }
        \\\
        {
          <a, e a,>2.
        }
      >>
    }
  }
>>
```



## See also

Snippets: [Section “Keyboards” in \*Snippets\*](#).

Internals Reference: [Section “Stem” in \*Internals Reference\*](#).


### 2.2.2 Piano

This section discusses notation issues that relate most directly to the piano.

#### Piano pedals

Pianos generally have three pedals that alter the way sound is produced: *sustain*, *sostenuto* (*sos.*), and *una corda* (*U.C.*). Sustain pedals are also found on vibraphones and celestas.

```
c4\sustainOn d e g
<c, f a>1\sustainOff
c4\sostenutoOn e g c,
<bes d f>1\sostenutoOff
c4\unaCorda d e g
<d fis a>1\treCorde
```



There are three styles of pedal indications: text, bracket, and mixed. The sustain pedal and the una corda pedal use the text style by default while the sostenuto pedal uses mixed by default.

```
c4\sustainOn g c2\sustainOff
\set Staff.pedalSustainStyle = #'mixed
c4\sustainOn g c d
d\sustainOff\sustainOn g, c2\sustainOff
\set Staff.pedalSustainStyle = #'bracket
c4\sustainOn g c d
d\sustainOff\sustainOn g, c2
\bar "|."
```



The placement of the pedal commands matches the physical movement of the sustain pedal during piano performance. Pedalling to the final bar line is indicated by omitting the final pedal off command.

Pedal indications may be placed in a `Dynamics` context, which aligns them on a horizontal line.

## See also

Notation Reference: [\[Ties\]](#), page 46.

Snippets: [Section “Keyboards” in \*Snippets\*](#).

Internals Reference: [Section “SustainPedal” in \*Internals Reference\*](#), [Section “SustainPedalLineSpanner” in \*Internals Reference\*](#), [Section “SustainEvent” in \*Internals Reference\*](#),

Section “SostenutoPedal” in *Internals Reference*, Section “SostenutoPedalLineSpanner” in *Internals Reference*, Section “SostenutoEvent” in *Internals Reference*, Section “UnaCordaPedal” in *Internals Reference*, Section “UnaCordaPedalLineSpanner” in *Internals Reference*, Section “UnaCordaEvent” in *Internals Reference*, Section “PianoPedalBracket” in *Internals Reference*, Section “Piano\_pedal\_engraver” in *Internals Reference*.

### 2.2.3 Accordion

This section discusses notation that is unique to the accordion.

#### Discant symbols

Accordions are often built with more than one set of reeds that may be in unison with, an octave above, or an octave below the written pitch. Each accordion maker has different names for the *shifts* that select the various reed combinations, such as *oboe*, *musette*, or *bandonium*, so a system of symbols has come into use to simplify the performance instructions.

#### Selected Snippets

*Accordion-discant symbols*

Accordion discant-specific symbols are added using `\markup`. The vertical placement of the symbols can be tweaked by changing the `\raise` arguments.

```
discant = \markup {
  \musicglyph #"accordion.discant"
}
dot = \markup {
  \musicglyph #"accordion.dot"
}
```

```
\layout { ragged-right = ##t }
```

```
% 16 voets register
accBasson = ^\markup {
  \combine
  \discant
  \raise #0.5 \dot
}
```

```
% een korig 8 en 16 voets register
accBandon = ^\markup {
  \combine
  \discant
  \combine
  \raise #0.5 \dot
  \raise #1.5 \dot
}
```

```
accVCello = ^\markup {
  \combine
  \discant
  \combine
  \raise #0.5 \dot
  \combine
  \raise #1.5 \dot
}
```

```

        \translate #'(1 . 0) \raise #1.5 \dot
    }

% 4-8-16 voets register
accHarmon = ^\markup {
    \combine
    \discant
    \combine
    \raise #0.5 \dot
    \combine
    \raise #1.5 \dot
    \raise #2.5 \dot
}

accTrombon = ^\markup {
    \combine
    \discant
    \combine
    \raise #0.5 \dot
    \combine
    \raise #1.5 \dot
    \combine
    \translate #'(1 . 0) \raise #1.5 \dot
    \translate #'(-1 . 0) \raise #1.5 \dot
}

% eenkorig 4 en 16 voets register
accOrgan = ^\markup {
    \combine
    \discant
    \combine
    \raise #0.5 \dot
    \raise #2.5 \dot
}

accMaster = ^\markup {
    \combine
    \discant
    \combine
    \raise #0.5 \dot
    \combine
    \raise #1.5 \dot
    \combine
    \translate #'(1 . 0) \raise #1.5 \dot
    \combine
    \translate #'(-1 . 0) \raise #1.5 \dot
    \raise #2.5 \dot
}

accAccord = ^\markup {
    \combine
    \discant

```



```

\combine
\raise #1.5 \dot
\combine
\translate #'(1 . 0) \raise #1.5 \dot
\combine
\translate #'(-1 . 0) \raise #1.5 \dot
\raise #2.5 \dot
}

```

```

accMusette = ^\markup {
\combine
\discant
\combine
\raise #1.5 \dot
\combine
\translate #'(1 . 0) \raise #1.5 \dot
\translate #'(-1 . 0) \raise #1.5 \dot
}

```

```

accCeleste = ^\markup {
\combine
\discant
\combine
\raise #1.5 \dot
\translate #'(-1 . 0) \raise #1.5 \dot
}

```

```

accOboe = ^\markup {
\combine
\discant
\combine
\raise #1.5 \dot
\raise #2.5 \dot
}

```

```

accClarin = ^\markup {
\combine
\discant
\raise #1.5 \dot
}

```

```

accPiccolo = ^\markup {
\combine
\discant
\raise #2.5 \dot
}

```

```

accViolin = ^\markup {
\combine
\discant
\combine
\raise #1.5 \dot
}


```

```

\combine
  \translate #'(1 . 0) \raise #1.5 \dot
  \raise #2.5 \dot
}

\relative c'' {
  c4 d\accBasson e f
  c4 d\accBandon e f
  c4 d\accVCello e f
  c4 d\accHarmon e f
  c4 d\accTrombon e f
  \break
  c4 d\accOrgan e f
  c4 d\accMaster e f
  c4 d\accAccord e f
  c4 d\accMusette e f
  c4 d\accCeleste e f
  \break
  c4 d\accOboe e f
  c4 d\accClarinet e f
  c4 d\accPiccolo e f
  c4 d\accViolin e f
}

```



See also

Snippets: [Section “Keyboards” in \*Snippets\*](#).

## 2.2.4 Harp

This section discusses notation issues that are unique to the harp.

### References for harps

Some common characteristics of harp music are covered elsewhere:

- The glissando is the most characteristic harp technique, [\[Glissando\]](#), page 120.
- A *bisbigliando* is written as a tremelo [\[Tremolo repeats\]](#), page 139.
- Natural harmonics are covered under [\[Harmonics\]](#), page 299.
- For directional arpeggios and non-arpeggios, see [\[Arpeggio\]](#), page 122.

## See also

Notation Reference: [Tremolo repeats], page 139, [Glissando], page 120, [Arpeggio], page 122, [Harmonics], page 299.

## Harp pedals


Harp harps have seven strings per octave that may be sounded at the natural, flattened, or sharpened pitch. In lever harps, each string is adjusted individually, but in pedal harps every string with the same pitch name is controlled by a single pedal. From the player's left to right, the pedals are D, C, and B on the left and E, F, G, and A on the right. The position of the pedals may be indicated with text marks:

```
\textLengthOn
cis1_\markup \concat \vcenter {
  [D \flat C \sharp B | E \sharp F \sharp G A \flat] }
c!1_\markup \concat \vcenter {
  [ C \natural ] }
```



or pedal diagrams:

```
\textLengthOn
cis1_\markup { \harp-pedal #"^v-|vv-^" }
c!1_\markup { \harp-pedal #"^o--|vv-^" }
```




The `\harp-pedal` command accepts a string of characters, where `^` is the highest pedal position (flattened pitch), `-` is the middle pedal position (natural pitch), `v` is the lowest pedal position (sharpened pitch), and `|` is the divider. A prefixed `o` will circle the following pedal symbol.

## See also

Notation Reference: [Text scripts], page 202, Section A.9.5 [Instrument Specific Markup], page 642.

## 2.3 Unfretted string instruments





This section provides information and references which are helpful when writing for unfretted string instruments, principally orchestral strings.

### 2.3.1 Common notation for unfretted strings

There is little specialist notation for unfretted string instruments. The music is notated on a single staff, and usually only a single voice is required. Two voices might be required for some double-stopped or divisi passages.

#### References for unfretted strings

Most of the notation which is useful for orchestral strings and other bowed instruments is covered elsewhere:

- Textual indications such as “pizz.” and “arco” are added as simple text – see [Text scripts], page 202.
- Fingerings, including the thumb indication, are described in [Fingering instructions], page 192.
- Double stopping is normally indicated by writing a chord, see [Chord notes], page 142. Directives for playing chords may be added, see [Arpeggio], page 122.
- A template for a string quartet can be found in Section “String quartet” in *Learning Manual*. Others are shown in the snippets.

#### See also

Learning Manual: Section “String quartet” in *Learning Manual*.

Notation Reference: [Text scripts], page 202, [Fingering instructions], page 192, [Chord notes], page 142, [Arpeggio], page 122.

Snippets: Section “Unfretted strings” in *Snippets*.

#### Bowing indications

Bowing indications are created as articulations, which are described in [Articulations and ornaments], page 105.


The bowing commands, `\upbow` and `\downbow`, are used with slurs as follows:

```
c4(\downbow d) e(\upbow f)
```



and the following example shows three ways in which an open A string on a violin might be indicated:

```
a4 \open
a^\markup { \teeny "II" }
a2^\markup { \small "sul A" }
```



## Predefined commands

`\downbow`, `\upbow`, `\open`.

## See also

Notation Reference: [\[Articulations and ornamentations\]](#), page 105, [\[Slurs\]](#), page 114.

## Harmonics

### *Natural harmonics*

Natural harmonics can be notated in several ways. A diamond-shaped note head generally means to touch the string where you would stop the note if it were not a diamond.

```
d4 e4.
\harmonicsOn
d8 e e
d4 e4.
\harmonicsOff
d8 e e
```



Alternatively a normal note head is shown at the pitch to be sounded together with a small circle to indicate it should be played as a harmonic:

```
d2^\flageolet d_\flageolet
```



A smaller circle may be created, see the snippet list in [\[References for unfretted strings\]](#), page 298.

### *Artificial harmonics*

Artificial harmonics are notated with two notes, one with a normal note head indicating the stopped position and one with an open diamond note head to indicate the harmonic position.

Artificial harmonics indicated with `\harmonic` do not show the dots. The context property `harmonicDots` should be set if dots are required.

```
<e a\harmonic>2. <c g'\harmonic>4
\set harmonicDots = ##t
<e a\harmonic>2. <c g'\harmonic>4
```



**Note:** `\harmonic` **must** be placed inside a chord construct even if there is only a single note. Normally `\harmonicsOn` would be used in this situation.

## See also

Music Glossary: [Section “harmonics” in Music Glossary](#).

Notation Reference: [\[Special note heads\]](#), page 32, [\[References for unfretted strings\]](#), page 298.

## Snap (Bartók) pizzicato


A *snap pizzicato* (also known as “Bartok pizz”) is a type of pizzicato where the string is deliberately plucked upwards (rather than sideways) such that it hits the fingerboard.

`c4\snappizzicato`



`<c' e g>4\snappizzicato`

`<c' e g>4^\snappizzicato`

`<c, e g>4_\snappizzicato`



## 2.4 Fretted string instruments



This section discusses several aspects of music notation that are unique to fretted string instruments.

### 2.4.1 Common notation for fretted strings

This section discusses common notation that is unique to fretted string instruments.

## References for fretted strings

Music for fretted string instruments is normally notated on a single staff, either in traditional music notation or in tablature. Sometimes the two types are combined, and it is especially common in popular music to use chord diagrams above a staff of traditional notation. The guitar and the banjo are transposing instruments, sounding an octave lower than written. Scores for these instruments should use the "treble\_8" clef (or `\transposition c` to get correct MIDI output). Some other elements pertinent to fretted string instruments are covered elsewhere:

- Fingerings are indicated as shown in [Fingering instructions], page 192.
- Instructions for *Laissez vibrer* ties as well as ties on arpeggios and tremolos can be found in [Ties], page 46.
- Instructions for handling multiple voices can be found in [Collision resolution], page 150.
- Instructions for indicating harmonics can be found in [Harmonics], page 299.

## See also


Notation Reference: [Fingering instructions], page 192, [Ties], page 46, [Collision resolution], page 150, [Instrument names], page 179, [Writing music in parallel], page 159, [Arpeggio], page 122, Section A.12 [List of articulations], page 654, [Clef], page 15, [Instrument transpositions], page 21.

## String number indications

The string on which a note should be played may be indicated by appending `\number` to a note inside a chord construct `<>`.


**Note:** String numbers **must** be defined inside a chord construct even if there is only a single note.

```
\clef "treble_8"
<c\5>4 <e\4> <g\3>2
<c,\5 e\4 g\3>1
```



When fingerings and string indications are used together, their placement is controlled by the order in which the two items appear in the code:

```
\clef "treble_8"
<g\3-0>2
<g-0\3>
```




## Selected Snippets

### *Controlling the placement of chord fingerings*

The placement of fingering numbers can be controlled precisely. For fingering orientation to apply, you must use a chord construct `<>` even if it is a single note.


```
\relative c' {
  \set fingeringOrientations = #'(left)
  <c-1 e-3 a-5>4
  \set fingeringOrientations = #'(down)
  <c-1 e-3 a-5>4
  \set fingeringOrientations = #'(down right up)
  <c-1 e-3 a-5>4
  \set fingeringOrientations = #'(up)
  <c-1 e-3 a-5>4
  \set fingeringOrientations = #'(left)
  <c-1>2
  \set fingeringOrientations = #'(down)
  <e-3>2
}
```



### *Allowing fingerings to be printed inside the staff*

By default, vertically oriented fingerings are positioned outside the staff. However, this behavior can be canceled. Note: you must use a chord construct `<>`, even if it is only a single note.

```
\relative c' {
  <c-1 e-2 g-3 b-5>2
  \override Fingering #'staff-padding = #'()
  <c-1 e-2 g-3 b-5>4 <g'-0>
}
```



## See also

Notation Reference: [\[Fingering instructions\]](#), page 192.

Snippets: [Section “Fretted strings”](#) in *Snippets*.

Internals Reference: [Section “StringNumber”](#) in *Internals Reference*, [Section “Fingering”](#) in *Internals Reference*.




## Default tablatures

Music for plucked string instruments is frequently notated using a finger/touch notation or tablature. In contrast to traditional notation pitches are not denoted with note heads, but by numbers (or letter-like symbols in historical intavolatura). The staff lines in tablature indicate the string on which the note is to be played, and a number placed on a staff line indicated the fret at which the corresponding string is to be pressed. Notes that are to be played simultaneously are vertically aligned.

By default, string 1 is the highest string, and corresponds to the top line on the `TabStaff`. The tuning of the `TabStaff` strings defaults to the standard guitar tuning (with 6 strings). The notes are printed as tablature, by using `TabStaff` and `TabVoice` contexts. A calligraphic tablature clef is added automatically.

```
\new TabStaff \relative c' {
  a,8 a' <c e> a
  d,8 a' <d f> a
}
```



Default tablatures do not contain any symbols for tone duration nor any other musical symbols such as e.g. expressive marks.

```
symbols = {
  \time 3/4
  c4-.^"Allegro" d( e)
  f4-. \f g a^\fermata
  \mark \default
  c8_.\<\( c16 c~ c2\!
  c'2.\prall\}
}
```

```
\score {
  <<
    \new Staff { \clef "G_8" \symbols }
    \new TabStaff { \symbols }
  >>
}
```


If all musical symbols used in traditional notation should also show up in tablature one has to apply the command `\tabFullNotation` in a `TabStaff`-context. Please bear in mind that half notes are double-stemmed in tablature in order to distinguish them from quarter notes.

```

symbols = {
  \time 3/4
  c4-.^"Allegro" d( e)
  f4-. \f g a^\fermata
  \mark \default
  c8_.\<(\ c16 c~ c2\!
  c'2.\prall\
}

\score {
  \new TabStaff {
    \tabFullNotation
    \symbols
  }
}

```



By default pitches are assigned to the lowest playing position on the fret-board (first position). Open strings are automatically preferred. If you would like a certain pitch to be played on a specific string you can add a string number indication to the pitch name. If you define pitch names and string numbers without a chord construct (<>) the string number indications do not appear in traditional notation. It is much more comfortable to define the playing position by using the value of `minimumFret`. The default value for `minimumFret` is 0.

```

\new StaffGroup <<
  \new Staff \relative c {
    \clef "treble_8"
    \time 2/4
    c16 d e f g4
    c,16\5 d\5 e\4 f\4 g4\4
    c,16 d e f g4
  }
  \new TabStaff \relative c {
    c16 d e f g4
    c,16\5 d\5 e\4 f\4 g4\4
    \set TabStaff.minimumFret = #5
    c,16 d e f g4
  }
>>

```

Chord constructs can be repeated by the chord repetition symbol `q`. In combination with tabulatures, its behavior of removing string and finger numbers alongside with other events is cumbersome, so you'll want to run

```
\chordRepeats #'(string-number-event fingering-event)
```

explicitly on music expressions in tabulature using [\[Chord repetition\]](#), page 143. This particular command is so common that it is available as `\tabChordRepeats`.

```
guitar = \relative c' {
  r8 <gis-6 cis-6 b-0>~ q4 q8~ q q4
}
```

```
\new StaffGroup <<
  \new Staff {
    \clef "treble_8"
    \guitar
  }
  \new TabStaff {
    \tabChordRepeats \guitar
  }
>>
```

Ties over a line break are parenthesized by default. The same holds for the second alternative of a repeat.

```
ties = \relative c' {
  \repeat volta 2 {
    e2. f4~
    f2 g2~
  }
  \alternative {
    { g4 f2. }
    { g4\repeatTie c,2. }
  }
  b1~
  \break
  b1
  \bar "|."
}
```

```
\score {
  <<
    \new StaffGroup <<
      \context Staff {
        \clef "treble_8"
        \ties
      }
    >>
  }
}
```

```

    }
    \context TabStaff {
      \ties
    }
  >>
>>
\layout {
  indent = #0
  ragged-right = ##t
}
}

```

The command `\hideSplitTiedTabNotes` cancels the behavior of engraving fret numbers in parentheses:

```

ties = \relative c' {
  \repeat volta 2 {
    e2. f4~
    f2 g2~ }
  \alternative {
    { g4 f2. }
    { g4\repeatTie c,2. }
  }
  b1~
  \break
  b1
  \bar "|"
}

\score {
  <<
  \new StaffGroup <<
  \context Staff {
    \clef "treble_8"
    \ties
  }
}

```

```

\context TabStaff {
  \hideSplitTiedTabNotes
  \ties
}
>>
>>
\layout {
  indent = #0
  ragged-right = ##t
}
}

```

Harmonic indications can be added to tablature notation as sounding pitches:

```

firstHarmonic = {
  d'4\4\harmonic
  g'4\3\harmonic
  b'2\2\harmonic
}
\score {
  <<
    \new Staff { \firstHarmonic }
    \new TabStaff { \firstHarmonic }
  >>
}

```

Note that the command `\harmonic` must always be attached to single notes (possibly inside of a chord) instead of whole chords. It only makes sense for open-string harmonics in the 12th fret. All other harmonics should be calculated by LilyPond. This can be achieved by indicating the fret where a finger of the fretting hand should touch a string.

```
fretHarmonics = {
  \harmonicByFret #5 d16\4
  \harmonicByFret #4 d16\4
  \harmonicByFret #3 d8\4
  \harmonicByFret #5 <g\3 b\2>2.
}
\score {
  <<
    \new Staff { \fretHarmonics }
    \new TabStaff { \fretHarmonics }
  >>
}
```

Alternatively, harmonics can be computed by defining the ratio of string lengths above and below the harmonic fingering.

```
ratioHarmonics = {
  \harmonicByRatio #1/2 <g\3 b\2 e'\1>4
  \harmonicByRatio #1/3 <g\3 b\2 e'\1>4
  \harmonicByRatio #1/4 { g8\3 b8\2 e'4\1 }
}
\score {
  <<
    \new Staff { \ratioHarmonics }
    \new TabStaff { \ratioHarmonics }
  >>
}
```


## Selected Snippets

### *Stem and beam behavior in tablature*

The direction of stems is controlled the same way in tablature as in traditional notation. Beams can be made horizontal, as shown in this example.

```
\new TabStaff {
  \relative c {
```

```
\tabFullNotation
g16 b d g b d g b
\stemDown
\override Beam #'concaveness = #10000
g,,16 b d g b d g b
}
```



### *Polyphony in tablature*


Polyphony is created the same way in a `TabStaff` as in a regular staff.

```
upper = \relative c' {
  \time 12/8
  \key e \minor
  \voiceOne
  r4. r8 e, fis g16 b g e e' b c b a g fis e
}

lower = \relative c {
  \key e \minor
  \voiceTwo
  r16 e d c b a g4 fis8 e fis g a b c
}

\score {
  <<
    \new StaffGroup = "tab with traditional" <<
      \new Staff = "guitar traditional" <<
        \clef "treble_8"
        \context Voice = "upper" \upper
        \context Voice = "lower" \lower
      >>
    \new TabStaff = "guitar tab" <<
      \context TabVoice = "upper" \upper
      \context TabVoice = "lower" \lower
    >>
  >>
}

```



*Reference for open-string harmonics*

Reference for open-string harmonics:

```
openStringHarmonics = {
  %first harmonic
  \harmonicByFret #12 e,\6_\markup{"1st harm."}
  \harmonicByRatio #1/2 e,\6
  %second harmonic
  \harmonicByFret #7 e,\6_\markup{"2nd harm. - - - -"}
  \harmonicByRatio #1/3 e,\6
  \harmonicByFret #19 e,\6
  \harmonicByRatio #2/3 e,\6
  %\harmonicByFret #19 < e,\6 a,\5 d\4 >
  %\harmonicByRatio #2/3 < e,\6 a,\5 d\4 >
  %third harmonic
  \harmonicByFret #5 e,\6_\markup{"3rd harm. - - - -"}
  \harmonicByRatio #1/4 e,\6
  \harmonicByFret #24 e,\6
  \harmonicByRatio #3/4 e,\6
  \break
  %fourth harmonic
  \harmonicByFret #4 e,\6_\markup{"4th harm. - - - - - - - - - - -"}
  \harmonicByRatio #1/5 e,\6
  \harmonicByFret #9 e,\6
  \harmonicByRatio #2/5 e,\6
  \harmonicByFret #16 e,\6
  \harmonicByRatio #3/5 e,\6
  %fifth harmonic
  \harmonicByFret #3 e,\6_\markup{"5th harm."}
  \harmonicByRatio #1/6 e,\6
  \break
  %sixth harmonic
  \harmonicByFret #2.7 e,\6_\markup{"6th harm."}
  \harmonicByRatio #1/7 e,\6
  %seventh harmonic
  \harmonicByFret #2.3 e,\6_\markup{"7th harm."}
  \harmonicByRatio #1/8 e,\6
  %eighth harmonic
  \harmonicByFret #2 e,\6_\markup{"8th harm."}
  \harmonicByRatio #1/9 e,\6
}

\score {
  <<
  \new Staff {
```



```

\new Voice {
  \clef "treble_8"
  \openStringHarmonics
}
}
\new TabStaff {
  \new TabVoice {
    \openStringHarmonics
  }
}
>>
}

```

1st harm. 2nd harm. ---- 3rd harm. ----

4th harm. ----- 5th harm.

6th harm. 7th harm. 8th harm.

### *Fretted-string harmonics in tablature*

Fretted-string harmonics:

```

pinchedHarmonics = {
  \textSpannerDown
  \override TextSpanner #'bound-details #'left #'text =
    \markup { \halign #-0.5 \teeny "PH" }
  \override TextSpanner #'style =
    #'dashed-line
  \override TextSpanner #'dash-period = #0.6
  \override TextSpanner #'bound-details #'right #'attach-dir = #1
  \override TextSpanner #'bound-details #'right #'text =
    \markup { \draw-line #'(0 . 1) }
  \override TextSpanner #'bound-details #'right #'padding = #-0.5
}

```

```

}

harmonics = {
  %artificial harmonics (AH)
  \textLengthOn
  <\parenthesize b b'\harmonic>4_\markup{ \teeny "AH 16" }
  <\parenthesize g g'\harmonic>4_\markup{ \teeny "AH 17" }
  <\parenthesize d' d''\harmonic>2_\markup{ \teeny "AH 19" }
  %pinched harmonics (PH)
  \pinchedHarmonics
  <a'\harmonic>2\startTextSpan
  <d''\harmonic>4
  <e'\harmonic>4\stopTextSpan
  %tapped harmonics (TH)
  <\parenthesize g\4 g'\harmonic>4_\markup{ \teeny "TH 17" }
  <\parenthesize a\4 a'\harmonic>4_\markup{ \teeny "TH 19" }
  <\parenthesize c'\3 c''\harmonic>2_\markup{ \teeny "TH 17" }
  %touch harmonics (TCH)
  a4( <e''\harmonic>2. )_\markup{ \teeny "TCH" }
}

frettedStrings = {
  %artificial harmonics (AH)
  \harmonicByFret #4 g4\3
  \harmonicByFret #5 d4\4
  \harmonicByFret #7 g2\3
  %pinched harmonics (PH)
  \harmonicByFret #7 d2\4
  \harmonicByFret #5 d4\4
  \harmonicByFret #7 a4\5
  %tapped harmonics (TH)
  \harmonicByFret #5 d4\4
  \harmonicByFret #7 d4\4
  \harmonicByFret #5 g2\3
  %touch harmonics (TCH)
  a4 \harmonicByFret #9 g2.\3
}

\score {
  <<
    \new Staff {
      \new Voice {
        \clef "treble_8"
        \harmonics
      }
    }
    \new TabStaff {
      \new TabVoice {
        \frettedStrings
      }
    }
  >>
}

```

}

*Slides in tablature*

Slides can be typeset in both `Staff` and `TabStaff` contexts:

```
slides = {
  c'8\3(\glissando d'8\3)
  c'8\3\glissando d'8\3
  \hideNotes
  \grace { g16\3\glissando }
  \unHideNotes
  c'4\3
  \afterGrace d'4\3\glissando {
    \stemDown \hideNotes
    g16\3 }
  \unHideNotes
}

\score {
  <<
    \new Staff { \clef "treble_8" \slides }
    \new TabStaff { \slides }
  >>
  \layout {
    \context {
      \Score
      \override Glissando #'minimum-length = #4
      \override Glissando #'springs-and-rods =
        \ly:spanner::set-spacing-rods
      \override Glissando #'thickness = #2
    }
  }
}
```

*Chord glissando in tablature*


Slides for chords can be indicated in both `Staff` and `TabStaff`. String numbers are necessary for `TabStaff` because automatic string calculations are different for chords and for single notes.

```

myMusic = \relative c' {
  <c\3 e\2 g\1>1 \glissando <f\3 a\2 c\1>
}

\score {
  <<
    \new Staff {
      \clef "treble_8"
      \myMusic
    }
    \new TabStaff {
      \myMusic
    }
  >>
}

```



## See also

Notation Reference: [Chord repetition], page 143, [Glissando], page 120, [Harmonics], page 299, [Stems], page 197, [Written-out repeats], page 135.

Snippets: Section “Fretted strings” in *Snippets*.

Internals Reference: Section “TabNoteHead” in *Internals Reference*, Section “TabStaff” in *Internals Reference*, Section “TabVoice” in *Internals Reference*, Section “Beam” in *Internals Reference*.

## Known issues and warnings


Chords are not handled in a special way, and hence the automatic string selector may easily select the same string for two notes in a chord.

In order to handle `\partcombine`, a `TabStaff` must use specially-created voices:

```

melodia = \partcombine { e4 g g g } { e4 e e e }
<<
  \new TabStaff <<
    \new TabVoice = "one" s1
    \new TabVoice = "two" s1
    \new TabVoice = "shared" s1
    \new TabVoice = "solo" s1
    { \melodia }
  >>
>>

```




Guitar special effects are limited to harmonics and slides.

## Custom tablatures

LilyPond tablature automatically calculates the fret for a note based on the string to which the note is assigned. In order to do this, the tuning of the strings must be specified. The tuning of the strings is given in the `stringTunings` property.

LilyPond comes with predefined string tunings for banjo, mandolin, guitar, bass guitar, ukulele, violin, viola, cello, and double bass. LilyPond automatically sets the correct transposition for predefined tunings. The following example is for bass guitar, which sounds an octave lower than written.

```
<<
\new Staff {
  \clef "bass_8"
  \relative c, {
    c4 d e f
  }
}
\new TabStaff {
  \set TabStaff.stringTunings = #bass-tuning
  \relative c, {
    c4 d e f
  }
}
>>
```



The default string tuning is `guitar-tuning`, which is the standard EAD-GBE tuning. Some other predefined tunings are `guitar-open-g-tuning`, `mandolin-tuning` and `banjo-open-g-tuning`. The predefined string tunings are found in `'ly/string-tuning-init.ly'`.

Any desired string tuning can be created. The `\stringTuning` function can be used to define a string tuning which can be used to set `stringTunings` for the current context.

Its argument is a chord construct defining the pitches of each string in the tuning. The chord construct must be in absolute octave mode, see [\[Absolute octave entry\]](#), page 1. The string with the highest number (generally the lowest string) must come first in the chord. For example, we can define a string tuning for a four-string instrument with pitches of `a''`, `d''`, `g'`, and `c'`:

```
mynotes = {
  c'4 e' g' c'' |
  e''4 g'' b'' c'''
}
```

```
<<
```

```

\new Staff {
  \clef treble
  \mynotes
}
\new TabStaff {
  \set stringTunings = \stringTuning <c' g' d'' a''>
  \mynotes
}
>>

```

The `stringTunings` property is also used by `FretBoards` to calculate automatic fret diagrams.

String tunings are used as part of the hash key for predefined fret diagrams (see [\[Predefined fret diagrams\]](#), page 327).

The previous example could also be written as follows:

```
"custom-tuning" = \stringTuning <c' g' d'' a''>
```

```

mynotes = {
  c'4 e' g' c'' |
  e''4 g'' b'' c'''
}

```

```

<<
\new Staff {
  \clef treble
  \mynotes
}
\new TabStaff {
  \set TabStaff.stringTunings = #custom-tuning
  \mynotes
}
>>

```

Internally, a string tuning is a Scheme list of string pitches, one for each string, ordered by string number from 1 to N, where string 1 is at the top of the tablature staff and string N is at the bottom. This ordinarily results in ordering from highest pitch to lowest pitch, but some instruments (e.g. ukulele) do not have strings ordered by pitch.

A string pitch in a string tuning list is a LilyPond pitch object. Pitch objects are created with the Scheme function `ly:make-pitch` (see [Section A.20 \[Scheme functions\]](#), page 697).

`\stringTuning` creates such an object from chord input.


LilyPond automatically calculates the number of lines in the `TabStaff` and the number of strings in an automatically calculated `FretBoard` as the number of elements in `stringTunings`.

To let all `TabStaff` contexts use the same custom tuning by default, you can use

```
\layout {
  \context {
    \TabStaff
    stringTunings = \stringTuning \notemode { <c' g' d'' a''> }
  }
}
```

A modern tab clef can also be used.

```
\new TabStaff {
  \clef moderntab
  <a, e a>1
  \break
  \clef tab
  <a, e a>1
}
```



2



The modern tab clef supports tablatures from 4 to 7 strings.

## See also

Notation Reference: [\[Absolute octave entry\]](#), page 1, [\[Predefined fret diagrams\]](#), page 327, [Section A.20 \[Scheme functions\]](#), page 697.

Installed Files: `'ly/string-tuning-init.ly'` `'scm/tablature.scm'`.

Snippets: [Section “Fretted strings” in Snippets](#).

Internals Reference: [Section “Tab\\_note\\_heads\\_engraver” in Internals Reference](#).

## Known issues and warnings


Automatic tablature calculations do not work properly in most cases for instruments where string pitches do not vary monotonically with string number, such as ukuleles.

## Fret diagram markups

Fret diagrams can be added to music as a markup to the desired note. The markup contains information about the desired fret diagram. There are three different fret-diagram markup interfaces: standard, terse, and verbose. The three interfaces produce equivalent markups, but have varying amounts of information in the markup string. Details about the syntax of the different markup strings used to define fret diagrams are found at [Section A.9.5 \[Instrument Specific Markup\]](#), page 642.


The standard fret diagram markup string indicates the string number and the fret number for each dot to be placed on the string. In addition, open and unplayed (muted) strings can be indicated.

```
<<
\context ChordNames {
  \chordmode {
    c1 d:m
  }
}
\context Staff {
  \clef "treble_8"
  <c e g c' e'>1^\markup {
    \fret-diagram #"6-x;5-3;4-2;3-o;2-1;1-o;"
  }
  <d a d' f'>1^\markup {
    \fret-diagram #"6-x;5-x;4-o;3-2;2-3;1-1;"
  }
}
>>
```



Barre indications can be added to the diagram from the fret-diagram markup string.


```
<<
\context ChordNames {
  \chordmode {
    f1 g
  }
}
\context Staff {
  \clef "treble_8"
  <f, c f a c' f'>1^\markup {
    \fret-diagram #"c:6-1-1;6-1;5-3;4-3;3-2;2-1;1-1;"
  }
  <g, d g b d' g'>1^\markup {
    \fret-diagram #"c:6-1-3;6-3;5-5;4-5;3-4;2-3;1-3;"
  }
}
>>
```






The size of the fret diagram, and the number of frets in the diagram can be changed in the fret-diagram markup string.

```
<<
\context ChordNames {
  \chordmode {
    f1 g
  }
}
\context Staff {
  \clef "treble_8"
  <f, c f a c' f'>1^\markup {
    \fret-diagram #"s:1.5;c:6-1-1;6-1;5-3;4-3;3-2;2-1;1-1;"
  }
  <g, b, d g b g'>1^\markup {
    \fret-diagram #"h:6;6-3;5-2;4-o;3-o;2-o;1-3;"
  }
}
>>
```




The number of strings in a fret diagram can be changed to accommodate different instruments such as banjos and ukuleles with the fret-diagram markup string.

```
<<
\context ChordNames {
  \chordmode {
    a1
  }
}
\context Staff {
  % An 'A' chord for ukulele
  a'1^\markup {
    \fret-diagram #"w:4;4-2-2;3-1-1;2-o;1-o;"
  }
}
>>
```




Fingering indications can be added, and the location of fingering labels can be controlled by the fret-diagram markup string.

```
<<
\context ChordNames {
  \chordmode {
    c1 d:m
  }
}
\context Staff {
  \clef "treble_8"
  <c e g c' e'>1^\markup {
    \fret-diagram #"f:1;6-x;5-3-3;4-2-2;3-o;2-1-1;1-o;"
  }
  <d a d' f'>1^\markup {
    \fret-diagram #"f:2;6-x;5-x;4-o;3-2-2;2-3-3;1-1-1;"
  }
}
>>
```



Dot radius and dot position can be controlled with the fret-diagram markup string.


```
<<
\context ChordNames {
  \chordmode {
    c1 d:m
  }
}
\context Staff {
  \clef "treble_8"
  <c e g c' e'>1^\markup {
    \fret-diagram #"d:0.35;6-x;5-3;4-2;3-o;2-1;1-o;"
  }
  <d a d' f'>1^\markup {
    \fret-diagram #"p:0.2;6-x;5-x;4-o;3-2;2-3;1-1;"
  }
}
>>
```



The fret-diagram-terse markup string omits string numbers; the string number is implied by the presence of semicolons. There is one semicolon for each string in the diagram. The first


semicolon corresponds to the highest string number and the last semicolon corresponds to the first string. Mute strings, open strings, and fret numbers can be indicated.

```
<<
\context ChordNames {
  \chordmode {
    c1 d:m
  }
}
\context Staff {
  \clef "treble_8"
  <c e g c' e'>1^\markup {
    \fret-diagram-terse #"x;3;2;o;1;o;"
  }
  <d a d' f'>1^\markup {
    \fret-diagram-terse #"x;x;o;2;3;1;"
  }
}
>>
```




Barre indicators can be included in the fret-diagram-terse markup string.

```
<<
\context ChordNames {
  \chordmode {
    f1 g
  }
}
\context Staff {
  \clef "treble_8"
  <f, c f a c' f'>1^\markup {
    \fret-diagram-terse #"1-(;3;3;2;1;1-);"
  }
  <g, d g b d' g'>1^\markup {
    \fret-diagram-terse #"3-(;5;5;4;3;3-);"
  }
}
>>
```



Fingering indications can be included in the fret-diagram-terse markup string.

```
<<
\context ChordNames {
  \chordmode {
    c1 d:m
  }
}
\context Staff {
  \override Voice.TextScript
    #'(fret-diagram-details finger-code) = #'below-string
  \clef "treble_8"
  <c e g c' e'>1^\markup {
    \fret-diagram-terse #"x;3-3;2-2;o;1-1;o;"
  }
  <d a d' f'>1^\markup {
    \fret-diagram-terse #"x;x;o;2-2;3-3;1-1;"
  }
}
>>
```



Other fret diagram properties must be adjusted using `\override` when using the `fret-diagram-terse` markup.


The `fret-diagram-verbose` markup string is in the format of a Scheme list. Each element of the list indicates an item to be placed on the fret diagram.

```
<<
\context ChordNames {
  \chordmode {
    c1 d:m
  }
}
\context Staff {
  \clef "treble_8"
  <c e g c' e'>1^\markup {
    \fret-diagram-verbose #'(
      (mute 6)
      (place-fret 5 3)
      (place-fret 4 2)
      (open 3)
      (place-fret 2 1)
      (open 1)
    )
  }
  <d a d' f'>1^\markup {
    \fret-diagram-verbose #'(
      (mute 6)
    )
  }
}
>>
```

```

        (mute 5)
        (open 4)
        (place-fret 3 2)
        (place-fret 2 3)
        (place-fret 1 1)
      )
    }
  }
>>

```



Fingering indications and barres can be included in a fret-diagram-verbose markup string. Unique to the fret-diagram-verbose interface is a capo indication that can be placed on the fret diagram. The capo indication is a thick bar that covers all strings. The fret with the capo will be the lowest fret in the fret diagram.

```


<<
  \context ChordNames {
    \chordmode {
      f1 g c
    }
  }
  \context Staff {
    \clef "treble_8"
    \override Voice.TextScript
      #'(fret-diagram-details finger-code) = #'below-string
    <f, c f a c' f'>1^\markup {
      \fret-diagram-verbose #'(
        (place-fret 6 1)
        (place-fret 5 3)
        (place-fret 4 3)
        (place-fret 3 2)
        (place-fret 2 1)
        (place-fret 1 1)
        (barre 6 1 1)
      )
    }
    <g, b, d g b g'>1^\markup {
      \fret-diagram-verbose #'(
        (place-fret 6 3 2)
        (place-fret 5 2 1)
        (open 4)
        (open 3)
        (open 2)
        (place-fret 1 3 3)
      )
    }
  }
}

```

```

<c e g c' e'>1^\markup {
  \fret-diagram-verbose #'(
    (capo 3)
    (mute 6)
    (place-fret 4 5 1)
    (place-fret 3 5 2)
    (place-fret 2 5 3)
  )
}
}
>>

```



All other fret diagram properties must be adjusted using `\override` when using the `fret-diagram-verbose` markup.

The graphical layout of a fret diagram can be customized according to user preference through the properties of the `fret-diagram-interface`. Details are found at [Section “fret-diagram-interface” in \*Internals Reference\*](#). For a fret diagram markup, the interface properties belong to `Voice.TextScript`.

## Selected Snippets

### *Changing fret orientations*

Fret diagrams can be oriented in three ways. By default the top string or fret in the different orientations will be aligned.

```
\include "predefined-guitar-fretboards.ly"
```

```


<<
\chords {
  c1
  c1
  c1
}
\new FretBoards {
  \chordmode {
    c1
    \override FretBoard #'(fret-diagram-details orientation) =
      #'landscape
    c1
    \override FretBoard #'(fret-diagram-details orientation) =
      #'opposing-landscape
    c1
  }
}
\new Voice {

```

```

c'1
c'1
c'
}
>>

```



### *Customizing markup fret diagrams*

Fret diagram properties can be set through 'fret-diagram-details. For markup fret diagrams, overrides can be applied to the Voice.TextScript object or directly to the markup.

```

<<
\chords { c1 | c | c | d }

\new Voice = "mel" {
  \textLengthOn
  % Set global properties of fret diagram
  \override TextScript #'size = #'1.2
  \override TextScript
    #'(fret-diagram-details finger-code) = #'in-dot
  \override TextScript
    #'(fret-diagram-details dot-color) = #'white

  %% C major for guitar, no barre, using defaults
  % terse style
  c'1^\markup { \fret-diagram-terse #"x;3-3;2-2;o;1-1;o;" }

  %% C major for guitar, barred on third fret
  % verbose style
  % size 1.0
  % roman fret label, finger labels below string, straight barre
  c'1^\markup {
    % standard size
    \override #'(size . 1.0) {
      \override #'(fret-diagram-details . (
        (number-type . roman-lower)
        (finger-code . in-dot)
        (barre-type . straight))) {
        \fret-diagram-verbose #'((mute 6)
          (place-fret 5 3 1)
          (place-fret 4 5 2)
          (place-fret 3 5 3)
          (place-fret 2 5 4)
          (place-fret 1 3 1)
          (barre 5 1 3))

```


```

    }
  }
}

%% C major for guitar, barred on third fret
% verbose style
% landscape orientation, arabic numbers, M for mute string
% no barre, fret label down or left, small mute label font
c'1^\markup {
  \override #'(fret-diagram-details . (
    (finger-code . below-string)
    (number-type . arabic)
    (label-dir . -1)
    (mute-string . "M")
    (orientation . landscape)
    (barre-type . none)
    (xo-font-magnification . 0.4)
    (xo-padding . 0.3))) {
    \fret-diagram-verbose #'(mute 6)
      (place-fret 5 3 1)
      (place-fret 4 5 2)
      (place-fret 3 5 3)
      (place-fret 2 5 4)
      (place-fret 1 3 1)
      (barre 5 1 3))
  }
}

%% simple D chord
% terse style
% larger dots, centered dots, fewer frets
% label below string
d'1^\markup {
  \override #'(fret-diagram-details . (
    (finger-code . below-string)
    (dot-radius . 0.35)
    (dot-position . 0.5)
    (fret-count . 3))) {
    \fret-diagram-terse #"x;x;o;2-1;3-2;2-3;"
  }
}
}
}
>>

```





## See also

Notation Reference: [Section A.9.5 \[Instrument Specific Markup\]](#), page 642.


Snippets: [Section “Fretted strings” in \*Snippets\*](#).

Internals Reference: [Section “fret-diagram-interface” in \*Internals Reference\*](#).

## Predefined fret diagrams

Fret diagrams can be displayed using the `FretBoards` context. By default, the `FretBoards` context will display fret diagrams that are stored in a lookup table:

```
\include "predefined-guitar-fretboards.ly"
\context FretBoards {
  \chordmode {
    c1 d
  }
}
```



The default predefined fret diagrams are contained in the file ‘`predefined-guitar-fretboards.ly`’. Fret diagrams are stored based on the pitches of a chord and the value of `stringTunings` that is currently in use. ‘`predefined-guitar-fretboards.ly`’ contains predefined fret diagrams only for `guitar-tuning`. Predefined fret diagrams can be added for other instruments or other tunings by following the examples found in ‘`predefined-guitar-fretboards.ly`’.

Fret diagrams for the ukulele are contained in the file ‘`predefined-ukulele-fretboards.ly`’.


```
\include "predefined-ukulele-fretboards.ly"
```

```
myChords = \chordmode { a1 a:m a:aug }
```

```
\new ChordNames {
  \myChords
}
```

```
\new FretBoards {
  \set stringTunings = #ukulele-tuning
  \myChords
}
```

**A Am A+**



Fret diagrams for the mandolin are contained in the file ‘`predefined-mandolin-fretboards.ly`’.

```
\include "predefined-mandolin-fretboards.ly"
```

```
myChords = \chordmode { c1 c:m7.5- c:aug }
```


```

\new ChordNames {
  \myChords
}

\new FretBoards {
  \set stringTunings = #mandolin-tuning
  \myChords
}

```

C   C<sup>∅</sup>   C+




Chord pitches can be entered either as simultaneous music or using chord mode (see [\[Chord mode overview\]](#), page 368).

```

\include "predefined-guitar-fretboards.ly"
\context FretBoards {
  \chordmode { c1 }
  <c' e' g'>1
}

```



It is common that both chord names and fret diagrams are displayed together. This is achieved by putting a **ChordNames** context in parallel with a **FretBoards** context and giving both contexts the same music.

```


\include "predefined-guitar-fretboards.ly"
mychords = \chordmode{
  c1 f g
}

```

```

<<
  \context ChordNames {
    \mychords
  }
  \context FretBoards {
    \mychords
  }
>>

```




Predefined fret diagrams are transposable, as long as a diagram for the transposed chord is stored in the fret diagram table.

```

\include "predefined-guitar-fretboards.ly"
mychords = \chordmode{
  c1 f g
}

mychordlist = {
  \mychords
  \transpose c e { \mychords }
}
<<
  \context ChordNames {
    \mychordlist
  }
  \context FretBoards {
    \mychordlist
  }
>>

```




The predefined fret diagram table for guitar contains eight chords (major, minor, augmented, diminished, dominant seventh, major seventh, minor seventh, dominant ninth) for each of 17 keys. The predefined fret diagram table for ukulele contains these chords plus an additional three chords (major sixth, suspended second, and suspended fourth). A complete list of the predefined fret diagrams is shown in [Section A.4 \[Predefined fretboard diagrams\]](#), page 573. If there is no entry in the table for a chord, the FretBoards engraver will calculate a fret-diagram using the automatic fret diagram functionality described in [\[Automatic fret diagrams\]](#), page 337.

```

\include "predefined-guitar-fretboards.ly"
mychords = \chordmode{
  c1 c:maj9
}

<<
  \context ChordNames {
    \mychords
  }
  \context FretBoards {
    \mychords
  }
>>

```




Fret diagrams can be added to the fret diagram table. To add a diagram, you must specify the hash table for the diagram, the chord for the diagram, the tuning to be used, and a definition for the diagram. Normally, the hash table will be *default-fret-table*. The diagram definition can be either a fret-diagram-terse definition string or a fret-diagram-verbose marking list.

```
\include "predefined-guitar-fretboards.ly"

\storePredefinedDiagram #default-fret-table
    \chordmode { c:maj9 }
    #guitar-tuning
    #"x;3-2;o;o;o;o;"
```

```
mychords = \chordmode {
  c1 c:maj9
}
```

```
<<
  \context ChordNames {
    \mychords
  }
  \context FretBoards {
    \mychords
  }
>>
```




Different fret diagrams for the same chord name can be stored using different octaves of pitches. The different octave should be at least two octaves above or below the default octave, because the octaves above and below the default octave are used for transposing fretboards.

```
\include "predefined-guitar-fretboards.ly"

\storePredefinedDiagram #default-fret-table
    \chordmode { c' ' }
    #guitar-tuning
    #(offset-fret 2 (chord-shape 'bes guitar-tuning))
```

```
mychords = \chordmode {
  c1 c' '
}
```

```
<<
  \context ChordNames {
    \mychords
  }
  \context FretBoards {
    \mychords
  }
>>
```



In addition to fret diagrams, LilyPond stores an internal list of chord shapes. The chord shapes are fret diagrams that can be shifted along the neck to different positions to provide different chords. Chord shapes can be added to the internal list and then used to define predefined fret diagrams. Because they can be moved to various positions on the neck, chord shapes will normally not contain any open strings. Like fret diagrams, chord shapes can be entered as either fret-diagram-terse strings or fret-diagram-verbose marking lists.

```
\include "predefined-guitar-fretboards.ly"

% Add a new chord shape


\addChordShape #'powerf #guitar-tuning #"1-1;3-3;3-4;x;x;x;"

% add some new chords based on the power chord shape

\storePredefinedDiagram #default-fret-table
    \chordmode { f'' }
    #guitar-tuning
    #(chord-shape 'powerf guitar-tuning)
\storePredefinedDiagram #default-fret-table
    \chordmode { g'' }
    #guitar-tuning
    #(offset-fret 2 (chord-shape 'powerf guitar-tuning))

mychords = \chordmode{
  f1 f'' g g''
}

<<
  \context ChordNames {
    \mychords
  }
  \context FretBoards {
    \mychords
  }
>>
```



The graphical layout of a fret diagram can be customized according to user preference through the properties of the `fret-diagram-interface`. Details are found at [Section “fret-diagram-interface” in \*Internals Reference\*](#). For a predefined fret diagram, the interface properties belong to `FretBoards.FretBoard`.

## Selected Snippets

### *Customizing fretboard fret diagrams*

Fret diagram properties can be set through `'fret-diagram-details`. For `FretBoard` fret diagrams, overrides are applied to the `FretBoards.FretBoard` object. Like `Voice`, `FretBoards` is a bottom level context, therefore can be omitted in property overrides.


```

\include "predefined-guitar-fretboards.ly"
\storePredefinedDiagram #default-fret-table \chordmode { c' }
      #guitar-tuning
      #"x;1-1-(;3-2;3-3;3-4;1-1-);"

<<
\new ChordNames {
  \chordmode { c1 | c | c | d }
}
\new FretBoards {
  % Set global properties of fret diagram
  \override FretBoards.FretBoard #'size = #'1.2
  \override FretBoard
    #'(fret-diagram-details finger-code) = #'in-dot
  \override FretBoard
    #'(fret-diagram-details dot-color) = #'white
  \chordmode {
    c
    \once \override FretBoard #'size = #'1.0
    \once \override FretBoard
      #'(fret-diagram-details barre-type) = #'straight
    \once \override FretBoard
      #'(fret-diagram-details dot-color) = #'black
    \once \override FretBoard
      #'(fret-diagram-details finger-code) = #'below-string
    c'
    \once \override FretBoard
      #'(fret-diagram-details barre-type) = #'none
    \once \override FretBoard
      #'(fret-diagram-details number-type) = #'arabic
    \once \override FretBoard
      #'(fret-diagram-details orientation) = #'landscape
    \once \override FretBoard
      #'(fret-diagram-details mute-string) = #'M"
    \once \override FretBoard
      #'(fret-diagram-details label-dir) = #LEFT
    \once \override FretBoard
      #'(fret-diagram-details dot-color) = #'black
    c'
    \once \override FretBoard
      #'(fret-diagram-details finger-code) = #'below-string
    \once \override FretBoard
      #'(fret-diagram-details dot-radius) = #0.35
    \once \override FretBoard
      #'(fret-diagram-details dot-position) = #0.5
    \once \override FretBoard
      #'(fret-diagram-details fret-count) = #3
    d
  }
}
\new Voice {
  c'1 | c' | c' | d'
}

```

&gt;&gt;



### *Defining predefined fretboards for other instruments*

Predefined fret diagrams can be added for new instruments in addition to the standards used for guitar. This file shows how this is done by defining a new string-tuning and a few predefined fretboards for the Venezuelan cuatro.

This file also shows how fingerings can be included in the chords used as reference points for the chord lookup, and displayed in the fret diagram and the `TabStaff`, but not the music.

These fretboards are not transposable because they contain string information. This is planned to be corrected in the future.

```
% add FretBoards for the Cuatro
% Note: This section could be put into a separate file
% predefined-cuatro-fretboards.ly
% and \included into each of your compositions
```

```
cuatroTuning = #`((ly:make-pitch 0 6 0)
                  ,(ly:make-pitch 1 3 SHARP)
                  ,(ly:make-pitch 1 1 0)
                  ,(ly:make-pitch 0 5 0))
```

```
dSix = { <a\4 b\1 d\3 fis\2> }
dMajor = { <a\4 d\1 d\3 fis \2> }
aMajSeven = { <a\4 cis\1 e\3 g\2> }
dMajSeven = { <a\4 c\1 d\3 fis\2> }
gMajor = { <b\4 b\1 d\3 g\2> }
```

```
\storePredefinedDiagram #default-fret-table \dSix
                        #cuatroTuning
                        #"o;o;o;o;"
\storePredefinedDiagram #default-fret-table \dMajor
                        #cuatroTuning
                        #"o;o;o;3-3;"
\storePredefinedDiagram #default-fret-table \aMajSeven
                        #cuatroTuning
                        #"o;2-2;1-1;2-3;"
\storePredefinedDiagram #default-fret-table \dMajSeven
                        #cuatroTuning
                        #"o;o;o;1-1;"
\storePredefinedDiagram #default-fret-table \gMajor
                        #cuatroTuning
                        #"2-2;o;1-1;o;"
```

```
% end of potential include file /predefined-cuatro-fretboards.ly
```

```

#(set-global-staff-size 16)

primerosNames = \chordmode {
  d:6 d a:maj7 d:maj7
  g
}
primeros = {
  \dSix \dMajor \aMajSeven \dMajSeven
  \gMajor
}

\score {
  <<
    \new ChordNames {
      \set chordChanges = ##t
      \primerosNames
    }

    \new Staff {
      \new Voice \with {
        \remove "New_fingering_engraver"
      }
      \relative c'' {
        \primeros
      }
    }

    \new FretBoards {
      \set stringTunings = #cuatroTuning
%      \override FretBoard
%      #'(fret-diagram-details string-count) = #'4
      \override FretBoard
        #'(fret-diagram-details finger-code) = #'in-dot
      \primeros
    }

    \new TabStaff \relative c'' {
      \set TabStaff.stringTunings = #cuatroTuning
      \primeros
    }
  >>

  \layout {
    \context {
      \Score
      \override SpacingSpanner
        #'base-shortest-duration = #(ly:make-moment 1 16)
    }
  }
  \midi { }

```



}

*chordChanges for FretBoards*

FretBoards can be set to display only when the chord changes or at the beginning of a new line.

```
\include "predefined-guitar-fretboards.ly"
```

```
myChords = \chordmode {
  c1 c1 \break
  \set chordChanges = ##t
  c1 c1 \break
  c1 c1 \break
}
```

```
<<
  \new ChordNames { \myChords }
  \new FretBoards { \myChords }
  \new Staff { \myChords }
>>
```

*Alternate fretboard tables*

Alternate fretboard tables can be created. These would be used in order to have alternate fretboards for a given chord.

In order to use an alternate fretboard table, the table must first be created. Fretboards are then added to the table.

The created fretboard table can be blank, or it can be copied from an existing table.

The table to be used in displaying predefined fretboards is selected by the property `\predefinedDiagramTable`.

```
\include "predefined-guitar-fretboards.ly"
```

```
% Make a blank new fretboard table
```

```
 #(define custom-fretboard-table-one (make-fretboard-table))
```

```
% Make a new fretboard table as a copy of default-fret-table
```

```
 #(define custom-fretboard-table-two (make-fretboard-table default-fret-table))
```

```
% Add a chord to custom-fretboard-table-one
```

```
\storePredefinedDiagram #custom-fretboard-table-one
      \chordmode{c}
      #guitar-tuning
      "3-(;3;5;5;5;3-);"
```

```
% Add a chord to custom-fretboard-table-two
```

```
\storePredefinedDiagram #custom-fretboard-table-two
      \chordmode{c}
      #guitar-tuning
      "x;3;5;5;5;o;"
```

```
<<
```

```
\chords {
  c1 | d1 |
  c1 | d1 |
  c1 | d1 |
}
\new FretBoards {
  \chordmode {
    \set predefinedDiagramTable = #default-fret-table
    c1 | d1 |
    \set predefinedDiagramTable = #custom-fretboard-table-one
    c1 | d1 |
    \set predefinedDiagramTable = #custom-fretboard-table-two
    c1 | d1 |
  }
}
\new Staff {
  \clef "treble_8"
  <<
    \chordmode {
      c1 | d1 |
      c1 | d1 |
      c1 | d1 |
    }
  >>
}
```

```

    }
    {
      s1\_markup "Default table" | s1 |
      s1\_markup \column {"New table" "from empty"} | s1 |
      s1\_markup \column {"New table" "from default"} | s1 |
    }
  >>
}
>>

```

## See also

Notation Reference: [\[Custom tablatures\]](#), page 315, [\[Automatic fret diagrams\]](#), page 337, [\[Chord mode overview\]](#), page 368, [Section A.4 \[Predefined fretboard diagrams\]](#), page 573.

Installed Files: `'ly/predefined-guitar-fretboards.ly'`, `'ly/predefined-guitar-ninth-fretboards.ly'`, `'ly/predefined-ukulele-fretboards.ly'`, `'ly/predefined-mandolin-fretboards.ly'`.

Snippets: [Section “Fretted strings” in \*Snippets\*](#).

Internals Reference: [Section “fret-diagram-interface” in \*Internals Reference\*](#).


## Automatic fret diagrams

Fret diagrams can be automatically created from entered notes using the `FretBoards` context. If no predefined diagram is available for the entered notes in the active `stringTunings`, this context calculates strings and frets that can be used to play the notes.

```

<<
  \context ChordNames {
    \chordmode {
      f1 g
    }
  }
  \context FretBoards {
    <f, c f a c' f'>1
    <g,\6 b, d g b g'>1
  }
  \context Staff {
    \clef "treble_8"
    <f, c f a c' f'>1
    <g, b, d g b' g'>1
  }
>>


```



As no predefined diagrams are loaded by default, automatic calculation of fret diagrams is the default behavior. Once default diagrams are loaded, automatic calculation can be enabled and disabled with predefined commands:

```
\storePredefinedDiagram #default-fret-table
                                <c e g c' e'>
                                #guitar-tuning
                                #"x;3-1-(;5-2;5-3;5-4;3-1-1-);"

<<
  \context ChordNames {
    \chordmode {
      c1 c c
    }
  }
  \context FretBoards {
    <c e g c' e'>1
    \predefinedFretboardsOff
    <c e g c' e'>1
    \predefinedFretboardsOn
    <c e g c' e'>1
  }
  \context Staff {
    \clef "treble_8"
    <c e g c' e'>1
    <c e g c' e'>1
    <c e g c' e'>1
  }
>>
```



Sometimes the fretboard calculator will be unable to find an acceptable diagram. This can often be remedied by manually assigning a note to a string. In many cases, only one note need be manually placed on a string; the rest of the notes will then be placed appropriately by the `FretBoards` context.


Fingerings can be added to `FretBoard` fret diagrams.

```
<<
  \context ChordNames {
    \chordmode {
      c1 d:m
    }
  }
```

```

    }
  }
  \context FretBoards {
    <c-3 e-2 g c'-1 e'>1
    <d a-2 d'-3 f'-1>1
  }
  \context Staff {
    \clef "treble_8"
    <c e g c' e'>1
    <d a d' f'>1
  }
}
>>

```




The minimum fret to be used in calculating strings and frets for the FretBoard context can be set with the `minimumFret` property.

```

<<
  \context ChordNames {
    \chordmode {
      d1:m d:m
    }
  }
  \context FretBoards {
    <d a d' f'>1
    \set FretBoards.minimumFret = #5
    <d a d' f'>1
  }
  \context Staff {
    \clef "treble_8"
    <d a d' f'>1
    <d a d' f'>1
  }
}
>>

```



The strings and frets for the FretBoards context depend on the `stringTunings` property, which has the same meaning as in the TabStaff context. See [\[Custom tablatures\]](#), page 315 for information on the `stringTunings` property.

The graphical layout of a fret diagram can be customized according to user preference through the properties of the `fret-diagram-interface`. Details are found at [Section “fret-diagram-interface” in \*Internals Reference\*](#). For a `FretBoards` fret diagram, the interface properties belong to `FretBoards.FretBoard`.

## Predefined commands

`\predefinedFretboardsOff`, `\predefinedFretboardsOn`.

## See also

Notation Reference: [\[Custom tablatures\]](#), page 315.

Snippets: [Section “Fretted strings” in \*Snippets\*](#).

Internals Reference: [Section “fret-diagram-interface” in \*Internals Reference\*](#).

## Known issues and warnings

Automatic fretboard calculations do not work properly for instruments with non-monotonic tunings.

## Right-hand fingerings

Right-hand fingerings *p-i-m-a* must be entered within a chord construct `<>` for them to be printed in the score, even when applied to a single note.

**Note:** There **must** be a hyphen before `\rightHandFinger` and a space before the closing `>`.

```
\clef "treble_8"
<c-\rightHandFinger #1 >4
<e-\rightHandFinger #2 >
<g-\rightHandFinger #3 >
<c-\rightHandFinger #4 >
<c,-\rightHandFinger #1 e-\rightHandFinger #2
  g-\rightHandFinger #3 c-\rightHandFinger #4 >1
```



For convenience, you can abbreviate `\rightHandFinger` to something short, for example `RH`, `#(define RH rightHandFinger)`

## Selected Snippets

### *Placement of right-hand fingerings*

It is possible to exercise greater control over the placement of right-hand fingerings by setting a specific property, as demonstrated in the following example. Note: you must use a chord construct

```
#(define RH rightHandFinger)
```

```
\relative c {
  \clef "treble_8"

  \set strokeFingerOrientations = #'(up down)
  <c-\RH #1 e-\RH #2 g-\RH #3 c-\RH #4 >4
```

```

\set strokeFingerOrientations = #'(up right down)
<c-\RH #1 e-\RH #2 g-\RH #3 c-\RH #4 >4

\set strokeFingerOrientations = #'(left)
<c-\RH #1 e-\RH #2 g-\RH #3 c-\RH #4 >2
}

```



*Fingerings string indications and right-hand fingerings*


This example combines left-hand fingering, string indications, and right-hand fingering.

```

\define RH rightHandFinger)

\relative c {
  \clef "treble_8"
  <c-3\5-\RH #1 >4
  <e-2\4-\RH #2 >4
  <g-0\3-\RH #3 >4
  <c-1\2-\RH #4 >4
}

```



## See also

Snippets: [Section “Fretted strings” in \*Snippets\*](#).

Internals Reference: [Section “StrokeFinger” in \*Internals Reference\*](#).

### 2.4.2 Guitar

Most of the notational issues associated with guitar music are covered sufficiently in the general fretted strings section, but there are a few more worth covering here. Occasionally users want to create songbook-type documents having only lyrics with chord indications above them. Since LilyPond is a music typesetter, it is not recommended for documents that have no music notation in them. A better alternative is a word processor, text editor, or, for experienced users, a typesetter like GuitarTeX.

#### Indicating position and barring

This example demonstrates how to include guitar position and barring indications.

```

\clef "treble_8"
b16 d g b e
\textSpannerDown
\override TextSpanner #'(bound-details left text) = #"XII "

```

```
g16\startTextSpan
b16 e g e b g\stopTextSpan
e16 b g d
```



## See also


Notation Reference: [Text spanners], page 203.

Snippets: Section “Fretted strings” in *Snippets*, Section “Expressive marks” in *Snippets*.

## Indicating harmonics and dampened notes

Special note heads can be used to indicate dampened notes or harmonics. Harmonics are normally further explained with a text markup.

```
\relative c' {
  \clef "treble_8"
  \override Staff.NoteHead #'style = #'harmonic-mixed
  d~\markup { \italic { \fontsize #-2 { "harm. 12" }}} <g b>1
}
```



Dampened notes (also called *dead notes*) are supported within normal and tablature staves:

```
music = \relative c' {
  < a\3 \deadNote c\2 a'\1 >4
  < b\3 \deadNote d\2 b'\1 >
  < c\3 \deadNote e\2 c'\1 >
  \deadNotesOn
  \times 2/3 { g8 b e }
  \deadNotesOff
  < a,\3 c\2 e\1 >1
}
\new StaffGroup <<
  \new Staff {
    \clef "treble_8"
    \music
  }
  \new TabStaff {
    \music
  }
>>
```





```

\score {
  <<
    \new ChordNames {
      \ChordsAndSymbols
    }
    \new Staff {
      \clef "treble_8"
      \ChordsAndSymbols
    }
    \new TabStaff {
      \ChordsAndSymbols
    }
  >>
}

```

The image displays a musical score for a guitar. The top staff is a treble clef staff with a common time signature 'C'. It contains six measures, each with a power chord symbol above the staff: E<sup>5</sup>, A<sup>5</sup>, C<sup>5</sup>, F<sup>5</sup>, A<sup>5</sup>, and G<sup>5</sup>. Below the staff is a guitar fretboard diagram with six strings and six frets. The fret numbers for each measure are: Measure 1 (E5): 8 (low E), 2 (A); Measure 2 (A5): 2 (A), 0 (E); Measure 3 (C5): 0 (C), 8 (G); Measure 4 (F5): 10 (F), 8 (C); Measure 5 (A5): 7 (A), 5 (E); Measure 6 (G5): 8 (G), 5 (B).

Power chord symbols are automatically switched off as soon as one of the other common chord modifier is used:

```

mixedChords = \chordmode {
  c,1
  \powerChords
  b,,1:1.5
  fis,,1:1.5.8
  g,,1:m
}
\score {
  <<
    \new ChordNames {
      \mixedChords
    }
    \new Staff {
      \clef "treble_8"
      \mixedChords
    }
    \new TabStaff {
      \mixedChords
    }
  >>
}

```

	C	B <sup>5</sup>	F <sup>#</sup> 5	Gm
5	0	4	4	0
4	2	2	2	1
3	3	2	2	3

## See also

Music Glossary: [Section “power chord”](#) in *Music Glossary*.

Notation Reference: [\[Extended and altered chords\]](#), page 370, [\[Printing chord names\]](#), page 373.

Snippets: [Section “Fretted strings”](#) in *Snippets*.

## 2.4.3 Banjo

### Banjo tablatures

LilyPond has basic support for the five-string banjo. When making tablatures for five-string banjo, use the banjo tablature format function to get correct fret numbers for the fifth string:

```
\new TabStaff <<
  \set TabStaff.tablatureFormat = #fret-number-tablature-format-banjo
  \set TabStaff.stringTunings = #banjo-open-g-tuning
  {
    \stemDown
    g8 d' g'\5 a b g e d' |
    g4 d''8\5 b' a'\2 g'\5 e'\2 d' |
    g4
  }
>>
```

5	0	2	0	2
4	0	10	5	0
3	0	0	0	0
2	0	0	0	0
1	0	0	0	0

A number of common tunings for the five-string banjo are predefined: `banjo-c-tuning` (gCGBD), `banjo-modal-tuning` (gDGCD), `banjo-open-d-tuning` (aDF#AD) and `banjo-open-dm-tuning` (aDFAD).

These may be converted to four-string tunings using the `four-string-banjo` function:

```
\set TabStaff.stringTunings = #(four-string-banjo banjo-c-tuning)
```

## See also

Snippets: [Section “Fretted strings”](#) in *Snippets*.

Installed Files: ‘`ly/string-tunings-init.ly`’

## 2.5 Percussion

### 2.5.1 Common notation for percussion

Rhythmic music is primarily used for percussion and drum notation, but it can also be used to show the rhythms of melodies.

## References for percussion

- Some percussion may be notated on a rhythmic staff; this is discussed in [\[Showing melody rhythms\]](#), page 70, and [\[Instantiating new staves\]](#), page 162.
- MIDI output is discussed in a separate section; please see [Section 3.5.6 \[Percussion in MIDI\]](#), page 466.

## See also


Notation Reference: [\[Showing melody rhythms\]](#), page 70, [\[Instantiating new staves\]](#), page 162. [Section 3.5.6 \[Percussion in MIDI\]](#), page 466.

Snippets: [Section “Percussion” in \*Snippets\*](#).

## Basic percussion notation


Percussion notes may be entered in `\drummode` mode, which is similar to the standard mode for entering notes. The simplest way to enter percussion notes is to use the `\drums` command, which creates the correct context and entry mode for percussion:

```
\drums {
  hihat4 hh bassdrum bd
}
```



This is shorthand for:

```
\new DrumStaff {
  \drummode {
    hihat4 hh bassdrum bd
  }
}
```



Each piece of percussion has a full name and an abbreviated name, and both can be used in input files. The full list of percussion note names may be found in [Section A.13 \[Percussion notes\]](#), page 655.

Note that the normal notation of pitches (such as `cis4`) in a `DrumStaff` context will cause an error message. Percussion clefs are added automatically to a `DrumStaff` context but they can also be set explicitly. Other clefs may be used as well.

```
\drums {
  \clef percussion
  bd4 bd bd bd
  \clef treble
  hh4 hh hh hh
}
```



There are a few issues concerning MIDI support for percussion instruments; for details please see [Section 3.5.6 \[Percussion in MIDI\]](#), page 466.

## See also

Notation Reference: [Section 3.5.6 \[Percussion in MIDI\]](#), page 466, [Section A.13 \[Percussion notes\]](#), page 655.

File: ‘[ly/drumpitch-init.ly](#)’

Snippets: [Section “Percussion” in \*Snippets\*](#).

## Drum rolls

Drum rolls are indicated with three slashes across the stem. For quarter notes or longer the three slashes are shown explicitly, eighth notes are shown with two slashes (the beam being the third), and drum rolls shorter than eighths have one stem slash to supplement the beams. This is achieved with the tremolo notation, as described in [\[Tremolo repeats\]](#), page 139.

```
\drums {
  \time 2/4
  sn16 sn8 sn16 sn8 sn8:32 ~
  sn8 sn8 sn4:32 ~
  sn4 sn8 sn16 sn16
  sn4 r4
}
```



Sticking can be indicated by placing placing markup for "R" or "L" above or below notes, as discussed in [Section 5.4.2 \[Direction and placement\]](#), page 543. The `staff-padding` property may be overridden to achieve a pleasing baseline.

```
\drums {
  \repeat unfold 2 {
    sn16^"L" sn^"R" sn^"L" sn^"L" sn^"R" sn^"L" sn^"R" sn^"R"
    \stemUp
    sn16_"L" sn_"R" sn_"L" sn_"L" sn_"R" sn_"L" sn_"R" sn_"R"
  }
}
```



## See also

Notation Reference: [\[Tremolo repeats\]](#), page 139.

Snippets: [Section “Percussion” in \*Snippets\*](#).

## Pitched percussion

Certain pitched percussion instruments (e.g. xylophone, vibraphone, and timpani) are written using normal staves. This is covered in other sections of the manual.

## See also

Notation Reference: [Section 3.5.6 \[Percussion in MIDI\]](#), page 466.

Snippets: [Section “Percussion” in \*Snippets\*](#).

## Percussion staves


A percussion part for more than one instrument typically uses a multiline staff where each position in the staff refers to one piece of percussion. To typeset the music, the notes must be interpreted in `DrumStaff` and `DrumVoice` context.

```
up = \drummode {
  crashcymbal4 hihat8 halfopenhihat hh hh hh openhihat
}
down = \drummode {
  bassdrum4 snare8 bd r bd sn4
}
\new DrumStaff <<
  \new DrumVoice { \voiceOne \up }
  \new DrumVoice { \voiceTwo \down }
>>
```



The above example shows verbose polyphonic notation. The short polyphonic notation, described in [Section “I’m hearing Voices” in \*Learning Manual\*](#), can also be used. For example,


```
\new DrumStaff <<
  \drummode {
    bd4 sn4 bd4 sn4
    << {
      \repeat unfold 16 hh16
    } \\ {
      bd4 sn4 bd4 sn4
    } >>
  }
>>
```




There are also other layout possibilities. To use these, set the property `drumStyleTable` in context `DrumVoice`. The following variables have been predefined:

`drums-style`

This is the default. It typesets a typical drum kit on a five-line staff:






The drum scheme supports six different toms. When there are fewer toms, simply select the toms that produce the desired result. For example, to get toms on the three middle lines you use `tommh`, `tomml`, and `tomfh`.


#### timbales-style

This typesets timbales on a two line staff:




#### congas-style

This typesets congas on a two line staff:




#### bongos-style

This typesets bongos on a two line staff:



#### percussion-style

To typeset all kinds of simple percussion on one line staves:




### Custom percussion staves

If you do not like any of the predefined lists you can define your own list at the top of your file.

```
#(define mydrums '(
  (bassdrum      default  #f      -1)
  (snare         default  #f      0)
  (hihat         cross    #f      1)
  (halfopenhihat cross    "halfopen" 1)
  (pedalhihat    xcircle  "stopped" 2)
  (lowtom        diamond  #f      3)))

up = \drummode { hh8 hh hhho hhho hhp4 hhp }
down = \drummode { bd4 sn bd toml8 toml }
```

```
\new DrumStaff <<
  \set DrumStaff.drumStyleTable = #(alist->hash-table mydrums)
  \new DrumVoice { \voiceOne \up }
  \new DrumVoice { \voiceTwo \down }
>>
```



## Selected Snippets

Here are some examples:

Two Woodblocks, entered with wbh (high woodblock) and wbl (low woodblock)

```
% These lines define the position of the woodblocks in the stave;
% if you like, you can change it or you can use special note heads
% for the woodblocks.
#(define mydrums '((hiwoodblock default #t 3)
                  (lowoodblock default #t -2)))


woodstaff = {
  % This defines a staff with only two lines.
  % It also defines the positions of the two lines.
  \override Staff.StaffSymbol #'line-positions = #'(-2 3)

  % This is necessary; if not entered, the barline would be too short!
  \override Staff.BarLine #'bar-extent = #'(-1.5 . 1.5)
}
```

```
\new DrumStaff {
  \set DrumStaff.drumStyleTable = #(alist->hash-table mydrums)

  % with this you load your new drum style table
  \woodstaff

  \drummode {
    \time 2/4
    wbl8 wbl16 wbl wbh8-> wbl |
    wbl8 wbl16 wbh-> ~ wbh wbl16 r8 |
  }
}
```



Note that in this special case the length of the barline must be altered with `\override Staff.BarLine #'bar-extent #'(from . to)`. Otherwise it would be too short. And you have also to define the positions of the two stafflines. For more information about these delicate things have a look at [\[Staff symbol\]](#), page 169.

A tambourine, entered with 'tamb':



```


#(define mydrums '((tambourine default #t 0)))

tambustaff = {
  \override Staff.StaffSymbol #'line-positions = #'( 0 )
  \override Staff.BarLine #'bar-extent = #'(-1.5 . 1.5)
  \set DrumStaff.instrumentName = #"Tambourine"
}

\new DrumStaff {
  \tambustaff
  \set DrumStaff.drumStyleTable = #(alist->hash-table mydrums)

  \drummode {
    \time 6/8
    tamb8. tamb16 tamb8 tamb tamb tamb |
    tamb4. tamb8 tamb tamb |
    % the trick with the scaled duration and the shorter rest
    % is necessary for the correct ending of the trill-span!
    tamb2.*5/6 \startTrillSpan s8 \stopTrillSpan |
  }
}

```



Music for Tam-Tam (entered with 'tt'):

```


#(define mydrums '((tamtam default #t 0)))

tamtamstaff = {
  \override Staff.StaffSymbol #'line-positions = #'( 0 )
  \override Staff.BarLine #'bar-extent = #'(-1.5 . 1.5)
  \set DrumStaff.instrumentName = #"Tamtam"
}

\new DrumStaff {
  \tamtamstaff
  \set DrumStaff.drumStyleTable = #(alist->hash-table mydrums)

  \drummode {
    tt 1 \pp \laissezVibrer
  }
}

```



Two different bells, entered with 'cb' (cowbell) and 'rb' (ridebell)

```

#(define mydrums '((ridebell default #t 3)
  (cowbell default #t -2)))

```

```

bellstaff = {

```

```

\override DrumStaff.StaffSymbol #'line-positions = #'(-2 3)
\set DrumStaff.drumStyleTable = #(alist->hash-table mydrums)
\override Staff.BarLine #'bar-extent = #'(-1.5 . 1.5)
\set DrumStaff.instrumentName = #"Different Bells"
}

\new DrumStaff {
  \bellstaff
  \drummode {
    \time 2/4
    rb8 rb cb cb16 rb-> ~ |
    rb16 rb8 rb16 cb8 cb |
  }
}

```



Here a short example taken from Stravinsky's 'L'histoire du Soldat'.

```

#(define mydrums '((bassdrum default #t 4)
                   (snare default #t -4)
                   (tambourine default #t 0)))

global = {
  \time 3/8 s4.
  \time 2/4 s2*2
  \time 3/8 s4.
  \time 2/4 s2
}

drumsA = {
  \context DrumVoice <<
    { \global }
    { \drummode {
      \autoBeamOff
      \stemDown sn8 \stemUp tamb s8 |
      sn4 \stemDown sn4 |
      \stemUp tamb8 \stemDown sn8 \stemUp sn16 \stemDown sn \stemUp sn8 |
      \stemDown sn8 \stemUp tamb s8 |
      \stemUp sn4 s8 \stemUp tamb
    }
  }
  >>
}

drumsB = {
  \drummode {
    s4 bd8 s2*2 s4 bd8 s4 bd8 s8
  }
}

```

```

\layout {
  indent = #40
}

\score {
  \new StaffGroup <<
    \new DrumStaff {
      \set DrumStaff.instrumentName = \markup {
        \column {
          "Tambourine"
          "et"
          "caisse claire s. timbre"
        }
      }
      \set DrumStaff.drumStyleTable = #(alist->hash-table mydrums)
      \drumsA
    }

    \new DrumStaff {
      \set DrumStaff.instrumentName = #"Grosse Caisse"
      \set DrumStaff.drumStyleTable = #(alist->hash-table mydrums)
      \drumsB }
  >>
}

```

Tambourine  
et  
caisse claire s. timbre

Grosse Caisse

## See also

Snippets: [Section “Percussion” in \*Snippets\*](#).

Internals Reference: [Section “DrumStaff” in \*Internals Reference\*](#), [Section “DrumVoice” in \*Internals Reference\*](#).

## Ghost notes

Ghost notes for drums and percussion may be created using the `\parenthesize` command detailed in [\[Parentheses\]](#), [page 196](#). However, the default `\drummode` does not include the `Parenthesis_engraver` plugin which allows this.

```


\new DrumStaff \with {
  \consists "Parenthesis_engraver"
}
<<
  \context DrumVoice = "1" { s1 }
  \context DrumVoice = "2" { s1 }
  \drummode {
    <<
      {
        hh8[ hh] <hh sn> hh16

```

```

    < \parenthesize sn > hh
    < \parenthesize sn > hh8 <hh sn> hh
  } \\
  {
    bd4 r4 bd8 bd r8 bd
  }
>>
}
>>

```



Also note that you must add chords (< > brackets) around each `\parenthesize` statement.

## See also

Snippets: [Section “Percussion” in Snippets](#).

## 2.6 Wind instruments

**Moderato assai**

This section includes elements of music notation that arise when writing specifically for wind instruments.

### 2.6.1 Common notation for wind instruments

This section discusses notation common to most wind instruments.

## References for wind instruments

Many notation issues for wind instruments pertain to breathing and tonguing:

- Breathing can be specified by rests or [\[Breath marks\]](#), [page 118](#).
- Legato playing is indicated by [\[Slurs\]](#), [page 114](#).
- Different types of tonguings, ranging from legato to non-legato to staccato are usually shown by articulation marks, sometimes combined with slurs, see [\[Articulations and ornamentations\]](#), [page 105](#) and [Section A.12 \[List of articulations\]](#), [page 654](#).
- Flutter tonguing is usually indicated by placing a tremolo mark and a text markup on the note. See [\[Tremolo repeats\]](#), [page 139](#).

Other aspects of musical notation that can apply to wind instruments:

- Many wind instruments are transposing instruments, see [\[Instrument transpositions\]](#), [page 21](#).

- The slide glissando are characteristic of the trombone, but other winds may perform keyed or valved glissandi. See [\[Glissando\]](#), page 120.
- Harmonic series glissandi, which are possible on all brass instruments but common for French Horns, are usually written out as [\[Grace notes\]](#), page 97.
- Pitch inflections at the end of a note are discussed in [\[Falls and doits\]](#), page 119.
- Key slaps or valve slaps are often shown by the **cross** style of [\[Special note heads\]](#), page 32.
- Woodwinds can overblow low notes to sound harmonics. These are shown by the **flageolet** articulation. See [Section A.12 \[List of articulations\]](#), page 654.
- The use of brass mutes is usually indicated by a text markup, but where there are many rapid changes it is better to use the **stopped** and **open** articulations. See [\[Articulations and ornamentations\]](#), page 105 and [Section A.12 \[List of articulations\]](#), page 654.
- Stopped horns are indicated by the **stopped** articulation. See [\[Articulations and ornamentations\]](#), page 105.

## Selected Snippets


*Changing \flageolet mark size*

To make the `\flageolet` circle smaller use the following Scheme function.

```
smallFlageolet =
#(let ((m (make-articulation "flageolet")))
  (set! (ly:music-property m 'tweaks)
    (acons 'font-size -3
      (ly:music-property m 'tweaks)))
  m)

\layout { ragged-right = ##f }

\relative c'' {
  d4~\flageolet_\markup { default size } d_\flageolet
  c4~\smallFlageolet_\markup { smaller } c_\smallFlageolet
}
```



## See also

Notation Reference: [\[Breath marks\]](#), page 118, [\[Slurs\]](#), page 114, [\[Articulations and ornamentations\]](#), page 105, [Section A.12 \[List of articulations\]](#), page 654, [\[Tremolo repeats\]](#), page 139, [\[Instrument transpositions\]](#), page 21, [\[Glissando\]](#), page 120, [\[Grace notes\]](#), page 97, [\[Falls and doits\]](#), page 119, [\[Special note heads\]](#), page 32,

Snippets: [Section “Winds” in Snippets](#).

## Fingerings

All wind instruments other than the trombone require the use of several fingers to produce each pitch. Some fingering examples are shown in the snippets below.

Woodwind diagrams can be produced and are described in [Section 2.6.3.1 \[Woodwind diagrams\]](#), page 359.

## Selected Snippets

### *Fingering symbols for wind instruments*

Special symbols can be achieved by combining existing glyphs, which is useful for wind instruments.

```
centermarkup = {
  \once \override TextScript #'self-alignment-X = #CENTER
  \once \override TextScript #'X-offset =#(ly:make-simple-closure
    `(+
      ,(ly:make-simple-closure (list
        ly:self-alignment-interface::centered-on-x-parent))
      ,(ly:make-simple-closure (list
        ly:self-alignment-interface::x-aligned-on-self))))
}
\score
{\relative c'
  {
    g\open
    \once \override TextScript #'staff-padding = #-1.0 \centermarkup
    g^\markup{\combine \musicglyph #"scripts.open" \musicglyph
      #"scripts.tenuto"}
    \centermarkup g^\markup{\combine \musicglyph #"scripts.open"
      \musicglyph #"scripts.stopped"}
    g\stopped
  }
}
```



### *Recorder fingering chart*

The following example demonstrates how fingering charts for wind instruments can be realized.

% range chart for paetzold contrabass recorder


```
centermarkup = {
  \once \override TextScript #'self-alignment-X = #CENTER
  \once \override TextScript #'X-offset =#(ly:make-simple-closure
    `(+
      ,(ly:make-simple-closure (list
        ly:self-alignment-interface::centered-on-x-parent))
      ,(ly:make-simple-closure (list
        ly:self-alignment-interface::x-aligned-on-self))))
}

\score {
  \new Staff \with {
    \remove "Time_signature_engraver"
    \override Stem #'stencil = ##f
  }
```

```

\override Flag #'stencil = ##f
\consists "Horizontal_bracket_engraver"
}
{
\clef bass
\set Score.timing = ##f
f,1*1/4 \glissando
\clef violin
gis'1*1/4
\stemDown a'4^\markup{1)}
\centermarkup
\once \override TextScript #'padding = #2
bes'1*1/4_\markup{\override #'(baseline-skip . 1.7) \column
{ \fontsize #-5 \slashed-digit #0 \finger 1 \finger 2 \finger 3 \finger 4
\finger 5 \finger 6 \finger 7} }
b'1*1/4
c''4^\markup{1)}
\centermarkup
\once \override TextScript #'padding = #2
cis''1*1/4
deh''1*1/4
\centermarkup
\once \override TextScript #'padding = #2
\once \override Staff.HorizontalBracket #'direction = #UP
e''1*1/4_\markup{\override #'(baseline-skip . 1.7) \column
{ \fontsize #-5 \slashed-digit #0 \finger 1 \finger 2 \finger 4
\finger 5} }\startGroup
f''1*1/4^\markup{2)}\stopGroup
}
}

```



See also

Notation Reference: [Section 2.6.3.1 \[Woodwind diagrams\]](#), page 359.

Snippets: Section “Winds” in *Snippets*.

### 2.6.2 Bagpipes

This section discusses notation common bagpipes.

## Bagpipe definitions

LilyPond contains special definitions for Scottish, Highland Bagpipe music; to use them, add

```
\include "bagpipe.ly"
```

to the top of your input file. This lets you add the special grace notes common to bagpipe music with short commands. For example, you could write `\taor` instead of

```
\grace { \small G32[ d G e ] }
```

‘bagpipe.ly’ also contains pitch definitions for the bagpipe notes in the appropriate octaves, so you do not need to worry about `\relative` or `\transpose`.

```
\include "bagpipe.ly"
```

```
{ \grg G4 \grg a \grg b \grg c \grg d \grg e \grg f \grA g A }
```



Bagpipe music nominally uses the key of D Major (even though that isn’t really true). However, since that is the only key that can be used, the key signature is normally not written out. To set this up correctly, always start your music with `\hideKeySignature`. If you for some reason want to show the key signature, you can use `\showKeySignature` instead.

Some modern music use cross fingering on c and f to flatten those notes. This can be indicated by `cflat` or `fflat`. Similarly, the piobaireachd high g can be written `gflat` when it occurs in light music.

## See also

Section “Winds” in *Snippets*.

## Bagpipe example

This is what the well known tune Amazing Grace looks like in bagpipe notation.

```
\include "bagpipe.ly"
```

```
\layout {
```

```
  indent = 0.0\cm
```

```
  \context { \Score \remove "Bar_number_engraver" }
```

```
}
```

```
\header {
```

```
  title = "Amazing Grace"
```

```
  meter = "Hymn"
```

```
  arranger = "Trad. arr."
```

```
}
```

```
{
```

```
  \hideKeySignature
```

```
  \time 3/4
```

```
  \grg \partial 4 a8. d16
```

```
  \slurd d2 \grg f8[ e32 d16.]
```

```
  \grg f2 \grg f8 e
```

```
  \thrwd d2 \grg b4
```

```
  \grG a2 \grg a8. d16
```

```
  \slurd d2 \grg f8[ e32 d16.]
```



```

\grg f2 \grg e8. f16
\dblA A2 \grg A4
\grg A2 f8. A16
\grg A2 \hdbl f8[ e32 d16.]
\grg f2 \grg f8 e
\thrwd d2 \grg b4
\grG a2 \grg a8. d16
\slurd d2 \grg f8[ e32 d16.]
\grg f2 e4
\thrwd d2.
\slurd d2
\bar "|."
}

```

## Amazing Grace

Hymn

Trad. arr.



See also

Section “Winds” in *Snippets*.

### 2.6.3 Woodwinds

This section discusses notation specifically for woodwind instruments.

#### 2.6.3.1 Woodwind diagrams


Woodwind diagrams can be used to indicate the fingering to be used for specific notes and are available for the following instruments:

- piccolo
- flute
- oboe

- clarinet
- bass clarinet
- saxophone
- bassoon
- contrabassoon

Woodwind diagrams are created as markups:

```
c1^\markup {
  \woodwind-diagram #'piccolo #'((lh . (gis))
                                (cc . (one three))
                                (rh . (ees)))
}
```



Keys can be open, partially-covered, ring-depressed, or fully covered:


```
\textLengthOn
c1^\markup {
  \center-column {
    "one quarter"
    \woodwind-diagram #'flute #'((cc . (one1q))
                                  (lh . ()))
                                  (rh . ()))
  }
}
```

```
c1^\markup {
  \center-column {
    "one half"
    \woodwind-diagram #'flute #'((cc . (one1h))
                                  (lh . ()))
                                  (rh . ()))
  }
}
```

```
c1^\markup {
  \center-column {
    "three quarter"
    \woodwind-diagram #'flute #'((cc . (one3q))
                                  (lh . ()))
                                  (rh . ()))
  }
}
```


```
c1^\markup {
  \center-column {
    "ring"
    \woodwind-diagram #'flute #'((cc . (oneR))
                        (lh . ()))
                        (rh . ()))
  }
}
```

```
c1^\markup {
  \center-column {
    "full"
    \woodwind-diagram #'flute #'((cc . (oneF two))
                        (lh . ()))
                        (rh . ()))
  }
}
```



Trills are indicated as shaded keys:

```
c1^\markup {
  \woodwind-diagram #'bass-clarinete
    #'((cc . (threeT four))
       (lh . ()))
       (rh . (b fis)))
}
```



A variety of trills can be displayed:

```
\textLengthOn
c1^\markup {
```

```

\center-column {
  "one quarter to ring"
  \woodwind-diagram #'flute #'((cc . (one1qTR))
                        (lh . ()))
                        (rh . ()))
}
}


c1^\markup {
  \center-column {
    "ring to shut"
    \woodwind-diagram #'flute #'((cc . (oneTR))
                                    (lh . ()))
                                    (rh . ()))
  }
}

c1^\markup {
  \center-column {
    "ring to open"
    \woodwind-diagram #'flute #'((cc . (oneRT))
                                    (lh . ()))
                                    (rh . ()))
  }
}

c1^\markup {
  \center-column {
    "open to shut"
    \woodwind-diagram #'flute #'((cc . (oneT))
                                    (lh . ()))
                                    (rh . ()))
  }
}

c1^\markup {
  \center-column {
    "one quarter to three quarters"
    \woodwind-diagram #'flute #'((cc . (one1qT3q))
                                    (lh . ()))
                                    (rh . ()))
  }
}

```



The list of all possible keys and settings for a given instrument can be displayed on the console or in the log file, although they will not show up in the music output:

```

#(print-keys-verbose 'flute)

```

New diagrams can be created by following the patterns in ‘`scm/define-woodwind-diagrams.scm`’ and ‘`scm/display-woodwind-diagrams.scm`’. However, this will require Scheme ability and may not be accessible to all users.

## Predefined commands

### Selected Snippets

#### *Woodwind diagrams listing*

The following music shows all of the woodwind diagrams currently defined in LilyPond.

```

\relative c' {
  \textLengthOn
  c1^
  \markup {
    \center-column {
      'piccolo
      " "
      \woodwind-diagram
      #'piccolo
      #'()
    }
  }

  c1^
  \markup {
    \center-column {
      'flute
      " "

```

```

        \woodwind-diagram
        #'flute
        #'()
    }
}
c1^\markup {
  \center-column {
    'oboe
    " "
    \woodwind-diagram
    #'oboe
    #'()
  }
}

c1^\markup {
  \center-column {
    'clarinet
    " "
    \woodwind-diagram
    #'clarinet
    #'()
  }
}

c1^\markup {
  \center-column {
    'bass-clarinet
    " "
    \woodwind-diagram
    #'bass-clarinet
    #'()
  }
}

c1^\markup {
  \center-column {
    'saxophone
    " "
    \woodwind-diagram
    #'saxophone
    #'()
  }
}

c1^\markup {
  \center-column {
    'bassoon
    " "
    \woodwind-diagram
    #'bassoon
    #'()
  }
}


```

```

    }
  }

  c1~\markup {
    \center-column {
      'contrabassoon
      " "
      \woodwind-diagram
      #'contrabassoon
      #'()
    }
  }
}

```



### Graphical and text woodwind diagrams

In many cases, the keys other than the central column can be displayed by key name as well as by graphical means.

```

\relative c'' {
  \textLengthOn
  c1~\markup
    \woodwind-diagram
    #'piccolo


```

```

      #'((cc . (one three))
        (lh . (gis))
        (rh . (ees)))

c^\markup
  \override #'(graphical . #f) {
    \woodwind-diagram
      #'piccolo
      #'((cc . (one three))
        (lh . (gis))
        (rh . (ees)))
  }
}

```



### *Changing the size of woodwind diagrams*

The size and thickness of woodwind diagrams can be changed.

```


\relative c'' {
  \textLengthOn
  c1^\markup
    \woodwind-diagram
      #'piccolo
      #'()

  c^\markup
    \override #'(size . 1.5) {
      \woodwind-diagram
        #'piccolo
        #'()
    }

  c^\markup
    \override #'(thickness . 0.15) {
      \woodwind-diagram
        #'piccolo
        #'()
    }
}

```





### Woodwind diagrams key lists

The snippet below produces a list of all possible keys and key settings for woodwind diagrams as defined in ‘scm/define-woodwind-diagrams.scm’. The list will be displayed on the console and in the log file, but not in the music.

```
#(print-keys-verbose 'piccolo)
#(print-keys-verbose 'flute)
#(print-keys-verbose 'flute-b-extension)
#(print-keys-verbose 'oboe)
#(print-keys-verbose 'clarinet)
#(print-keys-verbose 'bass-clarinet)
#(print-keys-verbose 'low-bass-clarinet)
#(print-keys-verbose 'saxophone)
#(print-keys-verbose 'baritone-saxophone)
#(print-keys-verbose 'bassoon)
#(print-keys-verbose 'contrabassoon)
```

### See also

Installed Files: ‘scm/define-woodwind-diagrams.scm’, ‘scm/display-woodwind-diagrams.scm’.

Snippets: [Section “Winds”](#) in *Snippets*.

Internals Reference: [Section “TextScript”](#) in *Internals Reference*, [Section “instrument-specific-markup-interface”](#) in *Internals Reference*.

## 2.7 Chord notation



1. Fair is the sun - shine, Fair - er the moon - light And all the stars\_in heav'n a - bove;  
2. Fair are the mead - ows, Fair - er the wood - land, Robed in the flowers of blooming spring;

Chords can be entered either as normal notes or in chord mode and displayed using a variety of traditional European chord naming conventions. Chord names and figured bass notation can also be displayed.

### 2.7.1 Chord mode


Chord mode is used to enter chords using an indicator of the chord structure, rather than the chord pitches.

#### Chord mode overview

Chords can be entered as simultaneous music, as discussed in [\[Chorded notes\]](#), page 142.

Chords can also be entered in “chord mode”, which is an input mode that focuses on the structures of chords in traditional European music, rather than on specific pitches. This is convenient for those who are familiar with using chord names to describe chords. More information on different input modes can be found at [Section 5.4.1 \[Input modes\]](#), page 541.


```
\chordmode { c1 g a g c }
```



Chords entered using chord mode are music elements, and can be transposed just like chords entered using simultaneous music. `\chordmode` is absolute, as `\relative` has no effect on `chordmode` blocks. However, in `\chordmode` the absolute pitches are one octave higher than in note mode.

Chord mode and note mode can be mixed in sequential music:

```
<c e g>2 <g b d>
\chordmode { c2 f }
<c e g>2 <g' b d>
\chordmode { f2 g }
```



#### See also

Music Glossary: [Section “chord” in \*Music Glossary\*](#).

Notation Reference: [\[Chorded notes\]](#), page 142, [Section 5.4.1 \[Input modes\]](#), page 541.

Snippets: [Section “Chords” in \*Snippets\*](#).

#### Known issues and warnings

Predefined shorthands for articulations and ornaments cannot be used on notes in chord mode, see [\[Articulations and ornamentations\]](#), page 105.

When chord mode and note mode are mixed in sequential music, and chord mode comes first, the note mode will create a new `Staff` context:

```
\chordmode { c2 f }
<c e g>2 <g' b d>
```



To avoid this behavior, explicitly create the **Staff** context:

```
\new Staff {
  \chordmode { c2 f }
  <c e g>2 <g' b d>
}
```



## Common chords

Major triads are entered by including the root and an optional duration:

```
\chordmode { c2 f4 g }
```




Minor, augmented, and diminished triads are entered by placing : and a quality modifier string after the duration:

```
\chordmode { c2:m f4:aug g:dim }
```





Seventh chords can be created:

```
\chordmode { c1:7 c:m7 c:maj7 c:dim7 c:aug7 }
```




The table below shows the actions of the quality modifiers on triads and seventh chords. The default seventh step added to chords is a minor or flatted seventh, which makes the dominant seventh the basic seventh chord. All alterations are relative to the dominant seventh. A more complete table of modifier usage is found at [Section A.2 \[Common chord modifiers\]](#), page 569.

Modifier	Action	Example
None	The default action; produces a major triad.	
m, m7	The minor chord. This modifier lowers the 3rd.	


dim, dim7      The diminished chord. This modifier lowers the 3rd, 5th and (if present) the 7th step.



aug      The augmented chord. This modifier raises the 5th step.



maj, maj7      The major 7th chord. This modifier adds a raised 7th step. The 7 following maj is optional. Do NOT use this modifier to create a major triad.



## See also

Notation Reference: [Section A.2 \[Common chord modifiers\]](#), page 569, [\[Extended and altered chords\]](#), page 370.

Snippets: [Section “Chords” in \*Snippets\*](#).

## Known issues and warnings


Only one quality modifier should be used per chord, typically on the highest step present in the chord. Chords with more than quality modifier will be parsed without an error or warning, but the results are unpredictable. Chords that cannot be achieved with a single quality modifier should be altered by individual pitches, as described in [\[Extended and altered chords\]](#), page 370.

## Extended and altered chords

Chord structures of arbitrary complexity can be created in chord mode. The modifier string can be used to extend a chord, add or remove chord steps, raise or lower chord steps, and add a bass note or create an inversion.

The first number following the `:` is taken to be the extent of the chord. The chord is constructed by sequentially adding thirds to the root until the specified number has been reached. Note that the seventh step added as part of an extended chord will be the minor or flatted seventh, not the major seventh. If the extent is not a third (e.g., 6), thirds are added up to the highest third below the extent, and then the step of the extent is added. The largest possible value for the extent is 13. Any larger value is interpreted as 13.


```
\chordmode {
  c1:2 c:3 c:4 c:5
  c1:6 c:7 c:8 c:9
  c1:10 c:11 c:12 c:13
  c1:14
}
```



Note that both `c:5` and `c` produce a C major triad.

Since an unaltered 11 does not sound good when combined with an unaltered 13, the 11 is removed from a `:13` chord (unless it is added explicitly).

```
\chordmode {
  c1:13 c:13.11 c:m13
}
```



Individual steps can be added to a chord. Additions follow the extent and are prefixed by a dot (.). The basic seventh step added to a chord is the minor or flatted seventh, rather than the major seventh.

```
\chordmode {
  c1:5.6 c:3.7.8 c:3.6.13
}
```



Added steps can be as high as desired.

```
\chordmode {
  c4:5.15 c:5.20 c:5.25 c:5.30
}
```



Added chord steps can be altered by suffixing a `-` or `+` sign to the number. To alter a step that is automatically included as part of the basic chord structure, add it as an altered step.

```
\chordmode {
  c1:7+ c:5+.3- c:3-.5-.7-
}
```



Following any steps to be added, a series of steps to be removed is introduced in a modifier string with a prefix of `^`. If more than one step is to be removed, the steps to be removed are separated by `.` following the initial `^`.

```
\chordmode {
  c1^3 c:7^5 c:9^3 c:9^3.5 c:13.11^3.7
}
```




The modifier `sus` can be added to the modifier string to create suspended chords. This removes the 3rd step from the chord. Append either 2 or 4 to add the 2nd or 4th step to the chord. `sus` is equivalent to `^3`; `sus4` is equivalent to `.4^3`.

```
\chordmode {
  c1:sus c:sus2 c:sus4 c:5.4^3
}
```




Inversions (putting a pitch other than the root on the bottom of the chord) and added bass notes can be specified by appending */pitch* to the chord.

```
\chordmode {
  c1 c/g c/f
}
```



A bass note that is part of the chord can be added, instead of moved as part of an inversion, by using */+pitch*.

```
\chordmode {
  c1 c/g c/+g
}
```



Chord modifiers that can be used to produce a variety of standard chords are shown in [Section A.2 \[Common chord modifiers\]](#), page 569.

## See also

Notation Reference: [Section A.2 \[Common chord modifiers\]](#), page 569.

Snippets: [Section “Chords” in Snippets](#).

## Known issues and warnings


Each step can only be present in a chord once. The following simply produces the augmented chord, since `5+` is interpreted last.

```
\chordmode { c1:5.5-.5+ }
```



Only the second inversion can be created by adding a bass note. The first inversion requires changing the root of the chord.

```
\chordmode {
  c'1: c':/g e:6-3-~5 e:m6-~5
}
```



## 2.7.2 Displaying chords

Chords can be displayed by name, in addition to the standard display as notes on a staff.

### Printing chord names


Chord names are printed in the `ChordNames` context:

```
\new ChordNames {
  \chordmode {
    c2 f4. g8
  }
}
```

C F G

Chords can be entered as simultaneous notes or through the use of chord mode. The displayed chord name will be the same, regardless of the mode of entry, unless there are inversions or added bass notes:

```
<<
\new ChordNames {
  <c e g>2 <f bes c>
  <f c' e g>1
  \chordmode {
    c2 f:sus4 c1:/f
  }
}
{
  <c e g>2 <f bes c>
  <f, c' e g>1
  \chordmode {
    c2 f:sus4 c1:/f
  }
}
>>
```



Rests passed to a `ChordNames` context will cause the `noChordSymbol` markup to be displayed.

```
<<
\new ChordNames \chordmode {
  c1
```

```

r1
g1
c1
}
\chordmode {
c1
r1
g1
c1
}
>>

```



`\chords { ... }` is a shortcut notation for `\new ChordNames { \chordmode { ... } }`.

```

\chords {
c2 f4.:m g8:maj7
}

```

C Fm G<sup>△</sup>

```

\new ChordNames {
\chordmode {
c2 f4.:m g8:maj7
}
}

```

C Fm G<sup>△</sup>

## Selected Snippets


*Showing chords at changes*

Chord names can be displayed only at the start of lines and when the chord changes.

```

harmonies = \chordmode {
c1:m c:m \break c:m c:m d
}
<<
\new ChordNames {
\set chordChanges = ##t
\harmonies
}
\new Staff {
\relative c' { \harmonies }
}
>>

```







*Simple lead sheet*

When put together, chord names, a melody, and lyrics form a lead sheet:

```
<<
\chords { c2 g:sus4 f e }
\relative c'' {
  a4 e c8 e r4
  b2 c4( d)
}
\addlyrics { One day this shall be free __ }
>>
```



## See also

Music Glossary: [Section “chord” in \*Music Glossary\*](#).

Notation Reference: [\[Writing music in parallel\]](#), page 159.

Snippets: [Section “Chords” in \*Snippets\*](#).

Internals Reference: [Section “ChordNames” in \*Internals Reference\*](#), [Section “ChordName” in \*Internals Reference\*](#), [Section “Chord\\_name\\_engraver” in \*Internals Reference\*](#), [Section “Volta\\_engraver” in \*Internals Reference\*](#), [Section “Bar\\_engraver” in \*Internals Reference\*](#).

## Known issues and warnings

Chords containing inversions or altered bass notes are not named properly if entered using simultaneous music.

## Customizing chord names

There is no unique system for naming chords. Different musical traditions use different names for the same set of chords. There are also different symbols displayed for a given chord name. The names and symbols displayed for chord names are customizable.

The basic chord name layout is a system for Jazz music, proposed by Klaus Ignatzek (see [Section “Literature list” in \*Essay\*](#)). The chord naming system can be modified as described below. An alternate jazz chord system has been developed using these modifications. The Ignatzek and alternate Jazz notation are shown on the chart in [Section A.1 \[Chord name chart\]](#), page 568.

In addition to the different naming systems, different note names are used for the root in different languages. The predefined variables `\germanChords`, `\semiGermanChords`, `\italianChords` and `\frenchChords` set these variables. The effect is demonstrated here:

default	E/D	Cm	B/B	B <sup>#</sup> /B <sup>#</sup>	B <sup>b</sup> /B <sup>b</sup>
german	E/d	Cm	H/h	H <sup>#</sup> /his	B/b
semi-german	E/d	Cm	H/h	H <sup>#</sup> /his	B <sup>b</sup> /b
italian	Mi/Re	Do m	Si/Si	Si <sup>#</sup> /Si <sup>#</sup>	Si <sup>b</sup> /Si <sup>b</sup>
french	Mi/Ré	Do m	Si/Si	Si <sup>#</sup> /Si <sup>#</sup>	Si <sup>b</sup> /Si <sup>b</sup>



German songbooks may indicate minor chords as lowercase letters, without any *m* suffix. This can be obtained by setting the `chordNameLowercaseMinor` property:

```
\chords {
  \set chordNameLowercaseMinor = ##t
  c2 d:m e:m f
}
```

C d e F

If none of the existing settings give the desired output, the chord name display can be tuned through the following properties.

#### `chordRootNamer`

The chord name is usually printed as a letter for the root with an optional alteration. The transformation from pitch to letter is done by this function. Special note names (for example, the German ‘H’ for a B-chord) can be produced by storing a new function in this property.

#### `majorSevenSymbol`

This property contains the markup object used to follow the output of `chordRootNamer` to identify a major 7 chord. Predefined options are `whiteTriangleMarkup` and `blackTriangleMarkup`.

#### `additionalPitchPrefix`

When the chord name contains additional pitches, they can optionally be prefixed with some text. The default is no prefix, in order to avoid too much visual clutter, but for small numbers of additional pitches this can be visually effective.

```
\new ChordNames {
  <c e g d'> % add9
  \set additionalPitchPrefix = #"add"
  <c e g d'> % add9
}
```

C<sup>9</sup> C<sup>add9</sup>

#### `chordNoteNamer`

When the chord name contains additional pitches other than the root (e.g., an added bass note), this function is used to print the additional pitch. By default the pitch is printed using `chordRootNamer`. The `chordNoteNamer` property can be set to a specialized function to change this behavior. For example, the bass note can be printed in lower case.

#### `chordNameSeparator`

Different parts of a chord name are normally separated by a small amount of horizontal space. By setting `chordNameSeparator`, you can use any desired markup for

a separator. This does not affect the separator between a chord and its bass note; to customize that, use `slashChordSeparator`.

```
\chords {
  c4:7.9- c:7.9-/g
  \set chordNameSeparator = \markup { "/" }
  \break
  c4:7.9- c:7.9-/g
}
```

$C^{7\flat 9} C^{7\flat 9}/G$

$C^{7/\flat 9} C^{7/\flat 9}/G$

#### `slashChordSeparator`

Chords can be played over a bass note other than the conventional root of the chord. These are known as “inversions” or “slash chords”, because the default way of notating them is with a forward slash between the main chord and the bass note. Therefore the value of `slashChordSeparator` defaults to a forward slash, but you can change it to any markup you choose.

```
\chords {
  c4:7.9- c:7.9-/g
  \set slashChordSeparator = \markup { " over " }
  \break
  c4:7.9- c:7.9-/g
}
```

$C^{7\flat 9} C^{7\flat 9}/G$

$C^{7\flat 9} C^{7\flat 9} \text{ over } G$

#### `chordNameExceptions`

This property is a list of pairs. The first item in each pair is a set of pitches used to identify the steps present in the chord. The second item is a markup that will follow the `chordRootNamer` output to create the chord name.

#### `minorChordModifier`

Minor chords are often denoted via a ‘m’ suffix to the right of the root of the chord. However some idioms prefer other suffices, such as a minus sign.

```
\chords {
  c4:min f:min7
  \set minorChordModifier = \markup { "-" }
  \break
  c4:min f:min7
}
```

$Cm Fm^7$

$C- F-^7$

**chordPrefixSpacer**

The modifier for minor chords as determined by `minorChordModifier` is usually printed immediately to the right of the root of the chord. A spacer can be placed between the root and the modifier by setting `chordPrefixSpacer`. The spacer is not used when the root is altered.

**Predefined commands**

`\whiteTriangleMarkup`, `\blackTriangleMarkup`, `\germanChords`, `\semiGermanChords`, `\italianChords`, `\frenchChords`.

**Selected Snippets***Chord name exceptions*

The property `chordNameExceptions` can be used to store a list of special notations for specific chords.


```
% modify maj9 and 6(add9)
% Exception music is chords with markups
chExceptionMusic = {
  <c e g b d'>1-\markup { \super "maj9" }
  <c e g a d'>1-\markup { \super "6(add9)" }
}

% Convert music to list and prepend to existing exceptions.
chExceptions = #( append
  ( sequential-music-to-chord-exceptions chExceptionMusic #t)
  ignatzekExceptions)

theMusic = \chordmode {
  g1:maj9 g1:6.9
  \set chordNameExceptions = #chExceptions
  g1:maj9 g1:6.9
}

\layout {
  ragged-right = ##t
}

<< \context ChordNames \theMusic
  \context Voice \theMusic
>>
```

*chord name major7*

The layout of the major 7 can be tuned with `majorSevenSymbol`.

```
\chords {
  c:7+
```

```
\set majorSevenSymbol = \markup { j7 }
c:7+
}
```

$C^{\triangle} C^{j7}$

*Adding bar lines to ChordNames context*

To add bar line indications in the `ChordNames` context, add the `Bar_engraver`.


```
\new ChordNames \with {
  \override BarLine #'bar-extent = #'(-2 . 2)
  \consists "Bar_engraver"
}
\chordmode {
  f1:maj7 f:7 bes:7
}
```

$F^{\triangle} \mid F^7 \mid B\flat^7 \mid$

*Volta below chords*

By adding the `Volta_engraver` to the relevant staff, volte can be put under chords.

```
\score {
  <<
    \chords {
      c1
      c1
    }
    \new Staff \with {
      \consists "Volta_engraver"
    }
    {
      \repeat volta 2 { c'1 }
      \alternative { c' }
    }
  >>
  \layout {
    \context {
      \Score
      \remove "Volta_engraver"
    }
  }
}
```



*Changing chord separator*

The separator between different parts of a chord name can be set to any markup.

```
\chords {
  c:7sus4
  \set chordNameSeparator
    = \markup { \typewriter | }
  c:7sus4
}
```

$C^7 \text{ sus4}$   $C^7 | \text{ sus4}$

**See also**

Notation Reference: [Section A.1 \[Chord name chart\]](#), page 568, [Section A.2 \[Common chord modifiers\]](#), page 569.

Essay on automated music engraving: [Section “Literature list” in \*Essay\*](#).


Installed Files: ‘scm/chords-ignatzek.scm’, ‘scm/chord-entry.scm’, ‘ly/chord-modifier-init.ly’.

Snippets: [Section “Chords” in \*Snippets\*](#).

**Known issues and warnings**

Chord names are determined from both the pitches that are present in the chord and the information on the chord structure that may have been entered in `\chordmode`. If the simultaneous pitches method of entering chords is used, undesired names result from inversions or bass notes.

```
myChords = \relative c' {
  \chordmode { c1 c/g c/f }
  <c e g>1 <g c e> <f c' e g>
}
<<
  \new ChordNames { \myChords }
  \new Staff { \myChords }
>>
```


**2.7.3 Figured bass**

*Adagio.*

Violino I.

Violino II.

Violone,  
e Cembalo.




Figured bass notation can be displayed.

## Introduction to figured bass

LilyPond has support for figured bass, also called thorough bass or basso continuo:

```
<<
\new Voice { \clef bass dis4 c d ais g fis}
\new FiguredBass {
  \figuremode {
    < 6 >4 < 7\+ >8 < 6+ [_!] >
    < 6 >4 <6 5 [3+] >
    < _ >4 < 6 5/>4
  }
}
>>
```



The support for figured bass consists of two parts: there is an input mode, introduced by `\figuremode`, that accepts entry of bass figures, and there is a context named `FiguredBass` that takes care of displaying `BassFigure` objects. Figured bass can also be displayed in `Staff` contexts.

`\figures{ ... }` is a shortcut notation for `\new FiguredBass { \figuremode { ... } }`.

Although the support for figured bass may superficially resemble chord support, it is much simpler. `\figuremode` mode simply stores the figures and the `FiguredBass` context prints them as entered. There is no conversion to pitches.

## See also

Music Glossary: [Section “figured bass” in \*Music Glossary\*](#).

Snippets: [Section “Chords” in \*Snippets\*](#).

## Entering figured bass

`\figuremode` is used to switch the input mode to figure mode. More information on different input modes can be found at [Section 5.4.1 \[Input modes\]](#), page 541.

In figure mode, a group of bass figures is delimited by `<` and `>`. The duration is entered after the `>`.

```
\new FiguredBass {
  \figuremode {
    <6 4>2
```

```
}
}
```

**6**  
**4**

Accidentals (including naturals) can be added to figures:

```
\figures {
  <7! 6+ 4-> <5++> <3-->
}
```

**7** **x5** **b3**  
**#6**  
**b4**

Augmented and diminished steps can be indicated:

```
\figures {
  <6\+ 5/> <7/>
}
```

**+6** **7**  
**5**

A backward slash through a figure (typically used for raised sixth steps) can be created:

```
\figures {
  <6> <6\\>
}
```

**6** **6**

Vertical spaces and brackets can be included in figures:

```
\figures {
  <[12 _!] 8 [6 4]>
}
```

**[12]**  
**[4]**  
**8**  
**[6]**  
**[4]**

Any text markup can be inserted as a figure:

```
\figures {
  <\markup { \tiny \number 6 \super (1) } 5>
}
```

**6**<sup>(1)</sup>  
**5**

Continuation lines can be used to indicate repeated figures:



```
<<
{
  \clef bass
  e4 d c b,
  e4 d c b,
}
\figures {
  \bassFigureExtendersOn
  <6 4>4 <6 3> <7 3> <7 3>
  \bassFigureExtendersOff
  <6 4>4 <6 3> <7 3> <7 3>
}
>>
```



In this case, the extender lines replace existing figures, unless the continuation lines have been explicitly terminated.

```
<<
\figures {
  \bassFigureExtendersOn
  <6 4>4 <6 4> <6\! 4\!> <6 4>
}
{
  \clef bass
  d4 d c c
}
>>
```



The table below summarizes the figure modifiers available.

Modifier	Purpose	Example
+, -, !	Accidentals	$\flat 7 \times 5 \flat 3$ $\sharp 6$ $\flat 4$
\+, /	Augmented and diminished steps	$+6$ $7$ $5$
\\	Raised sixth step	$\overset{\circ}{6}$

\!            End of continuation line



## Predefined commands

\bassFigureExtendersOn, \bassFigureExtendersOff.

## Selected Snippets

*Changing the positions of figured bass alterations*

Accidentals and plus signs can appear before or after the numbers, depending on the `figuredBassAlterationDirection` and `figuredBassPlusDirection` properties.

```
\figures {
  <6\+> <5+> <6 4-> r
  \set figuredBassAlterationDirection = #RIGHT
  <6\+> <5+> <6 4-> r
  \set figuredBassPlusDirection = #RIGHT
  <6\+> <5+> <6 4-> r
  \set figuredBassAlterationDirection = #LEFT
  <6\+> <5+> <6 4-> r
}
```

**+6 #5  $\frac{6}{\flat 4}$       +6 5#  $\frac{6}{4 \flat}$       6+ 5#  $\frac{6}{4 \flat}$       6+ #5  $\frac{6}{\flat 4}$**

## See also

Snippets: [Section “Chords” in \*Snippets\*](#).

Internals Reference: [Section “BassFigure” in \*Internals Reference\*](#), [Section “BassFigureAlign-ment” in \*Internals Reference\*](#), [Section “BassFigureLine” in \*Internals Reference\*](#), [Section “Bass-FigureBracket” in \*Internals Reference\*](#), [Section “BassFigureContinuation” in \*Internals Reference\*](#), [Section “FiguredBass” in \*Internals Reference\*](#).

## Displaying figured bass

Figured bass can be displayed using the `FiguredBass` context, or in most staff contexts.

When displayed in a `FiguredBass` context, the vertical location of the figures is independent of the notes on the staff.

```
<<
\relative c' {
  c4 c'8 r8 c,4 c'
}
\new FiguredBass {
  \figuremode {
    <4>4 <10 6>8 s8
    <6 4>4 <6 4>
  }
}
>>
```



In the example above, the `FiguredBass` context must be explicitly instantiated to avoid creating a second (empty) staff.


Figured bass can also be added to `Staff` contexts directly. In this case, the vertical position of the figures is adjusted automatically.

```
<<
  \new Staff = myStaff
  \figuremode {
    <4>4 <10 6>8 s8
    <6 4>4 <6 4>
  }
  %% Put notes on same Staff as figures
  \context Staff = myStaff
  {
    \clef bass
    c4 c'8 r8 c4 c'
  }
>>
```



When added in a `Staff` context, figured bass can be displayed above or below the staff.

```
<<
  \new Staff = myStaff
  \figuremode {
    <4>4 <10 6>8 s8
    \bassFigureStaffAlignmentDown
    <6 4>4 <6 4>
  }
  %% Put notes on same Staff as figures
  \context Staff = myStaff
  {
    \clef bass
    c4 c'8 r8 c4 c'
  }
>>
```



## Predefined commands

`\bassFigureStaffAlignmentDown,`  
`\bassFigureStaffAlignmentNeutral.`

`\bassFigureStaffAlignmentUp,`

## See also


Snippets: Section “Chords” in *Snippets*.

Internals Reference: Section “BassFigure” in *Internals Reference*, Section “BassFigureAlignment” in *Internals Reference*, Section “BassFigureLine” in *Internals Reference*, Section “BassFigureBracket” in *Internals Reference*, Section “BassFigureContinuation” in *Internals Reference*, Section “FiguredBass” in *Internals Reference*.

## Known issues and warnings

To ensure that continuation lines work properly, it is safest to use the same rhythm in the figure line as in the bass line.

```
<<
{
  \clef bass
  \repeat unfold 4 { f16. g32 } f8. es16 d8 es
}
\figures {
  \bassFigureExtendersOn
  % The extenders are correct here, with the same rhythm as the bass
  \repeat unfold 4 { <6 4->16. <6 4->32 }
  <5>8. r16 <6>8 <6\! 5->
}
>>
<<
{
  \clef bass
  \repeat unfold 4 { f16. g32 } f8. es16 d8 es
}
\figures {
  \bassFigureExtendersOn
  % The extenders are incorrect here, even though the timing is the same
  <6 4->4 <6 4->4
  <5>8. r16 <6>8 <6\! 5->
}
>>
```




When using extender lines, adjacent figures with the same number in a different figure location can cause the figure positions to invert.

```
<<
{ fis4 g g, e' }
\figures {
  \bassFigureExtendersOn
```

```

    <6 5>4 <5\! 4> < 5 _!> <6>
  }
>>

```




To avoid this problem, simply turn on extenders after the figure that begins the extender line and turn them off at the end of the extender line.

```

<<
{ fis4 g g, e' }
\figures {
  <6 5>4 <5 4>
  \bassFigureExtendersOn
  < 5 _!>4 <6>
  \bassFigureExtendersOff
}
>>

```



## 2.8 Contemporary music

From the beginning of the 20th Century there has been a massive expansion of compositional style and technique. New harmonic and rhythmic developments, an expansion of the pitch spectrum and the development of a wide range of new instrumental techniques have been accompanied by a parallel evolution and expansion of musical notation. The purpose of this section is to provide references and information relevant to working with these new notational techniques.

### 2.8.1 Pitch and harmony in contemporary music

This section highlights issues that are relevant to notating pitch and harmony in contemporary music.

#### References for pitch and harmony in contemporary music

- Standard quarter-tone notation is addressed in [\[Note names in other languages\]](#), page 7.
- Non-standard key signatures are addressed in [\[Key signature\]](#), page 19.
- Contemporary practises in displaying accidentals are addressed in [\[Automatic accidentals\]](#), page 22.

#### Microtonal notation

#### Contemporary key signatures and harmony

## 2.8.2 Contemporary approaches to rhythm

This section highlights issues that are relevant to the notation of rhythm in contemporary music.

### References for contemporary approaches to rhythm

- Compound time signatures are addressed in [Time signature], page 56.
- Basic polymetric notation is addressed in [Polymetric notation], page 66.
- Feathered beams are addressed in [Feathered beams], page 84.
- Mensurstriche bar lines (bar lines between staves only) are addressed in [Grouping staves], page 163.

### Tuplets in contemporary music

### Contemporary time signatures

### Extended polymetric notation

### Beams in contemporary music

### Bar lines in contemporary music

## 2.8.3 Graphical notation

## 2.8.4 Contemporary scoring techniques

## 2.8.5 New instrumental techniques

## 2.8.6 Further reading and scores of interest



This section suggests books, musical examples and other resources useful in studying contemporary musical notation.


### Books and articles on contemporary musical notation

- *Music Notation in the Twentieth Century: A Practical Guidebook* by Kurt Stone [W. W. Norton, 1980]
- *Music Notation: A Manual of Modern Practice* by Gardner Read [Taplinger, 1979]
- *Instrumentation and Orchestration* by Alfred Blatter [Schirmer, 2nd ed. 1997]

### Scores and musical examples

## 2.9 Ancient notation





Support for ancient notation includes features for mensural notation and Gregorian chant notation. These features can be accessed either by modifying style properties of graphical objects such as note heads and rests, or by using one of the pre-defined contexts for mensural or Gregorian notation.

Many graphical objects, such as note heads and flags, accidentals, time signatures, and rests, provide a `style` property, which can be changed to emulate several different styles of ancient notation. See

- [Mensural note heads], page 395,
- [Mensural accidentals and key signatures], page 397,
- [Mensural rests], page 396,
- [Mensural clefs], page 393,
- [Gregorian clefs], page 400,
- [Mensural flags], page 396,
- [Mensural time signatures], page 394.

Some notational concepts are introduced specifically for ancient notation,

- [Custodes], page 391,
- [Divisiones], page 401,
- [Ligatures], page 390.

## See also

Music Glossary: Section “custos” in *Music Glossary*, Section “ligature” in *Music Glossary*, Section “mensural notation” in *Music Glossary*.

Notation Reference: [Mensural note heads], page 395, [Mensural accidentals and key signatures], page 397, [Mensural rests], page 396, [Gregorian clefs], page 400, [Mensural flags], page 396, [Mensural time signatures], page 394, [Custodes], page 391, [Divisiones], page 401, [Ligatures], page 390.

### 2.9.1 Overview of the supported styles

Three styles are available for typesetting Gregorian chant:

- *Editio Vaticana* is a complete style for Gregorian chant, following the appearance of the Solesmes editions, the official chant books of the Vatican since 1904. LilyPond has support for all the notational signs used in this style, including ligatures, *custodes*, and special signs such as the quilisma and the oriscus.
- The *Editio Medicaea* style offers certain features used in the Medicaea (or Ratisbona) editions which were used prior to the Solesmes editions. The most significant differences from the *Vaticana* style are the clefs, which have downward-slanted strokes, and the note heads, which are square and regular.
- The *Hufnagel* (“horseshoe nail”) or *Gothic* style mimics the writing style in chant manuscripts from Germany and Central Europe during the middle ages. It is named after the basic note shape (the *virga*), which looks like a small nail.

Three styles emulate the appearance of late-medieval and renaissance manuscripts and prints of mensural music:

- The *Mensural* style most closely resembles the writing style used in late-medieval and early renaissance manuscripts, with its small and narrow, diamond-shaped note heads and its rests which approach a hand-drawn style.
- The *Neomensural* style is a modernized and stylized version of the former: the note heads are broader and the rests are made up of straight lines. This style is particularly suited, e.g., for incipits of transcribed pieces of mensural music.
- The *Petrucchi* style is named after Ottaviano Petrucci (1466-1539), the first printer to use movable type for music (in his *Harmonice musices odhecaton*, 1501). The style uses larger note heads than the other mensural styles.

*Baroque* and *Classical* are not complete styles but differ from the default style only in some details: certain note heads (Baroque) and the quarter rest (Classical).

Only the mensural style has alternatives for all aspects of the notation. Thus, there are no rests or flags in the Gregorian styles, since these signs are not used in plainchant notation, and the Petrucci style has no flags or accidentals of its own.

Each element of the notation can be changed independently of the others, so that one can use mensural flags, petrucci note heads, classical rests and vaticana clefs in the same piece, if one wishes.

## See also

Music Glossary: [Section “mensural notation” in \*Music Glossary\*](#), [Section “flag” in \*Music Glossary\*](#).

## 2.9.2 Ancient notation—common features

### Pre-defined contexts

For Gregorian chant and mensural notation, there are pre-defined voice and staff contexts available, which set all the various notation signs to values suitable for these styles. If one is satisfied with these defaults, one can proceed directly with note entry without worrying about the details on how to customize a context. See one of the pre-defined contexts `VaticanaVoice`, `VaticanaStaff`, `MensuralVoice`, and `MensuralStaff`. See further

- [\[Gregorian chant contexts\]](#), page 399,
- [\[Mensural contexts\]](#), page 392.

## See also

Music Glossary: [Section “mensural notation” in \*Music Glossary\*](#).

Notation Reference: [\[Gregorian chant contexts\]](#), page 399, [\[Mensural contexts\]](#), page 392.

## Ligatures

A ligature is a graphical symbol that represents at least two distinct notes. Ligatures originally appeared in the manuscripts of Gregorian chant notation to denote ascending or descending sequences of notes on the same syllable. They are also used in mensural notation.

Ligatures are entered by *enclosing* them in `\[` and `\]`. Some ligature styles may need additional input syntax specific for this particular type of ligature. By default, the `LigatureBracket` engraver just puts a square bracket above the ligature.

```
\transpose c c' {
  \[ g c a f d' \]
  a g f
  \[ e f a g \]
}
```





Two other ligature styles are available: the *Vaticana* for Gregorian chant, and the *Mensural* for mensural music (only white mensural ligatures are supported for mensural music, and with certain limitations). To use any of these styles, the default `Ligature_bracket_engraver` has to be replaced with one of the specialized ligature engravers in the `Voice` context, as explained in [\[White mensural ligatures\]](#), page 398 and [\[Gregorian square neume ligatures\]](#), page 403.

## See also

Music Glossary: [Section “ligature” in \*Music Glossary\*](#).

Notation Reference: [\[White mensural ligatures\]](#), page 398, [\[Gregorian square neume ligatures\]](#), page 403.

## Known issues and warnings

Ligatures need special spacing that has not yet been implemented. As a result, there is too much space between ligatures most of the time, and line breaking often is unsatisfactory. Also, lyrics do not correctly align with ligatures.

Accidentals must not be printed within a ligature, but instead need to be collected and printed in front of it.


The syntax still uses the deprecated infix style `\[ music expr \]`. For consistency reasons, it will eventually be changed to postfix style `note\[ ... note\]`.

## Custodes

A *custos* (plural: *custodes*; Latin word for “guard”) is a symbol that appears at the end of a staff. It anticipates the pitch of the first note of the following line, thus helping the performer to manage line breaks during performance.

Custodes were frequently used in music notation until the seventeenth century. Nowadays, they have survived only in a few particular forms of musical notation such as contemporary editions of Gregorian chant like the *Editio Vaticana*. There are different custos glyphs used in different flavors of notational style.

For typesetting custodes, just put a `Custos_engraver` into the `Staff` context when declaring the `\layout` block, and change the style of the custos with an `\override` if desired, as shown in the following example:



The custos glyph is selected by the `style` property. The styles supported are `vaticana`, `medicaea`, `hufnagel`, and `mensural`. They are demonstrated in the following fragment.

<code>vaticana</code>	<code>medicaea</code>	<code>hufnagel</code>	<code>mensural</code>
		✓	w

## See also

Music Glossary: [Section “custos”](#) in *Music Glossary*.

Internals Reference: [Section “Custos”](#) in *Internals Reference*.

Snippets: [Section “Ancient notation”](#) in *Snippets*.

## Figured bass support

There is limited support for figured bass notation from the Baroque period; see [Section 2.7.3 \[Figured bass\]](#), page 380.

## See also

Music Glossary: [Section “figured bass”](#) in *Music Glossary*.



Notation Reference: [Section 2.7.3 \[Figured bass\]](#), page 380.

## 2.9.3 Typesetting mensural music

### Mensural contexts

The predefined `MensuralVoice` and `MensuralStaff` contexts can be used to engrave a piece in mensural style. These contexts initialize all relevant context properties and grob properties to proper values, so you can immediately go ahead entering the chant, as the following excerpt demonstrates:

```
\score {
  <<
    \new MensuralVoice = "discantus" \transpose c c' {
      \override Score.BarNumber #'transparent = ##t {
        c'1\melisma bes a g\melismaEnd
        f\breve
        \[ f1\melisma a c'\breve d'\melismaEnd \]
        c'\longa
        c'\breve\melisma a1 g1\melismaEnd
        fis\longa^\signumcongruentiae
      }
    }
    \new Lyrics \lyricsto "discantus" {
      San -- ctus, San -- ctus, San -- ctus
    }
  >>
}
```












## See also

Music Glossary: [Section “mensural notation” in \*Music Glossary\*](#).

## Mensural clefs

The following table shows all mensural clefs that are supported via the `\clef` command. Some of the clefs use the same glyph, but differ only with respect to the line they are printed on. In such cases, a trailing number in the name is used to enumerate these clefs, numbered from the lowest to the highest line. Still, you can manually force a clef glyph to be typeset on an arbitrary line, as described in [\[Clef\]](#), [page 15](#). The note printed to the right side of each clef in the example column denotes the `c'` with respect to that clef.

Petrucchi used C clefs with differently balanced left-side vertical beams, depending on which staff line it is printed.

Description	Supported Clefs	Example
mensural C clef	<code>mensural-c1</code> , <code>mensural-c2</code> , <code>mensural-c3</code> , <code>mensural-c4</code>	
mensural F clef	<code>mensural-f</code>	
mensural G clef	<code>mensural-g</code>	
neomensural C clef	<code>neomensural-c1</code> , <code>neomensural-c2</code> , <code>neomensural-c3</code> , <code>neomensural-c4</code>	
petrucci style C clefs, for use on different staff lines (the example shows the 2nd staff line C clef)	<code>petrucci-c1</code> , <code>petrucci-c2</code> , <code>petrucci-c3</code> , <code>petrucci-c4</code> , <code>petrucci-c5</code>	
petrucci style F clefs, for use on different staff lines (the example shows the 3rd staff line F clef)	<code>petrucci-f3</code> , <code>petrucci-f4</code> , <code>petrucci-f5</code>	
petrucci style G clef	<code>petrucci-g</code>	

## See also

Music Glossary: [Section “mensural notation”](#) in *Music Glossary*, [Section “clef”](#) in *Music Glossary*.

Notation Reference: [\[Clef\]](#), page 15.

## Known issues and warnings


The mensural g clef is mapped to the Petrucci g clef.

## Mensural time signatures

There is limited support for mensuration signs (which are similar to, but not exactly the same as time signatures). The glyphs are hard-wired to particular time fractions. In other words, to get a particular mensuration sign with the `\time n/m` command, `n` and `m` have to be chosen according to the following table

$\text{C}$	$\text{C}$	$\text{C}$	$\text{C}$
<code>\time 4/4</code>	<code>\time 6/4</code>	<code>\time 2/2</code>	<code>\time 6/8</code>
$\text{O}$	$\text{O}$	$\text{O}$	$\text{O}$
<code>\time 3/2</code>	<code>\time 3/4</code>	<code>\time 9/4</code>	<code>\time 9/8</code>
$\text{C}$	$\text{C}$		
<code>\time 4/8</code>	<code>\time 2/4</code>		

Use the `style` property of grob `TimeSignature` to select ancient time signatures. Supported styles are `neomensural` and `mensural`. The above table uses the `neomensural` style. The following examples show the differences in style:



[\[Time signature\]](#), page 56, gives a general introduction to the use of time signatures.

## See also

Music Glossary: [Section “mensural notation”](#) in *Music Glossary*.

Notation Reference: [\[Time signature\]](#), page 56.

## Known issues and warnings

Ratios of note durations cannot change with the time signature, as those are not constant. For example, the ratio of 1 breve = 3 semibreves (*tempus perfectum*) can be made by hand, by setting

```
breveTP = #(ly:make-duration -1 0 3 2)
...
{ c\breveTP f1 }
```

This sets **breveTP** to 3/2 times 2 = 3 times a whole note.

The mensural68alt and neomensural68alt symbols (alternate symbols for 6/8) are not addressable with \time. Use \markup {\musicglyph #"timesig.mensural68alt"} instead.

## Mensural note heads

For ancient notation, a note head style other than the `default` style may be chosen. This is accomplished by setting the `style` property of the `NoteHead` object to `baroque`, `neomensural`, `mensural`, `petrucci`, `blackpetrucci` or `semipetrucci`.

The `baroque` style differs from the `default` style by:

- Providing a `maxima` note head, and
- Using a square shape for `\breve` note heads.

The `neomensural`, `mensural`, and `petrucci` styles differ from the `baroque` style by:


- Using rhomboidal heads for semibreves and all smaller durations, and
- Centering the stems on the note heads.

The `blackpetrucci` style produces note heads usable in black mensural notation or coloratio sections in white mensural notation. Because note head style does not influence flag count, in this style a semiminima should be notated as `a8*2`, not `a4`, otherwise it will look like a minima. The multiplier can be different if coloratio is used e.g. to notate triplets.

Use `semipetrucchi` style to draw half-colored note heads (breves, longas and maximas).

The following example demonstrates the `petrucci` style:

```
\set Score.skipBars = ##t
\autoBeamOff
\override NoteHead #'style = #'petrucci
a'\maxima a'\longa a'\breve a'1 a'2 a'4 a'8 a'16 a'
\override NoteHead #'style = #'semipetrucci
a'\breve*5/6
\override NoteHead #'style = #'blackpetrucci
a'8*4/3 a'
\override NoteHead #'style = #'petrucci
a'\longa
```



Section A.8 [Note head styles], page 608, gives an overview of all available note head styles.

See also


Music Glossary: Section “mensural notation” in *Music Glossary*, Section “note head” in *Music Glossary*.

Notation Reference: Section A.8 [Note head styles], page 608.

## Mensural flags

Use the `flag-style` property of grob `Stem` to select ancient flags. Besides the default flag style, only the `mensural` style is supported.

```
\override Flag #'style = #'mensural
\override Stem #'thickness = #1.0
\override NoteHead #'style = #'mensural
\autoBeamOff
c'8 d'8 e'8 f'8 c'16 d'16 e'16 f'16 c'32 d'32 e'32 f'32 s8
c''8 d''8 e''8 f''8 c''16 d''16 e''16 f''16 c''32 d''32 e''32 f''32
```



Note that the innermost flare of each mensural flag always is vertically aligned with a staff line.

There is no particular flag style for neo-mensural or Petrucci notation. There are no flags in Gregorian chant notation.

## See also

Music Glossary: [Section “mensural notation”](#) in *Music Glossary*, [Section “flag”](#) in *Music Glossary*.

## Known issues and warnings

The attachment of ancient flags to stems is slightly off.

Vertically aligning each flag with a staff line assumes that stems always end either exactly on or exactly in the middle between two staff lines. This may not always be true when using advanced layout features of classical notation (which however are typically out of scope for mensural notation).


## Mensural rests

Use the `style` property of grob `Rest` to select ancient rests. Supported styles are `classical`, `neomensural`, and `mensural`. `classical` differs from the default style only in that the quarter rest looks like a horizontally mirrored 8th rest. The `mensural` and the `neomensural` styles mimic the appearance of rests in manuscripts and prints up to the 16th century.

The following example demonstrates the `mensural` and `neomensural` styles:

```
\set Score.skipBars = ##t
\override Rest #'style = #'classical
r\longa^"classical" r\breve r1 r2 r4 r8 r16 s \break
\override Rest #'style = #'mensural
r\longa^"mensural" r\breve r1 r2 r4 r8 r16 s \break
\override Rest #'style = #'neomensural
r\longa^"neomensural" r\breve r1 r2 r4 r8 r16
```





There are no 32th and 64th rests specifically for the mensural or neo-mensural style. Instead, the rests from the default style will be taken.

## See also

Music Glossary: [Section “mensural notation” in \*Music Glossary\*](#).

Notation Reference: [\[Rests\]](#), page 49.

Snippets: [Section “Ancient notation” in \*Snippets\*](#).

## Known issues and warnings

The glyph for the maxima rest in mensural style is actually a perfect longa rest; use two (or three) longa rests to print a maxima rest. Longa rests are not grouped automatically, so have to be done manually by using pitched rests.

## Mensural accidentals and key signatures

The `mensural` style provides a sharp and a flat sign different from the default style. If called for, the natural sign will be taken from the `vaticana` style.

### mensural

♭ ✖

The style for accidentals and key signatures is controlled by the `glyph-name-alist` property of the grobs `Accidental` and `KeySignature`, respectively; e.g.:

```
\override Staff.Accidental #'glyph-name-alist = #alteration-mensural-glyph-name-alist
```

## See also

Music Glossary: [Section “mensural notation” in \*Music Glossary\*](#), [Section “Pitch names” in \*Music Glossary\*](#), [Section “accidental” in \*Music Glossary\*](#), [Section “key signature” in \*Music Glossary\*](#).

Notation Reference: [Section 1.1 \[Pitches\]](#), page 1, [\[Accidentals\]](#), page 5, [\[Automatic accidentals\]](#), page 22, [\[Key signature\]](#), page 19.

Internals Reference: [Section “KeySignature” in \*Internals Reference\*](#).

## Annotational accidentals (*musica ficta*)

In European music from before about 1600, singers were expected to chromatically alter notes at their own initiative according to certain rules. This is called *musica ficta*. In modern transcriptions, these accidentals are usually printed over the note.

Support for such suggested accidentals is included, and can be switched on by setting `suggestAccidentals` to true.

```
fis gis
\set suggestAccidentals = ##t
ais bis
```



This will treat *every* subsequent accidental as *musica ficta* until it is unset with `\set suggestAccidentals = ##f`. A more practical way is to use `\once \set suggestAccidentals = ##t`, which can even be defined as a convenient shorthand:

```
ficta = { \once \set suggestAccidentals = ##t }
\score { \relative c''
  \new MensuralVoice {
    \once \set suggestAccidentals = ##t
    bes4 a2 g2 \ficta fis8 \ficta e! fis2 g1
  }
}
```



## See also

Internals Reference: [Section “Accidental\\_engraver” in \*Internals Reference\*](#), [Section “AccidentalSuggestion” in \*Internals Reference\*](#).

## White mensural ligatures

There is limited support for white mensural ligatures.

To engrave white mensural ligatures, in the layout block, replace the `Ligature_bracket_engraver` with the `Mensural_ligature_engraver` in the `Voice` context:

```
\layout {
  \context {
    \Voice
    \remove Ligature_bracket_engraver
    \consists Mensural_ligature_engraver
  }
}
```

There is no additional input language to describe the shape of a white mensural ligature. The shape is rather determined solely from the pitch and duration of the enclosed notes. While this approach may take a new user a while to get accustomed to, it has the great advantage that the full musical information of the ligature is known internally. This is not only required for correct MIDI output, but also allows for automatic transcription of the ligatures.

At certain places two consecutive notes can be represented either as two squares or as an oblique parallelogram (flexa shape). In such cases the default is the two squares, but a flexa can be required by setting the `ligature-flexa` property of the *second* note head. The length of a flexa can be set by the note head property `flexa-width`.

For example,


```
\score {
  \transpose c c' {
    \set Score.timing = ##f
    \set Score.defaultBarType = "empty"
    \override NoteHead #'style = #'petrucci
    \override Staff.TimeSignature #'style = #'mensural
```



```

\clef "petrucci-g"
\[ c'\maxima g \]
\[ d\longa
  \override NoteHead #'ligature-flexa = ##t
  \once \override NoteHead #'flexa-width = #3.2
  c\breve f e d \]
\[ c'\maxima d'\longa \]
\[ e'1 a g\breve \]
}
\layout {
  \context {
    \Voice
    \remove Ligature_bracket_engraver
    \consists Mensural_ligature_engraver
  }
}

```



Without replacing `Ligature_bracket_engraver` with `Mensural_ligature_engraver`, the same music transcribes to the following



## See also

Music Glossary: [Section “ligature” in \*Music Glossary\*](#).

Notation Reference: [\[Gregorian square neume ligatures\]](#), page 403, [\[Ligatures\]](#), page 390.

## Known issues and warnings

Horizontal spacing of ligatures is poor. Accidentals may collide with previous notes.

### 2.9.4 Typesetting Gregorian chant

When typesetting a piece in Gregorian chant notation, the `Vaticana_ligature_engraver` automatically selects the proper note heads, so there is no need to explicitly set the note head style. Still, the note head style can be set, e.g., to `vaticana_punctum` to produce punctum neumes. Similarly, the `Mensural_ligature_engraver` automatically assembles mensural ligatures.

## See also

Music Glossary: [Section “ligature” in \*Music Glossary\*](#).

Notation Reference: [\[White mensural ligatures\]](#), page 398, [\[Ligatures\]](#), page 390.

## Gregorian chant contexts

The predefined `VaticanaVoiceContext` and `VaticanaStaffContext` can be used to engrave a piece of Gregorian chant in the style of the Editio Vaticana. These contexts initialize all relevant context properties and grob properties to proper values, so you can immediately go ahead entering the chant, as the following excerpt demonstrates:

```

\include "gregorian.ly"
\score {
  <<
    \new VaticanaVoice = "cantus" {
      \[ c'\melisma c' \flexa a \]
      \[ a \flexa \deminutum g\melismaEnd \]
      f \divisioMinima
      \[ f\melisma \pes a c' c' \pes d'\melismaEnd \]
      c' \divisioMinima \break
      \[ c'\melisma c' \flexa a \]
      \[ a \flexa \deminutum g\melismaEnd \] f \divisioMinima
    }
    \new Lyrics \lyricsto "cantus" {
      San- ctus, San- ctus, San- ctus
    }
  >>
}

```







San-ctus, San-ctus,




San-ctus

## Gregorian clefs

The following table shows all Gregorian clefs that are supported via the `\clef` command. Some of the clefs use the same glyph, but differ only with respect to the line they are printed on. In such cases, a trailing number in the name is used to enumerate these clefs, numbered from the lowest to the highest line. Still, you can manually force a clef glyph to be typeset on an arbitrary line, as described in [Clef], page 15. The note printed to the right side of each clef in the example column denotes the `c'` with respect to that clef.

Description	Supported Clefs	Example
Editio Vaticana style do clef	<code>vaticana-do1</code> , <code>vaticana-do2</code> , <code>vaticana-do3</code>	
Editio Vaticana style fa clef	<code>vaticana-fa1</code> , <code>vaticana-fa2</code>	
Editio Medicaea style do clef	<code>medicaea-do1</code> , <code>medicaea-do2</code> , <code>medicaea-do3</code>	
Editio Medicaea style fa clef	<code>medicaea-fa1</code> , <code>medicaea-fa2</code>	

hufnagel style do clef

hufnagel-do1, hufnagel-do2,  
hufnagel-do3

hufnagel style fa clef

hufnagel-fa1, hufnagel-fa2



hufnagel style combined do/fa clef

hufnagel-do-fa



## See also

Music Glossary: [Section “clef” in \*Music Glossary\*](#).

Notation Reference: [\[Clef\]](#), page 15.

## Gregorian accidentals and key signatures

Accidentals for the three different Gregorian styles are available:

### vaticana medicaea hufnagel



As shown, not all accidentals are supported by each style. When trying to access an unsupported accidental, LilyPond will switch to a different style.

The style for accidentals and key signatures is controlled by the `glyph-name-alist` property of the grobs `Accidental` and `KeySignature`, respectively; e.g.:

```
\override Staff.Accidental #'glyph-name-alist = #alteration-mensural-glyph-name-alist
```

## See also

Music Glossary: [Section “accidental” in \*Music Glossary\*](#), [Section “key signature” in \*Music Glossary\*](#).

Notation Reference: [Section 1.1 \[Pitches\]](#), page 1, [\[Accidentals\]](#), page 5, [\[Automatic accidentals\]](#), page 22, [\[Key signature\]](#), page 19.


Internals Reference: [Section “KeySignature” in \*Internals Reference\*](#).

## Divisiones

There are no rests in Gregorian chant notation; instead, it uses [\[Divisiones\]](#), page 401.

A *divisio* (plural: *divisiones*; Latin word for ‘division’) is a staff context symbol that is used to indicate the phrase and section structure of Gregorian music. The musical meaning of *divisio minima*, *divisio maior*, and *divisio maxima* can be characterized as short, medium, and long pause, somewhat like the breath marks from [\[Breath marks\]](#), page 118. The *finalis* sign not only marks the end of a chant, but is also frequently used within a single antiphonal/responsorial chant to mark the end of each section.

To use divisiones, include the file ‘`gregorian.ly`’. It contains definitions that you can apply by just inserting `\divisioMinima`, `\divisioMaior`, `\divisioMaxima`, and `\finalis` at proper places in the input. Some editions use *virgula* or *caesura* instead of *divisio minima*. Therefore, ‘`gregorian.ly`’ also defines `\virgula` and `\caesura`.



## Predefined commands

`\virgula`, `\caesura`, `\divisioMinima`, `\divisioMaior`, `\divisioMaxima`, `\finalis`.

## See also

Music Glossary: [Section “caesura” in \*Music Glossary\*](#), [Section “divisio” in \*Music Glossary\*](#).






Notation Reference: [\[Breath marks\]](#), page 118.

Installed Files: ‘gregorian.ly’.

## Gregorian articulation signs

In addition to the standard articulation signs described in section [\[Articulations and ornamentations\]](#), page 105, articulation signs specifically designed for use with notation in *Editio Vaticana* style are provided.

```
\include "gregorian.ly"
\score {
  \new VaticanaVoice {
    \override TextScript #'font-family = #'typewriter
    \override TextScript #'font-shape = #'upright
    \override Script #'padding = #-0.1
    a\ictus_"ictus " \bar "" \break
    a\circulus_"circulus " \bar "" \break
    a\semicirculus_"semicirculus " \bar "" \break
    a\accentus_"accentus " \bar "" \break
    \[ a_"episema" \epistemInitium \pes b \flexa a b \epistemFinis \flexa a \]
  }
}
```



## See also

Notation Reference: [Articulations and ornamentations], page 105.

Snippets: Section “Ancient notation” in *Snippets*.

Internals Reference: Section “Episema” in *Internals Reference*, Section “EpisemaEvent” in *Internals Reference*, Section “Episema\_engraver” in *Internals Reference*, Section “Script” in *Internals Reference*, Section “ScriptEvent” in *Internals Reference*, Section “Script\_engraver” in *Internals Reference*.

## Known issues and warnings

Some articulations are vertically placed too closely to the corresponding note heads.

## Augmentum dots (*morae*)

Augmentum dots, also called *morae*, are added with the music function `\augmentum`. Note that `\augmentum` is implemented as a unary music function rather than as head prefix. It applies to the immediately following music expression only. That is, `\augmentum \virga c` will have no visible effect. Instead, say `\virga \augmentum c` or `\augmentum {\virga c}`. Also note that you can say `\augmentum {a g}` as a shortcut for `\augmentum a \augmentum g`.

```
\include "gregorian.ly"
\score {
  \new VaticanaVoice {
    \[ \augmentum a \flexa \augmentum g \]
    \augmentum g
  }
}
```



## See also

Notation Reference: [Breath marks], page 118.

Internals Reference: Section “BreathingSign” in *Internals Reference*.

Snippets: Section “Ancient notation” in *Snippets*.

## Gregorian square neume ligatures

There is limited support for Gregorian square neumes notation (following the style of the Editio Vaticana). Core ligatures can already be typeset, but essential issues for serious typesetting are still lacking, such as (among others) horizontal alignment of multiple ligatures, lyrics alignment, and proper handling of accidentals.

The support for Gregorian neumes is enabled by `\includeing ‘gregorian.ly’` at the beginning of the file. This makes available a number of extra commands to produce the neume symbols used in plainchant notation.

Note heads can be *modified* and/or *joined*.

- The shape of the note head can be modified by *prefixing* the note name with any of the following commands: `\virga`, `\strophæ`, `\inclinatum`, `\auctum`, `\descendens`, `\ascendens`, `\oriscus`, `\quilisma`, `\deminutum`, `\cavum`, `\linea`.
- Ligatures, properly speaking (i.e. notes joined together), are produced by placing one of the joining commands `\pes` or `\flexa`, for upwards and downwards movement, respectively, *between* the notes to be joined.

A note name without any qualifiers will produce a *punctum*. All other neumes, including the single-note neumes with a different shape such as the *virga*, are in principle considered as ligatures and should therefore be placed between `\[...]`.

Single-note neumes:

- The *punctum* is the basic note shape (in the *Vaticana* style: a square with some curvation for typographical finesse). In addition to the regular *punctum*, there is also the oblique *punctum inclinatum*, produced with the prefix `\inclinatum`. The regular *punctum* can be modified with `\cavum`, which produces a hollow note, and `\linea`, which draws vertical lines on either side of the note.
- The *virga* has a descending stem on the right side. It is produced by the modifier `\virga`.

Ligatures

Unlike most other neumes notation systems, the typographical appearance of ligatures is not directly dictated by the input commands, but follows certain conventions dependent on musical meaning. For example, a three-note ligature with the musical shape low-high-low, such as `\[ a \pes b \flexa g ]`, produces a Torculus consisting of three Punctum heads, while the shape high-low-high, such as `\[ a \flexa g \pes b ]`, produces a Porrectus with a curved flexa shape and only a single Punctum head. There is no command to explicitly typeset the curved flexa shape; the decision of when to typeset a curved flexa shape is based on the musical input. The idea of this approach is to separate the musical aspects of the input from the notation style of the output. This way, the same input can be reused to typeset the same music in a different style of Gregorian chant notation.

Liquescent neumes

Another main category of notes in Gregorian chant is the so-called liquescent neumes. They are used under certain circumstances at the end of a syllable which ends in a ‘liquescent’ letter, i.e. the sounding consonants that can hold a tone (the nasals, l, r, v, j, and their diphthong equivalents). Thus, the liquescent neumes are never used alone (although some of them can be produced), and they always fall at the end of a ligature.

Liquescent neumes are represented graphically in two different, more or less interchangeable ways: with a smaller note or by ‘twisting’ the main note upwards or downwards. The first is produced by making a regular `pes` or `flexa` and modifying the shape of the second note: `\[ a \pes \deminutum b ]`, the second by modifying the shape of a single-note neume with `\auctum` and one of the direction markers `\descendens` or `\ascendens`, e.g., `\[ \auctum \descendens a ]`.

Special signs

A third category of signs is made up of a small number of signs with a special meaning (which, incidentally, in most cases is only vaguely known): the *quilisma*, the *oriscus*, and the *strophicus*. These are all produced by prefixing a note name with the corresponding modifier, `\quilisma`, `\oriscus`, or `\strophica`.

Virtually, within the ligature delimiters `\[` and `\]`, any number of heads may be accumulated to form a single ligature, and head prefixes like `\pes`, `\flexa`, `\virga`, `\inclinatum`, etc. may be mixed in as desired. The use of the set of rules that underlies the construction of the ligatures in the above table is accordingly extrapolated. This way, infinitely many different ligatures can be created.








Note that the use of these signs in the music itself follows certain rules, which are not checked by LilyPond. E.g., the *quilisma* is always the middle note of an ascending ligature, and usually falls on a half-tone step, but it is perfectly possible, although incorrect, to make a single-note quilisma.

In addition to the note signs, ‘gregorian.ly’ also defines the commands `\versus`, `\responsum`, `\ij`, `\iij`, `\IJ`, and `\IIJ`, that will produce the corresponding characters, e.g.,

for use in lyrics, as section markers, etc. These commands use special Unicode characters and will only work if a font is used which supports them.

The following table shows a limited, but still representative pool of Gregorian ligatures, together with the code fragments that produce the ligatures. The table is based on the extended neumes table of the 2nd volume of the *Antiphonale Romanum* (*Liber Hymnarius*), published 1983 by the monks of Solesmes. The first column gives the name of the ligature, with the main form in boldface and the liquescent forms in italics. The third column shows the code fragment that produces this ligature, using **g**, **a**, and **b** as example pitches.

### Single-note neums

Basic and <i>Liquescent</i> forms	Output	LilyPond code
<b>Punctum</b>		<code>\[ b \]</code>
		<code>\[ \cavum b \]</code>
		<code>\[ \linea b \]</code>
<i>Punctum Auctum Ascendens</i>		<code>\[ \auctum \ascendens b \]</code>
<i>Punctum Auctum Descendens</i>		<code>\[ \auctum \descendens b \]</code>
<b>Punctum inclinatum</b>		<code>\[ \inclinatum b \]</code>
<i>Punctum Inclinatum Auctum</i>		<code>\[ \inclinatum \auctum b \]</code>

*Punctum Inclinatum Parvum*

\[ \inclinatum \deminutum b \]

•

**Virga**

┐

**Two-note ligatures****Clivis vel Flexa**

\[ b \flexa g \]

┌┐

*Clivis Aucta Descendens*\[ b \flexa \auctum \descendens  
g \]

┌┐

*Clivis Aucta Ascendens*\[ b \flexa \auctum \ascendens  
g \]

┐┌

*Cephalicus*

\[ b \flexa \deminutum g \]

┌

**Podatus/Pes**

\[ g \pes b \]

┐┌

*Pes Auctus Descendens*\[ g \pes \auctum \descendens b  
\]

┐┌

*Pes Auctus Ascendens*\[ g \pes \auctum \ascendens b  
\]

┐┌



*Epiphonus*

\[ g \pes \deminutum b \]

*Pes Initio Debilis*

\[ \deminutum g \pes b \]

*Pes Auctus Descendens Initio Debilis*\[ \deminutum g \pes \auctum  
\descendens b \]**Multi-note ligatures****Torculus**

\[ a \pes b \flexa g \]

*Torculus Auctus Descendens*\[ a \pes b \flexa \auctum  
\descendens g \]*Torculus Deminutus*\[ a \pes b \flexa \deminutum g  
\]*Torculus Initio Debilis*\[ \deminutum a \pes b \flexa g  
\]*Torculus Auctus Descendens Initio  
Debilis*\[ \deminutum a \pes b \flexa  
\auctum \descendens g \]*Torculus Deminutus Initio Debilis*\[ \deminutum a \pes b \flexa  
\deminutum g \]

**Porrectus** $\backslash[ a \backslash flexa g \backslash pes b \backslash]$ *Porrectus Auctus Descendens* $\backslash[ a \backslash flexa g \backslash pes \backslash auctum \backslash descendens b \backslash]$ *Porrectus Deminutus* $\backslash[ a \backslash flexa g \backslash pes \backslash deminutum b \backslash]$ **Climacus** $\backslash[ \backslash virga b \backslash inclinatum a \backslash inclinatum g \backslash]$ *Climacus Auctus* $\backslash[ \backslash virga b \backslash inclinatum a \backslash inclinatum \backslash auctum g \backslash]$ *Climacus Deminutus* $\backslash[ \backslash virga b \backslash inclinatum a \backslash inclinatum \backslash deminutum g \backslash]$ **Scandicus** $\backslash[ g \backslash pes a \backslash virga b \backslash]$ *Scandicus Auctus Descendens* $\backslash[ g \backslash pes a \backslash pes \backslash auctum \backslash descendens b \backslash]$ *Scandicus Deminutus* $\backslash[ g \backslash pes a \backslash pes \backslash deminutum b \backslash]$ **Special Signs**

**Quilisma** $\backslash[ g \backslash pes \backslash quilisma a \backslash pes b \backslash]$ *Quilisma Pes Auctus Descendens* $\backslash[ \backslash quilisma g \backslash pes \backslash auctum \backslash descendens b \backslash]$ **Oriscus** $\backslash[ \backslash oriscus b \backslash]$ *Pes Quassus* $\backslash[ \backslash oriscus g \backslash pes \backslash virga b \backslash]$ *Pes Quassus Auctus Descendens* $\backslash[ \backslash oriscus g \backslash pes \backslash auctum \backslash descendens b \backslash]$ **Salicus** $\backslash[ g \backslash oriscus a \backslash pes \backslash virga b \backslash]$ *Salicus Auctus Descendens* $\backslash[ g \backslash oriscus a \backslash pes \backslash auctum \backslash descendens b \backslash]$ **(Apo)stroph** $\backslash[ \backslash stroph a b \backslash]$ *Stroph Aucta* $\backslash[ \backslash stroph a \backslash auctum b \backslash]$ **Bistroph** $\backslash[ \backslash stroph a b \backslash stroph a b \backslash]$ 

**Tristropha**

◆◆◆

```
\[ \stroph a b \stroph a b
\stroph a b \]
```

*Trigonus*

◆◆,

```
\[ \stroph a b \stroph a b
\stroph a a \]
```

**Predefined commands**

The following head prefixes are supported: `\virga`, `\stroph a`, `\inclinatum`, `\auctum`, `\descendens`, `\ascendens`, `\oriscus`, `\quilisma`, `\deminutum`, `\cavum`, `\linea`.

Head prefixes can be accumulated, though restrictions apply. For example, either `\descendens` or `\ascendens` can be applied to a head, but not both to the same head.

Two adjacent heads can be tied together with the `\pes` and `\flexa` infix commands for a rising and falling line of melody, respectively.

Use the unary music function `\augmentum` to add augmentum dots.

**See also**

Music Glossary: [Section “ligature” in \*Music Glossary\*](#).

Notation Reference: [\[Gregorian square neume ligatures\]](#), page 403, [\[White mensural ligatures\]](#), page 398, [\[Ligatures\]](#), page 390.

**Known issues and warnings**

When an `\augmentum` dot appears at the end of the last staff within a ligature, it is sometimes vertically placed wrong. As a workaround, add an additional skip note (e.g., `s8`) as last note of the staff.

`\augmentum` should be implemented as a head prefix rather than a unary music function, such that `\augmentum` can be intermixed with head prefixes in arbitrary order.

**2.9.5 Working with ancient music—scenarios and solutions**

Working with ancient music frequently involves particular tasks which differ considerably from the modern notation for which LilyPond is designed. In the rest of this section, a number of typical scenarios are outlined, with suggestions of solutions. These involve:

- how to make incipits (i.e. prefatory material to indicate what the original has looked like) to modern transcriptions of mensural music;
- how to achieve the *Mensurstriche* layout frequently used for modern transcriptions of polyphonic music;
- how to transcribe Gregorian chant in modern notation;
- how to generate both ancient and modern notation from the same source.

**Incipits**

TBC


**Mensurstriche layout**

*Mensurstriche* (‘mensuration lines’) is the accepted term for bar lines that are drawn between the staves of a system but not through the staves themselves. It is a common way to preserve

the rhythmic appearance of the original, i.e. not having to break syncopated notes at bar lines, while still providing the orientation aids that bar lines give.

The mensurstriche-layout where the bar lines do not show on the staves but between staves can be achieved with a `StaffGroup` instead of a `ChoirStaff`. The bar line on staves is blanked out by setting the `transparent` property.

```
global = {
  \override Staff.BarLine #'transparent = ##t
  s1 s
  % the final bar line is not interrupted
  \revert Staff.BarLine #'transparent
  \bar "|."
}
\new StaffGroup \relative c'' {
  <<
    \new Staff { << \global { c1 c } >> }
    \new Staff { << \global { c c } >> }
  >>
}
```



## Transcribing Gregorian chant

Gregorian chant can be transcribed into modern notation with a number of simple tweaks.

**Stems.** Stems can be left out altogether by `\remove`-ing the `Stem_engraver` from the `Voice` context:

```
\layout {
  ...
  \context {
    \Voice
    \remove "Stem_engraver"
  }
}
```

However, in some transcription styles, stems are used occasionally, for example to indicate the transition from a single-tone recitative to a fixed melodic gesture. In these cases, one can use either `\override Stem #'transparent = ##t` or `\override Stem #'length = #0` instead, and restore the stem when needed with the corresponding `\once \override Stem #'transparent = ##f` (see example below). When using stems that carry flags, make sure to set `\override Flag #'transparent = ##t` as well.

**Timing.** For unmetered chant, there are several alternatives.

The `Time_signature_engraver` can be removed from the `Staff` context without any negative side effects. The alternative, to make it transparent, will leave an empty space in the score, since the invisible signature will still take up space.

In many cases, `\set Score.timing = ##f` will give good results. Another alternative is to use `\CadenzaOn` and `\CadenzaOff`.

To remove the bar lines, the radical approach is to `\remove` the `Bar_engraver` from the `Staff` context. Again, one may want to use `\override BarLine #'transparent = ##t` instead, if an occasional barline is wanted.

A common type of transcription is recitativic chant where the repeated notes are indicated with a single breve. The text to the recitation tone can be dealt with in two different ways: either set as a single, left-aligned syllable:

```
\include "gregorian.ly"
chant = \relative c' {
  \clef "G_8"
  c\breve c4 b4 a c2 c4 \divisioMaior
  c\breve c4 c f, f \finalis
}

verba = \lyricmode {
  \once \override LyricText #'self-alignment-X = #-1
  "Noctem quietam et" fi -- nem per -- fec -- tum
  \once \override LyricText #'self-alignment-X = #-1
  "concedat nobis Dominus" om -- ni -- po -- tens.
}

\score {
  \new Staff <<
  \new Voice = "melody" \chant
  \new Lyrics = "one" \lyricsto melody \verba
  >>
  \layout {
    \context {
      \Staff
      \remove "Time_signature_engraver"
      \remove "Bar_engraver"
      \override Stem #'transparent = ##t
      \override Flag #'transparent = ##t
    }
  }
}
```



This works fine, as long as the text doesn't span a line break. If that is the case, an alternative is to add hidden notes to the score, here in combination with changing stem visibility:

```
\include "gregorian.ly"
chant = \relative c' {
  \clef "G_8"
  \set Score.timing = ##f
  c\breve \override NoteHead #'transparent = ##t c c c c c
}
```

```

\revert NoteHead #'transparent
\override Stem #'transparent = ##f \stemUp c4 b4 a
\override Stem #'transparent = ##t
\override Flag #'transparent = ##t c2 c4 \divisioMaior
c\breve \override NoteHead #'transparent = ##t c c c c c c c
\revert NoteHead #'transparent c4 c f, f \finalis
}

verba = \lyricmode {
  No -- ctem qui -- e -- tam et fi -- nem per -- fec -- tum
  con -- ce -- dat no -- bis Do -- mi -- nus om -- ni -- po -- tens.
}

\score {
  \new Staff <<
    \new Voice = "melody" \chant
    \new Lyrics \lyricsto "melody" \verba
  >>
  \layout {
    \context {
      \Staff
      \remove "Time_signature_engraver"
      \override BarLine #'transparent = ##t
      \override Stem #'transparent = ##t
      \override Flag #'transparent = ##t
    }
  }
}

```



Another common situation is transcription of neumatic or melismatic chants, i.e. chants with a varying number of notes to each syllable. In this case, one would want to set the syllable groups clearly apart, usually also the subdivisions of a longer melisma. One way to achieve this is to use a fixed `\time`, e.g., `1/4`, and let each syllable or note group fill one of these measures, with the help of tuplets or shorter durations. If the bar lines and all other rhythmical indications are made transparent, and the space around the bar lines is increased, this will give a fairly good representation in modern notation of the original.

To avoid that syllables of different width (such as “-ri” and “-rum”) spread the syllable note groups unevenly apart, the `'X-extent` property of the `LyricText` object may be set to a fixed value. Another, more cumbersome way would be to add the syllables as `\markup` elements. If further adjustments are necessary, this can be easily done with `s` ‘notes’.

```


spiritus = \relative c' {
  \time 1/4
  \override Lyrics.LyricText #'X-extent = #'(0 . 3)
  d4 \times 2/3 { f8 a g } g a a4 g f8 e
  d4 f8 g g8 d f g a g f4 g8 a a4 s
  \times 2/3 { g8 f d } e f g a g4
}

```

```

spirLyr = \lyricmode {
  Spi -- ri -- _ _ tus _ Do -- mi -- ni _ re -- ple -- _ vit _
  or -- _ bem _ ter -- ra -- _ rum, al -- _ _ le -- _ lu
  -- _ ia.
}
\score {
  \new Staff <<
    \new Voice = "chant" \spiritus
    \new Lyrics = "one" \lyricsto "chant" \spirLyr
  >>
  \layout {
    \context {
      \Staff
      \remove "Time_signature_engraver"
      \override BarLine #'X-extent = #'(-1 . 1)
      \override Stem #'transparent = ##t
      \override Flag #'transparent = ##t
      \override Beam #'transparent = ##t
      \override BarLine #'transparent = ##t
      \override TupletNumber #'transparent = ##t
    }
  }
}

```



## Ancient and modern from one source

TBC

## Editorial markings

### 2.10 World music

The purpose of this section is to highlight musical notation issues that are relevant to traditions outside the Western tradition.

#### 2.10.1 Common notation for non-Western music

This section discusses how to enter and print music scores that do not belong to the Western classical tradition, also referred to as *Common Practice Period*.

### Extending notation and tuning systems

Standard classical notation (also known as *Common Practice Period* notation) is commonly used in all sorts of music, not limited to ‘classical’ Western music. This notation is discussed



in [Section 1.1.1 \[Writing pitches\]](#), [page 1](#), and the various note names that may be used are explained in [\[Note names in other languages\]](#), [page 7](#).

However, many types of non-Western music (and some types of Western folk and traditional music) employ alternative or extended tuning systems that do not fit readily into standard classical notation.

In some cases standard notation is still used, with the pitch differences being implicit. For example, *Arabic music* is notated with standard semitone and quarter-tone accidentals, with the precise pitch alterations being determined by context. Italian note names are typically used, while the init file ‘arabic.ly’ provides a suitable set of macros and definitions extending the standard notation. For more details, see [Section 2.10.2 \[Arabic music\]](#), [page 415](#).

Other types of music require extended or unique notations. *Turkish classical music* or Ottoman music, for example, employs melodic forms known as *makamlar*, whose intervals are based on 1/9 divisions of the whole tone. Standard Western staff notes are still used, but with special accidentals unique to Turkish music, that are defined in the file ‘makam.ly’. For further information on Turkish classical music and makamlar, see [Section 2.10.3 \[Turkish classical music\]](#), [page 420](#).

To locate init files such as ‘arabic.ly’ or ‘makam.ly’ on your system, see [Section “Other sources of information” in Learning Manual](#).

## Selected Snippets

### *Makam example*

Makam is a type of melody from Turkey using 1/9th-tone microtonal alterations. Consult the initialization file ‘ly/makam.ly’ for details of pitch names and alterations.

```
% Initialize makam settings
\include "makam.ly"

\relative c' {
  \set Staff.keySignature = #`((6 . ,(- KOMA)) (3 . ,BAKIYE))
  c4 cc db fk
  gbm4 gfc gfb efk
  fk4 db cc c
}
```



## See also

Music Glossary: [Section “Common Practice Period” in Music Glossary](#), [Section “makamlar” in Music Glossary](#).

Learning Manual: [Section “Other sources of information” in Learning Manual](#).

Notation Reference: [Section 1.1.1 \[Writing pitches\]](#), [page 1](#), [\[Note names in other languages\]](#), [page 7](#), [Section 2.10.2 \[Arabic music\]](#), [page 415](#), [Section 2.10.3 \[Turkish classical music\]](#), [page 420](#).

## 2.10.2 Arabic music

This section highlights issues that are relevant to notating Arabic music.

## References for Arabic music

Arabic music so far has been mainly an oral tradition. When music is transcribed, it is usually in a sketch format, on which performers are expected to improvise significantly. Increasingly, Western notation, with a few variations, is adopted in order to communicate and preserve Arabic music.

Some elements of Western musical notation such as the transcription of chords or independent parts, are not required to typeset the more traditional Arabic pieces. There are however some different issues, such as the need to indicate medium intervals that are somewhere between a semi-tone and a tone, in addition to the minor and major intervals that are used in Western music. There is also the need to group and indicate a large number of different maqams (modes) that are part of Arabic music.

In general, Arabic music notation does not attempt to precisely indicate microtonal elements that are present in musical practice.

Several issues that are relevant to Arabic music are covered elsewhere:

- Note names and accidentals (including quarter tones) can be tailored as discussed in [Section 2.10.1 \[Common notation for non-Western music\]](#), page 414.
- Additional key signatures can also be tailored as described in [\[Key signature\]](#), page 19.
- Complex time signatures may require that notes be grouped manually as described in [\[Manual beams\]](#), page 82.
- *Takasim* which are rhythmically free improvisations may be written down omitting bar lines as described in [\[Unmetered music\]](#), page 64.

## See also

Notation Reference: [Section 2.10.1 \[Common notation for non-Western music\]](#), page 414, [\[Key signature\]](#), page 19, [\[Manual beams\]](#), page 82.

Snippets: [Section “World music” in \*Snippets\*](#).

## Arabic note names

The more traditional Arabic note names can be quite long and are not suitable for the purpose of music writing, so they are not used. English note names are not very familiar in Arabic music education, so Italian or Solfege note names (do, re, mi, fa, sol, la, si) are used instead; modifiers (accidentals) can also be used. Italian note names and accidentals are explained in [\[Note names in other languages\]](#), page 7; the use of standard Western notation to notate non-Western music is discussed in [Section 2.10.1 \[Common notation for non-Western music\]](#), page 414.

For example, this is how the Arabic *rast* scale can be notated:

```
\include "arabic.ly"
\relative do' {
  do re misb fa sol la sisb do sisb la sol fa misb re do
}
```



The symbol for semi-flat does not match the symbol which is used in Arabic notation. The `\dwn` symbol defined in ‘`arabic.ly`’ may be used preceding a flat symbol as a work around if it is important to use the specific Arabic semi-flat symbol. The appearance of the semi-flat symbol in the key signature cannot be altered by using this method.

```
\include "arabic.ly"
\relative do' {
  \set Staff.extraNatural = ##f
  dod dob dosd \dwn dob dobsb dodsd do do
}
```



## See also

Notation Reference: [Note names in other languages], page 7, Section 2.10.1 [Common notation for non-Western music], page 414.

Snippets: Section “World music” in *Snippets*.

## Arabic key signatures

In addition to the minor and major key signatures, the following key signatures are defined in ‘arabic.ly’: *bayati*, *rast*, *sikah*, *iraq*, and *kurd*. These key signatures define a small number of maqam groups rather than the large number of maqams that are in common use.

In general, a maqam uses the key signature of its group, or a neighbouring group, and varying accidentals are marked throughout the music.

For example to indicate the key signature of a maqam muhayer piece:

```
\key re \bayati
```

Here *re* is the default pitch of the muhayer maqam, and *bayati* is the name of the base maqam in the group.

While the key signature indicates the group, it is common for the title to indicate the more specific maqam, so in this example, the name of maqam muhayer should appear in the title.

Other maqams in the same bayati group, as shown in the table below: (bayati, hussaini, saba, and ushaq) can be indicated in the same way. These are all variations of the base and most common maqam in the group, which is bayati. They usually differ from the base maqam in their upper tetrachords, or certain flow details that don’t change their fundamental nature, as siblings.

The other maqam in the same group (Nawa) is related to bayati by modulation which is indicated in the table in parenthesis for those maqams that are modulations of their base maqam. Arabic maqams admit of only limited modulations, due to the nature of Arabic musical instruments. Nawa can be indicated as follows:

```
\key sol \bayati
```

In Arabic music, the same term such as bayati that is used to indicate a maqam group, is also a maqam which is usually the most important in the group, and can also be thought of as a base maqam.

Here is one suggested grouping that maps the more common maqams to key signatures:

maqam group	key	finalis	Other maqmas in group (finalis)
ajam	major	sib	jaharka (fa)
bayati	bayati	re	hussaini, muhayer, saba, ushaq, nawa (sol)
hijaz	kurd	re	shahnaz, shad arban (sol), hijazkar (do)
iraq	iraq	sisb	-

kurd	kurd	re	hijazkar kurd (do)
nahawand	minor	do	busalik (re), farah faza (sol)
nakriz	minor	do	nawa athar, hisar (re)
rast	rast	do	mahur, yakah (sol)
sikah	sikah	misb	huzam

## Selected Snippets

### *Non-traditional key signatures*

The commonly used `\key` command sets the `keySignature` property, in the `Staff` context.

To create non-standard key signatures, set this property directly. The format of this command is a list:

```
\set Staff.keySignature = #`(((octave . step) . alter) ((octave . step) . alter)
...)
```

where, for each element in the list, `octave` specifies the octave (0 being the octave from middle C to the B above), `step` specifies the note within the octave (0 means C and 6 means B), and `alter` is `,SHARP`, `,FLAT`, `,DOUBLE-SHARP` etc. (Note the leading comma.)

Alternatively, for each item in the list, using the more concise format `(step . alter)` specifies that the same alteration should hold in all octaves.

Here is an example of a possible key signature for generating a whole-tone scale:

```
\relative c' {
  \set Staff.keySignature = #`(((0 . 6) . ,FLAT)
                                ((0 . 5) . ,FLAT)
                                ((0 . 3) . ,SHARP))

  c4 d e fis
  aes4 bes c2
}
```



## See also

Music Glossary: [Section “maqam”](#) in *Music Glossary*, [Section “bayati”](#) in *Music Glossary*, [Section “rast”](#) in *Music Glossary*, [Section “sikah”](#) in *Music Glossary*, [Section “iraq”](#) in *Music Glossary*, [Section “kurd”](#) in *Music Glossary*.

Notation Reference: [\[Key signature\]](#), page 19.

Learning Manual: [Section “Accidentals and key signatures”](#) in *Learning Manual*.

Internals Reference: [Section “KeySignature”](#) in *Internals Reference*.

Snippets: [Section “World music”](#) in *Snippets*, [Section “Pitches”](#) in *Snippets*.

## Arabic time signatures

Some Arabic and Turkish music classical forms such as *Semai* use unusual time signatures such as 10/8. This may lead to an automatic grouping of notes that is quite different from existing typeset music, where notes may not be grouped on the beat, but in a manner that is difficult to match by adjusting automatic beaming. The alternative is to switch off automatic beaming and beam the notes manually. Even if a match to existing typeset music is not required, it may still be desirable to adjust the automatic beaming behaviour and/or use compound time signatures.


## Selected Snippets

### *Arabic improvisation*

For improvisations or taqasim which are temporarily free, the time signature can be omitted and `\cadenzaOn` can be used. Adjusting the accidental style might be required, since the absence of bar lines will cause the accidental to be marked only once. Here is an example of what could be the start of a hijaz improvisation:

```
\include "arabic.ly"

\relative sol' {
  \key re \kurd
  \accidentalStyle "forget"
  \cadenzaOn
  sol4 sol sol sol fad mib sol1 fad8 mib re4. r8 mib1 fad sol
}
```



## See also

Music Glossary: [Section “semai” in \*Music Glossary\*](#), [Section “taqasim” in \*Music Glossary\*](#).

Notation Reference: [\[Manual beams\]](#), page 82, [\[Automatic beams\]](#), page 72, [\[Unmetered music\]](#), page 64, [\[Automatic accidentals\]](#), page 22, [\[Setting automatic beam behavior\]](#), page 74, [\[Time signature\]](#), page 56.

Snippets: [Section “World music” in \*Snippets\*](#).

## Arabic music example

Here is a template that also uses the start of a Turkish *Semai* that is familiar in Arabic music education in order to illustrate some of the peculiarities of Arabic music notation, such as medium intervals and unusual modes that are discussed in this section.

```
\include "arabic.ly"
\score {
  \relative re' {
    \set Staff.extraNatural = ##f
    \set Staff.autoBeaming = ##f
    \key re \bayati
    \time 10/8

    re4 re'8 re16 [misb re do] sisb [la sisb do] re4 r8
    re16 [misb do re] sisb [do] la [sisb sol8] la [sisb] do [re] misb
    fa4 fa16 [misb] misb8. [re16] re8 [misb] re [do] sisb
    do4 sisb8 misb16 [re do sisb] la [do sisb la] la4 r8
  }
  \header {
    title = "Semai Muhayer"
    composer = "Jamil Bek"
  }
}
```



## See also

Snippets: [Section “World music” in \*Snippets\*](#).

## Further reading for Arabic music

1. *The music of the Arabs* by Habib Hassan Touma [Amadeus Press, 1996], contains a discussion of maqams and their method of groupings.

There are also various web sites that explain maqams and some provide audio examples such as :

- <http://www.maqamworld.com/>
- <http://www.turath.org/>

There are some variations in the details of how maqams are grouped, despite agreement on the criteria of grouping maqams that are related through common lower tetra chords, or through modulation.

2. There is not a complete consistency, sometimes even in the same text on how key signatures for particular maqams should be specified. It is common, however, to use a key signature per group, rather than a different key signature for each different maqam.

Method books by the following authors for the *Oud*, the Arabic lute, contain examples of mainly Turkish and Arabic compositions.

- Charbel Rouhana
- George Farah
- Ibrahim Ali Darwish Al-masri

### 2.10.3 Turkish classical music

This section highlights issues that are relevant to notating Turkish classical music.

## References for Turkish classical music

Turkish classical music developed in the Ottoman Empire in a period roughly contemporaneous with classical music in Europe, and has continued on into the 20th and 21st centuries as a vibrant and distinct tradition with its own compositional forms, theory and performance styles. Among its striking features is the use of microtonal intervals based on ‘commas’ of  $1/9$  of a tone, from which are constructed the melodic forms known as *makam* (plural *makamlar*).

Some issues relevant to Turkish classical music are covered elsewhere:

- Special note names and accidentals are explained in [Section 2.10.1 \[Common notation for non-Western music\]](#), page 414.

## Turkish note names

Pitches in Turkish classical music traditionally have unique names, and the basis of pitch on 1/9-tone divisions means makamlar employ a completely different set of intervals from Western scales and modes: *koma* (1/9 of a tone), *eksik bakiye* (3/9), *bakiye* (4/9), *küçük mücenneb* (5/9), *büyük mücenneb* (8/9), *tanîni* (a whole tone) and *artık ikili* (12/9 or 13/9 of a tone).

From a modern notational point of view it is convenient to use the standard Western staff notes (c, d, e, ...) with special accidentals that raise or lower notes by intervals of 1/9, 4/9, 5/9 and 8/9 of a tone. These accidentals are defined in the file ‘`makam.ly`’.

The following table lists:

- the name of these special accidentals,
- the accidental suffix that must be added to notes,
- and their pitch alteration as a fraction of one whole tone.

Accidental name	suffix	pitch alteration
büyük mücenneb (sharp)	-bm	+8/9
küçük mücenneb (sharp)	-k	+5/9
bakiye (sharp)	-b	+4/9
koma (sharp)	-c	+1/9
koma (flat)	-fc	-1/9
bakiye (flat)	-fb	-4/9
küçük mücenneb (flat)	-fk	-5/9
büyük mücenneb (flat)	-fbm	-8/9

For a more general explanation of non-Western music notation, see [Section 2.10.1 \[Common notation for non-Western music\]](#), page 414.

## See also

Music Glossary: [Section “makam” in \*Music Glossary\*](#), [Section “makamlar” in \*Music Glossary\*](#).

Notation Reference: [Section 2.10.1 \[Common notation for non-Western music\]](#), page 414.

## 3 General input and output

This section deals with general LilyPond input and output issues, rather than specific notation.

### 3.1 Input structure

The main format of input for LilyPond are text files. By convention, these files end with ‘.ly’.

#### 3.1.1 Structure of a score

A `\score` block must contain a single music expression delimited by curly brackets:

```
\score {
...
}
```


**Note:** There must be **only one** outer music expression in a `\score` block, and it **must** be surrounded by curly brackets.

This single music expression may be of any size, and may contain other music expressions to any complexity. All of these examples are music expressions:

```
{ c'4 c' c' c' }
{
  { c'4 c' c' c' }
  { d'4 d' d' d' }
}
```



```
<<
  \new Staff { c'4 c' c' c' }
  \new Staff { d'4 d' d' d' }
>>
```



```
{
  \new GrandStaff <<
    \new StaffGroup <<
      \new Staff { \flute }
      \new Staff { \oboe }
    >>
    \new StaffGroup <<
      \new Staff { \violinI }
      \new Staff { \violinII }
    >>
  >>
}
```



```
}
```

Comments are one exception to this general rule. (For others see [Section 3.1.5 \[File structure\]](#), [page 426](#).) Both single-line comments and comments delimited by `%{ .. %}` may be placed anywhere within an input file. They may be placed inside or outside a `\score` block, and inside or outside the single music expression within a `\score` block.

Remember that even in a file containing only a `\score` block, it is implicitly enclosed in a `\book` block. A `\book` block in a source file produces at least one output file, and by default the name of the output file produced is derived from the name of the input file, so `'fandangoforelephants.ly'` will produce `'fandangoforelephants.pdf'`.

(For more details about `\book` blocks, see [Section 3.1.2 \[Multiple scores in a book\]](#), [page 423](#), [Section 3.1.3 \[Multiple output files from one input file\]](#), [page 424](#) [Section 3.1.5 \[File structure\]](#), [page 426](#).)

## See also

Learning Manual: [Section “Working on input files” in \*Learning Manual\*](#), [Section “Music expressions explained” in \*Learning Manual\*](#), [Section “Score is a \(single\) compound musical expression” in \*Learning Manual\*](#).

### 3.1.2 Multiple scores in a book

A document may contain multiple pieces of music and text. Examples of these are an etude book, or an orchestral part with multiple movements. Each movement is entered with a `\score` block,

```
\score {
  ..music..
}
```

and texts are entered with a `\markup` block,

```
\markup {
  ..text..
}
```

All the movements and texts which appear in the same `'ly'` file will normally be typeset in the form of a single output file.

```
\score {
  ..
}
\markup {
  ..
}
\score {
  ..
}
```

One important exception is within lilypond-book documents, where you explicitly have to add a `\book` block, otherwise only the first `\score` or `\markup` will appear in the output.

The header for each piece of music can be put inside the `\score` block. The `piece` name from the header will be printed before each movement. The title for the entire book can be put inside the `\book`, but if it is not present, the `\header` which is at the top of the file is inserted.

```
\header {
  title = "Eight miniatures"
  composer = "Igor Stravinsky"
}
```

```

\score {
  ...
  \header { piece = "Romanze" }
}
\markup {
  ..text of second verse..
}
\markup {
  ..text of third verse..
}
\score {
  ...
  \header { piece = "Menuetto" }
}

```

Pieces of music may be grouped into book parts using `\bookpart` blocks. Book parts are separated by a page break, and can start with a title, like the book itself, by specifying a `\header` block.

```

\bookpart {
  \header {
    title = "Book title"
    subtitle = "First part"
  }
  \score { ... }
  ...
}
\bookpart {
  \header {
    subtitle = "Second part"
  }
  \score { ... }
  ...
}

```

### 3.1.3 Multiple output files from one input file

If you want multiple output files from the same `.ly` file, then you can add multiple `\book` blocks, where each such `\book` block will result in a separate output file. If you do not specify any `\book` block in the input file, LilyPond will implicitly treat the whole file as a single `\book` block, see [Section 3.1.5 \[File structure\]](#), page 426.

When producing multiple files from a single source file, Lilypond ensures that none of the output files from any `\book` block overwrites the output file produced by a preceding `\book` from the same input file.

It does this by adding a suffix to the output name for each `\book` which uses the default output file name derived from the input source file.

The default behaviour is to append a version-number suffix for each name which may clash, so

```

\book {
  \score { ... }
  \layout { ... }
}
\book {

```

```

\score { ... }
\layout { ... }
}
\book {
  \score { ... }
  \layout { ... }
}

```

in source file ‘eightminiatures.ly’ will produce

- ‘eightminiatures.pdf’,
- ‘eightminiatures-1.pdf’ and
- ‘eightminiatures-2.pdf’.

### 3.1.4 Output file names

Lilypond provides facilities to allow you to control what file names are used by the various back-ends when producing output files.

In the previous section, we saw how Lilypond prevents name-clashes when producing several outputs from a single source file. You also have the ability to specify your own suffixes for each `\book` block, so for example you can produce files called ‘eightminiatures-Romanze.pdf’, ‘eightminiatures-Menuetto.pdf’ and ‘eightminiatures-Nocturne.pdf’ by adding a `\bookOutputSuffix` declaration inside each `\book` block.

```

\book {
  \bookOutputSuffix "Romanze"
  \score { ... }
  \layout { ... }
}
\book {
  \bookOutputSuffix "Menuetto"
  \score { ... }
  \layout { ... }
}
\book {
  \bookOutputSuffix "Nocturne"
  \score { ... }
  \layout { ... }
}

```

You can also specify a different output filename for `book` block, by using `\bookOutputName` declarations

```

\book {
  \bookOutputName "Romanze"
  \score { ... }
  \layout { ... }
}
\book {
  \bookOutputName "Menuetto"
  \score { ... }
  \layout { ... }
}
\book {
  \bookOutputName "Nocturne"
  \score { ... }
}

```

```
\layout { ... }
}
```

The file above will produce these output files:

- ‘Romanze.pdf’,
- ‘Menuetto.pdf’ and
- ‘Nocturne.pdf’.

### 3.1.5 File structure

A ‘.ly’ file may contain any number of toplevel expressions, where a toplevel expression is one of the following:

- An output definition, such as `\paper`, `\midi`, and `\layout`. Such a definition at the toplevel changes the default book-wide settings. If more than one such definition of the same type is entered at the top level any definitions in the later expressions have precedence.
- A direct scheme expression, such as  `#(set-default-paper-size "a7" 'landscape)`  or  `#(ly:set-option 'point-and-click #f)` .
- A `\header` block. This sets the global header block. This is the block containing the definitions for book-wide settings, like composer, title, etc.
- A `\score` block. This score will be collected with other toplevel scores, and combined as a single `\book`. This behavior can be changed by setting the variable `toplevel-score-handler` at toplevel. The default handler is defined in the init file ‘`../scm/lily.scm`’.
- A `\book` block logically combines multiple movements (i.e., multiple `\score` blocks) in one document. If there are a number of `\scores`, one output file will be created for each `\book` block, in which all corresponding movements are concatenated. The only reason to explicitly specify `\book` blocks in a ‘.ly’ file is if you wish to create multiple output files from a single input file. One exception is within lilypond-book documents, where you explicitly have to add a `\book` block if you want more than a single `\score` or `\markup` in the same example. This behavior can be changed by setting the variable `toplevel-book-handler` at toplevel. The default handler is defined in the init file ‘`../scm/lily.scm`’.
- A `\bookpart` block. A book may be divided into several parts, using `\bookpart` blocks, in order to ease the page breaking, or to use different `\paper` settings in different parts.
- A compound music expression, such as

```
{ c'4 d' e'2 }
```

This will add the piece in a `\score` and format it in a single book together with all other toplevel `\scores` and music expressions. In other words, a file containing only the above music expression will be translated into

```
\book {
  \score {
    \new Staff {
      \new Voice {
        { c'4 d' e'2 }
      }
    }
    \layout { }
  }
  \paper { }
  \header { }
}
```

This behavior can be changed by setting the variable `toplevel-music-handler` at toplevel. The default handler is defined in the init file `../scm/lily.scm`.

- A markup text, a verse for example

```
\markup {
  2. The first line verse two.
}
```

Markup texts are rendered above, between or below the scores or music expressions, wherever they appear.

- A variable, such as

```
foo = { c4 d e d }
```

This can be used later on in the file by entering `\foo`. The name of a variable should have alphabetic characters only; no numbers, underscores or dashes.

The following example shows three things that may be entered at toplevel

```
\layout {
  % Don't justify the output
  ragged-right = ##t
}
```

```
\header {
  title = "Do-re-mi"
}
```

```
{ c'4 d' e2 }
```

At any point in a file, any of the following lexical instructions can be entered:

- `\version`
- `\include`
- `\sourcefilename`
- `\sourcefileline`
- A single-line comment, introduced by a leading `%` sign.
- A multi-line comment delimited by `%{ .. %}`.

Whitespace between items in the input stream is generally ignored, and may be freely omitted or extended to enhance readability. However, whitespace should always be used in the following circumstances to avoid errors:

- Around every opening and closing curly bracket.
- After every command or variable, i.e. every item that begins with a `\` sign.
- After every item that is to be interpreted as a Scheme expression, i.e. every item that begins with a `#` sign.
- To separate all elements of a Scheme expression.
- In `lyricmode` to separate all the terms in both `\override` and `\set` commands. In particular, spaces must be used around the dot and the equals sign in commands like `\override Score . LyricText #'font-size = #5` and before and after the entire command.

## See also

Learning Manual: [Section “How LilyPond input files work”](#) in *Learning Manual*.

## 3.2 Titles and headers

Almost all printed music includes a title and the composer's name; some pieces include a lot more information.

### 3.2.1 Creating titles headers and footers

#### Title blocks explained

There are two types of title blocks: the main title block that appears above of the first `\score` of a book, and individual title blocks that appear within each `\score` block. Text fields for both types are entered using a `\header` block.

If the book only has a single score, the `\header` block may be placed inside or outside of the `\score` block.

**Note:** Remember when adding a `\header` block inside a `\score` block, that the music expression must come before the `\header` block.

```
\header {
  title = "SUITE I."
  composer = "J. S. Bach."
}

\score {
  \new Staff \relative g, {
    \clef bass
    \key g \major
    \repeat unfold 2 { g16( d' b') a b d, b' d, } |
    \repeat unfold 2 { g,16( e' c') b c e, c' e, } |
  }
  \header {
    piece = "Prélude."
  }
}

\score {
  \new Staff \relative b {
    \clef bass
    \key g \major
    \partial 16 b16 |
    <g, d' b'~>4 b'16 a( g fis) g( d e fis) g( a b c) |
    d16( b g fis) g( e d c) b(c d e) fis( g a b) |
  }
  \header {
    piece = "Allemande."
  }
}
```

**SUITE I.**

J. S. Bach.

Prélude.



Allemande.



Text fields from the main title block of a book can be displayed in all `\score` blocks, or manually suppressed:


```
\book {
  \paper {
    print-all-headers = ##t
  }
  \header {
    title = "DAS WOHLTEMPERIRTE CLAVIER"
    subtitle = "TEIL I"
    % Do not display the tagline for this book
    tagline = ##f
  }
  \markup { \vspace #1 }
  \score {
    \new PianoStaff <<
      \new Staff { s1 }
      \new Staff { \clef "bass" s1 }
    >>
    \header {
      title = "PRAELUDIUM I"
      opus = "BWV 846"
      % Do not display the subtitle for this score
      subtitle = ##f
    }
  }
}
\score {
  \new PianoStaff <<
    \new Staff { s1 }
    \new Staff { \clef "bass" s1 }
  >>
  \header {
    title = "FUGA I"
    subsubtitle = "A 4 VOCI"
    opus = "BWV 846"
    % Do not display the subtitle for this score
    subtitle = ##f
  }
}
}
```

# DAS WOHLTEMPERIRTE CLAVIER

## TEIL I

### PRAELUDIUM I


BWV 846



### FUGA I

A 4 VOCI

BWV 846



#### See also

Notation Reference: [Section 3.1.5 \[File structure\]](#), page 426, [\[Custom layout for title blocks\]](#), page 434.

#### Default layout of book and score title blocks

The layout and formatting of title blocks are controlled by two `\paper` variables; `bookTitleMarkup` for the main `\header` title block and `scoreTitleMarkup` for individual `\header` blocks within a `\score`.

```
\header {
  % The following fields are centered
  dedication = "Dedication"
  title = "Title"
  subtitle = "Subtitle"
  subsubtitle = "Subsubtitle"
  instrument = "Instrument"

  % The following fields are left-aligned on the left side
  poet = "Poet"
  meter = "Meter"

  % The following fields are right-aligned on the right side
  composer = "Composer"
  arranger = "Arranger"
}

\score {
```




```

{ s1 }
\header {
  % The following fields are placed at opposite ends of the same line
  piece = "Piece"
  opus = "Opus"
}
}

```

	Dedication	
	<b>Title</b>	
	<b>Subtitle</b>	
	<b>Subsubtitle</b>	
Poet	<b>Instrument</b>	Composer
Meter		Arranger
Piece		Opus



Text fields left unset in a `\header` block are replaced with `\null` markups so that the space is not wasted.

The default settings for `scoreTitleMarkup` place the `piece` and `opus` text fields at opposite ends of the same line.

Use the `breakbefore` variable inside a `\header` block that is itself in a `\score` block, to make the top-level `\header` block titles appear on the first page on their own, with the music (defined in the `\score` block) starting on the next.

```

\book {
  \header {
    title = "This is my Title"
    subtitle = "This is my Subtitle"
    copyright = "This is the bottom of the first page"
  }
  \score {
    \repeat unfold 4 { e'' e'' e'' e'' }
    \header {
      piece = "This is the Music"
      breakbefore = ##t
    }
  }
}
}

```

# This is my Title

## This is my Subtitle

This is the bottom of the first page



Music engraving by LilyPond 2.15.29—[www.lilypond.org](http://www.lilypond.org)

### See also

Learning Manual: [Section “How LilyPond input files work”](#) in *Learning Manual*,

Notation Reference: [Section 3.1.5 \[File structure\]](#), page 426.

Installed Files: ‘`ly/titling-init.ly`’.

### Default layout of headers and footers

*Headers* and *footers* are lines of text appearing at the top and bottom of pages, separate from the main text of a book. They are controlled by the following `\paper` variables:

- `oddHeaderMarkup`
- `evenHeaderMarkup`
- `oddFooterMarkup`
- `evenFooterMarkup`

These markup variables can only access text fields from top-level `\header` blocks (which apply to all scores in the book) and are defined in ‘`ly/titling-init.ly`’. By default:

- page numbers are automatically placed on the top far left (if even) or top far right (if odd), starting from the second page.
- the `instrument` text field is placed in the center of every page, starting from the second page.
- the `copyright` text is centered on the bottom of the first page.
- the `tagline` is centered on the bottom of the last page, and below the `copyright` text if there is only a single page.



Music engraving by LilyPond 2.15.29—[www.lilypond.org](http://www.lilypond.org)

The default tagline can be changed by adding a `tagline` in the top-level `\header` block.

```
\book {
  \header {
    tagline = "... music notation for Everyone"
  }
  \score {
    \relative c' {
      c4 d e f
    }
  }
}
```



... music notation for Everyone

To remove the `tagline` set the value to `##f`.


### 3.2.2 Custom headers footers and titles

#### Custom text formatting for title blocks

Standard `\markup` commands can be used to customize any header, footer and title text within the `\header` block.

```
\score {
  { s1 }
  \header {
    piece = \markup { \fontsize #4 \bold "PRAELUDIUM I" }
    subtitle = \markup { \italic "(Excerpt)" }
  }
}
```

**PRAELUDIUM I**



## See also

Notation Reference: [Section 1.8.2 \[Formatting text\]](#), page 210.

## Custom layout for title blocks

`\markup` commands in the `\header` block are useful for simple text formatting, but they do not allow precise control over the placement of titles. To customize the placement of the text fields, use either or both of the following `\paper` variables:

- `bookTitleMarkup`
- `scoreTitleMarkup`

These markup variables are discussed in [\[Default layout of book and score title blocks\]](#), page 430.

The default settings for `scoreTitleMarkup` as defined in ‘`ly/titling-init.ly`’ are:


```
scoreTitleMarkup = \markup { \column {
  \on-the-fly #print-all-headers { \bookTitleMarkup \hspace #1 }
  \fill-line {
    \fromproperty #'header:piece
    \fromproperty #'header:opus
  }
}
```

This places the `piece` and `opus` text fields at opposite ends of the same line:

```
\score {
  { s1 }
  \header {
    piece = "PRAELUDIUM I"
    opus = "BWV 846"
  }
}
```

PRAELUDIUM I

BWV 846




This example redefines `scoreTitleMarkup` so that the `piece` text field is centered and in a large, bold font.

```
\book {
  \paper {
    indent = 0\mm
    scoreTitleMarkup = \markup {
      \fill-line {
        \null
        \fontsize #4 \bold \fromproperty #'header:piece
        \fromproperty #'header:opus
      }
    }
  }
}
```

```

}
\header { tagline = ##f }
\score {
  { s1 }
  \header {
    piece = "PRAELUDIUM I"
    opus = "BWV 846"
  }
}
}

```



Text fields normally reserved for the main title block can be included in individual score title blocks with the `print-all-headers` placed inside the `\paper` block. A disadvantage of using this method is that the text fields that are intended specifically for the top-level `\header` block need to be manually suppressed in every `\score` block. See [\[Title blocks explained\]](#), page 428.

To avoid this, add the desired text field to the `scoreTitleMarkup` definition. In the following example, the `composer` text field (normally associated with `bookTitleMarkup`) is added to `scoreTitleMarkup`, allowing each score to list a different composer:


```

\book {
  \paper {
    indent = 0\mm
    scoreTitleMarkup = \markup {
      \fill-line {
        \null
        \fontsize #4 \bold \fromproperty #'header:piece
        \fromproperty #'header:composer
      }
    }
  }
}
\header { tagline = ##f }
\score {
  { s1 }
  \header {
    piece = "MENUET"
    composer = "Christian Petzold"
  }
}
\score {
  { s1 }
  \header {
    piece = "RONDEAU"
    composer = "François Couperin"
  }
}
}


```

**MENUET**

Christian Petzold

**RONDEAU**

François Couperin




It is also possible to create your own custom text fields, and refer to them in the markup definition.

```
\book {
  \paper {
    indent = 0\mm
    scoreTitleMarkup = \markup {
      \fill-line {
        \null
        \override #'(direction . ,UP) {
          \dir-column {
            \center-align \fontsize #-1 \bold
            \fromproperty #'header:mycustomtext %% User-defined field
            \center-align \fontsize #4 \bold
            \fromproperty #'header:piece
          }
        }
      }
      \fromproperty #'header:opus
    }
  }
}
\header { tagline = ##f }
\score {
  { s1 }
  \header {
    piece = "FUGA I"
    mycustomtext = "A 4 VOICI" %% User-defined field
    opus = "BWV 846"
  }
}
}
```

**FUGA I**

A 4 VOICI

BWV 846

**See also**

Notation Reference: [\[Title blocks explained\]](#), page 428.




## Custom layout for headers and footers

`\markup` commands in the `\header` block are useful for simple text formatting, but they do not allow precise control over the placement of headers and footers. To customize the placement of the text fields, use either or both of the following `\paper` variables:

- `oddHeaderMarkup`
- `evenHeaderMarkup`
- `oddFooterMarkup`
- `evenFooterMarkup`

The following example centers page numbers at the bottom of every page. First, the default settings for `oddHeaderMarkup` and `evenHeaderMarkup` are removed by defining each as a *null* markup. Then, `oddFooterMarkup` is redefined with the page number centered. Finally, `evenFooterMarkup` is given the same layout by defining it as `\oddFooterMarkup`:

```
\book {
  \paper {
    print-page-number = ##t
    print-first-page-number = ##t
    oddHeaderMarkup = \markup \null
    evenHeaderMarkup = \markup \null
    oddFooterMarkup = \markup {
      \fill-line {
        \on-the-fly #print-page-number-check-first
        \fromproperty #'page:page-number-string
      }
    }
    evenFooterMarkup = \oddFooterMarkup
  }
  \score {
    \new Staff { s1 \break s1 \break s1 }
  }
}
```



## See also

Notation Reference: [Title blocks explained], page 428, [Default layout of book and score title blocks], page 430.

### 3.2.3 Creating footnotes

There are two types of footnotes that can be created; automatic footnotes and manual footnotes.

#### Footnotes overview

Automatic footnotes create incrementing, numerical indicators and manual footnotes allow a custom indicator to be created instead. All grobs, top-level `\markup` and chorded notes can be annotated.

The order in which each grob is drawn determines the order in which each indicator and so footnotes are created during compilation.

#### Automatic footnotes

Automatic footnotes take three arguments; the *Layout Object* to be annotated, the  $(x . y)$  position of the indicator and a `\markup` that will appear in the footnote at the bottom of the page.

The command `\footnote` must come *before* the grob that the footnote is being attached to:

```
\book {
  \header { tagline = ##f }
  \relative c' {
    \footnote #'(0.5 . -2) #'NoteHead
      \markup { The first note }
    a'4 b8
    \footnote #'(0.5 . 1) #'NoteHead
      \markup { The third note }
    e c4 d4
  }
}
```





---

<sup>1</sup>The first note  
<sup>2</sup>The third note

To annotate chorded notes, the `\footnote` must come *after* the note to which the footnote is being attached as a `TextScript`:



```
\book {
  \header { tagline = ##f }
  \relative c' {
    <
    c-\footnote #'(1 . -1.25) "Here is a C"
    es-\footnote #'(2 . -0.25) \markup { \italic "An E-flat" }
    g-\footnote #'(2 . 3) \markup { \bold "This is a G" }
    >1
  }
}
```



<sup>1</sup>**This is a G**  
<sup>2</sup>*An E-flat*  
<sup>3</sup>Here is a C

**Note:** When footnotes have the same vertical position, the footnotes are printed in order of descendancy; the higher the footnote, the higher up in the list.

Here are some more examples of footnoted grobs, also showing the relative position of the footnotes to the tagline and copyright.

```
\book {
  \header { copyright = \markup { "Copyright 1970" } }
  \relative c' {
    \footnote #'(-3 . 0) #'DynamicText
    \markup { \bold Forte }

    \footnote #'(0 . 1.5) #'Slur
    \markup { A slur }
    a'4\f(

    \footnote #'(0 . -2) #'Beam
    \markup { Beam }
    b8)[ e]

    \footnote #'(1 . -1) #'Stem
    \markup { \teeny { This is a stem } }
    c4
```

```

\footnote #'(0 . 0.5) #'AccidentalCautionary
  \markup \italic { A cautionary accidental }

\footnote #'(0.5 . -0.5) #'TextScript
  \markup \italic { Slow Down }
dis?4_"rit."
}
}

```



<sup>1</sup>A slur  
<sup>2</sup>**Forte**  
<sup>3</sup>Beam  
<sup>4</sup>This is a stem  
<sup>5</sup>*A cautionary accidental*  
<sup>6</sup>*Slow Down*  
 Copyright 1970

Music engraving by LilyPond 2.15.29—[www.lilypond.org](http://www.lilypond.org)

For top-level `\markup`, the `\auto-footnote` command is required:

```

\book {
  \header { tagline = ##f }
  \markup { \auto-footnote "A simple tune" \italic "By me" }
  \relative c' {
    a'4 b8 e c4 d
  }
}

```

A simple tune<sup>1</sup>




<sup>1</sup>*By me*

## Manual footnotes

Manual footnotes takes four arguments; the *Layout Object* to be annotated, the  $(x . y)$  position of the indicator and two `\markup` commands; the first is the indicator attached to the note or grob and the second is the footnote at the bottom of the page.

Like automatic footnotes, manual `\footnote` commands must come *after* the grob that the footnote is annotating and attached as a `TextScript`:


```
\book {
  \header { tagline = ##f }
  \relative c' {
    a'4-\footnote
      "1" #'(0.5 . -2) #'NoteHead \markup { \italic "1. The first note" }
    b8
    e-\footnote
      \markup { \bold "2" } #'(0.5 . 1) #'NoteHead "2. The second note"
    c4
    d\p-\footnote "3" #'(0.5 . -1) #'DynamicText "3. Piano"
  }
}
```



- 
1. *The first note*
  2. The second note
  3. Piano

To annotate chorded notes with manual footnotes:

```
\book {
  \header { tagline = ##f }
  \relative c' {
    <
    c-\footnote "1" #'(1 . -1.25) "1. C"
    es-\footnote
      \markup { \bold "b" } #'(2 . -0.25) "b. E-flat"
    g-\footnote "3" #'(2 . 3) \markup { \italic "iii. G" }
    >1
  }
}
```



iii. *G*  
 b. E-flat  
 1. C

**Note:** When footnotes have the same vertical position, the footnotes are printed in order of descendancy; the higher the footnote, the higher up in the list.

Here are some examples of manually footnoted grobs, also showing the relative position of the footnotes to the tagline and copyright

```
\book {
  \header { tagline = ##f }
  \relative c' {
    \footnote
      \markup { \teeny 1 } #'(-3 . 0) #'DynamicText
      \markup { 1. \bold Forte }

    \footnote
      \markup { \teeny b } #'(0 . 1.5) #'Slur
      \markup { b. A slur }
    a'4\f(

    \footnote
      \markup { \teeny 3 } #'(0 . -2) #'Beam
      \markup { 3. Beam }
    b8)[ e]

    \footnote
      \markup { 4 } #'(1 . -1) #'Stem
      \markup { \bold 4. { This is a stem } }
    c4


    \footnote
      \markup \concat \teeny { "sharp (v)" }
      #'(0 . 0.5) #'AccidentalCautionary
      \markup \italic { v. A cautionary accidental }

    \footnote
      \markup \concat \teeny { "a" } #'(0.5 . -0.5) #'TextScript
      \markup \italic { a. Slow Down }
    dis?4_"rit."
```

```

\breathe
\footnote
  \markup { \teeny \musicglyph #"rest.4" }
    #'(1.5 . -0.25) #'BreathingSign
  \markup { \null }
}
}

```



- b. A slur
- 1. **Forte**
- 3. Beam
- 4. This is a stem
- v. A *cautionary accidental*
- a. *Slow Down*

To manually footnote a top-level \markup:

```

\book {
  \header { tagline = ##f }
  \markup { "A simple tune" \footnote "*" \italic "* By me" }
  \relative c' {
    a'4 b8 e c4 d4
  }
}
}

```

A simple tune \*



\* *By me*

## See also

Learning Manual: [Section “Objects and interfaces”](#) in *Learning Manual*.

Notation Reference: [\[Balloon help\]](#), page 198, [Section 4.1 \[Page layout\]](#), page 469, [\[Text marks\]](#), page 205, [\[Text scripts\]](#), page 202, [Section 3.2 \[Titles and headers\]](#), page 428.

Internals Reference: [Section “FootnoteEvent”](#) in *Internals Reference*, [Section “FootnoteItem”](#) in *Internals Reference*, [Section “FootnoteSpanner”](#) in *Internals Reference*, [Section “Footnote-engraver”](#) in *Internals Reference*.

## Known issues and warnings

Multiple footnotes for the same page can only be stacked, one on top of the other, and cannot be printed on the same line. Footnotes cannot be attached to `MultiMeasureRests` and may collide with `Staff`, `\markup` objects and other `footnote` annotations. When using any manual `footnote` command a `\paper` block containing `footnote-auto-number = ##f` is required.

### 3.2.4 Reference to page numbers

A particular place of a score can be marked using the `\label` command, either at top-level or inside music. This label can then be referred to in a markup, to get the number of the page where the marked point is placed, using the `\page-ref` markup command.

```
\header { tagline = ##f }
\book {
  \label #'firstScore
  \score {
    {
      c'1
      \pageBreak \mark A \label #'markA
      c'1
    }
  }
  \markup { The first score begins on page \page-ref #'firstScore "0" "?" }
  \markup { Mark A is on page \page-ref #'markA "0" "?" }
}
```





The first score begins on page 1  
 Mark A is on page 2

The `\page-ref` markup command takes three arguments:

1. the label, a scheme symbol, eg. `#'firstScore`;
2. a markup that will be used as a gauge to estimate the dimensions of the markup;
3. a markup that will be used in place of the page number if the label is not known;

The reason why a gauge is needed is that, at the time markups are interpreted, the page breaking has not yet occurred, so the page numbers are not yet known. To work around this issue, the actual markup interpretation is delayed to a later time; however, the dimensions of the markup have to be known before, so a gauge is used to decide these dimensions. If the book has between 10 and 99 pages, it may be "00", ie. a two digit number.

## Predefined commands

`\label`, `\page-ref`.

### 3.2.5 Table of contents

A table of contents is included using the `\markuplist \table-of-contents` command. The elements which should appear in the table of contents are entered with the `\tocItem` command, which may be used either at top-level, or inside a music expression.

```
\markuplist \table-of-contents
\pageBreak

\tocItem \markup "First score"
\score {
  {
    c'4 % ...
    \tocItem \markup "Some particular point in the first score"
    d'4 % ...
  }
}

\tocItem \markup "Second score"
\score {
  {
    e'4 % ...
  }
}
```

The markups which are used to format the table of contents are defined in the `\paper` block. The default ones are `tocTitleMarkup`, for formatting the title of the table, and `tocItemMarkup`, for formatting the toc elements, composed of the element title and page number. These variables may be changed by the user:

```
\paper {
  %% Translate the toc title into French:
  tocTitleMarkup = \markup \huge \column {
    \fill-line { \null "Table des matières" \null }
    \hspace #1
  }
  %% use larger font size
  tocItemMarkup = \markup \large \fill-line {
    \fromproperty #'toc:text \fromproperty #'toc:page
  }
}
```

Note how the toc element text and page number are referred to in the `tocItemMarkup` definition.

New commands and markups may also be defined to build more elaborated table of contents:

- first, define a new markup variable in the `\paper` block
- then, define a music function which aims at adding a toc element using this markup paper variable.

In the following example, a new style is defined for entering act names in the table of contents of an opera:

```
\paper {
```



```

tocActMarkup = \markup \large \column {
  \hspace #1
  \fill-line { \null \italic \fromproperty #'toc:text \null }
  \hspace #1
}
}

tocAct =
#(define-music-function (parser location text) (markup?)
  (add-toc-item! 'tocActMarkup text))

```

## Table of Contents

### *Atto Primo*

Coro. Viva il nostro Alcide	1
Cesare. Presti omai l'Egizzia terra	1

### *Atto Secondo*

Sinfonia	1
Cleopatra. V'adoro, pupille, saette d'Amore	1

Dots can be added to fill the line between an item and its page number:

```

\header { tagline = ##f }
\paper {
  tocItemMarkup = \tocItemWithDotsMarkup
}

\book {
  \markuplist \table-of-contents
  \tocItem \markup { Allegro }
  \tocItem \markup { Largo }
  \markup \null
}

```

## Table of Contents

Allegro . . . . .	1
Largo . . . . .	1

## See also

Init files: ‘`../ly/toc-init.ly`’.

## Predefined commands

`\table-of-contents`, `\tocItem`.

## 3.3 Working with input files

### 3.3.1 Including LilyPond files

A large project may be split up into separate files. To refer to another file, use

```
\include "otherfile.ly"
```

The line `\include "otherfile.ly"` is equivalent to pasting the contents of `'otherfile.ly'` into the current file at the place where the `\include` appears. For example, in a large project you might write separate files for each instrument part and create a “full score” file which brings together the individual instrument files. Normally the included file will define a number of variables which then become available for use in the full score file. Tagged sections can be marked in included files to assist in making them usable in different places in a score, see [Section 3.3.2 \[Different editions from one source\]](#), page 449.

Files in the current working directory may be referenced by specifying just the file name after the `\include` command. Files in other locations may be included by giving either a full path reference or a relative path reference (but use the UNIX forward slash, `/`, rather than the DOS/Windows back slash, `\`, as the directory separator.) For example, if `'stuff.ly'` is located one directory higher than the current working directory, use

```
\include "../stuff.ly"
```

or if the included orchestral parts files are all located in a subdirectory called `'parts'` within the current directory, use

```
\include "parts/VI.ly"
\include "parts/VII.ly"
... etc
```

Files which are to be included can also contain `\include` statements of their own. By default, these second-level `\include` statements are not interpreted until they have been brought into the main file, so the file names they specify must all be relative to the directory containing the main file, not the directory containing the included file. However, this behavior can be changed by passing the option `'-drelative-includes'` option at the command line (or by adding `#{ly:set-option 'relative-includes #t}` at the top of the main input file). With `relative-includes` set, the path for each `\include` command will be taken relative to the file containing that command. This behavior is recommended and it will become the default behavior in a future version of lilypond.

Files can also be included from a directory in a search path specified as an option when invoking LilyPond from the command line. The included files are then specified using just their file name. For example, to compile `'main.ly'` which includes files located in a subdirectory called `'parts'` by this method, `cd` to the directory containing `'main.ly'` and enter

```
lilypond --include=parts main.ly
```

and in `main.ly` write

```
\include "VI.ly"
\include "VII.ly"
... etc
```

Files which are to be included in many scores may be placed in the LilyPond directory `'../ly'`. (The location of this directory is installation-dependent - see [Section “Other sources of information” in \*Learning Manual\*](#)). These files can then be included simply by naming them on an `\include` statement. This is how the language-dependent files like `'english.ly'` are included.

LilyPond includes a number of files by default when you start the program. These includes are not apparent to the user, but the files may be identified by running `lilypond --verbose` from the command line. This will display a list of paths and files that LilyPond uses, along with

much other information. Alternatively, the more important of these files are discussed in [Section “Other sources of information” in \*Learning Manual\*](#). These files may be edited, but changes to them will be lost on installing a new version of LilyPond.

Some simple examples of using `\include` are shown in [Section “Scores and parts” in \*Learning Manual\*](#).

## See also

Learning Manual: [Section “Other sources of information” in \*Learning Manual\*](#), [Section “Scores and parts” in \*Learning Manual\*](#).

## Known issues and warnings

If an included file is given a name which is the same as one in LilyPond’s installation files, LilyPond’s file from the installation files takes precedence.

### 3.3.2 Different editions from one source

Several methods can be used to generate different versions of a score from the same music source. Variables are perhaps the most useful for combining lengthy sections of music and/or annotation. Tags are more useful for selecting one section from several alternative shorter sections of music, and can also be used for splicing pieces of music together at different points.

Whichever method is used, separating the notation from the structure of the score will make it easier to change the structure while leaving the notation untouched.

## Using variables

If sections of the music are defined in variables they can be reused in different parts of the score, see [Section “Organizing pieces with variables” in \*Learning Manual\*](#). For example, an *a cappella* vocal score frequently includes a piano reduction of the parts for rehearsal purposes which is identical to the vocal music, so the music need be entered only once. Music from two variables may be combined on one staff, see [\[Automatic part combining\]](#), page 154. Here is an example:

```
sopranoMusic = \relative c' { a4 b c b8( a) }
altoMusic = \relative g' { e4 e e f }
tenorMusic = \relative c' { c4 b e d8( c) }
bassMusic = \relative c' { a4 gis a d, }
allLyrics = \lyricmode {King of glo -- ry }
<<
  \new Staff = "Soprano" \sopranoMusic
  \new Lyrics \allLyrics
  \new Staff = "Alto" \altoMusic
  \new Lyrics \allLyrics
  \new Staff = "Tenor" {
    \clef "treble_8"
    \tenorMusic
  }
  \new Lyrics \allLyrics
  \new Staff = "Bass" {
    \clef "bass"
    \bassMusic
  }
  \new Lyrics \allLyrics
  \new PianoStaff <<
    \new Staff = "RH" {
      \set Staff.printPartCombineTexts = ##f
```

```

\partcombine
\sopranoMusic
\altoMusic
}
\new Staff = "LH" {
  \set Staff.printPartCombineTexts = ##f
  \clef "bass"
  \partcombine
  \tenorMusic
  \bassMusic
}
>>
>>

```



Separate scores showing just the vocal parts or just the piano part can be produced by changing just the structural statements, leaving the musical notation unchanged.

For lengthy scores, the variable definitions may be placed in separate files which are then included, see [Section 3.3.1 \[Including LilyPond files\]](#), page 448.

## Using tags

The `\tag #'partA` command marks a music expression with the name *partA*. Expressions tagged in this way can be selected or filtered out by name later, using either `\keepWithTag #'name` or `\removeWithTag #'name`. The result of applying these filters to tagged music is as follows:

### Filter

Tagged music preceded by `\keepWithTag`  
 `#'name`

### Result

Untagged music and music tagged with *name* is included; music tagged with any other tag name is excluded.

Tagged music preceded by `\removeWithTag #'name` Untagged music and music tagged with any tag name other than *name* is included; music tagged with *name* is excluded.


Tagged music not preceded by either `\keepWithTag` or `\removeWithTag` All tagged and untagged music is included.

The arguments of the `\tag`, `\keepWithTag` and `\removeWithTag` commands should be a symbol (such as `#'score` or `#'part`), followed by a music expression.

In the following example, we see two versions of a piece of music, one showing trills with the usual notation, and one with trills explicitly expanded:

```
music = \relative g' {
  g8. c32 d
  \tag #'trills { d8.\trill }
  \tag #'expand { \repeat unfold 3 { e32 d } }
  c32 d
}
```

```
\score {
  \keepWithTag #'trills \music
}
\score {
  \keepWithTag #'expand \music
}
```



Alternatively, it is sometimes easier to exclude sections of music:

```
music = \relative g' {
  g8. c32 d
  \tag #'trills { d8.\trill }
  \tag #'expand { \repeat unfold 3 { e32 d } }
  c32 d
}
```

```
\score {
  \removeWithTag #'expand
  \music
}
\score {
  \removeWithTag #'trills
  \music
}
```





Tagged filtering can be applied to articulations, texts, etc. by prepending

`-\tag #'your-tag`

to an articulation. For example, this would define a note with a conditional fingering indication and a note with a conditional annotation:

```
c1-\tag #'finger ^4
c1-\tag #'warn ^"Watch!"
```

Multiple tags may be placed on expressions with multiple `\tag` entries:

```
music = \relative c'' {
  \tag #'a \tag #'both { a4 a a a }
  \tag #'b \tag #'both { b4 b b b }
}
<<
\keepWithTag #'a \music
\keepWithTag #'b \music
\keepWithTag #'both \music
>>
```



Multiple `\removeWithTag` filters may be applied to a single music expression to remove several differently named tagged sections:

```
music = \relative c'' {
  \tag #'A { a4 a a a }
  \tag #'B { b4 b b b }
  \tag #'C { c4 c c c }
  \tag #'D { d4 d d d }
}
{
  \removeWithTag #'B
  \removeWithTag #'C
  \music
}
```



Two or more `\keepWithTag` filters applied to a single music expression will cause *all* tagged sections to be removed, as the first filter will remove all tagged sections except the one named, and the second filter will remove even that tagged section.

Sometimes you want to splice some music at a particular place in an existing music expression. You can use `\pushToTag` and `\appendToTag` for adding material at the front or end of the `elements` of an existing music construct. Not every music construct has `elements`, but sequential and simultaneous music are safe bets:

```
test = { \tag #'here { \tag #'here <<c''>> } }
```

```
{
  \pushToTag #'here c'
  \pushToTag #'here e'
  \pushToTag #'here g' \test
  \appendToTag #'here c'
  \appendToTag #'here e'
  \appendToTag #'here g' \test
}
```



Both commands get a tag, the material to splice in at every occurrence of the tag, and the tagged expression. The commands make sure to copy everything that they change so that the original `\test` retains its meaning.

## See also

Learning Manual: [Section “Organizing pieces with variables” in \*Learning Manual\*](#).

Notation Reference: [\[Automatic part combining\]](#), page 154, [Section 3.3.1 \[Including LilyPond files\]](#), page 448.

## Using global settings

Global settings can be included from a separate file:

```
lilypond -dinclue=MY_SETTINGS.ly MY_SCORE.ly
```

Groups of settings such as page size, font or type face can be stored in separate files. This allows different editions from the same score as well as standard settings to be applied to many scores, simply by specifying the proper settings file.

This technique also works well with the use of style sheets, as discussed in [Section “Style sheets” in \*Learning Manual\*](#).

## See also

Learning Manual: [Section “Organizing pieces with variables” in \*Learning Manual\*](#), [Section “Style sheets” in \*Learning Manual\*](#).

Notation Reference: [Section 3.3.1 \[Including LilyPond files\]](#), page 448.

## 3.3.3 Special characters

### Text encoding

LilyPond uses the character repertoire defined by the Unicode consortium and ISO/IEC 10646. This defines a unique name and code point for the character sets used in virtually all modern languages and many others too. Unicode can be implemented using several different encodings. LilyPond uses the UTF-8 encoding (UTF stands for Unicode Transformation Format) which represents all common Latin characters in one byte, and represents other characters using a variable length format of up to four bytes.

The actual appearance of the characters is determined by the glyphs defined in the particular fonts available - a font defines the mapping of a subset of the Unicode code points to glyphs. LilyPond uses the Pango library to layout and render multi-lingual texts.

LilyPond does not perform any input-encoding conversions. This means that any text, be it title, lyric text, or musical instruction containing non-ASCII characters, must be encoded in UTF-8. The easiest way to enter such text is by using a Unicode-aware editor and saving the file with UTF-8 encoding. Most popular modern editors have UTF-8 support, for example, vim, Emacs, jEdit, and GEdit do. All MS Windows systems later than NT use Unicode as their native character encoding, so even Notepad can edit and save a file in UTF-8 format. A more functional alternative for Windows is BabelPad.

If a LilyPond input file containing a non-ASCII character is not saved in UTF-8 format the error message

```
FT_Get_Glyph_Name () error: invalid argument
```

will be generated.

Here is an example showing Cyrillic, Hebrew and Portuguese text:



## Unicode

To enter a single character for which the Unicode code point is known but which is not available in the editor being used, use either `\char ##xhhhh` or `\char #dddd` within a `\markup` block, where `hhhh` is the hexadecimal code for the character required and `dddd` is the corresponding decimal value. Leading zeroes may be omitted, but it is usual to specify all four characters in the hexadecimal representation. (Note that the UTF-8 encoding of the code point should *not* be used after `\char`, as UTF-8 encodings contain extra bits indicating the number of octets.) Unicode code charts and a character name index giving the code point in hexadecimal for any character can be found on the Unicode Consortium website, <http://www.unicode.org/>.


For example, `\char ##x03BE` and `\char #958` would both enter the Unicode U+03BE character, which has the Unicode name “Greek Small Letter Xi”.

Any Unicode code point may be entered in this way and if all special characters are entered in this format it is not necessary to save the input file in UTF-8 format. Of course, a font containing all such encoded characters must be installed and available to LilyPond.

The following example shows Unicode hexadecimal values being entered in four places – in a rehearsal mark, as articulation text, in lyrics and as stand-alone text below the score:

```
\score {
  \relative c'' {
    c1 \mark \markup { \char ##x03EE }
    c1_\markup { \tiny { \char ##x03B1 " to " \char ##x03C9 } }
  }
  \addlyrics { 0 \markup { \concat { Ph \char ##x0153 be! } } }
}
\markup { "Copyright 2008--2012" \char ##x00A9 }
```





Copyright 2008--2012 ©

To enter the copyright sign in the copyright notice use:

```
\header {
  copyright = \markup { \char ##x00A9 "2008" }
}
```

## ASCII aliases

A list of ASCII aliases for special characters can be included:


```
\paper {
  #(include-special-characters)
}
```

```
\markup "&flqq; &ndash; &OE;uvre incomplète&hellip; &frqq;"
```

```
\score {
  \new Staff { \repeat unfold 9 a'4 }
  \addlyrics {
    This is al -- so wor -- kin'~in ly -- rics: &ndash;_&OE;&hellip;
  }
}
```

```
\markup \column {
  "The replacement can be disabled:"
  "&ndash; &OE; &hellip;"
  \override #'(replacement-alist . ()) "&ndash; &OE; &hellip;"
}
```

« – Œuvre incomplète... »



The replacement can be disabled:

– Œ ...

&ndash; &OE; &hellip;

You can also make your own aliases, either globally:

```
\paper {
  #(add-text-replacements!
    '(("100" . "hundred")
      ("dpi" . "dots per inch")))
}
\markup "A 100 dpi."
```

A hundred dots per inch.

or locally:

```
\markup \replace #'(("100" . "hundred")
                      ("dpi" . "dots per inch")) "A 100 dpi."
```

A hundred dots per inch.

## See also

Notation Reference: [Section A.11 \[List of special characters\]](#), page 652.

Installed Files: ‘ly/text-replacements.ly’.

## 3.4 Controlling output

### 3.4.1 Extracting fragments of music

It is possible to quote small fragments of a large score directly from the output. This can be compared to clipping a piece of a paper score with scissors.

This is done by defining the measures that need to be cut out separately. For example, including the following definition

```
\layout {
  clip-regions
  = #(list
    (cons
      (make-rhythmic-location 5 1 2)
      (make-rhythmic-location 7 3 4)))
}
```

will extract a fragment starting halfway the fifth measure, ending in the seventh measure. The meaning of 5 1 2 is: after a 1/2 note in measure 5, and 7 3 4 after 3 quarter notes in measure 7.

More clip regions can be defined by adding more pairs of rhythmic-locations to the list.

In order to use this feature, LilyPond must be invoked with ‘-dclip-systems’. The clips are output as EPS files, and are converted to PDF and PNG if these formats are switched on as well.

For more information on output formats, see [Section “Invoking lilypond” in \*Application Usage\*](#).

### 3.4.2 Skipping corrected music

When entering or copying music, usually only the music near the end (where you are adding notes) is interesting to view and correct. To speed up this correction process, it is possible to skip typesetting of all but the last few measures. This is achieved by putting


```
showLastLength = R1*5
\score { ... }
```

in your source file. This will render only the last 5 measures (assuming 4/4 time signature) of every `\score` in the input file. For longer pieces, rendering only a small part is often an order of magnitude quicker than rendering it completely. When working on the beginning of a score you have already typeset (e.g. to add a new part), the `showFirstLength` property may be useful as well.

Skipping parts of a score can be controlled in a more fine-grained fashion with the property `Score.skipTypesetting`. When it is set, no typesetting is performed at all.

This property is also used to control output to the MIDI file. Note that it skips all events, including tempo and instrument changes. You have been warned.

```
c8 d
\set Score.skipTypesetting = ##t
e8 e e e e e e e
\set Score.skipTypesetting = ##f
c8 d b bes a g c2
```



In polyphonic music, `Score.skipTypesetting` will affect all voices and staves, saving even more time.

### 3.4.3 Alternative output formats

The default output formats for the printed score are Portable Document Format (PDF) and PostScript (PS). Scalable Vector Graphics (SVG), Encapsulated PostScript (EPS) and Portable Network Graphics (PNG) output formats are also available through command line options, see [Section “Command line options for lilypond”](#) in *Application Usage*.

### 3.4.4 Replacing the notation font

Gonville is an alternative to the Feta font used in LilyPond and can be downloaded from:

<http://www.chiark.greenend.org.uk/~sgtatham/gonville/>

Here are a few sample bars of music set in Gonville:



Here are a few sample bars of music set in LilyPond’s Feta font:



## Installation Instructions for MacOS

Download and extract the zip file. Copy the `lilyfonts` directory to `‘SHARE_DIR/lilypond/current’`; for more information, see [Section “Other sources of information”](#) in *Learning Manual*. Rename the existing `fonts` directory to `fonts_orig` and the `lilyfonts` directory to `fonts`. To revert back to Feta, reverse the process.

## See also

Learning Manual: [Section “Other sources of information”](#) in *Learning Manual*.

## Known issues and warnings

Gonville cannot be used to typeset ‘Ancient Music’ notation and it is likely newer glyphs in later releases of LilyPond may not exist in the Gonville font family. Please refer to the author’s website for more information on these and other specifics, including licensing of Gonville.

## 3.5 MIDI output

MIDI (Musical Instrument Digital Interface) is a standard for connecting and controlling digital instruments. A MIDI file is a series of notes in a number of tracks. It is not an actual sound file; you need special software to translate between the series of notes and actual sounds.

Pieces of music can be converted to MIDI files, so you can listen to what was entered. This is convenient for checking the music; octaves that are off or accidentals that were mistyped stand out very much when listening to the MIDI output.

Standard MIDI output is somewhat crude; optionally, an enhanced and more realistic MIDI output is available by means of [Section 3.5.7 \[The Articulate script\]](#), [page 467](#).

The MIDI output allocates a channel for each staff, and reserves channel 10 for drums. There are only 16 MIDI channels per device, so if the score contains more than 15 staves, MIDI channels will be reused.

### 3.5.1 Creating MIDI files

To create a MIDI output file from a LilyPond input file, add a `\midi` block to a score, for example,

```
\score {
  ...music...
  \midi { }
}
```

If there is a `\midi` block in a `\score` with no `\layout` block, only MIDI output will be produced. When notation is needed too, a `\layout` block must also be present.

```
\score {
  ...music...
  \midi { }
  \layout { }
}
```

Pitches, rhythms, ties, dynamics, and tempo changes are interpreted and translated correctly to the MIDI output. Dynamic marks, crescendi and decrescendi translate into MIDI volume levels. Dynamic marks translate to a fixed fraction of the available MIDI volume range. Crescendi and decrescendi make the volume vary linearly between their two extremes. The effect of dynamic markings on the MIDI output can be removed completely, see [Section 3.5.2 \[MIDI block\]](#), [page 460](#).

The initial tempo and later tempo changes can be specified with the `\tempo` command within the music notation. These are reflected in tempo changes in the MIDI output. This command will normally result in the metronome mark being printed, but this can be suppressed, see [\[Metronome marks\]](#), [page 61](#). An alternative way of specifying the initial or overall MIDI tempo is described below, see [Section 3.5.2 \[MIDI block\]](#), [page 460](#).

Due to some limitations on Windows, the default extension for MIDI files on Windows is `.mid`. Other operating systems still use the extension `.midi`. If a different extension is preferred, insert the following line at the top-level of the input file, before the start of any `\book`, `\bookpart` or `\score` blocks:

```
#(ly:set-option 'midi-extension "midi")
```

The line above will set the default extension for MIDI files to `.midi`.

Alternatively, this option can also be supplied on the command line:

```
lilypond ... -dmidi-extension=midi lilyFile.ly
```

## Instrument names

The MIDI instrument to be used is specified by setting the `Staff.midiInstrument` property to the instrument name. The name should be chosen from the list in [Section A.5 \[MIDI instruments\]](#), page 586.

```
\new Staff {
  \set Staff.midiInstrument = #"glockenspiel"
  ...notes...
}
\new Staff \with {midiInstrument = #"cello"} {
  ...notes...
}
```

If the selected instrument does not exactly match an instrument from the list of MIDI instruments, the Grand Piano ("acoustic grand") instrument is used.

## Selected Snippets

### *Changing MIDI output to one channel per voice*

When outputting MIDI, the default behavior is for each staff to represent one MIDI channel, with all the voices on a staff amalgamated. This minimizes the risk of running out of MIDI channels, since there are only 16 available per MIDI port, and most devices support only one port.

However, by moving the `Staff_performer` to the `Voice` context, each voice on a staff can have its own MIDI channel, as is demonstrated by the following example: despite being on the same staff, two MIDI channels are created, each with a different `midiInstrument`.

```
\score {
  \new Staff <<
    \new Voice \relative c''' {
      \set midiInstrument = #"flute"
      \voiceOne
      \key g \major
      \time 2/2
      r2 g-"Flute" ~
      g fis ~
      fis4 g8 fis e2 ~
      e4 d8 cis d2
    }
    \new Voice \relative c'' {
      \set midiInstrument = #"clarinet"
      \voiceTwo
      b1-"Clarinet"
      a2. b8 a
      g2. fis8 e
      fis2 r
    }
  >>
  \layout { }
  \midi {
    \context {
      \Staff
      \remove "Staff_performer"
    }
  }
}
```

```

\context {
  \Voice
  \consists "Staff_performer"
}
\context {
  \Score
  tempoWholesPerMinute = #(ly:make-moment 72 2)
}
}
}

```



## Known issues and warnings

Changes in the MIDI volume take place only on starting a note, so crescendi and decrescendi cannot affect the volume of a single note.

Not all midi players correctly handle tempo changes in the midi output. Players that are known to work include MS Windows Media Player and [timidity](#).

### 3.5.2 MIDI block

A `\midi` block must appear within a score block if MIDI output is required. It is analogous to the layout block, but somewhat simpler. Often, the `\midi` block is left empty, but it can contain context rearrangements, new context definitions or code to set the values of properties. For example, the following will set the initial tempo exported to a MIDI file without causing a tempo indication to be printed:

```

\score {
  ...music...
  \midi {
    \context {
      \Score
      tempoWholesPerMinute = #(ly:make-moment 72 4)
    }
  }
}

```

In this example the tempo is set to 72 quarter note beats per minute. This kind of tempo specification cannot take a dotted note length as an argument. If one is required, break the dotted note into smaller units. For example, a tempo of 90 dotted quarter notes per minute can be specified as 270 eighth notes per minute:

```
tempoWholesPerMinute = #(ly:make-moment 270 8)
```

Context definitions follow precisely the same syntax as those within a `\layout` block. Translation modules for sound are called performers. The contexts for MIDI output are defined in `../ly/performer-init.ly`, see [Section “Other sources of information” in \*Learning Manual\*](#). For example, to remove the effect of dynamics from the MIDI output, insert the following lines in the `\midi{ }` block.

```
\midi {
  ...
  \context {
    \Voice
    \remove "Dynamic_performer"
  }
}
```

MIDI output is created only when a `\midi` block is included within a score block defined with a `\score` command.

```
\score {
  { ...notes... }
  \midi { }
}
```

### 3.5.3 What goes into the MIDI output?

#### Supported in MIDI

The following items of notation are reflected in the MIDI output:

- Pitches
- Microtones (See [\[Accidentals\]](#), page 5. Rendering needs a player that supports pitch bend.)
- Chords entered as chord names
- Rhythms entered as note durations, including tuplets
- Tremolos entered without ‘:[number]’
- Ties
- Dynamic marks
- Crescendi, decrescendi over multiple notes
- Tempo changes entered with a tempo marking
- Lyrics

Using [Section 3.5.7 \[The Articulate script\]](#), page 467, a number of items are added to the above list:

- Articulations (slurs, staccato, etc)
- Trills, turns
- Rallentando and accelerando

#### Unsupported in MIDI

The following items of notation have no effect on the MIDI output, unless you use [Section 3.5.7 \[The Articulate script\]](#), page 467:

- Rhythms entered as annotations, e.g. swing
- Tempo changes entered as annotations with no tempo marking
- Staccato and other articulations and ornamentations
- Slurs and Phrasing slurs
- Crescendi, decrescendi over a single note
- Tremolos entered with ‘:[number]’
- Figured bass
- Microtonal chords

### 3.5.4 Repeats in MIDI

With a few minor additions, all types of repeats can be represented in the MIDI output. This is achieved by applying the `\unfoldRepeats` music function. This function changes all repeats to unfold repeats.

```
\unfoldRepeats {
  \repeat tremolo 8 { c'32 e' }
  \repeat percent 2 { c''8 d'' }
  \repeat volta 2 { c'4 d' e' f' }
  \alternative {
    { g' a' a' g' }
    { f' e' d' c' }
  }
}
\bar "|."
```



In scores containing multiple voices, unfolding of repeats in MIDI output will only occur correctly if *each* voice contains fully notated repeat indications.

When creating a score file using `\unfoldRepeats` for MIDI, it is necessary to make two `\score` blocks: one for MIDI (with unfolded repeats) and one for notation (with volta, tremolo, and percent repeats). For example,

```
\score {
  ..music..
  \layout { .. }
}
\score {
  \unfoldRepeats ..music..
  \midi { .. }
}
```

### 3.5.5 Controlling MIDI dynamics

MIDI dynamics are implemented by the `Dynamic_performer` which lives by default in the `Voice` context. It is possible to control the overall MIDI volume, the relative volume of dynamic markings and the relative volume of different instruments.

#### Dynamic marks

Dynamic marks are translated to a fixed fraction of the available MIDI volume range. The default fractions range from 0.25 for *ppppp* to 0.95 for *ffff*. The set of dynamic marks and the associated fractions can be seen in `'../scm/midi.scm'`, see [Section “Other sources of information” in Learning Manual](#). This set of fractions may be changed or extended by providing a function which takes a dynamic mark as its argument and returns the required fraction, and setting `Score.dynamicAbsoluteVolumeFunction` to this function.

For example, if a *rinforzando* dynamic marking, `\rfz`, is required, this will not by default have any effect on the MIDI volume, as this dynamic marking is not included in the default set.



Similarly, if a new dynamic marking has been defined with `make-dynamic-script` that too will not be included in the default set. The following example shows how the MIDI volume for such dynamic markings might be added. The Scheme function sets the fraction to 0.9 if a dynamic mark of `rfz` is found, or calls the default function otherwise.

```
#(define (myDynamics dynamic)
  (if (equal? dynamic "rfz")
      0.9
      (default-dynamic-absolute-volume dynamic)))

\score {
  \new Staff {
    \set Staff.midiInstrument = #"cello"
    \set Score.dynamicAbsoluteVolumeFunction = #myDynamics
    \new Voice {
      \relative c'' {
        a4\pp b c-\rfz
      }
    }
  }
  \layout {}
  \midi {}
}
```



Alternatively, if the whole table of fractions needs to be redefined, it would be better to use the `default-dynamic-absolute-volume` procedure in `../scm/midi.scm` and the associated table as a model. The final example in this section shows how this might be done.

## Overall MIDI volume

The minimum and maximum overall volume of MIDI dynamic markings is controlled by setting the properties `midiMinimumVolume` and `midiMaximumVolume` at the `Score` level. These properties have an effect only on dynamic marks, so if they are to apply from the start of the score a dynamic mark must be placed there. The fraction corresponding to each dynamic mark is modified with this formula

$$\text{midiMinimumVolume} + (\text{midiMaximumVolume} - \text{midiMinimumVolume}) * \text{fraction}$$

In the following example the dynamic range of the overall MIDI volume is limited to the range 0.2 - 0.5.

```
\score {
  <<
  \new Staff {
    \key g \major
    \time 2/2
    \set Staff.midiInstrument = #"flute"
    \new Voice \relative c''' {
      r2 g\mp g fis~
      fis4 g8 fis e2~
      e4 d8 cis d2
    }
  }
}
```

```

    }
  }
  \new Staff {
    \key g \major
    \set Staff.midiInstrument = #"clarinet"
    \new Voice \relative c'' {
      b1\p a2. b8 a
      g2. fis8 e
      fis2 r
    }
  }
}
>>
\layout {}
\midi {
  \context {
    \Score
    tempoWholesPerMinute = #(ly:make-moment 72 2)
    midiMinimumVolume = #0.2
    midiMaximumVolume = #0.5
  }
}
}

```



### Equalizing different instruments (i)

If the minimum and maximum MIDI volume properties are set in the **Staff** context the relative volumes of the MIDI instruments can be controlled. This gives a basic instrument equalizer, which can enhance the quality of the MIDI output remarkably.

In this example the volume of the clarinet is reduced relative to the volume of the flute. There must be a dynamic mark on the first note of each instrument for this to work correctly.

```

\score {
  <<
    \new Staff {
      \key g \major
      \time 2/2
      \set Staff.midiInstrument = #"flute"
      \set Staff.midiMinimumVolume = #0.7
      \set Staff.midiMaximumVolume = #0.9
      \new Voice \relative c''' {
        r2 g\mp g fis~
        fis4 g8 fis e2~
        e4 d8 cis d2
      }
    }
  }
}

```

```

\new Staff {
  \key g \major
  \set Staff.midiInstrument = #"clarinet"
  \set Staff.midiMinimumVolume = #0.3
  \set Staff.midiMaximumVolume = #0.6
  \new Voice \relative c'' {
    b1\p a2. b8 a
    g2. fis8 e
    fis2 r
  }
}
>>
\layout {}
\midi {
  \context {
    \Score
    tempoWholesPerMinute = #(ly:make-moment 72 2)
  }
}
}

```



### Equalizing different instruments (ii)

If the MIDI minimum and maximum volume properties are not set LilyPond will, by default, apply a small degree of equalization to a few instruments. The instruments and the equalization applied are shown in the table *instrument-equalizer-alist* in ‘*../scm/midi.scm*’.

This basic default equalizer can be replaced by setting `instrumentEqualizer` in the `Score` context to a new Scheme procedure which accepts a MIDI instrument name as its only argument and returns a pair of fractions giving the minimum and maximum volumes to be applied to that instrument. This replacement is done in the same way as shown for resetting the `dynamicAbsoluteVolumeFunction` at the start of this section. The default equalizer, *default-instrument-equalizer*, in ‘*../scm/midi.scm*’ shows how such a procedure might be written.

The following example sets the relative flute and clarinet volumes to the same values as the previous example.

```

#(define my-instrument-equalizer-alist '())

#(set! my-instrument-equalizer-alist
  (append
    '(
      ("flute" . (0.7 . 0.9))
      ("clarinet" . (0.3 . 0.6)))
    my-instrument-equalizer-alist))

#(define (my-instrument-equalizer s)

```

```

(let ((entry (assoc s my-instrument-equalizer-alist)))
  (if entry
    (cdr entry))))

\score {
  <<
    \new Staff {
      \key g \major
      \time 2/2
      \set Score.instrumentEqualizer = #my-instrument-equalizer
      \set Staff.midiInstrument = #"flute"
      \new Voice \relative c''' {
        r2 g\mp g fis~
        fis4 g8 fis e2~
        e4 d8 cis d2
      }
    }
    \new Staff {
      \key g \major
      \set Staff.midiInstrument = #"clarinet"
      \new Voice \relative c'' {
        b1\p a2. b8 a
        g2. fis8 e
        fis2 r
      }
    }
  >>
  \layout { }
  \midi {
    \context {
      \Score
      tempoWholesPerMinute = #(ly:make-moment 72 2)
    }
  }
}

```



### 3.5.6 Percussion in MIDI

Percussion instruments are generally notated in a **DrumStaff** context and when notated in this way they are outputted correctly to MIDI channel 10, but some pitched percussion instruments, like the xylophone, marimba, vibraphone, timpani, etc., are treated like “normal” instruments and music for these instruments should be entered in a normal **Staff** context, not a **DrumStaff** context, to obtain the correct MIDI output.

Some non-pitched percussion sounds included in the general MIDI standard, like melodic tom, taiko drum, synth drum, etc., cannot be reached via MIDI channel 10, so the notation

for such instruments should also be entered in a normal **Staff** context, using suitable normal pitches.

Many percussion instruments are not included in the general MIDI standard, e.g. castanets. The easiest, although unsatisfactory, method of producing some MIDI output when writing for such instruments is to substitute the nearest sound from the standard set.

## Known issues and warnings

Because the general MIDI standard does not contain rim shots, the sidestick is used for this purpose instead.

### 3.5.7 The Articulate script

A more realistic MIDI output is possible when using the Articulate script. It tries to take articulations (slurs, staccato, etc) into account, by replacing notes with sequential music of suitably time-scaled note plus skip. It also tries to unfold trills turns etc., and take rallentando and accelerando into account.

To use the Articulate script, you have to include it at the top of your input file,

```
\include "articulate.ly"
and in the \score section do
\unfoldRepeats \articulate <<
all the rest of the score...
>>
```

After altering your input file this way, the visual output is heavily altered, but the standard `\midi` block will produce a better MIDI file.

Although not essential for the Articulate script to work, you may want to insert the `\unfoldRepeats` command as it appears in the example shown above as it enables performing abbreviations such as *trills*.

## Known issues and warnings

Articulate shortens chords and some music (esp. organ music) could sound worse.

## 3.6 Extracting musical information

In addition to creating graphical output and MIDI, LilyPond can display musical information as text.

### 3.6.1 Displaying LilyPond notation

Displaying a music expression in LilyPond notation can be done with the music function `\displayLilyMusic`. To see the output, you will typically want to call LilyPond using the command line. For example,

```
{
  \displayLilyMusic \transpose c a, { c4 e g a bes }
}

will display
{ a,4 cis e fis g }
```

By default, LilyPond will print these messages to the console along with all the other LilyPond compilation messages. To split up these messages and save the results of `\display{STUFF}`, redirect the output to a file.

```
lilypond file.ly >display.txt
```

Note that Lilypond does not just display the music expression, but also interprets it (since `\displayLilyMusic` returns it in addition to displaying it). This is convenient since you can just insert `\displayLilyMusic` into existing music in order to get information about it. If you don't actually want Lilypond to interpret the displayed music as well as display it, use `\void` in order to have it ignored:

```
{
  \void \displayLilyMusic \transpose c a, { c4 e g a bes }
}
```

### 3.6.2 Displaying scheme music expressions

See [Section “Displaying music expressions”](#) in *Extending*.

### 3.6.3 Saving music events to a file

Music events can be saved to a file on a per-staff basis by including a file in your main score.

```
\include "event-listener.ly"
```

This will create file(s) called ‘`FILENAME-STAFFNAME.notes`’ or ‘`FILENAME-unnamed-staff.notes`’ for each staff. Note that if you have multiple unnamed staves, the events for all staves will be mixed together in the same file. The output looks like this:

```
0.000  note      57      4  p-c 2 12
0.000  dynamic   f
0.250  note      62      4  p-c 7 12
0.500  note      66      8  p-c 9 12
0.625  note      69      8  p-c 14 12
0.750  rest      4
0.750  breathe
```

The syntax is a tab-delimited line, with two fixed fields on each line followed by optional parameters.

```
time  type  ...params...
```

This information can easily be read into other programs such as python scripts, and can be very useful for researchers wishing to perform musical analysis or playback experiments with LilyPond.

### Known issues and warnings

Not all lilypond music events are supported by ‘`event-listener.ly`’. It is intended to be a well-crafted “proof of concept”. If some events that you want to see are not included, copy ‘`event-listener.ly`’ into your lilypond directory and modify the file so that it outputs the information you want.

## 4 Spacing issues

The global paper layout is determined by three factors: the page layout, the line breaks, and the spacing. These all influence each other. The choice of spacing determines how densely each system of music is set. This influences where line breaks are chosen, and thus ultimately, how many pages a piece of music takes.

Globally speaking, this procedure happens in four steps: first, flexible distances (‘springs’) are chosen, based on durations. All possible line breaking combinations are tried, and a ‘badness’ score is calculated for each. Then the height of each possible system is estimated. Finally, a page breaking and line breaking combination is chosen so that neither the horizontal nor the vertical spacing is too cramped or stretched.

Two types of blocks can contain layout settings: `\paper {...}` and `\layout {...}`. The `\paper` block contains page layout settings that are expected to be the same for all scores in a book, such as the paper height, or whether to print page numbers, etc. See [Section 4.1 \[Page layout\]](#), page 469. The `\layout` block contains score layout settings, such as the number of systems to use, or the space between staff-groups, etc. See [Section 4.2 \[Score layout\]](#), page 478.

### 4.1 Page layout

This section discusses page layout options for the `\paper` block.

#### 4.1.1 The `\paper` block

The `\paper` block can appear within a `\book` block, but not within a `\score` block. Settings in a `\paper` block apply to the entire book, which may include multiple scores. Settings that can appear in a `\paper` block include:

- the `set-paper-size` scheme function,
- `\paper` variables used for customizing page layout, and
- markup definitions used for customizing the layout of headers, footers, and titles.

The `set-paper-size` function is discussed in the next section, [Section 4.1.2 \[Paper size and automatic scaling\]](#), page 470. The `\paper` variables that deal with page layout are discussed in later sections. The markup definitions that deal with headers, footers, and titles are discussed in [Section 3.2.2 \[Custom headers footers and titles\]](#), page 433.

Most `\paper` variables will only work in a `\paper` block. The few that will also work in a `\layout` block are listed in [Section 4.2.1 \[The `\layout` block\]](#), page 478.

Except when specified otherwise, all `\paper` variables that correspond to distances on the page are measured in millimeters, unless a different unit is specified by the user. For example, the following declaration sets `top-margin` to ten millimeters:

```
\paper {
  top-margin = 10
}
```

To set it to 0.5 inches, use the `\in` unit suffix:

```
\paper {
  top-margin = 0.5\in
}
```

The available unit suffixes are `\mm`, `\cm`, `\in`, and `\pt`. These units are simple values for converting from millimeters; they are defined in ‘`ly/paper-defaults-init.ly`’. For the sake of clarity, when using millimeters, the `\mm` is typically included in the code, even though it is not technically necessary.

It is also possible to define `\paper` values using Scheme. The Scheme equivalent of the above example is:

```
\paper {
  #(define top-margin (* 0.5 in))
}
```

## See also

Notation Reference: [Section 4.1.2 \[Paper size and automatic scaling\]](#), page 470, [Section 3.2.2 \[Custom headers footers and titles\]](#), page 433, [Section 4.2.1 \[The \layout block\]](#), page 478.

Installed Files: ‘ly/paper-defaults-init.ly’.

## 4.1.2 Paper size and automatic scaling

### Setting paper size

Two functions are available for changing the paper size: `set-default-paper-size` and `set-paper-size`. `set-default-paper-size` must be placed in the toplevel scope, and `set-paper-size` must be placed in a `\paper` block:

```
 #(set-default-paper-size "a4")
\paper {
  #(set-paper-size "a4")
}
```

In the toplevel scope, the `set-default-paper-size` function can safely be called anywhere before the first `\paper` block. Within a `\paper` block, the safest place to call `set-paper-size` is at the top, above the list of variable declarations. The reasons for this are discussed in [\[Automatic scaling to paper size\]](#), page 470.

`set-default-paper-size` sets the size of all pages, whereas `set-paper-size` only sets the size of the pages that the `\paper` block applies to. For example, if the `\paper` block is at the top of the file, then it will apply the paper size to all pages. If the `\paper` block is inside a `\book`, then the paper size will only apply to that book.

Common paper sizes are available, including `a4`, `letter`, `legal`, and `11x17` (also known as tabloid). Many more paper sizes are supported by default. For details, see ‘`scm/paper.scm`’, and search for the definition of `paper-alist`.

**Note:** The default paper size is `a4`.

Extra sizes may be added by editing the definition of `paper-alist` in the initialization file ‘`scm/paper.scm`’, however they will be overridden on a subsequent install.

If the symbol ‘`landscape`’ is supplied as an argument to `set-default-paper-size`, pages will be rotated by 90 degrees, and wider line widths will be set accordingly.

```
 #(set-default-paper-size "a6" 'landscape)
```

## See also

Notation Reference: [\[Automatic scaling to paper size\]](#), page 470.

Installed Files: ‘`scm/paper.scm`’.

## Automatic scaling to paper size

If the paper size is changed with one of the scheme functions (`set-default-paper-size` or `set-paper-size`), the values of several `\paper` variables are automatically scaled to the new size. To bypass the automatic scaling for a particular variable, set the variable after setting the paper size. Note that the automatic scaling is not triggered by setting the `paper-height` or `paper-width` variables, even though `paper-width` can influence other values (this is separate



from scaling and is discussed below). The `set-default-paper-size` and `set-paper-size` functions are described in [\[Setting paper size\]](#), page 470.

The vertical dimensions affected by automatic scaling are `top-margin` and `bottom-margin` (see [Section 4.1.3 \[Fixed vertical spacing \paper variables\]](#), page 471). The horizontal dimensions affected by automatic scaling are `left-margin`, `right-margin`, `inner-margin`, `outer-margin`, `binding-offset`, `indent`, and `short-indent` (see [Section 4.1.5 \[Horizontal spacing \paper variables\]](#), page 474).

The default values for these dimensions are set in ‘`ly/paper-defaults-init.ly`’, using internal variables named `top-margin-default`, `bottom-margin-default`, etc. These are the values that result at the default paper size `a4`. For reference, with `a4` paper the `paper-height` is `297\mm` and the `paper-width` is `210\mm`.

## See also

Notation Reference: [Section 4.1.3 \[Fixed vertical spacing \paper variables\]](#), page 471, [Section 4.1.5 \[Horizontal spacing \paper variables\]](#), page 474.

Installed Files: ‘`ly/paper-defaults-init.ly`’, ‘`scm/paper.scm`’.

### 4.1.3 Fixed vertical spacing \paper variables

**Note:** Some `\paper` dimensions are automatically scaled to the paper size, which may lead to unexpected behavior. See [\[Automatic scaling to paper size\]](#), page 470.

Default values (before scaling) are defined in ‘`ly/paper-defaults-init.ly`’.

#### `paper-height`

The height of the page, unset by default. Note that the automatic scaling of some vertical dimensions is not affected by this.

#### `top-margin`

The margin between the top of the page and the top of the printable area. If the paper size is modified, this dimension’s default value is scaled accordingly.

#### `bottom-margin`

The margin between the bottom of the printable area and the bottom of the page. If the paper size is modified, this dimension’s default value is scaled accordingly.

#### `ragged-bottom`

If set to true, systems will not spread vertically down the page. This does not affect the last page. This should be set to true for pieces that have only two or three systems per page, for example orchestral scores.

#### `ragged-last-bottom`

If set to false, systems will spread vertically down the last page. Pieces that amply fill two pages or more should have this set to true. It also affects the last page of book parts, i.e. parts of a book created with `\bookpart` blocks.

## See also

Notation Reference: [\[Automatic scaling to paper size\]](#), page 470.

Installed Files: ‘`ly/paper-defaults-init.ly`’.

Snippets: [Section “Spacing” in \*Snippets\*](#).

## Known issues and warnings

The titles (from the `\header` block) are treated as a system, so `ragged-bottom` and `ragged-last-bottom` will add space between the titles and the first system of the score.

Explicitly defined paper-sizes will override any user-defined top or bottom margin settings.

### 4.1.4 Flexible vertical spacing `\paper` variables

In most cases, it is preferable for the vertical distances between certain items (such as margins, titles, systems, and separate scores) to be flexible, so that they stretch and compress nicely according to each situation. A number of `\paper` variables (listed below) are available to fine-tune the stretching behavior of these dimensions.

Note that the `\paper` variables discussed in this section do not control the spacing of staves within individual systems. Within-system spacing is controlled by grob properties, with settings typically entered inside a `\score` or `\layout` block, and not inside a `\paper` block. See [Section 4.4.1 \[Flexible vertical spacing within systems\]](#), page 488.

### Structure of flexible vertical spacing alists

Each of the flexible vertical spacing `\paper` variables is an alist (association list) containing four *keys*:

- **basic-distance** – the vertical distance, measured in staff-spaces, between the *reference points* of the two items, when no collisions would result, and no stretching or compressing is in effect. The reference point of a (title or top-level) markup is its highest point, and the reference point of a system is the vertical center of the nearest `StaffSymbol` – even if a non-staff line (such as a `Lyrics` context) is in the way. Values for **basic-distance** that are less than either **padding** or **minimum-distance** are not meaningful, since the resulting distance will never be less than either **padding** or **minimum-distance**.
- **minimum-distance** – the smallest allowable vertical distance, measured in staff-spaces, between the reference points of the two items, when compressing is in effect. Values for **minimum-distance** that are less than **padding** are not meaningful, since the resulting distance will never be less than **padding**.
- **padding** – the minimum required amount of unobstructed vertical whitespace between the bounding boxes (or skylines) of the two items, measured in staff-spaces.
- **stretchability** – a unitless measure of the dimension’s relative propensity to stretch. If zero, the distance will not stretch (unless collisions would result). When positive, the significance of a particular dimension’s **stretchability** value lies only in its relation to the **stretchability** values of the other dimensions. For example, if one dimension has twice the **stretchability** of another, it will stretch twice as easily. Values should be non-negative and finite. The value `+inf.0` triggers a `programming_error` and is ignored, but `1.0e7` can be used for an almost infinitely stretchable spring. If unset, the default value is set to **basic-distance**. Note that the dimension’s propensity to *compress* cannot be directly set by the user and is equal to  $(\text{basic-distance} - \text{minimum-distance})$ .

If a page has a ragged bottom, the resulting distance is the largest of:

- **basic-distance**,
- **minimum-distance**, and
- **padding** plus the smallest distance necessary to eliminate collisions.

Specific methods for modifying alists are discussed in [Section 5.3.6 \[Modifying alists\]](#), page 540. The following example demonstrates the two ways these alists can be modified. The first declaration updates one key-value individually, and the second completely redefines the variable:

```
\paper {
  system-system-spacing #'basic-distance = #8
  score-system-spacing =
    #'((basic-distance . 12)
      (minimum-distance . 6)
      (padding . 1)
      (stretchability . 12))
}
```

## List of flexible vertical spacing \paper variables

The names of these variables follow the format *upper-lower-spacing*, where *upper* and *lower* are the items to be spaced. Each distance is measured between the reference points of the two items (see the description of the alist structure above). Note that in these variable names, the term ‘markup’ refers to both *title markups* (`bookTitleMarkup` or `scoreTitleMarkup`) and *top-level markups* (see [Section 3.1.5 \[File structure\]](#), page 426). All distances are measured in staff-spaces.

Default settings are defined in ‘`ly/paper-defaults-init.ly`’.

**markup-system-spacing**  
the distance between a (title or top-level) markup and the system that follows it.

**score-markup-spacing**  
the distance between the last system of a score and the (title or top-level) markup that follows it.

**score-system-spacing**  
the distance between the last system of a score and the first system of the score that follows it, when no (title or top-level) markup exists between them.

**system-system-spacing**  
the distance between two systems in the same score.

**markup-markup-spacing**  
the distance between two (title or top-level) markups.

**last-bottom-spacing**  
the distance from the last system or top-level markup on a page to the bottom of the printable area (i.e. the top of the bottom margin).

**top-system-spacing**  
the distance from the top of the printable area (i.e. the bottom of the top margin) to the first system on a page, when there is no (title or top-level) markup between the two.

**top-markup-spacing**  
the distance from the top of the printable area (i.e. the bottom of the top margin) to the first (title or top-level) markup on a page, when there is no system between the two.

## See also

Notation Reference: [Section 4.4.1 \[Flexible vertical spacing within systems\]](#), page 488.

Installed Files: ‘`ly/paper-defaults-init.ly`’.

Snippets: [Section “Spacing” in Snippets](#).

### 4.1.5 Horizontal spacing `\paper` variables

**Note:** Some `\paper` dimensions are automatically scaled to the paper size, which may lead to unexpected behavior. See [\[Automatic scaling to paper size\]](#), page 470.

#### `\paper` variables for widths and margins

Default values (before scaling) that are not listed here are defined in `'ly/paper-defaults-init.ly'`.

##### `paper-width`

The width of the page, unset by default. While `paper-width` has no effect on the automatic scaling of some horizontal dimensions, it does influence the `line-width` variable. If both `paper-width` and `line-width` are set, then `left-margin` and `right-margin` will also be updated. Also see `check-consistency`.

##### `line-width`

The horizontal extent of the staff lines in unindented, non-ragged systems, equal to  $(\text{paper-width} - \text{left-margin} - \text{right-margin})$  when unset. If `line-width` is set, and both `left-margin` and `right-margin` are unset, then the margins will be updated to center the systems on the page automatically. Also see `check-consistency`. This variable can also be set in a `\layout` block.

##### `left-margin`

The margin between the left edge of the page and the start of the staff lines in unindented systems. If the paper size is modified, this dimension's default value is scaled accordingly. If `left-margin` is unset, and both `line-width` and `right-margin` are set, then `left-margin` is set to  $(\text{paper-width} - \text{line-width} - \text{right-margin})$ . If only `line-width` is set, then both margins are set to  $((\text{paper-width} - \text{line-width}) / 2)$ , and the systems are consequently centered on the page. Also see `check-consistency`.

##### `right-margin`

The margin between the right edge of the page and the end of the staff lines in non-ragged systems. If the paper size is modified, this dimension's default value is scaled accordingly. If `right-margin` is unset, and both `line-width` and `left-margin` are set, then `right-margin` is set to  $(\text{paper-width} - \text{line-width} - \text{left-margin})$ . If only `line-width` is set, then both margins are set to  $((\text{paper-width} - \text{line-width}) / 2)$ , and the systems are consequently centered on the page. Also see `check-consistency`.

##### `check-consistency`

If set to true, print a warning if `left-margin`, `line-width`, and `right-margin` do not exactly add up to `paper-width`, and replace each of these (except `paper-width`) with its default value (scaled to the paper size if necessary). If set to false, ignore any inconsistencies and allow systems to run off the edge of the page.

##### `ragged-right`

If set to true, systems will not fill the line width. Instead, systems end at their natural horizontal length. Default: `#t` for scores with only one system, and `#f` for scores with two or more systems. This variable can also be set in a `\layout` block.

##### `ragged-last`

If set to true, the last system in the score will not fill the line width. Instead the last system ends at its natural horizontal length. Default: `#f`. This variable can also be set in a `\layout` block.

## See also

Notation Reference: [\[Automatic scaling to paper size\]](#), page 470.

Installed Files: ‘ly/paper-defaults-init.ly’.

## Known issues and warnings

Explicitly defined paper-sizes will override any user-defined left or right margin settings.

### `\paper variables for two-sided mode`

Default values (before scaling) are defined in ‘ly/paper-defaults-init.ly’.

#### `two-sided`

If set to true, use `inner-margin`, `outer-margin` and `binding-offset` to determine margins depending on whether the page number is odd or even. This overrides `left-margin` and `right-margin`.

#### `inner-margin`

The margin all pages have at the inner side if they are part of a book. If the paper size is modified, this dimension’s default value is scaled accordingly. Works only with `two-sided` set to true.

#### `outer-margin`

The margin all pages have at the outer side if they are part of a book. If the paper size is modified, this dimension’s default value is scaled accordingly. Works only with `two-sided` set to true.

#### `binding-offset`

The amount `inner-margin` is increased to make sure nothing will be hidden by the binding. If the paper size is modified, this dimension’s default value is scaled accordingly. Works only with `two-sided` set to true.

## See also

Notation Reference: [\[Automatic scaling to paper size\]](#), page 470.

Installed Files: ‘ly/paper-defaults-init.ly’.

### `\paper variables for shifts and indents`

Default values (before scaling) that are not listed here are defined in ‘ly/paper-defaults-init.ly’.

#### `horizontal-shift`

The amount that all systems (including titles and system separators) are shifted to the right. Default: 0.0\mm.

#### `indent`

The level of indentation for the first system in a score. If the paper size is modified, this dimension’s default value is scaled accordingly. This variable can also be set in a `\layout` block.

#### `short-indent`

The level of indentation for all systems in a score besides the first system. If the paper size is modified, this dimension’s default value is scaled accordingly. This variable can also be set in a `\layout` block.

## See also

Notation Reference: [\[Automatic scaling to paper size\]](#), page 470.

Installed Files: ‘`ly/paper-defaults-init.ly`’.

Snippets: [Section “Spacing” in \*Snippets\*](#).

### 4.1.6 Other `\paper` variables

#### `\paper` variables for line breaking

##### `max-systems-per-page`

The maximum number of systems that will be placed on a page. This is currently supported only by the `ly:optimal-breaking` algorithm. Default: unset.

##### `min-systems-per-page`

The minimum number of systems that will be placed on a page. This may cause pages to be overfilled if it is made too large. This is currently supported only by the `ly:optimal-breaking` algorithm. Default: unset.

##### `systems-per-page`

The number of systems that should be placed on each page. This is currently supported only by the `ly:optimal-breaking` algorithm. Default: unset.

##### `system-count`

The number of systems to be used for a score. Default: unset. This variable can also be set in a `\layout` block.

## See also

Notation Reference: [Section 4.3.1 \[Line breaking\]](#), page 480.

#### `\paper` variables for page breaking

Default values not listed here are defined in ‘`ly/paper-defaults-init.ly`’

##### `blank-after-score-page-force`

The penalty for having a blank page after the end of one score and before the next. By default, this is smaller than `blank-page-force`, so that we prefer blank pages after scores to blank pages within a score.

##### `blank-last-page-force`

The penalty for ending the score on an odd-numbered page.

##### `blank-page-force`

The penalty for having a blank page in the middle of a score. This is not used by `ly:optimal-breaking` since it will never consider blank pages in the middle of a score.

##### `page-breaking`

The page-breaking algorithm to use. Choices are `ly:minimal-breaking`, `ly:page-turn-breaking`, and `ly:optimal-breaking`.

##### `page-breaking-system-system-spacing`

Tricks the page breaker into thinking that `system-system-spacing` is set to something different than it really is. For example, if `page-breaking-system-system-spacing #'padding` is set to something substantially larger than `system-system-spacing #'padding`, then the page-breaker will put fewer systems on each page. Default: unset.

##### `page-count`

The number of pages to be used for a score, unset by default.

## See also

Notation Reference: [Section 4.3.2 \[Page breaking\]](#), page 482, [Section 4.3.3 \[Optimal page breaking\]](#), page 483, [Section 4.3.4 \[Optimal page turning\]](#), page 483, [Section 4.3.5 \[Minimal page breaking\]](#), page 484.

Installed Files: ‘ly/paper-defaults-init.ly’.

## **\paper variables for page numbering**

Default values not listed here are defined in ‘ly/paper-defaults-init.ly’

### **auto-first-page-number**

The page breaking algorithm is affected by the first page number being odd or even. If set to true, the page breaking algorithm will decide whether to start with an odd or even number. This will result in the first page number remaining as is or being increased by one. Default: **#f**.

### **first-page-number**

The value of the page number on the first page.

### **print-first-page-number**

If set to true, a page number is printed on the first page.

### **print-page-number**

If set to false, page numbers are not printed.

## See also

Installed Files: ‘ly/paper-defaults-init.ly’.

## **Known issues and warnings**

Odd page numbers are always on the right. If you want the music to start on page 1 there must be a blank page on the back of the cover page so that page 1 is on the right hand side.

## **Miscellaneous \paper variables**

### **page-spacing-weight**

The relative importance of page (vertical) spacing and line (horizontal) spacing. High values will make page spacing more important. Default: 10.

### **print-all-headers**

If set to true, this will print all headers for each `\score` in the output. Normally only the `piece` and `opus` header variables are printed. Default: **#f**.

### **system-separator-markup**

A markup object that is inserted between systems, often used for orchestral scores. Default: unset. The `\slashSeparator` markup, defined in ‘ly/titling-init.ly’, is provided as a sensible default, for example:


```
#(set-default-paper-size "a8")

\book {
  \paper {
    system-separator-markup = \slashSeparator
  }
  \header {
    tagline = ##f
  }
}
```

```

\score {
  \relative c'' { c1 \break c1 \break c1 }
}

```



## See also

Installed Files: ‘ly/titling-init.ly’.

Snippets: [Section “Spacing” in \*Snippets\*](#).

## Known issues and warnings

The default page header puts the page number and the `instrument` field from the `\header` block on a line.

## 4.2 Score layout

This section discusses score layout options for the `\layout` block.

### 4.2.1 The `\layout` block

While the `\paper` block contains settings that relate to the page formatting of the whole document, the `\layout` block contains settings for score-specific layout. To set score layout options globally, enter them in a toplevel `\layout` block. To set layout options for an individual score, enter them in a `\layout` block inside the `\score` block, after the music. Settings that can appear in a `\layout` block include:

- the `layout-set-staff-size` scheme function,
- context modifications in `\context` blocks, and
- `\paper` variables that affect score layout.

The `layout-set-staff-size` function is discussed in the next section, [Section 4.2.2 \[Setting the staff size\]](#), page 479. Context modifications are discussed in a separate chapter; see [Section 5.1.4 \[Modifying context plug-ins\]](#), page 524 and [Section 5.1.5 \[Changing context default settings\]](#), page 526. The `\paper` variables that can appear in a `\layout` block are:

- `line-width`, `ragged-right` and `ragged-last` (see [\[Paper variables for widths and margins\]](#), page 474)
- `indent` and `short-indent` (see [\[Paper variables for shifts and indents\]](#), page 475)
- `system-count` (see [\[Paper variables for line breaking\]](#), page 476)

Here is an example `\layout` block:



```

\layout {
  indent = 2\cm
  \context {
    \StaffGroup
    \override StaffGrouper #'staff-staff-spacing #'basic-distance = #8
  }
  \context {
    \Voice
    \override TextScript #'padding = #1
    \override Glissando #'thickness = #3
  }
}

```

## See also

Notation Reference: [Section 5.1.5 \[Changing context default settings\]](#), page 526.

Snippets: [Section “Spacing” in \*Snippets\*](#).

### 4.2.2 Setting the staff size

The default **staff size** is set to 20 points. This may be changed in two ways:

To set the staff size globally for all scores in a file (or in a `book` block, to be precise), use `set-global-staff-size`.

```

#(set-global-staff-size 14)

```

This sets the global default size to 14pt staff height and scales all fonts accordingly.

To set the staff size individually for each score, use

```

\score{
  ...
  \layout {
    #(layout-set-staff-size 15)
  }
}

```

The Feta font provides musical symbols at eight different sizes. Each font is tuned for a different staff size: at a smaller size the font becomes heavier, to match the relatively heavier staff lines. The recommended font sizes are listed in the following table:

font name	staff height (pt)	staff height (mm)	use
feta11	11.22	3.9	pocket scores
feta13	12.60	4.4	
feta14	14.14	5.0	
feta16	15.87	5.6	
feta18	17.82	6.3	song books
feta20	20	7.0	standard parts
feta23	22.45	7.9	
feta26	25.2	8.9	

These fonts are available in any sizes. The context property `fontSize` and the layout property `staff-space` (in [Section “StaffSymbol” in \*Internals Reference\*](#)) can be used to tune the size for individual staves. The sizes of individual staves are relative to the global size.

## See also

Notation Reference: [\[Selecting notation font size\]](#), page 191.

Snippets: [Section “Spacing” in \*Snippets\*](#).

## Known issues and warnings

`layout-set-staff-size` does not change the distance between the staff lines.

## 4.3 Breaks

### 4.3.1 Line breaking

Line breaks are normally determined automatically. They are chosen so that lines look neither cramped nor loose, and consecutive lines have similar density.

To manually force a line break at a bar line, use the `\break` command:

```
c4 c c c | \break
c4 c c c |
```



By default, a `\break` in the middle of a measure is ignored, and a warning is printed. To force a line break in the middle of a measure, add an invisible bar line with `\bar ""`:

```
c4 c c
\bar "" \break
c |
c4 c c c |
```



A `\break` occurring at a bar line is also ignored if the previous measure ends in the middle of a note, such as when a tuplet begins and ends in different measures. To allow `\break` commands to work in these situations, remove the `Forbid_line_break_engraver` from the `Voice` context. Note that manually forced line breaks have to be added in parallel with the music:

```
\new Voice \with {
  \remove Forbid_line_break_engraver
} \relative c'' {
  <<
    { c2. \times 2/3 { c4 c c } c2. | }
    { s1 | \break s1 | }
  >>
```

}



Similarly, line breaks are normally forbidden when beams cross bar lines. This behavior can be changed by setting `\override Beam #'breakable = ##t`:

```
\override Beam #'breakable = ##t
c2. c8[ c | \break
c8 c] c2. |
```



The `\noBreak` command forbids a line break at the bar line where it is inserted.

The most basic settings influencing line spacing are `indent` and `line-width`. They are set in the `\layout` block. They control the indentation of the first line of music, and the lengths of the lines.

If `ragged-right` is set to true in the `\layout` block, then systems end at their natural horizontal length, instead of being spread horizontally to fill the whole line. This is useful for short fragments, and for checking how tight the natural spacing is.

The option `ragged-last` is similar to `ragged-right`, but affects only the last line of the piece.

```
\layout {
  indent = 0\mm
  line-width = 150\mm
  ragged-last = ##t
}
```

For line breaks at regular intervals use `\break` separated by skips and repeated with `\repeat`. For example, this would cause the following 28 measures (assuming 4/4 time) to be broken every 4 measures, and only there:

```
<<
\repeat unfold 7 {
  s1 \noBreak s1 \noBreak
  s1 \noBreak s1 \break
}
{ the actual music... }
>>
```

A linebreaking configuration can be saved as a `.ly` file automatically. This allows vertical alignments to be stretched to fit pages in a second formatting run. This is fairly new and complicated. More details are available in [Section “Spacing” in \*Snippets\*](#).

## Predefined commands

`\break`, `\noBreak`.

## See also

Notation Reference: [`\paper variables for line breaking`], page 476.

Snippets: Section “Spacing” in *Snippets*.

Internals Reference: Section “`LineBreakEvent`” in *Internals Reference*.

### 4.3.2 Page breaking

The default page breaking may be overridden by inserting `\pageBreak` or `\noPageBreak` commands. These commands are analogous to `\break` and `\noBreak`. They should be inserted at a bar line. These commands force and forbid a page-break from happening. Of course, the `\pageBreak` command also forces a line break.

The `\pageBreak` and `\noPageBreak` commands may also be inserted at top-level, between scores and top-level markups.

There are also analogous settings to `ragged-right` and `ragged-last` which have the same effect on vertical spacing: `ragged-bottom` and `ragged-last-bottom`. If set to `#t` the systems on all pages or just the last page respectively will not be justified vertically. See Section 4.1.3 [`Fixed vertical spacing \paper variables`], page 471.

Page breaks are computed by the `page-breaking` function. LilyPond provides three algorithms for computing page breaks, `ly:optimal-breaking`, `ly:page-turn-breaking` and `ly:minimal-breaking`. The default is `ly:optimal-breaking`, but the value can be changed in the `\paper` block:

```
\paper {
  page-breaking = #ly:page-turn-breaking
}
```

When a book has many scores and pages, the page breaking problem may be difficult to solve, requiring large processing time and memory. To ease the page breaking process, `\bookpart` blocks are used to divide the book into several parts: the page breaking occurs separately on each part. Different page breaking functions may also be used in different book parts.

```
\bookpart {
  \header {
    subtitle = "Preface"
  }
  \paper {
    %% In a part consisting mostly of text,
    %% ly:minimal-breaking may be preferred
    page-breaking = #ly:minimal-breaking
  }
  \markup { ... }
  ...
}
\bookpart {
  %% In this part, consisting of music, the default optimal
  %% page breaking function is used.
  \header {
    subtitle = "First movement"
  }
  \score { ... }
```

```
...
}
```

## Predefined commands

`\pageBreak`, `\noPageBreak`.

## See also

Notation Reference: [\[\paper variables for page breaking\]](#), page 476.

Snippets: [Section “Spacing” in \*Snippets\*](#).

### 4.3.3 Optimal page breaking

The `ly:optimal-breaking` function is LilyPond’s default method of determining page breaks. It attempts to find a page breaking that minimizes cramping and stretching, both horizontally and vertically. Unlike `ly:page-turn-breaking`, it has no concept of page turns.

## See also

Snippets: [Section “Spacing” in \*Snippets\*](#).

### 4.3.4 Optimal page turning

Often it is necessary to find a page breaking configuration so that there is a rest at the end of every second page. This way, the musician can turn the page without having to miss notes. The `ly:page-turn-breaking` function attempts to find a page breaking minimizing cramping and stretching, but with the additional restriction that it is only allowed to introduce page turns in specified places.

There are two steps to using this page breaking function. First, you must enable it in the `\paper` block, as explained in [Section 4.3.2 \[Page breaking\]](#), page 482. Then you must tell the function where you would like to allow page breaks.

There are two ways to achieve the second step. First, you can specify each potential page turn manually, by inserting `\allowPageTurn` into your input file at the appropriate places.

If this is too tedious, you can add a `Page_turn_engraver` to a `Staff` or `Voice` context. The `Page_turn_engraver` will scan the context for sections without notes (note that it does not scan for rests; it scans for the absence of notes. This is so that single-staff polyphony with rests in one of the parts does not throw off the `Page_turn_engraver`). When it finds a sufficiently long section without notes, the `Page_turn_engraver` will insert an `\allowPageTurn` at the final bar line in that section, unless there is a ‘special’ bar line (such as a double bar), in which case the `\allowPageTurn` will be inserted at the final ‘special’ bar line in the section.

The `Page_turn_engraver` reads the context property `minimumPageTurnLength` to determine how long a note-free section must be before a page turn is considered. The default value for `minimumPageTurnLength` is `(ly:make-moment 1 1)`. If you want to disable page turns, you can set it to something very large.

```
\new Staff \with { \consists "Page_turn_engraver" }
{
  a4 b c d |
  R1 | % a page turn will be allowed here
  a4 b c d |
  \set Staff.minimumPageTurnLength = #(ly:make-moment 5 2)
  R1 | % a page turn will not be allowed here
  a4 b r2 |
  R1*2 | % a page turn will be allowed here
  a1
}
```

```
}
```

The `Page_turn_engraver` detects volta repeats. It will only allow a page turn during the repeat if there is enough time at the beginning and end of the repeat to turn the page back. The `Page_turn_engraver` can also disable page turns if the repeat is very short. If you set the context property `minimumRepeatLengthForPageTurn` then the `Page_turn_engraver` will only allow turns in repeats whose duration is longer than this value.

The page turning commands, `\pageTurn`, `\noPageTurn` and `\allowPageTurn`, may also be used at top-level, between scores and top-level markups.

## Predefined commands

`\pageTurn`, `\noPageTurn`, `\allowPageTurn`.

## See also

Snippets: [Section “Spacing” in \*Snippets\*](#).

## Known issues and warnings

There should only be one `Page_turn_engraver` in a score. If there is more than one, they will interfere with each other.

### 4.3.5 Minimal page breaking

The `ly:minimal-breaking` function performs minimal computations to calculate the page breaking: it fills a page with as many systems as possible before moving to the next one. Thus, it may be preferred for scores with many pages, where the other page breaking functions could be too slow or memory demanding, or a lot of texts. It is enabled using:

```
\paper {
  page-breaking = #ly:minimal-breaking
}
```

## See also

Snippets: [Section “Spacing” in \*Snippets\*](#).

### 4.3.6 Explicit breaks

Lily sometimes rejects explicit `\break` and `\pageBreak` commands. There are two commands to override this behavior:

```
\override NonMusicalPaperColumn #'line-break-permission = ##f
\override NonMusicalPaperColumn #'page-break-permission = ##f
```

When `line-break-permission` is overridden to false, Lily will insert line breaks at explicit `\break` commands and nowhere else. When `page-break-permission` is overridden to false, Lily will insert page breaks at explicit `\pageBreak` commands and nowhere else.

```
\paper {
  indent = #0
  ragged-right = ##t
  ragged-bottom = ##t
}
```

```
music = \relative c'' { c8 c c c }
```

```
\score {
  \new Staff {
    \repeat unfold 2 { \music } \break
```

```

\repeat unfold 4 { \music } \break
\repeat unfold 6 { \music } \break
\repeat unfold 8 { \music } \pageBreak
\repeat unfold 8 { \music } \break
\repeat unfold 6 { \music } \break
\repeat unfold 4 { \music } \break
\repeat unfold 2 { \music }
}
\layout {
  \context {
    \Score
    \override NonMusicalPaperColumn #'line-break-permission = ##f
    \override NonMusicalPaperColumn #'page-break-permission = ##f
  }
}

```

The musical score consists of 20 measures of music, organized into eight staves. The first staff contains measures 1 through 4. The second staff contains measures 5 through 8. The third staff contains measures 9 through 12. The fourth staff contains measures 13 through 16. The fifth staff contains measures 17 through 20. The sixth staff contains measures 21 through 24. The seventh staff contains measures 25 through 28. The eighth staff contains measures 29 through 32. The music is written in a single system, with line and page breaks indicated by repeat unfold commands.

## See also

Snippets: [Section “Spacing” in \*Snippets\*](#).

### 4.3.7 Using an extra voice for breaks

Line- and page-breaking information usually appears within note entry directly.

```
music = \relative c'' { c4 c c c }
```

```
\score {
  \new Staff {
    \repeat unfold 2 { \music } \break
    \repeat unfold 3 { \music }
  }
}
```

This makes `\break` and `\pageBreak` commands easy to enter but mixes music entry with information that specifies how music should lay out on the page. You can keep music entry and line- and page-breaking information in two separate places by introducing an extra voice to contain the breaks. This extra voice contains only skips together with `\break`, `\pageBreak` and other breaking layout information.

```
music = \relative c'' { c4 c c c }
```

```
\score {
  \new Staff <<
    \new Voice {
      s1 * 2 \break
      s1 * 3 \break
      s1 * 6 \break
      s1 * 5 \break
    }
    \new Voice {
      \repeat unfold 2 { \music }
      \repeat unfold 3 { \music }
      \repeat unfold 6 { \music }
      \repeat unfold 5 { \music }
    }
  >>
}
```







This pattern becomes especially helpful when overriding `line-break-system-details` and the other useful but long properties of `NonMusicalPaperColumnGrob`, as explained in [Section 4.4 \[Vertical spacing\]](#), page 488.


```
music = \relative c'' { c4 c c c }
```

```
\score {
  \new Staff <<
    \new Voice {
      \overrideProperty "Score.NonMusicalPaperColumn"
        #'line-break-system-details #'((Y-offset . 0))
      s1 * 2 \break

      \overrideProperty "Score.NonMusicalPaperColumn"
        #'line-break-system-details #'((Y-offset . 35))
      s1 * 3 \break

      \overrideProperty "Score.NonMusicalPaperColumn"
        #'line-break-system-details #'((Y-offset . 70))
      s1 * 6 \break

      \overrideProperty "Score.NonMusicalPaperColumn"
        #'line-break-system-details #'((Y-offset . 105))
      s1 * 5 \break
    }
    \new Voice {
      \repeat unfold 2 { \music }
      \repeat unfold 3 { \music }
      \repeat unfold 6 { \music }
      \repeat unfold 5 { \music }
    }
  >>
}
```



## See also

Notation Reference: [Section 4.4 \[Vertical spacing\]](#), page 488.

Snippets: [Section “Spacing” in \*Snippets\*](#).

## 4.4 Vertical spacing

Vertical spacing is controlled by three things: the amount of space available (i.e., paper size and margins), the amount of space between systems, and the amount of space between staves inside a system.

### 4.4.1 Flexible vertical spacing within systems

Three separate mechanisms control the flexible vertical spacing within systems, one for each of the following categories:

- *ungrouped staves*,
- *grouped staves* (staves within a staff-group such as `ChoirStaff`, etc.), and
- *non-staff lines* (such as `Lyrics`, `ChordNames`, etc.).

The height of each system is determined in two steps. First, all of the staves are spaced according to the amount of space available. Then, the non-staff lines are distributed between the staves.

Note that the spacing mechanisms discussed in this section only control the vertical spacing of staves and non-staff lines within individual systems. The vertical spacing between separate systems, scores, markups, and margins is controlled by `\paper` variables, which are discussed in [Section 4.1.4 \[Flexible vertical spacing `\paper` variables\]](#), page 472.

### Within-system spacing properties


The within-system vertical spacing mechanisms are controlled by two sets of grob properties. The first set is associated with the `VerticalAxisGroup` grob, which is created by all staves and non-staff lines. The second set is associated with the `StaffGrouper` grob, which can be created by staff-groups, but only if explicitly called. These properties are described individually at the end of this section.

The names of these properties (except for `staff-affinity`) follow the format `item1-item2-spacing`, where `item1` and `item2` are the items to be spaced. Note that `item2` is not necessarily below `item1`; for example, `nonstaff-relatedstaff-spacing` will measure upwards from the non-staff line if `staff-affinity` is UP.

Each distance is measured between the *reference points* of the two items. The reference point for a staff is the vertical center of its `StaffSymbol` (i.e. the middle line if `line-count` is odd; the middle space if `line-count` is even). The reference points for individual non-staff lines are given in the following table:

Non-staff line	Reference point
<code>ChordNames</code>	baseline
<code>NoteNames</code>	baseline
<code>Lyrics</code>	baseline
<code>Dynamics</code>	vertical center
<code>FiguredBass</code>	highest point
<code>FretBoards</code>	top line

In the following image, horizontal lines indicate the positions of these reference points:



Each of the vertical spacing grob properties (except `staff-affinity`) uses the same alist structure as the `\paper` spacing variables discussed in [Section 4.1.4 \[Flexible vertical spacing \paper variables\]](#), page 472. Specific methods for modifying alists are discussed in [Section 5.3.6 \[Modifying alists\]](#), page 540. Grob properties should be adjusted with an `\override` inside a `\score` or `\layout` block, and not inside a `\paper` block.

The following example demonstrates the two ways these alists can be modified. The first declaration updates one key-value individually, and the second completely re-defines the property:

```
\new Staff \with {
  \override VerticalAxisGroup #'default-staff-staff-spacing
    #'basic-distance = #10
} { ... }

\new Staff \with {
  \override VerticalAxisGroup #'default-staff-staff-spacing =
    #'((basic-distance . 10)
      (minimum-distance . 9)
      (padding . 1)
      (stretchability . 10))
} { ... }
```

To change any spacing settings globally, put them in the `\layout` block:

```
\layout {
  \context {
    \Staff
    \override VerticalAxisGroup #'default-staff-staff-spacing
      #'basic-distance = #10
  }
}
```

Standard settings for the vertical spacing grob properties are listed in [Section “VerticalAxisGroup” in \*Internals Reference\*](#) and [Section “StaffGrouper” in \*Internals Reference\*](#). Default overrides for specific types of non-staff lines are listed in the relevant context descriptions in [Section “Contexts” in \*Internals Reference\*](#).

## Properties of the `VerticalAxisGroup` `grob`

`VerticalAxisGroup` properties are typically adjusted with an `\override` at the `Staff` level (or equivalent).

### `staff-staff-spacing`

Used to determine the distance between the current staff and the staff just below it in the same system, even if one or more non-staff lines (such as `Lyrics`) are placed between the two staves. Does not apply to the bottom staff of a system.

Initially, the `staff-staff-spacing` of a `VerticalAxisGroup` is a Scheme function that applies the properties of the `StaffGrouper` if the staff is part of a group, or the `default-staff-staff-spacing` of the staff otherwise. This allows staves to be spaced differently when they are grouped. For uniform spacing regardless of grouping, this function may be replaced by a flexible-spacing alist, using the complete-redefinition form of override shown above.

### `default-staff-staff-spacing`

A flexible-spacing alist defining the `staff-staff-spacing` used for ungrouped staves, unless `staff-staff-spacing` has been explicitly set with an `\override`.

### `staff-affinity`

The direction of the staff to use for spacing the current non-staff line. Choices are `UP`, `DOWN`, and `CENTER`. If `CENTER`, the non-staff line will be placed equidistant between the two nearest staves on either side, unless collisions or other spacing constraints prevent this. Adjacent non-staff lines should have non-increasing `staff-affinity` from top to bottom, e.g. a non-staff line set to `UP` should not immediately follow one that is set to `DOWN`. Non-staff lines at the top of a system should use `DOWN`; those at the bottom should use `UP`. Setting `staff-affinity` for a staff causes it to be treated as a non-staff line. Setting `staff-affinity` to `#f` causes a non-staff line to be treated as a staff. Setting `staff-affinity` to `UP`, `CENTER`, or `DOWN` causes a staff to be spaced as a non-staff line.

### `nonstaff-relatedstaff-spacing`

The distance between the current non-staff line and the nearest staff in the direction of `staff-affinity`, if there are no non-staff lines between the two, and `staff-affinity` is either `UP` or `DOWN`. If `staff-affinity` is `CENTER`, then `nonstaff-relatedstaff-spacing` is used for the nearest staves on *both* sides, even if other non-staff lines appear between the current one and either of the staves. This means that the placement of a non-staff line depends on both the surrounding staves and the surrounding non-staff lines. Setting the `stretchability` of one of these types of spacing to a small value will make that spacing dominate. Setting the `stretchability` to a large value will make that spacing have little effect.

### `nonstaff-nonstaff-spacing`

The distance between the current non-staff line and the next non-staff line in the direction of `staff-affinity`, if both are on the same side of the related staff, and `staff-affinity` is either `UP` or `DOWN`.

### `nonstaff-unrelatedstaff-spacing`

The distance between the current non-staff line and the staff in the opposite direction from `staff-affinity`, if there are no other non-staff lines between the two, and `staff-affinity` is either `UP` or `DOWN`. This can be used, for example, to require a minimum amount of padding between a `Lyrics` line and the staff to which it does not belong.

## Properties of the StaffGrouper grob

StaffGrouper properties are typically adjusted with an `\override` at the `StaffGroup` level (or equivalent).

### staff-staff-spacing

The distance between consecutive staves within the current staff-group. The `staff-staff-spacing` property of an individual staff's `VerticalAxisGroup` grob can be overridden with different spacing settings for that staff.

### staffgroup-staff-spacing

The distance between the last staff of the current staff-group and the staff just below it in the same system, even if one or more non-staff lines (such as `Lyrics`) exist between the two staves. Does not apply to the bottom staff of a system. The `staff-staff-spacing` property of an individual staff's `VerticalAxisGroup` grob can be overridden with different spacing settings for that staff.

## See also

Notation Reference: [Section 4.1.4 \[Flexible vertical spacing \paper variables\]](#), page 472, [Section 5.3.6 \[Modifying alists\]](#), page 540.

Internals Reference: [Section “Contexts” in Internals Reference](#), [Section “VerticalAxisGroup” in Internals Reference](#), [Section “StaffGrouper” in Internals Reference](#).

Installed Files: `'ly/engraver-init.ly'`, `'scm/define-grobs.scm'`.

## Spacing of ungrouped staves

*Staves* (such as `Staff`, `DrumStaff`, `TabStaff`, etc.) are contexts that can contain one or more voice contexts, but cannot contain any other staves.

The following properties affect the spacing of *ungrouped* staves:

- `VerticalAxisGroup` properties:
  - `default-staff-staff-spacing`
  - `staff-staff-spacing`

These grob properties are described individually above; see [\[Within-system spacing properties\]](#), page 488.

Additional properties are involved for staves that are part of a staff-group; see [\[Spacing of grouped staves\]](#), page 492.

The following example shows how the `default-staff-staff-spacing` property can affect the spacing of ungrouped staves. The same overrides applied to `staff-staff-spacing` would have the same effect, but would also apply in cases where the staves are combined in a group or groups.

```
\layout {
  \context {
    \Staff
    \override VerticalAxisGroup #'default-staff-staff-spacing =
      #'((basic-distance . 8)
         (minimum-distance . 7)
         (padding . 1))
  }
}

<<
% The very low note here needs more room than 'basic-distance
```

```
% can provide, so the distance between this staff and the next
% is determined by 'padding.
\new Staff { b,2 r | }

% Here, 'basic-distance provides enough room, and there is no
% need to compress the space (towards 'minimum-distance) to make
% room for anything else on the page, so the distance between
% this staff and the next is determined by 'basic-distance.
\new Staff { \clef bass g2 r | }

% By setting 'padding to a negative value, staves can be made to
% collide. The lowest acceptable value for 'basic-distance is 0.
\new Staff \with {
  \override VerticalAxisGroup #'default-staff-staff-spacing =
    #'((basic-distance . 3.5)
      (padding . -10))
} { \clef bass g2 r | }
\new Staff { \clef bass g2 r | }
>>
```



## See also

Installed Files: `'scm/define-grobs.scm'`.

Snippets: [Section “Spacing” in \*Snippets\*](#).

Internals Reference: [Section “VerticalAxisGroup” in \*Internals Reference\*](#).

## Spacing of grouped staves

In orchestral and other large scores, it is common to place staves in groups. The space between groups is typically larger than the space between staves of the same group.

*Staff-groups* (such as `StaffGroup`, `ChoirStaff`, etc.) are contexts that can contain one or more staves simultaneously.

The following properties affect the spacing of staves inside staff-groups:

- `VerticalAxisGroup` properties:
  - `staff-staff-spacing`
- `StaffGrouper` properties:
  - `staff-staff-spacing`
  - `staffgroup-staff-spacing`

These grob properties are described individually above; see [\[Within-system spacing properties\]](#), page 488.

The following example shows how properties of the `StaffGrouper` grob can affect the spacing of grouped staves:


```

\layout {
  \context {
    \Score
    \override StaffGrouper #'staff-staff-spacing #'padding = #0
    \override StaffGrouper #'staff-staff-spacing #'basic-distance = #1
  }
}

<<
  \new PianoStaff \with {
    \override StaffGrouper #'staffgroup-staff-spacing #'basic-distance = #20
  } <<
    \new Staff { c'1 }
    \new Staff { c'1 }
  >>

  \new StaffGroup <<
    \new Staff { c'1 }
    \new Staff { c'1 }
  >>
>>

```



## See also

Installed Files: ‘`scm/define-grobs.scm`’.

Snippets: [Section “Spacing” in \*Snippets\*](#).

Internals Reference: [Section “VerticalAxisGroup” in \*Internals Reference\*](#), [Section “StaffGrouper” in \*Internals Reference\*](#).

## Spacing of non-staff lines

*Non-staff lines* (such as Lyrics, ChordNames, etc.) are contexts whose layout objects are engraved like staves (i.e. in horizontal lines within systems). Specifically, non-staff lines are non-staff contexts that create the `VerticalAxisGroup` layout object.

The following properties affect the spacing of non-staff lines:

- `VerticalAxisGroup` properties:
  - `staff-affinity`
  - `nonstaff-relatedstaff-spacing`


- `nonstaff-nonstaff-spacing`
- `nonstaff-unrelatedstaff-spacing`

These grob properties are described individually above; see [\[Within-system spacing properties\]](#), page 488.

The following example shows how the `nonstaff-nonstaff-spacing` property can affect the spacing of consecutive non-staff lines. Here, by setting the `stretchability` key to a very high value, the lyrics are able to stretch much more than usual:

```
\layout {
  \context {
    \Lyrics
    \override VerticalAxisGroup
      #'nonstaff-nonstaff-spacing #'stretchability = #1000
  }
}

\new StaffGroup
<<
  \new Staff \with {
    \override VerticalAxisGroup #'staff-staff-spacing = #'((basic-distance . 30))
  } { c'1 }
  \new Lyrics \with {
    \override VerticalAxisGroup #'staff-affinity = #UP
  } \lyricmode { up }
  \new Lyrics \with {
    \override VerticalAxisGroup #'staff-affinity = #CENTER
  } \lyricmode { center }
  \new Lyrics \with {
    \override VerticalAxisGroup #'staff-affinity = #DOWN
  } \lyricmode { down }
  \new Staff { c'1 }
>>
```



## See also

Installed Files: `'ly/engraver-init.ly'`, `'scm/define-grobs.scm'`.

Snippets: [Section “Spacing” in \*Snippets\*](#).

Internals Reference: [Section “Contexts” in \*Internals Reference\*](#), [Section “VerticalAxisGroup” in \*Internals Reference\*](#).



### 4.4.2 Explicit staff and system positioning

One way to understand the flexible vertical spacing mechanisms explained above is as a collection of settings that control the amount of vertical padding between staves and systems.

It is possible to approach vertical spacing in a different way using `NonMusicalPaperColumn #'line-break-system-details`. While the flexible vertical spacing mechanisms specify vertical padding, `NonMusicalPaperColumn #'line-break-system-details` can specify exact vertical positions on the page.

`NonMusicalPaperColumn #'line-break-system-details` accepts an associative list of three different settings:

- `X-offset`
- `Y-offset`
- `alignment-distances`

Grob overrides, including the overrides for `NonMusicalPaperColumn` below, can occur in any of three different places in an input file:

- in the middle of note entry directly
- in a `\context` block
- in the `\with` block

When we override `NonMusicalPaperColumn`, we use the usual `\override` command in `\context` blocks and in the `\with` block. On the other hand, when we override `NonMusicalPaperColumn` in the middle of note entry, use the special `\overrideProperty` command. Here are some example `NonMusicalPaperColumn` overrides with the special `\overrideProperty` command:

```
\overrideProperty NonMusicalPaperColumn
  #'line-break-system-details #'((X-offset . 20))

\overrideProperty NonMusicalPaperColumn
  #'line-break-system-details #'((Y-offset . 40))

\overrideProperty NonMusicalPaperColumn
  #'line-break-system-details #'((X-offset . 20)
                                (Y-offset . 40))

\overrideProperty NonMusicalPaperColumn
  #'line-break-system-details #'((alignment-distances . (15)))

\overrideProperty NonMusicalPaperColumn
  #'line-break-system-details #'((X-offset . 20)
                                (Y-offset . 40)
                                (alignment-distances . (15)))
```

To understand how each of these different settings work, we begin by looking at an example that includes no overrides at all.

```
\header { tagline = ##f }
\paper { left-margin = 0\mm }
\book {
  \score {
    <<
    \new Staff <<
    \new Voice {
```

```

        s1*5 \break
        s1*5 \break
        s1*5 \break
    }
    \new Voice { \repeat unfold 15 { c'4 c' c' c' } }
>>
\new Staff {
    \repeat unfold 15 { d'4 d' d' d' }
}
>>
}
}

```

This score isolates line- and page-breaking information in a dedicated voice. This technique of creating a breaks voice will help keep layout separate from music entry as our example becomes more complicated. See [Section 4.3.7 \[Using an extra voice for breaks\]](#), page 486.

Explicit `\breaks` evenly divide the music into six measures per line. Vertical spacing results from LilyPond's defaults. To set the vertical startpoint of each system explicitly, we can set the `Y-offset` pair in the `line-break-system-details` attribute of the `NonMusicalPaperColumn` grob:

```


\header { tagline = ##f }
\paper { left-margin = 0\mm }
\book {
  \score {
    <<
    \new Staff <<
    \new Voice {
      \overrideProperty #"Score.NonMusicalPaperColumn"
        #'line-break-system-details #'((Y-offset . 0))
      s1*5 \break
      \overrideProperty #"Score.NonMusicalPaperColumn"
        #'line-break-system-details #'((Y-offset . 40))
    }
  }
}

```

```

s1*5 \break
\overrideProperty #"Score.NonMusicalPaperColumn"
  #'line-break-system-details #'((Y-offset . 80))
s1*5 \break
}
\new Voice { \repeat unfold 15 { c'4 c' c' c' } }
>>
\new Staff {
  \repeat unfold 15 { d'4 d' d' d' }
}
>>
}
}

```



Note that `line-break-system-details` takes an associative list of potentially many values, but that we set only one value here. Note, too, that the `Y-offset` property here determines the exact vertical position on the page at which each new system will render.

Now that we have set the vertical startpoint of each system explicitly, we can also set the vertical distances between staves within each system manually. We do this using the `alignment-distances` subproperty of `line-break-system-details`.

```
\header { tagline = ##f }
```

```

\paper { left-margin = 0\mm }
\book {
  \score {
    <<
      \new Staff <<
        \new Voice {
          \overrideProperty #"Score.NonMusicalPaperColumn"
            #'line-break-system-details #'((Y-offset . 20)
              (alignment-distances . (15)))

          s1*5 \break
          \overrideProperty #"Score.NonMusicalPaperColumn"
            #'line-break-system-details #'((Y-offset . 60)
              (alignment-distances . (15)))

          s1*5 \break
          \overrideProperty #"Score.NonMusicalPaperColumn"
            #'line-break-system-details #'((Y-offset . 100)
              (alignment-distances . (15)))

          s1*5 \break
        }
        \new Voice { \repeat unfold 15 { c'4 c' c' c' } }
      >>
      \new Staff {
        \repeat unfold 15 { d'4 d' d' d' }
      }
    >>
  }
}

```



Note that here we assign two different values to the `line-break-system-details` attribute of the `NonMusicalPaperColumn` grob. Though the `line-break-system-details` attribute alist accepts many additional spacing parameters (including, for example, a corresponding `X-offset` pair), we need only set the `Y-offset` and `alignment-distances` pairs to control the vertical startpoint of every system and every staff. Finally, note that `alignment-distances` specifies the vertical positioning of staves but not of staff groups.

```
\header { tagline = ##f }
\paper { left-margin = 0\mm }
\book {
  \score {
    <<
      \new Staff <<
        \new Voice {
          \overrideProperty #"Score.NonMusicalPaperColumn"
            #'line-break-system-details #'((Y-offset . 0)
                                           (alignment-distances . (30 10)))
        }
      }
    }
  }
```

```

s1*5 \break
\overrideProperty #"Score.NonMusicalPaperColumn"
  #'line-break-system-details #'((Y-offset . 60)
                                (alignment-distances . (10 10)))

s1*5 \break
\overrideProperty #"Score.NonMusicalPaperColumn"
  #'line-break-system-details #'((Y-offset . 100)
                                (alignment-distances . (10 30)))

s1*5 \break
}
\new Voice { \repeat unfold 15 { c'4 c' c' c' } }
>>
\new StaffGroup <<
  \new Staff { \repeat unfold 15 { d'4 d' d' d' } }
  \new Staff { \repeat unfold 15 { e'4 e' e' e' } }
>>
>>
}
}

```

The image displays three systems of musical notation, each consisting of a single staff and a grand staff (treble and bass staves). The first system shows a single staff above a grand staff. The second system shows a single staff above a grand staff, with a measure number '6' at the start. The third system shows a single staff above a grand staff, with a measure number '11' at the start. The grand staff in the third system has empty staves, indicating a spacing issue.

Some points to consider:

- When using `alignment-distances`, lyrics and other non-staff lines do not count as a staff.
- The units of the numbers passed to `X-offset`, `Y-offset` and `alignment-distances` are interpreted as multiples of the distance between adjacent staff lines. Positive values move staves and lyrics up, negative values move staves and lyrics down.
- Because the `NonMusicalPaperColumn #'line-break-system-details` settings given here allow the positioning of staves and systems anywhere on the page, it is possible to violate

paper or margin boundaries or even to print staves or systems on top of one another. Reasonable values passed to these different settings will avoid this.

## See also

Snippets: [Section “Spacing” in \*Snippets\*](#).

### 4.4.3 Vertical collision avoidance

Intuitively, there are some objects in musical notation that belong to the staff and there are other objects that should be placed outside the staff. Objects belonging outside the staff include things such as rehearsal marks, text and dynamic markings (from now on, these will be called outside-staff objects). LilyPond’s rule for the vertical placement of outside-staff objects is to place them as close to the staff as possible but not so close that they collide with another object.

LilyPond uses the `outside-staff-priority` property to determine whether a grob is an outside-staff object: if `outside-staff-priority` is a number, the grob is an outside-staff object. In addition, `outside-staff-priority` tells LilyPond in which order the objects should be placed.

First, LilyPond places all the objects that do not belong outside the staff. Then it sorts the outside-staff objects according to their `outside-staff-priority` (in increasing order). One by one, LilyPond takes the outside-staff objects and places them so that they do not collide with any objects that have already been placed. That is, if two outside-staff grobs are competing for the same space, the one with the lower `outside-staff-priority` will be placed closer to the staff.


```
c4_"Text"\pp
r2.
\once \override TextScript #'outside-staff-priority = #1
c4_"Text"\pp % this time the text will be closer to the staff
r2.
% by setting outside-staff-priority to a non-number,
% we disable the automatic collision avoidance
\once \override TextScript #'outside-staff-priority = ##f
\once \override DynamicLineSpanner #'outside-staff-priority = ##f
c4_"Text"\pp % now they will collide
```



The vertical padding between an outside-staff object and the previously-positioned grobs can be controlled with `outside-staff-padding`.

```
\once \override TextScript #'outside-staff-padding = #0
a'^"This text is placed very close to the note"
\once \override TextScript #'outside-staff-padding = #3
c^"This text is padded away from the previous text"
c^"This text is placed close to the previous text"
```





By default, outside-staff objects are placed only to avoid a horizontal collision with previously-positioned grobs. This can lead to situations in which objects are placed very close to each other horizontally. The vertical spacing between staves can also be set so that outside staff objects are interleaved. Setting `outside-staff-horizontal-padding` causes an object to be offset vertically so that such a situation doesn't occur.

```
% the markup is too close to the following note
c4~"Text"
c4
c''2
% setting outside-staff-horizontal-padding fixes this
R1
\once \override TextScript #'outside-staff-horizontal-padding = #1
c,,4~"Text"
c4
c''2
```



See also

Snippets: [Section “Spacing” in \*Snippets\*](#).

## 4.5 Horizontal spacing

### 4.5.1 Horizontal spacing overview

The spacing engine translates differences in durations into stretchable distances (‘springs’) of differing lengths. Longer durations get more space, shorter durations get less. The shortest durations get a fixed amount of space (which is controlled by `shortest-duration-space` in the [Section “SpacingSpanner” in \*Internals Reference\*](#) object). The longer the duration, the more space it gets: doubling a duration adds a fixed amount (this amount is controlled by `spacing-increment`) of space to the note.

For example, the following piece contains lots of half, quarter, and 8th notes; the eighth note is followed by 1 note head width (NHW). The quarter note is followed by 2 NHW, the half by 3 NHW, etc.

```
c2 c4. c8 c4. c8 c4. c8 c8
c8 c4 c4 c4
```



Normally, `spacing-increment` is set to 1.2 staff space, which is approximately the width of a note head, and `shortest-duration-space` is set to 2.0, meaning that the shortest note gets

2.4 staff space (2.0 times the `spacing-increment`) of horizontal space. This space is counted from the left edge of the symbol, so the shortest notes are generally followed by one NHW of space.

If one would follow the above procedure exactly, then adding a single 32nd note to a score that uses 8th and 16th notes, would widen up the entire score a lot. The shortest note is no longer a 16th, but a 32nd, thus adding 1 NHW to every note. To prevent this, the shortest duration for spacing is not the shortest note in the score, but rather the one which occurs most frequently.

The most common shortest duration is determined as follows: in every measure, the shortest duration is determined. The most common shortest duration is taken as the basis for the spacing, with the stipulation that this shortest duration should always be equal to or shorter than an 8th note. The shortest duration is printed when you run `lilypond` with the ‘`--verbose`’ option.

These durations may also be customized. If you set the `common-shortest-duration` in Section “`SpacingSpanner`” in *Internals Reference*, then this sets the base duration for spacing. The maximum duration for this base (normally an 8th), is set through `base-shortest-duration`.

Notes that are even shorter than the common shortest note are followed by a space that is proportional to their duration relative to the common shortest note. So if we were to add only a few 16th notes to the example above, they would be followed by half a NHW:

```
c2 c4. c8 c4. c16[ c] c4. c8 c8 c8 c4 c4 c4
```



In the *Essay on automated music engraving*, it was explained that stem directions influence spacing (see Section “`Optical spacing`” in *Essay*). This is controlled with the `stem-spacing-correction` property in the Section “`NoteSpacing`” in *Internals Reference*, object. These are generated for every Section “`Voice`” in *Internals Reference* context. The `StaffSpacing` object (generated in Section “`Staff`” in *Internals Reference* context) contains the same property for controlling the stem/bar line spacing. The following example shows these corrections, once with default settings, and once with exaggerated corrections:



Proportional notation is supported; see Section 4.5.5 [Proportional notation], page 508.

## See also

Snippets: Section “`Spacing`” in *Snippets*.

Internals Reference: Section “`SpacingSpanner`” in *Internals Reference*, Section “`NoteSpacing`” in *Internals Reference*, Section “`StaffSpacing`” in *Internals Reference*, Section “`NonMusicalPaperColumn`” in *Internals Reference*.

Essay on automated music engraving: Section “`Optical spacing`” in *Essay*.

## Known issues and warnings

There is no convenient mechanism to manually override spacing. The following work-around may be used to insert extra space into a score, adjusting the padding value as necessary.

```
\override Score.NonMusicalPaperColumn #'padding = #10
```

No work-around exists for decreasing the amount of space.

### 4.5.2 New spacing area

New sections with different spacing parameters can be started with `newSpacingSection`. This is useful when there are sections with a different notions of long and short notes.

In the following example, the time signature change introduces a new section, and hence the 16ths notes are spaced wider.

```
\time 2/4
c4 c8 c
c8 c c4 c16[ c c8] c4
\newSpacingSection
\time 4/16
c16[ c c8]
```



The `\newSpacingSection` command creates a new `SpacingSpanner` object, and hence new `\overrides` may be used in that location.

### See also

Snippets: [Section “Spacing” in \*Snippets\*](#).

Internals Reference: [Section “SpacingSpanner” in \*Internals Reference\*](#).

### 4.5.3 Changing horizontal spacing

Horizontal spacing may be altered with the `base-shortest-duration` property. Here we compare the same music; once without altering the property, and then altered. Larger values of `ly:make-moment` will produce smaller music. Note that `ly:make-moment` constructs a duration, so 1 4 is a longer duration than 1 16.

```
\score {
  \relative c'' {
    g4 e e2 | f4 d d2 | c4 d e f | g4 g g2 |
    g4 e e2 | f4 d d2 | c4 e g g | c,1 |
    d4 d d d | d4 e f2 | e4 e e e | e4 f g2 |
    g4 e e2 | f4 d d2 | c4 e g g | c,1 |
  }
}
```



```
\score {
```

```

\relative c'' {
  g4 e e2 | f4 d d2 | c4 d e f | g4 g g2 |
  g4 e e2 | f4 d d2 | c4 e g g | c,1 |
  d4 d d d | d4 e f2 | e4 e e e | e4 f g2 |
  g4 e e2 | f4 d d2 | c4 e g g | c,1 |
}
\layout {
  \context {
    \Score
    \override SpacingSpanner
      #'base-shortest-duration = #(ly:make-moment 1 16)
  }
}

```

## Selected Snippets

By default, spacing in tuplets depends on various non-duration factors (such as accidentals, clef changes, etc). To disregard such symbols and force uniform equal-duration spacing, use `Score.SpacingSpanner #'uniform-stretching`. This property can only be changed at the beginning of a score,

```


\score {
  <<
    \new Staff {
      \times 4/5 {
        c8 c8 c8 c8 c8
      }
      c8 c8 c8 c8
    }
    \new Staff {

```

```

      c8 c8 c8 c8
      \times 4/5 {
        c8 c8 c8 c8 c8
      }
    }
  >>
  \layout {
    \context {
      \Score
      \override SpacingSpanner #'uniform-stretching = ##t
    }
  }
}

```



When `strict-note-spacing` is set, notes are spaced without regard for clefs, bar lines, and grace notes,

```

\override Score.SpacingSpanner #'strict-note-spacing = ##t
\new Staff { c8[ c \clef alto c \grace { c16[ c] } c8 c c] c32[ c32] }

```



## See also

Snippets: [Section “Spacing” in \*Snippets\*](#).

### 4.5.4 Line length

The most basic settings influencing the spacing are `indent` and `line-width`. They are set in the `\layout` block. They control the indentation of the first line of music, and the lengths of the lines.

If `ragged-right` is set to true in the `\layout` block, then systems ends at their natural horizontal length, instead of being spread horizontally to fill the whole line. This is useful for short fragments, and for checking how tight the natural spacing is. The normal default setting is false, but if the score has only one system the default value is true.

The option `ragged-last` is similar to `ragged-right`, but only affects the last line of the piece. No restrictions are put on that line. The result is similar to formatting text paragraphs. In a paragraph, the last line simply takes its natural horizontal length.

```

\layout {
  indent = #0
  line-width = #150
  ragged-last = ##t
}

```

## See also

Snippets: [Section “Spacing” in \*Snippets\*](#).

### 4.5.5 Proportional notation

LilyPond supports proportional notation, a type of horizontal spacing in which each note consumes an amount of horizontal space exactly equivalent to its rhythmic duration. This type of proportional spacing is comparable to horizontal spacing on top of graph paper. Some late 20th- and early 21st-century scores use proportional notation to clarify complex rhythmic relationships or to facilitate the placement of timelines or other graphics directly in the score.

LilyPond supports five different settings for proportional notation, which may be used together or alone:

- `proportionalNotationDuration`
- `uniform-stretching`
- `strict-note-spacing`
- `\remove Separating_line_group_engraver`
- `\override PaperColumn #'used = ##t`

In the examples that follow, we explore these five different proportional notation settings and examine how these settings interact.

We start with the following one-measure example, which uses classical spacing with ragged-right turned on.

```
\score {
  <<
    \new RhythmicStaff {
      c'2
      c'16 c'16 c'16 c'16
      \times 4/5 {
        c'16 c'16 c'16 c'16 c'16
      }
    }
  >>
}
```



Notice that the half note which begins the measure takes up far less than half of the horizontal space of the measure. Likewise, the sixteenth notes and sixteenth-note quintuplets (or twentieth notes) which end the measure together take up far more than half the horizontal space of the measure.

In classical engraving, this spacing may be exactly what we want because we can borrow horizontal space from the half note and conserve horizontal space across the measure as a whole.


On the other hand, if we want to insert a measured timeline or other graphic above or below our score, we need proportional notation. We turn proportional notation on with the `proportionalNotationDuration` setting.

```
\score {
  <<
    \new RhythmicStaff {
      c'2
```

```

      c'16 c'16 c'16 c'16
      \times 4/5 {
        c'16 c'16 c'16 c'16 c'16
      }
    }
  >>
\layout {
  \context {
    \Score
    proportionalNotationDuration = #(ly:make-moment 1 20)
  }
}

```



The half note at the beginning of the measure and the faster notes in the second half of the measure now occupy equal amounts of horizontal space. We could place a measured timeline or graphic above or below this example.

The `proportionalNotationDuration` setting is a context setting that lives in `Score`. Remember that context settings can appear in one of three locations within our input file – in a `\with` block, in a `\context` block, or directly in music entry preceded by the `\set` command. As with all context settings, users can pick which of the three different locations they would like to set `proportionalNotationDuration` in to.

The `proportionalNotationDuration` setting takes a single argument, which is the reference duration against that all music will be spaced. The LilyPond Scheme function `make-moment` takes two arguments – a numerator and denominator which together express some fraction of a whole note. The call `(ly:make-moment 1 20)` therefore produces a reference duration of a twentieth note. Values such as `(ly:make-moment 1 16)`, `(ly:make-moment 1 8)`, and `(ly:make-moment 3 97)` are all possible as well.

How do we select the right reference duration to pass to `proportionalNotationDuration`? Usually by a process of trial and error, beginning with a duration close to the fastest (or smallest) duration in the piece. Smaller reference durations space music loosely; larger reference durations space music tightly.

```

\score {
  <<
    \new RhythmicStaff {
      c'2
      c'16 c'16 c'16 c'16
      \times 4/5 {
        c'16 c'16 c'16 c'16 c'16
      }
    }
  >>
\layout {
  \context {
    \Score
    proportionalNotationDuration = #(ly:make-moment 1 8)
  }
}

```

```

    }
  }


\score {
  <<
    \new RhythmicStaff {
      c'2
      c'16 c'16 c'16 c'16
      \times 4/5 {
        c'16 c'16 c'16 c'16 c'16
      }
    }
  >>
  \layout {
    \context {
      \Score
      proportionalNotationDuration = #(ly:make-moment 1 16)
    }
  }
}

```

```

\score {
  <<
    \new RhythmicStaff {
      c'2
      c'16 c'16 c'16 c'16
      \times 4/5 {
        c'16 c'16 c'16 c'16 c'16
      }
    }
  >>
  \layout {
    \context {
      \Score
      proportionalNotationDuration = #(ly:make-moment 1 32)
    }
  }
}

```



Note that too large a reference duration – such as the eighth note, above – spaces music too tightly and can cause note head collisions. Also that proportional notation in general takes up




more horizontal space than classical spacing. Proportional spacing provides rhythmic clarity at the expense of horizontal space.

Next we examine how to optimally space overlapping tuplets.


We start by examining what happens to our original example, with classical spacing, when we add a second staff with a different type of tuplet.

```
\score {
  <<
    \new RhythmicStaff {
      c'2
      c'16 c'16 c'16 c'16
      \times 4/5 {
        c'16 c'16 c'16 c'16 c'16
      }
    }
    \new RhythmicStaff {
      \times 8/9 {
        c'8 c'8 c'8 c'8 c'8 c'8 c'8 c'8 c'8
      }
    }
  >>
}
```



The spacing is bad because the evenly spaced notes of the bottom staff do not stretch uniformly. Classical engravings include very few complex triplets and so classical engraving rules can generate this type of result. Setting `proportionalNotationDuration` fixes this.

```
\score {
  <<
    \new RhythmicStaff {
      c'2
      c'16 c'16 c'16 c'16
      \times 4/5 {
        c'16 c'16 c'16 c'16 c'16
      }
    }
    \new RhythmicStaff {
      \times 8/9 {
        c'8 c'8 c'8 c'8 c'8 c'8 c'8 c'8 c'8
      }
    }
  >>
  \layout {
    \context {
      \Score
      proportionalNotationDuration = #(ly:make-moment 1 20)
    }
  }
}
```




But if we look very carefully we can see that notes of the second half of the 9-tuplet space ever so slightly more widely than the notes of the first half of the 9-tuplet. To ensure uniform stretching, we turn on `uniform-stretching`, which is a property of `SpacingSpanner`.

```

\score {
  <<
    \new RhythmicStaff {
      c'2
      c'16 c'16 c'16 c'16
      \times 4/5 {
        c'16 c'16 c'16 c'16 c'16
      }
    }
    \new RhythmicStaff {
      \times 8/9 {
        c'8 c'8 c'8 c'8 c'8 c'8 c'8 c'8 c'8
      }
    }
  >>
  \layout {
    \context {
      \Score
      proportionalNotationDuration = #(ly:make-moment 1 20)
      \override SpacingSpanner #'uniform-stretching = ##t
    }
  }
}

```



Our two-staff example now spaces exactly, our rhythmic relationships are visually clear, and we can include a measured timeline or graphic if we want.

Note that the LilyPond's proportional notation package expects that all proportional scores set the `SpacingSpanner`'s `'uniform-stretching` attribute to `##t`. Setting `proportionalNotationDuration` without also setting the `SpacingSpanner`'s `'uniform-stretching` attribute to `##t` will, for example, cause Skips to consume an incorrect amount of horizontal space.


The `SpacingSpanner` is an abstract grob that lives in the `Score` context. As with our settings of `proportionalNotationDuration`, overrides to the `SpacingSpanner` can occur in any of three different places in our input file – in the `Score \with` block, in a `Score \context` block, or in note entry directly.

There is by default only one `SpacingSpanner` per `Score`. This means that, by default, `uniform-stretching` is either turned on for the entire score or turned off for the entire score. We can, however, override this behavior and turn on different spacing features at different places in the score. We do this with the command `\newSpacingSection`. See [Section 4.5.2 \[New spacing area\]](#), page 505, for more info.

Next we examine the effects of the `Separating_line_group_engraver` and see why proportional scores frequently remove this engraver. The following example shows that there is a small amount of “prefatory” space just before the first note in each system.

```
\paper {
  indent = #0
}
```

```
\new Staff {
  c'1
  \break
  c'1
}
```



The amount of this prefatory space is the same whether after a time signature, a key signature or a clef. `Separating_line_group_engraver` is responsible for this space. Removing `Separating_line_group_engraver` reduces this space to zero.

```
\paper {
  indent = #0
}
```

```
\new Staff \with {
  \remove Separating_line_group_engraver
} {
  c'1
  \break
  c'1
}
```



non-musical elements like time signatures, key signatures, clefs and accidentals are problematic in proportional notation. None of these elements has rhythmic duration. But all of these elements consume horizontal space. Different proportional scores approach these problems differently.

It may be possible to avoid spacing problems with key signatures simply by not having any. This is a valid option since most proportional scores are contemporary music. The same may be true of time signatures, especially for those scores that include a measured timeline or other graphic. But these scores are exceptional and most proportional scores include at least some time signatures. Clefs and accidentals are even more essential.

So what strategies exist for spacing non-musical elements in a proportional context? One good option is the **strict-note-spacing** property of `SpacingSpanner`. Compare the two scores below:

```
\new Staff {
  \set Score.proportionalNotationDuration = #(ly:make-moment 1 16)
  c''8
  c''8
  c''8
  \clef alto
  d'8
  d'2
}
```

```
\new Staff {
  \set Score.proportionalNotationDuration = #(ly:make-moment 1 16)
  \override Score.SpacingSpanner #'strict-note-spacing = ##t
  c''8
  c''8
  c''8
  \clef alto
  d'8
  d'2
}
```



Both scores are proportional, but the spacing in the first score is too loose because of the clef change. The spacing of the second score remains strict, however, because strict-note-spacing is turned on. Turning on strict-note-spacing causes the width of time signatures, key signatures, clefs and accidentals to play no part in the spacing algorithm.

In addition to the settings given here, there are other settings that frequently appear in proportional scores. These include:

- \override SpacingSpanner #'strict-grace-spacing = ##t
- tupletFullLength = ##t
- \override Beam #'breakable = ##t

- `\override Glissando #'breakable = ##t`
- `\override TextSpanner #'breakable = ##t`
- `\remove Forbid_line_break_engraver` in the Voice context

These settings space grace notes strictly, extend tuplet brackets to mark both rhythmic start- and stop-points, and allow spanning elements to break across systems and pages. See the respective parts of the manual for these related settings.

## See also

Notation Reference: [Section 4.5.2 \[New spacing area\]](#), page 505.

Snippets: [Section “Spacing” in \*Snippets\*](#).

## 4.6 Fitting music onto fewer pages

Sometimes you can end up with one or two staves on a second (or third, or fourth...) page. This is annoying, especially if you look at previous pages and it looks like there is plenty of room left on those.

When investigating layout issues, `annotate-spacing` is an invaluable tool. This command prints the values of various layout spacing variables; for more details see the following section, [Section 4.6.1 \[Displaying spacing\]](#), page 515.


### 4.6.1 Displaying spacing

To graphically display the dimensions of vertical layout variables that may be altered for page formatting, set `annotate-spacing` in the `\paper` block:

```

#(set-default-paper-size "a6" 'landscape)
\book {
  \score { { c4 } }
  \paper { annotate-spacing = ##t }
}

```



All layout dimensions are displayed in staff-spaces, regardless of the units specified in the `\paper` or `\layout` block. In the above example, `paper-height` has a value of 59.75 `staff-spaces`, and the `staff-size` is 20 points (the default value). Note that:

$$\begin{aligned}
 1 \text{ point} &= (25.4/72.27) \text{ mm} \\
 1 \text{ staff-space} &= (\text{staff-size})/4 \text{ pts} \\
 &= (\text{staff-size})/4 \cdot (25.4/72.27) \text{ mm}
 \end{aligned}$$

In this case, one `staff-space` is approximately equal to 1.757mm. Thus the `paper-height` measurement of 59.75 `staff-spaces` is equivalent to 105 millimeters, the height of a6 paper in landscape orientation. The pairs  $(a,b)$  are intervals, where  $a$  is the lower edge and  $b$  the upper edge of the interval.

## See also

Notation Reference: [Section 4.2.2 \[Setting the staff size\]](#), page 479.

Snippets: [Section “Spacing” in \*Snippets\*](#).

## 4.6.2 Changing spacing

The output of `annotate-spacing` reveals vertical dimensions in great detail. For details about modifying margins and other layout variables, see [Section 4.1 \[Page layout\]](#), page 469.

Other than margins, there are a few other options to save space:

- Force systems to move as close together as possible (to fit as many systems as possible onto a page) while being spaced so that there is no blank space at the bottom of the page.

```
\paper {
  system-system-spacing = #'((basic-distance . 0.1) (padding . 0))
  ragged-last-bottom = ##f
  ragged-bottom = ##f
}
```

- Force the number of systems. This can help in two ways. Just setting a value, even the same value as the number of systems being typeset by default, will sometimes cause more systems to be fitted onto each page, as an estimation step is then bypassed, giving a more accurate fit to each page. Also, forcing an actual reduction in the number of systems may save a further page. For example, if the default layout has 11 systems, the following assignment will force a layout with 10 systems.

```
\paper {
  system-count = #10
}
```

- Avoid (or reduce) objects that increase the vertical size of a system. For example, volta repeats (or alternate repeats) require extra space. If these repeats are spread over two systems, they will take up more space than one system with the volta repeats and another system without. For example, dynamics that ‘stick out’ of a system can be moved closer to the staff:

$$e_4 \quad c \quad g \backslash f \quad c$$

```
e4 c g-\tweak #'X-offset #-2.7 -\tweak #'Y-offset #2.5 \f c
```



- Alter the horizontal spacing via `SpacingSpanner`. For more details, see [Section 4.5.3 \[Changing horizontal spacing\]](#), page 505. The following example illustrates the default spacing:

```
\score {
  \relative c'' {
    g4 e e2 |
    f4 d d2 |
    c4 d e f |
    g4 g g2 |
    g4 e e2 |
  }
}
```



The next example modifies `common-shortest-duration` from a value of 1/4 to 1/2. The quarter note is the most common and shortest duration in this example, so by making this duration longer, a ‘squeezing’ effect occurs:

```

\score {
  \relative c'' {
    g4 e e2 |
    f4 d d2 |
    c4 d e f |
    g4 g g2 |
    g4 e e2 |
  }
  \layout {
    \context {
      \Score
      \override SpacingSpanner
        #'common-shortest-duration = #(ly:make-moment 1 2)
    }
  }
}

```



The `common-shortest-duration` property cannot be modified dynamically, so it must always be placed in a `\context` block so that it applies to the whole score.

## See also

Notation Reference: [Section 4.1 \[Page layout\]](#), page 469, [Section 4.5.3 \[Changing horizontal spacing\]](#), page 505.

Snippets: [Section “Spacing” in \*Snippets\*](#).



## 5 Changing defaults

The purpose of LilyPond’s design is to provide the finest quality output by default. Nevertheless, it may happen that you need to change this default layout. The layout is controlled through a large number of ‘knobs and switches’ collectively called ‘properties’. A tutorial introduction to accessing and modifying these properties can be found in the Learning Manual, see [Section “Tweaking output” in \*Learning Manual\*](#). This should be read first. This chapter covers similar ground, but in a style more appropriate to a reference manual.

The definitive description of the controls available for tuning can be found in a separate document: [Section “the Internals Reference” in \*Internals Reference\*](#). That manual lists all the variables, functions and options available in LilyPond. It is written as a HTML document, which is available [on-line](#), and is also included with the LilyPond documentation package.

Internally, LilyPond uses Scheme (a LISP dialect) to provide infrastructure. Overriding layout decisions in effect accesses the program internals, which requires Scheme input. Scheme elements are introduced in a ‘.ly’ file with the hash mark #.<sup>1</sup>

### 5.1 Interpretation contexts

This section describes what contexts are, and how to modify them.

#### See also

Learning Manual: [Section “Contexts and engravers” in \*Learning Manual\*](#).

Installed Files: ‘ly/engraver-init.ly’, ‘ly/performer-init.ly’.

Snippets: [Section “Contexts and engravers” in \*Snippets\*](#).

Internals Reference: [Section “Contexts” in \*Internals Reference\*](#), [Section “Engravers and Performers” in \*Internals Reference\*](#).

#### 5.1.1 Contexts explained

Contexts are arranged hierarchically:

#### Score - the master of all contexts

This is the top level notation context. No other context can contain a Score context. By default the Score context handles the administration of time signatures and makes sure that items such as clefs, time signatures, and key-signatures are aligned across staves.

A Score context is instantiated implicitly when a `\score {...}` or `\layout {...}` block is processed.

#### Top-level contexts - staff containers

##### *StaffGroup*

Groups staves while adding a bracket on the left side, grouping the staves together. The bar lines of the contained staves are connected vertically. **StaffGroup** only consists of a collection of staves, with a bracket in front and spanning bar lines.

##### *ChoirStaff*

Identical to **StaffGroup** except that the bar lines of the contained staves are not connected vertically.

##### *GrandStaff*

---

<sup>1</sup> [Section “Scheme tutorial” in \*Extending\*](#), contains a short tutorial on entering numbers, lists, strings, and symbols in Scheme.

A group of staves, with a brace on the left side, grouping the staves together. The bar lines of the contained staves are connected vertically.

*PianoStaff*

Just like **GrandStaff**, but with support for instrument names to the left of each system.

## Intermediate-level contexts - staves

*Staff*

Handles clefs, bar lines, keys, accidentals. It can contain **Voice** contexts.

*RhythmicStaff*

Like **Staff** but for printing rhythms. Pitches are ignored; the notes are printed on one line.

*TabStaff*

Context for generating tablature. By default lays the music expression out as a guitar tablature, printed on six lines.

*DrumStaff*

Handles typesetting for percussion. Can contain **DrumVoice**

*VaticanaStaff*

Same as **Staff**, except that it is designed for typesetting a piece in gregorian style.

*MensuralStaff*

Same as **Staff**, except that it is designed for typesetting a piece in mensural style.

## Bottom-level contexts - voices

Voice-level contexts initialise certain properties and start appropriate engravers. Being bottom-level contexts, they cannot contain other contexts.

*Voice*

Corresponds to a voice on a staff. This context handles the conversion of dynamic signs, stems, beams, super- and sub-scripts, slurs, ties, and rests. You have to instantiate this explicitly if you require multiple voices on the same staff.

*VaticanaVoice*

Same as **Voice**, except that it is designed for typesetting a piece in gregorian style.

*MensuralVoice*

Same as **Voice**, with modifications for typesetting a piece in mensural style.

*Lyrics*

Corresponds to a voice with lyrics. Handles the printing of a single line of lyrics.

*DrumVoice*

The voice context used in a percussion staff.

*FiguredBass*

The context in which **BassFigure** objects are created from input entered in `\figuremode` mode.

*TabVoice*

The voice context used within a **TabStaff** context. Usually left to be created implicitly.

*CueVoice*

A voice context used to render notes of a reduced size, intended primarily for adding cue notes to a staff, see [\[Formatting cue notes\]](#), page 185. Usually left to be created implicitly.

*ChordNames*

Typesets chord names.

### 5.1.2 Creating contexts

For scores with only one voice and one staff, contexts are created automatically. For more complex scores, it is necessary to create them by hand. There are three commands that do this.


- The easiest command is `\new`, and it is also the quickest to type. It is prepended to a music expression, for example

```
\new type music expression
```

where *type* is a context name (like **Staff** or **Voice**). This command creates a new context, and starts interpreting the *music expression* with that.

A practical application of `\new` is a score with many staves. Each part that should be on its own staff, is preceded with `\new Staff`.

```
<<
  \new Staff { c4 c }
  \new Staff { d4 d }
>>
```



The `\new` command may also give a name to the context,

```
\new type = id music
```

However, this user specified name is only used if there is no other context already earlier with the same name.

- Like `\new`, the `\context` command also directs a music expression to a context object, but gives the context an explicit name. The syntax is

```
\context type = id music
```

This form will search for an existing context of type *type* called *id*. If that context does not exist yet, a new context with the specified name is created. This is useful if the context is referred to later on. For example, when setting lyrics the melody is in a named context

```
\context Voice = "tenor" music
```

so the texts can be properly aligned to its notes,

```
\new Lyrics \lyricsto "tenor" lyrics
```

Another possible use of named contexts is funneling two different music expressions into one context. In the following example, articulations and notes are entered separately,

```
music = { c4 c4 }
arts = { s4-. s4-> }
```

They are combined by sending both to the same **Voice** context,

```
<<
  \new Staff \context Voice = "A" \music
  \context Voice = "A" \arts
>>
```



With this mechanism, it is possible to define an Urtext (original edition), with the option to put several distinct articulations on the same notes.

- The third command for creating contexts is

```
\context type music
```

This is similar to `\context` with `= id`, but matches any context of type *type*, regardless of its given name.

This variant is used with music expressions that can be interpreted at several levels. For example, the `\applyOutput` command (see [Section “Running a function on all layout objects” in Extending](#)). Without an explicit `\context`, it is usually applied to *Voice*

```
\applyOutput #'context #function % apply to Voice
```

To have it interpreted at the *Score* or *Staff* level use these forms

```
\applyOutput #'Score #function
```

```
\applyOutput #'Staff #function
```

### 5.1.3 Keeping contexts alive

Contexts are usually terminated at the first musical moment in which they have nothing to do. So *Voice* contexts die as soon as they contain no events; *Staff* contexts die as soon as all the *Voice* contexts within them contain no events; etc. This can cause difficulties if earlier contexts which have died have to be referenced, for example, when changing staves with `\change` commands, associating lyrics with a voice with `\lyricsto` commands, or when adding further musical events to an earlier context.

There is an exception to this general rule: just one of the *Voice* contexts in a *Staff* context or in a `<<...>>` construct will always persist to the end of the enclosing *Staff* context or `<<...>>` construct, even though there may be periods when it has nothing to do. The context to persist in this way will be the first one encountered in the first enclosed `{...}` construct, ignoring any in enclosed `<<...>>` constructs.

Any context can be kept alive by ensuring it has something to do at every musical moment. *Staff* contexts are kept alive by ensuring one of their voices is kept alive. One way of doing this is to add spacer rests to a voice in parallel with the real music. These need to be added to every *Voice* context which needs to be kept alive. If several voices are to be used sporadically it is safest to keep them all alive rather than attempting to rely on the exceptions mentioned above.

In the following example, both voice A and voice B are kept alive in this way for the duration of the piece:

```
musicA = \relative c'' { d4 d d d }
musicB = \relative c'' { g4 g g g }
keepVoicesAlive = {
  <<
    \new Voice = "A" { s1*5 } % Keep Voice "A" alive for 5 bars
    \new Voice = "B" { s1*5 } % Keep Voice "B" alive for 5 bars
  >>
}


music = {
  \context Voice = "A" {
    \voiceOneStyle
    \musicA
  }
  \context Voice = "B" {
```

```

    \voiceTwoStyle
    \musicB
  }
  \context Voice = "A" { \musicA }
  \context Voice = "B" { \musicB }
  \context Voice = "A" { \musicA }
}

\score {
  \new Staff <<
    \keepVoicesAlive
    \music
  >>
}

```




The following example shows how a sporadic melody line with lyrics might be written using this approach. In a real situation the melody and accompaniment would consist of several different sections, of course.

```

melody = \relative c'' { a4 a a a }
accompaniment = \relative c' { d4 d d d }
words = \lyricmode { These words fol -- low the mel -- o -- dy }
\score {
  <<
    \new Staff = "music" {
      <<
        \new Voice = "melody" {
          \voiceOne
          s1*4 % Keep Voice "melody" alive for 4 bars
        }
        {
          \new Voice = "accompaniment" {
            \voiceTwo
            \accompaniment
          }
          <<
            \context Voice = "melody" { \melody }
            \context Voice = "accompaniment" { \accompaniment }
          >>
          \context Voice = "accompaniment" { \accompaniment }
          <<
            \context Voice = "melody" { \melody }
            \context Voice = "accompaniment" { \accompaniment }
          >>
        }
      >>
    }
    \new Lyrics \with { alignAboveContext = #"music" }
    \lyricsto "melody" { \words }
  }
}

```


```
>>
}
```



An alternative way, which may be better in many circumstances, is to keep the melody line alive by simply including spacer notes to line it up correctly with the accompaniment:

```
melody = \relative c' {
  s1 % skip a bar
  a4 a a a
  s1 % skip a bar
  a4 a a a
}
accompaniment = \relative c' {
  d4 d d d
  d4 d d d
  d4 d d d
  d4 d d d
}
words = \lyricmode { These words fol -- low the mel -- o -- dy }

\score {
  <<
    \new Staff = "music" {
      <<
        \new Voice = "melody" {
          \voiceOne
          \melody
        }
        \new Voice = "accompaniment" {
          \voiceTwo
          \accompaniment
        }
      >>
    }
    \new Lyrics \with { alignAboveContext = #"music" }
    \lyricsto "melody" { \words }
  >>
}
```



#### 5.1.4 Modifying context plug-ins

Notation contexts (like `Score` and `Staff`) not only store properties, they also contain plug-ins called ‘engravers’ that create notation elements. For example, the `Voice` context contains a `Note_heads_engraver` and the `Staff` context contains a `Key_signature_engraver`.

For a full a description of each plug-in, see *Internals Reference*  $\mapsto$  Translation  $\mapsto$  Engravers. Every context described in *Internals Reference*  $\mapsto$  Translation  $\mapsto$  Context. lists the engravers used for that context.

It can be useful to shuffle around these plug-ins. This is done by starting a new context with `\new` or `\context`, and modifying it,

```
\new context \with {
  \consists ...
  \consists ...
  \remove ...
  \remove ...
  etc.
}
{
  ..music..
}
```

where the ... should be the name of an engraver. Here is a simple example which removes `Time_signature_engraver` and `Clef_engraver` from a `Staff` context,

```
<<
  \new Staff {
    f2 g
  }
  \new Staff \with {
    \remove "Time_signature_engraver"
    \remove "Clef_engraver"
  } {
    f2 g2
  }
>>
```



In the second staff there are no time signature or clef symbols. This is a rather crude method of making objects disappear since it will affect the entire staff. This method also influences the spacing, which may or may not be desirable. More sophisticated methods of blanking objects are shown in [Section “Visibility and color of objects”](#) in *Learning Manual*.


The next example shows a practical application. Bar lines and time signatures are normally synchronized across the score. This is done by the `Timing_translator` and `Default_bar_line_engraver`. This plug-in keeps an administration of time signature, location within the measure, etc. By moving these engraver from `Score` to `Staff` context, we can have a score where each staff has its own time signature.

```
\score {
  <<
    \new Staff \with {
      \consists "Timing_translator"
      \consists "Default_bar_line_engraver"
    } {
```

```

        \time 3/4
        c4 c c c c c
    }
    \new Staff \with {
        \consists "Timing_translator"
        \consists "Default_bar_line_engraver"
    } {
        \time 2/4
        c4 c c c c c
    }
>>
\layout {
    \context {
        \Score
        \remove "Timing_translator"
        \remove "Default_bar_line_engraver"
    }
}

```



## Known issues and warnings

Usually the order in which the engravers are specified does not matter, but in a few special cases the order is important, for example where one engraver writes a property and another reads it, or where one engraver creates a grob and another must process it. The order in which the engravers are specified is the order in which they are called to carry out their processing.

The following orderings are important: the `Bar_engraver` must normally be first, and the `New_fingering_engraver` must come before the `Script_column_engraver`. There may be others with ordering dependencies.

### 5.1.5 Changing context default settings

The context settings which are to be used by default in `Score`, `Staff` and `Voice` contexts may be specified in a `\layout` block, as illustrated in the following example. The `\layout` block should be placed within the `\score` block to which it is to apply, but outside any music.

Note that the `\set` command itself and the context must be omitted when the context default values are specified in this way:

```

\score {
    \relative c'' {
        a4~"Really small, thicker stems, no time signature" a a a
        a a a a
    }
    \layout {


```



```

\context {
  \Staff
  fontSize = #-4
  \override Stem #'thickness = #4.0
  \remove "Time_signature_engraver"
}
}
}

```



In this example, the `\Staff` command specifies that the subsequent specifications are to be applied to all staves within this score block.

Modifications can be made to the `Score` context or all `Voice` contexts in a similar way.

Context changes can be placed in a variable and applied to a `\context` definition by prepending the modification with `\with`:

```

blubb = \with {
  fontSize = #-4
  \override Stem #'thickness = #4.0
  \remove "Time_signature_engraver"
}

```

```

bla = \with {
  fontSize = #3
  \override Stem #'thickness = #-2.0
}

```

```

melody = \relative c'' {
  a4 a a a |
  a4 a a a |
}


```

```

\score {
  <<
    \new Staff <<
      \melody
      s1*0^"Small, thicker stems, no time signature"
    >>
    \new Staff \bla <<
      \melody
      s1*0^"Different"
    >>
  >>
  \layout {
    \context {
      \Staff
      \blubb
    }
  }
}

```


}



### 5.1.6 Defining new contexts

Specific contexts, like `Staff` and `Voice`, are made of simple building blocks. It is possible to create new types of contexts with different combinations of engraver plug-ins.

The next example shows how to build a different type of `Voice` context from scratch. It will be similar to `Voice`, but only prints centered slash note heads. It can be used to indicate improvisation in jazz pieces,



These settings are defined within a `\context` block inside a `\layout` block,

```
\layout {
  \context {
    ...
  }
}
```

In the following discussion, the example input shown should go in place of the `...` in the previous fragment.

First it is necessary to define a name for the new context:

```
\name ImproVoice
```

Since it is similar to the `Voice`, we want commands that work on (existing) `Voices` to remain working. This is achieved by giving the new context an alias `Voice`,

```
\alias Voice
```

The context will print notes and instructive texts, so we need to add the engravers which provide this functionality,

```
\consists Note_heads_engraver
\consists Text_engraver
```

but we only need this on the center line,

```
\consists Pitch_squash_engraver
squashedPosition = #0
```

The [Section “Pitch\\_squash\\_engraver”](#) in *Internals Reference* modifies note heads (created by [Section “Note\\_heads\\_engraver”](#) in *Internals Reference*) and sets their vertical position to the value of `squashedPosition`, in this case 0, the center line.

The notes look like a slash, and have no stem,

```
\override NoteHead #'style = #'slash
\override Stem #'transparent = ##t
\override Flag #'transparent = ##t
```

All these plug-ins have to cooperate, and this is achieved with a special plug-in, which must be marked with the keyword `\type`. This should always be `Engraver_group`.

```
\type "Engraver_group"
```

Put together, we get

```
\context {
  \name ImproVoice
  \type "Engraver_group"
  \consists "Note_heads_engraver"
  \consists "Text_engraver"
  \consists Pitch_squash_engraver
  squashedPosition = #0
  \override NoteHead #'style = #'slash
  \override Stem #'transparent = ##t
  \override Flag #'transparent = ##t
  \alias Voice
}
```

Contexts form hierarchies. We want to hang the `ImproVoice` under `Staff`, just like normal Voices. Therefore, we modify the `Staff` definition with the `\accepts` command,

```
\context {
  \Staff
  \accepts ImproVoice
}
```

The opposite of `\accepts` is `\denies`, which is sometimes needed when reusing existing context definitions.

Putting both into a `\layout` block, like

```
\layout {
  \context {
    \name ImproVoice
    ...
  }
  \context {
    \Staff
    \accepts "ImproVoice"
  }
}
```

Then the output at the start of this subsection can be entered as

```
\relative c'' {
  a4 d8 bes8
  \new ImproVoice {
    c4^"ad lib" c
    c4 c^"undress"
    c c_"while playing :)"
  }
  a1
}
```

### 5.1.7 Context layout order

Contexts are normally positioned in a system from top to bottom in the order in which they are encountered in the input file. When contexts are nested, the outer context will include inner

nested contexts as specified in the input file, provided the inner contexts are included in the outer context’s “accepts” list. Nested contexts which are not included in the outer context’s “accepts” list will be repositioned below the outer context rather than nested within it.

The “accepts” list of a context can be changed with the `\accepts` and `\denies` commands. `\accepts` adds a context to the “accepts” list and `\denies` removes a context from the list. For example, it would not normally be desirable for chord names to be nested within a `Staff` context, so the `ChordNames` context is not included by default in the “accepts” list of the `Staff` context, but if this were to be required it can be done:

```
\score {
  \new Staff {
    c' d' e' f'
    \chords { d1:m7 b1:min7.5- }
  }
}
```



```
\score {
  \new Staff {
    c' d' e' f'
    \chords { d1:m7 b1:min7.5- }
  }
  \layout {
    \context {
      \Staff
      \accepts "ChordNames"
    }
  }
}
```



`\denies` is mainly used when a new context is being based on another, but the required nesting differs. For example, the `VaticanaStaff` context is based on the `Staff` context, but with the `VaticanaVoice` context substituted for the `Voice` context in the “accepts” list.

Note that a context will be silently created implicitly if a command is encountered when there is no suitable context available to contain it. This can give rise to unexpected new staves or scores.

## See also

Usage Manual: [Section “An extra staff appears” in Application Usage](#).

Installed Files: ‘`ly/engraver-init.ly`’.

## 5.2 Explaining the Internals Reference

### 5.2.1 Navigating the program reference

Suppose we want to move the fingering indication in the fragment below:

```
c-2
\stemUp
f
```



If you visit the documentation on fingering instructions (in [\[Fingering instructions\]](#), page 192), you will notice:

**See also**

Internals Reference: [Section “Fingering” in Internals Reference](#).

The programmer’s reference is available as an HTML document. It is highly recommended that you read it in HTML form, either online or by downloading the HTML documentation. This section will be much more difficult to understand if you are using the PDF manual.

Follow the link to [Section “Fingering” in Internals Reference](#). At the top of the page, you will see

Fingering objects are created by: [Section “Fingering\\_engraver” in Internals Reference](#) and [Section “New\\_fingering\\_engraver” in Internals Reference](#).

By following related links inside the program reference, we can follow the flow of information within the program:

- [Section “Fingering” in Internals Reference](#): Section “Fingering” in *Internals Reference* objects are created by: [Section “Fingering\\_engraver” in Internals Reference](#)
- [Section “Fingering\\_engraver” in Internals Reference](#): Music types accepted: [Section “fingering-event” in Internals Reference](#)
- [Section “fingering-event” in Internals Reference](#): Music event type `fingering-event` is in Music expressions named [Section “FingeringEvent” in Internals Reference](#)

This path goes against the flow of information in the program: it starts from the output, and ends at the input event. You could also start at an input event, and read with the flow of information, eventually ending up at the output object(s).

The program reference can also be browsed like a normal document. It contains chapters on **Music definitions** on [Section “Translation” in Internals Reference](#), and the [Section “Backend” in Internals Reference](#). Every chapter lists all the definitions used and all properties that may be tuned.

### 5.2.2 Layout interfaces

The HTML page that we found in the previous section describes the layout object called [Section “Fingering” in Internals Reference](#). Such an object is a symbol within the score. It has properties that store numbers (like thicknesses and directions), but also pointers to related objects. A layout object is also called a *Grob*, which is short for Graphical Object. For more details about Grobs, see [Section “grob-interface” in Internals Reference](#).

The page for `Fingering` lists the definitions for the `Fingering` object. For example, the page says

`padding` (dimension, in staff space):

0.5

which means that the number will be kept at a distance of at least 0.5 of the note head.

Each layout object may have several functions as a notational or typographical element. For example, the `Fingering` object has the following aspects

- Its size is independent of the horizontal spacing, unlike slurs or beams.
- It is a piece of text. Granted, it is usually a very short text.
- That piece of text is typeset with a font, unlike slurs or beams.
- Horizontally, the center of the symbol should be aligned to the center of the note head.
- Vertically, the symbol is placed next to the note and the staff.
- The vertical position is also coordinated with other superscript and subscript symbols.

Each of these aspects is captured in so-called *interfaces*, which are listed on the [Section “Fingering” in \*Internals Reference\*](#) page at the bottom

This object supports the following interfaces: [Section “item-interface” in \*Internals Reference\*](#), [Section “self-alignment-interface” in \*Internals Reference\*](#), [Section “side-position-interface” in \*Internals Reference\*](#), [Section “text-interface” in \*Internals Reference\*](#), [Section “text-script-interface” in \*Internals Reference\*](#), [Section “font-interface” in \*Internals Reference\*](#), [Section “finger-interface” in \*Internals Reference\*](#), and [Section “grob-interface” in \*Internals Reference\*](#).

Clicking any of the links will take you to the page of the respective object interface. Each interface has a number of properties. Some of them are not user-serviceable (‘Internal properties’), but others can be modified.

We have been talking of *the Fingering* object, but actually it does not amount to much. The initialization file (see [Section “Other sources of information” in \*Learning Manual\*](#)) ‘`scm/define-grobs.scm`’ shows the soul of the ‘object’,

```
(Fingering
 . ((padding . 0.5)
    (avoid-slur . around)
    (slur-padding . 0.2)
    (staff-padding . 0.5)
    (self-alignment-X . 0)
    (self-alignment-Y . 0)
    (script-priority . 100)
    (stencil . ,ly:text-interface::print)
    (direction . ,ly:script-interface::calc-direction)
    (font-encoding . fetaText)
    (font-size . -5) ; don't overlap when next to heads.
    (meta . ((class . Item)
              (interfaces . (finger-interface
                             font-interface
                             text-script-interface
                             text-interface
                             side-position-interface
                             self-alignment-interface
                             item-interface))))))
```

As you can see, the `Fingering` object is nothing more than a bunch of variable settings, and the webpage in the *Internals Reference* is directly generated from this definition.

### 5.2.3 Determining the grob property

Recall that we wanted to change the position of the **2** in

```
c-2
\stemUp
f
```



Since the **2** is vertically positioned next to its note, we have to meddle with the interface associated with this positioning. This is done using `side-position-interface`. The page for this interface says

`side-position-interface`

Position a victim object (this one) next to other objects (the support). The property `direction` signifies where to put the victim object relative to the support (left or right, up or down?)

Below this description, the variable `padding` is described as

`padding` (dimension, in staff space)

Add this much extra space between objects that are next to each other.

By increasing the value of `padding`, we can move the fingering away from the note head. The following command inserts 3 staff spaces of white between the note and the fingering:

```
\once \override Voice.Fingering #'padding = #3
```

Inserting this command before the Fingering object is created, i.e., before `c2`, yields the following result:

```
\once \override Voice.Fingering #'padding = #3
c-2
\stemUp
f
```



In this case, the context for this tweak is `Voice`. This fact can also be deduced from the program reference, for the page for the [Section “Fingering\\_engraver” in \*Internals Reference\*](#) plug-in says

Fingering\_engraver is part of contexts: ... [Section “Voice” in \*Internals Reference\*](#)

### 5.2.4 Naming conventions

Another thing that is needed, is an overview of the various naming conventions:

- scheme functions: lowercase-with-hyphens (incl. one-word names)
- scheme functions: `ly:plus-scheme-style`
- music events, music classes and music properties: as-scheme-functions
- Grob interfaces: `scheme-style`
- backend properties: `scheme-style` (but X and Y!)
- contexts (and MusicExpressions and grobs): Capitalized or CamelCase
- context properties: lowercaseFollowedByCamelCase
- engravers: Capitalized\_followed\_by\_lowercase\_and\_with\_underscores

Questions to be answered:

- Which of these are conventions and which are rules?
- Which are rules of the underlying language, and which are LP-specific?

## 5.3 Modifying properties

### 5.3.1 Overview of modifying properties

Each context is responsible for creating certain types of graphical objects. The settings used for printing these objects are also stored by context. By changing these settings, the appearance of objects can be altered.

There are two different kinds of properties stored in contexts: context properties and grob properties. Context properties are properties that apply to the context as a whole and control how the context itself is displayed. In contrast, grob properties apply to specific grob types that will be displayed in the context.

The `\set` and `\unset` commands are used to change values for context properties. The `\override` and `\revert` commands are used to change values for grob properties.

#### See also

Internals: [Section “Backend” in \*Internals Reference\*](#), [Section “All layout objects” in \*Internals Reference\*](#), [Section “OverrideProperty” in \*Internals Reference\*](#), [Section “RevertProperty” in \*Internals Reference\*](#), [Section “PropertySet” in \*Internals Reference\*](#).

#### Known issues and warnings

The back-end is not very strict in type-checking object properties. Cyclic references in Scheme values for properties can cause hangs or crashes, or both.

### 5.3.2 The `\set` command

Each context has a set of *properties*, variables contained in that context. Context properties are changed with the `\set` command, which has the following syntax:


```
\set context.property = #value
```

*value* is a Scheme object, which is why it must be preceded by the `#` character.

Contexts properties are usually named in `studlyCaps`. They mostly control the translation from music to notation, e.g. `localKeySignature` (for determining whether to print accidentals), or `measurePosition` (for determining when to print a bar line). Context properties can change value over time while interpreting a piece of music; `measurePosition` is an obvious example of this. Context properties are modified with `\set`.

For example, multimeasure rests will be combined into a single bar if the context property `skipBars` is set to `#t`:

```
R1*2
\set Score.skipBars = ##t
R1*2
```



If the *context* argument is left out, then the property will be set in the current bottom context (typically `ChordNames`, `Voice`, `TabVoice`, or `Lyrics`).

```
\set Score.autoBeaming = ##f
<<
{
  e8 e e e
  \set autoBeaming = ##t
```



```

      e8 e e e
    } \ {
      c8 c c c c8 c c c
    }
  >>

```



The change is applied ‘on-the-fly’, during the music, so that the setting only affects the second group of eighth notes.

Note that the bottom-most context does not always contain the property that you wish to change – for example, attempting to set the `skipBars` property of the default bottom context, in this case `Voice`, will have no effect, because `skipBars` is a property of the `Score` context.

```

R1*2
\set skipBars = ##t
R1*2

```



Contexts are hierarchical, so if an enclosing context was specified, for example `Staff`, then the change would also apply to all `Voices` in the current staff.

The `\unset` command:

```

\unset context.property


```

is used to remove the definition of *property* from *context*. This command removes the definition only if it is set in *context*. Properties that have been set in enclosing contexts will not be altered by an `\unset` in an enclosed context:

```

\set Score.autoBeaming = ##t
<<
{
  \unset autoBeaming
  e8 e e e
  \unset Score.autoBeaming
  e8 e e e
} \ {
  c8 c c c c8 c c c
}
>>

```



Like `\set`, the *context* argument does not have to be specified for a bottom context, so the two statements

```

\set Voice.autoBeaming = ##t
\set autoBeaming = ##t

```

are equivalent if the current bottom context is `Voice`.

Preceding a `\set` command by `\once` makes the setting apply to only a single time-step:

```
c4
\once \set fontSize = #4.7
c4
c4
```



A full description of all available context properties is in the internals reference, see Translation  $\mapsto$  Tunable context properties.

## See also

Internals Reference:

Section “Tunable context properties” in *Internals Reference*.

### 5.3.3 The `\override` command

There is a special type of context property: the grob description. Grob descriptions are named in **StudlyCaps** (starting with capital letters). They contain the ‘default settings’ for a particular kind of grob as an association list. See ‘`scm/define-grobs.scm`’ to see the settings for each grob description. Grob descriptions are modified with `\override`.

`\override` is actually a shorthand;

```
\override context.GrobName #'property = #value
```

is more or less equivalent to

```
\set context.GrobName =
  #(cons (cons 'property value)
    <previous value of context.GrobName>)
```

The value of `context.GrobName` (the alist) is used to initialize the properties of individual grobs. Grobs have properties, named in Scheme style, with **dashed-words**. The values of grob properties change during the formatting process: formatting basically amounts to computing properties using callback functions.

For example, we can increase the thickness of a note stem by overriding the **thickness** property of the **Stem** object:

```
c4 c
\override Voice.Stem #'thickness = #3.0
c4 c
```



If no context is specified in an `\override`, the bottom context is used:

```
{ \override Staff.Stem #'thickness = #3.0
  <<
    {
      e4 e
      \override Stem #'thickness = #0.5
      e4 e
    } \ {
```

```

      c4 c c c
    }
  >>
}

```



The effects of `\override` can be undone by `\revert`:

```

c4
\override Voice.Stem #'thickness = #3.0
c4 c
\revert Voice.Stem #'thickness
c4

```



The effects of `\override` and `\revert` apply to all grobs in the affected context from the current time forward:

```

{
  <<
  {
    e4
    \override Staff.Stem #'thickness = #3.0
    e4 e e
  } \ {
    c4 c c
    \revert Staff.Stem #'thickness
    c4
  }
  >>
}

```



`\once` can be used with `\override` to affect only the current time step:

```

{
  <<
  {
    \override Stem #'thickness = #3.0
    e4 e e e
  } \ {
    c4
    \once \override Stem #'thickness = #3.0
    c4 c c
  }
  >>
}

```

}



## See also

Internals Reference: [Section “Backend” in \*Internals Reference\*](#)

### 5.3.4 The `\tweak` command

Changing grob properties with `\override` causes the changes to apply to all of the given grobs in the context at the moment the change applies. Sometimes, however, it is desirable to have changes apply to just one grob, rather than to all grobs in the affected context. This is accomplished with the `\tweak` command, which has the following syntax:

```
\tweak #'grob-property #value
```

The `\tweak` command applies to the object that immediately follows `value` in the music stream.

For an introduction to the syntax and uses of the `tweak` command see [Section “Tweaking methods” in \*Learning Manual\*](#).

When several similar items are placed at the same musical moment, the `\override` command cannot be used to modify just one of them – this is where the `\tweak` command must be used. Items which may appear more than once at the same musical moment include the following:

- note heads of notes inside a chord
- articulation signs on a single note
- ties between notes in a chord
- tuplet brackets starting at the same time

In this example, the color of one note head and the type of another note head are modified within a single chord:

```
< c
  \tweak #'color #red
  d
  g
  \tweak #'duration-log #1
  a
> 4
```



`\tweak` can be used to modify slurs:

```
c-\tweak #'thickness #5 ( d e f)
```



For the `\tweak` command to work, it must remain immediately adjacent to the object to which it is to apply after the input file has been converted to a music stream. At times, LilyPond may insert additional items into the music stream during the parsing process. For example, when a note that is not explicitly part of a chord will be placed in a chord by LilyPond, so notes to be modified with `\tweak` must be placed inside a chord construct:

```
\tweak #'color #red c4
<\tweak #'color #red c>4
```



The `\tweak` command cannot be used to modify any item that does not appear explicitly in the input file. In particular it cannot be used to modify stems, beams or accidentals directly, since these are generated later by note heads, rather than by music elements in the input stream. Nor can `\tweak` be used to modify clefs or time signatures, since these become separated from any preceding `\tweak` command in the input stream by the automatic insertion of extra elements required to specify the context.

Several `\tweak` commands may be placed before a notational element – all affect it:

```
c
-\tweak #'style #'dashed-line
-\tweak #'dash-fraction #0.2
-\tweak #'thickness #3
-\tweak #'color #red
\glissando
f'
```



The music stream which is generated from a section of an input file, including any automatically inserted elements, may be examined, see [Section “Displaying music expressions” in \*Extending\*](#). This may be helpful in determining what may be modified by a `\tweak` command, or in determining how to adjust the input to make a `\tweak` apply.

## See also

Learning Manual: [Section “Tweaking methods” in \*Learning Manual\*](#).

Extending: [Section “Displaying music expressions” in \*Extending\*](#).

## Known issues and warnings

The `\tweak` command cannot be used inside a variable.

The `\tweak` commands cannot be used in `\lyricmode`.

The `\tweak` command will apply to only the first of several generated ties in a chord.

### 5.3.5 `\set` vs. `\override`

### 5.3.6 Modifying alists

Some user-configurable properties are internally represented as *alists* (association lists), which store pairs of *keys* and *values*. The structure of an alist is:

```
'((key1 . value1)
  (key2 . value2)
  (key3 . value3)
  ...)
```

If an alist is a grob property or `\paper` variable, its keys can be modified individually without affecting other keys.

For example, to reduce the space between adjacent staves in a staff-group, use the `staff-staff-spacing` property of the `StaffGrouper` grob. The property is an alist with four keys: `basic-distance`, `minimum-distance`, `padding`, and `stretchability`. The standard settings for this property are listed in the “Backend” section of the Internals Reference (see [Section “StaffGrouper” in Internals Reference](#)):

```
'((basic-distance . 9)
  (minimum-distance . 7)
  (padding . 1)
  (stretchability . 5))
```

One way to bring the staves closer together is by reducing the value of the `basic-distance` key (9) to match the value of `minimum-distance` (7). To modify a single key individually, use a *nested declaration*:

```
% default space between staves
\new PianoStaff <<
  \new Staff { \clef treble c''1 }
  \new Staff { \clef bass c1 }
>>


% reduced space between staves
\new PianoStaff \with {
  % this is the nested declaration
  \override StaffGrouper #'staff-staff-spacing #'basic-distance = #7
} <<
  \new Staff { \clef treble c''1 }
  \new Staff { \clef bass c1 }
>>
```



Using a nested declaration will update the specified key (such as `basic-distance` in the above example) without altering any other keys already set for the same property.

Now suppose we want the staves to be as close as possible without overlapping. The simplest way to do this is to set all four alist keys to zero. However, it is not necessary to enter four nested declarations, one for each key. Instead, the property can be completely re-defined with one declaration, as an alist:

```
\new PianoStaff \with {
  \override StaffGrouper #'staff-staff-spacing =
    #'((basic-distance . 0)
      (minimum-distance . 0)
      (padding . 0)
      (stretchability . 0))
} <<
  \new Staff { \clef treble c''1 }
  \new Staff { \clef bass c1 }
>>
```



Note that any keys not explicitly listed in the alist definition will be reset to their *default-when-unset* values. In the case of `staff-staff-spacing`, any unset key-values would be reset to zero (except `stretchability`, which takes the value of `basic-distance` when unset). Thus the following two declarations are equivalent:

```
\override StaffGrouper #'staff-staff-spacing =
  #'((basic-distance . 7))

\override StaffGrouper #'staff-staff-spacing =
  #'((basic-distance . 7)
    (minimum-distance . 0)
    (padding . 0)
    (stretchability . 7))
```

One (possibly unintended) consequence of this is the removal of any standard settings that are set in an initialization file and loaded each time an input file is compiled. In the above example, the standard settings for `padding` and `minimum-distance` (defined in ‘`scm/define-grobs.scm`’) are reset to their default-when-unset values (zero for both keys). Defining a property or variable as an alist (of any size) will always reset all unset key-values to their default-when-unset values. Unless this is the intended result, it is safer to update key-values individually with a nested declaration.

**Note:** Nested declarations will not work for context property alists (such as `beamExceptions`, `keySignature`, `timeSignatureSettings`, etc.). These properties can only be modified by completely re-defining them as alists.

## 5.4 Useful concepts and properties

### 5.4.1 Input modes

The way in which the notation contained within an input file is interpreted is determined by the current input mode.

#### Chord mode

This is activated with the `\chordmode` command, and causes input to be interpreted with the syntax of chord notation, see [Section 2.7 \[Chord notation\]](#), page 367. Chords are rendered as notes on a staff.

Chord mode is also activated with the `\chords` command. This also creates a new `ChordNames` context and causes the following input to be interpreted with the syntax of chord notation and rendered as chord names in the `ChordNames` context, see [\[Printing chord names\]](#), page 373.

### Drum mode

This is activated with the `\drummode` command, and causes input to be interpreted with the syntax of drum notation, see [\[Basic percussion notation\]](#), page 346.

Drum mode is also activated with the `\drums` command. This also creates a new `DrumStaff` context and causes the following input to be interpreted with the syntax of drum notation and rendered as drum symbols on a drum staff, see [\[Basic percussion notation\]](#), page 346.

### Figure mode

This is activated with the `\figuremode` command, and causes input to be interpreted with the syntax of figured bass, see [\[Entering figured bass\]](#), page 381.

Figure mode is also activated with the `\figures` command. This also creates a new `FiguredBass` context and causes the following input to be interpreted with the figured bass syntax and rendered as figured bass symbols in the `FiguredBass` context, see [\[Introduction to figured bass\]](#), page 381.

### Fret and tab modes

There are no special input modes for entering fret and tab symbols.

To create tab diagrams, enter notes or chords in note mode and render them in a `TabStaff` context, see [\[Default tablatures\]](#), page 303.

To create fret diagrams above a staff, you have two choices. You can either use the `FretBoards` context (see [\[Automatic fret diagrams\]](#), page 337 or you can enter them as a markup above the notes using the `\fret-diagram` command (see [\[Fret diagram markups\]](#), page 317).

### Lyrics mode

This is activated with the `\lyricmode` command, and causes input to be interpreted as lyric syllables with optional durations and associated lyric modifiers, see [Section 2.1 \[Vocal music\]](#), page 226.

Lyric mode is also activated with the `\addlyrics` command. This also creates a new `Lyrics` context and an implicit `\lyricsto` command which associates the following lyrics with the preceding music.

### Markup mode

This is activated with the `\markup` command, and causes input to be interpreted with the syntax of markup, see [Section A.9 \[Text markup commands\]](#), page 609.

### Note mode

This is the default mode or it may be activated with the `\notemode` command. Input is interpreted as pitches, durations, markup, etc and typeset as musical notation on a staff.

It is not normally necessary to specify note mode explicitly, but it may be useful to do so in certain situations, for example if you are in lyric mode, chord mode or any other mode and want to insert something that only can be done with note mode syntax.

For example, to indicate dynamic markings for the verses of a choral pieces it is necessary to enter note mode to interpret the markings:


```
{ c4 c4 c4 c4 }
\addlyrics {
```



```

\notemode{\set stanza = \markup{ \dynamic f 1. } }
To be sung loudly
}
\addlyrics {
\notemode{\set stanza = \markup{ \dynamic p 2. } }
To be sung quietly
}

```



### 5.4.2 Direction and placement

In typesetting music the direction and placement of many items is a matter of choice. For example, the stems of notes can be directed up or down; lyrics, dynamics, and other expressive marks may be placed above or below the staff; text may be aligned left, right or center; etc. Most of these choices may be left to be determined automatically by LilyPond, but in some cases it may be desirable to force a particular direction or placement.

#### Articulation direction indicators

By default some directions are always up or always down (e.g. dynamics or fermata), while other things can alternate between up or down based on the stem direction (like slurs or accents).

The default action may be overridden by prefixing the articulation by a *direction indicator*. Three direction indicators are available: `^` (meaning “up”), `_` (meaning “down”) and `-` (meaning “use default direction”). The direction indicator can usually be omitted, in which case `-` is assumed, but a direction indicator is **always** required before

- `\tweak` commands
- `\markup` commands
- `\tag` commands
- string markups, e.g. `-"string"`
- fingering instructions, e.g. `-1`
- articulation shortcuts, e.g. `-. , -> , --`

Direction indicators affect only the next note:

```

c2( c)
c2_( c)
c2( c)
c2^( c)

```



#### The direction property

The position or direction of many layout objects is controlled by the `direction` property.

The value of the `direction` property may be set to `1`, meaning “up” or “above”, or to `-1`, meaning “down” or “below”. The symbols `UP` and `DOWN` may be used instead of `1` and `-1` respectively. The default direction may be specified by setting `direction` to `0` or `CENTER`.

Alternatively, in many cases predefined commands exist to specify the direction. These are all of the form

`\xxxUp`, `\xxxDown`, `\xxxNeutral`

where `\xxxNeutral` means “use the default direction”. See [Section “Within-staff objects” in Learning Manual](#).

In a few cases, arpeggio being the only common example, the value of the `direction` property specifies whether the object is to be placed to the right or left of the parent object. In this case `-1` or `LEFT` means “to the left” and `1` or `RIGHT` means “to the right”. `0` or `CENTER` means “use the default” direction, as before.

These indications affect all notes until they are canceled.

```
c2( c)
\slurDown
c2( c)
c2( c)
\slurNeutral
c2( c)
```



### 5.4.3 Distances and measurements

Distances in LilyPond are of two types: absolute and scaled.

Absolute distances are used for specifying margins, indents, and other page layout details, and are by default specified in millimeters. Distances may be specified in other units by following the quantity by `\mm`, `\cm`, `\in` (inches), or `\pt` (points, 1/72.27 of an inch). Page layout distances can also be specified in scalable units (see the following paragraph) by appending `\staff-space` to the quantity. Page layout is described in detail in [Section 4.1 \[Page layout\]](#), page 469.

Scaled distances are always specified in units of the staff-space or, rarely, the half staff-space. The staff-space is the distance between two adjacent staff lines. The default value can be changed globally by setting the global staff size, or it can be overridden locally by changing the `staff-space` property of `StaffSymbol`. Scaled distances automatically scale with any change to the either the global staff size or the `staff-space` property of `StaffSymbol`, but fonts scale automatically only with changes to the global staff size. The global staff size thus enables the overall size of a rendered score to be easily varied. For the methods of setting the global staff size see [Section 4.2.2 \[Setting the staff size\]](#), page 479.

If just a section of a score needs to be rendered to a different scale, for example an ossia section or a footnote, the global staff size cannot simply be changed as this would affect the entire score. In such cases the change in size is made by overriding both the `staff-space` property of `StaffSymbol` and the size of the fonts. A Scheme function, `magstep`, is available to convert from a font size change to the equivalent change in `staff-space`. For an explanation and an example of its use, see [Section “Length and thickness of objects” in Learning Manual](#).

#### See also

Learning Manual: [Section “Length and thickness of objects” in Learning Manual](#).

Notation Reference: [Section 4.1 \[Page layout\]](#), page 469, [Section 4.2.2 \[Setting the staff size\]](#), page 479.

### 5.4.4 Staff symbol properties

The vertical position of staff lines and the number of staff lines can be defined at the same time. As the following example shows, note positions are not influenced by the staff line positions.

**Note:** The `'line-positions` property overrides the `'line-count` property. The number of staff lines is implicitly defined by the number of elements in the list of values for `'line-positions`.

```
\new Staff \with {
  \override StaffSymbol #'line-positions = #'(7 3 0 -4 -6 -7)
}
{ a4 e' f b | d1 }
```



The width of a staff can be modified. The units are staff spaces. The spacing of objects inside the staff is not affected by this setting.

```
\new Staff \with {
  \override StaffSymbol #'width = #23
}
{ a4 e' f b | d1 }
```



### 5.4.5 Spanners

Many objects of musical notation extend over several notes or even several bars. Examples are slurs, beams, tuplet brackets, volta repeat brackets, crescendi, trills, and glissandi. Such objects are collectively called “spanners”, and have special properties to control their appearance and behaviour. Some of these properties are common to all spanners; others are restricted to a sub-set of the spanners.

All spanners support the `spanner-interface`. A few, essentially those that draw a straight line between the two objects, support in addition the `line-spanner-interface`.

### Using the spanner-interface

This interface provides two properties that apply to several spanners.


*The minimum-length property*

The minimum length of the spanner is specified by the `minimum-length` property. Increasing this usually has the necessary effect of increasing the spacing of the notes between the two end points. However, this override has no effect on many spanners, as their length is determined by other considerations. A few examples where it is effective are shown below.

```
a~a
a
% increase the length of the tie
-\tweak #'minimum-length #5
~a
```



```
a1
\compressFullBarRests
R1*23
% increase the length of the rest bar
\once \override MultiMeasureRest #'minimum-length = #20
R1*23
a1
```



```
a \< a a a \!
% increase the length of the hairpin
\override Hairpin #'minimum-length = #20
a \< a a a \!
```



This override can also be used to increase the length of slurs and phrasing slurs:

```
a( a)
a
-\tweak #'minimum-length #5
( a)

a\(( a\))
a
-\tweak #'minimum-length #5
\(( a\))
```



For some layout objects, the `minimum-length` property becomes effective only if the `set-spacing-rods` procedure is called explicitly. To do this, the `springs-and-rods` property should be set to `ly:spanner::set-spacing-rods`. For example, the minimum length of a glissando has no effect unless the `springs-and-rods` property is set:

```
% default
e \glissando c'

% not effective alone
\once \override Glissando #'minimum-length = #20
e, \glissando c'

% effective only when both overrides are present
\once \override Glissando #'minimum-length = #20
\once \override Glissando #'springs-and-rods = #ly:spanner::set-spacing-rods
e, \glissando c'
```



The same is true of the Beam object:

```
% not effective alone
\once \override Beam #'minimum-length = #20
e8 e e e
```

```
% effective only when both overrides are present
\once \override Beam #'minimum-length = #20
\once \override Beam #'springs-and-rods = #ly:spanner::set-spacing-rods
e8 e e e
```



### *The to-barline property*

The second useful property of the `spanner-interface` is `to-barline`. By default this is true, causing hairpins and other spanners which are terminated on the first note of a measure to end instead on the immediately preceding bar line. If set to false, the spanner will extend beyond the bar line and end on the note itself:

```
a \< a a a a \! a a a \break
\override Hairpin #'to-barline = ##f
a \< a a a a \! a a a
```



This property is not effective for all spanners. For example, setting it to `#t` has no effect on slurs or phrasing slurs or on other spanners for which terminating on the bar line would not be meaningful.

## Using the line-spanner-interface

Objects which support the `line-spanner-interface` include

- `DynamicTextSpanner`
- `Glissando`
- `TextSpanner`
- `TrillSpanner`
- `VoiceFollower`

The routine responsible for drawing the stencils for these spanners is `ly:line-interface::print`. This routine determines the exact location of the two end points and draws a line between them, in the style requested. The locations of the two end points of the spanner are computed on-the-fly, but it is possible to override their Y-coordinates. The properties which need to be specified are nested two levels down within the property hierarchy, but the syntax of the `\override` command is quite simple:

```
e2 \glissando b
\once \override Glissando #'(bound-details left Y) = #3
\once \override Glissando #'(bound-details right Y) = #-2
e2 \glissando b
```



The units for the `Y` property are **staff-spaces**, with the center line of the staff being the zero point. For the glissando, this is the value for `Y` at the `X`-coordinate corresponding to the center point of each note head, if the line is imagined to be extended to there.

If `Y` is not set, the value is computed from the vertical position of the corresponding attachment point of the spanner.

In case of a line break, the values for the end points are specified by the **left-broken** and **right-broken** sub-lists of **bound-details**. For example:

```
\override Glissando #'breakable = ##t
\override Glissando #'(bound-details right-broken Y) = #-3
c1 \glissando \break
f1
```



A number of further properties of the **left** and **right** sub-lists of the **bound-details** property may be modified in the same way as `Y`:

**Y** This sets the `Y`-coordinate of the end point, in **staff-spaces** offset from the staff center line. By default, it is the center of the bound object, so a glissando points to the vertical center of the note head.

For horizontal spanners, such as text spanners and trill spanners, it is hardcoded to 0.

**attach-dir**

This determines where the line starts and ends in the `X`-direction, relative to the bound object. So, a value of `-1` (or **LEFT**) makes the line start/end at the left side of the note head it is attached to.

**X** This is the absolute `X`-coordinate of the end point. It is usually computed on the fly, and overriding it has little useful effect.

**stencil** Line spanners may have symbols at the beginning or end, which is contained in this sub-property. This is for internal use; it is recommended that **text** be used instead.

**text** This is a markup that is evaluated to yield the stencil. It is used to put *cresc.*, *tr* and other text on horizontal spanners.

```
\override TextSpanner #'(bound-details left text)
  = \markup { \small \bold Slower }
c2\startTextSpan b c a\stopTextSpan
```



stencil-align-dir-y  
stencil-offset

Without setting one of these, the stencil is simply put at the end-point, centered on the line, as defined by the X and Y sub-properties. Setting either `stencil-align-dir-y` or `stencil-offset` will move the symbol at the edge vertically relative to the end point of the line:

```
\override TextSpanner
  #'(bound-details left stencil-align-dir-y) = #-2
\override TextSpanner
  #'(bound-details right stencil-align-dir-y) = #UP

\override TextSpanner
  #'(bound-details left text) = #"ggg"
\override TextSpanner
  #'(bound-details right text) = #"hhh"
c4~\startTextSpan c c c \stopTextSpan
```



Note that negative values move the text *up*, contrary to the effect that might be expected, as a value of -1 or DOWN means align the *bottom* edge of the text with the spanner line. A value of 1 or UP aligns the top edge of the text with the spanner line.

**arrow** Setting this sub-property to `#t` produces an arrowhead at the end of the line.

**padding** This sub-property controls the space between the specified end point of the line and the actual end. Without padding, a glissando would start and end in the center of each note head.

The music function `\endSpanners` terminates the spanner which starts on the immediately following note prematurely. It is terminated after exactly one note, or at the following bar line if `to-barline` is true and a bar line occurs before the next note.

```
\endSpanners
c2 \startTextSpan c2 c2
\endSpanners
c2 \< c2 c2
```



When using `\endSpanners` it is not necessary to close `\startTextSpan` with `\stopTextSpan`, nor is it necessary to close hairpins with `\!`.

## See also

Internals Reference: [Section “TextSpanner”](#) in *Internals Reference*, [Section “Glissando”](#) in *Internals Reference*, [Section “VoiceFollower”](#) in *Internals Reference*, [Section “TrillSpanner”](#) in *Internals Reference*, [Section “line-spanner-interface”](#) in *Internals Reference*.

### 5.4.6 Visibility of objects

There are four main ways in which the visibility of layout objects can be controlled: their stencil can be removed, they can be made transparent, they can be colored white, or their `break-visibility` property can be overridden. The first three apply to all layout objects; the last to just a few – the *breakable* objects. The Learning Manual introduces these four techniques, see [Section “Visibility and color of objects”](#) in *Learning Manual*.

There are also a few other techniques which are specific to certain layout objects. These are covered under Special considerations.

## Removing the stencil

Every layout object has a stencil property. By default this is set to the specific function which draws that object. If this property is overridden to `#f` no function will be called and the object will not be drawn. The default action can be recovered with `\revert`.

```
a1 a
\override Score.BarLine #'stencil = ##f
a a
\revert Score.BarLine #'stencil
a a a
```



## Making objects transparent

Every layout object has a transparent property which by default is set to `#f`. If set to `#t` the object still occupies space but is made invisible.

```
a4 a
\once \override NoteHead #'transparent = ##t
a a
```



## Painting objects white

Every layout object has a color property which by default is set to `black`. If this is overridden to `white` the object will be indistinguishable from the white background. However, if the object crosses other objects the color of the crossing points will be determined by the order in which they are drawn, and this may leave a ghostly image of the white object, as shown here:

```
\override Staff.Clef #'color = #white
a1
```






This may be avoided by changing the order of printing the objects. All layout objects have a **layer** property which should be set to an integer. Objects with the lowest value of **layer** are drawn first, then objects with progressively higher values are drawn, so objects with higher values overwrite objects with lower values. By default most objects are assigned a **layer** value of 1, although a few objects, including **StaffSymbol** and **BarLine**, are assigned a value of 0. The order of printing objects with the same value of **layer** is indeterminate.

In the example above the white clef, with a default **layer** value of 1, is drawn after the staff lines (default **layer** value 0), so overwriting them. To change this, the **Clef** object must be given in a lower value of **layer**, say -1, so that it is drawn earlier:

```
\override Staff.Clef #'color = #white
\override Staff.Clef #'layer = #-1
a1
```



## Using break-visibility

Most layout objects are printed only once, but some like bar lines, clefs, time signatures and key signatures, may need to be printed twice when a line break occurs – once at the end of the line and again at the start of the next line. Such objects are called *breakable*, and have a property, the **break-visibility** property to control their visibility at the three positions in which they may appear – at the start of a line, within a line if they are changed, and at the end of a line if a change takes place there.

For example, the time signature by default will be printed at the start of the first line, but nowhere else unless it changes, when it will be printed at the point at which the change occurs. If this change occurs at the end of a line the new time signature will be printed at the start of the next line and a cautionary time signature will be printed at the end of the previous line as well.

This behaviour is controlled by the **break-visibility** property, which is explained in [Section “Visibility and color of objects” in \*Learning Manual\*](#). This property takes a vector of three booleans which, in order, determine whether the object is printed at the end of, within the body of, or at the beginning of a line. Or to be more precise, before a line break, where there is no line break, or after a line break.

Alternatively, these eight combinations may be specified by pre-defined functions, defined in ‘**scm/output-lib.scm**’, where the last three columns indicate whether the layout objects will be visible in the positions shown at the head of the columns:

Function	Vector	Before	At	After
form	form	no	break	break
all-visible	'#(#t #t #t)	yes	yes	yes
begin-of-line-visible	'#(#f #f #t)	no	no	yes
center-visible	'#(#f #t #f)	no	yes	no
end-of-line-visible	'#(#t #f #f)	yes	no	no
begin-of-line-invisible	'#(#t #t #f)	yes	yes	no
center-invisible	'#(#t #f #t)	yes	no	yes
end-of-line-invisible	'#(#f #t #t)	no	yes	yes

all-invisible                    '#(#f #f #f)    no    no    no

The default settings of **break-visibility** depend on the layout object. The following table shows all the layout objects of interest which are affected by **break-visibility** and the default setting of this property:

Layout object	Usual context	Default setting
BarLine	Score	calculated
BarNumber	Score	begin-of-line-visible
BreathingSign	Voice	begin-of-line-invisible
Clef	Staff	begin-of-line-visible
Custos	Staff	end-of-line-visible
DoublePercentRepeat	Voice	begin-of-line-invisible
KeySignature	Staff	begin-of-line-visible
OctavateEight	Staff	begin-of-line-visible
RehearsalMark	Score	end-of-line-invisible
TimeSignature	Staff	all-visible

The example below shows the use of the vector form to control the visibility of bar lines:

```
f4 g a b
f4 g a b
% Remove bar line at the end of the current line
\once \override Score.BarLine #'break-visibility = #'(#f #t #t)
\break
f4 g a b
f4 g a b
```



Although all three components of the vector used to override **break-visibility** must be present, not all of them are effective with every layout object, and some combinations may even give errors. The following limitations apply:

- Bar lines cannot be printed at start of line.
- A bar number cannot be printed at the start of the first line unless it is set to be different from 1.
- Clef – see below
- Double percent repeats are either all printed or all suppressed. Use **begin-of line-invisible** to print and **all-invisible** to suppress.
- Key signature – see below
- OctavateEight – see below

## Special considerations

### *Visibility following explicit changes*

The `break-visibility` property controls the visibility of key signatures and changes of clef only at the start of lines, i.e. after a break. It has no effect on the visibility of the key signature or clef following an explicit key change or an explicit clef change within or at the end of a line. In the following example the key signature following the explicit change to B-flat major is still visible, even though `all-invisible` is set.

```
\key g \major
f4 g a b
% Try to remove all key signatures
\override Staff.KeySignature #'break-visibility = #all-invisible
\key bes \major
f4 g a b
\break
f4 g a b
f4 g a b
```



The visibility of such explicit key signature and clef changes is controlled by the `explicitKeySignatureVisibility` and `explicitClefVisibility` properties. These are the equivalent of the `break-visibility` property and both take a vector of three booleans or the predefined functions listed above, exactly like `break-visibility`. Both are properties of the `Staff` context, not the layout objects themselves, and so they are set using the `\set` command. Both are set by default to `all-visible`. These properties control only the visibility of key signatures and clefs resulting from explicit changes and do not affect key signatures and clefs at the beginning of lines; `break-visibility` must still be overridden in the appropriate object to remove these.

```
\key g \major
f4 g a b
\set Staff.explicitKeySignatureVisibility = #all-invisible
\override Staff.KeySignature #'break-visibility = #all-invisible
\key bes \major
f4 g a b \break
f4 g a b
f4 g a b
```



*Visibility of cautionary accidentals*

To remove the cautionary accidentals printed at an explicit key change, set the Staff context property `printKeyCancellation` to `#f`:

```
\key g \major
f4 g a b
\set Staff.explicitKeySignatureVisibility = #all-invisible
\set Staff.printKeyCancellation = ##f
\override Staff.KeySignature #'break-visibility = #all-invisible
\key bes \major
f4 g a b \break
f4 g a b
f4 g a b
```



With these overrides only the accidentals before the notes remain to indicate the change of key.

*Automatic bars*

As a special case, the printing of bar lines can also be turned off by setting the `automaticBars` property in the Score context. If set to `#f`, bar lines will not be printed automatically; they must be explicitly created with a `\bar` command. Unlike the `\cadenzaOn` predefined command, measures are still counted. Bar generation will resume according to that count if this property is later set to `#t`. When set to `#f`, line breaks can occur only at explicit `\bar` commands.

*Octavated clefs*

The small octavation symbol on octavated clefs is produced by the `OctavateEight` layout object. Its visibility is automatically inherited from the `Clef` object, so it is not necessary to apply any required `break-visibility` overrides to the `OctavateEight` layout objects to suppress octavation symbols for invisible clefs.

For explicit clef changes, the `explicitClefVisibility` property controls both the clef symbol and any octavation symbol associated with it.

**See also**

Learning Manual: [Section “Visibility and color of objects”](#) in *Learning Manual*

**5.4.7 Line styles**

Some performance indications, e.g., *rallentando* and *accelerando* and *trills* are written as text and are extended over many measures with lines, sometimes dotted or wavy.

These all use the same routines as the glissando for drawing the texts and the lines, and tuning their behavior is therefore also done in the same way. It is done with a spanner, and the routine responsible for drawing the spanners is `ly:line-interface::print`. This routine determines the exact location of the two *span points* and draws a line between them, in the style requested.

Here is an example showing the different line styles available, and how to tune them.

```

d2 \glissando d'2
\once \override Glissando #'style = #'dashed-line
d,2 \glissando d'2
\override Glissando #'style = #'dotted-line
d,2 \glissando d'2
\override Glissando #'style = #'zigzag
d,2 \glissando d'2
\override Glissando #'style = #'trill
d,2 \glissando d'2

```



The locations of the end-points of the spanner are computed on-the-fly for every graphic object, but it is possible to override these:

```

e2 \glissando f
\once \override Glissando #'(bound-details right Y) = #-2
e2 \glissando f

```



The value for *Y* is set to -2 for the right end point. The left side may be similarly adjusted by specifying *left* instead of *right*.

If *Y* is not set, the value is computed from the vertical position of the left and right attachment points of the spanner.

Other adjustments of spanners are possible, for details, see [Section 5.4.5 \[Spanners\]](#), page 545.

### 5.4.8 Rotating objects

Both layout objects and elements of markup text can be rotated by any angle about any point, but the method of doing so differs.

#### Rotating layout objects

All layout objects which support the `grob-interface` can be rotated by setting their `rotation` property. This takes a list of three items: the angle of rotation counter-clockwise, and the *x* and *y* coordinates of the point relative to the object's reference point about which the rotation is to be performed. The angle of rotation is specified in degrees and the coordinates in staff-spaces.

The angle of rotation and the coordinates of the rotation point must be determined by trial and error.

There are only a few situations where the rotation of layout objects is useful; the following example shows one situation where they may be:

```

g4\< e' d' f\!
\override Hairpin #'rotation = #'(20 -1 0)
g,,4\< e' d' f\!

```



## Rotating markup

All markup text can be rotated to lie at any angle by prefixing it with the `\rotate` command. The command takes two arguments: the angle of rotation in degrees counter-clockwise and the text to be rotated. The extents of the text are not rotated: they take their values from the extremes of the x and y coordinates of the rotated text. In the following example the `outside-staff-priority` property for text is set to `#f` to disable the automatic collision avoidance, which would push some of the text too high.

```
\override TextScript #'outside-staff-priority = ##f
g4^\markup { \rotate #30 "a G" }
b^\markup { \rotate #30 "a B" }
des^\markup { \rotate #30 "a D-Flat" }
fis^\markup { \rotate #30 "an F-Sharp" }
```



## 5.5 Advanced tweaks

This section discusses various approaches to fine tuning the appearance of the printed score.

### See also

Learning Manual: [Section “Tweaking output”](#) in *Learning Manual*, [Section “Other sources of information”](#) in *Learning Manual*.

Notation Reference: [Section 5.2 \[Explaining the Internals Reference\]](#), page 530, [Section 5.3 \[Modifying properties\]](#), page 534.

Installed Files: `'scm/define-grobs.scm'`.

Snippets: [Section “Tweaks and overrides”](#) in *Snippets*.

Extending: [Section “Interfaces for programmers”](#) in *Extending*.

Internals Reference: [Section “All layout objects”](#) in *Internals Reference*.

### 5.5.1 Aligning objects

Graphical objects which support the `self-alignment-interface` and/or the `side-position-interface` can be aligned to a previously placed object in a variety of ways. For a list of these objects, see [Section “self-alignment-interface”](#) in *Internals Reference* and [Section “side-position-interface”](#) in *Internals Reference*.

All graphical objects have a reference point, a horizontal extent and a vertical extent. The horizontal extent is a pair of numbers giving the displacements from the reference point of the left and right edges, displacements to the left being negative. The vertical extent is a pair of numbers giving the displacement from the reference point to the bottom and top edges, displacements down being negative.

An object’s position on a staff is given by the values of the `X-offset` and `Y-offset` properties. The value of `X-offset` gives the displacement from the X coordinate of the reference point of the parent object, and the value of `Y-offset` gives the displacement from the center line of the staff. The values of `X-offset` and `Y-offset` may be set directly or may be set to be calculated by procedures in order to achieve alignment with the parent object.

**Note:** Many objects have special positioning considerations which cause any setting of `X-offset` or `Y-offset` to be ignored or modified, even though the object supports the `self-alignment-interface`. Overriding the `X-offset` or `Y-offset` properties to a fixed value causes the respective `self-alignment` property to be disregarded.

For example, an accidental can be repositioned vertically by setting `Y-offset` but any changes to `X-offset` have no effect.

Rehearsal marks may be aligned with breakable objects such as bar lines, clef symbols, time signature symbols and key signatures. There are special properties to be found in the `break-aligned-interface` for positioning rehearsal marks on such objects.


See also

[Using the `break-alignable-interface`], page 559, Section “Callback functions” in *Extending*.

Setting `X-offset` and `Y-offset` directly

Numerical values may be given to the `X-offset` and `Y-offset` properties of many objects. The following example shows three notes with the default fingering position and the positions with `X-offset` and `Y-offset` modified.

```
a-3
a
-\tweak #'X-offset #0
-\tweak #'Y-offset #0
-3
a
-\tweak #'X-offset #-1
-\tweak #'Y-offset #1
-3
```



Using the `side-position-interface`

An object which supports the `side-position-interface` can be placed next to its parent object so that the specified edges of the two objects touch. The object may be placed above, below, to the right or to the left of the parent. The parent cannot be specified; it is determined by the order of elements in the input stream. Most objects have the associated note head as their parent.

The values of the `side-axis` and `direction` properties determine where the object is to be placed, as follows:

side-axis property	direction property	Placement
0	-1	left
0	1	right
1	-1	below
1	1	above

When `side-axis` is 0, `X-offset` should be set to the procedure `ly:side-position-interface::x-aligned-side`. This procedure will return the

correct value of `X-offset` to place the object to the left or right side of the parent according to value of `direction`.

When `side-axis` is 1, `Y-offset` should be set to the procedure `ly:side-position-interface::y-aligned-side`. This procedure will return the correct value of `Y-offset` to place the object to the top or bottom of the parent according to value of `direction`.


## Using the self-alignment-interface

### *Self-aligning objects horizontally*

The horizontal alignment of an object which supports the `self-alignment-interface` is controlled by the value of the `self-alignment-X` property, provided the object's `X-offset` property is set to `ly:self-alignment-interface::x-aligned-on-self`. `self-alignment-X` may be given any real value, in units of half the total X extent of the object. Negative values move the object to the right, positive to the left. A value of 0 centers the object on the reference point of its parent, a value of -1 aligns the left edge of the object on the reference point of its parent, and a value of 1 aligns the right edge of the object on the reference point of its parent. The symbols `LEFT`, `CENTER`, and `RIGHT` may be used instead of the values -1, 0, and 1, respectively.

Normally the `\override` command would be used to modify the value of `self-alignment-X`, but the `\tweak` command can be used to separately align several annotations on a single note:

```
a'
-\tweak #'self-alignment-X #-1
^"left-aligned"
-\tweak #'self-alignment-X #0
^"center-aligned"
-\tweak #'self-alignment-X #RIGHT
^"right-aligned"
-\tweak #'self-alignment-X #-2.5
^"aligned further to the right"
```



### *Self-aligning objects vertically*

Objects may be aligned vertically in an analogous way to aligning them horizontally if the `Y-offset` property is set to `ly:self-alignment-interface::y-aligned-on-self`. However, other mechanisms are often involved in vertical alignment: the value of `Y-offset` is just one variable taken into account. This may make adjusting the value of some objects tricky. The units are just half the vertical extent of the object, which is usually quite small, so quite large numbers may be required. A value of -1 aligns the lower edge of the object with the reference point of the parent object, a value of 0 aligns the center of the object with the reference point of the parent, and a value of 1 aligns the top edge of the object with the reference point of the parent. The symbols `DOWN`, `CENTER`, and `UP` may be substituted for -1, 0, and 1, respectively.

### *Self-aligning objects in both directions*

By setting both `X-offset` and `Y-offset`, an object may be aligned in both directions simultaneously.



The following example shows how to adjust a fingering mark so that it nestles close to the note head.

```
a
-\tweak #'self-alignment-X #0.5 % move horizontally left
-\tweak #'Y-offset #ly:self-alignment-interface::y-aligned-on-self
-\tweak #'self-alignment-Y #-1 % move vertically up
-3 % third finger
```




### Using the break-alignable-interface

Rehearsal marks and bar numbers may be aligned with notation objects other than bar lines. These objects include ambitus, breathing-sign, clef, custos, staff-bar, left-edge, key-cancellation, key-signature, and time-signature.

By default, rehearsal marks and bar numbers will be horizontally centered above the object:

```
% The rehearsal mark will be centered above the Clef
\override Score.RehearsalMark #'break-align-symbols = #'(clef)
\key a \major
\clef treble
\mark ""
e1
% The rehearsal mark will be centered above the Time Signature
\override Score.RehearsalMark #'break-align-symbols = #'(time-signature)
\key a \major
\clef treble
\time 3/4
\mark ""
e2.
% The rehearsal mark will be centered above the Breath Mark
\override Score.RehearsalMark #'break-align-symbols = #'(breathing-sign)
\key a \major
\clef treble
\time 4/4
e1
\breathe
\mark ""
```




A list of possible target alignment objects may be specified. If some of the objects are invisible at that point due to the setting of **break-visibility** or the explicit visibility settings for keys and clefs, the rehearsal mark or bar number is aligned to the first object in the list which is visible. If no objects in the list are visible the object is aligned to the bar line. If the bar line is invisible the object is aligned to the place where the bar line would be.

```
% The rehearsal mark will be centered above the Key Signature
\override Score.RehearsalMark #'break-align-symbols = #'(key-signature clef)
```

```

\key a \major
\clef treble
\mark ""
e1
% The rehearsal mark will be centered above the Clef
\set Staff.explicitKeySignatureVisibility = #all-invisible
\override Score.RehearsalMark #'break-align-symbols = #'(key-signature clef)
\key a \major
\clef bass
\mark ""
gis,,1
% The rehearsal mark will be centered above the Bar Line
\set Staff.explicitKeySignatureVisibility = #all-invisible
\set Staff.explicitClefVisibility = #all-invisible
\override Score.RehearsalMark #'break-align-symbols = #'(key-signature clef)
\key a \major
\clef treble
\mark ""
e''1

```




The alignment of the rehearsal mark relative to the notation object can be changed, as shown in the following example. In a score with multiple staves, this setting should be done for all the staves.

```


% The RehearsalMark will be centered above the Key Signature
\override Score.RehearsalMark #'break-align-symbols = #'(key-signature)
\key a \major
\clef treble
\time 4/4
\mark ""
e1
% The RehearsalMark will be aligned with the left edge of the Key Signature
\once \override Score.KeySignature #'break-align-anchor-alignment = #LEFT
\mark ""
\key a \major
e1
% The RehearsalMark will be aligned with the right edge of the Key Signature
\once \override Score.KeySignature #'break-align-anchor-alignment = #RIGHT
\key a \major
\mark ""
e1

```



The rehearsal mark can also be offset to the right or left of the left edge by an arbitrary amount. The units are staff-spaces:

```
% The RehearsalMark will be aligned with the left edge of the Key Signature
% and then shifted right by 3.5 staff-spaces
\override Score.RehearsalMark #'break-align-symbols = #'(key-signature)
\once \override Score.KeySignature #'break-align-anchor = #3.5
\key a \major
\mark ""
e1
% The RehearsalMark will be aligned with the left edge of the Key Signature
% and then shifted left by 2 staff-spaces
\once \override Score.KeySignature #'break-align-anchor = #-2
\key a \major
\mark ""
e1
```



### 5.5.2 Vertical grouping of grobs

The `VerticalAlignment` and `VerticalAxisGroup` grobs work together. `VerticalAxisGroup` groups together different grobs like `Staff`, `Lyrics`, etc. `VerticalAlignment` then vertically aligns the different grobs grouped together by `VerticalAxisGroup`. There is usually only one `VerticalAlignment` per score but every `Staff`, `Lyrics`, etc. has its own `VerticalAxisGroup`.

### 5.5.3 Modifying stencils

All layout objects have a `stencil` property which is part of the `grob-interface`. By default, this property is usually set to a function specific to the object that is tailor-made to render the symbol which represents it in the output. For example, the standard setting for the `stencil` property of the `MultiMeasureRest` object is `ly:multi-measure-rest::print`.

The standard symbol for any object can be replaced by modifying the `stencil` property to reference a different, specially-written, procedure. This requires a high level of knowledge of the internal workings of LilyPond, but there is an easier way which can often produce adequate results.

This is to set the `stencil` property to the procedure which prints text – `ly:text-interface::print` – and to add a `text` property to the object which is set to contain the markup text which produces the required symbol. Due to the flexibility of markup, much can be achieved – see in particular [\[Graphic notation inside markup\]](#), page 217.

The following example demonstrates this by changing the note head symbol to a cross within a circle.

```
Xin0 = {
  \once \override NoteHead #'stencil = #ly:text-interface::print
  \once \override NoteHead #'text = \markup {
    \combine
      \halign #-0.7 \draw-circle #0.85 #0.2 ##f
      \musicglyph #"noteheads.s2cross"
  }
}
\relative c' {
  a a \Xin0 a a
}
```



Any of the glyphs in the feta Font can be supplied to the `\musicglyph` markup command – see [Section A.7 \[The Feta font\]](#), page 589.

## See also

Notation Reference: [\[Graphic notation inside markup\]](#), page 217, [Section 1.8.2 \[Formatting text\]](#), page 210, [Section A.9 \[Text markup commands\]](#), page 609, [Section A.7 \[The Feta font\]](#), page 589.

### 5.5.4 Modifying shapes

#### Modifying ties and slurs

Ties, slurs and phrasing slurs are drawn as third-order Bézier curves. If the shape of the tie or slur which is calculated automatically is not optimum, the shape may be modified manually by explicitly specifying the four control points required to define a third-order Bézier curve.

Third-order or cubic Bézier curves are defined by four control points. The first and fourth control points are precisely the starting and ending points of the curve. The intermediate two control points define the shape. Animations showing how the curve is drawn can be found on the web, but the following description may be helpful. The curve starts from the first control point heading directly towards the second, gradually bending over to head towards the third and continuing to bend over to head towards the fourth, arriving there travelling directly from the third control point. The curve is entirely contained in the quadrilateral defined by the four control points.

Here is an example of a case where the tie is not optimum, and where `\tieDown` would not help.

```
<<
{ e1~ e }
\\
{ r4 <g c,> <g c,> <g c,> }
>>
```



One way of improving this tie is to manually modify its control points, as follows.

The coordinates of the Bézier control points are specified in units of staff-spaces. The X coordinate is relative to the reference point of the note to which the tie or slur is attached, and the Y coordinate is relative to the staff center line. The coordinates are entered as a list of four pairs of decimal numbers (reals). One approach is to estimate the coordinates of the two end points, and then guess the two intermediate points. The optimum values are then found by trial and error.

It is useful to remember that a symmetric curve requires symmetric control points, and that Bézier curves have the useful property that transformations of the curve such as translation, rotation and scaling can be achieved by applying the same transformation to the curve's control points.

For the example above the following override gives a satisfactory tie. Note the placement – it has to be immediately before the note to which the start of the tie (or slur) is attached.

```
<<
{
  \once \override Tie
    #'control-points = #'((1 . -1) (3 . 0.6) (12.5 . 0.6) (14.5 . -1))
    e1 ~ e
}
\\
{ r4 <g c,> <g c,> <g c,> }
>>
```



## Known issues and warnings

It is not possible to modify shapes of ties or slurs by changing the `control-points` property if there are multiple ties or slurs at the same musical moment – the `\tweak` command will also not work in this case. However, the `tie-configuration` property of `TieColumn` can be overridden to set start line and direction as required.

## See also

Internals Reference: [Section “TieColumn” in Internals Reference](#).

### 5.5.5 Unpure-pure containers

Unpure-pure containers are useful for overriding *Y-axis* spacing calculations - specifically `Y-offset` and `Y-extent` - with a Scheme function instead of a literal (i.e. a number or pair).

For certain grobs, the `Y-extent` is based on the `stencil` property, overriding the `stencil` property of one of these will require an additional `Y-extent` override with an unpure-pure container. When a function overrides a `Y-offset` and/or `Y-extent` it is assumed that this will trigger line breaking calculations too early during compilation. So the function is not evaluated at all (usually returning a value of `0` or `'(0 . 0)`) which can result in collisions. A ‘pure’ function will not affect properties, objects or grob suicides and therefore will always have its Y-axis-related evaluated correctly.

Currently, there are about thirty functions that are already considered ‘pure’ and Unpure-pure containers are a way to set functions not on this list as ‘pure’. The ‘pure’ function is evaluated *before* any line-breaking and so the horizontal spacing can be adjusted ‘in time’. The ‘unpure’ function is then evaluated *after* line breaking.

**Note:** As it is difficult to always know which functions are on this list we recommend that any ‘pure’ functions you create do not use `Beam` or `VerticalAlignment` grobs.

An unpure-pure container is constructed as follows;

```
(ly:make-unpure-pure-container f0 f1)
```

where `f0` is a function taking  $n$  arguments ( $n \geq 1$ ) and the first argument must always be the grob. This is the function that gives the actual result. `f1` is the function being labeled as ‘pure’ that takes  $n + 2$  arguments. Again, the first argument must always still be the grob but the second and third are ‘start’ and ‘end’ arguments.

*start* and *end* are, for all intents and purposes, dummy values that only matter for **Spanners** (i.e **Hairpin** or **Beam**), that can return different height estimations based on a starting and ending column.

The rest are the other arguments to the first function (which may be none if  $n = 1$ ).

The results of the second function are used as an approximation of the value needed which is then used by the first function to get the real value which is then used for fine-tuning much later during the spacing process.

```
#(define (square-line-circle-space grob)
  (let* ((pitch (ly:event-property (ly:grob-property grob 'cause) 'pitch))
        (notename (ly:pitch-notename pitch)))
    (if (= 0 (modulo notename 2))
        (make-circle-stencil 0.5 0.0 #t)
        (make-filled-box-stencil '(0 . 1.0)
                                   '(-0.5 . 0.5))))))

squareLineCircleSpace = {
  \override NoteHead #'stencil = #square-line-circle-space
}

smartSquareLineCircleSpace = {
  \squareLineCircleSpace
  \override NoteHead #'Y-extent =
    #(ly:make-unpure-pure-container
      ly:grob::stencil-height
      (lambda (grob start end) (ly:grob::stencil-height grob)))
}

\new Voice \with { \remove "Stem_engraver" }
\relative c'' {
  \squareLineCircleSpace
  cis4 ces cisis c
  \smartSquareLineCircleSpace
  cis4 ces cisis c
}
```



In the first measure, without the unpure-pure container, the spacing engine does not know the width of the note head and lets it collide with the accidentals. In the second measure, with unpure-pure containers, the spacing engine knows the width of the note heads and avoids the collision by lengthening the line accordingly.

Usually for simple calculations nearly-identical functions for both the ‘unpure’ and ‘pure’ parts can be used, by only changing the number of arguments passed to, and the scope of, the function.

**Note:** If a function is labeled as ‘pure’ and it turns out not to be, the results can be unexpected.

## 5.6 Using music functions

Where tweaks need to be reused with different music expressions, it is often convenient to make the tweak part of a *music function*. In this section, we discuss only *substitution* functions, where the object is to substitute a variable into a piece of LilyPond input code. Other more complex functions are described in [Section “Music functions” in \*Extending\*](#).

### 5.6.1 Substitution function syntax

Making a function that substitutes a variable into LilyPond code is easy. The general form of these functions is

```
function =
#(define-music-function
  (parser location arg1 arg2 ...)
  (type1? type2? ...)
  #{
    ...music...
  #})
```

where

*argN*                                      *nth* argument

*typeN?*                                      a scheme *type predicate* for which *argN* must return *#t*.

*...music...*                                      normal LilyPond input, using \$ (in places where only LilyPond constructs are allowed) or # (to use it as a Scheme value or music function argument) to reference arguments (eg. '#arg1').

The *parser* and *location* arguments are mandatory, and are used in some advanced situations as described in the ‘Extending’ manual (see [Section “Music functions” in \*Extending\*](#)). For substitution functions, just be sure to include them.

The list of type predicates is also required. Some of the most common type predicates used in music functions are:

```
boolean?
cheap-list? (use instead of ‘list?’
  for faster processing)
ly:duration?
ly:music?
ly:pitch?
markup?
number?
pair?
string?
symbol?
```

For a list of available type predicates, see [Section A.19 \[Predefined type predicates\]](#), page 695. User-defined type predicates are also allowed.

**See also**

Notation Reference: [Section A.19 \[Predefined type predicates\]](#), page 695.

Extending: [Section “Music functions” in \*Extending\*](#).

Installed Files: ‘lily/music-scheme.cc’, ‘scm/c++.scm’, ‘scm/lily.scm’.

### 5.6.2 Substitution function examples

This section introduces some substitution function examples. These are not intended to be exhaustive, but rather to demonstrate some of the possibilities of simple substitution functions.

In the first example, a function is defined that simplifies setting the padding of a TextScript:

```

padText =
#(define-music-function
  (parser location padding)
  (number?)
  #{
    \once \override TextScript #'padding = #padding
  })

\relative c''' {
  c4^"piu mosso" b a b
  \padText #1.8
  c4^"piu mosso" d e f
  \padText #2.6
  c4^"piu mosso" fis a g
}

```



In addition to numbers, we can use music expressions such as notes for arguments to music functions:

```

custosNote =
#(define-music-function
  (parser location note)
  (ly:music?)
  #{
    \once \override Voice.NoteHead #'stencil =
      #ly:text-interface::print
    \once \override Voice.NoteHead #'text =
      \markup \musicglyph #"custodes.mensural.u0"
    \once \override Voice.Stem #'stencil = ##f
    $note
  })

\relative c' { c4 d e f \custosNote g }

```



Substitution functions with multiple arguments can be defined:


```

tempoPadded =
#(define-music-function
  (parser location padding tempotext)
  (number? string?)
  #{
    \once \override Score.MetronomeMark #'padding = #padding
    \tempo \markup { \bold #tempotext }
  })

```



```
\relative c'' {  
  \tempo \markup { "Low tempo" }  
  c4 d e f g1  
  \tempoPadded #4.0 #"High tempo"  
  g4 f e d c1  
}
```



## Appendix A Notation manual tables

### A.1 Chord name chart




The following chart shows two standard systems for printing chord names, along with the pitches they represent.











Ignatzek (default)	C	Cm	C+	C <sup>o</sup>
Alternative	C	C <sup>b3</sup>	C <sup>#5</sup>	C <sup>b3 b5</sup>
Def	C <sup>7</sup>	Cm <sup>7</sup>	C <sup>Δ</sup>	C <sup>o7</sup>
Alt <sup>5</sup>	C <sup>7</sup>	C <sup>7 b3</sup>	C <sup>#7</sup>	C <sup>b3 b5 b7</sup>
Def	C <sup>7 #5</sup>	Cm <sup>Δ</sup>	C <sup>Δ #5</sup>	C <sup>∅</sup>
Alt <sup>10</sup>	C <sup>7 #5</sup>	C <sup>b3 #7</sup>	C <sup>#5 #7</sup>	C <sup>7 b3 b5</sup>
Def	C <sup>6</sup>	Cm <sup>6</sup>	C <sup>9</sup>	Cm <sup>9</sup>
Alt <sup>14</sup>	C <sup>6</sup>	C <sup>b3 6</sup>	C <sup>9</sup>	C <sup>9 b3</sup>
Def	Cm <sup>13</sup>	Cm <sup>11</sup>	Cm <sup>7 b5 9</sup>	C <sup>7 b9</sup>
Alt <sup>b</sup>	C <sup>13 b3</sup>	C <sup>11 b3</sup>	C <sup>9 b3 b5</sup>	C <sup>7 b9</sup>
Def	C <sup>7 #9</sup>	C <sup>11</sup>	C <sup>7 #11</sup>	C <sup>13</sup>
Alt <sup>b2</sup>	C <sup>7 #9</sup>	C <sup>11</sup>	C <sup>9 #11</sup>	C <sup>13</sup>
Def	C <sup>7 #11 b13</sup>	C <sup>7 #5 #9</sup>	C <sup>7 #9 #11</sup>	C <sup>7 b13</sup>
Alt <sup>26</sup>	C <sup>9 #11 b13</sup>	C <sup>7 #5 #9</sup>	C <sup>7 #9 #11</sup>	C <sup>11 b13</sup>











Def	$C^{7\flat 9\flat 13}$	$C^{7\sharp 11}$	$C^{\triangle 9}$	$C^{7\flat 13}$
Alt	$C^{11\flat 9\flat 13}$	$C^{9\sharp 11}$	$C^{9\sharp 7}$	$C^{11\flat 13}$
				
Def	$C^{7\flat 9\flat 13}$	$C^{7\flat 9\flat 13}$	$C^{\triangle 9}$	$C^{\triangle 13}$
Alt	$C^{11\flat 9\flat 13}$	$C^{13\flat 9}$	$C^{9\sharp 7}$	$C^{13\sharp 7}$
				
Def	$C^{\triangle \sharp 11}$	$C^{7\flat 9\flat 13}$	$C^{sus4}$	$C^{7sus4}$
Alt	$C^{9\sharp 7\sharp 11}$	$C^{13\flat 9}$	$C^{add4\ 5}$	$C^{add4\ 5\ 7}$
				
Def	$C^{9sus4}$	$C^9$	$C^{m11}$	$C^{lyd}$
Alt	$C^{add4\ 5\ 7\ 9}$	$C^{add9}$	$C^{\flat 3\ add11}$	$C^{\sharp 7\ add\sharp 11}$
				
			$C^{alt}$	$C^{7\flat 9\flat 10\sharp 11\flat 13}$
				

## A.2 Common chord modifiers


The following table shows chord modifiers that can be used in `\chordmode` to generate standard chord structures.

Chord type	Intervals	Modifier(s)	Example
Major	Major third, perfect fifth	5 or nothing	
Minor	Minor third, perfect fifth	m or m5	
Augmented	Major third, augmented fifth	aug	


Diminished	Minor third, diminished fifth	dim	
Dominant seventh	Major triad, minor seventh	7	
Major seventh	Major triad, major seventh	maj7 or maj	
Minor seventh	Minor triad, minor seventh	m7	
Diminished seventh	Diminished triad, diminished seventh	dim7	
Augmented seventh	Augmented triad, minor seventh	aug7	
Half-diminished seventh	Diminished triad, minor seventh	m7.5-	
Minor-major seventh	Minor triad, major seventh	m7+	
Major sixth	Major triad, sixth	6	
Minor sixth	Minor triad, sixth	m6	

Dominant ninth	Dominant seventh, major ninth	9	
Major ninth	Major seventh, major ninth	maj9	
Minor ninth	Minor seventh, major ninth	m9	
Dominant eleventh	Dominant ninth, perfect eleventh	11	
Major eleventh	Major ninth, perfect eleventh	maj11	
Minor eleventh	Minor ninth, perfect eleventh	m11	
Dominant thirteenth	Dominant ninth, major thirteenth	13	
Dominant thirteenth	Dominant eleventh, major thirteenth	13.11	
Major thirteenth	Major eleventh, major thirteenth	maj13.11	
Minor thirteenth	Minor eleventh, major thirteenth	m13.11	


Suspended second    Major second, perfect fifth    sus2




Suspended fourth    Perfect fourth, perfect fifth    sus4



Power chord (two-voiced)    Perfect fifth    1.5



Power chord (three-voiced)    Perfect fifth, octave    1.5.8



### A.3 Predefined string tunings

The chart below shows the predefined string tunings.

**Guitar tunings**

guitar-tuning    guitar-seven-string-tuning    guitar-drop-d-tuning

guitar-open-g-tuning    guitar-open-d-tuning    guitar-dadgad-tuning

guitar-lute-tuning    guitar-asus4-tuning


**Bass tunings**

bass-tuning    bass-four-string-tuning    bass-drop-d-tuning

bass-five-string-tuning    bass-six-string-tuning

## Mandolin tunings


14 mandolin-tuning



## Banjo tunings

15 banjo-open-g-tuning


banjo-c-tuning



17 banjo-modal-tuning

banjo-open-d-tuning

banjo-open-dm-tuning



## Ukulele tunings


20 ukulele-tuning

ukulele-d-tuning



22 tenor-ukulele-tuning

baritone-ukulele-tuning



## Orchestral string tunings

24 violin-tuning

viola-tuning

cello-tuning

double-bass-tuning



## A.4 Predefined fretboard diagrams

The chart below shows the predefined fretboard diagrams for guitar.

18

10

19

$D^b$	$D^bm$	$D^b+$	$D^b^0$	$D^b^{o7}$	$D^b^7$	$D^b^{\Delta}$	$D^bm^7$	$D^b^9$
3 1 2 1	2 1 3	4 3 1 2	3 4	1 3 2 4	2 3 1 4	4 3 1 1 1	4 2 1	2 1 3 3 3

28

$D$	$Dm$	$D+$	$D^0$	$D^{o7}$	$D^7$	$D^{\Delta}$	$Dm^7$	$D^9$
1 3 2	2 3 1	2 3 1	1 3 1	1 2	2 1 3	1 2 3	2 1 1	2 1 3 3 3

37

$D^{\#}$	$D^{\#}m$	$D^{\#}+$	$D^{\#0}$	$D^{\#o7}$	$D^{\#7}$	$D^{\#\Delta}$	$D^{\#m^7}$	$D^{\#9}$
3 1 2 1	3 2 4 1	3 2 1 4	3 1 4 1	1 3 2 4	1 3 2 4	1 2 3 4	1 2 3 4	2 1 3 3 3

46

$E^b$	$E^bm$	$E^b+$	$E^b^0$	$E^b^{o7}$	$E^b^7$	$E^b^{\Delta}$	$E^bm^7$	$E^b^9$
3 1 2 1	3 2 4 1	3 2 1 4	3 1 4 1	1 3 2 4	1 3 2 4	1 2 3 4	1 2 3 4	2 1 3 3 3

55

$E$	$Em$	$E+$	$E^0$	$E^{o7}$	$E^7$	$E^{\Delta}$	$Em^7$	$E^9$
2 3 1	2 3	3 2 1	3 1 4 1	1 3 2 4	2 1	3 1 2	2	2 1 3

64

$F$	$Fm$	$F+$	$F^0$	$F^{o7}$	$F^7$	$F^{\Delta}$	$Fm^7$	$F^9$
1 3 4 2 1 1	1 3 4 1 1 1	1 3 4 2	3 1 4 1	1 2	1 3 1 2 1 1	3 2 1	1 3 1 1 1 1	1 3 1 2 1 4



73

$F\sharp$	$F\sharp m$	$F\sharp +$	$F\sharp^o$	$F\sharp^{o7}$	$F\sharp^7$	$F\sharp^{\Delta}$	$F\sharp m^7$	$F\sharp^9$

Musical notation for measures 73-81, showing various chord voicings for F# and F#m.

82

$G\flat$	$G\flat m$	$G\flat +$	$G\flat^o$	$G\flat^{o7}$	$G\flat^7$	$G\flat^{\Delta}$	$G\flat m^7$	$G\flat^9$

Musical notation for measures 82-90, showing various chord voicings for Gb and Gbm.

91

$G$	$Gm$	$G +$	$G^o$	$G^{o7}$	$G^7$	$G^{\Delta}$	$Gm^7$	$G^9$

Musical notation for measures 91-99, showing various chord voicings for G and Gm.

100

$G\sharp$	$G\sharp m$	$G\sharp +$	$G\sharp^o$	$G\sharp^{o7}$	$G\sharp^7$	$G\sharp^{\Delta}$	$G\sharp m^7$	$G\sharp^9$

Musical notation for measures 100-108, showing various chord voicings for G# and G#m.

109

$A\flat$	$A\flat m$	$A\flat +$	$A\flat^o$	$A\flat^{o7}$	$A\flat^7$	$A\flat^{\Delta}$	$A\flat m^7$	$A\flat^9$

Musical notation for measures 109-117, showing various chord voicings for Ab and Abm.

118

$A$	$Am$	$A +$	$A^o$	$A^{o7}$	$A^7$	$A^{\Delta}$	$Am^7$	$A^9$

Musical notation for measures 118-126, showing various chord voicings for A and Am.

Diagram showing fretboard diagrams and musical notation for chords A# and Bb.

**A# Chords:** A# (12341), A#m (13421), A#+ (21 443), A#<sup>0</sup> (1243), A#<sup>07</sup> (1324), A#<sup>7</sup> (12131), A#<sup>Δ</sup> (1324), A#m<sup>7</sup> (13121), A#<sup>9</sup> (131214 vi).

**Bb Chords:** Bb (12341), Bbm (13421), Bb+ (21 443), Bb<sup>0</sup> (1243), Bb<sup>07</sup> (1324), Bb<sup>7</sup> (12131), Bb<sup>Δ</sup> (1324), Bbm<sup>7</sup> (13121), Bb<sup>9</sup> (131214 vi).

**B Chords:** B (12341), Bm (13421), B+ (21 443), B<sup>0</sup> (1243), B<sup>07</sup> (1 2), B<sup>7</sup> (12131), B<sup>Δ</sup> (1324), Bm<sup>7</sup> (13121), B<sup>9</sup> (21333).

Musical notation examples are provided for each chord type, showing the corresponding notes on a staff.

The chart below shows the predefined fretboard diagrams for ukulele.

Diagram showing fretboard diagrams and musical notation for C major and C# major chords.

**C Major Chords:** C (3), Cm (123), C+ (1 4), C<sup>0</sup> (1324), C<sup>7</sup> (1), C<sup>Δ</sup> (1), Cm<sup>7</sup> (1111), C<sup>6</sup> (122), C<sup>sus2</sup> (13), C<sup>sus4</sup> (2 1), C<sup>9</sup> (2 1).


**C# Major Chords:** C# (1114), C#m (1233), C#+ (2114), C#<sup>0</sup> (1 2), C#<sup>7</sup> (1112), C#<sup>Δ</sup> (1113).

**C# Major Chords (continued):** C#m<sup>7</sup> (2213), C#<sup>6</sup> (1111), C#<sup>sus2</sup> (1233), C#<sup>sus4</sup> (1124), C#<sup>9</sup> (1312).

Musical notation examples are provided for each chord type, showing the corresponding notes on a staff.


23

$D\flat$   $D\flat m$   $D\flat +$   $D\flat^{\circ}$   $D\flat^7$   $D\flat^{\Delta}$




29

$D\flat m^7$   $D\flat^6$   $D\flat^{sus2}$   $D\flat^{sus4}$   $D\flat^9$




34

$D$   $Dm$   $D+$   $D^{\circ}$   $D^7$   $D^{\Delta}$   $Dm^7$   $D^6$   $D^{sus2}$   $D^{sus4}$   $D^9$




45

$D\sharp$   $D\sharp m$   $D\sharp +$   $D\sharp^{\circ}$   $D\sharp^7$   $D\sharp^{\Delta}$




51

$D\sharp m^7$   $D\sharp^6$   $D\sharp^{sus2}$   $D\sharp^{sus4}$   $D\sharp^9$



56

$E\flat$   $E\flat m$   $E\flat +$   $E\flat^{\circ}$   $E\flat^7$   $E\flat^{\Delta}$



62

$E\flat m^7$   $E\flat^6$   $E\flat^{sus2}$   $E\flat^{sus4}$   $E\flat^9$

67

$E$   $E m$   $E^+$   $E^o$   $E^7$   $E^\Delta$   $E m^7$   $E^6$   $E^{sus2}$   $E^{sus4}$   $E^9$

78

$F$   $F m$   $F^+$   $F^o$   $F^7$   $F^\Delta$   $F m^7$   $F^6$   $F^{sus2}$   $F^{sus4}$   $F^9$

89

$F^\sharp$   $F^\sharp m$   $F^\sharp^+$   $F^\sharp^o$   $F^\sharp^7$   $F^\sharp^\Delta$

95

$F^\sharp m^7$   $F^\sharp^6$   $F^\sharp^{sus2}$   $F^\sharp^{sus4}$   $F^\sharp^9$

100

$G\flat$   $G\flat m$   $G\flat^+$   $G\flat^o$   $G\flat^7$   $G\flat^\Delta$

106

$G\flat m^7$   $G\flat^6$   $G\flat^{sus2}$   $G\flat^{sus4}$   $G\flat^9$

1324 2214 1124 4123 1222

111

$G$   $Gm$   $G+$   $G^o$   $G^7$   $G^\Delta$   $Gm^7$   $G^6$   $G^{sus2}$   $G^{sus4}$   $G^9$

132 231 221 1 2 213 123 211 1 2 12 123 2314

122

$G^\sharp$   $G^\sharp m$   $G^\sharp +$   $G^\sharp^o$   $G^\sharp^7$   $G^\sharp^\Delta$

3121 1342 1 4 1324 1324 1233

128

$G^\sharp m^7$   $G^\sharp^6$   $G^\sharp^{sus2}$   $G^\sharp^{sus4}$   $G^\sharp^9$

1423 1324 2341 1333 1 32

133

$A\flat$   $A\flat m$   $A\flat +$   $A\flat^o$   $A\flat^7$   $A\flat^\Delta$

3121 1342 1 4 1324 1324 1233

139

$A\flat m^7$   $A\flat^6$   $A\flat^{sus2}$   $A\flat^{sus4}$   $A\flat^9$

1423 1324 2341 1333 1 32

144

A A<sup>o</sup> Am A<sup>+</sup> A<sup>o</sup> A<sup>7</sup> A<sup>Δ</sup> Am<sup>7</sup> A<sup>6</sup> A<sup>sus2</sup> A<sup>sus4</sup> A<sup>9</sup>

155

A<sup>#</sup> A<sup>#m</sup> A<sup>#+</sup> A<sup>#o</sup> A<sup>#7</sup> A<sup>#Δ</sup>

161

A<sup>#m</sup><sup>7</sup> A<sup>#6</sup> A<sup>#sus2</sup> A<sup>#sus4</sup> A<sup>#9</sup>

166

B<sup>b</sup> B<sup>b</sup>m B<sup>b+</sup> B<sup>b o</sup> B<sup>b7</sup> B<sup>bΔ</sup>

172

B<sup>b</sup>m<sup>7</sup> B<sup>b6</sup> B<sup>b sus2</sup> B<sup>b sus4</sup> B<sup>b9</sup>

177

B Bm B<sup>+</sup> B<sup>o</sup> B<sup>7</sup> B<sup>Δ</sup>

183

Bm<sup>7</sup> B<sup>6</sup> B<sup>sus2</sup> B<sup>sus4</sup> B<sup>9</sup>

The chart below shows the predefined fretboard diagrams for mandolin.

7

C C<sup>m</sup> C<sup>+</sup> C<sup>°7</sup> C<sup>7</sup> C<sup>Δ</sup>

Cm<sup>7</sup> C<sup>∅</sup> C<sup>6</sup> C<sup>sus2</sup> C<sup>sus4</sup> C<sup>9</sup>

C<sup>#</sup> C<sup>#m</sup> C<sup>#+</sup> C<sup>#°7</sup> C<sup>#7</sup> C<sup>#Δ</sup>

C<sup>#m7</sup> C<sup>#∅</sup> C<sup>#6</sup> C<sup>#sus2</sup> C<sup>#sus4</sup> C<sup>#9</sup>







D<sup>b</sup> D<sup>b</sup>m D<sup>b</sup><sup>+</sup> D<sup>b°7</sup> D<sup>b7</sup> D<sup>bΔ</sup>


13

19







25


31

$D\flat m^7$	$D\flat \emptyset$	$D\flat^6$	$D\flat^{sus2}$	$D\flat^{sus4}$	$D\flat^9$
					










37

$D$	$Dm$	$D+$	$D^{o7}$	$D^7$	$D^{\Delta}$
					










43

$Dm^7$	$D \emptyset$	$D^6$	$D^{sus2}$	$D^{sus4}$	$D^9$
					










49

$D\sharp$	$D\sharp m$	$D\sharp+$	$D\sharp^{o7}$	$D\sharp^7$	$D\sharp^{\Delta}$
					










55

$D\sharp m^7$	$D\sharp \emptyset$	$D\sharp^6$	$D\sharp^{sus2}$	$D\sharp^{sus4}$	$D\sharp^9$
					



61

$E\flat$	$E\flat m$	$E\flat+$	$E\flat^{o7}$	$E\flat^7$	$E\flat^{\Delta}$
					





67

$E\flat m^7$	$E\flat \emptyset$	$E\flat^6$	$E\flat^{sus2}$	$E\flat^{sus4}$	$E\flat^9$

73

$E$	$E m$	$E +$	$E^{o7}$	$E^7$	$E^{\Delta}$

79

$E m^7$	$E \emptyset$	$E^6$	$E^{sus2}$	$E^{sus4}$	$E^9$

85

$F$	$F m$	$F +$	$F^{o7}$	$F^7$	$F^{\Delta}$

91

$F m^7$	$F \emptyset$	$F^6$	$F^{sus2}$	$F^{sus4}$	$F^9$

97

$F\sharp$	$F\sharp m$	$F\sharp +$	$F\sharp^{o7}$	$F\sharp^7$	$F\sharp^{\Delta}$

103

$F\sharp m^7$	$F\sharp \emptyset$	$F\sharp^6$	$F\sharp^{sus2}$	$F\sharp^{sus4}$	$F\sharp^9$
1131	1121	3142	3111	4211	213

109

$G\flat$	$G\flat m$	$G\flat +$	$G\flat^{o7}$	$G\flat^7$	$G\flat^{\Delta}$
2341	1341	1234	2143	2131	2341

115

$G\flat m^7$	$G\flat \emptyset$	$G\flat^6$	$G\flat^{sus2}$	$G\flat^{sus4}$	$G\flat^9$
1131	1121	3142	3111	4211	213

121

$G$	$Gm$	$G+$	$G^{o7}$	$G^7$	$G^{\Delta}$
12	13	123	2143	21	11

127

$Gm^7$	$G \emptyset$	$G^6$	$G^{sus2}$	$G^{sus4}$	$G^9$
11	1121	2	3	11	1 4

133

$G\sharp$	$G\sharp m$	$G\sharp +$	$G\sharp^{o7}$	$G\sharp^7$	$G\sharp^{\Delta}$
1134	1124	1234	1 32	1132	1133

	$G\sharp m^7$	$G\sharp \emptyset$	$G\sharp^6$	$G\sharp^{sus2}$	$G\sharp^{sus4}$	$G\sharp^9$
	1122	1 22	1131	1114	1134	1324
139						
	$A\flat$	$A\flat m$	$A\flat +$	$A\flat^{o7}$	$A\flat^7$	$A\flat^{\Delta}$
	1134	1124	1234	1 32	1132	1133
145						
	$A\flat m^7$	$A\flat \emptyset$	$A\flat^6$	$A\flat^{sus2}$	$A\flat^{sus4}$	$A\flat^9$
	1122	1 22	1131	1114	1134	1324
151						
	$A$	$A m$	$A +$	$A^{o7}$	$A^7$	$A^{\Delta}$
	113	112	2341	2143	1132	1133
157						
	$A m^7$	$A \emptyset$	$A^6$	$A^{sus2}$	$A^{sus4}$	$A^9$
	1122	2134	1131	111	1	1324
163						
	$A\sharp$	$A\sharp m$	$A\sharp +$	$A\sharp^{o7}$	$A\sharp^7$	$A\sharp^{\Delta}$
	3 11	1124	3 12	2143	1132	3 1
169						

$A\sharp m^7$	$A\sharp \emptyset$	$A\sharp^6$	$A\sharp^{sus2}$	$A\sharp^{sus4}$	$A\sharp^9$
175					
$B\flat$	$B\flat m$	$B\flat +$	$B\flat^{o7}$	$B\flat^7$	$B\flat^{\Delta}$
181					
$B\flat m^7$	$B\flat \emptyset$	$B\flat^6$	$B\flat^{sus2}$	$B\flat^{sus4}$	$B\flat^9$
187					
$B$	$Bm$	$B +$	$B^{o7}$	$B^7$	$B^{\Delta}$
193					
$Bm^7$	$B \emptyset$	$B^6$	$B^{sus2}$	$B^{sus4}$	$B^9$
199					

## A.5 MIDI instruments

The following is a list of names that can be used for the `midiInstrument` property. The order of the instruments below, starting in the left-hand column moving down, corresponds to the General MIDI Standard's 128 Program Numbers.

acoustic grand  
bright acoustic

contrabass  
tremolo strings

lead 7 (fifths)  
lead 8 (bass+lead)

electric grand	pizzicato strings	pad 1 (new age)
honky-tonk	orchestral harp	pad 2 (warm)
electric piano 1	timpani	pad 3 (polysynth)
electric piano 2	string ensemble 1	pad 4 (choir)
harpsichord	string ensemble 2	pad 5 (bowed)
clav	synthstrings 1	pad 6 (metallic)
celesta	synthstrings 2	pad 7 (halo)
glockenspiel	choir aahs	pad 8 (sweep)
music box	voice oohs	fx 1 (rain)
vibraphone	synth voice	fx 2 (soundtrack)
marimba	orchestra hit	fx 3 (crystal)
xylophone	trumpet	fx 4 (atmosphere)
tubular bells	trombone	fx 5 (brightness)
dulcimer	tuba	fx 6 (goblins)
drawbar organ	muted trumpet	fx 7 (echoes)
percussive organ	french horn	fx 8 (sci-fi)
rock organ	brass section	sitar
church organ	synthbrass 1	banjo
reed organ	synthbrass 2	shamisen
accordion	soprano sax	koto
harmonica	alto sax	kalimba
concertina	tenor sax	bagpipe
acoustic guitar (nylon)	baritone sax	fiddle
acoustic guitar (steel)	oboe	shanai
electric guitar (jazz)	english horn	tinkle bell
electric guitar (clean)	bassoon	agogo
electric guitar (muted)	clarinet	steel drums
overdriven guitar	piccolo	woodblock
distorted guitar	flute	taiko drum
guitar harmonics	recorder	melodic tom
acoustic bass	pan flute	synth drum
electric bass (finger)	blown bottle	reverse cymbal
electric bass (pick)	shakuhachi	guitar fret noise
fretless bass	whistle	breath noise
slap bass 1	ocarina	seashore
slap bass 2	lead 1 (square)	bird tweet
synth bass 1	lead 2 (sawtooth)	telephone ring
synth bass 2	lead 3 (calliope)	helicopter
violin	lead 4 (chiff)	applause
viola	lead 5 (charang)	gunshot
cello	lead 6 (voice)	

## A.6 List of colors

### Normal colors

Usage syntax is detailed in [\[Coloring objects\]](#), page 195.

black	white	red	green
blue	cyan	magenta	yellow
grey	darkred	darkgreen	darkblue
darkcyan	darkmagenta	darkyellow	

## X color names

X color names come several variants:

Any name that is spelled as a single word with capitalization (e.g. ‘LightSlateBlue’) can also be spelled as space separated words without capitalization (e.g. ‘light slate blue’).

The word ‘grey’ can always be spelled ‘gray’ (e.g. ‘DarkSlateGray’).

Some names can take a numerical suffix (e.g. ‘LightSalmon4’).

### Color Names without a numerical suffix:

snow	GhostWhite	WhiteSmoke	gainsboro	FloralWhite
OldLace	linen	AntiqueWhite	PapayaWhip	BlanchedAlmond
bisque	PeachPuff	NavajoWhite	moccasin	cornsilk
ivory	LemonChiffon	seashell	honeydew	MintCream
azure	AliceBlue	lavender	LavenderBlush	MistyRose
white	black	DarkSlateGrey	DimGrey	SlateGrey
LightSlateGrey	grey	LightGrey	MidnightBlue	navy
NavyBlue	CornflowerBlue	DarkSlateBlue	SlateBlue	MediumSlateBlue
LightSlateBlue	MediumBlue	RoyalBlue	blue	DodgerBlue
DeepSkyBlue	SkyBlue	LightSkyBlue	SteelBlue	LightSteelBlue
LightBlue	PowderBlue	PaleTurquoise	DarkTurquoise	MediumTurquoise
turquoise	cyan	LightCyan	CadetBlue	MediumAquamarine
aquamarine	DarkGreen	DarkOliveGreen	DarkSeaGreen	SeaGreen
MediumSeaGreen	LightSeaGreen	PaleGreen	SpringGreen	LawnGreen
green	chartreuse	MediumSpringGreen	GreenYellow	LimeGreen
YellowGreen	ForestGreen	OliveDrab	DarkKhaki	khaki
PaleGoldenrod	LightGoldenrodYellow	LightYellow	yellow	gold
LightGoldenrod	goldenrod	DarkGoldenrod	RosyBrown	IndianRed
SaddleBrown	sienna	peru	burlywood	beige
wheat	SandyBrown	tan	chocolate	firebrick
brown	DarkSalmon	salmon	LightSalmon	orange
DarkOrange	coral	LightCoral	tomato	OrangeRed
red	HotPink	DeepPink	pink	LightPink
PaleVioletRed	maroon	MediumVioletRed	VioletRed	magenta
violet	plum	orchid	MediumOrchid	DarkOrchid
DarkViolet	BlueViolet	purple	MediumPurple	thistle
DarkGrey	DarkBlue	DarkCyan	DarkMagenta	DarkRed
LightGreen				

### Color names with a numerical suffix

In the following names the suffix N can be a number in the range 1-4:

snowN	seashellN	AntiqueWhiteN	bisqueN	PeachPuffN
NavajoWhiteN	LemonChiffonN	cornsilkN	ivoryN	honeydewN
LavenderBlushN	MistyRoseN	azureN	SlateBlueN	RoyalBlueN
blueN	DodgerBlueN	SteelBlueN	DeepSkyBlueN	SkyBlueN
LightSkyBlueN	LightSteelBlueN	LightBlueN	LightCyanN	PaleTurquoiseN
CadetBlueN	turquoiseN	cyanN	aquamarineN	DarkSeaGreenN
SeaGreenN	PaleGreenN	SpringGreenN	greenN	chartreuseN
OliveDrabN	DarkOliveGreenN	khakiN	LightGoldenrodN	LightYellowN
yellowN	goldN	goldenrodN	DarkGoldenrodN	RosyBrownN
IndianRedN	siennaN	burlywoodN	wheatN	tanN
chocolateN	firebrickN	brownN	salmonN	LightSalmonN

orangeN	DarkOrangeN	coralN	tomatoN	OrangeRedN
redN	DeepPinkN	HotPinkN	pinkN	LightPinkN
PaleVioletRedN	maroonN	VioletRedN	magentaN	orchidN
plumN	MediumOrchidN	DarkOrchidN	purpleN	MediumPurpleN
thistleN				

## Grey Scale

A grey scale can be obtained using:










greyN

Where N is in the range 0-100.

## A.7 The Feta font

The following symbols are available in the Emmentaler font and may be accessed directly using text markup with the name of the glyph as shown in the tables below, such as `g^\markup {\musicglyph #"scripts.segno" }` or `\markup {\musicglyph #"five"}`. For more information, see [Section 1.8.2 \[Formatting text\]](#), page 210.

### Clef glyphs

clefs.C		clefs.C_change	
clefs.F		clefs.F_change	
clefs.G		clefs.G_change	
clefs.percussion		clefs.percussion_change	
clefs.tab		clefs.tab_change	

### Time Signature glyphs

timesig.C44		timesig.C22	
-------------	---	-------------	---

### Number glyphs





plus	+	comma	,
hyphen	-	period	.

zero	<b>0</b>	one	<b>1</b>
two	<b>2</b>	three	<b>3</b>
four	<b>4</b>	five	<b>5</b>
six	<b>6</b>	seven	<b>7</b>
eight	<b>8</b>	nine	<b>9</b>







## Accidental glyphs

accidentals.sharp	<b>#</b>	accidentals .sharp.arrowup	<b>#↑</b>
accidentals .sharp.arrowdown	<b>#↓</b>	accidentals .sharp.arrowboth	<b>#↕</b>
accidentals.sharp .slashslash.stem	<b>‡</b>	accidentals.sharp .slashslashslash.stemstem	<b>‡‡</b>
accidentals.sharp .slashslashslash.stem	<b>‡‡</b>	accidentals.sharp .slashslash.stemstemstem	<b>‡‡‡</b>
accidentals.natural	<b>♮</b>	accidentals .natural.arrowup	<b>♮↑</b>
accidentals .natural.arrowdown	<b>♮↓</b>	accidentals .natural.arrowboth	<b>♮↕</b>
accidentals.flat	<b>♭</b>	accidentals.flat.arrowup	<b>♭↑</b>
accidentals .flat.arrowdown	<b>♭↓</b>	accidentals .flat.arrowboth	<b>♭↕</b>
accidentals.flat.slash	<b>♭/</b>	accidentals.flat .slashslash	<b>♭‡</b>
accidentals .mirroredflat.flat	<b>♮♭</b>	accidentals.mirroredflat	<b>♮♭</b>





















accidentals .mirroredflat.backslash		accidentals.flatflat	
accidentals .flatflat.slash		accidentals.doublsharp	
accidentals.rightparen	)	accidentals.leftparen	(





























## Default Notehead glyphs

noteheads.uM2		noteheads.dM2	
noteheads.sM1		noteheads.s0	
noteheads.s1		noteheads.s2	

## Special Notehead glyphs

noteheads.sM1double		noteheads.s0diamond	
noteheads.s1diamond		noteheads.s2diamond	
noteheads.s0triangle		noteheads.d1triangle	
noteheads.ultriangle		noteheads.u2triangle	
noteheads.d2triangle		noteheads.s0slash	
noteheads.s1slash		noteheads.s2slash	
noteheads.s0cross		noteheads.s1cross	
noteheads.s2cross		noteheads.s2xcircle	
noteheads.s0harmonic		noteheads.s2harmonic	

## Shape-note Notehead glyphs
















<code>noteheads.s0do</code>		<code>noteheads.d1do</code>	
<code>noteheads.u1do</code>		<code>noteheads.d2do</code>	
<code>noteheads.u2do</code>		<code>noteheads.s0doThin</code>	
<code>noteheads.d1doThin</code>		<code>noteheads.u1doThin</code>	
<code>noteheads.d2doThin</code>		<code>noteheads.u2doThin</code>	
<code>noteheads.s0re</code>		<code>noteheads.u1re</code>	
<code>noteheads.d1re</code>		<code>noteheads.u2re</code>	
<code>noteheads.d2re</code>		<code>noteheads.s0reThin</code>	
<code>noteheads.u1reThin</code>		<code>noteheads.d1reThin</code>	
<code>noteheads.u2reThin</code>		<code>noteheads.d2reThin</code>	
<code>noteheads.s0mi</code>		<code>noteheads.s1mi</code>	
<code>noteheads.s2mi</code>		<code>noteheads.s0miMirror</code>	
<code>noteheads.s1miMirror</code>		<code>noteheads.s2miMirror</code>	
<code>noteheads.s0miThin</code>		<code>noteheads.s1miThin</code>	

noteheads.s2miThin	◆	noteheads.u0fa	▷
noteheads.d0fa	▷	noteheads.u1fa	▷
noteheads.d1fa	▷	noteheads.u2fa	◀
noteheads.d2fa	▶	noteheads.u0faThin	▷
noteheads.d0faThin	▷	noteheads.u1faThin	▷
noteheads.d1faThin	▷	noteheads.u2faThin	◀
noteheads.d2faThin	▶	noteheads.s0sol	◊
noteheads.s1sol	◊	noteheads.s2sol	●
noteheads.s0la	◻	noteheads.s1la	◻
noteheads.s2la	■	noteheads.s0laThin	◻
noteheads.s1laThin	◻	noteheads.s2laThin	■
noteheads.s0ti	◇	noteheads.ulti	◇
noteheads.d1ti	◇	noteheads.u2ti	◆
noteheads.d2ti	◆	noteheads.s0tiThin	◇
noteheads.ultiThin	◇	noteheads.d1tiThin	◇













<code>noteheads.u2tiThin</code>	◀	<code>noteheads.d2tiThin</code>	◀
<code>noteheads.u0doFunk</code>	▷	<code>noteheads.d0doFunk</code>	▷
<code>noteheads.u1doFunk</code>	▷	<code>noteheads.d1doFunk</code>	▷
<code>noteheads.u2doFunk</code>	▷	<code>noteheads.d2doFunk</code>	▷
<code>noteheads.u0reFunk</code>	▷	<code>noteheads.d0reFunk</code>	▷
<code>noteheads.u1reFunk</code>	▷	<code>noteheads.d1reFunk</code>	▷
<code>noteheads.u2reFunk</code>	▷	<code>noteheads.d2reFunk</code>	▷
<code>noteheads.u0miFunk</code>	◊	<code>noteheads.d0miFunk</code>	◊
<code>noteheads.u1miFunk</code>	◊	<code>noteheads.d1miFunk</code>	◊
<code>noteheads.s2miFunk</code>	◆	<code>noteheads.u0faFunk</code>	▷
<code>noteheads.d0faFunk</code>	▷	<code>noteheads.u1faFunk</code>	▷
<code>noteheads.d1faFunk</code>	▷	<code>noteheads.u2faFunk</code>	▷
<code>noteheads.d2faFunk</code>	▷	<code>noteheads.s0solFunk</code>	○
<code>noteheads.s1solFunk</code>	○	<code>noteheads.s2solFunk</code>	●
<code>noteheads.s0laFunk</code>	□	<code>noteheads.s1laFunk</code>	□

noteheads.s2laFunk	■	noteheads.u0tiFunk	▷
noteheads.d0tiFunk	◁	noteheads.u1tiFunk	▷
noteheads.d1tiFunk	◁	noteheads.u2tiFunk	►
noteheads.d2tiFunk	◀	noteheads.s0doWalker	▵
noteheads.u1doWalker	▽	noteheads.d1doWalker	▵
noteheads.u2doWalker	▼	noteheads.d2doWalker	▲
noteheads.s0reWalker	◁	noteheads.u1reWalker	▷
noteheads.d1reWalker	◁	noteheads.u2reWalker	►
noteheads.d2reWalker	◀	noteheads.s0miWalker	◇
noteheads.s1miWalker	◇	noteheads.s2miWalker	◆
noteheads.s0faWalker	▵	noteheads.u1faWalker	▽
noteheads.d1faWalker	▵	noteheads.u2faWalker	▼
noteheads.d2faWalker	▴	noteheads.s0laWalker	□
noteheads.s1laWalker	□	noteheads.s2laWalker	■
noteheads.s0tiWalker	◁	noteheads.ultiWalker	▷
noteheads.d1tiWalker	◁	noteheads.u2tiWalker	►
noteheads.d2tiWalker	◀		

**Rest glyphs**

rests.0		rests.1	
rests.0o		rests.1o	
rests.M3		rests.M2	
rests.M1		rests.M1o	
rests.2		rests.2classical	
rests.3		rests.4	
rests.5		rests.6	
rests.7			

**Flag glyphs**

flags.u3		flags.u4	
flags.u5		flags.u6	
flags.u7		flags.d3	
flags.d4		flags.d5	
flags.d6		flags.d7	
flags.ugrace		flags.dgrace	

## Dot glyphs

dots.dot                      .

## Dynamic glyphs


space                                      f                                      ***f***

m                                      ***m***                                      p                                      ***p***


r                                      ***r***                                      s                                      ***s***

z                                      ***z***

## Script glyphs


scripts.ufermata                                            scripts.dfermata                      

scripts.ushortfermata                                            scripts.dshortfermata                      

scripts.ulongfermata                                            scripts.dlongfermata                      

scripts.uverylongfermata                                            scripts.dverylongfermata                      

scripts.thumb                                                                            scripts.sforzato                                      







scripts.espr                                                                            scripts.staccato                                      .

scripts.ustaccatissimo                                                            scripts.dstaccatissimo                                      









scripts.tenuto                                      —                                      scripts.uportato                                      

<code>scripts.dportato</code>		<code>scripts.umarcato</code>	
<code>scripts.dmarcato</code>		<code>scripts.open</code>	
<code>scripts.halfopen</code>		<code>scripts.halfopenvertical</code>	
<code>scripts.stopped</code>		<code>scripts.upbow</code>	
<code>scripts.downbow</code>		<code>scripts.reverseturn</code>	
<code>scripts.turn</code>		<code>scripts.trill</code>	
<code>scripts.upedalheel</code>		<code>scripts.dpedalheel</code>	
<code>scripts.upedaltoe</code>		<code>scripts.dpedaltoe</code>	
<code>scripts.flageolet</code>		<code>scripts.segno</code>	
<code>scripts.varsegno</code>		<code>scripts.coda</code>	
<code>scripts.varcoda</code>		<code>scripts.rcomma</code>	
<code>scripts.lcomma</code>		<code>scripts.rvarcomma</code>	
<code>scripts.lvarcomma</code>		<code>scripts.arpeggio</code>	
<code>scripts.trill_element</code>		<code>scripts.arpeggio .arrow.M1</code>	
<code>scripts.arpeggio.arrow.1</code>		<code>scripts.trilelement</code>	





<code>scripts.prall</code>		<code>scripts.mordent</code>	
<code>scripts.prallprall</code>		<code>scripts.prallmordent</code>	
<code>scripts.upprall</code>		<code>scripts.upmordent</code>	
<code>scripts.pralldown</code>		<code>scripts.downprall</code>	
<code>scripts.downmordent</code>		<code>scripts.prallup</code>	
<code>scripts.lineprall</code>		<code>scripts.caesura.curved</code>	
<code>scripts.caesura.straight</code>		<code>scripts.snappizzicato</code>	
<code>scripts.ictus</code>		<code>scripts.uaccentus</code>	
<code>scripts.daccentus</code>		<code>scripts.usemicirculus</code>	
<code>scripts.dsemicirculus</code>		<code>scripts.circulus</code>	
<code>scripts.augmentum</code>		<code>scripts.usignumcongruentiae</code>	
<code>scripts.dsignumcongruentiae</code>			

### Arrowhead glyphs

<code>arrowheads.open.01</code>		<code>arrowheads.open.0M1</code>	
<code>arrowheads.open.11</code>		<code>arrowheads.open.1M1</code>	
<code>arrowheads.close.01</code>		<code>arrowheads.close.0M1</code>	
<code>arrowheads.close.11</code>		<code>arrowheads.close.1M1</code>	


## Bracket-tip glyphs

<code>brackettips.up</code>		<code>brackettips.down</code>	
-----------------------------	---	-------------------------------	---

## Pedal glyphs



<code>pedal.*</code>		<code>pedal.M</code>	
----------------------	---	----------------------	---



<code>pedal..</code>		<code>pedal.P</code>	
----------------------	---	----------------------	---

<code>pedal.d</code>		<code>pedal.e</code>	
----------------------	---	----------------------	---

<code>pedal.Ped</code>			
------------------------	---	--	--

## Accordion glyphs

<code>accordion.discant</code>		<code>accordion.dot</code>	
--------------------------------	---	----------------------------	---

<code>accordion.freebass</code>		<code>accordion.stdbass</code>	
---------------------------------	---	--------------------------------	---




<code>accordion.bayanbass</code>		<code>accordion.oldEE</code>	
----------------------------------	---	------------------------------	---

<code>accordion.push</code>		<code>accordion.pull</code>	
-----------------------------	---	-----------------------------	---
















## Tie glyphs

<code>ties.lyric.short</code>		<code>ties.lyric.default</code>	
-------------------------------	---	---------------------------------	---

## Vaticana glyphs

<code>clefs.vaticana.do</code>		<code>clefs.vaticana.do_change</code>	
<code>clefs.vaticana.fa</code>		<code>clefs.vaticana.fa_change</code>	
<code>custodes.vaticana.u0</code>		<code>custodes.vaticana.u1</code>	
<code>custodes.vaticana.u2</code>		<code>custodes.vaticana.d0</code>	
<code>custodes.vaticana.d1</code>		<code>custodes.vaticana.d2</code>	
<code>accidentals.vaticanaM1</code>		<code>accidentals.vaticana0</code>	
<code>dots.dotvaticana</code>		<code>noteheads</code> <code>.svaticana.punctum</code>	
<code>noteheads.svaticana</code> <code>.punctum.cavum</code>		<code>noteheads.svaticana</code> <code>.linea.punctum</code>	
<code>noteheads.svaticana</code> <code>.linea.punctum.cavum</code>		<code>noteheads.svaticana</code> <code>.inclinatum</code>	
<code>noteheads.svaticana.lpes</code>		<code>noteheads</code> <code>.svaticana.vlpes</code>	
<code>noteheads.svaticana.upes</code>		<code>noteheads</code> <code>.svaticana.vupes</code>	
<code>noteheads</code> <code>.svaticana.plica</code>		<code>noteheads</code> <code>.svaticana.vplica</code>	
<code>noteheads</code> <code>.svaticana.epiphonus</code>		<code>noteheads.svaticana</code> <code>.vepiphonus</code>	
<code>noteheads.svaticana</code> <code>.reverse.plica</code>		<code>noteheads.svaticana</code> <code>.reverse.vplica</code>	
<code>noteheads.svaticana</code> <code>.inner.cephalicus</code>		<code>noteheads.svaticana</code> <code>.cephalicus</code>	
<code>noteheads</code> <code>.svaticana.quilisma</code>			

## Medicaea glyphs

<code>clefs.medicaea.do</code>		<code>clefs.medicaea.do_change</code>	
<code>clefs.medicaea.fa</code>		<code>clefs.medicaea.fa_change</code>	
<code>custodes.medicaea.u0</code>		<code>custodes.medicaea.u1</code>	
<code>custodes.medicaea.u2</code>		<code>custodes.medicaea.d0</code>	
<code>custodes.medicaea.d1</code>		<code>custodes.medicaea.d2</code>	
<code>accidentals.medicaeaM1</code>		<code>noteheads.smedicaea.inclinatum</code>	
<code>noteheads.smedicaea.punctum</code>		<code>noteheads.smedicaea.rvirga</code>	
<code>noteheads.smedicaea.virga</code>			

## Hufnagel glyphs

<code>clefs.hufnagel.do</code>		<code>clefs.hufnagel.do_change</code>	
<code>clefs.hufnagel.fa</code>		<code>clefs.hufnagel.fa_change</code>	
<code>clefs.hufnagel.do.fa</code>		<code>clefs.hufnagel.do.fa_change</code>	
<code>custodes.hufnagel.u0</code>		<code>custodes.hufnagel.u1</code>	
<code>custodes.hufnagel.u2</code>		<code>custodes.hufnagel.d0</code>	
<code>custodes.hufnagel.d1</code>		<code>custodes.hufnagel.d2</code>	

accidentals.hufnagelM1		noteheads	
		.shufnagel.punctum	

noteheads		noteheads.shufnagel.lpes	
.shufnagel.virga			

## Mensural glyphs

rests.M3mensural		rests.M2mensural	
------------------	---	------------------	---

rests.M1mensural		rests.0mensural	
------------------	---	-----------------	---

rests.1mensural		rests.2mensural	
-----------------	---	-----------------	---

rests.3mensural		rests.4mensural	
-----------------	---	-----------------	---

clefs.mensural.c		clefs.mensural.c_change	
------------------	---	-------------------------	---

clefs.mensural.f		clefs.mensural.f_change	
------------------	---	-------------------------	---


clefs.mensural.g		clefs.mensural.g_change	
------------------	---	-------------------------	---

custodes.mensural.u0		custodes.mensural.u1	
----------------------	---	----------------------	---































custodes.mensural.u2		custodes.mensural.d0	
----------------------	---	----------------------	---















custodes.mensural.d1		custodes.mensural.d2	
----------------------	---	----------------------	---

accidentals.mensural1		accidentals.mensuralM1	
-----------------------	---	------------------------	---

















flags.mensuralu03		flags.mensuralu13	
-------------------	---	-------------------	---

flags.mensuralu23	)	flags.mensurald03	(
flags.mensurald13	(	flags.mensurald23	(
flags.mensuralu04	}	flags.mensuralu14	}
flags.mensuralu24	}	flags.mensurald04	{
flags.mensurald14	{	flags.mensurald24	{
flags.mensuralu05	}	flags.mensuralu15	}
flags.mensuralu25	}	flags.mensurald05	{
flags.mensurald15	{	flags.mensurald25	{
flags.mensuralu06	}	flags.mensuralu16	}
flags.mensuralu26	}	flags.mensurald06	{
flags.mensurald16	{	flags.mensurald26	{
timesig.mensural44	C	timesig.mensural22	¢
timesig.mensural32	O	timesig.mensural64	⊙
timesig.mensural94	⊙	timesig.mensural34	⊕



















timesig.mensural68		timesig.mensural98	
timesig.mensural48		timesig.mensural68alt	
timesig.mensural24		noteheads.um3mensural	
noteheads.dm3mensural		noteheads.sm3ligmensural	
noteheads.um2mensural		noteheads.dm2mensural	
noteheads.sm2ligmensural		noteheads.sm1mensural	
noteheads.ur3mensural		noteheads.dr3mensural	
noteheads .sr3ligmensural		noteheads.ur2mensural	
noteheads.dr2mensural		noteheads .sr2ligmensural	
noteheads.sr1mensural		noteheads .um3semimensural	
noteheads .dm3semimensural		noteheads .sm3semiligmensural	
noteheads .um2semimensural		noteheads .dm2semimensural	
noteheads .sm2semiligmensural		noteheads .sm1semimensural	
noteheads .ur3semimensural		noteheads .dr3semimensural	
noteheads .sr3semiligmensural		noteheads .ur2semimensural	

noteheads .drM2semimensural		noteheads .srM2semiligmensural	
noteheads .srM1semimensural		noteheads .uM3blackmensural	
noteheads .dM3blackmensural		noteheads .sM3blackligmensural	
noteheads .uM2blackmensural		noteheads .dM2blackmensural	
noteheads .sM2blackligmensural		noteheads .sM1blackmensural	
noteheads.s0mensural		noteheads.s1mensural	
noteheads.s2mensural		noteheads .s0blackmensural	











## Neomensural glyphs











rests.M3neomensural		rests.M2neomensural	
rests.M1neomensural		rests.0neomensural	
rests.1neomensural		rests.2neomensural	
rests.3neomensural		rests.4neomensural	
clefs.neomensural.c		clefs.neomensural .c_change	
timesig.neomensural44		timesig.neomensural22	
timesig.neomensural32		timesig.neomensural64	
timesig.neomensural94		timesig.neomensural34	










timesig.neomensural68		timesig.neomensural98	
timesig.neomensural48		timesig.neomensural68alt	
timesig.neomensural24		noteheads.um3neomensural	
noteheads.dm3neomensural		noteheads.um2neomensural	
noteheads.dm2neomensural		noteheads.sm1neomensural	
noteheads .urM3neomensural		noteheads .drM3neomensural	
noteheads .urM2neomensural		noteheads .drM2neomensural	
noteheads .srM1neomensural		noteheads.s0neomensural	
noteheads.slneomensural		noteheads.s2neomensural	

## Petrucchi glyphs

clefs.petrucchi.c1		clefs.petrucchi.c1_change	
clefs.petrucchi.c2		clefs.petrucchi.c2_change	
clefs.petrucchi.c3		clefs.petrucchi.c3_change	
clefs.petrucchi.c4		clefs.petrucchi.c4_change	
clefs.petrucchi.c5		clefs.petrucchi.c5_change	

<code>clefs.petrucchi.f</code>		<code>clefs.petrucchi.f_change</code>	
<code>clefs.petrucchi.g</code>		<code>clefs.petrucchi.g_change</code>	
<code>noteheads.s0petrucci</code>		<code>noteheads.s1petrucci</code>	
<code>noteheads.s2petrucci</code>		<code>noteheads.s0blackpetrucci</code>	
<code>noteheads.s1blackpetrucci</code>		<code>noteheads.s2blackpetrucci</code>	


## Solesmes glyphs

<code>noteheads.ssolesmes.incl.parvum</code>		<code>noteheads.ssolesmes.auct.asc</code>	
<code>noteheads.ssolesmes.auct.desc</code>		<code>noteheads.ssolesmes.incl.auctum</code>	
<code>noteheads.ssolesmes.stropha</code>		<code>noteheads.ssolesmes.stropha.aucta</code>	
<code>noteheads.ssolesmes.oriscus</code>			


## A.8 Note head styles

The following styles may be used for note heads.


default                      altdefault



9                      baroque                      neomensural



17                      mensural                      petrucci



25      harmonic      harmonic-black

33      harmonic-mixed      diamond

41      cross      xcircle

49      triangle      slash

## A.9 Text markup commands

The following commands can all be used inside `\markup { }`.

### A.9.1 Font

`\abs-fontsize size (number) arg (markup)`

Use *size* as the absolute font size to display *arg*. Adjusts `baseline-skip` and `word-space` accordingly.

```
\markup {
  default text font size
  \hspace #2
  \abs-fontsize #16 { text font size 16 }
  \hspace #2
  \abs-fontsize #12 { text font size 12 }
}
```

default text font size    **text font size 16**    text font size 12

`\bold arg (markup)`

Switch to bold font-series.

```
\markup {
  default
  \hspace #2
  \bold
  bold
}
```

default    **bold**

`\box arg (markup)`

Draw a box round *arg*. Looks at `thickness`, `box-padding` and `font-size` properties to determine line thickness and padding around the markup.

```
\markup {
  \override #'(box-padding . 0.5)
  \box
  \line { V. S. }
}
```

V. S.

Used properties:

- `box-padding` (0.2)
- `font-size` (0)
- `thickness` (1)

`\caps arg` (markup)

Copy of the `\smallCaps` command.

```
\markup {
  default
  \hspace #2
  \caps {
    Text in small caps
  }
}
```

default TEXT IN SMALL CAPS

`\dynamic arg` (markup)

Use the dynamic font. This font only contains **s**, **f**, **m**, **z**, **p**, and **r**. When producing phrases, like ‘più **f**’, the normal words (like ‘più’) should be done in a different font. The recommended font for this is bold and italic.

```
\markup {
  \dynamic {
    sfzp
  }
}
```

***sfzp***

`\finger arg` (markup)

Set *arg* as small numbers.

```
\markup {
  \finger {
    1 2 3 4 5
  }
}
```

**1 2 3 4 5**

`\fontCaps arg` (markup)

Set `font-shape` to caps

Note: `\fontCaps` requires the installation and selection of fonts which support the caps font shape.

`\fontsize` *increment* (number) *arg* (markup)

Add *increment* to the font-size. Adjusts **baseline-skip** accordingly.

```
\markup {
  default
  \hspace #2
  \fontsize #-1.5
  smaller
}
```

**default**    **smaller**

Used properties:

- **baseline-skip** (2)
- **word-space** (1)
- **font-size** (0)

`\huge` *arg* (markup)

Set font size to +2.

```
\markup {
  default
  \hspace #2
  \huge
  huge
}
```

**default**    **huge**

`\italic` *arg* (markup)

Use italic **font-shape** for *arg*.

```
\markup {
  default
  \hspace #2
  \italic
  italic
}
```

**default**    ***italic***

`\large` *arg* (markup)

Set font size to +1.

```
\markup {
  default
  \hspace #2
  \large
  large
}
```

**default**    **large**

`\larger` *arg* (markup)

Increase the font size relative to the current setting.

```
\markup {
  default
  \hspace #2
  \larger
  larger
}
```

default    larger

`\magnify` *sz* (number) *arg* (markup)

Set the font magnification for its argument. In the following example, the middle A is 10% larger:

```
A \magnify #1.1 { A } A
```

Note: Magnification only works if a font name is explicitly selected. Use `\fontsize` otherwise.

```
\markup {
  default
  \hspace #2
  \magnify #1.5 {
    50% larger
  }
}
```

default    50% larger

`\medium` *arg* (markup)

Switch to medium font-series (in contrast to bold).

```
\markup {
  \bold {
    some bold text
    \hspace #2
    \medium {
      medium font series
    }
    \hspace #2
    bold again
  }
}
```

**some bold text**    medium font series    **bold again**

`\normal-size-sub` *arg* (markup)

Set *arg* in subscript with a normal font size.

```
\markup {
  default
  \normal-size-sub {
    subscript in standard size
  }
}
```

default    subscript in standard size

Used properties:

- `baseline-skip`

`\normal-size-super arg` (markup)

Set *arg* in superscript with a normal font size.

```
\markup {
  default
  \normal-size-super {
    superscript in standard size
  }
}
```

**default** superscript in standard size

Used properties:

- `baseline-skip`

`\normal-text arg` (markup)

Set all font related properties (except the size) to get the default normal text font, no matter what font was used earlier.

```
\markup {
  \huge \bold \sans \caps {
    huge bold sans caps
    \hspace #2
    \normal-text {
      huge normal
    }
  }
  \hspace #2
  as before
}
```

**HUGE BOLD SANS CAPS** huge normal **AS BEFORE**

`\normalsize arg` (markup)

Set font size to default.

```
\markup {
  \teeny {
    this is very small
    \hspace #2
    \normalsize {
      normal size
    }
  }
  \hspace #2
  teeny again
}
```

this is very small **normal size** teeny again

`\number arg` (markup)

Set font family to `number`, which yields the font used for time signatures and fingerings. This font contains numbers and some punctuation; it has no letters.

```
\markup {
  \number {
    0 1 2 3 4 5 6 7 8 9 . ,
  }
}
```

**0123456789.,**

`\replace` *replacements* (list) *arg* (markup)

Used to automatically replace a string by another in the markup *arg*. Each pair of the alist *replacements* specifies what should be replaced. The **key** is the string to be replaced by the **value** string.

```
\markup \replace #'(("thx" . "Thanks!")) thx
```

**Thanks!**

`\roman` *arg* (markup)

Set font family to roman.

```
\markup {
  \sans \bold {
    sans serif, bold
    \hspace #2
    \roman {
      text in roman font family
    }
    \hspace #2
    return to sans
  }
}
```

**sans serif, bold    text in roman font family    return to sans**

`\sans` *arg* (markup)

Switch to the sans serif font family.

```
\markup {
  default
  \hspace #2
  \sans {
    sans serif
  }
}
```

**default    sans serif**

`\simple` *str* (string)

A simple text string; `\markup { foo }` is equivalent with `\markup { \simple #"foo" }`.

Note: for creating standard text markup or defining new markup commands, the use of `\simple` is unnecessary.

```
\markup {
  \simple #"simple"
```



```

\simple #"text"
\simple #"strings"
}

```

simple text strings

`\small arg` (markup)  
Set font size to -1.

```

\markup {
  default
  \hspace #2
  \small
  small
}

```

default    small

`\smallCaps arg` (markup)  
Emit *arg* as small caps.  
Note: `\smallCaps` does not support accented characters.

```

\markup {
  default
  \hspace #2
  \smallCaps {
    Text in small caps
  }
}

```

default    TEXT IN SMALL CAPS

`\smaller arg` (markup)  
Decrease the font size relative to the current setting.

```

\markup {
  \fontsize #3.5 {
    some large text
    \hspace #2
    \smaller {
      a bit smaller
    }
    \hspace #2
    more large text
  }
}

```

some large text    a bit smaller    more large text

`\sub arg` (markup)  
Set *arg* in subscript.

```

\markup {
  \concat {
    H

```

```

\sub {
  2
}
0
}
}

```

$$\text{H}_2\text{O}$$

Used properties:

- `baseline-skip`
- `font-size (0)`

`\super arg (markup)`  
Set *arg* in superscript.

```

\markup {
  E =
  \concat {
    mc
    \super
    2
  }
}

```

$$E = mc^2$$

Used properties:

- `baseline-skip`
- `font-size (0)`

`\teeny arg (markup)`  
Set font size to -3.

```

\markup {
  default
  \hspace #2
  \teeny
  teeny
}

```

**default**    *teeny*

`\text arg (markup)`  
Use a text font instead of music symbol or music alphabet font.

```

\markup {
  \number {
    1, 2,
    \text {
      three, four,
    }
  }
  5
}

```

}

**1, 2, three, four, 5**

`\tiny arg` (markup)

Set font size to -2.

```
\markup {
  default
  \hspace #2
  \tiny
  tiny
}
```

default tiny

`\typewriter arg` (markup)

Use font-family typewriter for *arg*.

```
\markup {
  default
  \hspace #2
  \typewriter
  typewriter
}
```

default typewriter

`\underline arg` (markup)

Underline *arg*. Looks at `thickness` to determine line thickness, and `offset` to determine line y-offset.

```
\markup \fill-line {
  \underline "underlined"
  \override #'(offset . 5)
  \override #'(thickness . 1)
  \underline "underlined"
  \override #'(offset . 1)
  \override #'(thickness . 5)
  \underline "underlined"
}
```

underlined

underlined

underlined

Used properties:

- `offset` (2)
- `thickness` (1)

`\upright arg` (markup)

Set font-shape to upright. This is the opposite of *italic*.

```
\markup {
  \italic {
    italic text
  }
  \hspace #2
  \upright {
```

```

        upright text
      }
      \hspace #2
      italic again
    }
  }

italic text   upright text   italic again

```

### A.9.2 Align

`\center-align` *arg* (markup)

Align *arg* to its X center.

```

\markup {
  \column {
    one
    \center-align
    two
    three
  }
}

```

```

one
two
three

```

`\center-column` *args* (markup list)

Put *args* in a centered column.

```

\markup {
  \center-column {
    one
    two
    three
  }
}

```

```

one
two
three

```

Used properties:

- `baseline-skip`

`\column` *args* (markup list)

Stack the markups in *args* vertically. The property `baseline-skip` determines the space between markups in *args*.

```

\markup {
  \column {
    one
    two
    three
  }
}

```

one  
two  
three

Used properties:

- `baseline-skip`

`\combine` *arg1* (markup) *arg2* (markup)

Print two markups on top of each other.

Note: `\combine` cannot take a list of markups enclosed in curly braces as an argument; the follow example will not compile:

```
\combine { a list }
\markup {
  \fontsize #5
  \override #'(thickness . 2)
  \combine
    \draw-line #'(0 . 4)
    \arrow-head #Y #DOWN ##f
}
```



`\concat` *args* (markup list)

Concatenate *args* in a horizontal line, without spaces in between. Strings and simple markups are concatenated on the input level, allowing ligatures. For example, `\concat { "f" \simple #"i" }` is equivalent to `"fi"`.

```
\markup {
  \concat {
    one
    two
    three
  }
}
```

onetwothree

`\dir-column` *args* (markup list)

Make a column of *args*, going up or down, depending on the setting of the `direction` layout property.

```
\markup {
  \override #`(direction . ,UP) {
    \dir-column {
      going up
    }
  }
  \hspace #1
  \dir-column {
    going down
  }
  \hspace #1
  \override #'(direction . 1) {
    \dir-column {
      going up
    }
  }
}
```

```

    }
  }
}

up      up
going  going  going
      down

```

Used properties:

- `baseline-skip`
- `direction`

`\fill-line` *args* (markup list)

Put *markups* in a horizontal line of width *line-width*. The markups are spaced or flushed to fill the entire line. If there are no arguments, return an empty stencil.

```

\markup {
  \column {
    \fill-line {
      Words evenly spaced across the page
    }
    \null
    \fill-line {
      \line { Text markups }
      \line {
        \italic { evenly spaced }
      }
      \line { across the page }
    }
  }
}

```

Words          evenly          spaced          across          the          page

Text markups                      *evenly spaced*                      across the page

Used properties:

- `line-width` (#f)
- `word-space` (0.6)
- `text-direction` (1)

`\fill-with-pattern` *space* (number) *dir* (direction) *pattern* (markup) *left* (markup) *right* (markup)

Put *left* and *right* in a horizontal line of width *line-width* with a line of markups *pattern* in between. Patterns are spaced apart by *space*. Patterns are aligned to the *dir* markup.

```

\markup \column {
  "right-aligned : "
  \fill-with-pattern #1 #RIGHT . first right
  \fill-with-pattern #1 #RIGHT . second right
  \null
  "center-aligned : "
  \fill-with-pattern #1.5 #CENTER - left right
}

```

```

\null
"left-aligned :
\override #'(line-width . 50)
\fill-with-pattern #2 #LEFT : left first
\override #'(line-width . 50)
\fill-with-pattern #2 #LEFT : left second
}

```

```

right-aligned :
first ..... right
second ..... right

```

```

center-aligned :
left - - - - - right

```

```

left-aligned :
left: : : : : : : : : : : : : : : first
left: : : : : : : : : : : : : : : second

```

Used properties:

- line-width
- word-space

`\general-align axis (integer) dir (number) arg (markup)`

Align *arg* in *axis* direction to the *dir* side.

```

\markup {
  \column {
    one
    \general-align #X #LEFT
    two
    three
  }
  \null
  one
  \general-align #X #CENTER
  two
  three
}
\markup {
  \line {
    one
    \general-align #Y #UP
    two
    three
  }
  \null
  \line {
    one
    \general-align #Y #3.2
    two
    three
  }
}

```

}

one  
two  
three

one  
two  
three

one two three

one three  
two

`\halign` *dir* (number) *arg* (markup)

Set horizontal alignment. If *dir* is `-1`, then it is left-aligned, while `+1` is right. Values in between interpolate alignment accordingly.

```
\markup {
  \column {
    one
    \halign #LEFT
    two
    three
    \null
    one
    \halign #CENTER
    two
    three
    \null
    one
    \halign #RIGHT
    two
    three
    \null
    one
    \halign #-5
    two
    three
  }
}
```



one  
two  
three

one  
two  
three


one  
two  
three

one  
two  
three

`\hcenter-in` *length* (number) *arg* (markup)

Center *arg* horizontally within a box of extending *length*/2 to the left and right.

```
\new StaffGroup <<
  \new Staff {
    \set Staff.instrumentName = \markup {
      \hcenter-in #12
      Oboe
    }
    c'1
  }
  \new Staff {
    \set Staff.instrumentName = \markup {
      \hcenter-in #12
      Bassoon
    }
    \clef tenor
    c'1
  }
>>
```



`\hspace` *amount* (number)

Create an invisible object taking up horizontal space *amount*.

```
\markup {
  one
  \hspace #2
  two
  \hspace #8
  three
}
```

one    two            three

Used properties:

- `word-space`

`\justify-field` *symbol* (symbol)

Justify the data which has been assigned to *symbol*.

```
\header {
  title = "My title"
  myText = "Lorem ipsum dolor sit amet, consectetur adipisicing
    elit, sed do eiusmod tempor incididunt ut labore et dolore magna
    aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco
    laboris nisi ut aliquip ex ea commodo consequat."
}

\paper {
  bookTitleMarkup = \markup {
    \column {
      \fill-line { \fromproperty #'header:title }
      \null
      \justify-field #'header:myText
    }
  }
}

\markup {
  \null
}
```

My title

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.

`\justify` *args* (markup list)

Like `\wordwrap`, but with lines stretched to justify the margins. Use `\override #'(line-width . X)` to set the line width; *X* is the number of staff spaces.

```
\markup {
  \justify {
    Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed
    do eiusmod tempor incididunt ut labore et dolore magna aliqua.
    Ut enim ad minim veniam, quis nostrud exercitation ullamco
    laboris nisi ut aliquip ex ea commodo consequat.
  }
}
```

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.

Used properties:

- `text-direction` (1)
- `word-space`
- `line-width` (#f)
- `baseline-skip`

`\justify-string` *arg* (string)

Justify a string. Paragraphs may be separated with double newlines

```
\markup {
  \override #'(line-width . 40)
  \justify-string #"Lorem ipsum dolor sit amet, consectetur
    adipisicing elit, sed do eiusmod tempor incididunt ut labore
    et dolore magna aliqua.

    Ut enim ad minim veniam, quis nostrud exercitation ullamco
    laboris nisi ut aliquip ex ea commodo consequat.

    Excepteur sint occaecat cupidatat non proident, sunt in culpa
    qui officia deserunt mollit anim id est laborum"
}
```

Lorem ipsum dolor sit amet,  
consectetur adipisicing elit, sed do  
eiusmod tempor incididunt ut labore et  
dolore magna aliqua.

Ut enim ad minim veniam, quis nostrud  
exercitation ullamco laboris nisi ut  
aliquip ex ea commodo consequat.

Excepteur sint occaecat cupidatat non  
proident, sunt in culpa qui officia  
deserunt mollit anim id est laborum

Used properties:

- `text-direction` (1)
- `word-space`
- `line-width`
- `baseline-skip`

`\left-align` *arg* (markup)

Align *arg* on its left edge.

```
\markup {
  \column {
    one
    \left-align
    two
    three
  }
}
```

one  
two  
three

`\left-column` *args* (markup list)

Put *args* in a left-aligned column.

```
\markup {
  \left-column {
    one
    two
    three
  }
}
```

one  
two  
three

Used properties:

- `baseline-skip`

`\line` *args* (markup list)

Put *args* in a horizontal line. The property `word-space` determines the space between markups in *args*.

```
\markup {
  \line {
    one two three
  }
}
```

one two three

Used properties:

- `text-direction` (1)
- `word-space`

`\lower` *amount* (number) *arg* (markup)

Lower *arg* by the distance *amount*. A negative *amount* indicates raising; see also `\raise`.

```
\markup {
  one
  \lower #3
  two
  three
}
```

one      three  
two

`\pad-around` *amount* (number) *arg* (markup)

Add padding *amount* all around *arg*.

```
\markup {
  \box {
    default
  }
}
```

```

    }
    \hspace #2
    \box {
      \pad-around #0.5 {
        padded
      }
    }
  }
}

```

default	padded
---------	--------

`\pad-markup` *amount* (number) *arg* (markup)  
Add space around a markup object.

```

\markup {
  \box {
    default
  }
  \hspace #2
  \box {
    \pad-markup #1 {
      padded
    }
  }
}

```

default	padded
---------	--------

`\pad-to-box` *x-ext* (pair of numbers) *y-ext* (pair of numbers) *arg* (markup)  
Make *arg* take at least *x-ext*, *y-ext* space.

```

\markup {
  \box {
    default
  }
  \hspace #4
  \box {
    \pad-to-box #'(0 . 10) #'(0 . 3) {
      padded
    }
  }
}

```

default	padded
---------	--------

`\pad-x` *amount* (number) *arg* (markup)  
Add padding *amount* around *arg* in the X direction.

```

\markup {
  \box {
    default
  }
}

```

```

\hspace #4
\box {
  \pad-x #2 {
    padded
  }
}
}

```

default	padded
---------	--------

`\put-adjacent` *axis* (integer) *dir* (direction) *arg1* (markup) *arg2* (markup)

Put *arg2* next to *arg1*, without moving *arg1*.

`\raise` *amount* (number) *arg* (markup)

Raise *arg* by the distance *amount*. A negative *amount* indicates lowering, see also `\lower`.

The argument to `\raise` is the vertical displacement amount, measured in (global) staff spaces. `\raise` and `\super` raise objects in relation to their surrounding markups.

If the text object itself is positioned above or below the staff, then `\raise` cannot be used to move it, since the mechanism that positions it next to the staff cancels any shift made with `\raise`. For vertical positioning, use the `padding` and/or `extra-offset` properties.

```

\markup {
  C
  \small
  \bold
  \raise #1.0
  9/7+
}

```

**C 9/7+**

`\right-align` *arg* (markup)

Align *arg* on its right edge.

```

\markup {
  \column {
    one
    \right-align
    two
    three
  }
}

```

one  
two  
three

`\right-column` *args* (markup list)

Put *args* in a right-aligned column.

```
\markup {
  \right-column {
    one
    two
    three
  }
}
```

```
one
two
three
```

Used properties:

- `baseline-skip`

`\rotate` *ang* (number) *arg* (markup)

Rotate object with *ang* degrees around its center.

```
\markup {
  default
  \hspace #2
  \rotate #45
  \line {
    rotated 45°
  }
}
```

```
default
```

```
rotated 45°
```

`\translate` *offset* (pair of numbers) *arg* (markup)

Translate *arg* relative to its surroundings. *offset* is a pair of numbers representing the displacement in the X and Y axis.

```
\markup {
  *
  \translate #'(2 . 3)
  \line { translated two spaces right, three up }
}
```

```
translated two spaces right, three up
```

```
*
```

`\translate-scaled` *offset* (pair of numbers) *arg* (markup)

Translate *arg* by *offset*, scaling the offset by the `font-size`.

```
\markup {
  \fontsize #5 {
    * \translate #'(2 . 3) translate
    \hspace #2
    * \translate-scaled #'(2 . 3) translate-scaled
  }
}
```

# \* **translate** \*

## translate-scaled

Used properties:

- `font-size` (0)

`\vcenter` *arg* (markup)

Align *arg* to its Y center.

```
\markup {
  one
  \vcenter
  two
  three
}
```

one *two* three

`\vspace` *amount* (number)

Create an invisible object taking up vertical space of *amount* multiplied by 3.

```
\markup {
  \center-column {
    one
    \vspace #2
    two
    \vspace #5
    three
  }
}
```

one

two

three

`\wordwrap-field` *symbol* (symbol)

Wordwrap the data which has been assigned to *symbol*.

```
\header {
  title = "My title"
  myText = "Lorem ipsum dolor sit amet, consectetur adipisicing
    elit, sed do eiusmod tempor incididunt ut labore et dolore
    magna aliqua. Ut enim ad minim veniam, quis nostrud
    exercitation ullamco laboris nisi ut aliquip ex ea commodo
    consequat."
}
```

```
\paper {
```



```

bookTitleMarkup = \markup {
  \column {
    \fill-line { \fromproperty #'header:title }
    \null
    \wordwrap-field #'header:myText
  }
}

\markup {
  \null
}

```

My title

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.

`\wordwrap` *args* (markup list)

Simple wordwrap. Use `\override #'(line-width . X)` to set the line width, where *X* is the number of staff spaces.

```

\markup {
  \wordwrap {
    Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed
    do eiusmod tempor incididunt ut labore et dolore magna aliqua.
    Ut enim ad minim veniam, quis nostrud exercitation ullamco
    laboris nisi ut aliquip ex ea commodo consequat.
  }
}

```

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.

Used properties:

- `text-direction` (1)
- `word-space`
- `line-width` (*#f*)
- `baseline-skip`

`\wordwrap-string` *arg* (string)

Wordwrap a string. Paragraphs may be separated with double newlines.

```

\markup {
  \override #'(line-width . 40)
  \wordwrap-string #"Lorem ipsum dolor sit amet, consectetur

```

```

    adipisicing elit, sed do eiusmod tempor incididunt ut labore
    et dolore magna aliqua.

    Ut enim ad minim veniam, quis nostrud exercitation ullamco
    laboris nisi ut aliquip ex ea commodo consequat.

    Excepteur sint occaecat cupidatat non proident, sunt in culpa
    qui officia deserunt mollit anim id est laborum"
}

```

Lorem ipsum dolor sit amet,  
 consectetur adipisicing elit, sed do  
 eiusmod tempor incididunt ut labore  
 et dolore magna aliqua.  
 Ut enim ad minim veniam, quis  
 nostrud exercitation ullamco laboris  
 nisi ut aliquip ex ea commodo  
 consequat.  
 Excepteur sint occaecat cupidatat non  
 proident, sunt in culpa qui officia  
 deserunt mollit anim id est laborum

Used properties:

- `text-direction` (1)
- `word-space`
- `line-width`
- `baseline-skip`

### A.9.3 Graphic

`\arrow-head` *axis* (integer) *dir* (direction) *filled* (boolean)

Produce an arrow head in specified direction and axis. Use the filled head if *filled* is specified.

```

\markup {
  \fontsize #5 {
    \general-align #Y #DOWN {
      \arrow-head #Y #UP ##t
      \arrow-head #Y #DOWN ##f
      \hspace #2
      \arrow-head #X #RIGHT ##f
      \arrow-head #X #LEFT ##f
    }
  }
}

```

▲ ▼ ➤ ➤

`\beam` *width* (number) *slope* (number) *thickness* (number)

Create a beam with the specified parameters.

```
\markup {
  \beam #5 #1 #2
}
```



`\bracket arg (markup)`  
Draw vertical brackets around *arg*.

```
\markup {
  \bracket {
    \note #"2." #UP
  }
}
```



`\circle arg (markup)`  
Draw a circle around *arg*. Use `thickness`, `circle-padding` and `font-size` properties to determine line thickness and padding around the markup.

```
\markup {
  \circle {
    Hi
  }
}
```



Used properties:

- `circle-padding` (0.2)
- `font-size` (0)
- `thickness` (1)

`\draw-circle radius (number) thickness (number) filled (boolean)`  
A circle of radius *radius* and thickness *thickness*, optionally filled.

```
\markup {
  \draw-circle #2 #0.5 ##f
  \hspace #2
  \draw-circle #2 #0 ##t
}
```



`\draw-hline`

Draws a line across a page, where the property `span-factor` controls what fraction of the page is taken up.

```
\markup {
  \column {
    \draw-hline
  }
}
```

```

\override #'(span-factor . 1/3)
\draw-hline
}
}

```

---

Used properties:

- `span-factor` (1)
- `line-width`
- `draw-line-markup`

`\draw-line` *dest* (pair of numbers)

A simple line.

```

\markup {
  \draw-line #'(4 . 4)
  \override #'(thickness . 5)
  \draw-line #'(-3 . 0)
}

```



Used properties:

- `thickness` (1)


`\epsfile` *axis* (number) *size* (number) *file-name* (string)

Inline an EPS image. The image is scaled along *axis* to *size*.

```

\markup {
  \general-align #Y #DOWN {
    \epsfile #X #20 #"context-example.eps"
    \epsfile #Y #20 #"context-example.eps"
  }
}

```



`\filled-box` *xext* (pair of numbers) *yext* (pair of numbers) *blot* (number)

Draw a box with rounded corners of dimensions *xext* and *yext*. For example,

```

\filled-box #'(-.3 . 1.8) #'(-.3 . 1.8) #0

```

creates a box extending horizontally from -0.3 to 1.8 and vertically from -0.3 up to 1.8, with corners formed from a circle of diameter 0 (i.e., sharp corners).

```

\markup {
  \filled-box #'(0 . 4) #'(0 . 4) #0
  \filled-box #'(0 . 2) #'(-4 . 2) #0.4
}

```

```

\filled-box #'(1 . 8) #'(0 . 7) #0.2
\with-color #white
\filled-box #'(-4.5 . -2.5) #'(3.5 . 5.5) #0.7
}

```



`\hbracket` *arg* (markup)  
 Draw horizontal brackets around *arg*.

```

\markup {
  \hbracket {
    \line {
      one two three
    }
  }
}

```

one two three

`\parenthesize` *arg* (markup)  
 Draw parentheses around *arg*. This is useful for parenthesizing a column containing several lines of text.

```

\markup {
  \line {
    \parenthesize {
      \column {
        foo
        bar
      }
    }
    \override #'(angularity . 2) {
      \parenthesize {
        \column {
          bah
          baz
        }
      }
    }
  }
}

```

$\left(\begin{smallmatrix} \text{foo} \\ \text{bar} \end{smallmatrix}\right)\left(\begin{smallmatrix} \text{bah} \\ \text{baz} \end{smallmatrix}\right)$

Used properties:

- `width` (0.25)
- `thickness` (1)
- `size` (1)

- padding
- angularity (0)

`\path thickness (number) commands (list)`

Draws a path with line thickness *thickness* according to the directions given in *commands*. *commands* is a list of lists where the *car* of each sublist is a drawing command and the *cdr* comprises the associated arguments for each command.

Line-cap styles and line-join styles may be customized by overriding the `line-cap-style` and `line-join-style` properties, respectively. Available line-cap styles are 'butt, 'round, and 'square. Available line-join styles are 'miter, 'round, and 'bevel.

The property `filled` specifies whether or not the path is filled with color.

There are seven commands available to use in the list *commands*: `moveto`, `rmoveto`, `lineto`, `rlineto`, `curveto`, `rcurveto`, and `closepath`. Note that the commands that begin with *r* are the relative variants of the other three commands.

The commands `moveto`, `rmoveto`, `lineto`, and `rlineto` take 2 arguments; they are the X and Y coordinates for the destination point.

The commands `curveto` and `rcurveto` create cubic Bézier curves, and take 6 arguments; the first two are the X and Y coordinates for the first control point, the second two are the X and Y coordinates for the second control point, and the last two are the X and Y coordinates for the destination point.

The `closepath` command takes zero arguments and closes the current subpath in the active path.

Note that a sequence of commands *must* begin with a `moveto` or `rmoveto` to work with the SVG output.

```
samplePath =
  #'((moveto 0 0)
    (lineto -1 1)
    (lineto 1 1)
    (lineto 1 -1)
    (curveto -5 -5 -5 5 -1 0)
    (closepath))
```

```
\markup {
  \path #0.25 #samplePath
}
```



Used properties:

- filled (#f)
- line-join-style (round)
- line-cap-style (round)

`\postscript str (string)`

This inserts *str* directly into the output as a PostScript command string.

```
ringsps = #
0.15 setlinewidth
0.9 0.6 moveto
0.4 0.6 0.5 0 361 arc
```

```

stroke
1.0 0.6 0.5 0 361 arc
stroke
"

rings = \markup {
  \with-dimensions #'(-0.2 . 1.6) #'(0 . 1.2)
  \postscript #ringsps
}

\relative c'' {
  c2^\rings
  a2_\rings
}

```



`\rounded-box` *arg* (markup)

Draw a box with rounded corners around *arg*. Looks at **thickness**, **box-padding** and **font-size** properties to determine line thickness and padding around the markup; the **corner-radius** property makes it possible to define another shape for the corners (default is 1).

```

c4^\markup {
  \rounded-box {
    Overtura
  }
}
c,8. c16 c4 r

```



Used properties:

- **box-padding** (0.5)
- **font-size** (0)
- **corner-radius** (1)
- **thickness** (1)

`\scale factor-pair` (pair of numbers) *arg* (markup)

Scale *arg*. *factor-pair* is a pair of numbers representing the scaling-factor in the X and Y axes. Negative values may be used to produce mirror images.

```

\markup {
  \line {
    \scale #'(2 . 1)
    stretched
    \scale #'(1 . -1)
    mirrored
  }
}

```

}

**stretched** `\triangle` *filled* (boolean)

A triangle, either filled or empty.

```
\markup {
  \triangle ##t
  \hspace #2
  \triangle ##f
}
```



Used properties:

- `baseline-skip` (2)
- `font-size` (0)
- `thickness` (0.1)

`\with-url` *url* (string) *arg* (markup)Add a link to URL *url* around *arg*. This only works in the PDF backend.

```
\markup {
  \with-url #"http://lilypond.org/web/" {
    LilyPond ... \italic {
      music notation for everyone
    }
  }
}
```

LilyPond ... *music notation for everyone*

### A.9.4 Music

`\customTabClef` *num-strings* (integer) *staff-space* (number)

Draw a tab clef sans-serif style.

`\doubleflat`

Draw a double flat symbol.

```
\markup {
  \doubleflat
}
```

`\doublesharp`

Draw a double sharp symbol.

```
\markup {
  \doublesharp
}
```

`\flat`

Draw a flat symbol.



```
\markup {
  \flat
}
```



`\musicglyph glyph-name (string)`

*glyph-name* is converted to a musical symbol; for example, `\musicglyph #\"accidentals.natural\"` selects the natural sign from the music font. See [Section “The Feta font” in \*Notation Reference\*](#) for a complete listing of the possible glyphs.

```
\markup {
  \musicglyph #\"f\"
  \musicglyph #\"rests.2\"
  \musicglyph #\"clefs.G_change\"
}
```



`\natural`

Draw a natural symbol.


```
\markup {
  \natural
}
```



`\note-by-number log (number) dot-count (number) dir (number)`

Construct a note symbol, with stem. By using fractional values for *dir*, longer or shorter stems can be obtained.

```
\markup {
  \note-by-number #3 #0 #DOWN
  \hspace #2
  \note-by-number #1 #2 #0.8
}
```



Used properties:

- `style '()`
- `font-size (0)`

`\note duration (string) dir (number)`

This produces a note with a stem pointing in *dir* direction, with the *duration* for the note head type and augmentation dots. For example, `\note #\"4.\" #-0.75` creates a dotted quarter note, with a shortened down stem.

```
\markup {
  \override #'(style . cross) {
    \note #\"4.\" #UP
  }
```

```

}
\hspace #2
\note #"breve" #0
}

```



Used properties:

- `style ('')`
- `font-size (0)`

`\score score (score)`

Inline an image of music.

```

\markup {
  \score {
    \new PianoStaff <<
      \new Staff \relative c' {
        \key f \major
        \time 3/4
        \mark \markup { Allegro }
        f2\p( a4)
        c2( a4)
        bes2( g'4)
        f8( e) e4 r
      }
      \new Staff \relative c {
        \clef bass
        \key f \major
        \time 3/4
        f8( a c a c a
        f c' es c es c)
        f,( bes d bes d bes)
        f( g bes g bes g)
      }
    >>
    \layout {
      indent = 0.0\cm
      \context {
        \Score
        \override RehearsalMark
          #'break-align-symbols = #'(time-signature key-signature)
        \override RehearsalMark
          #'self-alignment-X = #LEFT
      }
      \context {
        \Staff
        \override TimeSignature
          #'break-align-anchor-alignment = #LEFT
      }
    }
  }
}

```



Used properties:

- `baseline-skip`

`\semiflat`

Draw a semiflat symbol.

```
\markup {
  \semiflat
}
```

♭

`\semisharp`

Draw a semisharp symbol.

```
\markup {
  \semisharp
}
```

♮

`\sesquiflat`

Draw a 3/2 flat symbol.

```
\markup {
  \sesquiflat
}
```

♭

`\sesquisharp`

Draw a 3/2 sharp symbol.

```
\markup {
  \sesquisharp
}
```

♯

`\sharp`

Draw a sharp symbol.

```
\markup {
  \sharp
}
```

♯

`\tied-lyric` *str* (string)

Like `simple-markup`, but use tie characters for ‘~’ tilde symbols.

```
\markup \column {
  \tied-lyric #"Siam navi~all'onde~algenti Lasciate~in abbandono"
  \tied-lyric #"Impetuosi venti I nostri~affetti sono"
  \tied-lyric #"Ogni diletto~e scoglio Tutta la vita~e~un mar."
}
```

Siam naviall'onde algenti Lasciatein abbandono  
 Impetuosi venti I nostriaffetti sono  
 Ogni dilettoe scoglio Tutta la vitae un mar.

Used properties:

- `word-space`

### A.9.5 Instrument Specific Markup

`\fret-diagram` *definition-string* (string)

Make a (guitar) fret diagram. For example, say

```
\markup \fret-diagram #"s:0.75;6-x;5-x;4-o;3-2;2-3;1-2;"
```

for fret spacing 3/4 of staff space, D chord diagram

Syntax rules for *definition-string*:

- Diagram items are separated by semicolons.
- Possible items:
  - `s: number` – Set the fret spacing of the diagram (in staff spaces). Default: 1.
  - `t: number` – Set the line thickness (in staff spaces). Default: 0.05.
  - `h: number` – Set the height of the diagram in frets. Default: 4.
  - `w: number` – Set the width of the diagram in strings. Default: 6.
  - `f: number` – Set fingering label type (0 = none, 1 = in circle on string, 2 = below string). Default: 0.
  - `d: number` – Set radius of dot, in terms of fret spacing. Default: 0.25.
  - `p: number` – Set the position of the dot in the fret space. 0.5 is centered; 1 is on lower fret bar, 0 is on upper fret bar. Default: 0.6.
  - `c: string1-string2-fret` – Include a barre mark from *string1* to *string2* on *fret*.
  - `string-fret` – Place a dot on *string* at *fret*. If *fret* is ‘o’, *string* is identified as open. If *fret* is ‘x’, *string* is identified as muted.
  - `string-fret-fingering` – Place a dot on *string* at *fret*, and label with *fingering* as defined by the `f:` code.
- Note: There is no limit to the number of fret indications per string.

Used properties:

- `thickness` (0.5)
- `fret-diagram-details`
- `size` (1.0)
- `align-dir` (-0.4)

`\fret-diagram-terse` *definition-string* (string)

Make a fret diagram markup using terse string-based syntax.

Here is an example

```
\markup \fret-diagram-terse #"x;x;o;2;3;2;"
```

for a D chord diagram.

Syntax rules for *definition-string*:

- Strings are terminated by semicolons; the number of semicolons is the number of strings in the diagram.
- Mute strings are indicated by ‘x’.
- Open strings are indicated by ‘o’.
- A number indicates a fret indication at that fret.
- If there are multiple fret indicators desired on a string, they should be separated by spaces.
- Fingerings are given by following the fret number with a –, followed by the finger indicator, e.g. ‘3–2’ for playing the third fret with the second finger.
- Where a barre indicator is desired, follow the fret (or fingering) symbol with –( to start a barre and –) to end the barre.

Used properties:

- `thickness` (0.5)
- `fret-diagram-details`
- `size` (1.0)
- `align-dir` (-0.4)

```
\fret-diagram-verbose marking-list (pair)
```

Make a fret diagram containing the symbols indicated in *marking-list*.

For example,

```
\markup \fret-diagram-verbose
  #'((mute 6) (mute 5) (open 4)
    (place-fret 3 2) (place-fret 2 3) (place-fret 1 2))
```

produces a standard D chord diagram without fingering indications.

Possible elements in *marking-list*:

```
(mute string-number)
```

Place a small ‘x’ at the top of string *string-number*.

```
(open string-number)
```

Place a small ‘o’ at the top of string *string-number*.

```
(barre start-string end-string fret-number)
```

Place a barre indicator (much like a tie) from string *start-string* to string *end-string* at fret *fret-number*.

```
(capo fret-number)
```

Place a capo indicator (a large solid bar) across the entire fretboard at fret location *fret-number*. Also, set fret *fret-number* to be the lowest fret on the fret diagram.

```
(place-fret string-number fret-number [finger-value
[color-modifier]])
```

Place a fret playing indication on string *string-number* at fret *fret-number* with an optional fingering label *finger-value*, and an optional color modifier *color-modifier*. By default, the fret playing indicator is a solid dot. This can be globally changed by setting the value of the variable *dot-color*. Setting *color-modifier* to `inverted` inverts the dot color

for a specific fingering. If the *finger* part of the `place-fret` element is present, *finger-value* will be displayed according to the setting of the variable *finger-code*. There is no limit to the number of fret indications per string.

Used properties:

- `thickness` (0.5)
- `fret-diagram-details`
- `size` (1.0)
- `align-dir` (-0.4)

`\harp-pedal` *definition-string* (string)

Make a harp pedal diagram.

Possible elements in *definition-string*:

- ˆ            pedal is up
- pedal is neutral
- v            pedal is down
- |            vertical divider line
- o            the following pedal should be circled (indicating a change)

The function also checks if the string has the typical form of three pedals, then the divider and then the remaining four pedals. If not it prints out a warning. However, in any case, it will also print each symbol in the order as given. This means you can place the divider (even multiple dividers) anywhere you want, but you'll have to live with the warnings.

The appearance of the diagram can be tweaked inter alia using the size property of the TextScript grob (`\override Voice.TextScript #'size = #0.3`) for the overall, the thickness property (`\override Voice.TextScript #'thickness = #3`) for the line thickness of the horizontal line and the divider. The remaining configuration (box sizes, offsets and spaces) is done by the `harp-pedal-details` list of properties (`\override Voice.TextScript #'harp-pedal-details #'box-width = #1`). It contains the following settings: `box-offset` (vertical shift of the box center for up/down pedals), `box-width`, `box-height`, `space-before-divider` (the spacing between two boxes before the divider) and `space-after-divider` (box spacing after the divider).

`\markup \harp-pedal #"ˆ-v|--ovˆ"`



Used properties:

- `thickness` (0.5)
- `harp-pedal-details` ('')
- `size` (1.2)

`\woodwind-diagram` *instrument* (symbol) *user-draw-commands* (list)

Make a woodwind-instrument diagram. For example, say

```
\markup \woodwind-diagram
  #'oboe #'((lh . (d ees)) (cc . (five3qT1q)) (rh . (gis)))
```

for an oboe with the left-hand d key, left-hand ees key, and right-hand gis key depressed while the five-hole of the central column effectuates a trill between 1/4 and 3/4 closed.

The following instruments are supported:

- piccolo
- flute
- oboe
- clarinet
- bass-clarinet
- saxophone
- bassoon
- contrabassoon

To see all of the callable keys for a given instrument, include the function (`print-keys 'instrument`) in your .ly file, where instrument is the instrument whose keys you want to print.

Certain keys allow for special configurations. The entire gamut of configurations possible is as follows:

- 1q (1/4 covered)
- 1h (1/2 covered)
- 3q (3/4 covered)
- R (ring depressed)
- F (fully covered; the default if no state put)

Additionally, these configurations can be used in trills. So, for example, `three3qTR` effectuates a trill between 3/4 full and ring depressed on the three hole. As another example, `threeRT` effectuates a trill between R and open, whereas `threeTR` effectuates a trill between open and shut. To see all of the possibilities for all of the keys of a given instrument, invoke (`print-keys-verbose 'instrument`).

Lastly, substituting an empty list for the pressed-key alist will result in a diagram with all of the keys drawn but none filled, for example:

```
\markup \woodwind-diagram #'oboe #'
```

Used properties:

- `graphical` (#t)
- `thickness` (0.1)
- `size` (1)

## A.9.6 Other

`\auto-footnote mkup` (markup) `note` (markup)

Have footnote *note* act as an annotation to the markup *mkup*.

```
\markup {
  \auto-footnote a b
  \override #'(padding . 0.2)
  \auto-footnote c d
}
```

a c

The footnote will be annotated automatically.

Used properties:

- `padding` (0.0)
- `raise` (0.5)

`\backslashed-digit` *num* (integer)

A feta number, with backslash. This is for use in the context of figured bass notation.

```
\markup {
  \backslashed-digit #5
  \hspace #2
  \override #'(thickness . 3)
  \backslashed-digit #7
}
```

5 7

Used properties:

- `thickness` (1.6)
- `font-size` (0)

`\char` *num* (integer)

Produce a single character. Characters encoded in hexadecimal format require the prefix `#x`.

```
\markup {
  \char #65 \char ##x00a9
}
```

A ©

`\eyeglasses`

Prints out eyeglasses, indicating strongly to look at the conductor.

```
\markup { \eyeglasses }
```

60'

`\footnote` *mkup* (markup) *note* (markup)

Have footnote *note* act as an annotation to the markup *mkup*.

```
\markup {
  \auto-footnote a b
  \override #'(padding . 0.2)
  \auto-footnote c d
}
```

a c

The footnote will not be annotated automatically.

`\fraction` *arg1* (markup) *arg2* (markup)

Make a fraction of two markups.

```
\markup {
  \fraction 355 113
}
```



}

$$\pi \approx \frac{355}{113}$$

Used properties:

- `font-size` (0)

`\fromproperty` *symbol* (symbol)

Read the *symbol* from property settings, and produce a stencil from the markup contained within. If *symbol* is not defined, it returns an empty markup.

```
\header {
  myTitle = "myTitle"
  title = \markup {
    from
    \italic
    \fromproperty #'header:myTitle
  }
}
\markup {
  \null
}
```

**from *myTitle***

`\left-brace` *size* (number)

A feta brace in point size *size*.

```
\markup {
  \left-brace #35
  \hspace #2
  \left-brace #45
}
```

{ }

`\lookup` *glyph-name* (string)

Lookup a glyph by name.

```
\markup {
  \override #'(font-encoding . fetaBraces) {
    \lookup #"brace200"
    \hspace #2
    \rotate #180
    \lookup #"brace180"
  }
}
```

$$\left\{ \begin{array}{l} \left( \right. \\ \left. \right) \end{array} \right\}$$

`\markalphabet` *num* (integer)

Make a markup letter for *num*. The letters start with A to Z and continue with double letters.

```
\markup {
  \markalphabet #8
  \hspace #2
  \markalphabet #26
}
```

I AA

`\markletter` *num* (integer)

Make a markup letter for *num*. The letters start with A to Z (skipping letter I), and continue with double letters.

```
\markup {
  \markletter #8
  \hspace #2
  \markletter #26
}
```

J AB

`\null`

An empty markup with extents of a single point.

```
\markup {
  \null
}
```

`\on-the-fly` *procedure* (procedure) *arg* (markup)

Apply the *procedure* markup command to *arg*. *procedure* should take a single argument.

`\override` *new-prop* (pair) *arg* (markup)

Add the argument *new-prop* to the property list. Properties may be any property supported by Section “font-interface” in *Internals Reference*, Section “text-interface” in *Internals Reference* and Section “instrument-specific-markup-interface” in *Internals Reference*.

```
\markup {
  \line {
    \column {
      default
      baseline-skip
    }
    \hspace #2
    \override #'(baseline-skip . 4) {
      \column {
```

```

        increased
      baseline-skip
    }
  }
}

```

```

default      increased
baseline-skip baseline-skip

```

`\page-link` *page-number* (number) *arg* (markup)

Add a link to the page *page-number* around *arg*. This only works in the PDF backend.

```

\markup {
  \page-link #2 { \italic { This links to page 2... } }
}

```

*This links to page 2...*

`\page-ref` *label* (symbol) *gauge* (markup) *default* (markup)

Reference to a page number. *label* is the label set on the referenced page (using the `\label` command), *gauge* a markup used to estimate the maximum width of the page number, and *default* the value to display when *label* is not found.

`\pattern` *count* (integer) *axis* (integer) *space* (number) *pattern* (markup)

Prints *count* times a *pattern* markup. Patterns are spaced apart by *space*. Patterns are distributed on *axis*.

```

\markup \column {
  "Horizontally repeated : "
  \pattern #7 #X #2 \flat
  \null
  "Vertically repeated : "
  \pattern #3 #Y #0.5 \flat
}

```

Horizontally repeated :

b b b b b b b

Vertically repeated :

b  
b  
b

`\property-recursive` *symbol* (symbol)

Print out a warning when a header field markup contains some recursive markup definition.

`\right-brace` *size* (number)

A feta brace in point size *size*, rotated 180 degrees.

```

\markup {
  \right-brace #45
}

```

```

\hspace #2
\right-brace #35
}

```

```

{
}

```

`\slashed-digit` *num* (integer)

A feta number, with slash. This is for use in the context of figured bass notation.

```

\markup {
  \slashed-digit #5
  \hspace #2
  \override #'(thickness . 3)
  \slashed-digit #7
}

```

**5 7**

Used properties:

- `thickness` (1.6)
- `font-size` (0)

`\stencil` *stil* (stencil)

Use a stencil as markup.

```

\markup {
  \stencil #(make-circle-stencil 2 0 #t)
}

```



`\strut`

Create a box of the same height as the space in the current font.

`\transparent` *arg* (markup)

Make *arg* transparent.

```

\markup {
  \transparent {
    invisible text
  }
}

```

`\verbatim-file` *name* (string)

Read the contents of file *name*, and include it verbatim.

```

\markup {
  \verbatim-file #"simple.ly"
}

```

```

%% A simple piece in LilyPond, a scale.
\relative c' {
  c d e f g a b c
}
%% Optional helper for automatic updating by convert-ly.
%% May be omitted.
\version "2.14.0"

```


`\whiteout` *arg* (markup)

Provide a white background for *arg*.

```

\markup {
  \combine
    \filled-box #'(-1 . 10) #'(-3 . 4) #1
    \whiteout whiteout
}

```



`\with-color` *color* (color) *arg* (markup)

Draw *arg* in color specified by *color*.

```

\markup {
  \with-color #red
  red
  \hspace #2
  \with-color #green
  green
  \hspace #2
  \with-color #blue
  blue
}

```

red green blue

`\with-dimensions` *x* (pair of numbers) *y* (pair of numbers) *arg* (markup)

Set the dimensions of *arg* to *x* and *y*.

`\with-link` *label* (symbol) *arg* (markup)

Add a link to the page holding label *label* around *arg*. This only works in the PDF backend.

```

\markup {
  \with-link #'label {
    \italic { This links to the page containing the label... }
  }
}

```

*This links to the page containing the label...*

## A.10 Text markup list commands

The following commands can all be used with `\markuplist`:

`\column-lines` *args* (markup list)

Like `\column`, but return a list of lines instead of a single markup. `baseline-skip` determines the space between each markup in *args*.

Used properties:

- `baseline-skip`

`\justified-lines` *args* (markup list)

Like `\justify`, but return a list of lines instead of a single markup. Use `\override-lines #'(line-width . X)` to set the line width; *X* is the number of staff spaces.

Used properties:

- `text-direction` (1)
- `word-space`
- `line-width` (*#f*)
- `baseline-skip`

`\override-lines` *new-prop* (pair) *args* (markup list)

Like `\override`, for markup lists.

`\table-of-contents`

`\wordwrap-internal` *justify* (boolean) *args* (markup list)

Internal markup list command used to define `\justify` and `\wordwrap`.

Used properties:

- `text-direction` (1)
- `word-space`
- `line-width` (*#f*)

`\wordwrap-lines` *args* (markup list)

Like `\wordwrap`, but return a list of lines instead of a single markup. Use `\override-lines #'(line-width . X)` to set the line width, where *X* is the number of staff spaces.

Used properties:

- `text-direction` (1)
- `word-space`
- `line-width` (*#f*)
- `baseline-skip`

`\wordwrap-string-internal` *justify* (boolean) *arg* (string)

Internal markup list command used to define `\justify-string` and `\wordwrap-string`.

Used properties:

- `text-direction` (1)
- `word-space`
- `line-width`

## A.11 List of special characters

The following special characters references can be used; for more details, see [\[ASCII aliases\]](#), page 455.

The HTML syntax is used and most of these references are the same as HTML. The rest of them are inspired by L<sup>A</sup>T<sub>E</sub>X.

The characters are boxed so that you can see their size. A small padding has been added between the character and the box for more readability.



`&hellip;`      `...` `&ndash;`      `=` `&mdash;`      `=` `&iexcl;`      `!`

<code>&amp;iquest;</code>		<code>&amp;solidus;</code>		<code>&amp;flq;</code>		<code>&amp;frq;</code>	
<code>&amp;flqq;</code>		<code>&amp;frqq;</code>		<code>&amp;glq;</code>		<code>&amp;grq;</code>	
<code>&amp;glqq;</code>		<code>&amp;grqq;</code>		<code>&amp;elq;</code>		<code>&amp;erq;</code>	
<code>&amp;elqq;</code>		<code>&amp;erqq;</code>		<code>&amp;ensp;</code>		<code>&amp;emsp;</code>	
<code>&amp;thinsp;</code>		<code>&amp;nbspc;</code>		<code>&amp;nnnbspc;</code>		<code>&amp;zwj;</code>	
<code>&amp;zwnj;</code>		<code>&amp;middot;</code>		<code>&amp;bull;</code>		<code>&amp;copyright;</code>	
<code>&amp;registered;</code>		<code>&amp;trademark;</code>		<code>&amp;dagger;</code>		<code>&amp;Dagger;</code>	
<code>&amp;numero;</code>		<code>&amp;ordf;</code>		<code>&amp;ordm;</code>		<code>&amp;para;</code>	
<code>&amp;sect;</code>		<code>&amp;deg;</code>		<code>&amp;numero;</code>		<code>&amp;permil;</code>	
<code>&amp;brvbar;</code>		<code>&amp;acute;</code>		<code>&amp;acutedbl;</code>		<code>&amp;grave;</code>	
<code>&amp;breve;</code>		<code>&amp;caron;</code>		<code>&amp;cedilla;</code>		<code>&amp;circumflex;</code>	
<code>&amp;diaeresis;</code>		<code>&amp;macron;</code>		<code>&amp;aa;</code>		<code>&amp;AA;</code>	
<code>&amp;ae;</code>		<code>&amp;AE;</code>		<code>&amp;dh;</code>		<code>&amp;DH;</code>	
<code>&amp;dj;</code>		<code>&amp;DJ;</code>		<code>&amp;l;</code>		<code>&amp;L;</code>	
<code>&amp;ng;</code>		<code>&amp;NG;</code>		<code>&amp;o;</code>		<code>&amp;O;</code>	
<code>&amp;oe;</code>		<code>&amp;OE;</code>		<code>&amp;s;</code>		<code>&amp;ss;</code>	
<code>&amp;th;</code>		<code>&amp;TH;</code>		<code>&amp;plus;</code>		<code>&amp;minus;</code>	
<code>&amp;times;</code>		<code>&amp;div;</code>		<code>&amp;sup1;</code>		<code>&amp;sup2;</code>	
<code>&amp;sup3;</code>		<code>&amp;sqrt;</code>		<code>&amp;increment;</code>		<code>&amp;infty;</code>	
<code>&amp;sum;</code>		<code>&amp;pm;</code>		<code>&amp;bulletop;</code>		<code>&amp;partial;</code>	
<code>&amp;neg;</code>		<code>&amp;currency;</code>		<code>&amp;dollar;</code>		<code>&amp;euro;</code>	
<code>&amp;pounds;</code>		<code>&amp;yen;</code>		<code>&amp;cent;</code>			




## A.12 List of articulations

The following scripts are available in the Feta font and may be attached to notes (eg. ‘c\accent’).


### Articulation scripts



### Ornament scripts




### Fermata scripts







## Instrument-specific scripts




## Repeat sign scripts



## Ancient scripts



## A.13 Percussion notes



crashcymbal: cymbc		
chinesecymbal: cymch		ridebell: rb
splashcymbal: cyms	ridecymbalb: cymrb	cowbell: cb
mutehibongo: boh	openhibongo: boho	lobongo: bol
hibongo: boh	mutelobongo: bolm	openlobongo: bolo
mutehiconga: cghm	openhiconga: cghe	openloconga: cglo
muteloconga: cglm	hiconga: cgh	loconga: cgl
hitimbale: timh	hiagogo: agh	
lotimbale: timl	loagogo: agl	
hisidestick: ssh	losidestick: ssl	
sidestick: ss		
shortguiro: guis	guiro: gui	maracas: mar
longguiro: guil	cabasa: cab	
shortwhistle: whs		
longwhistle: whl		
handclap: hc	vibraslap: vibs	
tambourine: tamb	tamtam: tt	
claves: cl	lowoodblock: wbl	
hiwoodblock: wbh		
mutecuica: cuim	mutetriangle: trim	opentriangle: trio
opencuica: cuio	triangle: tri	
oneup: ua	threeup: uc	fiveup: ue
twoup: ub	fourup: ud	
onedown: da	threedown: dc	fivedown: de
twodown: db	fourdown: dd	

## A.14 Technical glossary

A glossary of the technical terms and concepts used internally in LilyPond. These terms may appear in the manuals, on mailing lists or in the source code.

### **alist**

An association list or **alist** for short is a Scheme pair which associates a value with a key: (key . value). For example, in `'scm/lily.scm'`, the alist “type-p-name-alist” associates certain type predicates (e.g. `ly:music?`) with names (e.g. “music”) so that type-check failures can be reported with a console message that includes the name of the expected type predicate.

### **callback**

A **callback** is a routine, function or method whose reference is passed as an argument in a call to another routine, so allowing the called routine to invoke it. The technique enables a lower-level software layer to call a function defined in a higher layer. Callbacks are used extensively in LilyPond to permit user-level Scheme code to define how many low-level actions are performed.

### **closure**

In Scheme, a **closure** is created when a function, usually a lambda expression, is passed as a variable. The closure contains the function’s code plus references to the lexical bindings of the function’s free variables (i.e. those variables used in the expression but defined outside it). When this function is applied to different arguments later, the free variable bindings that were captured in the closure are used to obtain the values of the free variables to be used in the calculation. One useful property of closures is the retention of internal variable values between invocations, so permitting state to be maintained.

A **simple closure** is a closure whose expression has no free variables and hence no free variable bindings.

A simple closure is represented in LilyPond by a smob containing the expression and a method to apply the expression to a passed list of arguments.

### **glyph**

A **glyph** is a particular graphical representation of a typographic character, or a combination of two characters forming a ligature. A set of glyphs with a single style and shape comprise a font, and a set of fonts covering several styles and sizes comprise a typeface.

### **See also**

Notation Reference: [Section 1.8.3 \[Fonts\]](#), page 223, [Section 3.3.3 \[Special characters\]](#), page 453.

### **grob**

LilyPond objects which represent items of notation in the printed output such as note heads, stems, slurs, ties, fingering, clefs, etc are called ‘Layout objects’, often known as ‘GRaphical OBjects’, or **grobs** for short. They are represented by instances of the **Grob** class.

### **See also**

Learning Manual: [Section “Objects and interfaces”](#) in *Learning Manual*, [Section “Naming conventions of objects and properties”](#) in *Learning Manual*, [Section “Properties of layout objects”](#) in *Learning Manual*.

Internals Reference: [Section “grob-interface”](#) in *Internals Reference*, [Section “All layout objects”](#) in *Internals Reference*.

## immutable

An **immutable** object is one whose state cannot be modified after creation, in contrast to a mutable object, which can be modified after creation.

In LilyPond, immutable or shared properties define the default style and behavior of grobs. They are shared between many objects. In apparent contradiction to the name, they can be changed using `\override` and `\revert`.

## See also

Notation Reference: [\[mutable\]](#), page 658.

## interface

Actions and properties which are common to a number of grobs are grouped together in an object called a **grob-interface**, or just ‘interface’ for short.

## See also

Learning Manual: [Section “Objects and interfaces”](#) in *Learning Manual*, [Section “Naming conventions of objects and properties”](#) in *Learning Manual*, [Section “Properties found in interfaces”](#) in *Learning Manual*.

Notation Reference: [Section 5.2.2 \[Layout interfaces\]](#), page 531.

Internals Reference: [Section “Graphical Object Interfaces”](#) in *Internals Reference*.

## lexer

A **lexer** is a program which converts a sequence of characters into a sequence of tokens, a process called lexical analysis. The LilyPond lexer converts the stream obtained from an input ‘.ly’ file into a tokenized stream more suited to the next stage of processing - parsing, for which see [\[parser\]](#), page 658. The LilyPond lexer is built with Flex from the lexer file ‘lily/lexer.ll’ which contains the lexical rules. This file is part of the source code and is not included in the LilyPond binary installation.

## mutable

A **mutable** object is one whose state can be modified after creation, in contrast to an immutable object, whose state is fixed at the time of creation.

In LilyPond, mutable properties contain values that are specific to one grob. Typically, lists of other objects or results from computations are stored in mutable properties.

## See also

Notation Reference: [\[immutable\]](#), page 658.

## output-def

An instance of the **Output-def** class contains the methods and data structures associated with an output block. Instances are created for midi, layout and paper blocks.

## parser

A **parser** analyzes the sequence of tokens produced by a lexer to determine its grammatical structure, grouping the tokens progressively into larger groupings according to the rules of the grammar. If the sequence of tokens is valid the end product is a tree of tokens whose root is the grammar’s start symbol. If this cannot be achieved the file is invalid and an appropriate error message is produced. The syntactic groupings and the rules for constructing the groupings from their parts for the LilyPond syntax are defined in ‘lily/parser.yy’ and shown in Backus

Normal Form (BNF) in [Appendix C \[LilyPond grammar\], page 723](#). This file is used to build the parser during the program build by the parser generator, Bison. It is part of the source code and is not included in the LilyPond binary installation.

## parser variable

These are variables defined directly in Scheme. Their direct use by users is strongly discouraged, because their scoping semantics can be confusing.

When the value of such a variable is changed in a `.ly` file, the change is global, and unless explicitly reverted, the new value will persist to the end of the file, affecting subsequent `\score` blocks as well as external files added with the `\include` command. This can lead to unintended consequences and in complex typesetting projects the consequent errors can be difficult to track down.

LilyPond uses the following parser variables:

- `afterGraceFraction`
- `musicQuotes`
- `mode`
- `output-count`
- `output-suffix`
- `parseStringResult`
- `partCombineListener`
- `pitchnames`
- `toplevel-bookparts`
- `toplevel-scores`
- `showLastLength`
- `showFirstLength`

## prob

**Property Objects**, or **probs** for short, are instances of the `Prob` class, a simple base class for objects which have mutable and immutable property lists and the methods to manipulate them. The `Music` and `Stream_event` classes derive from `Prob`. Instances of the `Prob` class are also created to hold the formatted content of system grobs and titling blocks during page layout.

## simple closure

See [\[closure\], page 657](#).

## smob

**Smobs**, or **ScheMe Objects**, are part of the mechanism used by Guile to export C and C++ objects to Scheme code. In LilyPond, smobs are created from C++ objects through macros. There are two types of smob objects: simple smobs, intended for simple immutable objects like numbers, and complex smobs, used for objects with identities. If you have access to the LilyPond sources, more information can be found in `'lily/includes/smob.hh'`.

## stencil

An instance of the **stencil** class holds the information required to print a typographical object. It is a simple smob containing a confining box, which defines the vertical and horizontal extents of the object, and a Scheme expression which will print the object when evaluated. Stencils may be combined to form more complex stencils defined by a tree of Scheme expressions formed from the Scheme expressions of the component stencils.

The `stencil` property, which connects a grob to its stencil, is defined in the `grob-interface` interface.

## See also

Internals Reference: [Section “grob-interface”](#) in *Internals Reference*.

## A.15 All context properties

`additionalPitchPrefix` (string)

Text with which to prefix additional pitches within a chord name.

`aDueText` (markup)

Text to print at a unisono passage.

`alignAboveContext` (string)

Where to insert newly created context in vertical alignment.

`alignBassFigureAccidentals` (boolean)

If true, then the accidentals are aligned in bass figure context.

`alignBelowContext` (string)

Where to insert newly created context in vertical alignment.

`alternativeNumberingStyle` (symbol)

The style of an alternative’s bar numbers. Can be `numbers` for going back to the same number or `numbers-with-letters` for going back to the same number with letter suffixes. No setting will not go back in measure-number time.

`associatedVoice` (string)

Name of the `Voice` that has the melody for this `Lyrics` line.

`autoAccidentals` (list)

List of different ways to typeset an accidental.

For determining when to print an accidental, several different rules are tried. The rule that gives the highest number of accidentals is used.

Each entry in the list is either a symbol or a procedure.

*symbol*     The symbol is the name of the context in which the following rules are to be applied. For example, if *context* is [Section “Score” in Internals Reference](#) then all staves share accidentals, and if *context* is [Section “Staff” in Internals Reference](#) then all voices in the same staff share accidentals, but staves do not.

*procedure*     The procedure represents an accidental rule to be applied to the previously specified context.

The procedure takes the following arguments:

`context`     The current context to which the rule should be applied.

`pitch`     The pitch of the note to be evaluated.

`barnum`     The current bar number.

`measurepos`

The current measure position.

The procedure returns a pair of booleans. The first states whether an extra natural should be added. The second states whether an accidental should be printed. (`#t` . `#f`) does not make sense.

**autoBeamCheck** (procedure)

A procedure taking three arguments, *context*, *dir* [start/stop (-1 or 1)], and *test* [shortest note in the beam]. A non-**#f** return value starts or stops the auto beam.

**autoBeaming** (boolean)

If set to true then beams are generated automatically.

**autoCautionaries** (list)

List similar to **autoAccidentals**, but it controls cautionary accidentals rather than normal ones. Both lists are tried, and the one giving the most accidentals wins. In case of draw, a normal accidental is typeset.

**automaticBars** (boolean)

If set to false then bar lines will not be printed automatically; they must be explicitly created with a **\bar** command. Unlike the **\cadenzaOn** keyword, measures are still counted. Bar line generation will resume according to that count if this property is unset.

**barAlways** (boolean)

If set to true a bar line is drawn after each note.

**barCheckSynchronize** (boolean)

If true then reset **measurePosition** when finding a bar check.

**barNumberFormatter** (procedure)

A procedure that takes a bar number, measure position, and alternative number and returns a markup of the bar number to print.

**barNumberVisibility** (procedure)

A procedure that takes a bar number and a measure position and returns whether the corresponding bar number should be printed.

**baseMoment** (moment)

Smallest unit of time that will stand on its own as a subdivided section.

**bassFigureFormatFunction** (procedure)

A procedure that is called to produce the formatting for a **BassFigure** grob. It takes a list of **BassFigureEvents**, a context, and the grob to format.

**bassStaffProperties** (list)

An alist of property settings to apply for the down staff of **PianoStaff**. Used by **\autochange**.

**beamExceptions** (list)

An alist of exceptions to autobeam rules that normally end on beats.

**beatStructure** (list)

List of **baseMoments** that are combined to make beats.

**chordChanges** (boolean)

Only show changes in chords scheme?

**chordNameExceptions** (list)

An alist of chord exceptions. Contains (*chord* . *markup*) entries.

**chordNameExceptionsFull** (list)

An alist of full chord exceptions. Contains (*chord* . *markup*) entries.

**chordNameExceptionsPartial** (list)

An alist of partial chord exceptions. Contains (*chord* . (*prefix-markup* *suffix-markup*)) entries.

**chordNameFunction** (procedure)

The function that converts lists of pitches to chord names.

**chordNameLowercaseMinor** (boolean)

Downcase roots of minor chords?

**chordNameSeparator** (markup)

The markup object used to separate parts of a chord name.

**chordNoteNamer** (procedure)

A function that converts from a pitch object to a text markup. Used for single pitches.

**chordPrefixSpacer** (number)

The space added between the root symbol and the prefix of a chord name.

**chordRootNamer** (procedure)

A function that converts from a pitch object to a text markup. Used for chords.

**clefGlyph** (string)

Name of the symbol within the music font.

**clefOctavation** (integer)

Add this much extra octavation. Values of 7 and -7 are common.

**clefPosition** (number)

Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

**completionBusy** (boolean)

Whether a completion-note head is playing.

**connectArpeggios** (boolean)

If set, connect arpeggios across piano staff.

**countPercentRepeats** (boolean)

If set, produce counters for percent repeats.

**createKeyOnClefChange** (boolean)

Print a key signature whenever the clef is changed.

**createSpacing** (boolean)

Create **StaffSpacing** objects? Should be set for staves.

**crescendoSpanner** (symbol)

The type of spanner to be used for crescendi. Available values are ‘**hairpin**’ and ‘**text**’. If unset, a hairpin crescendo is used.

**crescendoText** (markup)

The text to print at start of non-hairpin crescendo, i.e., ‘**cresc.**’.

**cueClefGlyph** (string)

Name of the symbol within the music font.

**cueClefOctavation** (integer)

Add this much extra octavation. Values of 7 and -7 are common.

**cueClefPosition** (number)

Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

**currentBarNumber** (integer)

Contains the current barnumber. This property is incremented at every bar line.



**decrescendoSpanner** (symbol)

The type of spanner to be used for decrescendi. Available values are ‘hairpin’ and ‘text’. If unset, a hairpin decrescendo is used.

**decrescendoText** (markup)

The text to print at start of non-hairpin decrescendo, i.e., ‘dim.’.

**defaultBarType** (string)

Set the default type of bar line. See **whichBar** for information on available bar types.

This variable is read by [Section “Timing-translator” in \*Internals Reference\*](#) at [Section “Score” in \*Internals Reference\*](#) level.

**defaultStrings** (list)

A list of strings to use in calculating frets for tablatures and fretboards if no strings are provided in the notes for the current moment.

**doubleRepeatType** (string)

Set the default bar line for double repeats.

**doubleSlurs** (boolean)

If set, two slurs are created for every slurred note, one above and one below the chord.

**drumPitchTable** (hash table)

A table mapping percussion instruments (symbols) to pitches.

**drumStyleTable** (hash table)

A hash table which maps drums to layout settings. Predefined values: ‘drums-style’, ‘timbales-style’, ‘congas-style’, ‘bongos-style’, and ‘percussion-style’.

The layout style is a hash table, containing the drum-pitches (e.g., the symbol ‘hihat’) as keys, and a list (*notehead-style script vertical-position*) as values.

**explicitClefVisibility** (vector)

‘break-visibility’ function for clef changes.

**explicitCueClefVisibility** (vector)

‘break-visibility’ function for cue clef changes.

**explicitKeySignatureVisibility** (vector)

‘break-visibility’ function for explicit key changes. ‘\override’ of the break-visibility property will set the visibility for normal (i.e., at the start of the line) key signatures.

**extendersOverRests** (boolean)

Whether to continue extenders as they cross a rest.

**extraNatural** (boolean)

Whether to typeset an extra natural sign before accidentals that reduce the effect of a previous alteration.

**figuredBassAlterationDirection** (direction)

Where to put alterations relative to the main figure.

**figuredBassCenterContinuations** (boolean)

Whether to vertically center pairs of extender lines. This does not work with three or more lines.

**figuredBassFormatter** (procedure)

A routine generating a markup for a bass figure.

**figuredBassPlusDirection** (direction)

Where to put plus signs relative to the main figure.

**fingeringOrientations** (list)

A list of symbols, containing ‘left’, ‘right’, ‘up’ and/or ‘down’. This list determines where fingerings are put relative to the chord being fingered.

**firstClef** (boolean)

If true, create a new clef when starting a staff.

**followVoice** (boolean)

If set, note heads are tracked across staff switches by a thin line.

**fontSize** (number)

The relative size of all grobs in a context.

**forbidBreak** (boolean)

If set to #t, prevent a line break at this point.

**forceClef** (boolean)

Show clef symbol, even if it has not changed. Only active for the first clef after the property is set, not for the full staff.

**fretLabels** (list)

A list of strings or Scheme-formatted markups containing, in the correct order, the labels to be used for lettered frets in tablature.

**glissandoMap** (list)

A map in the form of ‘(source1 . target1) (source2 . target2) (sourcen . targetn)’ showing the glissandi to be drawn for note columns. The value ‘()’ will default to ‘((0 . 0) (1 . 1) (n . n))’, where n is the minimal number of note-heads in the two note columns between which the glissandi occur.

**gridInterval** (moment)

Interval for which to generate **GridPoints**.

**handleNegativeFrets** (symbol)

How the automatic fret calculator should handle calculated negative frets. Values include ‘ignore’, to leave them out of the diagram completely, ‘include’, to include them as calculated, and ‘recalculate’, to ignore the specified string and find a string where they will fit with a positive fret number.

**harmonicAccidentals** (boolean)

If set, harmonic notes in chords get accidentals.

**harmonicDots** (boolean)

If set, harmonic notes in dotted chords get dots.

**highStringOne** (boolean)

Whether the first string is the string with highest pitch on the instrument. This used by the automatic string selector for tablature notation.

**ignoreBarChecks** (boolean)

Ignore bar checks.

**ignoreFiguredBassRest** (boolean)

Don’t swallow rest events.

**ignoreMelismata** (boolean)

Ignore melismata for this [Section “Lyrics” in \*Internals Reference\*](#) line.

`implicitBassFigures` (list)

A list of bass figures that are not printed as numbers, but only as extender lines.

`implicitTimeSignatureVisibility` (vector)

break visibility for the default time signature.

`includeGraceNotes` (boolean)

Do not ignore grace notes for [Section “Lyrics” in \*Internals Reference\*](#).

`instrumentCueName` (markup)

The name to print if another instrument is to be taken.

`instrumentEqualizer` (procedure)

A function taking a string (instrument name), and returning a (*min* . *max*) pair of numbers for the loudness range of the instrument.

`instrumentName` (markup)

The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`instrumentTransposition` (pitch)

Define the transposition of the instrument. Its value is the pitch that sounds like middle C. This is used to transpose the MIDI output, and `\quotes`.

`internalBarNumber` (integer)

Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`keepAliveInterfaces` (list)

A list of symbols, signifying grob interfaces that are worth keeping a staff with `remove-empty` set around for.

`keyAlterationOrder` (list)

An alist that defines in what order alterations should be printed. The format is (*step* . *alter*), where *step* is a number from 0 to 6 and *alter* from -2 (sharp) to 2 (flat).

`keySignature` (list)

The current key signature. This is an alist containing (*step* . *alter*) or ((*octave* . *step*) . *alter*), where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`lyricMelismaAlignment` (number)

Alignment to use for a melisma syllable.

`majorSevenSymbol` (markup)

How should the major 7th be formatted in a chord name?

`markFormatter` (procedure)

A procedure taking as arguments the context and the rehearsal mark. It should return the formatted mark as a markup object.

`maximumFretStretch` (number)

Don't allocate frets further than this from specified frets.

`measureLength` (moment)

Length of one measure in the current time signature.

`measurePosition` (moment)

How much of the current measure have we had. This can be set manually to create incomplete measures.

**melismaBusyProperties** (list)

A list of properties (symbols) to determine whether a melisma is playing. Setting this property will influence how lyrics are aligned to notes. For example, if set to '(melismaBusy beamMelismaBusy), only manual melismata and manual beams are considered. Possible values include `melismaBusy`, `slurMelismaBusy`, `tieMelismaBusy`, and `beamMelismaBusy`.

**metronomeMarkFormatter** (procedure)

How to produce a metronome markup. Called with two arguments: a `TempoChangeEvent` and context.

**middleCClefPosition** (number)

The position of the middle C, as determined only by the clef. This can be calculated by looking at `clefPosition` and `clefGlyph`.

**middleCCuePosition** (number)

The position of the middle C, as determined only by the clef of the cue notes. This can be calculated by looking at `cueClefPosition` and `cueClefGlyph`.

**middleCOffset** (number)

The offset of middle C from the position given by `middleCClefPosition`. This is used for ottava brackets.

**middleCPosition** (number)

The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

**midiChannelMapping** (symbol)

How to map MIDI channels: per `instrument` (default), `staff` or `voice`.

**midiInstrument** (string)

Name of the MIDI instrument to use.

**midiMaximumVolume** (number)

Analogous to `midiMinimumVolume`.

**midiMergeUnisons** (boolean)

If true, output only one MIDI note-on event when notes with the same pitch, in the same MIDI-file track, overlap.

**midiMinimumVolume** (number)

Set the minimum loudness for MIDI. Ranges from 0 to 1.

**minimumFret** (number)

The tablature auto string-selecting mechanism selects the highest string with a fret at least `minimumFret`.

**minimumPageTurnLength** (moment)

Minimum length of a rest for a page turn to be allowed.

**minimumRepeatLengthForPageTurn** (moment)

Minimum length of a repeated section for a page turn to be allowed within that section.

**minorChordModifier** (markup)

Markup displayed following the root for a minor chord

**noChordSymbol** (markup)

Markup to be displayed for rests in a `ChordNames` context.

`noteToFretFunction` (procedure)

Convert list of notes and list of defined strings to full list of strings and fret numbers.  
Parameters: The context, a list of note events, a list of tabstring events, and the fretboard grob if a fretboard is desired.

`ottavation` (markup)

If set, the text for an ottava spanner. Changing this creates a new text spanner.

`output` (music output)

The output produced by a score-level translator during music interpretation.

`partCombineTextsOnNote` (boolean)

Print part-combine texts only on the next note rather than immediately on rests or skips.

`pedalSostenutoStrings` (list)

See `pedalSustainStrings`.

`pedalSostenutoStyle` (symbol)

See `pedalSustainStyle`.

`pedalSustainStrings` (list)

A list of strings to print for sustain-pedal. Format is (*up updown down*), where each of the three is the string to print when this is done with the pedal.

`pedalSustainStyle` (symbol)

A symbol that indicates how to print sustain pedals: `text`, `bracket` or `mixed` (both).

`pedalUnaCordaStrings` (list)

See `pedalSustainStrings`.

`pedalUnaCordaStyle` (symbol)

See `pedalSustainStyle`.

`predefinedDiagramTable` (hash table)

The hash table of predefined fret diagrams to use in `FretBoards`.

`printKeyCancellation` (boolean)

Print restoration alterations before a key signature change.

`printOctaveNames` (boolean)

Print octave marks for the `NoteNames` context.

`printPartCombineTexts` (boolean)

Set 'Solo' and 'A due' texts in the part combiner?

`proportionalNotationDuration` (moment)

Global override for shortest-playing duration. This is used for switching on proportional notation.

`rehearsalMark` (integer)

The last rehearsal mark printed.

`repeatCommands` (list)

This property is a list of commands of the form (`list 'volta x`), where `x` is a string or `#f`. `'end-repeat` is also accepted as a command.

`repeatCountVisibility` (procedure)

A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

- restCompletionBusy** (boolean)  
Signal whether a completion-rest is active.
- restNumberThreshold** (number)  
If a multimeasure rest has more measures than this, a number is printed.
- searchForVoice** (boolean)  
Signal whether a search should be made of all contexts in the context hierarchy for a voice to provide rhythms for the lyrics.
- shapeNoteStyles** (vector)  
Vector of symbols, listing style for each note head relative to the tonic (qv.) of the scale.
- shortInstrumentName** (markup)  
See **instrumentName**.
- shortVocalName** (markup)  
Name of a vocal line, short version.
- skipBars** (boolean)  
If set to true, then skip the empty bars that are produced by multimeasure notes and rests. These bars will not appear on the printed output. If not set (the default), multimeasure notes and rests expand into their full length, printing the appropriate number of empty bars so that synchronization with other voices is preserved.
- ```
{
  r1 r1*3 R1*3
  \set Score.skipBars= ##t
  r1*3 R1*3
}
```
- skipTypesetting** (boolean)  
If true, no typesetting is done, speeding up the interpretation phase. Useful for debugging large scores.
- slashChordSeparator** (markup)  
The markup object used to separate a chord name from its root note in case of inversions or slash chords.
- soloIIIText** (markup)  
The text for the start of a solo for voice ‘two’ when part-combining.
- soloText** (markup)  
The text for the start of a solo when part-combining.
- squashedPosition** (integer)  
Vertical position of squashing for [Section “Pitch\\_squash\\_engraver”](#) in *Internals Reference*.
- staffLineLayoutFunction** (procedure)  
Layout of staff lines, **traditional**, or **semitone**.
- stanza** (markup)  
Stanza ‘number’ to print before the start of a verse. Use in **Lyrics** context.
- stemLeftBeamCount** (integer)  
Specify the number of beams to draw on the left side of the next note. Overrides automatic beaming. The value is only used once, and then it is erased.
- stemRightBeamCount** (integer)  
See **stemLeftBeamCount**.

**strictBeatBeaming** (boolean)

Should partial beams reflect the beat structure even if it causes flags to hang out?

**stringNumberOrientations** (list)

See **fingeringOrientations**.

**stringOneTopmost** (boolean)

Whether the first string is printed on the top line of the tablature.

**stringTunings** (list)

The tablature strings tuning. It is a list of the pitches of each string (starting with the lowest numbered one).

**strokeFingerOrientations** (list)

See **fingeringOrientations**.

**subdivideBeams** (boolean)

If set, multiple beams will be subdivided at **baseMoment** positions by only drawing one beam over the beat.

**suggestAccidentals** (boolean)

If set, accidentals are typeset as cautionary suggestions over the note.

**systemStartDelimiter** (symbol)

Which grob to make for the start of the system/staff? Set to **SystemStartBrace**, **SystemStartBracket** or **SystemStartBar**.

**systemStartDelimiterHierarchy** (pair)

A nested list, indicating the nesting of a start delimiters.

**tablatureFormat** (procedure)

A function formatting a tablature note head. Called with three arguments: context, string number and, fret number. It returns the text as a markup.

**tabStaffLineLayoutFunction** (procedure)

A function determining the staff position of a tablature note head. Called with two arguments: the context and the string.

**tempoHideNote** (boolean)

Hide the note = count in tempo marks.

**tempoWholesPerMinute** (moment)

The tempo in whole notes per minute.

**tieWaitForNote** (boolean)

If true, tied notes do not have to follow each other directly. This can be used for writing out arpeggios.

**timeSignatureFraction** (fraction, as pair)

A pair of numbers, signifying the time signature. For example, '(4 . 4) is a 4/4 time signature.

**timeSignatureSettings** (list)

A nested alist of settings for time signatures. Contains elements for various time signatures. The element for each time signature contains entries for **baseMoment**, **beatStructure**, and **beamExceptions**.

**timing** (boolean)

Keep administration of measure length, position, bar number, etc.? Switch off for cadenzas.

**tonic** (pitch)

The tonic of the current scale.

**topLevelAlignment** (boolean)

If true, the *Vertical\_align\_engraver* will create a *VerticalAlignment*; otherwise, it will create a *StaffGrouper*

**trebleStaffProperties** (list)

An alist of property settings to apply for the up staff of *PianoStaff*. Used by *\autochange*.

**tremoloFlags** (integer)

The number of tremolo flags to add if no number is specified.

**tupletFullLength** (boolean)

If set, the tuplet is printed up to the start of the next note.

**tupletFullLengthNote** (boolean)

If set, end at the next note, otherwise end on the matter (time signatures, etc.) before the note.

**tupletSpannerDuration** (moment)

Normally, a tuplet bracket is as wide as the *\times* expression that gave rise to it. By setting this property, you can make brackets last shorter.

```
{
  \set tupletSpannerDuration = #(ly:make-moment 1 4)
  \times 2/3 { c8 c c c c c }
}
```

**useBassFigureExtenders** (boolean)

Whether to use extender lines for repeated bass figures.

**vocalName** (markup)

Name of a vocal line.

**voltaSpannerDuration** (moment)

This specifies the maximum duration to use for the brackets printed for *\alternative*. This can be used to shrink the length of brackets in the situation where one alternative is very large.

**whichBar** (string)

This property is read to determine what type of bar line to create.

Example:

```
\set Staff.whichBar = "|:"
```

This will create a start-repeat bar in this staff only. Valid values are described in [Section “bar-line-interface” in \*Internals Reference\*](#).

## A.16 Layout properties

**add-stem-support** (boolean)

If set, the *Stem* object is included in this script’s support.

**after-line-breaking** (boolean)

Dummy property, used to trigger callback for *after-line-breaking*.

**align-dir** (direction)

Which side to align? -1: left side, 0: around center of width, 1: right side.



- allow-loose-spacing** (boolean)  
If set, column can be detached from main spacing.
- allow-span-bar** (boolean)  
If false, no inter-staff bar line will be created below this bar line.
- alteration** (number)  
Alteration numbers for accidental.
- alteration-alist** (list)  
List of (*pitch* . *accidental*) pairs for key signature.
- annotation** (string)  
Annotate a grob for debug purposes.
- annotation-balloon** (boolean)  
Print the balloon around an annotation.
- annotation-line** (boolean)  
Print the line from an annotation to the grob that it annotates.
- arpeggio-direction** (direction)  
If set, put an arrow on the arpeggio squiggly line.
- arrow-length** (number)  
Arrow length.
- arrow-width** (number)  
Arrow width.
- auto-knee-gap** (dimension, in staff space)  
If a gap is found between note heads where a horizontal beam fits that is larger than this number, make a kneed beam.
- automatically-numbered** (boolean)  
Should a footnote be automatically numbered?
- average-spacing-wishes** (boolean)  
If set, the spacing wishes are averaged over staves.
- avoid-note-head** (boolean)  
If set, the stem of a chord does not pass through all note heads, but starts at the last note head.
- avoid-scripts** (boolean)  
If set, a tuplet bracket avoids the scripts associated with the note heads it encompasses.
- avoid-slur** (symbol)  
Method of handling slur collisions. Choices are **inside**, **outside**, **around**, and **ignore**. **inside** adjusts the slur if needed to keep the grob inside the slur. **outside** moves the grob vertically to the outside of the slur. **around** moves the grob vertically to the outside of the slur only if there is a collision. **ignore** does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), **outside** and **around** behave like **ignore**.
- axes** (list)  
List of axis numbers. In the case of alignment grobs, this should contain only one number.
- bar-extent** (pair of numbers)  
The Y-extent of the actual bar line. This may differ from **Y-extent** because it does not include the dots in a repeat bar line.

**base-shortest-duration** (moment)

Spacing is based on the shortest notes in a piece. Normally, pieces are spaced as if notes at least as short as this are present.

**baseline-skip** (dimension, in staff space)

Distance between base lines of multiple lines of text.

**beam-thickness** (dimension, in staff space)

Beam thickness, measured in **staff-space** units.

**beam-width** (dimension, in staff space)

Width of the tremolo sign.

**beamed-stem-shorten** (list)

How much to shorten beamed stems, when their direction is forced. It is a list, since the value is different depending on the number of flags and beams.

**beaming** (pair)

Pair of number lists. Each number list specifies which beams to make. 0 is the central beam, 1 is the next beam toward the note, etc. This information is used to determine how to connect the beaming patterns from stem to stem inside a beam.

**beamlet-default-length** (pair)

A pair of numbers. The first number specifies the default length of a beamlet that sticks out of the left hand side of this stem; the second number specifies the default length of the beamlet to the right. The actual length of a beamlet is determined by taking either the default length or the length specified by **beamlet-max-length-proportion**, whichever is smaller.

**beamlet-max-length-proportion** (pair)

The maximum length of a beamlet, as a proportion of the distance between two adjacent stems.

**before-line-breaking** (boolean)

Dummy property, used to trigger a callback function.

**between-cols** (pair)

Where to attach a loose column to.

**bound-details** (list)

An alist of properties for determining attachments of spanners to edges.

**bound-padding** (number)

The amount of padding to insert around spanner bounds.

**bracket-flare** (pair of numbers)

A pair of numbers specifying how much edges of brackets should slant outward. Value 0.0 means straight edges.

**bracket-visibility** (boolean or symbol)

This controls the visibility of the tuplet bracket. Setting it to false prevents printing of the bracket. Setting the property to **if-no-beam** makes it print only if there is no beam associated with this tuplet bracket.

**break-align-anchor** (number)

Grobs aligned to this break-align grob will have their X-offsets shifted by this number. In bar lines, for example, this is used to position grobs relative to the (visual) center of the bar line.

**break-align-anchor-alignment** (number)

Read by `ly:break-aligned-interface::calc-extent-aligned-anchor` for aligning an anchor to a grob's extent.

**break-align-orders** (vector)

Defines the order in which prefatory matter (clefs, key signatures) appears. The format is a vector of length 3, where each element is one order for end-of-line, middle of line, and start-of-line, respectively. An order is a list of symbols.

For example, clefs are put after key signatures by setting

```
\override Score.BreakAlignment #'break-align-orders =
  #(make-vector 3 '(span-bar
                    breathing-sign
                    staff-bar
                    key
                    clef
                    time-signature))
```

**break-align-symbol** (symbol)

This key is used for aligning and spacing breakable items.

**break-align-symbols** (list)

A list of symbols that determine which break-aligned grobs to align this to. If the grob selected by the first symbol in the list is invisible due to break-visibility, we will align to the next grob (and so on). Choices are `left-edge`, `ambitus`, `breathing-sign`, `clef`, `staff-bar`, `key-cancellation`, `key-signature`, `time-signature`, and `custos`.

**break-overshoot** (pair of numbers)

How much does a broken spanner stick out of its bounds?

**break-visibility** (vector)

A vector of 3 booleans,  `#(end-of-line unbroken begin-of-line)`. `#t` means visible, `#f` means killed.

**breakable** (boolean)

Allow breaks here.

**broken-bound-padding** (number)

The amount of padding to insert when a spanner is broken at a line break.

**c0-position** (integer)

An integer indicating the position of middle C.

**circled-tip** (boolean)

Put a circle at start/end of hairpins (`al/del niente`).

**clip-edges** (boolean)

Allow outward pointing beamlets at the edges of beams?

**collapse-height** (dimension, in staff space)

Minimum height of system start delimiter. If equal or smaller, the bracket/brace/line is removed.

**collision-bias** (number)

Number determining how much to favor the left (negative) or right (positive). Larger absolute values in either direction will push a collision in this direction.

**collision-interfaces** (list)

A list of interfaces for which automatic beam-collision resolution is run.

- collision-padding** (number)  
Amount of padding to apply after a collision is detected via the self-alignment-interface.
- collision-voice-only** (boolean)  
Does automatic beam collision apply only to the voice in which the beam was created?
- color** (color)  
The color of this grob.
- common-shortest-duration** (moment)  
The most common shortest note length. This is used in spacing. Enlarging this sets the score tighter.
- concaveness** (number)  
A beam is concave if its inner stems are closer to the beam than the two outside stems. This number is a measure of the closeness of the inner stems. It is used for damping the slope of the beam.
- connect-to-neighbor** (pair)  
Pair of booleans, indicating whether this grob looks as a continued break.
- control-points** (list)  
List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.
- damping** (number)  
Amount of beam slope damping.
- dash-definition** (pair)  
List of **dash-elements** defining the dash structure. Each **dash-element** has a starting t value, an ending t-value, a **dash-fraction**, and a **dash-period**.
- dash-fraction** (number)  
Size of the dashes, relative to **dash-period**. Should be between 0.0 (no line) and 1.0 (continuous line).
- dash-period** (number)  
The length of one dash together with whitespace. If negative, no line is drawn at all.
- default-direction** (direction)  
Direction determined by note head positions.
- default-staff-staff-spacing** (list)  
The settings to use for **staff-staff-spacing** when it is unset, for ungrouped staves and for grouped staves that do not have the relevant **StaffGrouper** property set (**staff-staff-spacing** or **staffgroup-staff-spacing**).
- details** (list)  
Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a **details** property.
- digit-names** (vector)  
Names for string finger digits.
- direction** (direction)  
If **side-axis** is 0 (or X), then this property determines whether the object is placed LEFT, CENTER or RIGHT with respect to the other object. Otherwise, it determines

whether the object is placed UP, CENTER or DOWN. Numerical values may also be used: UP=1, DOWN=-1, LEFT=-1, RIGHT=1, CENTER=0.

**dot-count** (integer)

The number of dots.

**dot-negative-kern** (number)

The space to remove between a dot and a slash in percent repeat glyphs. Larger values bring the two elements closer together.

**dot-placement-list** (list)

List consisting of (*description string-number fret-number finger-number*) entries used to define fret diagrams.

**duration-log** (integer)

The 2-log of the note head duration, i.e., 0 = whole note, 1 = half note, etc.

**eccentricity** (number)

How asymmetrical to make a slur. Positive means move the center to the right.

**edge-height** (pair)

A pair of numbers specifying the heights of the vertical edges: (*left-height . right-height*).

**edge-text** (pair)

A pair specifying the texts to be set at the edges: (*left-text . right-text*).

**expand-limit** (integer)

Maximum number of measures expanded in church rests.

**extra-dy** (number)

Slope glissandi this much extra.

**extra-offset** (pair of numbers)

A pair representing an offset. This offset is added just before outputting the symbol, so the typesetting engine is completely oblivious to it. The values are measured in **staff-space** units of the staff's **StaffSymbol**.

**extra-spacing-height** (pair of numbers)

In the horizontal spacing problem, we increase the height of each item by this amount (by adding the 'car' to the bottom of the item and adding the 'cdr' to the top of the item). In order to make a grob infinitely high (to prevent the horizontal spacing problem from placing any other grobs above or below this grob), set this to (**-inf.0 . +inf.0**).

**extra-spacing-width** (pair of numbers)

In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to (**+inf.0 . -inf.0**).

**extra-X-extent** (pair of numbers)

A grob is enlarged in X dimension by this much.

**extra-Y-extent** (pair of numbers)

A grob is enlarged in Y dimension by this much.

**flag-count** (number)

The number of tremolo beams.

**font-encoding** (symbol)

The font encoding is the broadest category for selecting a font. Currently, only LilyPond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

**font-family** (symbol)

The font family is the broadest category for selecting text fonts. Options include: `sans`, `roman`.

**font-name** (string)

Specifies a file name (without extension) of the font to load. This setting overrides selection using `font-family`, `font-series` and `font-shape`.

**font-series** (symbol)

Select the series of a font. Choices include `medium`, `bold`, `bold-narrow`, etc.

**font-shape** (symbol)

Select the shape of a font. Choices include `upright`, `italic`, `caps`.

**font-size** (number)

The font size, compared to the 'normal' size. 0 is style-sheet's normal size, -1 is smaller, +1 is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

**footnote** (boolean)

Should this be a footnote or in-note?

**footnote-text** (markup)

A footnote for the grob.

**force-hshift** (number)

This specifies a manual shift for notes in collisions. The unit is the note head width of the first voice note. This is used by [Section "note-collision-interface" in \*Internals Reference\*](#).

**forced-spacing** (number)

Spacing forced between grobs, used in various ligature engravers.

**fraction** (fraction, as pair)

Numerator and denominator of a time signature object.

**french-beaming** (boolean)

Use French beaming style for this stem. The stem stops at the innermost beams.

**fret-diagram-details** (list)

An alist of detailed grob properties for fret diagrams. Each alist entry consists of a (*property* . *value*) pair. The properties which can be included in `fret-diagram-details` include the following:

- `barre-type` – Type of barre indication used. Choices include `curved`, `straight`, and `none`. Default `curved`.
- `capo-thickness` – Thickness of capo indicator, in multiples of fret-space. Default value 0.5.
- `dot-color` – Color of dots. Options include `black` and `white`. Default `black`.
- `dot-label-font-mag` – Magnification for font used to label fret dots. Default value 1.
- `dot-position` – Location of dot in fret space. Default 0.6 for dots without labels, 0.95-dot-radius for dots with labels.

- **dot-radius** – Radius of dots, in terms of fret spaces. Default value 0.425 for labeled dots, 0.25 for unlabeled dots.
- **finger-code** – Code for the type of fingering indication used. Options include **none**, **in-dot**, and **below-string**. Default **none** for markup fret diagrams, **below-string** for FretBoards fret diagrams.
- **fret-count** – The number of frets. Default 4.
- **fret-label-custom-format** – The format string to be used label the lowest fret number, when **number-type** equals to **custom**. Default `"~a"`.
- **fret-label-font-mag** – The magnification of the font used to label the lowest fret number. Default 0.5.
- **fret-label-vertical-offset** – The offset of the fret label from the center of the fret in direction parallel to strings. Default 0.
- **label-dir** – Side to which the fret label is attached. -1, **LEFT**, or **DOWN** for left or down; 1, **RIGHT**, or **UP** for right or up. Default **RIGHT**.
- **mute-string** – Character string to be used to indicate muted string. Default `"x"`.
- **number-type** – Type of numbers to use in fret label. Choices include **roman-lower**, **roman-upper**, **arabic** and **custom**. In the later case, the format string is supplied by the **fret-label-custom-format** property. Default **roman-lower**.
- **open-string** – Character string to be used to indicate open string. Default `"o"`.
- **orientation** – Orientation of fret-diagram. Options include **normal**, **landscape**, and **opposing-landscape**. Default **normal**.
- **string-count** – The number of strings. Default 6.
- **string-label-font-mag** – The magnification of the font used to label fingerings at the string, rather than in the dot. Default value 0.6 for **normal** orientation, 0.5 for **landscape** and **opposing-landscape**.
- **string-thickness-factor** – Factor for changing thickness of each string in the fret diagram. Thickness of string  $k$  is given by  $\text{thickness} * (1 + \text{string-thickness-factor})^{(k-1)}$ . Default 0.
- **top-fret-thickness** – The thickness of the top fret line, as a multiple of the standard thickness. Default value 3.
- **xo-font-magnification** – Magnification used for mute and open string indicators. Default value 0.5.
- **xo-padding** – Padding for open and mute indicators from top fret. Default value 0.25.

**full-length-padding** (number)

How much padding to use at the right side of a full-length tuplet bracket.

**full-length-to-extent** (boolean)

Run to the extent of the column for a full-length tuplet bracket.

**full-measure-extra-space** (number)

Extra space that is allocated at the beginning of a measure with only one note. This property is read from the `NonMusicalPaperColumn` that begins the measure.

**full-size-change** (boolean)

Don't make a change clef smaller.

- gap** (dimension, in staff space)  
Size of a gap in a variable symbol.
- gap-count** (integer)  
Number of gapped beams for tremolo.
- glissando-skip** (boolean)  
Should this **NoteHead** be skipped by glissandi?
- glyph** (string)  
A string determining what ‘style’ of glyph is typeset. Valid choices depend on the function that is reading this property.
- glyph-name** (string)  
The glyph name within the font.
- glyph-name-alist** (list)  
An alist of key-string pairs.
- graphical** (boolean)  
Display in graphical (vs. text) form.
- grow-direction** (direction)  
Crescendo or decrescendo?
- hair-thickness** (number)  
Thickness of the thin line in a bar line.
- harp-pedal-details** (list)  
An alist of detailed grob properties for harp pedal diagrams. Each alist entry consists of a (*property* . *value*) pair. The properties which can be included in harp-pedal-details include the following:
- **box-offset** – Vertical shift of the center of flat/sharp pedal boxes above/below the horizontal line. Default value 0.8.
  - **box-width** – Width of each pedal box. Default value 0.4.
  - **box-height** – Height of each pedal box. Default value 1.0.
  - **space-before-divider** – Space between boxes before the first divider (so that the diagram can be made symmetric). Default value 0.8.
  - **space-after-divider** – Space between boxes after the first divider. Default value 0.8.
  - **circle-thickness** – Thickness (in unit of the line-thickness) of the ellipse around circled pedals. Default value 0.5.
  - **circle-x-padding** – Padding in X direction of the ellipse around circled pedals. Default value 0.15.
  - **circle-y-padding** – Padding in Y direction of the ellipse around circled pedals. Default value 0.2.
- head-direction** (direction)  
Are the note heads left or right in a semitie?
- height** (dimension, in staff space)  
Height of an object in **staff-space** units.
- height-limit** (dimension, in staff space)  
Maximum slur height: The longer the slur, the closer it is to this height.
- hide-tied-accidental-after-break** (boolean)  
If set, an accidental that appears on a tied note after a line break will not be displayed.



**horizontal-shift** (integer)

An integer that identifies ranking of **NoteColumns** for horizontal shifting. This is used by [Section “note-collision-interface”](#) in *Internals Reference*.

**horizontal-skylines** (pair of skylines)

Two skylines, one to the left and one to the right of this grob.

**id** (string)

An id string for the grob. Depending on the typesetting backend being used, this id will be assigned to a group containing all of the stencils that comprise a given grob. For example, in the svg backend, the string will be assigned to the **id** attribute of a group (<g>) that encloses the stencils that comprise the grob. In the Postscript backend, as there is no way to group items, the setting of the id property will have no effect.

**ignore-collision** (boolean)

If set, don't do note collision resolution on this **NoteColumn**.

**implicit** (boolean)

Is this an implicit bass figure?

**inspect-index** (integer)

If debugging is set, set beam and slur configuration to this index, and print the respective scores.

**inspect-quants** (pair of numbers)

If debugging is set, set beam and slur quants to this position, and print the respective scores.

**keep-inside-line** (boolean)

If set, this column cannot have objects sticking into the margin.

**kern** (dimension, in staff space)

Amount of extra white space to add. For bar lines, this is the amount of space after a thick line.

**knee** (boolean)

Is this beam kneed?

**knee-spacing-correction** (number)

Factor for the optical correction amount for kneed beams. Set between 0 for no correction and 1 for full correction.

**labels** (list)

List of labels (symbols) placed on a column.

**layer** (integer)

An integer which determines the order of printing objects. Objects with the lowest value of layer are drawn first, then objects with progressively higher values are drawn, so objects with higher values overwrite objects with lower values. By default most objects are assigned a layer value of 1.

**ledger-extra** (dimension, in staff space)

Extra distance from staff line to draw ledger lines for.

**ledger-line-thickness** (pair of numbers)

The thickness of ledger lines. It is the sum of 2 numbers: The first is the factor for line thickness, and the second for staff space. Both contributions are added.

**ledger-positions** (list)

Repeating pattern for the vertical positions of ledger lines. Bracketed groups are always shown together.

**left-bound-info** (list)

An alist of properties for determining attachments of spanners to edges.

**left-padding** (dimension, in staff space)

The amount of space that is put left to an object (e.g., a lyric extender).

**length** (dimension, in staff space)

User override for the stem length of unbeamed stems.

**length-fraction** (number)

Multiplier for lengths. Used for determining ledger lines and stem lengths.

**line-break-penalty** (number)

Penalty for a line break at this column. This affects the choices of the line breaker; it avoids a line break at a column with a positive penalty and prefers a line break at a column with a negative penalty.

**line-break-permission** (symbol)

Instructs the line breaker on whether to put a line break at this column. Can be **force** or **allow**.

**line-break-system-details** (list)

An alist of properties to use if this column is the start of a system.

**line-count** (integer)

The number of staff lines.

**line-positions** (list)

Vertical positions of staff lines.

**line-thickness** (number)

The thickness of the tie or slur contour.

**long-text** (markup)

Text markup. See [Section “Formatting text” in \*Notation Reference\*](#).

**max-beam-connect** (integer)

Maximum number of beams to connect to beams from this stem. Further beams are typeset as beamlets.

**max-stretch** (number)

The maximum amount that this `VerticalAxisGroup` can be vertically stretched (for example, in order to better fill a page).

**measure-count** (integer)

The number of measures for a multi-measure rest.

**measure-length** (moment)

Length of a measure. Used in some spacing situations.

**merge-differently-dotted** (boolean)

Merge note heads in collisions, even if they have a different number of dots. This is normal notation for some types of polyphonic music.

**merge-differently-dotted** only applies to opposing stem directions (i.e., voice 1 & 2).

**merge-differently-headed** (boolean)

Merge note heads in collisions, even if they have different note heads. The smaller of the two heads is rendered invisible. This is used in polyphonic guitar notation. The value of this setting is used by [Section “note-collision-interface” in \*Internals Reference\*](#).

**merge-differently-headed** only applies to opposing stem directions (i.e., voice 1 & 2).

**minimum-distance** (dimension, in staff space)

Minimum distance between rest and notes or beam.

**minimum-length** (dimension, in staff space)

Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the **springs-and-rods** property. If added to a **Tie**, this sets the minimum distance between noteheads.

**minimum-length-fraction** (number)

Minimum length of ledger line as fraction of note head size.

**minimum-space** (dimension, in staff space)

Minimum distance that the victim should move (after padding).

**minimum-X-extent** (pair of numbers)

Minimum size of an object in X dimension, measured in **staff-space** units.

**minimum-Y-extent** (pair of numbers)

Minimum size of an object in Y dimension, measured in **staff-space** units.

**neutral-direction** (direction)

Which direction to take in the center of the staff.

**neutral-position** (number)

Position (in half staff spaces) where to flip the direction of custos stem.

**next** (graphical (layout) object)

Object that is next relation (e.g., the lyric syllable following an extender).

**no-alignment** (boolean)

If set, don't place this grob in a **VerticalAlignment**; rather, place it using its own **Y-offset** callback.

**no-ledgers** (boolean)

If set, don't draw ledger lines on this object.

**no-stem-extend** (boolean)

If set, notes with ledger lines do not get stems extending to the middle staff line.

**non-break-align-symbols** (list)

A list of symbols that determine which NON-break-aligned interfaces to align this to.

**non-default** (boolean)

Set for manually specified clefs.

**non-musical** (boolean)

True if the grob belongs to a **NonMusicalPaperColumn**.

**nonstaff-nonstaff-spacing** (list)

The spacing alist controlling the distance between the current non-staff line and the next non-staff line in the direction of **staff-affinity**, if both are on the same side of the related staff, and **staff-affinity** is either UP or DOWN. See **staff-staff-spacing** for a description of the alist structure.

**nonstaff-relatedstaff-spacing** (list)

The spacing alist controlling the distance between the current non-staff line and the nearest staff in the direction of **staff-affinity**, if there are no non-staff lines between the two, and **staff-affinity** is either UP or DOWN. If **staff-affinity** is CENTER, then **nonstaff-relatedstaff-spacing** is used for the nearest staves on *both* sides, even if other non-staff lines appear between the current one and either of the staves. See **staff-staff-spacing** for a description of the alist structure.

**nonstaff-unrelatedstaff-spacing** (list)

The spacing alist controlling the distance between the current non-staff line and the nearest staff in the opposite direction from **staff-affinity**, if there are no other non-staff lines between the two, and **staff-affinity** is either UP or DOWN. See **staff-staff-spacing** for a description of the alist structure.

**normalized-endpoints** (pair)

Represents left and right placement over the total spanner, where the width of the spanner is normalized between 0 and 1.

**note-names** (vector)

Vector of strings containing names for easy-notation note heads.

**outside-staff-horizontal-padding** (number)

By default, an outside-staff-object can be placed so that it is very close to another grob horizontally. If this property is set, the outside-staff-object is raised so that it is not so close to its neighbor.

**outside-staff-padding** (number)

The padding to place between this grob and the staff when spacing according to **outside-staff-priority**.

**outside-staff-priority** (number)

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller **outside-staff-priority** is closer to the staff.

**packed-spacing** (boolean)

If set, the notes are spaced as tightly as possible.

**padding** (dimension, in staff space)

Add this much extra space between objects that are next to each other.

**padding-pairs** (list)

An alist mapping (*name* . *name*) to distances.

**page-break-penalty** (number)

Penalty for page break at this column. This affects the choices of the page breaker; it avoids a page break at a column with a positive penalty and prefers a page break at a column with a negative penalty.

**page-break-permission** (symbol)

Instructs the page breaker on whether to put a page break at this column. Can be *force* or *allow*.

**page-turn-penalty** (number)

Penalty for a page turn at this column. This affects the choices of the page breaker; it avoids a page turn at a column with a positive penalty and prefers a page turn at a column with a negative penalty.

- page-turn-permission** (symbol)  
Instructs the page breaker on whether to put a page turn at this column. Can be **force** or **allow**.
- parenthesized** (boolean)  
Parenthesize this grob.
- positions** (pair of numbers)  
Pair of staff coordinates (*left* . *right*), where both *left* and *right* are in **staff-space** units of the current staff. For slurs, this value selects which slur candidate to use; if extreme positions are requested, the closest one is taken.
- prefer-dotted-right** (boolean)  
For note collisions, prefer to shift dotted up-note to the right, rather than shifting just the dot.
- ratio** (number)  
Parameter for slur shape. The higher this number, the quicker the slur attains its **height-limit**.
- remove-empty** (boolean)  
If set, remove group if it contains no interesting items.
- remove-first** (boolean)  
Remove the first staff of an orchestral score?
- replacement-alist** (list)  
Alist of strings. The key is a string of the pattern to be replaced. The value is a string of what should be displayed. Useful for ligatures.
- restore-first** (boolean)  
Print a natural before the accidental.
- rhythmic-location** (rhythmic location)  
Where (bar number, measure position) in the score.
- right-bound-info** (list)  
An alist of properties for determining attachments of spanners to edges.
- right-padding** (dimension, in staff space)  
Space to insert on the right side of an object (e.g., between note and its accidentals).
- rotation** (list)  
Number of degrees to rotate this object, and what point to rotate around. For example, '(45 0 0) rotates by 45 degrees around the center of this object.
- round-up-exceptions** (list)  
A list of pairs where car is the numerator and cdr the denominator of a moment. Each pair in this list means that the multi-measure rests of the corresponding length will be rounded up to the longer rest. See *round-up-to-longer-rest*.
- round-up-to-longer-rest** (boolean)  
Displays the longer multi-measure rest when the length of a measure is between two values of **usable-duration-logs**. For example, displays a breve instead of a whole in a 3/2 measure.
- same-direction-correction** (number)  
Optical correction amount for stems that are placed in tight configurations. This amount is used for stems with the same direction to compensate for note head to stem distance.

**script-priority** (number)

A sorting key that determines in what order a script is within a stack of scripts.

**self-alignment-X** (number)

Specify alignment of an object. The value -1 means left aligned, 0 centered, and 1 right-aligned in X direction. Other numerical values may also be specified.

**self-alignment-Y** (number)

Like **self-alignment-X** but for the Y axis.

**shorten-pair** (pair of numbers)

The lengths to shorten a text-spanner on both sides, for example a pedal bracket. Positive values shorten the text-spanner, while negative values lengthen it.

**shortest-duration-space** (dimension, in staff space)

Start with this much space for the shortest duration. This is expressed in **spacing-increment** as unit. See also [Section “spacing-spanner-interface” in \*Internals Reference\*](#).

**shortest-playing-duration** (moment)

The duration of the shortest note playing here.

**shortest-starter-duration** (moment)

The duration of the shortest note that starts here.

**side-axis** (number)

If the value is X (or equivalently 0), the object is placed horizontally next to the other object. If the value is Y or 1, it is placed vertically.

**side-relative-direction** (direction)

Multiply direction of **direction-source** with this to get the direction of this object.

**simple-Y** (boolean)

Should the Y placement of a spanner disregard changes in system heights?

**size** (number)

Size of object, relative to standard size.

**skip-quanting** (boolean)

Should beam quanting be skipped?

**skyline-horizontal-padding** (number)

For determining the vertical distance between two staves, it is possible to have a configuration which would result in a tight interleaving of grobs from the top staff and the bottom staff. The larger this parameter is, the farther apart the staves are placed in such a configuration.

**skyline-vertical-padding** (number)

The amount by which the left and right skylines of a column are padded vertically, beyond the **Y-extents** and **extra-spacing-heights** of the constituent grobs in the column. Increase this to prevent interleaving of grobs from adjacent columns.

**slash-negative-kern** (number)

The space to remove between slashes in percent repeat glyphs. Larger values bring the two elements closer together.

**slope** (number)

The slope of this object.

**slur-padding** (number)

Extra distance between slur and script.

**space-alist** (list)

A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: (*break-align-symbol* *type* . *distance*), where *type* can be the symbols `minimum-space` or `extra-space`.

**space-to-barline** (boolean)

If set, the distance between a note and the following non-musical column will be measured to the bar line instead of to the beginning of the non-musical column. If there is a clef change followed by a bar line, for example, this means that we will try to space the non-musical column as though the clef is not there.

**spacing-increment** (number)

Add this much space for a doubled duration. Typically, the width of a note head. See also [Section “spacing-spanner-interface” in \*Internals Reference\*](#).

**spacing-pair** (pair)

A pair of alignment symbols which set an object’s spacing relative to its left and right `BreakAlignments`.

For example, a `MultiMeasureRest` will ignore prefatory items at its bounds (i.e., clefs, key signatures and time signatures) using the following override:

```
\override MultiMeasureRest
  #'spacing-pair = #'(staff-bar . staff-bar)
```

**spanner-id** (string)

An identifier to distinguish concurrent spanners.

**springs-and-rods** (boolean)

Dummy variable for triggering spacing routines.

**stacking-dir** (direction)

Stack objects in which direction?

**staff-affinity** (direction)

The direction of the staff to use for spacing the current non-staff line. Choices are `UP`, `DOWN`, and `CENTER`. If `CENTER`, the non-staff line will be placed equidistant between the two nearest staves on either side, unless collisions or other spacing constraints prevent this. Setting `staff-affinity` for a staff causes it to be treated as a non-staff line. Setting `staff-affinity` to `#f` causes a non-staff line to be treated as a staff.

**staff-padding** (dimension, in staff space)

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics `p` and `f`) on their baselines.

**staff-position** (number)

Vertical position, measured in half staff spaces, counted from the middle line.

**staff-space** (dimension, in staff space)

Amount of space between staff lines, expressed in global `staff-space`.

**staff-staff-spacing** (list)

When applied to a staff-group’s `StaffGrouper` grob, this spacing alist controls the distance between consecutive staves within the staff-group. When applied to a staff’s `VerticalAxisGroup` grob, it controls the distance between the staff and the nearest staff below it in the same system, replacing any settings inherited from the `StaffGrouper` grob of the containing staff-group, if there is one. This property remains in effect even when non-staff lines appear between staves. The alist can contain the following keys:

- **basic-distance** – the vertical distance, measured in staff-spaces, between the reference points of the two items when no collisions would result, and no stretching or compressing is in effect.
- **minimum-distance** – the smallest allowable vertical distance, measured in staff-spaces, between the reference points of the two items, when compressing is in effect.
- **padding** – the minimum required amount of unobstructed vertical whitespace between the bounding boxes (or skylines) of the two items, measured in staff-spaces.
- **stretchability** – a unitless measure of the dimension’s relative propensity to stretch. If zero, the distance will not stretch (unless collisions would result).

**staffgroup-staff-spacing** (list)

The spacing alist controlling the distance between the last staff of the current staff-group and the staff just below it in the same system, even if one or more non-staff lines exist between the two staves. If the **staff-staff-spacing** property of the staff’s **VerticalAxisGroup** grob is set, that is used instead. See **staff-staff-spacing** for a description of the alist structure.

**stem-attachment** (pair of numbers)

An (x . y) pair where the stem attaches to the notehead.

**stem-begin-position** (number)

User override for the begin position of a stem.

**stem-spacing-correction** (number)

Optical correction amount for stems that are placed in tight configurations. For opposite directions, this amount is the correction for two normal sized stems that overlap completely.

**stemlet-length** (number)

How long should be a stem over a rest?

**stencil** (stencil)

The symbol to print.

**stencils** (list)

Multiple stencils, used as intermediate value.

**strict-grace-spacing** (boolean)

If set, main notes are spaced normally, then grace notes are put left of the musical columns for the main notes.

**strict-note-spacing** (boolean)

If set, unbroken columns with non-musical material (clefs, bar lines, etc.) are not spaced separately, but put before musical columns.

**stroke-style** (string)

Set to "grace" to turn stroke through flag on.

**style** (symbol)

This setting determines in what style a grob is typeset. Valid choices depend on the **stencil** callback reading this property.

**text** (markup)

Text markup. See [Section “Formatting text” in \*Notation Reference\*](#).

**text-direction** (direction)

This controls the ordering of the words. The default **RIGHT** is for roman text. Arabic or Hebrew should use **LEFT**.



**thick-thickness** (number)

Bar line thickness, measured in **line-thickness**.

**thickness** (number)

Line thickness, generally measured in **line-thickness**.

**thin-kern** (number)

The space after a hair-line in a bar line.

**tie-configuration** (list)

List of (**position** . **dir**) pairs, indicating the desired tie configuration, where *position* is the offset from the center of the staff in staff space and *dir* indicates the direction of the tie (1=>up, -1=>down, 0=>center). A non-pair entry in the list causes the corresponding tie to be formatted automatically.

**to-barline** (boolean)

If true, the spanner will stop at the bar line just before it would otherwise stop.

**toward-stem-shift** (number)

Amount by which scripts are shifted toward the stem if their direction coincides with the stem direction. 0.0 means keep the default position (centered on the note head), 1.0 means centered on the stem. Interpolated values are possible.

**transparent** (boolean)

This makes the grob invisible.

**uniform-stretching** (boolean)

If set, items stretch proportionally to their durations. This looks better in complex polyphonic patterns.

**usable-duration-logs** (list)

List of **duration-logs** that can be used in typesetting the grob.

**use-skylines** (boolean)

Should skylines be used for side positioning?

**used** (boolean)

If set, this spacing column is kept in the spacing problem.

**vertical-skylines** (pair of skylines)

Two skylines, one above and one below this grob.

**when** (moment)

Global time step associated with this column happen?

**whiteout** (boolean)

If true, the grob is printed over a white background to white-out underlying material, if the grob is visible. Usually #f by default.

**width** (dimension, in staff space)

The width of a grob measured in staff space.

**word-space** (dimension, in staff space)

Space to insert between words in texts.

**X-extent** (pair of numbers)

Hard coded extent in X direction.

**X-offset** (number)

The horizontal amount that this object is moved relative to its X-parent.

**X-positions** (pair of numbers)

Pair of X staff coordinates of a spanner in the form (*left* . *right*), where both *left* and *right* are in **staff-space** units of the current staff.

**Y-extent** (pair of numbers)

Hard coded extent in Y direction.

**Y-offset** (number)

The vertical amount that this object is moved relative to its Y-parent.

**zigzag-length** (dimension, in staff space)

The length of the lines of a zigzag, relative to **zigzag-width**. A value of 1 gives 60-degree zigzags.

**zigzag-width** (dimension, in staff space)

The width of one zigzag squiggle. This number is adjusted slightly so that the glissando line can be constructed from a whole number of squiggles.

## A.17 Available music functions

**acciacatura** [music] - *music* (music)

Create an acciacatura from the following music expression

**accidentalStyle** [music] - *context* [symbol] *style* (string)

Set accidental style to *style*, a string. If an optional *context* symbol is given, e.g. **#'Staff** or **#'Voice**, the settings are applied to that context. Otherwise, the context defaults to **'Staff'**, except for piano styles, which use **'GrandStaff'** as a context.

**addChordShape** [music] - *key-symbol* (symbol) *tuning* (pair) *shape-definition* (string or pair)

Add chord shape *shape-definition* to the *chord-shape-table* hash with the key (**cons** *key-symbol* *tuning*).

**addInstrumentDefinition** [void] - *name* (string) *lst* (list)

Create instrument *name* with properties *list*.

**addQuote** [void] - *name* (string) *music* (music)

Define *music* as a quotable music expression named *name*

**afterGrace** [music] - *main* (music) *grace* (music)

Create *grace* note(s) after a *main* music expression.

**allowPageTurn** [music]

Allow a page turn. May be used at toplevel (ie between scores or markups), or inside a score.

**appendToTag** [music] - *tag* (symbol) *more* (music) *music* (music)

Append *more* to the **elements** of all music expressions in *music* that are tagged with *tag*.

**applyContext** [music] - *proc* (procedure)

Modify context properties with Scheme procedure *proc*.

**applyMusic** [music] - *func* (procedure) *music* (music)

Apply procedure *func* to *music*.

**applyOutput** [music] - *ctx* (symbol) *proc* (procedure)

Apply function *proc* to every layout object in context *ctx*

**appoggiatura** [music] - *music* (music)

Create an appoggiatura from *music*

|                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>assertBeamQuant</code> [music] - <i>l</i> (pair) <i>r</i> (pair)                                                              | Testing function: check whether the beam quantas <i>l</i> and <i>r</i> are correct                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <code>assertBeamSlope</code> [music] - <i>comp</i> (procedure)                                                                      | Testing function: check whether the slope of the beam is the same as <i>comp</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>autochange</code> [music] - <i>music</i> (music)                                                                              | Make voices that switch between staves automatically                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>balloonGrobText</code> [music] - <i>grob-name</i> (symbol) <i>offset</i> (pair of numbers) <i>text</i> (markup)               | Attach <i>text</i> to <i>grob-name</i> at offset <i>offset</i> (use like <code>\once</code> )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>balloonText</code> [music] - <i>offset</i> (pair of numbers) <i>text</i> (markup)                                             | Attach <i>text</i> at <i>offset</i> (use like <code>\tweak</code> )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>bar</code> [music] - <i>type</i> (string)                                                                                     | Insert a bar line of type <i>type</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>barNumberCheck</code> [music] - <i>n</i> (integer)                                                                            | Print a warning if the current bar number is not <i>n</i> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>bendAfter</code> [music] - <i>delta</i> (real number)                                                                         | Create a fall or doit of pitch interval <i>delta</i> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>bookOutputName</code> [void] - <i>newfilename</i> (string)                                                                    | Direct output for the current book block to <i>newfilename</i> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>bookOutputSuffix</code> [void] - <i>newsuffix</i> (string)                                                                    | Set the output filename suffix for the current book block to <i>newsuffix</i> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>breathe</code> [music]                                                                                                        | Insert a breath mark.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>chordRepeats</code> [music] - <i>event-types</i> [list] <i>music</i> (music)                                                  | Walk through <i>music</i> putting the notes of the previous chord into repeat chords, as well as an optional list of <i>event-types</i> such as <code>#'(string-number-event)</code> .                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>clef</code> [music] - <i>type</i> (string)                                                                                    | Set the current clef to <i>type</i> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>compoundMeter</code> [music] - <i>args</i> (pair)                                                                             | Create compound time signatures. The argument is a Scheme list of lists. Each list describes one fraction, with the last entry being the denominator, while the first entries describe the summands in the numerator. If the time signature consists of just one fraction, the list can be given directly, i.e. not as a list containing a single list. For example, a time signature of $(3+1)/8 + 2/4$ would be created as <code>\compoundMeter #'((3 1 8) (2 4))</code> , and a time signature of $(3+2)/8$ as <code>\compoundMeter #'((3 2 8))</code> or shorter <code>\compoundMeter #'(3 2 8)</code> . |
| <code>cueClef</code> [music] - <i>type</i> (string)                                                                                 | Set the current cue clef to <i>type</i> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>cueClefUnset</code> [music]                                                                                                   | Unset the current cue clef.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>cueDuring</code> [music] - <i>what</i> (string) <i>dir</i> (direction) <i>main-music</i> (music)                              | Insert contents of quote <i>what</i> corresponding to <i>main-music</i> , in a CueVoice oriented by <i>dir</i> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>cueDuringWithClef</code> [music] - <i>what</i> (string) <i>dir</i> (direction) <i>clef</i> (string) <i>main-music</i> (music) | Insert contents of quote <i>what</i> corresponding to <i>main-music</i> , in a CueVoice oriented by <i>dir</i> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

- deadNote** [music] - *note* (music)  
Print *note* with a cross-shaped note head.
- defaultNoteHeads** [music]  
Revert to the default note head style.
- displayLilyMusic** [music] - *music* (music)  
Display the LilyPond input representation of *music* to the console.
- displayMusic** [music] - *music* (music)  
Display the internal representation of *music* to the console.
- endSpanners** [music] - *music* (music)  
Terminate the next spanner prematurely after exactly one note without the need of a specific end spanner.
- featherDurations** [music] - *factor* (moment) *argument* (music)  
Adjust durations of music in *argument* by rational *factor*.
- footnote** [music] - *text* [markup] *offset* (pair of numbers) *grob-name* [symbol] *footnote* (markup)  
Attach *text* at *offset* with *text* referring to *footnote*. If *text* is given as `\default`, use autonumbering instead. Note that, for this to take effect, auto-numbering must be turned on in the paper block. Otherwise, no number will appear. Footnotes are applied like articulations. If a symbol *grob-name* is specified, all grobs of that kind at the current time step are affected.
- grace** [music] - *music* (music)  
Insert *music* as grace notes.
- grobdescriptions** (any type) - *descriptions* (list)  
Create a context modification from *descriptions*, a list in the format of `all-grob-descriptions`.
- harmonicByFret** [music] - *fret* (number) *music* (music)  
Convert *music* into harmonics; the resulting notes resemble harmonics played on a fretted instrument by touching the strings above *fret*.
- harmonicByRatio** [music] - *ratio* (number) *music* (music)  
Convert *music* into harmonics; the resulting notes resemble harmonics played on a fretted instrument by touching the strings above the point given through *ratio*.
- harmonicNote** [music] - *note* (music)  
Print *note* with a diamond-shaped note head.
- harmonicsOn** [music]  
Set the default note head style to a diamond-shaped style.
- instrumentSwitch** [music] - *name* (string)  
Switch instrument to *name*, which must be predefined with `\addInstrumentDefinition`.
- inversion** [music] - *around* (pitch) *to* (pitch) *music* (music)  
Invert *music* about *around* and transpose from *around* to *to*.
- keepWithTag** [music] - *tag* (symbol) *music* (music)  
Include only elements of *music* that are tagged with *tag*.
- key** [music] - *tonic* [pitch] *pitch-alist* [list]  
Set key to *tonic* and scale *pitch-alist*. If both are null, just generate `KeyChangeEvent`.

- killCues** [music] - *music* (music)  
Remove cue notes from *music*.
- label** [music] - *label* (symbol)  
Create *label* as a bookmarking label.
- language** [void] - *language* (string)  
Set note names for language *language*.
- languageRestore** [void]  
Restore a previously-saved pitchnames alist.
- languageSaveAndChange** [void] - *language* (string)  
Store the previous pitchnames alist, and set a new one.
- makeClusters** [music] - *arg* (music)  
Display chords in *arg* as clusters.
- makeDefaultStringTuning** [void] - *symbol* (symbol) *pitches* (list)  
This defines a string tuning *symbol* via a list of *pitches*. The *symbol* also gets registered in **defaultStringTunings** for documentation purposes.
- mark** [music] - *label* [any type]  
Make the music for the \mark command.
- modalInversion** [music] - *around* (pitch) *to* (pitch) *scale* (music) *music* (music)  
Invert *music* about *around* using *scale* and transpose from *around* to *to*.
- modalTranspose** [music] - *from* (pitch) *to* (pitch) *scale* (music) *music* (music)  
Transpose *music* from pitch *from* to pitch *to* using *scale*.
- musicMap** [music] - *proc* (procedure) *mus* (music)  
Apply *proc* to *mus* and all of the music it contains.
- noPageBreak** [music]  
Forbid a page break. May be used at toplevel (i.e., between scores or markups), or inside a score.
- noPageTurn** [music]  
Forbid a page turn. May be used at toplevel (i.e., between scores or markups), or inside a score.
- octaveCheck** [music] - *pitch* (pitch)  
Octave check.
- once** [music] - *music* (music)  
Set **once** to **#t** on all layout instruction events in *music*.
- ottava** [music] - *octave* (integer)  
Set the octavation.
- overrideProperty** [music] - *name* (string) *property* (symbol) *value* (any type)  
Set *property* to *value* in all grobs named *name*. The *name* argument is a string of the form "Context.GrobName" or "GrobName".
- overrideTimeSignatureSettings** [music] - *time-signature* (pair) *base-moment* (pair) *beat-structure* (list) *beam-exceptions* (list)  
Override **timeSignatureSettings** for time signatures of *time-signature* to have settings of *base-moment*, *beat-structure*, and *beam-exceptions*.
- pageBreak** [music]  
Force a page break. May be used at toplevel (i.e., between scores or markups), or inside a score.

**pageTurn** [music]

Force a page turn between two scores or top-level markups.

**palmMute** [music] - *note* (music)

Print *note* with a triangle-shaped note head.

**palmMuteOn** [music]

Set the default note head style to a triangle-shaped style.

**parallelMusic** [void] - *voice-ids* (list) *music* (music)

Define parallel music sequences, separated by '|' (bar check signs), and assign them to the identifiers provided in *voice-ids*.

*voice-ids*: a list of music identifiers (symbols containing only letters)

*music*: a music sequence, containing BarChecks as limiting expressions.

Example:

```
\parallelMusic #'(A B C) {
  c c | d d | e e |
  d d | e e | f f |
}
<==>
A = { c c | d d | }
B = { d d | e e | }
C = { e e | f f | }
```

**parenthesize** [music] - *arg* (music)

Tag *arg* to be parenthesized.

**partcombine** [music] - *part1* (music) *part2* (music)

Take the music in *part1* and *part2* and typeset so that they share a staff.

**partcombineDown** [music] - *part1* (music) *part2* (music)

Take the music in *part1* and *part2* and typeset so that they share a staff with stems directed downward.

**partcombineForce** [music] - *type* (symbol-or-boolean) *once* (boolean)

Override the part-combiner.

**partcombineUp** [music] - *part1* (music) *part2* (music)

Take the music in *part1* and *part2* and typeset so that they share a staff with stems directed upward.

**partial** [music] - *dur* (duration)

Make a partial measure.

**phrasingSlurDashPattern** [music] - *dash-fraction* (number) *dash-period* (number)

Set up a custom style of dash pattern for *dash-fraction* ratio of line to space repeated at *dash-period* interval for phrasing slurs.

**pitchedTrill** [music] - *main-note* (music) *secondary-note* (music)

Print a trill with *main-note* as the main note of the trill and print *secondary-note* as a stemless note head in parentheses.

**pointAndClickOff** [music]

Suppress generating extra code in final-format (e.g. pdf) files to point back to the lilypond source statement.

**pointAndClickOn** [music]

Enable generation of code in final-format (e.g. pdf) files to reference the originating lilypond source statement; this is helpful when developing a score but generates bigger final-format files.

- pointAndClickTypes** [void] - *types* (list or symbol)  
Set a type or list of types (such as `#'note-event`) for which point-and-click info is generated.
- pushToTag** [music] - *tag* (symbol) *more* (music) *music* (music)  
Add *more* to the front of **elements** of all music expressions in *music* that are tagged with *tag*.
- quoteDuring** [music] - *what* (string) *main-music* (music)  
Indicate a section of music to be quoted. *what* indicates the name of the quoted voice, as specified in an `\addQuote` command. *main-music* is used to indicate the length of music to be quoted; usually contains spacers or multi-measure rests.
- relative** [music] - *pitch* [pitch] *music* (music)  
Make *music* relative to *pitch* (default `c'`).
- removeWithTag** [music] - *tag* (symbol) *music* (music)  
Remove elements of *music* that are tagged with *tag*.
- resetRelativeOctave** [music] - *pitch* (pitch)  
Set the octave inside a `\relative` section.
- retrograde** [music] - *music* (music)  
Return *music* in reverse order.
- revertTimeSignatureSettings** [music] - *time-signature* (pair)  
Revert **timeSignatureSettings** for time signatures of *time-signature*.
- rightHandFinger** [music] - *finger* (number or string)  
Apply *finger* as a fingering indication.
- scaleDurations** [music] - *fraction* (fraction, as pair) *music* (music)  
Multiply the duration of events in *music* by *fraction*.
- settingsFrom** (any type) - *ctx* [symbol] *music* (music)  
Take the layout instruction events from *music*, optionally restricted to those applying to context type *ctx*, and return a context modification duplicating their effect.
- shiftDurations** [music] - *dur* (integer) *dots* (integer) *arg* (music)  
Change the duration of *arg* by adding *dur* to the **durlog** of *arg* and *dots* to the **dots** of *arg*.
- skip** [music] - *dur* (duration)  
Skip forward by *dur*.
- slashedGrace** [music] - *music* (music)  
Create slashed graces (slashes through stems, but no slur) from the following music expression
- slurDashPattern** [music] - *dash-fraction* (number) *dash-period* (number)  
Set up a custom style of dash pattern for *dash-fraction* ratio of line to space repeated at *dash-period* interval for slurs.
- spacingTweaks** [music] - *parameters* (list)  
Set the system stretch, by reading the 'system-stretch' property of the 'parameters' assoc list.
- storePredefinedDiagram** [music] - *fretboard-table* (hash table) *chord* (music) *tuning* (pair) *diagram-definition* (string or pair)  
Add predefined fret diagram defined by *diagram-definition* for the chord pitches *chord* and the stringTuning *tuning*.

- stringTuning** (any type) - *chord* (music)  
Convert *chord* to a string tuning. *chord* must be in absolute pitches and should have the highest string number (generally the lowest pitch) first.
- styledNoteHeads** [music] - *style* (symbol) *heads* (list or symbol) *music* (music)  
Set *heads* in *music* to *style*.
- tabChordRepeats** [music] - *event-types* [list] *music* (music)  
Walk through *music* putting the notes, fingerings and string numbers of the previous chord into repeat chords, as well as an optional list of *event-types* such as `#'(articulation-event)`.
- tabChordRepetition** [void]  
Include the string and fingering information in a chord repetition. This function is deprecated; try using **abChordRepeats** instead.
- tag** [music] - *tag* (symbol) *arg* (music)  
Add *tag* to the **tags** property of *arg*.
- tieDashPattern** [music] - *dash-fraction* (number) *dash-period* (number)  
Set up a custom style of dash pattern for *dash-fraction* ratio of line to space repeated at *dash-period* interval for ties.
- time** [music] - *beat-structure* [number list] *fraction* (fraction, as pair)  
Set *fraction* as time signature, with optional number list *beat-structure* before it.
- times** [music] - *fraction* (fraction, as pair) *music* (music)  
Scale *music* in time by *fraction*.
- tocItem** [music] - *text* (markup)  
Add a line to the table of content, using the **tocItemMarkup** paper variable markup
- transpose** [music] - *from* (pitch) *to* (pitch) *music* (music)  
Transpose *music* from pitch *from* to pitch *to*.
- transposedCueDuring** [music] - *what* (string) *dir* (direction) *pitch* (pitch) *main-music* (music)  
Insert notes from the part *what* into a voice called **cue**, using the transposition defined by *pitch*. This happens simultaneously with *main-music*, which is usually a rest. The argument *dir* determines whether the cue notes should be notated as a first or second voice.
- transposition** [music] - *pitch* (pitch)  
Set instrument transposition
- tweak** [music] - *sym* (symbol) *val* (any type) *arg* (music)  
Add *sym* . *val* to the **tweaks** property of *arg*.
- unfoldRepeats** [music] - *music* (music)  
Force any `\repeat volta`, `\repeat tremolo` or `\repeat percent` commands in *music* to be interpreted as `\repeat unfold`.
- void** [void] - *arg* (any type)  
Accept a scheme argument, return a void expression. Use this if you want to have a scheme expression evaluated because of its side-effects, but its value ignored.
- withMusicProperty** [music] - *sym* (symbol) *val* (any type) *music* (music)  
Set *sym* to *val* in *music*.
- xNote** [music] - *note* (music)  
Print *note* with a cross-shaped note head.
- xNotesOn** [music]  
Set the default note head style to a cross-shaped style.



## A.18 Context modification identifiers

The following commands are defined for use as context modifications within a `\layout` or `\with` block.

### RemoveEmptyStaves

Remove staves which are considered to be empty according to the list of interfaces set by `keepAliveInterfaces`.

- Removes Section ‘‘Axis\_group\_engraver’’ in *Internals Reference*.
- Removes Section ‘‘Hara\_kiri\_engraver’’ in *Internals Reference*.
- Adds Section ‘‘Hara\_kiri\_engraver’’ in *Internals Reference*.
- Sets grob property `remove-empty` in Section ‘‘VerticalAxisGroup’’ in *Internals Reference* to `#t`.

## A.19 Predefined type predicates

### R5RS primary predicates

| Type predicate          | Description |
|-------------------------|-------------|
| <code>boolean?</code>   | boolean     |
| <code>char?</code>      | character   |
| <code>number?</code>    | number      |
| <code>pair?</code>      | pair        |
| <code>port?</code>      | port        |
| <code>procedure?</code> | procedure   |
| <code>string?</code>    | string      |
| <code>symbol?</code>    | symbol      |
| <code>vector?</code>    | vector      |

### R5RS secondary predicates

| Type predicate                | Description                                                        |
|-------------------------------|--------------------------------------------------------------------|
| <code>char-alphabetic?</code> | alphabetic character                                               |
| <code>char-lower-case?</code> | lower-case character                                               |
| <code>char-numeric?</code>    | numeric character                                                  |
| <code>char-upper-case?</code> | upper-case character                                               |
| <code>char-whitespace?</code> | whitespace character                                               |
| <code>complex?</code>         | complex number                                                     |
| <code>eof-object?</code>      | end-of-file object                                                 |
| <code>even?</code>            | even number                                                        |
| <code>exact?</code>           | exact number                                                       |
| <code>inexact?</code>         | inexact number                                                     |
| <code>input-port?</code>      | input port                                                         |
| <code>integer?</code>         | integer                                                            |
| <code>list?</code>            | list ( <i>use <code>cheap-list?</code> for faster processing</i> ) |
| <code>negative?</code>        | negative number                                                    |
| <code>null?</code>            | null                                                               |
| <code>odd?</code>             | odd number                                                         |
| <code>output-port?</code>     | output port                                                        |
| <code>positive?</code>        | positive number                                                    |
| <code>rational?</code>        | rational number                                                    |

|                    |             |
|--------------------|-------------|
| <code>real?</code> | real number |
| <code>zero?</code> | zero        |

## Guile predicates

| Type predicate           | Description |
|--------------------------|-------------|
| <code>hash-table?</code> | hash table  |

## LilyPond scheme predicates

| Type predicate                    | Description                                                                  |
|-----------------------------------|------------------------------------------------------------------------------|
| <code>boolean-or-symbol?</code>   | boolean or symbol                                                            |
| <code>cheap-list?</code>          | list ( <i>use this instead of <code>list?</code> for faster processing</i> ) |
| <code>color?</code>               | color                                                                        |
| <code>fraction?</code>            | fraction, as pair                                                            |
| <code>grob-list?</code>           | list of grobs                                                                |
| <code>index?</code>               | non-negative integer                                                         |
| <code>list-or-symbol?</code>      | list or symbol                                                               |
| <code>markup?</code>              | markup                                                                       |
| <code>markup-command-list?</code> | markup command list                                                          |
| <code>markup-list?</code>         | markup list                                                                  |
| <code>moment-pair?</code>         | pair of moment objects                                                       |
| <code>number-list?</code>         | number list                                                                  |
| <code>number-or-grob?</code>      | number or grob                                                               |
| <code>number-or-pair?</code>      | number or pair                                                               |
| <code>number-or-string?</code>    | number or string                                                             |
| <code>number-pair?</code>         | pair of numbers                                                              |
| <code>rhythmic-location?</code>   | rhythmic location                                                            |
| <code>scheme?</code>              | any type                                                                     |
| <code>string-or-pair?</code>      | string or pair                                                               |
| <code>string-or-symbol?</code>    | string or symbol                                                             |
| <code>void?</code>                | void                                                                         |

## LilyPond exported predicates

| Type predicate                  | Description               |
|---------------------------------|---------------------------|
| <code>ly:box?</code>            | box                       |
| <code>ly:context?</code>        | context                   |
| <code>ly:context-mod?</code>    | context modification      |
| <code>ly:dimension?</code>      | dimension, in staff space |
| <code>ly:dir?</code>            | direction                 |
| <code>ly:dispatcher?</code>     | dispatcher                |
| <code>ly:duration?</code>       | duration                  |
| <code>ly:event?</code>          | post event                |
| <code>ly:font-metric?</code>    | font metric               |
| <code>ly:grob?</code>           | graphical (layout) object |
| <code>ly:grob-array?</code>     | array of grobs            |
| <code>ly:input-location?</code> | input location            |
| <code>ly:item?</code>           | item                      |
| <code>ly:iterator?</code>       | iterator                  |
| <code>ly:lily-lexer?</code>     | lily-lexer                |

|                                        |                                    |
|----------------------------------------|------------------------------------|
| <code>ly:lily-parser?</code>           | <code>lily-parser</code>           |
| <code>ly:listener?</code>              | <code>listener</code>              |
| <code>ly:moment?</code>                | <code>moment</code>                |
| <code>ly:music?</code>                 | <code>music</code>                 |
| <code>ly:music-function?</code>        | <code>music function</code>        |
| <code>ly:music-list?</code>            | <code>list of music objects</code> |
| <code>ly:music-output?</code>          | <code>music output</code>          |
| <code>ly:otf-font?</code>              | <code>OpenType font</code>         |
| <code>ly:output-def?</code>            | <code>output definition</code>     |
| <code>ly:page-marker?</code>           | <code>page marker</code>           |
| <code>ly:pango-font?</code>            | <code>pango font</code>            |
| <code>ly:paper-book?</code>            | <code>paper book</code>            |
| <code>ly:paper-system?</code>          | <code>paper-system Prob</code>     |
| <code>ly:pitch?</code>                 | <code>pitch</code>                 |
| <code>ly:prob?</code>                  | <code>property object</code>       |
| <code>ly:score?</code>                 | <code>score</code>                 |
| <code>ly:simple-closure?</code>        | <code>simple closure</code>        |
| <code>ly:skyline?</code>               | <code>skyline</code>               |
| <code>ly:skyline-pair?</code>          | <code>pair of skylines</code>      |
| <code>ly:source-file?</code>           | <code>source file</code>           |
| <code>ly:spanner?</code>               | <code>spanner</code>               |
| <code>ly:spring?</code>                | <code>spring</code>                |
| <code>ly:stencil?</code>               | <code>stencil</code>               |
| <code>ly:stream-event?</code>          | <code>stream event</code>          |
| <code>ly:translator?</code>            | <code>translator</code>            |
| <code>ly:translator-group?</code>      | <code>translator group</code>      |
| <code>ly:unpure-pure-container?</code> | <code>unpure/pure container</code> |

## A.20 Scheme functions

|                                                                                                                                                                                     |                                          |            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|------------|
| <code>ly:add-context-mod</code>                                                                                                                                                     | <i>contextmods</i> <i>modification</i>   | [Function] |
| Adds the given context <i>modification</i> to the list <i>contextmods</i> of context modifications.                                                                                 |                                          |            |
| <code>ly:add-file-name-alist</code>                                                                                                                                                 | <i>alist</i>                             | [Function] |
| Add mappings for error messages from <i>alist</i> .                                                                                                                                 |                                          |            |
| <code>ly:add-interface</code>                                                                                                                                                       | <i>iface</i> <i>desc</i> <i>props</i>    | [Function] |
| Add a new grob interface. <i>iface</i> is the interface name, <i>desc</i> is the interface description, and <i>props</i> is the list of user-settable properties for the interface. |                                          |            |
| <code>ly:add-listener</code>                                                                                                                                                        | <i>list</i> <i>disp</i> <i>cl</i>        | [Function] |
| Add the listener <i>list</i> to the dispatcher <i>disp</i> . Whenever <i>disp</i> hears an event of class <i>cl</i> , it is forwarded to <i>list</i> .                              |                                          |            |
| <code>ly:add-option</code>                                                                                                                                                          | <i>sym</i> <i>val</i> <i>description</i> | [Function] |
| Add a program option <i>sym</i> . <i>val</i> is the default value and <i>description</i> is a string description.                                                                   |                                          |            |
| <code>ly:all-grob-interfaces</code>                                                                                                                                                 |                                          | [Function] |
| Return the hash table with all grob interface descriptions.                                                                                                                         |                                          |            |
| <code>ly:all-options</code>                                                                                                                                                         |                                          | [Function] |
| Get all option settings in an alist.                                                                                                                                                |                                          |            |
| <code>ly:all-stencil-expressions</code>                                                                                                                                             |                                          | [Function] |
| Return all symbols recognized as stencil expressions.                                                                                                                               |                                          |            |

|                                                                                                                                                                                                                                           |            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>ly:assoc-get</b> <i>key alist default-value strict-checking</i>                                                                                                                                                                        | [Function] |
| Return value if <i>key</i> in <i>alist</i> , else <i>default-value</i> (or <b>#f</b> if not specified). If <i>strict-checking</i> is set to <b>#t</b> and <i>key</i> is not in <i>alist</i> , a <code>programming-error</code> is output. |            |
| <b>ly:axis-group-interface::add-element</b> <i>grob grob-element</i>                                                                                                                                                                      | [Function] |
| Set <i>grob</i> the parent of <i>grob-element</i> on all axes of <i>grob</i> .                                                                                                                                                            |            |
| <b>ly:basic-progress</b> <i>str rest</i>                                                                                                                                                                                                  | [Function] |
| A Scheme callable function to issue a basic progress message <i>str</i> . The message is formatted with <b>format</b> and <i>rest</i> .                                                                                                   |            |
| <b>ly:beam-score-count</b>                                                                                                                                                                                                                | [Function] |
| count number of beam scores.                                                                                                                                                                                                              |            |
| <b>ly:book-add-bookpart!</b> <i>book-smob book-part</i>                                                                                                                                                                                   | [Function] |
| Add <i>book-part</i> to <i>book-smob</i> book part list.                                                                                                                                                                                  |            |
| <b>ly:book-add-score!</b> <i>book-smob score</i>                                                                                                                                                                                          | [Function] |
| Add <i>score</i> to <i>book-smob</i> score list.                                                                                                                                                                                          |            |
| <b>ly:book-book-parts</b> <i>book</i>                                                                                                                                                                                                     | [Function] |
| Return book parts in <i>book</i> .                                                                                                                                                                                                        |            |
| <b>ly:book-header</b> <i>book</i>                                                                                                                                                                                                         | [Function] |
| Return header in <i>book</i> .                                                                                                                                                                                                            |            |
| <b>ly:book-paper</b> <i>book</i>                                                                                                                                                                                                          | [Function] |
| Return paper in <i>book</i> .                                                                                                                                                                                                             |            |
| <b>ly:book-process</b> <i>book-smob default-paper default-layout output</i>                                                                                                                                                               | [Function] |
| Print book. <i>output</i> is passed to the backend unchanged. For example, it may be a string (for file based outputs) or a socket (for network based output).                                                                            |            |
| <b>ly:book-process-to-systems</b> <i>book-smob default-paper default-layout output</i>                                                                                                                                                    | [Function] |
| Print book. <i>output</i> is passed to the backend unchanged. For example, it may be a string (for file based outputs) or a socket (for network based output).                                                                            |            |
| <b>ly:book-scores</b> <i>book</i>                                                                                                                                                                                                         | [Function] |
| Return scores in <i>book</i> .                                                                                                                                                                                                            |            |
| <b>ly:box?</b> <i>x</i>                                                                                                                                                                                                                   | [Function] |
| Is <i>x</i> a <code>Box</code> object?                                                                                                                                                                                                    |            |
| <b>ly:bp</b> <i>num</i>                                                                                                                                                                                                                   | [Function] |
| <i>num</i> bigpoints (1/72th inch).                                                                                                                                                                                                       |            |
| <b>ly:bracket</b> <i>a iv t p</i>                                                                                                                                                                                                         | [Function] |
| Make a bracket in direction <i>a</i> . The extent of the bracket is given by <i>iv</i> . The wings protrude by an amount of <i>p</i> , which may be negative. The thickness is given by <i>t</i> .                                        |            |
| <b>ly:broadcast</b> <i>disp ev</i>                                                                                                                                                                                                        | [Function] |
| Send the stream event <i>ev</i> to the dispatcher <i>disp</i> .                                                                                                                                                                           |            |
| <b>ly:camel-case-&gt;lisp-identifier</b> <i>name-sym</i>                                                                                                                                                                                  | [Function] |
| Convert <code>FooBar_Bla</code> to <code>foo-bar-bla</code> style symbol.                                                                                                                                                                 |            |

|                                                                                                                                                                                                                                                                                     |            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>ly:chain-assoc-get</b> <i>key achain default-value strict-checking</i>                                                                                                                                                                                                           | [Function] |
| Return value for <i>key</i> from a list of alists <i>achain</i> . If no entry is found, return <i>default-value</i> or <b>#f</b> if <i>default-value</i> is not specified. With <i>strict-checking</i> set to <b>#t</b> , a <code>programming-error</code> is output in such cases. |            |
| <b>ly:check-expected-warnings</b>                                                                                                                                                                                                                                                   | [Function] |
| Check whether all expected warnings have really been triggered.                                                                                                                                                                                                                     |            |
| <b>ly:cm</b> <i>num</i>                                                                                                                                                                                                                                                             | [Function] |
| <i>num</i> cm.                                                                                                                                                                                                                                                                      |            |
| <b>ly:command-line-code</b>                                                                                                                                                                                                                                                         | [Function] |
| The Scheme code specified on command-line with ‘-e’.                                                                                                                                                                                                                                |            |
| <b>ly:command-line-options</b>                                                                                                                                                                                                                                                      | [Function] |
| The Scheme options specified on command-line with ‘-d’.                                                                                                                                                                                                                             |            |
| <b>ly:connect-dispatchers</b> <i>to from</i>                                                                                                                                                                                                                                        | [Function] |
| Make the dispatcher <i>to</i> listen to events from <i>from</i> .                                                                                                                                                                                                                   |            |
| <b>ly:context?</b> <i>x</i>                                                                                                                                                                                                                                                         | [Function] |
| Is <i>x</i> a <code>Context</code> object?                                                                                                                                                                                                                                          |            |
| <b>ly:context-current-moment</b> <i>context</i>                                                                                                                                                                                                                                     | [Function] |
| Return the current moment of <i>context</i> .                                                                                                                                                                                                                                       |            |
| <b>ly:context-event-source</b> <i>context</i>                                                                                                                                                                                                                                       | [Function] |
| Return <code>event-source</code> of context <i>context</i> .                                                                                                                                                                                                                        |            |
| <b>ly:context-events-below</b> <i>context</i>                                                                                                                                                                                                                                       | [Function] |
| Return a <code>stream-distributor</code> that distributes all events from <i>context</i> and all its subcontexts.                                                                                                                                                                   |            |
| <b>ly:context-find</b> <i>context name</i>                                                                                                                                                                                                                                          | [Function] |
| Find a parent of <i>context</i> that has name or alias <i>name</i> . Return <b>#f</b> if not found.                                                                                                                                                                                 |            |
| <b>ly:context-grob-definition</b> <i>context name</i>                                                                                                                                                                                                                               | [Function] |
| Return the definition of <i>name</i> (a symbol) within <i>context</i> as an alist.                                                                                                                                                                                                  |            |
| <b>ly:context-id</b> <i>context</i>                                                                                                                                                                                                                                                 | [Function] |
| Return the ID string of <i>context</i> , i.e., for <code>\context Voice = "one" ...</code> return the string <code>one</code> .                                                                                                                                                     |            |
| <b>ly:context-mod?</b> <i>x</i>                                                                                                                                                                                                                                                     | [Function] |
| Is <i>x</i> a <code>Context_mod</code> object?                                                                                                                                                                                                                                      |            |
| <b>ly:context-name</b> <i>context</i>                                                                                                                                                                                                                                               | [Function] |
| Return the name of <i>context</i> , i.e., for <code>\context Voice = "one" ...</code> return the symbol <code>Voice</code> .                                                                                                                                                        |            |
| <b>ly:context-now</b> <i>context</i>                                                                                                                                                                                                                                                | [Function] |
| Return <code>now-moment</code> of context <i>context</i> .                                                                                                                                                                                                                          |            |
| <b>ly:context-parent</b> <i>context</i>                                                                                                                                                                                                                                             | [Function] |
| Return the parent of <i>context</i> , <b>#f</b> if none.                                                                                                                                                                                                                            |            |
| <b>ly:context-property</b> <i>context sym def</i>                                                                                                                                                                                                                                   | [Function] |
| Return the value for property <i>sym</i> in <i>context</i> . If <i>def</i> is given, and property value is ‘()’, return <i>def</i> .                                                                                                                                                |            |

|                                                                                                                                                                                                                    |            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>ly:context-property-where-defined</b> <i>context name</i>                                                                                                                                                       | [Function] |
| Return the context above <i>context</i> where <i>name</i> is defined.                                                                                                                                              |            |
| <b>ly:context-pushpop-property</b> <i>context grob eltpop val</i>                                                                                                                                                  | [Function] |
| Do a single <code>\override</code> or <code>\revert</code> operation in <i>context</i> . The grob definition <i>grob</i> is extended with <i>eltpop</i> (if <i>val</i> is specified) or reverted (if unspecified). |            |
| <b>ly:context-set-property!</b> <i>context name val</i>                                                                                                                                                            | [Function] |
| Set value of property <i>name</i> in context <i>context</i> to <i>val</i> .                                                                                                                                        |            |
| <b>ly:context-unset-property</b> <i>context name</i>                                                                                                                                                               | [Function] |
| Unset value of property <i>name</i> in context <i>context</i> .                                                                                                                                                    |            |
| <b>ly:debug</b> <i>str rest</i>                                                                                                                                                                                    | [Function] |
| A Scheme callable function to issue a debug message <i>str</i> . The message is formatted with <i>format</i> and <i>rest</i> .                                                                                     |            |
| <b>ly:default-scale</b>                                                                                                                                                                                            | [Function] |
| Get the global default scale.                                                                                                                                                                                      |            |
| <b>ly:dimension?</b> <i>d</i>                                                                                                                                                                                      | [Function] |
| Return <i>d</i> as a number. Used to distinguish length variables from normal numbers.                                                                                                                             |            |
| <b>ly:dir?</b> <i>s</i>                                                                                                                                                                                            | [Function] |
| Is <i>s</i> a direction? Valid directions are -1, 0, or 1, where -1 represents left or down, 1 represents right or up, and 0 represents a neutral direction.                                                       |            |
| <b>ly:dispatcher?</b> <i>x</i>                                                                                                                                                                                     | [Function] |
| Is <i>x</i> a <code>Dispatcher</code> object?                                                                                                                                                                      |            |
| <b>ly:duration?</b> <i>x</i>                                                                                                                                                                                       | [Function] |
| Is <i>x</i> a <code>Duration</code> object?                                                                                                                                                                        |            |
| <b>ly:duration&lt;?</b> <i>p1 p2</i>                                                                                                                                                                               | [Function] |
| Is <i>p1</i> shorter than <i>p2</i> ?                                                                                                                                                                              |            |
| <b>ly:duration-&gt;string</b> <i>dur</i>                                                                                                                                                                           | [Function] |
| Convert <i>dur</i> to a string.                                                                                                                                                                                    |            |
| <b>ly:duration-dot-count</b> <i>dur</i>                                                                                                                                                                            | [Function] |
| Extract the dot count from <i>dur</i> .                                                                                                                                                                            |            |
| <b>ly:duration-factor</b> <i>dur</i>                                                                                                                                                                               | [Function] |
| Extract the compression factor from <i>dur</i> . Return it as a pair.                                                                                                                                              |            |
| <b>ly:duration-length</b> <i>dur</i>                                                                                                                                                                               | [Function] |
| The length of the duration as a <code>moment</code> .                                                                                                                                                              |            |
| <b>ly:duration-log</b> <i>dur</i>                                                                                                                                                                                  | [Function] |
| Extract the duration log from <i>dur</i> .                                                                                                                                                                         |            |
| <b>ly:effective-prefix</b>                                                                                                                                                                                         | [Function] |
| Return effective prefix.                                                                                                                                                                                           |            |
| <b>ly:encode-string-for-pdf</b> <i>str</i>                                                                                                                                                                         | [Function] |
| Encode the given string to either Latin1 (which is a subset of the <code>PDFDocEncoding</code> ) or if that's not possible to full UTF-16BE with Byte-Order-Mark (BOM).                                            |            |

- ly:engraver-announce-end-grob** *engraver grob cause* [Function]  
 Announce the end of a grob (i.e., the end of a spanner) originating from given *engraver* instance, with *grob* being a grob. *cause* should either be another grob or a music event.
- ly:engraver-make-grob** *engraver grob-name cause* [Function]  
 Create a grob originating from given *engraver* instance, with given *grob-name*, a symbol. *cause* should either be another grob or a music event.
- ly:error** *str rest* [Function]  
 A Scheme callable function to issue the error *str*. The error is formatted with **format** and *rest*.
- ly:eval-simple-closure** *delayed closure scm-start scm-end* [Function]  
 Evaluate a simple *closure* with the given *delayed* argument. If *scm-start* and *scm-end* are defined, evaluate it purely with those start and end points.
- ly:event?** *obj* [Function]  
 Is *obj* a proper (non-rhythmic) event object?
- ly:event-deep-copy** *m* [Function]  
 Copy *m* and all sub expressions of *m*.
- ly:event-property** *sev sym* [Function]  
 Get the property *sym* of stream event *mus*. If *sym* is undefined, return '().
- ly:event-set-property!** *ev sym val* [Function]  
 Set property *sym* in event *ev* to *val*.
- ly:expand-environment** *str* [Function]  
 Expand **\$VAR** and **\${VAR}** in *str*.
- ly:expect-warning** *str rest* [Function]  
 A Scheme callable function to register a warning to be expected and subsequently suppressed. If the warning is not encountered, a warning about the missing warning will be shown. The message should be translated with (**\_ ...**) and changing parameters given after the format string.
- ly:find-file** *name* [Function]  
 Return the absolute file name of *name*, or **#f** if not found.
- ly:font-config-add-directory** *dir* [Function]  
 Add directory *dir* to FontConfig.
- ly:font-config-add-font** *font* [Function]  
 Add font *font* to FontConfig.
- ly:font-config-display-fonts** [Function]  
 Dump a list of all fonts visible to FontConfig.
- ly:font-config-get-font-file** *name* [Function]  
 Get the file for font *name*.
- ly:font-design-size** *font* [Function]  
 Given the font metric *font*, return the design size, relative to the current output-scale.
- ly:font-file-name** *font* [Function]  
 Given the font metric *font*, return the corresponding file name.

- ly:font-get-glyph** *font name* [Function]  
 Return a stencil from *font* for the glyph named *name*. If the glyph is not available, return an empty stencil.  
 Note that this command can only be used to access glyphs from fonts loaded with **ly:system-font-load**; currently, this means either the Emmentaler or Emmentaler-Brace fonts, corresponding to the font encodings **fetaMusic** and **fetaBraces**, respectively.
- ly:font-glyph-name-to-charcode** *font name* [Function]  
 Return the character code for glyph *name* in *font*.  
 Note that this command can only be used to access glyphs from fonts loaded with **ly:system-font-load**; currently, this means either the Emmentaler or Emmentaler-Brace fonts, corresponding to the font encodings **fetaMusic** and **fetaBraces**, respectively.
- ly:font-glyph-name-to-index** *font name* [Function]  
 Return the index for *name* in *font*.  
 Note that this command can only be used to access glyphs from fonts loaded with **ly:system-font-load**; currently, this means either the Emmentaler or Emmentaler-Brace fonts, corresponding to the font encodings **fetaMusic** and **fetaBraces**, respectively.
- ly:font-index-to-charcode** *font index* [Function]  
 Return the character code for *index* in *font*.  
 Note that this command can only be used to access glyphs from fonts loaded with **ly:system-font-load**; currently, this means either the Emmentaler or Emmentaler-Brace fonts, corresponding to the font encodings **fetaMusic** and **fetaBraces**, respectively.
- ly:font-magnification** *font* [Function]  
 Given the font metric *font*, return the magnification, relative to the current output-scale.
- ly:font-metric?** *x* [Function]  
 Is *x* a **Font\_metric** object?
- ly:font-name** *font* [Function]  
 Given the font metric *font*, return the corresponding name.
- ly:font-sub-fonts** *font* [Function]  
 Given the font metric *font* of an OpenType font, return the names of the subfonts within *font*.
- ly:format** *str rest* [Function]  
 LilyPond specific format, supporting **~a** and **~[0-9]f**. Basic support for **~s** is also provided.
- ly:format-output** *context* [Function]  
 Given a global context in its final state, process it and return the **Music\_output** object in its final state.
- ly:get-all-function-documentation** [Function]  
 Get a hash table with all LilyPond Scheme extension functions.
- ly:get-all-translators** [Function]  
 Return a list of all translator objects that may be instantiated.
- ly:get-context-mods** *contextmod* [Function]  
 Returns the list of context modifications stored in *contextmod*.
- ly:get-listened-event-classes** [Function]  
 Return a list of all event classes that some translator listens to.



|                                                                                                                                                                                                        |            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>ly:get-option</code> <i>var</i>                                                                                                                                                                  | [Function] |
| Get a global option setting.                                                                                                                                                                           |            |
| <code>ly:get-spacing-spec</code> <i>from-scm to-scm</i>                                                                                                                                                | [Function] |
| Return the spacing spec going between the two given grobs, <i>from-scm</i> and <i>to-scm</i> .                                                                                                         |            |
| <code>ly:gettext</code> <i>original</i>                                                                                                                                                                | [Function] |
| A Scheme wrapper function for <code>gettext</code> .                                                                                                                                                   |            |
| <code>ly:grob?</code> <i>x</i>                                                                                                                                                                         | [Function] |
| Is <i>x</i> a Grob object?                                                                                                                                                                             |            |
| <code>ly:grob-alist-chain</code> <i>grob global</i>                                                                                                                                                    | [Function] |
| Get an alist chain for grob <i>grob</i> , with <i>global</i> as the global default. If unspecified, <code>font-defaults</code> from the layout block is taken.                                         |            |
| <code>ly:grob-array?</code> <i>x</i>                                                                                                                                                                   | [Function] |
| Is <i>x</i> a <code>Grob_array</code> object?                                                                                                                                                          |            |
| <code>ly:grob-array-&gt;list</code> <i>grob-arr</i>                                                                                                                                                    | [Function] |
| Return the elements of <i>grob-arr</i> as a Scheme list.                                                                                                                                               |            |
| <code>ly:grob-array-length</code> <i>grob-arr</i>                                                                                                                                                      | [Function] |
| Return the length of <i>grob-arr</i> .                                                                                                                                                                 |            |
| <code>ly:grob-array-ref</code> <i>grob-arr index</i>                                                                                                                                                   | [Function] |
| Retrieve the <i>index</i> th element of <i>grob-arr</i> .                                                                                                                                              |            |
| <code>ly:grob-basic-properties</code> <i>grob</i>                                                                                                                                                      | [Function] |
| Get the immutable properties of <i>grob</i> .                                                                                                                                                          |            |
| <code>ly:grob-chain-callback</code> <i>grob proc sym</i>                                                                                                                                               | [Function] |
| Find the callback that is stored as property <i>sym</i> of grob <i>grob</i> and chain <i>proc</i> to the head of this, meaning that it is called using <i>grob</i> and the previous callback's result. |            |
| <code>ly:grob-common-refpoint</code> <i>grob other axis</i>                                                                                                                                            | [Function] |
| Find the common refpoint of <i>grob</i> and <i>other</i> for <i>axis</i> .                                                                                                                             |            |
| <code>ly:grob-common-refpoint-of-array</code> <i>grob others axis</i>                                                                                                                                  | [Function] |
| Find the common refpoint of <i>grob</i> and <i>others</i> (a grob-array) for <i>axis</i> .                                                                                                             |            |
| <code>ly:grob-default-font</code> <i>grob</i>                                                                                                                                                          | [Function] |
| Return the default font for grob <i>grob</i> .                                                                                                                                                         |            |
| <code>ly:grob-extent</code> <i>grob refp axis</i>                                                                                                                                                      | [Function] |
| Get the extent in <i>axis</i> direction of <i>grob</i> relative to the grob <i>refp</i> .                                                                                                              |            |
| <code>ly:grob-interfaces</code> <i>grob</i>                                                                                                                                                            | [Function] |
| Return the interfaces list of grob <i>grob</i> .                                                                                                                                                       |            |
| <code>ly:grob-layout</code> <i>grob</i>                                                                                                                                                                | [Function] |
| Get <code>\layout</code> definition from grob <i>grob</i> .                                                                                                                                            |            |
| <code>ly:grob-object</code> <i>grob sym</i>                                                                                                                                                            | [Function] |
| Return the value of a pointer in grob <i>grob</i> of property <i>sym</i> . It returns '() (end-of-list) if <i>sym</i> is undefined in <i>grob</i> .                                                    |            |

|                                                                                                                                                    |            |
|----------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>ly:grob-original</b> <i>grob</i>                                                                                                                | [Function] |
| Return the unbroken original grob of <i>grob</i> .                                                                                                 |            |
| <b>ly:grob-parent</b> <i>grob axis</i>                                                                                                             | [Function] |
| Get the parent of <i>grob</i> . <i>axis</i> is 0 for the X-axis, 1 for the Y-axis.                                                                 |            |
| <b>ly:grob-pq&lt;?</b> <i>a b</i>                                                                                                                  | [Function] |
| Compare two grob priority queue entries. This is an internal function.                                                                             |            |
| <b>ly:grob-properties</b> <i>grob</i>                                                                                                              | [Function] |
| Get the mutable properties of <i>grob</i> .                                                                                                        |            |
| <b>ly:grob-property</b> <i>grob sym val</i>                                                                                                        | [Function] |
| Return the value for property <i>sym</i> of <i>grob</i> . If no value is found, return <i>val</i> or '()' if <i>val</i> is not specified.          |            |
| <b>ly:grob-property-data</b> <i>grob sym</i>                                                                                                       | [Function] |
| Return the value for property <i>sym</i> of <i>grob</i> , but do not process callbacks.                                                            |            |
| <b>ly:grob-pure-height</b> <i>grob refp beg end val</i>                                                                                            | [Function] |
| Return the pure height of <i>grob</i> given refpoint <i>refp</i> . If no value is found, return <i>val</i> or '()' if <i>val</i> is not specified. |            |
| <b>ly:grob-pure-property</b> <i>grob sym beg end val</i>                                                                                           | [Function] |
| Return the pure value for property <i>sym</i> of <i>grob</i> . If no value is found, return <i>val</i> or '()' if <i>val</i> is not specified.     |            |
| <b>ly:grob-relative-coordinate</b> <i>grob refp axis</i>                                                                                           | [Function] |
| Get the coordinate in <i>axis</i> direction of <i>grob</i> relative to the grob <i>refp</i> .                                                      |            |
| <b>ly:grob-robust-relative-extent</b> <i>grob refp axis</i>                                                                                        | [Function] |
| Get the extent in <i>axis</i> direction of <i>grob</i> relative to the grob <i>refp</i> , or (0,0) if empty.                                       |            |
| <b>ly:grob-script-priority-less</b> <i>a b</i>                                                                                                     | [Function] |
| Compare two grobs by script priority. For internal use.                                                                                            |            |
| <b>ly:grob-set-nested-property!</b> <i>grob symlist val</i>                                                                                        | [Function] |
| Set nested property <i>symlist</i> in grob <i>grob</i> to value <i>val</i> .                                                                       |            |
| <b>ly:grob-set-object!</b> <i>grob sym val</i>                                                                                                     | [Function] |
| Set <i>sym</i> in grob <i>grob</i> to value <i>val</i> .                                                                                           |            |
| <b>ly:grob-set-parent!</b> <i>grob axis parent-grob</i>                                                                                            | [Function] |
| Set <i>parent-grob</i> the parent of grob <i>grob</i> in axis <i>axis</i> .                                                                        |            |
| <b>ly:grob-set-property!</b> <i>grob sym val</i>                                                                                                   | [Function] |
| Set <i>sym</i> in grob <i>grob</i> to value <i>val</i> .                                                                                           |            |
| <b>ly:grob-staff-position</b> <i>sg</i>                                                                                                            | [Function] |
| Return the Y-position of <i>sg</i> relative to the staff.                                                                                          |            |
| <b>ly:grob-suicide!</b> <i>grob</i>                                                                                                                | [Function] |
| Kill <i>grob</i> .                                                                                                                                 |            |
| <b>ly:grob-system</b> <i>grob</i>                                                                                                                  | [Function] |
| Return the system grob of <i>grob</i> .                                                                                                            |            |

|                                                                                                                                                                                                 |            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>ly:grob-translate-axis!</b> <i>grob d a</i>                                                                                                                                                  | [Function] |
| Translate <i>grob</i> on axis <i>a</i> over distance <i>d</i> .                                                                                                                                 |            |
| <b>ly:gulp-file</b> <i>name size</i>                                                                                                                                                            | [Function] |
| Read <i>size</i> characters from the file <i>name</i> , and return its contents in a string. If <i>size</i> is undefined, the entire file is read. The file is looked up using the search path. |            |
| <b>ly:hash-table-keys</b> <i>tab</i>                                                                                                                                                            | [Function] |
| Return a list of keys in <i>tab</i> .                                                                                                                                                           |            |
| <b>ly:inch</b> <i>num</i>                                                                                                                                                                       | [Function] |
| <i>num</i> inches.                                                                                                                                                                              |            |
| <b>ly:input-both-locations</b> <i>sip</i>                                                                                                                                                       | [Function] |
| Return input location in <i>sip</i> as (file-name first-line first-column last-line last-column).                                                                                               |            |
| <b>ly:input-file-line-char-column</b> <i>sip</i>                                                                                                                                                | [Function] |
| Return input location in <i>sip</i> as (file-name line char column).                                                                                                                            |            |
| <b>ly:input-location?</b> <i>x</i>                                                                                                                                                              | [Function] |
| Is <i>x</i> an input-location?                                                                                                                                                                  |            |
| <b>ly:input-message</b> <i>sip msg rest</i>                                                                                                                                                     | [Function] |
| Print <i>msg</i> as a GNU compliant error message, pointing to the location in <i>sip</i> . <i>msg</i> is interpreted similar to <b>format</b> 's argument, using <i>rest</i> .                 |            |
| <b>ly:input-warning</b> <i>sip msg rest</i>                                                                                                                                                     | [Function] |
| Print <i>msg</i> as a GNU compliant warning message, pointing to the location in <i>sip</i> . <i>msg</i> is interpreted similar to <b>format</b> 's argument, using <i>rest</i> .               |            |
| <b>ly:interpret-music-expression</b> <i>mus ctx</i>                                                                                                                                             | [Function] |
| Interpret the music expression <i>mus</i> in the global context <i>ctx</i> . The context is returned in its final state.                                                                        |            |
| <b>ly:interpret-stencil-expression</b> <i>expr func arg1 offset</i>                                                                                                                             | [Function] |
| Parse <i>expr</i> , feed bits to <i>func</i> with first arg <i>arg1</i> having offset <i>offset</i> .                                                                                           |            |
| <b>ly:intlog2</b> <i>d</i>                                                                                                                                                                      | [Function] |
| The 2-logarithm of 1/ <i>d</i> .                                                                                                                                                                |            |
| <b>ly:is-listened-event-class</b> <i>sym</i>                                                                                                                                                    | [Function] |
| Is <i>sym</i> a listened event class?                                                                                                                                                           |            |
| <b>ly:item?</b> <i>g</i>                                                                                                                                                                        | [Function] |
| Is <i>g</i> an Item object?                                                                                                                                                                     |            |
| <b>ly:item-break-dir</b> <i>it</i>                                                                                                                                                              | [Function] |
| The break status direction of item <i>it</i> . -1 means end of line, 0 unbroken, and 1 beginning of line.                                                                                       |            |
| <b>ly:iterator?</b> <i>x</i>                                                                                                                                                                    | [Function] |
| Is <i>x</i> a Music_iterator object?                                                                                                                                                            |            |
| <b>ly:lexer-keywords</b> <i>lexer</i>                                                                                                                                                           | [Function] |
| Return a list of (KEY . CODE) pairs, signifying the LilyPond reserved words list.                                                                                                               |            |

|                                                                                                                                                                                                                                                                                                                           |            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>ly:lily-lexer?</code> <i>x</i>                                                                                                                                                                                                                                                                                      | [Function] |
| Is <i>x</i> a <code>Lily_lexer</code> object?                                                                                                                                                                                                                                                                             |            |
| <code>ly:lily-parser?</code> <i>x</i>                                                                                                                                                                                                                                                                                     | [Function] |
| Is <i>x</i> a <code>Lily_parser</code> object?                                                                                                                                                                                                                                                                            |            |
| <code>ly:listener?</code> <i>x</i>                                                                                                                                                                                                                                                                                        | [Function] |
| Is <i>x</i> a <code>Listener</code> object?                                                                                                                                                                                                                                                                               |            |
| <code>ly:make-book</code> <i>paper header scores</i>                                                                                                                                                                                                                                                                      | [Function] |
| Make a <code>\book</code> of <i>paper</i> and <i>header</i> (which may be <code>#f</code> as well) containing <code>\scores</code> .                                                                                                                                                                                      |            |
| <code>ly:make-book-part</code> <i>scores</i>                                                                                                                                                                                                                                                                              | [Function] |
| Make a <code>\bookpart</code> containing <code>\scores</code> .                                                                                                                                                                                                                                                           |            |
| <code>ly:make-context-mod</code> <i>mod-list</i>                                                                                                                                                                                                                                                                          | [Function] |
| Creates a context modification, optionally initialized via the list of modifications <i>mod-list</i> .                                                                                                                                                                                                                    |            |
| <code>ly:make-dispatcher</code>                                                                                                                                                                                                                                                                                           | [Function] |
| Return a newly created dispatcher.                                                                                                                                                                                                                                                                                        |            |
| <code>ly:make-duration</code> <i>length dotcount num den</i>                                                                                                                                                                                                                                                              | [Function] |
| <i>length</i> is the negative logarithm (base 2) of the duration: 1 is a half note, 2 is a quarter note, 3 is an eighth note, etc. The number of dots after the note is given by the optional argument <i>dotcount</i> .                                                                                                  |            |
| The duration factor is optionally given by <i>num</i> and <i>den</i> .                                                                                                                                                                                                                                                    |            |
| A duration is a musical duration, i.e., a length of time described by a power of two (whole, half, quarter, etc.) and a number of augmentation dots.                                                                                                                                                                      |            |
| <code>ly:make-global-context</code> <i>output-def</i>                                                                                                                                                                                                                                                                     | [Function] |
| Set up a global interpretation context, using the output block <i>output-def</i> . The context is returned.                                                                                                                                                                                                               |            |
| <code>ly:make-global-translator</code> <i>global</i>                                                                                                                                                                                                                                                                      | [Function] |
| Create a translator group and connect it to the global context <i>global</i> . The translator group is returned.                                                                                                                                                                                                          |            |
| <code>ly:make-listener</code> <i>callback</i>                                                                                                                                                                                                                                                                             | [Function] |
| Create a listener. Any time the listener hears an object, it will call <i>callback</i> with that object. <i>callback</i> should take exactly one argument.                                                                                                                                                                |            |
| <code>ly:make-moment</code> <i>n d gn gd</i>                                                                                                                                                                                                                                                                              | [Function] |
| Create the rational number with main timing <i>n/d</i> , and optional grace timing <i>gn/gd</i> .                                                                                                                                                                                                                         |            |
| A <i>moment</i> is a point in musical time. It consists of a pair of rationals ( <i>m</i> , <i>g</i> ), where <i>m</i> is the timing for the main notes, and <i>g</i> the timing for grace notes. In absence of grace notes, <i>g</i> is zero.                                                                            |            |
| <code>ly:make-music</code> <i>props</i>                                                                                                                                                                                                                                                                                   | [Function] |
| Make a C++ <code>Music</code> object and initialize it with <i>props</i> .                                                                                                                                                                                                                                                |            |
| This function is for internal use and is only called by <code>make-music</code> , which is the preferred interface for creating music objects.                                                                                                                                                                            |            |
| <code>ly:make-music-function</code> <i>signature func</i>                                                                                                                                                                                                                                                                 | [Function] |
| Make a function to process music, to be used for the parser. <i>func</i> is the function, and <i>signature</i> describes its arguments. <i>signature</i> 's <code>cdr</code> is a list containing either <code>ly:music?</code> predicates or other type predicates. Its <code>car</code> is the syntax function to call. |            |

|                                                                                                                                                                                                                                                                                                 |            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>ly:make-music-relative!</b> <i>music pitch</i>                                                                                                                                                                                                                                               | [Function] |
| Make <i>music</i> relative to <i>pitch</i> , return final pitch.                                                                                                                                                                                                                                |            |
| <b>ly:make-output-def</b>                                                                                                                                                                                                                                                                       | [Function] |
| Make an output definition.                                                                                                                                                                                                                                                                      |            |
| <b>ly:make-page-label-marker</b> <i>label</i>                                                                                                                                                                                                                                                   | [Function] |
| Return page marker with label <i>label</i> .                                                                                                                                                                                                                                                    |            |
| <b>ly:make-page-permission-marker</b> <i>symbol permission</i>                                                                                                                                                                                                                                  | [Function] |
| Return page marker with page breaking and turning permissions.                                                                                                                                                                                                                                  |            |
| <b>ly:make-pango-description-string</b> <i>chain size</i>                                                                                                                                                                                                                                       | [Function] |
| Make a PangoFontDescription string for the property alist <i>chain</i> at size <i>size</i> .                                                                                                                                                                                                    |            |
| <b>ly:make-paper-outputter</b> <i>port format</i>                                                                                                                                                                                                                                               | [Function] |
| Create an outputter that evaluates within <i>output-format</i> , writing to <i>port</i> .                                                                                                                                                                                                       |            |
| <b>ly:make-pitch</b> <i>octave note alter</i>                                                                                                                                                                                                                                                   | [Function] |
| <i>octave</i> is specified by an integer, zero for the octave containing middle C. <i>note</i> is a number indexing the global default scale, with 0 corresponding to pitch C and 6 usually corresponding to pitch B. <i>alter</i> is a rational number of 200-cent whole tones for alteration. |            |
| <b>ly:make-prob</b> <i>type init rest</i>                                                                                                                                                                                                                                                       | [Function] |
| Create a Prob object.                                                                                                                                                                                                                                                                           |            |
| <b>ly:make-scale</b> <i>steps</i>                                                                                                                                                                                                                                                               | [Function] |
| Create a scale. The argument is a vector of rational numbers, each of which represents the number of 200 cent tones of a pitch above the tonic.                                                                                                                                                 |            |
| <b>ly:make-score</b> <i>music</i>                                                                                                                                                                                                                                                               | [Function] |
| Return score with <i>music</i> encapsulated in it.                                                                                                                                                                                                                                              |            |
| <b>ly:make-simple-closure</b> <i>expr</i>                                                                                                                                                                                                                                                       | [Function] |
| Make a simple closure. <i>expr</i> should be form of <i>(func a1 a2 ...)</i> , and will be invoked as <i>(func delayed-arg a1 a2 ...)</i> .                                                                                                                                                     |            |
| <b>ly:make-spring</b> <i>ideal min-dist</i>                                                                                                                                                                                                                                                     | [Function] |
| Make a spring. <i>ideal</i> is the ideal distance of the spring, and <i>min-dist</i> is the minimum distance.                                                                                                                                                                                   |            |
| <b>ly:make-stencil</b> <i>expr xext yext</i>                                                                                                                                                                                                                                                    | [Function] |
| Stencils are device independent output expressions. They carry two pieces of information:                                                                                                                                                                                                       |            |
| 1. A specification of how to print this object. This specification is processed by the output backends, for example ‘ <i>scm/output-ps.scm</i> ’.                                                                                                                                               |            |
| 2. The vertical and horizontal extents of the object, given as pairs. If an extent is unspecified (or if you use (1000 . -1000) as its value), it is taken to be empty.                                                                                                                         |            |
| <b>ly:make-stream-event</b> <i>cl proplist</i>                                                                                                                                                                                                                                                  | [Function] |
| Create a stream event of class <i>cl</i> with the given mutable property list.                                                                                                                                                                                                                  |            |
| <b>ly:make-unpure-pure-container</b> <i>unpure pure</i>                                                                                                                                                                                                                                         | [Function] |
| Make an unpure-pure container. <i>unpure</i> should be an unpure expression, and <i>pure</i> should be a pure expression. If <i>pure</i> is omitted, the value of <i>unpure</i> will be used twice.                                                                                             |            |
| <b>ly:message</b> <i>str rest</i>                                                                                                                                                                                                                                                               | [Function] |
| A Scheme callable function to issue the message <i>str</i> . The message is formatted with <b>format</b> and <i>rest</i> .                                                                                                                                                                      |            |

|                                                                                                                                                                        |            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>ly:minimal-breaking</code> <i>pb</i>                                                                                                                             | [Function] |
| Break (pages and lines) the <code>Paper_book</code> object <i>pb</i> without looking for optimal spacing: stack as many lines on a page before moving to the next one. |            |
| <code>ly:mm</code> <i>num</i>                                                                                                                                          | [Function] |
| <i>num</i> mm.                                                                                                                                                         |            |
| <code>ly:module-&gt;alist</code> <i>mod</i>                                                                                                                            | [Function] |
| Dump the contents of module <i>mod</i> as an alist.                                                                                                                    |            |
| <code>ly:module-copy</code> <i>dest src</i>                                                                                                                            | [Function] |
| Copy all bindings from module <i>src</i> into <i>dest</i> .                                                                                                            |            |
| <code>ly:modules-lookup</code> <i>modules sym def</i>                                                                                                                  | [Function] |
| Look up <i>sym</i> in the list <i>modules</i> , returning the first occurrence. If not found, return <i>def</i> or <code>#f</code> if <i>def</i> isn't specified.      |            |
| <code>ly:moment?</code> <i>x</i>                                                                                                                                       | [Function] |
| Is <i>x</i> a <code>Moment</code> object?                                                                                                                              |            |
| <code>ly:moment&lt;?</code> <i>a b</i>                                                                                                                                 | [Function] |
| Compare two moments.                                                                                                                                                   |            |
| <code>ly:moment-add</code> <i>a b</i>                                                                                                                                  | [Function] |
| Add two moments.                                                                                                                                                       |            |
| <code>ly:moment-div</code> <i>a b</i>                                                                                                                                  | [Function] |
| Divide two moments.                                                                                                                                                    |            |
| <code>ly:moment-grace-denominator</code> <i>mom</i>                                                                                                                    | [Function] |
| Extract denominator from grace timing.                                                                                                                                 |            |
| <code>ly:moment-grace-numerator</code> <i>mom</i>                                                                                                                      | [Function] |
| Extract numerator from grace timing.                                                                                                                                   |            |
| <code>ly:moment-main-denominator</code> <i>mom</i>                                                                                                                     | [Function] |
| Extract denominator from main timing.                                                                                                                                  |            |
| <code>ly:moment-main-numerator</code> <i>mom</i>                                                                                                                       | [Function] |
| Extract numerator from main timing.                                                                                                                                    |            |
| <code>ly:moment-mod</code> <i>a b</i>                                                                                                                                  | [Function] |
| Modulo of two moments.                                                                                                                                                 |            |
| <code>ly:moment-mul</code> <i>a b</i>                                                                                                                                  | [Function] |
| Multiply two moments.                                                                                                                                                  |            |
| <code>ly:moment-sub</code> <i>a b</i>                                                                                                                                  | [Function] |
| Subtract two moments.                                                                                                                                                  |            |
| <code>ly:music?</code> <i>obj</i>                                                                                                                                      | [Function] |
| Is <i>obj</i> a music object?                                                                                                                                          |            |
| <code>ly:music-compress</code> <i>m factor</i>                                                                                                                         | [Function] |
| Compress music object <i>m</i> by moment <i>factor</i> .                                                                                                               |            |
| <code>ly:music-deep-copy</code> <i>m</i>                                                                                                                               | [Function] |
| Copy <i>m</i> and all sub expressions of <i>m</i> .                                                                                                                    |            |

|                                                                                                                                                                                          |            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>ly:music-duration-compress</code> <i>mus fact</i>                                                                                                                                  | [Function] |
| Compress <i>mus</i> by factor <i>fact</i> , which is a <b>Moment</b> .                                                                                                                   |            |
| <code>ly:music-duration-length</code> <i>mus</i>                                                                                                                                         | [Function] |
| Extract the duration field from <i>mus</i> and return the length.                                                                                                                        |            |
| <code>ly:music-function?</code> <i>x</i>                                                                                                                                                 | [Function] |
| Is <i>x</i> a <b>music-function</b> ?                                                                                                                                                    |            |
| <code>ly:music-function-extract</code> <i>x</i>                                                                                                                                          | [Function] |
| Return the Scheme function inside <i>x</i> .                                                                                                                                             |            |
| <code>ly:music-length</code> <i>mus</i>                                                                                                                                                  | [Function] |
| Get the length of music expression <i>mus</i> and return it as a <b>Moment</b> object.                                                                                                   |            |
| <code>ly:music-list?</code> <i>lst</i>                                                                                                                                                   | [Function] |
| Is <i>lst</i> a list of music objects?                                                                                                                                                   |            |
| <code>ly:music-mutable-properties</code> <i>mus</i>                                                                                                                                      | [Function] |
| Return an alist containing the mutable properties of <i>mus</i> . The immutable properties are not available, since they are constant and initialized by the <b>make-music</b> function. |            |
| <code>ly:music-output?</code> <i>x</i>                                                                                                                                                   | [Function] |
| Is <i>x</i> a <b>Music_output</b> object?                                                                                                                                                |            |
| <code>ly:music-property</code> <i>mus sym val</i>                                                                                                                                        | [Function] |
| Return the value for property <i>sym</i> of music expression <i>mus</i> . If no value is found, return <i>val</i> or '()' if <i>val</i> is not specified.                                |            |
| <code>ly:music-set-property!</code> <i>mus sym val</i>                                                                                                                                   | [Function] |
| Set property <i>sym</i> in music expression <i>mus</i> to <i>val</i> .                                                                                                                   |            |
| <code>ly:music-transpose</code> <i>m p</i>                                                                                                                                               | [Function] |
| Transpose <i>m</i> such that central C is mapped to <i>p</i> . Return <i>m</i> .                                                                                                         |            |
| <code>ly:note-column-accidentals</code> <i>note-column</i>                                                                                                                               | [Function] |
| Return the <b>AccidentalPlacement</b> grob from <i>note-column</i> if any, or <b>SCM_EOL</b> otherwise.                                                                                  |            |
| <code>ly:note-column-dot-column</code> <i>note-column</i>                                                                                                                                | [Function] |
| Return the <b>DotColumn</b> grob from <i>note-column</i> if any, or <b>SCM_EOL</b> otherwise.                                                                                            |            |
| <code>ly:note-head::stem-attachment</code> <i>font-metric glyph-name</i>                                                                                                                 | [Function] |
| Get attachment in <i>font-metric</i> for attaching a stem to notehead <i>glyph-name</i> .                                                                                                |            |
| <code>ly:number-&gt;string</code> <i>s</i>                                                                                                                                               | [Function] |
| Convert <i>s</i> to a string without generating many decimals.                                                                                                                           |            |
| <code>ly:optimal-breaking</code> <i>pb</i>                                                                                                                                               | [Function] |
| Optimally break (pages and lines) the <b>Paper_book</b> object <i>pb</i> to minimize badness in both vertical and horizontal spacing.                                                    |            |
| <code>ly:option-usage</code> <i>port</i>                                                                                                                                                 | [Function] |
| Print <b>ly:set-option</b> usage. Optional <i>port</i> argument for the destination defaults to current output port.                                                                     |            |
| <code>ly:otf-&gt;cff</code> <i>otf-file-name</i>                                                                                                                                         | [Function] |
| Convert the contents of an OTF file to a CFF file, returning it as a string.                                                                                                             |            |

|                                                                                                                                                                                     |            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>ly:otf-font? font</code>                                                                                                                                                      | [Function] |
| Is <i>font</i> an OpenType font?                                                                                                                                                    |            |
| <code>ly:otf-font-glyph-info font glyph</code>                                                                                                                                      | [Function] |
| Given the font metric <i>font</i> of an OpenType font, return the information about named glyph <i>glyph</i> (a string).                                                            |            |
| <code>ly:otf-font-table-data font tag</code>                                                                                                                                        | [Function] |
| Extract a table <i>tag</i> from <i>font</i> . Return empty string for non-existent <i>tag</i> .                                                                                     |            |
| <code>ly:otf-glyph-count font</code>                                                                                                                                                | [Function] |
| Return the number of glyphs in <i>font</i> .                                                                                                                                        |            |
| <code>ly:otf-glyph-list font</code>                                                                                                                                                 | [Function] |
| Return a list of glyph names for <i>font</i> .                                                                                                                                      |            |
| <code>ly:output-def? def</code>                                                                                                                                                     | [Function] |
| Is <i>def</i> an output definition?                                                                                                                                                 |            |
| <code>ly:output-def-clone def</code>                                                                                                                                                | [Function] |
| Clone output definition <i>def</i> .                                                                                                                                                |            |
| <code>ly:output-def-lookup def sym val</code>                                                                                                                                       | [Function] |
| Return the value of <i>sym</i> in output definition <i>def</i> (e.g., <code>\paper</code> ). If no value is found, return <i>val</i> or <code>()</code> if <i>val</i> is undefined. |            |
| <code>ly:output-def-parent def</code>                                                                                                                                               | [Function] |
| Return the parent output definition of <i>def</i> .                                                                                                                                 |            |
| <code>ly:output-def-scope def</code>                                                                                                                                                | [Function] |
| Return the variable scope inside <i>def</i> .                                                                                                                                       |            |
| <code>ly:output-def-set-variable! def sym val</code>                                                                                                                                | [Function] |
| Set an output definition <i>def</i> variable <i>sym</i> to <i>val</i> .                                                                                                             |            |
| <code>ly:output-description output-def</code>                                                                                                                                       | [Function] |
| Return the description of translators in <i>output-def</i> .                                                                                                                        |            |
| <code>ly:output-formats</code>                                                                                                                                                      | [Function] |
| Formats passed to <code>--format</code> as a list of strings, used for the output.                                                                                                  |            |
| <code>ly:outputter-close outputter</code>                                                                                                                                           | [Function] |
| Close port of <i>outputter</i> .                                                                                                                                                    |            |
| <code>ly:outputter-dump-stencil outputter stencil</code>                                                                                                                            | [Function] |
| Dump stencil <i>expr</i> onto <i>outputter</i> .                                                                                                                                    |            |
| <code>ly:outputter-dump-string outputter str</code>                                                                                                                                 | [Function] |
| Dump <i>str</i> onto <i>outputter</i> .                                                                                                                                             |            |
| <code>ly:outputter-module outputter</code>                                                                                                                                          | [Function] |
| Return output module of <i>outputter</i> .                                                                                                                                          |            |
| <code>ly:outputter-output-scheme outputter expr</code>                                                                                                                              | [Function] |
| Eval <i>expr</i> in module of <i>outputter</i> .                                                                                                                                    |            |
| <code>ly:outputter-port outputter</code>                                                                                                                                            | [Function] |
| Return output port for <i>outputter</i> .                                                                                                                                           |            |



|                                                                                                                                                                                                  |            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>ly:page-marker? x</code>                                                                                                                                                                   | [Function] |
| Is <i>x</i> a <code>Page_marker</code> object?                                                                                                                                                   |            |
| <code>ly:page-turn-breaking pb</code>                                                                                                                                                            | [Function] |
| Optimally break (pages and lines) the <code>Paper_book</code> object <i>pb</i> such that page turns only happen in specified places, returning its pages.                                        |            |
| <code>ly:pango-font? f</code>                                                                                                                                                                    | [Function] |
| Is <i>f</i> a pango font?                                                                                                                                                                        |            |
| <code>ly:pango-font-physical-fonts f</code>                                                                                                                                                      | [Function] |
| Return alist of ( <code>ps-name file-name font-index</code> ) lists for Pango font <i>f</i> .                                                                                                    |            |
| <code>ly:paper-book? x</code>                                                                                                                                                                    | [Function] |
| Is <i>x</i> a <code>Paper_book</code> object?                                                                                                                                                    |            |
| <code>ly:paper-book-header pb</code>                                                                                                                                                             | [Function] |
| Return the header definition ( <code>\header</code> ) in <code>Paper_book</code> object <i>pb</i> .                                                                                              |            |
| <code>ly:paper-book-pages pb</code>                                                                                                                                                              | [Function] |
| Return pages in <code>Paper_book</code> object <i>pb</i> .                                                                                                                                       |            |
| <code>ly:paper-book-paper pb</code>                                                                                                                                                              | [Function] |
| Return the paper output definition ( <code>\paper</code> ) in <code>Paper_book</code> object <i>pb</i> .                                                                                         |            |
| <code>ly:paper-book-performances pb</code>                                                                                                                                                       | [Function] |
| Return performances in <code>Paper_book</code> object <i>pb</i> .                                                                                                                                |            |
| <code>ly:paper-book-scopes pb</code>                                                                                                                                                             | [Function] |
| Return scopes in <code>Paper_book</code> object <i>pb</i> .                                                                                                                                      |            |
| <code>ly:paper-book-systems pb</code>                                                                                                                                                            | [Function] |
| Return systems in <code>Paper_book</code> object <i>pb</i> .                                                                                                                                     |            |
| <code>ly:paper-fonts def</code>                                                                                                                                                                  | [Function] |
| Return a list containing the fonts from output definition <i>def</i> (e.g., <code>\paper</code> ).                                                                                               |            |
| <code>ly:paper-get-font def chain</code>                                                                                                                                                         | [Function] |
| Find a font metric in output definition <i>def</i> satisfying the font-qualifiers in alist chain <i>chain</i> , and return it. (An alist chain is a list of alists, containing grob properties.) |            |
| <code>ly:paper-get-number def sym</code>                                                                                                                                                         | [Function] |
| Return the value of variable <i>sym</i> in output definition <i>def</i> as a double.                                                                                                             |            |
| <code>ly:paper-outputscales def</code>                                                                                                                                                           | [Function] |
| Return the output-scale for output definition <i>def</i> .                                                                                                                                       |            |
| <code>ly:paper-score-paper-systems paper-score</code>                                                                                                                                            | [Function] |
| Return vector of <code>paper_system</code> objects from <i>paper-score</i> .                                                                                                                     |            |
| <code>ly:paper-system? obj</code>                                                                                                                                                                | [Function] |
| Is <i>obj</i> a C++ Prob object of type <code>paper-system</code> ?                                                                                                                              |            |
| <code>ly:paper-system-minimum-distance sys1 sys2</code>                                                                                                                                          | [Function] |
| Measure the minimum distance between these two paper-systems, using their stored skylines if possible and falling back to their extents otherwise.                                               |            |

|                                                                                                                                                                                                           |            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>ly:parse-file</b> <i>name</i>                                                                                                                                                                          | [Function] |
| Parse a single .ly file. Upon failure, throw <b>ly-file-failed</b> key.                                                                                                                                   |            |
| <b>ly:parse-string-expression</b> <i>parser-smob ly-code filename line</i>                                                                                                                                | [Function] |
| Parse the string <i>ly-code</i> with <i>parser-smob</i> . Return the contained music expression. <i>filename</i> and <i>line</i> are optional source indicators.                                          |            |
| <b>ly:parser-clear-error</b> <i>parser</i>                                                                                                                                                                | [Function] |
| Clear the error flag for the parser.                                                                                                                                                                      |            |
| <b>ly:parser-clone</b> <i>parser-smob closures</i>                                                                                                                                                        | [Function] |
| Return a clone of <i>parser-smob</i> . An association list of port positions to closures can be specified in <i>closures</i> in order to have \$ and # interpreted in their original lexical environment. |            |
| <b>ly:parser-define!</b> <i>parser-smob symbol val</i>                                                                                                                                                    | [Function] |
| Bind <i>symbol</i> to <i>val</i> in <i>parser-smob</i> 's module.                                                                                                                                         |            |
| <b>ly:parser-error</b> <i>parser msg input</i>                                                                                                                                                            | [Function] |
| Display an error message and make the parser fail.                                                                                                                                                        |            |
| <b>ly:parser-has-error?</b> <i>parser</i>                                                                                                                                                                 | [Function] |
| Does <i>parser</i> have an error flag?                                                                                                                                                                    |            |
| <b>ly:parser-include-string</b> <i>parser-smob ly-code</i>                                                                                                                                                | [Function] |
| Include the string <i>ly-code</i> into the input stream for <i>parser-smob</i> . Can only be used in immediate Scheme expressions (\$ instead of #).                                                      |            |
| <b>ly:parser-lexer</b> <i>parser-smob</i>                                                                                                                                                                 | [Function] |
| Return the lexer for <i>parser-smob</i> .                                                                                                                                                                 |            |
| <b>ly:parser-lookup</b> <i>parser-smob symbol</i>                                                                                                                                                         | [Function] |
| Look up <i>symbol</i> in <i>parser-smob</i> 's module. Return '() if not defined.                                                                                                                         |            |
| <b>ly:parser-output-name</b> <i>parser</i>                                                                                                                                                                | [Function] |
| Return the base name of the output file.                                                                                                                                                                  |            |
| <b>ly:parser-parse-string</b> <i>parser-smob ly-code</i>                                                                                                                                                  | [Function] |
| Parse the string <i>ly-code</i> with <i>parser-smob</i> . Upon failure, throw <b>ly-file-failed</b> key.                                                                                                  |            |
| <b>ly:parser-set-note-names</b> <i>parser names</i>                                                                                                                                                       | [Function] |
| Replace current note names in <i>parser</i> . <i>names</i> is an alist of symbols. This only has effect if the current mode is notes.                                                                     |            |
| <b>ly:performance-write</b> <i>performance filename</i>                                                                                                                                                   | [Function] |
| Write <i>performance</i> to <i>filename</i> .                                                                                                                                                             |            |
| <b>ly:pfb-&gt;pfa</b> <i>pfb-file-name</i>                                                                                                                                                                | [Function] |
| Convert the contents of a Type 1 font in PFB format to PFA format.                                                                                                                                        |            |
| <b>ly:pitch?</b> <i>x</i>                                                                                                                                                                                 | [Function] |
| Is <i>x</i> a Pitch object?                                                                                                                                                                               |            |
| <b>ly:pitch&lt;?</b> <i>p1 p2</i>                                                                                                                                                                         | [Function] |
| Is <i>p1</i> lexicographically smaller than <i>p2</i> ?                                                                                                                                                   |            |
| <b>ly:pitch-alteration</b> <i>pp</i>                                                                                                                                                                      | [Function] |
| Extract the alteration from pitch <i>pp</i> .                                                                                                                                                             |            |

|                                                                                                                                                       |            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>ly:pitch-diff</b> <i>pitch root</i>                                                                                                                | [Function] |
| Return pitch <i>delta</i> such that <i>pitch</i> transposed by <i>delta</i> equals <i>root</i> .                                                      |            |
| <b>ly:pitch-negate</b> <i>p</i>                                                                                                                       | [Function] |
| Negate <i>p</i> .                                                                                                                                     |            |
| <b>ly:pitch-notename</b> <i>pp</i>                                                                                                                    | [Function] |
| Extract the note name from pitch <i>pp</i> .                                                                                                          |            |
| <b>ly:pitch-octave</b> <i>pp</i>                                                                                                                      | [Function] |
| Extract the octave from pitch <i>pp</i> .                                                                                                             |            |
| <b>ly:pitch-quartertones</b> <i>pp</i>                                                                                                                | [Function] |
| Calculate the number of quarter tones of <i>pp</i> from middle C.                                                                                     |            |
| <b>ly:pitch-semitones</b> <i>pp</i>                                                                                                                   | [Function] |
| Calculate the number of semitones of <i>pp</i> from middle C.                                                                                         |            |
| <b>ly:pitch-steps</b> <i>p</i>                                                                                                                        | [Function] |
| Number of steps counted from middle C of the pitch <i>p</i> .                                                                                         |            |
| <b>ly:pitch-transpose</b> <i>p delta</i>                                                                                                              | [Function] |
| Transpose <i>p</i> by the amount <i>delta</i> , where <i>delta</i> is relative to middle C.                                                           |            |
| <b>ly:pointer-group-interface::add-grob</b> <i>grob sym grob-element</i>                                                                              | [Function] |
| Add <i>grob-element</i> to <i>grob</i> 's <i>sym</i> grob array.                                                                                      |            |
| <b>ly:position-on-line?</b> <i>sg spos</i>                                                                                                            | [Function] |
| Return whether <i>spos</i> is on a line of the staff associated with the grob <i>sg</i> (even on an extender line).                                   |            |
| <b>ly:prob?</b> <i>x</i>                                                                                                                              | [Function] |
| Is <i>x</i> a Prob object?                                                                                                                            |            |
| <b>ly:prob-immutable-properties</b> <i>prob</i>                                                                                                       | [Function] |
| Retrieve an alist of immutable properties.                                                                                                            |            |
| <b>ly:prob-mutable-properties</b> <i>prob</i>                                                                                                         | [Function] |
| Retrieve an alist of mutable properties.                                                                                                              |            |
| <b>ly:prob-property</b> <i>prob sym val</i>                                                                                                           | [Function] |
| Return the value for property <i>sym</i> of Prob object <i>prob</i> . If no value is found, return <i>val</i> or '()' if <i>val</i> is not specified. |            |
| <b>ly:prob-property?</b> <i>obj sym</i>                                                                                                               | [Function] |
| Is boolean prop <i>sym</i> of <i>obj</i> set?                                                                                                         |            |
| <b>ly:prob-set-property!</b> <i>obj sym value</i>                                                                                                     | [Function] |
| Set property <i>sym</i> of <i>obj</i> to <i>value</i> .                                                                                               |            |
| <b>ly:prob-type?</b> <i>obj type</i>                                                                                                                  | [Function] |
| Is <i>obj</i> the specified prob-type?                                                                                                                |            |
| <b>ly:programming-error</b> <i>str rest</i>                                                                                                           | [Function] |
| A Scheme callable function to issue the internal warning <i>str</i> . The message is formatted with <i>format</i> and <i>rest</i> .                   |            |

|                                                                                                                                                                             |            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>ly:progress</b> <i>str rest</i>                                                                                                                                          | [Function] |
| A Scheme callable function to print progress <i>str</i> . The message is formatted with <b>format</b> and <i>rest</i> .                                                     |            |
| <b>ly:property-lookup-stats</b> <i>sym</i>                                                                                                                                  | [Function] |
| Return hash table with a property access corresponding to <i>sym</i> . Choices are <b>prob</b> , <b>grob</b> , and <b>context</b> .                                         |            |
| <b>ly:protects</b>                                                                                                                                                          | [Function] |
| Return hash of protected objects.                                                                                                                                           |            |
| <b>ly:pt</b> <i>num</i>                                                                                                                                                     | [Function] |
| <i>num</i> printer points.                                                                                                                                                  |            |
| <b>ly:register-stencil-expression</b> <i>symbol</i>                                                                                                                         | [Function] |
| Add <i>symbol</i> as head of a stencil expression.                                                                                                                          |            |
| <b>ly:relative-group-extent</b> <i>elements common axis</i>                                                                                                                 | [Function] |
| Determine the extent of <i>elements</i> relative to <i>common</i> in the <i>axis</i> direction.                                                                             |            |
| <b>ly:reset-all-fonts</b>                                                                                                                                                   | [Function] |
| Forget all about previously loaded fonts.                                                                                                                                   |            |
| <b>ly:round-filled-box</b> <i>xext yext blot</i>                                                                                                                            | [Function] |
| Make a <b>Stencil</b> object that prints a black box of dimensions <i>xext</i> , <i>yext</i> and roundness <i>blot</i> .                                                    |            |
| <b>ly:round-filled-polygon</b> <i>points blot</i>                                                                                                                           | [Function] |
| Make a <b>Stencil</b> object that prints a black polygon with corners at the points defined by <i>points</i> (list of coordinate pairs) and roundness <i>blot</i> .         |            |
| <b>ly:run-translator</b> <i>mus output-def</i>                                                                                                                              | [Function] |
| Process <i>mus</i> according to <i>output-def</i> . An interpretation context is set up, and <i>mus</i> is interpreted with it. The context is returned in its final state. |            |
| Optionally, this routine takes an object-key to uniquely identify the score block containing it.                                                                            |            |
| <b>ly:score?</b> <i>x</i>                                                                                                                                                   | [Function] |
| Is <i>x</i> a <b>Score</b> object?                                                                                                                                          |            |
| <b>ly:score-add-output-def!</b> <i>score def</i>                                                                                                                            | [Function] |
| Add an output definition <i>def</i> to <i>score</i> .                                                                                                                       |            |
| <b>ly:score-embedded-format</b> <i>score layout</i>                                                                                                                         | [Function] |
| Run <i>score</i> through <i>layout</i> (an output definition) scaled to correct output-scale already, returning a list of layout-lines.                                     |            |
| <b>ly:score-error?</b> <i>score</i>                                                                                                                                         | [Function] |
| Was there an error in the score?                                                                                                                                            |            |
| <b>ly:score-header</b> <i>score</i>                                                                                                                                         | [Function] |
| Return score header.                                                                                                                                                        |            |
| <b>ly:score-music</b> <i>score</i>                                                                                                                                          | [Function] |
| Return score music.                                                                                                                                                         |            |
| <b>ly:score-output-defs</b> <i>score</i>                                                                                                                                    | [Function] |
| All output definitions in a score.                                                                                                                                          |            |

- ly:score-set-header!** *score module* [Function]  
Set the score header.
- ly:set-default-scale** *scale* [Function]  
Set the global default scale. This determines the tuning of pitches with no accidentals or key signatures. The first pitch is C. Alterations are calculated relative to this scale. The number of pitches in this scale determines the number of scale steps that make up an octave. Usually the 7-note major scale.
- ly:set-grob-modification-callback** *cb* [Function]  
Specify a procedure that will be called every time LilyPond modifies a grob property. The callback will receive as arguments the grob that is being modified, the name of the C++ file in which the modification was requested, the line number in the C++ file in which the modification was requested, the name of the function in which the modification was requested, the property to be changed, and the new value for the property.
- ly:set-middle-C!** *context* [Function]  
Set the `middleCPosition` variable in *context* based on the variables `middleCClefPosition` and `middleCOffset`.
- ly:set-option** *var val* [Function]  
Set a program option.
- ly:set-property-cache-callback** *cb* [Function]  
Specify a procedure that will be called whenever lilypond calculates a callback function and caches the result. The callback will receive as arguments the grob whose property it is, the name of the property, the name of the callback that calculated the property, and the new (cached) value of the property.
- ly:simple-closure?** *clos* [Function]  
Is *clos* a simple closure?
- ly:skyline?** *x* [Function]  
Is *x* a `Skyline` object?
- ly:skyline-pair?** *x* [Function]  
Is *x* a `Skyline_pair` object?
- ly:slur-score-count** [Function]  
count number of slur scores.
- ly:smob-protects** [Function]  
Return LilyPond's internal smob protection list.
- ly:solve-spring-rod-problem** *springs rods length ragged* [Function]  
Solve a spring and rod problem for *count* objects, that are connected by *count*-1 *springs*, and an arbitrary number of *rods*. *count* is implicitly given by *springs* and *rods*. The *springs* argument has the format (*ideal*, *inverse\_hook*) and *rods* is of the form (*idx1*, *idx2*, *distance*).  
*length* is a number, *ragged* a boolean.  
The function returns a list containing the force (positive for stretching, negative for compressing and *#f* for non-satisfied constraints) followed by *spring-count*+1 positions of the objects.
- ly:source-file?** *x* [Function]  
Is *x* a `Source_file` object?

|                                                                                                                                                                                                                                                                                                                     |            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>ly:spanner?</code> <i>g</i>                                                                                                                                                                                                                                                                                   | [Function] |
| Is <i>g</i> a <code>spanner</code> object?                                                                                                                                                                                                                                                                          |            |
| <code>ly:spanner-bound</code> <i>spanner dir</i>                                                                                                                                                                                                                                                                    | [Function] |
| Get one of the bounds of <i>spanner</i> . <i>dir</i> is -1 for left, and 1 for right.                                                                                                                                                                                                                               |            |
| <code>ly:spanner-broken-into</code> <i>spanner</i>                                                                                                                                                                                                                                                                  | [Function] |
| Return broken-into list for <i>spanner</i> .                                                                                                                                                                                                                                                                        |            |
| <code>ly:spanner-set-bound!</code> <i>spanner dir item</i>                                                                                                                                                                                                                                                          | [Function] |
| Set grob <i>item</i> as bound in direction <i>dir</i> for <i>spanner</i> .                                                                                                                                                                                                                                          |            |
| <code>ly:spawn</code> <i>command rest</i>                                                                                                                                                                                                                                                                           | [Function] |
| Simple interface to <code>g_spawn_sync</code> <i>str</i> . The error is formatted with <code>format</code> and <i>rest</i> .                                                                                                                                                                                        |            |
| <code>ly:spring?</code> <i>x</i>                                                                                                                                                                                                                                                                                    | [Function] |
| Is <i>x</i> a <code>Spring</code> object?                                                                                                                                                                                                                                                                           |            |
| <code>ly:spring-set-inverse-compress-strength!</code> <i>spring strength</i>                                                                                                                                                                                                                                        | [Function] |
| Set the inverse compress <i>strength</i> of <i>spring</i> .                                                                                                                                                                                                                                                         |            |
| <code>ly:spring-set-inverse-stretch-strength!</code> <i>spring strength</i>                                                                                                                                                                                                                                         | [Function] |
| Set the inverse stretch <i>strength</i> of <i>spring</i> .                                                                                                                                                                                                                                                          |            |
| <code>ly:staff-symbol-line-thickness</code> <i>grob</i>                                                                                                                                                                                                                                                             | [Function] |
| Returns the <code>line-thickness</code> of the staff associated with <i>grob</i> .                                                                                                                                                                                                                                  |            |
| <code>ly:staff-symbol-staff-radius</code> <i>grob</i>                                                                                                                                                                                                                                                               | [Function] |
| Returns the radius of the staff associated with <i>grob</i> .                                                                                                                                                                                                                                                       |            |
| <code>ly:staff-symbol-staff-space</code> <i>grob</i>                                                                                                                                                                                                                                                                | [Function] |
| Returns the <code>staff-space</code> of the staff associated with <i>grob</i> .                                                                                                                                                                                                                                     |            |
| <code>ly:start-environment</code>                                                                                                                                                                                                                                                                                   | [Function] |
| Return the environment (a list of strings) that was in effect at program start.                                                                                                                                                                                                                                     |            |
| <code>ly:stderr-redirect</code> <i>file-name mode</i>                                                                                                                                                                                                                                                               | [Function] |
| Redirect stderr to <i>file-name</i> , opened with <i>mode</i> .                                                                                                                                                                                                                                                     |            |
| <code>ly:stencil?</code> <i>x</i>                                                                                                                                                                                                                                                                                   | [Function] |
| Is <i>x</i> a <code>Stencil</code> object?                                                                                                                                                                                                                                                                          |            |
| <code>ly:stencil-add</code> <i>args</i>                                                                                                                                                                                                                                                                             | [Function] |
| Combine stencils. Takes any number of arguments.                                                                                                                                                                                                                                                                    |            |
| <code>ly:stencil-aligned-to</code> <i>stil axis dir</i>                                                                                                                                                                                                                                                             | [Function] |
| Align <i>stil</i> using its own extents. <i>dir</i> is a number. -1 and 1 are left and right, respectively. Other values are interpolated (so 0 means the center).                                                                                                                                                  |            |
| <code>ly:stencil-combine-at-edge</code> <i>first axis direction second padding</i>                                                                                                                                                                                                                                  | [Function] |
| Construct a stencil by putting <i>second</i> next to <i>first</i> . <i>axis</i> can be 0 (x-axis) or 1 (y-axis). <i>direction</i> can be -1 (left or down) or 1 (right or up). The stencils are juxtaposed with <i>padding</i> as extra space. <i>first</i> and <i>second</i> may also be '()' or <code>#f</code> . |            |
| <code>ly:stencil-empty?</code> <i>stil</i>                                                                                                                                                                                                                                                                          | [Function] |
| Return whether <i>stil</i> is empty.                                                                                                                                                                                                                                                                                |            |

- ly:stencil-expr** *stil* [Function]  
Return the expression of *stil*.
- ly:stencil-extent** *stil axis* [Function]  
Return a pair of numbers signifying the extent of *stil* in *axis* direction (0 or 1 for x and y axis, respectively).
- ly:stencil-fonts** *s* [Function]  
Analyze *s*, and return a list of fonts used in *s*.
- ly:stencil-in-color** *stc r g b* [Function]  
Put *stc* in a different color.
- ly:stencil-rotate** *stil angle x y* [Function]  
Return a stencil *stil* rotated *angle* degrees around the relative offset (*x*, *y*). E.g. an offset of (-1, 1) will rotate the stencil around the left upper corner.
- ly:stencil-rotate-absolute** *stil angle x y* [Function]  
Return a stencil *stil* rotated *angle* degrees around point (*x*, *y*), given in absolute coordinates.
- ly:stencil-scale** *stil x y* [Function]  
Scale *stil* using the horizontal and vertical scaling factors *x* and *y*.
- ly:stencil-translate** *stil offset* [Function]  
Return a *stil*, but translated by *offset* (a pair of numbers).
- ly:stencil-translate-axis** *stil amount axis* [Function]  
Return a copy of *stil* but translated by *amount* in *axis* direction.
- ly:stream-event?** *obj* [Function]  
Is *obj* a `Stream_event` object?
- ly:string-percent-encode** *str* [Function]  
Encode all characters in string *str* with hexadecimal percent escape sequences, with the following exceptions: characters -, ., /, and \_; and characters in ranges 0-9, A-Z, and a-z.
- ly:string-substitute** *a b s* [Function]  
Replace string *a* by string *b* in string *s*.
- ly:system-font-load** *name* [Function]  
Load the OpenType system font '*name.otf*'. Fonts loaded with this command must contain three additional SFNT font tables called LILC, LILF, and LILY, needed for typesetting musical elements. Currently, only the Emmentaler and the Emmentaler-Brace fonts fulfill these requirements.  
  
Note that only `ly:font-get-glyph` and derived code (like `\lookup`) can access glyphs from the system fonts; text strings are handled exclusively via the Pango interface.
- ly:text-interface::interpret-markup** [Function]  
Convert a text markup into a stencil. Takes three arguments, *layout*, *props*, and *markup*.  
*layout* is a `\layout` block; it may be obtained from a grob with `ly:grob-layout`. *props* is an alist chain, i.e. a list of alists. This is typically obtained with `(ly:grob-alist-chain grob (ly:output-def-lookup layout 'text-font-defaults))`. *markup* is the markup text to be processed.
- ly:translate-cpp-warning-scheme** *str* [Function]  
Translates a string in C++ printf format and modifies it to use it for scheme formatting.

|                                                                                                                                                                                                                                                                      |            |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <code>ly:translator?</code> <i>x</i>                                                                                                                                                                                                                                 | [Function] |
| Is <i>x</i> a <code>Translator</code> object?                                                                                                                                                                                                                        |            |
| <code>ly:translator-context</code> <i>trans</i>                                                                                                                                                                                                                      | [Function] |
| Return the context of the translator object <i>trans</i> .                                                                                                                                                                                                           |            |
| <code>ly:translator-description</code> <i>me</i>                                                                                                                                                                                                                     | [Function] |
| Return an alist of properties of translator <i>me</i> .                                                                                                                                                                                                              |            |
| <code>ly:translator-group?</code> <i>x</i>                                                                                                                                                                                                                           | [Function] |
| Is <i>x</i> a <code>Translator_group</code> object?                                                                                                                                                                                                                  |            |
| <code>ly:translator-name</code> <i>trans</i>                                                                                                                                                                                                                         | [Function] |
| Return the type name of the translator object <i>trans</i> . The name is a symbol.                                                                                                                                                                                   |            |
| <code>ly:transpose-key-alist</code> <i>l pit</i>                                                                                                                                                                                                                     | [Function] |
| Make a new key alist of <i>l</i> transposed by pitch <i>pit</i> .                                                                                                                                                                                                    |            |
| <code>ly:truncate-list!</code> <i>lst i</i>                                                                                                                                                                                                                          | [Function] |
| Take at most the first <i>i</i> of list <i>lst</i> .                                                                                                                                                                                                                 |            |
| <code>ly:ttf-&gt;pfa</code> <i>ttf-file-name idx</i>                                                                                                                                                                                                                 | [Function] |
| Convert the contents of a TrueType font file to PostScript Type 42 font, returning it as a string. The optional <i>idx</i> argument is useful for TrueType collections (TTC) only; it specifies the font index within the TTC. The default value of <i>idx</i> is 0. |            |
| <code>ly:ttf-ps-name</code> <i>ttf-file-name idx</i>                                                                                                                                                                                                                 | [Function] |
| Extract the PostScript name from a TrueType font. The optional <i>idx</i> argument is useful for TrueType collections (TTC) only; it specifies the font index within the TTC. The default value of <i>idx</i> is 0.                                                  |            |
| <code>ly:unit</code>                                                                                                                                                                                                                                                 | [Function] |
| Return the unit used for lengths as a string.                                                                                                                                                                                                                        |            |
| <code>ly:unpure-pure-container?</code> <i>clos</i>                                                                                                                                                                                                                   | [Function] |
| Is <i>clos</i> an unpure pure container?                                                                                                                                                                                                                             |            |
| <code>ly:unpure-pure-container-pure-part</code> <i>pc</i>                                                                                                                                                                                                            | [Function] |
| Return the pure part of <i>pc</i> .                                                                                                                                                                                                                                  |            |
| <code>ly:unpure-pure-container-unpure-part</code> <i>pc</i>                                                                                                                                                                                                          | [Function] |
| Return the unpure part of <i>pc</i> .                                                                                                                                                                                                                                |            |
| <code>ly:usage</code>                                                                                                                                                                                                                                                | [Function] |
| Print usage message.                                                                                                                                                                                                                                                 |            |
| <code>ly:verbose-output?</code>                                                                                                                                                                                                                                      | [Function] |
| Was verbose output requested, i.e. loglevel at least <code>DEBUG</code> ?                                                                                                                                                                                            |            |
| <code>ly:version</code>                                                                                                                                                                                                                                              | [Function] |
| Return the current lilypond version as a list, e.g., (1 3 127 uu1).                                                                                                                                                                                                  |            |
| <code>ly:warning</code> <i>str rest</i>                                                                                                                                                                                                                              | [Function] |
| A Scheme callable function to issue the warning <i>str</i> . The message is formatted with <code>format</code> and <i>rest</i> .                                                                                                                                     |            |
| <code>ly:warning-located</code> <i>location str rest</i>                                                                                                                                                                                                             | [Function] |
| A Scheme callable function to issue the warning <i>str</i> at the specified location in an input file. The message is formatted with <code>format</code> and <i>rest</i> .                                                                                           |            |








`ly:wide-char->utf-8 wc`

[Function]

Encode the Unicode codepoint *wc*, an integer, as UTF-8.

## Appendix B Cheat sheet

| Syntax                               | Description       | Example                                                                               |
|--------------------------------------|-------------------|---------------------------------------------------------------------------------------|
| <code>1 2 8 16</code>                | durations         |    |
| <code>c4. c4..</code>                | augmentation dots |    |
| <code>c d e f g a b</code>           | scale             |   |
| <code>fis bes</code>                 | alteration        |  |
| <code>\clef treble \clef bass</code> | clefs             |  |
| <code>\time 3/4 \time 4/4</code>     | time signature    |  |
| <code>r4 r8</code>                   | rest              |  |
| <code>d ~ d</code>                   | tie               |  |
| <code>\key es \major</code>          | key signature     |  |

`note'`

raise octave

`note,`

lower octave

`c( d e)`

slur

`c\ ( c( d) e\)`

phrasing slur

`a8[ b]`

beam

`<< \new Staff ... >>`

more staves

`c-> c-.`

articulations

`c2\mf c\s fz`

dynamics

`a\< a a\!`

crescendo



`a\> a a\!`

decrescendo

`< >`

chord

`\partial 8`

pickup / upbeat

`\times 2/3 {f g a}`

triplets

`\grace`

grace notes

`\lyricmode { twinkle }`

entering lyrics

twinkle


`\new Lyrics`

printing lyrics

twinkle

`twin -- kle`

lyric hyphen

`\chordmode { c:dim f:maj7 }`

chords

`\context ChordNames`

printing chord names

 $C^{\circ} F^{\Delta}$ `<<{e f} \ \ {c d}>>`

polyphony

`s4 s8 s16`

spacer rests

## Appendix C LilyPond grammar

This appendix contains a description of the LilyPond grammar, as output from the parser.

Grammar

```

1 start_symbol:  lilypond

3 start_symbol:  "#{ "  embedded_lilypond

4 lilypond:  /* empty */
5           | lilypond toplevel_expression
6           | lilypond assignment
7           | lilypond error
8           | lilypond "\version-error"

9 toplevel_expression:  lilypond_header
10                      | book_block
11                      | bookpart_block
12                      | score_block
13                      | composite_music
14                      | full_markup
15                      | full_markup_list
16                      | output_def

17 embedded_scm_bare:  SCM_TOKEN
18                   | SCM_IDENTIFIER

19 embedded_scm_bare_arg:  embedded_scm_bare
20                       | STRING
21                       | STRING_IDENTIFIER
22                       | full_markup
23                       | full_markup_list
24                       | context_modification
25                       | score_block
26                       | context_def_spec_block
27                       | book_block
28                       | bookpart_block
29                       | output_def

30 embedded_scm:  embedded_scm_bare
31              | scm_function_call

32 embedded_scm_arg:  embedded_scm_bare_arg
33                  | scm_function_call
34                  | music_arg

35 scm_function_call:  SCM_FUNCTION function_arglist

36 embedded_lilypond:  /* empty */
37                   | identifier_init
38                   | music music music_list
39                   | error

```

```

40             | "\version-error" embedded_lilypond

41 lilypond_header_body: /* empty */
42             | lilypond_header_body assignment

43 lilypond_header:  "\header" '{' lilypond_header_body '}'

44 assignment_id:  STRING
45             | LYRICS_STRING

46 assignment:  assignment_id '=' identifier_init
47             | assignment_id property_path '=' identifier_init
48             | embedded_scm

49 identifier_init:  score_block
50             | book_block
51             | bookpart_block
52             | output_def
53             | context_def_spec_block
54             | music
55             | post_event_nofinger
56             | number_expression
57             | string
58             | embedded_scm
59             | full_markup
60             | full_markup_list
61             | context_modification

62 context_def_spec_block:  "\context" '{' context_def_spec_body '}'

63 context_def_spec_body:  /* empty */
64             | CONTEXT_DEF_IDENTIFIER
65             | context_def_spec_body embedded_scm
66             | context_def_spec_body context_mod
67             | context_def_spec_body context_modification

68 book_block:  "\book" '{' book_body '}'

69 book_body:  /* empty */
70             | BOOK_IDENTIFIER
71             | book_body paper_block
72             | book_body bookpart_block
73             | book_body score_block
74             | book_body composite_music
75             | book_body full_markup
76             | book_body full_markup_list
77             | book_body lilypond_header
78             | book_body embedded_scm
79             | book_body error

80 bookpart_block:  "\bookpart" '{' bookpart_body '}'

```

```

81 bookpart_body: /* empty */
82             | BOOK_IDENTIFIER
83             | bookpart_body paper_block
84             | bookpart_body score_block
85             | bookpart_body composite_music
86             | bookpart_body full_markup
87             | bookpart_body full_markup_list
88             | bookpart_body lilypond_header
89             | bookpart_body embedded_scm
90             | bookpart_body error

91 score_block:  "\score" '{' score_body '}'

92 score_body:  music
93             | SCORE_IDENTIFIER
94             | score_body lilypond_header
95             | score_body output_def
96             | score_body error

97 paper_block: output_def

98 output_def:  output_def_body '}'

99 output_def_head:  "\paper"
100                 | "\midi"
101                 | "\layout"

102 output_def_head_with_mode_switch:  output_def_head

103 output_def_body:  output_def_head_with_mode_switch '{'
104                 | output_def_head_with_mode_switch
105                   '{'
106                   OUTPUT_DEF_IDENTIFIER
107                   | output_def_body assignment
108                   | output_def_body context_def_spec_block
109                   | output_def_body error

108 tempo_event:  "\tempo" steno_duration '=' tempo_range
109             |  "\tempo" scalar_closed steno_duration '=' tempo_range
110             |  "\tempo" scalar

111 music_list: /* empty */
112           | music_list music
113           | music_list embedded_scm
114           | music_list error

115 braced_music_list:  '{' music_list '}'

116 music:  simple_music
117       | lyric_element_music
118       | composite_music

```

```

119 music_arg:  simple_music
120           | composite_music

121 repeated_music:  "\repeat" simple_string unsigned_number music
122                | "\repeat"
                  simple_string
                  unsigned_number
                  music
                  "\alternative"
                  braced_music_list

123 sequential_music:  "\sequential" braced_music_list
124                  | braced_music_list

125 simultaneous_music:  "\simultaneous" braced_music_list
126                    | "<<" music_list ">>"

127 simple_music:  event_chord
128              | music_property_def
129              | context_change

131 context_modification:  "\with" '{' context_mod_list '}'
132                      | "\with" CONTEXT_MOD_IDENTIFIER
133                      | CONTEXT_MOD_IDENTIFIER
134                      | "\with" embedded_scm_closed

135 optional_context_mod:  /* empty */
136                      | context_modification

137 context_mod_list:  /* empty */
138                  | context_mod_list context_mod
139                  | context_mod_list CONTEXT_MOD_IDENTIFIER
140                  | context_mod_list embedded_scm

141 composite_music:  complex_music
142                | music_bare

143 closed_music:  music_bare
144              | complex_music_prefix closed_music

145 music_bare:  mode_changed_music
146            | MUSIC_IDENTIFIER
147            | grouped_music_list

148 grouped_music_list:  simultaneous_music
149                   | sequential_music

150 function_arglist_skip:  function_arglist_common
151                       | "optional?" "ly:pitch?" function_arglist_skip
152                       | "optional?" "ly:duration?" function_arglist_skip
153                       | "optional?" "scheme?" function_arglist_skip

```



```

154 function_arglist_nonbackup: "optional?"
                                "ly:pitch?"
                                function_arglist
                                pitch_also_in_chords
155 | "optional?"
                                "ly:duration?"
                                function_arglist_closed
                                duration_length
156 | "optional?"
                                "scheme?"
                                function_arglist
                                embedded_scm_arg_closed
157 | "optional?"
                                "scheme?"
                                function_arglist_closed
                                bare_number_closed
158 | "optional?"
                                "scheme?"
                                function_arglist_closed
                                FRACTION
159 | "optional?"
                                "scheme?"
                                function_arglist_closed
                                post_event_nofinger
160 | "optional?"
                                "scheme?"
                                function_arglist_closed
                                '-'
                                UNSIGNED
161 | "optional?"
                                "scheme?"
                                function_arglist_closed
                                '-'
                                REAL
162 | "optional?"
                                "scheme?"
                                function_arglist_closed
                                '-'
                                NUMBER_IDENTIFIER

163 function_arglist_keep: function_arglist_common
164 | function_arglist_backup

165 function_arglist_closed_keep: function_arglist_closed_common
166 | function_arglist_backup

167 function_arglist_backup: "optional?"
                             "scheme?"
                             function_arglist_keep
                             embedded_scm_arg_closed
168 | "optional?"
                             "scheme?"

```

```

function_arglist_closed_keep
post_event_nofinger
169 | "optional?"
    "scheme?"
    function_arglist_keep
    lyric_element
170 | "optional?"
    "scheme?"
    function_arglist_closed_keep
    UNSIGNED
171 | "optional?"
    "scheme?"
    function_arglist_closed_keep
    REAL
172 | "optional?"
    "scheme?"
    function_arglist_closed_keep
    NUMBER_IDENTIFIER
173 | "optional?"
    "scheme?"
    function_arglist_closed_keep
    FRACTION
174 | "optional?"
    "scheme?"
    function_arglist_closed_keep
    '_'
    UNSIGNED
175 | "optional?"
    "scheme?"
    function_arglist_closed_keep
    '_'
    REAL
176 | "optional?"
    "scheme?"
    function_arglist_closed_keep
    '_'
    NUMBER_IDENTIFIER
177 | "optional?"
    "ly:pitch?"
    function_arglist_keep
    pitch_also_in_chords
178 | "optional?"
    "ly:duration?"
    function_arglist_closed_keep
    duration_length
179 | "optional?"
    "scheme?"
    function_arglist_backup
    "(backed-up?)"
180 | function_arglist_backup
    "(reparsed?)"
    embedded_scm_arg_closed

```

```

181             | function_arglist_backup
                  "(reparsed?)"
                  bare_number
182             | function_arglist_backup "(reparsed?)" fraction

183 function_arglist: function_arglist_common
184                 | function_arglist_nonbackup

185 function_arglist_common: function_arglist_bare
186                         | "scheme?"
                              function_arglist_optional
                              embedded_scm_arg
187                         | "scheme?"
                              function_arglist_closed_optional
                              bare_number
188                         | "scheme?"
                              function_arglist_closed_optional
                              fraction
189                         | "scheme?"
                              function_arglist_closed_optional
                              post_event_nofinger
190                         | function_arglist_common_minus
191                         | function_arglist_common_lyric

192 function_arglist_common_lyric: "scheme?"
                              function_arglist_optional
                              lyric_element
193                             | function_arglist_common_lyric
                              "(reparsed?)"
                              lyric_element_arg

194 function_arglist_common_minus: "scheme?"
                              function_arglist_closed_optional
                              ' _ '
                              UNSIGNED
195                             | "scheme?"
                              function_arglist_closed_optional
                              ' _ '
                              REAL
196                             | "scheme?"
                              function_arglist_closed_optional
                              ' _ '
                              NUMBER_IDENTIFIER
197                             | function_arglist_common_minus
                              "(reparsed?)"
                              bare_number

198 function_arglist_closed: function_arglist_closed_common
199                         | function_arglist_nonbackup

200 function_arglist_closed_common: function_arglist_bare
201                               | "scheme?"

```

```

function_arglist_optional
embedded_scm_arg_closed
202 | "scheme?"
function_arglist_closed_optional
bare_number
203 | "scheme?"
function_arglist_closed_optional
'-'
UNSIGNED
204 | "scheme?"
function_arglist_closed_optional
'-'
REAL
205 | "scheme?"
function_arglist_closed_optional
'-'
NUMBER_IDENTIFIER
206 | "scheme?"
function_arglist_closed_optional
post_event_nofinger
207 | "scheme?"
function_arglist_closed_optional
fraction
208 | "scheme?"
function_arglist_optional
lyric_element

209 function_arglist_optional: function_arglist_keep
210 | function_arglist_backup "(backed-up?)"
211 | "optional?"
"ly:pitch?"
function_arglist_optional
212 | "optional?"
"ly:duration?"
function_arglist_optional

213 function_arglist_closed_optional: function_arglist_closed_keep
214 | function_arglist_backup
"(backed-up?)"
215 | "optional?"
"ly:pitch?"
function_arglist_closed_optional
216 | "optional?"
"ly:duration?"
function_arglist_closed_optional

217 embedded_scm_closed: embedded_scm_bare
218 | scm_function_call_closed

219 embedded_scm_arg_closed: embedded_scm_bare_arg
220 | scm_function_call_closed
221 | closed_music

```

```

222 scm_function_call_closed:  SCM_FUNCTION function_arglist_closed

223 function_arglist_bare:  EXPECT_NO_MORE_ARGS
224                        | "ly:pitch?"
                           function_arglist_optional
                           pitch_also_in_chords
225                        | "ly:duration?"
                           function_arglist_closed_optional
                           duration_length
226                        | "optional?"
                           "ly:pitch?"
                           function_arglist_skip
                           "\default"
227                        | "optional?"
                           "ly:duration?"
                           function_arglist_skip
                           "\default"
228                        | "optional?"
                           "scheme?"
                           function_arglist_skip
                           "\default"

229 music_function_call:  MUSIC_FUNCTION function_arglist

230 optional_id:  /* empty */
231              | '=' simple_string

232 complex_music:  music_function_call
233                | repeated_music
234                | re_rhythmed_music
235                | complex_music_prefix music

236 complex_music_prefix:  "\context"
                           simple_string
                           optional_id
                           optional_context_mod
237                | "\new"
                           simple_string
                           optional_id
                           optional_context_mod

238 mode_changed_music:  mode_changing_head grouped_music_list
239                    | mode_changing_head_with_context
                           optional_context_mod
                           grouped_music_list

240 mode_changing_head:  "\notemode"
241                    | "\drummode"
242                    | "\figuremode"
243                    | "\chordmode"
244                    | "\lyricmode"

```

```

245 mode_changing_head_with_context:  "\drums"
246                                |  "\figures"
247                                |  "\chords"
248                                |  "\lyrics"

250 new_lyrics:  "\addlyrics"  composite_music

252 new_lyrics:  new_lyrics "\addlyrics"  composite_music

253 re_rhythmed_music:  composite_music new_lyrics

255 re_rhythmed_music:  "\lyricsto" simple_string  music

256 context_change:  "\change" STRING '=' STRING

257 property_path_revved:  embedded_scm_closed
258                        |  property_path_revved embedded_scm_closed

259 property_path:  property_path_revved

260 property_operation:  STRING '=' scalar
261                    |  "\unset" simple_string
262                    |  "\override" simple_string property_path '=' scalar
263                    |  "\revert" simple_string embedded_scm

264 context_def_mod:  "\consists"
265                  |  "\remove"
266                  |  "\accepts"
267                  |  "\defaultchild"
268                  |  "\denies"
269                  |  "\alias"
270                  |  "\type"
271                  |  "\description"
272                  |  "\name"

273 context_mod:  property_operation
274              |  context_def_mod STRING
275              |  context_def_mod embedded_scm

276 context_prop_spec:  simple_string
277                  |  simple_string '.' simple_string

278 simple_music_property_def:  "\override"
                              context_prop_spec
                              property_path
                              '='
                              scalar
279                  |  "\revert" context_prop_spec embedded_scm
280                  |  "\set" context_prop_spec '=' scalar
281                  |  "\unset" context_prop_spec

```

```

282 music_property_def:  simple_music_property_def

283 string:  STRING
284         | STRING_IDENTIFIER
285         | string '+' string

286 simple_string:  STRING
287                | LYRICS_STRING
288                | STRING_IDENTIFIER

289 scalar:  embedded_scm_arg
290         | bare_number
291         | lyric_element

292 scalar_closed:  embedded_scm_arg_closed
293                | bare_number
294                | lyric_element

295 event_chord:  simple_element post_events
296              | simple_chord_elements post_events
297              | CHORD_REPETITION optional_notemode_duration post_events
298              | MULTI_MEASURE_REST optional_notemode_duration post_events
299              | command_element
300              | note_chord_element

301 note_chord_element:  chord_body optional_notemode_duration post_events

302 chord_body:  "<" chord_body_elements ">"

303 chord_body_elements:  /* empty */
304                      | chord_body_elements chord_body_element

305 chord_body_element:  pitch
                      | exclamations
                      | questions
                      | octave_check
                      | post_events
306                      | DRUM_PITCH post_events
307                      | music_function_chord_body

308 music_function_chord_body:  music_function_call
309                          | MUSIC_IDENTIFIER

310 music_function_event:  MUSIC_FUNCTION function_arglist_closed

311 event_function_event:  EVENT_FUNCTION function_arglist_closed

312 command_element:  command_event
313                  | "\"["
314                  | "\"]"
315                  | "\"
316                  | "'"

```

```

317 command_event:  "~"
318                | tempo_event

319 post_events:    /* empty */
320                | post_events post_event

321 post_event_nofinger:  direction_less_event
322                      | script_dir music_function_event
323                      | "--"
324                      | "__"
325                      | script_dir direction_reqd_event
326                      | script_dir direction_less_event
327                      | string_number_event
328                      | '^' fingering
329                      | '-' fingering

330 post_event:      post_event_nofinger
331                | '-' fingering

332 string_number_event:  E_UNSIGNED

333 direction_less_char: '['
334                     | ']'
335                     | '~'
336                     | '('
337                     | ')'
338                     | "\!"
339                     | "\"("
340                     | "\"\"
341                     | "\">"
342                     | "\"<"

343 direction_less_event:  direction_less_char
344                      | EVENT_IDENTIFIER
345                      | tremolo_type
346                      | event_function_event

347 direction_reqd_event:  gen_text_def
348                      | script_abbreviation

349 octave_check:  /* empty */
350               | '='
351               | '=' sub_quotes
352               | '=' sup_quotes

353 sup_quotes:  '''
354             | sup_quotes '''

355 sub_quotes:  ','
356             | sub_quotes ','

```



```

357 steno_pitch:  NOTENAME_PITCH
358             | NOTENAME_PITCH sup_quotes
359             | NOTENAME_PITCH sub_quotes

360 steno_tonic_pitch:  TONICNAME_PITCH
361                   | TONICNAME_PITCH sup_quotes
362                   | TONICNAME_PITCH sub_quotes

363 pitch:  steno_pitch
364       | PITCH_IDENTIFIER

365 pitch_also_in_chords:  pitch
366                     | steno_tonic_pitch

367 gen_text_def:  full_markup
368             | simple_string

369 fingering:  UNSIGNED

370 script_abbreviation:  '^'
371                     | '+'
372                     | '-'
373                     | '|'
374                     | ">"
375                     | '.'
376                     | '_'

377 script_dir:  '_'
378           | '^'
379           | '-'

380 duration_length:  multiplied_duration

381 optional_notemode_duration:  /* empty */
382                           | multiplied_duration

383 steno_duration:  bare_unsigned dots
384               | DURATION_IDENTIFIER dots

385 multiplied_duration:  steno_duration
386                   | multiplied_duration '*' bare_unsigned
387                   | multiplied_duration '*' FRACTION

388 fraction:  FRACTION
389         | UNSIGNED '/' UNSIGNED

390 dots:  /* empty */
391       | dots '.'

392 tremolo_type:  ':'
393             | ':' bare_unsigned

```

```

394 bass_number:  UNSIGNED
395             |  STRING
396             |  full_markup

397 figured_bass_alteration:  '-'
398                         |  '+'
399                         |  '!'

400 bass_figure:  "_"
401             |  bass_number
402             |  bass_figure ']'
403             |  bass_figure figured_bass_alteration
404             |  bass_figure figured_bass_modification

405 figured_bass_modification:  "\+"
406                         |  "\!"
407                         |  '/'
408                         |  "\"

409 br_bass_figure:  bass_figure
410             |  '[' bass_figure

411 figure_list:  /* empty */
412             |  figure_list br_bass_figure

413 figure_spec:  FIGURE_OPEN figure_list FIGURE_CLOSE

414 optional_rest:  /* empty */
415             |  "\"rest"

416 simple_element:  pitch
                  exclamations
                  questions
                  octave_check
                  optional_notemode_duration
                  optional_rest
417             |  DRUM_PITCH optional_notemode_duration
418             |  RESTNAME optional_notemode_duration

419 simple_chord_elements:  new_chord
420             |  figure_spec optional_notemode_duration

421 lyric_element:  lyric_markup
422             |  LYRICS_STRING

423 lyric_element_arg:  lyric_element
424             |  lyric_element multiplied_duration post_events
425             |  lyric_element post_event post_events
426             |  LYRIC_ELEMENT optional_notemode_duration post_events

427 lyric_element_music:  lyric_element
                       optional_notemode_duration

```

```
                                post_events

428 new_chord:  steno_tonic_pitch optional_notemode_duration
429             | steno_tonic_pitch
                  optional_notemode_duration
                  chord_separator
                  chord_items

430 chord_items: /* empty */
431             | chord_items chord_item

432 chord_separator: ":"
433                 | "^"
434                 | "/" steno_tonic_pitch
435                 | "/" steno_tonic_pitch

436 chord_item:  chord_separator
437             | step_numbers
438             | CHORD_MODIFIER

439 step_numbers: step_number
440             | step_numbers '.' step_number

441 step_number: bare_unsigned
442             | bare_unsigned '+'
443             | bare_unsigned "-"

444 tempo_range: bare_unsigned
445             | bare_unsigned '~' bare_unsigned

446 number_expression: number_expression '+' number_term
447                   | number_expression '-' number_term
448                   | number_term

449 number_term:  number_factor
450             | number_factor '*' number_factor
451             | number_factor '/' number_factor

452 number_factor: '-' number_factor
453             | bare_number

454 bare_number:  bare_number_closed
455             | UNSIGNED NUMBER_IDENTIFIER
456             | REAL NUMBER_IDENTIFIER

457 bare_number_closed: UNSIGNED
458                   | REAL
459                   | NUMBER_IDENTIFIER

460 bare_unsigned:  UNSIGNED

461 unsigned_number: UNSIGNED
```

```

462          | NUMBER_IDENTIFIER

463 exclamations: /* empty */
464          | exclamations '!'

465 questions: /* empty */
466          | questions '?'

467 lyric_markup: LYRIC_MARKUP_IDENTIFIER

469 lyric_markup: LYRIC_MARKUP markup_top

470 full_markup_list: MARKUPLIST_IDENTIFIER

472 full_markup_list: "\markuplist" markup_list

473 full_markup: MARKUP_IDENTIFIER

475 full_markup: "\markup" markup_top

476 markup_top: markup_list
477          | markup_head_1_list simple_markup
478          | simple_markup

480 markup_scm: embedded_scm_bare "(backed-up?)"

481 markup_list: MARKUPLIST_IDENTIFIER
482          | markup_composed_list
483          | markup_braced_list
484          | markup_command_list
485          | markup_scm MARKUPLIST_IDENTIFIER

486 markup_composed_list: markup_head_1_list markup_braced_list

487 markup_braced_list: '{' markup_braced_list_body '}'

488 markup_braced_list_body: /* empty */
489          | markup_braced_list_body markup
490          | markup_braced_list_body markup_list

491 markup_command_list: MARKUP_LIST_FUNCTION markup_command_list_arguments

492 markup_command_basic_arguments: "markup-list?"
                                markup_command_list_arguments
                                markup_list
493          | "scheme?"
                                markup_command_list_arguments
                                embedded_scm_closed
494          | EXPECT_NO_MORE_ARGS

495 markup_command_list_arguments: markup_command_basic_arguments
496          | "markup?"

```

```

                                markup_command_list_arguments
                                markup

497 markup_head_1_item:  MARKUP_FUNCTION
                        "markup?"
                        markup_command_list_arguments

498 markup_head_1_list:  markup_head_1_item
499                      | markup_head_1_list markup_head_1_item

500 simple_markup:  STRING
501                | MARKUP_IDENTIFIER
502                | LYRIC_MARKUP_IDENTIFIER
503                | STRING_IDENTIFIER

505 simple_markup:  "\score" 0 '{' score_body '}'
506                | MARKUP_FUNCTION markup_command_basic_arguments
507                | markup_scm MARKUP_IDENTIFIER

508 markup:  markup_head_1_list simple_markup
509          | simple_markup

```

Terminals, with rules where they appear

```

168 169 170 171 172 173 174 175 176 177 178 179 211 212 215 216
172 173 174 175 176 179 186 187 188 189 192 194 195 196 201 202
203 204 205 206 207 208 228 493
226 227 228
397 447 452
"#{" (352) 3
"(backed-up?" (347) 179 210 214 480
"(reparsed?" (348) 180 181 182 193 197
"--" (317) 443
"-" (338) 323
"/" (318) 434
"/+" (314) 435
":" (316) 432
"<" (319) 302
"<<" (321) 126
">" (320) 302 374
">>" (322) 126
"!\" (327) 338 406
\" (323) 315 408
\" (329) 339
\" (326) 340
\"+\" (332) 405
\"<\" (331) 342
\">\" (324) 341
\"[\" (328) 313

```

"\]" (330) 314  
 "\accepts" (273) 266  
 "\addlyrics" (262) 250 252  
 "\alias" (274) 269  
 "\alternative" (260) 122  
 "\book" (275) 68  
 "\bookpart" (276) 80  
 "\C[haracter]" (325)  
 "\change" (277) 256  
 "\chordmode" (278) 243  
 "\chords" (279) 247  
 "\consists" (280) 264  
 "\context" (281) 62 236  
 "\default" (263) 226 227 228  
 "\defaultchild" (282) 267  
 "\denies" (283) 268  
 "\description" (284) 271  
 "\drummode" (285) 241  
 "\drums" (286) 245  
 "\figuremode" (287) 242  
 "\figures" (288) 246  
 "\header" (289) 43  
 "\layout" (291) 101  
 "\lyricmode" (292) 244  
 "\lyrics" (293) 248  
 "\lyricsto" (294) 255  
 "\markup" (295) 475  
 "\markuplist" (296) 472  
 "\midi" (297) 100  
 "\name" (298) 272  
 "\new" (313) 237  
 "\notemode" (299) 240  
 "\override" (300) 262 278  
 "\paper" (301) 99  
 "\remove" (302) 265  
 "\repeat" (259) 121 122  
 "\rest" (303) 415  
 "\revert" (304) 263 279  
 "\score" (305) 91 505  
 "\sequential" (306) 123  
 "\set" (307) 280  
 "\simultaneous" (308) 125  
 "\tempo" (309) 108 109 110  
 "\type" (310) 270  
 "\unset" (311) 261 281  
 "\version-error" (290) 8 40  
 "\with" (312) 131 132 134  
 "\~" (333) 317  
 "^" (315) 433  
 "\_" (337) 400  
 "\_\_" (334) 324  
 "ly:duration?" (345) 152 155 178 212 216 225 227

```

"ly:pitch?" (344) 151 154 177 211 215 224 226
"markup-list?" (349) 492
"markup?" (343) 496 497
"optional?" (350) 151 152 153 154 155 156 157 158 159 160 161 162 167
"scheme?" (346) 153 156 157 158 159 160 161 162 167 168 169 170 171
$end (0) 0
'!' (33) 399 464
''' (39) 353 354
'(' (40) 336
')' (41) 337
'*' (42) 386 387 450
'+' (43) 285 371 398 442 446
',' (44) 355 356
'-' (45) 160 161 162 174 175 176 194 195 196 203 204 205 331 372 379
'.' (46) 277 375 391 440
'/' (47) 389 407 451
':' (58) 392 393
'=' (61) 46 47 108 109 231 256 260 262 278 280 350 351 352
'?' (63) 466
'[' (91) 333 410
']' (93) 334 402
'^' (94) 328 370 378
'_' (95) 329 376 377
'{' (123) 43 62 68 80 91 103 104 115 131 487 505
'|' (124) 316 373
'}' (125) 43 62 68 80 91 98 115 131 487 505
'~' (126) 335 445
BOOK_IDENTIFIER (353) 70 82
CHORD_MODIFIER (355) 438
CHORD_REPETITION (356) 297
CHORDMODIFIER_PITCH (354)
CHORDMODIFIERS (339)
COMPOSITE (261)
CONTEXT_DEF_IDENTIFIER (357) 64
CONTEXT_MOD_IDENTIFIER (358) 132 133 139
DRUM_PITCH (359) 306 417
DURATION_IDENTIFIER (265) 384
E_UNSIGNED (342) 332
error (256) 7 39 79 90 96 107 114
EVENT_FUNCTION (361) 311
EVENT_IDENTIFIER (360) 344
EXPECT_NO_MORE_ARGS (351) 223 494
FIGURE_CLOSE (335) 413
FIGURE_OPEN (336) 413
FRACTION (362) 158 173 387 388
FUNCTION_ARGLIST (264)
LYRIC_ELEMENT (364) 426
LYRIC_MARKUP (340) 469
LYRIC_MARKUP_IDENTIFIER (365) 467 502
LYRICS_STRING (363) 45 287 422
MARKUP_FUNCTION (366) 497 506
MARKUP_IDENTIFIER (368) 473 501 507

```

MARKUP\_LIST\_FUNCTION (367) 491  
 MARKUPLIST\_IDENTIFIER (369) 470 481 485  
 MULTI\_MEASURE\_REST (341) 298  
 MUSIC\_FUNCTION (370) 229 310  
 MUSIC\_IDENTIFIER (371) 146 309  
 NOTENAME\_PITCH (269) 357 358 359  
 NUMBER\_IDENTIFIER (271) 162 172 176 196 205 455 456 459 462  
 OUTPUT\_DEF\_IDENTIFIER (372) 104  
 PITCH\_IDENTIFIER (270) 364  
 PREC\_BOT (258)  
 PREC\_TOP (272)  
 REAL (266) 161 171 175 195 204 456 458  
 RESTNAME (373) 418  
 SCM\_FUNCTION (374) 35 222  
 SCM\_IDENTIFIER (375) 18  
 SCM\_TOKEN (376) 17  
 SCORE\_IDENTIFIER (377) 93  
 STRING (378) 20 44 256 260 274 283 286 395 500  
 STRING\_IDENTIFIER (379) 21 284 288 503  
 TONICNAME\_PITCH (268) 360 361 362  
 UNARY\_MINUS (380)  
 UNSIGNED (267) 160 170 174 194 203 369 389 394 455 457 460 461

Nonterminals, with rules where they appear

assignment (161)  
     on left: 46 47 48, on right: 6 42 105  
 assignment\_id (160)  
     on left: 44 45, on right: 46 47  
 bare\_number\_closed (294)  
     on left: 457 458 459, on right: 157 454  
 bass\_number (270)  
     on left: 394 395 396, on right: 401  
 book\_block (165)  
     on left: 68, on right: 10 27 50  
 bookpart\_block (167)  
     on left: 80, on right: 11 28 51 72  
 br\_bass\_figure (274)  
     on left: 409 410, on right: 412  
 braced\_music\_list (178)  
     on left: 115, on right: 122 123 124 125  
 chord\_body (237)  
     on left: 302, on right: 301  
 chord\_body\_element (239)  
     on left: 305 306 307, on right: 304  
 chord\_body\_elements (238)  
     on left: 303 304, on right: 302 304  
 chord\_item (286)  
     on left: 436 437 438, on right: 431  
 chord\_items (284)  
     on left: 430 431, on right: 429 431



chord\_separator (285)  
   on left: 432 433 434 435, on right: 429 436  
 closed\_music (190)  
   on left: 143 144, on right: 144 221  
 command\_element (243)  
   on left: 312 313 314 315 316, on right: 299  
 command\_event (244)  
   on left: 317 318, on right: 312  
 complex\_music (212)  
   on left: 232 233 234 235, on right: 141  
 complex\_music\_prefix (213)  
   on left: 236 237, on right: 144 235  
 context\_change (222)  
   on left: 256, on right: 129  
 context\_def\_spec\_block (163)  
   on left: 62, on right: 26 53 106  
 context\_mod (227)  
   on left: 273 274 275, on right: 66 138  
 context\_prop\_spec (228)  
   on left: 276 277, on right: 278 279 280 281  
 direction\_less\_event (250)  
   on left: 343 344 345 346, on right: 321 326  
 direction\_reqd\_event (251)  
   on left: 347 348, on right: 325  
 dots (268)  
   on left: 390 391, on right: 383 384 391  
 duration\_length (263)  
   on left: 380, on right: 155 178 225  
 embedded\_lilypond (157)  
   on left: 36 37 38 39 40, on right: 3 40  
 embedded\_scm\_arg (155)  
   on left: 32 33 34, on right: 186 289  
 embedded\_scm\_bare (152)  
   on left: 17 18, on right: 19 30 217 480  
 embedded\_scm\_closed (206)  
   on left: 217 218, on right: 134 257 258 493  
 event\_chord (235)  
   on left: 295 296 297 298 299 300, on right: 127  
 event\_function\_event (242)  
   on left: 311, on right: 346  
 exclamations (297)  
   on left: 463 464, on right: 305 416 464  
 figure\_list (275)  
   on left: 411 412, on right: 412 413  
 figure\_spec (276)  
   on left: 413, on right: 420  
 figured\_bass\_alteration (271)  
   on left: 397 398 399, on right: 403  
 figured\_bass\_modification (273)  
   on left: 405 406 407 408, on right: 404  
 fingering (260)  
   on left: 369, on right: 328 329 331

```

fraction (267)
  on left: 388 389, on right: 182 188 207
full_markup (303)
  on left: 473 475, on right: 14 22 59 75 86 367 396
full_markup_list (301)
  on left: 470 472, on right: 15 23 60 76 87
function_arglist (198)
  on left: 183 184, on right: 35 154 156 229
function_arglist_common_lyric (200)
  on left: 192 193, on right: 191 193
function_arglist_keep (195)
  on left: 163 164, on right: 167 169 177 209
gen_text_def (259)
  on left: 367 368, on right: 347
grouped_music_list (192)
  on left: 148 149, on right: 147 238 239
lilypond (150)
  on left: 4 5 6 7 8, on right: 1 5 6 7 8
lilypond_header (159)
  on left: 43, on right: 9 77 88 94
lilypond_header_body (158)
  on left: 41 42, on right: 42 43
lyric_element_arg (281)
  on left: 423 424 425 426, on right: 193
lyric_element_music (282)
  on left: 427, on right: 117
lyric_markup (299)
  on left: 467 469, on right: 421
markup (319)
  on left: 508 509, on right: 489 496
markup_braced_list (310)
  on left: 487, on right: 483 486
markup_braced_list_body (311)
  on left: 488 489 490, on right: 487 489 490
markup_command_list (312)
  on left: 491, on right: 484
markup_composed_list (309)
  on left: 486, on right: 482
markup_head_1_item (315)
  on left: 497, on right: 498 499
markup_head_1_list (316)
  on left: 498 499, on right: 477 486 499 508
markup_list (308)
  on left: 481 482 483 484 485, on right: 472 476 490 492
markup_scm (306)
  on left: 480, on right: 485 507
markup_top (305)
  on left: 476 477 478, on right: 469 475
mode_changed_music (214)
  on left: 238 239, on right: 145
mode_changing_head (215)
  on left: 240 241 242 243 244, on right: 238

```

```

music (179)
    on left: 116 117 118, on right: 38 54 92 112 121 122 235 255
music_arg (180)
    on left: 119 120, on right: 34
music_bare (191)
    on left: 145 146 147, on right: 142 143
music_function_call (210)
    on left: 229, on right: 232 308
music_function_chord_body (240)
    on left: 308 309, on right: 307
music_function_event (241)
    on left: 310, on right: 322
music_property_def (230)
    on left: 282, on right: 128
new_chord (283)
    on left: 428 429, on right: 419
new_lyrics (217)
    on left: 250 252, on right: 252 253
note_chord_element (236)
    on left: 301, on right: 300
number_expression (290)
    on left: 446 447 448, on right: 56 446 447
number_factor (292)
    on left: 452 453, on right: 449 450 451 452
number_term (291)
    on left: 449 450 451, on right: 446 447 448
octave_check (252)
    on left: 349 350 351 352, on right: 305 416
optional_context_mod (187)
    on left: 135 136, on right: 236 237 239
optional_id (211)
    on left: 230 231, on right: 236 237
optional_rest (277)
    on left: 414 415, on right: 416
output_def (172)
    on left: 98, on right: 16 29 52 95 97
output_def_head (173)
    on left: 99 100 101, on right: 102
output_def_head_with_mode_switch (174)
    on left: 102, on right: 103 104
paper_block (171)
    on left: 97, on right: 71 83
pitch (257)
    on left: 363 364, on right: 305 365 416
pitch_also_in_chords (258)
    on left: 365 366, on right: 154 177 224
post_event (247)
    on left: 330 331, on right: 320 425
property_operation (225)
    on left: 260 261 262 263, on right: 273
property_path (224)
    on left: 259, on right: 47 262 278

```

```

property_path_revved (223)
  on left: 257 258, on right: 258 259
questions (298)
  on left: 465 466, on right: 305 416 466
re_rhythmed_music (220)
  on left: 253 255, on right: 234
repeated_music (181)
  on left: 121 122, on right: 233
scalar (233)
  on left: 289 290 291, on right: 110 260 262 278 280
scalar_closed (234)
  on left: 292 293 294, on right: 109
scm_function_call (156)
  on left: 35, on right: 31 33
scm_function_call_closed (208)
  on left: 222, on right: 218 220
score_block (169)
  on left: 91, on right: 12 25 49 73 84
score_body (170)
  on left: 92 93 94 95 96, on right: 91 94 95 96 505
script_dir (262)
  on left: 377 378 379, on right: 322 325 326
sequential_music (182)
  on left: 123 124, on right: 149
simple_chord_elements (279)
  on left: 419 420, on right: 296
simple_element (278)
  on left: 416 417 418, on right: 295
simple_music (184)
  on left: 127 128 129, on right: 116 119
simple_music_property_def (229)
  on left: 278 279 280 281, on right: 282
simultaneous_music (183)
  on left: 125 126, on right: 148
start_symbol (148)
  on left: 1 3, on right: 0
steno_duration (265)
  on left: 383 384, on right: 108 109 385
steno_pitch (255)
  on left: 357 358 359, on right: 363
step_number (288)
  on left: 441 442 443, on right: 439 440
step_numbers (287)
  on left: 439 440, on right: 437 440
string (231)
  on left: 283 284 285, on right: 57 285
string_number_event (248)
  on left: 332, on right: 327
sub_quotes (254)
  on left: 355 356, on right: 351 356 359 362
sup_quotes (253)
  on left: 353 354, on right: 352 354 358 361

```

```
tempo_event (176)
  on left: 108 109 110, on right: 318
tempo_range (289)
  on left: 444 445, on right: 108 109
toplevel_expression (151)
  on left: 9 10 11 12 13 14 15 16, on right: 5
tremolo_type (269)
  on left: 392 393, on right: 345
unsigned_number (296)
  on left: 461 462, on right: 121 122
```

## Appendix D GNU Free Documentation License

Version 1.3, 3 November 2008

Copyright © 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.

<http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

### 0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

### 1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

The “publisher” means any person or entity that distributes copies of the Document to the public.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

## 2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

## 3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document’s license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both

covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

#### 4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its



Title Page, then add an item describing the Modified Version as stated in the previous sentence.

- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the “History” section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled “Acknowledgements” or “Dedications”, Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled “Endorsements”. Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled “Endorsements” or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version’s license notice. These titles must be distinct from any other section titles.

You may add a section Entitled “Endorsements”, provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

## 5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled “History” in the various original documents, forming one section Entitled “History”; likewise combine any sections Entitled “Acknowledgements”, and any sections Entitled “Dedications”. You must delete all sections Entitled “Endorsements.”

## 6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

## 7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

## 8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

## 9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

#### 10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy’s public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

#### 11. RELICENSING

“Massive Multiauthor Collaboration Site” (or “MMC Site”) means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A “Massive Multiauthor Collaboration” (or “MMC”) contained in the site means any set of copyrightable works thus published on the MMC site.

“CC-BY-SA” means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

“Incorporate” means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is “eligible for relicensing” if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

## ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C)  year  your name.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.3
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts.  A copy of the license is included in the section entitled ``GNU
Free Documentation License''.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with
the Front-Cover Texts being list, and with the Back-Cover Texts
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

## Appendix E LilyPond command index

This index lists all the LilyPond commands and keywords with links to those sections of the manual which describe or discuss their use. Each link is in two parts. The first part points to the exact location in the manual where the command or keyword appears; the second part points to the start of the section of the manual in which the command or keyword appears.

|                 |                                         |
|-----------------|-----------------------------------------|
| !               | ~                                       |
| ! ..... 5       | ~ ..... 371                             |
| ,               | -                                       |
| ' ..... 1       | - ..... 234                             |
| ,               | \                                       |
| , ..... 1       | \! ..... 107                            |
| -               | \( ..... 117                            |
| - ..... 105     | \) ..... 117                            |
| .               | \< ..... 107                            |
| . ..... 39      | \> ..... 107                            |
| /               | \abs-fontsize ..... 609                 |
| / ..... 372     | \accent ..... 105                       |
| /+ ..... 372    | \accepts ..... 528, 529                 |
| :               | \acciaccatura ..... 97                  |
| : ..... 140     | \accidentalStyle ..... 22               |
| <               | \addChordShape ..... 331                |
| < ..... 142     | \addInstrumentDefinition ..... 182, 189 |
| <...> ..... 142 | \addlyrics ..... 228, 230, 231          |
| =               | \addQuote ..... 183                     |
| = ..... 8       | \aeolian ..... 19                       |
| >               | \afterGrace ..... 98                    |
| > ..... 142     | \aikenHeads ..... 35                    |
| ?               | \aikenHeadsMinor ..... 35               |
| ? ..... 5       | \alias ..... 528                        |
| [               | \allowPageTurn ..... 484                |
| [ ..... 82      | \alternative ..... 127                  |
| ]               | \appendToTag ..... 450                  |
| ] ..... 82      | \appoggiatura ..... 97                  |
|                 | \arpeggio ..... 122                     |
|                 | \arpeggioArrowDown ..... 122            |
|                 | \arpeggioArrowUp ..... 122              |
|                 | \arpeggioBracket ..... 122              |
|                 | \arpeggioNormal ..... 122               |
|                 | \arpeggioParenthesis ..... 122          |
|                 | \arpeggioParenthesisDashed ..... 122    |
|                 | \arrow-head ..... 219                   |
|                 | \arrow-head ..... 632                   |
|                 | \ascendens ..... 403, 410               |
|                 | \auctum ..... 403, 410                  |
|                 | \augmentum ..... 410                    |
|                 | \auto-footnote ..... 645                |
|                 | \autoBeamOff ..... 72                   |
|                 | \autoBeamOn ..... 72                    |
|                 | \autochange ..... 288                   |
|                 | \backslashed-digit ..... 646            |
|                 | \balloonGrobText ..... 198              |
|                 | \balloonLengthOff ..... 198             |
|                 | \balloonLengthOn ..... 198              |
|                 | \balloonText ..... 198                  |
|                 | \bar ..... 85, 89                       |
|                 | \barNumberCheck ..... 95                |

|                                          |               |                                          |          |
|------------------------------------------|---------------|------------------------------------------|----------|
| <code>\beam</code> .....                 | 632           | <code>\dotsNeutral</code> .....          | 39       |
| <code>\bendAfter</code> .....            | 119           | <code>\dotsUp</code> .....               | 39       |
| <code>\bold</code> .....                 | 212, 609      | <code>\doubleflat</code> .....           | 638      |
| <code>\book</code> .....                 | 423, 426      | <code>\doublesharp</code> .....          | 638      |
| <code>\bookOutputName</code> .....       | 425           | <code>\downbow</code> .....              | 105      |
| <code>\bookOutputSuffix</code> .....     | 425           | <code>\downbow</code> .....              | 298      |
| <code>\bookpart</code> .....             | 424, 426      | <code>\downmordent</code> .....          | 105      |
| <code>\bookpart</code> .....             | 482           | <code>\downprall</code> .....            | 105      |
| <code>\box</code> .....                  | 217, 609      | <code>\draw-circle</code> .....          | 219      |
| <code>\bracket</code> .....              | 112, 217, 633 | <code>\draw-circle</code> .....          | 633      |
| <code>\break</code> .....                | 482           | <code>\draw-hline</code> .....           | 633      |
| <code>\breathe</code> .....              | 118           | <code>\draw-line</code> .....            | 219      |
| <code>\breve</code> .....                | 38            | <code>\draw-line</code> .....            | 634      |
| <code>\breve</code> .....                | 49            | <code>\drummode</code> .....             | 162      |
| <code>\cadenzaOff</code> .....           | 64            | <code>\dynamic</code> .....              | 112, 610 |
| <code>\cadenzaOn</code> .....            | 64            | <code>\dynamicDown</code> .....          | 109      |
| <code>\caesura</code> .....              | 402           | <code>\dynamicNeutral</code> .....       | 109      |
| <code>\caps</code> .....                 | 610           | <code>\dynamicUp</code> .....            | 109      |
| <code>\cavum</code> .....                | 403, 410      | <code>\easyHeadsOff</code> .....         | 33       |
| <code>\center-align</code> .....         | 214, 618      | <code>\easyHeadsOn</code> .....          | 33       |
| <code>\center-column</code> .....        | 216, 618      | <code>\epsfile</code> .....              | 219      |
| <code>\change</code> .....               | 286           | <code>\epsfile</code> .....              | 634      |
| <code>\char</code> .....                 | 646           | <code>\espressivo</code> .....           | 105      |
| <code>\chordmode</code> .....            | 4, 12, 328    | <code>\espressivo</code> .....           | 108      |
| <code>\chordRepeats</code> .....         | 305           | <code>\expandFullBarRests</code> .....   | 53, 54   |
| <code>\chords</code> .....               | 374           | <code>\eyeglasses</code> .....           | 646      |
| <code>\circle</code> .....               | 217, 633      | <code>\f</code> .....                    | 107      |
| <code>\clef</code> .....                 | 15            | <code>\featherDurations</code> .....     | 84       |
| <code>\cm</code> .....                   | 544           | <code>\fermata</code> .....              | 105      |
| <code>\coda</code> .....                 | 105           | <code>\fermataMarkup</code> .....        | 53, 54   |
| <code>\column</code> .....               | 216, 618      | <code>\fermataMarkup</code> .....        | 105      |
| <code>\column-lines</code> .....         | 651           | <code>\ff</code> .....                   | 107      |
| <code>\combine</code> .....              | 219           | <code>\fff</code> .....                  | 107      |
| <code>\combine</code> .....              | 619           | <code>\ffff</code> .....                 | 107      |
| <code>\compoundMeter</code> .....        | 68            | <code>\fffff</code> .....                | 107      |
| <code>\compressFullBarRests</code> ..... | 53, 54        | <code>\fill-line</code> .....            | 216, 620 |
| <code>\concat</code> .....               | 619           | <code>\fill-with-pattern</code> .....    | 620      |
| <code>\consists</code> .....             | 528           | <code>\filled-box</code> .....           | 219      |
| <code>\context</code> .....              | 521           | <code>\filled-box</code> .....           | 634      |
| <code>\cr</code> .....                   | 107           | <code>\finalis</code> .....              | 402      |
| <code>\cresc</code> .....                | 108           | <code>\finger</code> .....               | 192      |
| <code>\crescHairpin</code> .....         | 109           | <code>\finger</code> .....               | 610      |
| <code>\crescTextCresc</code> .....       | 109           | <code>\flageolet</code> .....            | 105      |
| <code>\cueClef</code> .....              | 185           | <code>\flat</code> .....                 | 638      |
| <code>\cueDuring</code> .....            | 185           | <code>\flexa</code> .....                | 410      |
| <code>\cueDuringWithClef</code> .....    | 185           | <code>\fontCaps</code> .....             | 610      |
| <code>\customTabClef</code> .....        | 638           | <code>\fontsize</code> .....             | 212, 611 |
| <code>\decr</code> .....                 | 107           | <code>\footnote</code> .....             | 646      |
| <code>\decresc</code> .....              | 108           | <code>\fp</code> .....                   | 107      |
| <code>\defaultTimeSignature</code> ..... | 57            | <code>\fraction</code> .....             | 646      |
| <code>\deminutum</code> .....            | 403, 410      | <code>\frenchChords</code> .....         | 378      |
| <code>\denies</code> .....               | 528, 529      | <code>\fret-diagram</code> .....         | 319, 642 |
| <code>\descendens</code> .....           | 403, 410      | <code>\fret-diagram-terse</code> .....   | 320, 642 |
| <code>\dim</code> .....                  | 108           | <code>\fret-diagram-verbose</code> ..... | 322, 643 |
| <code>\dimHairpin</code> .....           | 109           | <code>\fromproperty</code> .....         | 647      |
| <code>\dimTextDecr</code> .....          | 109           | <code>\funkHeads</code> .....            | 35       |
| <code>\dimTextDecresc</code> .....       | 109           | <code>\funkHeadsMinor</code> .....       | 35       |
| <code>\dimTextDim</code> .....           | 109           | <code>\general-align</code> .....        | 215, 621 |
| <code>\dir-column</code> .....           | 619           | <code>\germanChords</code> .....         | 378      |
| <code>\displayLilyMusic</code> .....     | 467           | <code>\glissando</code> .....            | 120      |
| <code>\divisioMaior</code> .....         | 402           | <code>\grace</code> .....                | 97       |
| <code>\divisioMaxima</code> .....        | 402           | <code>\halfopen</code> .....             | 105      |
| <code>\divisioMinima</code> .....        | 402           | <code>\halign</code> .....               | 214, 622 |
| <code>\dorian</code> .....               | 19            | <code>\harmonic</code> .....             | 299      |
| <code>\dotsDown</code> .....             | 39            | <code>\harmonic</code> .....             | 307      |

|                                           |               |                                                   |               |
|-------------------------------------------|---------------|---------------------------------------------------|---------------|
| <code>\harmonicByFret</code> .....        | 307           | <code>\markuplist</code> .....                    | 222           |
| <code>\harmonicByRatio</code> .....       | 307           | <code>\markuplist</code> .....                    | 223           |
| <code>\harmonicsOff</code> .....          | 299           | <code>\maxima</code> .....                        | 38            |
| <code>\harmonicsOn</code> .....           | 299           | <code>\maxima</code> .....                        | 49            |
| <code>\harp-pedal</code> .....            | 644           | <code>\medium</code> .....                        | 612           |
| <code>\hbracket</code> .....              | 217, 635      | <code>\melisma</code> .....                       | 234           |
| <code>\hcenter-in</code> .....            | 623           | <code>\melismaEnd</code> .....                    | 234           |
| <code>\header</code> .....                | 426           | <code>\mergeDifferentlyDottedOff</code> .....     | 150           |
| <code>\hideKeySignature</code> .....      | 358           | <code>\mergeDifferentlyDottedOn</code> .....      | 150           |
| <code>\hideNotes</code> .....             | 194           | <code>\mergeDifferentlyHeadedOff</code> .....     | 150           |
| <code>\hideSplitTiedTabNotes</code> ..... | 306           | <code>\mergeDifferentlyHeadedOn</code> .....      | 150           |
| <code>\hideStaffSwitch</code> .....       | 289           | <code>\mf</code> .....                            | 107           |
| <code>\hspace</code> .....                | 623           | <code>\midi</code> .....                          | 426           |
| <code>\huge</code> .....                  | 191, 214, 611 | <code>\minor</code> .....                         | 19            |
| <code>\improvisationOff</code> .....      | 37            | <code>\mixolydian</code> .....                    | 19            |
| <code>\improvisationOff</code> .....      | 70            | <code>\mm</code> .....                            | 544           |
| <code>\improvisationOn</code> .....       | 37            | <code>\modalInversion</code> .....                | 14            |
| <code>\improvisationOn</code> .....       | 70            | <code>\modalTranspose</code> .....                | 13            |
| <code>\in</code> .....                    | 544           | <code>\mordent</code> .....                       | 105           |
| <code>\inclinatum</code> .....            | 403, 410      | <code>\mp</code> .....                            | 107           |
| <code>\include</code> .....               | 448           | <code>\musicglyph</code> .....                    | 96, 639       |
| <code>\instrumentSwitch</code> .....      | 182           | <code>\name</code> .....                          | 528           |
| <code>\inversion</code> .....             | 12            | <code>\natural</code> .....                       | 639           |
| <code>\ionian</code> .....                | 19            | <code>\new</code> .....                           | 521           |
| <code>\italianChords</code> .....         | 378           | <code>\noBeam</code> .....                        | 82            |
| <code>\italic</code> .....                | 212, 611      | <code>\noBreak</code> .....                       | 482           |
| <code>\justified-lines</code> .....       | 222           | <code>\noPageBreak</code> .....                   | 483           |
| <code>\justified-lines</code> .....       | 652           | <code>\noPageTurn</code> .....                    | 484           |
| <code>\justify</code> .....               | 216, 624      | <code>\normal-size-sub</code> .....               | 612           |
| <code>\justify-field</code> .....         | 624           | <code>\normal-size-super</code> .....             | 613           |
| <code>\justify-string</code> .....        | 625           | <code>\normal-text</code> .....                   | 613           |
| <code>\keepWithTag</code> .....           | 450           | <code>\normalsize</code> .....                    | 191, 214, 613 |
| <code>\key</code> .....                   | 19, 35        | <code>\note</code> .....                          | 639           |
| <code>\killCues</code> .....              | 189           | <code>\note-by-number</code> .....                | 639           |
| <code>\label</code> .....                 | 446           | <code>\null</code> .....                          | 215, 648      |
| <code>\laissezVibrer</code> .....         | 47            | <code>\number</code> .....                        | 613           |
| <code>\large</code> .....                 | 191, 214, 611 | <code>\numericTimeSignature</code> .....          | 57            |
| <code>\larger</code> .....                | 212, 214, 611 | <code>\octaveCheck</code> .....                   | 8             |
| <code>\layout</code> .....                | 426, 478      | <code>\on-the-fly</code> .....                    | 648           |
| <code>\left-align</code> .....            | 214, 625      | <code>\once</code> .....                          | 537           |
| <code>\left-brace</code> .....            | 647           | <code>\oneVoice</code> .....                      | 146           |
| <code>\left-column</code> .....           | 626           | <code>\open</code> .....                          | 105           |
| <code>\lheel</code> .....                 | 105           | <code>\open</code> .....                          | 298           |
| <code>\line</code> .....                  | 626           | <code>\oriscus</code> .....                       | 403, 410      |
| <code>\linea</code> .....                 | 403, 410      | <code>\ottava</code> .....                        | 20            |
| <code>\lineprall</code> .....             | 105           | <code>\override</code> .....                      | 536, 648      |
| <code>\locrian</code> .....               | 19            | <code>\override in \lyricmode</code> .....        | 227           |
| <code>\longa</code> .....                 | 38            | <code>\override-lines</code> .....                | 652           |
| <code>\longa</code> .....                 | 49            | <code>\overrideTimeSignatureSettings</code> ..... | 57            |
| <code>\longfermata</code> .....           | 105           | <code>\p</code> .....                             | 107           |
| <code>\lookup</code> .....                | 647           | <code>\pad-around</code> .....                    | 218, 626      |
| <code>\lower</code> .....                 | 215, 626      | <code>\pad-markup</code> .....                    | 218, 627      |
| <code>\ltoe</code> .....                  | 105           | <code>\pad-to-box</code> .....                    | 218, 627      |
| <code>\lydian</code> .....                | 19            | <code>\pad-x</code> .....                         | 218, 627      |
| <code>\lyricmode</code> .....             | 227, 228      | <code>\page-link</code> .....                     | 649           |
| <code>\lyricsto</code> .....              | 228, 230      | <code>\page-ref</code> .....                      | 446, 649      |
| <code>\magnify</code> .....               | 212, 612      | <code>\pageBreak</code> .....                     | 483           |
| <code>\major</code> .....                 | 19            | <code>\pageTurn</code> .....                      | 484           |
| <code>\makeClusters</code> .....          | 145           | <code>\paper</code> .....                         | 426, 470      |
| <code>\marcato</code> .....               | 105           | <code>\parallelMusic</code> .....                 | 159           |
| <code>\mark</code> .....                  | 95, 205       | <code>\parenthesize</code> .....                  | 196, 635      |
| <code>\markalphabet</code> .....          | 648           | <code>\partcombine</code> .....                   | 154           |
| <code>\markletter</code> .....            | 648           | <code>\partcombineApart</code> .....              | 155           |
| <code>\markup</code> .....                | 205, 209, 210 | <code>\partcombineAutomatic</code> .....          | 155           |
| <code>\markuplist</code> .....            | 209           | <code>\partcombineChords</code> .....             | 155           |

|                                                 |               |                                               |               |
|-------------------------------------------------|---------------|-----------------------------------------------|---------------|
| <code>\partcombineSoloI</code> .....            | 155           | <code>\sans</code> .....                      | 614           |
| <code>\partcombineSoloII</code> .....           | 155           | <code>\scale</code> .....                     | 637           |
| <code>\partcombineUnisono</code> .....          | 155           | <code>\scaleDurations</code> .....            | 45, 66        |
| <code>\partial</code> .....                     | 63, 127, 129  | <code>\score</code> .....                     | 422, 426, 640 |
| <code>\path</code> .....                        | 636           | <code>\segno</code> .....                     | 105           |
| <code>\pattern</code> .....                     | 649           | <code>\semiflat</code> .....                  | 641           |
| <code>\pes</code> .....                         | 410           | <code>\semiGermanChords</code> .....          | 378           |
| <code>\phrasingSlurDashed</code> .....          | 117           | <code>\semisharp</code> .....                 | 641           |
| <code>\phrasingSlurDashPattern</code> .....     | 117           | <code>\sesquiflat</code> .....                | 641           |
| <code>\phrasingSlurDotted</code> .....          | 117           | <code>\sesquisharp</code> .....               | 641           |
| <code>\phrasingSlurDown</code> .....            | 117           | <code>\set</code> .....                       | 74, 534       |
| <code>\phrasingSlurHalfDashed</code> .....      | 117           | <code>\sf</code> .....                        | 107           |
| <code>\phrasingSlurHalfSolid</code> .....       | 117           | <code>\sff</code> .....                       | 107           |
| <code>\phrasingSlurNeutral</code> .....         | 117           | <code>\sfz</code> .....                       | 107           |
| <code>\phrasingSlurSolid</code> .....           | 117           | <code>\sharp</code> .....                     | 641           |
| <code>\phrasingSlurUp</code> .....              | 117           | <code>\shiftOff</code> .....                  | 150           |
| <code>\phrygian</code> .....                    | 19            | <code>\shiftOn</code> .....                   | 150           |
| <code>\pitchedTrill</code> .....                | 126           | <code>\shiftOnn</code> .....                  | 150           |
| <code>\portato</code> .....                     | 105           | <code>\shiftOnnn</code> .....                 | 150           |
| <code>\postscript</code> .....                  | 219           | <code>\shortfermata</code> .....              | 105           |
| <code>\postscript</code> .....                  | 636           | <code>\showKeySignature</code> .....          | 358           |
| <code>\powerChords</code> .....                 | 343           | <code>\showStaffSwitch</code> .....           | 289           |
| <code>\pp</code> .....                          | 107           | <code>\signumcongruentiae</code> .....        | 105           |
| <code>\ppp</code> .....                         | 107           | <code>\simple</code> .....                    | 614           |
| <code>\pppp</code> .....                        | 107           | <code>\skip</code> .....                      | 51, 249       |
| <code>\ppppp</code> .....                       | 107           | <code>\slashed-digit</code> .....             | 650           |
| <code>\prall</code> .....                       | 105           | <code>\slashedGrace</code> .....              | 97            |
| <code>\pralldown</code> .....                   | 105           | <code>\slurDashed</code> .....                | 114           |
| <code>\prallmordent</code> .....                | 105           | <code>\slurDashPattern</code> .....           | 115           |
| <code>\prallprall</code> .....                  | 105           | <code>\slurDotted</code> .....                | 114           |
| <code>\prallup</code> .....                     | 105           | <code>\slurDown</code> .....                  | 114           |
| <code>\predefinedFretboardsOff</code> .....     | 338           | <code>\slurHalfDashed</code> .....            | 115           |
| <code>\predefinedFretboardsOn</code> .....      | 338           | <code>\slurHalfSolid</code> .....             | 115           |
| <code>\property-recursive</code> .....          | 649           | <code>\slurNeutral</code> .....               | 114           |
| <code>\pt</code> .....                          | 544           | <code>\slurSolid</code> .....                 | 114           |
| <code>\pushToTag</code> .....                   | 450           | <code>\slurUp</code> .....                    | 115           |
| <code>\put-adjacent</code> .....                | 628           | <code>\small</code> .....                     | 191, 214, 615 |
| <code>\quilisma</code> .....                    | 403, 410      | <code>\smallCaps</code> .....                 | 615           |
| <code>\quoteDuring</code> .....                 | 183, 185      | <code>\smaller</code> .....                   | 212, 214, 615 |
| <code>\raise</code> .....                       | 215, 628      | <code>\snappizzicato</code> .....             | 105           |
| <code>\relative</code> .....                    | 2, 4, 12, 288 | <code>\sostenutoOff</code> .....              | 292           |
| <code>\RemoveEmptyStaves</code> .....           | 176, 177      | <code>\sostenutoOn</code> .....               | 292           |
| <code>\removeWithTag</code> .....               | 450           | <code>\southernHarmonyHeads</code> .....      | 35            |
| <code>\repeat</code> .....                      | 127           | <code>\southernHarmonyHeadsMinor</code> ..... | 35            |
| <code>\repeat percent</code> .....              | 137           | <code>\sp</code> .....                        | 107           |
| <code>\repeat tremolo</code> .....              | 139           | <code>\spp</code> .....                       | 107           |
| <code>\repeatTie</code> .....                   | 46, 130, 250  | <code>\staccatissimo</code> .....             | 105           |
| <code>\replace</code> .....                     | 614           | <code>\staccato</code> .....                  | 105           |
| <code>\rest</code> .....                        | 49            | <code>\startGroup</code> .....                | 201           |
| <code>\retrograde</code> .....                  | 13            | <code>\startStaff</code> .....                | 169, 172      |
| <code>\reverseturn</code> .....                 | 105           | <code>\startTrillSpan</code> .....            | 125           |
| <code>\revert</code> .....                      | 537           | <code>\stemDown</code> .....                  | 197           |
| <code>\revertTimeSignatureSettings</code> ..... | 58            | <code>\stemNeutral</code> .....               | 197           |
| <code>\rfz</code> .....                         | 107           | <code>\stemUp</code> .....                    | 197           |
| <code>\rheel</code> .....                       | 105           | <code>\stencil</code> .....                   | 650           |
| <code>\right-align</code> .....                 | 214, 628      | <code>\stopGroup</code> .....                 | 201           |
| <code>\right-brace</code> .....                 | 649           | <code>\stopped</code> .....                   | 105           |
| <code>\right-column</code> .....                | 628           | <code>\stopStaff</code> .....                 | 169, 172, 176 |
| <code>\rightHandFinger</code> .....             | 340           | <code>\stopTrillSpan</code> .....             | 125           |
| <code>\roman</code> .....                       | 614           | <code>\storePredefinedDiagram</code> .....    | 331           |
| <code>\rotate</code> .....                      | 629           | <code>\stringTuning</code> .....              | 315           |
| <code>\rounded-box</code> .....                 | 217, 637      | <code>\strophia</code> .....                  | 403, 410      |
| <code>\rtoe</code> .....                        | 105           | <code>\strut</code> .....                     | 650           |
| <code>\sacredHarpHeads</code> .....             | 35            | <code>\sub</code> .....                       | 213, 615      |
| <code>\sacredHarpHeadsMinor</code> .....        | 35            | <code>\super</code> .....                     | 213, 616      |





|             |          |
|-------------|----------|
| autoBeaming | 74       |
| autoBeamOff | 72       |
| autoBeamOn  | 72       |
| autochange  | 288, 689 |

## B

|                              |               |
|------------------------------|---------------|
| Balloon_engraver             | 198           |
| balloonGrobText              | 198, 689      |
| balloonLengthOff             | 198           |
| balloonLengthOn              | 198           |
| balloonText                  | 198, 689      |
| banjo-c-tuning               | 345           |
| banjo-modal-tuning           | 345           |
| banjo-open-d-tuning          | 345           |
| banjo-open-dm-tuning         | 345           |
| bar                          | 85, 89, 689   |
| barCheckSynchronize          | 94            |
| BarNumber                    | 90            |
| barNumberCheck               | 95, 689       |
| barNumberVisibility          | 90            |
| bartype                      | 89            |
| base-shortest-duration       | 504           |
| baseMoment                   | 74            |
| beamExceptions               | 74            |
| beatStructure                | 74            |
| bendAfter                    | 119, 689      |
| binding-offset               | 475           |
| blank-after-score-page-force | 476           |
| blank-last-page-force        | 476           |
| blank-page-force             | 476           |
| bold                         | 212           |
| bookOutputName               | 689           |
| bookOutputSuffix             | 689           |
| bottom-margin                | 471           |
| box                          | 217           |
| bracket                      | 112, 217, 292 |
| breakable                    | 73            |
| breathe                      | 118, 689      |
| breve                        | 38            |
| breve                        | 49            |

## C

|                         |            |
|-------------------------|------------|
| cadenzaOff              | 64         |
| cadenzaOn               | 64         |
| center-align            | 214        |
| center-column           | 216        |
| change                  | 286        |
| check-consistency       | 474        |
| chordChanges            | 374        |
| chordmode               | 4, 12, 328 |
| chordNameExceptions     | 377        |
| chordNameLowercaseMinor | 376        |
| ChordNames              | 328        |
| chordNameSeparator      | 376        |
| chordNoteNamer          | 376        |
| chordPrefixSpacer       | 378        |
| chordRepeats            | 689        |
| chordRootNamer          | 376        |
| circle                  | 217        |
| clef                    | 15, 689    |
| color                   | 195        |
| column                  | 216        |

|                           |          |
|---------------------------|----------|
| combine                   | 219      |
| common-shortest-duration  | 504      |
| Completion_heads_engraver | 69       |
| Completion_rest_engraver  | 69       |
| compoundMeter             | 689      |
| compressFullBarRests      | 53, 54   |
| consists                  | 528      |
| controlpitch              | 8        |
| cr                        | 107      |
| cresc                     | 108      |
| crescHairpin              | 109      |
| crescTextCresc            | 109      |
| cross                     | 32       |
| cross-staff               | 290      |
| cueClef                   | 185, 689 |
| cueClefUnset              | 689      |
| cueDuring                 | 185, 689 |
| cueDuringWithClef         | 185, 689 |
| currentBarNumber          | 90       |
| currentBarNumber          | 103      |

## D

|                             |          |
|-----------------------------|----------|
| deadNote                    | 690      |
| decr                        | 107      |
| decresc                     | 108      |
| default                     | 22, 24   |
| default-staff-staff-spacing | 488      |
| defaultBarType              | 89       |
| defaultNoteHeads            | 690      |
| defaultTimeSignature        | 57       |
| denies                      | 528      |
| dim                         | 108, 369 |
| dimHairpin                  | 109      |
| dimTextDecr                 | 109      |
| dimTextDecresc              | 109      |
| dimTextDim                  | 109      |
| displayLilyMusic            | 690      |
| displayMusic                | 690      |
| dodecaphonic                | 27       |
| dorian                      | 19       |
| dotsDown                    | 39       |
| dotsNeutral                 | 39       |
| dotsUp                      | 39       |
| draw-circle                 | 219      |
| draw-line                   | 219      |
| drummode                    | 162      |
| DrumStaff                   | 162      |
| dynamic                     | 112      |
| dynamicDown                 | 109      |
| DynamicLineSpanner          | 109      |
| dynamicNeutral              | 109      |
| dynamicUp                   | 109      |

## E

|                    |        |
|--------------------|--------|
| easyHeadsOff       | 33     |
| easyHeadsOn        | 33     |
| endSpanners        | 690    |
| epsfile            | 219    |
| espressivo         | 108    |
| expandFullBarRests | 53, 54 |
| extra-offset       | 488    |

**F**

|                        |         |
|------------------------|---------|
| f                      | 107     |
| featherDurations       | 84, 690 |
| fermataMarkup          | 53, 54  |
| ff                     | 107     |
| fff                    | 107     |
| ffff                   | 107     |
| fffff                  | 107     |
| fill-line              | 216     |
| filled-box             | 219     |
| finger                 | 192     |
| first-page-number      | 477     |
| flag-style             | 290     |
| followVoice            | 289     |
| font-interface         | 192     |
| font-interface         | 223     |
| font-size              | 191     |
| font-size              | 192     |
| fontsize               | 212     |
| fontSize               | 191     |
| footnote               | 690     |
| forget                 | 28      |
| four-string-banjo      | 345     |
| fp                     | 107     |
| fret-diagram           | 319     |
| fret-diagram-interface | 324     |
| fret-diagram-terse     | 320     |
| fret-diagram-verbose   | 322     |
| FretBoards             | 327     |
| funkHeads              | 35      |
| funkHeadsMinor         | 35      |

**G**

|                             |     |
|-----------------------------|-----|
| general-align               | 215 |
| glissando                   | 120 |
| grace                       | 690 |
| GregorianTranscriptionStaff | 162 |
| Grid_line_span_engraver     | 199 |
| Grid_point_engraver         | 199 |
| gridInterval                | 199 |
| grobdescriptions            | 690 |
| grow-direction              | 84  |

**H**

|                             |          |
|-----------------------------|----------|
| halign                      | 214      |
| harmonicByFret              | 690      |
| harmonicByRatio             | 690      |
| harmonicNote                | 690      |
| harmonicsOn                 | 690      |
| hbracket                    | 217      |
| hideKeySignature            | 358      |
| hideNotes                   | 194      |
| hideStaffSwitch             | 289      |
| horizontal-shift            | 475      |
| Horizontal_bracket_engraver | 201      |
| huge                        | 191, 214 |

**I**

|                  |    |
|------------------|----|
| improvisationOff | 37 |
| improvisationOff | 70 |
| improvisationOn  | 37 |

|                  |               |
|------------------|---------------|
| improvisationOn  | 70            |
| indent           | 180, 475, 507 |
| inner-margin     | 475           |
| instrumentSwitch | 182, 690      |
| inversion        | 690           |
| ionian           | 19            |
| italic           | 212           |

**J**

|                 |     |
|-----------------|-----|
| justified-lines | 222 |
| justify         | 216 |

**K**

|             |             |
|-------------|-------------|
| keepWithTag | 690         |
| key         | 19, 35, 690 |
| killCues    | 189, 691    |

**L**

|                       |          |
|-----------------------|----------|
| label                 | 691      |
| laissezVibrer         | 47       |
| language              | 691      |
| languageRestore       | 691      |
| languageSaveAndChange | 691      |
| large                 | 191, 214 |
| larger                | 212, 214 |
| last-bottom-spacing   | 473      |
| layout file           | 479      |
| left-align            | 214      |
| left-margin           | 474      |
| length                | 290      |
| line-width            | 474, 507 |
| locrian               | 19       |
| longa                 | 38       |
| longa                 | 49       |
| lower                 | 215      |
| ly:minimal-breaking   | 484      |
| ly:optimal-breaking   | 483      |
| ly:page-turn-breaking | 483      |
| lydian                | 19       |

**M**

|                         |               |
|-------------------------|---------------|
| m                       | 369           |
| magnify                 | 212           |
| magstep                 | 191           |
| magstep                 | 544           |
| maj                     | 369           |
| major                   | 19            |
| major seven symbols     | 378           |
| majorSevenSymbol        | 376           |
| make-dynamic-script     | 113           |
| make-pango-font-tree    | 225           |
| makeClusters            | 145           |
| makeClusters            | 691           |
| makeDefaultStringTuning | 691           |
| mark                    | 95, 205, 691  |
| markup                  | 205, 209, 210 |
| markup-markup-spacing   | 473           |
| markup-system-spacing   | 473           |
| markuplist              | 209           |
| markuplist              | 222           |

|                                |          |
|--------------------------------|----------|
| markuplist                     | 223      |
| max-systems-per-page           | 476      |
| maxima                         | 38       |
| maxima                         | 49       |
| measureLength                  | 74, 103  |
| measurePosition                | 63, 103  |
| MensuralStaff                  | 162      |
| mergeDifferentlyDottedOff      | 150      |
| mergeDifferentlyDottedOn       | 150      |
| mergeDifferentlyHeadedOff      | 150      |
| mergeDifferentlyHeadedOn       | 150      |
| mf                             | 107      |
| min-systems-per-page           | 476      |
| minimum-Y-extent               | 488      |
| minimumFret                    | 304, 339 |
| minimumPageTurnLength          | 483      |
| minimumRepeatLengthForPageTurn | 484      |
| minor                          | 19       |
| minorChordModifier             | 377      |
| mixed                          | 292      |
| mixolydian                     | 19       |
| modalInversion                 | 14, 691  |
| modalTranspose                 | 13, 691  |
| modern                         | 25       |
| modern-cautionary              | 25       |
| modern-voice                   | 25       |
| modern-voice-cautionary        | 25       |
| mp                             | 107      |
| MultiMeasureRestText           | 53       |
| musicglyph                     | 96       |
| musicMap                       | 691      |

## N

|                                 |          |
|---------------------------------|----------|
| name                            | 528      |
| neo-modern                      | 26       |
| neo-modern-cautionary           | 26       |
| neo-modern-voice                | 27       |
| neo-modern-voice-cautionary     | 27       |
| no-reset                        | 27       |
| noBeam                          | 82       |
| nonstaff-nonstaff-spacing       | 488      |
| nonstaff-relatedstaff-spacing   | 488      |
| nonstaff-unrelatedstaff-spacing | 488      |
| noPageBreak                     | 691      |
| noPageTurn                      | 691      |
| normalsize                      | 191, 214 |
| Note_heads_engraver             | 69       |
| null                            | 215      |
| numericTimeSignature            | 57       |

## O

|                                  |        |
|----------------------------------|--------|
| octaveCheck                      | 8, 691 |
| once                             | 691    |
| oneVoice                         | 146    |
| ottava                           | 20     |
| ottava                           | 691    |
| outer-margin                     | 475    |
| outside-staff-horizontal-padding | 502    |
| outside-staff-padding            | 502    |
| outside-staff-priority           | 502    |
| overrideProperty                 | 691    |
| overrideTimeSignatureSettings    | 691    |

## P

|                                     |          |
|-------------------------------------|----------|
| p                                   | 107      |
| pad-around                          | 218      |
| pad-markup                          | 218      |
| pad-to-box                          | 218      |
| pad-x                               | 218      |
| page-breaking                       | 476      |
| page-breaking-system-system-spacing | 476      |
| page-count                          | 476      |
| page-spacing-weight                 | 477      |
| pageBreak                           | 691      |
| pageTurn                            | 692      |
| palmMute                            | 692      |
| palmMuteOn                          | 692      |
| paper-height                        | 471      |
| paper-width                         | 474      |
| parallelMusic                       | 159, 692 |
| parenthesize                        | 196, 692 |
| partcombine                         | 154, 692 |
| partcombineApart                    | 155      |
| partcombineAutomatic                | 155      |
| partcombineChords                   | 155      |
| partcombineDown                     | 692      |
| partcombineForce                    | 692      |
| partcombineSoloI                    | 155      |
| partcombineSoloII                   | 155      |
| partcombineUnisono                  | 155      |
| partcombineUp                       | 692      |
| partial                             | 63, 692  |
| pedalSustainStyle                   | 292      |
| percent                             | 137      |
| phrasingSlurDashed                  | 117      |
| phrasingSlurDashPattern             | 117, 692 |
| phrasingSlurDotted                  | 117      |
| phrasingSlurDown                    | 117      |
| phrasingSlurHalfDashed              | 117      |
| phrasingSlurHalfSolid               | 117      |
| phrasingSlurNeutral                 | 117      |
| phrasingSlurSolid                   | 117      |
| phrasingSlurUp                      | 117      |
| phrygian                            | 19       |
| piano                               | 26       |
| piano-cautionary                    | 26       |
| PianoStaff                          | 286, 288 |
| pipeSymbol                          | 95       |
| Pitch_squash_engraver               | 70       |
| pitchedTrill                        | 126, 692 |
| pointAndClickOff                    | 692      |
| pointAndClickOn                     | 692      |
| pointAndClickTypes                  | 693      |
| postscript                          | 219      |
| powerChords                         | 343      |
| pp                                  | 107      |
| ppp                                 | 107      |
| pppp                                | 107      |
| ppppp                               | 107      |
| predefinedFretboardsOff             | 338      |
| predefinedFretboardsOn              | 338      |
| print-all-headers                   | 477      |
| print-first-page-number             | 477      |
| print-page-number                   | 477      |
| pushToTag                           | 693      |

## Q

|                     |               |
|---------------------|---------------|
| quotedCueEventTypes | 184           |
| quotedEventTypes    | 184           |
| quoteDuring         | 183, 185, 693 |

## R

|                             |                    |
|-----------------------------|--------------------|
| r                           | 49                 |
| R                           | 52                 |
| ragged-bottom               | 471                |
| ragged-last                 | 474, 507           |
| ragged-last-bottom          | 471                |
| ragged-right                | 474, 507           |
| raise                       | 215                |
| relative                    | 2, 4, 12, 288, 693 |
| removeWithTag               | 693                |
| repeatCommands              | 133                |
| repeatTie                   | 46                 |
| resetRelativeOctave         | 693                |
| rest                        | 49                 |
| retrograde                  | 13, 693            |
| revertTimeSignatureSettings | 693                |
| rfz                         | 107                |
| rgb-color                   | 196                |
| RhythmicStaff               | 162                |
| right-align                 | 214                |
| right-margin                | 474                |
| rightHandFinger             | 340, 693           |
| rounded-box                 | 217                |

## S

|                      |             |
|----------------------|-------------|
| s                    | 51          |
| sacredHarpHeads      | 35          |
| sacredHarpHeadsMinor | 35          |
| scaleDurations       | 45, 66, 693 |
| score-markup-spacing | 473         |
| score-system-spacing | 473         |
| self-alignment-X     | 488         |
| set                  | 74          |
| set-octavation       | 20          |
| settingsFrom         | 693         |
| sf                   | 107         |
| sff                  | 107         |
| sfz                  | 107         |
| shiftDurations       | 693         |
| shiftOff             | 150         |
| shiftOn              | 150         |
| shiftOnn             | 150         |
| shiftOnnn            | 150         |
| short-indent         | 180, 475    |
| show-available-fonts | 225         |
| showFirstLength      | 456         |
| showKeySignature     | 358         |
| showLastLength       | 456         |
| showStaffSwitch      | 289         |
| skip                 | 51, 693     |
| skipTypesetting      | 456         |
| slashChordSeparator  | 377         |
| slashedGrace         | 693         |
| slurDashed           | 114         |
| slurDashPattern      | 115, 693    |
| slurDotted           | 114         |
| slurDown             | 114         |

|                           |               |
|---------------------------|---------------|
| slurHalfDashed            | 115           |
| slurHalfSolid             | 115           |
| slurNeutral               | 114           |
| slurSolid                 | 114           |
| slurUp                    | 115           |
| small                     | 191, 214      |
| smaller                   | 212, 214      |
| sostenutoOff              | 292           |
| sostenutoOn               | 292           |
| southernHarmonyHeads      | 35            |
| southernHarmonyHeadsMinor | 35            |
| sp                        | 107           |
| spacing                   | 504           |
| spacingTweaks             | 693           |
| spp                       | 107           |
| staff-affinity            | 488           |
| staff-staff-spacing       | 488           |
| Staff_midiInstrument      | 459           |
| Staff_symbol_engraver     | 176           |
| staffgroup-staff-spacing  | 488           |
| start-repeat              | 133           |
| startGroup                | 201           |
| startStaff                | 169, 172      |
| startTrillSpan            | 125           |
| Stem                      | 290           |
| stem-spacing-correction   | 504           |
| stemDown                  | 197           |
| stemLeftBeamCount         | 82            |
| stemNeutral               | 197           |
| stemRightBeamCount        | 82            |
| stemUp                    | 197           |
| stopGroup                 | 201           |
| stopStaff                 | 169, 172, 176 |
| stopTrillSpan             | 125           |
| storePredefinedDiagram    | 331, 693      |
| stringTuning              | 315, 694      |
| stringTunings             | 315, 327      |
| styledNoteHeads           | 694           |
| sub                       | 213           |
| suggestAccidentals        | 397           |
| super                     | 213           |
| sus                       | 372           |
| sustainOff                | 292           |
| sustainOn                 | 292           |
| system-count              | 476           |
| system-separator-markup   | 477           |
| system-system-spacing     | 473           |
| systems-per-page          | 476           |

## T

|                    |          |
|--------------------|----------|
| tabChordRepeats    | 694      |
| tabChordRepetition | 694      |
| TabStaff           | 162, 303 |
| TabVoice           | 303      |
| tag                | 694      |
| taor               | 358      |
| teaching           | 27       |
| teeny              | 191, 214 |
| tempo              | 61       |
| text               | 292      |
| textLengthOff      | 54, 203  |
| textLengthOn       | 54, 203  |
| textSpannerDown    | 204      |

textSpannerNeutral..... 204  
 textSpannerUp..... 204  
 thumb..... 192  
 tieDashed..... 47  
 tieDashPattern..... 694  
 tieDotted..... 47  
 tieDown..... 47  
 tieNeutral..... 47  
 tieSolid..... 47  
 tieUp..... 47  
 time..... 56, 74, 694  
 times..... 40, 66, 694  
 timeSignatureFraction..... 66  
 tiny..... 191, 214  
 tocItem..... 694  
 top-margin..... 471  
 top-markup-spacing..... 473  
 top-system-spacing..... 473  
 translate..... 215  
 translate-scaled..... 215  
 transpose..... 4, 9, 12, 694  
 transposedCueDuring..... 188, 694  
 transposition..... 21, 183, 694  
 treCorde..... 292  
 tremolo..... 139  
 tremoloFlags..... 140  
 triangle..... 219  
 trill..... 125  
 tupletDown..... 41  
 tupletNeutral..... 41  
 TupletNumber..... 41  
 tupletNumberFormatFunction..... 41  
 tupletSpannerDuration..... 41  
 tupletUp..... 41  
 tweak..... 694  
 two-sided..... 475

type..... 528

## U

unaCorda..... 292  
 underline..... 212  
 unfold..... 135  
 unfoldRepeats..... 694  
 unHideNotes..... 194

## V

VaticanaStaff..... 162  
 VerticalAxisGroup..... 488  
 voice..... 22, 24  
 Voice..... 146  
 voiceOne..... 146  
 void..... 694

## W

walkerHeads..... 35  
 walkerHeadsMinor..... 35  
 whichBar..... 89  
 with-color..... 195  
 withMusicProperty..... 694  
 wordwrap..... 216  
 wordwrap-lines..... 222

## X

X-offset..... 488  
 x11-color..... 195, 196  
 xNote..... 694  
 xNotesOn..... 694

## Appendix F LilyPond index

In addition to all the LilyPond commands and keywords, this index lists musical terms and words which relate to each of them, with links to those sections of the manual which describe or discuss that topic. Each link is in two parts. The first part points to the exact location in the manual where the topic appears; the second part points to the start of the section of the manual where that topic is discussed.

|             |     |                                  |               |
|-------------|-----|----------------------------------|---------------|
| !           |     | ^                                |               |
| ! .....     | 5   | ^ .....                          | 371           |
| ,           |     | -                                |               |
| ' .....     | 1   | - .....                          | 234           |
| ,           |     | \                                |               |
| , .....     | 1   | \! .....                         | 107           |
| -           |     | \( .....                         | 117           |
| - .....     | 105 | \) .....                         | 117           |
| .           |     | \< .....                         | 107           |
| . .....     | 39  | \> .....                         | 107           |
| /           |     | \abs-fontsize .....              | 609           |
| / .....     | 372 | \accent .....                    | 105           |
| /+ .....    | 372 | \accepts .....                   | 528, 529      |
| :           |     | \acciaccatura .....              | 97            |
| : .....     | 140 | \accidentalStyle .....           | 22            |
| <           |     | \addChordShape .....             | 331           |
| < .....     | 142 | \addInstrumentDefinition .....   | 182, 189      |
| <...> ..... | 142 | \addlyrics .....                 | 228, 230, 231 |
| =           |     | \addQuote .....                  | 183           |
| = .....     | 8   | \aeolian .....                   | 19            |
| >           |     | \afterGrace .....                | 98            |
| > .....     | 142 | \aikenHeads .....                | 35            |
| ?           |     | \aikenHeadsMinor .....           | 35            |
| ? .....     | 5   | \alias .....                     | 528           |
| [           |     | \allowPageTurn .....             | 484           |
| [ .....     | 82  | \alternative .....               | 127           |
| ]           |     | \appendToTag .....               | 450           |
| ] .....     | 82  | \appoggiatura .....              | 97            |
|             |     | \arpeggio .....                  | 122           |
|             |     | \arpeggioArrowDown .....         | 122           |
|             |     | \arpeggioArrowUp .....           | 122           |
|             |     | \arpeggioBracket .....           | 122           |
|             |     | \arpeggioNormal .....            | 122           |
|             |     | \arpeggioParenthesis .....       | 122           |
|             |     | \arpeggioParenthesisDashed ..... | 122           |
|             |     | \arrow-head .....                | 219           |
|             |     | \arrow-head .....                | 632           |
|             |     | \ascendens .....                 | 403, 410      |
|             |     | \auctum .....                    | 403, 410      |
|             |     | \augmentum .....                 | 410           |
|             |     | \auto-footnote .....             | 645           |
|             |     | \autoBeamOff .....               | 72            |
|             |     | \autoBeamOn .....                | 72            |
|             |     | \autochange .....                | 288           |
|             |     | \backslashed-digit .....         | 646           |
|             |     | \balloonGrobText .....           | 198           |
|             |     | \balloonLengthOff .....          | 198           |
|             |     | \balloonLengthOn .....           | 198           |
|             |     | \balloonText .....               | 198           |
|             |     | \bar .....                       | 85, 89        |

|                                          |               |                                          |          |
|------------------------------------------|---------------|------------------------------------------|----------|
| <code>\barNumberCheck</code> .....       | 95            | <code>\dotsDown</code> .....             | 39       |
| <code>\beam</code> .....                 | 632           | <code>\dotsNeutral</code> .....          | 39       |
| <code>\bendAfter</code> .....            | 119           | <code>\dotsUp</code> .....               | 39       |
| <code>\bold</code> .....                 | 212, 609      | <code>\doubleflat</code> .....           | 638      |
| <code>\book</code> .....                 | 423, 426      | <code>\doublesharp</code> .....          | 638      |
| <code>\bookOutputName</code> .....       | 425           | <code>\downbow</code> .....              | 105      |
| <code>\bookOutputSuffix</code> .....     | 425           | <code>\downbow</code> .....              | 298      |
| <code>\bookpart</code> .....             | 424, 426      | <code>\downmordent</code> .....          | 105      |
| <code>\bookpart</code> .....             | 482           | <code>\downprall</code> .....            | 105      |
| <code>\box</code> .....                  | 217, 609      | <code>\draw-circle</code> .....          | 219      |
| <code>\bracket</code> .....              | 112, 217, 633 | <code>\draw-circle</code> .....          | 633      |
| <code>\break</code> .....                | 482           | <code>\draw-hline</code> .....           | 633      |
| <code>\breathe</code> .....              | 118           | <code>\draw-line</code> .....            | 219      |
| <code>\breve</code> .....                | 38            | <code>\draw-line</code> .....            | 634      |
| <code>\breve</code> .....                | 49            | <code>\drummode</code> .....             | 162      |
| <code>\cadenzaOff</code> .....           | 64            | <code>\dynamic</code> .....              | 112, 610 |
| <code>\cadenzaOn</code> .....            | 64            | <code>\dynamicDown</code> .....          | 109      |
| <code>\caesura</code> .....              | 402           | <code>\dynamicNeutral</code> .....       | 109      |
| <code>\caps</code> .....                 | 610           | <code>\dynamicUp</code> .....            | 109      |
| <code>\cavum</code> .....                | 403, 410      | <code>\easyHeadsOff</code> .....         | 33       |
| <code>\center-align</code> .....         | 214, 618      | <code>\easyHeadsOn</code> .....          | 33       |
| <code>\center-column</code> .....        | 216, 618      | <code>\epsfile</code> .....              | 219      |
| <code>\change</code> .....               | 286           | <code>\epsfile</code> .....              | 634      |
| <code>\char</code> .....                 | 646           | <code>\espressivo</code> .....           | 105      |
| <code>\chordmode</code> .....            | 4, 12, 328    | <code>\espressivo</code> .....           | 108      |
| <code>\chordRepeats</code> .....         | 305           | <code>\expandFullBarRests</code> .....   | 53, 54   |
| <code>\chords</code> .....               | 374           | <code>\eyeglasses</code> .....           | 646      |
| <code>\circle</code> .....               | 217, 633      | <code>\f</code> .....                    | 107      |
| <code>\clef</code> .....                 | 15            | <code>\featherDurations</code> .....     | 84       |
| <code>\cm</code> .....                   | 544           | <code>\fermata</code> .....              | 105      |
| <code>\coda</code> .....                 | 105           | <code>\fermataMarkup</code> .....        | 53, 54   |
| <code>\column</code> .....               | 216, 618      | <code>\fermataMarkup</code> .....        | 105      |
| <code>\column-lines</code> .....         | 651           | <code>\ff</code> .....                   | 107      |
| <code>\combine</code> .....              | 219           | <code>\fff</code> .....                  | 107      |
| <code>\combine</code> .....              | 619           | <code>\ffff</code> .....                 | 107      |
| <code>\compoundMeter</code> .....        | 68            | <code>\fffff</code> .....                | 107      |
| <code>\compressFullBarRests</code> ..... | 53, 54        | <code>\fill-line</code> .....            | 216, 620 |
| <code>\concat</code> .....               | 619           | <code>\fill-with-pattern</code> .....    | 620      |
| <code>\consists</code> .....             | 528           | <code>\filled-box</code> .....           | 219      |
| <code>\context</code> .....              | 521           | <code>\filled-box</code> .....           | 634      |
| <code>\cr</code> .....                   | 107           | <code>\finalis</code> .....              | 402      |
| <code>\cresc</code> .....                | 108           | <code>\finger</code> .....               | 192      |
| <code>\crescHairpin</code> .....         | 109           | <code>\finger</code> .....               | 610      |
| <code>\crescTextCresc</code> .....       | 109           | <code>\flageolet</code> .....            | 105      |
| <code>\cueClef</code> .....              | 185           | <code>\flat</code> .....                 | 638      |
| <code>\cueDuring</code> .....            | 185           | <code>\flexa</code> .....                | 410      |
| <code>\cueDuringWithClef</code> .....    | 185           | <code>\fontCaps</code> .....             | 610      |
| <code>\customTabClef</code> .....        | 638           | <code>\fontsize</code> .....             | 212, 611 |
| <code>\decr</code> .....                 | 107           | <code>\footnote</code> .....             | 646      |
| <code>\decresc</code> .....              | 108           | <code>\fp</code> .....                   | 107      |
| <code>\defaultTimeSignature</code> ..... | 57            | <code>\fraction</code> .....             | 646      |
| <code>\deminutum</code> .....            | 403, 410      | <code>\frenchChords</code> .....         | 378      |
| <code>\denies</code> .....               | 528, 529      | <code>\fret-diagram</code> .....         | 319, 642 |
| <code>\descendens</code> .....           | 403, 410      | <code>\fret-diagram-terse</code> .....   | 320, 642 |
| <code>\dim</code> .....                  | 108           | <code>\fret-diagram-verbose</code> ..... | 322, 643 |
| <code>\dimHairpin</code> .....           | 109           | <code>\fromproperty</code> .....         | 647      |
| <code>\dimTextDecr</code> .....          | 109           | <code>\funkHeads</code> .....            | 35       |
| <code>\dimTextDecresc</code> .....       | 109           | <code>\funkHeadsMinor</code> .....       | 35       |
| <code>\dimTextDim</code> .....           | 109           | <code>\general-align</code> .....        | 215, 621 |
| <code>\dir-column</code> .....           | 619           | <code>\germanChords</code> .....         | 378      |
| <code>\displayLilyMusic</code> .....     | 467           | <code>\glissando</code> .....            | 120      |
| <code>\divisioMaior</code> .....         | 402           | <code>\grace</code> .....                | 97       |
| <code>\divisioMaxima</code> .....        | 402           | <code>\halfopen</code> .....             | 105      |
| <code>\divisioMinima</code> .....        | 402           | <code>\halign</code> .....               | 214, 622 |
| <code>\dorian</code> .....               | 19            | <code>\harmonic</code> .....             | 299      |



|                                           |               |                                                   |               |
|-------------------------------------------|---------------|---------------------------------------------------|---------------|
| <code>\harmonic</code> .....              | 307           | <code>\markuplist</code> .....                    | 209           |
| <code>\harmonicByFret</code> .....        | 307           | <code>\markuplist</code> .....                    | 222           |
| <code>\harmonicByRatio</code> .....       | 307           | <code>\markuplist</code> .....                    | 223           |
| <code>\harmonicsOff</code> .....          | 299           | <code>\maxima</code> .....                        | 38            |
| <code>\harmonicsOn</code> .....           | 299           | <code>\maxima</code> .....                        | 49            |
| <code>\harp-pedal</code> .....            | 644           | <code>\medium</code> .....                        | 612           |
| <code>\hbracket</code> .....              | 217, 635      | <code>\melisma</code> .....                       | 234           |
| <code>\hcenter-in</code> .....            | 623           | <code>\melismaEnd</code> .....                    | 234           |
| <code>\header</code> .....                | 426           | <code>\mergeDifferentlyDottedOff</code> .....     | 150           |
| <code>\hideKeySignature</code> .....      | 358           | <code>\mergeDifferentlyDottedOn</code> .....      | 150           |
| <code>\hideNotes</code> .....             | 194           | <code>\mergeDifferentlyHeadedOff</code> .....     | 150           |
| <code>\hideSplitTiedTabNotes</code> ..... | 306           | <code>\mergeDifferentlyHeadedOn</code> .....      | 150           |
| <code>\hideStaffSwitch</code> .....       | 289           | <code>\mf</code> .....                            | 107           |
| <code>\hspace</code> .....                | 623           | <code>\midi</code> .....                          | 426           |
| <code>\huge</code> .....                  | 191, 214, 611 | <code>\minor</code> .....                         | 19            |
| <code>\improvisationOff</code> .....      | 37            | <code>\mixolydian</code> .....                    | 19            |
| <code>\improvisationOff</code> .....      | 70            | <code>\mm</code> .....                            | 544           |
| <code>\improvisationOn</code> .....       | 37            | <code>\modalInversion</code> .....                | 14            |
| <code>\improvisationOn</code> .....       | 70            | <code>\modalTranspose</code> .....                | 13            |
| <code>\in</code> .....                    | 544           | <code>\mordent</code> .....                       | 105           |
| <code>\inclinatum</code> .....            | 403, 410      | <code>\mp</code> .....                            | 107           |
| <code>\include</code> .....               | 448           | <code>\musicglyph</code> .....                    | 96, 639       |
| <code>\instrumentSwitch</code> .....      | 182           | <code>\name</code> .....                          | 528           |
| <code>\inversion</code> .....             | 12            | <code>\natural</code> .....                       | 639           |
| <code>\ionian</code> .....                | 19            | <code>\new</code> .....                           | 521           |
| <code>\italianChords</code> .....         | 378           | <code>\noBeam</code> .....                        | 82            |
| <code>\italic</code> .....                | 212, 611      | <code>\noBreak</code> .....                       | 482           |
| <code>\justified-lines</code> .....       | 222           | <code>\noPageBreak</code> .....                   | 483           |
| <code>\justified-lines</code> .....       | 652           | <code>\noPageTurn</code> .....                    | 484           |
| <code>\justify</code> .....               | 216, 624      | <code>\normal-size-sub</code> .....               | 612           |
| <code>\justify-field</code> .....         | 624           | <code>\normal-size-super</code> .....             | 613           |
| <code>\justify-string</code> .....        | 625           | <code>\normal-text</code> .....                   | 613           |
| <code>\keepWithTag</code> .....           | 450           | <code>\normalsize</code> .....                    | 191, 214, 613 |
| <code>\key</code> .....                   | 19, 35        | <code>\note</code> .....                          | 639           |
| <code>\killCues</code> .....              | 189           | <code>\note-by-number</code> .....                | 639           |
| <code>\label</code> .....                 | 446           | <code>\null</code> .....                          | 215, 648      |
| <code>\laissezVibrer</code> .....         | 47            | <code>\number</code> .....                        | 613           |
| <code>\large</code> .....                 | 191, 214, 611 | <code>\numericTimeSignature</code> .....          | 57            |
| <code>\larger</code> .....                | 212, 214, 611 | <code>\octaveCheck</code> .....                   | 8             |
| <code>\layout</code> .....                | 426, 478      | <code>\on-the-fly</code> .....                    | 648           |
| <code>\left-align</code> .....            | 214, 625      | <code>\once</code> .....                          | 535           |
| <code>\left-brace</code> .....            | 647           | <code>\once</code> .....                          | 537           |
| <code>\left-column</code> .....           | 626           | <code>\oneVoice</code> .....                      | 146           |
| <code>\lheel</code> .....                 | 105           | <code>\open</code> .....                          | 105           |
| <code>\line</code> .....                  | 626           | <code>\open</code> .....                          | 298           |
| <code>\linea</code> .....                 | 403, 410      | <code>\oriscus</code> .....                       | 403, 410      |
| <code>\lineprall</code> .....             | 105           | <code>\ottava</code> .....                        | 20            |
| <code>\locrian</code> .....               | 19            | <code>\override</code> .....                      | 536, 648      |
| <code>\longa</code> .....                 | 38            | <code>\override in \lyricmode</code> .....        | 227           |
| <code>\longa</code> .....                 | 49            | <code>\override-lines</code> .....                | 652           |
| <code>\longfermata</code> .....           | 105           | <code>\overrideTimeSignatureSettings</code> ..... | 57            |
| <code>\lookup</code> .....                | 647           | <code>\p</code> .....                             | 107           |
| <code>\lower</code> .....                 | 215, 626      | <code>\pad-around</code> .....                    | 218, 626      |
| <code>\ltoe</code> .....                  | 105           | <code>\pad-markup</code> .....                    | 218, 627      |
| <code>\lydian</code> .....                | 19            | <code>\pad-to-box</code> .....                    | 218, 627      |
| <code>\lyricmode</code> .....             | 227, 228      | <code>\pad-x</code> .....                         | 218, 627      |
| <code>\lyricsto</code> .....              | 228, 230      | <code>\page-link</code> .....                     | 649           |
| <code>\magnify</code> .....               | 212, 612      | <code>\page-ref</code> .....                      | 446, 649      |
| <code>\major</code> .....                 | 19            | <code>\pageBreak</code> .....                     | 483           |
| <code>\makeClusters</code> .....          | 145           | <code>\pageTurn</code> .....                      | 484           |
| <code>\marcato</code> .....               | 105           | <code>\paper</code> .....                         | 426, 470      |
| <code>\mark</code> .....                  | 95, 205       | <code>\parallelMusic</code> .....                 | 159           |
| <code>\markalphabet</code> .....          | 648           | <code>\parenthesize</code> .....                  | 196, 635      |
| <code>\markletter</code> .....            | 648           | <code>\partcombine</code> .....                   | 154           |
| <code>\markup</code> .....                | 205, 209, 210 | <code>\partcombineApart</code> .....              | 155           |

|                                                 |               |                                               |               |
|-------------------------------------------------|---------------|-----------------------------------------------|---------------|
| <code>\partcombineAutomatic</code> .....        | 155           | <code>\sacredHarpHeads</code> .....           | 35            |
| <code>\partcombineChords</code> .....           | 155           | <code>\sacredHarpHeadsMinor</code> .....      | 35            |
| <code>\partcombineSoloI</code> .....            | 155           | <code>\sans</code> .....                      | 614           |
| <code>\partcombineSoloII</code> .....           | 155           | <code>\scale</code> .....                     | 637           |
| <code>\partcombineUnisono</code> .....          | 155           | <code>\scaleDurations</code> .....            | 45, 66        |
| <code>\partial</code> .....                     | 63, 127, 129  | <code>\score</code> .....                     | 422, 426, 640 |
| <code>\path</code> .....                        | 636           | <code>\segno</code> .....                     | 105           |
| <code>\pattern</code> .....                     | 649           | <code>\semiflat</code> .....                  | 641           |
| <code>\pes</code> .....                         | 410           | <code>\semiGermanChords</code> .....          | 378           |
| <code>\phrasingSlurDashed</code> .....          | 117           | <code>\semisharp</code> .....                 | 641           |
| <code>\phrasingSlurDashPattern</code> .....     | 117           | <code>\sesquiflat</code> .....                | 641           |
| <code>\phrasingSlurDotted</code> .....          | 117           | <code>\sesquisharp</code> .....               | 641           |
| <code>\phrasingSlurDown</code> .....            | 117           | <code>\set</code> .....                       | 74, 534       |
| <code>\phrasingSlurHalfDashed</code> .....      | 117           | <code>\sf</code> .....                        | 107           |
| <code>\phrasingSlurHalfSolid</code> .....       | 117           | <code>\sff</code> .....                       | 107           |
| <code>\phrasingSlurNeutral</code> .....         | 117           | <code>\sfz</code> .....                       | 107           |
| <code>\phrasingSlurSolid</code> .....           | 117           | <code>\sharp</code> .....                     | 641           |
| <code>\phrasingSlurUp</code> .....              | 117           | <code>\shiftOff</code> .....                  | 150           |
| <code>\phrygian</code> .....                    | 19            | <code>\shiftOn</code> .....                   | 150           |
| <code>\pitchedTrill</code> .....                | 126           | <code>\shiftOnn</code> .....                  | 150           |
| <code>\portato</code> .....                     | 105           | <code>\shiftOnnn</code> .....                 | 150           |
| <code>\postscript</code> .....                  | 219           | <code>\shortfermata</code> .....              | 105           |
| <code>\postscript</code> .....                  | 636           | <code>\showKeySignature</code> .....          | 358           |
| <code>\powerChords</code> .....                 | 343           | <code>\showStaffSwitch</code> .....           | 289           |
| <code>\pp</code> .....                          | 107           | <code>\signumcongruentiae</code> .....        | 105           |
| <code>\ppp</code> .....                         | 107           | <code>\simple</code> .....                    | 614           |
| <code>\pppp</code> .....                        | 107           | <code>\skip</code> .....                      | 51, 249       |
| <code>\ppppp</code> .....                       | 107           | <code>\slashed-digit</code> .....             | 650           |
| <code>\prall</code> .....                       | 105           | <code>\slashedGrace</code> .....              | 97            |
| <code>\pralldown</code> .....                   | 105           | <code>\slurDashed</code> .....                | 114           |
| <code>\prallmordent</code> .....                | 105           | <code>\slurDashPattern</code> .....           | 115           |
| <code>\prallprall</code> .....                  | 105           | <code>\slurDotted</code> .....                | 114           |
| <code>\prallup</code> .....                     | 105           | <code>\slurDown</code> .....                  | 114           |
| <code>\predefinedFretboardsOff</code> .....     | 338           | <code>\slurHalfDashed</code> .....            | 115           |
| <code>\predefinedFretboardsOn</code> .....      | 338           | <code>\slurHalfSolid</code> .....             | 115           |
| <code>\property-recursive</code> .....          | 649           | <code>\slurNeutral</code> .....               | 114           |
| <code>\pt</code> .....                          | 544           | <code>\slurSolid</code> .....                 | 114           |
| <code>\pushToTag</code> .....                   | 450           | <code>\slurUp</code> .....                    | 115           |
| <code>\put-adjacent</code> .....                | 628           | <code>\small</code> .....                     | 191, 214, 615 |
| <code>\quilisma</code> .....                    | 403, 410      | <code>\smallCaps</code> .....                 | 615           |
| <code>\quoteDuring</code> .....                 | 183, 185      | <code>\smaller</code> .....                   | 212, 214, 615 |
| <code>\raise</code> .....                       | 215, 628      | <code>\snappizzicato</code> .....             | 105           |
| <code>\relative</code> .....                    | 2, 4, 12, 288 | <code>\sostenutoOff</code> .....              | 292           |
| <code>\RemoveEmptyStaves</code> .....           | 176, 177      | <code>\sostenutoOn</code> .....               | 292           |
| <code>\removeWithTag</code> .....               | 450           | <code>\southernHarmonyHeads</code> .....      | 35            |
| <code>\repeat</code> .....                      | 127           | <code>\southernHarmonyHeadsMinor</code> ..... | 35            |
| <code>\repeat percent</code> .....              | 137           | <code>\sp</code> .....                        | 107           |
| <code>\repeat tremolo</code> .....              | 139           | <code>\spp</code> .....                       | 107           |
| <code>\repeatTie</code> .....                   | 46, 130, 250  | <code>\staccatissimo</code> .....             | 105           |
| <code>\replace</code> .....                     | 614           | <code>\staccato</code> .....                  | 105           |
| <code>\rest</code> .....                        | 49            | <code>\startGroup</code> .....                | 201           |
| <code>\retrograde</code> .....                  | 13            | <code>\startStaff</code> .....                | 169, 172      |
| <code>\reverseturn</code> .....                 | 105           | <code>\startTrillSpan</code> .....            | 125           |
| <code>\revert</code> .....                      | 537           | <code>\stemDown</code> .....                  | 197           |
| <code>\revertTimeSignatureSettings</code> ..... | 58            | <code>\stemNeutral</code> .....               | 197           |
| <code>\rfz</code> .....                         | 107           | <code>\stemUp</code> .....                    | 197           |
| <code>\rheel</code> .....                       | 105           | <code>\stencil</code> .....                   | 650           |
| <code>\right-align</code> .....                 | 214, 628      | <code>\stopGroup</code> .....                 | 201           |
| <code>\right-brace</code> .....                 | 649           | <code>\stopped</code> .....                   | 105           |
| <code>\right-column</code> .....                | 628           | <code>\stopStaff</code> .....                 | 169, 172, 176 |
| <code>\rightHandFinger</code> .....             | 340           | <code>\stopTrillSpan</code> .....             | 125           |
| <code>\roman</code> .....                       | 614           | <code>\storePredefinedDiagram</code> .....    | 331           |
| <code>\rotate</code> .....                      | 629           | <code>\stringTuning</code> .....              | 315           |
| <code>\rounded-box</code> .....                 | 217, 637      | <code>\strophia</code> .....                  | 403, 410      |
| <code>\rtoe</code> .....                        | 105           | <code>\strut</code> .....                     | 650           |

|                                         |               |                                                  |          |
|-----------------------------------------|---------------|--------------------------------------------------|----------|
| <code>\sub</code> .....                 | 213, 615      | <code>\voiceNeutralStyle</code> .....            | 149      |
| <code>\super</code> .....               | 213, 616      | <code>\voiceOne</code> .....                     | 146      |
| <code>\sustainOff</code> .....          | 292           | <code>\voiceOne ... \voiceFour</code> .....      | 146      |
| <code>\sustainOn</code> .....           | 292           | <code>\voiceOneStyle</code> .....                | 149      |
| <code>\tabChordRepeats</code> .....     | 305           | <code>\voiceThreeStyle</code> .....              | 149      |
| <code>\tabFullNotation</code> .....     | 303           | <code>\voiceTwoStyle</code> .....                | 149      |
| <code>\table-of-contents</code> .....   | 447, 652      | <code>\void</code> .....                         | 467      |
| <code>\tag</code> .....                 | 450           | <code>\vspace</code> .....                       | 630      |
| <code>\taor</code> .....                | 358           | <code>\walkerHeads</code> .....                  | 35       |
| <code>\teeny</code> .....               | 191, 214, 616 | <code>\walkerHeadsMinor</code> .....             | 35       |
| <code>\tempo</code> .....               | 61            | <code>\whiteout</code> .....                     | 651      |
| <code>\tenuto</code> .....              | 105           | <code>\with</code> .....                         | 525      |
| <code>\text</code> .....                | 616           | <code>\with-color</code> .....                   | 195, 651 |
| <code>\textLengthOff</code> .....       | 54, 203       | <code>\with-dimensions</code> .....              | 651      |
| <code>\textLengthOn</code> .....        | 54, 203       | <code>\with-link</code> .....                    | 651      |
| <code>\textSpannerDown</code> .....     | 204           | <code>\with-url</code> .....                     | 638      |
| <code>\textSpannerNeutral</code> .....  | 204           | <code>\woodwind-diagram</code> .....             | 644      |
| <code>\textSpannerUp</code> .....       | 204           | <code>\wordwrap</code> .....                     | 216, 631 |
| <code>\thumb</code> .....               | 105, 192      | <code>\wordwrap-field</code> .....               | 630      |
| <code>\tied-lyric</code> .....          | 641           | <code>\wordwrap-internal</code> .....            | 652      |
| <code>\tieDashed</code> .....           | 47            | <code>\wordwrap-lines</code> .....               | 222      |
| <code>\tieDotted</code> .....           | 47            | <code>\wordwrap-lines</code> .....               | 652      |
| <code>\tieDown</code> .....             | 47            | <code>\wordwrap-string</code> .....              | 631      |
| <code>\tieNeutral</code> .....          | 47            | <code>\wordwrap-string-internal</code> .....     | 652      |
| <code>\tieSolid</code> .....            | 47            |                                                  |          |
| <code>\tieUp</code> .....               | 47            |                                                  |          |
| <code>\time</code> .....                | 56, 74        | .....                                            | 94, 95   |
| <code>\times</code> .....               | 40, 66        | ~                                                |          |
| <code>\tiny</code> .....                | 191, 214, 617 | ~ .....                                          | 46       |
| <code>\tocItem</code> .....             | 447           |                                                  |          |
| <code>\translate</code> .....           | 215, 629      | <b>1</b>                                         |          |
| <code>\translate-scaled</code> .....    | 215, 629      | 15ma .....                                       | 20       |
| <code>\transparent</code> .....         | 650           |                                                  |          |
| <code>\transpose</code> .....           | 4, 9, 12      | <b>8</b>                                         |          |
| <code>\transposedCueDuring</code> ..... | 188           | 8va .....                                        | 20       |
| <code>\transposition</code> .....       | 21, 183       | 8ve .....                                        | 20       |
| <code>\treCorde</code> .....            | 292           |                                                  |          |
| <code>\triangle</code> .....            | 219           | <b>A</b>                                         |          |
| <code>\triangle</code> .....            | 638           | a due part .....                                 | 154      |
| <code>\trill</code> .....               | 105           | absolute.....                                    | 1        |
| <code>\trill</code> .....               | 125           | absolute dynamics .....                          | 107      |
| <code>\tupletDown</code> .....          | 41            | absolute octave entry.....                       | 1        |
| <code>\tupletNeutral</code> .....       | 41            | absolute octave specification.....               | 1        |
| <code>\tupletUp</code> .....            | 41            | accelerando in MIDI .....                        | 461      |
| <code>\turn</code> .....                | 105           | accent.....                                      | 105, 654 |
| <code>\tweak</code> .....               | 538           | accentus .....                                   | 654      |
| <code>\type</code> .....                | 528           | <b>accepts</b> .....                             | 528      |
| <code>\typewriter</code> .....          | 617           | acciaccatura .....                               | 97       |
| <code>\unaCorda</code> .....            | 292           | <b>acciaccatura</b> .....                        | 688      |
| <code>\underline</code> .....           | 212, 617      | acciaccatura, multi-note.....                    | 101      |
| <code>\unfoldRepeats</code> .....       | 462           | accidental.....                                  | 5        |
| <code>\unHideNotes</code> .....         | 194           | accidental on tied note .....                    | 5        |
| <code>\unset</code> .....               | 535           | accidental style .....                           | 22       |
| <code>\upbow</code> .....               | 105           | accidental style, cautionary, modern voice ..... | 25       |
| <code>\upbow</code> .....               | 298           | accidental style, default .....                  | 22, 24   |
| <code>\upmordent</code> .....           | 105           | accidental style, forget .....                   | 28       |
| <code>\upprall</code> .....             | 105           | accidental style, modern .....                   | 24, 25   |
| <code>\upright</code> .....             | 617           | accidental style, modern voice cautionary .....  | 25       |
| <code>\varcoda</code> .....             | 105           |                                                  |          |
| <code>\vcenter</code> .....             | 630           |                                                  |          |
| <code>\verbatim-file</code> .....       | 650           |                                                  |          |
| <code>\verylongfermata</code> .....     | 105           |                                                  |          |
| <code>\virga</code> .....               | 403, 410      |                                                  |          |
| <code>\virgula</code> .....             | 402           |                                                  |          |
| <code>\voiceFourStyle</code> .....      | 149           |                                                  |          |

|                                                     |               |
|-----------------------------------------------------|---------------|
| accidental style, modern-cautionary .....           | 24            |
| accidental style, neo-modern .....                  | 26            |
| accidental style, neo-modern-cautionary .....       | 26            |
| accidental style, neo-modern-voice .....            | 27            |
| accidental style, neo-modern-voice-cautionary ..... | 27            |
| accidental style, no reset .....                    | 27            |
| accidental style, piano .....                       | 26            |
| accidental style, piano cautionary .....            | 26            |
| accidental style, teaching .....                    | 27            |
| accidental style, voice .....                       | 24            |
| accidental style, voice, modern cautionary .....    | 25            |
| accidental, cautionary .....                        | 5             |
| Accidental, musica ficta .....                      | 397           |
| accidental, parenthesized .....                     | 5             |
| accidental, quarter-tone .....                      | 6             |
| accidental, reminder .....                          | 5             |
| accidentals .....                                   | 22, 397, 401  |
| accidentals and simultaneous notes .....            | 28            |
| accidentals in chords .....                         | 28            |
| accidentals, automatic .....                        | 22            |
| accidentals, modern .....                           | 25            |
| accidentals, modern cautionary style .....          | 25            |
| accidentals, modern style .....                     | 25            |
| accidentals, multivoice .....                       | 25            |
| accidentals, piano .....                            | 26            |
| accidentals, piano cautionary .....                 | 26            |
| accidentalStyle .....                               | 688           |
| accordion .....                                     | 293           |
| accordion discant symbols .....                     | 293           |
| accordion shift symbols .....                       | 293           |
| accordion shifts .....                              | 293           |
| addChordShape .....                                 | 331, 688      |
| adding a white background to text .....             | 651           |
| adding custom fret diagrams .....                   | 329           |
| addInstrumentDefinition .....                       | 182, 189, 688 |
| additionalPitchPrefix .....                         | 376           |
| additions, in chords .....                          | 371           |
| addQuote .....                                      | 183, 688      |
| adjusting staff symbol .....                        | 545           |
| aeolian .....                                       | 19            |
| afterGrace .....                                    | 98, 688       |
| afterGraceFraction .....                            | 659           |
| Aiken shape note heads .....                        | 35            |
| aikenHeads .....                                    | 35            |
| aikenHeadsMinor .....                               | 35            |
| al niente .....                                     | 110           |
| alias .....                                         | 528           |
| align to objects .....                              | 559           |
| aligning markup text .....                          | 214           |
| aligning markups .....                              | 214           |
| aligning text .....                                 | 214           |
| aligning to cadenza .....                           | 103           |
| alignment, text, commands .....                     | 217           |
| alist .....                                         | 657           |
| allowPageTurn .....                                 | 688           |
| altered chords .....                                | 370           |
| alternate endings .....                             | 127           |
| alternate endings, repeats .....                    | 135           |
| alternate repeats .....                             | 135           |
| alternative endings and lyrics .....                | 249           |
| alternative endings, with ties .....                | 130           |
| alternative melody, switching to .....              | 257           |
| alto clef .....                                     | 15            |
| Amazing Grace bagpipe example .....                 | 358           |
| ambitus .....                                       | 29            |
| anacrusis in a repeat .....                         | 129           |
| anacrusis .....                                     | 63            |
| analysis, musicological .....                       | 201           |
| ancient clef .....                                  | 15            |
| angled hairpins .....                               | 555           |
| annotate-spacing .....                              | 515           |
| anthems .....                                       | 262           |
| appendToTag .....                                   | 688           |
| applyContext .....                                  | 688           |
| applyMusic .....                                    | 688           |
| applyOutput .....                                   | 688           |
| appoggiatura .....                                  | 97            |
| appoggiatura .....                                  | 688           |
| Arabic key signatures .....                         | 417           |
| Arabic music .....                                  | 416           |
| Arabic music example .....                          | 419           |
| Arabic music template .....                         | 419           |
| Arabic note names .....                             | 416           |
| Arabic semi-flat symbol .....                       | 416           |
| Arabic time signatures .....                        | 418           |
| arpeggio .....                                      | 122           |
| arpeggio symbols, special .....                     | 122           |
| arpeggio, cross-staff parenthesis-style .....       | 125           |
| arpeggio, parenthesis-style, cross-staff .....      | 125           |
| arpeggioArrowDown .....                             | 122           |
| arpeggioArrowUp .....                               | 122           |
| arpeggioBracket .....                               | 122           |
| arpeggioNormal .....                                | 122           |
| arpeggioParenthesis .....                           | 122           |
| arpeggioParenthesisDashed .....                     | 122           |
| arrow-head .....                                    | 219           |
| Articulate scripts .....                            | 461           |
| articulation-event .....                            | 184           |
| articulations .....                                 | 105, 402      |
| articulations in MIDI .....                         | 461           |
| artificial harmonics .....                          | 299           |
| assertBeamQuant .....                               | 689           |
| assertBeamSlope .....                               | 689           |
| associatedVoice .....                               | 228           |
| associatedVoice .....                               | 230, 257      |
| association list .....                              | 657           |
| aug .....                                           | 369           |
| auto-first-page-number .....                        | 477           |
| autoBeaming .....                                   | 74            |
| autobeaming properties for time signatures .....    | 57            |
| autoBeamOff .....                                   | 72            |
| autoBeamOn .....                                    | 72            |
| autochange .....                                    | 288, 689      |
| autochange and relative music .....                 | 288           |
| automatic accidentals .....                         | 22            |
| automatic chord diagrams .....                      | 337           |
| automatic fret diagrams .....                       | 337           |
| automatic part combining .....                      | 154           |
| automatic staff changes .....                       | 288           |
| automaticBars .....                                 | 554           |
| available fonts, listing .....                      | 225           |
| <b>B</b>                                            |               |
| backslashed digits .....                            | 646           |
| bagpipe .....                                       | 358           |
| bagpipe example .....                               | 358           |
| balloon .....                                       | 198           |
| balloon help .....                                  | 198           |

|                                                         |             |
|---------------------------------------------------------|-------------|
| <b>Balloon_engraver</b> .....                           | 198         |
| <b>balloonGrobText</b> .....                            | 198, 689    |
| <b>balloonLengthOff</b> .....                           | 198         |
| <b>balloonLengthOn</b> .....                            | 198         |
| <b>balloonText</b> .....                                | 198, 689    |
| <b>banjo tablature</b> .....                            | 300         |
| <b>banjo tablatures</b> .....                           | 345         |
| <b>banjo tunings</b> .....                              | 345         |
| <b>banjo-c-tuning</b> .....                             | 345         |
| <b>banjo-modal-tuning</b> .....                         | 345         |
| <b>banjo-open-d-tuning</b> .....                        | 345         |
| <b>banjo-open-dm-tuning</b> .....                       | 345         |
| <b>bar</b> .....                                        | 85, 89, 689 |
| <b>bar check</b> .....                                  | 94          |
| <b>bar lines</b> .....                                  | 85          |
| <b>bar lines, closing</b> .....                         | 85          |
| <b>bar lines, default, changing</b> .....               | 89          |
| <b>bar lines, double</b> .....                          | 85          |
| <b>bar lines, invisible</b> .....                       | 86          |
| <b>bar lines, manual</b> .....                          | 86          |
| <b>bar lines, suppressing</b> .....                     | 554         |
| <b>bar lines, symbols on</b> .....                      | 205         |
| <b>bar lines, turning off</b> .....                     | 64          |
| <b>bar number</b> .....                                 | 103         |
| <b>bar number alignment</b> .....                       | 93          |
| <b>bar number check</b> .....                           | 94          |
| <b>bar number collision</b> .....                       | 94          |
| <b>bar number, format</b> .....                         | 91          |
| <b>bar numbering, turning off</b> .....                 | 64          |
| <b>bar numbers</b> .....                                | 90          |
| <b>bar numbers, regular spacing</b> .....               | 90          |
| <b>bar numbers, with letters</b> .....                  | 92          |
| <b>bar numbers, with repeats</b> .....                  | 92          |
| <b>barCheckSynchronize</b> .....                        | 94          |
| <b>baritone clef</b> .....                              | 15          |
| <b>BarNumber</b> .....                                  | 90          |
| <b>barNumberCheck</b> .....                             | 95, 689     |
| <b>barNumberVisibility</b> .....                        | 90          |
| <b>barre indications</b> .....                          | 318         |
| <b>Bartók pizzicato</b> .....                           | 300         |
| <b>bartype</b> .....                                    | 89          |
| <b>base-shortest-duration</b> .....                     | 504         |
| <b>baseMoment</b> .....                                 | 74          |
| <b>bass clef</b> .....                                  | 15          |
| <b>bass note, for chords</b> .....                      | 372         |
| <b>Bass, figured</b> .....                              | 381         |
| <b>Bass, thorough</b> .....                             | 381         |
| <b>Basso continuo</b> .....                             | 381         |
| <b>beam, endings in a score</b> .....                   | 80          |
| <b>beam, endings with multiple voices</b> .....         | 80          |
| <b>beamExceptions</b> .....                             | 74          |
| <b>beaming, time signature default properties</b> ..... | 57          |
| <b>beamlets, orienting</b> .....                        | 78          |
| <b>beams, \partcombine with \autoBeamOff</b> .....      | 73          |
| <b>beams, cross-staff</b> .....                         | 286         |
| <b>beams, customizing rules</b> .....                   | 72          |
| <b>beams, feathered</b> .....                           | 84          |
| <b>beams, in cadenzas</b> .....                         | 65          |
| <b>beams, in unmetered music</b> .....                  | 65          |
| <b>beams, line breaks</b> .....                         | 73          |
| <b>beams, manual</b> .....                              | 72, 82      |
| <b>beams, subdividing</b> .....                         | 78          |
| <b>beams, with knee gap</b> .....                       | 73          |
| <b>beams, with lyrics</b> .....                         | 74          |
| <b>beams, with melismata</b> .....                      | 73          |

|                                               |               |
|-----------------------------------------------|---------------|
| beams, with polymetric meters . . . . .       | 66            |
| beats per minute . . . . .                    | 61            |
| beats, grouping . . . . .                     | 79            |
| <b>beatStructure</b> . . . . .                | 74            |
| beginners' music . . . . .                    | 33            |
| <b>bendAfter</b> . . . . .                    | 119, 689      |
| Bézier curves, control points . . . . .       | 562           |
| binding gutter . . . . .                      | 475           |
| <b>binding-offset</b> . . . . .               | 475           |
| bisbiglando . . . . .                         | 296           |
| Bison . . . . .                               | 658           |
| <b>blank-after-score-page-force</b> . . . . . | 476           |
| <b>blank-last-page-force</b> . . . . .        | 476           |
| <b>blank-page-force</b> . . . . .             | 476           |
| BNF . . . . .                                 | 658           |
| <b>bold</b> . . . . .                         | 212           |
| <b>bookOutputName</b> . . . . .               | 689           |
| <b>bookOutputSuffix</b> . . . . .             | 689           |
| <b>bottom-margin</b> . . . . .                | 471           |
| bowing indications . . . . .                  | 298           |
| <b>box</b> . . . . .                          | 217           |
| brace, vertical . . . . .                     | 163           |
| braces, nesting of . . . . .                  | 166           |
| braces, various sizes . . . . .               | 223           |
| <b>bracket</b> . . . . .                      | 112, 217, 292 |
| bracket, horizontal . . . . .                 | 201           |
| bracket, phrasing . . . . .                   | 201           |
| bracket, vertical . . . . .                   | 163           |
| bracket, volta . . . . .                      | 133           |
| brackets . . . . .                            | 201           |
| brackets, angle . . . . .                     | 142           |
| brackets, nesting of . . . . .                | 166           |
| break-align-symbols . . . . .                 | 559           |
| break-visibility . . . . .                    | 551           |
| <b>breakable</b> . . . . .                    | 73            |
| breakbefore . . . . .                         | 431           |
| breaking lines . . . . .                      | 480           |
| breaking pages . . . . .                      | 507           |
| breaks in unmetred music . . . . .            | 65            |
| breath marks . . . . .                        | 118           |
| <b>breathe</b> . . . . .                      | 118, 689      |
| <b>breve</b> . . . . .                        | 38            |
| <b>breve</b> . . . . .                        | 49            |
| breve rest . . . . .                          | 49            |
| broken chord . . . . .                        | 122           |

## C

|                                         |         |
|-----------------------------------------|---------|
| C clef.....                             | 15      |
| cadenza.....                            | 64, 103 |
| cadenza line breaks.....                | 65      |
| cadenza page breaks.....                | 65      |
| cadenza, aligning to.....               | 103     |
| cadenza, with beams.....                | 65      |
| <b>cadenzaOff</b> .....                 | 64      |
| <b>cadenzaOn</b> .....                  | 64      |
| caesura.....                            | 119     |
| callback.....                           | 657     |
| capo.....                               | 322     |
| cautionary accidental.....              | 5       |
| cautionary accidental style, piano..... | 26      |
| cautionary accidentals, piano.....      | 26      |
| <b>center-align</b> .....               | 214     |
| <b>center-column</b> .....              | 216     |
| centered dynamics in piano music.....   | 286     |

|                                                        |            |                                                  |              |
|--------------------------------------------------------|------------|--------------------------------------------------|--------------|
| centering a column of text .....                       | 618        | clef, french .....                               | 15           |
| centering text on the page .....                       | 216        | clef, G .....                                    | 15           |
| <b>change</b> .....                                    | 286        | clef, mezzosoprano .....                         | 15           |
| changing direction of text columns .....               | 619        | clef, moderntab .....                            | 317          |
| changing fonts .....                                   | 212        | clef, percussion .....                           | 346          |
| changing instrument names .....                        | 181        | clef, soprano .....                              | 15           |
| changing properties .....                              | 534        | clef, subbass .....                              | 15           |
| changing staff automatically .....                     | 288        | clef, tab .....                                  | 317          |
| changing staff manually .....                          | 286        | clef, tenor .....                                | 15           |
| chants .....                                           | 273        | clef, transposing .....                          | 16           |
| character names .....                                  | 266        | clef, treble .....                               | 15           |
| <b>check-consistency</b> .....                         | 474        | clef, varbaritone .....                          | 15           |
| choir staff .....                                      | 163        | clef, violin .....                               | 15           |
| choral tenor clef .....                                | 16         | clef, visibility following explicit change ..... | 553          |
| chord chords .....                                     | 368        | clefs .....                                      | 393, 400     |
| chord diagrams .....                                   | 317, 327   | clefs, visibility of octavation .....            | 554          |
| chord diagrams, automatic .....                        | 337        | closing bar lines .....                          | 85           |
| chord glissandi .....                                  | 307        | closure .....                                    | 657          |
| chord inversions .....                                 | 372        | cluster .....                                    | 145          |
| chord mode .....                                       | 368        | coda .....                                       | 96, 105, 654 |
| chord names .....                                      | 368, 373   | coda on bar line .....                           | 205          |
| Chord names in MIDI .....                              | 461        | collision, bar number .....                      | 94           |
| chord names with fret diagrams .....                   | 328        | collisions .....                                 | 150          |
| chord quality .....                                    | 369        | collisions, clashing note columns .....          | 145          |
| chord shapes for fretted instruments .....             | 331        | collisions, cross-staff voices .....             | 287          |
| chord steps, altering .....                            | 371        | collisions, ignoring .....                       | 145, 154     |
| chord, broken .....                                    | 122        | <b>color</b> .....                               | 195          |
| chord, modifying one note in .....                     | 538        | color in chords .....                            | 196          |
| Chord, repetition .....                                | 143, 305   | color, rgb .....                                 | 196          |
| <b>chordChanges</b> .....                              | 374        | colored notes .....                              | 195          |
| <b>chordmode</b> .....                                 | 4, 12, 328 | colored notes in chords .....                    | 196          |
| <b>chordNameExceptions</b> .....                       | 377        | colored objects .....                            | 195          |
| <b>chordNameLowercaseMinor</b> .....                   | 376        | coloring notes .....                             | 195          |
| <b>ChordNames</b> .....                                | 328        | coloring objects .....                           | 195, 550     |
| <b>chordNameSeparator</b> .....                        | 376        | coloring text .....                              | 651          |
| <b>chordNoteNamer</b> .....                            | 376        | coloring voices .....                            | 149          |
| <b>chordPrefixSpacer</b> .....                         | 378        | colors .....                                     | 195          |
| <b>chordRepeats</b> .....                              | 689        | Colors, list of .....                            | 587          |
| <b>chordRootNamer</b> .....                            | 376        | <b>column</b> .....                              | 216          |
| chords .....                                           | 142, 373   | columns, text .....                              | 216          |
| chords and relative octave entry .....                 | 4          | <b>combine</b> .....                             | 219          |
| chords and ties .....                                  | 46         | combining parts .....                            | 154          |
| chords, accidentals in .....                           | 28         | comma intervals .....                            | 420          |
| chords, cross-staff .....                              | 290        | <b>common-shortest-duration</b> .....            | 504          |
| chords, fingering .....                                | 192        | <b>Completion_heads_engraver</b> .....           | 69           |
| chords, jazz .....                                     | 375        | <b>Completion_rest_engraver</b> .....            | 69           |
| chords, power .....                                    | 343        | compound time signatures .....                   | 68           |
| chords, relative pitch .....                           | 142        | <b>compoundMeter</b> .....                       | 689          |
| chords, splitting across staves with \autochange ..... | 289        | <b>compressFullBarRests</b> .....                | 53, 54       |
| chords, suppressing repeated .....                     | 374        | compressing music .....                          | 45           |
| Christian Harmony note heads .....                     | 35         | concatenating text .....                         | 619          |
| church modes .....                                     | 19         | condensing rests .....                           | 56           |
| church rest .....                                      | 54         | <b>consists</b> .....                            | 528          |
| <b>circle</b> .....                                    | 217        | Context, creating .....                          | 521          |
| circling text .....                                    | 633        | contexts, defining new .....                     | 528          |
| circulus .....                                         | 654        | contexts, keeping alive .....                    | 522          |
| clef .....                                             | 5          | contexts, layout order .....                     | 529          |
| <b>clef</b> .....                                      | 15, 689    | contexts, lifetime .....                         | 522          |
| clef, alto .....                                       | 15         | control pitch .....                              | 8            |
| clef, ancient .....                                    | 15         | control points, Bézier curves .....              | 562          |
| clef, baritone .....                                   | 15         | control points, tweaking .....                   | 539          |
| clef, bass .....                                       | 15         | controlling general text alignment .....         | 621          |
| clef, C .....                                          | 15         | <b>controlpitch</b> .....                        | 8            |
| clef, F .....                                          | 15         | copyright sign .....                             | 455          |
|                                                        |            | <b>cr</b> .....                                  | 107          |



creating contexts..... 522  
 creating empty text objects..... 648  
 creating horizontal spaces in text..... 623  
 creating text fractions..... 646  
 creating vertical spaces in text..... 630, 650  
**cresc**..... 108  
 crescendo..... 107  
 crescendo-event..... 184  
**crescHairpin**..... 109  
**crescTextCresc**..... 109  
**cross**..... 32  
 cross note heads..... 32  
 cross staff chords..... 290  
 cross staff line..... 289  
 cross staff notes..... 290  
 cross staff stems..... 290  
 cross-staff..... 289  
**cross-staff**..... 290  
 cross-staff beams..... 286  
 cross-staff chords..... 290  
 cross-staff collisions..... 287  
 cross-staff line..... 289  
 cross-staff notes..... 286, 290  
 cross-staff parenthesis-style arpeggio..... 125  
 cross-staff stems..... 290  
 cross-staff tremolo..... 141  
 cue notes..... 183, 185  
 cue notes, formatting..... 185  
 cue notes, removing..... 189  
**cueClef**..... 185, 689  
**cueClefUnset**..... 689  
**cueDuring**..... 185, 689  
**cueDuringWithClef**..... 185, 689  
 cues, musical..... 268  
**CueVoice**..... 185  
**currentBarNumber**..... 90  
**currentBarNumber**..... 103  
 custodes..... 391  
 custom fret diagrams..... 317  
 custom fret diagrams, adding..... 329  
 custom rehearsal mark..... 96  
 custom string tunings..... 315  
 customized fret diagram..... 324  
 customizing chord names..... 375  
 custos..... 391

## D

D.S. al Fine..... 96  
 dampened notes on fretted instruments..... 342  
 dashed phrasing slur..... 117  
 dashed slur..... 114  
 dashed ties..... 47  
**deadNote**..... 690  
 decorating text..... 217  
**decr**..... 107  
**decresc**..... 108  
 decrescendo..... 107  
**default**..... 22, 24  
 default accidental style..... 22, 24  
 default bar lines, changing..... 89  
 default note duration..... 39  
 default note names..... 5  
**default-staff-staff-spacing**..... 488  
**defaultBarType**..... 89

**defaultNoteHeads**..... 690  
**defaultTimeSignature**..... 57  
**denies**..... 528  
 diagram, fret, customized..... 324  
 diagrams, chord for fretted instruments..... 317  
 diagrams, fret..... 317  
 diagrams, fret, transposing..... 328  
 diamond note heads..... 32  
 diamond-shaped note heads..... 299  
**dim**..... 108, 369  
**dimHairpin**..... 109  
 diminuendo..... 107  
**dimTextDecr**..... 109  
**dimTextDecresc**..... 109  
**dimTextDim**..... 109  
 discant symbols, accordion..... 293  
**displayLilyMusic**..... 690  
**displayMusic**..... 690  
 distance between staves..... 488  
 distances, absolute..... 544  
 distances, scaled..... 544  
 divided lyrics..... 253  
 divisio..... 401  
 divisiones..... 401  
**dodecaphonic**..... 27  
 dodecaphonic accidental style..... 27  
 dodecaphonic style, neo-modern..... 27  
 doits..... 119  
**dorian**..... 19  
**dotsDown**..... 39  
**dotsNeutral**..... 39  
**dotsUp**..... 39  
 dotted notes..... 39  
 dotted phrasing slurs..... 117  
 dotted slur..... 114  
 dotted ties..... 47  
 double bar lines..... 85  
 double flat..... 5  
 double sharp..... 5  
 double time signatures..... 66  
 double-dotted notes..... 39  
 down bow indication..... 298  
 downbow..... 105, 654  
 downmordent..... 654  
 downprall..... 654  
**draw-circle**..... 219  
**draw-line**..... 219  
 drawing a line across a page..... 633  
 drawing beams within text..... 632  
 drawing boxes with rounded corners..... 634  
 drawing boxes with rounded corners around text..... 637  
 drawing circles within text..... 633  
 drawing graphic objects..... 217  
 drawing lines within text..... 634  
 drawing paths..... 636  
 drawing solid boxes within text..... 634  
 drawing staff symbol..... 545  
 drawing triangles within text..... 638  
 drum staff..... 162  
**drummode**..... 162  
 drums..... 346, 348  
**DrumStaff**..... 162  
 duration, default..... 39  
 durations, of notes..... 38

|                                            |     |
|--------------------------------------------|-----|
| durations, scaling .....                   | 44  |
| <b>dynamic</b> .....                       | 112 |
| dynamic marks, multiple on one note .....  | 108 |
| dynamic marks, new .....                   | 112 |
| dynamic-event .....                        | 184 |
| <b>dynamicDown</b> .....                   | 109 |
| <b>DynamicLineSpanner</b> .....            | 109 |
| <b>dynamicNeutral</b> .....                | 109 |
| dynamics .....                             | 107 |
| dynamics, absolute .....                   | 107 |
| dynamics, centered in keyboard music ..... | 286 |
| dynamics, editorial .....                  | 112 |
| dynamics, parenthesis .....                | 112 |
| dynamics, vertical positioning .....       | 109 |
| <b>dynamicUp</b> .....                     | 109 |

## E

|                                                   |        |
|---------------------------------------------------|--------|
| easy notation .....                               | 33     |
| easy play note heads .....                        | 33     |
| <b>easyHeadsOff</b> .....                         | 33     |
| <b>easyHeadsOn</b> .....                          | 33     |
| editorial dynamics .....                          | 112    |
| embedded graphics .....                           | 219    |
| embedding graphic objects .....                   | 217    |
| empty staves .....                                | 176    |
| encapsulated postscript output .....              | 457    |
| enclosing text in a box with rounded corners .... | 637    |
| enclosing text within a box .....                 | 609    |
| end repeat .....                                  | 133    |
| <b>endSpanners</b> .....                          | 690    |
| engravers, including in contexts .....            | 528    |
| entering lyrics .....                             | 227    |
| EPS output .....                                  | 457    |
| <b>epsfile</b> .....                              | 219    |
| espressivo .....                                  | 105    |
| <b>espressivo</b> .....                           | 108    |
| espressivo .....                                  | 654    |
| espressivo articulation .....                     | 108    |
| exceptions, chord names .....                     | 378    |
| <b>expandFullBarRests</b> .....                   | 53, 54 |
| expanding music .....                             | 45     |
| <b>explicitClefVisibility</b> .....               | 553    |
| <b>explicitKeySignatureVisibility</b> .....       | 553    |
| expressions, markup .....                         | 210    |
| extended chords .....                             | 370    |
| extender .....                                    | 238    |
| <b>extra-offset</b> .....                         | 488    |

## F

|                                     |              |
|-------------------------------------|--------------|
| <b>f</b> .....                      | 107          |
| F clef .....                        | 15           |
| falls .....                         | 119          |
| <b>featherDurations</b> .....       | 84, 690      |
| feathered beams .....               | 84           |
| fermata .....                       | 96, 105, 654 |
| fermata on bar line .....           | 205          |
| fermata on multi-measure rest ..... | 53           |
| <b>fermataMarkup</b> .....          | 53, 54       |
| Feta font .....                     | 589          |
| <b>ff</b> .....                     | 107          |
| <b>fff</b> .....                    | 107          |
| <b>ffff</b> .....                   | 107          |

|                                                     |          |
|-----------------------------------------------------|----------|
| <b>fffff</b> .....                                  | 107      |
| Figured bass .....                                  | 381      |
| figured bass alignment .....                        | 385      |
| figured bass extender lines .....                   | 384      |
| <b>fill-line</b> .....                              | 216      |
| <b>filled-box</b> .....                             | 219      |
| finalis .....                                       | 401      |
| finding available fonts .....                       | 225      |
| <b>finger</b> .....                                 | 192      |
| finger change .....                                 | 192      |
| fingerings .....                                    | 192      |
| fingerings chords .....                             | 192      |
| fingerings instructions for chords .....            | 192      |
| fingerings vs. string numbers .....                 | 301      |
| fingerings and multi-measure rests .....            | 56       |
| fingerings, adding to fret diagrams .....           | 338      |
| fingerings, right hand for fretted instruments .... | 340      |
| <b>first-page-number</b> .....                      | 477      |
| <b>flag-style</b> .....                             | 290      |
| flageolet .....                                     | 105, 654 |
| flags .....                                         | 396      |
| flat .....                                          | 5        |
| flat, double .....                                  | 5        |
| Flex .....                                          | 658      |
| follow voice .....                                  | 289      |
| <b>followVoice</b> .....                            | 289      |
| font .....                                          | 657      |
| font families .....                                 | 213      |
| font families, setting .....                        | 225      |
| font size .....                                     | 212      |
| font size (notation) .....                          | 191      |
| font size (notation) scaling .....                  | 191      |
| font size (notation), standard .....                | 192      |
| font size, setting .....                            | 479      |
| font switching .....                                | 212      |
| Font, Feta .....                                    | 589      |
| <b>font-interface</b> .....                         | 192      |
| <b>font-interface</b> .....                         | 223      |
| <b>font-size</b> .....                              | 191      |
| <b>font-size</b> .....                              | 192      |
| fonts, changing for entire document .....           | 225      |
| fonts, explained .....                              | 223      |
| fonts, finding available .....                      | 225      |
| fonts, non-text in markup .....                     | 223      |
| <b>fontsize</b> .....                               | 212      |
| <b>fontSize</b> .....                               | 191      |
| foot marks .....                                    | 105      |
| <b>footnote</b> .....                               | 690      |
| footnotes, manual .....                             | 441      |
| <b>forget</b> .....                                 | 28       |
| forget accidental style .....                       | 28       |
| format, rehearsal mark .....                        | 96       |
| formatting in lyrics .....                          | 227      |
| formatting text spanners .....                      | 203      |
| formatting, cue notes .....                         | 185      |
| four bar music .....                                | 481      |
| <b>four-string-banjo</b> .....                      | 345      |
| <b>fp</b> .....                                     | 107      |
| fragments .....                                     | 185      |
| fragments, quoting .....                            | 183      |
| framing text .....                                  | 217      |
| french clef .....                                   | 15       |
| Frenched score .....                                | 176      |
| Frenched staff .....                                | 176      |
| Frenched staves .....                               | 172      |



|                                                      |          |
|------------------------------------------------------|----------|
| fret                                                 | 304      |
| fret diagram, customized                             | 324      |
| fret diagrams                                        | 317, 327 |
| fret diagrams with chord names                       | 328      |
| fret diagrams, adding custom                         | 329      |
| fret diagrams, adding fingerings                     | 338      |
| fret diagrams, automatic                             | 337      |
| fret diagrams, custom                                | 317      |
| fret diagrams, mandolin                              | 327      |
| fret diagrams, transposing                           | 328      |
| fret diagrams, ukulele                               | 327      |
| <b>fret-diagram</b>                                  | 319      |
| fret-diagram markup                                  | 319      |
| <b>fret-diagram-interface</b>                        | 324      |
| <b>fret-diagram-terse</b>                            | 320      |
| fret-diagram-terse markup                            | 320      |
| <b>fret-diagram-verbose</b>                          | 322      |
| fret-diagram-verbose markup                          | 322      |
| <b>FretBoards</b>                                    | 327      |
| fretted instruments, chord shapes                    | 331      |
| fretted instruments, dampened notes                  | 342      |
| fretted instruments, harmonics                       | 342      |
| fretted instruments, indicating position and barring | 341      |
| fretted instruments, predefined string tunings       | 315      |
| fretted instruments, right hand fingerings           | 340      |
| full-measure rests                                   | 52       |
| Funk shape note heads                                | 35       |
| <b>funkHeads</b>                                     | 35       |
| <b>funkHeadsMinor</b>                                | 35       |

## G

|                                       |          |
|---------------------------------------|----------|
| G clef                                | 15       |
| <b>general-align</b>                  | 215      |
| ghost notes                           | 196      |
| <b>glissando</b>                      | 120      |
| global variable                       | 659      |
| glyph                                 | 657      |
| glyphs, music                         | 96       |
| <b>grace</b>                          | 690      |
| grace notes                           | 97, 358  |
| grace notes and lyrics                | 256      |
| grace notes within tuplet brackets    | 44       |
| grace notes, changing layout settings | 99       |
| grace notes, following                | 98       |
| grace notes, tweaking                 | 99       |
| grace-note synchronization            | 101      |
| grammar for LilyPond                  | 658      |
| grand staff                           | 163      |
| graphic notation                      | 219      |
| graphic objects, drawing              | 217      |
| graphic objects, embedding            | 217      |
| graphical object interfaces           | 658      |
| graphical objects                     | 657      |
| graphics, embedding                   | 217, 219 |
| Gregorian square neumes ligatures     | 403      |
| Gregorian transcription staff         | 162      |
| <b>GregorianTranscriptionStaff</b>    | 162      |
| grid lines                            | 199      |
| <b>Grid_line_span_engraver</b>        | 199      |
| <b>Grid_point_engraver</b>            | 199      |
| <b>gridInterval</b>                   | 199      |
| grob                                  | 531, 657 |
| grob properties                       | 536      |

|                                   |     |
|-----------------------------------|-----|
| grob-interface                    | 658 |
| <b>grobdescriptions</b>           | 690 |
| grobs, overwriting                | 550 |
| grobs, visibility of              | 550 |
| grouping beats                    | 79  |
| <b>grow-direction</b>             | 84  |
| guitar chord charts               | 70  |
| guitar note heads                 | 32  |
| guitar strumming rhythms, showing | 70  |
| guitar tablature                  | 300 |
| gutter                            | 475 |

## H

|                                            |          |
|--------------------------------------------|----------|
| hairpin                                    | 107      |
| hairpins, angled                           | 555      |
| halfopen                                   | 654      |
| <b>halign</b>                              | 214      |
| harmonic indications in tablature notation | 307      |
| harmonic note heads                        | 32       |
| Harmonica Sacra note heads                 | 35       |
| <b>harmonicByFret</b>                      | 690      |
| <b>harmonicByRatio</b>                     | 690      |
| <b>harmonicNote</b>                        | 690      |
| harmonics on fretted instruments           | 342      |
| harmonics, artificial                      | 299      |
| harmonics, natural                         | 299      |
| <b>harmonicsOn</b>                         | 690      |
| harp pedal diagrams                        | 297      |
| harp pedals                                | 297      |
| harps                                      | 296      |
| <b>hbracket</b>                            | 217      |
| help, balloon                              | 198      |
| hidden notes                               | 194      |
| <b>hideKeySignature</b>                    | 358      |
| <b>hideNotes</b>                           | 194      |
| <b>hideStaffSwitch</b>                     | 289      |
| hiding ancient staves                      | 177      |
| hiding of staves                           | 176      |
| hiding rhythmic staves                     | 177      |
| horizontal bracket                         | 201      |
| horizontal spacing                         | 503      |
| horizontal spacing, overriding             | 563      |
| horizontal text alignment                  | 214      |
| <b>horizontal-shift</b>                    | 475      |
| <b>Horizontal_bracket_engraver</b>         | 201      |
| horizontally centering text                | 618      |
| hufnagel                                   | 389      |
| <b>huge</b>                                | 191, 214 |
| hymns                                      | 273      |
| hyphens                                    | 238      |

## I

|                              |     |
|------------------------------|-----|
| ictus                        | 654 |
| images, embedding            | 219 |
| immutable objects            | 658 |
| immutable properties         | 658 |
| importing stencils into text | 650 |
| improvisation                | 37  |
| <b>improvisationOff</b>      | 37  |
| <b>improvisationOff</b>      | 70  |
| <b>improvisationOn</b>       | 37  |
| <b>improvisationOn</b>       | 70  |

|                                                                  |               |
|------------------------------------------------------------------|---------------|
| include-settings .....                                           | 453           |
| including files .....                                            | 448           |
| <b>indent</b> .....                                              | 180, 475, 507 |
| indicating No Chord in ChordNames .....                          | 373           |
| indicating position and barring for fretted<br>instruments ..... | 341           |
| inlining an Encapsulated PostScript image .....                  | 634           |
| <b>inner-margin</b> .....                                        | 475           |
| inserting music into text .....                                  | 640           |
| inserting PostScript directly into text .....                    | 636           |
| inserting URL links into text .....                              | 638           |
| instrument names .....                                           | 179, 459      |
| instrument names, adding to other contexts .....                 | 181           |
| instrument names, centering .....                                | 180           |
| instrument names, changing .....                                 | 181           |
| instrument names, complex .....                                  | 179           |
| instrument names, short .....                                    | 179           |
| instrument switch .....                                          | 182           |
| instruments, transposing .....                                   | 10            |
| <b>instrumentSwitch</b> .....                                    | 182, 690      |
| interface .....                                                  | 658           |
| interface, layout .....                                          | 531           |
| interleaved music .....                                          | 159           |
| Internals Reference .....                                        | 519           |
| inversion .....                                                  | 12            |
| <b>inversion</b> .....                                           | 690           |
| inversion, modal .....                                           | 14            |
| invisible notes .....                                            | 194           |
| invisible rest .....                                             | 51            |
| invisible stem .....                                             | 197           |
| <b>ionian</b> .....                                              | 19            |
| <b>italic</b> .....                                              | 212           |

## J

|                                |     |
|--------------------------------|-----|
| jazz chords .....              | 375 |
| justified text .....           | 216 |
| <b>justified-lines</b> .....   | 222 |
| <b>justify</b> .....           | 216 |
| justifying lines of text ..... | 652 |
| justifying text .....          | 624 |

## K

|                                                              |                 |
|--------------------------------------------------------------|-----------------|
| keep tagged music .....                                      | 450             |
| <b>keepWithTag</b> .....                                     | 690             |
| <b>key</b> .....                                             | 19, 35, 690     |
| key signature .....                                          | 5, 19, 397, 401 |
| key signature, visibility following explicit change<br>..... | 553             |
| keyboard instrument staves .....                             | 286             |
| keyboard music, centering dynamics .....                     | 286             |
| keyed instrument staves .....                                | 286             |
| <b>killCues</b> .....                                        | 189, 691        |
| kirchenpausen .....                                          | 54              |
| knee gap, with beams .....                                   | 73              |

## L

|                             |     |
|-----------------------------|-----|
| <b>label</b> .....          | 691 |
| <i>laissez vibrer</i> ..... | 47  |
| <b>laissezVibrer</b> .....  | 47  |
| landscape .....             | 470 |
| <b>language</b> .....       | 691 |

|                                                |          |
|------------------------------------------------|----------|
| language, note names in other .....            | 7        |
| language, pitch names in other .....           | 7        |
| <b>languageRestore</b> .....                   | 691      |
| <b>languageSaveAndChange</b> .....             | 691      |
| <b>large</b> .....                             | 191, 214 |
| <b>larger</b> .....                            | 212, 214 |
| <b>last-bottom-spacing</b> .....               | 473      |
| layers .....                                   | 550      |
| <b>layout file</b> .....                       | 479      |
| layout interface .....                         | 531      |
| layout objects .....                           | 657      |
| ledger lines .....                             | 169      |
| ledger lines, internal .....                   | 169      |
| ledger lines, modifying .....                  | 169      |
| left aligning text .....                       | 625      |
| <b>left-align</b> .....                        | 214      |
| <b>left-margin</b> .....                       | 474      |
| <b>length</b> .....                            | 290      |
| length of notes .....                          | 38       |
| lexer .....                                    | 658      |
| heel .....                                     | 654      |
| Ligatures .....                                | 390      |
| ligatures in text .....                        | 619      |
| line breaks .....                              | 86, 480  |
| line breaks in cadenzas .....                  | 65       |
| line breaks in unmetered music .....           | 65       |
| line breaks, beams .....                       | 73       |
| line, cross-staff .....                        | 289      |
| line, staff-change .....                       | 289      |
| line, staff-change follower .....              | 289      |
| <b>line-width</b> .....                        | 474, 507 |
| lineprall .....                                | 654      |
| lines, grid .....                              | 199      |
| lines, vertical between staves .....           | 199      |
| List of colors .....                           | 587      |
| listing available fonts .....                  | 225      |
| <b>locrian</b> .....                           | 19       |
| <b>longa</b> .....                             | 38       |
| <b>longa</b> .....                             | 49       |
| longa rest .....                               | 49       |
| longfermata .....                              | 654      |
| <b>lower</b> .....                             | 215      |
| lowering text .....                            | 626      |
| ltoe .....                                     | 654      |
| <b>ly:minimal-breaking</b> .....               | 484      |
| <b>ly:optimal-breaking</b> .....               | 483      |
| <b>ly:page-turn-breaking</b> .....             | 483      |
| <b>lydian</b> .....                            | 19       |
| lyrics and melodies .....                      | 230      |
| lyrics and tied notes .....                    | 250      |
| lyrics assigned to one voice .....             | 146      |
| lyrics on grace notes .....                    | 256      |
| lyrics punctuation .....                       | 227      |
| lyrics, aligning to a melody .....             | 228      |
| lyrics, aligning with sporadic melody .....    | 523      |
| lyrics, divided .....                          | 253      |
| lyrics, entering .....                         | 227      |
| lyrics, formatting .....                       | 227      |
| Lyrics, increasing space between .....         | 244      |
| lyrics, keeping inside margin .....            | 203      |
| lyrics, positioning .....                      | 240      |
| lyrics, repeating .....                        | 246      |
| lyrics, repeats with alternative endings ..... | 249      |
| lyrics, skip .....                             | 51       |
| lyrics, skipping notes .....                   | 249      |

lyrics, using variables ..... 238  
 lyrics, with beams..... 74

## M

**m** ..... 369  
**magnify** ..... 212  
 magnifying text ..... 612  
**magstep** ..... 191  
**magstep** ..... 544  
**maj** ..... 369  
**major** ..... 19  
 major seven symbols ..... 378  
**majorSevenSymbol** ..... 376  
**makam** ..... 420, 421  
**makamlar** ..... 420, 421  
**make-dynamic-script** ..... 113  
**make-pango-font-tree** ..... 225  
**makeClusters** ..... 145  
**makeClusters** ..... 691  
**makeDefaultStringTuning** ..... 691  
 manual bar lines ..... 86  
 manual beams ..... 72, 82  
 manual beams, direction shorthand for ..... 82  
 manual beams, grace notes ..... 82  
 manual measure lines ..... 86  
 manual rehearsal mark ..... 96  
 manual repeat mark ..... 133  
 manual staff changes ..... 286  
**Manuals** ..... 1  
**maqam** ..... 416  
**maqams** ..... 416  
**marcato** ..... 105, 654  
 margin, text running over ..... 203  
**mark** ..... 95, 205, 691  
 mark, phrasing ..... 117  
 mark, rehearsal ..... 95  
 mark, rehearsal, format ..... 96  
 mark, rehearsal, manual ..... 96  
 mark, rehearsal, style ..... 96  
 marks, text ..... 205  
**markup** ..... 205, 209, 210  
 markup expressions ..... 210  
 markup mode, quoted text ..... 211  
 markup mode, special characters ..... 211  
 markup on multi-measure rest ..... 53  
 markup syntax ..... 210  
 markup text ..... 210  
 markup text alignment commands ..... 217  
 markup text padding ..... 218  
 markup text, aligning ..... 214  
 markup text, decorating ..... 217  
 markup text, framing ..... 217  
 markup text, justified ..... 216  
 markup text, multi-page ..... 222  
 markup text, wordwrapped ..... 216  
 markup, centering on the page ..... 216  
 markup, multi-line ..... 216  
 markup, multi-page ..... 222  
 markup, music notation inside ..... 220  
 markup, score inside ..... 221  
**markup-markup-spacing** ..... 473  
**markup-system-spacing** ..... 473  
**markuplist** ..... 209

**markuplist** ..... 222  
**markuplist** ..... 223  
 markups, aligning ..... 214  
**max-systems-per-page** ..... 476  
**maxima** ..... 38  
**maxima** ..... 49  
 maxima rest ..... 49  
 measure check ..... 94  
 measure groupings ..... 79  
 measure lines ..... 85  
 measure lines, invisible ..... 86  
 measure lines, manual ..... 86  
 measure number ..... 103  
 measure number and repeats ..... 133  
 measure number check ..... 94  
 measure number, format ..... 91  
 measure numbers ..... 90  
 measure repeats ..... 137  
 measure sub-grouping ..... 79  
 measure, partial ..... 63  
 measure, pickup ..... 63  
**measureLength** ..... 74, 103  
**measurePosition** ..... 63, 103  
 Medicaea, Editio ..... 389  
 medium intervals ..... 416  
 melisma ..... 234, 238  
 melismata ..... 234  
 melismata, with beams ..... 73  
 melody rhythms, showing ..... 70  
 mensural ..... 389, 390  
 Mensural ligatures ..... 398  
 mensural music, transcription of ..... 165  
**MensuralStaff** ..... 162  
 MensuralStaffContext ..... 392  
 MensuralVoiceContext ..... 392  
 mensuration sign ..... 394  
 mensurstriche layout ..... 165  
**mergeDifferentlyDottedOff** ..... 150  
**mergeDifferentlyDottedOn** ..... 150  
**mergeDifferentlyHeadedOff** ..... 150  
**mergeDifferentlyHeadedOn** ..... 150  
 merging notes ..... 150  
 merging text ..... 619  
 meter ..... 56  
 meter style ..... 57  
 meter, polymetric ..... 66  
 metronome mark ..... 61  
 metronome marking with text ..... 61  
 mezzosoprano clef ..... 15  
**mf** ..... 107  
 microtones ..... 8  
 Microtones in MIDI ..... 461  
 MIDI ..... 21, 458  
 MIDI block ..... 460  
 MIDI context definitions ..... 460  
 MIDI transposition ..... 21  
 MIDI, articulations ..... 461  
 MIDI, chord names ..... 461  
 MIDI, microtones ..... 461  
 MIDI, Pitches ..... 461  
 MIDI, quarter tones ..... 461  
 MIDI, Rhythms ..... 461  
**min-systems-per-page** ..... 476  
**minimum-Y-extent** ..... 488  
**minimumFret** ..... 304, 339

|                                                          |          |
|----------------------------------------------------------|----------|
| <code>minimumPageTurnLength</code> .....                 | 483      |
| <code>minimumRepeatLengthForPageTurn</code> .....        | 484      |
| <code>minor</code> .....                                 | 19       |
| <code>minorChordModifier</code> .....                    | 377      |
| <code>mirroring markup</code> .....                      | 637      |
| <code>mixed</code> .....                                 | 292      |
| <code>mixolydian</code> .....                            | 19       |
| <code>modal inversion</code> .....                       | 14       |
| <code>modal transformations</code> .....                 | 13       |
| <code>modal transposition</code> .....                   | 13       |
| <code>modalInversion</code> .....                        | 14, 691  |
| <code>modalTranspose</code> .....                        | 13, 691  |
| <code>mode</code> .....                                  | 659      |
| <code>modern</code> .....                                | 25       |
| <code>modern accidental style</code> .....               | 24, 25   |
| <code>modern accidentals</code> .....                    | 25       |
| <code>modern cautionary accidental style</code> .....    | 25       |
| <code>modern style accidentals</code> .....              | 25       |
| <code>modern style cautionary accidentals</code> .....   | 25       |
| <code>modern-cautionary</code> .....                     | 25       |
| <code>modern-cautionary accidental style</code> .....    | 24       |
| <code>modern-voice</code> .....                          | 25       |
| <code>modern-voice-cautionary</code> .....               | 25       |
| <code>moderntab clef</code> .....                        | 317      |
| <code>modes</code> .....                                 | 19       |
| <code>modifiers, in chords</code> .....                  | 369      |
| <code>mordent</code> .....                               | 105, 654 |
| <code>mordent, down</code> .....                         | 105      |
| <code>mordent, up</code> .....                           | 105      |
| <code>movements, multiple</code> .....                   | 423      |
| <code>mp</code> .....                                    | 107      |
| <code>multi-line markup</code> .....                     | 216      |
| <code>multi-line text</code> .....                       | 216      |
| <code>multi-measure rest with markup</code> .....        | 53       |
| <code>multi-measure rest, attaching fermata</code> ..... | 53       |
| <code>multi-measure rest, attaching text</code> .....    | 53       |
| <code>multi-measure rest, contracting</code> .....       | 53       |
| <code>multi-measure rest, expanding</code> .....         | 53       |
| <code>multi-measure rest, script</code> .....            | 53       |
| <code>multi-measure rests</code> .....                   | 52       |
| <code>multi-measure rests and fingerings</code> .....    | 56       |
| <code>multi-measure rests, positioning</code> .....      | 54       |
| <code>multi-note acciaccatura</code> .....               | 101      |
| <code>multi-page markup</code> .....                     | 222      |
| <code>MultiMeasureRestText</code> .....                  | 53       |
| <code>multiple dynamic marks on one note</code> .....    | 108      |
| <code>multiple phrasing slurs</code> .....               | 117      |
| <code>multiple slurs</code> .....                        | 114      |
| <code>multiple voices</code> .....                       | 150      |
| <code>multivoice accidentals</code> .....                | 25       |
| <code>music glyphs</code> .....                          | 96       |
| <code>music inside markup</code> .....                   | 220      |
| <code>music, beginners'</code> .....                     | 33       |
| <code>music, unmetred</code> .....                       | 103      |
| <code>Musica ficta</code> .....                          | 397      |
| <code>musical cues</code> .....                          | 268      |
| <code>musicglyph</code> .....                            | 96       |
| <code>musicMap</code> .....                              | 691      |
| <code>musicological analysis</code> .....                | 201      |
| <code>musicQuotes</code> .....                           | 659      |
| <code>mutable objects</code> .....                       | 658      |
| <code>mutable properties</code> .....                    | 658      |

## N

|                                                                 |          |
|-----------------------------------------------------------------|----------|
| <code>N.C. symbol</code> .....                                  | 373      |
| <code>name</code> .....                                         | 528      |
| <code>name of singer</code> .....                               | 255      |
| <code>names, character</code> .....                             | 266      |
| <code>natural harmonics</code> .....                            | 299      |
| <code>natural pitch</code> .....                                | 5        |
| <code>natural sign</code> .....                                 | 5        |
| <code>neo-modern</code> .....                                   | 26       |
| <code>neo-modern accidental style</code> .....                  | 26       |
| <code>neo-modern-cautionary</code> .....                        | 26       |
| <code>neo-modern-cautionary accidental style</code> .....       | 26       |
| <code>neo-modern-voice</code> .....                             | 27       |
| <code>neo-modern-voice accidental style</code> .....            | 27       |
| <code>neo-modern-voice-cautionary</code> .....                  | 27       |
| <code>neo-modern-voice-cautionary accidental style</code> ..... | 27       |
| <code>neomensural</code> .....                                  | 390      |
| <code>nested repeat</code> .....                                | 133      |
| <code>nested staff brackets</code> .....                        | 166      |
| <code>nesting of staves</code> .....                            | 166      |
| <code>new contexts</code> .....                                 | 521      |
| <code>new dynamic marks</code> .....                            | 112      |
| <code>new staff</code> .....                                    | 162      |
| <code>niente, al</code> .....                                   | 110      |
| <code>no chord symbol</code> .....                              | 373      |
| <code>no reset accidental style</code> .....                    | 27       |
| <code>no-reset</code> .....                                     | 27       |
| <code>noBeam</code> .....                                       | 82       |
| <code>non-ASCII characters</code> .....                         | 453      |
| <code>non-empty texts</code> .....                              | 202      |
| <code>non-musical symbols</code> .....                          | 219      |
| <code>non-text fonts in markup</code> .....                     | 223      |
| <code>nonstaff-nonstaff-spacing</code> .....                    | 488      |
| <code>nonstaff-relatedstaff-spacing</code> .....                | 488      |
| <code>nonstaff-unrelatedstaff-spacing</code> .....              | 488      |
| <code>noPageBreak</code> .....                                  | 691      |
| <code>noPageTurn</code> .....                                   | 691      |
| <code>normal repeat</code> .....                                | 127      |
| <code>normalsize</code> .....                                   | 191, 214 |
| <code>notation font size</code> .....                           | 191      |
| <code>notation inside markup</code> .....                       | 220      |
| <code>notation, explaining</code> .....                         | 198      |
| <code>notation, graphic</code> .....                            | 219      |
| <code>note cluster</code> .....                                 | 145      |
| <code>note collisions</code> .....                              | 150      |
| <code>note duration, default</code> .....                       | 39       |
| <code>note durations</code> .....                               | 38       |
| <code>note grouping bracket</code> .....                        | 201      |
| <code>note head styles</code> .....                             | 32, 608  |
| <code>note heads</code> .....                                   | 191      |
| <code>note heads, Aiken</code> .....                            | 35       |
| <code>note heads, ancient</code> .....                          | 395      |
| <code>note heads, Christian Harmony</code> .....                | 35       |
| <code>note heads, cross</code> .....                            | 32       |
| <code>note heads, diamond</code> .....                          | 32       |
| <code>note heads, diamond-shaped</code> .....                   | 299      |
| <code>note heads, easy notation</code> .....                    | 33       |
| <code>note heads, easy play</code> .....                        | 33       |
| <code>note heads, Funk</code> .....                             | 35       |
| <code>note heads, guitar</code> .....                           | 32       |
| <code>note heads, harmonic</code> .....                         | 32       |
| <code>note heads, Harmonica Sacra</code> .....                  | 35       |
| <code>note heads, improvisation</code> .....                    | 37       |
| <code>note heads, parlato</code> .....                          | 32       |

|                                              |          |
|----------------------------------------------|----------|
| note heads, practice .....                   | 33       |
| note heads, sacred harp .....                | 35       |
| note heads, shape .....                      | 35       |
| note heads, slashed .....                    | 37       |
| note heads, Southern Harmony .....           | 35       |
| note heads, special .....                    | 32       |
| note heads, Walker .....                     | 35       |
| note lengths .....                           | 38       |
| note names, default .....                    | 5        |
| note names, Dutch .....                      | 5        |
| note names, other languages .....            | 7        |
| note-event .....                             | 184      |
| <b>Note_heads_engraver</b> .....             | 69       |
| notes within text by log and dot-count ..... | 639      |
| notes within text by string .....            | 639      |
| notes, colored .....                         | 195      |
| notes, colored in chords .....               | 196      |
| notes, cross-staff .....                     | 286, 290 |
| notes, dotted .....                          | 39       |
| notes, double-dotted .....                   | 39       |
| notes, ghost .....                           | 196      |
| notes, hidden .....                          | 194      |
| notes, invisible .....                       | 194      |
| notes, parenthesized .....                   | 196      |
| notes, smaller .....                         | 185      |
| notes, splitting .....                       | 69       |
| notes, transparent .....                     | 194      |
| notes, transposition of .....                | 9        |
| <b>null</b> .....                            | 215      |
| numbers, bar .....                           | 90       |
| numbers, measure .....                       | 90       |
| <b>numericTimeSignature</b> .....            | 57       |

## O

|                                      |          |
|--------------------------------------|----------|
| objects, colored .....               | 195      |
| objects, coloring .....              | 550      |
| objects, overwriting .....           | 550      |
| objects, rotating .....              | 555      |
| objects, visibility of .....         | 550      |
| octavated clefs, visibility of ..... | 554      |
| octavation .....                     | 20       |
| octave changing mark .....           | 1        |
| octave check .....                   | 8        |
| octave correction .....              | 8        |
| octave entry, absolute .....         | 1        |
| octave entry, relative .....         | 2        |
| octave specification, absolute ..... | 1        |
| octave specification, relative ..... | 2        |
| octave transposition .....           | 16       |
| <b>octaveCheck</b> .....             | 8, 691   |
| <b>once</b> .....                    | 691      |
| <b>oneVoice</b> .....                | 146      |
| open .....                           | 105, 654 |
| open string indication .....         | 298      |
| operation, inversion .....           | 12       |
| operation, modal inversion .....     | 14       |
| operation, retrograde .....          | 13       |
| operation, transposition .....       | 13       |
| operations, modal .....              | 13       |
| oratorio .....                       | 262      |
| orchestral strings .....             | 298      |
| organ pedal marks .....              | 105      |
| orientation .....                    | 470      |

|                                                |          |
|------------------------------------------------|----------|
| ornamentation .....                            | 105      |
| ornaments .....                                | 97, 105  |
| ossia .....                                    | 172, 177 |
| <b>ottava</b> .....                            | 20       |
| <b>ottava</b> .....                            | 691      |
| Ottoman music .....                            | 420      |
| <b>outer-margin</b> .....                      | 475      |
| output-count .....                             | 659      |
| output-def .....                               | 658      |
| output-suffix .....                            | 659      |
| <b>outside-staff-horizontal-padding</b> .....  | 502      |
| <b>outside-staff-padding</b> .....             | 502      |
| <b>outside-staff-priority</b> .....            | 502      |
| <b>overrideProperty</b> .....                  | 691      |
| overrides in lyric mode .....                  | 227      |
| overrides, reverting .....                     | 537      |
| <b>overrideTimeSignatureSettings</b> .....     | 691      |
| overriding for only one moment .....           | 537      |
| overriding properties within text markup ..... | 648      |
| overwriting objects .....                      | 550      |

## P

|                                                  |          |
|--------------------------------------------------|----------|
| <b>p</b> .....                                   | 107      |
| <b>pad-around</b> .....                          | 218      |
| <b>pad-markup</b> .....                          | 218      |
| <b>pad-to-box</b> .....                          | 218      |
| <b>pad-x</b> .....                               | 218      |
| padding .....                                    | 533      |
| padding around text .....                        | 218      |
| padding text .....                               | 627      |
| padding text horizontally .....                  | 627      |
| page breaks .....                                | 507      |
| page breaks in cadenzas .....                    | 65       |
| page breaks in unmeasured music .....            | 65       |
| page layout .....                                | 507      |
| page numbers, auto-numbering .....               | 477      |
| page numbers, specify the first .....            | 477      |
| page numbers, suppress .....                     | 477      |
| page size .....                                  | 470      |
| <b>page-breaking</b> .....                       | 476      |
| <b>page-breaking-system-system-spacing</b> ..... | 476      |
| <b>page-count</b> .....                          | 476      |
| <b>page-spacing-weight</b> .....                 | 477      |
| <b>pageBreak</b> .....                           | 691      |
| <b>pageTurn</b> .....                            | 692      |
| <b>palmMute</b> .....                            | 692      |
| <b>palmMuteOn</b> .....                          | 692      |
| Pango .....                                      | 223      |
| paper size .....                                 | 470      |
| <b>paper-height</b> .....                        | 471      |
| <b>paper-width</b> .....                         | 474      |
| parallel music .....                             | 159      |
| <b>parallelMusic</b> .....                       | 159, 692 |
| parentheses .....                                | 196      |
| <b>parenthesize</b> .....                        | 196, 692 |
| parenthesized accidental .....                   | 5        |
| parlato .....                                    | 271      |
| parlato note heads .....                         | 32       |
| parser .....                                     | 658      |
| parser variable .....                            | 659      |
| <b>parseStringResult</b> .....                   | 659      |
| part combiner .....                              | 154      |
| part songs .....                                 | 262      |

|                                                              |          |                                                                      |          |
|--------------------------------------------------------------|----------|----------------------------------------------------------------------|----------|
| <code>partcombine</code> .....                               | 154, 692 | <code>pickup in a repeat</code> .....                                | 129      |
| <code>partcombineApart</code> .....                          | 155      | <code>pickup measure</code> .....                                    | 63       |
| <code>partcombineAutomatic</code> .....                      | 155      | <code>pipeSymbol</code> .....                                        | 95       |
| <code>partcombineChords</code> .....                         | 155      | <code>pitch names</code> .....                                       | 1        |
| <code>partcombineDown</code> .....                           | 692      | <code>pitch names, other languages</code> .....                      | 7        |
| <code>partcombineForce</code> .....                          | 692      | <code>pitch range</code> .....                                       | 29       |
| <code>partCombineListener</code> .....                       | 659      | <code>Pitch_squash_engraver</code> .....                             | 70       |
| <code>partcombineSoloI</code> .....                          | 155      | <code>pitched trill with accidental</code> .....                     | 126      |
| <code>partcombineSoloII</code> .....                         | 155      | <code>pitched trills</code> .....                                    | 126      |
| <code>partcombineUnisono</code> .....                        | 155      | <code>pitchedTrill</code> .....                                      | 126, 692 |
| <code>partcombineUp</code> .....                             | 692      | <code>pitches</code> .....                                           | 1        |
| <code>partial</code> .....                                   | 63, 692  | <code>Pitches in MIDI</code> .....                                   | 461      |
| <code>partial measure</code> .....                           | 63       | <code>pitches, transposition of</code> .....                         | 9        |
| <code>paths, drawing</code> .....                            | 636      | <code>pitchnames</code> .....                                        | 659      |
| <code>pause mark</code> .....                                | 118      | <code>pizzicato, Bartók</code> .....                                 | 300      |
| <code>pedal diagrams, harp</code> .....                      | 297      | <code>pizzicato, snap</code> .....                                   | 300      |
| <code>pedal indication styles</code> .....                   | 292      | <code>placement of lyrics</code> .....                               | 240      |
| <code>pedal indication, bracket</code> .....                 | 292      | <code>placing horizontal brackets around text</code> .....           | 635      |
| <code>pedal indication, mixed</code> .....                   | 292      | <code>placing parentheses around text</code> .....                   | 635      |
| <code>pedal indication, text</code> .....                    | 292      | <code>placing vertical brackets around text</code> .....             | 633      |
| <code>pedal marks, organ</code> .....                        | 105      | <code>pointAndClickOff</code> .....                                  | 692      |
| <code>pedal sustain style</code> .....                       | 292      | <code>pointAndClickOn</code> .....                                   | 692      |
| <code>pedal, sostenuto</code> .....                          | 292      | <code>pointAndClickTypes</code> .....                                | 693      |
| <code>pedal, sustain</code> .....                            | 292      | <code>polymetric meters, with beams</code> .....                     | 66       |
| <code>pedals, harp</code> .....                              | 297      | <code>polymetric scores</code> .....                                 | 525      |
| <code>pedals, piano</code> .....                             | 292      | <code>polymetric signatures</code> .....                             | 66       |
| <code>pedalSustainStyle</code> .....                         | 292      | <code>polyphonic music</code> .....                                  | 150      |
| <code>percent</code> .....                                   | 137      | <code>polyphony, single-staff</code> .....                           | 146      |
| <code>percent repeats</code> .....                           | 137      | <code>portato</code> .....                                           | 105, 654 |
| <code>percussion</code> .....                                | 346, 348 | <code>positioning multi-measure rests</code> .....                   | 54       |
| <code>percussion clef</code> .....                           | 346      | <code>postscript</code> .....                                        | 219      |
| <code>percussion staff</code> .....                          | 162      | <code>power chords</code> .....                                      | 343      |
| <code>Petrucci</code> .....                                  | 389, 390 | <code>powerChords</code> .....                                       | 343      |
| <code>phrasing bracket</code> .....                          | 201      | <code>pp</code> .....                                                | 107      |
| <code>phrasing marks</code> .....                            | 117      | <code>ppp</code> .....                                               | 107      |
| <code>phrasing slur</code> .....                             | 114      | <code>pppp</code> .....                                              | 107      |
| <code>phrasing slur, dashed</code> .....                     | 117      | <code>ppppp</code> .....                                             | 107      |
| <code>phrasing slur, defining dash patterns</code> .....     | 117      | <code>practice note heads</code> .....                               | 33       |
| <code>phrasing slur, dotted</code> .....                     | 117      | <code>prall</code> .....                                             | 105, 654 |
| <code>phrasing slur, half solid and half dashed</code> ..... | 117      | <code>prall, down</code> .....                                       | 105      |
| <code>phrasing slur, multiple</code> .....                   | 117      | <code>prall, up</code> .....                                         | 105      |
| <code>phrasing slur, simultaneous</code> .....               | 117      | <code>pralldown</code> .....                                         | 654      |
| <code>phrasing slurs</code> .....                            | 117      | <code>prallmordent</code> .....                                      | 105, 654 |
| <code>phrasing, in lyrics</code> .....                       | 234      | <code>prallprall</code> .....                                        | 105, 654 |
| <code>phrasingSlurDashed</code> .....                        | 117      | <code>prallup</code> .....                                           | 654      |
| <code>phrasingSlurDashPattern</code> .....                   | 117, 692 | <code>predefined string tunings for fretted instruments</code> ..... | 315      |
| <code>phrasingSlurDotted</code> .....                        | 117      | <code>predefinedFretboardsOff</code> .....                           | 338      |
| <code>phrasingSlurDown</code> .....                          | 117      | <code>predefinedFretboardsOn</code> .....                            | 338      |
| <code>phrasingSlurHalfDashed</code> .....                    | 117      | <code>prima volta</code> .....                                       | 127      |
| <code>phrasingSlurHalfSolid</code> .....                     | 117      | <code>print-all-headers</code> .....                                 | 477      |
| <code>phrasingSlurNeutral</code> .....                       | 117      | <code>print-first-page-number</code> .....                           | 477      |
| <code>phrasingSlurSolid</code> .....                         | 117      | <code>print-page-number</code> .....                                 | 477      |
| <code>phrasingSlurUp</code> .....                            | 117      | <code>printing chord names</code> .....                              | 373      |
| <code>phrygian</code> .....                                  | 19       | <code>printing order</code> .....                                    | 550      |
| <code>piano</code> .....                                     | 26       | <code>printing reserved characters</code> .....                      | 211      |
| <code>piano accidental style</code> .....                    | 26       | <code>printing special characters</code> .....                       | 211      |
| <code>piano accidentals</code> .....                         | 26       | <code>prob</code> .....                                              | 659      |
| <code>piano cautionary accidental style</code> .....         | 26       | <code>properties</code> .....                                        | 534      |
| <code>piano cautionary accidentals</code> .....              | 26       | <code>properties, grob</code> .....                                  | 536      |
| <code>piano music, centering dynamics</code> .....           | 286      | <code>property object</code> .....                                   | 659      |
| <code>piano pedals</code> .....                              | 292      | <code>psalms</code> .....                                            | 273      |
| <code>piano staff</code> .....                               | 163      | <code>punctuation in lyrics</code> .....                             | 227      |
| <code>piano staves</code> .....                              | 286      | <code>pure containers, Scheme</code> .....                           | 563      |
| <code>piano-cautionary</code> .....                          | 26       | <code>pushToTag</code> .....                                         | 693      |
| <code>PianoStaff</code> .....                                | 286, 288 |                                                                      |          |



putting space around text ..... 627

## Q

quarter tones ..... 5  
 Quarter tones in MIDI ..... 461  
 quarter-tone accidental ..... 6  
 quote, voices ..... 183  
 quoted text ..... 202  
 quoted text in markup mode ..... 211  
**quotedCueEventTypes** ..... 184  
**quotedEventTypes** ..... 184  
**quoteDuring** ..... 183, 185, 693  
 quotes in lyrics ..... 227  
 quotes, in lyrics ..... 234

## R

**r** ..... 49  
**R** ..... 52  
**ragged-bottom** ..... 471  
**ragged-last** ..... 474, 507  
**ragged-last-bottom** ..... 471  
**ragged-right** ..... 474, 507  
 railroad tracks ..... 119  
**raise** ..... 215  
 raising text ..... 628  
 rallentando in MIDI ..... 461  
 range of pitches ..... 29  
 Ratisbona, Editio ..... 389  
 referencing page labels in text ..... 651  
 referencing page numbers in text ..... 649  
 regular line breaks ..... 481  
 rehearsal mark format ..... 96  
 rehearsal mark style ..... 96  
 rehearsal mark, manual ..... 96  
 rehearsal marks ..... 95  
**relative** ..... 2, 4, 12, 288, 693  
 relative music and autochange ..... 288  
 relative octave entry ..... 2  
 relative octave entry and chords ..... 4  
 relative octave entry and transposition ..... 4  
 relative octave specification ..... 2  
 relative pitch, chords ..... 142  
 religious music ..... 273  
 reminder accidental ..... 5  
 removals, in chords ..... 371  
 remove tagged music ..... 450  
**RemoveEmptyStaves** ..... 695  
**removeWithTag** ..... 693  
 removing cue notes ..... 189  
 renaissance music ..... 165  
 repeat and measure number ..... 133  
 repeat and slur ..... 133  
 repeat bars ..... 85  
 repeat number, changing ..... 133  
 repeat timing information ..... 133  
 repeat volta, changing ..... 133  
 repeat with alternate endings ..... 127  
 repeat with anacrusis ..... 129  
 repeat with pickup ..... 129  
 repeat with upbeat ..... 129  
 repeat, ambiguous ..... 133  
 repeat, end ..... 133

repeat, manual ..... 133  
 repeat, measure ..... 137  
 repeat, nested ..... 133  
 repeat, normal ..... 127  
 repeat, percent ..... 137  
 repeat, short ..... 137  
 repeat, start ..... 133  
 repeat, tremolo ..... 139  
**repeatCommands** ..... 133  
 repeating lyrics with alternative endings ..... 249  
 repeating ties ..... 46  
 repeats ..... 87  
 repeats and lyrics ..... 246  
 repeats in MIDI ..... 462  
 repeats, alternative ..... 135  
 repeats, alternative bar numbers ..... 132  
 repeats, bar numbers letters ..... 132  
 repeats, unfold ..... 135  
 repeats, with ties ..... 130  
 repeats, written-out ..... 135  
**repeatTie** ..... 46  
 repetition, using **q** ..... 143, 305  
 reserved characters, printing ..... 211  
**resetRelativeOctave** ..... 693  
 resizing of staves ..... 172  
**rest** ..... 49  
 rest, church ..... 54  
 rest, collisions of ..... 56  
 rest, condensing ordinary ..... 56  
 rest, entering durations ..... 49  
 rest, full-measure ..... 52  
 rest, invisible ..... 51  
 rest, multi-measure ..... 49, 52  
 rest, specifying vertical position ..... 49  
 rest, whole for a full measure ..... 52  
 rest, whole-measure ..... 49  
 rest-event ..... 184  
 restoring default properties for time signatures ..... 58  
 rests, ancient ..... 396  
 rests, splitting ..... 69  
**retrograde** ..... 13, 693  
 retrograde transformation ..... 13  
 reversion ..... 105, 654  
 reverting overrides ..... 537  
**revertTimeSignatureSettings** ..... 693  
**rfz** ..... 107  
 rgb color ..... 196  
**rgb-color** ..... 196  
 rheel ..... 654  
 rhythmic staff ..... 162  
**RhythmicStaff** ..... 162  
 Rhythms in MIDI ..... 461  
 rhythms, showing melody ..... 70  
 right aligning text ..... 628  
 right hand fingerings for fretted instruments ..... 340  
**right-align** ..... 214  
**right-margin** ..... 474  
**rightHandFinger** ..... 340, 693  
 root of chord ..... 369  
 rotating objects ..... 555  
 rotating text ..... 629  
**rounded-box** ..... 217  
 rtote ..... 654

## S

|                                                 |                  |
|-------------------------------------------------|------------------|
| <b>s</b> .....                                  | 51               |
| sacred harp note heads .....                    | 35               |
| <b>sacredHarpHeads</b> .....                    | 35               |
| <b>sacredHarpHeadsMinor</b> .....               | 35               |
| <b>SATB</b> .....                               | 262              |
| scalable vector graphics output .....           | 457              |
| <b>scaleDurations</b> .....                     | 45, 66, 693      |
| scaling durations .....                         | 44               |
| scaling markup .....                            | 637              |
| scaling text .....                              | 629              |
| Scheme object .....                             | 659              |
| Scheme variable .....                           | 659              |
| Scheme, pure containers .....                   | 563              |
| Scheme, unpure containers .....                 | 563              |
| score inside markup .....                       | 221              |
| <b>score-markup-spacing</b> .....               | 473              |
| <b>score-system-spacing</b> .....               | 473              |
| Scottish highland bagpipe .....                 | 358              |
| script on multi-measure rest .....              | 53               |
| scripts .....                                   | 105              |
| seconda volta .....                             | 127              |
| segno .....                                     | 87, 96, 105, 654 |
| segno on bar line .....                         | 205              |
| selecting font size (notation) .....            | 191              |
| <b>self-alignment-X</b> .....                   | 488              |
| Semai form .....                                | 418              |
| semi-flat .....                                 | 8                |
| Semi-flat symbol appearance .....               | 416              |
| semi-flats .....                                | 5                |
| semi-sharp .....                                | 8                |
| semi-sharps .....                               | 5                |
| semicirculus .....                              | 654              |
| separate text .....                             | 209              |
| sesqui-flat .....                               | 8                |
| sesqui-sharp .....                              | 8                |
| <b>set</b> .....                                | 74               |
| <b>set-octavation</b> .....                     | 20               |
| setting extent of text objects .....            | 651              |
| setting horizontal text alignment .....         | 622              |
| setting subscript in standard font size .....   | 612              |
| setting superscript in standard font size ..... | 613              |
| <b>settingsFrom</b> .....                       | 693              |
| seventh chords .....                            | 369              |
| <b>sf</b> .....                                 | 107              |
| <b>sff</b> .....                                | 107              |
| <b>sfz</b> .....                                | 107              |
| shape notes .....                               | 35               |
| shared properties .....                         | 658              |
| sharp .....                                     | 5                |
| sharp, double .....                             | 5                |
| shift note .....                                | 150              |
| shift rest, automatic .....                     | 150              |
| <b>shiftDurations</b> .....                     | 693              |
| shifting voices .....                           | 150              |
| <b>shiftOff</b> .....                           | 150              |
| <b>shiftOn</b> .....                            | 150              |
| <b>shiftOnn</b> .....                           | 150              |
| <b>shiftOnnn</b> .....                          | 150              |
| <b>short-indent</b> .....                       | 180, 475         |
| shortfermata .....                              | 654              |
| <b>show-available-fonts</b> .....               | 225              |
| <b>showFirstLength</b> .....                    | 456              |
| <b>showFirstLength</b> .....                    | 659              |
| <b>showKeySignature</b> .....                   | 358              |
| <b>showLastLength</b> .....                     | 456              |
| <b>showLastLength</b> .....                     | 659              |
| <b>showStaffSwitch</b> .....                    | 289              |
| signatures, polymetric .....                    | 66               |
| signumcongruentiae .....                        | 654              |
| simple closure .....                            | 657              |
| simple text strings .....                       | 614              |
| simple text strings with tie characters .....   | 641              |
| simultaneous notes and accidentals .....        | 28               |
| simultaneous phrasing slurs .....               | 117              |
| simultaneous slurs .....                        | 114              |
| singer name .....                               | 255              |
| single-staff polyphony .....                    | 146              |
| <b>skip</b> .....                               | 51, 693          |
| skipping notes in lyrics .....                  | 249              |
| <b>skipTypesetting</b> .....                    | 456              |
| <b>slashChordSeparator</b> .....                | 377              |
| slashed digits .....                            | 650              |
| slashed note heads .....                        | 37               |
| <b>slashedGrace</b> .....                       | 693              |
| slides in tablature notation .....              | 307              |
| slur and repeat .....                           | 133              |
| slur style .....                                | 114              |
| slur, dashed .....                              | 114              |
| slur, dashed phrasing .....                     | 117              |
| slur, defining dash patterns .....              | 115              |
| slur, defining dash patterns for phrasing ..... | 117              |
| slur, dotted .....                              | 114              |
| slur, dotted phrasing .....                     | 117              |
| slur, half dashed and half solid .....          | 115              |
| slur, half solid and half dashed phrasing ..... | 117              |
| slur, multiple phrasing .....                   | 117              |
| slur, phrasing .....                            | 114, 117         |
| slur, phrasing, defining dash patterns .....    | 117              |
| slur, simultaneous phrasing .....               | 117              |
| slur, solid .....                               | 114              |
| slur-event .....                                | 184              |
| <b>slurDashed</b> .....                         | 114              |
| <b>slurDashPattern</b> .....                    | 115, 693         |
| <b>slurDotted</b> .....                         | 114              |
| <b>slurDown</b> .....                           | 114              |
| <b>slurHalfDashed</b> .....                     | 115              |
| <b>slurHalfSolid</b> .....                      | 115              |
| <b>slurNeutral</b> .....                        | 114              |
| slurs .....                                     | 114              |
| slurs, above notes .....                        | 114              |
| slurs, below notes .....                        | 114              |
| slurs, manual placement .....                   | 114              |
| slurs, modifying .....                          | 562              |
| slurs, multiple .....                           | 114              |
| slurs, simultaneous .....                       | 114              |
| <b>slurSolid</b> .....                          | 114              |
| <b>slurUp</b> .....                             | 115              |
| <b>small</b> .....                              | 191, 214         |
| <b>smaller</b> .....                            | 212, 214         |
| smaller notes .....                             | 185              |
| smob .....                                      | 659              |
| snap pizzicato .....                            | 300              |
| snappizzicato .....                             | 654              |
| Solesmes .....                                  | 389              |
| solid slur .....                                | 114              |
| solo part .....                                 | 154              |
| soprano clef .....                              | 15               |
| sos .....                                       | 292              |



|                                    |          |                                |               |
|------------------------------------|----------|--------------------------------|---------------|
| sostenuto pedal                    | 292      | standalone text                | 209           |
| <b>sostenutoOff</b>                | 292      | standard font size (notation)  | 192           |
| <b>sostenutoOn</b>                 | 292      | stanza number                  | 254           |
| Sound                              | 458      | start of system                | 163           |
| Southern Harmony note heads        | 35       | start repeat                   | 133           |
| <b>southernHarmonyHeads</b>        | 35       | <b>start-repeat</b>            | 133           |
| <b>southernHarmonyHeadsMinor</b>   | 35       | <b>startGroup</b>              | 201           |
| <b>sp</b>                          | 107      | <b>startStaff</b>              | 169, 172      |
| space between staves               | 488      | <b>startTrillSpan</b>          | 125           |
| space inside systems               | 488      | staves, keyboard instruments   | 286           |
| spacer note                        | 51       | staves, keyed instruments      | 286           |
| spacer rest                        | 51       | staves, multiple               | 163           |
| spaces in lyrics                   | 227      | staves, nested                 | 166           |
| spaces, in lyrics                  | 234      | staves, piano                  | 286           |
| <b>spacing</b>                     | 504      | stem                           | 197           |
| Spacing lyrics                     | 244      | <b>Stem</b>                    | 290           |
| spacing, display of layout         | 515      | stem, direction                | 197           |
| spacing, horizontal                | 503      | stem, down                     | 197           |
| spacing, vertical                  | 488      | stem, invisible                | 197           |
| <b>spacingTweaks</b>               | 693      | stem, neutral                  | 197           |
| special arpeggio symbols           | 122      | stem, up                       | 197           |
| special characters                 | 453      | stem, with slash               | 99            |
| special characters in markup mode  | 211      | <b>stem-spacing-correction</b> | 504           |
| special note heads                 | 32       | <b>stemDown</b>                | 197           |
| splice into tagged music           | 450      | <b>stemLeftBeamCount</b>       | 82            |
| splitting notes                    | 69       | <b>stemNeutral</b>             | 197           |
| splitting rests                    | 69       | <b>stemRightBeamCount</b>      | 82            |
| <b>spp</b>                         | 107      | stems, cross-staff             | 290           |
| Sprechgesang                       | 271      | <b>stemUp</b>                  | 197           |
| Square neumes ligatures            | 403      | stencil                        | 659           |
| staccatissimo                      | 105, 654 | stencil, removing              | 550           |
| staccato                           | 105, 654 | <b>stopGroup</b>               | 201           |
| stacking text in a column          | 618      | stopped                        | 105, 654      |
| staff change line                  | 289      | <b>stopStaff</b>               | 169, 172, 176 |
| staff changes, automatic           | 288      | <b>stopTrillSpan</b>           | 125           |
| staff changes, manual              | 286      | <b>storePredefinedDiagram</b>  | 331, 693      |
| staff distance                     | 488      | string numbers                 | 301           |
| staff group                        | 163      | string vs. fingering numbers   | 301           |
| staff initiation                   | 162      | string, indicating open        | 298           |
| staff instantiation                | 162      | strings, orchestral            | 298           |
| staff lines, modifying             | 169      | strings, writing for           | 298           |
| staff lines, stopping and starting | 169      | <b>stringTuning</b>            | 315, 694      |
| staff size, setting                | 479      | <b>stringTunings</b>           | 315, 327      |
| staff switching                    | 289      | strumming rhythms, showing     | 70            |
| staff symbol                       | 169      | style, rehearsal mark          | 96            |
| staff symbol, setting of           | 545      | style, slur                    | 114           |
| staff, choir                       | 163      | <b>styledNoteHeads</b>         | 694           |
| staff, drum                        | 162      | styles, note heads             | 32            |
| staff, empty                       | 176      | styles, voice                  | 149           |
| staff, Frenched                    | 172      | <b>sub</b>                     | 213           |
| staff, grand                       | 163      | subbass clef                   | 15            |
| staff, hiding                      | 176      | subscript                      | 213           |
| staff, multiple                    | 163      | subscript text                 | 615           |
| staff, nested                      | 166      | <b>suggestAccidentals</b>      | 397           |
| staff, new                         | 162      | <b>super</b>                   | 213           |
| staff, percussion                  | 162      | superscript                    | 213           |
| staff, piano                       | 163      | superscript text               | 616           |
| staff, resizing of                 | 172      | <b>sus</b>                     | 372           |
| staff, single                      | 162      | sustain pedal                  | 292           |
| <b>staff-affinity</b>              | 488      | sustain pedal style            | 292           |
| staff-change line                  | 289      | <b>sustainOff</b>              | 292           |
| <b>staff-staff-spacing</b>         | 488      | <b>sustainOn</b>               | 292           |
| <b>Staff.midiInstrument</b>        | 459      | SVG output                     | 457           |
| <b>Staff_symbol_engraver</b>       | 176      | switching fonts                | 212           |
| <b>staffgroup-staff-spacing</b>    | 488      | switching instruments          | 182           |

|                                 |     |
|---------------------------------|-----|
| syllable durations, automatic   | 230 |
| symbols, non-musical            | 219 |
| syntax, markup                  | 210 |
| system                          | 163 |
| system separator mark           | 168 |
| system start delimiters         | 163 |
| system start delimiters, nested | 166 |
| <b>system-count</b>             | 476 |
| <b>system-separator-markup</b>  | 477 |
| <b>system-system-spacing</b>    | 473 |
| <b>systems-per-page</b>         | 476 |

## T

|                                      |               |
|--------------------------------------|---------------|
| tab clef                             | 317           |
| <b>tabChordRepeats</b>               | 694           |
| <b>tabChordRepetition</b>            | 694           |
| tablature                            | 162, 300      |
| tablature and harmonic indications   | 307           |
| tablature and slides                 | 307           |
| tablature, banjo                     | 300, 315, 345 |
| tablature, bass                      | 315           |
| tablature, bass guitar               | 315           |
| tablature, cello                     | 315           |
| tablature, custom string tunings     | 315           |
| tablature, double bass               | 315           |
| tablature, guitar                    | 300, 315      |
| tablature, mandolin                  | 315           |
| tablature, predefined string tunings | 315           |
| tablature, ukulele                   | 315           |
| tablature, viola                     | 315           |
| tablature, violin                    | 315           |
| tablaturs, basic                     | 303           |
| tablaturs, custom                    | 315           |
| tablaturs, default                   | 303           |
| tabstaff                             | 162           |
| <b>TabStaff</b>                      | 162, 303      |
| <b>TabVoice</b>                      | 303           |
| tag                                  | 450           |
| <b>tag</b>                           | 694           |
| <b>taor</b>                          | 358           |
| taqasim                              | 418           |
| <b>teaching</b>                      | 27            |
| teaching accidental style            | 27            |
| <b>teeny</b>                         | 191, 214      |
| Template Arabic music                | 419           |
| <b>tempo</b>                         | 61            |
| tempo marks within tuplet brackets   | 44            |
| tenor clef                           | 15            |
| tenor clef, choral                   | 16            |
| tenuto                               | 105, 654      |
| <b>text</b>                          | 292           |
| text alignment commands              | 217           |
| text columns, left-aligned           | 626           |
| text columns, right-aligned          | 628           |
| text in columns                      | 216           |
| text in volta bracket                | 134           |
| text items, non-empty                | 202           |
| text marks                           | 205           |
| text markup                          | 210           |
| text on bar line                     | 205           |
| text on multi-measure rest           | 53            |
| text outside margin                  | 203           |
| text padding                         | 218           |

|                                                     |             |
|-----------------------------------------------------|-------------|
| Text scripts                                        | 202         |
| text size                                           | 212         |
| text spanners                                       | 203         |
| text spanners, formatting                           | 203         |
| text spread over multiple pages                     | 222         |
| text, aligning                                      | 214         |
| text, centering on the page                         | 216         |
| text, decorating                                    | 217         |
| text, framing                                       | 217         |
| text, horizontal alignment                          | 214         |
| text, justified                                     | 216         |
| text, keeping inside margin                         | 203         |
| text, multi-line                                    | 216         |
| Text, other languages                               | 202         |
| text, separate                                      | 209         |
| text, standalone                                    | 209         |
| text, top-level                                     | 209         |
| text, vertical alignment                            | 215         |
| text, wordwrapped                                   | 216         |
| <b>textLengthOff</b>                                | 54, 203     |
| <b>textLengthOn</b>                                 | 54, 203     |
| <b>textSpannerDown</b>                              | 204         |
| <b>textSpannerNeutral</b>                           | 204         |
| <b>textSpannerUp</b>                                | 204         |
| Thorough bass                                       | 381         |
| <b>thumb</b>                                        | 192         |
| thumb                                               | 654         |
| thumb marking                                       | 105         |
| thumb-script                                        | 192         |
| tie                                                 | 46          |
| tied note, accidental                               | 5           |
| <b>tieDashed</b>                                    | 47          |
| <b>tieDashPattern</b>                               | 694         |
| <b>tieDotted</b>                                    | 47          |
| <b>tieDown</b>                                      | 47          |
| <b>tieNeutral</b>                                   | 47          |
| ties and chords                                     | 46          |
| ties and volta brackets                             | 46          |
| ties, alternative endings                           | 130         |
| ties, appearance                                    | 47          |
| ties, dashed                                        | 47          |
| ties, dotted                                        | 47          |
| ties, in lyrics                                     | 234         |
| ties, in repeats                                    | 130         |
| ties, laissez vibrer                                | 47          |
| ties, modifying                                     | 562         |
| ties, placement                                     | 47          |
| ties, repeating                                     | 46          |
| <b>tieSolid</b>                                     | 47          |
| <b>tieUp</b>                                        | 47          |
| <b>time</b>                                         | 56, 74, 694 |
| time administration                                 | 103         |
| time signature                                      | 56          |
| time signature default settings                     | 57          |
| time signature properties, restoring default values | 58          |
| time signature style                                | 57          |
| time signature, compound                            | 68          |
| time signature, visibility of                       | 56          |
| time signatures                                     | 394         |
| time signatures, double                             | 66          |
| Time signatures, multiple                           | 525         |
| time signatures, polymetric                         | 66          |
| <b>times</b>                                        | 40, 66, 694 |
| <b>timeSignatureFraction</b>                        | 66          |

|                                              |               |                                       |          |
|----------------------------------------------|---------------|---------------------------------------|----------|
| timing (within the score).....               | 103           | Turkish music.....                    | 420      |
| timing information and repeats.....          | 133           | Turkish note names.....               | 421      |
| <b>tiny</b> .....                            | 191, 214      | turn.....                             | 105, 654 |
| <b>tocItem</b> .....                         | 694           | turns in MIDI.....                    | 461      |
| <b>Top</b> .....                             | 1             | <b>tweak</b> .....                    | 694      |
| top-level text.....                          | 209           | tweaking.....                         | 538      |
| <b>top-margin</b> .....                      | 471           | tweaking control points.....          | 539      |
| <b>top-markup-spacing</b> .....              | 473           | tweaking grace notes.....             | 99       |
| <b>top-system-spacing</b> .....              | 473           | tweaks in a variable.....             | 539      |
| toplevel-bookparts.....                      | 659           | tweaks in lyrics.....                 | 539      |
| toplevel-scores.....                         | 659           | <b>two-sided</b> .....                | 475      |
| transcription of mensural music.....         | 165           | <b>type</b> .....                     | 528      |
| transformation, retrograde.....              | 13            | typeface.....                         | 657      |
| transformations, modal.....                  | 13            | typeset text.....                     | 210      |
| <b>translate</b> .....                       | 215           |                                       |          |
| <b>translate-scaled</b> .....                | 215           | <b>U</b>                              |          |
| translating text.....                        | 629           | U.C.....                              | 292      |
| transparent notes.....                       | 194           | ukulele.....                          | 319      |
| transparent, making objects.....             | 550           | una corda.....                        | 292      |
| <b>transpose</b> .....                       | 4, 9, 12, 694 | <b>unaCorda</b> .....                 | 292      |
| <b>transposedCueDuring</b> .....             | 188, 694      | <b>underline</b> .....                | 212      |
| transposing.....                             | 9             | underlining text.....                 | 617      |
| transposing clef.....                        | 16            | <b>unfold</b> .....                   | 135      |
| transposing fret diagrams.....               | 328           | unfold repeat.....                    | 135      |
| transposing instrument.....                  | 21            | unfold repeat, alternate endings..... | 135      |
| transposing instruments.....                 | 10            | <b>unfoldRepeats</b> .....            | 694      |
| transposition.....                           | 9             | <b>unHideNotes</b> .....              | 194      |
| <b>transposition</b> .....                   | 21, 183, 694  | Unicode.....                          | 454      |
| transposition and relative octave entry..... | 4             | unmetered music.....                  | 64, 103  |
| transposition of notes.....                  | 9             | unmetered music, line breaks.....     | 65       |
| transposition of pitches.....                | 9             | unmetered music, page breaks.....     | 65       |
| transposition, instrument.....               | 21            | unmetered music, with beams.....      | 65       |
| transposition, MIDI.....                     | 21            | unpure containers, Scheme.....        | 563      |
| transposition, modal.....                    | 13            | up bow indication.....                | 298      |
| tre corde.....                               | 292           | upbeat.....                           | 63       |
| treble clef.....                             | 15            | upbeat in a repeat.....               | 129      |
| <b>treCorde</b> .....                        | 292           | upbow.....                            | 105, 654 |
| <b>tremolo</b> .....                         | 139           | upmordent.....                        | 654      |
| tremolo beams.....                           | 139           | upprall.....                          | 654      |
| tremolo marks.....                           | 140           | UTF-8.....                            | 453      |
| tremolo, cross-staff.....                    | 141           |                                       |          |
| <b>tremoloFlags</b> .....                    | 140           |                                       |          |
| triads.....                                  | 369           | <b>V</b>                              |          |
| <b>triangle</b> .....                        | 219           | varbaritone clef.....                 | 15       |
| trill.....                                   | 105           | varcoda.....                          | 105, 654 |
| <b>trill</b> .....                           | 125           | variables.....                        | 427      |
| trill.....                                   | 654           | variables, use of.....                | 449      |
| trill with accidental.....                   | 126           | Vaticana, Editio.....                 | 389      |
| trills.....                                  | 125           | <b>VaticanaStaff</b> .....            | 162      |
| trills in MIDI.....                          | 461           | VaticanaStaffContext.....             | 399      |
| trills, pitched.....                         | 126           | VaticanaVoiceContext.....             | 399      |
| triplet formatting.....                      | 41            | vertical lines between staves.....    | 199      |
| triplets.....                                | 40            | vertical positioning of dynamics..... | 109      |
| tuning, non-Western.....                     | 415           | vertical spacing.....                 | 488, 507 |
| tunings, banjo.....                          | 345           | vertical text alignment.....          | 215      |
| tuplet bracket placement.....                | 41            | <b>VerticalAxisGroup</b> .....        | 488      |
| tuplet formatting.....                       | 41            | vertically centering text.....        | 630      |
| Tuplet number changes.....                   | 41            | verylongfermata.....                  | 654      |
| <b>tupletDown</b> .....                      | 41            | violin clef.....                      | 15       |
| <b>tupletNeutral</b> .....                   | 41            | visibility of objects.....            | 550      |
| <b>TupletNumber</b> .....                    | 41            | visibility of octavated clefs.....    | 554      |
| <b>tupletNumberFormatFunction</b> .....      | 41            | <b>voice</b> .....                    | 22, 24   |
| tuplets.....                                 | 40            | voice.....                            | 146      |
| <b>tupletSpannerDuration</b> .....           | 41            |                                       |          |
| <b>tupletUp</b> .....                        | 41            |                                       |          |

|                                             |          |
|---------------------------------------------|----------|
| <b>Voice</b> .....                          | 146      |
| voice accidental style.....                 | 24       |
| voice styles .....                          | 149      |
| voice, following .....                      | 289      |
| <b>voiceOne</b> .....                       | 146      |
| voices, \partcombine with \autoBeamOff..... | 73       |
| voices, divided .....                       | 264      |
| voices, multiple .....                      | 150      |
| voices, quoting .....                       | 183, 185 |
| <b>void</b> .....                           | 694      |
| <b>volta</b> .....                          | 127      |
| volta bracket.....                          | 133      |
| volta bracket with text .....               | 134      |
| volta brackets and ties .....               | 46       |
| volta, prima .....                          | 127      |
| volta, seconda.....                         | 127      |

## W

|                               |    |
|-------------------------------|----|
| Walker shape note heads ..... | 35 |
| <b>walkerHeads</b> .....      | 35 |

|                                    |     |
|------------------------------------|-----|
| <b>walkerHeadsMinor</b> .....      | 35  |
| <b>whichBar</b> .....              | 89  |
| White mensural ligatures.....      | 398 |
| whitespace.....                    | 427 |
| whole rest for a full measure..... | 52  |
| wind instruments .....             | 354 |
| <b>with-color</b> .....            | 195 |
| <b>withMusicProperty</b> .....     | 694 |
| <b>wordwrap</b> .....              | 216 |
| <b>wordwrap-lines</b> .....        | 222 |
| wordwrapped text .....             | 216 |
| writing music in parallel .....    | 159 |
| written-out repeats .....          | 135 |

## X

|                        |          |
|------------------------|----------|
| <b>X-offset</b> .....  | 488      |
| <b>x11 color</b> ..... | 195, 196 |
| <b>x11-color</b> ..... | 195, 196 |
| <b>xNote</b> .....     | 694      |
| <b>xNotesOn</b> .....  | 694      |