

Hypertext marks in L^AT_EX

Sebastian Rahtz

Email: [sebastian.rahtz at oucs.ox.ac.uk](mailto:sebastian.rahtz@oucs.ox.ac.uk)

Heiko Oberdiek (maintainer)

Email: [heiko.oberdiek at googlemail.com](mailto:heiko.oberdiek@gmail.com)

2012/09/27 v6.83g

1 Documentation overview for hyperref

The documentation for package `hyperref` consists of several files:

[Manual](#) The **USER MANUAL** (also available as HTML).

[README](#) The **README** file (also available as text file). Here information is collected that is not yet in the manual: new features, package compatibility, limitations, known problems, ...

[ChangeLog](#) This file records the version history (also available as text file).

[Options](#) This file provides a short option summary.

[Bookmark talk, slides](#) Slides for the talk “PDF information and navigation elements with hyperref, pdfTeX and thumbpdf” at EuroT_EX 1999.

[Bookmark talk, paper](#) The paper version of the talk.

Source code documentation:

 [hyperref.dtx](#) This is the source code documentation for hyperref (this file).

[backref.dtx](#) “Back referencing from bibliographical citations”

[nameref.dtx](#) “Section name references in L^AT_EX”

2 Contents

1	Documentation overview for hyperref	1
2	Contents	2
3	File hycheck.tex	7
4	Package options and setup	11
4.1	Save catcodes	11
4.2	Version check	13
4.3	Checks with regular expressions	14
4.4	Compatibility with format dumps	15
4.5	Switches	16
5	Common help macros	17
5.1	Macros for recursions	17
5.2	Babel's protection of shorthand characters	18
5.3	Coordinate transformations	18
6	Dealing with PDF strings	19
6.1	Description of PDF strings	19
6.2	Definition of <code>\pdfstringdef</code>	19
6.2.1	Preprocessing	20
6.2.2	Expansion	26
6.2.3	Postprocessing	27
6.3	Encodings	31
6.3.1	XeTeX	31
6.3.2	Workaround for package linguex	33
6.3.3	Catcodes saving and restoring for <code>.def</code> files	33
6.3.4	PD1 encoding	34
6.3.5	PU encoding	34
6.4	Additional user commands	35
6.4.1	<code>\texorpdfstring</code>	35
6.4.2	Hooks for <code>\pdfstringdef</code>	35
6.5	Help macros for expansion	36
6.5.1	<code>\ignorespaces</code>	36
6.5.2	Babel languages	36
6.5.3	CJK patch	42
6.5.4	CJK bookmarks	42
6.5.5	CJK unicode	44
6.5.6	<code>\@inmathwarn-Patch</code>	48
6.5.7	Unexpandable spaces	49
6.5.8	Marker for commands	50
6.5.9	<code>\hspace fix</code>	50
6.5.10	Fix for AMS classes	50
6.5.11	Reference commands	50
6.5.12	Redefining the defining commands	53
6.5.13	<code>\ifnextchar</code>	54
6.5.14	<code>\@protected@testoptifnextchar</code>	54
6.6	Help macros for postprocessing	54
6.6.1	Generic warning.	54
6.6.2	Protecting spaces	55
6.6.3	Remove grouping braces	56

6.6.4	Catcode check	57
6.6.5	Check for wrong glyphs	61
6.6.6	Replacing tokens	62
6.6.7	Support for package <code>xspace</code>	62
6.6.8	Converting to Unicode	63
6.6.9	Support for UTF-8 input encoding	65
6.6.10	Support for die faces (ifsym et. al.)	69
6.6.11	Support for moon phases of package <code>china2e</code>	70
6.6.12	Support for package <code>pifont</code>	70
7	Support of other packages	71
7.1	Class memoir	71
7.2	Package subfigure	71
7.3	Package xr and xr-hyper	72
8	Help macros for links	73
9	Options	74
9.1	Help macros	75
9.2	Defining the options	77
10	Options for different drivers	81
11	Options to add extra features	85
12	Language options	86
13	Options to change appearance of links	93
14	Bookmarking	93
15	PDF-specific options	95
15.1	Package <code>xspace</code> support	106
15.2	Option <code>draft</code>	107
15.3	PDF/A	107
15.4	Patch for babel's <code>\texttilde</code>	108
15.4.1	Driver loading	110
15.4.2	Bookmarks	113
16	User hypertext macros	116
16.1	Link box support for XeTeX	122
17	Underlying basic hypertext macros	123
18	Option ‘destlabel’	127
19	Compatibility with the <i>L^AT_EX</i>2html package	129
20	Forms creation	129
20.1	Field flags	129
20.1.1	Declarations of field flags	131
20.1.2	Set submit flags	133
20.1.3	Set annot flags in fields	134
20.1.4	Pushbutton field	134
20.1.5	Check box field	135

20.1.6	Radio button field	135
20.1.7	Text fields	135
20.1.8	Choice fields	136
20.2	Choice field	136
20.3	Forms	138
21	Setup	146
22	Low-level utility macros	147
23	Localized nullifying of package	148
24	Package nohyperref	148
25	The Mangling Of Aux and Toc Files	149
26	Title strings	151
27	Page numbers	152
28	Every page	152
28.1	PDF /PageLabels	153
28.1.1	pdfTeX and VTeX	156
28.1.2	xetex	158
28.1.3	pdfmarkbase, dvipdfm, xetex	158
29	Automated L^AT_EX hypertext cross-references	160
30	Package lastpage support	166
31	Package ifthen support	167
32	Package titlesec and titletoc support	167
33	Package varioref support	168
34	Package longtable support	169
35	Equations	169
36	Footnotes	174
37	Float captions	179
38	Bibliographic references	181
38.1	Package harvard	185
38.2	Package chicago	186
39	Page numbers	187
40	Table of contents	189
41	New counters	191
42	AMS L^AT_EX compatibility	191
42.1	\@addtoreset and \numberwithin patches	192

43 Included figures	193
44 hyperindex entries	193
45 Compatibility with foiltex	196
46 Compatibility with seminar slide package	197
47 Configuration files	205
47.1 PS/PDF strings	205
47.2 pdftex	206
47.2.1 Fix for problem with different nesting levels	220
47.3 hypertex	221
47.4 dviwindo	224
47.5 dvipdfm/xetex dvi to PDF converter	228
47.6 VTeX typesetting system	238
47.7 Fix for Adobe bug number 466320	250
47.8 Direct pdfmark support	251
47.9 Rokicki's dvips	265
47.10 VTeX's vtexpdfmark driver	267
47.11 Textures	268
47.12 dvipsone	273
47.13 TeX4ht	276
48 Driver-specific form support	278
48.1 pdfmarks	278
48.2 HyperTeX	285
48.3 TeX4ht	286
48.4 pdfTeX	288
48.5 dvipdfm, xetex	296
48.6 Common forms part	303
49 Bookmarks in the PDF file	310
49.1 Bookmarks	311
49.1.1 Rerun warning	314
49.1.2 Driver stuff	314
50 Compatibility with koma-script classes	320
51 Encoding definition files for encodings of PDF strings	321
51.1 PD1 encoding	321
51.2 PU encoding	329
51.2.1 NFSS2 accents	329
51.2.2 Basic Latin: U+0000 to U+007F	331
51.2.3 Latin-1 Supplement: U+0080 to U+00FF	333
51.2.4 Latin Extended-A: U+0080 to U+017F	337
51.2.5 Latin Extended-B: U+0180 to U+024F	342
51.2.6 IPA Extensions: U+0250 to U+02AF	346
51.2.7 Spacing Modifier Letters: U+02B0 to U+02FF	352
51.2.8 Combining Diacritical Marks: U+0300 to U+036F	353
51.2.9 Greek and Coptic: U+0370 to U+03FF	353
51.2.10 Cyrillic: U+0400 to U+04FF	356
51.2.11 Hebrew: U+0590 to U+05FF	367
51.2.12 Thai: U+0E00 to U+0E7F	368

51.2.13	Phonetic Extensions: U+1D00 to U+1D7F	368
51.2.14	Phonetic Extensions Supplement: U+1D80 to U+1DBF . . .	369
51.2.15	Latin Extended Additional: U+1E00 to U+1EFF	369
51.2.16	General Punctuation: U+2000 to U+206F	375
51.2.17	Superscripts and Subscripts: U+2070 to U+209F	376
51.2.18	Currency Symbols: U+20A0 to U+20CF	378
51.2.19	Letterlike Symbols: U+2100 to U+214F	378
51.2.20	Number Forms: U+2150 to U+218F	379
51.2.21	Arrows: U+2190 to U+21FF	380
51.2.22	Mathematical Operators: U+2200 to U+22FF	383
51.2.23	Miscellaneous Technical: U+2300 to U+23FF	394
51.2.24	Control Pictures: U+2400 to U+243F	395
51.2.25	Optical Character Recognition: U+2440 to U+245F	395
51.2.26	Enclosed Alphanumerics: U+2460 to U+24FF	395
51.2.27	Box Drawing: U+2500 to 257F	398
51.2.28	Geometric Shapes: U+25A0 to U+25FF	398
51.2.29	Miscellaneous Symbols: U+2600 to U+26FF	399
51.2.30	Dingbats: U+2700 to U+27BF	403
51.2.31	Miscellaneous Mathematical Symbols-A: U+27C0 to U+27EF	406
51.2.32	Supplemental Arrows-A: U+27F0 to U+27FF	406
51.2.33	Supplemental Arrows-B: U+2900 to U+297F	407
51.2.34	Miscellaneous Mathematical Symbols-B: U+2980 to U+29FF	409
51.2.35	Supplemental Mathematical Operators: U+2A00 to U+2AFF	409
51.2.36	Miscellaneous Symbols and Arrows: U+2B00 to U+2BFF .	412
51.2.37	Latin Extended-C: U+2C60 to U+2C7F	413
51.2.38	Supplemental Punctuation: U+2E00 to U+2E7F	413
51.2.39	Modifier Tone Letters: U+A700 to U+A71F	413
51.2.40	Latin Extended-D: U+A720 to U+A7FF	413
51.2.41	Alphabetic Presentation Forms: U+FB00 to U+FB4F . . .	413
51.2.42	Musical Symbols: U+1D100 to U+1D1FF	413
51.2.43	Miscellaneous Symbols and Pictographs: U+1F300 to U+1F5FF	414
51.2.44	Transport and Map Symbols: U+1F680 to U+1F6FF . . .	414
51.2.45	Miscellaneous	414
51.2.46	Aliases	415
51.3	PU encoding, additions for VnT _E X	415
51.4	PU encoding, additions for Arabi	417
52	End of file hycheck.tex	441
53	Index	442

3 File hycheck.tex

Many commands of L^AT_EX or other packages cannot be overloaded, but have to be redefined by hyperref directly. If these commands change in newer versions, these changes are not noticed by hyperref. With this test file this situation can be checked. It defines the command `\checkcommand` that is more powerful than L^AT_EX's `\CheckCommand`, because it takes `\DeclareRobustCommand` and optional parameters better into account.

```
1 <*check>
2 \documentclass{article}
3 \makeatletter
```

`\checklatex` Optional argument: release date of L^AT_EX.

```
4 \newcommand*{\checklatex}[1]{}{%
5   \typeout{}%
6   \typeout{* Format: 'LaTeX2e' #1}%
7   \typeout{\space\space Loaded: '\fmtname' \fmtversion}%
8 }%
```

`\checkpackage` The argument of `\checkpackage` is the package name without extension optionally followed by a release date.

```
9 \newcommand*{\checkpackage}[1]{}%
10 \def\HyC@package{#1}%
11 \let\HyC@date\@empty
12 \@ifnextchar\HyC@getDate\HyC@checkPackage
13 }
```

`\HyC@getDate` The release date is scanned.

```
14 \def\HyC@getDate[#1]{}%
15 \def\HyC@date{#1}%
16 \HyC@checkPackage
17 }
```

`\HyC@checkPackage`

```
18 \def\HyC@checkPackage{%
19   \typeout{}%
20   \begingroup
21   \edef\x{\endgroup
22     \noexpand\RequirePackage{\HyC@package}%
23     \ifx\HyC@date\@empty\relax\else\HyC@date\fi%
24   }%
25   \x
26   \typeout{}%
27   \typeout{%
28     * Package '\HyC@package'%
29     \ifx\HyC@date\@empty
30       \else
31         \space\HyC@date
32       \fi
33   }%
34   \@ifundefined{ver@\HyC@package.sty}{%
35   }{%
36     \typeout{%
37       \space\space Loaded: '\HyC@package' %
38       \cname ver@\HyC@package.sty\endcsname
39     }%
```

```

40 }%
41 }

```

`\checkcommand` The macro `\checkcommand` parses the next tokens as a L^AT_EX definition and compares this definition with the current meaning of that command.

```

42 \newcommand*{\checkcommand}[1]{%
43   \begingroup
44   \ifx\long#1\relax
45     \expandafter\HyC@checklong
46   \else
47     \def\HyC@defcmd{#1}%
48     \expandafter\let\expandafter\HyC@next
49       \csname HyC@\expandafter\@gobble\string#1\endcsname
50     \expandafter\HyC@checkcommand
51   \fi
52 }

```

`\HyC@checklong` The definition command `\def` or `\edef` is read.

```

53 \def\HyC@checklong#1{%
54   \def\HyC@defcmd{\long#1}%
55   \expandafter\let\expandafter\HyC@next
56     \csname HyC@\expandafter\@gobble\string#1\endcsname
57   \HyC@checkcommand
58 }

```

`\HyC@checkcommand` The optional star of L^AT_EX's definitions is parsed.

```

59 \def\HyC@checkcommand{%
60   \ifx\HyC@next\relax
61     \PackageError{hycheck}{%
62       Unknown command '\expandafter\strip@prefix\meaning\HyC@cmd'%
63     }\@ehd
64     \expandafter\endinput
65   \fi
66   \@ifstar{%
67     \def\HyC@star{*}%
68     \HyC@check
69   }{%
70     \let\HyC@star\@empty
71     \HyC@check
72   }%
73 }

```

`\HyC@check` The macro `\HyC@check` reads the definition command.

```

74 \def\HyC@check#1{%
75   \def\HyC@cmd{#1}%
76   \let\HyC@org@cmd#1%
77   \let#1\relax
78   \let\HyC@param\@empty
79   \HyC@Toks{}%
80   \let\HyC@org@optcmd\HyC@noValue
81   \let\HyC@org@robustcmd\HyC@noValue
82   \let\HyC@org@robustoptcmd\HyC@noValue
83   \HyC@next
84 }

```

`\HyC@noValue`

```

85 \def\HyC@noValue{NoValue}

```


`\HyC@newcommand` The code for `\newcommand`.

```
86 \def\HyC@newcommand{%
87   \let\HyC@@cmd\HyC@cmd
88   \@ifnextchar[\HyC@nc@opt\HyC@nc@noopt
89 }
```

`\HyC@Toks` A register for storing the default value of an optional argument.

```
90 \newtoks\HyC@Toks
```

`\HyC@nc@noopt` This macro `\HyC@nc@noopt` is called, if the parser has reached the definition text.

```
91 \long\def\HyC@nc@noopt#1{%
92   \edef\x{%
93     \expandafter\noexpand\HyC@defcmd
94     \HyC@star
95     \expandafter\noexpand\HyC@cmd
96     \HyC@param\the\HyC@Toks
97   }%
98   \x{#1}%
99   \HyC@doCheck
100 }
```

`\HyC@nc@opt` This macro scans the first optional argument of a L^AT_EX definition (number of arguments).

```
101 \def\HyC@nc@opt[#1]{%
102   \def\HyC@param{{#1}}%
103   \@ifnextchar[\HyC@nc@default\HyC@nc@noopt
104 }
```

`\HyC@nc@default` Macro `\HyC@nc@default` scans the default for an optional argument.

```
105 \def\HyC@nc@default[#1]{%
106   \HyC@Toks={{#1}}%
107   \edef\HyC@optcmd{%
108     \expandafter\noexpand
109     \csname\expandafter\string\HyC@@cmd\endcsname
110   }%
111   \expandafter\let\expandafter\HyC@org@optcmd\HyC@optcmd
112   \HyC@nc@noopt
113 }
```

`\HyC@DeclareRobustCommand` `\DeclareRobustCommand{\cmd}` makes the command `\cmd` robust, that then calls `\cmd␣` with an space at the end of the command name, defined by `\newcommand`. Therefore the further parsing is done by `\HyC@nc@opt` or `\HyC@nc@noopt` of the `\HyC@newcommand` chain.

```
114 \def\HyC@DeclareRobustCommand{%
115   \edef\HyC@robustcmd{%
116     \expandafter\noexpand
117     \csname\expandafter\expandafter\expandafter\@gobble
118     \expandafter\string\HyC@cmd\space\endcsname
119   }%
120   \expandafter\let\expandafter\HyC@org@robustcmd\HyC@robustcmd
121   \expandafter\let\HyC@robustcmd\relax
122   \let\HyC@@cmd\HyC@robustcmd
123   \@ifnextchar[\HyC@nc@opt\HyC@nc@noopt
124 }
```

`\HyC@def` The parameter text of `\def` or `\edef` is stored in the token register `\HyC@Toks`.

```

\HyC@edef 125 \def\HyC@def#1#{%
126   \HyC@Toks={#1}%
127   \HyC@nc@noopt
128 }
129 \let\HyC@edef\HyC@def

```

`\HyC@doCheck` This command performs the checks and prints the result.

```

130 \def\HyC@doCheck{%
131   \typeout{* Checking ‘\HyC@string\HyC@cmd’}%
132   \HyC@checkItem{cmd}%
133   \HyC@checkItem{robustcmd}%
134   \HyC@checkItem{optcmd}%
135   \HyC@checkItem{robustoptcmd}%
136   \endgroup
137 }

```

`\HyC@checkItem` A single check.

```

138 \def\HyC@checkItem#1{%
139   \expandafter\ifx\csname HyC@org@#1\endcsname\HyC@noValue
140   \else
141     \expandafter\expandafter\expandafter\ifx
142     \csname HyC@#1\expandafter\endcsname
143     \csname HyC@org@#1\endcsname
144     \expandafter\HyC@checkOk\csname HyC@#1\endcsname
145   \else
146     \expandafter\HyC@checkFailed
147     \csname HyC@#1\expandafter\endcsname
148     \csname HyC@org@#1\endcsname
149   \fi
150 \fi
151 }

```

`\HyC@string` Some shorthands.

```

\HyC@meaning 152 \def\HyC@string#1{\expandafter\string#1}
153 \def\HyC@meaning#1{\expandafter\meaning#1}

```

`\HyC@checkOk` The result, if the check succeeds.

```

154 \def\HyC@checkOk#1{%
155   \typeout{\space\space‘\HyC@string#1’ ok.}%
156 }

```

`\HyC@checkFailed` The result, if the check fails.

```

157 \def\HyC@checkFailed#1#2{%
158   \typeout{\space\space‘\HyC@string#1’ failed.}%
159   \typeout{\space\space* original: \meaning#2}%
160   \typeout{\space\space* expected: \HyC@meaning#1}%
161 }

162 % *****
163 \</check>
164 \<*/package>

```

4 Package options and setup

4.1 Save catcodes

There are many packages that change the standard catcodes.

First we save the original meaning of ‘ and = in the token register \toks@, because we need the two characters in the macros \Hy@SetCatcodes and \Hy@RestoreCatcodes.

```
165 \begingroup
166 \@makeother\'%
167 \@makeother\=%
168 \edef\x{%
169   \edef\noexpand\x{%
170     \endgroup
171     \noexpand\toks@{%
172       \catcode 96=\noexpand\the\catcode'\noexpand'\relax
173       \catcode 61=\noexpand\the\catcode'\noexpand\=\relax
174     }%
175   }%
176   \noexpand\x
177 }%
178 \x
179 \@makeother\'
180 \@makeother\=
```

\Hy@SetCatcodes

```
181 \def\Hy@SetCatcodes{%
182   \@makeother\'%
183   \@makeother\=%
184   \catcode'\$=3 %
185   \catcode'\&=4 %
186   \catcode'\^=7 %
187   \catcode'\_ =8 %
188   \@makeother\| %
189   \@makeother\: %
190   \@makeother\(%
191   \@makeother\) %
192   \@makeother\[ %
193   \@makeother\] %
194   \@makeother\/ %
195   \@makeother\! %
196   \@makeother\< %
197   \@makeother\> %
198   \@makeother\. %
199   \@makeother\; %
200   \@makeother\+ %
201   \@makeother\- %
202   \@makeother\" %
203   \@makeother\' %
204 }
```

\Hy@RestoreCatcodes

```
205 \begingroup
206 \def\x#1{\catcode'\noexpand#1=\the\catcode'#1\relax}%
207 \xdef\Hy@RestoreCatcodes{%
208   \the\toks@
209   \x\$%
```

```

210 \x\&%
211 \x\^%
212 \x\_%
213 \x\|%
214 \x\:%
215 \x\( %
216 \x\) %
217 \x\[ %
218 \x\] %
219 \x\/%
220 \x\!%
221 \x\<%
222 \x\>%
223 \x\.%
224 \x\;%
225 \x\+%
226 \x\-%
227 \x\"%
228 \x\'%
229 }%
230 \endgroup

```

```

231 \Hy@SetCatcodes

```

It needs the December 95 release of L^AT_EX, because it uses `\protected@write`, and it defines commands in options; and the page setup internal code changed at that point. It'll probably break with the later releases!

Use package `hobsub-hyperref` for faster package loading.

```

232 \IfFileExists{hobsub-hyperref.sty}{%
233 \RequirePackage{hobsub-hyperref}[2011/01/30]%
234 }{}

235 \RequirePackage{ltxcmds}[2010/11/12]
236 \RequirePackage{ifpdf}[2006/02/20]
237 \RequirePackage{pdftexcmds}[2009/04/10]
238 \@ifpackagelater{pdftexcmds}{2010/11/04}{%}{%
239 \ltx@ifundefined{pdfdraftmode}{%
240 \let\pdf@ifdraftmode\ltx@secondoftwo
241 }{%
242 \ifpdf
243 \def\pdf@ifdraftmode{%
244 \ifnum\pdfdraftmode=\ltx@one
245 \expandafter\ltx@firstoftwo
246 \else
247 \expandafter\ltx@secondoftwo
248 \fi
249 }%
250 \else
251 \let\pdf@ifdraftmode\ltx@secondoftwo
252 \fi
253 }%
254 }

255 \RequirePackage{infwarerr}[2010/04/08]
256 \RequirePackage{keyval}[1997/11/10]
257 \RequirePackage{kvsetkeys}[2007/09/29]
258 \RequirePackage{pdfescape}[2007/11/11]
259 \RequirePackage{ifvtex}
260 \RequirePackage{ifxetex}[2006/08/21]

```

```

261 \RequirePackage{hycolor}
262 \RequirePackage{letltxmacro}[2008/06/13]
263 \RequirePackage{auxhook}[2009/12/14]
264 \def\Hy@Error{\@PackageError{hyperref}}
265 \def\Hy@Warning{\@PackageWarning{hyperref}}
266 \def\Hy@WarningNoLine{\@PackageWarningNoLine{hyperref}}
267 \def\Hy@Info{\@PackageInfo{hyperref}}
268 \def\Hy@InfoNoLine{\@PackageInfoNoLine{hyperref}}
269 \def\Hy@Message#1{%
270   \GenericWarning{%
271     (hyperref)\@spaces\@spaces\@spaces\@spaces
272   }{%
273     Package hyperref Message: #1\ltx@gobble
274   }%
275 }

```

4.2 Version check

\Hy@VersionChecked

```

276 \chardef\Hy@VersionChecked=0 %

```

\Hy@VersionCheck

```

277 \def\Hy@VersionCheck#1{%
278   \begingroup
279   \ltx@ifundefined{ver@hyperref.sty}{%
280     \Hy@Error{%
281       This should not happen!\MessageBreak
282       Missing hyperref version%
283     }\@ehd
284   }{%
285     \ltx@ifundefined{ver@#1}{%
286       \Hy@Error{%
287         This should not happen!\MessageBreak
288         Missing version of '#1'%
289       }\@ehd
290     }{%
291       \def\x##1##2##3{%
292         \expandafter\expandafter\expandafter\Hy@@VersionCheck
293         \expandafter\expandafter\expandafter##2%
294         \csname ver@##3\endcsname##1##1\@nil
295       }%
296       \x{ }\y{hyperref.sty}%
297       \x{ }\z{#1}%
298       \ifx\y\z
299         \else
300         \edef\a{#1}%
301         \edef\b{\HyOpt@CustomDriver.def}%
302         \ifx\a\b
303           \Hy@WarningNoLine{%
304             Version mismatch (custom driver)!\MessageBreak
305             * \y: hyperref.sty\MessageBreak
306             * \z: \a
307           }%
308         \else
309           \Hy@Error{%
310             Version mismatch!\MessageBreak
311             * \y: hyperref.sty\MessageBreak

```

```

312      * \z: \a
313    }\@ehd
314    \fi
315    \fi
316  }%
317 }%
318 \endgroup
319 \chardef\Hy@VersionChecked=1 %
320 }

```

\Hy@@VersionCheck

```

321 \def\Hy@@VersionCheck #1#2 #3 #4\@nil{%
322 \def#1{#2 #3}%
323 }

```

4.3 Checks with regular expressions

```

324 \ltx@ifundefined{pdfmatch}{%
325 \let\Hy@Match\ltx@gobblefour
326 }{%
327 \def\Hy@Match#1#2{%
328 \begingroup
329 \edef\~{\ltx@backslashchar\string~}%
330 \edef\.\{\ltx@backslashchar.}%
331 \edef\[\{\ltx@backslashchar[]}%
332 \edef\$\{\ltx@backslashchar$}%
333 \edef\(\{\ltx@backslashchar(}%
334 \edef\)\{\ltx@backslashchar)}%
335 \edef\|\{\ltx@backslashchar|}%
336 \edef\*\{\ltx@backslashchar*}%
337 \edef\+\{\ltx@backslashchar+}%
338 \edef\?\{\ltx@backslashchar?}%
339 \edef\{\{\ltx@backslashchar\ltx@leftbracechar}%
340 \edef\}\{\ltx@rightbracechar}%
341 \edef\\{\ltx@backslashchar\ltx@backslashchar}%
342 \let\ \ltx@space
343 \ifcase\pdfmatch{#2}{#1} %
344 \endgroup
345 \expandafter\ltx@secondoftwo
346 \or
347 \endgroup
348 \expandafter\ltx@firstoftwo
349 \else
350 \Hy@Warning{%
351 Internal error: Wrong pattern!\MessageBreak
352 --> #2 <--\MessageBreak
353 Pattern check ignored%
354 }%
355 \endgroup
356 \expandafter\ltx@firstoftwo
357 \fi
358 }%
359 \ltx@ifpackagelater{ltxcmds}{2010/09/11}{%
360 \begingroup
361 \lccode'0='{\relax
362 \lowercase{\endgroup
363 \def\ltx@leftbracechar{0}%

```

```

364 }%
365 \begingroup
366 \lccode'0='}\relax
367 \lowercase{\endgroup
368 \def\ltx@rightbracechar{0}%
369 }%
370 }%
371 }

```

4.4 Compatibility with format dumps

`\AfterBeginDocument` For use with pre-compiled formats, created using the `ldump` package, there needs to be 2 hooks for adding material delayed until `\begin{document}`. These are called `\AfterBeginDocument` and `\AtBeginDocument`. If `ldump` is not loaded, then a single hook suffices for normal L^AT_EX processing.

The default definition of `\AfterBeginDocument` cannot be done by `\let` because of problems with `xypic`.

```

372 \@ifundefined{AfterBeginDocument}{%
373 \def\AfterBeginDocument{\AtBeginDocument}%
374 }{}%

```

`\Hy@AtBeginDocument` For the case that package ‘hyperref’ is loaded using `\AtBeginDocument`, we have to wrap the calls of `\AtBeginDocument`/`\AfterBeginDocument` in `\AtEndOfPackage`. However, packages must be loaded in `\AtEndOfPackage` *before* package ‘kvoptions’ has to perform its option cleanup. Therefore we use a hook.

```

375 \def\Hy@AtBeginDocument{%
376 \ltx@LocalAppendToMacro\Hy@AtBeginDocumentHook
377 }

```

`\Hy@AtEndOfPackage`

```

378 \def\Hy@AtEndOfPackage{%
379 \ltx@LocalAppendToMacro\Hy@AtEndOfPackageHook
380 }

```

`\Hy@AtBeginDocumentHook`

```

381 \let\Hy@AtBeginDocumentHook\ltx@empty

```

`\Hy@AtEndOfPackageHook`

```

382 \let\Hy@AtEndOfPackageHook\ltx@empty

```

Install the hook, before package ‘kvoptions’ is loaded.

```

383 \AtEndOfPackage{%
384 \Hy@AtEndOfPackageHook
385 \let\Hy@AtEndOfPackageHook\@undefined
386 \AfterBeginDocument{%
387 \Hy@AtBeginDocumentHook}%
388 \let\Hy@AtBeginDocumentHook\@undefined
389 }%
390 }

```

Package `kvoptions` is used for processing options that are given as key value pairs. The package provides `\ProcessKeyvalOptions`, formerly known as `\ProcessOptionsWithKV`.

```

391 \RequirePackage{kvoptions}[2009/07/21]

```

4.5 Switches

```
392 \newif\ifHy@stoppeearly
393 \newif\ifHy@typexml
394 \newif\ifHy@activeanchor
395 \newif\ifHy@backref
396 \newif\ifHy@bookmarks
397 \newif\ifHy@bookmarksnumbered
398 \newif\ifHy@bookmarksopen
399 \newif\ifHy@breaklinks
400 \newif\ifHy@pdfcenterwindow
401 \newif\ifHy@CJKbookmarks
402 \newif\ifHy@colorlinks
403 \newif\ifHy@destlabel
404 \newif\ifHy@draft
405 \let\Hy@finaltrue\Hy@draftfalse
406 \let\Hy@finalfalse\Hy@drafttrue
407 \newif\ifHy@pdfescapeform
408 \newif\ifHy@hyperfigures
409 \newif\ifHy@pdfitwindow
410 \newif\ifHy@frenchlinks
411 \newif\ifHy@hyperfootnotes
412 \newif\ifHy@hyperindex
413 \newif\ifHy@hypertextnames
414 \newif\ifHy@implicit
415 \newif\ifHy@linktocpage
416 \newif\ifHy@localanchorname
417 \newif\ifHy@pdfmenubar
418 \newif\ifHy@naturalnames
419 \newif\ifHy@nesting
420 \newif\ifHy@pdfnewwindowset
421 \newif\ifHy@pdfnewwindow
422 \newif\ifHy@ocgcolorlinks
423 \newif\ifHy@pageanchor
424 \newif\ifHy@pdfpagelabels
425 \newif\ifHy@pdfpagehidden
426 \newif\ifHy@pdfstring
427 \newif\ifHy@plainpages
428 \newif\ifHy@psize
429 \newif\ifHy@raiselinks
430 \newif\ifHy@seminarslides
431 \newif\ifHy@setpagesize
432 \newif\ifHy@texht
433 \newif\ifHy@psdextra
434 \newif\ifHy@pdftoolbar
435 \newif\ifHy@unicode
436 \newif\ifHy@pdfusetitle
437 \newif\ifHy@verbose
438 \let\Hy@debugtrue\Hy@verbosettrue
439 \let\Hy@debugfalse\Hy@verbosefalse
440 \newif\ifHy@pdfwindowui
441 \newif\ifHy@pdfdisplaydoctitle
442 \newif\ifHy@pdfa
```

Defaults for the switches are now set.

```
443 \Hy@backreffalse
444 \Hy@bookmarksnumberedfalse
445 \Hy@bookmarksopenfalse
```



```

446 \Hy@bookmarkstrue
447 \Hy@breaklinksfalse
448 \Hy@pdfcenterwindowfalse
449 \Hy@CJKbookmarksfalse
450 \Hy@destlabelfalse
451 \Hy@pdfescapeformfalse
452 \Hy@hyperfiguresfalse
453 \Hy@pdf-fitwindowfalse
454 \Hy@hyperfootnotesttrue
455 \Hy@hyperindextrue
456 \Hy@hypertextnamestrue
457 \Hy@implittrue
458 \Hy@linktocpagefalse
459 \Hy@localanchornamefalse
460 \Hy@pdfmenubartrue
461 \Hy@naturalnamesfalse
462 \Hy@nestingfalse
463 \Hy@pdfnewwindowsetfalse
464 \Hy@pdfnewwindowfalse
465 \Hy@pageanchortrue
466 \Hy@pdfpagelabelstrue
467 \Hy@pdfpagehiddenfalse
468 \Hy@pdfstringfalse
469 \Hy@plainpagesfalse
470 \Hy@raiselinksfalse
471 \Hy@setpagesizetrue
472 \Hy@texhtfalse
473 \Hy@psdextrafalse
474 \Hy@pdftoolbartrue
475 \Hy@typexmlfalse
476 \Hy@unicodedefalse
477 \Hy@pdfusetitlefalse
478 \Hy@verbosefalse
479 \Hy@pdfwindowuitrue
480 \Hy@pdfdisplaydoctitlefalse
481 \Hy@pdfafalse

```

5 Common help macros

\Hy@StepCount

```

482 \def\Hy@StepCount#1{\advance#1 by 1 }%

```

\Hy@GlobalStepCount

```

483 \def\Hy@GlobalStepCount#1{\global\advance#1 by 1 }%

```

```

484 \newdimen\@linkdim
485 \let\Hy@driver\ltx@empty
486 \let\MaybeStopEarly\relax
487 \newcount\Hy@linkcounter
488 \newcount\Hy@pagecounter
489 \Hy@linkcounter0
490 \Hy@pagecounter0

```

5.1 Macros for recursions

```

491 \let\Hy@ReturnEnd\@empty
492 \long\def\Hy@ReturnAfterFiFiEnd#1\fi#2\Hy@ReturnEnd{\fi\fi#1}

```

```
493 \long\def\Hy@ReturnAfterElseFiFiEnd#1\else#2\Hy@ReturnEnd{\fi\fi#1}
```

5.2 Babel's protection of shorthand characters

`\Hy@safe@activetrue` Babel's switch setting commands cannot be used directly, because they can be undefined if babel is not loaded.

```
494 \def\Hy@safe@activetrue{\csname @safe@activetrue\endcsname}
495 \def\Hy@safe@activesfalse{\csname @safe@activesfalse\endcsname}
```

5.3 Coordinate transformations

At some places numbers in pdf units are expected (eg: FitBH, ...). The following macros perform the transformation from TeX units (pt) to PDF units (bp).

`\hypercalsbp` The user macro `\hypercalsbp` can be used, for example, inside option values:

```
pdfstartview={FitBH \hypercalsbp{\paperheight-\topmargin-1in}}
```

- It cannot be used inside `\usepackage`, because LaTeX expands the options before package hyperref is loaded and `\hypercalsbp` is defined.
- With e-TeX extensions an expandable implementation is very easy; `\hypercalsbp` can be used everywhere and is expanded at use.
- Without e-TeX's features `\hypercalsbp` cannot be implemented expandable (practically) and have to be supported by `\hypercalsbpdef`. Limitations:
 - Works only in options that use `\hypercalsbpdef` (currently only `pdfstartview`).
 - For calculations package calc has to be loaded.
 - The expansion of the argument is done at definition time.

Example (TeX):

```
\usepackage{calc}
\usepackage[...]{hyperref}
\hypersetup{
  pdfstartview={FitBH \hypercalsbp{\paperheight-\topmargin-1in
    -\headheight-\headsep}
}
```

`\hypercalsbp`

```
496 \begingroup\expandafter\expandafter\expandafter\endgroup
497 \expandafter\ifx\csname dimexpr\endcsname\relax
498   \def\hypercalsbpdef#1#2{%
499     \begingroup
500       \toks@{}%
501       \HyCal@scan#2\hypercalsbp\@nil
502     \expandafter\endgroup
503     \expandafter\def\expandafter#1\expandafter{\the\toks@}%
504   }%
505 \def\HyCal@scan#1\hypercalsbp#2\@nil{%
506   \toks@\expandafter{\the\toks@ #1}%
507   \ifx\#2\%
508     \else
509       \ltx@ReturnAfterFi{%
510         \HyCal@do#2\@nil
511       }%
512   }
```

```

512 \fi
513 }%
514 \def\HyCal@do#1#2\@nil{%
515 \@ifpackageloaded{calc}{}{%
516 \Hy@Warning{%
517 For calculations \string\hypercalcbp\space needs\MessageBreak
518 package calc or e-TeX%
519 }%
520 }%
521 \setlength{\dimen@}{#1}%
522 \setlength{\dimen@}{0.99626401\dimen@}%
523 \edef\x{%
524 \toks@{%
525 \the\toks@
526 \strip@pt\dimen@
527 }%
528 }\x
529 \HyCal@scan#2\@nil
530 }%
531 \else
532 \def\hypercalcbp#1{%
533 \strip@pt\dimexpr 0.99626401\dimexpr(#1)\relax\relax
534 }%
535 \def\hypercalcbpdef{\def}%
536 \fi

```

6 Dealing with PDF strings

The PDF string stuff done by Heiko Oberdiek.

Naming convention: All internal commands that are only needed by `\pdfstringdef` are prefixed with `\HyPsd@`.

6.1 Description of PDF strings

The PDF specification defines several places to hold text strings (bookmark names, document information, text annotations, etc.). The PDF strings have following properties:

- They are surrounded by parentheses. The hexadecimal form is not supported.
- Like PostScript language strings they use the same escaping mechanism:

<code>\\</code>	the backslash itself
<code>\), \((</code>	unbalanced parentheses
<code>\n, \r, \t, \b, \f</code>	special white space escape sequences
<code>\ddd</code>	octal character code <code>ddd</code>
- Strings are stored either in `PDFDocEncoding`, which is a superset of ISO-Latin1 and is compatible with Unicode with character codes below 256, or in Unicode.

6.2 Definition of `\pdfstringdef`

The central macro for dealing with PDF strings is `\pdfstringdef`. It defines a command `#1` to be the result of the conversion from the string in `#2` to a legal

PDFDocEncoded string. Currently the definition is global, but this can be changed in the future.

Important: In T_EX's view PDF strings are written to a file and are expanded only in its mouth. Stomach commands that cannot be expanded further aren't executed, they are written verbatim. But the PDF reader that reads such a string isn't a T_EX interpreter!

The macro `\pdfstringdef` consists of three main parts:

1. Preprocessing. Here the expansion is prepared. The encoding is set and many commands are redefined, so that they work appropriate.
2. Expansion. The T_EX string is expanded the first time to get a PDF string.
3. Postprocessing. The result of the expansion is checked and converted to the final form.

`\pdfstringdef` `\pdfstringdef` works on the tokens in `#2` and converts them to a PDF string as far as possible:

- The result should obey the rules of the PDF specification for strings.
- The string can safely be processed by T_EX, because the tokens have only cat-codes 10 until 12.

The result is stored in the command token given in `#1`.

```
537 \def\pdfstringdef#1#2{%
```

Many redefinitions are needed, so all the work is done in a group.

```
538 \begingroup
```

6.2.1 Preprocessing

Octal escape sequences. To avoid problems with eight bit or non printable characters, the octal escape notation is supported. So most glyphs in the encoding definitions for PD1 and PU produce these octal escape sequences. All three octal digits have to be used:

- Wrong results are avoided, if digits follow that are not part of the octal sequence.
- Macros rely on the fact that the octal sequences always consist of three digits (vtex driver, Unicode support).

The escape sequences start with a backslash. By `\string` it will be printed. Therefore it is ensured that the T_EX escape character indeed prints as a normal backslash. Eventually this line can be removed, because this is standard L^AT_EX behaviour.

```
539 \escapechar'\%
```

From the view of T_EX a octal sequence consists of the command tokens `\0` until `\3` and two digits. For saving tokens `\0`, `\1`, `\2`, and `\3` are directly used without a preceding `\string` in the glyph definitions. This is done here locally by defining the `\0` until `\3` commands. So the user can use octal escape sequences directly, the disadvantage is that a previous definition of this short commands does not apply.

```
540 \edef\0{\string\0}%
```

```
541 \edef\1{\string\1}%
```

```
542 \edef\2{\string\2}%
```

```
543 \edef\3{\string\3}%
```

Setting font encoding. The unicode encoding uses \8 and \9 as marker for the higher byte. \8 is an abbreviation for the higher bytes 0 until 7 that can be expressed by one digit. \8 will be converted to \00. However \9 only marks the next three digits as higher byte and will be removed later.

The encoding is set by \enc@update for optimizing reasons.

```

544 \ifHy@unicode
545 \edef\8{\string\8}%
546 \edef\9{\string\9}%
547 \fontencoding{PU}%
548 \HyPsd@UTFviii
549 \def\ifpdfstringunicode###1##2{##1}%
550 \else
551 \fontencoding{PD1}%
552 \def\ifpdfstringunicode###1##2{##2}%
553 \fi
554 \let\utf@viii@undeferr\HyPsd@utf@viii@undeferr
555 \enc@update

```

Internal encoding commands. \pdfstringdef interpretes text strings which are not allowed to contain mathematical stuff. The text glyph commands will produce a warning, if called in math mode. But this warning disturbs while expanding. Therefore we check for math mode here, before \@inmathwarn will be disabled (see below).

```

556 \@inmathwarn\pdfstringdef

```

If a glyph is used, that isn't in the PD1/PU encoding there will be an infinite error loop, because the NFSS encoding stuff have to be expanded unprotected (\edef), so that the assignments of \@changed@cmd don't take place. To patch this behaviour I only found \@inmathwarn as a usable hook. While an \edef a warning message by \@inmathwarn or \TextSymbolUnavailable cannot be give out, so \@inmathwarn should be disabled. And with the help of it the assignments in \@changed@cmd can easily be caught (see below).

```

557 \let\@inmathwarn\HyPsd@inmathwarn

```

Unknown composite characters are built with \add@accent, so it is redefined to provide a warning.

```

558 \let\add@accent\HyPsd@add@accent

```

Commands that don't use NFSS directly. There are several commands that prints characters in the printable ASCII area that don't obey the NFSS, so they have to be redefined here.

```

559 \let\{\textbraceleft
560 \let\}\textbraceright
561 \let\\\textbackslash
562 \let\#\textnumbersign
563 \let\$\textdollar
564 \let\%\textpercent
565 \let\&\textampersand
566 % \let\~\textasciitilde
567 \let\_ \textunderscore
568 \let\P\textparagraph
569 \let\ldots\textellipsis
570 \let\dots\textellipsis

```

Newline `\newline` or `\\` do not work in bookmarks, in text annotations they should expand to `\r`. In pdf strings `\\` stands for a backslash. Therefore the commands are disabled now. The user can redefine them for a result what he want:

backslash: `\pdfstringdefDisableCommands{\let\\\textbackslash}`

new line: `\pdfstringdefDisableCommands{\let\\\textCR}`

disabled: `\pdfstringdefDisableCommands{\let\\\empty}`

At any case, however, the optional argument or the star cannot be scanned in a 100% sure manner.

```
571 \def\{\pdfstringdefWarn\}%
572 \def\newline{\pdfstringdefWarn\newline}%
```

Logos. Because the box shifting used in the \TeX logo does not work while writing to a file, the standard \TeX logos are redefined.

```
573 \def\TeX{\TeX}%
574 \def\LaTeX{\LaTeX}%
575 \def\LaTeXe{%
576   \LaTeX2%
577   \ifHy@unicode\textepsilon\else e\fi
578 }%
579 \def\eTeX{%
580   \ifHy@unicode\textepsilon\else e\fi
581   -\TeX%
582 }%
583 \def\SlTeX{\SlTeX}%
584 \def\MF{Metafont}%
585 \def\MP{Metapost}%
```

Standard font commands. Because font changes do not work, the standard font switching commands are disabled.

```
586 \let\fontencoding\@gobble
587 \let\fontfamily\@gobble
588 \let\fontseries\@gobble
589 \let\fontshape\@gobble
590 \let\fontsize\@gobbletwo
591 \let\selectfont\@empty
592 \let\usefont\@gobblefour
593 \let\emph\@firstofone
594 \let\textnormal\@firstofone
595 \let\textrm\@firstofone
596 \let\textsf\@firstofone
597 \let\texttt\@firstofone
598 \let\textbf\@firstofone
599 \let\textmd\@firstofone
600 \let\textit\@firstofone
601 \let\textsc\@firstofone
602 \let\textsl\@firstofone
603 \let\textup\@firstofone
604 \let\normalfont\@empty
605 \let\rmfamily\@empty
606 \let\sffamily\@empty
607 \let\ttfamily\@empty
```

```

608 \let\bfseries\@empty
609 \let\mdseries\@empty
610 \let\itshape\@empty
611 \let\scshape\@empty
612 \let\slshape\@empty
613 \let\upshape\@empty
614 \let\em\@empty
615 \let\rm\@empty
616 \let\Huge\@empty
617 \let\LARGE\@empty
618 \let\Large\@empty
619 \let\footnotesize\@empty
620 \let\huge\@empty
621 \let\large\@empty
622 \let\normalsize\@empty
623 \let\scriptsize\@empty
624 \let\small\@empty
625 \let\tiny\@empty
626 \let\mathversion\@gobble
627 \let\phantom\@gobble
628 \let\vphantom\@gobble
629 \let\hphantom\@gobble

```

Package pifont.

```

630 \let\ding\HyPsd@ding
631 \let\Cube\HyPsd@DieFace
632 %* \HyPsd@DieFace -> \epsdice (epsdice)
633 %* \HyPsd@DieFace -> \fcdice (hhcount)

```

Environments.

```

634 \def\begin#1{\csname#1\endcsname}%
635 \def\end#1{\csname end#1\endcsname}%

```

Package color.

```

636 \def\textcolor##1##{\@secondoftwo}%

```

Upper- and lowercase.

```

637 \def\MakeUppercase{\MakeUppercaseUnsupportedInPdfStrings}%
638 \def\MakeLowercase{\MakeLowercaseUnsupportedInPdfStrings}%

```

Support of math commands without prefix `text`. This is controlled by option “psdextra” and only activated with Unicode PDF strings.

```

639 \ifHy@psdextra
640 \ifHy@unicode
641 \csname psdmapshortnames\endcsname
642 \csname psdaliasnames\endcsname
643 \fi
644 \fi

```

Package babel. Wherever “naturalnames” is used, disable `\textlatin` (from Babel 3.6k). Thanks to Felix Neubauer (Email: Felix.Neubauer@gmx.net).

```

645 \let\foreignlanguage\@secondoftwo
646 \let\textlatin\@firstofone
647 \ltx@ifundefined{language@group}{\@firstofone}{\@secondoftwo}%

```

```

648 \csname HyPsd@babel@\language@group\endcsname
649 }%
650 \HyPsd@GreekPatch
651 \HyPsd@SpanishPatch
652 \HyPsd@RussianPatch
653 \HyPsd@BabelPatch
654 \let\@safe@activetrue\relax
655 \let\@safe@activesfalse\relax
    Disable \cyr, used in russianb.ldf.
656 \let\cyr\relax
    Redefine \es@roman, used in spanish.ldf.
657 \let\es@roman\@Roman

```

Package german.

```

658 \let\glqq\textglqq
659 \let\grqq\textgrqq
660 \let\glq\textglq
661 \let\grq\textgrq
662 \let\flqq\textflqq
663 \let\frqq\textfrqq
664 \let\flq\textflq
665 \let\frq\textfrq

```

Package french. The support is deferred, because it needs `\GenericError` to be disabled (see below).

Package FrenchPro. This package uses:

```

    \if@mid@expandable{not fully expandable code}{fully expandable
    code}
666 \let\if@mid@expandable\@firstoftwo

```

AMS classes.

```

667 \HyPsd@AMSClassfix

```

Redefinition of `\hspace` `\hspace` don't work in bookmarks, the following fix tries to set a space if the argument is a positive length.

```

668 \let\hspace\HyPsd@hspace

```

Commands of referencing and indexing systems. Some \LaTeX commands that are legal in `\section` commands have to be disabled here.

```

669 \let\label\@gobble
670 \let\index\@gobble
671 \let\glossary\@gobble
672 \let\href\HyPsd@href
673 \let\@mkboth\@gobbletwo
    The \ref and \pageref is much more complicate because of their star form.
674 \let\ref\HyPsd@ref
675 \let\pageref\HyPsd@pageref
676 \let\nameref\HyPsd@nameref
677 \let\autoref\HyPsd@autoref

```


Miscellaneous commands.

```
678 \let\leavevmode\@empty
679 \let\mbox\@empty
```

`\halign` causes error messages because of the template character `#`.

```
680 \def\halign{\pdfstringdefWarn\halign\@gobble}%
681 \let\ignorespaces\HyPsd@ignorespaces
682 \let\Hy@SectionAnchorHref\@gobble
683 \let\ensuremath\@firstofone
```

Patch for cjk bookmarks.

```
684 \HyPsd@CJKhook
```

User hook. The switch `\Hy@pdfstring` is turned on. So user commands can detect that they are processed not to be typesetted within \TeX 's stomach, but to be expanded by the mouth to give a PDF string. At this place before interpreting the string in `#2` additional redefinitions can be added by the hook `\pdfstringdef-PreHook`.

The position in the middle of the redefinitions is a compromise: The user should be able to provide his own (perhaps better) redefinitions, but some commands should have their original meaning, because they can be used in the hook (`\bgroup`, or `\@protected@testopt`, and `\@ifnextchar` for `\renewcommand`).

```
685 \Hy@pdfstringtrue
686 \pdfstringdefPreHook
```

Spaces. For checking the token of the string, spaces must be masked, because they cannot be caught by undelimited arguments.

```
687 \HyPsd@LetUnexpandableSpace\space
688 \HyPsd@LetUnexpandableSpace\ %
689 \HyPsd@LetUnexpandableSpace~%
690 \HyPsd@LetUnexpandableSpace\nobreakspace
```

Package xspace.

```
691 \ltx@ifundefined{@xspace}{%
692 \let\xspace\HyPsd@ITALCORR
693 }{%
694 \let\xspace\HyPsd@XSPACE
695 }%
696 \let\/\HyPsd@ITALCORR
697 \let\bgroup\/%
698 \let\egroup\/%
```

Redefinitions of miscellaneous commands. Hyphenation does not make sense.

```
699 \let\discretionary\@gobbletwo
```

`\@ifstar` is defined in \LaTeX as follows:

```
\def\@ifstar#1{\@ifnextchar *{\@firstoftwo{#1}}}
```

`\@ifnextchar` doesn't work, because it uses stomach commands like `\let` and `\futurelet`. But it doesn't break. Whereas `\@firstoftwo{#1}` gives an error message because `\@firstoftwo` misses its second argument.

A mimicry of `\@ifnextchar` only with expandible commands would be very extensive and the result would be only an approximation. So here a cheaper solution follows in order to get rid of the error message at least:

```

700 \def\@ifnextchar{\HyPsd@ifnextchar\@ifnextchar}%
701 \def\kernel@ifnextchar{\HyPsd@ifnextchar\kernel@ifnextchar}%
702 \def\new@ifnextchar{\HyPsd@ifnextchar\new@ifnextchar}%
703 \let\@protected@testopt\HyPsd@protected@testopt

```

Support for package ‘xargs’:

```

704 \let\@protected@testopt@xargs\HyPsd@protected@testopt

```

6.2.2 Expansion

There are several possibilities to expand tokens within \LaTeX :

`\protected@edef`: The weakest form isn’t usable, because it does not expand the font encoding commands. They are made robust and protect themselves.

`\csname`: First the string is expanded within a `\csname` and `\endcsname`. Then the command name is converted to characters with catcode 12 by `\string` and the first escape character removed by `\@gobble`. This method has the great *advantage* that stomach tokens that aren’t allowed in PDF strings are detected by \TeX and reported as errors in order to force the user to write correct things. So he get no wrong results by forgetting the proofreading of his text. But the *disadvantage* is that old wrong code cannot processed without errors. Mainly the error message is very cryptic and for the normal user hard to understand. \TeX provides no way to catch the error caused by `\csname` or allows to support the user with a descriptive error message. Therefore the experienced user had to enable this behaviour by an option `exactdef` in previous versions less or equal 6.50.

`\edef` This version uses this standard form for expansion. It is stronger than \LaTeX ’s `\protected@edef`. So the font encoding mechanism works and the glyph commands are converted to the correct tokens for PDF strings with the definitions of the PD1 encoding. Because the protecting mechanism of \LaTeX doesn’t work within an `\edef`, there are situations thinkable where code can break. For example, assignments and definitions aren’t performed and so undefined command errors or argument parsing errors can occur. But this is only a compatibility problem with old texts. Now there are possibilities to write code that gives correct PDF strings (see `\texorpdfstring`). In the most cases unexpandable commands and tokens (math shift, grouping characters) remains. They don’t cause an error like with `\csname`. However a PDF reader isn’t \TeX , so these tokens are viewed verbatim. So this version detects them now, and removes them with an descriptive warning for the user. As additional features xspace support is possible and grouping characters can be used without problems, because they are removed silently.

Generic messages. While expanding via `\xdef` the `\Generic...` messages don’t work and causes problems (error messages, invalid .out file). So they are disabled while expanding and removed silently, because a user warning would be too expensive (memory and runtime, `\pdfstringdef` is slow enough).

```

705 \begingroup
706 \let\GenericError\@gobblefour
707 \let\GenericWarning\@gobbletwo
708 \let\GenericInfo\@gobbletwo

```

Package french. This fix only works, if `\GenericError` is disabled.

```

709 \ifx\nofrenchguillemets\@undefined
710 \else
711 \nofrenchguillemets
712 \fi

```

Definition commands and expansion. Redefining the defining commands (see sec. 6.5.12). The original meaning of `\xdef` is saved in `\Hy@temp`.

```

713 \let\Hy@temp\xdef
714 \let\def\HyPsd@DefCommand
715 \let\gdef\HyPsd@DefCommand
716 \let\edef\HyPsd@DefCommand
717 \let\xdef\HyPsd@DefCommand
718 \let\futurelet\HyPsd@LetCommand
719 \let\let\HyPsd@LetCommand
720 \Hy@temp#1{#2}%
721 \endgroup

```

6.2.3 Postprocessing

If the string is empty time can be saved by omitting the postprocessing process.

```

722 \ifx#1\@empty
723 \else

```

Protecting spaces and removing grouping characters. In order to check the tokens we must separate them. This will be done with `TEX`'s argument parsing. With this method we must the following item takes into account, that makes makes things a little more complicate:

- `TEX` does not accept a space as an undelimited argument, it cancels space tokens while looking for an undelimited argument. Therefore we must protect the spaces now.
- An argument can be a single token or a group of many tokens. And within curly braces tokens aren't find by `TEX`'s argument scanning process. Third curly braces as grouping characters cannot be expanded further, so they don't vanish by the string expansion above. So these characters with catcode 1 and 2 are removed in the following and replaced by an marker for the xspace support.
- `TEX` silently removes the outmost pair of braces of an argument. To prevent this on unwanted places, in the following the character `|` is appended to the string to make an outer brace to an inner one.

First the top level spaces are protected by replacing. Then the string is scanned to detect token groups. Each token group will now be space protected and again scanned for another token groups.

```

724 \HyPsd@ProtectSpaces#1%
725 \let\HyPsd@String\@empty
726 \expandafter\HyPsd@RemoveBraces\expandafter{#1|}%
727 \global\let#1\HyPsd@String

```

Check tokens. After removing the spaces and the grouping characters the string now should only consists of the following tokens/catcodes:

- 0 command names with start with an escape character.
- 3 math shift
- 4 alignment tabs
- 6 parameter, but this is unlikely.
- 7 superscript
- 8 subscript
- 11 letter
- 12 other
- 13 commands that are active characters.

After `\HyPsd@CheckCatcodes` the command `\HyPsd@RemoveMask` is reused to remove the group protection character `|`. This character is needed to ensure that the string at least consists of one token if `\HyPsd@CheckCatcodes` is called.

Because of internal local assignments and tabulars group braces are used.

```

728 \let\HyPsd@SPACEOPTI\relax
729 {%
730 \let\HyPsd@String\@empty
731 \expandafter\HyPsd@CheckCatcodes#1\HyPsd@End
732 \global\let#1\HyPsd@String
733 }%
734 \expandafter\HyPsd@RemoveMask\expandafter
735 |\expandafter\@empty#1\HyPsd@End#1%
```

`\HyPsd@CheckCatcodes` should no have removed the tokens with catcode 3, 4, 7, and 8. Because a parameter token (6) would cause to many errors before, there should now be only tokens with catcodes 11 or 12. So I think there is no need for a safety step like:

```
\xdef#1{\expandafter\strip@prefix\meaning#1}%
```

Looking for wrong glyphs. The case that glyphs aren't defined in the PD1 encoding is caught above in such a way, that the glyph name and a marker is inserted into the string. Now we can safely scan the string for this marker and provide a descriptive warning.

```

736 \expandafter
737 \HyPsd@Subst\expandafter{\HyPsd@GLYPHERR}{\relax}#1%
738 \let\HyPsd@String\@empty
739 \expandafter\HyPsd@GlyphProcess#1\relax\@empty
740 \global\let#1\HyPsd@String
```

Backslash. The double backslash disturbs parsing octal sequences, for example in an string like `abc\\051` the sequence `\051` is detected although the second `\` belongs to the first backslash.

```
741 \HyPsd@StringSubst{\}{\textbackslash}#1%
```

Spaces. All spaces have already the form `\040`. The last postprocessing step will be an optimizing of the spaces, so we already introduce already the necessary command `\HyPsd@SPACEOPTI`. But first it is defined to be `\relax` in order to prevent a too early expansion by an `\edef`. Secondly a `\relax` serves as a marker for a token that is detected by `\xspace`.

The code of `frenchb.ldf` can produce an additional space before `\guillemotright`, because `\lastskip` and `\unskip` do not work. Therefore it is removed here.

```

742 \ifHy@unicode
743 \expandafter\HyPsd@StringSubst\csname 80\040\endcsname
744 \HyPsd@SPACEOPTI#1%
745 \edef\Hy@temp@A{\HyPsd@SPACEOPTI\HyPsd@SPACEOPTI\80\273}%
746 \expandafter\HyPsd@Subst\expandafter{\Hy@temp@A}%
747 {\HyPsd@SPACEOPTI\80\273}#1%
748 \else
749 \HyPsd@StringSubst{\040}\HyPsd@SPACEOPTI#1%
750 \expandafter\HyPsd@Subst\expandafter{%
751 \expandafter\HyPsd@SPACEOPTI\expandafter\HyPsd@SPACEOPTI
752 \string\273}\HyPsd@SPACEOPTI\273}#1%
753 \fi

```

Right parenthesis. Also `\xspace` detects a right parenthesis. For the `\xspace` support and the following parenthesis check the different parenthesis notations `)`, `\)`, and `\051` are converted to one type `\)` and before `\HyPsd@empty` with the meaning of `\relax` is introduced for `\xspace`. By redefining to `\@empty` `\HyPsd@empty` can easily be removed later.

```

754 \ifHy@unicode
755 \HyPsd@StringSubst{\}){\80\051}#1%
756 \HyPsd@Subst){\80\051}#1%
757 \let\HyPsd@empty\relax
758 \expandafter\HyPsd@StringSubst\csname 80\051\endcsname
759 {\HyPsd@empty\80\051}#1%
760 \else
761 \HyPsd@StringSubst{\}){\051}#1%
762 \HyPsd@Subst){\051}#1%
763 \let\HyPsd@empty\relax
764 \HyPsd@StringSubst{\051}{\HyPsd@empty\string\)}#1%
765 \fi

```

Support for package `xspace`. `\xspace` looks for the next token and decides if it expands to a space or not. Following tokens prevent its transformation to a space: Beginning and end of group, handled above by replacing by an italic correction, several punctuation marks, a closing parentheses, and several spaces.

Without package `xspace` there are tokens with catcode 11 and 12, `\HyPsd@empty` and `\HyPsd@SPACEOPTI`. With package `xspace` marker for the italic correction `\/` and `\xspace` come with. In the package `xspace` case the two markers are replaced by commands and an `\edef` performs the `\xspace` processing.

In the opposite of the original `\xspace` `\HyPsd@xspace` uses an argument instead of a `\futurelet`, so we have to provide such an argument, if `\HyPsd@xspace` comes last. Because `\HyPsd@Subst` with several equal tokens (`--`) needs a safe last token, in both cases the string gets an additional `\HyPsd@empty`.

```

766 \expandafter\HyPsd@Subst\expandafter{\//}\HyPsd@empty#1%
767 \ltx@ifundefined{@xspace}{%
768 }{%
769 \let\HyPsd@xspace\relax
770 \expandafter\HyPsd@Subst\expandafter
771 {\HyPsd@XSPACE}\HyPsd@xspace#1%
772 \let\HyPsd@xspace\HyPsd@doxspace
773 }%
774 \xdef#1{#1\HyPsd@empty}%

```

Ligatures. \TeX forms ligatures in its stomach, but the PDF strings are treated only by \TeX 's mouth. The `PDFDocEncoding` contains some ligatures, but the

current version 3 of the AcrobatReader lacks the `fi` and `fl` glyphs, and the Linux version lacks the `emdash` and `endash` glyphs. So the necessary code is provided here, but currently disabled, hoping that version 4 of the AcrobatReader is better. To break the ligatures the user can use an empty group, because it leads to an insertion of an `\HyPsd@empty`. If this ligature code will be enabled some day, then the italic correction should also break the ligatures. Currently this occurs only, if package `xspace` is loaded.

Since newer AcrobatReader versions now show the en- and emdash in a correct way (AR7/Linux, AR8/Linux), the substitution code for them is enabled starting with version 6.78l.

```

775 \HyPsd@Subst{---}\textemdash#1%
776 \HyPsd@Subst{--}\textendash#1%
777 % \HyPsd@Subst{fi}\textfi#1%
778 % \HyPsd@Subst{fl}\textfl#1%
779 \HyPsd@Subst{!}\textexclamdown#1%
780 \HyPsd@Subst{?}\textquestiondown#1%
```

With the next `\edef` we get rid of the token `\HyPsd@empty`.

```

781 \let\HyPsd@empty\@empty
```

Left parentheses. Left parentheses are now converted to safe forms to avoid problems with unmatched ones (`\(` with PDFDocEncoding, the octal sequence with Unicode).

An optimization is possible. Matched parentheses can be replaced by a `()` pair. But this code is removed to save `TEX` memory and time.

```

782 \ifHy@unicode
783 \HyPsd@StringSubst\(\textparenleft#1%
784 \HyPsd@Subst(\textparenleft#1%
785 \else
786 \HyPsd@StringSubst\({\050}#1%
787 \HyPsd@Subst({\050}#1%
788 \HyPsd@StringSubst{\050}{\string\{ }#1%
789 \fi
```

Optimizing spaces. Spaces are often used, but they have a very long form `\040`. They are converted back to real spaces, but not all, so that no space follows after another. In the bookmark case several spaces are written to the `.out` file, but if the entries are read back, several spaces are merged to a single one.

With Unicode the spaces are replaced by their octal sequences.

```

790 \ifHy@unicode
791 \edef\HyPsd@SPACEOPTI{\80\040}%
792 \else
793 \let\HyPsd@SPACEOPTI\HyPsd@spaceopti
794 \fi
795 \xdef#1{#1\@empty}%
796 \fi
```

Converting to Unicode. At last the eight bit letters have to be converted to Unicode, the masks `\8` and `\9` are removed and the Unicode marker is added.

```

797 \endgroup
798 \begingroup
799 \ifHy@unicode
800 \HyPsd@ConvertToUnicode#1%
```

Try conversion back to PDFDocEncoding.

```
801 \ifx\HyPsd@pdfencoding\HyPsd@pdfencoding@auto
802 \ltx@ifundefined{StringEncodingConvertTest}{%
803 }{%
804 \EdefUnescapeString\HyPsd@temp#1%
805 \ifxetex
806 \let\HyPsd@UnescapedString\HyPsd@temp
807 \StringEncodingConvertTest\HyPsd@temp\HyPsd@temp
808 {utf16be}{ascii-print}{%
809 \EdefEscapeString\HyPsd@temp\HyPsd@temp
810 \global\let#1\HyPsd@temp
811 \HyPsd@EscapeTeX#1%
812 \Hy@unicodedefalse
813 }{%
814 \HyPsd@ToBigChars#1%
815 }%
816 \else
817 \StringEncodingConvertTest\HyPsd@temp\HyPsd@temp
818 {utf16be}{pdfdoc}{%
819 \EdefEscapeString\HyPsd@temp\HyPsd@temp
820 \global\let#1\HyPsd@temp
821 \HyPsd@EscapeTeX#1%
822 \Hy@unicodedefalse
823 }{}}%
824 \fi
825 }%
826 \fi
827 \fi
828 \HyPsd@XeTeXBigCharsfalse
```

User hook. The hook `\pdfstringdefPostHook` can be used for the purpose to postprocess the string further.

```
829 \pdfstringdefPostHook#1%
830 \endgroup
831 }
```

`\Hy@pdfstringdef`

```
832 \def\Hy@pdfstringdef#1#2{%
833 \pdfstringdef\Hy@gtemp{#2}%
834 \let#1\Hy@gtemp
835 }
```

6.3 Encodings

6.3.1 XeTeX

```
836 \edef\Hy@temp{\catcode0=\the\catcode0\relax}
837 \catcode\z@=12 %
838 \ifxetex
839 \expandafter\@firstofone
840 \else
841 \let\HyPsd@XeTeXBigCharstrue\@empty
842 \let\HyPsd@XeTeXBigCharsfalse\@empty
843 \expandafter\@gobble
844 \fi
845 {%
846 \newif\ifHyPsd@XeTeXBigChars
```

```

847 \def\HyPsd@XeTeXBigCharsfalse{%
848   \global\let\ifHyPsd@XeTeXBigChars\iffalse
849 }%
850 \def\HyPsd@XeTeXBigCharstrue{%
851   \global\let\ifHyPsd@XeTeXBigChars\iftrue
852 }%
853 \def\HyPsd@ToBigChars#1{%
854   \ifHyPsd@XeTeXBigChars
855     \EdefEscapeHex\HyPsd@UnescapedString{%
856       \expandafter\@gobbletwo\HyPsd@UnescapedString
857     }%
858     \begingroup
859     \toks@{}%
860     \escapechar=92\relax
861     \let\x\HyPsd@ToBigChar
862     \expandafter\HyPsd@ToBigChar\HyPsd@UnescapedString
863     \relax\relax\relax\relax\relax\relax\relax
864     \edef\x{%
865       \endgroup
866       \gdef\noexpand#1{\the\toks@}%
867     }%
868     \x
869   \fi
870 }%
871 \def\HyPsd@ToBigChar#1#2#3#4{%
872   \ifx\relax#1\relax
873     \let\x\relax
874   \else
875     \count@=#1#2#3#4\relax
876     \let\y\@empty
877     \lccode\z@=\count@
878     \ifnum\count@=40 % (
879       \let\y\@backslashchar
880     \else
881       \ifnum\count@=41 % )
882         \let\y\@backslashchar
883       \else
884         \ifnum\count@=92 % backslash
885           \let\y\@backslashchar
886         \else
887           \ifnum\count@=10 % newline
888             \edef\y##1{\string\n}%
889           \else
890             \ifnum\count@=13 % carriage return
891               \edef\y##1{\string\r}%
892             \fi
893           \fi
894         \fi
895       \fi
896     \fi
897   \lowercase{%
898     \toks@\expandafter{%
899       \the\expandafter\toks@
900     \y
901     ^^@%
902   }%
903 }%

```



```

904 \fi
905 \x
906 }%
907 }
908 \Hy@temp

```

6.3.2 Workaround for package linguex

```

909 \@ifpackageloaded{linguex}{%
910 \let\HyLinguex@OrgB\b
911 \let\HyLinguex@OrgC\c
912 \let\HyLinguex@OrgD\d
913 \def\HyLinguex@Restore{%
914 \let\b\HyLinguex@OrgB
915 \let\c\HyLinguex@OrgC
916 \let\d\HyLinguex@OrgD
917 }%
918 \Hy@AtEndOfPackage{%
919 \pdfstringdefDisableCommands{%
920 \ltx@ifundefined{oldb}{\let\b\oldb}%
921 \ltx@ifundefined{oldc}{\let\c\oldc}%
922 \ltx@ifundefined{oldd}{\let\d\oldd}%
923 }%
924 }%
925 }{%
926 \let\HyLinguex@Restore\relax
927 }%

```

6.3.3 Catcodes saving and restoring for .def files

\Hy@SaveCatcodeSettings

```

928 \def\Hy@SaveCatcodeSettings#1{%
929 \expandafter\edef\csname Hy@cat@#1\endcsname{%
930 \endlinechar=\the\endlinechar\relax
931 \catcode32 \the\catcode32\relax % (space)
932 \catcode34 \the\catcode34\relax % "
933 \catcode35 \the\catcode35\relax % #
934 \catcode37 \the\catcode37\relax % (percent)
935 \catcode40 \the\catcode40\relax % (
936 \catcode41 \the\catcode41\relax % )
937 \catcode42 \the\catcode42\relax % *
938 \catcode46 \the\catcode46\relax % .
939 \catcode58 \the\catcode58\relax % :
940 \catcode60 \the\catcode60\relax % <
941 \catcode61 \the\catcode61\relax % =
942 \catcode62 \the\catcode62\relax % >
943 \catcode64 \the\catcode64\relax % @
944 \catcode91 \the\catcode91\relax % [
945 \catcode92 \the\catcode92\relax % \
946 \catcode93 \the\catcode93\relax % ]
947 \catcode123 \the\catcode123\relax % {
948 \catcode124 \the\catcode124\relax % |
949 \catcode125 \the\catcode125\relax % }
950 }%
951 \endlinechar=-1 %
952 \catcode32 10 % (space)
953 \catcode34 12 % "
954 \catcode35 6 % #
955 \catcode37 14 % (percent)

```

```

956 \catcode40 12 % (
957 \catcode41 12 % )
958 \catcode42 12 % *
959 \catcode46 12 % .
960 \catcode58 12 % :
961 \catcode60 12 % <
962 \catcode61 12 % =
963 \catcode62 12 % >
964 \catcode91 12 % [
965 \catcode92 0 % \
966 \catcode93 12 % ]
967 \catcode123 1 % {
968 \catcode124 12 % |
969 \catcode125 2 % }
970 \makeatletter
971 }

```

`\Hy@RestoreCatcodeSettings`

```

972 \def\Hy@RestoreCatcodeSettings#1{%
973   \csname Hy@cat@#1\endcsname
974   \expandafter\let\csname Hy@cat@#1\endcsname\relax
975 }

```

6.3.4 PD1 encoding

The PD1 encoding implements the PDFDocEncoding for use with L^AT_EX 2_ε's NFSS. Because the informational strings are not set by T_EX's typesetting mechanism but for interpreting by the PDF reader, the glyphs of the PD1 encoding are implemented to be safely written to a file (PDF output file, .out file).

The PD1 encoding can be specified as an option of the 'fontenc' package or loaded here. It does not matter what font family is selected, as T_EX does not process it anyway. So use CM.

```

976 \@ifundefined{T@PD1}{%
977   \Hy@SaveCatcodeSettings{pd1}%
978   \input{pd1enc.def}%
979   \Hy@RestoreCatcodeSettings{pd1}%
980   \HyLinguex@Restore
981 }{}
982 \DeclareFontFamily{PD1}{pdf}{}
983 \DeclareFontShape{PD1}{pdf}{m}{n}{<-> cmr10 }{}
984 \DeclareFontSubstitution{PD1}{pdf}{m}{n}

```

6.3.5 PU encoding

The PU encoding implements the Unicode encoding for use with L^AT_EX's NFSS. Because of large memory requirements the encoding file for Unicode support is only loaded, if option `unicode` is specified as package option.

`\HyPsd@LoadUnicode` Because the file `puenc.def` takes a lot of memory, the loading is defined in the macro `\HyPsd@LoadUnicode` called by the package option `unicode`.

```

985 \def\HyPsd@LoadUnicode{%
986   \@ifundefined{T@PU}{%
987     \Hy@SaveCatcodeSettings{pu}%
988     \input{puenc.def}%
989     \Hy@RestoreCatcodeSettings{pu}%
990     \HyLinguex@Restore

```

```

991 }{}%
992 \DeclareFontFamily{PU}{pdf}{}%
993 \DeclareFontShape{PU}{pdf}{m}{n}{ <-> cmr10 }{}%
994 \DeclareFontSubstitution{PU}{pdf}{m}{n}%
995 \HyPsd@LoadExtra
996 \let\HyPsd@LoadUnicode\relax
997 }

```

`\HyPsd@LoadExtra`

```

998 \def\HyPsd@LoadExtra{%
999   \ifHy@psdextra
1000     \ltx@iffileloaded{puenc.def}{}%
1001     \Hy@SaveCatcodeSettings{psdextra}%
1002     \input{psdextra.def}%
1003     \Hy@RestoreCatcodeSettings{psdextra}%
1004     \let\HyPsd@LoadExtra\relax
1005   }{}%
1006 \fi
1007 }

```

6.4 Additional user commands

6.4.1 `\texorpdfstring`

`\texorpdfstring` While expanding the string in `\pdfstringdef` the switch `\ifHy@pdfstring` is set. This is used by the full expandible macro `\texorpdfstring`. It expects two arguments, the first contains the string that will be set and processed by \TeX 's stomach, the second contains the replacement for PDF strings.

```

1008 \def\texorpdfstring{%
1009   \ifHy@pdfstring
1010     \expandafter\@secondoftwo
1011   \else
1012     \expandafter\@firstoftwo
1013   \fi
1014 }

```

6.4.2 Hooks for `\pdfstringdef`

`\pdfstringdefPreHook` Default definition of the hooks for `\pdfstringdef`. The construct `\@ifundefined` with `\let` is a little bit faster than `\providecommand`.

`\pdfstringdefPostHook`

```

1015 \@ifundefined{pdfstringdefPreHook}{}%
1016 \let\pdfstringdefPreHook\@empty
1017 }{}
1018 \@ifundefined{pdfstringdefPostHook}{}%
1019 \let\pdfstringdefPostHook\@gobble
1020 }{}

```

`\pdfstringdefDisableCommands`

In `\pdfstringdefPreHook` the user can add code that is executed before the string, that have to be converted by `\pdfstringdef`, is expanded. So replacements for problematic macros can be given. The code in `\pdfstringdefPreHook` should not be replaced perhaps by an `\renewcommand`, because a previous meaning gets lost.

Macro `\pdfstringdefDisableCommands` avoids this, because it reuses the old meaning of the hook and appends the new code to `\pdfstringdefPreHook`, e.g.:

```

\pdfstringdefDisableCommands{%

```

```

\let~\textasciitilde
\def\url{\pdfstringdefWarn\url}%
\let\textcolor\@gobble
}%

```

In the argument of `\pdfstringdefDisableCommands` the character `@` can be used in command names. So it is easy to use useful \LaTeX commands like `\@gobble` or `\@firstofone`.

```

1021 \def\pdfstringdefDisableCommands{%
1022   \begingroup
1023     \makeatletter
1024     \HyPsd@DisableCommands
1025 }

```

`\HyPsd@DisableCommands`

```

1026 \long\def\HyPsd@DisableCommands#1{%
1027   \ltx@GlobalAppendToMacro\pdfstringdefPreHook{#1}%
1028   \endgroup
1029 }

```

`\pdfstringdefWarn` The purpose of `\pdfstringdefWarn` is to produce a warning message, so the user can see, that something can go wrong with the conversion to PDF strings.

The prefix `\<>`- is added to the token. `\noexpand` protects the probably undefined one during the first expansion step. Then `\HyPsd@CheckCatcodes` can detect the not allowed token, `\HyPsd@CatcodeWarning` prints a warning message, after `\HyPsd@RemovePrefix` has removed the prefix.

`\pdfstringdefWarn` is intended for document authors or package writers, examples for use can be seen in the definition of `\HyPsd@ifnextchar` or `\HyPsd@protected@testopt`.

```

1030 \def\pdfstringdefWarn#1{%
1031   \expandafter\noexpand\csname<>-string#1\endcsname
1032 }

```

6.5 Help macros for expansion

6.5.1 `\ignorespaces`

`\HyPsd@ignorespaces` With the help of a trick using `\romannumeral` the effect of `\ignorespaces` can be simulated a little, In a special case using an alphabetic constant `\romannumeral` eats an optional space. If the constant is zero, then the `\romannumeral` expression vanishes. The following macro uses this trick twice, thus `\HyPsd@ignorespaces` eats up to two following spaces.

```

1033 \begingroup
1034   \catcode0=12 %
1035   \def\x{\endgroup
1036     \def\HyPsd@ignorespaces{%
1037       \romannumeral\expandafter'\expandafter^^@%
1038       \romannumeral'^^@%
1039     }%
1040   }%
1041   \x

```

6.5.2 Babel languages

Since version 2008/03/16 v3.8j babel uses inside `\AtBeginDocument`:

```

\pdfstringdefDisableCommands{%
  \languageshorthands{system}%
}

```

As consequence the shorthands are shown in the bookmarks, not its result. Therefore `\languageshorthands` is disabled before the user hook. If there is a need to use the command, then `\HyOrg@languageshorthands` can be used inside `\pdfstringdefDisableCommands`.

```

1042 \def\HyPsd@BabelPatch{%
1043   \let\HyOrg@languageshorthands\languageshorthands
1044   \let\languageshorthands\HyPsd@LanguageShorthands
1045 }
1046 \begingroup\expandafter\expandafter\expandafter\endgroup
1047 \expandafter\ifx\csname pdf@stricmp\endcsname\relax
1048   \let\HyPsd@langshort@system\@empty
1049   \def\HyPsd@LanguageShorthands#1{%
1050     \expandafter\ifx\csname HyPsd@langshort@#1\endcsname
1051       \HyPsd@langshort@system
1052     \expandafter\@gobble
1053   \else
1054     \expandafter\@firstofone
1055   \fi
1056   {%
1057     \HyOrg@languageshorthands{#1}%
1058   }%
1059 }%
1060 \else
1061   \def\HyPsd@LanguageShorthands#1{%
1062     \ifnum\pdf@stricmp{#1}{system}=\z@
1063       \expandafter\@gobble
1064     \else
1065       \expandafter\@firstofone
1066     \fi
1067     {%
1068       \HyOrg@languageshorthands{#1}%
1069     }%
1070   }%
1071 \fi
1072 \def\Hy@temp{%
1073   \ifpackageloaded{babel}{%
1074     \ifpackagelater{babel}{2008/03/16}{%
1075       \let\Hy@temp\@empty
1076     }{%
1077       \def\HyPsd@BabelPatch{%
1078         \let\HyOrg@languageshorthands\languageshorthands
1079       }%
1080     }%
1081   }{}%
1082 }
1083 \Hy@temp
1084 \expandafter\Hy@AtBeginDocument\expandafter{\Hy@temp}
1085 \newif\ifHy@next

```

Nothing to do for english.

```

1086 \ltx@ifundefined{danish@sh@"@sel}{}{%
1087   \def\HyPsd@babel@danish{%
1088     \declare@shorthand{danish}{"}{}%

```

```

1089 \declare@shorthand{danish}{~}{-}%
1090 }%
1091 }
1092 \ltx@ifundefined{dutch@sh@}{@sel}{-}{%
1093 \def\HyPsd@babel@dutch{%
1094 \declare@shorthand{dutch}{~}{-}%
1095 \declare@shorthand{dutch}{~}{-}%
1096 }%
1097 }
1098 \ltx@ifundefined{finnish@sh@}{@sel}{-}{%
1099 \def\HyPsd@babel@finnish{%
1100 \declare@shorthand{finnish}{~}{-}%
1101 }%
1102 }
1103 \ltx@ifundefined{french@sh@}{@sel}{-}{%
1104 \def\HyPsd@babel@frenchb{%
1105 \def\guill@spacing{ }%
1106 }%
1107 }
1108 \ltx@ifundefined{german@sh@}{@sel}{-}{%
1109 \def\HyPsd@babel@german{%
1110 \declare@shorthand{german}{f}{f}%
1111 \declare@shorthand{german}{~}{-}%
1112 \declare@shorthand{german}{~}{-}%
1113 }%
1114 }
1115 \ltx@ifundefined{macedonian@sh@}{@sel}{-}{%
1116 \def\HyPsd@babel@macedonian{%
1117 \declare@shorthand{macedonian}{~}{-}%
1118 \declare@shorthand{macedonian}{~}{-}%
1119 }%
1120 }{}
1121 \ltx@ifundefined{ngerman@sh@}{@sel}{-}{%
1122 \def\HyPsd@babel@ngerman{%
1123 \declare@shorthand{ngerman}{~}{-}%
1124 \declare@shorthand{ngerman}{~}{-}%
1125 }%
1126 }
1127 \ltx@ifundefined{portuges@sh@}{@sel}{-}{%
1128 \def\HyPsd@babel@portuges{%
1129 \declare@shorthand{portuges}{~}{-}%
1130 }%
1131 }
1132 \ltx@ifundefined{russian@sh@}{@sel}{-}{%
1133 \def\HyPsd@babel@russian{%
1134 \declare@shorthand{russian}{~}{-}%
1135 \declare@shorthand{russian}{~}{-}%
1136 }%
1137 }
1138 \ltx@ifundefined{slovene@sh@}{@sel}{-}{%
1139 \def\HyPsd@babel@slovene{%
1140 \declare@shorthand{slovene}{~}{-}%
1141 }%
1142 }

```

Nested quoting environments are not supported (<<, >>).

```

1143 \ltx@ifundefined{spanish@sh@}{@sel}{-}{%
1144 \def\HyPsd@babel@spanish{%

```

```

1145 \declare@shorthand{spanish}{<<}{\guillemotleft}%
1146 \declare@shorthand{spanish}{>>}{\guillemotright}%
1147 \declare@shorthand{spanish}{"}={-}%
1148 \declare@shorthand{spanish}{"}~}{-}%
1149 \declare@shorthand{spanish}{"!}{\textexclamdown}%
1150 \declare@shorthand{spanish}{"?}{\textquestiondown}%
1151 }%
1152 }
1153 \ltx@ifundefined{swedish@sh@"@sel}{-}{-}%
1154 \def\HyPsd@babel@swedish{%
1155 \declare@shorthand{swedish}{"}|}{-}%
1156 \declare@shorthand{swedish}{"}~}{-}%
1157 }%
1158 }
1159 \ltx@ifundefined{ukrainian@sh@"@sel}{-}{-}%
1160 \def\HyPsd@babel@ukrainian{%
1161 \declare@shorthand{ukrainian}{"}|}{-}%
1162 \declare@shorthand{ukrainian}{"}~}{-}%
1163 }%
1164 }
1165 \ltx@ifundefined{usorbian@sh@"@sel}{-}{-}%
1166 \def\HyPsd@babel@usorbian{%
1167 \declare@shorthand{usorbian}{"}f}{f}%
1168 \declare@shorthand{usorbian}{"}|}{-}%
1169 }%
1170 }
1171 \ltx@ifundefined{greek@sh@\string~@sel}{-}{-}%
1172 \let\HyPsd@GreekPatch@empty
1173 }{%
1174 \def\HyPsd@GreekPatch{%
1175 \let\greeknumeral\HyPsd@greeknumeral
1176 \let\Greeknumeral\HyPsd@Greeknumeral
1177 }%
1178 }
1179 \def\HyPsd@greeknumeral#1{%
1180 \HyPsd@GreekNum\@firstoftwo{#1}%
1181 }
1182 \def\HyPsd@Greeknumeral#1{%
1183 \HyPsd@GreekNum\@secondoftwo{#1}%
1184 }
1185 \def\HyPsd@GreekNum#1#2{%
1186 \ifHy@unicode
1187 \ifnum#2<\@ne
1188 \@arabic{#2}%
1189 \else
1190 \ifnum#2<1000000 %
1191 \HyPsd@@GreekNum#1{#2}%
1192 \else
1193 \@arabic{#2}%
1194 \fi
1195 \fi
1196 \else
1197 \@arabic{#2}%
1198 \fi
1199 }
1200 \def\HyPsd@@GreekNum#1#2{%
1201 \ifnum#2<\@m

```

```

1202 \ifnum#2<10 %
1203 \expandafter\HyPsd@GreekNumI
1204 \expandafter\@gobble\expandafter#1\number#2%
1205 \else
1206 \ifnum#2<100 %
1207 \expandafter\HyPsd@GreekNumII
1208 \expandafter\@gobble\expandafter#1\number#2%
1209 \else
1210 \expandafter\HyPsd@GreekNumIII
1211 \expandafter\@gobble\expandafter#1\number#2%
1212 \fi
1213 \fi
1214 \ifnum#2>\z@
1215 \textnumeralsigngreek
1216 \fi
1217 \else
1218 \ifnum#2<\@M
1219 \expandafter\HyPsd@GreekNumIV\expandafter#1\number#2%
1220 \else
1221 \ifnum#2<100000 %
1222 \expandafter\HyPsd@GreekNumV\expandafter#1\number#2%
1223 \else
1224 \expandafter\HyPsd@GreekNumVI\expandafter#1\number#2%
1225 \fi
1226 \fi
1227 \fi
1228 }
1229 \def\HyPsd@GreekNumI#1#2#3{%
1230 #1{%
1231 \ifnum#3>\z@
1232 \textnumeralsignlowergreek
1233 \fi
1234 }%
1235 \expandafter#2%
1236 \ifcase#3 %
1237 {}{}%
1238 \or\textalpha\textAlpha
1239 \or\textbeta\textBeta
1240 \or\textgamma\textGamma
1241 \or\textdelta\textDelta
1242 \or\textepsilon\textEpsilon
1243 \or\textstigmagreek\textStigmagreek
1244 \or\textzeta\textZeta
1245 \or\texteta\textEta
1246 \or\texttheta\textTheta
1247 \else
1248 {}{}%
1249 \fi
1250 }
1251 \def\HyPsd@GreekNumII#1#2#3#4{%
1252 #1{%
1253 \ifnum#3>\z@
1254 \textnumeralsignlowergreek
1255 \fi
1256 }%
1257 \expandafter#2%
1258 \ifcase#3 %

```



```

1259  {}{}%
1260  \or\textiota\textIota
1261  \or\textkappa\textKappa
1262  \or\textlambda\textLambda
1263  \or\textmu\textMu
1264  \or\textnu\textNu
1265  \or\textxi\textXi
1266  \or\textomicron\textOmicron
1267  \or\textpi\textPi
1268  \or\textkoppagreek\textKoppagreek
1269  \else
1270  {}{}%
1271  \fi
1272  \HyPsd@GreekNumI#1#2#4%
1273 }
1274 \def\HyPsd@GreekNumIII#1#2#3#4#5{%
1275 #1{%
1276   \ifnum#3>\z@
1277     \textnumeralsignlowergreek
1278   \fi
1279 }%
1280 \expandafter#2%
1281 \ifcase#3 %
1282   {}{}%
1283   \or\extrho\textRho
1284   \or\textsigma\textSigma
1285   \or\texttau\textTau
1286   \or\textupsilon\textUpsilon
1287   \or\textphi\textPhi
1288   \or\textchi\textChi
1289   \or\textpsi\textPsi
1290   \or\textomega\textOmega
1291   \or\textsampigreek\textSampigreek
1292   \else
1293     {}{}%
1294   \fi
1295   \HyPsd@GreekNumII#1#2#4#5%
1296 }
1297 \def\HyPsd@GreekNumIV#1#2#3#4#5{%
1298   \HyPsd@GreekNumI\@firstofone#1#2%
1299   \HyPsd@@@GreekNum#1{#3#4#5}%
1300 }
1301 \def\HyPsd@GreekNumV#1#2#3#4#5#6{%
1302   \HyPsd@GreekNumII\@firstofone#1#2#3%
1303   \HyPsd@@@GreekNum#1{#4#5#6}%
1304 }
1305 \def\HyPsd@GreekNumVI#1#2#3#4#5#6#7{%
1306   \HyPsd@GreekNumIII\@firstofone#1#2#3#4%
1307   \HyPsd@@@GreekNum#1{#5#6#7}%
1308 }
1309 \def\HyPsd@SpanishPatch{%
1310   \ltx@ifundefined{es@save@dot}{%
1311     }{%
1312       \let\.\es@save@dot
1313     }%
1314 }

```

Shorthand "- of 'russianb.ldf' is not expandable, therefore it is disabled and replaced by -.

```

1315 \def\HyPsd@RussianPatch{%
1316   \ltx@ifundefined{russian@sh@"@-@}{%
1317     }{%
1318     \@namedef{russian@sh@"@-@}{-}%
1319   }%
1320 }
```

6.5.3 CJK patch

```

1321 \RequirePackage{intcalc}[2007/09/27]

\HyPsd@CJKhook
1322 \def\HyPsd@CJKhook{%
1323   \ltx@ifpackageloaded{CJK}{%
1324     \let\CJK@kern\relax
1325     \let\CJKkern\relax
1326     \let\CJK@CJK\relax
1327     \ifHy@CJKbookmarks
1328       \HyPsd@CJKhook@bookmarks
1329     \fi
1330     \HyPsd@CJKhook@unicode
1331   }{%
1332 }
```

6.5.4 CJK bookmarks

\HyPsd@CJKhook Some internal commands of package cjk are redefined to avoid error messages. For a rudimental support of CJK bookmarks the active characters are redefined so that they print themselves.

After preprocessing of Big5 encoded data the following string for a double-byte character is emitted:

```
^^7f<arg1>^^7f<arg2>^^7f
```

<arg1> is the first byte in the range (always > 0x80); <arg2> is the second byte in decimal notation ($\geq 0x40$).

```

1333 \begingroup
1334   \catcode"7F=\active
1335   \toks@{%
1336     \let\CJK@ignorespaces\empty
1337     \def\CJK@char#1{\@gobbletwo}%
1338     \let\CJK@charx\@gobblefour
1339     \let\CJK@punctchar\@gobblefour
1340     \def\CJK@punctcharx#1{\@gobblefour}%
1341     \catcode"7F=\active
1342     \def^^7f#1^^7f#2^^7f{%
1343       \string #1\HyPsd@DecimalToOctal{#2}%
1344     }%
1345     % ... ?
1346     \ifHy@unicode
1347       \def\Hy@cjkpu{\80}%
1348     \else
1349       \let\Hy@cjkpu\@empty
1350     \fi
1351   \HyPsd@CJKActiveChars
```

```

1352 }%
1353 \count@=127 %
1354 \@whilenum\count@<255 \do{%
1355   \advance\count@ by 1 %
1356   \lccode'\~=\count@
1357   \lowercase{%
1358     \toks@\expandafter{\the\toks@ ~}%
1359   }%
1360 }%
1361 \toks@\expandafter{\the\toks@ !}%
1362 \xdef\HyPsd@CJKhook@bookmarks{%
1363   \the\toks@
1364 }%
1365 \endgroup

```

\HyPsd@CJKActiveChars The macro \HyPsd@CJKActiveChars is only defined to limit the memory consumption of \HyPsd@CJKhook.

```

1366 \def\HyPsd@CJKActiveChars#1{%
1367   \ifx#1!%
1368     \let\HyPsd@CJKActiveChars\relax
1369   \else
1370     \edef#1{\noexpand\Hy@cjkpu\string#1}%
1371   \fi
1372   \HyPsd@CJKActiveChars
1373 }

```

\HyPsd@DecimalToOctal A character, given by the decimal number is converted to a PDF character.

```

1374 \def\HyPsd@DecimalToOctal#1{%
1375   \ifcase #1 %
1376     \000\or \001\or \002\or \003\or \004\or \005\or \006\or \007%
1377     \or \010\or \011\or \012\or \013\or \014\or \015\or \016\or \017%
1378     \or \020\or \021\or \022\or \023\or \024\or \025\or \026\or \027%
1379     \or \030\or \031\or \032\or \033\or \034\or \035\or \036\or \037%
1380     \or \040\or \041\or \042\or \043\or \044\or \045\or \046\or \047%
1381     \or \050\or \051\or \052\or \053\or \054\or \055\or \056\or \057%
1382     \or 0\or 1\or 2\or 3\or 4\or 5\or 6\or 7%
1383     \or 8\or 9\or \072\or \073\or \074\or \075\or \076\or \077%
1384     \or @\or A\or B\or C\or D\or E\or F\or G%
1385     \or H\or I\or J\or K\or L\or M\or N\or O%
1386     \or P\or Q\or R\or S\or T\or U\or V\or W%
1387     \or X\or Y\or Z\or \133\or \134\or \135\or \136\or \137%
1388     \or \140\or a\or b\or c\or d\or e\or f\or g%
1389     \or h\or i\or j\or k\or l\or m\or n\or o%
1390     \or p\or q\or r\or s\or t\or u\or v\or w%
1391     \or x\or y\or z\or \173\or \174\or \175\or \176\or \177%
1392     \or \200\or \201\or \202\or \203\or \204\or \205\or \206\or \207%
1393     \or \210\or \211\or \212\or \213\or \214\or \215\or \216\or \217%
1394     \or \220\or \221\or \222\or \223\or \224\or \225\or \226\or \227%
1395     \or \230\or \231\or \232\or \233\or \234\or \235\or \236\or \237%
1396     \or \240\or \241\or \242\or \243\or \244\or \245\or \246\or \247%
1397     \or \250\or \251\or \252\or \253\or \254\or \255\or \256\or \257%
1398     \or \260\or \261\or \262\or \263\or \264\or \265\or \266\or \267%
1399     \or \270\or \271\or \272\or \273\or \274\or \275\or \276\or \277%
1400     \or \300\or \301\or \302\or \303\or \304\or \305\or \306\or \307%
1401     \or \310\or \311\or \312\or \313\or \314\or \315\or \316\or \317%
1402     \or \320\or \321\or \322\or \323\or \324\or \325\or \326\or \327%
1403     \or \330\or \331\or \332\or \333\or \334\or \335\or \336\or \337%

```

```

1404 \or \340\or \341\or \342\or \343\or \344\or \345\or \346\or \347%
1405 \or \350\or \351\or \352\or \353\or \354\or \355\or \356\or \357%
1406 \or \360\or \361\or \362\or \363\or \364\or \365\or \366\or \367%
1407 \or \370\or \371\or \372\or \373\or \374\or \375\or \376\or \377%
1408 \fi
1409 }

```

6.5.5 CJK unicode

\HyPsd@CJKhook@unicode

```

1410 \def\HyPsd@CJKhook@unicode{%
1411 \let\Unicode\HyPsd@CJK@Unicode
1412 \let\CJKnumber\HyPsd@CJKnumber
1413 \let\CJKdigits\HyPsd@CJKdigits
1414 }

```

\HyPsd@CJK@Unicode

```

1415 \def\HyPsd@CJK@Unicode#1#2{%
1416 \ifnum#1<256 %
1417 \HyPsd@DecimalToOctalFirst{#1}%
1418 \HyPsd@DecimalToOctalSecond{#2}%
1419 \else
1420 \933%
1421 \expandafter\expandafter\expandafter\HyPsd@HighA
1422 \intcalcDiv{#1}{4}!%
1423 \933%
1424 \ifcase\intcalcMod{#1}{4} %
1425 4\or 5\or 6\or 7%
1426 \fi
1427 \HyPsd@DecimalToOctalSecond{#2}%
1428 \fi
1429 }

1430 \def\HyPsd@HighA#1!{%
1431 \expandafter\expandafter\expandafter\HyPsd@HighB
1432 \IntCalcDiv#1!64!!%
1433 \expandafter\expandafter\expandafter\HyPsd@HighD
1434 \IntCalcMod#1!64!!%
1435 }
1436 \def\HyPsd@HighB#1!{%
1437 \expandafter\expandafter\expandafter\HyPsd@HighC
1438 \IntCalcDec#1!!%
1439 }
1440 \def\HyPsd@HighC#1!{%
1441 \IntCalcDiv#1!4!%
1442 \@backslashchar
1443 \IntCalcMod#1!4!%
1444 }
1445 \def\HyPsd@HighD#1!{%
1446 \ifcase\IntCalcDiv#1!8! %
1447 0\or 1\or 2\or 3\or 4\or 5\or 6\or 7%
1448 \fi
1449 \ifcase\IntCalcMod#1!8! %
1450 0\or 1\or 2\or 3\or 4\or 5\or 6\or 7%
1451 \fi
1452 }
1453 \def\HyPsd@DecimalToOctalFirst#1{%

```

```

1454 \9%
1455 \ifcase#1 %
1456     000\or 001\or 002\or 003\or 004\or 005\or 006\or 007%
1457     \or 010\or 011\or 012\or 013\or 014\or 015\or 016\or 017%
1458     \or 020\or 021\or 022\or 023\or 024\or 025\or 026\or 027%
1459     \or 030\or 031\or 032\or 033\or 034\or 035\or 036\or 037%
1460     \or 040\or 041\or 042\or 043\or 044\or 045\or 046\or 047%
1461     \or 050\or 051\or 052\or 053\or 054\or 055\or 056\or 057%
1462     \or 060\or 061\or 062\or 063\or 064\or 065\or 066\or 067%
1463     \or 070\or 071\or 072\or 073\or 074\or 075\or 076\or 077%
1464     \or 100\or 101\or 102\or 103\or 104\or 105\or 106\or 107%
1465     \or 120\or 111\or 112\or 113\or 114\or 115\or 116\or 117%
1466     \or 120\or 121\or 122\or 123\or 124\or 125\or 126\or 127%
1467     \or 130\or 131\or 132\or 133\or 134\or 135\or 136\or 137%
1468     \or 140\or 141\or 142\or 143\or 144\or 145\or 146\or 147%
1469     \or 150\or 151\or 152\or 153\or 154\or 155\or 156\or 157%
1470     \or 160\or 161\or 162\or 163\or 164\or 165\or 166\or 167%
1471     \or 170\or 171\or 172\or 173\or 174\or 175\or 176\or 177%
1472     \or 200\or 201\or 202\or 203\or 204\or 205\or 206\or 207%
1473     \or 210\or 211\or 212\or 213\or 214\or 215\or 216\or 217%
1474     \or 220\or 221\or 222\or 223\or 224\or 225\or 226\or 227%
1475     \or 230\or 231\or 232\or 233\or 234\or 235\or 236\or 237%
1476     \or 240\or 241\or 242\or 243\or 244\or 245\or 246\or 247%
1477     \or 250\or 251\or 252\or 253\or 254\or 255\or 256\or 257%
1478     \or 260\or 261\or 262\or 263\or 264\or 265\or 266\or 267%
1479     \or 270\or 271\or 272\or 273\or 274\or 275\or 276\or 277%
1480     \or 300\or 301\or 302\or 303\or 304\or 305\or 306\or 307%
1481     \or 310\or 311\or 312\or 313\or 314\or 315\or 316\or 317%
1482     \or 320\or 321\or 322\or 323\or 324\or 325\or 326\or 327%
1483     \or 330\or 331\or 332\or 333\or 334\or 335\or 336\or 337%
1484     \or 340\or 341\or 342\or 343\or 344\or 345\or 346\or 347%
1485     \or 350\or 351\or 352\or 353\or 354\or 355\or 356\or 357%
1486     \or 360\or 361\or 362\or 363\or 364\or 365\or 366\or 367%
1487     \or 370\or 371\or 372\or 373\or 374\or 375\or 376\or 377%
1488 \fi
1489 }
1490 \def\HyPsd@DecimalToOctalSecond#1{%
1491     \ifcase #1 %
1492         \000\or \001\or \002\or \003\or \004\or \005\or \006\or \007%
1493         \or \010\or \011\or \012\or \013\or \014\or \015\or \016\or \017%
1494         \or \020\or \021\or \022\or \023\or \024\or \025\or \026\or \027%
1495         \or \030\or \031\or \032\or \033\or \034\or \035\or \036\or \037%
1496         \or \040\or \041\or \042\or \043\or \044\or \045\or \046\or \047%
1497         \or \050\or \051\or \052\or \053\or \054\or \055\or \056\or \057%
1498         \or \060\or \061\or \062\or \063\or \064\or \065\or \066\or \067%
1499         \or \070\or \071\or \072\or \073\or \074\or \075\or \076\or \077%
1500         \or \100\or \101\or \102\or \103\or \104\or \105\or \106\or \107%
1501         \or \110\or \111\or \112\or \113\or \114\or \115\or \116\or \117%
1502         \or \120\or \121\or \122\or \123\or \124\or \125\or \126\or \127%
1503         \or \130\or \131\or \132\or \133\or \134\or \135\or \136\or \137%
1504         \or \140\or \141\or \142\or \143\or \144\or \145\or \146\or \147%
1505         \or \150\or \151\or \152\or \153\or \154\or \155\or \156\or \157%
1506         \or \160\or \161\or \162\or \163\or \164\or \165\or \166\or \167%
1507         \or \170\or \171\or \172\or \173\or \174\or \175\or \176\or \177%
1508         \or \200\or \201\or \202\or \203\or \204\or \205\or \206\or \207%
1509         \or \210\or \211\or \212\or \213\or \214\or \215\or \216\or \217%
1510         \or \220\or \221\or \222\or \223\or \224\or \225\or \226\or \227%

```

```

1511 \or \230\or \231\or \232\or \233\or \234\or \235\or \236\or \237%
1512 \or \240\or \241\or \242\or \243\or \244\or \245\or \246\or \247%
1513 \or \250\or \251\or \252\or \253\or \254\or \255\or \256\or \257%
1514 \or \260\or \261\or \262\or \263\or \264\or \265\or \266\or \267%
1515 \or \270\or \271\or \272\or \273\or \274\or \275\or \276\or \277%
1516 \or \300\or \301\or \302\or \303\or \304\or \305\or \306\or \307%
1517 \or \310\or \311\or \312\or \313\or \314\or \315\or \316\or \317%
1518 \or \320\or \321\or \322\or \323\or \324\or \325\or \326\or \327%
1519 \or \330\or \331\or \332\or \333\or \334\or \335\or \336\or \337%
1520 \or \340\or \341\or \342\or \343\or \344\or \345\or \346\or \347%
1521 \or \350\or \351\or \352\or \353\or \354\or \355\or \356\or \357%
1522 \or \360\or \361\or \362\or \363\or \364\or \365\or \366\or \367%
1523 \or \370\or \371\or \372\or \373\or \374\or \375\or \376\or \377%
1524 \fi
1525 }

1526 \def\HyPsd@CJKnumber#1{%
1527 \ifnum#1<\z@
1528 \CJK@minus
1529 \expandafter\HyPsd@@CJKnumber\expandafter{\number-\number#1}%
1530 \else
1531 \expandafter\HyPsd@@CJKnumber\expandafter{\number#1}%
1532 \fi
1533 }

1534 \def\HyPsd@@CJKnumber#1{%
1535 \ifcase#1 %
1536 \CJK@zero\or\CJK@one\or\CJK@two\or\CJK@three\or\CJK@four\or
1537 \CJK@five\or\CJK@six\or\CJK@seven\or\CJK@eight\or\CJK@nine\or
1538 \CJK@ten\or\CJK@ten\CJK@one\or\CJK@ten\CJK@two\or
1539 \CJK@ten\CJK@three\or\CJK@ten\CJK@four\or\CJK@ten\CJK@five\or
1540 \CJK@ten\CJK@six\or\CJK@ten\CJK@seven\or\CJK@ten\CJK@eight\or
1541 \CJK@ten\CJK@nine
1542 \else
1543 \ifnum#1<10000 %
1544 \HyPsd@CJKnumberFour#1!\@empty{20}%
1545 \@empty
1546 \else
1547 \ifnum#1<100000000 %
1548 \expandafter\expandafter\expandafter\HyPsd@CJKnumberFour
1549 \IntCalcDiv#1!10000!%
1550 !\{20}%
1551 \CJK@tenthousand
1552 \expandafter\expandafter\expandafter\HyPsd@CJKnumberFour
1553 \IntCalcMod#1!10000!%
1554 !\CJK@zero{10}%
1555 \@empty
1556 \else
1557 \expandafter\HyPsd@CJKnumberLarge
1558 \number\IntCalcDiv#1!100000000!\expandafter!%
1559 \number\IntCalcMod#1!100000000!!%
1560 \fi
1561 \fi
1562 \fi
1563 }

1564 \def\HyPsd@CJKnumberLarge#1!#2!{%
1565 \HyPsd@CJKnumberFour#1!\{20}%
1566 \CJK@hundredmillion
1567 \ifnum#2=\z@

```

```

1568 \else
1569 \expandafter\expandafter\expandafter\HyPsd@CJKnumberFour
1570 \IntCalcDiv#2!10000!%
1571 !\CJK@zero{10}%
1572 \CJK@tenthousand
1573 \expandafter\expandafter\expandafter\HyPsd@CJKnumberFour
1574 \IntCalcMod#2!10000!%
1575 !\CJK@zero{10}%
1576 \@empty
1577 \fi
1578 }
1579 \def\HyPsd@CJKnumberFour#1!#2#3{%
1580 \ifnum#1=\z@
1581 \expandafter\@gobble
1582 \else
1583 \ifnum#1<1000 %
1584 #2%
1585 \HyPsd@CJKnumberThree#1!#{#3}%
1586 \else
1587 \HyPsd@@CJKnumber{\IntCalcDiv#1!1000!}%
1588 \CJK@thousand
1589 \expandafter\expandafter\expandafter\HyPsd@CJKnumberThree
1590 \IntCalcMod#1!1000!%
1591 !\CJK@zero{10}%
1592 \fi
1593 \fi
1594 }
1595 \def\HyPsd@CJKnumberThree#1!#2#3{%
1596 \ifnum#1=\z@
1597 \else
1598 \ifnum#1<100 %
1599 #2%
1600 \HyPsd@CJKnumberTwo#1!#{#3}%
1601 \else
1602 \HyPsd@@CJKnumber{\IntCalcDiv#1!100!}%
1603 \CJK@hundred
1604 \expandafter\expandafter\expandafter\HyPsd@CJKnumberTwo
1605 \IntCalcMod#1!100!%
1606 !\CJK@zero{10}%
1607 \fi
1608 \fi
1609 }
1610 \def\HyPsd@CJKnumberTwo#1!#2#3{%
1611 \ifnum#1=\z@
1612 \else
1613 \ifnum#1<#3 %
1614 #2%
1615 \HyPsd@@CJKnumber{#1}%
1616 \else
1617 \HyPsd@@CJKnumber{\IntCalcDiv#1!10!}%
1618 \CJK@ten
1619 \ifnum\IntCalcMod#1!10!=\z@
1620 \else
1621 \HyPsd@@CJKnumber{\IntCalcMod#1!10!}%
1622 \fi
1623 \fi
1624 \fi

```

```

1625 }
1626 \def\HyPsd@CJKdigits#1{%
1627   \ifx*#1\relax
1628     \expandafter\HyPsd@@CJKdigits\expandafter\CJK@zero
1629   \else
1630     \HyPsd@@CJKdigits\CJK@null{#1}%
1631   \fi
1632 }
1633 \def\HyPsd@@CJKdigits#1#2{%
1634   \ifx\#2\%
1635     \else
1636       \HyPsd@@@CJKdigits#1#2\@nil
1637     \fi
1638 }%
1639 \def\HyPsd@@@CJKdigits#1#2#3\@nil{%
1640   \HyPsd@CJKdigit#1{#2}%
1641   \ifx\#3\%
1642     \expandafter\@gobble
1643   \else
1644     \expandafter\@firstofone
1645   \fi
1646   {%
1647     \HyPsd@@@CJKdigits#1#3\@nil
1648   }%
1649 }
1650 \def\HyPsd@CJKdigit#1#2{%
1651   \ifcase#2 %
1652     #1\or
1653     \CJK@one\or\CJK@two\or\CJK@three\or\CJK@four\or
1654     \CJK@five\or\CJK@six\or\CJK@seven\or\CJK@eight\or\CJK@nine
1655   \fi
1656 }

```

6.5.6 \@inmathwarn-Patch

`\HyPsd@inmathwarn` The patch of `\@inmathwarn` is needed to get rid of the infinite error loop with glyphs of other encodings (see the explanation above). Potentially the patch is dangerous, if the code in `ltoutenc.dtx` changes. Checked with \LaTeX 2 ϵ versions [1998/06/01] and [1998/12/01]. I expect that versions below [1995/12/01] don't work.

To understand the patch easier, the original code of `\@current@cmd` and `\@changed@cmd` follows (\LaTeX 2 ϵ release [1998/12/01]). In the normal case `\pdfstringdef` is executed in a context where `\protect` has the meaning of `\@typeset-protect` ($=\relax$).

```

\def\@current@cmd#1{%
  \ifx\protect\@typeset@protect
    \@inmathwarn#1%
  \else
    \noexpand#1\expandafter\@gobble
  \fi}
\def\@changed@cmd#1#2{%
  \ifx\protect\@typeset@protect
    \@inmathwarn#1%
    \expandafter\ifx\csname\cf@encoding\string#1\endcsname\relax
      \expandafter\ifx\csname?\string#1\endcsname\relax
        \expandafter\def\csname?\string#1\endcsname{%

```



```

        \TextSymbolUnavailable#1%
      }%
    \fi
    \global\expandafter\let
      \csname\cf@encoding\string#1\expandafter\endcsname
      \csname ?\string#1\endcsname
    \fi
    \csname\cf@encoding\string#1%
      \expandafter\endcsname
    \else
      \noexpand#1%
    \fi}
\gdef\TextSymbolUnavailable#1{%
  \@latex@error{%
    Command \protect#1 unavailable in encoding \cf@encoding%
  }\@eha}
\def\@inmathwarn#1{%
  \ifmmode
    \@latex@warning{Command \protect#1 invalid in math mode}%
  \fi}

1657 \def\HyPsd@inmathwarn#1#2{%
1658   \ifx#2\expandafter
1659     \expandafter\ifx\csname\cf@encoding\string#1\endcsname\relax
1660       \HyPsd@GLYPHERR
1661       \expandafter\@gobble\string#1%
1662     >%
1663     \expandafter\expandafter\expandafter\HyPsd@EndWithElse
1664   \else
1665     \expandafter\expandafter\expandafter\HyPsd@GobbleFiFi
1666   \fi
1667 \else
1668   \expandafter#2%
1669 \fi
1670 }
1671 \def\HyPsd@GobbleFiFi#1\fi#2\fi{}
1672 \def\HyPsd@EndWithElse#1\else\else}

\HyPsd@add@accent

1673 \def\HyPsd@add@accent#1#2{%
1674   \HyPsd@GLYPHERR\expandafter\@gobble\string#1+\string#2>%
1675   #2%
1676 }%

```

6.5.7 Unexpandable spaces

`\HyPsd@LetUnexpandableSpace` In `\HyPsd@@ProtectSpaces` the space tokens are replaced by not expandable commands, that work like spaces:

- So they can be caught by undelimited arguments.
- And they work in number, `dimen`, and `skip` assignments.

These properties are used in `\HyPsd@CheckCatcodes`.

```

1677 \def\HyPsd@LetUnexpandableSpace#1{%
1678   \expandafter\futurelet\expandafter#1\expandafter\@gobble\space\relax
1679 }

```

`\HyPsd@UnexpandableSpace` `\HyPsd@UnexpandableSpace` is used in `\HyPsd@@ProtectSpaces`. In `\yPsd@@ProtectSpaces` the space tokens are replaced by unexpandable commands `\HyPsd@UnexpandableSpace`, but that have the effect of spaces.

```
1680 \HyPsd@LetUnexpandableSpace\HyPsd@UnexpandableSpace
```

6.5.8 Marker for commands

`\HyPsd@XSPACE` Some commands and informations cannot be utilized before the string expansion and the checking process. Command names are filtered out, so we need another way to transport the information: An unusual `#` with catcode 12 marks the beginning of the extra information.

```
1681 \edef\HyPsd@XSPACE{\string#\string X}
1682 \edef\HyPsd@ITALCORR{\string#\string I}
1683 \edef\HyPsd@GLYPHERR{\string#\string G}
```

6.5.9 `\hspace` fix

`\HyPsd@hspace`

```
1684 \def\HyPsd@hspace#1{\HyPsd@@hspace#1*END}
```

`\HyPsd@@hspace` `\HyPsd@@hspace` checks whether `\hspace` is called in its star form.

```
1685 \def\HyPsd@@hspace#1*#2END{%
1686   \ifx\#2\%
1687     \HyPsd@hspacetest{#1}%
1688   \else
1689     \expandafter\HyPsd@hspacetest
1690   \fi
1691 }
```

`\HyPsd@hspacetest` `\HyPsd@hspacetest` replaces the `\hspace` by a space, if the length is greater than zero.

```
1692 \def\HyPsd@hspacetest#1{\ifdim#1>\z@\space\fi}
```

6.5.10 Fix for AMS classes

```
1693 \ltx@ifundefined{tocsection}{%
1694   \let\HyPsd@AMSclassfix\relax
1695 }{%
1696   \def\HyPsd@AMSclassfix{%
1697     \let\tocpart\HyPsd@tocsection
1698     \let\tocchapter\HyPsd@tocsection
1699     \let\tocappendix\HyPsd@tocsection
1700     \let\tocsection\HyPsd@tocsection
1701     \let\tocsubsection\HyPsd@tocsection
1702     \let\tocsubsubsection\HyPsd@tocsection
1703     \let\tocparagraph\HyPsd@tocsection
1704   }%
1705   \def\HyPsd@tocsection#1#2#3{%
1706     \if @#2@ \else \if @#1@ \else #1 \fi #2. \fi
1707     #3%
1708   }%
1709 }
```

6.5.11 Reference commands

`\HyPsd@href`

```
1710 \def\HyPsd@href#1#{\@secondoftwo}
```

`\HyPsd@ref` Macro `\HyPsd@ref` calls the macro `\HyPsd@@ref` for star checking. The same methods like in `\HyPsd@hspace` is used.

```
1711 \def\HyPsd@ref#1{\HyPsd@@ref#1*\END}%
```

`\HyPsd@@ref` Macro `\HyPsd@@ref` checks if a star is present.

```
1712 \def\HyPsd@@ref#1*#2\END{%
1713   \ifx\#2\%
1714     \HyPsd@@@ref{#1}%
1715   \else
1716     \expandafter\HyPsd@@@ref
1717   \fi
1718 }%
```

`\HyPsd@@@ref` `\HyPsd@@@ref` does the work and extracts the first argument.

```
1719 \def\HyPsd@@@ref#1{%
1720   \expandafter\ifx\csname r@#1\endcsname\relax
1721     ??%
1722   \else
1723     \expandafter\expandafter\expandafter
1724     \@car\csname r@#1\endcsname\@nil
1725   \fi
1726 }
```

`\HyPsd@pageref` Macro `\HyPsd@pageref` calls the macro `\HyPsd@@pageref` for star checking. The same methods like in `\HyPsd@hspace` is used.

```
1727 \def\HyPsd@pageref#1{\HyPsd@@pageref#1*\END}
```

`\HyPsd@@pageref` Macro `\HyPsd@@pageref` checks if a star is present.

```
1728 \def\HyPsd@@pageref#1*#2\END{%
1729   \ifx\#2\%
1730     \HyPsd@@@pageref{#1}%
1731   \else
1732     \expandafter\HyPsd@@@pageref
1733   \fi
1734 }
```

`\HyPsd@@@pageref` `\HyPsd@@@pageref` does the work and extracts the second argument.

```
1735 \def\HyPsd@@@pageref#1{%
1736   \expandafter\ifx\csname r@#1\endcsname\relax
1737     ??%
1738   \else
1739     \expandafter\expandafter\expandafter\expandafter
1740     \expandafter\expandafter\expandafter\@car
1741     \expandafter\expandafter\expandafter\@gobble
1742     \csname r@#1\endcsname{}\@nil
1743   \fi
1744 }
```

`\HyPsd@nameref` Macro `\HyPsd@nameref` calls the macro `\HyPsd@@nameref` for star checking. The same methods like in `\HyPsd@hspace` is used.

```
1745 \def\HyPsd@nameref#1{\HyPsd@@nameref#1*\END}
```

`\HyPsd@@nameref` Macro `\HyPsd@@nameref` checks if a star is present.

```
1746 \def\HyPsd@@nameref#1*#2\END{%
1747   \ifx\#2\%
1748     \HyPsd@@@nameref{#1}%
```

```

1749 \else
1750 \expandafter\HyPsd@@@nameref
1751 \fi
1752 }

```

\HyPsd@@@nameref \HyPsd@@@nameref does the work and extracts the third argument.

```

1753 \def\HyPsd@@@nameref#1{%
1754 \expandafter\ifx\csname r@#1\endcsname\relax
1755 ??%
1756 \else
1757 \expandafter\expandafter\expandafter\expandafter
1758 \expandafter\expandafter\expandafter\@car
1759 \expandafter\expandafter\expandafter\@gobbletwo
1760 \csname r@#1\endcsname\}\}\@nil
1761 \fi
1762 }

```

\HyPsd@autoref Macro \HyPsd@autoref calls the macro \HyPsd@@autoref for star checking. The same methods like in \HyPsd@hspace is used.

```

1763 \def\HyPsd@autoref#1{\HyPsd@@autoref#1*\END}

```

\HyPsd@@autoref Macro \HyPsd@@autoref checks if a star is present.

```

1764 \def\HyPsd@@autoref#1*#2\END{%
1765 \ifx\#2\%
1766 \HyPsd@@@autoref{#1}%
1767 \else
1768 \expandafter\HyPsd@@@autoref
1769 \fi
1770 }

```

\HyPsd@@@autoref \HyPsd@@@autoref does the work and extracts the second argument.

```

1771 \def\HyPsd@@@autoref#1{%
1772 \expandafter\ifx\csname r@#1\endcsname\relax
1773 ??%
1774 \else
1775 \expandafter\expandafter\expandafter\HyPsd@autorefname
1776 \csname r@#1\endcsname\}\}\}\@nil
1777 \expandafter\expandafter\expandafter
1778 \@car\csname r@#1\endcsname\@nil
1779 \fi
1780 }

```

\HyPsd@autorefname At least a basic definition for getting the \autoref name.

```

1781 \def\HyPsd@autorefname#1#2#3#4#5\@nil{%
1782 \ifx\#4\%
1783 \else
1784 \HyPsd@@@autorefname#4.\@nil
1785 \fi
1786 }

```

\HyPsd@@@autorefname

```

1787 \def\HyPsd@@@autorefname#1.#2\@nil{%
1788 \ltx@ifundefined{#1autorefname}{%
1789 \ltx@ifundefined{#1name}{%
1790 }{%
1791 \csname#1name\endcsname\space
1792 }%

```

```

1793 }{%
1794   \csname#1\autorefname\endcsname\space
1795 }%
1796 }

```

6.5.12 Redefining the defining commands

Definitions aren't allowed, because they aren't executed in an only expanding context. So the command to be defined isn't defined and can perhaps be undefined. This would causes TeX to stop with an error message. With a deep trick it is possible to define commands in such a context: `\csname` does the job, it defines the command to be `\relax`, if it has no meaning.

Active characters cannot be defined with this trick. It is possible to define all undefined active characters (perhaps that they have the meaning of `\relax`). To avoid side effects this should be done in `\pdfstringdef` shortly before the `\xdef` job. But checking and defining all possible active characters of the full range (0 until 255) would take a while. `\pdfstringdef` is slow enough, so this isn't done.

`\HyPsd@DefCommand` and `\HyPsd@LetCommand` expands to the commands `\<def>-command` and `\<let>-command` with the meaning of `\def` and `\let`. So it is detected by `\HyPsd@CheckCatcodes` and the command name `\<def>-command` or `\<let>-command` should indicate a forbidden definition command.

The command to be defined is converted to a string and back to a command name with the help of `\csname`. If the command is already defined, `\noexpand` prevents a further expansion, even though the command would expand to legal stuff. If the command don't have the meaning of `\relax`, `\HyPsd@CheckCatcodes` will produce a warning. (The command itself can be legal, but the warning is legitimate because of the position after a defining command.)

The difference between `\HyPsd@DefCommand` and `\HyPsd@LetCommand` is that the first one also cancels this arguments, the parameter and definition text. The right side of the `\let` commands cannot be canceled with an undelimited parameter because of a possible space token after `\futurelet`.

To avoid unmathcted `\if...` tokens, the cases `\let\if...\iftrue` and `\let\if...\iffalse` are checked and ignored.

```

\HyPsd@DefCommand
\HyPsd@LetCommand
1797 \begingroup
1798   \def\x#1#2{%
1799     \endgroup
1800     \let#1\def
1801     \def\HyPsd@DefCommand##1##2###{%
1802       #1%
1803       \expandafter\noexpand
1804         \csname\expandafter\@gobble\string##1\@empty\endcsname
1805       \@gobble
1806     }%
1807     \let#2\let
1808     \def\HyPsd@@LetCommand##1{%
1809       \expandafter\ifx\csname##1\expandafter\endcsname
1810         \csname iftrue\endcsname
1811       \pdfstringdefWarn\let
1812       \expandafter\@gobble
1813     \else
1814       \expandafter\ifx\csname##1\expandafter\endcsname
1815         \csname iffalse\endcsname

```

```

1816      \pdfstringdefWarn\let
1817      \expandafter\expandafter\expandafter\@gobble
1818      \else
1819      #2%
1820      \expandafter\noexpand
1821      \csname##1\expandafter\expandafter\expandafter\endcsname
1822      \fi
1823      \fi
1824      }%
1825      }%
1826 \expandafter\x\csname <def>-command\expandafter\endcsname
1827      \csname <let>-command\endcsname
1828 \def\HyPsd@LetCommand#1{%
1829 \expandafter\expandafter\expandafter\HyPsd@@LetCommand
1830 \expandafter\expandafter\expandafter{%
1831 \expandafter\@gobble\string#1\@empty
1832 }%
1833 }

```

6.5.13 \ifnextchar

`\HyPsd@ifnextchar` In `\pdfstringdef \ifnextchar` is disabled via a `\let` command to save time. First a warning message is given, then the three arguments are canceled. `\ifnextchar` cannot work in a correct manner, because it uses `\futurelet`, but this is a stomach feature, that doesn't work in an expanding context. There are several variants of `\ifnextchar`:

- `\@ifnextchar`
- `\kernel@ifnextchar`
- `\new@ifnextchar` from package `amsgen.sty` (bug report latex/3662).

```

1834 \def\HyPsd@ifnextchar#1{%
1835 \pdfstringdefWarn#1%
1836 \expandafter\@gobbletwo\@gobble
1837 }

```

6.5.14 \@protected@testoptifnextchar

`\HyPsd@protected@testopt` Macros with optional arguments doesn't work properly, because they call `\ifnextchar` to detect the optional argument (see the explanation of `\HyPsd@ifnextchar`). But a warning, that `\ifnextchar` doesn't work, doesn't help the user very much. Therefore `\@protected@testopt` is also disabled, because its first argument is the problematic macro with the optional argument and it is called before `\ifnextchar`.

```

1838 \def\HyPsd@protected@testopt#1{%
1839 \pdfstringdefWarn#1%
1840 \@gobbletwo
1841 }

```

6.6 Help macros for postprocessing

6.6.1 Generic warning.

`\HyPsd@Warning` For several reasons `\space` is masked and does not have its normal meaning. But it is used in warning messages, so it is redefined locally:

```

1842 \def\HyPsd@Warning#1{%
1843   \begingroup
1844   \let\space\ltx@space
1845   \Hy@Warning{#1}%
1846 \endgroup
1847 }

```

6.6.2 Protecting spaces

```

1848 \RequirePackage{etexcmds}[2007/09/09]
1849 \ifetex@unexpanded
1850   \expandafter\@secondoftwo
1851 \else
1852   \expandafter\@firstoftwo
1853 \fi
1854 {%

```

`\HyPsd@ProtectSpaces` `\HyPsd@ProtectSpaces` calls with the expanded string `\HyPsd@@ProtectSpacesFi`. The expanded string is protected by `|` at the beginning and end of the expanded string. Because of this there can be no group at the beginning or end of the string and grouping characters are not removed by the call of `\HyPsd@@ProtectSpacesFi`.

```

1855 \def\HyPsd@ProtectSpaces#1{%
1856   \iftrue
1857     \expandafter\HyPsd@@ProtectSpacesFi
1858     \expandafter|\expandafter\@empty#1| \HyPsd@End#1%
1859   \fi
1860 }%

```

`\HyPsd@@ProtectSpacesFi` The string can contain command tokens, so it is better to use an `\def` instead of an `\edef`.

```

1861 \def\HyPsd@@ProtectSpacesFi#1 #2\HyPsd@End#3\fi{%
1862   \fi
1863   \ifx\scrollmode#2\scrollmode
1864     \HyPsd@RemoveMask#1\HyPsd@End#3%
1865   \else
1866     \gdef#3{#1\HyPsd@UnexpandableSpace#2}%
1867     \expandafter\HyPsd@@ProtectSpacesFi#3\HyPsd@End#3%
1868   \fi
1869 }%

```

Remove mask.

`\HyPsd@RemoveMask` `\HyPsd@RemoveMask` removes the protecting `|`. It is used by `\HyPsd@@ProtectSpacesFi` and by the code in `\pdfstringdef` that removes the grouping characters.

```

1870 \def\HyPsd@RemoveMask|#1|\HyPsd@End#2{%
1871   \toks@\expandafter{#1}%
1872   \xdef#2{\the\toks@}%
1873 }%

1874 }{%
1875   \let\HyPsd@fi\fi
1876   \def\HyPsd@ProtectSpaces#1{%
1877     \xdef#1{%
1878       \iftrue
1879         \expandafter\HyPsd@@ProtectSpacesFi

```

```

1880     \expandafter\expandafter\@empty#1| %
1881     \HyPsd@fi
1882 }%
1883 \expandafter\HyPsd@RemoveMask#1\HyPsd@End#1%
1884 }%
1885 \def\HyPsd@@ProtectSpacesFi#1 #2\HyPsd@fi{%
1886   \fi
1887   \etex@unexpanded{#1}%
1888   \ifx\scrollmode#2\scrollmode
1889   \else
1890     \HyPsd@@ProtectSpacesFi\HyPsd@UnexpandableSpace#2%
1891     \HyPsd@fi
1892   }%
1893 \def\HyPsd@RemoveMask|#1|\HyPsd@End#2{%
1894   \xdef#2{\etex@unexpanded\expandafter{#1}}%
1895 }%
1896 }

```

6.6.3 Remove grouping braces

`\HyPsd@RemoveBraces` *#1* contains the expanded string, the result will be locally written in command `\HyPsd@String`.

```

1897 \def\HyPsd@RemoveBraces#1{%
1898   \ifx\scrollmode#1\scrollmode
1899   \else
1900     \HyPsd@@RemoveBracesFi#1\HyPsd@End{#1}%
1901     \fi
1902 }

```

`\HyPsd@@RemoveBraces` `\HyPsd@@RemoveBraces` is called with the expanded string, the end marked by `\HyPsd@End`, the expanded string again, but enclosed in braces and the string command. The first expanded string is scanned by the parameter text *#1#2*. By a comparison with the original form in *#3* we can decide whether *#1* is a single token or a group. To avoid the case that *#2* is a group, the string is extended by a `|` before.

While removing the grouping braces an italic correction marker is inserted for supporting package `xspace` and letting ligatures broken.

Because the string is already expanded, the `\if` commands should disappeared. So we can move some parts out of the argument of `\ltx@ReturnAfterFi`.

```

1903 \def\HyPsd@@RemoveBracesFi#1#2\HyPsd@End#3\fi{%
1904   \fi
1905   \def\Hy@temp@A{#1#2}%
1906   \def\Hy@temp@B{#3}%
1907   \ifx\Hy@temp@A\Hy@temp@B
1908     \expandafter\def\expandafter\HyPsd@String\expandafter{%
1909       \HyPsd@String#1%
1910     }%
1911   \ifx\scrollmode#2\scrollmode
1912   \else
1913     \Hy@ReturnAfterFiFiEnd{%
1914       \HyPsd@RemoveBraces{#2}%
1915     }%
1916   \fi
1917 \else
1918   \def\Hy@temp@A{#1}%
1919   \HyPsd@AppendItalcrr\HyPsd@String

```



```

1920 \ifx\Hy@temp@A\@empty
1921 \Hy@ReturnAfterElseFiFiEnd{%
1922 \HyPsd@RemoveBraces{#2}%
1923 }%
1924 \else
1925 \HyPsd@ProtectSpaces\Hy@temp@A
1926 \HyPsd@AppendItalcorr\Hy@temp@A
1927 \Hy@ReturnAfterFiFiEnd{%
1928 \expandafter\HyPsd@RemoveBraces\expandafter
1929 {\Hy@temp@A#2}%
1930 }%
1931 \fi
1932 \fi
1933 \Hy@ReturnEnd
1934 }

```

`\HyPsd@AppendItalcorr` The string can contain commands yet, so it is better to use `\def` instead of a shorter `\edef`. The two help macros limit the count of `\expandafter`.

```

1935 \def\HyPsd@AppendItalcorr#1{%
1936 \expandafter\HyPsd@@AppendItalcorr\expandafter{/}%#1%
1937 }
1938 \def\HyPsd@@AppendItalcorr#1#2{%
1939 \expandafter\def\expandafter#2\expandafter{#2#1}%
1940 }

```

6.6.4 Catcode check

Workaround for LuaTeX. `\HyPsd@CheckCatcodes` might trigger a bug of LuaTeX (0.60.2, 0.70.1, 0.70.2, ...) in the comparison with `\ifcat`, see <http://tracker.luatex.org/view.php?id=773>.

```

1941 \ltx@ifundefined{directlua}{%
1942 }{%
1943 \expandafter\ifx\csname\endcsname\relax\fi
1944 }

```

Check catcodes.

`\HyPsd@CheckCatcodes` Because `\ifcat` expands its arguments, this is prevented by `\noexpand`. In case of command tokens and active characters `\ifcat` now sees a `\relax`. After protecting spaces and removing braces `#1` should be a single token, no group of several tokens, nor an empty group. (So the `\expandafter\relax` between `\ifcat` and `\noexpand` is only for safety and it should be possible to remove it.)

`\protect` and `\relax` should be removed silently. But it is too dangerous and breaks some code giving them the meaning of `\@empty`. So commands with the meaning of `\protect` are removed here. (`\protect` should have the meaning of `\@typeset@protect` that is equal to `\relax`).

For the comparison with active characters, `~` cannot be used because it has the meaning of a blank space here. And active characters need to be checked, if they have been defined using `\protected`.

```

1945 \begingroup
1946 \catcode'\Q=\active
1947 \let Q\ltx@empty
1948 \gdef\HyPsd@CheckCatcodes#1#2\HyPsd@End{%
1949 \global\let\HyPsd@Rest\relax
1950 \ifcat\relax\noexpand#1\relax

```

```

1951 \ifx#1\protect
1952 \else
1953 \ifx#1\penalty
1954 \setbox\z@=\hbox{%
1955 \afterassignment\HyPsd@AfterCountRemove
1956 \count@=#2\HyPsd@End
1957 }%
1958 \else
1959 \ifx#1\kern
1960 \setbox\z@=\hbox{%
1961 \afterassignment\HyPsd@AfterDimenRemove
1962 \dimen@=#2\HyPsd@End
1963 }%
1964 \else
1965 \ifx#1\hskip
1966 \setbox\z@=\hbox{%
1967 \afterassignment\HyPsd@AfterSkipRemove
1968 \skip@=#2\HyPsd@End
1969 }%
1970 \else
1971 \HyPsd@CatcodeWarning{#1}%
1972 \fi
1973 \fi
1974 \fi
1975 \fi
1976 \else
1977 \ifcat\noexpand#1\noexpandQ% active character
1978 \expandafter\expandafter\expandafter\def
1979 \expandafter\expandafter\expandafter\HyPsd@String
1980 \expandafter\expandafter\expandafter{%
1981 \expandafter\HyPsd@String\string#1%
1982 }%
1983 \else
1984 \ifcat#1A% letter
1985 \expandafter\def\expandafter\HyPsd@String\expandafter{%
1986 \HyPsd@String#1%
1987 }%
1988 \else
1989 \ifcat#1 % SPACE
1990 \expandafter\def\expandafter\HyPsd@String\expandafter{%
1991 \HyPsd@String\HyPsd@SPACEOPTI
1992 }%
1993 \else
1994 \ifcat$#1%
1995 \HyPsd@CatcodeWarning{math shift}%
1996 \else
1997 \ifcat&#1%
1998 \HyPsd@CatcodeWarning{alignment tab}%
1999 \else
2000 \ifcat^#1%
2001 \HyPsd@CatcodeWarning{superscript}%
2002 \else
2003 \ifcat_#1%
2004 \HyPsd@CatcodeWarning{subscript}%
2005 \else
2006 \expandafter\def\expandafter\HyPsd@String\expandafter{%
2007 \HyPsd@String#1%

```

```

2008         }%
2009         \fi
2010     \fi
2011 \fi
2012 \fi
2013 \fi
2014 \fi
2015 \fi
2016 \fi
2017 \ifx\HyPsd@Rest\relax
2018     \ifx\scrollmode#2\scrollmode
2019     \else
2020         \Hy@ReturnAfterFiFiEnd{%
2021             \HyPsd@CheckCatcodes#2\HyPsd@End
2022         }%
2023     \fi
2024 \else
2025     \ifx\HyPsd@Rest\@empty
2026     \else
2027         \Hy@ReturnAfterFiFiEnd{%
2028             \expandafter\HyPsd@CheckCatcodes\HyPsd@Rest\HyPsd@End
2029         }%
2030     \fi
2031 \fi
2032 \Hy@ReturnEnd
2033 }%
2034 \endgroup

```

Remove counts, dimens, skips.

`\HyPsd@AfterCountRemove` Counts like `\penalty` are removed silently.

```

2035 \def\HyPsd@AfterCountRemove#1\HyPsd@End{%
2036     \gdef\HyPsd@Rest{#1}%
2037 }

```

`\HyPsd@AfterDimenRemove` If the value of the `dimen` (`\kern`) is zero, it can be removed silently. All other values are difficult to interpret. Negative values do not work in bookmarks. Should positive values be removed or should they be replaced by space(s)? The following code replaces positive values greater than `1ex` with a space and removes them else.

```

2038 \def\HyPsd@AfterDimenRemove#1\HyPsd@End{%
2039     \ifdim\ifx\HyPsd@String\@empty\z@\else\dimen@>1ex %
2040         \HyPsd@ReplaceSpaceWarning{\string\kern\space\the\dimen@}%
2041         \gdef\HyPsd@Rest{\HyPsd@UnexpandableSpace #1}%
2042     \else
2043         \ifdim\dimen@=\z@
2044         \else
2045             \HyPsd@RemoveSpaceWarning{\string\kern\space\the\dimen@}%
2046         \fi
2047         \gdef\HyPsd@Rest{#1}%
2048     \fi
2049 }

```

`\HyPsd@AfterSkipRemove` The glue part of skips do not work in PDF strings and are ignored. Skips (`\hskip`), that are not zero, have the same interpreting problems like `dimens` (see above).

```

2050 \def\HyPsd@AfterSkipRemove#1\HyPsd@End{%
2051     \ifdim\ifx\HyPsd@String\@empty\z@\else\skip@>1ex %
2052         \HyPsd@ReplaceSpaceWarning{\string\hskip\space\the\skip@}%

```

```

2053 \gdef\HyPsd@Rest{\HyPsd@UnexpandableSpace #1}%
2054 \else
2055 \ifdim\skip@=\z@
2056 \else
2057 \HyPsd@RemoveSpaceWarning{\string\kern\space\the\skip@}%
2058 \fi
2059 \gdef\HyPsd@Rest{#1}%
2060 \fi
2061 }

```

Catcode warnings.

\HyPsd@CatcodeWarning \HyPsd@CatcodeWarning produces a warning for the user.

```

2062 \def\HyPsd@CatcodeWarning#1{%
2063 \HyPsd@Warning{%
2064 Token not allowed in a PDF string (%)
2065 \ifHy@unicode
2066 Unicode%
2067 \else
2068 PDFDocEncoding%
2069 \fi
2070 }:%
2071 \MessageBreak removing '\HyPsd@RemoveCmdPrefix#1'%
2072 }%
2073 }
2074 \begingroup
2075 \catcode'\|=0 %
2076 \catcode'\|=12 %
2077 \gdef\HyPsd@RemoveCmdPrefix#1{%
2078 |expandafter\HyPsd@@RemoveCmdPrefix
2079 |string#1|@empty\<>-|@empty|@empty
2080 }%
2081 \gdef\HyPsd@@RemoveCmdPrefix#1\<>-#2|@empty#3|@empty{#1#2}%
2082 \endgroup

```

\HyPsd@RemoveSpaceWarning

```

2083 \def\HyPsd@RemoveSpaceWarning#1{%
2084 \HyPsd@Warning{%
2085 Token not allowed in a PDF string (%)
2086 \ifHy@unicode
2087 Unicode%
2088 \else
2089 PDFDocEncoding%
2090 \fi
2091 }:%
2092 \MessageBreak #1\MessageBreak
2093 removed%
2094 }%
2095 }

```

\HyPsd@ReplaceSpaceWarning

```

2096 \def\HyPsd@ReplaceSpaceWarning#1{%
2097 \HyPsd@Warning{%
2098 Token not allowed in a PDF string (%)
2099 \ifHy@unicode
2100 Unicode%
2101 \else

```

```

2102     PDFDocEncoding%
2103     \fi
2104     ):%
2105     \MessageBreak #1\MessageBreak
2106     replaced by space%
2107     }%
2108 }

```

6.6.5 Check for wrong glyphs

A wrong glyph is marked with `\relax`, the glyph name follows, delimited by `>`. `\@empty` ends the string.

```

2109 \def\HyPsd@GlyphProcess#1\relax#2\@empty{%
2110   \expandafter\def\expandafter\HyPsd@String\expandafter{%
2111     \HyPsd@String#1%
2112   }%
2113   \ifx\#2\%
2114   \else
2115     \ltx@ReturnAfterFi{%
2116       \HyPsd@GlyphProcessWarning#2\@empty
2117     }%
2118   \fi
2119 }
2120 \def\HyPsd@GlyphProcessWarning#1>#2\@empty{%
2121   \HyPsd@@@GlyphProcessWarning#1++>%
2122   \HyPsd@GlyphProcess#2\@empty
2123 }
2124 \def\HyPsd@@@GlyphProcessWarning#1+#2+#3>{%
2125   \ifx\#2\%
2126     \HyPsd@Warning{%
2127       Glyph not defined in %
2128       P\ifHy@unicode U\else D1\fi\space encoding,\MessageBreak
2129       removing '@backslashchar#1'%
2130     }%
2131   \else
2132     \HyPsd@Warning{%
2133       Composite letter '@backslashchar#1+#2'\MessageBreak
2134       not defined in P\ifHy@unicode U\else D1\fi\space encoding,%
2135       \MessageBreak
2136       removing '@backslashchar#1'%
2137     }%
2138   \fi
2139 }

```

Spaces.

`\HyPsd@spaceopti` In the string the spaces are represented by `\HyPsd@spaceopti` tokens. Within an `\edef` it prints itself as a simple space and looks for its next argument. If another space follows, so it replaces the next `\HyPsd@spaceopti` by an protected space `\040`.

```

2140 \def\HyPsd@spaceopti#1{ % first space
2141   \ifx\HyPsd@spaceopti#1%
2142     \040%
2143   \else
2144     #1%
2145   \fi
2146 }%

```

6.6.6 Replacing tokens

`\HyPsd@Subst` To save tokens `\HyPsd@StringSubst` is a wrapper for the command `\HyPsd@Subst` that does all the work: In string stored in command `#3` it replaces the tokens `#1` with `#2`.

```
#1    Exact the tokens that should be replaced.
#2    The replacement (don't need to be expanded).
#3    Command with the string.
2147 \def\HyPsd@Subst#1#2#3{%
2148   \def\HyPsd@@ReplaceFi##1#1##2\END\fi{%
2149     \fi
2150     ##1%
2151     \ifx\scrollmode##2\scrollmode
2152     \else
2153       #2%
2154       \HyPsd@@ReplaceFi##2\END
2155     \fi
2156   }%
2157   \xdef#3{%
2158     \iftrue
2159       \expandafter\HyPsd@@ReplaceFi#3#1\END
2160     \fi
2161   }%
2162 }
```

`\HyPsd@StringSubst` To save tokens in `\pdfstringdef` `\HyPsd@StringSubst` is a wrapper, that expands argument `#1` before calling `\HyPsd@Subst`.

```
2163 \def\HyPsd@StringSubst#1{%
2164   \expandafter\HyPsd@Subst\expandafter{\string#1}%
2165 }
```

`\HyPsd@EscapeTeX`

```
2166 \begingroup
2167   \lccode'\!='\%%
2168   \lccode'\|='\%%
2169   \lccode'\(='\{%
2170   \lccode'\)='\}%
2171   \lccode'0=\ltx@zero
2172   \lccode'1=\ltx@zero
2173   \lccode'3=\ltx@zero
2174   \lccode'4=\ltx@zero
2175   \lccode'5=\ltx@zero
2176   \lccode'7=\ltx@zero
2177 \lowercase{\endgroup
2178   \def\HyPsd@EscapeTeX#1{%
2179     \HyPsd@Subst!{|045}#1%
2180     \HyPsd@Subst({|173}#1%
2181     \HyPsd@Subst){|175}#1%
2182   }%
2183 }
```

6.6.7 Support for package `xspace`

`\HyPsd@doxspace` `\xspace` does not work, because it uses a `\futurelet` that cannot be executed in \TeX 's mouth. So this implementation uses an argument to examine the next token. In a previous version I reused `\@xspace`, but this version is shorter and easier to understand.

```

2184 \def\HyPsd@doxspace#1{%
2185   \ifx#1\relax\else
2186     \ifx#1.\else
2187       \ifx#1:\else
2188         \ifx#1,\else
2189         \ifx#1;\else
2190         \ifx#1!\else
2191         \ifx#1?\else
2192         \ifx#1/\else
2193         \ifx#1-\else
2194         \ifx#1'\else
2195         \HyPsd@SPACEOPTI
2196       \fi
2197     \fi
2198   \fi
2199 \fi
2200 \fi
2201 \fi
2202 \fi
2203 \fi
2204 \fi
2205 \fi
2206 #1%
2207 }%

```

6.6.8 Converting to Unicode

Eight bit characters are converted to the sixteen bit ones, \8 is replaced by \00, and \9 is removed. The result should be a valid Unicode PDF string without the Unicode marker at the beginning.

```

2208 \begingroup
2209   \catcode'\|=0 %
2210   \catcode'\|=12 %

```

\HyPsd@ConvertToUnicode

```

2211 |gdef|HyPsd@ConvertToUnicode#1{%
2212   |xdef#1{%
2213     |expandafter|HyPsd@DoConvert#1|@empty|@empty|@empty
2214   }%
2215   |ifx#1|@empty
2216   |else
2217     |xdef#1{%
2218       \376\377%
2219       #1%
2220     }%
2221   |fi
2222 }%

```

\HyPsd@DoConvert

```

2223 |gdef|HyPsd@DoConvert#1{%
2224   |ifx#1|@empty
2225   |else
2226     |ltx@ReturnAfterFi{%
2227       |ifx#1\%%
2228       \%%
2229       |expandafter|HyPsd@DoEscape
2230     |else

```

```

2231      |HyPsd@Char{#1}%
2232      |expandafter|HyPsd@DoConvert
2233      |fi
2234    }%
2235    |fi
2236  }%

```

\HyPsd@DoEscape

```

2237 |gdef|HyPsd@DoEscape#1{%
2238   |ifx#19%
2239   |expandafter|HyPsd@GetTwoBytes
2240   |else
2241   |ltx@ReturnAfterFi{%
2242   |ifx#18%
2243   00%
2244   |expandafter|HyPsd@GetTwoBytes
2245   |else
2246   #1%
2247   |expandafter|HyPsd@GetOneByte
2248   |fi
2249   }%
2250   |fi
2251 }%

```

\HyPsd@GetTwoBytes

```

2252 |gdef|HyPsd@GetTwoBytes#1\#2#3#4{%
2253   #1\#2#3#4%
2254   |HyPsd@DoConvert
2255 }%

```

\HyPsd@GetOneByte

```

2256 |gdef|HyPsd@GetOneByte#1#2{%
2257   #1#2%
2258   |HyPsd@DoConvert
2259 }%
2260 |endgroup

```

\HyPsd@@GetNextTwoTokens \TeX does only allow nine parameters, so we need another macro to get more arguments.

```

2261 \def\HyPsd@GetNextTwoTokens#1#2#3\END#4{%
2262   \xdef#4{#4#1#2}%
2263   \HyPsd@@ConvertToUnicode#3\END#4%
2264 }

```

\HyPsd@Char

```

2265 \begingroup
2266   \catcode0=9 %
2267   \catcode'\^=7 %
2268   \catcode'\^^=12 %
2269   \def\x{^^^^0000}%
2270 \expandafter\endgroup
2271 \ifx\x\@empty
2272   \def\HyPsd@Char#1{%
2273     \ifnum'#1<128 %
2274       \@backslashchar 000#1%
2275     \else
2276       \ifnum'#1<65536 %

```



```

2277 \expandafter\HyPsd@CharTwoByte\number'#1!%
2278 \else
2279 \expandafter\expandafter\expandafter\HyPsd@CharSurrogate
2280 \intcalcSub{'#1}{65536}!%
2281 \fi
2282 \fi
2283 }%
2284 \def\HyPsd@CharTwoByte#1!{%
2285 \expandafter\expandafter\expandafter\HyPsd@CharOctByte
2286 \IntCalcDiv#1!256!!%
2287 \expandafter\expandafter\expandafter\HyPsd@CharOctByte
2288 \IntCalcMod#1!256!!%
2289 }%
2290 \def\HyPsd@CharOctByte#1!{%
2291 \@backslashchar
2292 \IntCalcDiv#1!64!%
2293 \intcalcDiv{\IntCalcMod#1!64!}{8}%
2294 \IntCalcMod#1!8!%
2295 }%
2296 \def\HyPsd@CharSurrogate#1!{%
2297 \@backslashchar 33%
2298 \IntCalcDiv#1!262144!%
2299 \expandafter\expandafter\expandafter\HyPsd@CharOctByte
2300 \intcalcDiv{\IntCalcMod#1!262144!}{1024}!%
2301 \@backslashchar 33%
2302 \expandafter\expandafter\expandafter\IntCalcAdd
2303 \intcalcDiv{\IntCalcMod#1!1024!}{256}!4!%
2304 \expandafter\expandafter\expandafter\HyPsd@CharOctByte
2305 \IntCalcMod#1!256!!%
2306 }%
2307 \else
2308 \def\HyPsd@Char#1{%
2309 \@backslashchar 000#1%
2310 }%
2311 \fi

```

6.6.9 Support for UTF-8 input encoding

After `\usepackage[utf8]{inputenc}` there are macros that expect the UTF-8 octets as arguments. Therefore we can calculate the PDF octal sequences directly. Because the PDF format is limited to UCS-2, conversion macros are needed for UTF-8 sequences with two and three octets only.

This calculation must be done in an expandable context, so we use `eTeX` here for performance reasons. Unhappily the results of divisions are rounded. Thus a circumvention via `\dimexpr` is used, e.g.:

`\numexpr 123/4\relax` is replaced by
`\number\dimexpr.25\dimexpr 123sp\relax\relax`

```

2312 \begingroup\expandafter\expandafter\expandafter\endgroup
2313 \expandafter\ifx\csname numexpr\endcsname\relax
2314 \let\HyPsd@UTFviii\relax
2315 \else
2316 \begingroup
2317 \lccode'\~='^^f4\relax
2318 \lowercase{\endgroup
2319 \def\HyPsd@UTFviii{%

```

```

2320 \let\UTFviii@two@octets\HyPsd@UTFviii@two
2321 \let\UTFviii@three@octets\HyPsd@UTFviii@three
2322 \let\UTFviii@four@octets\HyPsd@UTFviii@four
2323 \ifx~\HyPsd@UTFviii@ccxliv@undef
2324 \let~\HyPsd@UTFviii@ccxliv@def
2325 \fi
2326 \let\unichar\HyPsd@unichar
2327 }%
2328 }%
2329 \def\HyPsd@UTFviii@ccxliv@undef{\@inpenc@undefined@{utf8}}}%
2330 \edef\HyPsd@UTFviii@ccxliv@def{%
2331 \noexpand\UTFviii@four@octets\string ^f4%
2332 }%

```

The two octet form of UTF-8 110aaabb (A) and 10cccd (B) must be converted into octal numbers 00a and bcd. The result is \8a\bcd (with a, b, c, d as octal numbers). The conversion equations.

$$a := A/4 - 48 \quad (1)$$

$$b := A - 4 * (A/4) \quad (2)$$

$$c := B/8 - 8 * ((8 * (B/8))/8) \quad (3)$$

$$d := B - 8 * (B/8) \quad (4)$$

$$(5)$$

```

2333 \def\HyPsd@UTFviii@two#1#2{%
2334 \expandafter\HyPsd@UTFviii@@two
2335 \number\dimexpr.25\dimexpr'#1sp\expandafter\relax\expandafter| %
2336 \number'#1\expandafter| %
2337 \number\dimexpr.125\dimexpr'#2sp\expandafter\relax\expandafter| %
2338 \number'#2 \@nil
2339 }%
2340 \def\HyPsd@UTFviii@@two#1|#2|#3|#4@nil{%
2341 \expandafter\8%
2342 \number\numexpr #1-48\expandafter\relax
2343 \csname\number\numexpr #2-4*#1\relax\expandafter\endcsname
2344 \number\numexpr #3-8*%
2345 \number\dimexpr.125\dimexpr#3sp\relax\relax\expandafter\relax
2346 \number\numexpr #4-8*#3\relax
2347 }%

```

Three octet form: 1110aabb (A), 10bcccd (B), and 10eeefff (C). The result is \9abc\def (with a, ..., f as octal numbers). The conversion equations:

$$a := A/4 - 56 \quad (6)$$

$$b := 2 * (A - 4 * (A/4)) + ((B - 128 < 32)?0 : 1) \quad (7)$$

$$c := B/4 - 32 - ((B - 128 < 32)?0 : 8) \quad (8)$$

$$d := B - 4 * (B/4) \quad (9)$$

$$e := C/8 - 16 \quad (10)$$

$$f := C - 8 * (C/8) \quad (11)$$

$$(12)$$

```

2348 \def\HyPsd@UTFviii@three#1#2#3{%
2349 \expandafter\HyPsd@UTFviii@@three
2350 \number\dimexpr.25\dimexpr'#1sp\expandafter\relax\expandafter| %
2351 \number'#1\expandafter| %

```

```

2352 \number\ifnum\numexpr'#2-128\relax <32 0\else 1\fi\expandafter| %
2353 \number\dimexpr.25\dimexpr'#2sp\expandafter\relax\expandafter| %
2354 \number'#2\expandafter| %
2355 \number\dimexpr.125\dimexpr'#3sp\expandafter\relax\expandafter| %
2356 \number'#3 \@nil
2357 }%
2358 \def\HyPsd@UTFviii@@three#1|#2|#3|#4|#5|#6|#7\@nil{%
2359 \expandafter\9%
2360 \number\numexpr #1-56\expandafter\relax
2361 \number\numexpr 2*(#2-4*#1)+#3\expandafter\relax
2362 \number\numexpr #4 - 32 -\ifcase#3 0\else 8\fi\expandafter\relax
2363 \csname\number\numexpr #5-4*#4\relax\expandafter\endcsname
2364 \number\numexpr #6-16\expandafter\relax
2365 \number\numexpr #7-8*#6\relax
2366 }%

```

Surrogates: 4 octets in UTF-8, a surrogate pair in UTF-16. High surrogate range: U+D800–U+DBFF, low surrogate range: U+DC00–U+DFFF.

```

UTF-8: 11110uuu 10uuzzzz 10yyyyyy 10xxxxxx
www = uuuu - 1
UTF-16: 110110ww wwzzzzyy 110111yy yyxxxxxx
octal: 011 011 0ww 0ww zzz zyy 011 011 1yy 0yy xxx xxx

```

```

2367 \def\HyPsd@UTFviii@four#1#2{%
2368 \expandafter\HyPsd@@UTFviii@four\number
2369 \numexpr-1+('#1-240)*4+\dimexpr.0625\dimexpr'#2sp-128sp%
2370 \expandafter|\number
2371 \numexpr'#2-16*\dimexpr.0625\dimexpr'#2sp| %
2372 }%
2373 \def\HyPsd@@UTFviii@four#1|#2|#3{%
2374 \933\number\dimexpr.25\dimexpr#1sp\relax\relax
2375 \csname\number\numexpr#1-4*\dimexpr.25\dimexpr#1sp\endcsname
2376 \ifodd#2 %
2377 \number\numexpr(#2-1)/2\relax
2378 \else
2379 \number\numexpr#2/2\relax
2380 \fi
2381 \number\numexpr\ifodd#2 4+\fi
2382 \dimexpr.0625\dimexpr'#3sp-128sp\relax\relax\relax
2383 \933%
2384 \expandafter\HyPsd@@@UTFviii@four\number
2385 \numexpr'#3-16*\dimexpr.0625\dimexpr'#3sp| %
2386 }%
2387 \def\HyPsd@@@UTFviii@four#1|#2{%
2388 \number\numexpr4+\dimexpr.25\dimexpr#1sp\relax\relax\relax
2389 \csname\number\numexpr#1-4*\dimexpr.25\dimexpr#1sp\endcsname
2390 \number\dimexpr.125\dimexpr'#2sp-128sp\relax\relax
2391 \number\numexpr'#2-8*\dimexpr.125\dimexpr'#2sp\relax\relax\relax
2392 }%

```

Input encoding utf8x of package ucs uses macro \unichar. Values greater than "FFFF are not supported.

```

2393 \def\HyPsd@unichar#1{%
2394 \ifHy@unicode
2395 \ifnum#1>"10FFFF %
2396 \HyPsd@UnicodeReplacementCharacter % illegal
2397 \else
2398 \ifnum#1>"FFFF %

```

High-surrogate code point. ("D800 = 55296, \p@ = 1pt = 65536sp)

```
2399      \expandafter\HyPsd@unichar\expandafter{%
2400      \number\numexpr 55296+%
2401      \dimexpr.0009765625\dimexpr\number#1sp-\p@
2402      \relax\relax\relax
2403      }%
```

Low-surrogate code point. ("DC00 = 56320, "DC00 - 65536 = -9216)

```
2404      \expandafter\HyPsd@unichar\expandafter{%
2405      \number\numexpr#1-9216%
2406      -1024*\dimexpr.0009765625\dimexpr\number#1sp-\p@
2407      \relax\relax\relax
2408      }%
2409      \else
2410      \ifnum#1>"7FF %
2411      \9%
2412      \expandafter\HyPsd@unichar@first@byte\expandafter{%
2413      \number
2414      \dimexpr.00390625\dimexpr\number#1sp\relax\relax
2415      }%
2416      \else
2417      \8%
2418      \number\dimexpr.00390625\dimexpr\number#1sp\relax\relax
2419      \fi
2420      \expandafter\HyPsd@unichar@second@byte\expandafter{%
2421      \number
2422      \numexpr#1-256*\number
2423      \dimexpr.00390625\dimexpr\number#1sp\relax\relax\relax
2424      }%
2425      \fi
2426      \fi
2427      \else
2428      .% unsupported (Unicode -> PDF Doc Encoding)
2429      \fi
2430      }%
2431      \def\HyPsd@UnicodeReplacementCharacter{\9377\375}%
2432      \def\HyPsd@unichar@first@byte#1{%
2433      \number\dimexpr.015625\dimexpr#1sp\relax\relax
2434      \expandafter\HyPsd@unichar@octtwo\expandafter{%
2435      \number
2436      \numexpr#1-64*\number\dimexpr.015625\dimexpr#1sp%
2437      \relax\relax\relax
2438      }%
2439      }%
2440      \def\HyPsd@unichar@second@byte#1{%
2441      \csname\number\dimexpr.015625\dimexpr#1sp\relax\relax\endcsname
2442      \expandafter\HyPsd@unichar@octtwo\expandafter{%
2443      \number
2444      \numexpr#1-64*\number\dimexpr.015625\dimexpr#1sp%
2445      \relax\relax\relax
2446      }%
2447      }%
2448      \def\HyPsd@unichar@octtwo#1{%
2449      \number\dimexpr.125\dimexpr#1sp\relax\relax
2450      \number\numexpr#1-8*\number\dimexpr.125\dimexpr#1sp%
2451      \relax\relax\relax
2452      }%
```

2453 \fi

\HyPsd@utf@viii@undeferr \utf@viii@undeferr comes from file utf8x.def from package ucs.

```
2454 \def\HyPsd@utf@viii@undeferr#1#2#3#4#5#6{%
2455   \ifx\@gobble#1%
2456   \else
2457     [Please insert \textbackslash PrerenderUnicode%
2458     \textbraceleft#1\textbraceright\space
2459     into preamble]%
2460   \fi
2461 }%
```

6.6.10 Support for die faces (ifsym et. al.)

\HyPsd@DieFace Die faces are provided by

Package	Macro
ifsym	\Cube
epsdice	\epsdice
hhcount	\fcdice

\Cube and \epsdice restrict the range to the numbers one to six. \fcdice generates for larger numbers several dice faces with the sum matching the number. The implementation for the PDF strings follows \fcdice.

```
2462 \def\HyPsd@DieFace#1{%
2463   \ifHy@unicode
2464     \ifnum#1<1 %
2465       \HyPsd@UnicodeReplacementCharacter
2466     \else
2467       \ifnum#1>6 %
2468         \9046\205%
2469         \expandafter\expandafter\expandafter
2470         \HyPsd@DieFaceLarge\intcalcSub{#1}{6}!%
2471       \else
2472         \9046\20\intcalcDec{#1}%
2473       \fi
2474     \fi
2475   \else
2476     .% Die faces are not part of PDFDocEncoding
2477   \fi
2478 }
```

\HyPsd@DieFaceLarge

```
2479 \def\HyPsd@DieFaceLarge#1!{%
2480   \ifnum#1>6 %
2481     \expandafter\ltx@firstoftwo
2482   \else
2483     \expandafter\ltx@secondoftwo
2484   \fi
2485   {%
2486     \9046\205%
2487     \expandafter\expandafter\expandafter
2488     \HyPsd@DieFaceLarge\IntCalcSub#1!6!!%
2489   }{%
2490     \9046\20\IntCalcDec#1!%
2491   }%
2492 }
```

6.6.11 Support for moon phases of package china2e

```

2493 \def\HyPsd@MoonPha#1{%
2494   \ifcase\intcalcNum{#1} %
2495     \HyPsd@UnicodeReplacementCharacter
2496   \or % 1
2497   % U+1F31A NEW MOON WITH FACE; \MoonPha{1} (china2e)
2498   \9330\074\9337\032%
2499   \or % 2
2500   \HyPsd@UnicodeReplacementCharacter
2501   \or % 3
2502   % U+1F31D FULL MOON WITH FACE; \MoonPha{3} (china2e)
2503   \9330\074\9337\035%
2504   \or % 4
2505   % U+1F31C LAST QUARTER MOON WITH FACE; \MoonPha{4} (china2e)
2506   \9330\074\9337\034%
2507   \else
2508     \HyPsd@UnicodeReplacementCharacter
2509   \fi
2510 }
2511 %* \HyPsd@MoonPha -> \MoonPha

```

6.6.12 Support for package pifont

\HyPsd@ding

```

2512 \def\HyPsd@ding#1{%
2513   \ifHy@unicode
2514     \ifnum#1<32 %
2515       \HyPsd@UnicodeReplacementCharacter
2516     \else
2517       \ifnum#1>254 %
2518         \HyPsd@UnicodeReplacementCharacter
2519       \else
2520         \ifnum#1<127 %
2521           \expandafter\expandafter\expandafter
2522           \HyPsd@@@ding\intcalcNum{#1}!%
2523         \else
2524           \ifnum#1>160 %
2525             \expandafter\expandafter\expandafter
2526             \HyPsd@@@ding\intcalcNum{#1}!%
2527           \else
2528             \HyPsd@UnicodeReplacementCharacter
2529           \fi
2530         \fi
2531       \fi
2532     \fi
2533   \else
2534     .% Dingbats are not part of PDFDocEncoding
2535   \fi
2536 }

```

\HyPsd@@@ding

```

2537 \def\HyPsd@@@ding#1!{%
2538   \ltx@ifundefined{HyPsd@ding@#1}{%
2539     \ifnum#1<127 %
2540       \9047%
2541       \HyPsd@DecimalToOctalSecond{\IntCalcSub#1!32!}%
2542     \else

```

```

2543 \ifnum#1<168 %
2544 \9047\14\IntCalcSub#1!160!%
2545 \else
2546 \ifnum#1>181 %
2547 \9047\HyPsd@DecimalToOctalSecond{\IntCalcSub#1!64!}%
2548 \else
2549 % 172..181 -> U+2460..U+2469
2550 \9044\HyPsd@DecimalToOctalSecond{\IntCalcSub#1!76!}%
2551 \fi
2552 \fi
2553 \fi
2554 }{%
2555 \csname HyPsd@ding@#1\endcsname
2556 }%
2557 }

2558 \@namedef{HyPsd@ding@32}{\space}
2559 % U+260E BLACK TELEPHONE
2560 \@namedef{HyPsd@ding@37}{\9046\016}% U+260E
2561 % U+261B BLACK RIGHT POINTING INDEX
2562 \@namedef{HyPsd@ding@42}{\9046\033}% U+261B
2563 % U+261E WHITE RIGHT POINTING INDEX
2564 \@namedef{HyPsd@ding@43}{\9046\036}% U+261E
2565 % U+2605 BLACK STAR
2566 \@namedef{HyPsd@ding@72}{\9046\005}% U+2605
2567 % U+25CF BLACK CIRCLE
2568 \@namedef{HyPsd@ding@108}{\9045\317}% U+25CF
2569 % U+25A0 BLACK SQUARE
2570 \@namedef{HyPsd@ding@110}{\9045\240}% U+25A0
2571 % U+25B2 BLACK UP-POINTING TRIANGLE
2572 \@namedef{HyPsd@ding@115}{\9045\262}% U+25B2
2573 % U+25BC BLACK DOWN-POINTING TRIANGLE
2574 \@namedef{HyPsd@ding@116}{\9045\274}% U+25BC
2575 % U+25C6 BLACK DIAMOND
2576 \@namedef{HyPsd@ding@117}{\9045\306}% U+25C6
2577 % U+25D7 RIGHT HALF BLACK CIRCLE
2578 \@namedef{HyPsd@ding@119}{\9045\327}% U+25D7
2579 \@namedef{HyPsd@ding@168}{\textclubsuitblack}%
2580 \@namedef{HyPsd@ding@169}{\textdiamondsuitblack}%
2581 \@namedef{HyPsd@ding@170}{\textheartsuitblack}%
2582 \@namedef{HyPsd@ding@171}{\textspadesuitblack}%
2583 \@namedef{HyPsd@ding@213}{\textrightarrow}%
2584 \@namedef{HyPsd@ding@214}{\textleftarrow}%
2585 \@namedef{HyPsd@ding@215}{\textupdownarrow}%
2586 \@namedef{HyPsd@ding@240}{\HyPsd@UnicodeReplacementCharacter}

```

7 Support of other packages

7.1 Class memoir

```

2587 \@ifclassloaded{memoir}{%
2588 \Hy@AtEndOfPackage{\RequirePackage{memhfixc}}%
2589 }{}

```

7.2 Package subfigure

Added fix for version 2.1. Here \sub@label is defined.

```

2590 \@ifpackageloaded{subfigure}{%
2591   \ltx@ifundefined{sub@label}{%
2592     \Hy@hypertexnamesfalse
2593   }{%
2594     \renewcommand*{\sub@label}[1]{%
2595       \@bsphack
2596       \subfig@oldlabel{#1}%
2597       \if@filesw
2598         \begingroup
2599           \edef\@currentlabstr{%
2600             \expandafter\strip@prefix\meaning\@currentlabelname
2601           }%
2602           \protected@write\@auxout{}{%
2603             \string\newlabel{sub@#1}{%
2604               {\@nameuse{\@thesub\@captive}}%
2605               {\thepage}%
2606               {%
2607                 \expandafter\strip@period\@currentlabstr
2608                 \relax.\relax\@@@%
2609               }%
2610               {\@currentHref}%
2611               {}%
2612             }%
2613           }%
2614         \endgroup
2615       \fi
2616       \@esphack
2617     }%
2618     \@ifpackagelater{subfigure}{2002/03/26}{%
2619       \providecommand*\@toclevel@subfigure{1}%
2620       \providecommand*\@toclevel@subtable{1}%
2621     }%
2622   }%
2623 }{}

```

7.3 Package xr and xr-hyper

The beta version of xr that supports `\XR@addURL` is called **xr-hyper**. Therefore we test for the macro itself and not for the package name:

```

2624 \ltx@ifundefined{XR@addURL}{%
2625 }{}

```

If reading external aux files check whether they have a non zero fourth field in `\newlabel` and if so, add the URL as the fifth field.

```

2626 \def\XR@addURL#1{\XR@@dURL#1{}{}{}{}\\}%
2627 \def\XR@@dURL#1#2#3#4#5\\{%
2628   {#1}{#2}%
2629   \if!#4!%
2630     \else
2631       {#3}{#4}{\XR@URL}%
2632     \fi
2633   }%
2634 }

2635 \def\Hy@true{true}
2636 \def\Hy@false{false}

```

Providing dummy definitions.


```

2637 \let\literalps@out\@gobble
2638 \newcommand\pdfbookmark[3][]{\{}
2639 \def\Acrobatmenu#1#2{\leavevmode#2}
2640 \def\Hy@writebookmark#1#2#3#4#5{\%

```

8 Help macros for links

Anchors get created on the baseline of where they occur. If an XYZ PDF view is set, this means that the link places the top of the screen *on the baseline* of the target. If this is an equation, for instance, it means that you cannot see anything. Some links, of course, are created at the start of environments, and so it works. To allow for this, anchors are raised, where possible, by some small amount. This defaults to `\baselineskip`, but users can set it to something else in two ways (thanks to Heiko Oberdiek for suggesting this):

1. Redefine `\HyperRaiseLinkDefault` to be eg the height of a `\strut`
2. Redefine `\HyperRaiseLinkHook` to do something complicated; it must give a value to `\HyperRaiseLinkLength`, which is what actually gets used

```

2641 \let\HyperRaiseLinkHook\@empty
2642 \def\HyperRaiseLinkDefault{\baselineskip}

```

`\HyperRaiseLinkHook` allows the user to reassign `\HyperRaiseLinkLength`.

```

2643 \newcount\Hy@SavedSpaceFactor
2644 \def\Hy@SaveSpaceFactor{\%
2645   \global\Hy@SavedSpaceFactor=\ifhmode\spacefactor\else\z@\fi
2646 }
2647 \def\Hy@RestoreSpaceFactor{\%
2648   \relax
2649   \ifhmode
2650     \ifnum\Hy@SavedSpaceFactor>\z@
2651       \spacefactor=\Hy@SavedSpaceFactor
2652     \fi
2653   \fi
2654 }
2655 \def\Hy@SaveSavedSpaceFactor{\%
2656   \edef\Hy@RestoreSavedSpaceFactor{\%
2657     \global\Hy@SavedSpaceFactor=\the\Hy@SavedSpaceFactor\relax
2658   }%
2659 }
2660 \def\Hy@raisedlink#1{\%
2661   \ifvmode
2662     #1%
2663   \else
2664     \Hy@SaveSpaceFactor
2665     \penalty\@M
2666     \smash{\%
2667       \begingroup
2668         \let\HyperRaiseLinkLength\@tempdima
2669         \setlength\HyperRaiseLinkLength\HyperRaiseLinkDefault
2670         \HyperRaiseLinkHook
2671       \expandafter\endgroup
2672       \expandafter\raise\the\HyperRaiseLinkLength\hbox{\%
2673         \Hy@RestoreSpaceFactor
2674         #1%
2675       \Hy@SaveSpaceFactor

```

```

2676 }%
2677 }%
2678 \Hy@RestoreSpaceFactor
2679 \fi
2680 }

```

\Hy@SaveLastskip Inserting a \special command to set a destination destroys the \lastskip value.
\Hy@RestoreLastskip

```

2681 \def\Hy@SaveLastskip{%
2682 \let\Hy@RestoreLastskip\relax
2683 \ifvmode
2684 \ifdim\lastskip=\z@
2685 \let\Hy@RestoreLastskip\nobreak
2686 \else
2687 \begingroup
2688 \skip@=-\lastskip
2689 \edef\x{%
2690 \endgroup
2691 \def\noexpand\Hy@RestoreLastskip{%
2692 \noexpand\ifvmode
2693 \noexpand\nobreak
2694 \vskip\the\skip@
2695 \vskip\the\lastskip\relax
2696 \noexpand\fi
2697 }%
2698 }%
2699 \x
2700 \fi
2701 \else
2702 \ifhmode
2703 \ifdim\lastskip=\z@
2704 \let\Hy@RestoreLastskip\nobreak
2705 \else
2706 \begingroup
2707 \skip@=-\lastskip
2708 \edef\x{%
2709 \endgroup
2710 \def\noexpand\Hy@RestoreLastskip{%
2711 \noexpand\ifhmode
2712 \noexpand\nobreak
2713 \hskip\the\skip@
2714 \hskip\the\lastskip\relax
2715 \noexpand\fi
2716 }%
2717 }%
2718 \x
2719 \fi
2720 \fi
2721 \fi
2722 }%

```

9 Options

```

2723 \SetupKeyvalOptions{%
2724 family=Hyp,%
2725 prefix=HyOpt%
2726 }

```

9.1 Help macros

`\IfHyperBooleanExists`

```
2727 \def\IfHyperBooleanExists#1{%
2728   \ltx@ifundefined{Hy@#1false}\ltx@secondoftwo{%
2729     \ltx@ifundefined{KV@Hyp@#1@default}\ltx@secondoftwo\ltx@firstoftwo
2730   }%
2731 }

2732 \@namedef{KV@Hyp@stoppeearly@default}{}
```

`\IfHyperBoolean`

```
2733 \def\IfHyperBoolean#1{%
2734   \IfHyperBooleanExists{#1}{%
2735     \csname ifHy@#1\endcsname
2736     \expandafter\ltx@firstoftwo
2737   \else
2738     \expandafter\ltx@secondoftwo
2739   \fi
2740 } \ltx@secondoftwo
2741 }
```

`\Hy@boolkey`

```
2742 \def\Hy@boolkey#1#2{%
2743   \edef\Hy@tempa{#2}%
2744   \lowercase\expandafter{%
2745     \expandafter\def\expandafter\Hy@tempa\expandafter{\Hy@tempa}%
2746   }%
2747   \ifx\Hy@tempa\@empty
2748     \let\Hy@tempa\Hy@true
2749   \fi
2750   \ifx\Hy@tempa\Hy@true
2751   \else
2752     \ifx\Hy@tempa\Hy@false
2753     \else
2754       \let\Hy@tempa\relax
2755     \fi
2756   \fi
2757   \ifx\Hy@tempa\relax
2758     \Hy@WarnOptionValue{#2}{#1}{‘true’ or ‘false’}%
2759   \else
2760     \Hy@Info{Option ‘#1’ set ‘\Hy@tempa’}%
2761     \csname Hy@#1\Hy@tempa\endcsname
2762   \fi
2763 }
```

`\Hy@WarnOptionValue`

```
2764 \def\Hy@WarnOptionValue#1#2#3{%
2765   \Hy@Warning{%
2766     Unexpected value ‘#1’\MessageBreak
2767     of option ‘#2’ instead of\MessageBreak
2768     #3%
2769   }%
2770 }
```

`\Hy@DisableOption`

```
2771 \def\Hy@DisableOption#1{%
```

```

2772 \ltx@ifundefined{KV@Hyp@#1@default}{%
2773   \define@key{Hyp}{#1}%
2774 }{%
2775   \define@key{Hyp}{#1}[]%
2776 }%
2777 {\Hy@WarnOptionDisabled{#1}}%
2778 }

```

`\Hy@WarnOptionDisabled`

```

2779 \def\Hy@WarnOptionDisabled#1{%
2780   \Hy@Warning{%
2781     Option ‘#1’ has already been used,\MessageBreak
2782     setting the option has no effect%
2783   }%
2784 }

```

`\Hy@CheckOptionValue` Some options take a string value out of a limited set of values. Macro `\Hy@CheckOptionValue` checks whether the given value `#1` for option `#2` is a member of the value list `#3`.

```

2785 \def\Hy@CheckOptionValue#1#2#3{%
2786   \begingroup
2787   \edef\x{#1}%
2788   \@onelevel@sanitize\x
2789   \let\y=y%
2790   \def\do##1##2{%
2791     \def\z{##1}%
2792     \@onelevel@sanitize\z
2793     \ifx\x\z
2794       \let\y=n%
2795       \let\do\@gobbletwo
2796     \fi
2797   }%
2798   #3%
2799   \ifx\y y%
2800     \def\do##1##2{%
2801       * ‘##1’%
2802       \ifx\\##2\\\else\space(##2)\fi
2803       \MessageBreak
2804     }%
2805     \Hy@Warning{%
2806       Values of option ‘#2’:\MessageBreak
2807       #3%
2808       * An empty value disables the option.\MessageBreak
2809       Unknown value ‘\x’%
2810     }%
2811     \fi
2812   \endgroup
2813 }

```

`\Hy@DefNameKey` **#1:** option name
#2: `\do` list with known values, first argument of `\do` is value, second argument is a comment.

```

2814 \def\Hy@DefNameKey#1{%
2815   \expandafter\Hy@@DefNameKey\csname @#1\endcsname{#1}%
2816 }

```

```

\Hy@@DefNameKey #1: macro for value storage
#2: option name
#3: \do list with known values.
2817 \def\Hy@@DefNameKey#1#2#3{%
2818 \define@key{Hyp}{#2}{%
2819 \edef#1{##1}%
2820 \ifx#1\@empty
2821 \else
2822 \Hy@CheckOptionValue{##1}{#2}{#3}%
2823 \fi
2824 }%
2825 \let#1\@empty
2826 }

```

```

\Hy@UseNameKey
2827 \def\Hy@UseNameKey#1#2{%
2828 \ifx#2\@empty
2829 \else
2830 /#1/#2%
2831 \fi
2832 }

```

9.2 Defining the options

```

2833 \define@key{Hyp}{implicit}[true]{%
2834 \Hy@boolkey{implicit}{#1}%
2835 }
2836 \define@key{Hyp}{draft}[true]{%
2837 \Hy@boolkey{draft}{#1}%
2838 }
2839 \define@key{Hyp}{final}[true]{%
2840 \Hy@boolkey{final}{#1}%
2841 }
2842 \let\KV@Hyp@nolinks\KV@Hyp@draft
2843 \def\Hy@ObsoletePaperOption#1{%
2844 \Hy@WarningNoLine{%
2845 Option ‘#1’ is no longer used%
2846 }%
2847 \define@key{Hyp}{#1}[true]{}%
2848 }
2849 \def\Hy@temp#1{%
2850 \define@key{Hyp}{#1}[true]{%
2851 \Hy@ObsoletePaperOption{#1}%
2852 }%
2853 }
2854 \Hy@temp{a4paper}
2855 \Hy@temp{a5paper}
2856 \Hy@temp{b5paper}
2857 \Hy@temp{letterpaper}
2858 \Hy@temp{legalpaper}
2859 \Hy@temp{executivepaper}
2860 \define@key{Hyp}{setpagesize}[true]{%
2861 \Hy@boolkey{setpagesize}{#1}%
2862 }
2863 \define@key{Hyp}{debug}[true]{%
2864 \Hy@boolkey{debug}{#1}%

```

```

2865 }
2866 \define@key{Hyp}{linktocpage}[true]{%
2867   \Hy@boolkey{linktocpage}{#1}%
2868   \ifHy@linktocpage
2869     \let\Hy@linktoc\Hy@linktoc@page
2870   \else
2871     \let\Hy@linktoc\Hy@linktoc@section
2872   \fi
2873 }
2874 \chardef\Hy@linktoc@none=0 %
2875 \chardef\Hy@linktoc@section=1 %
2876 \chardef\Hy@linktoc@page=2 %
2877 \chardef\Hy@linktoc@all=3 %
2878 \ifHy@linktocpage
2879   \let\Hy@linktoc\Hy@linktoc@page
2880 \else
2881   \let\Hy@linktoc\Hy@linktoc@section
2882 \fi
2883 \define@key{Hyp}{linktoc}{%
2884   \@ifundefined{Hy@linktoc@#1}{%
2885     \Hy@Warning{%
2886       Unexpected value '#1' of\MessageBreak
2887       option 'linktoc' instead of 'none',\MessageBreak
2888       'section', 'page' or 'all'%
2889     }%
2890   }{%
2891     \expandafter\let\expandafter\Hy@linktoc
2892       \csname Hy@linktoc@#1\endcsname
2893   }%
2894 }
2895 \define@key{Hyp}{extension}{\def\XR@ext{#1}}
2896 \let\XR@ext\relax
2897 \define@key{Hyp}{verbose}[true]{%
2898   \Hy@boolkey{verbose}{#1}%
2899 }
2900 \define@key{Hyp}{typexml}[true]{%
2901   \Hy@boolkey{typexml}{#1}%
2902 }

```

If we are going to PDF via HyperTeX \special commands, the dvips (-z option) processor does not know the *height* of a link, as it works solely on the position of the closing \special. If we use this option, the \special is raised up by the right amount, to fool the dvi processor.

```

2903 \define@key{Hyp}{raiselinks}[true]{%
2904   \Hy@boolkey{raiselinks}{#1}%
2905 }

```

Most PDF-creating drivers do not allow links to be broken

```

2906 \def\Hy@setbreaklinks#1{%
2907   \csname breaklinks#1\endcsname
2908 }
2909 \def\Hy@breaklinks@unsupported{%
2910   \ifx\Hy@setbreaklinks\@gobble
2911     \ifHy@breaklinks
2912       \Hy@WarningNoLine{%
2913         You have enabled option 'breaklinks'\MessageBreak
2914         But driver '\Hy@driver.def' does not support this.\MessageBreak
2915         Expect trouble with the link areas of broken links%

```

```

2916     }%
2917   \fi
2918 \fi
2919 }

2920 \define@key{Hyp}{breaklinks}[true]{%
2921   \Hy@boolkey{breaklinks}{#1}%
2922   \let\Hy@setbreaklinks\@gobble
2923 }

2924 \define@key{Hyp}{localanchorname}[true]{%
2925   \Hy@boolkey{localanchorname}{#1}%
2926 }

```

Determines whether an automatic anchor is put on each page

```

2927 \define@key{Hyp}{pageanchor}[true]{%
2928   \Hy@boolkey{pageanchor}{#1}%
2929 }

```

Are the page links done as plain arabic numbers, or do they follow the formatting of the package? The latter loses if you put in typesetting like `\textbf` or the like.

```

2930 \define@key{Hyp}{plainpages}[true]{%
2931   \Hy@boolkey{plainpages}{#1}%
2932 }

```

Are the names for anchors made as per the HyperTeX system, or do they simply use what \LaTeX provides?

```

2933 \define@key{Hyp}{naturalnames}[true]{%
2934   \Hy@boolkey{naturalnames}{#1}%
2935 }

```

Completely ignore the names as per the HyperTeX system, and use unique counters.

```

2936 \define@key{Hyp}{hypertexnames}[true]{%
2937   \Hy@boolkey{hypertexnames}{#1}%
2938 }

```

Currently, dvips doesn't allow anchors nested within targets, so this option tries to stop that happening. Other processors may be able to cope.

```

2939 \define@key{Hyp}{nesting}[true]{%
2940   \Hy@boolkey{nesting}{#1}%
2941 }

```

```

2942 \define@key{Hyp}{destlabel}[true]{%
2943   \Hy@boolkey{destlabel}{#1}%
2944 }

```

```

2945 \define@key{Hyp}{unicode}[true]{%
2946   \Hy@boolkey{unicode}{#1}%
2947   \ifHy@unicode
2948     \def\HyPsd@pdfencoding{unicode}%
2949     \HyPsd@LoadUnicode
2950   \else
2951     \def\HyPsd@pdfencoding{pdfdoc}%
2952   \fi
2953 }

```

```

2954 \Hy@AtBeginDocument{%
2955   \ifx\HyPsd@LoadUnicode\relax
2956   \else
2957     \def\HyPsd@LoadUnicode{%
2958       \Hy@Error{%
2959         Unicode support for bookmarks is not available.\MessageBreak
2960         Activate unicode support by using one of the options\MessageBreak

```

```

2961     'unicode', 'pdfencoding=unicode', 'pdfencoding=auto'\MessageBreak
2962     in the preamble%
2963 } \@ehc
2964 \global\let\HyPsd@LoadUnicode\relax
2965 \global\Hy@unicodedefalse
2966 \global\let\Hy@unicodetrue\Hy@unicodedefalse
2967 }%
2968 \fi
2969 }

2970 \define@key{Hyp}{pdfencoding}{%
2971 \edef\HyPsd@temp{#1}%
2972 \ifx\HyPsd@temp\HyPsd@pdfencoding@pdfdoc
2973 \let\HyPsd@pdfencoding\HyPsd@temp
2974 \Hy@unicodedefalse
2975 \else
2976 \ifcase\ifx\HyPsd@temp\HyPsd@pdfencoding@unicode
2977 \z@
2978 \else
2979 \ifx\HyPsd@temp\HyPsd@pdfencoding@auto
2980 \z@
2981 \else
2982 \@ne
2983 \fi
2984 \fi
2985 \let\HyPsd@pdfencoding\HyPsd@temp
2986 \hypersetup{unicode}%
2987 \ifHy@unicode
2988 \def\HyPsd@pdfencoding{#1}%
2989 \ifx\HyPsd@pdfencoding\HyPsd@pdfencoding@auto
2990 \HyPsd@LoadStringEncoding
2991 \fi
2992 \else
2993 \Hy@Warning{Cannot switch to unicode bookmarks}%
2994 \let\HyPsd@pdfencoding\HyPsd@pdfencoding@pdfdoc
2995 \fi
2996 \else
2997 \@onelevel@sanitize\HyPsd@temp
2998 \Hy@Warning{%
2999 Values of option 'pdfencoding':\MessageBreak
3000 'pdfdoc', 'unicode', 'auto'.\MessageBreak
3001 Ignoring unknown value '\HyPsd@temp'%
3002 }%
3003 \fi
3004 \fi
3005 }
3006 \def\HyPsd@pdfencoding@auto{auto}
3007 \def\HyPsd@pdfencoding@pdfdoc{pdfdoc}
3008 \def\HyPsd@pdfencoding@unicode{unicode}
3009 \let\HyPsd@pdfencoding\Hy@pdfencoding@pdfdoc
3010 \def\HyPsd@LoadStringEncoding{%
3011 \RequirePackage{stringenc}[2009/12/15]%
3012 \let\HyPsd@LoadStringEncoding\relax
3013 }
3014 \Hy@AtBeginDocument{%
3015 \@ifpackageloaded{stringenc}{%
3016 \let\HyPsd@LoadStringEncoding\relax
3017 }{%

```



```

3018 \def\HyPsd@LoadStringEnc{%
3019 \Hy@WarningNoLine{%
3020 Missing package 'stringenc'. Use 'pdfencoding=auto'\MessageBreak
3021 in the preamble or load the package there%
3022 }%
3023 }%
3024 }%
3025 }

3026 \define@key{Hyp}{psdextra}[true]{%
3027 \Hy@boolkey{psdextra}{#1}%
3028 \HyPsd@LoadExtra
3029 }

3030 \def\hypersetup{\kvsetkeys{Hyp}}

3031 \newif\ifHy@setpdfversion
3032 \define@key{Hyp}{pdfversion}{%
3033 \ifundefined{Hy@pdfversion@#1}{%
3034 \PackageWarning{hyperref}{%
3035 Unsupported PDF version '#1'.\MessageBreak
3036 Valid values: 1.2 until 1.9%
3037 }%
3038 }{%
3039 \Hy@setpdfversiontrue
3040 \edef\Hy@pdfversion{\@nameuse{Hy@pdfversion@#1}}%
3041 }%
3042 }
3043 \@namedef{Hy@pdfversion@1.2}{2}%
3044 \@namedef{Hy@pdfversion@1.3}{3}%
3045 \@namedef{Hy@pdfversion@1.4}{4}%
3046 \@namedef{Hy@pdfversion@1.5}{5}%
3047 \@namedef{Hy@pdfversion@1.6}{6}%
3048 \@namedef{Hy@pdfversion@1.7}{7}%
3049 \@namedef{Hy@pdfversion@1.8}{8}%
3050 \@namedef{Hy@pdfversion@1.9}{9}%
3051 \def\Hy@pdfversion{2}

```

10 Options for different drivers

```

3052 \newif\ifHy@DviMode
3053 \let\Hy@DviErrMsg\ltx@empty
3054 \ifpdf
3055 \def\Hy@DviErrMsg{pdfTeX or LuaTeX is running in PDF mode}%
3056 \else
3057 \ifxetex
3058 \def\Hy@DviErrMsg{XeTeX is running}%
3059 \else
3060 \ifvtex
3061 \ifvtexdvi
3062 \Hy@DviModetrue
3063 \else
3064 \def\Hy@DviErrMsg{VTeX is running, but not in DVI mode}%
3065 \fi
3066 \else
3067 \Hy@DviModetrue
3068 \fi
3069 \fi
3070 \fi

```

```

3071 \def\HyOpt@CheckDvi#1{%
3072   \ifHy@DviMode
3073     \expandafter\ltx@firstofone
3074   \else
3075     \Hy@Error{%
3076       Wrong DVI mode driver option '#1',\MessageBreak
3077       because \Hy@DviErrMsg
3078     }\@ehc
3079   \expandafter\ltx@gobble
3080 \fi
3081 }

3082 \DeclareVoidOption{tex4ht}{%
3083   \Hy@texhttrue
3084   \kvsetkeys{Hyp}{colorlinks=true}%
3085   \def\BeforeTeXIVht{\RequirePackage{color}}}%
3086   \def\Hy@driver{htex4ht}%
3087   \def\MaybeStopEarly{%
3088     \Hy@Message{Stopped early}%
3089   \Hy@AtBeginDocument{%
3090     \PDF@FinishDoc
3091     \gdef\PDF@FinishDoc{}}%
3092   }%
3093   \endinput
3094 }%
3095 }

3096 \DeclareVoidOption{pdftex}{%
3097   \ifpdf
3098     \def\Hy@driver{hpdftex}%
3099   \else
3100     \Hy@Error{%
3101       Wrong driver option 'pdftex',\MessageBreak
3102       because pdfTeX in PDF mode is not detected%
3103     }\@ehc
3104   \fi
3105 }

3106 \DeclareVoidOption{nativepdf}{%
3107   \HyOpt@CheckDvi{nativepdf}{%
3108     \def\Hy@driver{hdvips}%
3109   }%
3110 }

3111 \DeclareVoidOption{dvipdfm}{%
3112   \HyOpt@CheckDvi{dvipdfm}{%
3113     \def\Hy@driver{hdvipdfm}%
3114   }%
3115 }

3116 \DeclareVoidOption{dvipdfmx}{%
3117   \HyOpt@CheckDvi{dvipdfmx}{%
3118     \def\Hy@driver{hdvipdfm}%
3119   }%
3120 }

3121 \define@key{Hyp}{dvipdfmx-outline-open}[true]{%
3122   \expandafter\ifx\csname if#1\expandafter\endcsname
3123     \csname iftrue\endcsname
3124   \chardef\SpecialDvipdfmxOutlineOpen\@ne
3125 \else
3126   \chardef\SpecialDvipdfmxOutlineOpen\z@
3127 \fi

```

```

3128 }
3129 \DeclareVoidOption{xetex}{%
3130   \ifxetex
3131     \def\Hy@driver{hxtex}%
3132   \else
3133     \Hy@Error{%
3134       Wrong driver option 'xetex',\MessageBreak
3135       because XeTeX is not detected%
3136     }\@ehc
3137   \fi
3138 }
3139 \DeclareVoidOption{pdfmark}{%
3140   \HyOpt@CheckDvi{pdfmark}{%
3141     \def\Hy@driver{hdvips}%
3142   }%
3143 }
3144 \DeclareVoidOption{dvips}{%
3145   \HyOpt@CheckDvi{dvips}{%
3146     \def\Hy@driver{hdvips}%
3147   }%
3148 }
3149 \DeclareVoidOption{hypertex}{%
3150   \HyOpt@CheckDvi{hypertex}{%
3151     \def\Hy@driver{hypertex}%
3152   }%
3153 }
3154 \let\Hy@MaybeStopNow\relax
3155 \DeclareVoidOption{vtex}{%
3156   \ifvtex
3157     \ifnum 0\ifnum\OpMode<1 1\fi \ifnum\OpMode>3 1\fi =0 %
3158     \def\Hy@driver{hvtex}%
3159   \else
3160     \ifnum\OpMode=10\relax
3161       \def\Hy@driver{hvtexhtm}%
3162       \def\MaybeStopEarly{%
3163         \Hy@Message{Stopped early}%
3164         \Hy@AtBeginDocument{%
3165           \PDF@FinishDoc
3166           \gdef\PDF@FinishDoc{}%
3167         }%
3168       \endinput
3169     }%
3170   \else
3171     \Hy@Error{%
3172       Wrong driver option 'vtex',\MessageBreak
3173       because of wrong OpMode (\the\OpMode)%
3174     }\@ehc
3175   \fi
3176 }
3177 \else
3178   \Hy@Error{%
3179     Wrong driver option 'vtex',\MessageBreak
3180     because VTeX is not running%
3181   }\@ehc
3182 }
3183 }
3184 \DeclareVoidOption{vtexpdfmark}{%

```

```

3185 \ifvtex
3186   \ifnum 0\ifnum\OpMode<1 1\fi \ifnum\OpMode>3 1\fi =0 %
3187   \def\Hy@driver{hvtexmrk}%
3188   \else
3189     \Hy@Error{%
3190       Wrong driver option 'vtexpdfmark',\MessageBreak
3191       because of wrong OpMode (\the\OpMode)%
3192     }\@ehc
3193   \fi
3194 \else
3195   \Hy@Error{%
3196     Wrong driver option 'vtexpdfmark',\MessageBreak
3197     because VTeX is not running%
3198   }\@ehc
3199 \fi
3200 }
3201 \DeclareVoidOption{dviwindo}{}%
3202 \HyOpt@CheckDvi{dviwindo}{}%
3203 \def\Hy@driver{hdviwind}%
3204 \kvsetkeys{Hyp}{colorlinks}%
3205 \PassOptionsToPackage{dviwindo}{color}%
3206 }%
3207 }
3208 \DeclareVoidOption{dvipsone}{}%
3209 \HyOpt@CheckDvi{dvipsone}{}%
3210 \def\Hy@driver{hdvipson}%
3211 }%
3212 }
3213 \DeclareVoidOption{textures}{}%
3214 \HyOpt@CheckDvi{textures}{}%
3215 \def\Hy@driver{htexture}%
3216 }%
3217 }
3218 \DeclareVoidOption{latex2html}{}%
3219 \HyOpt@CheckDvi{latex2html}{}%
3220 \Hy@AtBeginDocument{\@@@latextohtmlX}%
3221 }%
3222 }

```

No more special treatment for ps2pdf. Let it sink or swim.

```

3223 \DeclareVoidOption{ps2pdf}{}%
3224 \HyOpt@CheckDvi{ps2pdf}{}%
3225 \def\Hy@driver{hdvips}%
3226 }%
3227 }
3228 \let\HyOpt@DriverFallback\ltx@empty
3229 \define@key{Hyp}{driverfallback}{}%
3230 \ifHy@DviMode
3231   \def\HyOpt@DriverFallback{#1}%
3232   \Hy@Match\HyOpt@DriverFallback{%
3233     ~(|dvipdfm|dvipdfmx|dvips|dvipsone|dviwindo|hypertex|ps2pdf|
3234     latex2html|tex4ht)$%
3235   }{}{%
3236     \let\HyOpt@DriverFallback\ltx@empty
3237   }%
3238 \fi
3239 }

```

```

3240 \let\HyOpt@CustomDriver\ltx@empty
3241 \define@key{Hyp}{customdriver}{%
3242   \IfFileExists{#1.def}{%
3243     \def\HyOpt@CustomDriver{#1}%
3244   }{%
3245     \Hy@Warning{%
3246       Missing driver file '#1.def',\MessageBreak
3247       ignoring custom driver%
3248     }%
3249   }%
3250 }

```

11 Options to add extra features

Make included figures (assuming they use the standard graphics package) be hypertext links. Off by default. Needs more work.

```

3251 \define@key{Hyp}{hyperfigures}[true]{%
3252   \Hy@boolkey{hyperfigures}{#1}%
3253 }

```

The automatic footnote linking can be disabled by option hyperfootnotes.

```

3254 \define@key{Hyp}{hyperfootnotes}[true]{%
3255   \Hy@boolkey{hyperfootnotes}{#1}%
3256 }

```

Set up back-referencing to be hyper links, by page, slide or section number,

```

3257 \def\back@none{none}
3258 \def\back@section{section}
3259 \def\back@page{page}
3260 \def\back@slide{slide}
3261 \define@key{Hyp}{backref}[section]{%
3262   \lowercase{\def\Hy@tempa{#1}}%
3263   \ifx\Hy@tempa\@empty
3264     \let\Hy@tempa\back@section
3265   \fi
3266   \ifx\Hy@tempa\Hy@false
3267     \let\Hy@tempa\back@none
3268   \fi
3269   \ifx\Hy@tempa\back@slide
3270     \let\Hy@tempa\back@section
3271   \fi
3272   \ifx\Hy@tempa\back@page
3273     \PassOptionsToPackage{hyperpageref}{backref}%
3274     \Hy@backreftrue
3275   \else
3276     \ifx\Hy@tempa\back@section
3277       \PassOptionsToPackage{hyperref}{backref}%
3278       \Hy@backreftrue
3279     \else
3280       \ifx\Hy@tempa\back@none
3281         \Hy@backreffalse
3282       \else
3283         \Hy@WarnOptionValue{#1}{backref}{%
3284           'section', 'slide', 'page', 'none',\MessageBreak
3285           or 'false'}%
3286       \fi
3287     \fi
3288   \fi

```

```

3289 }
3290 \define@key{Hyp}{pagebackref}[true]{%
3291   \edef\Hy@tempa{#1}%
3292   \lowercase\expandafter{%
3293     \expandafter\def\expandafter\Hy@tempa\expandafter{\Hy@tempa}%
3294   }%
3295   \ifx\Hy@tempa\@empty
3296     \let\Hy@tempa\Hy@true
3297   \fi
3298   \ifx\Hy@tempa\Hy@true
3299     \PassOptionsToPackage{hyperpageref}{backref}%
3300     \Hy@backreftrue
3301   \else
3302     \ifx\Hy@tempa\Hy@false
3303       \Hy@backreffalse
3304     \else
3305       \Hy@WarnOptionValue{#1}{pagebackref}{‘true’ or ‘false’}%
3306     \fi
3307   \fi
3308 }

```

Make index entries be links back to the relevant pages. By default this is turned on, but may be stopped.

```

3309 \define@key{Hyp}{hyperindex}[true]{%
3310   \Hy@boolkey{hyperindex}{#1}%
3311 }

```

Configuration of encap char.

```

3312 \define@key{Hyp}{encap}[|]{%
3313   \def\HyInd@EncapChar{#1}%
3314 }

```

12 Language options

The \autoref feature depends on the language.

```

3315 \def\HyLang@afrikaans{%
3316   \def\equationautorefname{Vergelyking}%
3317   \def\footnoteautorefname{Voetnota}%
3318   \def\itemautorefname{Item}%
3319   \def\figureautorefname{Figuur}%
3320   \def\tableautorefname{Tabel}%
3321   \def\partautorefname{Deel}%
3322   \def\appendixautorefname{Bylae}%
3323   \def\chapterautorefname{Hoofstuk}%
3324   \def\sectionautorefname{Afdeling}%
3325   \def\subsectionautorefname{Subafdeling}%
3326   \def\subsubsectionautorefname{Subsubafdeling}%
3327   \def\paragraphautorefname{Paragraaf}%
3328   \def\subparagraphautorefname{Subparagraaf}%
3329   \def\FancyVerbLineautorefname{Lyn}%
3330   \def\theoremautorefname{Teorema}%
3331   \def\pageautorefname{Bladsy}%
3332 }
3333 \def\HyLang@english{%
3334   \def\equationautorefname{Equation}%
3335   \def\footnoteautorefname{footnote}%
3336   \def\itemautorefname{item}%

```

```

3337 \def\figureautorefname{Figure}%
3338 \def\tableautorefname{Table}%
3339 \def\partautorefname{Part}%
3340 \def\appendixautorefname{Appendix}%
3341 \def\chapterautorefname{chapter}%
3342 \def\sectionautorefname{section}%
3343 \def\subsectionautorefname{subsection}%
3344 \def\subsubsectionautorefname{subsubsection}%
3345 \def\paragraphautorefname{paragraph}%
3346 \def\subparagraphautorefname{subparagraph}%
3347 \def\FancyVerbLineautorefname{line}%
3348 \def\theoremautorefname{Theorem}%
3349 \def\pageautorefname{page}%
3350 }
3351 \def\HyLang@french{%
3352 \def\equationautorefname{'Equation}%
3353 \def\footnoteautorefname{note}%
3354 \def\itemautorefname{item}%
3355 \def\figureautorefname{Figure}%
3356 \def\tableautorefname{Tableau}%
3357 \def\partautorefname{Partie}%
3358 \def\appendixautorefname{Appendice}%
3359 \def\chapterautorefname{chapitre}%
3360 \def\sectionautorefname{section}%
3361 \def\subsectionautorefname{sous-section}%
3362 \def\subsubsectionautorefname{sous-sous-section}%
3363 \def\paragraphautorefname{paragraphe}%
3364 \def\subparagraphautorefname{sous-paragraphe}%
3365 \def\FancyVerbLineautorefname{ligne}%
3366 \def\theoremautorefname{Th\'eor\`eme}%
3367 \def\pageautorefname{page}%
3368 }
3369 \def\HyLang@german{%
3370 \def\equationautorefname{Gleichung}%
3371 \def\footnoteautorefname{Fu\ss note}%
3372 \def\itemautorefname{Punkt}%
3373 \def\figureautorefname{Abbildung}%
3374 \def\tableautorefname{Tabelle}%
3375 \def\partautorefname{Teil}%
3376 \def\appendixautorefname{Anhang}%
3377 \def\chapterautorefname{Kapitel}%
3378 \def\sectionautorefname{Abschnitt}%
3379 \def\subsectionautorefname{Unterabschnitt}%
3380 \def\subsubsectionautorefname{Unterunterabschnitt}%
3381 \def\paragraphautorefname{Absatz}%
3382 \def\subparagraphautorefname{Unterabsatz}%
3383 \def\FancyVerbLineautorefname{Zeile}%
3384 \def\theoremautorefname{Theorem}%
3385 \def\pageautorefname{Seite}%
3386 }
3387 \def\HyLang@italian{%
3388 \def\equationautorefname{Equazione}%
3389 \def\footnoteautorefname{nota}%
3390 \def\itemautorefname{punto}%
3391 \def\figureautorefname{Figura}%
3392 \def\tableautorefname{Tabella}%
3393 \def\partautorefname{Parte}%

```

```

3394 \def\appendixautorefname{Appendice}%
3395 \def\chapterautorefname{Capitolo}%
3396 \def\sectionautorefname{sezione}%
3397 \def\subsectionautorefname{sottosezione}%
3398 \def\subsubsectionautorefname{sottosottosezione}%
3399 \def\paragraphautorefname{paragrafo}%
3400 \def\subparagraphautorefname{sottoparagrafo}%
3401 \def\FancyVerbLineautorefname{linea}%
3402 \def\theoremautorefname{Teorema}%
3403 \def\pageautorefname{Pag.\@}%
3404 }
3405 \def\HyLang@magyar{%
3406 \def\equationautorefname{Egyenlet}%
3407 \def\footnoteautorefname{l\'abjegyzet}%
3408 \def\itemautorefname{Elem}%
3409 \def\figureautorefname{'Abra}%
3410 \def\tableautorefname{T\'abl\'azat}%
3411 \def\partautorefname{R\'esz}%
3412 \def\appendixautorefname{F\'uggel\'ek}%
3413 \def\chapterautorefname{fejezet}%
3414 \def\sectionautorefname{szakasz}%
3415 \def\subsectionautorefname{alszakasz}%
3416 \def\subsubsectionautorefname{alalszakasz}%
3417 \def\paragraphautorefname{bekezd\'es}%
3418 \def\subparagraphautorefname{albekezd\'es}%
3419 \def\FancyVerbLineautorefname{sor}%
3420 \def\theoremautorefname{T\'etel}%
3421 \def\pageautorefname{oldal}%
3422 }
3423 \def\HyLang@portuges{%
3424 \def\equationautorefname{Equa\c c\~ao}%
3425 \def\footnoteautorefname{Nota de rodap\'e}%
3426 \def\itemautorefname{Item}%
3427 \def\figureautorefname{Figura}%
3428 \def\tableautorefname{Tabela}%
3429 \def\partautorefname{Parte}%
3430 \def\appendixautorefname{Ap\~endice}%
3431 \def\chapterautorefname{Cap\'itulo}%
3432 \def\sectionautorefname{Se\c c\~ao}%
3433 \def\subsectionautorefname{Subse\c c\~ao}%
3434 \def\subsubsectionautorefname{Subsubse\c c\~ao}%
3435 \def\paragraphautorefname{par\'agrafo}%
3436 \def\subparagraphautorefname{subpar\'agrafo}%
3437 \def\FancyVerbLineautorefname{linha}%
3438 \def\theoremautorefname{Teorema}%
3439 \def\pageautorefname{P\'agina}%
3440 }

```

Next commented section for Russian is provided by Olga Lapko.

Next follow the checked reference names with commented variants and explanations. All they are abbreviated and they won't create a grammatical problems in the *middle* of sentences.

The most weak points in these abbreviations are the `\equationautorefname`, `\theoremautorefname` and the `\FancyVerbLineautorefname`. But those three, and also the `\footnoteautorefname` are not *too* often referenced. Another rather weak point is the `\appendixautorefname`.

```

3441 \def\HyLang@russian{%

```


The abbreviated reference to the equation: it is not for “the good face of the book”, but maybe it will be better to get the company for the `\theoremautorefname`?

```
3442 \def\equationautorefname{\cyr\cyrv\cyrry\cyrr.}%
```

The name of the equation reference has common form for both nominative and accusative but changes in other forms, like “of `\autoref{auto}`” etc. The full name must follow full name of the `\theoremautorefname`.

```
3443 % \def\equationautorefname{%
3444 %   \cyr\cyrv\cyrry\cyrr\cyra\cyrrh\cyre\cyrn\cyri\cyre
3445 % }%
```

The variant of footnote has abbreviation form of the synonym of the word “footnote”. This variant of abbreviated synonym has alternative status (maybe obsolete?).

```
3446 \def\footnoteautorefname{%
3447   \cyr\cyrp\cyro\cyrd\cyrs\cyrt\cyrr.\ \cyrp\cyrr\cyri\cyrm.%
3448 }%
```

Commented form of the full synonym for “footnote”. It has common form for both nominative and accusative but changes in other forms, like “of `\autoref{auto}`”

```
3449 % \def\footnoteautorefname{%
3450 %   \cyr\cyrp\cyro\cyrd\cyrs\cyrt\cyrr\cyro\cyrch\cyrn\cyro\cyre\ %
3451 %   \cyrp\cyrr\cyri\cyrm\cyre\cyrch\cyra\cyrn\cyri\cyre
3452 % }%
```

Commented forms of the “footnote”: have different forms, the same is for the nominative and accusative. (The others needed?)

```
3453 % \def\Nomfootnoteautorefname{\cyr\cyrs\cyrn\cyro\cyrs\cyrk\cyra}%
3454 % \def\Accfootnoteautorefname{\cyr\cyrs\cyrn\cyro\cyrs\cyrk\cyru}%
```

Name of the list item, can be confused with the paragraph reference name, but reader could understand meaning from context(?). Commented variant has common form for both nominative and accusative but changes in other forms, like “of `\autoref{auto}`” etc.

```
3455 \def\itemautorefname{\cyr\cyrp.}%
3456 % \def\itemautorefname{\cyr\cyrp\cyru\cyrk\cyrt}%
```

Names of the figure and table have stable (standard) abbreviation forms. No problem in the middle of sentence.

```
3457 \def\figureautorefname{\cyr\cyrr\cyri\cyrs.}%
3458 \def\tableautorefname{\cyr\cyrt\cyra\cyrb\cyrl.}%
```

Names of the part, chapter, section(s) have stable (standard) abbreviation forms. No problem in the middle of sentence.

```
3459 \def\partautorefname{\cyr\cyrch.}%
3460 \def\chapterautorefname{\cyr\cyrg\cyrl.}%
3461 \def\sectionautorefname{\cyr\cyrr\cyra\cyrz\cyrd.}%
```

Name of the appendix can use this abbreviation, but it is not standard for books, i.e. not for “the good face of the book”. Commented variant has common form for both nominative and accusative but changes in other forms, like “of `\autoref{auto}`” etc.

```
3462 \def\appendixautorefname{\cyr\cyrp\cyrr\cyri\cyrl.}%
3463 % \def\appendixautorefname{%
3464 %   \cyr\cyrp\cyrr\cyri\cyrl\cyro\cyrrh\cyre\cyrn\cyri\cyre
3465 % }%
```

The sectioning command have stable (almost standard) and common abbreviation form for all levels (the meaning of these references visible from the section number). No problem.

```

3466 \def\subsectionautorefname{\cyr\cyrr\cyra\cyrz\cyrd.}%
3467 \def\subsubsectionautorefname{\cyr\cyrr\cyra\cyrz\cyrd.}%

```

The names of references to paragraphs also have stable (almost standard) and common abbreviation form for all levels (the meaning of these references is visible from the section number). No problem in the middle of sentence.

```

3468 \def\paragraphautorefname{\cyr\cyrp.}%
3469 \def\subparagraphautorefname{\cyr\cyrp.}%

```

Commented variant can be used in books but since it has common form for both nominative and accusative but it changes in other forms, like “of \autoref{auto}” etc.

```

3470 % \def\paragraphautorefname{\cyr\cyrp\cyru\cyrn\cyrk\cyrt}%
3471 % \def\subparagraphautorefname{\cyr\cyrp\cyru\cyrn\cyrk\cyrt}%

```

The name of verbatim line. Here could be a standard of the abbreviation (used very rare). But the author preprint publications (which have not any editor or corrector) can use this abbreviation for the page reference. So the meaning of the line reference can be read as reference to the page.

```

3472 \def\FancyVerbLineautorefname{\cyr\cyrs\cyrt\cyrr.}%

```

Commented names of the “verbatim line”: have different forms, also the nominative and accusative.

```

3473 % \def\NomFancyVerbLineautorefname{\cyr\cyrs\cyrt\cyrr\cyro\cyrk\cyra}%
3474 % \def\AccFancyVerbLineautorefname{\cyr\cyrs\cyrt\cyrr\cyro\cyrk\cyru}%

```

The alternative, ve-e-e-ery professional abbreviation, was used in typography markup for typesetters.

```

3475 % \def\FancyVerbLineautorefname{\cyr\cyrs\cyrt\cyrr\cyrk.}%

```

The names of theorem: if we want have “the good face of the book”, so the theorem reference must have the full name (like equation reference). But ...

```

3476 \def\theoremautorefname{\cyr\cyrt\cyre\cyro\cyrr.}%

```

Commented forms of the “theorem”: have different forms, also the nominative and accusative.

```

3477 % \def\Nomtheoremautorefname{\cyr\cyrt\cyre\cyro\cyrr\cyre\cyrm\cyra}%
3478 % \def\Acctheoremautorefname{\cyr\cyrt\cyre\cyro\cyrr\cyre\cyrm\cyru}%

```

Name of the page stable (standard) abbreviation form. No problem.

```

3479 \def\pageautorefname{\cyr\cyrs.}%
3480 }

```

```

3481 \def\HyLang@spanish{%
3482 \def\equationautorefname{Ecuaci'on}%
3483 \def\footnoteautorefname{Nota a pie de p'agina}%
3484 \def\itemautorefname{Elemento}%
3485 \def\figureautorefname{Figura}%
3486 \def\tableautorefname{Tabla}%
3487 \def\partautorefname{Parte}%
3488 \def\appendixautorefname{Ap'endice}%
3489 \def\chapterautorefname{Cap'itulo}%
3490 \def\sectionautorefname{Secci'on}%
3491 \def\subsectionautorefname{Subsecci'on}%
3492 \def\subsubsectionautorefname{Subsubsecci'on}%
3493 \def\paragraphautorefname{P'arrafo}%
3494 \def\subparagraphautorefname{Subp'arrafo}%
3495 \def\FancyVerbLineautorefname{L'inea}%
3496 \def\theoremautorefname{Teorema}%
3497 \def\pageautorefname{P'agina}%

```

```

3498 }
3499 \def\HyLang@vietnamese{%
3500 \def\equationautorefname{Ph\uhorn{}}\ohorn{}ng tr\`inh}%
3501 \def\footnoteautorefname{Ch\`u th\`ich}%
3502 \def\itemautorefname{m\`d{u}c}%
3503 \def\figureautorefname{H\`inh}%
3504 \def\tableautorefname{B\`h{a}ng}%
3505 \def\partautorefname{Ph\`acircumflex{}n}%
3506 \def\appendixautorefname{Ph\`d{u} l\`d{u}c}%
3507 \def\chapterautorefname{ch\uhorn{}}\ohorn{}ng}%
3508 \def\sectionautorefname{m\`d{u}c}%
3509 \def\subsectionautorefname{m\`d{u}c}%
3510 \def\subsubsectionautorefname{m\`d{u}c}%
3511 \def\paragraphautorefname{dj{}}o\`d{a}n}%
3512 \def\subparagraphautorefname{dj{}}o\`d{a}n}%
3513 \def\FancyVerbLineautorefname{d\`ong}%
3514 \def\theoremautorefname{DJ{}}d{i}nh l\`y}%
3515 \def\pageautorefname{Trang}%
3516 }

```

Instead of package babel's definition of `\addto` the implementation of package `varioref` is used. Additionally argument `#1` is checked for `\relax`.

```

3517 \def\HyLang@addto#1#2{%
3518   #2%
3519   \@temptokena{#2}%
3520   \ifx#1\relax
3521     \let#1\@empty
3522   \fi
3523   \ifx#1\@undefined
3524     \edef#1{\the\@temptokena}%
3525   \else
3526     \toks@\expandafter{#1}%
3527     \edef#1{\the\toks@\the\@temptokena}%
3528   \fi
3529   \@temptokena{}\toks@\@temptokena
3530 }

3531 \def\HyLang@DeclareLang#1#2#3{%
3532 \ifpackagewith{babel}{#1}{%
3533   \expandafter\HyLang@addto
3534     \csname extras#1\expandafter\endcsname
3535     \csname HyLang@#2\endcsname
3536   \begingroup
3537     \edef\x{\endgroup
3538       #3%
3539     }%
3540     \x
3541     \@namedef{HyLang@#1@done}{}%
3542   }{}%
3543   \begingroup
3544     \edef\x##1##2{%
3545       \noexpand\ifx##2\relax
3546         \errmessage{No definitions for language #2' found!}%
3547       \noexpand\fi
3548     \endgroup
3549     \noexpand\define@key{Hyp}{#1}[]{%
3550       \noexpand\@ifundefined{HyLang@#1@done}{%
3551         \noexpand\HyLang@addto{\noexpand##1}{\noexpand##2}%

```

```

3552      #3%
3553      \noexpand\@namedef{HyLang@#1@done}{}%
3554    }{}%
3555  }%
3556 }%
3557 \expandafter\x\csname extras#1\expandafter\endcsname
3558       \csname HyLang@#2\endcsname
3559 }
3560 \HyLang@DeclareLang{english}{english}{}
3561 \HyLang@DeclareLang{UKenglish}{english}{}
3562 \HyLang@DeclareLang{british}{english}{}
3563 \HyLang@DeclareLang{USenglish}{english}{}
3564 \HyLang@DeclareLang{american}{english}{}
3565 \HyLang@DeclareLang{german}{german}{}
3566 \HyLang@DeclareLang{austrian}{german}{}
3567 \HyLang@DeclareLang{ngerman}{german}{}
3568 \HyLang@DeclareLang{naustrian}{german}{}
3569 \HyLang@DeclareLang{russian}{russian}{\noexpand\hypersetup{unicode}}
3570 \HyLang@DeclareLang{brazil}{portuges}{}
3571 \HyLang@DeclareLang{brazilian}{portuges}{}
3572 \HyLang@DeclareLang{portuguese}{portuges}{}
3573 \HyLang@DeclareLang{spanish}{spanish}{}
3574 \HyLang@DeclareLang{afrikaans}{afrikaans}{}
3575 \HyLang@DeclareLang{french}{french}{}
3576 \HyLang@DeclareLang{frenchb}{french}{}
3577 \HyLang@DeclareLang{francais}{french}{}
3578 \HyLang@DeclareLang{acadian}{french}{}
3579 \HyLang@DeclareLang{canadien}{french}{}
3580 \HyLang@DeclareLang{italian}{italian}{}
3581 \HyLang@DeclareLang{magyar}{magyar}{}
3582 \HyLang@DeclareLang{hungarian}{magyar}{}

```

More work is needed in case of options `vietnamese` and `vietnam`.

```

3583 \DeclareVoidOption{vietnamese}{%
3584   \HyLang@addto\extrasvietnamese\HyLang@vietnamese
3585   \Hy@AtEndOfPackage{%
3586     \@ifundefined{T@PU}{}{}%
3587     \input{puvnenc.def}%
3588   }%
3589 }%
3590 }
3591 \DeclareVoidOption{vietnam}{%
3592   \HyLang@addto\extrasvietnam\HyLang@vietnamese
3593   \Hy@AtEndOfPackage{%
3594     \@ifundefined{T@PU}{}{}%
3595     \input{puvnenc.def}%
3596   }%
3597 }%
3598 }

```

Similar for option `arabic` that just loads the additions to PU encoding for Arabi.

```

3599 \DeclareVoidOption{arabic}{%
3600   \Hy@AtEndOfPackage{%
3601     \@ifundefined{T@PU}{}{}%
3602     \input{puarenc.def}%
3603   }%
3604 }%
3605 }

```

13 Options to change appearance of links

Colouring links at the L^AT_EX level is useful for debugging, perhaps.

```
3606 \define@key{Hyp}{colorlinks}[true]{%
3607   \Hy@boolkey{colorlinks}{#1}%
3608 }
3609 \DeclareVoidOption{hidelinks}{%
3610   \Hy@colorlinksfalse
3611   \Hy@ocgcolorlinksfalse
3612   \Hy@frenchlinksfalse
3613   \def\Hy@colorlink##1{\begingroup}%
3614   \def\Hy@endcolorlink{\endgroup}%
3615   \def\@pdfborder{0 0 0}%
3616   \let\@pdfborderstyle\ltx@empty
3617 }
3618 \define@key{Hyp}{ocgcolorlinks}[true]{%
3619   \Hy@boolkey{ocgcolorlinks}{#1}%
3620 }
3621 \Hy@AtBeginDocument{%
3622   \begingroup
3623   \ifundefined{OBJ@OCG@view}{%
3624     \ifHy@ocgcolorlinks
3625       \Hy@Warning{%
3626         Driver does not support ‘ocgcolorlinks’,\MessageBreak
3627         using ‘colorlinks’ instead%
3628       }%
3629     \fi
3630   }{%
3631   \endgroup
3632 }
3633 \define@key{Hyp}{frenchlinks}[true]{%
3634   \Hy@boolkey{frenchlinks}{#1}%
3635 }
```

14 Bookmarking

```
3636 \begingroup\expandafter\expandafter\expandafter\endgroup
3637 \expandafter\ifx\csname chapter\endcsname\relax
3638   \def\toclevel@part{0}%
3639 \else
3640   \def\toclevel@part{-1}%
3641 \fi
3642 \def\toclevel@chapter{0}
3643 \def\toclevel@section{1}
3644 \def\toclevel@subsection{2}
3645 \def\toclevel@subsubsection{3}
3646 \def\toclevel@paragraph{4}
3647 \def\toclevel@subparagraph{5}
3648 \def\toclevel@figure{0}
3649 \def\toclevel@table{0}
3650 \@ifpackageloaded{listings}{%
3651   \providecommand*\theHlstlisting{\thelstlisting}%
3652   \providecommand*\toclevel@lstlisting{0}%
3653 }{}
3654 \@ifpackageloaded{listing}{%
3655   \providecommand*\theHlisting{\thelisting}%
3656 }
```

```

3656 \providecommand*\toclevel@listing{0}%
3657 }{}

```

```

3658 \define@key{Hyp}{bookmarks}[true]{%
3659   \Hy@boolkey{bookmarks}{#1}%
3660 }

```

```

3661 \define@key{Hyp}{bookmarksopen}[true]{%
3662   \Hy@boolkey{bookmarksopen}{#1}%
3663 }

```

The depth of the outlines is controlled by option `bookmarksdepth`. The option acts globally and distinguishes three cases:

- `bookmarksdepth`: Without value `hyperref` uses counter `tocdepth` (compatible behaviour and default).
- `bookmarksdepth=<number>`: the depth is set to `<number>`.
- `bookmarksdepth=<name>`: The `<name>` must not start with a number or minus sign. It is a document division name (part, chapter, section, ...). Internally the value of macro `\toclevel@<name>` is used.

```

3664 \let\Hy@bookmarksdepth\c@tocdepth
3665 \define@key{Hyp}{bookmarksdepth}[]{}%
3666 \begingroup
3667   \edef\x{#1}%
3668   \ifx\x\empty
3669     \global\let\Hy@bookmarksdepth\c@tocdepth
3670   \else
3671     \@ifundefined{toclevel@\x}{%
3672       \@onelevel@sanitize\x
3673       \edef\y{\expandafter\@car\x\@nil}%
3674       \ifcase 0\expandafter\ifx\y-1\fi
3675         \expandafter\ifnum\expandafter'\y>47 %
3676         \expandafter\ifnum\expandafter'\y<58 1\fi\fi\relax
3677       \Hy@Warning{Unknown document division name (\x)}%
3678     \else
3679       \setbox\z@=\hbox{%
3680         \count@=\x
3681         \xdef\Hy@bookmarksdepth{\the\count@}%
3682       }%
3683     \fi
3684   }{}%
3685   \setbox\z@=\hbox{%
3686     \count@=\csname toclevel@\x\endcsname
3687     \xdef\Hy@bookmarksdepth{\the\count@}%
3688   }%
3689 }%
3690 \fi
3691 \endgroup
3692 }

```

‘bookmarksopenlevel’ to specify the open level. From Heiko Oberdiek.

```

3693 \define@key{Hyp}{bookmarksopenlevel}{%
3694   \def\@bookmarksopenlevel{#1}%
3695 }
3696 \def\@bookmarksopenlevel{\maxdimen}
3697 % ‘bookmarkstype’ to specify which ‘toc’ file to mimic
3698 \define@key{Hyp}{bookmarkstype}{%
3699   \def\Hy@bookmarkstype{#1}%

```

```

3700 }
3701 \def\Hy@bookmarkstype{toc}

```

Richard Curnow <richard@curnow.demon.co.uk> suggested this functionality. It adds section numbers etc to bookmarks.

```

3702 \define@key{Hyp}{bookmarksnumbered}[true]{%
3703   \Hy@boolkey{bookmarksnumbered}{#1}%
3704 }

```

Option CJKbookmarks enables the patch for CJK bookmarks.

```

3705 \define@key{Hyp}{CJKbookmarks}[true]{%
3706   \Hy@boolkey{CJKbookmarks}{#1}%
3707 }

3708 \def\Hy@temp#1{%
3709   \expandafter\Hy@@temp\csname @#1color\endcsname{#1}%
3710 }
3711 \def\Hy@@temp#1#2#3{%
3712   \define@key{Hyp}{#2color}{%
3713     \HyColor@HyperrefColor{##1}#1%
3714   }%
3715   \def#1{#3}%
3716 }
3717 \Hy@temp{link}{red}
3718 \Hy@temp{anchor}{black}
3719 \Hy@temp{cite}{green}
3720 \Hy@temp{file}{cyan}
3721 \Hy@temp{url}{magenta}
3722 \Hy@temp{menu}{red}
3723 \Hy@temp{run}{\@filecolor}
3724 \define@key{Hyp}{pagecolor}{%
3725   \Hy@WarningPageColor
3726 }
3727 \def\Hy@WarningPageColor{%
3728   \Hy@WarningNoLine{Option 'pagecolor' is not available anymore}%
3729   \global\let\Hy@WarningPageColor\relax
3730 }
3731 \define@key{Hyp}{allcolors}{%
3732   \HyColor@HyperrefColor{#1}\@linkcolor
3733   \HyColor@HyperrefColor{#1}\@anchorcolor
3734   \HyColor@HyperrefColor{#1}\@citecolor
3735   \HyColor@HyperrefColor{#1}\@filecolor
3736   \HyColor@HyperrefColor{#1}\@urlcolor
3737   \HyColor@HyperrefColor{#1}\@menucolor
3738   \HyColor@HyperrefColor{#1}\@runcolor
3739 }

3740 \def\hyperbaseurl#1{\def\@baseurl{#1}}
3741 \define@key{Hyp}{baseurl}{\hyperbaseurl{#1}}
3742 \let\@baseurl\empty
3743 \def\hyperlinkfileprefix#1{\def\Hy@linkfileprefix{#1}}
3744 \define@key{Hyp}{linkfileprefix}{\hyperlinkfileprefix{#1}}
3745 \hyperlinkfileprefix{file:}

```

15 PDF-specific options

`\@pdfpagetransition` The value of option `pdfpagetransition` is stored in `\@pdfpagetransition`. Its initial value is set to `\relax` in order to be able to differentiate between a not used option

and an option with an empty value.

```

3746 \let\@pdfpagetransition\relax
3747 \define@key{Hyp}{pdfpagetransition}{%
3748   \def\@pdfpagetransition{#1}%
3749 }
```

`\@pdfpageduration` The value of option `pdfpageduration` is stored in `\@pdfpageduration`. Its initial value is set to `\relax` in order to be able to differentiate between a not used option and an option with an empty value.

```

3750 \let\@pdfpageduration\relax
3751 \define@key{Hyp}{pdfpageduration}{%
3752   \def\@pdfpageduration{#1}%
3753   \Hy@Match\@pdfpageduration{%
3754     ^([0-9]+\.[0-9]*|[0-9]*\.[0-9]+)$%
3755   }{ }{%
3756     \Hy@Warning{%
3757       Invalid value '\@pdfpageduration'\MessageBreak
3758       of option 'pdfpageduration'\MessageBreak
3759       is replaced by an empty value%
3760     }%
3761     \let\@pdfpageduration\ltx@empty
3762   }%
3763 }
```

The entry for the `/Hid` key in the page object is only necessary, if it is used and set to true for at least one time. If it is always false, then the `/Hid` key is not written to the pdf page object in order not to enlarge the pdf file.

```

3764 \newif\ifHy@useHidKey
3765 \Hy@useHidKeyfalse
3766 \define@key{Hyp}{pdfpagehidden}[true]{%
3767   \Hy@boolkey{pdfpagehidden}{#1}%
3768   \ifHy@pdfpagehidden
3769     \global\Hy@useHidKeytrue
3770   \fi
3771 }
```

The value of the `bordercolor` options are not processed by the color package. Therefore the value consists of space separated rgb numbers in the range 0 until 1.

Package `xcolor` provides `\XC@bordercolor` since version 1.1. If the two spaces in the color specification are missing, then the value is processed as color specification from package `xcolor` by using `\XC@bordercolor` (since `xcolor` 2004/05/09 v1.11, versions 2005/03/24 v2.02 until 2006/11/28 v2.10 do not work because of a bug that is fixed in 2007/01/21 v2.11).

```

3772 \def\Hy@ColorList{cite,file,link,menu,run,url}
3773 \@for\Hy@temp:=\Hy@ColorList\do{%
3774   \edef\Hy@temp{%
3775     \noexpand\define@key{Hyp}{\Hy@temp bordercolor}{%
3776       \noexpand\HyColor@HyperrefBorderColor
3777         {##1}%
3778       \expandafter\noexpand\csname @\Hy@temp bordercolor\endcsname
3779       {hyperref}%
3780       {\Hy@temp bordercolor}%
3781     }%
3782   }%
3783   \Hy@temp
```



```

3784 }
3785 \define@key{Hyp}{pagebordercolor}{%
3786   \Hy@WarningPageBorderColor
3787 }
3788 \def\Hy@WarningPageBorderColor{%
3789   \Hy@WarningNoLine{Option 'pagebordercolor' is not available anymore}%
3790   \global\let\Hy@WarningPageBorderColor\relax
3791 }
3792 \define@key{Hyp}{allbordercolors}{%
3793   \def\Hy@temp##1##2{%
3794     \HyColor@HyperrefBorderColor{#1}##1{hyperref}{##2bordercolor}%
3795   }%
3796   \Hy@temp\@citebordercolor{cite}%
3797   \Hy@temp\@filebordercolor{file}%
3798   \Hy@temp\@linkbordercolor{link}%
3799   \Hy@temp\@menubordercolor{menu}%
3800   \Hy@temp\@runbordercolor{run}%
3801   \Hy@temp\@urlbordercolor{url}%
3802 }
3803 \define@key{Hyp}{pdfhighlight}{\def\@pdfhighlight{#1}}
3804 \Hy@DefNameKey{pdfhighlight}{%
3805   \do{/I}{Invert}%
3806   \do{/N}{None}%
3807   \do{/O}{Outline}%
3808   \do{/P}{Push}%
3809 }
3810 \define@key{Hyp}{pdfborder}{%
3811   \let\Hy@temp\@pdfborder
3812   \def\@pdfborder{#1}%
3813   \Hy@Match\@pdfborder{%
3814     ~\HyPat@NonNegativeReal/ %
3815     \HyPat@NonNegativeReal/ %
3816     \HyPat@NonNegativeReal/%
3817     ( ?\[ \HyPat@NonNegativeReal/( \HyPat@NonNegativeReal/)*\])?%%
3818   }{ }{%
3819     \Hy@Warning{%
3820       Invalid value '\@pdfborder'\MessageBreak
3821       for option 'pdfborder'\MessageBreak
3822       Option setting is ignored%
3823     }%
3824     \let\@pdfborder\Hy@temp
3825   }%
3826 }
3827 \define@key{Hyp}{pdfborderstyle}{%
3828   \let\Hy@temp\@pdfborderstyle
3829   \def\@pdfborderstyle{#1}%
3830   \Hy@Match\@pdfborderstyle{%
3831     ~%
3832     ( */Type */Border%
3833     | */W +\HyPat@NonNegativeReal/%
3834     | */S */[SDBIU]%
3835     | */D *[ ( \HyPat@NonNegativeReal/( \HyPat@NonNegativeReal/)? )? ]%
3836     )* *%%
3837   }{ }{%
3838     \Hy@Warning{%
3839       Invalid value '\@pdfborderstyle'\MessageBreak
3840       for option 'pdfborderstyle'\MessageBreak

```

```

3841     Option setting is ignored%
3842 }%
3843 \let\@pdfborderstyle\Hy@temp
3844 }%
3845 }
3846 \def\Hy@setpdfborder{%
3847 \ifx\@pdfborder\@empty
3848 \else
3849 /Border[\@pdfborder]%
3850 \fi
3851 \ifx\@pdfborderstyle\@empty
3852 \else
3853 /BS<<\@pdfborderstyle>>%
3854 \fi
3855 }
3856 \Hy@DefNameKey{pdfpagemode}{%
3857 \do{UseNone}{}%
3858 \do{UseOutlines}{}%
3859 \do{UseThumbs}{}%
3860 \do{FullScreen}{}%
3861 \do{UseOC}{PDF 1.5}%
3862 \do{UseAttachments}{PDF 1.6}%
3863 }
3864 \Hy@DefNameKey{pdfnonfullscreenpagemode}{%
3865 \do{UseNone}{}%
3866 \do{UseOutlines}{}%
3867 \do{UseThumbs}{}%
3868 \do{FullScreen}{}%
3869 \do{UseOC}{PDF 1.5}%
3870 \do{UseAttachments}{PDF 1.6}%
3871 }
3872 \Hy@DefNameKey{pdfdirection}{%
3873 \do{L2R}{Left to right}%
3874 \do{R2L}{Right to left}%
3875 }
3876 \Hy@DefNameKey{pdfviewarea}{%
3877 \do{MediaBox}{}%
3878 \do{CropBox}{}%
3879 \do{BleedBox}{}%
3880 \do{TrimBox}{}%
3881 \do{ArtBox}{}%
3882 }
3883 \Hy@DefNameKey{pdfviewclip}{%
3884 \do{MediaBox}{}%
3885 \do{CropBox}{}%
3886 \do{BleedBox}{}%
3887 \do{TrimBox}{}%
3888 \do{ArtBox}{}%
3889 }
3890 \Hy@DefNameKey{pdfprintarea}{%
3891 \do{MediaBox}{}%
3892 \do{CropBox}{}%
3893 \do{BleedBox}{}%
3894 \do{TrimBox}{}%
3895 \do{ArtBox}{}%
3896 }
3897 \Hy@DefNameKey{pdfprintclip}{%

```

```

3898 \do{MediaBox}{}%
3899 \do{CropBox}{}%
3900 \do{BleedBox}{}%
3901 \do{TrimBox}{}%
3902 \do{ArtBox}{}%
3903 }
3904 \Hy@DefNameKey{pdfprintscaling}{%
3905 \do{AppDefault}{}%
3906 \do{None}{}%
3907 }
3908 \Hy@DefNameKey{pdfduplex}{%
3909 \do{Simplex}{}%
3910 \do{DuplexFlipShortEdge}{}%
3911 \do{DuplexFlipLongEdge}{}%
3912 }
3913 \Hy@DefNameKey{pdfpicktraybypdfsize}{%
3914 \do{true}{}%
3915 \do{false}{}%
3916 }
3917 \define@key{Hyp}{pdfprintpagerange}{%
3918 \def\@pdfprintpagerange{#1}%
3919 }
3920 \Hy@DefNameKey{pdfnumcopies}{%
3921 \do{2}{two copies}%
3922 \do{3}{three copies}%
3923 \do{4}{four copies}%
3924 \do{5}{five copies}%
3925 }
3926 \define@key{Hyp}{pdfusetitle}[true]{%
3927 \Hy@boolkey{pdfusetitle}{#1}%
3928 }
3929 \def\HyXeTeX@CheckUnicode{%
3930 \ifxetex
3931 \ifHy@unicode
3932 \else
3933 \Hy@WarningNoLine{%
3934 XeTeX driver only supports unicode.\MessageBreak
3935 Enabling option 'unicode'%
3936 }%
3937 \kvsetkeys{Hyp}{unicode}%
3938 \fi
3939 \else
3940 \let\HyXeTeX@CheckUnicode\relax
3941 \fi
3942 }
3943 \def\HyPsd@PrerenderUnicode#1{%
3944 \begingroup
3945 \expandafter\ifx\csname PrerenderUnicode\endcsname\relax
3946 \else
3947 \sbox0{%
3948 \let\GenericInfo\@gobbletwo
3949 \let\GenericWarning\@gobbletwo
3950 \let\GenericError\@gobblefour
3951 \PrerenderUnicode{#1}%
3952 }%
3953 \fi
3954 \endgroup

```

```

3955 }
3956 \define@key{Hyp}{pdftitle}{%
3957   \HyXeTeX@CheckUnicode
3958   \HyPsd@XeTeXBigCharstrue
3959   \HyPsd@PrerenderUnicode{#1}%
3960   \pdfstringdef\@pdftitle{#1}%
3961 }
3962 \define@key{Hyp}{pdfauthor}{%
3963   \HyXeTeX@CheckUnicode
3964   \HyPsd@XeTeXBigCharstrue
3965   \HyPsd@PrerenderUnicode{#1}%
3966   \pdfstringdef\@pdfauthor{#1}%
3967 }
3968 \define@key{Hyp}{pdfproducer}{%
3969   \HyXeTeX@CheckUnicode
3970   \HyPsd@XeTeXBigCharstrue
3971   \HyPsd@PrerenderUnicode{#1}%
3972   \pdfstringdef\@pdfproducer{#1}%
3973   \ifxetex
3974     \Hy@Warning{%
3975       pdfproducer: %
3976       xdvipdfmx will use its own setting\MessageBreak
3977       instead of the value given%
3978     }%
3979   \else
3980     \def\Hy@temp{hdvipdfm}%
3981     \ifx\Hy@driver\Hy@temp
3982       \Hy@Warning{%
3983         pdfproducer: %
3984         dvipdfm(x) will use its own setting\MessageBreak
3985         instead of the value given%
3986       }%
3987     \fi
3988   \fi
3989 }
3990 \define@key{Hyp}{pdfcreator}{%
3991   \HyXeTeX@CheckUnicode
3992   \HyPsd@XeTeXBigCharstrue
3993   \HyPsd@PrerenderUnicode{#1}%
3994   \pdfstringdef\@pdfcreator{#1}%
3995 }
3996 \define@key{Hyp}{pdfcreationdate}{%
3997   \begingroup
3998   \Hy@unicodfalse
3999   \pdfstringdef\@pdfcreationdate{#1}%
4000 \endgroup
4001 }
4002 \define@key{Hyp}{pdfmoddate}{%
4003   \begingroup
4004   \Hy@unicodfalse
4005   \pdfstringdef\@pdfmoddate{#1}%
4006 \endgroup
4007 }
4008 \define@key{Hyp}{pdfsubject}{%
4009   \HyXeTeX@CheckUnicode
4010   \HyPsd@XeTeXBigCharstrue
4011   \HyPsd@PrerenderUnicode{#1}%

```

```

4012 \pdfstringdef\@pdfsubject{#1}%
4013 }
4014 \define@key{Hyp}{pdfkeywords}{%
4015 \HyXeTeX@CheckUnicode
4016 \HyPsd@XeTeXBigCharstrue
4017 \HyPsd@PrerenderUnicode{#1}%
4018 \pdfstringdef\@pdfkeywords{#1}%
4019 }
4020 \define@key{Hyp}{pdftrapped}{%
4021 \lowercase{\edef\Hy@temp{#1}}}%
4022 \ifx\Hy@temp\HyInfo@trapped@true
4023 \def\@pdftrapped{True}%
4024 \else
4025 \ifx\Hy@temp\HyInfo@trapped@false
4026 \def\@pdftrapped{False}%
4027 \else
4028 \ifx\Hy@temp\HyInfo@trapped@unknown
4029 \def\@pdftrapped{Unknown}%
4030 \else
4031 \ifx\Hy@temp\@empty
4032 \else
4033 \Hy@Warning{%
4034   Unsupported value '#1'\MessageBreak
4035   for option 'pdftrapped'%
4036 }%
4037 \fi
4038 \def\@pdftrapped{}%
4039 \fi
4040 \fi
4041 \fi
4042 }
4043 \def\HyInfo@trapped@true{true}
4044 \def\HyInfo@trapped@false{false}
4045 \def\HyInfo@trapped@unknown{unknown}
4046 \def\HyInfo@TrappedUnsupported{%
4047 \ifx\@pdftrapped\@empty
4048 \else
4049 \Hy@WarningNoLine{'pdftrapped' is not supported by this driver}%
4050 \gdef\HyInfo@TrappedUnsupported{}%
4051 \fi
4052 }
4053 \define@key{Hyp}{pdfinfo}{%
4054 \kvsetkeys{pdfinfo}{#1}%
4055 }
4056 \def\Hy@temp#1{%
4057 \lowercase{\Hy@temp@A{#1}}{#1}%
4058 }
4059 \def\Hy@temp@A#1#2{%
4060 \define@key{pdfinfo}{#2}{%
4061 \hypersetup{pdf#1={##1}}}%
4062 }%
4063 }
4064 \Hy@temp{Title}
4065 \Hy@temp{Author}
4066 \Hy@temp{Keywords}
4067 \Hy@temp{Subject}
4068 \Hy@temp{Creator}

```

```

4069 \Hy@temp{Producer}
4070 \Hy@temp{CreationDate}
4071 \Hy@temp{ModDate}
4072 \Hy@temp{Trapped}
4073 \newif\ifHyInfo@AddonUnsupported
4074 \kv@set@family@handler{pdfinfo}{%
4075   \HyInfo@AddonHandler{#1}{#2}%
4076 }
4077 \let\HyInfo@do\relax
4078 \def\HyInfo@AddonHandler#1#2{%
4079   \ifx\kv@value\relax
4080     \Hy@Warning{%
4081       Option 'pdfinfo': ignoring key '\kv@key' without value%
4082     }%
4083   \else
4084     \EdefEscapeName\HyInfo@KeyEscaped{\kv@key}%
4085     \EdefUnescapeName\HyInfo@Key{\HyInfo@KeyEscaped}%
4086     \expandafter\ifx\curname KV@pdfinfo@\HyInfo@Key\endcurname\relax
4087     \ifHyInfo@AddonUnsupported
4088       \Hy@Warning{%
4089         This driver does not support additional\MessageBreak
4090         information entries, therefore\MessageBreak
4091         '\kv@key' is ignored%
4092       }%
4093     \else
4094       \define@key{pdfinfo}{\HyInfo@Key}{%
4095         \HyXeTeX@CheckUnicode
4096         \HyPsd@XeTeXBigCharstrue
4097         \HyPsd@PrerenderUnicode{##1}%
4098         \pdfstringdef\HyInfo@Value{##1}%
4099         \expandafter\let\curname HyInfo@Value@\HyInfo@Key\endcurname
4100         \HyInfo@Value
4101       }%
4102     \edef\HyInfo@AddonList{%
4103       \HyInfo@AddonList
4104       \HyInfo@do{\HyInfo@Key}%
4105     }%
4106     \kv@parse@normalized{%
4107       \HyInfo@Key={#2}%
4108     }{%
4109       \kv@processor@default{pdfinfo}%
4110     }%
4111     \fi
4112   \else
4113     \kv@parse@normalized{%
4114       \HyInfo@Key={#2}%
4115     }{%
4116       \kv@processor@default{pdfinfo}%
4117     }%
4118     \fi
4119   \fi
4120 }
4121 \def\HyInfo@GenerateAddons{%
4122   \ifHyInfo@AddonUnsupported
4123     \def\HyInfo@Addons{}%
4124   \else
4125     \begingroup

```

```

4126 \toks@{}%
4127 \def\HyInfo@do###1{%
4128 \EdefEscapeName\HyInfo@Key{###1}%
4129 \edef\x{%
4130 \toks@{}%
4131 \the\toks@
4132 /\HyInfo@Key(\csname HyInfo@Value@###1\endcsname)%
4133 }%
4134 }%
4135 \x
4136 }%
4137 \HyInfo@AddonList
4138 \edef\x{\endgroup
4139 \def\noexpand\HyInfo@Addons{\the\toks@}%
4140 }%
4141 \x
4142 \fi
4143 }
4144 \let\HyInfo@AddonList\ltx@empty

4145 \define@key{Hyp}{pdfview}{\calculate@pdfview#1 \}
4146 \define@key{Hyp}{pdfinkmargin}{\setpdfinkmargin{#1}}
4147 \let\setpdfinkmargin@gobble
4148 \def\calculate@pdfview#1 #2\{%
4149 \def\@pdfview{#1}%
4150 \ifx\#2\%
4151 \def\@pdfviewparams{-32768}%
4152 \else
4153 \def\@pdfviewparams{ #2}%
4154 \fi
4155 }
4156 \begingroup\expandafter\expandafter\expandafter\endgroup
4157 \expandafter\ifx\csname numexpr\endcsname\relax
4158 \def\Hy@number#1{%
4159 \expandafter\@firstofone\expandafter{\number#1}%
4160 }%
4161 \else
4162 \def\Hy@number#1{%
4163 \the\numexpr#1\relax
4164 }%
4165 \fi
4166 \define@key{Hyp}{pdfstartpage}{%
4167 \ifx\#1\%
4168 \let\@pdfstartpage\ltx@empty
4169 \else
4170 \edef\@pdfstartpage{\Hy@number{#1}}%
4171 \fi
4172 }%
4173 \define@key{Hyp}{pdfstartview}{%
4174 \ifx\#1\%
4175 \let\@pdfstartview\ltx@empty
4176 \else
4177 \hypercalcbpdef\@pdfstartview{/#1}%
4178 \fi
4179 }
4180 \def\HyPat@NonNegativeReal/{%
4181 \ *([0-9]+\.[0-9]*|[0-9]*\.[0-9]+) *%
4182 }

```

```

4183 \define@key{Hyp}{pdfremotestartview}{%
4184   \ifx\#1\%
4185     \def\@pdfremotestartview{/Fit}%
4186   \else
4187     \hypercalcbpdef\@pdfremotestartview{#1}%
4188     \edef\@pdfremotestartview{\@pdfremotestartview}%
4189     \Hy@Match\@pdfremotestartview{%
4190       ^{XYZ -?(null|\HyPat@NonNegativeReal/) %
4191         -(null|\HyPat@NonNegativeReal/) %
4192         (null|\HyPat@NonNegativeReal/)|%
4193         Fit(|B| %
4194           (H|V|BH|BV) (null|\HyPat@NonNegativeReal/)|%
4195           R \HyPat@NonNegativeReal/ \HyPat@NonNegativeReal/ %
4196           \HyPat@NonNegativeReal/ \HyPat@NonNegativeReal/%
4197         )}$%
4198     }{}{%
4199       \Hy@Warning{%
4200         Invalid value '\@pdfremotestartview'\MessageBreak
4201         of 'pdfremotestartview'\MessageBreak
4202         is replaced by 'Fit'%
4203       }%
4204       \let\@pdfremotestartview\@empty
4205     }%
4206     \ifx\@pdfremotestartview\@empty
4207       \def\@pdfremotestartview{/Fit}%
4208     \else
4209       \edef\@pdfremotestartview{/ \@pdfremotestartview}%
4210     \fi
4211   \fi
4212 }
4213 \define@key{Hyp}{pdfpagescrop}{\edef\@pdfpagescrop{#1}}
4214 \define@key{Hyp}{pdftoolbar}[true]{%
4215   \Hy@boolkey{pdftoolbar}{#1}%
4216 }
4217 \define@key{Hyp}{pdfmenubar}[true]{%
4218   \Hy@boolkey{pdfmenubar}{#1}%
4219 }
4220 \define@key{Hyp}{pdfwindowui}[true]{%
4221   \Hy@boolkey{pdfwindowui}{#1}%
4222 }
4223 \define@key{Hyp}{pdffitwindow}[true]{%
4224   \Hy@boolkey{pdffitwindow}{#1}%
4225 }
4226 \define@key{Hyp}{pdfcenterwindow}[true]{%
4227   \Hy@boolkey{pdfcenterwindow}{#1}%
4228 }
4229 \define@key{Hyp}{pdfdisplaydoctitle}[true]{%
4230   \Hy@boolkey{pdfdisplaydoctitle}{#1}%
4231 }
4232 \define@key{Hyp}{pdfa}[true]{%
4233   \Hy@boolkey{pdfa}{#1}%
4234 }
4235 \define@key{Hyp}{pdfnewwindow}[true]{%
4236   \def\Hy@temp{#1}%
4237   \ifx\Hy@temp\@empty
4238     \Hy@pdfnewwindowsetfalse
4239   \else

```



```

4240 \Hy@pdfnewwindowsettrue
4241 \Hy@boolkey{pdfnewwindow}{#1}%
4242 \fi
4243 }
4244 \def\Hy@SetNewWindow{%
4245 \ifHy@pdfnewwindowset
4246 /NewWindow %
4247 \ifHy@pdfnewwindow true\else false\fi
4248 \fi
4249 }
4250 \Hy@DefNameKey{pdfpagelayout}{%
4251 \do{SinglePage}{}%
4252 \do{OneColumn}{}%
4253 \do{TwoColumnLeft}{}%
4254 \do{TwoColumnRight}{}%
4255 \do{TwoPageLeft}{PDF 1.5}%
4256 \do{TwoPageRight}{PDF 1.5}%
4257 }
4258 \define@key{Hyp}{pdflang}{%
4259 \def\@pdflang{#1}%
4260 }
4261 \define@key{Hyp}{pdfpagelabels}[true]{%
4262 \Hy@boolkey{pdfpagelabels}{#1}%
4263 }
4264 \define@key{Hyp}{pdfescapeform}[true]{%
4265 \Hy@boolkey{pdfescapeform}{#1}%
4266 }

```

Default values:

```

4267 \def\@linkbordercolor{1 0 0}
4268 \def\@urlbordercolor{0 1 1}
4269 \def\@menubordercolor{1 0 0}
4270 \def\@filebordercolor{0 .5 .5}
4271 \def\@runbordercolor{0 .7 .7}
4272 \def\@citebordercolor{0 1 0}
4273 \def\@pdfhighlight{/I}
4274 \let\@pdftitle\ltx@empty
4275 \let\@pdfauthor\ltx@empty
4276 \let\@pdfproducer\relax
4277 \def\@pdfcreator{LaTeX with hyperref package}
4278 \let\@pdfcreationdate\ltx@empty
4279 \let\@pdfmoddate\ltx@empty
4280 \let\@pdfsubject\ltx@empty
4281 \let\@pdfkeywords\ltx@empty
4282 \let\@pdftrapped\ltx@empty
4283 \let\@pdfpagescrop\ltx@empty
4284 \def\@pdfstartview{/Fit}
4285 \def\@pdfremotestartview{/Fit}
4286 \def\@pdfstartpage{1}
4287 \let\@pdfprintpagerange\ltx@empty
4288 \let\@pdflang\ltx@empty
4289 \let\PDF@SetupDoc\@empty
4290 \let\PDF@FinishDoc\@empty
4291 \let\phantomsection\@empty
4292 \let\special@paper\@empty
4293 \def\HyperDestNameFilter#1{#1}
4294 \Hy@AtBeginDocument{%
4295 \begingroup

```

```

4296 \edef\x{\@ifundefined{stockheight}\paperheight\stockheight}%
4297 \dimen@=\x\relax
4298 \ifdim\dimen@>\z@
4299 \else
4300 \dimen@=11in\relax
4301 \Hy@WarningNoLine{%
4302   Height of page (\expandafter\string\x) %
4303   is invalid (\the\x),\MessageBreak
4304   using 11in%
4305 }%
4306 \fi
4307 \dimen@=0.99626401\dimen@
4308 \xdef\Hy@pageheight{\strip@pt\dimen@}%
4309 \endgroup
4310 }
4311 \def\HyInd@EncapChar{\|}

```

Allow the user to use `\ExecuteOptions` in the `cfg` file even though this package does not use the normal option mechanism. Use `\hyper@normalise` as a scratch macro, since it is going to be defined in a couple of lines anyway.

```

4312 \let\hyper@normalise\ExecuteOptions
4313 \let\ExecuteOptions\hypersetup
4314 \Hy@RestoreCatcodes
4315 \InputIfFileExists{hyperref.cfg}{-}{-}
4316 \Hy@SetCatcodes
4317 \let\ExecuteOptions\hyper@normalise
4318 \ifx\Hy@MaybeStopNow\relax
4319 \else
4320 \Hy@stoppedearlytrue
4321 \expandafter\Hy@MaybeStopNow
4322 \fi
4323 \Hy@stoppedearlyfalse

```

To add flexibility, we will not use the ordinary processing of package options, but put them through the *keyval* package. This section was written by David Carlisle.

```

4324 \SetupKeyvalOptions{family=Hyp}
4325 \DeclareLocalOptions{%
4326   a4paper,a5paper,b5paper,letterpaper,legalpaper,executivepaper%
4327 }

```

Add option `tex4ht` if package `tex4ht` is loaded.

```

4328 \@ifpackageloaded{tex4ht}{%
4329   \@ifpackagewith{hyperref}{tex4ht}{-}{-}%
4330   \PassOptionsToPackage{tex4ht}{hyperref}%
4331 }%
4332 }{-}

4333 \let\ReadBookmarks\relax
4334 \ProcessKeyvalOptions{Hyp}

```

After processing options.

15.1 Package `xspace` support

```

4335 \def\Hy@xspace@end{}
4336 \ltx@ifundefined{xspaceaddexceptions}{%
4337   \Hy@AtBeginDocument{%
4338     \ltx@ifundefined{xspaceaddexceptions}{%
4339       }%

```

```

4340 \def\Hy@xspace@end{%
4341 \ltx@gobble{end for xspace}%
4342 }%
4343 \xspaceaddexceptions{%
4344 \Hy@xspace@end,\hyper@linkend,\hyper@anchorend
4345 }%
4346 }%
4347 }%
4348 }{%
4349 \def\Hy@xspace@end{%
4350 \ltx@gobble{end for xspace}%
4351 }%
4352 \xspaceaddexceptions{\Hy@xspace@end,\hyper@linkend,\hyper@anchorend}%
4353 }

```

15.2 Option draft

```

4354 \Hy@AtBeginDocument{%
4355 \ifHy@draft
4356 \let\hyper@@anchor\@gobble
4357 \gdef\hyper@link#1#2#3{#3\Hy@xspace@end}%
4358 \def\hyper@anchorstart#1#2{#2\Hy@xspace@end}%
4359 \def\hyper@anchorend{\Hy@xspace@end}%
4360 \let\hyper@linkstart\@gobbletwo
4361 \def\hyper@linkend{\Hy@xspace@end}%
4362 \def\hyper@linkurl#1#2{#1\Hy@xspace@end}%
4363 \def\hyper@linkfile#1#2#3{#1\Hy@xspace@end}%
4364 \def\hyper@link@[#1]#2#3#4{#4\Hy@xspace@end}%
4365 \def\Acrobatmenu#1#2{\leavevmode#2\Hy@xspace@end}%
4366 \let\PDF@SetupDoc\@empty
4367 \let\PDF@FinishDoc\@empty
4368 \let\@fifthoffive\@secondoftwo
4369 \let\@secondoffive\@secondoftwo
4370 \let\ReadBookmarks\relax
4371 \let\WriteBookmarks\relax
4372 \Hy@WarningNoLine{Draft mode on}%
4373 \fi
4374 \Hy@DisableOption{draft}%
4375 \Hy@DisableOption{nolinks}%
4376 \Hy@DisableOption{final}%
4377 }

```

15.3 PDF/A

```

4378 \Hy@DisableOption{pdfa}
4379 \ifHy@pdfa
4380 \kvsetkeys{Hyp}{pdfversion=1.4}%
4381 \Hy@DisableOption{pdfversion}%
4382 \def\Hy@Acrobatmenu#1#2{%
4383 \leavevmode
4384 \begingroup
4385 \edef\x{#1}%
4386 \@onelevel@sanitize\x
4387 \ifx\x\Hy@NextPage
4388 \let\y=Y%
4389 \else
4390 \ifx\x\Hy@PrevPage
4391 \let\y=Y%
4392 \else

```

```

4393     \ifx\x\Hy@FirstPage
4394     \let\y=Y%
4395     \else
4396     \ifx\x\Hy@LastPage
4397     \let\y=Y%
4398     \else
4399     \let\y=N%
4400     \fi
4401     \fi
4402     \fi
4403     \fi
4404     \expandafter\endgroup
4405     \ifx\y Y%
4406     \else
4407     \Hy@Error{%
4408     PDF/A: Named action ‘#1’ is not permitted%
4409     }\@ehc
4410     {#2}%
4411     \expandafter\@gobble
4412     \fi
4413     }%
4414     \def\Hy@temp#1{%
4415     \expandafter\def\csname Hy@#1\endcsname{#1}%
4416     \expandafter\@onelevel@sanitize\csname Hy@#1\endcsname
4417     }%
4418     \Hy@temp{NextPage}%
4419     \Hy@temp{PrevPage}%
4420     \Hy@temp{FirstPage}%
4421     \Hy@temp{LastPage}%
4422     \else
4423     \def\Hy@Acrobatmenu#1#2{\leavevmode}%
4424     \fi

```

15.4 Patch for babel’s \texttilde

Babel does not define `\texttilde` in NFSS2 manner, so the NFSS2 definitions of PD1 or PU encoding is not compatible. To fix this, `\texttilde` is defined in babel manner.

```

4425 \Hy@nextfalse
4426 \ltx@ifundefined{spanish@sh@}{\Hy@nexttrue}
4427 \ltx@ifundefined{galician@sh@}{\Hy@nexttrue}
4428 \ltx@ifundefined{estonian@sh@}{\Hy@nexttrue}
4429 \ifHy@next
4430 \let\texttilde\~%
4431 \fi

4432 \def\Hy@wrapper@babel#1#2{%
4433 \begingroup
4434 \Hy@safe@activetrue
4435 \set@display@protect
4436 \edef\x{#2}%
4437 \@onelevel@sanitize\x
4438 \toks@{#1}%
4439 \edef\x{\endgroup\the\toks@{\x}}%
4440 \x
4441 }
4442 \def\Hy@WrapperDef#1{%
4443 \begingroup

```

```

4444 \escapechar=\m@ne
4445 \xdef\Hy@gtemp{%
4446 \expandafter\noexpand\csname HyWrap@\string#1\endcsname
4447 }%
4448 \endgroup
4449 \edef#1{%
4450 \noexpand\Hy@wrapper@babel
4451 \expandafter\noexpand\Hy@gtemp
4452 }%
4453 \expandafter\def\Hy@gtemp
4454 }

4455 \ifHy@hyperfigures
4456 \Hy@Info{Hyper figures ON}%
4457 \else
4458 \Hy@Info{Hyper figures OFF}%
4459 \fi
4460 \ifHy@nesting
4461 \Hy@Info{Link nesting ON}%
4462 \else
4463 \Hy@Info{Link nesting OFF}%
4464 \fi
4465 \ifHy@hyperindex
4466 \Hy@Info{Hyper index ON}%
4467 \else
4468 \Hy@Info{Hyper index OFF}%
4469 \fi
4470 \ifHy@plainpages
4471 \Hy@Info{Plain pages ON}%
4472 \else
4473 \Hy@Info{Plain pages OFF}%
4474 \fi
4475 \ifHy@backref
4476 \Hy@Info{Backreferencing ON}%
4477 \else
4478 \Hy@Info{Backreferencing OFF}%
4479 \fi
4480 \ifHy@typexml
4481 \Hy@AtEndOfPackage{%
4482 \RequirePackage{color}%
4483 \RequirePackage{nameref}[2012/07/28]%
4484 }%
4485 \fi
4486 \Hy@DisableOption{typexml}
4487 \ifHy@implicit
4488 \Hy@InfoNoLine{Implicit mode ON; LaTeX internals redefined}%
4489 \else
4490 \Hy@InfoNoLine{Implicit mode OFF; no redefinition of LaTeX internals}%
4491 \def\MaybeStopEarly{%
4492 \Hy@Message{Stopped early}%
4493 \Hy@AtBeginDocument{%
4494 \PDF@FinishDoc
4495 \gdef\PDF@FinishDoc{}}%
4496 }%
4497 \endinput
4498 }%
4499 \Hy@AtBeginDocument{%
4500 \let\autoref\ref

```

```

4501 \let\autopageref\pageref
4502 \ifx\@pdfpagemode\@empty
4503 \gdef\@pdfpagemode{UseNone}%
4504 \fi
4505 \global\Hy@backreffalse
4506 }%
4507 \Hy@AtEndOfPackage{%
4508 \global\let\ReadBookmarks\relax
4509 \global\let\WriteBookmarks\relax
4510 }%
4511 \fi
4512 \Hy@DisableOption{implicit}

```

15.4.1 Driver loading

```

4513 \Hy@AtEndOfPackage{%
4514 \@ifpackageloaded{tex4ht}{%
4515 \def\Hy@driver{htex4ht}%
4516 \Hy@texhttrue
4517 }{}%

```

Some drivers can be detected. Check for these drivers, whether the given driver option is ok. Otherwise force the right driver or use the default driver.

```

4518 \ifx\Hy@driver\@empty
4519 \else
4520 \def\Hy@temp{hpdftex}%
4521 \ifpdf
4522 \ifx\Hy@driver\Hy@temp
4523 \else
4524 \Hy@WarningNoLine{%
4525 Wrong driver ‘\Hy@driver.def’;\MessageBreak
4526 pdfTeX is running in PDF mode.\MessageBreak
4527 Forcing driver ‘\Hy@temp.def’%
4528 }%
4529 \let\Hy@driver\Hy@temp
4530 \fi
4531 \else
4532 \ifx\Hy@driver\Hy@temp
4533 \Hy@WarningNoLine{%
4534 Wrong driver ‘\Hy@driver.def’;\MessageBreak
4535 pdfTeX is not running in PDF mode.\MessageBreak
4536 Using default driver%
4537 }%
4538 \let\Hy@driver\@empty
4539 \fi
4540 \fi
4541 \fi
4542 \ifHy@texht
4543 \else
4544 \ifx\Hy@driver\@empty
4545 \else
4546 \def\Hy@temp{hxdetex}%
4547 \ifxdetex
4548 \ifx\Hy@driver\Hy@temp
4549 \else
4550 \Hy@WarningNoLine{%
4551 Wrong driver ‘\Hy@driver.def’;\MessageBreak
4552 XeTeX is running.\MessageBreak

```

```

4553         Forcing driver ‘\Hy@temp.def’ for XeTeX%
4554     }%
4555     \let\Hy@driver\Hy@temp
4556 \fi
4557 \fi
4558 \fi
4559 \fi
4560 \ifx\Hy@driver\@empty
4561 \else
4562     \def\Hy@temp{hvtexhtm}%
4563     \ifvtexhtml
4564         \ifx\Hy@driver\Hy@temp
4565         \else
4566             \Hy@WarningNoLine{%
4567                 Wrong driver ‘\Hy@driver.def’;\MessageBreak
4568                 VTeX is running in HTML mode.\MessageBreak
4569                 Forcing driver ‘\Hy@temp.def’%
4570             }%
4571             \let\Hy@driver\Hy@temp
4572         \fi
4573     \else
4574         \ifx\Hy@driver\Hy@temp
4575         \Hy@WarningNoLine{%
4576             Wrong driver ‘\Hy@driver.def’;\MessageBreak
4577             VTeX is not running in HTML mode.\MessageBreak
4578             Using default driver%
4579         }%
4580         \let\Hy@driver\@empty
4581     \fi
4582 \fi
4583 \fi

```

If the driver is not given, find the right driver or use the default driver.

```

4584 \let\HyOpt@DriverType\ltx@empty
4585 \ifx\HyOpt@CustomDriver\ltx@empty
4586     \ifx\Hy@driver\@empty
4587         \def\HyOpt@DriverType{ (autodetected)}%
4588         \providecommand*{\Hy@defaultdriver}{hypertex}%
4589         \ifpdf
4590             \def\Hy@driver{hpdfTEX}%
4591         \else
4592             \ifxetex
4593                 \def\Hy@driver{hxetex}%
4594             \else
4595                 \ifvtexhtml
4596                     \def\Hy@driver{hvtexhtm}%
4597                 \def\MaybeStopEarly{%
4598                     \Hy@Message{Stopped early}%
4599                     \Hy@AtBeginDocument{%
4600                         \PDF@FinishDoc
4601                         \gdef\PDF@FinishDoc{}%
4602                     }%
4603                 \endinput
4604             }%
4605         \else
4606             \ifvtexpdf
4607                 \def\Hy@driver{hvtex}%
4608             \else

```

```

4609         \ifvtexps
4610         \def\Hy@driver{hvtex}%
4611     \else
4612         \ifx\HyOpt@DriverFallback\ltx@empty
4613         \let\Hy@driver\Hy@defaultdriver
4614         \def\HyOpt@DriverType{ (default)}%
4615     \else
4616         \begingroup
4617         \toks@{\expandafter{\HyOpt@DriverFallback}}%
4618         \edef\x{\endgroup
4619             \noexpand\kvsetkeys{Hyp}{\the\toks@}}%
4620         }%
4621         \x
4622         \ifx\Hy@driver\ltx@empty
4623         \let\Hy@driver\Hy@defaultdriver
4624         \def\HyOpt@DriverType{ (default)}%
4625     \else
4626         \def\HyOpt@DriverType{ (fallback)}%
4627     \fi
4628 \fi
4629 \fi
4630 \fi
4631 \fi
4632 \fi
4633 \fi
4634 \ifx\Hy@driver\Hy@defaultdriver
4635     \def\Hy@temp{hdvwind}%
4636     \ifx\Hy@temp\Hy@driver
4637         \kvsetkeys{Hyp}{colorlinks}%
4638         \PassOptionsToPackage{dviwindo}{color}%
4639     \fi
4640 \fi
4641 \fi
4642 \else
4643     \def\HyOpt@DriverType{ (custom)}%
4644     \let\Hy@driver\HyOpt@CustomDriver
4645 \fi
4646 \Hy@Message{Driver\HyOpt@DriverType: \Hy@driver}%
4647 \chardef\Hy@VersionChecked=0 %
4648 \input{\Hy@driver.def}%
4649 \ifcase\Hy@VersionChecked
4650     \Hy@VersionCheck{\Hy@driver.def}%
4651 \fi
4652 \let\@unprocessedoptions\relax
4653 \Hy@RestoreCatcodes
4654 \Hy@DisableOption{tex4ht}%
4655 \Hy@DisableOption{pdftex}%
4656 \Hy@DisableOption{nativepdf}%
4657 \Hy@DisableOption{dvipdfm}%
4658 \Hy@DisableOption{dvipdfmx}%
4659 \Hy@DisableOption{dvipdfmx-outline-open}%
4660 \Hy@DisableOption{pdfmark}%
4661 \Hy@DisableOption{dvips}%
4662 \Hy@DisableOption{hypertex}%
4663 \Hy@DisableOption{vtex}%
4664 \Hy@DisableOption{vtexpdfmark}%
4665 \Hy@DisableOption{dviwindo}%

```



```

4666 \Hy@DisableOption{dvipsone}%
4667 \Hy@DisableOption{textures}%
4668 \Hy@DisableOption{latex2html}%
4669 \Hy@DisableOption{ps2pdf}%
4670 \Hy@DisableOption{xetex}%
4671 \Hy@DisableOption{driverfallback}%
4672 \Hy@DisableOption{customdriver}%
4673 \Hy@DisableOption{pdfversion}%
4674 }

```

Support for open outlines is enabled for XeTeX ≥ 0.9995 . I don't know, if older versions also support this. AFAIK older dvipdfmx versions will break, thus the switch cannot be turned on by default.

```

4675 \newif\ifHy@DvipdfmxOutlineOpen
4676 \ifxetex
4677   \ifdim\number\XeTeXversion\XeTeXrevision in<0.9995in %
4678   \else
4679     \chardef\SpecialDvipdfmxOutlineOpen\@ne
4680     \Hy@DvipdfmxOutlineOpenttrue
4681   \fi
4682 \fi
4683 \begingroup\expandafter\expandafter\expandafter\endgroup
4684 \expandafter\ifx\csname SpecialDvipdfmxOutlineOpen\endcsname\relax
4685 \else
4686   \ifnum\SpecialDvipdfmxOutlineOpen>\z@
4687     \Hy@DvipdfmxOutlineOpenttrue
4688   \fi
4689 \fi

```

15.4.2 Bookmarks

```

4690 \def\WriteBookmarks{0}
4691 \def\@bookmarkopenstatus#1{%
4692   \ifHy@bookmarksopen

```

The purpose of the \@firstofone-number-space-construct is that no \relax will be inserted by TeX before the \else:

```

4693   \ifnum#1<\expandafter\@firstofone\expandafter
4694     {\number\@bookmarkopenlevel} % explicit space
4695   \else
4696     -%
4697   \fi
4698 \else
4699   -%
4700 \fi
4701 }
4702 \ifHy@bookmarks
4703   \Hy@Info{Bookmarks ON}%
4704   \ifx\@pdfpagemode\@empty
4705     \def\@pdfpagemode{UseOutlines}%
4706   \fi
4707 \else
4708   \let\@bookmarkopenstatus\ltx@gobble
4709   \Hy@Info{Bookmarks OFF}%
4710   \Hy@AtEndOfPackage{%
4711     \global\let\ReadBookmarks\relax
4712     \global\let\WriteBookmarks\relax
4713   }%
4714   \ifx\@pdfpagemode\@empty

```

```

4715 \def\@pdfpagemode{UseNone}%
4716 \fi
4717 \fi
4718 \Hy@DisableOption{bookmarks}

Add wrapper for setting standard catcodes (babel's shorthands).
4719 \def\Hy@CatcodeWrapper#1{%
4720 \let\Hy@EndWrap\ltx@empty
4721 \def\TMP@EnsureCode##1##2{%
4722 \edef\Hy@EndWrap{%
4723 \Hy@EndWrap
4724 \catcode##1 \the\catcode##1\relax
4725 }%
4726 \catcode##1 ##2\relax
4727 }%
4728 \TMP@EnsureCode{10}{12}% ^^J
4729 \TMP@EnsureCode{33}{12}% !
4730 \TMP@EnsureCode{34}{12}% "
4731 \TMP@EnsureCode{36}{3}% $ (math)
4732 \TMP@EnsureCode{38}{4}% & (alignment)
4733 \TMP@EnsureCode{39}{12}% '
4734 \TMP@EnsureCode{40}{12}% (
4735 \TMP@EnsureCode{41}{12}% )
4736 \TMP@EnsureCode{42}{12}% *
4737 \TMP@EnsureCode{43}{12}% +
4738 \TMP@EnsureCode{44}{12}% ,
4739 \TMP@EnsureCode{45}{12}% -
4740 \TMP@EnsureCode{46}{12}% .
4741 \TMP@EnsureCode{47}{12}% /
4742 \TMP@EnsureCode{58}{12}% :
4743 \TMP@EnsureCode{59}{12}% ;
4744 \TMP@EnsureCode{60}{12}% <
4745 \TMP@EnsureCode{61}{12}% =
4746 \TMP@EnsureCode{62}{12}% >
4747 \TMP@EnsureCode{63}{12}% ?
4748 \TMP@EnsureCode{91}{12}% [
4749 \TMP@EnsureCode{93}{12}% ]
4750 \TMP@EnsureCode{94}{7}% ^ (superscript)
4751 \TMP@EnsureCode{95}{8}% _ (subscript)
4752 \TMP@EnsureCode{96}{12}% '
4753 \TMP@EnsureCode{124}{12}% |
4754 \TMP@EnsureCode{126}{13}% ~ (active)
4755 #1\relax
4756 \Hy@EndWrap
4757 }

```

\HyColor@UseColor expects a macro as argument. It contains the color specification.

```

4758 \Hy@AtBeginDocument{%
4759 \ifHy@ocgcolorlinks
4760 \kvsetkeys{Hyp}{colorlinks}%
4761 \ifHy@pdfa
4762 \Hy@Warning{%
4763 PDF/A: Optional Content Groups are prohibited,\MessageBreak
4764 using 'colorlinks' instead of 'ocgcolorlinks'%
4765 }%
4766 \Hy@ocgcolorlinksfalse
4767 \fi
4768 \fi

```

```

4769 \ifHy@ocgcolorlinks
4770 \else
4771   \Hy@DisableOption{ocgcolorlinks}%
4772 \fi
4773 \ifHy@colorlinks
4774   \def\@pdfborder{0 0 0}%
4775   \let\@pdfborderstyle\@empty
4776   \ifHy@typexml
4777   \else
4778     \Hy@CatcodeWrapper{%
4779       \RequirePackage{color}%
4780     }%
4781   \fi
4782   \def\Hy@colorlink#1{%
4783     \begingroup
4784     \HyColor@UseColor#1%
4785   }%
4786   \def\Hy@endcolorlink{\endgroup}%
4787   \Hy@Info{Link coloring ON}%
4788 \else
4789   \ifHy@frenchlinks
4790     \def\Hy@colorlink#1{\begingroup\fontshape{sc}\selectfont}%
4791     \def\Hy@endcolorlink{\endgroup}%
4792     \Hy@Info{French linking ON}%
4793   \else
4794     \def\Hy@colorlink#1{\begingroup}%
4795     \def\Hy@endcolorlink{\endgroup}%
4796     \Hy@Info{Link coloring OFF}%
4797   \fi
4798 \fi
4799 \Hy@DisableOption{colorlinks}%
4800 \Hy@DisableOption{frenchlinks}%
4801 \ifHy@texht
4802   \long\def\@firstoffive#1#2#3#4#5{#1}%
4803   \long\def\@secondoffive#1#2#3#4#5{#2}%
4804   \long\def\@thirdoffive#1#2#3#4#5{#3}%
4805   \long\def\@fourthoffive#1#2#3#4#5{#4}%
4806   \long\def\@fifthoffive#1#2#3#4#5{#5}%
4807   \providecommand*\@safe@activetrue{}%
4808   \providecommand*\@safe@activesfalse{}%
4809   \def\T@ref#1{%
4810     \Hy@safe@activetrue
4811     \expandafter\@setref\csname r@#1\endcsname\@firstoffive{#1}%
4812     \Hy@safe@activesfalse
4813   }%
4814   \def\T@pageref#1{%
4815     \Hy@safe@activetrue
4816     \expandafter\@setref\csname r@#1\endcsname\@secondoffive{#1}%
4817     \Hy@safe@activesfalse
4818   }%
4819 \else
4820   \ifHy@typexml
4821   \else
4822     \Hy@CatcodeWrapper{%
4823       \RequirePackage{nameref}[2012/07/28]%
4824     }%

```

```

4825 \fi
4826 \fi
4827 \DeclareRobustCommand\ref{%
4828 \ifstar\@refstar\T@ref
4829 }%
4830 \DeclareRobustCommand\pageref{%
4831 \ifstar\@pagerefstar\T@pageref
4832 }%
4833 % \ifclassloaded{memoir}{%
4834 % \ltx@ifundefined{@mem@titlerefno link}\ltx@secondoftwo{%
4835 % \ltx@ifundefined{@mem@titleref}\ltx@secondoftwo\ltx@firstoftwo
4836 % }%
4837 % }\ltx@secondoftwo
4838 % {%
4839 % \DeclareRobustCommand*{\nameref}{%
4840 % \ifstar\@mem@titlerefno link\@mem@titleref
4841 % }%
4842 % }{%
4843 \DeclareRobustCommand*{\nameref}{%
4844 \ifstar\@namerefstar\T@nameref
4845 }%
4846 % }%
4847 }
4848 \Hy@AtBeginDocument{%
4849 \ifHy@texht
4850 \else
4851 \Hy@CatcodeWrapper\ReadBookmarks
4852 \fi
4853 }
4854 \ifHy@backref
4855 \RequirePackage{backref}%
4856 \else
4857 \let\Hy@backout\@gobble
4858 \fi
4859 \Hy@DisableOption{backref}
4860 \Hy@DisableOption{pagebackref}
4861 \Hy@activeanchorfalse

```

16 User hypertext macros

We need to normalise all user commands taking a URL argument; Within the argument the following special definitions apply: `\#`, `\%`, `~` produce `#`, `%`, `~` respectively. for consistency `\~` produces `~` as well. At the *top level only* ie not within the argument of another command, you can use `#` and `%` unescaped, to produce themselves. even if, say, `#` is entered as `#` it will be converted to `\#` so it does not die if written to an aux file etc. `\#` will write as `#` locally while making `\specials`.

```

4862 \begingroup
4863 \endlinechar=-1 %
4864 \catcode'\^^A=14 %
4865 \catcode'\^^M\active
4866 \catcode'\%\active
4867 \catcode'\#\active
4868 \catcode'\_\active
4869 \catcode'\$\active
4870 \catcode'\&\active

```

```

4871 \gdef\hyper@normalise{^^A
4872 \begingroup
4873 \catcode'\^^M\active
4874 \def^^M{ }^^A
4875 \catcode'\%\active
4876 \let%\@percentchar
4877 \let%\@percentchar
4878 \catcode'\#\active
4879 \def#{\hyper@hash}^^A
4880 \def\#{\hyper@hash}^^A
4881 \@makeother\&^^A
4882 \edef&{\string&}^^A
4883 \edef&{\string&}^^A
4884 \edef\textunderscore{\string_}^^A
4885 \let_\textunderscore
4886 \catcode'\_\active
4887 \let_\textunderscore
4888 \let~\hyper@tilde
4889 \let~\hyper@tilde
4890 \let\textasciitilde\hyper@tilde
4891 \let\\\@backslashchar
4892 \edef$\string$}^^A
4893 \Hy@safe@activestrue
4894 \hyper@n@rmalise
4895 }^^A
4896 \catcode'\#=6 ^^A
4897 \gdef\Hy@ActiveCarriageReturn{^^M}^^A
4898 \gdef\hyper@n@rmalise#1#2{^^A
4899 \def\Hy@tempa{#2}^^A
4900 \ifx\Hy@tempa\Hy@ActiveCarriageReturn
4901 \ltx@ReturnAfterElseFi{^^A
4902 \hyper@@normalise{#1}^^A
4903 }^^A
4904 \else
4905 \ltx@ReturnAfterFi{^^A
4906 \hyper@@normalise{#1}{#2}^^A
4907 }^^A
4908 \fi
4909 }^^A
4910 \gdef\hyper@@normalise#1#2{^^A
4911 \edef\Hy@tempa{^^A
4912 \endgroup
4913 \noexpand#1{\Hy@RemovePercentCr#2%\^^M\@nil}^^A
4914 }^^A
4915 \Hy@tempa
4916 }^^A
4917 \gdef\Hy@RemovePercentCr#1%\^^M#2\@nil{^^A
4918 #1^^A
4919 \ifx\limits#2\limits
4920 \else
4921 \ltx@ReturnAfterFi{^^A
4922 \Hy@RemovePercentCr #2\@nil
4923 }^^A
4924 \fi
4925 }^^A
4926 \endgroup
4927 \providecommand*\hyper@chars{%

```

```

4928 \let\#\hyper@hash
4929 \let\%\@percentchar
4930 \Hy@safe@activetrue
4931 }

4932 \def\hyperlink#1#2{%
4933 \hyper@@link{}\{#1\}{#2}%
4934 }

4935 \def\Hy@VerboseLinkStart#1#2{%
4936 \ifHy@verbose
4937 \begingroup
4938 \Hy@safe@activetrue
4939 \xdef\Hy@VerboseGlobalTemp{(#1) '#2'}%
4940 \Hy@Info{Reference \Hy@VerboseGlobalTemp}%
4941 \xdef\Hy@VerboseGlobalTemp{%
4942 \Hy@VerboseGlobalTemp, %
4943 line \the\inputlineno
4944 }%
4945 \endgroup
4946 \let\Hy@VerboseLinkInfo\Hy@VerboseGlobalTemp
4947 \@onelevel@sanitize\Hy@VerboseLinkInfo
4948 \fi
4949 }

4950 \def\Hy@VerboseLinkInfo{<VerboseLinkInfo>}
4951 \def\Hy@VerboseLinkStop{%
4952 \ifHy@verbose
4953 \begingroup
4954 \edef\x{\endgroup
4955 \write\m@ne{%
4956 Package 'hyperref' Info: %
4957 End of reference \Hy@VerboseLinkInfo.%
4958 }%
4959 }%
4960 \x
4961 \fi
4962 }

4963 \def\Hy@VerboseAnchor#1{%
4964 \ifHy@verbose
4965 \begingroup
4966 \Hy@safe@activetrue
4967 \Hy@Info{Anchor '\HyperDestNameFilter{#1}'}%
4968 \endgroup
4969 \fi
4970 }

4971 \def\Hy@AllowHyphens{%
4972 \relax
4973 \ifhmode
4974 \penalty\@M
4975 \hskip\z@skip
4976 \fi
4977 }

4978 \DeclareRobustCommand*\href{[1][]{%
4979 \begingroup
4980 \setkeys{href}{#1}%
4981 \@ifnextchar\bgroup\Hy@href{\hyper@normalise\href@}%
4982 }

```

```

4983 \def\Hy@href#{%
4984   \hyper@normalise\href@
4985 }
4986 \begingroup
4987   \catcode'\$=6 %
4988   \catcode'\#=12 %
4989   \gdef\href@#1{\expandafter\href@split$1##\}%
4990   \gdef\href@split$1##$2##$3\\$4{%
4991     \hyper@@link{$1}{$2}{$3}{$4}%
4992   }
4993 }%
4994 \endgroup

```

Option ‘page’.

```

4995 \define@key{href}{page}{%
4996   \def\Hy@href@page{#1}%
4997 }
4998 \let\Hy@href@page\@empty
4999 \newcount\c@Hy@tempcnt
5000 \def\theHy@tempcnt{\the\c@Hy@tempcnt}
5001 \def\Hy@MakeRemoteAction{%
5002   \ifx\Hy@href@page\@empty
5003     \def\Hy@href@page{0}%
5004   \else
5005     \setcounter{Hy@tempcnt}{\Hy@href@page}%
5006     \ifnum\c@Hy@tempcnt<\@ne
5007       \Hy@Warning{%
5008         Invalid page number (\theHy@tempcnt)\MessageBreak
5009         for remote PDF file.\MessageBreak
5010         Using page 1%
5011       }%
5012       \def\Hy@href@page{0}%
5013     \else
5014       \global\advance\c@Hy@tempcnt\m@ne
5015       \edef\Hy@href@page{\theHy@tempcnt}%
5016     \fi
5017   \fi

```

If a next action is set, then also a new window should be opened. Otherwise AR reclaims that it closes the current file with discarding the next actions.

```

5018   \ifx\Hy@href@nextactionraw\@empty
5019   \else
5020     \Hy@pdfnewwindowsettrue
5021     \Hy@pdfnewwindowtrue
5022   \fi
5023 }

```

Option ‘pdfremotestartview’.

```

5024 \define@key{href}{pdfremotestartview}{%
5025   \setkeys{Hyp}{pdfremotestartview={#1}}%
5026 }

```

Option ‘pdfnewwindow’.

```

5027 \let\KV@href@pdfnewwindow\KV@Hyp@pdfnewwindow
5028 \let\KV@href@pdfnewwindow@default\KV@Hyp@pdfnewwindow@default

```

Option ‘ismap’.

```

5029 \newif\ifHy@href@ismap
5030 \define@key{href}{ismap}[true]{%

```

```

5031 \ltx@ifundefined{Hy@href@ismap#1}{%
5032   \Hy@Error{%
5033     Invalid value (#1) for key 'ismap'.\MessageBreak
5034     Permitted values are 'true' or 'false'.\MessageBreak
5035     Ignoring 'ismap'%
5036   } \@ehc
5037 }{%
5038   \csname Hy@href@ismap#1\endcsname
5039 }%
5040 }

```

Option ‘nextactionraw’.

```

5041 \let\Hy@href@nextactionraw\@empty
5042 \define@key{href}{nextactionraw}{%
5043   \edef\Hy@href@nextactionraw{#1}%
5044   \ifx\Hy@href@nextactionraw\@empty
5045     \else
5046       \Hy@Match\Hy@href@nextactionraw{%
5047         ^(\HyPat@ObjRef/|<.*[/S[/].+>>|%
5048         \[( ?\HyPat@ObjRef/|<.*[/S[/].+>>)+ ?)]$%
5049       }%
5050       \Hy@Warning{Invalid value for 'nextactionraw':\MessageBreak
5051         \Hy@href@nextactionraw\MessageBreak
5052         The action is discarded%
5053       }%
5054     }%
5055     \ifx\Hy@href@nextactionraw\@empty
5056       \else
5057         \edef\Hy@href@nextactionraw{/Next \Hy@href@nextactionraw}%
5058       \fi
5059     \fi
5060 }
5061 \def\HyPat@ObjRef/{.+}

```

Load package `url.sty` and save the meaning of the original `\url` in `\nolinkurl`.

```

5062 \RequirePackage{url}
5063 \let\HyOrg@url\url
5064 \def\Hurl{\begingroup \Url}
5065 \DeclareRobustCommand*\nolinkurl{\hyper@normalise\nolinkurl@}
5066 \def\nolinkurl@#1{\Hurl{#1}}
5067 \DeclareRobustCommand*\url{\hyper@normalise:url@}
5068 \def\url@#1{\hyper@linkurl{\Hurl{#1}}{#1}}

5069 \DeclareRobustCommand*\hyperimage{\hyper@normalise\hyper@image}
5070 \providecommand\hyper@image[2]{#2}

5071 \def\hypertarget#1#2{%
5072   \ifHy@nesting
5073     \hyper@@anchor{#1}{#2}%
5074   \else
5075     \hyper@@anchor{#1}{\relax}#2%
5076   \fi
5077 }

```

`\hyperref` is more complicated, as it includes the concept of a category of link, used to make the name. This is not really used in this package. `\hyperdef` sets up an anchor in the same way. They each have three parameters of category, linkname, and marked text, and `\hyperref` also has a first parameter of URL. If there is an optional first parameter to `\hyperdef`, it is the name of a \LaTeX label

which can be used in a short form of `\hyperref` later, to avoid remembering the name and category.

```

5078 \DeclareRobustCommand*{\hyperref}{%
5079   \@ifnextchar[{\Hy@babelnormalise\label@hyperref}\@hyperref
5080 }
5081 \def\Hy@babelnormalise#1[#2]{%
5082   \begingroup
5083     \Hy@safe@activetrue
5084     \edef\Hy@tempa{%
5085       \endgroup
5086       \noexpand#1[#2]}%
5087   }%
5088   \Hy@tempa
5089 }
5090 \def\@hyperref{\hyper@normalise\@hyperref}
5091 \def\@hyperref#1#2#3{%
5092   \edef\ref@one{\ifx\#2\else#2.\fi#3}%
5093   \expandafter\tryhyper@link\ref@one\{#1}%
5094 }
5095 \def\tryhyper@link#1\#2{%
5096   \hyper@@link{#2}{#1}%
5097 }

5098 \def\hyperdef{\@ifnextchar[{\label@hyperdef}\@hyperdef}]
5099 \def\@hyperdef#1#2#3{% category, name, text
5100   \ifx\#1\%
5101     \def\Hy@AnchorName{#2}%
5102   \else
5103     \def\Hy@AnchorName{#1.#2}%
5104   \fi
5105   \ifHy@nesting
5106     \expandafter\hyper@@anchor\expandafter{\Hy@AnchorName}{#3}%
5107   \else
5108     \expandafter\hyper@@anchor\expandafter{\Hy@AnchorName}{\relax}#3%
5109   \fi
5110 }

```

We also have a need to give a L^AT_EX *label* to a hyper reference, to ease the pain of referring to it later.

```

5111 \def\label@hyperref[#1]{%
5112   \expandafter\label@@hyperref\csname r@#1\endcsname{#1}%
5113 }%
5114 \def\label@@hyperref#1#2#3{%
5115   \ifx#1\relax
5116     \protect\G@refundefinedtrue
5117     \@latex@warning{%
5118       Hyper reference ‘#2’ on page \thepage \space undefined%
5119     }%
5120     \begingroup
5121       #3%
5122     \endgroup
5123   \else
5124     \hyper@@link{\expandafter\@fifthoffive#1}%
5125     {\expandafter\@fourthoffive#1\@empty\@empty}{#3}%
5126   \fi
5127 }
5128 \def\label@hyperdef[#1]#2#3#4{% label name, category, name,
5129                               % anchor text

```

```

5130 \@bsphack
5131 \ifx\|#2\%
5132   \def\Hy@AnchorName{#3}%
5133 \else
5134   \def\Hy@AnchorName{#2.#3}%
5135 \fi
5136 \if@filesw
5137   \protected@write\@auxout{}\{%
5138     \string\newlabel{#1}{\{}{\}\{\}\Hy@AnchorName}{\}}%
5139   }%
5140 \fi
5141 \@esphack
5142 \ifHy@nesting
5143   \expandafter\hyper@@anchor\expandafter{\Hy@AnchorName}{#4}%
5144 \else
5145   \expandafter\hyper@@anchor\expandafter{\Hy@AnchorName}{\relax}#4%
5146 \fi
5147 }

```

16.1 Link box support for XeTeX

```

5148 \newdimen\XeTeXLinkMargin
5149 \setlength{\XeTeXLinkMargin}{2pt}
5150 \ifxetex
5151   \font\XeTeXLink@font=pzdr at 1sp\relax
5152   \newcommand*\XeTeXLink@space{\%
5153     \begingroup
5154       \XeTeXLink@font
5155       \@xxxii
5156     \endgroup
5157   }%
5158   \newcommand{\XeTeXLinkBox}[1]{%
5159     \begingroup
5160       \leavevmode
5161       \sbox\z@{#1}%
5162       \begingroup
5163         \dimen@=\dp\z@
5164         \advance\dimen@\XeTeXLinkMargin
5165         \setbox\tw@=\llap{%
5166           \hb@xt@\XeTeXLinkMargin{%
5167             \lower\dimen@\hbox{\XeTeXLink@space}%
5168             \hss
5169           }%
5170         }%
5171         \dp\tw@=\dp\z@
5172         \ht\tw@=\ht\z@
5173         \copy\tw@
5174       \endgroup
5175       \copy\z@
5176       \dimen@=\ht\z@
5177       \advance\dimen@\XeTeXLinkMargin
5178       \setbox\tw@=\rlap{%
5179         \hb@xt@\XeTeXLinkMargin{%
5180           \hss
5181           \raise\dimen@\hbox{\XeTeXLink@space}%
5182         }%
5183       }%

```

```

5184 \dp\tw@=\dp\z@
5185 \ht\tw@=\ht\z@
5186 \copy\tw@
5187 \endgroup
5188 }%
5189 \else
5190 \newcommand*{\XeTeXLinkBox}[1]{%
5191 \begingroup
5192 \leavevmode
5193 \sbox\z@{#1}%
5194 \copy\z@
5195 \endgroup
5196 }%
5197 \fi

```

17 Underlying basic hypertext macros

Links have an optional type, a filename (possibly a URL), an internal name, and some marked text. (Caution: the internal name may contain babel shorthand characters.) If the second parameter is empty, its an internal link, otherwise we need to open another file or a URL. A link start has a type, and a URL.

```

5198 \def\hyper@@link{\let\Hy@reserved@a\relax
5199 \@ifnextchar{\hyper@link@}{\hyper@link@[link]}}%
5200 }
5201 % #1: type
5202 % #2: URL
5203 % #3: destination name
5204 % #4: text
5205 \def\hyper@link@[#1]#2#3#4{%
5206 \ltx@ifempty{#4}{% link text
5207 \Hy@Warning{Suppressing empty link}%
5208 }{%
5209 \begingroup
5210 \protected@edef\Hy@tempa{#2}%
5211 \edef\Hy@tempb{#3}%
5212 \ifx\Hy@tempa\ltx@empty
5213 \toks@{%
5214 \endgroup
5215 \hyper@link{#1}%
5216 }%
5217 \else
5218 \toks@{%
5219 \endgroup
5220 \expandafter\hyper@readexternallink#2\{\{#1}%
5221 }%
5222 \fi
5223 \Hy@safe@activestrue
5224 \Hy@safe@activesfalse
5225 \toks@\expandafter{%
5226 \the\expandafter\toks@
5227 \expandafter{\Hy@tempb}{#4}%
5228 }%
5229 \the\toks@
5230 }%
5231 }

```

The problem here is that the first (URL) parameter may be a local file: reference (in which case some browsers treat it differently) or a genuine URL, in which case

we'll have to activate a real Web browser. Note that a simple name is also a URL, as that is interpreted as a relative file name. We have to worry about # signs in a local file as well.

```

5232 \def\hyper@readexternallink#1\\#2#3#4{%
5233   \begingroup
5234   \let\\\relax
5235   \expandafter\endgroup
5236   \expandafter\@hyper@@readexternallink#1\\#{#2}{#3}{#4}%
5237 }
5238 \def\@hyper@@readexternallink#1\\#2#3#4{%

```

Parameters are:

1. The URL or file name
2. The type
3. The internal name
4. The link string

We need to get the 1st parameter properly expanded, so we delimit the arguments rather than passing it inside a group.

```

5239   \@hyper@readexternallink{#2}{#3}{#4}#1::\#{#1}%
5240 }

```

Now (potentially), we are passed: 1) The link type 2) The internal name, 3) the link string, 4) the URL type (http, mailto, file etc), 5) the URL details 6) anything after a real : in the URL 7) the whole URL again

```

5241 \def\@pdftempwordfile{file}%
5242 \def\@pdftempwordrun{run}%
5243 \def\@hyper@readexternallink#1#2#3#4:#5:#6\\#7{%

```

If there are no colons at all (#6 is blank), its a local file; if the URL type (#4) is blank, its probably a Mac filename, so treat it like a file: URL. The only flaw is if its a relative Mac path, with several colon-separated elements — then we lose. Such names must be prefixed with an explicit dvi:

```

5244   \ifx\\#6\\%
5245     \@hyper@linkfile file:#7\\#{#3}{#2}{#7}%
5246   \else
5247     \ifx\\#4\\%
5248       \@hyper@linkfile file:#7\\#{#3}{#2}{#7}%
5249     \else

```

If the URL type is 'file', pass it for local opening

```

5250     \def\@pdftempa{#4}%
5251     \ifx\@pdftempa\@pdftempwordfile
5252       \@hyper@linkfile#7\\#{#3}{#2}{#7}%
5253     \else

```

if it starts 'run:', its to launch an application.

```

5254     \ifx\@pdftempa\@pdftempwordrun
5255       \ifHy@pdfa
5256         \Hy@Error{%
5257           PDF/A: Launch action is prohibited%
5258         }\@ehc
5259       \begingroup
5260       \leavevmode
5261       #2%

```

```

5262         \endgroup
5263     \else
5264         \@hyper@launch#7\{\#3}\#2}%
5265     \fi
5266 \else

```

otherwise its a URL

```

5267         \hyper@linkurl{\#3}\#7\ifx\#2\else\hyper@hash#2\fi}%
5268     \fi
5269 \fi
5270 \fi
5271 \fi
5272 }

```

By default, turn run: into file:

```

5273 \def\@hyper@launch run:#1\#2#3{% filename, anchor text, linkname
5274 \hyper@linkurl{\#2}%
5275 \Hy@linkfileprefix
5276 #1%
5277 \ifx\#3\%
5278 \else
5279 \hyper@hash
5280 #3%
5281 \fi
5282 }%
5283 }

```

D P Story <story@uakron.edu> pointed out that relative paths starting .. fell over. Switched to using \filename@parse to solve this.

```

5284 \def\@hyper@linkfile file:#1\#2#3#4{%
5285 %file url,link string, name, original uri
5286 \filename@parse{\#1}%
5287 \ifx\filename@ext\relax
5288 \edef\filename@ext{\XR@ext}%
5289 \fi
5290 \def\use@file{\filename@area\filename@base.\filename@ext}%
5291 \Hy@ifStringEndsWith\filename@ext\XR@ext{%
5292 \hyper@linkfile{\#2}\use@file\#3}%
5293 }{%
5294 \ifx\@baseurl\empty
5295 \hyper@linkurl{\#2}%
5296 #4\ifx\#3\else\hyper@hash#3\fi
5297 }%
5298 \else
5299 \hyper@linkurl{\#2}\use@file\ifx\#3\else\hyper@hash#3\fi}%
5300 \fi
5301 }%
5302 }

5303 \def\Hy@ifStringEndsWith#1#2{%
5304 \begingroup
5305 \edef\x{\#1}%
5306 \@onelevel@sanitize\x
5307 \edef\x{.\x}%
5308 \edef\y{\#2}%
5309 \@onelevel@sanitize\y
5310 \edef\y{.\y}%
5311 \expandafter\def\expandafter\z\expandafter##\expandafter1\y##2\@nil{%
5312 \endgroup

```

```

5313 \ifx\relax##2\relax
5314 \expandafter\ltx@secondoftwo
5315 \else
5316 \expandafter\ltx@firstoftwo
5317 \fi
5318 }%
5319 \expandafter\expandafter\expandafter\z\expandafter\x\y\@nil
5320 }

5321 \def\Hy@StringLocalhost{localhost}
5322 \@onelevel@sanitize\Hy@StringLocalhost
5323 \def\Hy@CleanupFile#1{%
5324 \edef#1{#1}%
5325 \expandafter\Hy@@CleanupFile#1\hbox{//\hbox\@nil{#1}%
5326 }
5327 \def\Hy@@CleanupFile#1//#2/#3\hbox#4\@nil#5{%
5328 \begingroup
5329 \toks@{\endgroup}%
5330 \def\x{#1}%
5331 \ifx\x\@empty
5332 \def\x{#2}%
5333 \ifx\x\@empty
5334 \toks@{\endgroup\def#5{/#3}}%
5335 \else
5336 \@onelevel@sanitize\x
5337 \ifx\x\Hy@StringLocalhost
5338 \toks@{\endgroup\def#5{/#3}}%
5339 \fi
5340 \fi
5341 \fi
5342 \the\toks@
5343 }

```

Anchors have a name, and marked text. We have to be careful with the marked text, as if we break off part of something to put a `\special` around it, all hell breaks loose. Therefore, we check the category code of the first token, and only proceed if its safe. Tanmoy sorted this out.

A curious case arises if the original parameter was in braces. That means that `#2` comes here a multiple letters, and the `noexpand` just looks at the first one, putting the rest in the output. Yuck.

```

5344 \long\def\hyper@@anchor#1#2{\@hyper@@anchor#1\relax#2\relax}
5345 \long\def\@hyper@@anchor#1\relax#2#3\relax{%
5346 \ifx\#1\%
5347 #2\Hy@Warning{Ignoring empty anchor}%
5348 \else
5349 \def\anchor@spot{#2#3}%
5350 \let\put@me@back\@empty
5351 \ifx\relax#2\relax
5352 \else
5353 \ifHy@nesting
5354 \else
5355 \ifcat a\noexpand#2\relax
5356 \else
5357 \ifcat 0\noexpand#2 \relax
5358 \else
5359 % \typeout{Anchor start is not alphanumeric %
5360 % on input line\the\inputlineno%
5361 % }%

```

```

5362         \let\anchor@spot\@empty
5363         \def\put@me@back{#2#3}%
5364     \fi
5365 \fi
5366 \fi
5367 \fi
5368 \ifHy@activeanchor
5369     \anchor@spot
5370 \else
5371     \hyper@anchor{#1}%
5372 \fi
5373 \expandafter\put@me@back
5374 \fi
5375 \let\anchor@spot\@empty
5376 }
5377 \let\anchor@spot\ltx@empty

```

18 Option ‘destlabel’

```

5378 \ifHy@destlabel

\hyper@newdestlabel

5379 \def\hyper@newdestlabel#1#2{%
5380     \begingroup
5381     \Hy@safe@activetrue
5382     \edef\x{\endgroup
5383         \noexpand\@newl@bel{HyDL}{#1}{#2}%
5384     }%
5385     \x
5386 }%

\hyper@destlabel@hook

5387 \providecommand*{\hyper@destlabel@hook}{}%

\Hy@DestRename

5388 \newcommand*{\Hy@DestRename}[2]{%
5389     \ltx@ifundefined{HyDL!#1}{%
5390         \begingroup
5391         \Hy@safe@activetrue
5392         \edef\dest@name{#1}%
5393         \edef\label@name{#2}%
5394         \hyper@destlabel@hook
5395         \Hy@IsNotEmpty{dest@name}{%
5396             \Hy@IsNotEmpty{label@name}{%
5397                 \global\expandafter
5398                 \let\csname HyDL!#1\endcsname\ltx@empty
5399                 \if@files
5400                     \protected@write\@auxout{}{%
5401                         \string\hyper@newdestlabel
5402                         {#1}%
5403                         {\label@name}%
5404                     }%
5405                 \fi
5406             }%
5407         }%
5408         \endgroup
5409     }{}%

```

```

5410 }%

\HyperDestRename
5411 \newcommand*{\HyperDestRename}[2]{%
5412   \AtBeginDocument{%
5413     \Hy@DestRename{#1}{#2}%
5414   }%
5415 }%
5416 \AtBeginDocument{%
5417   \let\HyperDestRename\Hy@DestRename
5418 }%

\Hy@IsNotEmpty
5419 \def\Hy@IsNotEmpty#1{%
5420   \ltx@ifundefined{#1}\ltx@gobble{%
5421     \expandafter\ifx\csname#1\endcsname\ltx@empty
5422       \expandafter\ltx@gobble
5423     \else
5424       \expandafter\ltx@firstofone
5425     \fi
5426   }%
5427 }%

5428 \ltx@GlobalAppendToMacro\label@hook{%
5429   \HyperDestRename\@currentHref\label@name
5430 }%

\HyperDestLabelReplace
5431 \def\HyperDestLabelReplace#1{%
5432   \ltx@ifundefined{HyDL@#1}{%
5433     #1%
5434   }{%
5435     \csname HyDL@#1\endcsname
5436   }%
5437 }%

\HyperDestNameFilter
5438 \let\HyperDestNameFilter\HyperDestLabelReplace

5439 \else

\hyper@newdestlabel
5440 \let\hyper@newdestlabel\ltx@gobbletwo

\HyperDestLabelReplace
5441 \let\HyperDestLabelReplace\ltx@firstofone

\HyperDestRename
@gobbletwo
5442 \fi
5443 \Hy@DisableOption{destlabel}

Provide a dummy default definition of \hyper@newdestlabel inside the .aux
files.
5444 \AddLineBeginAux{%
5445   \string\providecommand\string\hyper@newdestlabel[2]{}%
5446 }

```


19 Compatibility with the *L^AT_EX2html* package

Map our macro names on to Nikos', so that documents prepared for that system will work without change.

Note, however, that the whole complicated structure for segmenting documents is not supported; it is assumed that the user will load `html.sty` first, and then `hyperref.sty`, so that the definitions in `html.sty` take effect, and are then overridden in a few circumstances by this package.

```
5447 \let\htmladdimg\hyperimage
5448 \def\htmladdnormallink#1#2{\href{#2}{#1}}
5449 \def\htmladdnormallinkfoot#1#2{\href{#2}{#1}\footnote{#2}}
5450 \def\htmlref#1#2{% anchor text, label
5451   \label@hyperref[{#2}]{#1}%
5452 }
```

This is really too much. The *L^AT_EX2html* package defines its own `\hyperref` command, with a different syntax. Was this always here? Its weird, anyway. We interpret it in the 'printed' way, since we are about fidelity to the page.

```
5453 \def\@@latextohtmlX{%
5454   \let\hhyperref\hyperref
5455   \def\hyperref##1##2##3##4{% anchor text for HTML
5456     % text to print before label in print
5457     % label
5458     % post-label text in print
5459     ##2\ref{##4}##3%
5460   }%
5461 }
```

20 Forms creation

Allow for creation of PDF or HTML forms. The effects here are limited somewhat by the need to support both output formats, so it may not be as clever as something which only wants to make PDF forms.

I (Sebastian) could not have started this without the encouragement of T V Raman.

20.1 Field flags

The field flags are organized in a bit set.

```
5462 \RequirePackage{bitset}
```

Each flag has a option name, an `\if` switch, and a bit position. The default is always 'false', the flag is clear. This is also the default of the switch created by `\newif`.

The names of the flags in the PDF specification (1.7) are used as lowercase option names.

```
\HyField@NewFlag #1: type: F annot flags, Ff field flags
#2: PDF name
#3: PDF position
5463 \def\HyField@NewFlag#1#2{%
5464   \lowercase{\HyField@NewOption{#2}}%
5465   \lowercase{\HyField@NewBitsetFlag{#2}}{#2}{#1}%
5466 }
```

```

\HyField@NewFlagOnly
5467 \def\HyField@NewFlagOnly#1#2{%
5468   \lowercase{\HyField@NewBitsetFlag{#2}}{#2}{#1}%
5469 }

\HyField@NewOption #1: option name
5470 \def\HyField@NewOption#1{%
5471   \expandafter\newif\csname ifFld@#1\endcsname
5472   \define@key{Field}{#1}[true]{%
5473     \lowercase{\Field@boolkey{##1}}{#1}%
5474   }%
5475 }

\HyField@NewBitsetFlag Package 'bitset' uses zero based positions, the PDF specification starts with one.
#1: option
#2: PDF name
#3: type: F annot flags, Ff field flags
#4: PDF position
5476 \def\HyField@NewBitsetFlag#1#2#3#4{%
5477   \begingroup
5478     \count@=#4\relax
5479     \advance\count@\m@ne
5480     \def\x##1{%
5481       \endgroup
5482       \expandafter\def\csname HyField@#3@#1\endcsname{##1}%
5483       \expandafter\ifx\csname HyField@#3@#1\endcsname\relax
5484         \expandafter\edef\csname HyField@#3@#1\endcsname{%
5485           (\number#4) #2%
5486         }%
5487       \else
5488         \expandafter\edef\csname HyField@#3@#1\endcsname{%
5489           \csname HyField@#3@#1\endcsname
5490           /#2%
5491         }%
5492       \fi
5493     }%
5494     \expandafter\x\expandafter{\the\count@}%
5495 }

\HyField@UseFlag The bit set is HyField@#1
5496 \def\HyField@UseFlag#1#2{%
5497   \lowercase{\HyField@@UseFlag{#2}}{#1}%
5498 }

\HyField@@UseFlag
5499 \def\HyField@@UseFlag#1#2{%
5500   \bitsetSetValue{HyField@#2}{%
5501     \csname HyField@#2@#1\endcsname
5502   }{%
5503     \csname ifFld@#1\endcsname 1\else 0\fi
5504   }%
5505 }

\HyField@SetFlag The bit set is HyField@#1
5506 \def\HyField@SetFlag#1#2{%
5507   \lowercase{\HyField@@SetFlag{#2}}{#1}%
5508 }

```

```

\HyField@@SetFlag
5509 \def\HyField@@SetFlag#1#2{%
5510 \bitsetSetValue{HyField@#2}{%
5511 \csname HyField@#2@#1\endcsname
5512 }{1}%
5513 }

\HyField@PrintFlags
5514 \def\HyField@PrintFlags#1#2{%
5515 \ifHy@verbose
5516 \begingroup
5517 \let\Hy@temp\@empty
5518 \let\MessageBreak\relax
5519 \expandafter\@for\expandafter\x\expandafter:\expandafter=%
5520 \bitsetGetSetBitList{HyField@#1}\do{%
5521 \edef\Hy@temp{%
5522 \Hy@temp
5523 \csname HyField@#1@\x\endcsname\MessageBreak
5524 }%
5525 }%
5526 \edef\x{\endgroup
5527 \noexpand\Hy@Info{%
5528 Field flags: %
5529 \expandafter\ifx\@car#1\@nil S\else/\fi
5530 #1 %
5531 \bitsetGetDec{HyField@#1} %
5532 (0x\bitsetGetHex{HyField@#1}{32})\MessageBreak
5533 \Hy@temp
5534 for #2%
5535 }%
5536 }\x
5537 \fi
5538 }

```

20.1.1 Declarations of field flags

“Table 8.70 Field flags common to all field types”

```

5539 \HyField@NewFlag{Ff}{ReadOnly}{1}
5540 \HyField@NewFlag{Ff}{Required}{2}
5541 \HyField@NewFlag{Ff}{NoExport}{3}

```

“Table 8.75 Field flags specific to button fields”

```

5542 \HyField@NewFlag{Ff}{NoToggleToOff}{15}
5543 \HyField@NewFlag{Ff}{Radio}{16}
5544 \HyField@NewFlag{Ff}{Pushbutton}{17}
5545 \HyField@NewFlag{Ff}{RadiosInUnison}{26}

```

“Table 8.77 Field flags specific to text fields”

```

5546 \HyField@NewFlag{Ff}{Multiline}{13}
5547 \HyField@NewFlag{Ff}{Password}{14}
5548 \HyField@NewFlag{Ff}{FileSelect}{21}% PDF 1.4
5549 \HyField@NewFlag{Ff}{DoNotSpellCheck}{23}% PDF 1.4
5550 \HyField@NewFlag{Ff}{DoNotScroll}{24}% PDF 1.4
5551 \HyField@NewFlag{Ff}{Comb}{25}% PDF 1.4
5552 \HyField@NewFlag{Ff}{RichText}{26}% PDF 1.5

```

“Table 8.79 field flags specific to choice fields”

```

5553 \HyField@NewFlag{Ff}{Combo}{18}

```

```

5554 \HyField@NewFlag{Ff}{Edit}{19}
5555 \HyField@NewFlag{Ff}{Sort}{20}
5556 \HyField@NewFlag{Ff}{MultiSelect}{22}% PDF 1.4
5557 % \HyField@NewFlag{Ff}{DoNotSpellCheck}{23}% PDF 1.4
5558 \HyField@NewFlag{Ff}{CommitOnSelChange}{27}% PDF 1.5

```

Signature fields are not supported.

Until 6.76i hyperref uses field option ‘combo’ to set three flags ‘Combo’, ‘Edit’, and ‘Sort’. Option ‘popdown’ sets flag ‘Combo’ only.

```

5559 \newif\ifFld@popdown
5560 \define@key{Field}{popdown}[true]{%
5561 \lowercase{\Field@boolkey{#1}}{popdown}%
5562 }

```

Annotation flags. The form objects are widget annotations. There are two flags for readonly settings, the one in the annotation flags is ignored, instead the other in the field flags is used.

Flag **Print** is not much useful, because hyperref do not use the appearance entry of the annotations for most fields.

```

5563 \HyField@NewFlag{F}{Invisible}{1}
5564 \HyField@NewFlag{F}{Hidden}{2}% PDF 1.2
5565 \HyField@NewFlag{F}{Print}{3}% PDF 1.2
5566 \HyField@NewFlag{F}{NoZoom}{4}% PDF 1.2
5567 \HyField@NewFlag{F}{NoRotate}{5}% PDF 1.3
5568 \HyField@NewFlag{F}{NoView}{6}% PDF 1.3
5569 \HyField@NewFlag{F}{Locked}{8}% PDF 1.4
5570 \HyField@NewFlag{F}{ToggleNoView}{9}% PDF 1.5
5571 \HyField@NewFlag{F}{LockedContents}{10}% PDF 1.7

5572 \ifHy@pdfa
5573 \def\HyField@PDFAFflagWarning#1#2{%
5574 \Hy@Warning{%
5575 PDF/A: Annotation flag ‘#1’ must\MessageBreak
5576 be set to ‘#2’%
5577 }%
5578 }%
5579 \Fld@invisiblefalse
5580 \def\Fld@invisibletrue{%
5581 \HyField@PDFAFflagWarning{invisible}{false}%
5582 }%
5583 \Fld@hiddenfalse
5584 \def\Fld@hiddentrue{%
5585 \HyField@PDFAFflagWarning{hidden}{false}%
5586 }%
5587 \Fld@printtrue
5588 \def\Fld@printfalse{%
5589 \HyField@PDFAFflagWarning{print}{true}%
5590 }%
5591 \Fld@nozoomtrue
5592 \def\Fld@nozoomfalse{%
5593 \HyField@PDFAFflagWarning{nozoom}{true}%
5594 }%
5595 \Fld@norotatetrue
5596 \def\Fld@norotatefalse{%
5597 \HyField@PDFAFflagWarning{norotate}{true}%
5598 }%
5599 \Fld@noviewfalse
5600 \def\Fld@noviewtrue{%

```

```

5601 \HyField@PDFAFIWarning{noview}{false}%
5602 }%
5603 \fi

```

Submit flags. Flag 1 Include/Exclude is not supported, use option noexport instead.

```

5604 \HyField@NewFlag{Submit}{IncludeNoValueFields}{2}
5605 \HyField@NewFlagOnly{Submit}{ExportFormat}{3}
5606 \HyField@NewFlag{Submit}{GetMethod}{4}
5607 \HyField@NewFlag{Submit}{SubmitCoordinates}{5}
5608 \HyField@NewFlagOnly{Submit}{XFDF}{6}
5609 \HyField@NewFlag{Submit}{IncludeAppendSaves}{7}
5610 \HyField@NewFlag{Submit}{IncludeAnnotations}{8}
5611 \HyField@NewFlagOnly{Submit}{SubmitPDF}{9}
5612 \HyField@NewFlag{Submit}{CanonicalFormat}{10}
5613 \HyField@NewFlag{Submit}{ExclNonUserAnnots}{11}
5614 \HyField@NewFlag{Submit}{ExclFKey}{12}
5615 \HyField@NewFlag{Submit}{EmbedForm}{14}

5616 \define@key{Field}{export}{%
5617 \lowercase{\def\Hy@temp{#1}}%
5618 \@ifundefined{Fld@export@\Hy@temp}{%
5619 \onelevel@sanitize\Hy@temp
5620 \Hy@Error{%
5621 Unknown export format '\Hy@temp'.\MessageBreak
5622 Known formats are 'FDF', 'HTML', 'XFDF', and 'PDF'%
5623 }\@ehc
5624 }{%
5625 \let\Fld@export\Hy@temp
5626 }%
5627 }
5628 \def\Fld@export{fdf}
5629 \@namedef{Fld@export@fdf}{0}%
5630 \@namedef{Fld@export@html}{1}%
5631 \@namedef{Fld@export@xfdf}{2}%
5632 \@namedef{Fld@export@pdf}{3}%

```

20.1.2 Set submit flags

\HyField@FlagsSubmit

```

5633 \def\HyField@FlagsSubmit{%
5634 \bitsetReset{HyField@Submit}%
5635 \ifcase\@nameuse{Fld@export@\Fld@export} %
5636 % FDF
5637 \HyField@UseFlag{Submit}{IncludeNoValueFields}%
5638 \HyField@UseFlag{Submit}{SubmitCoordinates}%
5639 \HyField@UseFlag{Submit}{IncludeAppendSaves}%
5640 \HyField@UseFlag{Submit}{IncludeAnnotations}%
5641 \HyField@UseFlag{Submit}{CanonicalFormat}%
5642 \HyField@UseFlag{Submit}{ExclNonUserAnnots}%
5643 \HyField@UseFlag{Submit}{ExclFKey}%
5644 \HyField@UseFlag{Submit}{EmbedForm}%
5645 \or % HTML
5646 \HyField@SetFlag{Submit}{ExportFormat}%
5647 \HyField@UseFlag{Submit}{IncludeNoValueFields}%
5648 \HyField@UseFlag{Submit}{GetMethod}%
5649 \HyField@UseFlag{Submit}{SubmitCoordinates}%
5650 \HyField@UseFlag{Submit}{CanonicalFormat}%

```

```

5651 \or % XFDF
5652   \HyField@SetFlag{Submit}{XFDF}%
5653   \HyField@UseFlag{Submit}{IncludeNoValueFields}%
5654   \HyField@UseFlag{Submit}{SubmitCoordinates}%
5655   \HyField@UseFlag{Submit}{CanonicalFormat}%
5656 \or % PDF
5657   \HyField@SetFlag{Submit}{SubmitPDF}%
5658   \HyField@UseFlag{Submit}{GetMethod}%
5659 \fi
5660 \HyField@PrintFlags{Submit}{submit button field}%
5661 \bitsetIsEmpty{HyField@Submit}{%
5662   \let\Fld@submitflags\ltx@empty
5663 }{%
5664   \edef\Fld@submitflags{/Flags \bitsetGetDec{HyField@Submit}}%
5665 }%
5666 }

```

20.1.3 Set annot flags in fields

\HyField@FlagsAnnot

```

5667 \def\HyField@FlagsAnnot#1{%
5668   \bitsetReset{HyField@F}%
5669   \HyField@UseFlag{F}{Invisible}%
5670   \HyField@UseFlag{F}{Hidden}%
5671   \HyField@UseFlag{F}{Print}%
5672   \HyField@UseFlag{F}{NoZoom}%
5673   \HyField@UseFlag{F}{NoRotate}%
5674   \HyField@UseFlag{F}{NoView}%
5675   \HyField@UseFlag{F}{Locked}%
5676   \HyField@UseFlag{F}{ToggleNoView}%
5677   \HyField@UseFlag{F}{LockedContents}%
5678   \HyField@PrintFlags{F}{#1}%
5679   \bitsetIsEmpty{HyField@F}{%
5680     \let\Fld@annotflags\ltx@empty
5681   }{%
5682     \edef\Fld@annotflags{/F \bitsetGetDec{HyField@F}}%
5683   }%
5684 }

```

20.1.4 Pushbutton field

\HyField@FlagsPushButton

```

5685 \def\HyField@FlagsPushButton{%
5686   \HyField@FlagsAnnot{push button field}%
5687   \bitsetReset{HyField@Ff}%
5688   \HyField@UseFlag{Ff}{ReadOnly}%
5689   \HyField@UseFlag{Ff}{Required}%
5690   \HyField@UseFlag{Ff}{NoExport}%
5691   \HyField@SetFlag{Ff}{PushButton}%
5692   \HyField@PrintFlags{Ff}{push button field}%
5693   \bitsetIsEmpty{HyField@Ff}{%
5694     \let\Fld@flags\ltx@empty
5695   }{%
5696     \edef\Fld@flags{/Ff \bitsetGetDec{HyField@Ff}}%
5697   }%
5698 }

```

20.1.5 Check box field

\HyField@FlagsCheckBox

```
5699 \def\HyField@FlagsCheckBox{%
5700   \HyField@FlagsAnnot{check box field}%
5701   \bitsetReset{HyField@Ff}%
5702   \HyField@UseFlag{Ff}{ReadOnly}%
5703   \HyField@UseFlag{Ff}{Required}%
5704   \HyField@UseFlag{Ff}{NoExport}%
5705   \HyField@PrintFlags{Ff}{check box field}%
5706   \bitsetIsEmpty{HyField@Ff}{%
5707     \let\Fld@flags\ltx@empty
5708   }{%
5709     \edef\Fld@flags{/Ff \bitsetGetDec{HyField@Ff}}%
5710   }%
5711 }
```

20.1.6 Radio button field

\HyField@FlagsRadioButton

```
5712 \def\HyField@FlagsRadioButton{%
5713   \HyField@FlagsAnnot{radio button field}%
5714   \bitsetReset{HyField@Ff}%
5715   \HyField@UseFlag{Ff}{ReadOnly}%
5716   \HyField@UseFlag{Ff}{Required}%
5717   \HyField@UseFlag{Ff}{NoExport}%
5718   \HyField@UseFlag{Ff}{NoToggleToOff}%
5719   \HyField@SetFlag{Ff}{Radio}%
5720   \HyField@UseFlag{Ff}{RadiosInUnison}%
5721   \HyField@PrintFlags{Ff}{radio button field}%
5722   \bitsetIsEmpty{HyField@Ff}{%
5723     \let\Fld@flags\ltx@empty
5724   }{%
5725     \edef\Fld@flags{/Ff \bitsetGetDec{HyField@Ff}}%
5726   }%
5727 }
```

20.1.7 Text fields

\HyField@FlagsText

```
5728 \def\HyField@FlagsText{%
5729   \HyField@FlagsAnnot{text field}%
5730   \bitsetReset{HyField@Ff}%
5731   \HyField@UseFlag{Ff}{ReadOnly}%
5732   \HyField@UseFlag{Ff}{Required}%
5733   \HyField@UseFlag{Ff}{NoExport}%
5734   \HyField@UseFlag{Ff}{Multiline}%
5735   \HyField@UseFlag{Ff}{Password}%
5736   \HyField@UseFlag{Ff}{FileSelect}%
5737   \HyField@UseFlag{Ff}{DoNotSpellCheck}%
5738   \HyField@UseFlag{Ff}{DoNotScroll}%
5739   \ifFld@comb
5740     \ifcase0\ifFld@multiline
5741       \else\ifFld@password
5742       \else\ifFld@fileselect
5743       \else 1\fi\fi\fi\relax
5744     \Hy@Error{%
```

```

5745     Field option 'comb' cannot used together with\MessageBreak
5746     'multiline', 'password', or 'fileselect'%
5747   }\@ehc
5748   \else
5749     \HyField@UseFlag{Ff}{Comb}%
5750   \fi
5751 \fi
5752 \HyField@UseFlag{Ff}{RichText}%
5753 \HyField@PrintFlags{Ff}{text field}%
5754 \bitsetIsEmpty{HyField@Ff}{%
5755   \let\Fld@flags\ltx@empty
5756 }{%
5757   \edef\Fld@flags{/Ff \bitsetGetDec{HyField@Ff}}%
5758 }%
5759 }

```

20.1.8 Choice fields

\HyField@FlagsChoice

```

5760 \def\HyField@FlagsChoice{%
5761   \HyField@FlagsAnnot{choice field}%
5762   \bitsetReset{HyField@Ff}%
5763   \HyField@UseFlag{Ff}{ReadOnly}%
5764   \HyField@UseFlag{Ff}{Required}%
5765   \HyField@UseFlag{Ff}{NoExport}%
5766   \HyField@UseFlag{Ff}{Combo}%
5767   \ifFld@combo
5768     \HyField@UseFlag{Ff}{Edit}%
5769   \fi
5770   \HyField@UseFlag{Ff}{Sort}%
5771   \HyField@UseFlag{Ff}{MultiSelect}%
5772   \ifFld@combo
5773     \ifFld@edit
5774       \HyField@UseFlag{Ff}{DoNotSpellCheck}%
5775     \fi
5776   \fi
5777   \HyField@UseFlag{Ff}{CommitOnSelChange}%
5778   \HyField@PrintFlags{Ff}{choice field}%
5779   \bitsetIsEmpty{HyField@Ff}{%
5780     \let\Fld@flags\ltx@empty
5781   }{%
5782     \edef\Fld@flags{/Ff \bitsetGetDec{HyField@Ff}}%
5783   }%
5784 }

```

20.2 Choice field

\HyField@PDFChoices #1: list of choices in key value syntax, key = exported name, value = displayed text.

Input: \Fld@default, \Fld@value, \ifFld@multiselect

Result: \Fld@choices with entries: /Opt, /DV, /V, /I.

```

5785 \def\HyField@PDFChoices#1{%
5786   \begingroup
5787   \global\let\Fld@choices\ltx@empty
5788   \let\HyTmp@optlist\ltx@empty
5789   \let\HyTmp@optitem\relax

```



```

5790 \count@=0 %
5791 \kv@parse{#1}{%
5792 \Hy@pdfstringdef\kv@key\kv@key
5793 \ifx\kv@value\relax
5794 \ifnum\Hy@pdfversion<3 % implementation note 122, PDF spec 1.7
5795 \xdef\Fld@choices{\Fld@choices(\kv@key)(\kv@key)}}%
5796 \else
5797 \xdef\Fld@choices{\Fld@choices(\kv@key)}%
5798 \fi
5799 \else
5800 \Hy@pdfstringdef\kv@value\kv@value
5801 \xdef\Fld@choices{\Fld@choices(\kv@value)(\kv@key)}}%
5802 \fi
5803 \edef\HyTmp@optlist{%
5804 \HyTmp@optlist
5805 \HyTmp@optitem{the\count@}{\kv@key}0%
5806 }%
5807 \advance\count@ by 1 %
5808 \@gobbletwo
5809 }%
5810 \xdef\Fld@choices{/Opt[\Fld@choices]}%
5811 \ifFld@multiselect
5812 \HyField@@PDFChoices{DV}\Fld@default
5813 \HyField@@PDFChoices{V}\Fld@value
5814 \else
5815 \ifx\Fld@default\relax
5816 \else
5817 \pdfstringdef\Hy@gtemp\Fld@default
5818 \xdef\Fld@choices{\Fld@choices/DV(\Hy@gtemp)}%
5819 \fi
5820 \ifx\Fld@value\relax
5821 \else
5822 \pdfstringdef\Hy@gtemp\Fld@value
5823 \xdef\Fld@choices{\Fld@choices/V(\Hy@gtemp)}%
5824 \fi
5825 \fi
5826 \endgroup
5827 }

```

\HyField@@PDFChoices

```

5828 \def\HyField@@PDFChoices#1#2{%
5829 \ifx#2\relax
5830 \else
5831 \count@=0 %
5832 \def\HyTmp@optitem##1##2##3{%
5833 \def\HyTmp@key{##2}%
5834 \ifx\HyTmp@key\Hy@gtemp
5835 \expandafter\def\expandafter\HyTmp@optlist\expandafter{%
5836 \HyTmp@optlist
5837 \HyTmp@optitem{##1}{##2}1%
5838 }%
5839 \let\HyTmp@found=Y%
5840 \else
5841 \expandafter\def\expandafter\HyTmp@optlist\expandafter{%
5842 \HyTmp@optlist
5843 \HyTmp@optitem{##1}{##2}##3%
5844 }%
5845 \fi

```

```

5846 }%
5847 \expandafter\comma@parse\expandafter{#2}{%
5848 \pdfstringdef\Hy@gtemp\comma@entry
5849 \let\HyTmp@found=N %
5850 \expandafter\let\expandafter\HyTmp@optlist\expandafter\@empty
5851 \HyTmp@optlist
5852 \ifx\HyTmp@found Y%
5853 \advance\count@ by 1 %
5854 \else
5855 \@onelevel@sanitize\comma@entry
5856 \PackageWarning{hyperref}{%
5857 \string\ChoiceBox: Ignoring value ‘\comma@entry’,%
5858 \MessageBreak
5859 it cannot be found in the choices%
5860 }%
5861 \fi
5862 \@gobble
5863 }%
5864 \def\HyTmp@optitem##1##2##3{%
5865 \ifnum##3=1 %
5866 (##2)%
5867 \fi
5868 }%
5869 \ifcase\count@
5870 \or
5871 \xdef\Fld@choices{\Fld@choices/#1\HyTmp@optlist}%
5872 \else
5873 \xdef\Fld@choices{\Fld@choices/#1[\HyTmp@optlist]}%
5874 \ifx#1V%
5875 \def\HyTmp@optitem##1##2##3{%
5876 \ifnum##3=1 %
5877 \@firstofone{ ##1}%
5878 \fi
5879 }%
5880 \edef\HyTmp@optlist{\HyTmp@optlist}%
5881 \xdef\Fld@choices{%
5882 \Fld@choices
5883 /I[\expandafter\@firstofone\HyTmp@optlist]%
5884 }%
5885 \fi
5886 \fi
5887 \fi
5888 }

```

20.3 Forms

\HyField@SetKeys

```

5889 \def\HyField@SetKeys{%
5890 \kvsetkeys{Field}%
5891 }

5892 \newif\ifFld@checked
5893 \newif\ifFld@disabled
5894 \Fld@checkedfalse
5895 \Fld@disabledfalse
5896 \newcount\Fld@menulength
5897 \newdimen\Field@Width

```

```

5898 \newdimen\Fld@charsize
5899 \Fld@charsize=10\p@
5900 \def\Fld@maxlen{0}
5901 \def\Fld@align{0}
5902 \def\Fld@color{0 0 0 rg}
5903 \def\Fld@bcolor{1 1 1}
5904 \def\Fld@bordercolor{1 0 0}
5905 \def\Fld@bordersep{1\p@}
5906 \def\Fld@borderwidth{1}
5907 \def\Fld@borderstyle{S}
5908 \def\Fld@cbsymbol{4}
5909 \def\Fld@radiosymbol{H}
5910 \def\Fld@rotation{0}
5911 \def\Form{\@ifnextchar{\@Form}{\@Form[]}}
5912 \def\endForm{\@endForm}
5913 \newif\ifForm@html
5914 \Form@htmlfalse
5915 \def\Form@boolkey#1#2{%
5916   \csname Form@#2\ifx\relax#1\relax true\else#1\fi\endcsname
5917 }
5918 \define@key{Form}{action}{%
5919   \hyper@normalise\Hy@DefFormAction{#1}%
5920 }
5921 \def\Hy@DefFormAction{\def\Form@action}
5922 \def\enc@html{html}
5923 \define@key{Form}{encoding}{%
5924   \def\Hy@tempa{#1}%
5925   \ifx\Hy@tempa\enc@html
5926     \Form@htmltrue
5927     \def\Fld@export{html}%
5928   \else
5929     \Hy@Warning{%
5930       Form 'encoding' key with \MessageBreak
5931       unknown value '#1'%
5932     }%
5933     \Form@htmlfalse
5934   \fi
5935 }
5936 \define@key{Form}{method}{%
5937   \lowercase{\def\Hy@temp{#1}}%
5938   \@ifundefined{Form@method@\Hy@temp}{%
5939     \@onelevel@sanitize\Hy@temp
5940     \Hy@Error{%
5941       Unknown method '\Hy@temp'\MessageBreak
5942       Known values are 'post' and 'get'%
5943     }\@ehc
5944   }{%
5945     \let\Form@method\Hy@temp
5946     \ifcase\@nameuse{Form@method@\Hy@temp} %
5947       \Fld@getmethodfalse
5948     \else
5949       \Fld@getmethodtrue
5950     \fi
5951   }%
5952 }
5953 \def\Form@method{}
5954 \@namedef{Form@method@post}{0}

```

```

5955 \@namedef{Form@method@get}{1}
5956 \newif\ifHyField@NeedAppearances
5957 \def\HyField@NeedAppearancesfalse{%
5958   \global\let\ifHyField@NeedAppearances\iffalse
5959 }
5960 \def\HyField@NeedAppearancetrue{%
5961   \global\let\ifHyField@NeedAppearances\iftrue
5962 }
5963 \HyField@NeedAppearancetrue
5964 \define@key{Form}{NeedAppearances}[true]{%
5965   \edef\Hy@tempa{#1}%
5966   \ifx\Hy@tempa\Hy@true
5967     \HyField@NeedAppearancetrue
5968   \else
5969     \ifx\Hy@tempa\Hy@false
5970       \HyField@NeedAppearancesfalse
5971     \else
5972       \Hy@Error{%
5973         Unexpected value '\Hy@tempa'\MessageBreak
5974         of option 'NeedAppearances' instead of\MessageBreak
5975         'true' or 'false'%
5976       }\@ehc
5977   \fi
5978 \fi
5979 }
5980 \def\Field@boolkey#1#2{%
5981   \csname Fld@#2\ifx\relax#1\relax true\else#1\fi\endcsname
5982 }
5983 \ifHy@texht
5984   \newtoks\Field@toks
5985   \Field@toks={ }%
5986   \def\Field@addtoks#1#2{%
5987     \edef\@processme{\Field@toks{the\Field@toks\space #1="#2"}}%
5988     \@processme
5989   }%
5990 \else
5991   \def\Hy@WarnHTMLFieldOption#1{%
5992     \Hy@Warning{%
5993       HTML field option '#1'\MessageBreak
5994       is ignored%
5995     }%
5996   }%
5997 \fi
5998 \def\Fld@checkequals#1=#2=#3\\{%
5999   \def\@currDisplay{#1}%
6000   \ifx\\#2\\%
6001     \def\@currValue{#1}%
6002   \else
6003     \def\@currValue{#2}%
6004   \fi
6005 }
6006 \define@key{Field}{loc}{%
6007   \def\Fld@loc{#1}%
6008 }
6009 \define@key{Field}{checked}[true]{%
6010   \lowercase{\Field@boolkey{#1}}{checked}%
6011 }

```

```

6012 \define@key{Field}{disabled}[true]{%
6013   \lowercase{\Field@boolkey{#1}}{disabled}%
6014 }
6015 \ifHy@texht
6016   \define@key{Field}{accesskey}{%
6017     \Field@addtoks{accesskey}{#1}%
6018   }%
6019   \define@key{Field}{tabkey}{%
6020     \Field@addtoks{tabkey}{#1}%
6021   }%
6022 \else
6023   \define@key{Field}{accesskey}{%
6024     \Hy@WarnHTMLFieldOption{accesskey}%
6025   }%
6026   \define@key{Field}{tabkey}{%
6027     \Hy@WarnHTMLFieldOption{tabkey}%
6028   }%
6029 \fi
6030 \define@key{Field}{name}{%
6031   \def\Fld@name{#1}%
6032 }
6033 \let\Fld@altname\relax
6034 \define@key{Field}{altname}{%
6035   \def\Fld@altname{#1}%
6036 }
6037 \let\Fld@mappingname\relax
6038 \define@key{Field}{mappingname}{%
6039   \def\Fld@mappingname{#1}%
6040 }
6041 \define@key{Field}{width}{%
6042   \def\Fld@width{#1}%
6043   \Field@Width#1\setbox0=\hbox{m}%
6044 }
6045 \define@key{Field}{maxlen}{%
6046   \def\Fld@maxlen{#1}%
6047 }
6048 \define@key{Field}{menulength}{%
6049   \Fld@menulength=#1\relax
6050 }
6051 \define@key{Field}{height}{%
6052   \def\Fld@height{#1}%
6053 }
6054 \define@key{Field}{charsize}{%
6055   \setlength{\Fld@charsize}{#1}%
6056 }
6057 \define@key{Field}{borderwidth}{%
6058   \Hy@defaultbp\Fld@borderwidth{#1}%
6059 }
6060 \def\Hy@defaultbp#1#2{%
6061   \begingroup
6062     \afterassignment\Hy@defaultbpAux
6063     \dimen@=#2bp\relax{#1}{#2}%
6064 }
6065 \begingroup\expandafter\expandafter\expandafter\endgroup
6066 \expandafter\ifx\csname dimexpr\endcsname\relax
6067   \def\Hy@defaultbpAux#1\relax#2#3{%
6068     \ifx!#1!%

```

```

6069 \endgroup
6070 \def#2{#3}%
6071 \else
6072 \dimen@=.99626\dimen@
6073 \edef\x{\endgroup
6074 \def\noexpand#2{%
6075 \strip@pt\dimen@
6076 }%
6077 }\x
6078 \fi
6079 }%
6080 \else
6081 \def\Hy@defaultbpAux#1\relax#2#3{%
6082 \ifx!#1!%
6083 \endgroup
6084 \def#2{#3}%
6085 \else
6086 \edef\x{\endgroup
6087 \def\noexpand#2{%
6088 \strip@pt\dimexpr\dimen@*800/803\relax
6089 }%
6090 }\x
6091 \fi
6092 }%
6093 \fi
6094 \define@key{Field}{borderstyle}{%
6095 \let\Hy@temp\Fld@borderstyle
6096 \def\Fld@borderstyle{#1}%
6097 \Hy@Match\Fld@borderstyle{%
6098 ~[SDBIU]$%
6099 }-}{%
6100 \Hy@Warning{%
6101 Invalid value '@pdfborderstyle'\MessageBreak
6102 for option 'pdfborderstyle'. Valid values:\MessageBreak
6103 \space\space S (Solid), D (Dashed), B (Beveled),\MessageBreak
6104 \space\space I (Inset), U (Underline)\MessageBreak
6105 Option setting is ignored%
6106 }%
6107 \let\Fld@borderstyle\Hy@temp
6108 }%
6109 }
6110 \define@key{Field}{bordersep}{%
6111 \def\Fld@bordersep{#1}%
6112 }
6113 \define@key{Field}{default}{%
6114 \def\Fld@default{#1}%
6115 }
6116 \define@key{Field}{align}{%
6117 \def\Fld@align{#1}%
6118 }
6119 \define@key{Field}{value}{%
6120 \def\Fld@value{#1}%
6121 }
6122 \define@key{Field}{checkboxsymbol}{%
6123 \Fld@DingDef\Fld@cbsymbol{#1}%
6124 }
6125 \define@key{Field}{radiosymbol}{%

```

```

6126 \Fld@DingDef\Fld@radiosymbol{#1}%
6127 }
6128 \def\Fld@DingDef#1#2{%
6129 \let\Fld@temp\ltx@empty
6130 \Fld@@@DingDef#2\ding{}}\@nil
6131 \let#1\Fld@temp
6132 }
6133 \def\Fld@@@DingDef#1\ding#2#3\@nil{%
6134 \expandafter\def\expandafter\Fld@temp\expandafter{%
6135 \Fld@temp
6136 #1%
6137 }%
6138 \ifx\\#3\\%
6139 \expandafter\@gobble
6140 \else
6141 \begingroup
6142 \lccode'0=#2\relax
6143 \lowercase{\endgroup
6144 \expandafter\def\expandafter\Fld@temp\expandafter{%
6145 \Fld@temp
6146 0%
6147 }%
6148 }%
6149 \expandafter\@firstofone
6150 \fi
6151 {%
6152 \Fld@@@DingDef#3\@nil
6153 }%
6154 }

6155 \define@key{Field}{rotation}{%
6156 \def\Fld@rotation{#1}%
6157 }

6158 \define@key{Field}{backgroundcolor}{%
6159 \HyColor@FieldBColor{#1}\Fld@bcolor{hyperref}{backgroundcolor}%
6160 }
6161 \define@key{Field}{bordercolor}{%
6162 \HyColor@FieldBColor{#1}\Fld@bordercolor{hyperref}{bordercolor}%
6163 }
6164 \define@key{Field}{color}{%
6165 \HyColor@FieldColor{#1}\Fld@color{hyperref}{color}%
6166 }

6167 \let\Fld@onclick@code\ltx@empty
6168 \let\Fld@format@code\ltx@empty
6169 \let\Fld@validate@code\ltx@empty
6170 \let\Fld@calculate@code\ltx@empty
6171 \let\Fld@keystroke@code\ltx@empty
6172 \let\Fld@onfocus@code\ltx@empty
6173 \let\Fld@onblur@code\ltx@empty
6174 \let\Fld@onmousedown@code\ltx@empty
6175 \let\Fld@onmouseup@code\ltx@empty
6176 \let\Fld@onenter@code\ltx@empty
6177 \let\Fld@onexit@code\ltx@empty
6178 \def\Hy@temp#1{%
6179 \expandafter\Hy@@temp\csname Fld@#1@code\endcsname{#1}%
6180 }
6181 \def\Hy@@temp#1#2{%

```

```

6182 \ifHy@pdfa
6183   \define@key{Field}{#2}{%
6184     \Hy@Error{%
6185       PDF/A: Additional action '#2' is prohibited%
6186     }\@ehc
6187   }%
6188 \else
6189   \define@key{Field}{#2}{%
6190     \def#1{##1}%
6191   }%
6192 \fi
6193 }
6194 \Hy@temp{keystroke}
6195 \Hy@temp{format}
6196 \Hy@temp{validate}
6197 \Hy@temp{calculate}
6198 \Hy@temp{onfocus}
6199 \Hy@temp{onblur}
6200 \Hy@temp{onenter}
6201 \Hy@temp{onexit}
6202 \ifHy@texht
6203   \def\Hy@temp#1{%
6204     \define@key{Field}{#1}{%
6205       \Field@addtoks{#1}{##1}%
6206     }%
6207   }%
6208 \else
6209   \def\Hy@temp#1{%
6210     \define@key{Field}{#1}{%
6211       \Hy@WarnHTMLFieldOption{#1}%
6212     }%
6213   }%
6214 \fi
6215 \Hy@temp{ondblclick}
6216 \Hy@temp{onmousedown}
6217 \Hy@temp{onmouseup}
6218 \Hy@temp{onmouseover}
6219 \Hy@temp{onmousemove}
6220 \Hy@temp{onmouseout}
6221 \Hy@temp{onkeydown}
6222 \Hy@temp{onkeyup}
6223 \Hy@temp{onselect}
6224 \Hy@temp{onchange}
6225 \Hy@temp{onkeypress}
6226 \ifHy@texht
6227   \define@key{Field}{onclick}{%
6228     \Field@addtoks{onclick}{#1}%
6229   }%
6230 \else
6231   \ifHy@pdfa
6232     \define@key{Field}{onclick}{%
6233       \Hy@Error{%
6234         PDF/A: Action 'onclick' is prohibited%
6235       }\@ehc
6236     }%
6237   \else
6238     \define@key{Field}{onclick}{%

```



```

6239 \def\Fld@onclick@code{#1}%
6240 }%
6241 \fi
6242 \fi

6243 \DeclareRobustCommand\TextField{%
6244 \@ifnextchar[{\@TextField}{\@TextField[]}%
6245 }
6246 \DeclareRobustCommand\ChoiceMenu{%
6247 \@ifnextchar[{\@ChoiceMenu}{\@ChoiceMenu[]}%
6248 }
6249 \DeclareRobustCommand\CheckBox{%
6250 \@ifnextchar[{\@CheckBox}{\@CheckBox[]}%
6251 }
6252 \DeclareRobustCommand\PushButton{%
6253 \@ifnextchar[{\@PushButton}{\@PushButton[]}%
6254 }
6255 \DeclareRobustCommand\Gauge{%
6256 \@ifnextchar[{\@Gauge}{\@Gauge[]}%
6257 }
6258 \DeclareRobustCommand\Submit{%
6259 \@ifnextchar[{\@Submit}{\@Submit[]}%
6260 }
6261 \DeclareRobustCommand\Reset{%
6262 \@ifnextchar[{\@Reset}{\@Reset[]}%
6263 }
6264 \def\LayoutTextField#1#2{% label, field
6265 #1 #2%
6266 }
6267 \def\LayoutChoiceField#1#2{% label, field
6268 #1 #2%
6269 }
6270 \def\LayoutCheckField#1#2{% label, field
6271 #1 #2%
6272 }
6273 \def\LayoutPushButtonField#1{% button
6274 #1%
6275 }
6276 \def\MakeRadioField#1#2{\vbox to #2{\hbox to #1{\hfill}\vfill}}
6277 \def\MakeCheckField#1#2{\vbox to #2{\hbox to #1{\hfill}\vfill}}
6278 \def\MakeTextField#1#2{\vbox to #2{\hbox to #1{\hfill}\vfill}}
6279 \def\MakeChoiceField#1#2{\vbox to #2{\hbox to #1{\hfill}\vfill}}
6280 \def\MakeButtonField#1{%
6281 \sbox0{%
6282 \hskip\Fld@borderwidth bp#1\hskip\Fld@borderwidth bp%
6283 }%
6284 \@tempdima\ht0 %
6285 \advance\@tempdima by \Fld@borderwidth bp %
6286 \advance\@tempdima by \Fld@borderwidth bp %
6287 \ht0\@tempdima
6288 \@tempdima\dp0 %
6289 \advance\@tempdima by \Fld@borderwidth bp %
6290 \advance\@tempdima by \Fld@borderwidth bp %
6291 \dp0\@tempdima
6292 \box0\relax
6293 }
6294 \def\DefaultHeightofSubmit{14pt}
6295 \def\DefaultWidthofSubmit{2cm}

```

```

6296 \def\DefaultHeightofReset{14pt}
6297 \def\DefaultWidthofReset{2cm}
6298 \def\DefaultHeightofCheckBox{\baselineskip}
6299 \def\DefaultWidthofCheckBox{\baselineskip}
6300 \def\DefaultHeightofChoiceMenu{\baselineskip}
6301 \def\DefaultWidthofChoiceMenu{\baselineskip}
6302 \def\DefaultHeightofText{\baselineskip}
6303 \def\DefaultHeightofTextMultiline{4\baselineskip}
6304 \def\DefaultWidthofText{3cm}
6305 \def\DefaultOptionsofSubmit{print,name=Submit,noexport}
6306 \def\DefaultOptionsofReset{print,name=Reset,noexport}
6307 \def\DefaultOptionsofPushButton{print}
6308 \def\DefaultOptionsofCheckBox{print}
6309 \def\DefaultOptionsofText{print}

```

Default options for the types of \ChoiceMenu.

```

6310 \def\DefaultOptionsofListBox{print}
6311 \def\DefaultOptionsofComboBox{print,edit,sort}
6312 \def\DefaultOptionsofPopdownBox{print}
6313 \def\DefaultOptionsofRadio{print,notoggletooff}

```

21 Setup

```

6314 \ifHy@hyperfigures
6315 \Hy@Info{Hyper figures ON}%
6316 \else
6317 \Hy@Info{Hyper figures OFF}%
6318 \fi
6319 \ifHy@nesting
6320 \Hy@Info{Link nesting ON}%
6321 \else
6322 \Hy@Info{Link nesting OFF}%
6323 \fi
6324 \ifHy@hyperindex
6325 \Hy@Info{Hyper index ON}%
6326 \else
6327 \Hy@Info{Hyper index OFF}%
6328 \fi
6329 \ifHy@backref
6330 \Hy@Info{backreferencing ON}%
6331 \else
6332 \Hy@Info{backreferencing OFF}%
6333 \fi
6334 \ifHy@colorlinks
6335 \Hy@Info{Link coloring ON}%
6336 \else
6337 \Hy@Info{Link coloring OFF}%
6338 \fi
6339 \ifHy@ocgcolorlinks
6340 \Hy@Info{Link coloring with OCG ON}%
6341 \else
6342 \Hy@Info{Link coloring with OCG OFF}%
6343 \fi
6344 \ifHy@pdfa
6345 \Hy@Info{PDF/A mode ON}%
6346 \else
6347 \Hy@Info{PDF/A mode OFF}%

```

6348 \fi

22 Low-level utility macros

We need unrestricted access to the #, ~ and " characters, so make them nice macros.

```
6349 \edef\hyper@hash{\string#}  
6350 \edef\hyper@tilde{\string~}  
6351 \edef\hyper@quote{\string"}
```

Support \label before \begin{document}.

```
6352 \def\@currentHref{Doc-Start}  
6353 \let\Hy@footnote@currentHref\@empty
```

We give the start of document a special label; this is used in backreferencing-by-section, to allow for cites before any sectioning commands. Set up PDF info.

```
6354 \Hy@AtBeginDocument{%  
6355   \Hy@pdfstringtrue  
6356   \PDF@SetupDoc  
6357   \let\PDF@SetupDoc\@empty  
6358   \Hy@DisableOption{pdfpagescrop}%  
6359   \Hy@DisableOption{pdfpagemode}%  
6360   \Hy@DisableOption{pdfnonfullscreenpagemode}%  
6361   \Hy@DisableOption{pdfdirection}%  
6362   \Hy@DisableOption{pdfviewarea}%  
6363   \Hy@DisableOption{pdfviewclip}%  
6364   \Hy@DisableOption{pdfprintarea}%  
6365   \Hy@DisableOption{pdfprintclip}%  
6366   \Hy@DisableOption{pdfprintscaling}%  
6367   \Hy@DisableOption{pdfduplex}%  
6368   \Hy@DisableOption{pdfpicktraybypdfsize}%  
6369   \Hy@DisableOption{pdfprintpagerange}%  
6370   \Hy@DisableOption{pdfnumcopies}%  
6371   \Hy@DisableOption{pdfstartview}%  
6372   \Hy@DisableOption{pdfstartpage}%  
6373   \Hy@DisableOption{pdftoolbar}%  
6374   \Hy@DisableOption{pdfmenubar}%  
6375   \Hy@DisableOption{pdfwindowui}%  
6376   \Hy@DisableOption{pdfwindow}%  
6377   \Hy@DisableOption{pdfcenterwindow}%  
6378   \Hy@DisableOption{pdfdisplaydoctitle}%  
6379   \Hy@DisableOption{pdfpagelayout}%  
6380   \Hy@DisableOption{pdflang}%  
6381   \Hy@DisableOption{baseurl}%  
6382   \ifHy@texht\else\hyper@anchorstart{Doc-Start}\hyper@anchorend\fi  
6383   \Hy@pdfstringfalse  
6384 }
```

Ignore star from referencing macros:

```
6385 \LetLtxMacro\NoHy@OrgRef\ref  
6386 \DeclareRobustCommand*{\ref}{%  
6387   \@ifstar\NoHy@OrgRef\NoHy@OrgRef  
6388 }  
6389 \LetLtxMacro\NoHy@OrgPageRef\pageref  
6390 \DeclareRobustCommand*{\pageref}{%  
6391   \@ifstar\NoHy@OrgPageRef\NoHy@OrgPageRef  
6392 }
```

23 Localized nullifying of package

Sometimes we just don't want the wretched package interfering with us. Define an environment we can put in manually, or include in a style file, which stops the hypertext functions doing anything. This is used, for instance, in the Elsevier classes, to stop `hyperref` playing havoc in the front matter.

```

6393 \def\NoHyper{%
6394   \def\hyper@link@[##1]##2##3##4{##4\Hy@xspace@end}%
6395   \def\hyper@@anchor##1##2{##2\Hy@xspace@end}%
6396   \global\let\hyper@livelink\hyper@link
6397   \gdef\hyper@link##1##2##3{##3\Hy@xspace@end}%
6398   \let\hyper@anchor\ltx@gobble
6399   \let\hyper@anchorstart\ltx@gobble
6400   \def\hyper@anchorend{\Hy@xspace@end}%
6401   \let\hyper@linkstart\ltx@gobbletwo
6402   \def\hyper@linkend{\Hy@xspace@end}%
6403   \def\hyper@linkurl##1##2{##1\Hy@xspace@end}%
6404   \def\hyper@linkfile##1##2##3{##1\Hy@xspace@end}%
6405   \let\Hy@backout\@gobble
6406 }
6407 \def\stop@hyper{%
6408   \def\hyper@link@[##1]##2##3##4{##4\Hy@xspace@end}%
6409   \let\Hy@backout\@gobble
6410   \let\hyper@@anchor\ltx@gobble
6411   \def\hyper@link##1##2##3{##3\Hy@xspace@end}%
6412   \let\hyper@anchor\ltx@gobble
6413   \let\hyper@anchorstart\ltx@gobble
6414   \def\hyper@anchorend{\Hy@xspace@end}%
6415   \let\hyper@linkstart\ltx@gobbletwo
6416   \def\hyper@linkend{\Hy@xspace@end}%
6417   \def\hyper@linkurl##1##2{##1\Hy@xspace@end}%
6418   \def\hyper@linkfile##1##2##3{##1\Hy@xspace@end}%
6419 }
6420 \def\endNoHyper{%
6421   \global\let\hyper@link\hyper@livelink
6422 }
6423 \end{package}

```

24 Package nohyperref

This package is introduced by Sebastian Rahtz.

Package `nohyperref` is a dummy package that defines some low level and some top-level commands. It is done for `jadetex`, which calls `hyperref` low-level commands, but it would also be useful with people using normal `hyperref`, who really do not want the package loaded at all.

Some low-level commands:

```

6424 \nohyperref
6425 \RequirePackage{letltxmacro}[2008/06/13]
6426 \let\hyper@@anchor\@gobble
6427 \def\hyper@link##1##2##3{##3}%
6428 \let\hyper@anchorstart\@gobble
6429 \let\hyper@anchorend\@empty
6430 \let\hyper@linkstart\@gobbletwo
6431 \let\hyper@linkend\@empty
6432 \def\hyper@linkurl##1##2{##1}%

```

```

6433 \def\hyper@linkfile#1#2#3{#1}%
6434 \def\hyper@link@{#1}#2#3{#1}%
6435 \let\PDF@SetupDoc\@empty
6436 \let\PDF@FinishDoc\@empty
6437 \def\nohyperpage#1{#1}

```

Some top-level commands:

```

6438 \def\Acrobatmenu#1#2{\leavevmode#2}
6439 \let\pdfstringdefDisableCommands\@gobbletwo
6440 \let\texorpdfstring\@firstoftwo
6441 \let\pdfbookmark\@undefined
6442 \newcommand\pdfbookmark[3]{}
6443 \let\phantomsection\@empty
6444 \let\hypersetup\@gobble
6445 \let\hyperbaseurl\@gobble
6446 \newcommand*\href[3]{}
6447 \let\hyperdef\@gobbletwo
6448 \let\hyperlink\@gobble
6449 \let\hypertarget\@gobble
6450 \def\hyperref{%
6451   \@ifnextchar\@gobbleopt{\expandafter\@gobbletwo\@gobble}%
6452 }
6453 \long\def\@gobbleopt[#1]{}
6454 \let\hyperpage\@empty

```

Ignore star from referencing macros:

```

6455 \LetLtxMacro\NoHy@OrgRef\ref
6456 \DeclareRobustCommand*\ref{%
6457   \@ifstar\NoHy@OrgRef\NoHy@OrgRef
6458 }
6459 \LetLtxMacro\NoHy@OrgPageRef\pageref
6460 \DeclareRobustCommand*\pageref{%
6461   \@ifstar\NoHy@OrgPageRef\NoHy@OrgPageRef
6462 }
6463 \</nohyperref>

```

25 The Mangling Of Aux and Toc Files

Some extra tests so that the hyperref package may be removed or added to a document without having to remove .aux and .toc files (this section is by David Carlisle) All the code is delayed to `\begin{document}`

```

6464 \<*package>
6465 \Hy@AtBeginDocument{%

```

First the code to deal with removing the hyperref package from a document.

Write some stuff into the aux file so if the next run is done without hyperref, then `\contentsline` and `\newlabel` are defined to cope with the extra arguments.

```

6466   \if@filesw
6467     \ifHy@typexml
6468       \immediate\closeout\@mainaux
6469       \immediate\openout\@mainaux\jobname.aux\relax
6470       \immediate\write\@auxout{<relaxxml>\relax}%
6471     \fi
6472     \immediate\write\@auxout{%
6473       \string\providecommand\string\HyperFirstAtBeginDocument{%
6474         \string\AtBeginDocument}^^J%
6475       \string\HyperFirstAtBeginDocument{%

```

```

6476 \string\ifx\string\hyper@anchor\string\@undefined^^J%
6477 \string\global\string\let\string\oldcontentsline\string\contentsline^^J%
6478 \string\gdef\string\contentsline%
6479 \string#1\string#2\string#3\string#4{%
6480 \string\oldcontentsline%
6481 {\string#1}{\string#2}{\string#3}}^^J%
6482 \string\global\string\let\string\oldnewlabel\string\newlabel^^J%
6483 \string\gdef\string\newlabel\string#1\string#2{%
6484 \string\newlabelxx{\string#1}\string#2}^^J%
6485 \string\gdef\string\newlabelxx%
6486 \string#1\string#2\string#3\string#4\string#5\string#6{%
6487 \string\oldnewlabel{\string#1}{\string#2}{\string#3}}^^J%

```

But the new aux file will be read again at the end, with the normal definitions expected, so better put things back as they were.

```

6488 \string\AtEndDocument{%
6489 \string\ifx\string\hyper@anchor\string\@undefined^^J%
6490 \string\let\string\contentsline\string\oldcontentsline^^J%
6491 \string\let\string\newlabel\string\oldnewlabel^^J%
6492 \string\fi%
6493 }^^J%

```

If the document is being run with hyperref put this definition into the aux file, so we can spot it on the next run.

```

6494 \string\fi%
6495 }^^J%
6496 \string\global\string\let\string\hyper@last\relax^^J%
6497 \string\gdef\string\HyperFirstAtBeginDocument\string#1{\string#1}%
6498 }%
6499 \fi
6500 \let\HyperFirstAtBeginDocument\ltx@firstofone

```

Now the code to deal with adding the hyperref package to a document with aux and toc written the standard way.

If hyperref was used last time, do nothing. If it was not used, or an old version of hyperref was used, don't use that TOC at all but generate a warning. Not ideal, but better than failing with pre-5.0 hyperref TOCs.

```

6501 \ifx\hyper@last\@undefined
6502 \def\@starttoc#1{%
6503 \begingroup
6504 \makeatletter
6505 \ltx@ifpackageloaded{parskip}{\parskip\z@}{}%
6506 \IfFileExists{\jobname.#1}{%
6507 \Hy@WarningNoLine{%
6508 old #1 file detected, not used; run LaTeX again%
6509 }%
6510 }{}%
6511 \if@files
6512 \expandafter\newwrite\csname tf@#1\endcsname
6513 \immediate\openout\csname tf@#1\endcsname \jobname.#1\relax
6514 \fi
6515 \@nobreakfalse
6516 \endgroup
6517 }%
6518 \def\newlabel#1#2{\@newl@bel r{#1}{#2}{-}{-}{-}}%
6519 \fi
6520 }

```

26 Title strings

If options `pdftitle` and `pdfauthor` are not used, these informations for the pdf information dictionary can be extracted by the nd

```

6521 \ifHy@pdfusetitle
6522   \let\HyOrg@title\title
6523   \let\HyOrg@author\author
6524   \def\title{\@ifnextchar{\Hy@scanopttitle}{\Hy@scantitle}}%
6525   \def\Hy@scanopttitle[#1]{%
6526     \gdef\Hy@title{#1}%
6527     \HyOrg@title{#1}%
6528   }%
6529   \def\Hy@scantitle#1{%
6530     \gdef\Hy@title{#1}%
6531     \HyOrg@title{#1}%
6532   }%
6533   \def\author{\@ifnextchar{\Hy@scanoptauthor}{\Hy@scanauthor}}%
6534   \def\Hy@scanoptauthor[#1]{%
6535     \gdef\Hy@author{#1}%
6536     \HyOrg@author{#1}%
6537   }%
6538   \def\Hy@scanauthor#1{%
6539     \gdef\Hy@author{#1}%
6540     \HyOrg@author{#1}%
6541   }%

```

The case, that `or` re given before `hyperref` is loaded, is much more complicate, because LaTeX initializes the macros `title` and `author` with LaTeX error and warning messages.

```

6542 \begingroup
6543   \def\process@me#1\@nil#2{%
6544     \expandafter\let\expandafter\x\csname @#2\endcsname
6545     \edef\y{\expandafter\strip@prefix\meaning\x}%
6546     \def\c##1##2\@nil{%
6547       \ifx\\##1\\%
6548         \else
6549           \expandafter\gdef\csname Hy@#2\expandafter\endcsname
6550             \expandafter{\x}%
6551       \fi
6552     }%
6553     \expandafter\c\y\relax#1\@nil
6554   }%
6555   \expandafter\process@me\string\@latex@\@nil{title}%
6556   \expandafter\process@me\string\@latex@\@nil{author}%
6557 \endgroup
6558 \fi
6559 \Hy@DisableOption{pdfusetitle}

```

Macro `\Hy@UseMaketitleInfos` is used in the driver files, before the information entries are used.

The newline macro `\newline` or `\\` is much more complicate. In the title a good replacement can be a space, but can be already a space after `\\` in the title string. So this space is removed by scanning for the next non-empty argument.

In the macro `\author` the newline can perhaps separate the different authors, so the newline expands here to a comma with space.

The possible arguments such as space or the optional argument after the newline macros are not detected.

```

6560 \def\Hy@UseMaketitleString#1{%
6561   \ltx@ifundefined{Hy@#1}{}%
6562   \begingroup
6563     \let\Hy@saved@hook\pdfstringdefPreHook
6564     \pdfstringdefDisableCommands{%
6565       \expandafter\let\expandafter\\\csname Hy@newline@#1\endcsname
6566       \let\newline\\%
6567     }%
6568     \expandafter\ifx\csname @pdf#1\endcsname\@empty
6569       \expandafter\pdfstringdef\csname @pdf#1\endcsname{%
6570         \csname Hy@#1\endcsname\@empty
6571       }%
6572     \fi
6573     \global\let\pdfstringdefPreHook\Hy@saved@hook
6574   \endgroup
6575 }%
6576 }
6577 \def\Hy@newline@title#1{ #1}
6578 \def\Hy@newline@author#1{, #1}
6579 \def\Hy@UseMaketitleInfos{%
6580   \Hy@UseMaketitleString{title}%
6581   \Hy@UseMaketitleString{author}%
6582 }

```

27 Page numbers

This stuff is done by Heiko Oberdiek.

28 Every page

```

6583 \RequirePackage{atbegshi}[2007/09/09]
6584 \let\Hy@EveryPageHook\ltx@empty
6585 \let\Hy@EveryPageBoxHook\ltx@empty
6586 \let\Hy@FirstPageHook\ltx@empty
6587 \AtBeginShipout{%
6588   \Hy@EveryPageHook
6589   \ifx\Hy@EveryPageBoxHook\ltx@empty
6590     \else
6591       \setbox\AtBeginShipoutBox=\vbox{%
6592         \offinterlineskip
6593         \Hy@EveryPageBoxHook
6594         \box\AtBeginShipoutBox
6595       }%
6596     \fi
6597 }
6598 \ltx@iffileloaded{hpdftex.def}{%
6599   \AtBeginShipout{%
6600     \Hy@FirstPageHook
6601     \global\let\Hy@FirstPageHook\ltx@empty
6602   }%
6603 }{%
6604   \AtBeginShipoutFirst{%
6605     \Hy@FirstPageHook
6606   }%
6607 }
6608 \g@addto@macro\Hy@FirstPageHook{%

```



```

6609 \PDF@FinishDoc
6610 \global\let\PDF@FinishDoc\ltx@empty
6611 }

```

28.1 PDF /PageLabels

Internal macros of this module are marked with \HyPL@.

```

6612 \ifHy@pdfpagelabels
6613 \begingroup\expandafter\expandafter\expandafter\endgroup
6614 \expandafter\ifx\csname thepage\endcsname\relax
6615 \Hy@pdfpagelabelsfalse
6616 \Hy@WarningNoLine{%
6617   Option 'pdfpagelabels' is turned off\MessageBreak
6618   because \string\thepage\space is undefined%
6619 }%
6620 \csname fi\endcsname
6621 \csname iffalse\expandafter\endcsname
6622 \fi

```

\thispdfpagelabel The command \thispdfpagelabel allows to label a special page without the re-definition of \thepage for the page.

```

6623 \def\thispdfpagelabel#1{%
6624   \gdef\HyPL@thisLabel{#1}%
6625 }%
6626 \global\let\HyPL@thisLabel\relax

```

\HyPL@Labels The page labels are collected in \HyPL@Labels and set at the end of the document.

```

6627 \let\HyPL@Labels\ltx@empty

```

\Hy@abspage We have to know the the absolute page number and introduce a new counter for that.

```

6628 \newcount\Hy@abspage
6629 \Hy@abspage=0 %

```

For comparisons with the values of the previous page, some variables are needed:

```

6630 \def\HyPL@LastType{init}%
6631 \def\HyPL@LastNumber{0}%
6632 \let\HyPL@LastPrefix\ltx@empty

```

Definitions for the PDF names of the L^AT_EX pendants.

```

6633 \def\HyPL@arabic{D}%
6634 \def\HyPL@Roman{R}%
6635 \def\HyPL@roman{r}%
6636 \def\HyPL@Alph{A}%
6637 \def\HyPL@alph{a}%
6638 \let\HyPL@SlidesSetPage\ltx@empty
6639 \ltx@ifclassloaded{slides}{%
6640   \def\HyPL@SlidesSetPage{%
6641     \advance\c@page\ltx@one
6642     \ifnum\value{page}>\ltx@one
6643       \protected@edef\HyPL@SlidesOptionalPage{%
6644         \Hy@SlidesFormatOptionalPage{\thepage}%
6645       }%
6646     \else
6647       \let\HyPL@SlidesOptionalPage\ltx@empty
6648     \fi
6649     \advance\c@page-\ltx@one

```

```

6650 \def\HyPL@page{%
6651 \csname the\Hy@SlidesPage\endcsname
6652 \HyPL@SlidesOptionalPage
6653 }%
6654 }%
6655 }{}%

```

`\HyPL@EveryPage` If a page is shipout and the page number is known, `\HyPL@EveryPage` has to be called. It stores the current page label.

```

6656 \def\HyPL@EveryPage{%
6657 \begingroup
6658 \ifx\HyPL@thisLabel\relax
6659 \let\HyPL@page\thepage
6660 \HyPL@SlidesSetPage
6661 \else
6662 \let\HyPL@page\HyPL@thisLabel
6663 \global\let\HyPL@thisLabel\relax
6664 \fi
6665 \let\HyPL@Type\relax
6666 \ifnum\c@page>0 %
6667 \ifx\HyPL@SlidesSetPage\ltx@empty
6668 \expandafter\HyPL@CheckThePage\HyPL@page\@nil
6669 \fi
6670 \fi
6671 \let\Hy@temp Y%
6672 \ifx\HyPL@Type\HyPL@LastType
6673 \else
6674 \let\Hy@temp N%
6675 \fi
6676 \ifx\HyPL@Type\relax
6677 \pdfstringdef\HyPL@Prefix{\HyPL@page}%
6678 \else
6679 \pdfstringdef\HyPL@Prefix\HyPL@Prefix
6680 \fi
6681 \ifx\HyPL@Prefix\HyPL@LastPrefix
6682 \else
6683 \let\Hy@temp N%
6684 \fi
6685 \if Y\Hy@temp
6686 \advance\c@page by -1 %
6687 \ifnum\HyPL@LastNumber=\the\c@page\relax
6688 \else
6689 \let\Hy@temp N%
6690 \fi
6691 \Hy@StepCount\c@page
6692 \fi
6693 \if N\Hy@temp
6694 \ifx\HyPL@Type\relax
6695 \HyPL@StorePageLabel{/P(\HyPL@Prefix)}%
6696 \else
6697 \HyPL@StorePageLabel{%
6698 \ifx\HyPL@Prefix\@empty
6699 \else
6700 /P(\HyPL@Prefix)%
6701 \fi
6702 /S/\csname HyPL\HyPL@Type\endcsname
6703 \ifnum\the\c@page=1 %

```

```

6704         \else
6705         \space/St \the\c@page
6706         \fi
6707     }%
6708     \fi
6709     \fi
6710     \xdef\HyPL@LastNumber{\the\c@page}%
6711     \global\let\HyPL@LastType\HyPL@Type
6712     \global\let\HyPL@LastPrefix\HyPL@Prefix
6713     \endgroup
6714     \Hy@GlobalStepCount\Hy@abspage
6715 }%

```

`\HyPL@CheckThePage` Macro `\HyPL@CheckThePage` calls `\HyPL@@CheckThePage` that does the job.

```

6716 \def\HyPL@CheckThePage#1\@nil{%
6717   \HyPL@@CheckThePage{#1}#1\csname\endcsname\c@page\@nil
6718 }%

```

`\HyPL@@CheckThePage` The first check is, is `\thepage` is defined such as in L^AT_EX, e.g.: `\csname @arabic\endcsname\c@page`. In the current implementation the check fails, if there is another `\csname` before.

The second check tries to detect `\arabic{page}` at the end of the definition text of `\thepage`.

```

6719 \def\HyPL@@CheckThePage#1#2\csname#3\endcsname\c@page#4\@nil{%
6720   \def\Hy@tempa{#4}%
6721   \def\Hy@tempb{\csname\endcsname\c@page}%
6722   \ifx\Hy@tempa\Hy@tempb
6723     \expandafter\ifx\csname HyPL#3\endcsname\relax
6724     \else
6725       \def\HyPL@Type{#3}%
6726       \def\HyPL@Prefix{#2}%
6727     \fi
6728   \else
6729     \begingroup
6730     \let\Hy@next\endgroup
6731     \let\HyPL@found\@undefined
6732     \def\arabic{\HyPL@Format{arabic}}%
6733     \def\Roman{\HyPL@Format{Roman}}%
6734     \def\roman{\HyPL@Format{roman}}%
6735     \def\Alph{\HyPL@Format{Alph}}%
6736     \def\alph{\HyPL@Format{alph}}%
6737     \protected@edef\Hy@temp{#1}%
6738     \ifx\HyPL@found\relax
6739       \toks@{\expandafter\Hy@temp}%
6740       \edef\Hy@next{\endgroup
6741         \noexpand\HyPL@@@CheckThePage\the\toks@
6742         \noexpand\HyPL@found\relax\noexpand\@nil
6743       }%
6744     \fi
6745     \Hy@next
6746   \fi
6747 }%

```

`\HyPL@Format` The help macro `\HyPL@Format` is executed while a `\protected@edef` in the second check method of `\HyPL@@CheckPage`. The first occurrences of, for example, `\arabic{page}` is marked by `\HyPL@found` that is also defined by `\csname`.

```

6748 \def\HyPL@Format#1#2{%

```

```

6749 \ifx\HyPL@found\@undefined
6750 \expandafter\ifx\csname c@#2\endcsname\c@page
6751 \expandafter\noexpand\csname HyPL@found\endcsname{#1}%
6752 \else
6753 \expandafter\noexpand\csname#1\endcsname{#2}%
6754 \fi
6755 \else
6756 \expandafter\noexpand\csname#1\endcsname{#2}%
6757 \fi
6758 }%

```

`\HyPL@@@CheckThePage` If the second check method is successful, `\HyPL@@@CheckThePage` scans the result of `\HyPL@Format` and stores the found values.

```

6759 \def\HyPL@@@CheckThePage#1\HyPL@found#2#3\@nil{%
6760 \def\Hy@tempa{#3}%
6761 \def\Hy@tempb{\HyPL@found\relax}%
6762 \ifx\Hy@tempa\Hy@tempb
6763 \def\HyPL@Type{#2}%
6764 \def\HyPL@Prefix{#1}%
6765 \fi
6766 }%

```

`\HyPL@StorePageLabel` Dummy for drivers that does not support `/PageLabel`.

```

6767 \providecommand*{\HyPL@StorePageLabel}[1]{}%

```

`\HyPL@Useless` The `/PageLabels` entry does not make sense, if the absolute page numbers and the page labels are the same. Then `\HyPL@Labels` has the meaning of `\HyPL@Useless`.

```

6768 \def\HyPL@Useless{0<</S/D>>}%
6769 \@onelevel@sanitize\HyPL@Useless

```

`\HyPL@SetPageLabels` The page labels are written to the PDF catalogue. The command `\Hy@PutCatalog` is defined in the driver files.

```

6770 \def\HyPL@SetPageLabels{%
6771 \@onelevel@sanitize\HyPL@Labels
6772 \ifx\HyPL@Labels\@empty
6773 \else
6774 \ifx\HyPL@Labels\HyPL@Useless
6775 \else
6776 \Hy@PutCatalog{/PageLabels<</Nums[\HyPL@Labels]>>}%
6777 \fi
6778 \fi
6779 }%

```

```

6780 \g@addto@macro\Hy@EveryPageHook{\HyPL@EveryPage}%
6781 \fi

```

Option ‘pdfpagelabels’ has been used and is now disabled.

```

6782 \Hy@DisableOption{pdfpagelabels}
6783 </package>

```

28.1.1 pdfTeX and VTeX

Because of pdfTeX’s `\pdfcatalog` command the `/PageLabels` entry can set at end of document in the first run.

\Hy@PutCatalog

```

6784 < *pdfTeX>
6785 \pdf@ifdraftmode{%
6786   \let\Hy@PutCatalog\ltx@gobble
6787 }{%
6788   \let\Hy@PutCatalog\pdfcatalog
6789 }
6790 < /pdfTeX>

```

The code for VTeX is more complicate, because it does not allow the direct access to the /Catalog object. The command scans its argument and looks for a /PageLabels entry.

VTeX 6.59g is the first version, that implements \special{!pdfpagelabels...}. For this version \VTeXversion reports 660.

```

6791 < *vtex>
6792 \providecommand*{\XR@ext}{pdf}
6793 \edef\Hy@VTeXversion{%
6794   \ifx\VTeXversion\@undefined
6795     \z@
6796   \else
6797     \ifx\VTeXversion\relax
6798       \z@
6799     \else
6800       \VTeXversion
6801     \fi
6802   \fi
6803 }
6804 \begingroup
6805   \ifnum\Hy@VTeXversion<660 %
6806     \gdef\Hy@PutCatalog#1{%
6807       \Hy@WarningNoLine{%
6808         VTeX 6.59g or above required for pdfpagelabels%
6809       }%
6810     }%
6811   \else
6812     \gdef\Hy@PutCatalog#1{%
6813       \Hy@vt@PutCatalog#1/PageLabels<<>>\@nil
6814     }%
6815     \gdef\Hy@vt@PutCatalog#1/PageLabels<<#2>>#3\@nil{%
6816       \ifx\#2\%
6817         \else
6818           \immediate\special{!pdfpagelabels #2}%
6819         \fi
6820       }%
6821     \fi
6822 \endgroup
6823 < /vtex>

6824 < *pdfTeX | vtex>

```

\HyPL@StorePageLabel This macro adds the entry #1 to \HyPL@Labels.

```

6825 \ifHy@pdfpagelabels
6826   \def\HyPL@StorePageLabel#1{%
6827     \toks@\expandafter{\HyPL@Labels}%
6828     \xdef\HyPL@Labels{%
6829       \the\toks@
6830       \the\Hy@abspace<<#1>>%

```

```

6831 }%
6832 }%

```

Package atveryend is used to get behind the final `\clearpage` and to avoid a `\clearpage` in `\AtEndDocument`. Then the PDF catalog entry for `\PageLabels` is set.

```

6833 \RequirePackage{atveryend}[2009/12/07]%
6834 \AtVeryEndDocument{%
6835   \HyPL@SetPageLabels
6836 }%

6837 \fi
6838 </pdfTeX | vtex>

```

28.1.2 xetex

```

6839 <*xetex>
6840 \HyPsd@LoadUnicode
6841 \Hy@unicodetrue
6842 \ifx\HyPsd@pdfencoding\HyPsd@pdfencoding@unicode
6843 \else
6844   \let\HyPsd@pdfencoding\HyPsd@pdfencoding@auto
6845 \fi
6846 \HyPsd@LoadStringEnc
6847 \define@key{Hyp}{unicode}[true]{%
6848   \Hy@boolkey{unicode}{#1}%
6849   \ifHy@unicode
6850   \else
6851     \Hy@Warning{%
6852       XeTeX driver only supports 'unicode=true'. Ignoring\MessageBreak
6853       option setting 'unicode=false'%
6854     }%
6855     \Hy@unicodetrue
6856   \fi
6857 }
6858 \define@key{Hyp}{pdfencoding}{%
6859   \edef\HyPsd@temp{#1}%
6860   \ifx\HyPsd@temp\HyPsd@pdfencoding@unicode
6861     \let\HyPsd@pdfencoding\HyPsd@temp
6862   \else
6863     \ifx\HyPsd@temp\HyPsd@pdfencoding@auto
6864       \let\HyPsd@pdfencoding\HyPsd@temp
6865     \else
6866       \Hy@Warning{%
6867         XeTeX driver only supports\MessageBreak
6868         'pdfencoding=unicode|auto'. Ignoring option\MessageBreak
6869         setting 'pdfencoding=\HyPsd@temp'%
6870       }%
6871     \fi
6872   \fi
6873 }
6874 \let\HyXeTeX@CheckUnicode\relax
6875 </xetex>

```

28.1.3 pdfmarkbase, dvipdfm, xetex

```

6876 <*pdfmarkbase>
6877 \begingroup
6878 \@ifundefined{headerps@out}{-}{%

```

```

6879 \toks@\expandafter{\Hy@FirstPageHook}%
6880 \xdef\Hy@FirstPageHook{%
6881 \noexpand\headerps@out{%
6882 systemdict /pdfmark known%
6883 {%
6884 userdict /?pdfmark systemdict /exec get put%
6885 }{%
6886 userdict /?pdfmark systemdict /pop get put %
6887 userdict /pdfmark systemdict /cleartomark get put%
6888 }%
6889 ifelse%
6890 }%
6891 \the\toks@
6892 }%
6893 }%
6894 \endgroup
6895 \pdfmarkbase

```

\Hy@PutCatalog

```

6896 \dvi\pdfm | xetex\def\Hy@PutCatalog#1{\@pdfm@mark{docview <<#1>>}}
6897 \pdfmarkbase
6898 \def\Hy@PutCatalog#1{%
6899 \pdfmark{pdfmark=/PUT,Raw={\string{Catalog\string} <<#1>>}}%
6900 }
6901 \pdfmarkbase

6902 \pdfmarkbase | dvi\pdfm | xetex
6903 \ifHy@pdfpagelabels

```

\HyPL@StorePageLabel This macro writes a string to the .aux file.

```

6904 \def\HyPL@StorePageLabel#1{%
6905 \if@filesw
6906 \begin{group}
6907 \edef\Hy@tempa{\the\Hy@abspage<<#1>>}%
6908 \immediate\write\@mainaux{%
6909 \string\HyPL@Entry{\Hy@tempa}%
6910 }%
6911 \end{group}
6912 \fi
6913 }%

```

Write a dummy definition of \HyPL@Entry for the case, that the next run is done without hyperref. A marker for the rerun warning is set and the /PageLabels is written.

```

6914 \Hy@AtBeginDocument{%
6915 \if@filesw
6916 \immediate\write\@mainaux{%
6917 \string\providecommand\string*\string\HyPL@Entry[1]{}%
6918 }%
6919 \fi
6920 \ifx\HyPL@Labels\@empty
6921 \Hy@WarningNoLine{Rerun to get /PageLabels entry}%
6922 \else
6923 \HyPL@SetPageLabels
6924 \fi
6925 \let\HyPL@Entry\@gobble
6926 }%

```

`\HyPL@Entry`

```

6927 \def\HyPL@Entry#1{%
6928   \expandafter\gdef\expandafter\HyPL@Labels\expandafter{%
6929     \HyPL@Labels
6930     #1%
6931   }%
6932 }%

6933 \fi
6934 </pdfmarkbase | dvipdfm | xetex>
6935 <*package>

6936 \ifx\MaybeStopEarly\relax
6937 \else
6938   \Hy@stoppedearyltrue
6939   \expandafter\MaybeStopEarly
6940 \fi
6941 \Hy@stoppedearylfalse

```

29 Automated L^AT_EX hypertext cross-references

Anything which can be referenced advances some counter; we overload this to put in a hypertext starting point (with no visible anchor), and make a note of that for later use in `\label`. This will fail badly if `\theH<name>` does not expand to a sensible reference. This means that classes or package which introduce new elements need to define an equivalent `\theH<name>` for every `\the<name>`. We do make a trap to make `\theH<name>` be the same as `\arabic{<name>}`, if `\theH<name>` is not defined, but this is not necessarily a good idea. Alternatively, the ‘naturalnames’ option uses whatever L^AT_EX provides, which may be useable. But then it's up to you to make sure these are legal PDF and HTML names. The ‘hypertextnames=false’ option just makes up arbitrary names.

All the shenanigans is to make sure section numbers etc are always arabic, separated by dots. Who knows how people will set up `\@currentlabel`? If they put spaces in, or brackets (quite legal) then the hypertext processors will get upset.

But this is flaky, and open to abuse. Styles like `subeqn` will mess it up, for starters. Appendices are an issue, too. We just hope to cover most situations. We can at least cope with the standard sectioning structure, allowing for `\part` and `\chapter`.

Start with a fallback for equations

```

6942 \def\Hy@CounterExists#1{%
6943   \begingroup\expandafter\expandafter\expandafter\endgroup
6944   \expandafter\ifx\csname c@#1\endcsname\relax
6945     \expandafter\@gobble
6946   \else
6947     \begingroup\expandafter\expandafter\expandafter\endgroup
6948     \expandafter\ifx\csname the#1\endcsname\relax
6949       \expandafter\expandafter\expandafter\@gobble
6950     \else
6951       \expandafter\expandafter\expandafter\@firstofone
6952     \fi
6953   \fi
6954 }
6955 \Hy@CounterExists{section}{%
6956   \providecommand\theHequation{\theHsection.\arabic{equation}}}%
6957 }

```



```

6958 \Hy@CounterExists{part}{%
6959 \providecommand\theHpart{\arabic{part}}}%
6960 }
6961 \ltx@ifundefined{thechapter}{%
6962 \providecommand\theHsection {\arabic{section}}%
6963 \providecommand\theHfigure {\arabic{figure}}%
6964 \providecommand\theHtable {\arabic{table}}%
6965 }{%
6966 \providecommand\theHchapter {\arabic{chapter}}%
6967 \providecommand\theHfigure {\theHchapter.\arabic{figure}}%
6968 \providecommand\theHtable {\theHchapter.\arabic{table}}%
6969 \providecommand\theHsection {\theHchapter.\arabic{section}}%
6970 }
6971 \providecommand\theHsubsection {\theHsection.\arabic{subsection}}
6972 \providecommand\theHsubsubsection{\theHsubsection.\arabic{subsubsection}}
6973 \providecommand\theHparagraph {\theHsubsubsection.\arabic{paragraph}}
6974 \providecommand\theHsubparagraph {\theHparagraph.\arabic{subparagraph}}
6975 \providecommand\theHtheorem {\theHsection.\arabic{theorem}}
6976 \providecommand\theHthm {\theHsection.\arabic{thm}}

```

Thanks to Greta Meyer (gbd@pop.cwru.edu) for making me realize that enumeration starts at 0 for every list! But `\item` occurs inside `\trivlist`, so check if its a real `\item` before incrementing counters.

```

6977 \let\H@item\item
6978 \newcounter{Item}
6979 \def\theHItem{\arabic{Item}}
6980 \def\item{%
6981 \@hyper@itemfalse
6982 \if@nmbrlist\@hyper@itemtrue\fi
6983 \H@item
6984 }
6985 \providecommand\theHenumi {\theHItem}
6986 \providecommand\theHenumii {\theHItem}
6987 \providecommand\theHenumiii {\theHItem}
6988 \providecommand\theHenumiv {\theHItem}
6989 \providecommand\theHHfootnote {\arabic{Hfootnote}}
6990 \providecommand\theHmpfootnote{\arabic{mpfootnote}}
6991 \@ifundefined{theHHmpfootnote}{%
6992 \let\theHHmpfootnote\theHHfootnote
6993 }{}

```

Tanmoy asked for this default handling of undefined `\theH<name>` situations. It really isn't clear what would be ideal, whether to turn off hyperizing of unknown elements, to pick up the textual definition of the counter, or to default it to something like `\arabic{name}`. We take the latter course, slightly worriedly.

```

6994 \let\H@refstepcounter\refstepcounter
6995 \edef\name@of@eq{equation}%
6996 \edef\name@of@slide{slide}%

```

We do not want the handler for `\refstepcounter` to cut in during the processing of `\item` (we handle that separately), so we provide a bypass conditional.

```

6997 \newif\if@hyper@item
6998 \newif\if@skiphyperref
6999 \@hyper@itemfalse
7000 \@skiphyperreffalse
7001 \def\refstepcounter#1{%
7002 \ifHy@pdfstring
7003 \else

```

```

7004 \H@refstepcounter{#1}%
7005 \edef\This@name{#1}%
7006 \ifx\This@name\name@of@slide
7007 \else
7008 \if@skiphyperref
7009 \else
7010 \if@hyper@item
7011 \stepcounter{Item}%
7012 \hyper@refstepcounter{Item}%
7013 \@hyper@itemfalse
7014 \else
7015 \hyper@refstepcounter{#1}%
7016 \fi
7017 \fi
7018 \fi
7019 \fi
7020 }
7021 \let\Hy@saved@refstepcounter\refstepcounter

```

AMS \LaTeX processes all equations twice; we want to make sure that the hyper stuff is not executed twice, so we use the AMS `\ifmeasuring@`, initialized if AMS math is not used.

```

7022 \@ifpackageloaded{amsmath}{\newif\ifmeasuring@\measuring@false}

```

`\hyper@refstepcounter`

```

7023 \def\hyper@refstepcounter#1{%
7024 \edef\This@name{#1}%
7025 \ifx\This@name\name@of@eq
7026 \@ifundefined{theHequation}{%
7027 \make@stripped@name{\theequation}%
7028 \let\theHequation\newname
7029 }{}%
7030 \fi
7031 \HyCnt@ProvideTheHCounter{#1}%
7032 \hyper@makecurrent{#1}%
7033 \ifmeasuring@
7034 \else
7035 \Hy@raisedlink{%
7036 \hyper@anchorstart{\@currentHref}\hyper@anchorend
7037 }%
7038 \fi
7039 }

```

`\Hy@ProvideTheHCounter` `\theH<counter>` is not set for counters that are defined before ‘hyperref’ is loaded. In `\clearcount`, the clear counter list of the artificial counter `@ckpt`, \LaTeX remembers the defined counters (needed for `\include`). We check the clear counter lists, whether our counter is present. If we found it, then we add the parent counter value to `\theH<counter>`. The `\@elt` list is used in sanitized form for the comparison, because the list might contain other stuff than `\@elts`. Also it simplifies the implementation, because \LaTeX , substring search `\in@` can be used.

```

7040 \def\HyCnt@ProvideTheHCounter#1{%
7041 \@ifundefined{theH#1}{%
7042 \expandafter\def\csname theH#1\endcsname{}%
7043 \def\Hy@temp{\@elt{#1}}%
7044 \ltx@onelevel@sanitize\Hy@temp
7045 \let\HyOrg@elt\@elt
7046 \edef\@elt{%

```

```

7047 \noexpand\HyCnt@LookForParentCounter
7048 \expandafter\noexpand\csname theH#1\endcsname
7049 }%
7050 \cl@@ckpt
7051 \let\@elt\HyOrg@elt
7052 \expandafter
7053 \ltx@LocalAppendToMacro\csname theH#1\expandafter\endcsname
7054 \expandafter{%
7055 \expandafter\@arabic\csname c@#1\endcsname
7056 }%
7057 }{}%
7058 }

```

\Hy@LookForParentCounter

```

7059 \def\HyCnt@LookForParentCounter#1#2{%
7060 \expandafter\let\expandafter\Hy@temp@A\csname cl@#2\endcsname
7061 \ltx@ifundefined{cl@#2}{%
7062 }{%
7063 \ltx@onelevel@sanitize\Hy@temp@A
7064 \edef\Hy@temp@A{%
7065 \noexpand\in@{\Hy@temp}{\Hy@temp@A}%
7066 }\Hy@temp@A
7067 \ifin@
7068 \ltx@ifundefined{theH#2}{%
7069 \expandafter\ltx@LocalAppendToMacro\expandafter#1%
7070 \expandafter{%
7071 \expandafter\@arabic\csname c@#2\endcsname.%
7072 }%
7073 }{%
7074 \expandafter\ltx@LocalAppendToMacro\expandafter#1%
7075 \expandafter{%
7076 \csname theH#2\endcsname.%
7077 }%
7078 }%
7079 \fi
7080 }%
7081 }

```

After \appendix “chapter” (or “section” for classes without chapter) should be replaced by “appendix” to get \autoref work. Macro \Hy@chapapp contains the current valid name like \@chapapp, which cannot be used, because this string depends on the current language.

The “french” package defines counter \thechapter by \newcounterchapter, if \@ifundefinedchapter.

```

7082 \begingroup\expandafter\expandafter\expandafter\endgroup
7083 \expandafter\ifx\csname chapter\endcsname\relax
7084 \def\Hy@chapterstring{section}%
7085 \else
7086 \def\Hy@chapterstring{chapter}%
7087 \fi
7088 \def\Hy@appendixstring{appendix}
7089 \def\Hy@chapapp{\Hy@chapterstring}
7090 \ltx@ifundefined{appendix}{%
7091 }{%
7092 \let\HyOrg@appendix\appendix
7093 \def\Hy@AlphNoErr#1{%
7094 \ifnum\value{#1}>26 %

```

```

7095     Alph\number\value{#1}%
7096   \else
7097     \ifnum\value{#1}<1 %
7098       Alph\number\value{#1}%
7099     \else
7100       \Alph{#1}%
7101     \fi
7102   \fi
7103 }%
7104 \def\appendix{%
7105   \ltx@ifundefined{chapter}{%
7106     \gdef\theHsection{\Hy@AlphNoErr{section}}%
7107   }{%
7108     \gdef\theHchapter{\Hy@AlphNoErr{chapter}}%
7109   }%
7110   \xdef\Hy@chapapp{\Hy@appendixstring}%
7111   \HyOrg@appendix
7112 }%
7113 }

```

\Hy@Test@alph

```

7114 \def\Hy@Test@alph#1{%
7115   \ifcase#1\or
7116     a\or b\or c\or d\or e\or f\or g\or h\or i\or j\or
7117     k\or l\or m\or n\or o\or p\or q\or r\or s\or t\or
7118     u\or v\or w\or x\or y\or z%
7119   \else
7120     \@ctrerr
7121   \fi
7122 }

```

\Hy@Test@Alph

```

7123 \def\Hy@Test@Alph#1{%
7124   \ifcase#1\or
7125     A\or B\or C\or D\or E\or F\or G\or H\or I\or J\or
7126     K\or L\or M\or N\or O\or P\or Q\or R\or S\or T\or
7127     U\or V\or W\or X\or Y\or Z%
7128   \else
7129     \@ctrerr
7130   \fi
7131 }

```

\hyper@makecurrent Because of Babel mucking around, nullify \textlatin when making names. And \@number because of babel's lrbabel.def.

```

7132 \def\hyper@makecurrent#1{%
7133   \begingroup
7134     \Hy@safe@activetrue
7135     \edef\Hy@param{#1}%
7136     \ifx\Hy@param\Hy@chapterstring
7137       \let\Hy@param\Hy@chapapp
7138     \fi
7139     \ifHy@hypertextnames
7140       \let\@number\@firstofone
7141       \def\@fnsymbol##1{\fnsymbol\number##1}%
7142       \def\@arabic##1{\number##1}%
7143       \ifx\@alph\Hy@Test@alph
7144         \else

```

```

7145 \def\@alph{alph\number}%
7146 \fi
7147 \ifx\@Alph\Hy@Test@Alph
7148 \else
7149 \def\@Alph{Alph\number}%
7150 \fi
7151 \ifHy@naturalnames
7152 \let\textlatin\@firstofone
7153 \xdef\HyperGlobalCurrentHref{\csname the#1\endcsname}%
7154 \else
7155 \xdef\HyperGlobalCurrentHref{%
7156 \csname
7157 the%
7158 \expandafter\ifx\csname theH#1\endcsname\relax\else H\fi
7159 #1%
7160 \endcsname
7161 }%
7162 \fi
7163 \xdef\HyperGlobalCurrentHref{%
7164 \Hy@param.\expandafter\strip@prefix\meaning\HyperGlobalCurrentHref
7165 }%
7166 \else
7167 \Hy@GlobalStepCount\Hy@linkcounter
7168 \xdef\HyperGlobalCurrentHref{\Hy@param.\the\Hy@linkcounter}%
7169 \fi
7170 \endgroup
7171 \let\HyperLocalCurrentHref\HyperGlobalCurrentHref
7172 \ifHy@localanchorname
7173 \let\@currentHref\HyperLocalCurrentHref
7174 \else
7175 \global\let\@currentHref\HyperGlobalCurrentHref
7176 \fi
7177 }

```

\Hy@MakeCurrentHref

```

7178 \def\Hy@MakeCurrentHref#1{%
7179 \edef\HyperLocalCurrentHref{#1}%
7180 \@onelevel@sanitize\HyperLocalCurrentHref
7181 \global\let\HyperGlobalCurrentHref\HyperLocalCurrentHref
7182 \let\HyperLocalCurrentHref\HyperGlobalCurrentHref
7183 \ifHy@localanchorname
7184 \let\@currentHref\HyperLocalCurrentHref
7185 \else
7186 \global\let\@currentHref\HyperGlobalCurrentHref
7187 \fi
7188 }

```

\Hy@MakeCurrentHrefAuto

```

7189 \def\Hy@MakeCurrentHrefAuto#1{%
7190 \Hy@GlobalStepCount\Hy@linkcounter
7191 \Hy@MakeCurrentHref{#1.\the\Hy@linkcounter}%
7192 }

```

\@currentHlabel \@currrentHlabel is only defined for compatibility with package ‘hypdvips’.

```

7193 \def\@currentHlabel{\@currentHref}

7194 \@ifpackageloaded{fancyvrb}{%

```

```

7195 \@@ifpackagelater{fancyvrb}{1998/05/20}{-}{-}%
7196 \def\FV@StepLineNo{%
7197   \FV@SetLineNo
7198   \def\FV@StepLineNo{\H@refstepcounter{FancyVerbLine}}%
7199   \FV@StepLineNo
7200 }%
7201 }%
7202 }-}

```

30 Package lastpage support

Package lastpage directly writes the `\newlabel` command to the aux file. Because package hyperref requires additional arguments, the internal command `\lastpage@putlabel` is redefined. The patch is deferred by `\AtBeginDocument`, because it is possible that package lastpage is loaded after package hyperref. The same algorithm (options `hypertextnames` and `plainpages`) is used to get the page anchor name as in `\Hy@EveryPageAnchor` (see sec. 39). The link will not work if option `pageanchor` is set to false.

```

\lastpage@putlabel
7203 \Hy@AtBeginDocument{%
7204   \@@ifclassloaded{revtex4}{-}%
7205   \@@namedef{ver@lastpage.sty}{1994/06/25}%
7206   }-}%
7207 \@@ifpackageloaded{lastpage}{-}%
7208   \ifHy@pageanchor
7209   \else
7210     \Hy@WarningNoLine{%
7211       The \string\pageref{LastPage} link doesn't work\MessageBreak
7212       with disabled option 'pageanchor'%
7213     }%
7214   \fi
7215   \def\lastpage@putlabel{%
7216     \addtocounter{page}{-1}%
7217     \if@filesw
7218       \begingroup
7219         \let\@number\@firstofone
7220         \ifHy@pageanchor
7221           \ifHy@hypertextnames
7222             \ifHy@plainpages
7223               \def\Hy@temp{\arabic{page}}%
7224             \else
7225               \Hy@unicodedefalse
7226               \pdfstringdef\Hy@temp{\thepage}%
7227             \fi
7228           \else
7229             \def\Hy@temp{\the\Hy@pagecounter}%
7230           \fi
7231         \fi
7232         \immediate\write\@auxout{%
7233           \string\newlabel
7234           {LastPage}{-}{\thepage}{-}%
7235           \ifHy@pageanchor page.\Hy@temp\fi}{-}}%
7236       }%
7237     \endgroup
7238   \fi

```

```

7239 \addtocounter{page}{1}%
7240 }%
7241 \@ifclassloaded{revtex4}{%
7242 \begingroup
7243 \toks@{\expandafter{\lastpage@putlabel}}%
7244 \edef\x{\endgroup
7245 \def\noexpand\lastpage@putlabel{%
7246 \noexpand\stepcounter{page}%
7247 \the\toks@
7248 \noexpand\addtocounter{page}\noexpand\m@ne
7249 }%
7250 }%
7251 \x
7252 }{}%
7253 }{}%
7254 }
7255 \endpackage
7256 \check
7257 \checkpackage{lastpage}[1994/06/25]
7258 \checkcommand\def\lastpage@putlabel{%
7259 \addtocounter{page}{-1}%
7260 \immediate\write\@auxout{%
7261 \string\newlabel{LastPage}{{}\{\thepage}}%
7262 }%
7263 \addtocounter{page}{1}%
7264 }
7265 \endcheck
7266 \endpackage

```

31 Package ifthen support

Since version 6.75a this is done in package nameref.

For compatibility `\hypergetref` and `\hypergetpageref` are still provided. But they do not generate warnings, if the reference is undefined.

```

7267 \def\hypergetref#1{\getrefbykeydefault{#1}{}{??}}
7268 \def\hypergetpageref#1{\getrefbykeydefault{#1}{page}{0}}

```

32 Package titlesec and titletoc support

This code is contributed by Javier Bezos (Email: jbezos@arrakis.es).

Package titlesec support:

```

7269 \@ifpackageloaded{titlesec}{%
7270 \def\ttl@Hy@steplink#1{%
7271 \Hy@MakeCurrentHrefAuto{#1*}%
7272 \edef\ttl@Hy@saveanchor{%
7273 \noexpand\Hy@raisedlink{%
7274 \noexpand\hyper@anchorstart{\@currentHref}%
7275 \noexpand\hyper@anchorend
7276 \def\noexpand\ttl@Hy@SavedCurrentHref{\@currentHref}%
7277 \noexpand\ttl@Hy@PatchSaveWrite
7278 }%
7279 }%
7280 }%
7281 \def\ttl@Hy@PatchSaveWrite{%
7282 \begingroup

```

```

7283 \toks@\expandafter{\ttl@savewrite}%
7284 \edef\x{\endgroup
7285 \def\noexpand\ttl@savewrite{%
7286 \let\noexpand\@currentHref
7287 \noexpand\ttl@Hy@SavedCurrentHref
7288 \the\toks@
7289 }%
7290 }%
7291 \x
7292 }%
7293 \def\ttl@Hy@refstepcounter#1{%
7294 \let\ttl@b\Hy@raisedlink
7295 \def\Hy@raisedlink##1{%
7296 \def\ttl@Hy@saveanchor{\Hy@raisedlink{##1}}%
7297 }%
7298 \refstepcounter{#1}%
7299 \let\Hy@raisedlink\ttl@b
7300 }%
7301 }{}

Package titletoc support:
7302 \@ifpackageloaded{titletoc}{%
7303 \def\ttl@gobblecontents#1#2#3#4{\ignorespaces}%
7304 }{}

```

33 Package varioref support

Package nameref uses five arguments for the ref system. Fix provided by Felix Neubauer (felix.neubauer@gmx.net).

```

7305 \def\Hy@varioref@undefined{??}{??}{-}{-}{-}
7306 \@ifpackageloaded{varioref}{%
7307 \def\vref@pagenum#1#2{%
7308 \@ifundefined{r@#2}{%
7309 \expandafter\let\csname r@#2\endcsname\Hy@varioref@undefined
7310 }{}%
7311 \edef#1{\getpagerefnumber{#2}}%
7312 }%
7313 }{}

```

Package varioref redefines `\refstepcounter`, thus it needs fixing, if the package is loaded *after* `hyperref`.

```

7314 \def\Hy@varioref@refstepcounter#1{%
7315 \stepcounter{#1}%
7316 \protected@edef\@currentlabel{%
7317 \csname p@#1\expandafter\endcsname\csname the#1\endcsname
7318 }%
7319 }
7320 \AtBeginDocument{%
7321 \ifx\refstepcounter\Hy@varioref@refstepcounter
7322 \let\H@refstepcounter\refstepcounter
7323 \let\refstepcounter\Hy@saved@refstepcounter
7324 \fi
7325 }

```


34 Package longtable support

Sometimes the anchor of the longtable goes to the previous page. Thus the following patch separates the anchor setting and counter incrementation by hyperref's `\refstepcounter` and the anchor setting is moved after `\vskip\LTpre`.

Patch of `\LT@array`: replace `\refstepcounter` by the original `\H@refstepcounter` without anchor generation

```

7326 \@ifpackageloaded{longtable}{%
7327   \begingroup
7328   \def\y{\LT@array}%
7329   \@ifundefined{scr@LT@array}{%
7330     \@ifundefined{adl@LT@array}{\def\y{\adl@LT@array}}{%
7331       \def\y{\scr@LT@array}}%
7332   \long\def\x\refstepcounter#1#2\@sharp#3#4\@nil{%
7333     \expandafter\endgroup
7334     \expandafter\def\y[##1]##2{%
7335       \H@refstepcounter{#1}%
7336       \hyper@makecurrent{table}%
7337       \let\Hy@LT@currentHref\@currentHref
7338       #2\@sharp###4%
7339     }%
7340   }%
7341   \expandafter\expandafter\expandafter\x\y[{#1}]{#2}\@nil

```

Patch of `\LT@start`: add anchor before first line after `\vskip\LTpre`

```

7342   \begingroup
7343   \def\x#1\ifvoid\LT@foot#2\fi#3\@nil{%
7344     \endgroup
7345     \def\LT@start{%
7346       #1%
7347       \ifvoid\LT@foot#2\fi
7348       \let\@currentHref\Hy@LT@currentHref
7349       \Hy@raisedlink{%
7350         \hyper@anchorstart{\@currentHref}\hyper@anchorend
7351       }%
7352       #3%
7353     }%
7354   }%
7355   \expandafter\x\LT@start\@nil
7356 }{}

```

35 Equations

We want to make the whole equation a target anchor. Overload equation, temporarily reverting to original `\refstepcounter`. If, however, it is in AMS math, we do not do anything, as the tag mechanism is used there (see section 42). The exception is that we move the equation incrementation inside the math environment to avoid specials outside and a wrong vertical spacing of equation environments.

```

7357 \let\new@refstepcounter\refstepcounter
7358 \let\H@equation\equation
7359 \let\H@endequation\endequation

7360 \@ifpackageloaded{amsmath}{%
7361   \long\def\Hy@temp{%
7362     \incr@eqnum
7363     \mathdisplay@push

```

```

7364 \st@rredfalse \global\@eqnswtrue
7365 \mathdisplay{equation}%
7366 }%
7367 \ifx\Hy@temp\equation
7368 \expandafter\ifx\csname if@fleqn\expandafter\endcsname
7369 \csname iftrue\endcsname
7370 \else
7371 \long\def\equation{%
7372 \mathdisplay@push
7373 \st@rredfalse \global\@eqnswtrue
7374 \mathdisplay{equation}%
7375 \incr@eqnum
7376 }%
7377 \fi
7378 \fi
7379 }{%
7380 \def\equation{%
7381 \let\refstepcounter\H@refstepcounter
7382 \H@equation
7383 \@ifundefined{theHequation}{%
7384 \make@stripped@name{\theequation}%
7385 \let\theHequation\newname
7386 }{}%
7387 \hyper@makecurrent{equation}%

```

`\mathopen` is needed in case the equation starts with an unary minus, for example.

```

7388 \mathopen{%
7389 \Hy@raisedlink{\hyper@anchorstart{\@currentHref}}}%
7390 }%
7391 \let\refstepcounter\new@refstepcounter
7392 }%
7393 \def\endequation{%
7394 \ifx\Hy@raisedlink\ltx@empty
7395 \hyper@anchorend
7396 \else
7397 \mathclose{\Hy@raisedlink{\hyper@anchorend}}}%
7398 \fi
7399 \H@endequation
7400 }%
7401 }

```

My goodness, why can't L^AT_EX be consistent? Why is `\eqnarray` set up differently from other objects?

People (you know who you are, Thomas Beuth) sometimes make an `eqnarray` where *all* the lines end with `\notag`, so there is no suitable anchor at all. In this case, pass by on the other side.

```

7402 \newif\if@eqnstar
7403 \@eqnstarfalse
7404 \let\H@eqnarray\eqnarray
7405 \let\H@endeqnarray\endeqnarray
7406 \def\eqnarray{%
7407 \let\Hy@reserved@a\relax
7408 \def\@currentHref{}%
7409 \H@eqnarray
7410 \if@eqnstar
7411 \else
7412 \ifx\\\@currentHref\\%
7413 \else

```

```

7414 \ifundefined{theHequation}{%
7415 \make@stripped@name{\theequation}%
7416 \let\theHequation\newname
7417 }{}%
7418 \hyper@makecurrent{equation}%
7419 \mathopen{%
7420 \Hy@raisedlink{%
7421 \hyper@anchorstart{\@currentHref}\hyper@anchorend
7422 }%
7423 }%
7424 \fi
7425 \fi
7426 }
7427 \def\endeqnarray{%
7428 \H@endeqnarray
7429 }

```

This is quite heavy-handed, but it works for now. If its an `eqnarray*` we need to disable the hyperref actions. There may well be a cleaner way to trap this. Bill Moss found this.

```

7430 \@namedef{eqnarray*}{%
7431 \def\@eqnocr{\nonumber\@seqnocr}\@eqnstartrue\eqnarray
7432 }
7433 \@namedef{endeqnarray*}{%
7434 \nonumber\endeqnarray\@eqnstarfalse
7435 }

```

Then again, we have the *subeqnarray* package. Tanmoy provided some code for this:

```

7436 \ltx@ifundefined{subeqnarray}{}{%
7437 \let\H@subeqnarray\subeqnarray
7438 \let\H@endsubeqnarray\endsubeqnarray
7439 \def\subeqnarray{%
7440 \let\Hy@reserved@a\relax
7441 \H@subeqnarray
7442 \@ifundefined{theHequation}{%
7443 \make@stripped@name{\theequation}%
7444 \let\theHequation\newname
7445 }{}%
7446 \hyper@makecurrent{equation}%
7447 \hyper@anchorstart{\@currentHref}\hyper@anchorend
7448 }%
7449 \def\endsubeqnarray{%
7450 \H@endsubeqnarray
7451 }%
7452 \providecommand\theHsubequation{\theHequation\alph{subequation}}%
7453 }

```

The aim of this macro is to produce a sanitized version of its argument, to make it a safe label.

```

7454 \def\make@stripped@name#1{%
7455 \begingroup
7456 \escapechar\m@ne
7457 \global\let\newname\@empty
7458 \protected@edef\Hy@tempa{#1}%
7459 \edef\@tempb{%
7460 \noexpand\@tfor\noexpand\Hy@tempa:=%
7461 \expandafter\strip@prefix\meaning\Hy@tempa

```

```

7462 }%
7463 \@tempb\do{%
7464   \if{\Hy@tempa\else
7465     \if{\Hy@tempa\else
7466       \xdef\newname{\newname\Hy@tempa}%
7467     \fi
7468   \fi
7469 }%
7470 \endgroup
7471 }

```

Support for amsmath's subequations:

```

7472 \begingroup\expandafter\expandafter\expandafter\endgroup
7473 \expandafter\ifx\csname subequations\endcsname\relax
7474 \else
7475   \let\HyOrg@subequations\subequations
7476   \def\subequations{%
7477     \stepcounter{equation}%
7478     \protected@edef\theHparentequation{%
7479       \ifundefined{theHequation}\theequation\theHequation
7480     }%
7481     \addtocounter{equation}{-1}%
7482     \HyOrg@subequations
7483     \def\theHequation{\theHparentequation\alph{equation}}%
7484     \ignorespaces
7485   }%
7486 \fi

```

Support for package `amsthm` (Daniel Müllner):

```

7487 \@ifpackageloaded{amsthm}{%

```

Class `amsbook` uses a different definition of `\@thm`, where two lines are added (thanks to Dan Luecking for his analysis):

```

    \let\thm@indent\indent % indent
    \thm@headfont{\scshape}% heading font small caps

7488 \def\Hy@temp#1#2#3{%
7489   \ifhmode\unskip\unskip\par\fi
7490   \normalfont
7491   \trivlist
7492   \let\thmheadnl\relax
7493   \let\thm@swap\@gobble
7494   \let\thm@indent\indent % indent
7495   \thm@headfont{\scshape}% heading font small caps
7496   \thm@notefont{\fontseries\mddefault\upshape}%
7497   \thm@headpunct{.}% add period after heading
7498   \thm@headsep 5\p@ plus\p@ minus\p@\relax
7499   \thm@space@setup
7500   #1% style overrides
7501   \@topsep \thm@preskip % used by thm head
7502   \@topsepadd \thm@postskip % used by \@endparenv
7503   \def\@tempa{#2}\ifx\@empty\@tempa
7504     \def\@tempa{\@oparg{\@begintheorem{#3}{}}{}}%
7505   \else
7506     \refstepcounter{#2}%
7507     \def\@tempa{%
7508       \@oparg{\@begintheorem{#3}{\csname the#2\endcsname}}{}}%
7509   }%
7510 \fi

```

```

7511 \@tempa
7512 }%
7513 \ifx\Hy@temp\@thm
7514 \def\@thm#1#2#3{%
7515 \ifhmode
7516 \unskip\unskip\par
7517 \fi
7518 \normalfont
7519 \trivlist
7520 \let\thmheadnl\relax
7521 \let\thm@swap\@gobble
7522 \let\thm@indent\indent % indent
7523 \thm@headfont{\scshape}% heading font small caps
7524 \thm@notefont{\fontseries\mddefault\upshape}%
7525 \thm@headpunct{.}% add period after heading
7526 \thm@headsep 5\p@ plus\p@ minus\p@\relax
7527 \thm@space@setup
7528 #1% style overrides
7529 \@topsep \thm@preskip % used by thm head
7530 \@topsepadd \thm@postskip % used by \@endparenv
7531 \def\dth@counter{#2}%
7532 \ifx\@empty\dth@counter
7533 \def\@tempa{%
7534 \@oparg{\@begintheorem{#3}{}}{}%
7535 }%
7536 \else
7537 \H@refstepcounter{#2}%
7538 \hyper@makecurrent{#2}%
7539 \let\Hy@dth@currentHref\@currentHref
7540 \def\@tempa{%
7541 \@oparg{\@begintheorem{#3}{\csname the#2\endcsname}}{}%
7542 }%
7543 \fi
7544 \@tempa
7545 }%
7546 \else
7547 \def\@thm#1#2#3{%
7548 \ifhmode
7549 \unskip\unskip\par
7550 \fi
7551 \normalfont
7552 \trivlist
7553 \let\thmheadnl\relax
7554 \let\thm@swap\@gobble
7555 \thm@notefont{\fontseries\mddefault\upshape}%
7556 \thm@headpunct{.}% add period after heading
7557 \thm@headsep 5\p@ plus\p@ minus\p@\relax
7558 \thm@space@setup
7559 #1% style overrides
7560 \@topsep \thm@preskip % used by thm head
7561 \@topsepadd \thm@postskip % used by \@endparenv
7562 \def\dth@counter{#2}%
7563 \ifx\@empty\dth@counter
7564 \def\@tempa{%
7565 \@oparg{\@begintheorem{#3}{}}{}%
7566 }%
7567 \else

```

```

7568 \H@refstepcounter{#2}%
7569 \hyper@makecurrent{#2}%
7570 \let\Hy@dth@currentHref\@currentHref
7571 \def\@tempa{%
7572 \@oparg{\@begintheorem{#3}{\csname the#2\endcsname}}{}%
7573 }%
7574 \fi
7575 \@tempa
7576 }%
7577 \fi
7578 \dth@everypar={%
7579 \@minipagefalse
7580 \global\@newlistfalse
7581 \@noparitemfalse
7582 \if@inlabel
7583 \global\@inlabelfalse
7584 \begingroup
7585 \setbox\z@\lastbox
7586 \ifvoid\z@
7587 \kern-\itemindent
7588 \fi
7589 \endgroup
7590 \ifx\@empty\dth@counter
7591 \else
7592 \Hy@raisedlink{%
7593 \hyper@anchorstart{%
7594 \ltx@ifundefined{Hy@dth@currentHref}%
7595 \@currentHref\Hy@dth@currentHref
7596 }\hyper@anchorend
7597 }%
7598 \fi
7599 \unhbox\@labels
7600 \fi
7601 \if@nobreak
7602 \@nobreakfalse \clubpenalty\@M
7603 \else
7604 \clubpenalty\@clubpenalty \everypar{}%
7605 \fi
7606 }%
7607 }{}

```

36 Footnotes

The footnote mark is a hypertext link, and the text is a target. We separately number the footnotes sequentially through the text, separately from whatever labels the text assigns. Too hard to keep track of markers otherwise. If the raw forms `\footnotemark` and `\footnotetext` are used, force them to use un-hyper original.

```

7608 \ifHy@hyperfootnotes
7609 \newcounter{Hfootnote}%
7610 \let\H@@footnotetext\@footnotetext
7611 \let\H@@footnotemark\@footnotemark
7612 \def\@xfootnotenext[#1]{%
7613 \begingroup
7614 \csname c@\@mpfn\endcsname #1\relax
7615 \unrestored@protected@xdef\@thefnmark{\thempfn}%

```

```

7616 \endgroup
7617 \ifx\@footnotetext\@mpfootnotetext
7618 \expandafter\H@@mpfootnotetext
7619 \else
7620 \expandafter\H@@footnotetext
7621 \fi
7622 }%
7623 \def\@xfootnotemark[#1]{%
7624 \begingroup
7625 \c@footnote #1\relax
7626 \unrestored@protected@xdef\@thefnmark{\thefootnote}%
7627 \endgroup
7628 \H@@footnotemark
7629 }%
7630 \let\H@@mpfootnotetext\@mpfootnotetext
7631 \long\def\@mpfootnotetext#1{%
7632 \H@@mpfootnotetext{%
7633 \ifHy@nesting
7634 \expandafter\ltx@firstoftwo
7635 \else
7636 \expandafter\ltx@secondoftwo
7637 \fi
7638 {%
7639 \expandafter\hyper@@anchor\expandafter{%
7640 \Hy@footnote@currentHref
7641 }{#1}%
7642 }{%
7643 \Hy@raisedlink{%
7644 \expandafter\hyper@@anchor\expandafter{%
7645 \Hy@footnote@currentHref
7646 }{\relax}%
7647 }#1%
7648 }%
7649 }%
7650 }%
7651 \long\def\@footnotetext#1{%
7652 \H@@footnotetext{%
7653 \ifHy@nesting
7654 \expandafter\ltx@firstoftwo
7655 \else
7656 \expandafter\ltx@secondoftwo
7657 \fi
7658 {%
7659 \expandafter\hyper@@anchor\expandafter{%
7660 \Hy@footnote@currentHref
7661 }{#1}%
7662 }{%
7663 \Hy@raisedlink{%
7664 \expandafter\hyper@@anchor\expandafter{%
7665 \Hy@footnote@currentHref
7666 }{\relax}%
7667 }%
7668 \let\@currentHref\Hy@footnote@currentHref
7669 \let\@currentlabelname\@empty
7670 #1%
7671 }%
7672 }%

```

7673 }%

Redefine `\@footnotemark`, borrowing its code (at the cost of getting out of sync with `latex.ltx`), to take advantage of its white space and hyphenation fudges. If we just overload it, we can get variant documents (the word before the footnote is treated differently). Thanks to David Carlisle and Brian Ripley for confusing and helping me on this.

```

7674 \def\@footnotemark{%
7675   \leavevmode
7676   \ifhmode\edef\x@sf{\the\spacefactor}\nobreak\fi
7677   \stepcounter{Hfootnote}%
7678   \global\let\Hy@saved@currentHref\@currentHref
7679   \hyper@makecurrent{Hfootnote}%
7680   \global\let\Hy@footnote@currentHref\@currentHref
7681   \global\let\@currentHref\Hy@saved@currentHref
7682   \hyper@linkstart{link}{\Hy@footnote@currentHref}%
7683   \@makefnmark
7684   \hyper@linkend
7685   \ifhmode\spacefactor\x@sf\fi
7686   \relax
7687 }%
```

Tabularx causes footnote problems, disable the linking if that is loaded. Since v6.82i footnotes are only disabled inside the environment ‘`tabularx`’.

```

7688 \@ifpackageloaded{tabularx}{%
7689   \let\HyOrg@TX@endtabularx\TX@endtabularx
7690   \def\Hy@tabularx@hook{%
7691     \let\@footnotetext\H@@footnotetext
7692     \let\@footnotemark\H@@footnotemark
7693     \let\@mpfootnotetext\H@@mpfootnotetext
7694   }%
7695   \begingroup
7696     \toks@\expandafter{\TX@endtabularx}%
7697     \xdef\Hy@gtemp{%
7698       \noexpand\Hy@tabularx@hook
7699       \the\toks@
7700     }%
7701   \endgroup
7702   \let\TX@endtabularx\Hy@gtemp
7703 }{ }%
```

Support for footnotes in `p` columns of `longtable`. Here `\footnote` commands are splitted into `\footnotemark` and a call of `\footnotetext` with the optional argument, that is not supported by `hyperref`. The result is a link by `\footnotemark` without valid anchor

```

7704 \@ifpackageloaded{longtable}{%
7705   \CheckCommand*{\LT@p@ftntext}[1]{%
7706     \edef\@tempa{%
7707       \the\LT@p@ftn
7708       \noexpand\footnotetext[\the\c@footnote]%
7709     }%
7710     \global\LT@p@ftn\expandafter{\@tempa{#1}}%
7711   }%
7712   \long\def\LT@p@ftntext#1{%
7713     \edef\@tempa{%
7714       \the\LT@p@ftn
7715       \begingroup
7716       \noexpand\c@footnote=\the\c@footnote\relax
```



```

7717 \noexpand\protected@xdef\noexpand\@thefnmark{%
7718 \noexpand\thempfn
7719 }%
7720 \noexpand\Hy@LT@footnotetext{%
7721 \Hy@footnote@currentHref
7722 }%
7723 }%
7724 \global\LT@p@ftn\expandafter{%
7725 \@tempa{#1}%
7726 \endgroup
7727 }%
7728 }%
7729 \long\def\Hy@LT@footnotetext#1#2{%
7730 \H@@@footnotetext{%
7731 \ifHy@nesting
7732 \hyper@@anchor{#1}{#2}%
7733 \else
7734 \Hy@raisedlink{%
7735 \hyper@@anchor{#1}{\relax}%
7736 }%
7737 \def\@currentHref{#1}%
7738 \let\@currentlabelname\@empty
7739 #2%
7740 \fi
7741 }%
7742 }%
7743 }{}%

```

Footnotes for fancyvrb (Fix by Manuel Pégourié-Gonnard).

```

7744 \@ifpackageloaded{fancyvrb}{%
7745 \def\V@@@footnotetext{%
7746 \insert\footins\bgroup
7747 \csname reset@font\endcsname
7748 \footnotesize
7749 \interlinepenalty\interfootnotelinepenalty
7750 \splittopskip\footnotesep
7751 \splitmaxdepth\dp\strutbox
7752 \floatingpenalty \@MM
7753 \hsize\columnwidth
7754 \@parboxrestore
7755 \edef\@currentlabel{\csname p@footnote\endcsname\@thefnmark}%
7756 \@makefnmark{}%
7757 \rule{\z@}{\footnotesep}%
7758 \bgroup
7759 \aftergroup\V@@@footnotetext
7760 \Hy@raisedlink{%
7761 \expandafter\hyper@@anchor\expandafter{%
7762 \Hy@footnote@currentHref
7763 }{\relax}%
7764 }%
7765 \let\@currentHref\Hy@footnote@currentHref
7766 \let\@currentlabelname\@empty
7767 \ignorespaces
7768 }%
7769 }{}%

```

KOMA-Script defines `\footref` that uses both `\ref` and `\@footnotemark` resulting in two links, one of them wrong.

```

7770 \def\Hy@temp#1{%
7771   \begingroup
7772   \unrestored@protected@xdef\@thefnmark{\ref{#1}}}%
7773   \endgroup
7774   \@footnotemark
7775 }%
7776 \ifx\Hy@temp\footref
7777   \def\footref#1{%
7778     \begingroup
7779     \unrestored@protected@xdef\@thefnmark{\ref{#1}}}%
7780     \endgroup
7781     \H@@@footnotemark
7782   }%
7783 \fi

```

But the special footnotes in `\maketitle` are much too hard to deal with properly. Let them revert to plain behaviour. The koma classes add an optional argument.

```

7784 \let\HyOrg@maketitle\maketitle
7785 \def\maketitle{%
7786   \let\Hy@saved@footnotemark\@footnotemark
7787   \let\Hy@saved@footnotetext\@footnotetext
7788   \let\@footnotemark\H@@@footnotemark
7789   \let\@footnotetext\H@@@footnotetext
7790   \@ifnextchar[\Hy@maketitle@optarg{% ]
7791     \HyOrg@maketitle
7792     \Hy@maketitle@end
7793   }%
7794 }%
7795 \def\Hy@maketitle@optarg[#1]{%
7796   \HyOrg@maketitle[{#1}]%
7797   \Hy@maketitle@end
7798 }%
7799 \def\Hy@maketitle@end{%
7800   \ifx\@footnotemark\H@@@footnotemark
7801     \let\@footnotemark\Hy@saved@footnotemark
7802   \fi
7803   \ifx\@footnotetext\H@@@footnotetext
7804     \let\@footnotetext\Hy@saved@footnotetext
7805   \fi
7806 }%

```

`\realfootnote` Does anyone remember the function and purpose of `\realfootnote`?

```

7807 \def\realfootnote{%
7808   \@ifnextchar[\@xfootnote{%
7809     \stepcounter{\@mpfn}%
7810     \protected@xdef\@thefnmark{\thempfn}%
7811     \H@@@footnotemark\H@@@footnotetext
7812   }%
7813 }%
7814 \fi
7815 \Hy@DisableOption{hyperfootnotes}
7816 \</package>
7817 \< *check>
7818 \checklatex
7819 \checkcommand\def\@xfootnotenext[#1]{%

```

```

7820 \begingroup
7821 \csname c@\@mpfn\endcsname #1\relax
7822 \unrestored@protected@xdef\@thefnmark{\thempfn}%
7823 \endgroup
7824 \@footnotetext
7825 }
7826 \checkcommand\def\@xfootnotemark[#1]{%
7827 \begingroup
7828 \c@footnote #1\relax
7829 \unrestored@protected@xdef\@thefnmark{\thefootnote}%
7830 \endgroup
7831 \@footnotemark
7832 }
7833 \checkcommand\def\@footnotemark{%
7834 \leavevmode
7835 \ifhmode\edef\@x@sf{\the\spacefactor}\nobreak\fi
7836 \@makefnmark
7837 \ifhmode\spacefactor\@x@sf\fi
7838 \relax
7839 }
7840 </check>
7841 <*package>

```

37 Float captions

Make the float caption the hypertext anchor; curiously enough, we can't just copy the definition of `\@caption`. Its all to do with expansion. It screws up. Sigh.

```

7842 \def\caption{%
7843 \ifx\@captive\@undefined
7844 \latex@error{\noexpand\caption outside float}\@ehd
7845 \expandafter\@gobble
7846 \else
7847 \H@refstepcounter\@captive
7848 \let\Hy@tempa\@caption
7849 \@ifundefined{float@caption}{%
7850 }{%
7851 \expandafter\ifx\csname @float@c@\@captive\endcsname
7852 \float@caption
7853 \let\Hy@tempa\Hy@float@caption
7854 \fi
7855 }%
7856 \expandafter\@firstofone
7857 \fi
7858 {\@dblarg{\Hy@tempa\@captive}}%
7859 }
7860 \long\def\@caption#1[#2]#3{%
7861 \expandafter\ifx\csname if@capstart\expandafter\endcsname
7862 \csname iftrue\endcsname
7863 \global\let\@currentHref\hc@currentHref
7864 \else
7865 \hyper@makecurrent{\@captive}%
7866 \fi
7867 \@ifundefined{NR@getttitle}{%
7868 \def\@currentlabelname{#2}%
7869 }{%
7870 \NR@getttitle{#2}%

```

```

7871 }%
7872 \par\addcontentsline{\csname ext@#1\endcsname}{#1}{%
7873 \protect\numberline{\csname the#1\endcsname}{\ignorespaces #2}%
7874 }%
7875 \begingroup
7876 \@@parboxrestore
7877 \if@minipage
7878 \@@setminipage
7879 \fi
7880 \normalsize
7881 \expandafter\ifx\csname if@capstart\expandafter\endcsname
7882 \csname iftrue\endcsname
7883 \global\@capstartfalse
7884 \@@makecaption{\csname fnum@#1\endcsname}{\ignorespaces#3}%
7885 \else
7886 \@@makecaption{\csname fnum@#1\endcsname}{%
7887 \ignorespaces

```

If we cannot have nesting, the anchor is empty.

```

7888 \ifHy@nesting
7889 \expandafter\hyper@@anchor\expandafter{\@currentHref}{#3}%
7890 \else
7891 \Hy@raisedlink{%
7892 \expandafter\hyper@@anchor\expandafter{%
7893 \@currentHref
7894 }{\relax}%
7895 }%
7896 #3%
7897 \fi
7898 }%
7899 \fi
7900 \par
7901 \endgroup
7902 }

```

Compatibility with float.sty: anchor setting at the top of the float, if the float is controlled by float.sty. Several `\caption` commands inside one float are not supported.

`\HyNew@float@makebox` is introduced as feature request of Axel Sommerfeldt to make the life easier for his package ‘caption’.

```

7903 \let\Hy@float@caption\@caption
7904 \newcommand{\HyNew@float@makebox}[1]{%
7905 \HyOrg@float@makebox{%
7906 #1\relax
7907 \ifx\Hy@float@currentHref\@undefined
7908 \else
7909 \expandafter\hyper@@anchor\expandafter{%
7910 \Hy@float@currentHref
7911 }{\relax}%
7912 \global\let\Hy@float@currentHref\@undefined
7913 \fi
7914 }%
7915 }%
7916 \ifpackageloaded{float}{%
7917 \def\Hy@float@caption{%
7918 \ifx\Hy@float@currentHref\@undefined
7919 \hyper@makecurrent{\@cuptype}%
7920 \global\let\Hy@float@currentHref\@currentHref

```

```

7921 \else
7922 \let\@currentHref\Hy@float@currentHref
7923 \fi
7924 \float@caption
7925 }%
7926 \let\HyOrg@float@makebox\float@makebox
7927 \let\float@makebox\HyNew@float@makebox
7928 }{}

7929 \end{package}
7930 \check{
7931 \checklatex[1999/06/01 - 2000/06/01]
7932 \checkcommand\def\caption{%
7933 \ifx\@capttype\@undefined
7934 \@latex@error{\noexpand\caption outside float}\@ehd
7935 \expandafter\@gobble
7936 \else
7937 \refstepcounter\@capttype
7938 \expandafter\@firstofone
7939 \fi
7940 {\@dblarg{\@caption\@capttype}}}%
7941 }
7942 \checkcommand\long\def\@caption#1[#2]#3{%
7943 \par
7944 \addcontentsline{\csname ext@#1\endcsname}{#1}{%
7945 \protect\numberline{\csname the#1\endcsname}{\ignorespaces #2}%
7946 }%
7947 \begingroup
7948 \@parboxrestore
7949 \if@minipage
7950 \@setminipage
7951 \fi
7952 \normalsize
7953 \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par
7954 \endgroup
7955 }
7956 \end{check}
7957 \end{package}

```

38 Bibliographic references

This is not very robust, since many styles redefine these things. The package used to redefine `\@citex` and the like; then we tried adding the `hyperref` call explicitly into the `.aux` file. Now we redefine `\bibcite`; this still breaks some citation packages so we have to work around them. But this remains extremely dangerous. Any or all of *achemso* and *drftcite* may break.

However, lets make an attempt to get *natbib* right, because thats a powerful, important package. Patrick Daly (daly@linmpi.mpg.de) has provided hooks for us, so all we need to do is activate them.

```

7958 \def\hyper@natlinkstart#1{%
7959 \Hy@backout{#1}%
7960 \hyper@linkstart{cite}{cite.#1}%
7961 \def\hyper@nat@current{#1}%
7962 }
7963 \def\hyper@natlinkend{%
7964 \hyper@linkend

```

```

7965 }
7966 \def\hyper@natlinkbreak#1#2{%
7967   \hyper@linkend#1\hyper@linkstart{cite}{cite.#2}%
7968 }
7969 \def\hyper@natanchorstart#1{%
7970   \Hy@raisedlink{\hyper@anchorstart{cite.#1}}%
7971 }
7972 \def\hyper@natanchorend{\hyper@anchorend}

```

Do not play games if we have natbib support. Macro extra@binfo added for chapterbib support. Chapterbib also wants \@extra@binfo in the hyper-link, but since the link tag is not expanded immediately, we use \@extra@b@citeb, so cites in a chapter will link to the bibliography in that chapter.

```

7973 \ltx@ifundefined{NAT@parse}{%
7974   \providecommand*\@extra@binfo{}%
7975   \providecommand*\@extra@b@citeb{}%
7976   \def\bibcite#1#2{%
7977     \@newl@bel{b}{#1\@extra@binfo}{%
7978       \hyper@link{cite}{cite.#1\@extra@b@citeb}{#2}%
7979     }%
7980   }%
7981   \gdef\@extra@binfo{}%

```

Package babel redefines \bibcite with macro \bbl@cite@choice. It needs to be overwritten to avoid the warning “Label(s) may have changed.”.

```

7982 \let\Hy@bibcite\bibcite
7983 \begingroup
7984   \@ifundefined{bbl@cite@choice}{}{%
7985     \g@addto@macro\bbl@cite@choice{%
7986       \let\bibcite\Hy@bibcite
7987     }%
7988   }%
7989 \endgroup

```

\@BIBLABEL is working around a ‘feature’ of RevTeX.

```

7990 \providecommand*\@BIBLABEL{\@biblabel}%
7991 \def\@bibitem[#1]#2{%
7992   \@skiphyperreftrue
7993   \H@item[%
7994     \ifx\Hy@raisedlink\@empty
7995       \hyper@anchorstart{cite.#2\@extra@b@citeb}%
7996       \@BIBLABEL{#1}%
7997       \hyper@anchorend
7998     \else
7999       \Hy@raisedlink{%
8000         \hyper@anchorstart{cite.#2\@extra@b@citeb}\hyper@anchorend
8001       }%
8002       \@BIBLABEL{#1}%
8003     \fi
8004     \hfill
8005   ]%
8006   \@skiphyperreffalse
8007   \if@filesw
8008     \begingroup
8009       \let\protect\noexpand
8010       \immediate\write\@auxout{%
8011         \string\bibcite{#2}{#1}%
8012       }%

```

```

8013 \endgroup
8014 \fi
8015 \ignorespaces
8016 }%

```

Since `\bibitem` is doing its own labelling, call the raw version of `\item`, to avoid extra spurious labels

```

8017 \def\@bibitem#1{%
8018 \@skiphyperreftrue\H@item\@skiphyperreffalse
8019 \Hy@raisedlink{%
8020 \hyper@anchorstart{cite.#1\@extra@b@citeb}\relax\hyper@anchorend
8021 }%
8022 \if@filesw
8023 \begingroup
8024 \let\protect\noexpand
8025 \immediate\write\@auxout{%
8026 \string\bibcite{#1}{\the\value{\@listctr}}}%
8027 }%
8028 \endgroup
8029 \fi
8030 \ignorespaces
8031 }%
8032 }{}

8033 \</package>
8034 \< *check>
8035 \checklatex
8036 \checkcommand\def\@lbibitem[#1]#2{%
8037 \item[\@biblabel{#1}\hfill]%
8038 \if@filesw
8039 {%
8040 \let\protect\noexpand
8041 \immediate\write\@auxout{%
8042 \string\bibcite{#2}{#1}%
8043 }%
8044 }%
8045 \fi
8046 \ignorespaces
8047 }
8048 \checkcommand\def\@bibitem#1{%
8049 \item
8050 \if@filesw
8051 \immediate\write\@auxout{%
8052 \string\bibcite{#1}{\the\value{\@listctr}}}%
8053 }%
8054 \fi
8055 \ignorespaces
8056 }
8057 \</check>
8058 \< *package>

```

RevTeX (bless its little heart) takes over `\bibcite` and looks at the result to measure something. Make this a hypertext link and it goes ape. Therefore, make an anodyne result first, call its business, then go back to the real thing.

```

8059 \ifclassloaded{revtex}{%
8060 \Hy@Info{*** compatibility with revtex **** }%
8061 \def\revtex@checking#1#2{%
8062 \expandafter\let\expandafter\T@temp\csname b@#1\endcsname

```

```

8063 \expandafter\def\csname b@#1\endcsname{#2}%
8064 \SetMaxRnhefLabel{#1}%
8065 \expandafter\let\csname b@#1\endcsname\T@temp
8066 }%

```

Tanmoy provided this replacement for CITEX. Lord knows what it does. For chapterbib added: extra@b@citeb

```

8067 \ifundefined{@CITE}{\def\CITE{\@cite}}}%
8068 \providecommand*{\@extra@b@citeb}{}%
8069 \def\CITEX[#1]#2{%
8070 \let\@citea\@empty
8071 \leavevmode
8072 \unskip
8073 $~{%
8074 \scriptstyle
8075 \@CITE{%
8076 \@for\@citeb:=#2\do{%
8077 \@citea
8078 \def\@citea{,\penalty\@m\ }%
8079 \edef\@citeb{\expandafter\@firstofone\@citeb}%
8080 \if@filesw
8081 \immediate\write\@auxout{\string\citation{\@citeb}}%
8082 \fi
8083 \ifundefined{b@\@citeb\extra@b@citeb}{%
8084 \mbox{\reset@font\bfseries ?}%
8085 \G@refundefinedtrue
8086 \@latex@warning{%
8087 Citation ‘\@citeb’ on page \thepage \space undefined%
8088 }%
8089 }{%
8090 {\csname b@\@citeb\@extra@b@citeb\endcsname}%
8091 }%
8092 }%
8093 }{#1}%
8094 }$%
8095 }%

```

No, life is too short. I am not going to understand the Revtex `\@collapse` macro, I shall just restore the original behaviour of `\@citex`; sigh. This is SO vile.

```

8096 \def\@citex[#1]#2{%
8097 \let\@citea\@empty
8098 \@cite{%
8099 \@for\@citeb:=#2\do{%
8100 \@citea
8101 \def\@citea{,\penalty\@m\ }%
8102 \edef\@citeb{\expandafter\@firstofone\@citeb}%
8103 \if@filesw
8104 \immediate\write\@auxout{\string\citation{\@citeb}}%
8105 \fi
8106 \ifundefined{b@\@citeb\@extra@b@citeb}{%
8107 \mbox{\reset@font\bfseries ?}%
8108 \G@refundefinedtrue
8109 \@latex@warning{%
8110 Citation ‘\@citeb’ on page \thepage \space undefined%
8111 }%
8112 }{%
8113 \hbox{\csname b@\@citeb\@extra@b@citeb\endcsname}%
8114 }%

```



```

8115 }%
8116 }{#1}%
8117 }%
8118 }{}

```

38.1 Package harvard

Override Peter Williams' Harvard package; we have to a) make each of the citation types into a link; b) make each citation write a backref entry, and c) kick off a backreference section for each bibliography entry.

The redefinitions have to be deferred to `\begin{document}`, because if `harvard.sty` is loaded and `html.sty` is present and detects pdfTeX, then `hyperref` is already loaded at the begin of `harvard.sty`, and the `\newcommand` macros causes error messages.

```

8119 \@ifpackageloaded{harvard}{%
8120   \Hy@AtBeginDocument{%
8121     \Hy@Info{*** compatibility with harvard **** }%
8122     \Hy@raiselinksfalse
8123     \def\harvardcite#1#2#3#4{%
8124       \global\@namedef{HAR@fn@#1}{\hyper@link[cite]{#1}{#2}}%
8125       \global\@namedef{HAR@an@#1}{\hyper@link[cite]{#1}{#3}}%
8126       \global\@namedef{HAR@yr@#1}{\hyper@link[cite]{#1}{#4}}%
8127       \global\@namedef{HAR@df@#1}{\csname HAR@fn@#1\endcsname}%
8128     }%
8129     \def\HAR@citetoaux#1{%
8130       \if@filesw\immediate\write\@auxout{\string\citation{#1}}\fi%
8131       \ifHy@backref
8132         \ifx\@empty\@currentlabel
8133         \else
8134           \@bsphack
8135           \if@filesw
8136             \protected@write\@auxout{}{%
8137               \string\@writefile{brf}{%
8138                 \string\backcite{#1}{%
8139                   {thepage}{\@currentlabel}{\@currentHref}%
8140                 }%
8141               }%
8142             }%
8143           \fi
8144           \@esphack
8145         \fi
8146       \fi
8147     }%
8148     \def\harvarditem{%
8149       \@ifnextchar[{\@harvarditem}{\@harvarditem[\null]}%
8150     }%
8151     \def\@harvarditem[#1]#2#3#4#5\par{%
8152       \item[]%
8153       \hyper@anchorstart{cite.#4}\relax\hyper@anchorend
8154       \if@filesw
8155         \begingroup
8156         \def\protect##1{\string ##1\space}%
8157         \ifthenelse{\equal{#1}{\null}}{%
8158           {\def\next{{#4}{#2}{#3}}}%
8159           {\def\next{{#4}{#2}{#1}{#3}}}%
8160         \immediate\write\@auxout{\string\harvardcite\codeof\next}%

```

```

8161 \endgroup
8162 \fi
8163 \protect\hspace*{-\labelwidth}%
8164 \protect\hspace*{-\labelsep}%
8165 \ignorespaces
8166 #5%
8167 \ifHy@backref
8168 \newblock
8169 \backref{\csname br@#4\endcsname}%
8170 \fi
8171 \par
8172 }%

```

\HAR@checkcitations Package hyperref has added \hyper@@link, so the original test \HAR@checkcitations will fail every time and always will appear the “Changed labels” warning. So we have to redefine \Har@checkcitations:

```

8173 \long\def\HAR@checkcitations#1#2#3#4{%
8174 \def\HAR@tempa{\hyper@@link[cite]{\cite.#1}{#2}}%
8175 \expandafter\ifx\csname HAR@fn@#1\endcsname\HAR@tempa
8176 \def\HAR@tempa{\hyper@@link[cite]{\cite.#1}{#3}}%
8177 \expandafter\ifx\csname HAR@an@#1\endcsname\HAR@tempa
8178 \def\HAR@tempa{\hyper@@link[cite]{\cite.#1}{#4}}%
8179 \expandafter\ifx\csname HAR@yr@#1\endcsname\HAR@tempa
8180 \else
8181 \@tempswatrue
8182 \fi
8183 \else
8184 \@tempswatrue
8185 \fi
8186 \else
8187 \@tempswatrue
8188 \fi
8189 }%
8190 }%
8191 {}

```

38.2 Package chicago

The links by \citeN and \shortciteN should include the closing parentheses.

```

8192 \@ifpackageloaded{chicago}{%

```

\citeN

```

8193 \def\citeN{%
8194 \def\@citeseppen{-1000}%
8195 \def\@cite##1##2{##1}%
8196 \def\citeauthoryear##1##2##3{##1 (##3\@cite@opt)}%
8197 \@citedata@opt
8198 }%

```

\shortciteN

```

8199 \def\shortciteN{%
8200 \def\@citeseppen{-1000}%
8201 \def\@cite##1##2{##1}%
8202 \def\citeauthoryear##1##2##3{##2 (##3\@cite@opt)}%
8203 \@citedata@opt
8204 }%

```

\@citedata@opt

```
8205 \def\@citedata@opt{%
8206   \let\@cite@opt\@empty
8207   \@ifnextchar [{%
8208     \@tempswatrue
8209     \@citedatax@opt
8210   }{%
8211     \@tempswafalse
8212     \@citedatax[]%
8213   }%
8214 }%
```

\@citedatax@opt

```
8215 \def\@citedatax@opt[#1]{%
8216   \def\@cite@opt{, #1}%
8217   \@citedatax[{#1}]%
8218 }%

8219 }
```

39 Page numbers

The last page should not contain a /Dur key, because there is no page after the last page. Therefore at the last page there should be a command `\hypersetup{pdfpageduration={}}`. This can be set with `\AtEndDocument`, but it can be too late, if the last page is already finished, or too early, if lots of float pages will follow. Therefore currently nothing is done by hyperref.

This where we supply a destination for each page.

```
8220 \ltx@ifclassloaded{slides}{%
8221   \def\Hy@SlidesFormatOptionalPage#1{(#1)}%
8222   \def\Hy@PageAnchorSlidesPlain{%
8223     \advance\c@page\ltx@one
8224     \edef\Hy@TempPageAnchor{%
8225       \noexpand\hyper@@anchor{%
8226         page.\the\c@slide.\the\c@overlay.\the\c@note%
8227         \ifnum\c@page=\ltx@one
8228           \else
8229             .\the\c@page
8230         \fi
8231       }%
8232     }%
8233     \advance\c@page-\ltx@one
8234   }%
8235   \def\Hy@PageAnchorSlide{%
8236     \advance\c@page\ltx@one
8237     \ifnum\c@page>\ltx@one
8238       \ltx@ifundefined{theHpage}{%
8239         \protected@edef\Hy@TheSlideOptionalPage{%
8240           \Hy@SlidesFormatOptionalPage{theHpage}%
8241         }%
8242       }{%
8243         \protected@edef\Hy@TheSlideOptionalPage{%
8244           \Hy@SlidesFormatOptionalPage{theHpage}%
8245         }%
8246       }%
8247     \else
```

```

8248 \def\Hy@TheSlideOptionalPage{}%
8249 \fi
8250 \advance\c@page-\ltx@one
8251 \pdfstringdef\@the@H@page{%
8252 \csname
8253 the%
8254 \ltx@ifundefined{theH\Hy@SlidesPage}{H}%
8255 \Hy@SlidesPage
8256 \endcsname
8257 \Hy@TheSlideOptionalPage
8258 }%
8259 \ltx@gobblethree
8260 }%
8261 \def\Hy@SlidesPage{slide}%
8262 \g@addto@macro\slide{%
8263 \def\Hy@SlidesPage{slide}%
8264 }%
8265 \g@addto@macro\overlay{%
8266 \def\Hy@SlidesPage{overlay}%
8267 }%
8268 \g@addto@macro\note{%
8269 \def\Hy@SlidesPage{note}%
8270 }%
8271 }{%
8272 \def\Hy@PageAnchorSlidesPlain{}%
8273 \def\Hy@PageAnchorSlide{}%
8274 }
8275 \def\Hy@EveryPageAnchor{%
8276 \Hy@DistillerDestFix
8277 \ifHy@pageanchor
8278 \ifHy@hypertexnames
8279 \ifHy@plainpages
8280 \def\Hy@TempPageAnchor{\hyper@@anchor{page.\the\c@page}}%
8281 \Hy@PageAnchorSlidesPlain
8282 \else
8283 \begingroup
8284 \let\@number\@firstofone
8285 \Hy@unicodefalse
8286 \Hy@PageAnchorSlide
8287 \pdfstringdef\@the@H@page{\thepage}%
8288 \endgroup
8289 \EdefUnescapeString\@the@H@page{\@the@H@page}%
8290 \def\Hy@TempPageAnchor{\hyper@@anchor{page.\@the@H@page}}%
8291 \fi
8292 \else
8293 \Hy@GlobalStepCount\Hy@pagecounter
8294 \def\Hy@TempPageAnchor{%
8295 \hyper@@anchor{page.\the\Hy@pagecounter}%
8296 }%
8297 \fi
8298 \vbox to 0pt{%
8299 \kern\voffset
8300 \kern\topmargin
8301 \kern-1bp\relax
8302 \hbox to 0pt{%
8303 \kern\hoffset
8304 \kern@ifodd\value{page}%

```

```

8305         \oddsidemargin
8306         \else
8307         \evensidemargin
8308         \fi
8309         \kern-1bp\relax
8310         \Hy@TempPageAnchor\relax
8311         \hss
8312     }%
8313     \vss
8314 }%
8315 \fi
8316 }
8317 \g@addto@macro\Hy@EveryPageBoxHook{%
8318 \Hy@EveryPageAnchor
8319 }

```

40 Table of contents

TV Raman noticed that people who add arbitrary material into the TOC generate a bad or null link. We avoid that by checking if the current destination is empty. But if ‘the most recent destination’ is not what you expect, you will be in trouble.

```

8320 \def\addcontentsline#1#2#3{% toc extension, type, tag
8321 \begingroup
8322 \let\label\@gobble
8323 \ifx\@currentHref\@empty
8324 \Hy@Warning{%
8325 No destination for bookmark of \string\addcontentsline,%
8326 \MessageBreak destination is added%
8327 }%
8328 \phantomsection
8329 \fi
8330 \expandafter\ifx\csname toplevel@#2\endcsname\relax
8331 \begingroup
8332 \def\Hy@tempa{#1}%
8333 \ifx\Hy@tempa\Hy@bookmarkstype
8334 \Hy@WarningNoLine{%
8335 bookmark level for unknown #2 defaults to 0%
8336 }%
8337 \else
8338 \Hy@Info{bookmark level for unknown #2 defaults to 0}%
8339 \fi
8340 \endgroup
8341 \expandafter\gdef\csname toplevel@#2\endcsname{0}%
8342 \fi
8343 \edef\Hy@toplevel{\csname toplevel@#2\endcsname}%
8344 \Hy@writebookmark{\csname the#2\endcsname}%
8345 {#3}%
8346 {\@currentHref}%
8347 {\Hy@toplevel}%
8348 {#1}%
8349 \ifHy@verbose
8350 \begingroup
8351 \def\Hy@tempa{#3}%
8352 \@onelevel@sanitize\Hy@tempa
8353 \let\temp@online\on@line
8354 \let\on@line\@empty

```

```

8355 \Hy@Info{%
8356 bookmark\temp@online:\MessageBreak
8357 thecounter {\csname the#2\endcsname}\MessageBreak
8358 text {\Hy@tempa}\MessageBreak
8359 reference {\@currentHref}\MessageBreak
8360 toplevel {\Hy@toclevel}\MessageBreak
8361 type {#1}%
8362 }%
8363 \endgroup
8364 \fi
8365 \addtocontents{#1}{%
8366 \protect\contentsline{#2}{#3}{\thepage}{\@currentHref}%
8367 }%
8368 \endgroup
8369 }

```

`\contentsline` The page number might be empty. In this case the link for the page number is suppressed to avoid little link boxes.

```

8370 \def\contentsline#1#2#3#4{%
8371 \begingroup
8372 \Hy@safe@activetrue
8373 \edef\x{\endgroup
8374 \def\noexpand\Hy@tocdestname{#4}%
8375 }\x
8376 \ifx\Hy@tocdestname\ltx@empty
8377 \csname l@#1\endcsname{#2}{#3}%
8378 \else
8379 \ifcase\Hy@linktoc % none
8380 \csname l@#1\endcsname{#2}{#3}%
8381 \or % section
8382 \csname l@#1\endcsname{%
8383 \hyper@linkstart{link}{\Hy@tocdestname}{#2}\hyper@linkend
8384 }{#3}%
8385 \or % page
8386 \def\Hy@temp{#3}%
8387 \ifx\Hy@temp\ltx@empty
8388 \csname l@#1\endcsname{#2}{#3}%
8389 \else
8390 \csname l@#1\endcsname{#2}{#3}%
8391 \hyper@linkstart{link}{\Hy@tocdestname}{#3}\hyper@linkend
8392 }%
8393 \fi
8394 \else % all
8395 \def\Hy@temp{#3}%
8396 \ifx\Hy@temp\ltx@empty
8397 \csname l@#1\endcsname{%
8398 \hyper@linkstart{link}{\Hy@tocdestname}{#2}\hyper@linkend
8399 }{}%
8400 \else
8401 \csname l@#1\endcsname{%
8402 \hyper@linkstart{link}{\Hy@tocdestname}{#2}\hyper@linkend
8403 }{%
8404 \hyper@linkstart{link}{\Hy@tocdestname}{#3}\hyper@linkend
8405 }%
8406 \fi
8407 \fi
8408 \fi

```

```

8409 }

8410 </package>
8411 <*check>
8412 \checklatex
8413 \checkcommand\def\addcontentsline#1#2#3{%
8414   \addtocontents{#1}{\protect\contentsline{#2}{#3}{\thepage}}}%
8415 }
8416 \checkcommand\def\contentsline#1{\csname l@#1\endcsname}
8417 </check>
8418 <*package>

```

41 New counters

The whole theorem business makes up new counters on the fly; we are going to intercept this. Sigh. Do it at the level where new counters are defined.

```

8419 \let\H@definecounter\@definecounter
8420 \def\@definecounter#1{%
8421   \H@definecounter{#1}%
8422   \expandafter\gdef\csname theH#1\endcsname{\arabic{#1}}%
8423 }

```

But what if they have used the optional argument to e.g. `\newtheorem` to determine when the numbering is reset? OK, we'll trap that too.

```

8424 \let\H@newctr\@newctr
8425 \def\@newctr#1[#2]{%
8426   \H@newctr#1[#2]}%
8427 \expandafter\gdef\csname theH#1\endcsname{%
8428   \csname the\@ifundefined{theH#2}{-}{H}#2\endcsname.\arabic{#1}%
8429 }%
8430 }

```

42 AMS \LaTeX compatibility

Oh, no, they don't use anything as simple as `\refstepcounter` in the AMS! We need to intercept some low-level operations of theirs. Damned if we are going to try and work out what they get up to. Just stick a label of 'AMS' on the front, and use the label *they* worked out. If that produces something invalid, I give up. They'll change all the code again anyway, I expect (SR).

Version 6.77p uses a patch by Ross Moore.

```

8431 \ifpackageloaded{amsmath}{%
8432   \def\Hy@make@anchor{%
8433     \Hy@MakeCurrentHrefAuto{AMS}%
8434     \Hy@raisedlink{\hyper@anchorstart{\@currentHref}\hyper@anchorend}%
8435   }%
8436   \def\Hy@make@df@tag@@#1{%
8437     \gdef\df@tag{%
8438       \maketag@@@{\Hy@make@anchor#1}%
8439     \def\@currentlabel{#1}%
8440   }%
8441   }%
8442   \def\Hy@make@df@tag@@@#1{%
8443     \gdef\df@tag{%
8444       \tagform@{\Hy@make@anchor#1}%
8445       \toks@{\xp{p@equation{#1}}}%

```

```

8446 \edef\@currentlabel{\the\toks@}%
8447 }%
8448 }%
8449 \let\HyOrg@make@df@tag@@\make@df@tag@@
8450 \let\HyOrg@make@df@tag@@@\make@df@tag@@@
8451 \let\make@df@tag@@\Hy@make@df@tag@@
8452 \let\make@df@tag@@@\Hy@make@df@tag@@@
8453 }{}

```

Only play with `\seteqlebal` if we are using pdf_{tex}. Other drivers cause problems; requested by Michael Downes (AMS).

```

8454 \@ifpackagewith{hyperref}{pdftex}{%
8455 \let\H@seteqlabel\@seteqlabel
8456 \def\@seteqlabel#1{%
8457 \H@seteqlabel{#1}%
8458 \xdef\@currentHref{AMS.\the\Hy@linkcounter}%
8459 \Hy@raisedlink{%
8460 \hyper@anchorstart{\@currentHref}\hyper@anchorend
8461 }%
8462 }%
8463 }{}

```

This code I simply cannot remember what I was trying to achieve. The final result seems to do nothing anyway.

```

\let\H@tagform@\tagform@
\def\tagform@#1{%
\maketag@@@{\hyper@@anchor{\@currentHref}%
{(\ignorespaces#1\unskip)}}%
}
\def\eqref#1{\textup{\H@tagform@\ref{#1}}}

```

42.1 `\@addtoreset` and `\numberwithin` patches

`\@addtoreset` puts a counter to the reset list of another counter. After a reset the counter starts again with perhaps already used values. Therefore the `hyperref` version of the counter print command `\theHcounter` is redefined in order to add the parent counter.

```

8464 \let\HyOrg@addtoreset\@addtoreset
8465 \def\@addtoreset#1#2{%
8466 \HyOrg@addtoreset{#1}{#2}%
8467 \expandafter\xdef\csname theH#1\endcsname{%
8468 \expandafter\noexpand
8469 \csname the\@ifundefined{theH#2}{ }H#2\endcsname
8470 .\noexpand\the\noexpand\value{#1}%
8471 }%
8472 }

```

`\numberwithin` A appropriate definition of `hyperref`'s companion counter (`\theH...`) is added for correct link names.

```

8473 </package>
8474 < *check>
8475 \checkpackage{amsmath}[1999/12/14 - 2000/06/06]
8476 \checkcommand\newcommand{\numberwithin}[3][\arabic]{%
8477 \@ifundefined{c@#2}{\@nocounterr{#2}}{%
8478 \@ifundefined{c@#3}{\@nocnterr{#3}}{%
8479 \@addtoreset{#2}{#3}%
8480 \@xp\xdef\csname the#2\endcsname{%

```



```

8481 \exp\@nx\csname the#3\endcsname.\@nx#1{#2}%
8482 }%
8483 }%
8484 }%
8485 }%
8486 \check
8487 \*package
8488 \ifpackageloaded{amsmath}{%
8489 \ifpackagelater{amsmath}{1999/12/14}{%
8490 \renewcommand*{\numberwithin}{3}[\arabic]{%
8491 \ifundefined{c@#2}{\@nocounterr{#2}}{%
8492 \ifundefined{c@#3}{\@nocnterr{#3}}{%
8493 \HyOrg@addtoreset{#2}{#3}%
8494 \exp\xdef\csname the#2\endcsname{%
8495 \exp\@nx\csname the#3\endcsname.\@nx#1{#2}%
8496 }%
8497 \exp\xdef\csname theH#2\endcsname{%
8498 \exp\@nx
8499 \csname the\ifundefined{theH#3}{H#3\endcsname
8500 \@nx#1{#2}%
8501 }%
8502 }%
8503 }%
8504 }%
8505 }{%
8506 \Hy@WarningNoLine{%
8507 \string\numberwithin\space of package 'amsmath' %
8508 only fixed\MessageBreak
8509 for version 2000/06/06 v2.12 or newer%
8510 }%
8511 }%
8512 }{}

```

43 Included figures

Simply intercept the low level graphics package macro.

```

8513 \ifHy@hyperfigures
8514 \let\Hy@Gin@setfile\Gin@setfile
8515 \def\Gin@setfile#1#2#3{%
8516 \hyperimage{#3}{\Hy@Gin@setfile{#1}{#2}{#3}}%
8517 }%
8518 \fi
8519 \Hy@DisableOption{hyperfigures}

```

44 hyperindex entries

Internal command names are prefixed with \HyInd@.

Hyper-indexing works crudely, by forcing code onto the end of the index entry with the | feature; this puts a hyperlink around the printed page numbers. It will not proceed if the author has already used the | specifier for something like boldening entries. That would make Makeindex fail (cannot have two | specifiers). The solution is for the author to use generic coding, and put in the requisite \hyperpage in his/her own macros along with the boldness.

This section is poor stuff; it's open to all sorts of abuse. Sensible large projects will design their own indexing macros any bypass this.

```

8520 \ifHy@hyperindex
8521   \def\HyInd@ParenLeft{()%
8522   \def\HyInd@ParenRight{)%}
8523   \def\hyperindexformat#1#2{%
8524     \let\HyOrg@hyperpage\hyperpage
8525     \let\hyperpage\@firstofone
8526     #1{\HyOrg@hyperpage{#2}}%
8527     \let\hyperpage\HyOrg@hyperpage
8528   }%
8529   \Hy@nextfalse
8530   \@ifpackageloaded{multind}{\Hy@nexttrue}{}%
8531   \@ifpackageloaded{index}{\Hy@nexttrue}{}%
8532   \@ifpackageloaded{amsmidx}{\Hy@nexttrue}{}%
8533   \begingroup
8534     \lccode'\|=\expandafter'\HyInd@EncapChar\relax
8535     \lccode'\|/'=\|\\relax
8536   \lowercase{\endgroup
8537   \ifHy@next
8538     \let\HyInd@org@wrindex\@wrindex
8539     \def\@wrindex#1#2{\HyInd@@wrindex{#1}#2||\}%
8540     \def\HyInd@@wrindex#1#2|#3|#4\{\%
8541       \ifx\|#3\%
8542         \HyInd@org@wrindex{#1}{#2|hyperpage}%
8543       \else
8544         \HyInd@@@wrindex{#1}{#2}#3\%
8545       \fi
8546     }%
8547     \def\HyInd@@@wrindex#1#2#3#4\{\%
8548     \def\Hy@temp@A{#3}%
8549     \ifcase0\ifx\Hy@temp@A\HyInd@ParenLeft 1\fi
8550       \ifx\Hy@temp@A\HyInd@ParenRight 1\fi
8551       \relax
8552       \HyInd@org@wrindex{#1}{%
8553         #2|hyperindexformat{/#3#4}%
8554       }%
8555     \else
8556       \ifx\|#4\%
8557         \ifx\Hy@temp@A\HyInd@ParenRight
8558           \HyInd@org@wrindex{#1}{#2|#3}%
8559         \else
8560           \HyInd@org@wrindex{#1}{#2|#3hyperpage}%
8561         \fi
8562       \else
8563         \HyInd@org@wrindex{#1}{%
8564           #2|#3hyperindexformat{/#4}%
8565         }%
8566       \fi
8567     \fi
8568   }%
8569   \else
8570     \def\@wrindex#1{\@@wrindex#1||\}%
8571     \def\@@wrindex#1|#2|#3\{\%
8572     \if@filesw
8573       \ifx\|#2\%
8574         \protected@write\@indexfile{}{%

```

```

8575         \string\indexentry{#1|hyperpage}{\thepage}%
8576     }%
8577     \else
8578         \HyInd@@@wrindex{#1}#2\\%
8579     \fi
8580 \fi
8581 \endgroup
8582 \@esphack
8583 }%
8584 \def\HyInd@@@wrindex#1#2#3\\{%
8585     \def\Hy@temp@A{#2}%
8586     \ifcase0\ifx\Hy@temp@A\HyInd@ParenLeft 1\fi
8587         \ifx\Hy@temp@A\HyInd@ParenRight 1\fi
8588         \relax
8589     \protected@write\@indexfile{}{%
8590         \string\indexentry{%
8591             #1|hyperindexformat{/#2#3}%
8592         }\thepage}%
8593     }%
8594     \else
8595         \ifx\\#3\\%
8596             \ifx\Hy@temp@A\HyInd@ParenRight
8597                 \protected@write\@indexfile{}{%
8598                     \string\indexentry{#1|#2}{\thepage}%
8599                 }%
8600             \else
8601                 \protected@write\@indexfile{}{%
8602                     \string\indexentry{#1|#2hyperpage}{\thepage}%
8603                 }%
8604             \fi
8605         \else
8606             \protected@write\@indexfile{}{%
8607                 \string\indexentry{%
8608                     #1|#2hyperindexformat{/#3}%
8609                 }\thepage}%
8610             }%
8611         \fi
8612     \fi
8613 }%
8614 \fi
8615 }%
8616 \fi
8617 \Hy@DisableOption{hyperindex}
8618 \Hy@DisableOption{encap}

```

`\nohyperpage` The definition of `\nohyperpage` is just a precaution. It is used to mark code that does not belong to a page number, but `\nohyperpage` is never executed.

```
8619 \def\nohyperpage#1{#1}
```

This again is quite flaky, but allow for the common situation of a page range separated by en-rule. We split this into two different hyperlinked pages.

```

8620 \def\hyperpage#1{%
8621     \HyInd@hyperpage#1\nohyperpage{}\@nil
8622 }
8623 \def\HyInd@hyperpage#1\nohyperpage#2#3\@nil{%
8624     \HyInd@@@hyperpage{#1}%
8625     #2%

```

```

8626 \def\Hy@temp{#3}%
8627 \ifx\Hy@temp\@empty
8628 \else
8629 \ltx@ReturnAfterFi{%
8630 \HyInd@hyperpage#3\@nil
8631 }%
8632 \fi
8633 }
8634 \def\HyInd@@hyperpage#1{\@hyperpage#1----\}
8635 \def\@hyperpage#1--#2--#3\{\{%
8636 \ifx\#2\%
8637 \@commahyperpage{#1}%
8638 \else
8639 \HyInd@pagelink{#1}--\HyInd@pagelink{#2}%
8640 \fi
8641 }
8642 \def\@commahyperpage#1{\@@commahyperpage#1, \}
8643 \def\@@commahyperpage#1, #2, #3\{\{%
8644 \ifx\#2\%
8645 \HyInd@pagelink{#1}%
8646 \else
8647 \HyInd@pagelink{#1}, \HyInd@pagelink{#2}%
8648 \fi
8649 }

```

The argument of `\hyperpage` can be empty. And the line breaking algorithm of `Makeindex` can introduce spaces. So we have to remove them.

```

8650 \def\HyInd@pagelink#1{%
8651 \begingroup
8652 \toks@={}%
8653 \HyInd@removespaces#1 \@nil
8654 \endgroup
8655 }
8656 \def\HyInd@removespaces#1 #2\@nil{%
8657 \toks@=\expandafter{\the\toks@#1}%
8658 \ifx\#2\%
8659 \edef\x{\the\toks@}%
8660 \ifx\x\@empty
8661 \else
8662 \hyperlink{page.\the\toks@}{\the\toks@}%
8663 \fi
8664 \else
8665 \ltx@ReturnAfterFi{%
8666 \HyInd@removespaces#2\@nil
8667 }%
8668 \fi
8669 }

```

45 Compatibility with foiltex

```

8670 \@ifclassloaded{foils}{%
8671 \providecommand*\ext@table{lot}%
8672 \providecommand*\ext@figure{lof}%
8673 }{}

```

46 Compatibility with seminar slide package

This requires `seminar.bg2`, version 1.6 or later. Contributions by Denis Girou (denis.girou@idris.fr).

```
8674 \@ifclassloaded{seminar}{%
8675   \Hy@seminarslidestrue
8676   \providecommand\theHslide{\arabic{slide}}%
8677 }{%
8678   \Hy@seminarslidesfalse
8679 }
8680 \@ifpackageloaded{slidesec}{%
8681   \providecommand\theHslidesection {\arabic{slidesection}}%
8682   \providecommand\theHslidesubsection{%
8683     \theHslidesection.\arabic{slidesubsection}}%
8684 }%
8685 \def\slide@heading[#1]#2{%
8686   \H@refstepcounter{slidesection}%
8687   \@addtoreset{slidesubsection}{slidesection}%
8688   \addtocontents{los}{%
8689     \protect\l@slide{\the\c@slidesection}{\ignorespaces#1}%
8690     {\@SCTR}{slideheading.\theslidesection}}%
8691   }%
8692   \def\Hy@tempa{#2}%
8693   \ifx\Hy@tempa\@empty
8694   \else
8695     {%
8696       \edef\@currentlabel{%
8697         \csname p@slidesection\endcsname\theslidesection
8698       }%
8699       \makeslideheading{#2}%
8700     }%
8701   \fi
8702   \gdef\theslideheading{#1}%
8703   \gdef\theslidesubheading{}%
8704   \ifHy@bookmarksnumbered
8705     \def\Hy@slidetitle{\theslidesection\space #1}%
8706   \else
8707     \def\Hy@slidetitle{#1}%
8708   \fi
8709   \ifHy@hypertextnames
8710     \ifHy@naturalnames
8711       \hyper@@anchor{slideheading.\theslidesection}{\relax}%
8712       \Hy@writebookmark
8713         {\theslidesection}%
8714         {\Hy@slidetitle}%
8715         {slideheading.\theslidesection}%
8716         {1}%
8717       {toc}%
8718     \else
8719       \hyper@@anchor{slideheading.\theHslidesection}{\relax}%
8720       \Hy@writebookmark
8721         {\theslidesection}%
8722         {\Hy@slidetitle}%
8723         {slideheading.\theHslidesection}%
8724         {1}%
8725       {toc}%
8726   \fi
```

```

8727 \else
8728 \Hy@GlobalStepCount\Hy@linkcounter
8729 \hyper@@anchor{slideheading.\the\Hy@linkcounter}{\relax}%
8730 \Hy@writebookmark
8731 {\theslidesubsection}%
8732 {\Hy@slidetitle}%
8733 {slideheading.\the\Hy@linkcounter}%
8734 {1}%
8735 {toc}%
8736 \fi
8737 }%
8738 \def\slide@subheading[#1]#2{%
8739 \H@refstepcounter{slidesubsection}%
8740 \addtocontents{los}{%
8741 \protect\l@subslide{\the\c@slidesubsection}{\ignorespaces#1}%
8742 {\@SCTR}{slideheading.\theslidesubsection}%
8743 }%
8744 \def\Hy@tempa{#2}%
8745 \ifx\Hy@tempa\@empty
8746 \else
8747 {%
8748 \edef\@currentlabel{%
8749 \csname p@slidesubsection\endcsname\theslidesubsection
8750 }%
8751 \makeslide@subheading{#2}%
8752 }%
8753 \fi
8754 \gdef\theslide@subheading{#1}%
8755 \ifHy@bookmarksnumbered
8756 \def\Hy@slidetitle{\theslidesubsection\space #1}%
8757 \else
8758 \def\Hy@slidetitle{#1}%
8759 \fi
8760 \ifHy@hypertextnames
8761 \ifHy@naturalnames
8762 \hyper@@anchor{slideheading.\theslidesubsection}{\relax}%
8763 \Hy@writebookmark
8764 {\theslidesubsection}%
8765 {\Hy@slidetitle}%
8766 {slideheading.\theslidesubsection}%
8767 {2}%
8768 {toc}%
8769 \else
8770 \hyper@@anchor{slideheading.\theHslidesubsection}{\relax}%
8771 \Hy@writebookmark
8772 {\theslidesubsection}%
8773 {\Hy@slidetitle}%
8774 {slideheading.\theHslidesubsection}%
8775 {2}%
8776 {toc}%
8777 \fi
8778 \else
8779 \Hy@GlobalStepCount\Hy@linkcounter
8780 \hyper@@anchor{slideheading.\the\Hy@linkcounter}{\relax}%
8781 \Hy@writebookmark
8782 {\theslidesubsection}%
8783 {\Hy@slidetitle}%

```

```

8784     {slideheading.\the\Hy@linkcounter}%
8785     {1}%
8786     {toc}%
8787   \fi
8788 }%
8789 \providecommand*\listslidenamename{List of Slides}%
8790 \def\listofslides{%
8791   \section*{%
8792     \listslidenamename
8793     \@mkboth{%
8794       \expandafter\MakeUppercase\listslidenamename
8795     }{%
8796       \expandafter\MakeUppercase\listslidenamename
8797     }%
8798   }%
8799   \def\l@slide###1##2###3###4{%
8800     \slide@undottedcline{%
8801       \slidenumberline{##3}{\hyperlink{##4}{##2}}%
8802     }{%
8803     }%
8804     \let\l@subslide\l@slide
8805     \@startlos
8806   }%
8807   \def\slide@contents{%
8808     \def\l@slide###1##2###3###4{%
8809       \slide@ccline{\slidenumberline{##3}{\hyperlink{##4}{##2}}}{##3}%
8810     }%
8811     \let\l@subslide\@gobblefour
8812     \@startlos
8813   }%
8814   \def\Slide@contents{%
8815     \def\l@slide###1##2###3###4{%
8816       \ifcase\lslide@flag
8817         \message{##1 ** \the\c@slidesection}%
8818         \ifnum##1>\c@slidesection
8819           \def\lslide@flag{1}%
8820           {%
8821             \large
8822             \slide@ccline{%
8823               \slidenumberline{$\Rightarrow\bullet$}%
8824               {\hyperlink{##4}{##2}}%
8825             }{##3}%
8826           }%
8827         \else
8828           {%
8829             \large
8830             \slide@ccline{%
8831               \slidenumberline{$\surd\;\bullet$}%
8832               {\hyperlink{##4}{##2}}%
8833             }{##3}%
8834           }%
8835         \fi
8836       \or
8837       \def\lslide@flag{2}%
8838       {%
8839         \large
8840         \slide@ccline{%

```

```

8841      \slidenumberline{$\bullet$}%
8842      {\hyperlink{##4}{##2}}}%
8843      }{##3}%
8844      }%
8845      \or
8846      {%
8847      \large
8848      \slide@cline{%
8849      \slidenumberline{$\bullet$}%
8850      {\hyperlink{##4}{##2}}}%
8851      }{##3}%
8852      }%
8853      \fi
8854      }%
8855      \def\l@subslide##1##2##3##4{%
8856      \ifnum\lslide@flag=1 %
8857      \@undottedtocline{2}{3.8em}{3.2em}{\hyperlink{##4}{##2}}{}}%
8858      \fi
8859      }%
8860      \def\lslide@flag{0}%
8861      \@startlos
8862      }%
8863      }{}

```

This breaks TeX4ht, so leave it to last. Emend `\@setref` to put out a hypertext link as well as its normal text (which is used as an anchor). (`\endinput` have to be on the same line like `\fi`, or you have to use `\expandafter` before.)

```

8864 \ifHy@texht
8865   \expandafter\endinput
8866 \fi
8867 \let\real@setref\@setref
8868 \def\@setref#1#2#3{% csname, extract group, refname
8869   \ifx#1\relax
8870     \protect\G@refundefinedtrue
8871     \nfss@text{\reset@font\bfseries ??}%
8872     \@latex@warning{%
8873       Reference ‘#3’ on page \thepage \space undefined%
8874     }%
8875   \else
8876     \expandafter\Hy@setref@link#1\@empty\@empty\@nil{#2}%
8877   \fi
8878 }

```

`\Hy@setref@link` extracts the reference information entries, because `\hyper@@link` does not expand arguments for the automatic link type detection.

```

8879 \def\Hy@setref@link#1#2#3#4#5#6\@nil#7{%
8880   \begingroup
8881     \toks0={\hyper@@link{#5}{#4}}%
8882     \toks1=\expandafter{#7{#1}{#2}{#3}{#4}{#5}}%
8883     \edef\x{\endgroup
8884       \the\toks0 {\the\toks1 }%
8885     }%
8886     \x
8887   }
8888 \def\@pagesetref#1#2#3{% csname, extract macro, ref
8889   \ifx#1\relax
8890     \protect\G@refundefinedtrue
8891     \nfss@text{\reset@font\bfseries ??}%

```



```

8892 \latex@warning{%
8893   Reference '#3' on page \thepage \space undefined%
8894 }%
8895 \else
8896 \protect\hyper@@link
8897 {\expandafter\@fifthoffive#1}%
8898 {page.\expandafter\@secondoffive#1}%
8899 {\expandafter\@secondoffive#1}%
8900 \fi
8901 }

8902 \end{package}
8903 \check
8904 \checklatex
8905 \checkcommand\def\@setref#1#2#3{%
8906 \ifx#1\relax
8907 \protect\G@refundefinedtrue
8908 \nfss@text{\reset@font\bfseries ??}%
8909 \latex@warning{%
8910   Reference '#3' on page \thepage\space undefined%
8911 }%
8912 \else
8913 \expandafter#2#1\relax
8914 \fi
8915 }
8916 \end{check}
8917 \end{package}

```

Now some extended referencing. `\ref*` and `\pageref*` are not linked, and `\autoref` prefixes with a tag based on the type.

```

8918 \def\HyRef@StarSetRef#1{%
8919 \begingroup
8920 \Hy@safe@activetrue
8921 \edef\x{#1}%
8922 \@onelevel@sanitize\x
8923 \edef\x{\endgroup
8924   \noexpand\HyRef@@StarSetRef
8925   \expandafter\noexpand\csname r@\x\endcsname{\x}%
8926 }%
8927 \x
8928 }
8929 \def\HyRef@@StarSetRef#1#2#3{%
8930 \ifx#1\@undefined
8931 \let#1\relax
8932 \fi
8933 \real@setref#1#3{#2}%
8934 }
8935 \def\@refstar#1{%
8936 \HyRef@StarSetRef{#1}\@firstoffive
8937 }
8938 \def\@pagerefstar#1{%
8939 \HyRef@StarSetRef{#1}\@secondoffive
8940 }
8941 \def\@namerefstar#1{%
8942 \HyRef@StarSetRef{#1}\@thirdoffive
8943 }
8944 \Hy@AtBeginDocument{%
8945 \ifpackageloaded{varioref}{%

```

```

8946 \def\@Refstar#1{%
8947   \HyRef@StarSetRef{#1}\HyRef@MakeUppercaseFirstOfFive
8948 }%
8949 \def\HyRef@MakeUppercaseFirstOfFive#1#2#3#4#5{%
8950   \MakeUppercase#1%
8951 }%
8952 \DeclareRobustCommand*{\Ref}{%
8953   \@ifstar\@Refstar\HyRef@Ref
8954 }%
8955 \def\HyRef@Ref#1{%
8956   \hyperref[{#1}]{\Ref*{#1}}%
8957 }%
8958 \def\Vr@f#1{%
8959   \leavevmode\unskip\vref@space
8960   \hyperref[{#1}]{%
8961     \Ref*{#1}%
8962     \let\vref@space\nobreakspace
8963     \@vpageref[\unskip]{#1}%
8964   }%
8965 }%
8966 \def\vr@f#1{%
8967   \leavevmode\unskip\vref@space
8968   \begingroup
8969   \let\T@pageref\@pagerefstar
8970   \hyperref[{#1}]{%
8971     \ref*{#1}%
8972     \vpageref[\unskip]{#1}%
8973   }%
8974   \endgroup
8975 }%
8976 }{%%
8977 }
8978 \DeclareRobustCommand*{\autopageref}{%
8979   \@ifstar{%
8980     \HyRef@autopagerefname\pageref*%
8981   }\HyRef@autopageref
8982 }
8983 \def\HyRef@autopageref#1{%
8984   \hyperref[{#1}]{\HyRef@autopagerefname\pageref*{#1}}%
8985 }
8986 \def\HyRef@autopagerefname{%
8987   \ltx@ifundefined{pageautorefname}{%
8988     \ltx@ifundefined{pagename}{%
8989       \Hy@Warning{No autoref name for 'page'}%
8990     }{%
8991       \pagename\nobreakspace
8992     }%
8993   }{%
8994     \pageautorefname\nobreakspace
8995   }%
8996 }

```

\leavevmode is added to make package wrapfigure happy, if \autoref starts a paragraph.

```

8997 \DeclareRobustCommand*{\autoref}{%
8998   \leavevmode
8999   \@ifstar{\HyRef@autoref\@gobbletwo}{\HyRef@autoref\hyper@@link}%
9000 }

```

```

9001 \def\HyRef@autoref#1#2{%
9002   \begingroup
9003   \Hy@safe@activestrue
9004   \expandafter\HyRef@autosetref\csname r@#2\endcsname{#2}{#1}%
9005   \endgroup
9006 }
9007 \def\HyRef@autosetref#1#2#3{% link command, csname, refname
9008   \HyRef@ShowKeysRef{#2}%
9009   \ifcase 0\ifx#1\relax 1\fi\ifx#1\Hy@varioref@undefined 1\fi\relax
9010   \edef\HyRef@thisref{%
9011     \expandafter\@fourthoffive#1\@empty\@empty\@empty
9012   }%
9013   \expandafter\HyRef@testreftype\HyRef@thisref.\.%
9014   \Hy@safe@activesfalse
9015   #3{%
9016     \expandafter\@fifthoffive#1\@empty\@empty\@empty
9017   }{%
9018     \expandafter\@fourthoffive#1\@empty\@empty\@empty
9019   }{%
9020     \HyRef@currentHtag
9021     \expandafter\@firstoffive#1\@empty\@empty\@empty
9022     \null
9023   }%
9024   \else
9025     \protect\G@refundefinedtrue
9026     \nfss@text{\reset@font\bfseries ??}%
9027     \@latex@warning{%
9028       Reference ‘#2’ on page \thepage\space undefined%
9029     }%
9030   \fi
9031 }
9032 \def\HyRef@testreftype#1.#2\{%
9033   \ltx@ifundefined{#1autorefname}{%
9034     \ltx@ifundefined{#1name}{%
9035       \HyRef@StripStar#1\*\@nil{#1}%
9036       \ltx@ifundefined{\HyRef@name autorefname}{%
9037         \ltx@ifundefined{\HyRef@name name}{%
9038           \def\HyRef@currentHtag{%
9039             \Hy@Warning{No autoref name for ‘#1’}%
9040           }{%
9041             \edef\HyRef@currentHtag{%
9042               \expandafter\noexpand\csname\HyRef@name name\endcsname
9043               \noexpand~%
9044             }%
9045           }%
9046         }{%
9047           \edef\HyRef@currentHtag{%
9048             \expandafter\noexpand
9049             \csname\HyRef@name autorefname\endcsname
9050             \noexpand~%
9051           }%
9052         }%
9053       }{%
9054         \edef\HyRef@currentHtag{%
9055           \expandafter\noexpand\csname#1name\endcsname
9056           \noexpand~%
9057         }%

```

```

9058 }%
9059 }{%
9060 \edef\HyRef@currentHtag{%
9061   \expandafter\noexpand\csname#1\autorefname\endcsname
9062   \noexpand~%
9063 }%
9064 }%
9065 }
9066 \def\HyRef@StripStar#1*\#2\@nil#3{%
9067   \def\HyRef@name{#2}%
9068   \ifx\HyRef@name\HyRef@CaseStar
9069     \def\HyRef@name{#1}%
9070   \else
9071     \def\HyRef@name{#3}%
9072   \fi
9073 }
9074 \def\HyRef@CaseStar{*\\}
9075 \def\HyRef@currentHtag{}

```

Support for package showkeys.

\HyRef@ShowKeysRef

```

9076 \let\HyRef@ShowKeysRef@gobble
9077 \def\HyRef@ShowKeysInit{%
9078   \begingroup\expandafter\expandafter\expandafter\endgroup
9079   \expandafter\ifx\csname SK@@label\endcsname\relax
9080   \else
9081     \ifx\SK@ref\@empty
9082     \else
9083       \def\HyRef@ShowKeysRef{%
9084         \SK@\SK@\ref
9085       }%
9086     \fi
9087   \fi
9088 }
9089 \@ifpackageloaded{showkeys}{%
9090   \HyRef@ShowKeysInit
9091 }{%
9092   \Hy@AtBeginDocument{%
9093     \@ifpackageloaded{showkeys}{%
9094       \HyRef@ShowKeysInit
9095     }{%
9096     }%
9097 }

```

Defaults for the names that \autoref uses.

```

9098 \providecommand*\AMSautorefname{\equationautorefname}
9099 \providecommand*\Hfootnoteautorefname{\footnoteautorefname}
9100 \providecommand*\Itemautorefname{\itemautorefname}
9101 \providecommand*\itemautorefname{item}
9102 \providecommand*\equationautorefname{Equation}
9103 \providecommand*\footnoteautorefname{footnote}
9104 \providecommand*\itemautorefname{item}
9105 \providecommand*\figureautorefname{Figure}
9106 \providecommand*\tableautorefname{Table}
9107 \providecommand*\partautorefname{Part}
9108 \providecommand*\appendixautorefname{Appendix}
9109 \providecommand*\chapterautorefname{chapter}

```

```

9110 \providecommand*\sectionautorefname{section}
9111 \providecommand*\subsectionautorefname{subsection}
9112 \providecommand*\subsubsectionautorefname{subsubsection}
9113 \providecommand*\paragraphautorefname{paragraph}
9114 \providecommand*\subparagraphautorefname{subparagraph}
9115 \providecommand*\FancyVerbLineautorefname{line}
9116 \providecommand*\theoremautorefname{Theorem}
9117 \providecommand*\pageautorefname{page}
9118 \end{package}

```

47 Configuration files

47.1 PS/PDF strings

Some drivers write PS or PDF strings. These strings are delimited by parentheses, therefore a lonely unmatched parenthesis must be avoided to avoid PS or PDF syntax errors. Also the backslash character itself has to be protected.

`\Hy@pstringdef` Therefore such strings should be passed through `\Hy@pstringdef`. The first argument holds a macro for the result, the second argument is the string that needs protecting. Since version 1.30.0 pdf_T_EX offers `\pdfescapestring`.

```

9119 (*pdfTEX | dvipdfm | xetex | vtex | pdfmarkbase | dviwindo)
9120 \begingroup\expandafter\expandafter\expandafter\endgroup
9121 \expandafter\ifx\csname pdf@escapestring\endcsname\relax
9122 \begingroup
9123 \catcode'\=0 %
9124 \@makeother\%
9125 |@firstofone{|endgroup
9126 |def|Hy@pstringdef#1#2{%
9127 |begingroup
9128 |edef~{|string~}%
9129 |xdef|Hy@gtemp{#2}%
9130 |endgroup
9131 |let#1|Hy@gtemp
9132 |@onelevel@sanitize#1%
9133 |edef#1{|expandafter|Hy@ExchangeBackslash#1|@nil}%
9134 |edef#1{|expandafter|Hy@ExchangeLeftParenthesis#1(|@nil}%
9135 |edef#1{|expandafter|Hy@ExchangeRightParenthesis#1)|@nil}%
9136 }%
9137 |def|Hy@ExchangeBackslash#1|#2|@nil{%
9138 #1%
9139 |ifx|\#2|\%%
9140 |else
9141 \\\%
9142 |ltx@ReturnAfterFi{%
9143 |Hy@ExchangeBackslash#2|@nil
9144 }%
9145 |fi
9146 }%
9147 }%
9148 \def|Hy@ExchangeLeftParenthesis#1(#2|@nil{%
9149 #1%
9150 \ifx\#2\%%
9151 \else
9152 \@backslashchar(%
9153 \ltx@ReturnAfterFi{%

```

```

9154 \Hy@ExchangeLeftParenthesis#2\@nil
9155 }%
9156 \fi
9157 }%
9158 \def\Hy@ExchangeRightParenthesis#1)#2\@nil{%
9159 #1%
9160 \ifx\#2\%
9161 \else
9162 \@backslashchar)%
9163 \ltx@ReturnAfterFi{%
9164 \Hy@ExchangeRightParenthesis#2\@nil
9165 }%
9166 \fi
9167 }%
9168 \else
9169 \def\Hy@pstringdef#1#2{%
9170 \begingroup
9171 \edef~{\string~}%
9172 \xdef\Hy@gtemp{\pdf@escapestring{#2}}%
9173 \endgroup
9174 \let#1\Hy@gtemp
9175 }%
9176 \fi
9177 </pdfTeX | dvipdfm | xetex | vtex | pdfmarkbase | dviwindo>

```

47.2 pdfTeX

```

9178 <*pdfTeX>
9179 \providecommand*\XR@ext}{pdf}
9180 \Hy@setbreaklinks{true}
9181 \def\HyPat@ObjRef{%
9182 [0-9]*[1-9][0-9]* 0 R%
9183 }

```

This driver is for Han The Thanh's T_EX variant which produces PDF directly. This has new primitives to do PDF things, which usually translate almost directly to PDF code, so there is a lot of flexibility which we do not at present harness.

Set PDF version if requested by option pdfversion.

- pdfT_EX 1.10a, 2003-01-16: \pdfoptionpdfminorversion
- pdfT_EX 1.30, 2005-08-081: \pdfminorversion

```

9184 \let\Hy@pdfminorversion\relax
9185 \begingroup\expandafter\expandafter\expandafter\endgroup
9186 \expandafter\ifx\csname pdfminorversion\endcsname\relax
9187 \begingroup\expandafter\expandafter\expandafter\endgroup
9188 \expandafter\ifx\csname pdfoptionpdfminorversion\endcsname\relax
9189 \else
9190 \def\Hy@pdfminorversion{\pdfoptionpdfminorversion}%
9191 \fi
9192 \else
9193 \def\Hy@pdfminorversion{\pdfminorversion}%
9194 \fi
9195 \@ifundefined{Hy@pdfminorversion}{%
9196 \PackageInfo{hyperref}{%
9197 PDF version is not set, because pdfTeX is too old (<1.10a)%
9198 }%
9199 }{%

```

```

9200 \ifHy@ocgcolorlinks
9201   \ifnum\Hy@pdfminorversion<5 %
9202     \kvsetkeys{Hyp}{pdfversion=1.5}%
9203   \fi
9204 \fi
9205 \ifHy@setpdfversion
9206   \ifnum\Hy@pdfversion<5 %
9207     \ltx@ifundefined{pdfobjcompresslevel}{%
9208       }{%
9209         \ifHy@verbose
9210           \Hy@InfoNoLine{%
9211             PDF object streams are disabled, because they are%
9212             \MessageBreak
9213             not supported in requested PDF version %
9214             1.\Hy@pdfversion
9215           }%
9216         \fi
9217         \pdfobjcompresslevel=\ltx@zero
9218       }%
9219     \fi
9220   \ifnum\Hy@pdfminorversion=\Hy@pdfversion\relax
9221   \else
9222     \let\Hy@temp\ltx@empty
9223     \def\Hy@temp@A#1#2{%
9224       \ifnum#1>\ltx@zero
9225         \edef\Hy@temp{%
9226           \Hy@temp
9227           \space\space
9228           \the#1\space #2%
9229           \ifnum#1=\ltx@one\else s\fi
9230           \MessageBreak
9231         }%
9232       \fi
9233     }%
9234     \Hy@temp@A\pdflastobj{PDF object}%
9235     \Hy@temp@A\pdflastxform{form XObject}%
9236     \Hy@temp@A\pdflastximage{image XObject}%
9237     \Hy@temp@A\pdflastannot{annotation}%
9238     \ltx@ifundefined{pdflastlink}{%
9239       }{%
9240         \Hy@temp@A\pdflastlink{link}%
9241       }%
9242     \ifx\Hy@temp\ltx@empty
9243       \Hy@pdfminorversion=\Hy@pdfversion\relax
9244     \else
9245       \let\Hy@temp@A\ltx@empty
9246       \ifnum\Hy@pdfversion=4 %
9247         \IfFileExists{pdf14.sty}{%
9248           \def\Hy@temp@A{%
9249             \MessageBreak
9250             Or \string\RequirePackage{pdf14} can be used%
9251             \MessageBreak
9252             before \string\documentclass\space as shortcut%
9253           }%
9254         }{}%
9255       \fi
9256       \Hy@WarningNoLine{%

```

```

9257     The PDF version number could not be set,\MessageBreak
9258     because some PDF objects are already written:%
9259     \MessageBreak
9260     \Hy@temp
9261     The version should be set as early as possible:%
9262     \MessageBreak
9263     \space\space
9264     \expandafter\string\Hy@pdfminorversion=\Hy@pdfversion
9265     \string\relax
9266     \ifnum\Hy@pdfversion<5 %
9267     \ltx@ifundefined{pdfobjcompresslevel}{%
9268     }{%
9269     \MessageBreak
9270     \space\space
9271     \string\pdfobjcompresslevel=0\string\relax
9272     }%
9273     \fi
9274     \Hy@temp@A
9275     }%
9276     \fi
9277     \fi
9278     \PackageInfo{hyperref}{%
9279     \expandafter\string\Hy@pdfminorversion
9280     :=\number\Hy@pdfversion\space
9281     }%
9282     \fi
9283     \edef\Hy@pdfversion{\number\Hy@pdfminorversion}%
9284 }
9285 \Hy@DisableOption{pdfversion}%

9286 \ifHy@ocgcolorlinks
9287 \pdf@ifdraftmode{}{%
9288 \immediate\pdfobj{%
9289 <<%
9290 /Type/OCG%
9291 /Name(View)%
9292 /Usage<<%
9293 /Print<<%
9294 /PrintState/OFF%
9295 >>%
9296 /View<<%
9297 /ViewState/ON%
9298 >>%
9299 >>%
9300 >>%
9301 }%
9302 \edef\OBJ@OCG@view{\the\pdflastobj\space 0 R}%
9303 \immediate\pdfobj{%
9304 <<%
9305 /Type/OCG%
9306 /Name(Print)%
9307 /Usage<<%
9308 /Print<<%
9309 /PrintState/ON%
9310 >>%
9311 /View<<%
9312 /ViewState/OFF%
9313 >>%

```



```

9314     >>%
9315     >>%
9316 }%
9317 \edef\OBJ@OCG@print{\the\pdflastobj\space 0 R}%
9318 \immediate\pdfobj{%
9319 [%
9320   \OBJ@OCG@view\space\OBJ@OCG@print
9321 ]%
9322 }%
9323 \edef\OBJ@OCGs{\the\pdflastobj\space 0 R}%
9324 \pdfcatalog{%
9325   /OCProperties<<%
9326     /OCGs \OBJ@OCGs
9327   /D<<%
9328     /OFF[\OBJ@OCG@print]%
9329   /AS[%
9330     <<%
9331       /Event/View%
9332       /OCGs \OBJ@OCGs
9333       /Category[/View]%
9334     >>%
9335     <<%
9336       /Event/Print%
9337       /OCGs \OBJ@OCGs
9338       /Category[/Print]%
9339     >>%
9340     <<%
9341       /Event/Export%
9342       /OCGs \OBJ@OCGs
9343       /Category[/Print]%
9344     >>%
9345   ]%
9346   >>%
9347   >>%
9348 }%
9349 \begingroup
9350 \edef\x{\endgroup
9351   \pdfpageresources{%
9352     \the\pdfpageresources
9353     /Properties<<%
9354       /OCView \OBJ@OCG@view
9355       /OCPrint \OBJ@OCG@print
9356     >>%
9357   }%
9358 }%
9359 \x
9360 }%
9361 \Hy@AtBeginDocument{%
9362   \def\Hy@colorlink#1{%
9363     \begingroup
9364       \ifHy@ocgcolorlinks
9365         \def\Hy@ocgcolor{#1}%
9366         \setbox0=\hbox\bgroup\color@begingroup
9367       \else
9368         \HyColor@UseColor#1%
9369       \fi
9370   }%

```

```

9371 \def\Hy@endcolorlink{%
9372 \ifHy@ocgcolorlinks
9373 \color@endgroup\egroup
9374 \mbox{%
9375 \pdfliteral page{/OC/OCPrint BDC}%
9376 \rlap{\copy0}%
9377 \pdfliteral page{EMC/OC/OCView BDC}%
9378 \begingroup
9379 \expandafter\HyColor@UseColor\Hy@ocgcolor
9380 \box0 %
9381 \endgroup
9382 \pdfliteral page{EMC}%
9383 }%
9384 \fi
9385 \endgroup
9386 }%
9387 }%
9388 \else
9389 \Hy@DisableOption{ocgcolorlinks}%
9390 \fi

```

First, allow for some changes and additions to pdftex syntax:

```

9391 \def\setpdfinkmargin#1{\pdfinkmargin#1}
9392 \ifx\pdfstartlink\@undefined% less than version 14
9393 \let\pdfstartlink\pdfannotlink
9394 \let\pdfinkmargin\@tempdima
9395 \let\pdfxform\pdfform
9396 \let\pdfastxform\pdfastform
9397 \let\pdfrefxform\pdfrefform
9398 \else
9399 \pdfinkmargin1pt %
9400 \fi

```

First set up the default linking

```

9401 \providecommand*\@pdfview{XYZ}

```

First define the anchors:

```

9402 \Hy@WrapperDef\new@pdfink#1{%
9403 \ifhmode
9404 \@savsf\spacefactor
9405 \fi
9406 \Hy@SaveLastskip
9407 \Hy@VerboseAnchor{#1}%
9408 \Hy@pstringdef\Hy@pstringDest{\HyperDestNameFilter{#1}}%
9409 \Hy@DestName\Hy@pstringDest\@pdfview
9410 \Hy@RestoreLastskip
9411 \ifhmode
9412 \spacefactor\@savsf
9413 \fi
9414 }
9415 \let\pdf@endanchor\@empty

```

`\Hy@DestName` Wrap the call of `\pdfdest name` in `\Hy@DestName`. Then it can easier be caught by package `hypdestopt`.

```

9416 \def\Hy@DestName#1#2{%
9417 \pdfdest name{#1}#2\relax
9418 }

```

Now the links; the interesting part here is the set of attributes which define how the link looks. We probably want to add a border and color it, but there are other choices. This directly translates to PDF code, so consult the manual for how to change this. We will add an interface at some point.

```

9419 \providecommand*\pdfborder{0 0 1}
9420 \providecommand*\pdfborderstyle{}
9421 \def\Hy@undefinedname{UNDEFINED}
9422 \def\find@pdflink#1#2{%
9423   \leavevmode
9424   \protected@edef\Hy@testname{#2}%
9425   \ifx\Hy@testname\@empty
9426     \Hy@Warning{%
9427       Empty destination name,\MessageBreak
9428       using '\Hy@undefinedname'%
9429     }%
9430   \let\Hy@testname\Hy@undefinedname
9431   \else
9432     \Hy@pstringdef\Hy@testname{%
9433       \expandafter\HyperDestNameFilter\expandafter{\Hy@testname}%
9434     }%
9435   \fi
9436   \Hy@StartlinkName{%
9437     \ifHy@pdfa /F 4\fi
9438     \Hy@setpdfborder
9439     \ifx\@pdfhighlight\@empty
9440       \else
9441         /H\@pdfhighlight
9442       \fi
9443     \ifx\CurrentBorderColor\relax
9444       \else
9445         /C[\CurrentBorderColor]%
9446       \fi
9447   }\Hy@testname
9448   \expandafter\Hy@colorlink\csname @#1color\endcsname
9449 }
9450 \def\Hy@StartlinkName#1#2{%
9451   \pdfstartlink attr{#1}goto name{#2}\relax
9452 }
9453 \def\close@pdflink{%
9454   \Hy@endcolorlink
9455   \Hy@VerboseLinkStop
9456   \pdfendlink
9457 }
9458 \def\hyper@anchor#1{%
9459   \new@pdflink{#1}\anchor@spot\pdf@endanchor
9460 }
9461 \def\hyper@anchorstart#1{%
9462   \new@pdflink{#1}%
9463   \Hy@activeanchortrue
9464 }
9465 \def\hyper@anchorend{%
9466   \pdf@endanchor
9467   \Hy@activeanchorfalse
9468 }
9469 \def\hyper@linkstart#1#2{%
9470   \Hy@VerboseLinkStart{#1}{#2}%
9471   \ltx@ifundefined{@#1bordercolor}{%

```

```

9472 \let\CurrentBorderColor\relax
9473 }{%
9474 \edef\CurrentBorderColor{\csname @#1bordercolor\endcsname}%
9475 }%
9476 \find@pdfink{#1}{#2}%
9477 }
9478 \def\hyper@linkend{\close@pdfink}
9479 \def\hyper@link#1#2#3{%
9480 \Hy@VerboseLinkStart{#1}{#2}%
9481 \ltx@ifundefined{@#1bordercolor}{%
9482 \let\CurrentBorderColor\relax
9483 }{%
9484 \edef\CurrentBorderColor{\csname @#1bordercolor\endcsname}%
9485 }%
9486 \find@pdfink{#1}{#2}#3\Hy@xspace@end
9487 \close@pdfink
9488 }
9489 \let\CurrentBorderColor\@linkbordercolor
9490 \def\hyper@linkurl#1#2{%
9491 \begingroup
9492 \Hy@pstringdef\Hy@pstringURI{#2}%
9493 \hyper@chars
9494 \leavevmode
9495 \pdfstartlink
9496 attr{%
9497 \Hy@setpdfborder
9498 \ifx\@pdfhighlight\@empty
9499 \else
9500 /H\@pdfhighlight
9501 \fi
9502 \ifx\@urlbordercolor\relax
9503 \else
9504 /C[\@urlbordercolor]%
9505 \fi
9506 }%
9507 user{%
9508 /Subtype/Link%
9509 \ifHy@pdfa /F 4\fi
9510 /A<<%
9511 /Type/Action%
9512 /S/URI%
9513 /URI(\Hy@pstringURI)%
9514 \ifHy@href@ismap
9515 /IsMap true%
9516 \fi
9517 \Hy@href@nextactionraw
9518 >>%
9519 }%
9520 \relax
9521 \Hy@colorlink\@urlcolor#1\Hy@xspace@end
9522 \close@pdfink
9523 \endgroup
9524 }
9525 \def\hyper@linkfile#1#2#3{% anchor text, filename, linkname
9526 \begingroup
9527 \def\Hy@pstringF{#2}%
9528 \Hy@CleanupFile\Hy@pstringF

```

```

9529 \Hy@pstringdef\Hy@pstringF\Hy@pstringF
9530 \Hy@pstringdef\Hy@pstringD{#3}%
9531 \Hy@MakeRemoteAction
9532 \leavevmode
9533 \pdfstartlink
9534 attr{%
9535   \Hy@setpdfborder
9536   \ifx\@pdfhighlight\@empty
9537   \else
9538     /H\@pdfhighlight
9539   \fi
9540   \ifx\@filebordercolor\relax
9541   \else
9542     /C[\@filebordercolor]%
9543   \fi
9544 }%
9545 user {%
9546   /Subtype/Link%
9547   \ifHy@pdfa /F 4\fi
9548   /A<<%
9549   /F(\Hy@pstringF)%
9550   /S/GoToR%
9551   \Hy@SetNewWindow

```

If #3 is empty, page 0; if its a number, Page number, otherwise a named destination.

```
\afterassignment\xxx\count@=0\foo!
```

```

\def\xxx#1!{%
  \ifx\xxx#1\xxx
    foo was an integer
  \else
    it wasnt
  \fi}

```

```

9552 \ifx\#3\%
9553   /D[\Hy@href@page\@pdfremotestartview]%
9554 \else
9555   /D(\Hy@pstringD)%
9556 \fi
9557 \Hy@href@nextactionraw
9558 >>%
9559 }%
9560 \relax
9561 \Hy@colorlink\@filecolor#1\Hy@xspace@end
9562 \close@pdfink
9563 \endgroup
9564 }
9565 \def\@hyper@launch run:#1\#2#3{% filename, anchor text linkname
9566 \begingroup
9567 \Hy@pstringdef\Hy@pstringF{#1}%
9568 \Hy@pstringdef\Hy@pstringP{#3}%
9569 \leavevmode
9570 \pdfstartlink
9571 attr{%
9572   \Hy@setpdfborder
9573   \ifx\@pdfhighlight\@empty

```

```

9574     \else
9575         /H\@pdfhighlight
9576     \fi
9577     \ifx\@runbordercolor\relax
9578     \else
9579         /C[\@runbordercolor]%
9580     \fi
9581 }%
9582 user {%
9583     /Subtype/Link%
9584     \ifHy@pdfa /F 4\fi
9585     /A<<%
9586         /F(\Hy@pstringF)%
9587         /S/Launch%
9588         \Hy@SetNewWindow
9589         \ifx\#3\%
9590         \else
9591             /Win<</P(\Hy@pstringP)/F(\Hy@pstringF)>>%
9592         \fi
9593         \Hy@href@nextactionraw
9594     >>%
9595 }%
9596 \relax
9597 \Hy@colorlink\@runcolor#2\Hy@xspace@end
9598 \close@pdflink
9599 \endgroup
9600 }

```

\@pdfproducer

```

9601 \ifx\@pdfproducer\relax
9602 \begin@group\expandafter\expandafter\expandafter\endgroup
9603 \expandafter\ifx\csname luatexversion\endcsname\relax
9604 \def\@pdfproducer{pdfTeX}%
9605 \ifx\TeXversion\@undefined
9606 \else
9607 \ifx\TeXversion\relax
9608 \else
9609 \ifnum\TeXversion>0 %
9610 \def\@pdfproducer{pdfTeX}%
9611 \fi
9612 \fi
9613 \fi
9614 \ifx\pdfTeXversion\@undefined
9615 \else
9616 \ifnum\pdfTeXversion<100 %
9617 \edef\@pdfproducer{%
9618     \@pdfproducer
9619     \the\pdfTeXversion.\pdfTeXrevision
9620 }%
9621 \else
9622 \ifnum\pdfTeXversion<130 %
9623 \edef\@pdfproducer{%
9624     \@pdfproducer-
9625     \expandafter\@car\the\pdfTeXversion\@empty\@nil.%
9626     \expandafter\@cdr\the\pdfTeXversion\@empty\@nil
9627     \pdfTeXrevision
9628 }%

```

```

9629 \else
9630 \ifnum\pdfTeXversion<140 %
9631 \else
9632 \def\@pdfproducer{pdfTeX}%
9633 \fi
9634 \edef\@pdfproducer{%
9635 \@pdfproducer-%
9636 \expandafter\@car\the\pdfTeXversion\@empty\@nil.%
9637 \expandafter\@cdr\the\pdfTeXversion\@empty\@nil.%
9638 \pdfTeXrevision
9639 }%
9640 \fi
9641 \fi
9642 \fi
9643 \else
9644 \begingroup
9645 \count@=\luatexversion
9646 \divide\count@ by 100 %
9647 \edef\x{\the\count@}%
9648 \count@=-\x\relax
9649 \multiply\count@ by 100 %
9650 \advance\count@ by \luatexversion
9651 \edef\x{\endgroup
9652 \def\noexpand\@pdfproducer{%
9653 LuaTeX-\x.\the\count@.\luatexrevision
9654 }%
9655 }%
9656 \x
9657 \fi
9658 \fi

```

\PDF@SetupDox

```

9659 \def\PDF@SetupDoc{%
9660 \ifx\@pdfpagescrop\@empty
9661 \else
9662 \edef\process@me{%
9663 \pdfpagesattr={%
9664 /CropBox[\@pdfpagescrop]%
9665 \expandafter\ifx\expandafter\\\the\pdfpagesattr\\%
9666 \else
9667 ^^J\the\pdfpagesattr
9668 \fi
9669 }%
9670 }%
9671 \process@me
9672 \fi
9673 \Hy@pstringdef\Hy@pstringB{\@baseurl}%
9674 \pdfcatalog{%
9675 /PageMode/\@pdfpagemode
9676 \ifx\@baseurl\@empty
9677 \else
9678 /URI<</Base(\Hy@pstringB)>>%
9679 \fi
9680 }%
9681 \ifx\@pdfstartpage\@empty
9682 \else
9683 \ifx\@pdfstartview\@empty
9684 \else

```

```

9685     openaction goto page\@pdfstartpage{\@pdfstartview}%
9686     \fi
9687 \fi
9688 \edef\Hy@temp{%
9689     \ifHy@pdftoolbar\else /HideToolbar true\fi
9690     \ifHy@pdfmenubar\else /HideMenubar true\fi
9691     \ifHy@pdfwindowui\else /HideWindowUI true\fi
9692     \ifHy@pdfwindow /FitWindow true\fi
9693     \ifHy@pdfcenterwindow /CenterWindow true\fi
9694     \ifHy@pdfdisplaydoctitle /DisplayDocTitle true\fi
9695     \Hy@UseNameKey{NonFullScreenPageMode}\@pdfnonfullscreenpagemode
9696     \Hy@UseNameKey{Direction}\@pdfdirection
9697     \Hy@UseNameKey{ViewArea}\@pdfviewarea
9698     \Hy@UseNameKey{ViewClip}\@pdfviewclip
9699     \Hy@UseNameKey{PrintArea}\@pdfprintarea
9700     \Hy@UseNameKey{PrintClip}\@pdfprintclip
9701     \Hy@UseNameKey{PrintScaling}\@pdfprintscaling
9702     \Hy@UseNameKey{Duplex}\@pdfduplex
9703     \ifx\@pdfpicktraybypdfsize\@empty
9704     \else
9705         /PickTrayByPDFSize \@pdfpicktraybypdfsize
9706     \fi
9707     \ifx\@pdfprintpagerange\@empty
9708     \else
9709         /PrintPageRange[\@pdfprintpagerange]%
9710     \fi
9711     \ifx\@pdfnumcopies\@empty
9712     \else
9713         /NumCopies \@pdfnumcopies
9714     \fi
9715 }%
9716 \pdfcatalog{%
9717     \ifx\Hy@temp\@empty
9718     \else
9719         /ViewerPreferences<<\Hy@temp>>%
9720     \fi
9721     \Hy@UseNameKey{PageLayout}\@pdfpagelayout
9722     \ifx\@pdflang\@empty
9723     \else
9724         /Lang(\@pdflang)%
9725     \fi
9726 }%
9727 }

```

\PDF@FinishDoc

```

9728 \def\PDF@FinishDoc{%
9729     \pdf@ifdraftmode{}{%
9730         \Hy@UseMaketitleInfos
9731         \HyInfo@GenerateAddons
9732     \pdfinfo{%
9733         /Author(\@pdfauthor)%
9734         /Title(\@pdftitle)%
9735         /Subject(\@pdfsubject)%
9736         /Creator(\@pdfcreator)%
9737         \ifx\@pdfcreationdate\@empty
9738         \else
9739             /CreationDate(\@pdfcreationdate)%
9740         \fi

```



```

9741 \ifx\@pdfmoddate\@empty
9742 \else
9743 /ModDate(\@pdfmoddate)%
9744 \fi
9745 \ifx\@pdfproducer\relax
9746 \else
9747 /Producer(\@pdfproducer)%
9748 \fi
9749 /Keywords(\@pdfkeywords)%
9750 \ifx\@pdftrapped\@empty
9751 \else
9752 /Trapped/\@pdftrapped
9753 \fi
9754 \HyInfo@Addons
9755 }%
9756 }%
9757 \Hy@DisableOption{pdfauthor}%
9758 \Hy@DisableOption{pdftitle}%
9759 \Hy@DisableOption{pdfsubject}%
9760 \Hy@DisableOption{pdfcreator}%
9761 \Hy@DisableOption{pdfcreationdate}%
9762 \Hy@DisableOption{pdfmoddate}%
9763 \Hy@DisableOption{pdfproducer}%
9764 \Hy@DisableOption{pdfkeywords}%
9765 \Hy@DisableOption{pdftrapped}%
9766 \Hy@DisableOption{pdfinfo}%
9767 }

```

`\hyper@pagetransition` `\@pdfpagetransition` is initialized with `\relax`. So it indicates, if option `pdfpagetransition` is used. First previous `/Trans` entries are removed. If a new `/Trans` key exists, it is appended to `\pdfpageattr`.

```

9768 \def\hyper@pagetransition{%
9769 \ifx\@pdfpagetransition\relax
9770 \else
9771 \expandafter\Hy@RemoveTransPageAttr
9772 \the\pdfpageattr^^J/Trans{>>\END
9773 \ifx\@pdfpagetransition\@empty
9774 \else
9775 \edef\@processme{%
9776 \global\pdfpageattr{%
9777 \the\pdfpageattr
9778 ^^J/Trans << /S /\@pdfpagetransition\space >>%
9779 }%
9780 }%
9781 \@processme
9782 \fi
9783 \fi
9784 }

```

`\Hy@RemoveTransPageAttr` Macro `\Hy@RemoveTransPageAttr` removes a `/Trans` entry from `\pdfpageattr`. It is called with the end marker `^^J/Trans{>>\END`. The trick is the empty group that does not appear in legal `\pdfpageattr` code. It appears in argument #2 and shows, whether the parameter text catches a really `/Trans` object or the end marker.

```

9785 \gdef\Hy@RemoveTransPageAttr#1^^J/Trans#2#3>>#4\END{%
9786 \ifx\#2\%
9787 \global\pdfpageattr{#1}%

```

```

9788 \else
9789 \Hy@RemoveTransPageAttr#1#4\END
9790 \fi
9791 }

```

`\hyper@pageduration` `\@pdfpageduration` is initialized with `\relax`. So it indicates, if option `pdfpage-` `duration` is used. First previous `/Dur` entries are removed. If a new `/Dur` key exists, it is appended to `\pdfpageattr`.

```

9792 \def\hyper@pageduration{%
9793 \ifx\@pdfpageduration\relax
9794 \else
9795 \expandafter
9796 \Hy@RemoveDurPageAttr\the\pdfpageattr^^J/Dur{} \END
9797 \ifx\@pdfpageduration\@empty
9798 \else
9799 \edef\@processme{%
9800 \global\pdfpageattr{%
9801 \the\pdfpageattr
9802 ^^J/Dur \@pdfpageduration\space
9803 }%
9804 }%
9805 \@processme
9806 \fi
9807 \fi
9808 }

```

`\Hy@RemoveDurPageAttr` Macro `\Hy@RemoveDurPageAttr` removes a `/Dur` entry from `\pdfpageattr`. It is called with the end marker `^^J/Dur{} \END`. The trick is the empty group that does not appear in legal `\pdfpageattr` code. It appears in argument `#2` and shows, whether the parameter text catches a really `/Dur` object or the end marker.

```

9809 \gdef\Hy@RemoveDurPageAttr#1^^J/Dur#2#3 #4\END{%
9810 \ifx\#2\%
9811 \global\pdfpageattr{#1}%
9812 \else
9813 \Hy@RemoveDurPageAttr#1#4\END
9814 \fi
9815 }

```

`\hyper@pagehidden` The boolean value of the key `/Hid` is stored in switch `\ifHy@pdfpagehidden`. First previous `/Hid` entries are removed, then the new one is appended, if the value is true (the PDF default is false).

```

9816 \def\hyper@pagehidden{%
9817 \ifHy@useHidKey
9818 \expandafter
9819 \Hy@RemoveHidPageAttr\the\pdfpageattr^^J/Hid{} \END
9820 \ifHy@pdfpagehidden
9821 \edef\@processme{%
9822 \global\pdfpageattr{%
9823 \the\pdfpageattr
9824 ^^J/Hid true % SPACE
9825 }%
9826 }%
9827 \@processme
9828 \fi
9829 \fi
9830 }

```

`\Hy@RemoveHidPageAttr` Macro `\Hy@RemoveHidPageAttr` removes a `/Hid` entry from `\pdfpageattr`. It is called with the end marker `^^J/Hid{} \END`. The trick is the empty group that does not appear in legal `\pdfpageattr` code. It appears in argument `#2` and shows, whether the parameter text catches a really `/Hid` object or the end marker.

```

9831 \gdef\Hy@RemoveHidPageAttr#1^^J/Hid#2#3 #4\END{%
9832   \ifx\#2\%
9833     \global\pdfpageattr{#1}%
9834   \else
9835     \Hy@RemoveHidPageAttr#1#4\END
9836   \fi
9837 }

9838 \pdf@ifdraftmode{}{%
9839   \g@addto@macro\Hy@EveryPageHook{%
9840     \hyper@pagetransition
9841     \hyper@pageduration
9842     \hyper@pagehidden
9843   }%
9844 }
```

Also XeTeX support `\pdfpagewidth` and `\pdfpageheight`, but it does not provide `\pdfhorigin` and `\pdfvorigin`.

```

9845 </pdfTeX>
9846 (*pdfTeX | xetex)
9847 \Hy@AtBeginDocument{%
9848   \ifHy@setpagesize
9849     \expandafter\@firstofone
9850   \else
9851     \expandafter\@gobble
9852   \fi
9853 }%
9854 \@ifclassloaded{seminar}{%
9855 (*pdfTeX)
9856   \setlength{\pdfhorigin}{1truein}%
9857   \setlength{\pdfvorigin}{1truein}%
9858 </pdfTeX>
9859   \ifportrait
9860     \ifdim\paperwidth=\z@
9861     \else
9862       \setlength{\pdfpagewidth}{\strip@pt\paperwidth truept}%
9863     \fi
9864     \ifdim\paperheight=\z@
9865     \else
9866       \setlength{\pdfpageheight}{\strip@pt\paperheight truept}%
9867     \fi
9868   \else
9869     \ifdim\paperheight=\z@
9870     \else
9871       \setlength{\pdfpagewidth}{\strip@pt\paperheight truept}%
9872     \fi
9873     \ifdim\paperwidth=\z@
9874     \else
9875       \setlength{\pdfpageheight}{\strip@pt\paperwidth truept}%
9876     \fi
9877   \fi
9878 }{%
9879   \ltx@ifundefined{stockwidth}{%
```

```

9880 \ifdim\paperwidth>\z@
9881 \setlength{\pdfpagewidth}{\paperwidth}%
9882 \fi
9883 \ifdim\paperheight>\z@
9884 \setlength{\pdfpageheight}{\paperheight}%
9885 \fi
9886 }{%
9887 \ifdim\stockwidth>\z@
9888 \setlength{\pdfpagewidth}{\stockwidth}%
9889 \fi
9890 \ifdim\stockheight>\z@
9891 \setlength{\pdfpageheight}{\stockheight}%
9892 \fi
9893 }%
9894 }%
9895 }%
9896 \Hy@DisableOption{setpagesize}%
9897 }
9898 </pdftex|xetex>
9899 <*pdftex>
9900 \def\Acrobatmenu#1#2{%
9901 \Hy@Acrobatmenu{#1}{#2}{%
9902 \leavevmode
9903 \EdefEscapeName\Hy@temp@menu{#1}%
9904 \pdfstartlink
9905 attr{%
9906 \Hy@setpdfborder
9907 \ifx\@pdfhighlight\@empty
9908 \else
9909 /H\@pdfhighlight
9910 \fi
9911 \ifx\@menubordercolor\relax
9912 \else
9913 /C[\@menubordercolor]%
9914 \fi
9915 }%
9916 user{%
9917 /Subtype/Link%
9918 \ifHy@pdfa /F 4\fi
9919 /A<<%
9920 /S/Named%
9921 /N/\Hy@temp@menu
9922 \Hy@href@nextactionraw
9923 >>%
9924 }%
9925 \relax
9926 \Hy@colorlink\@menucolor#2%
9927 \closepdflink
9928 }%
9929 }

```

47.2.1 Fix for problem with different nesting levels

`\AtBeginShipoutFirst` adds an additional box layer around the first output page. This disturbs pdfTeX's low level link commands `\pdfstartlink` and `\pdfendlink`, if a link is broken across the first and second output page.

The problem could be fixed by replacing `\AtBeginShipoutFirst`, because the

box layer is not necessary for pdfTeX—no `\specials` need to be inserted. However it's easier to add an additional box level for the pages after the first one. Also `\AtBeginShipoutFirst` could be invoked independently from `hyperref`.

Since version 2011/10/05 v1.16 of package 'atbegshi' `\AtBeginShipoutFirst` does not add a additional box layer.

```

9930 \def\Hy@FixNotFirstPage{%
9931   \gdef\Hy@FixNotFirstPage{%
9932     \setbox\AtBeginShipoutBox=\hbox{%
9933       \copy\AtBeginShipoutBox
9934     }%
9935   }%
9936 }
9937 \ltx@ifpackagelater{atbegshi}{2011/10/05}{%
9938 }{%
9939   \AtBeginShipout{\Hy@FixNotFirstPage}%
9940 }
9941 \</pdfTeX>

```

47.3 hypertex

The HyperTeX specification (this is borrowed from an article by Arthur Smith) says that conformant viewers/translators must recognize the following set of `\special` commands:

href: `html:`

name: `html:`

end: `html:`

image: `html:`

base_name: `html:<base href = "href_string">`

The *href*, *name* and *end* commands are used to do the basic hypertext operations of establishing links between sections of documents. The *image* command is intended (as with current html viewers) to place an image of arbitrary graphical format on the page in the current location. The *base_name* command is be used to communicate to the *dvi* viewer the full (URL) location of the current document so that files specified by relative URL's may be retrieved correctly.

The *href* and *name* commands must be paired with an *end* command later in the TeX file — the TeX commands between the two ends of a pair form an *anchor* in the document. In the case of an *href* command, the *anchor* is to be highlighted in the *dvi* viewer, and when clicked on will cause the scene to shift to the destination specified by *href_string*. The *anchor* associated with a name command represents a possible location to which other hypertext links may refer, either as local references (of the form `href="#name_string"` with the *name_string* identical to the one in the name command) or as part of a URL (of the form `URL#name_string`). Here *href_string* is a valid URL or local identifier, while *name_string* could be any string at all: the only caveat is that `'` characters should be escaped with a backslash (`\`), and if it looks like a URL name it may cause problems.

```

9942 \<{*hypertex>
9943 \providecommand*\XR@ext\{dvi}
9944 \let\PDF@FinishDoc\ltx@empty

```

```

9945 \def\PDF@SetupDoc{%
9946   \ifx\@baseurl\@empty
9947   \else
9948     \special{html:<base href="\@baseurl">}%
9949   \fi
9950 }
9951 \Hy@WrapperDef\hyper@anchor#1{%
9952   \Hy@SaveLastskip
9953   \Hy@VerboseAnchor{#1}%
9954   \begingroup
9955     \let\protect=\string
9956     \hyper@chars
9957     \special{html:<a name=%
9958       \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}%
9959   \endgroup
9960   \Hy@activeanchortrue
9961   \Hy@colorlink\@anchorcolor\anchor@spot\Hy@endcolorlink
9962   \special{html:</a>}%
9963   \Hy@activeanchorfalse
9964   \Hy@RestoreLastskip
9965 }
9966 \Hy@WrapperDef\hyper@anchorstart#1{%
9967   \Hy@SaveLastskip
9968   \Hy@VerboseAnchor{#1}%
9969   \begingroup
9970     \hyper@chars
9971     \special{html:<a name=%
9972       \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}%
9973   \endgroup
9974   \Hy@activeanchortrue
9975 }
9976 \def\hyper@anchorend{%
9977   \special{html:</a>}%
9978   \Hy@activeanchorfalse
9979   \Hy@RestoreLastskip
9980 }
9981 \def\@urltype{url}
9982 \def\hyper@linkstart#1#2{%
9983   \Hy@VerboseLinkStart{#1}{#2}%
9984   \expandafter\Hy@colorlink\csname @#1color\endcsname
9985   \def\Hy@tempa{#1}%
9986   \ifx\Hy@tempa\@urltype
9987     \special{html:<a href=\hyper@quote#2\hyper@quote>}%
9988   \else
9989     \begingroup
9990       \hyper@chars
9991       \special{html:<a href=%
9992         \hyper@quote\#\HyperDestNameFilter{#2}\hyper@quote>}%
9993     \endgroup
9994   \fi
9995 }
9996 \def\hyper@linkend{%
9997   \special{html:</a>}%
9998   \Hy@endcolorlink
9999 }
10000 \def\hyper@linkfile#1#2#3{%
10001   \hyper@linkurl{#1}{\Hy@linkfileprefix#2\ifx\\#3\\else\##3\fi}%

```

```

10002 }
10003 \def\hyper@linkurl#1#2{%

```

If we want to raise up the final link `\special`, we need to get its height; ask me why L^AT_EX constructs make this totally foul up, and make us revert to basic T_EX. I do not know.

```

10004 \leavevmode
10005 \ifHy@raiselinks
10006 \Hy@SaveSpaceFactor
10007 \Hy@SaveSavedSpaceFactor
10008 \sbox\@tempboxa{\Hy@RestoreSpaceFactor#1}%
10009 \Hy@RestoreSavedSpaceFactor
10010 \@linkdim\dp\@tempboxa
10011 \lower\@linkdim\hbox{%
10012 \hyper@chars
10013 \special{html:<a href=\hyper@quote#2\hyper@quote>}}%
10014 }%
10015 \Hy@colorlink\@urlcolor
10016 \Hy@RestoreSpaceFactor
10017 #1%
10018 \Hy@SaveSpaceFactor
10019 \@linkdim\ht\@tempboxa

```

Because of the interaction with the dvihps processor, we have to subtract a little from the height. This is not clean, or checked. Check with Mark Doyle about what gives here. It may not be needed with the new dvips (Jan 1997).

```

10020 \advance\@linkdim by -6.5\p@
10021 \raise\@linkdim\hbox{\special{html:</a>}}%
10022 \Hy@endcolorlink
10023 \Hy@RestoreSpaceFactor
10024 \else
10025 \begingroup
10026 \hyper@chars
10027 \special{html:<a href=\hyper@quote#2\hyper@quote>}}%
10028 \Hy@colorlink\@urlcolor#1\Hy@xspace@end
10029 \special{html:</a>}}%
10030 \Hy@endcolorlink
10031 \endgroup
10032 \fi
10033 }

```

Very poor implementation of `\hyper@link` without considering #1.

```

10034 \def\hyper@link#1#2#3{%
10035 \Hy@VerboseLinkStart{#1}{#2}%
10036 \hyper@linkurl{#3}{\# \Hy@DestNameFilter{#2}}%
10037 }

10038 \def\hyper@image#1#2{%
10039 \begingroup
10040 \hyper@chars
10041 \special{html:<img src=\hyper@quote#1\hyper@quote>}}%
10042 \endgroup
10043 }
10044 </hypertex>
10045 <*\dviwindo>

```

47.4 dviwindo

[This was developed by David Carlisle]. Within a file dviwindo hyperlinking is used, for external URL's a call to `\wwwbrowser` is made. (You can define this command before or after loading the hyperref package if the default `c:/netscape/netscape` is not suitable) Dviwindo could in fact handle external links to dvi files on the same machine without calling a web browser, but that would mean parsing the URL to recognise such, and this is currently not done.

This was more or less blindly copied from the hypertext cfg. For dviwindo, \LaTeX must specify the size of the active area for links. For some hooks this information is available but for some, the start and end of the link are specified separately in which case a fixed size area of 10000000sp wide by `\baselineskip` high is used.

```
10046 \providecommand*\XR@ext}{dvi}
10047 \providecommand*\wwwbrowser{c:\string\netscape\string\netscape}
10048 \Hy@WrapperDef\hyper@anchor#1{%
10049   \Hy@SaveLastskip
10050   \Hy@VerboseAnchor{#1}%
10051   \begingroup
10052     \let\protect=\string
10053     \special{mark: #1}%
10054   \endgroup
10055   \Hy@Activeanchortrue
10056   \Hy@colorlink\@anchorcolor\anchor@spot\Hy@endcolorlink
10057   \Hy@activeanchorfalse
10058   \Hy@RestoreLastskip
10059 }
10060 \Hy@WrapperDef\hyper@anchorstart#1{%
10061   \Hy@SaveLastskip
10062   \Hy@VerboseAnchor{#1}%
10063   \special{mark: #1}%
10064   \Hy@activeanchortrue
10065 }
10066 \def\hyper@anchorend{%
10067   \Hy@activeanchorfalse
10068   \Hy@RestoreLastskip
10069 }
10070 \def\hyper@linkstart#1#2{%
10071   \Hy@VerboseLinkStart{#1}{#2}%
10072   \expandafter\Hy@colorlink\csname @#1color\endcsname
10073   \special{button: %
10074     10000000 %
10075     \number\baselineskip\space
10076     #2%
10077   }%
10078 }
10079 \def\hyper@linkend{%
10080   \Hy@endcolorlink
10081 }
10082 \def\hyper@link#1#2#3{%
10083   \Hy@VerboseLinkStart{#1}{#2}%
10084   \leavevmode
10085   \ifHy@raiselinks
10086     \Hy@SaveSpaceFactor
10087     \Hy@SaveSavedSpaceFactor
10088     \sbox\@tempboxa{\Hy@RestoreSpaceFactor#3}%
10089     \Hy@RestoreSavedSpaceFactor
```



```

10090 \@linkdim\dp\@tempboxa
10091 \lower\@linkdim\hbox{%
10092 \special{button: %
10093 \number\wd\@tempboxa\space
10094 \number\ht\@tempboxa\space
10095 #2%
10096 }%
10097 \expandafter\Hy@colorlink\csname @#1color\endcsname
10098 \Hy@RestoreSpaceFactor
10099 #3\Hy@xspace@end
10100 \Hy@SaveSpaceFactor
10101 \Hy@endcolorlink
10102 }%
10103 \@linkdim\ht\@tempboxa
10104 \advance\@linkdim by -6.5\p@
10105 \raise\@linkdim\hbox{}%
10106 \Hy@RestoreSpaceFactor
10107 \else
10108 \special{button: %
10109 \number\wd\@tempboxa\space
10110 \number\ht\@tempboxa\space
10111 #2%
10112 }%
10113 \expandafter\Hy@colorlink\csname @#1color\endcsname
10114 #3\Hy@xspace@end
10115 \Hy@endcolorlink
10116 \fi
10117 }
10118 \def\hyper@linkurl#1#2{%
10119 \begingroup
10120 \hyper@chars
10121 \leavevmode
10122 \ifHy@raiselinks
10123 \Hy@SaveSpaceFactor
10124 \Hy@SaveSavedSpaceFactor
10125 \sbox\@tempboxa{\Hy@RestoreSpaceFactor#1}%
10126 \Hy@RestoreSavedSpaceFactor
10127 \@linkdim\dp\@tempboxa
10128 \lower\@linkdim\hbox{%
10129 \special{button: %
10130 \number\wd\@tempboxa\space
10131 \number\ht\@tempboxa\space
10132 launch: \wwwbrowser\space
10133 #2%
10134 }%
10135 \Hy@colorlink\@urlcolor
10136 \Hy@RestoreSpaceFactor
10137 #1\Hy@xspace@end
10138 \Hy@SaveSpaceFactor
10139 \Hy@endcolorlink
10140 }%
10141 \@linkdim\ht\@tempboxa
10142 \advance\@linkdim by -6.5\p@
10143 \raise\@linkdim\hbox{}%
10144 \Hy@RestoreSpaceFactor
10145 \else
10146 \special{button: %

```

```

10147 \number\wd\@tempboxa\space
10148 \number\ht\@tempboxa\space
10149 launch: \wwwbrowser\space
10150 #2%
10151 }%
10152 \Hy@colorlink\@urlcolor
10153 #1\Hy@xspace@end
10154 \Hy@endcolorlink
10155 \fi
10156 \endgroup
10157 }
10158 \def\hyper@linkfile#1#2#3{%
10159 \begingroup
10160 \hyper@chars
10161 \leavevmode
10162 \ifHy@raiselinks
10163 \Hy@SaveSpaceFactor
10164 \Hy@SaveSavedSpaceFactor
10165 \sbox\@tempboxa{\Hy@RestoreSpaceFactor#1}%
10166 \Hy@RestoreSavedSpaceFactor
10167 \@linkdim\dp\@tempboxa
10168 \lower\@linkdim\hbox{%
10169 \special{button: %
10170 \number\wd\@tempboxa\space
10171 \number\ht\@tempboxa\space
10172 #3,%
10173 file: #2%
10174 }%
10175 \Hy@colorlink\@filecolor
10176 \Hy@RestoreSpaceFactor
10177 #1\Hy@xspace@end
10178 \Hy@SaveSpaceFactor
10179 \Hy@endcolorlink
10180 }%
10181 \@linkdim\ht\@tempboxa
10182 \advance\@linkdim by -6.5\p@
10183 \raise\@linkdim\hbox{}}%
10184 \Hy@RestoreSpaceFactor
10185 \else
10186 \special{button: %
10187 \number\wd\@tempboxa\space
10188 \number\ht\@tempboxa\space
10189 #3,%
10190 file: #2%
10191 }%
10192 \Hy@colorlink\@filecolor
10193 #1\Hy@xspace@end
10194 \Hy@endcolorlink
10195 \fi
10196 \endgroup
10197 }
10198 \ifx\@pdfproducer\relax
10199 \def\@pdfproducer{dviwindo + Distiller}%
10200 \fi
10201 \HyInfo@AddonUnsupportedtrue
10202 \def\PDF@FinishDoc{%
10203 \Hy@UseMaketitleInfos

```

```

10204 \HyInfo@TrappedUnsupported
10205 \special{PDF: Keywords \@pdfkeywords}%
10206 \special{PDF: Title \@pdftitle}%
10207 \special{PDF: Creator \@pdfcreator}%
10208 \ifx\@pdfcreationdate\@empty
10209 \else
10210 \special{PDF: CreationDate \@pdfcreationdate}%
10211 \fi
10212 \ifx\@pdfmoddate\@empty
10213 \else
10214 \special{PDF: ModDate \@pdfmoddate}%
10215 \fi
10216 \special{PDF: Author \@pdfauthor}%
10217 \ifx\@pdfproducer\relax
10218 \else
10219 \special{PDF: Producer \@pdfproducer}%
10220 \fi
10221 \special{PDF: Subject \@pdfsubject}%
10222 \Hy@DisableOption{pdfauthor}%
10223 \Hy@DisableOption{pdftitle}%
10224 \Hy@DisableOption{pdfsubject}%
10225 \Hy@DisableOption{pdfcreator}%
10226 \Hy@DisableOption{pdfcreationdate}%
10227 \Hy@DisableOption{pdfmoddate}%
10228 \Hy@DisableOption{pdfproducer}%
10229 \Hy@DisableOption{pdfkeywords}%
10230 \Hy@DisableOption{pdftrapped}%
10231 \Hy@DisableOption{pdfinfo}%
10232 }
10233 \def\PDF@SetupDoc{%
10234 \ifx\@baseurl\@empty
10235 \else
10236 \special{PDF: Base \@baseurl}%
10237 \fi
10238 \ifx\@pdfpagescrop\@empty\else
10239 \special{PDF: BBox \@pdfpagescrop}%
10240 \fi
10241 \def\Hy@temp{}%
10242 \ifx\@pdfstartpage\@empty
10243 \else
10244 \ifx\@pdfstartview\@empty
10245 \else
10246 \edef\Hy@temp{%
10247 ,Page=\@pdfstartpage
10248 ,View=\@pdfstartview
10249 }%
10250 \fi
10251 \fi
10252 \edef\Hy@temp{%
10253 \noexpand\pdfmark{%
10254 pdfmark=/DOCVIEW,%
10255 PageMode=/\@pdfpagemode
10256 \Hy@temp
10257 }%
10258 }%
10259 \Hy@temp
10260 \ifx\@pdfpagescrop\@empty

```

```

10261 \else
10262   \pdfmark{pdfmark=/PAGES,CropBox=\@pdfpagescrop}%
10263 \fi
10264 \edef\Hy@temp{%
10265   \ifHy@pdftoolbar\else /HideToolbar true\fi
10266   \ifHy@pdfmenubar\else /HideMenubar true\fi
10267   \ifHy@pdfwindowui\else /HideWindowUI true\fi
10268   \ifHy@pdffitwindow /FitWindow true\fi
10269   \ifHy@pdfcenterwindow /CenterWindow true\fi
10270   \ifHy@pdfdisplaydoctitle /DisplayDocTitle true\fi
10271   \Hy@UseNameKey{NonFullScreenPageMode}\@pdfnonfullscreenpagemode
10272   \Hy@UseNameKey{Direction}\@pdfdirection
10273   \Hy@UseNameKey{ViewArea}\@pdfviewarea
10274   \Hy@UseNameKey{ViewClip}\@pdfviewclip
10275   \Hy@UseNameKey{PrintArea}\@pdfprintarea
10276   \Hy@UseNameKey{PrintClip}\@pdfprintclip
10277   \Hy@UseNameKey{PrintScaling}\@pdfprintscaling
10278   \Hy@UseNameKey{Duplex}\@pdfduplex
10279   \ifx\@pdfpicktraybypdfsize\@empty
10280   \else
10281     /PickTrayByPDFSize \@pdfpicktraybypdfsize
10282   \fi
10283   \ifx\@pdfprintpagerange\@empty
10284   \else
10285     /PrintPageRange[\@pdfprintpagerange]%
10286   \fi
10287   \ifx\@pdfnumcopies\@empty
10288   \else
10289     /NumCopies \@pdfnumcopies
10290   \fi
10291 }%
10292 \pdfmark{pdfmark=/PUT,%
10293   Raw={%
10294     \string{Catalog\string}<<%
10295     \ifx\Hy@temp\@empty
10296     \else
10297       /ViewerPreferences<<\Hy@temp>>%
10298     \fi
10299     \Hy@UseNameKey{PageLayout}\@pdfpagelayout
10300     \ifx\@pdflang\@empty
10301     \else
10302       /Lang(\@pdflang)%
10303     \fi
10304     >>%
10305   }%
10306 }%
10307 }
10308 </dviwindo>
10309 <*dvipdfm|xetex>

```

47.5 dvipdfm/xetex dvi to PDF converter

Provided by Mark Wicks (mwicks@kettering.edu)

```

10310 \providecommand*\XR@ext}{pdf}
10311 \Hy@setbreaklinks{true}
10312 \def\HyPat@ObjRef{%
10313   @[\^ ]+%

```

```

10314 }
10315 \newsavebox{\pdfm@box}
10316 \def\@pdfm@mark#1{\special{pdf:#1}}
10317 \Hy@WrapperDef\@pdfm@dest#1{%
10318   \Hy@SaveLastskip
10319   \Hy@VerboseAnchor{#1}%
10320   \begingroup
10321     \Hy@pstringdef\Hy@pstringDest{\HyperDestNameFilter{#1}}%
10322     \def\x{XYZ}%
10323     \ifx\x\@pdfview
10324       \def\x{XYZ @xpos @ypos null}%
10325     \else
10326       \def\x{FitH}%
10327       \ifx\x\@pdfview
10328         \def\x{FitH @ypos}%
10329       \else
10330         \def\x{FitBH}%
10331         \ifx\x\@pdfview
10332           \def\x{FitBH @ypos}%
10333         \else
10334           \def\x{FitV}%
10335           \ifx\x\@pdfview
10336             \def\x{FitV @xpos}%
10337           \else
10338             \def\x{FitBV}%
10339             \ifx\x\@pdfview
10340               \def\x{FitBV @xpos}%
10341             \else
10342               \def\x{Fit}%
10343               \ifx\x\@pdfview
10344                 \let\x\@pdfview
10345               \else
10346                 \def\x{FitB}%
10347                 \ifx\x\@pdfview
10348                   \let\x\@pdfview
10349                 \else
10350                   \def\x{FitR}%
10351                   \ifx\x\@pdfview
10352                     \Hy@Warning{'pdfview=FitR' is not supported}%
10353                     \def\x{XYZ @xpos @ypos null}%
10354                   \else
10355                     \@onelevel@sanitize\@pdfview
10356                     \Hy@Warning{%
10357                       Unknown value '\@pdfview' for pdfview%
10358                     }%
10359                     \def\x{XYZ @xpos @ypos null}%
10360                   \fi
10361                 \fi
10362             \fi
10363           \fi
10364         \fi
10365       \fi
10366     \fi
10367   \fi
10368   \@pdfm@mark{dest (\Hy@pstringDest) [@thispage /\x]}%
10369 \endgroup
10370 \Hy@RestoreLastskip

```

```

10371 }
10372 \providecommand*\@pdfview{XYZ}
10373 \providecommand*\@pdfborder{0 0 1}
10374 \providecommand*\@pdfborderstyle{}
10375 \def\hyper@anchor#1{%
10376   \@pdfm@dest{#1}%
10377 }
10378 \def\hyper@anchorstart#1{%
10379   \Hy@activeanchortrue
10380   \@pdfm@dest{#1}%
10381 }
10382 \def\hyper@anchorend{%
10383   \Hy@activeanchorfalse
10384 }
10385 \newcounter{Hy@AnnotLevel}
10386 \ifHy@ocgcolorlinks
10387   \def\OBJ@OCG@view{@OCG@view}%
10388   \@pdfm@mark{%
10389     obj \OBJ@OCG@view <<%
10390       /Type/OCG%
10391       /Name(View)%
10392       /Usage<<%
10393       /Print<<%
10394       /PrintState/OFF%
10395       >>%
10396       /View<<%
10397       /ViewState/ON%
10398       >>%
10399       >>%
10400     }%
10401   }%
10402   \@pdfm@mark{close \OBJ@OCG@view}%
10403   \def\OBJ@OCG@print{@OCG@print}%
10404   \@pdfm@mark{%
10405     obj \OBJ@OCG@print <<%
10406       /Type/OCG%
10407       /Name(Print)%
10408       /Usage<<%
10409       /Print<<%
10410       /PrintState/ON%
10411       >>%
10412       /View<<%
10413       /ViewState/OFF%
10414       >>%
10415       >>%
10416     }%
10417   }%
10418   \@pdfm@mark{close \OBJ@OCG@print}%
10419   \def\OBJ@OCGs{@OCGs}%
10420   \@pdfm@mark{%
10421     obj \OBJ@OCGs [%
10422       \OBJ@OCG@view\space\OBJ@OCG@print
10423     ]%
10424   }%
10425   \@pdfm@mark{close \OBJ@OCGs}%
10426   \@pdfm@mark{%
10427     put @catalog <<%

```

```

10428 /OCProperties<<%
10429 /OCGs \OBJ@OCGs
10430 /D<<%
10431 /OFF[\OBJ@OCG@print]%
10432 /AS[%
10433 <<%
10434 /Event/View%
10435 /OCGs \OBJ@OCGs
10436 /Category[/View]%
10437 >>%
10438 <<%
10439 /Event/Print%
10440 /OCGs \OBJ@OCGs
10441 /Category[/Print]%
10442 >>%
10443 <<%
10444 /Event/Export%
10445 /OCGs \OBJ@OCGs
10446 /Category[/Print]%
10447 >>%
10448 ]%
10449 >>%
10450 >>%
10451 >>%
10452 }%
10453 \AtBeginShipout{%
10454 \setbox\AtBeginShipoutBox=\hbox{%
10455 \copy\AtBeginShipoutBox
10456 \@pdfm@mark{%
10457 put @resources <<%
10458 /Properties<<%
10459 /OCView \OBJ@OCG@view
10460 /OCPrint \OBJ@OCG@print
10461 >>%
10462 >>%
10463 }%
10464 }%
10465 }%
10466 \Hy@AtBeginDocument{%
10467 \def\Hy@colorlink#1{%
10468 \begingroup
10469 \ifHy@ocgcolorlinks
10470 \def\Hy@ocgcolor{#1}%
10471 \setbox0=\hbox\bgroup\color@begingroup
10472 \else
10473 \HyColor@UseColor#1%
10474 \fi
10475 }%
10476 \def\Hy@endcolorlink{%
10477 \ifHy@ocgcolorlinks
10478 \color@endgroup\egroup
10479 \mbox{%
10480 \@pdfm@mark{content /OC/OCPrint BDC}%
10481 \rlap{\copy0}%
10482 \@pdfm@mark{content EMC/OC/OCView BDC}%
10483 \begingroup
10484 \expandafter\HyColor@UseColor\Hy@ocgcolor

```

```

10485         \box0 %
10486     \endgroup
10487     \@pdfm@mark{content EMC}%
10488 }%
10489 \fi
10490 \endgroup
10491 }%
10492 }%
10493 \else
10494     \Hy@DisableOption{ocgcolorlinks}%
10495 \fi

10496 \def\Hy@BeginAnnot#1{%
10497     \stepcounter{Hy@AnnotLevel}%
10498     \ifnum\value{Hy@AnnotLevel}=\@ne
10499         #1%
10500     \fi
10501 }
10502 \def\Hy@endAnnot{%
10503     \ifnum\value{Hy@AnnotLevel}=\@ne
10504         \Hy@endcolorlink
10505         \@pdfm@mark{eann}%
10506     \fi
10507     \addtocounter{Hy@AnnotLevel}\m@ne
10508 }

10509 \def\Hy@undefinedname{UNDEFINED}
10510 \def\hyper@linkstart#1#2{%
10511     \Hy@VerboseLinkStart{#1}{#2}%
10512     \leavevmode
10513     \Hy@BeginAnnot{%
10514         \protected@edef\Hy@testname{#2}%
10515         \ifx\Hy@testname\@empty
10516             \Hy@Warning{%
10517                 Empty destination name,\MessageBreak
10518                 using '\Hy@undefinedname'%
10519             }%
10520         \let\Hy@testname\Hy@undefinedname
10521     \else
10522         \Hy@pstringdef\Hy@testname{%
10523             \expandafter\HyperDestNameFilter\expandafter{%
10524                 \Hy@testname
10525             }%
10526         }%
10527     \fi
10528     \@pdfm@mark{%
10529         bann<<%
10530         /Type/Annot%
10531         /Subtype/Link%
10532         \ifHy@pdfa /F 4\fi
10533         \Hy@setpdfborder
10534         \expandafter\ifx\csname @#1bordercolor\endcsname\relax
10535         \else
10536             /C[\csname @#1bordercolor\endcsname]%
10537         \fi
10538         /A<<%
10539         /S/GoTo%
10540         /D(\Hy@testname)%
10541         \Hy@href@nextactionraw

```



```

10542     >>%
10543     >>%
10544     }%
10545     \expandafter\Hy@colorlink\csname @#1color\endcsname
10546     }%
10547 }
10548 \def\hyper@linkend{\Hy@EndAnnot}%
10549 \def\hyper@link#1#2#3{%
10550   \hyper@linkstart{#1}{#2}#3\Hy@xspace@end\hyper@linkend
10551 }
10552 \def\hyper@linkfile#1#2#3{%
10553   \leavevmode
10554   \Hy@BeginAnnot{%
10555     \def\Hy@pstringF{#2}%
10556     \Hy@CleanupFile\Hy@pstringF
10557     \Hy@pstringdef\Hy@pstringF\Hy@pstringF
10558     \Hy@pstringdef\Hy@pstringD{#3}%
10559     \Hy@MakeRemoteAction
10560     \@pdfm@mark{%
10561       bann<<%
10562         /Type/Annot%
10563         /Subtype/Link%
10564         \ifHy@pdfa /F 4\fi
10565         \Hy@setpdfborder
10566         \ifx\@filebordercolor\relax
10567           \else
10568             /C[\@filebordercolor]%
10569           \fi
10570         /A<<%
10571         /S/GoToR%
10572         /F(\Hy@pstringF)%
10573         /D%
10574         \ifx\#3\%
10575           [\Hy@href@page\@pdfremotestartview]%
10576         \else
10577           (\Hy@pstringD)%
10578         \fi
10579         \Hy@SetNewWindow
10580         \Hy@href@nextactionraw
10581       >>%
10582       >>%
10583     }%
10584     \Hy@colorlink\@filecolor
10585   }%
10586   #1\Hy@xspace@end
10587   \Hy@EndAnnot
10588 }
10589 \def\@hyper@launch run:#1\#2#3{% filename, anchor text linkname
10590   \leavevmode
10591   \Hy@BeginAnnot{%
10592     \Hy@pstringdef\Hy@pstringF{#1}%
10593     \Hy@pstringdef\Hy@pstringP{#3}%
10594     \@pdfm@mark{%
10595       bann<<%
10596         /Type/Annot%
10597         /Subtype/Link%
10598         \ifHy@pdfa /F 4\fi

```

```

10599 \Hy@setpdfborder
10600 \ifx\@runbordercolor\relax
10601 \else
10602 /C[\@runbordercolor]%
10603 \fi
10604 /A<<%
10605 /F(\Hy@pstringF)%
10606 /S/Launch%
10607 \Hy@SetNewWindow
10608 \ifx\#3\%
10609 \else
10610 /Win<</P(\Hy@pstringP)/F(\Hy@pstringF)>>%
10611 \fi
10612 \Hy@href@nextactionraw
10613 >>%
10614 >>%
10615 }%
10616 \Hy@colorlink\@runcolor
10617 }%
10618 #2\Hy@xspace@end
10619 \Hy@EndAnnot
10620 }
10621 \def\hyper@linkurl#1#2{%
10622 \leavevmode
10623 \Hy@BeginAnnot{%
10624 \Hy@pstringdef\Hy@pstringURI{#2}%
10625 \@pdfm@mark{%
10626 bann<<%
10627 /Type/Annot%
10628 /Subtype/Link%
10629 \ifHy@pdfa /F 4\fi
10630 \Hy@setpdfborder
10631 \ifx\@urlbordercolor\relax
10632 \else
10633 /C[\@urlbordercolor]%
10634 \fi
10635 /A<<%
10636 /S/URI%
10637 /URI(\Hy@pstringURI)%
10638 \ifHy@href@ismap
10639 /IsMap true%
10640 \fi
10641 \Hy@href@nextactionraw
10642 >>%
10643 >>%
10644 }%
10645 \Hy@colorlink\@urlcolor
10646 }%
10647 #1\Hy@xspace@end
10648 \Hy@EndAnnot
10649 }
10650 \def\Acrobatmenu#1#2{%
10651 \Hy@Acrobatmenu{#1}{#2}{%
10652 \Hy@BeginAnnot{%
10653 \EdefEscapeName\Hy@temp@menu{#1}%
10654 \@pdfm@mark{%
10655 bann<<%

```

```

10656      /Type/Annot%
10657      /Subtype/Link%
10658      \ifHy@pdfa /F 4\fi
10659      \Hy@setpdfborder
10660      \ifx\@menubordercolor\relax
10661      \else
10662      /C[\@menubordercolor]%
10663      \fi
10664      /A<<%
10665      /S/Named%
10666      /N/\Hy@temp@menu
10667      \Hy@href@nextactionraw
10668      >>%
10669      >>%
10670      }%
10671      \Hy@colorlink\@menucolor
10672      }%
10673      #2\Hy@xspace@end
10674      \Hy@endAnnot
10675      }%
10676    }
10677    \ifx\@pdfproducer\relax
10678    \def\@pdfproducer{dvipdfm}%

```

Detect XeTeX. However, but xdvipdfmx will overwrite it in the final PDF file.

```

10679    \begingroup\expandafter\expandafter\expandafter\endgroup
10680    \expandafter\ifx\csname XeTeXversion\endcsname\relax
10681    \else
10682    \edef\@pdfproducer{XeTeX \the\XeTeXversion\XeTeXrevision}%
10683    \fi
10684    \fi
10685    \def\PDF@FinishDoc{%
10686    \Hy@UseMaketitleInfos
10687    \HyInfo@GenerateAddons
10688    \@pdfm@mark{%
10689    docinfo<<%
10690    /Title(\@pdftitle)%
10691    /Subject(\@pdfsubject)%
10692    /Creator(\@pdfcreator)%
10693    \ifx\@pdfcreationdate\@empty
10694    \else
10695    /CreationDate(\@pdfcreationdate)%
10696    \fi
10697    \ifx\@pdfmoddate\@empty
10698    \else
10699    /ModDate(\@pdfmoddate)%
10700    \fi
10701    /Author(\@pdfauthor)%
10702    \ifx\@pdfproducer\relax
10703    \else
10704    /Producer(\@pdfproducer)%
10705    \fi
10706    /Keywords(\@pdfkeywords)%
10707    \ifx\@pdftrapped\@empty
10708    \else
10709    /Trapped/\@pdftrapped
10710    \fi
10711    \HyInfo@Addons

```

```

10712 >>%
10713 }%
10714 \Hy@DisableOption{pdfauthor}%
10715 \Hy@DisableOption{pdftitle}%
10716 \Hy@DisableOption{pdfsubject}%
10717 \Hy@DisableOption{pdfcreator}%
10718 \Hy@DisableOption{pdfcreationdate}%
10719 \Hy@DisableOption{pdfmoddate}%
10720 \Hy@DisableOption{pdfproducer}%
10721 \Hy@DisableOption{pdfkeywords}%
10722 \Hy@DisableOption{pdftrapped}%
10723 \Hy@DisableOption{pdfinfo}%
10724 }

10725 \def\PDF@SetupDoc{%
10726 \edef\Hy@temp{%
10727 \ifHy@pdftoolbar\else /HideToolbar true\fi
10728 \ifHy@pdfmenubar\else /HideMenubar true\fi
10729 \ifHy@pdfwindowui\else /HideWindowUI true\fi
10730 \ifHy@pdfwindow /FitWindow true\fi
10731 \ifHy@pdfcenterwindow /CenterWindow true\fi
10732 \ifHy@pdfdisplaydoctitle /DisplayDocTitle true\fi
10733 \Hy@UseNameKey{NonFullScreenPageMode}\@pdfnonfullscreenpagemode
10734 \Hy@UseNameKey{Direction}\@pdfdirection
10735 \Hy@UseNameKey{ViewArea}\@pdfviewarea
10736 \Hy@UseNameKey{ViewClip}\@pdfviewclip
10737 \Hy@UseNameKey{PrintArea}\@pdfprintarea
10738 \Hy@UseNameKey{PrintClip}\@pdfprintclip
10739 \Hy@UseNameKey{PrintScaling}\@pdfprintscaling
10740 \Hy@UseNameKey{Duplex}\@pdfduplex
10741 \ifx\@pdfpicktraybypdfsize\@empty
10742 \else
10743 /PickTrayByPDFSize \@pdfpicktraybypdfsize
10744 \fi
10745 \ifx\@pdfprintpagerange\@empty
10746 \else
10747 /PrintPageRange[\@pdfprintpagerange]%
10748 \fi
10749 \ifx\@pdfnumcopies\@empty
10750 \else
10751 /NumCopies \@pdfnumcopies
10752 \fi
10753 }%
10754 \Hy@pstringdef\Hy@pstringB{\@baseurl}%
10755 \@pdfm@mark{%
10756 docview<<%
10757 \ifx\@pdfstartpage\@empty
10758 \else
10759 \ifx\@pdfstartview\@empty
10760 \else
10761 /OpenAction[@page\@pdfstartpage\@pdfstartview]%
10762 \fi
10763 \fi
10764 \ifx\@baseurl\@empty
10765 \else
10766 /URI<</Base(\Hy@pstringB)>>%
10767 \fi
10768 /PageMode/\@pdfpagemode

```

```

10769 \ifx\Hy@temp\@empty
10770 \else
10771 /ViewerPreferences<<\Hy@temp>>%
10772 \fi
10773 \Hy@UseNameKey{PageLayout}\@pdfpagelayout
10774 \ifx\@pdflang\@empty
10775 \else
10776 /Lang(\@pdflang)%
10777 \fi
10778 >>%
10779 }%
10780 \ifx\@pdfpagescrop\@empty
10781 \else
10782 \@pdfm@mark{put @pages <</CropBox[\@pdfpagescrop]>>}%
10783 \fi
10784 }
10785 </dvipdfm | xetex>
10786 <*dvipdfm | xetex>

```

\hyper@pagetransition

```

10787 \def\hyper@pagetransition{%
10788 \ifx\@pdfpagetransition\relax
10789 \else
10790 \ifx\@pdfpagetransition\@empty
10791 \else
10792 \special{pdf:put @thispage %
10793 <</Trans<</S/\@pdfpagetransition>>>>%
10794 }%
10795 \fi
10796 \fi
10797 }

```

\hyper@pageduration

```

10798 \def\hyper@pageduration{%
10799 \ifx\@pdfpageduration\relax
10800 \else
10801 \ifx\@pdfpageduration\@empty
10802 \else
10803 \special{pdf:put @thispage %
10804 <</Dur \@pdfpageduration>>>>%
10805 }%
10806 \fi
10807 \fi
10808 }

```

\hyper@pagehidden

```

10809 \def\hyper@pagehidden{%
10810 \ifHy@useHidKey
10811 \special{pdf:put @thispage %
10812 <</Hid \ifHy@pdfpagehidden true\else false\fi>>>>%
10813 }%
10814 \fi
10815 }

10816 \g@addto@macro\Hy@EveryPageBoxHook{%
10817 \hyper@pagetransition
10818 \hyper@pageduration

```

```

10819 \hyper@pagehidden
10820 }
10821 </dvipdfm | xetex>

```

XeTeX uses pdfTeX's method `\pdfpagewidth` and `\pdfpageheight` for setting the paper size.

```

10822 <*dvipdfm>
10823 \AtBeginShipoutFirst{%
10824   \ifHy@setpagesize
10825     \begingroup
10826       \@ifundefined{stockwidth}{%
10827         \ifdim\paperwidth>\z@
10828           \ifdim\paperheight>\z@
10829             \special{papersize=\the\paperwidth,\the\paperheight}%
10830           \fi
10831         \fi
10832       }{%
10833         \ifdim\stockwidth>\z@
10834           \ifdim\stockheight>\z@
10835             \special{papersize=\the\stockwidth,\the\stockheight}%
10836           \fi
10837         \fi
10838       }%
10839     \endgroup
10840   \fi
10841   \Hy@DisableOption{setpagesize}%
10842 }
10843 </dvipdfm>

```

47.6 VTeX typesetting system

Provided by MicroPress, May 1998. They require VTeX version 6.02 or newer; see <http://www.micropress-inc.com/> for details.

```

10844 <*vtexhtml>
10845 \providecommand*{\XR@ext}{htm}
10846 \RequirePackage{vtexhtml}
10847 \newif\if@Localurl
10848 \let\PDF@FinishDoc\ltx@empty
10849 \def\PDF@SetupDoc{%
10850   \ifx\@baseurl\@empty
10851     \else
10852       \special{!direct <base href="\@baseurl">}%
10853     \fi
10854 }
10855 \def\@urltype{url}
10856 \def\hyper@link#1#2#3{%
10857   \Hy@VerboseLinkStart{#1}{#2}%
10858   \leavevmode
10859   \special{!direct <a href=%
10860     \hyper@quote\hyper@hash\HyperDestNameFilter{#2}\hyper@quote>}%
10861   #3\Hy@xspace@end
10862   \special{!direct </a>}%
10863 }
10864 \def\hyper@linkurl#1#2{%
10865   \begingroup
10866     \hyper@chars
10867     \leavevmode

```

```

10868 \MathBSuppress=1\relax
10869 \special{!direct <a href=%
10870 \hyper@quote\HyperDestNameFilter{#2}\hyper@quote>}}%
10871 #1\Hy@xspace@end
10872 \MathBSuppress=0\relax
10873 \special{!direct </a>}}%
10874 \endgroup
10875 }
10876 \def\hyper@linkfile#1#2#3{%
10877 \hyper@linkurl{#1}{\Hy@linkfileprefix#2\ifx\\#3\\else\##3\fi}%
10878 }
10879 \def\hyper@linkstart#1#2{%
10880 \Hy@VerboseLinkStart{#1}{#2}%
10881 \def\Hy@tempa{#1}\ifx\Hy@tempa\@urlltype
10882 \@Localurltrue
10883 \special{!direct <a href=\hyper@quote#2\hyper@quote>}}%
10884 \else
10885 \@Localurlfalse
10886 \begingroup
10887 \hyper@chars
10888 \special{!aref \HyperDestNameFilter{#2}}}%
10889 \endgroup
10890 \fi
10891 }
10892 \def\hyper@linkend{%
10893 \if@Localurl
10894 \special{!endaref}}%
10895 \else
10896 \special{!direct </a>}}%
10897 \fi
10898 }
10899 \Hy@WrapperDef\hyper@anchorstart#1{%
10900 \Hy@SaveLastskip
10901 \Hy@VerboseAnchor{#1}%
10902 \begingroup
10903 \hyper@chars
10904 \special{!aname #1}%
10905 \special{!direct <a name=%
10906 \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}}%
10907 \endgroup
10908 \Hy@activeanchortrue
10909 }
10910 \def\hyper@anchorend{%
10911 \special{!direct </a>}}%
10912 \Hy@activeanchorfalse
10913 \Hy@RestoreLastskip
10914 }
10915 \Hy@WrapperDef\hyper@anchor#1{%
10916 \Hy@SaveLastskip
10917 \Hy@VerboseAnchor{#1}%
10918 \begingroup
10919 \let\protect=\string
10920 \hyper@chars
10921 \leavevmode
10922 \special{!aname #1}%
10923 \special{!direct <a name=%
10924 \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}}%

```

```

10925 \endgroup
10926 \Hy@activeanchortrue
10927 \bgroup\anchor@spot\egroup
10928 \special{!direct </a>}%
10929 \Hy@activeanchorfalse
10930 \Hy@RestoreLastskip
10931 }
10932 \def\@Form[#1]{%
10933 \Hy@Message{Sorry, TeXpider does not yet support FORMs}%
10934 }
10935 \let\@endForm\ltx@empty
10936 \def\@Gauge[#1]#2#3#4{% parameters, label, minimum, maximum
10937 \Hy@Message{Sorry, TeXpider does not yet support FORM gauges}%
10938 }
10939 \def\@TextField[#1]#2{% parameters, label
10940 \Hy@Message{Sorry, TeXpider does not yet support FORM text fields}%
10941 }
10942 \def\@CheckBox[#1]#2{% parameters, label
10943 \Hy@Message{Sorry, TeXpider does not yet support FORM checkboxes}%
10944 }
10945 \def\@ChoiceMenu[#1]#2#3{% parameters, label, choices
10946 \Hy@Message{Sorry, TeXpider does not yet support FORM choice menus}%
10947 }
10948 \def\@PushButton[#1]#2{% parameters, label
10949 \Hy@Message{Sorry, TeXpider does not yet support FORM pushbuttons}%
10950 }
10951 \def\@Reset[#1]#2{%
10952 \Hy@Message{Sorry, TeXpider does not yet support FORMs}%
10953 }
10954 \def\@Submit[#1]#2{%
10955 \Hy@Message{Sorry, TeXpider does not yet support FORMs}%
10956 }
10957 </vtexhtml>
10958 <*\vtex>

```

VTeX version 6.68 supports `\mediawidth` and `\mediaheight`. The `\ifx` construct is better than a `\csname`, because it avoids the definition and the hash table entry of a previous undefined macro.

```

10959 \ifx\mediaheight\@undefined
10960 \else
10961 \ifx\mediaheight\relax
10962 \else
10963 \ifHy@setpagesize
10964 \providecommand*\VTeXInitMediaSize{%
10965 \ltx@ifundefined{stockwidth}{%
10966 \ifdim\paperheight>0pt %
10967 \setlength\mediaheight\paperheight
10968 \fi
10969 \ifdim\paperheight>0pt %
10970 \setlength\mediawidth\paperwidth
10971 \fi
10972 }{%
10973 \ifdim\stockheight>0pt %
10974 \setlength\mediaheight\stockheight
10975 \fi
10976 \ifdim\stockwidth>0pt %
10977 \setlength\mediawidth\stockwidth

```



```

10978         \fi
10979     }%
10980 }%
10981 \Hy@AtBeginDocument{\VTeXInitMediaSize}%
10982 \fi
10983 \Hy@DisableOption{setpagesize}%
10984 \fi
10985 \fi

```

Older versions of VTeX require xyz in lower case.

```

10986 \providecommand*\@pdfview{xyz}
10987 \providecommand*\@pdfborder{0 0 1}
10988 \providecommand*\@pdfborderstyle{}
10989 \let\CurrentBorderColor\@linkbordercolor
10990 \Hy@WrapperDef\hyper@anchor#1{%
10991     \Hy@SaveLastskip
10992     \Hy@VerboseAnchor{#1}%
10993     \begingroup
10994         \let\protect=\string
10995         \hyper@chars
10996         \special{!aname \HyperDestNameFilter{#1};\@pdfview}%
10997     \endgroup
10998     \Hy@activeanchortrue
10999     \Hy@colorlink\@anchorcolor\anchor@spot\Hy@endcolorlink
11000     \Hy@activeanchorfalse
11001     \Hy@RestoreLastskip
11002 }
11003 \Hy@WrapperDef\hyper@anchorstart#1{%
11004     \Hy@SaveLastskip
11005     \Hy@VerboseAnchor{#1}%
11006     \begingroup
11007         \hyper@chars
11008         \special{!aname \HyperDestNameFilter{#1};\@pdfview}%
11009     \endgroup
11010     \Hy@activeanchortrue
11011 }
11012 \def\hyper@anchorend{%
11013     \Hy@activeanchorfalse
11014     \Hy@RestoreLastskip
11015 }
11016 \def\@urltype{url}
11017 \def\Hy@undefinedname{UNDEFINED}
11018 \def\hyper@linkstart#1#2{%
11019     \Hy@VerboseLinkStart{#1}{#2}%
11020     \Hy@pstringdef\Hy@pstringURI{#2}%
11021     \expandafter\Hy@colorlink\csname @#1color\endcsname
11022     \ltx@ifundefined{@#1bordercolor}{%
11023         \let\CurrentBorderColor\relax
11024     }{%
11025         \edef\CurrentBorderColor{%
11026             \csname @#1bordercolor\endcsname
11027         }%
11028     }%
11029     \def\Hy@tempa{#1}%
11030     \ifx\Hy@tempa\@urltype
11031         \special{!%
11032             aref <u=/Type/Action/S/URI/URI(\Hy@pstringURI)%
11033             \ifHy@href@ismap

```

```

11034      /IsMap true%
11035      \fi
11036      \Hy@href@nextactionraw
11037      >;%
11038      a=<%
11039      \ifHy@pdfa /F 4\fi
11040      \Hy@setpdfborder
11041      \ifx\CurrentBorderColor\relax
11042      \else
11043      /C [\CurrentBorderColor]%
11044      \fi
11045      >%
11046      }%
11047  \else
11048  \protected@edef\Hy@testname{#2}%
11049  \ifx\Hy@testname\@empty
11050  \Hy@Warning{%
11051    Empty destination name,\MessageBreak
11052    using '\Hy@undefinedname'%
11053  }%
11054  \let\Hy@testname\Hy@undefinedname
11055  \fi
11056  \special{!%
11057    aref \expandafter\HyperDestNameFilter
11058    \expandafter{\Hy@testname};%
11059    a=<%
11060    \ifHy@pdfa /F 4\fi
11061    \Hy@setpdfborder
11062    \ifx\CurrentBorderColor\relax
11063    \else
11064    /C [\CurrentBorderColor]%
11065    \fi
11066    >%
11067    }%
11068  \fi
11069 }
11070 \def\hyper@linkend{%
11071   \special{!endaref}%
11072   \Hy@endcolorlink
11073 }
11074 \def\hyper@linkfile#1#2#3{%
11075   \leavevmode
11076   \def\Hy@pstringF{#2}%
11077   \Hy@CleanupFile\Hy@pstringF
11078   \special{!%
11079     aref <%
11080     \ifnum\Hy@VTeXversion>753 \ifHy@pdfnewwindow n\fi\fi
11081     f=\Hy@pstringF>#3;%
11082     a=<%
11083     \ifHy@pdfa /F 4\fi
11084     \Hy@setpdfborder
11085     \ifx\@filebordercolor\relax
11086     \else
11087     /C [\@filebordercolor]%
11088     \fi
11089     >%
11090     }%

```

```

11091 \Hy@colorlink\@filecolor
11092 #1\Hy@xspace@end
11093 \Hy@endcolorlink
11094 \special{!endaref}%
11095 }
11096 \def\hyper@linkurl#1#2{%
11097 \begingroup
11098 \Hy@pstringdef\Hy@pstringURI{#2}%
11099 \hyper@chars
11100 \leavevmode
11101 \special{!%
11102   aref <u=/Type/Action/S/URI/URI(\Hy@pstringURI)%
11103   \ifHy@href@ismap
11104     /IsMap true%
11105   \fi
11106   \Hy@href@nextactionraw
11107   >,%
11108   a=<%
11109   \ifHy@pdfa /F 4\fi
11110   \Hy@setpdfborder
11111   \ifx\@urlbordercolor\relax
11112   \else
11113     /C [\@urlbordercolor]%
11114   \fi
11115   >%
11116 }%
11117 \Hy@colorlink\@urlcolor
11118 #1\Hy@xspace@end
11119 \Hy@endcolorlink
11120 \special{!endaref}%
11121 \endgroup
11122 }
11123 \def\hyper@link#1#2#3{%
11124 \Hy@VerboseLinkStart{#1}{#2}%
11125 \ltx@ifundefined{@#1bordercolor}{%
11126 \let\CurrentBorderColor\relax
11127 }{%
11128 \edef\CurrentBorderColor{\csname @#1bordercolor\endcsname}%
11129 }%
11130 \leavevmode
11131 \protected@edef\Hy@testname{#2}%
11132 \ifx\Hy@testname\@empty
11133 \Hy@Warning{%
11134   Empty destination name,\MessageBreak
11135   using '\Hy@undefinedname'%
11136 }%
11137 \let\Hy@testname\Hy@undefinedname
11138 \fi
11139 \special{!%
11140   aref \expandafter\HyperDestNameFilter
11141     \expandafter{\Hy@testname};%
11142   a=<%
11143   \ifHy@pdfa /F 4\fi
11144   \Hy@setpdfborder
11145   \ifx\CurrentBorderColor\relax
11146   \else
11147     /C [\CurrentBorderColor]%

```

```

11148 \fi
11149 >%
11150 }%
11151 \expandafter
11152 \Hy@colorlink\csname @#1color\endcsname
11153 #3\Hy@xspace@end
11154 \Hy@endcolorlink
11155 \special{!endaref}%
11156 }
11157 \def\hyper@image#1#2{%
11158 \hyper@linkurl{#2}{#1}%
11159 }
11160 \def\@hyper@launch run:#1\#2#3{%
11161 \Hy@pstringdef\Hy@pstringF{#1}%
11162 \Hy@pstringdef\Hy@pstringP{#3}%
11163 \leavevmode
11164 \special{!aref %
11165 <u=%
11166 /Type/Action%
11167 /S/Launch%
11168 /F(\Hy@pstringF)%
11169 \Hy@SetNewWindow
11170 \ifx\#3\%
11171 \else
11172 /Win<</F(\Hy@pstringF)/P(\Hy@pstringP)>>%
11173 \fi
11174 \Hy@href@nextactionraw
11175 >,%
11176 a=<%
11177 \ifHy@pdfa /F 4\fi
11178 \Hy@setpdfborder
11179 \ifx\@runbordercolor\relax
11180 \else
11181 /C[\@runbordercolor]%
11182 \fi
11183 >%
11184 }%
11185 \Hy@colorlink\@runcolor
11186 #2\Hy@xspace@end
11187 \Hy@endcolorlink
11188 \special{!endaref}%
11189 }
11190 \def\Acrobatmenu#1#2{%
11191 \EdefEscapeName\Hy@temp@menu{#1}%
11192 \Hy@Acrobatmenu{#1}{#2}{%
11193 \special{!%
11194 aref <u=/S /Named /N /\Hy@temp@menu>;%
11195 a=<%
11196 \ifHy@pdfa /F 4\fi
11197 \Hy@setpdfborder
11198 \ifx\@menubordercolor\relax
11199 \else
11200 /C[\@menubordercolor]%
11201 \fi
11202 >%
11203 }%
11204 \Hy@colorlink\@menucolor

```

```

11205    #2\Hy@xspace@end
11206    \Hy@endcolorlink
11207    \special{!endaref}%
11208  }%
11209 }

```

The following code (transition effects) is made by Alex Kostin.
The code below makes sense for V_T_EX 7.02 or later.
Please never use `\@ifundefined{VTeXversion}{..}{..}` *globally*.

```

11210 \ifnum\Hy@VTeXversion<702 %
11211 \else
11212   \def\hyper@pagetransition{%
11213     \ifx\@pdfpagetransition\relax
11214     \else
11215     \ifx\@pdfpagetransition\@empty

```

Standard incantation.

1. Does an old entry have to be deleted? 2. If 1=yes, how to delete?

```

11216   \else
11217     \hvtex@parse@trans\@pdfpagetransition
11218   \fi
11219 \fi
11220 }%

```

I have to write an “honest” parser to convert raw PDF code into V_T_EX
`\special`. (AVK)

Syntax of V_T_EX `\special{!trans <transition_effect>}`:

```

<transition_effect> ::= <transition_style>[,<transition_duration>]
<transition_style> ::= <Blinds_effect> | <Box_effect> |
                      <Dissolve_effect> | <Glitter_effect> |
                      <Split_effect> | <Wipe_effect>
<Blinds_effect> ::= B[<effect_dimension>]
<Box_effect> ::= X[<effect_motion>]
<Dissolve_effect> ::= D
<Glitter_effect> ::= G[<effect_direction>]
<Split_effect> ::= S[<effect_motion>][<effect_dimension>]
<Wipe_effect> ::= W[<effect_direction>]
<Replace_effect> ::= R
<effect_direction> ::= <number>
<effect_dimension> ::= H | V
<effect_motion> ::= I | O
<transition_duration> ::= <number>

```

Transition codes:

```

11221 \def\hvtex@trans@effect@Blinds{\def\hvtex@trans@code{B}}%
11222 \def\hvtex@trans@effect@Box{\def\hvtex@trans@code{X}}%
11223 \def\hvtex@trans@effect@Dissolve{\def\hvtex@trans@code{D}}%
11224 \def\hvtex@trans@effect@Glitter{\def\hvtex@trans@code{G}}%
11225 \def\hvtex@trans@effect@Split{\def\hvtex@trans@code{S}}%
11226 \def\hvtex@trans@effect@Wipe{\def\hvtex@trans@code{W}}%
11227 \def\hvtex@trans@effect@R{\def\hvtex@trans@code{R}}%

```

Optional parameters:

```

11228 \def\hvtex@par@dimension{/Dm}%
11229 \def\hvtex@par@direction{/Di}%
11230 \def\hvtex@par@duration{/D}%
11231 \def\hvtex@par@motion{/M}%

```

Tokenizer:

```
11232 \def\hvtex@gettoken{%
11233 \expandafter\hvtex@gettoken@\hvtex@buffer\@nil
11234 }%
```

Notice that tokens in the input buffer must be space delimited.

```
11235 \def\hvtex@gettoken@#1 #2\@nil{%
11236 \edef\hvtex@token{#1}%
11237 \edef\hvtex@buffer{#2}%
11238 }%
11239 \def\hvtex@parse@trans#1{%
```

Initializing code:

```
11240 \let\hvtex@trans@code\@empty
11241 \let\hvtex@param@dimension\@empty
11242 \let\hvtex@param@direction\@empty
11243 \let\hvtex@param@duration\@empty
11244 \let\hvtex@param@motion\@empty
11245 \edef\hvtex@buffer{#1\space}%
```

First token is the PDF transition name without escape.

```
11246 \hvtex@gettoken
11247 \ifx\hvtex@token\@empty
```

Leading space(s)?

```
11248 \ifx\hvtex@buffer\@empty
```

The buffer is empty, nothing to do.

```
11249 \else
11250 \hvtex@gettoken
11251 \fi
11252 \fi
11253 \csname hvtex@trans@effect@\hvtex@token\endcsname
```

Now is time to parse optional parameters.

```
11254 \hvtex@trans@params
11255 }%
```

Reentrant macro to parse optional parameters.

```
11256 \def\hvtex@trans@params{%
11257 \ifx\hvtex@buffer\@empty
11258 \else
11259 \hvtex@gettoken
11260 \let\hvtex@trans@par\hvtex@token
11261 \ifx\hvtex@buffer\@empty
11262 \else
11263 \hvtex@gettoken
11264 \ifx\hvtex@trans@par\hvtex@par@duration
```

/D is the effect duration in seconds. V_{TEX} special takes it in milliseconds.

```
11265 \let\hvtex@param@duration\hvtex@token
11266 \else \ifx\hvtex@trans@par\hvtex@par@motion
```

/M can be either /I or /O

```
11267 \expandafter\edef\expandafter\hvtex@param@motion
11268 \expandafter{\expandafter\@gobble\hvtex@token}%
11269 \else \ifx\hvtex@trans@par\hvtex@par@dimension
```

/Dm can be either /H or /V

```
11270 \expandafter\edef\expandafter\hvtex@param@dimension
11271 \expandafter{\expandafter\@gobble\hvtex@token}%
11272 \else \ifx\hvtex@trans@par\hvtex@par@direction
```

Valid values for /Di are 0, 270, 315 (the Glitter effect) or 0, 90, 180, 270 (the Wipe effect).

```

11273      \let\hvtex@param@direction\hvtex@token
11274      \fi\fi\fi\fi
11275      \fi
11276      \fi
11277      \ifx\hvtex@buffer\@empty
11278      \let\next\hvtex@produce@trans
11279      \else
11280      \let\next\hvtex@trans@params
11281      \fi
11282      \next
11283  }%

```

Merge <transition_effect> and issue the special when possible. Too lazy to validate optional parameters.

```

11284  \def\hvtex@produce@trans{%
11285  \let\vtex@trans@special\@empty
11286  \if S\hvtex@trans@code
11287  \edef\vtex@trans@special{\hvtex@trans@code
11288  \hvtex@param@dimension\hvtex@param@motion}%
11289  \else\if B\hvtex@trans@code
11290  \edef\vtex@trans@special{%
11291  \hvtex@trans@code\hvtex@param@dimension
11292  }%
11293  \else\if X\hvtex@trans@code
11294  \edef\vtex@trans@special{%
11295  \hvtex@trans@code\hvtex@param@motion
11296  }%
11297  \else\if W\hvtex@trans@code
11298  \edef\vtex@trans@special{%
11299  \hvtex@trans@code\hvtex@param@direction
11300  }%
11301  \else\if D\hvtex@trans@code
11302  \let\vtex@trans@special\hvtex@trans@code
11303  \else\if R\hvtex@trans@code
11304  \let\vtex@trans@special\hvtex@trans@code
11305  \else\if G\hvtex@trans@code
11306  \edef\vtex@trans@special{%
11307  \hvtex@trans@code\hvtex@param@direction
11308  }%
11309  \fi\fi\fi\fi\fi\fi
11310  \ifx\vtex@trans@special\@empty
11311  \else
11312  \ifx\hvtex@param@duration\@empty
11313  \else
11314  \setlength{\dimen@}{\hvtex@param@duration\p}%

```

I'm not guilty of possible overflow.

```

11315  \multiply\dimen@\@m
11316  \edef\vtex@trans@special{%
11317  \vtex@trans@special,\strip@pt\dimen@
11318  }%
11319  \fi

```

And all the mess is just for this.

```

11320  \special{!trans \vtex@trans@special}%
11321  \fi

```

```

11322 }%
11323 \def\hyper@pageduration{%
11324 \ifx\@pdfpageduration\relax
11325 \else
11326 \ifx\@pdfpageduration\@empty
11327 \special{!duration-}%
11328 \else
11329 \special{!duration \@pdfpageduration}%
11330 \fi
11331 \fi
11332 }%
11333 \def\hyper@pagehidden{%
11334 \ifHy@useHidKey
11335 \special{!hidden\ifHy@pdfpagehidden +\else -\fi}%
11336 \fi
11337 }%
11338 \g@addto@macro\Hy@EveryPageBoxHook{%
11339 \hyper@pagetransition
11340 \hyper@pageduration
11341 \hyper@pagehidden
11342 }%
11343 \fi

```

Caution: In opposite to the other drivers, the argument of `\special{!onopen #1}` is a reference name. The VTeX's postscript mode will work with a version higher than 7.0x.

The command `\VTeXOS` is defined since version 7.45. Magic values encode the operating system:

- 1: WinTel
- 2: Linux
- 3: OS/2
- 4: MacOS
- 5: MacOS/X

```

11344 \ifx\@pdfproducer\relax
11345 \def\@pdfproducer{VTeX}%
11346 \ifnum\Hy@VTeXversion>\z@
11347 \count@\VTeXversion
11348 \divide\count@ 100 %
11349 \edef\@pdfproducer{\@pdfproducer\space v\the\count@}%
11350 \multiply\count@ -100 %
11351 \advance\count@\VTeXversion
11352 \edef\@pdfproducer{%
11353 \@pdfproducer
11354 .\ifnum\count@<10 0\fi\the\count@
11355 \ifx\VTeXOS\@undefined\else
11356 \ifnum\VTeXOS>0 %
11357 \ifnum\VTeXOS<6 %
11358 \space%
11359 \ifcase\VTeXOS
11360 \or Windows\or Linux\or OS/2\or MacOS\or MacOS/X%
11361 \fi
11362 )%
11363 \fi
11364 \fi
11365 \fi
11366 ,\space
11367 \ifnum\OpMode=\@ne PDF\else PS\fi

```



```

11368 \space backend%
11369 \ifx\gexmode\@undefined\else
11370 \ifnum\gexmode>\z@\space with GeX\fi
11371 \fi
11372 }%
11373 \fi
11374 \fi

```

Current `!pdfinfo` key syntax:

Key	Field	Type
a	A uthor	String
b	C rop B ox	String
c	C reator	String
k	K eywords	String
l	P age L ayout	PS
p	P age M ode	PS
r	P roducer	String
s	S ubject	String
t	T itle	String
u	U RI	PS
v	V iew P references	PS

Note: PS objects that are dicts are in `<<...>>` (yuck; no choice).

```

11375 \def\PDF@SetupDoc{%
11376 \ifx\@pdfpagescrop\@empty
11377 \else
11378 \special{!pdfinfo b=<\@pdfpagescrop>}%
11379 \fi
11380 \ifx\@pdfstartpage\@empty
11381 \else
11382 \ifx\@pdfstartview\@empty
11383 \else
11384 \special{!onopen Page\@pdfstartpage}%
11385 \fi
11386 \fi
11387 \special{!pdfinfo p=</\@pdfpagemode>}%
11388 \ifx\@baseurl\@empty
11389 \else
11390 \special{!pdfinfo u=<<</Base (\@baseurl)>>>}%
11391 \fi
11392 \special{!pdfinfo v=<<<%
11393 \ifHy@pdftoolbar\else /HideToolbar true\fi
11394 \ifHy@pdfmenubar\else /HideMenubar true\fi
11395 \ifHy@pdfwindowui\else /HideWindowUI true\fi
11396 \ifHy@pdffitwindow /FitWindow true\fi
11397 \ifHy@pdfcenterwindow /CenterWindow true\fi
11398 \ifHy@pdfdisplaydoctitle /DisplayDocTitle true\fi
11399 \Hy@UseNameKey{NonFullScreenPageMode}\@pdfnonfullscreenpagemode
11400 \Hy@UseNameKey{Direction}\@pdfdirection
11401 \Hy@UseNameKey{ViewArea}\@pdfviewarea
11402 \Hy@UseNameKey{ViewClip}\@pdfviewclip
11403 \Hy@UseNameKey{PrintArea}\@pdfprintarea
11404 \Hy@UseNameKey{PrintClip}\@pdfprintclip
11405 \Hy@UseNameKey{PrintScaling}\@pdfprintscaling
11406 \Hy@UseNameKey{Duplex}\@pdfduplex
11407 \ifx\@pdfpicktraybypdfsize\@empty
11408 \else
11409 /PickTrayByPDFSize \@pdfpicktraybypdfsize

```

```

11410 \fi
11411 \ifx\@pdfprintpagerange\@empty
11412 \else
11413 /PrintPageRange[\@pdfprintpagerange]%
11414 \fi
11415 \ifx\@pdfnumcopies\@empty
11416 \else
11417 /NumCopies \@pdfnumcopies
11418 \fi
11419 >>>}%
11420 \ifx\@pdfpagelayout\@empty
11421 \else
11422 \special{!pdfinfo l=</\@pdfpagelayout\space>}%
11423 \fi
11424 }%
11425 \HyInfo@AddonUnsupportedtrue
11426 \define@key{Hyp}{pdfcreationdate}{%
11427 \Hy@Warning{%
11428 VTeX does not support pdfcreationdate.\MessageBreak
11429 Therefore its setting is ignored%
11430 }%
11431 }
11432 \define@key{Hyp}{pdfmoddate}{%
11433 \Hy@Warning{%
11434 VTeX does not support pdfmoddate.\MessageBreak
11435 Therefore its setting is ignored%
11436 }%
11437 }
11438 \def\PDF@FinishDoc{%
11439 \Hy@UseMaketitleInfos
11440 \HyInfo@TrappedUnsupported
11441 \special{!pdfinfo a=<\@pdfauthor>}%
11442 \special{!pdfinfo t=<\@pdftitle>}%
11443 \special{!pdfinfo s=<\@pdfsubject>}%
11444 \special{!pdfinfo c=<\@pdfcreator>}%
11445 \ifx\@pdfproducer\relax
11446 \else
11447 \special{!pdfinfo r=<\@pdfproducer>}%
11448 \fi
11449 \special{!pdfinfo k=<\@pdfkeywords>}%
11450 \Hy@DisableOption{pdfauthor}%
11451 \Hy@DisableOption{pdftitle}%
11452 \Hy@DisableOption{pdfsubject}%
11453 \Hy@DisableOption{pdfcreator}%
11454 \Hy@DisableOption{pdfcreationdate}%
11455 \Hy@DisableOption{pdfmoddate}%
11456 \Hy@DisableOption{pdfproducer}%
11457 \Hy@DisableOption{pdfkeywords}%
11458 \Hy@DisableOption{pdftrapped}%
11459 \Hy@DisableOption{pdfinfo}%
11460 }
11461 </vtex>

```

47.7 Fix for Adobe bug number 466320

If a destination occurs at the very begin of a page, the destination is moved to the previous page by Adobe Distiller 5. As workaround Adobe suggests:

```

/showpage {
  //showpage
  clippath stroke erasepage
} bind def

```

But unfortunately this fix generates an empty page at the end of the document. Therefore another fix is used by writing some clipped text.

```

11462 <dviwindo>\def\literalps@out#1{\special{ps:#1}}%
11463 <package>\providecommand*\Hy@DistillerDestFix{}
11464 <*pdfmark | dviwindo>
11465 \def\Hy@DistillerDestFix{%
11466   \begingroup
11467     \let\x\literalps@out

```

The fix has to be passed unchanged through GeX, if VTeX in PostScript mode with GeX is used.

```

11468   \ifnum \@ifundefined{OpMode}{0}{%
11469     \@ifundefined{gexmode}{0}{%
11470       \ifnum\gexmode>0 \OpMode\else 0\fi
11471     }>1 %
11472   \def\x##1{%
11473     \immediate\special{!=##1}%
11474   }%
11475   \fi
11476   \x{%
11477     /product where{%
11478       pop %
11479       product(Distiller)search{%
11480         pop pop pop %
11481         version(.)search{%
11482           exch pop exch pop%
11483           (3011)eq{%
11484             gsave %
11485             newpath 0 0 moveto closepath clip%
11486             /Courier findfont 10 scalefont setfont %
11487             72 72 moveto(.)show %
11488             grestore%
11489           }if%
11490         }{pop}ifelse%
11491       }{pop}ifelse%
11492     }if%
11493   }%
11494   \endgroup
11495 }
11496 </pdfmark | dviwindo>

```

47.8 Direct pdfmark support

Drivers that load pdfmark.def have to provide the correct macro definitions of

```

\@pdfproducer   for document information
\literalps@out  PostScript output
\headerps@out   PostScript output that goes in the header area

```

and the correct definitions of the following PostScript procedures:

H.S	start of anchor, link or rect
#1 H.A	end of anchor, argument=baselineskip in pt
#1 H.L	end of link, argument=baselineskip in pt
H.R	end of rect
H.B	raw rect code

```

11497 \*pdfmark
11498 \Hy@breaklinks@unsupported
11499 \def\HyPat@ObjRef{%
11500   \{[~{}]+\}%
11501 }
11502 \Hy@WrapperDef\hyper@anchor#1{%
11503   \Hy@SaveLastskip
11504   \Hy@VerboseAnchor{#1}%
11505   \begingroup
11506     \pdfmark[\anchor@spot]{%
11507       pdfmark=/DEST,%
11508       linktype=anchor,%
11509       View=/\@pdfview \@pdfviewparams,%
11510       DestAnchor={#1}%
11511     }%
11512   \endgroup
11513   \Hy@RestoreLastskip
11514 }
11515 \ltx@ifundefined{hyper@anchorstart}{\endinput}
11516 \Hy@WrapperDef\hyper@anchorstart#1{%
11517   \Hy@SaveLastskip
11518   \Hy@VerboseAnchor{#1}%
11519   \literalps@out{H.S}%
11520   \Hy@AllowHyphens
11521   \xdef\hyper@currentanchor{#1}%
11522   \Hy@activeanchortrue
11523 }
11524 \def\hyper@anchorend{%
11525   \literalps@out{\strip@pt@and@otherjunk\baselineskip\space H.A}%
11526   \pdfmark{%
11527     pdfmark=/DEST,%
11528     linktype=anchor,%
11529     View=/\@pdfview \@pdfviewparams,%
11530     DestAnchor=\hyper@currentanchor,%
11531   }%
11532   \Hy@activeanchorfalse
11533   \Hy@RestoreLastskip
11534 }
11535 \def\hyper@linkstart#1#2{%
11536   \Hy@VerboseLinkStart{#1}{#2}%
11537   \ifHy@breaklinks
11538   \else
11539     \leavevmode
11540     \ifmmode
11541       \def\Hy@LinkMath{$}%
11542     \else
11543       \let\Hy@LinkMath\ltx@empty
11544     \fi
11545     \Hy@SaveSpaceFactor
11546     \hbox\bgroup
11547     \Hy@RestoreSpaceFactor
11548     \Hy@LinkMath

```

```

11549 \fi
11550 \expandafter\Hy@colorlink\csname @#1color\endcsname
11551 \literalps@out{H.S}%
11552 \Hy@AllowHyphens
11553 \xdef\hyper@currentanchor{#2}%
11554 \gdef\hyper@currentlinktype{#1}%
11555 }
11556 \def\hyper@linkend{%
11557 \literalps@out{\strip@pt@and@otherjunk\baselineskip\space H.L}%
11558 \ltx@ifundefined{@\hyper@currentlinktype bordercolor}{%
11559 \let\Hy@tempcolor\relax
11560 }{%
11561 \edef\Hy@tempcolor{%
11562 \csname @\hyper@currentlinktype bordercolor\endcsname
11563 }%
11564 }%
11565 \pdfmark{%
11566 pdfmark=/ANN,%
11567 linktype=link,%
11568 Subtype=/Link,%
11569 PDFAFlags=4,%
11570 Dest=\hyper@currentanchor,%
11571 AcroHighlight=\@pdfhighlight,%
11572 Border=\@pdfborder,%
11573 BorderStyle=\@pdfborderstyle,%
11574 Color=\Hy@tempcolor,%
11575 Raw=H.B%
11576 }%
11577 \Hy@endcolorlink
11578 \ifHy@breaklinks
11579 \else
11580 \Hy@LinkMath
11581 \Hy@SaveSpaceFactor
11582 \egroup
11583 \Hy@RestoreSpaceFactor
11584 \fi
11585 }

```

We have to allow for `\baselineskip` having an optional stretch and shrink (you meet this in slide packages, for instance), so we need to strip off the junk. David Carlisle, of course, wrote this bit of code.

```

11586 \begingroup
11587 \catcode'P=12 %
11588 \catcode'T=12 %
11589 \lowercase{\endgroup
11590 \gdef\rem@ptetc#1.#2PT#3!{#1\ifnum#2>\z@.#2\fi}%
11591 }
11592 \def\strip@pt@and@otherjunk#1{\expandafter\rem@ptetc\the#1!}

```

`\hyper@pagetransition`

```

11593 \def\hyper@pagetransition{%
11594 \ifx\@pdfpagetransition\relax
11595 \else
11596 \ifx\@pdfpagetransition\@empty
11597 % 1. Does an old entry have to be deleted?
11598 % 2. If 1=yes, how to delete?
11599 \else

```

```

11600 \pdfmark{%
11601 pdfmark=/PUT,%
11602 Raw={%
11603 \string{ThisPage\string}%
11604 <</Trans << /S /\@pdfpagetransition\space >> >>%
11605 }%
11606 }%
11607 \fi
11608 \fi
11609 }

```

\hyper@pageduration

```

11610 \def\hyper@pageduration{%
11611 \ifx\@pdfpageduration\relax
11612 \else
11613 \ifx\@pdfpageduration\@empty
11614 % 1. Does an old entry have to be deleted?
11615 % 2. If 1=yes, how to delete?
11616 \else
11617 \pdfmark{%
11618 pdfmark=/PUT,%
11619 Raw={%
11620 \string{ThisPage\string}%
11621 <</Dur \@pdfpageduration>>%
11622 }%
11623 }%
11624 \fi
11625 \fi
11626 }

```

\hyper@pagehidden

```

11627 \def\hyper@pagehidden{%
11628 \ifHy@useHidKey
11629 \pdfmark{%
11630 pdfmark=/PUT,%
11631 Raw={%
11632 \string{ThisPage\string}%
11633 <</Hid \ifHy@pdfpagehidden true\else false\fi>>%
11634 }%
11635 }%
11636 \fi
11637 }

```

```

11638 \g@addto@macro\Hy@EveryPageBoxHook{%
11639 \hyper@pagetransition
11640 \hyper@pageduration
11641 \hyper@pagehidden
11642 }

```

```

11643 \def\hyper@image#1#2{%
11644 \hyper@linkurl{#2}{#1}%
11645 }
11646 \def\Hy@undefinedname{UNDEFINED}
11647 \def\hyper@link#1#2#3{%
11648 \Hy@VerboseLinkStart{#1}{#2}%
11649 \ltx@ifundefined{@#1bordercolor}{%
11650 \let\Hy@tempcolor\relax
11651 }{%

```

```

11652 \edef\Hy@tempcolor{\csname @#1bordercolor\endcsname}%
11653 }%
11654 \begingroup
11655 \protected@edef\Hy@testname{#2}%
11656 \ifx\Hy@testname\@empty
11657 \Hy@Warning{%
11658 Empty destination name,\MessageBreak
11659 using '\Hy@undefinedname'%
11660 }%
11661 \let\Hy@testname\Hy@undefinedname
11662 \fi
11663 \pdfmark[{#3}]{%
11664 Color=\Hy@tempcolor,%
11665 linktype={#1},%
11666 AcroHighlight=\@pdfhighlight,%
11667 Border=\@pdfborder,%
11668 BorderStyle=\@pdfborderstyle,%
11669 pdfmark=/ANN,%
11670 Subtype=/Link,%
11671 PDFAFlags=4,%
11672 Dest=\Hy@testname
11673 }%
11674 \endgroup
11675 }
11676 \newtoks\pdf@docset
11677 \def\PDF@FinishDoc{%
11678 \Hy@UseMaketitleInfos
11679 \Hy@Info@GenerateAddons
11680 \let\Hy@temp\@empty
11681 \ifx\@pdfcreationdate\@empty
11682 \else
11683 \def\Hy@temp{CreationDate=\@pdfcreationdate,}%
11684 \fi
11685 \ifx\@pdfmoddate\@empty
11686 \else
11687 \expandafter\def\expandafter\Hy@temp\expandafter{%
11688 \Hy@temp
11689 ModDate=\@pdfmoddate,%
11690 }%
11691 \fi
11692 \ifx\@pdfproducer\relax
11693 \else
11694 \expandafter\def\expandafter\Hy@temp\expandafter{%
11695 \Hy@temp
11696 Producer=\@pdfproducer,%
11697 }%
11698 \fi
11699 \expandafter
11700 \pdfmark\expandafter{%
11701 \Hy@temp
11702 pdfmark=/DOCINFO,%
11703 Title=\@pdftitle,%
11704 Subject=\@pdfsubject,%
11705 Creator=\@pdfcreator,%
11706 Author=\@pdfauthor,%
11707 Keywords=\@pdfkeywords,%
11708 Trapped=\@pdftrapped

```

```

11709 }%
11710 \ifx\HyInfo@Addons\@empty
11711 \else
11712 \pdfmark{%
11713 pdfmark=/DOCINFO,%
11714 Raw={\HyInfo@Addons}%
11715 }%
11716 \fi
11717 \Hy@DisableOption{pdfauthor}%
11718 \Hy@DisableOption{pdftitle}%
11719 \Hy@DisableOption{pdfsubject}%
11720 \Hy@DisableOption{pdfcreator}%
11721 \Hy@DisableOption{pdfcreationdate}%
11722 \Hy@DisableOption{pdfmoddate}%
11723 \Hy@DisableOption{pdfproducer}%
11724 \Hy@DisableOption{pdfkeywords}%
11725 \Hy@DisableOption{pdftrapped}%
11726 \Hy@DisableOption{pdfinfo}%
11727 }
11728 \def\PDF@SetupDoc{%
11729 \def\Hy@temp{}%
11730 \ifx\@pdfstartpage\@empty
11731 \else
11732 \ifx\@pdfstartview\@empty
11733 \else
11734 \edef\Hy@temp{%
11735 ,Page=\@pdfstartpage
11736 ,View=\@pdfstartview
11737 }%
11738 \fi
11739 \fi
11740 \edef\Hy@temp{%
11741 \noexpand\pdfmark{%
11742 pdfmark=/DOCVIEW,%
11743 PageMode=/\@pdfpagemode
11744 \Hy@temp
11745 }%
11746 }%
11747 \Hy@temp
11748 \ifx\@pdfpagescrop\@empty
11749 \else
11750 \pdfmark{pdfmark=/PAGES,CropBox=\@pdfpagescrop}%
11751 \fi
11752 \edef\Hy@temp{%
11753 \ifHy@pdftoolbar\else /HideToolbar true\fi
11754 \ifHy@pdfmenubar\else /HideMenubar true\fi
11755 \ifHy@pdfwindowui\else /HideWindowUI true\fi
11756 \ifHy@pdfwindow /FitWindow true\fi
11757 \ifHy@pdfcenterwindow /CenterWindow true\fi
11758 \ifHy@pdfdisplaydoctitle /DisplayDocTitle true\fi
11759 \Hy@UseNameKey{NonFullScreenPageMode}\@pdfnonfullscreenpagemode
11760 \Hy@UseNameKey{Direction}\@pdfdirection
11761 \Hy@UseNameKey{ViewArea}\@pdfviewarea
11762 \Hy@UseNameKey{ViewClip}\@pdfviewclip
11763 \Hy@UseNameKey{PrintArea}\@pdfprintarea
11764 \Hy@UseNameKey{PrintClip}\@pdfprintclip
11765 \Hy@UseNameKey{PrintScaling}\@pdfprintscaling

```



```

11766 \Hy@UseNameKey{Duplex}\@pdfduplex
11767 \ifx\@pdfpicktraybypdfsize\@empty
11768 \else
11769 /PickTrayByPDFSize \@pdfpicktraybypdfsize
11770 \fi
11771 \ifx\@pdfprintpagerange\@empty
11772 \else
11773 /PrintPageRange[\@pdfprintpagerange]%
11774 \fi
11775 \ifx\@pdfnumcopies\@empty
11776 \else
11777 /NumCopies \@pdfnumcopies
11778 \fi
11779 }%
11780 \Hy@pstringdef\Hy@pstringB{\@baseurl}%
11781 \pdfmark{%
11782 pdfmark=/PUT,%
11783 Raw={%
11784 \string{Catalog\string}<<%
11785 \ifx\Hy@temp\@empty
11786 \else
11787 /ViewerPreferences<<\Hy@temp>>%
11788 \fi
11789 \Hy@UseNameKey{PageLayout}\@pdfpagelayout
11790 \ifx\@pdflang\@empty
11791 \else
11792 /Lang(\@pdflang)%
11793 \fi
11794 \ifx\@baseurl\@empty
11795 \else
11796 /URI<</Base(\Hy@pstringB)>>%
11797 \fi
11798 >>%
11799 }%
11800 }%
11801 }
11802 </pdfmark>
11803 <*pdfmarkbase>

```

We define a single macro, pdfmark, which uses the ‘keyval’ system to define the various allowable keys; these are *exactly* as listed in the pdfmark reference for Acrobat 3.0. The only addition is pdfmark which specifies the type of pdfmark to create (like ANN, LINK etc). The surrounding round and square brackets in the pdfmark commands are supplied, but you have to put in / characters as needed for the values.

```

11804 \newif\ifHy@pdfmarkerror
11805 \def\pdfmark{\@ifnextchar{\pdfmark@}{\pdfmark@[]}}
11806 \def\pdfmark@[#1]#2{%
11807 \Hy@pdfmarkerrorfalse
11808 \edef\@processme{\noexpand\pdf@toks={\the\pdf@defaulttoks}}%
11809 \@processme
11810 \let\pdf@type\relax
11811 \kvsetkeys{PDF}{#2}%
11812 \ifHy@pdfmarkerror
11813 \else
11814 \ifx\pdf@type\relax
11815 \Hy@WarningNoLine{no pdfmark type specified in #2!!}%

```

```

11816 \ifx\|#1\|%
11817 \else
11818 \pdf@rect{#1}%
11819 \fi
11820 \else
11821 \ifx\|#1\|%
11822 \literalps@out{%
11823 [\the\pdf@toks\space\pdf@type\space pdfmark%
11824 ]%
11825 \else
11826 \ltx@ifundefined{@\pdf@linktype color}{%
11827 \Hy@colorlink\@linkcolor
11828 }{%
11829 \expandafter\Hy@colorlink
11830 \csname @\pdf@linktype color\endcsname
11831 }%
11832 \pdf@rect{#1}%
11833 \literalps@out{%
11834 [\the\pdf@toks\space\pdf@type\space pdfmark%
11835 ]%
11836 \Hy@endcolorlink
11837 \fi
11838 \fi
11839 \fi
11840 }

```

The complicated bit is working out the right enclosing rectangle of some piece of T_EX text, needed by the /Rect key. This solution originates with Toby Thain (tobyth@netspace.net.au).

For the case breaklinks is enabled, I have added two hooks, the first one for package setouterhbox, it provides a hopefully better method without setting the text twice.

```
\usepackage[hyperref]{setouterhbox}
```

With the second hook, also you can set the text twice, e.g.:

```

\long\def\Hy@setouterhbox#1#2{\long\def\my@temp{#2}}
\def\Hy@breaklinksunhbox#1{\my@temp}

```

```

11841 \newsavebox{\pdf@box}
11842 \providecommand*{\Hy@setouterhbox}{\sbox}
11843 \providecommand*{\Hy@breaklinksunhbox}{\unhbox}
11844 \def\Hy@DEST{/DEST}
11845 \def\pdf@rect#1{%
11846 \begingroup
11847 \chardef\x=1 %
11848 \def\Hy@temp{#1}%
11849 \ifx\Hy@temp\ltx@empty
11850 \chardef\x=0 %
11851 \else
11852 \def\y{\anchor@spot}%
11853 \ifx\Hy@temp\y
11854 \def\y{\relax}%
11855 \ifx\anchor@spot\y
11856 \chardef\x=0 %
11857 \fi
11858 \fi
11859 \fi

```

```

11860 \expandafter\endgroup
11861 \ifcase\x
11862   \literalps@out{H.S}%
11863   \literalps@out{H.R}%
11864 \else
11865   \leavevmode
11866   \Hy@SaveSpaceFactor
11867   \ifmmode
11868     \def\Hy@LinkMath{$}%
11869   \else
11870     \let\Hy@LinkMath\ltx@empty
11871   \fi
11872   \ifHy@breaklinks
11873     \Hy@setouterhbox\pdf@box{%
11874       \Hy@RestoreSpaceFactor
11875       \Hy@LinkMath
11876       \Hy@AllowHyphens#1\Hy@xspace@end
11877       \Hy@LinkMath
11878       \Hy@SaveSpaceFactor
11879     }%
11880   \else
11881     \sbox\pdf@box{%
11882       \Hy@RestoreSpaceFactor
11883       \Hy@LinkMath
11884       #1\Hy@xspace@end
11885       \Hy@LinkMath
11886       \Hy@SaveSpaceFactor
11887     }%
11888   \fi
11889   \dimen@ \ht\pdf@box
11890   \ifdim\dp\pdf@box=\z@
11891     \literalps@out{H.S}%
11892   \else
11893     \lower\dp\pdf@box\hbox{\literalps@out{H.S}}%
11894   \fi

```

If the text has to be horizontal mode stuff then just unbox the saved box like this, which saves executing it twice, which can mess up counters etc (thanks DPC...).

```

11895   \ifHy@breaklinks
11896     \ifhmode
11897       \Hy@breaklinksunhbox\pdf@box
11898     \else
11899       \box\pdf@box
11900     \fi
11901   \else
11902     \expandafter\box\pdf@box
11903   \fi

```

but if it can have multiple paragraphs you'd need one of these, but in that case the measured box size would be wrong anyway.

```

\ifHy@breaklinks#1\else\box\pdf@box\fi
\ifHy@breaklinks{#1}\else\box\pdf@box\fi

11904   \ifdim\dimen@=\z@
11905     \literalps@out{H.R}%
11906   \else
11907     \raise\dimen@\hbox{\literalps@out{H.R}}%
11908   \fi

```

```

11909 \Hy@RestoreSpaceFactor
11910 \fi
11911 \ifx\pdf@type\Hy@DEST
11912 \else
11913 \pdf@addtoksx{H.B}%
11914 \fi
11915 }

```

All the supplied material is stored in a token list; since I do not feel sure I quite understand these, things may not work as expected with expansion. We'll have to experiment.

```

11916 \newtoks\pdf@toks
11917 \newtoks\pdf@defaulttoks
11918 \pdf@defaulttoks={}
11919 \def\pdf@addtoks#1#2{%
11920 \edef\@processme{\pdf@toks{\the\pdf@toks/#2 #1}}%
11921 \@processme
11922 }
11923 \def\pdf@addtoksx#1{%
11924 \edef\@processme{\pdf@toks{\the\pdf@toks\space #1}}%
11925 \@processme
11926 }
11927 \def\PDFdefaults#1{%
11928 \pdf@defaulttoks={#1}%
11929 }

```

This is the list of allowed keys. See the Acrobat manual for an explanation.

```

11930 % what is the type of pdfmark?
11931 \define@key{PDF}{pdfmark}{\def\pdf@type{#1}}
11932 % what is the link type?
11933 \define@key{PDF}{linktype}{\def\pdf@linktype{#1}}
11934 \def\pdf@linktype{link}
11935 % parameter is a stream of PDF
11936 \define@key{PDF}{Raw}{\pdf@addtoksx{#1}}
11937 % parameter is a name
11938 \define@key{PDF}{Action}{\pdf@addtoks{#1}{Action}}
11939 % parameter is a array
11940 \define@key{PDF}{Border}{%
11941 \edef\Hy@temp{#1}%
11942 \ifx\Hy@temp\@empty
11943 \else
11944 \pdf@addtoks{[#1]\Hy@BorderArrayPatch}{Border}% hash-ok
11945 \fi
11946 }
11947 \let\Hy@BorderArrayPatch\@empty
11948 % parameter is a dictionary
11949 \define@key{PDF}{BorderStyle}{%
11950 \edef\Hy@temp{#1}%
11951 \ifx\Hy@temp\@empty
11952 \else
11953 \pdf@addtoks{<<#1>>}{BS}%
11954 \fi
11955 }
11956 % parameter is a array
11957 \define@key{PDF}{Color}{%
11958 \ifx\relax#1\relax
11959 \else
11960 \pdf@addtoks{[#1]}{Color}% hash-ok

```

```

11961 \fi
11962 }
11963 % parameter is a string
11964 \define@key{PDF}{Contents}{\pdf@addtoks{(#1)}{Contents}}
11965 % parameter is a integer
11966 \define@key{PDF}{Count}{\pdf@addtoks{#1}{Count}}
11967 % parameter is a array
11968 \define@key{PDF}{CropBox}{\pdf@addtoks{#1}{CropBox}}% hash-ok
11969 % parameter is a string
11970 \define@key{PDF}{DOSFile}{\pdf@addtoks{(#1)}{DOSFile}}
11971 % parameter is a string or file
11972 \define@key{PDF}{DataSource}{\pdf@addtoks{(#1)}{DataSource}}
11973 % parameter is a destination
11974 \define@key{PDF}{Dest}{%
11975   \Hy@pstringdef\Hy@pstringDest{\HyperDestNameFilter{#1}}%
11976   \ifx\Hy@pstringDest\@empty
11977     \Hy@pdfmarkerrortrue
11978     \Hy@Warning{Destination with empty name ignored}%
11979   \else
11980     \pdf@addtoks{(\Hy@pstringDest) cvn}{Dest}%
11981   \fi
11982 }
11983 \define@key{PDF}{DestAnchor}{%
11984   \Hy@pstringdef\Hy@pstringDest{\HyperDestNameFilter{#1}}%
11985   \ifx\Hy@pstringDest\@empty
11986     \Hy@pdfmarkerrortrue
11987     \Hy@Warning{Destination with empty name ignored}%
11988   \else
11989     \pdf@addtoks{(\Hy@pstringDest) cvn}{Dest}%
11990   \fi
11991 }
11992 % parameter is a string
11993 \define@key{PDF}{Dir}{\pdf@addtoks{(#1)}{Dir}}
11994 % parameter is a string
11995 \define@key{PDF}{File}{\pdf@addtoks{(#1)}{File}}
11996 % parameter is a int
11997 \define@key{PDF}{Flags}{\pdf@addtoks{#1}{Flags}}
11998 \define@key{PDF}{PDFAFlags}{%
11999   \ifHy@pdfa
12000     \pdf@addtoks{#1}{F}%
12001   \fi
12002 }
12003 % parameter is a name
12004 \define@key{PDF}{AcroHighlight}{%
12005   \begingroup
12006     \edef\x{#1}%
12007     \expandafter\endgroup\ifx\x\@empty
12008     \else
12009       \pdf@addtoks{#1}{H}%
12010     \fi
12011 }
12012 % parameter is a string
12013 \define@key{PDF}{ID}{\pdf@addtoks{[#1]}{ID}}% hash-ok
12014 % parameter is a string
12015 \define@key{PDF}{MacFile}{\pdf@addtoks{(#1)}{MacFile}}
12016 % parameter is a string
12017 \define@key{PDF}{ModDate}{\pdf@addtoks{(#1)}{ModDate}}

```

```

12018 % parameter is a string
12019 \define@key{PDF}{Op}{\pdf@addtoks{(#1)}{Op}}
12020 % parameter is a Boolean
12021 \define@key{PDF}{Open}{\pdf@addtoks{#1}{Open}}
12022 % parameter is a integer or name
12023 \define@key{PDF}{Page}{\pdf@addtoks{#1}{Page}}
12024 % parameter is a name
12025 \define@key{PDF}{PageMode}{\pdf@addtoks{#1}{PageMode}}
12026 % parameter is a string
12027 \define@key{PDF}{Params}{\pdf@addtoks{(#1)}{Params}}
12028 % parameter is a array
12029 \define@key{PDF}{Rect}{\pdf@addtoks{[#1]}{Rect}}% hash-ok
12030 % parameter is a integer
12031 \define@key{PDF}{SrcPg}{\pdf@addtoks{#1}{SrcPg}}
12032 % parameter is a name
12033 \define@key{PDF}{Subtype}{\pdf@addtoks{#1}{Subtype}}
12034 % parameter is a string
12035 \define@key{PDF}{Title}{\pdf@addtoks{(#1)}{Title}}
12036 % parameter is a string
12037 \define@key{PDF}{Unix}{\pdf@addtoks{(#1)}{Unix}}
12038 % parameter is a string
12039 \define@key{PDF}{UnixFile}{\pdf@addtoks{(#1)}{UnixFile}}
12040 % parameter is an array
12041 \define@key{PDF}{View}{\pdf@addtoks{[#1]}{View}}% hash-ok
12042 % parameter is a string
12043 \define@key{PDF}{WinFile}{\pdf@addtoks{(#1)}{WinFile}}

These are the keys used in the DOCINFO section.
12044 \define@key{PDF}{Author}{\pdf@addtoks{(#1)}{Author}}
12045 \define@key{PDF}{Creator}{\pdf@addtoks{(#1)}{Creator}}
12046 \define@key{PDF}{CreationDate}{\pdf@addtoks{(#1)}{CreationDate}}
12047 \define@key{PDF}{ModDate}{\pdf@addtoks{(#1)}{ModDate}}
12048 \define@key{PDF}{Producer}{\pdf@addtoks{(#1)}{Producer}}
12049 \define@key{PDF}{Subject}{\pdf@addtoks{(#1)}{Subject}}
12050 \define@key{PDF}{Keywords}{\pdf@addtoks{(#1)}{Keywords}}
12051 \define@key{PDF}{ModDate}{\pdf@addtoks{(#1)}{ModDate}}
12052 \define@key{PDF}{Base}{\pdf@addtoks{(#1)}{Base}}
12053 \define@key{PDF}{URI}{\pdf@addtoks{#1}{URI}}
12054 \define@key{PDF}{Trapped}{%
12055   \edef\Hy@temp{#1}%
12056   \ifx\Hy@temp\@empty
12057   \else
12058     \pdf@addtoks{/#1}{Trapped}%
12059   \fi
12060 }
12061
12062 </pdfmarkbase>
12063 <*pdfmark>
12064 \def\Acrobatmenu#1#2{%
12065   \EdefEscapeName\Hy@temp@menu{#1}%
12066   \Hy@Acrobatmenu{#1}{#2}{%
12067     \pdfmark[#2]}{%
12068     linktype=menu,%
12069     pdfmark=/ANN,%
12070     AcroHighlight=\@pdfhighlight,%
12071     Border=\@pdfborder,%
12072     BorderStyle=\@pdfborderstyle,%
12073     Color=\@menubordercolor,%

```

```

12074     Action={<</Subtype/Named/N/\Hy@temp@menu>>},%
12075     Subtype=/Link,%
12076     PDFAFlags=4%
12077   }%
12078 }%
12079 }

```

And now for some useful examples:

```

12080 \def\PDFNextPage{\@ifnextchar{\PDFNextPage@}{\PDFNextPage@[]}%
12081 \def\PDFNextPage@[#1]#2{%
12082   \pdfmark[{#2}]{%
12083     #1,%
12084     Border=\@pdfborder,%
12085     BorderStyle=\@pdfborderstyle,%
12086     Color=.2 .1 .5,%
12087     pdfmark=/ANN,%
12088     Subtype=/Link,%
12089     PDFAFlags=4,%
12090     Page=/Next%
12091   }%
12092 }
12093 \def\PDFPreviousPage{%
12094   \@ifnextchar{\PDFPreviousPage@}{\PDFPreviousPage@[]}%
12095 }
12096 \def\PDFPreviousPage@[#1]#2{%
12097   \pdfmark[{#2}]{%
12098     #1,%
12099     Border=\@pdfborder,%
12100     BorderStyle=\@pdfborderstyle,%
12101     Color=.4 .4 .1,%
12102     pdfmark=/ANN,%
12103     Subtype=/Link,%
12104     PDFAFlags=4,%
12105     Page=/Prev%
12106   }%
12107 }
12108 \def\PDFOpen#1{%
12109   \pdfmark{#1,pdfmark=/DOCVIEW}%
12110 }

```

This will only work if you use Distiller 2.1 or higher.

```

12111 \def\hyper@linkurl#1#2{%
12112   \begingroup
12113   \Hy@pstringdef\Hy@pstringURI{#2}%
12114   \hyper@chars
12115   \leavevmode
12116   \pdfmark[{#1}]{%
12117     pdfmark=/ANN,%
12118     linktype=url,%
12119     AcroHighlight=\@pdfhighlight,%
12120     Border=\@pdfborder,%
12121     BorderStyle=\@pdfborderstyle,%
12122     Color=\@urlbordercolor,%
12123     Action={<<%
12124       /Subtype/URI%
12125       /URI(\Hy@pstringURI)%
12126       \ifHy@href@ismap
12127         /IsMap true%

```

```

12128     \fi
12129     >>},%
12130     Subtype=/Link,%
12131     PDFAFlags=4%
12132 }%
12133 \endgroup
12134 }
12135 \def\hyper@linkfile#1#2#3{%
12136 \begingroup
12137 \def\Hy@pstringF{#2}%
12138 \Hy@CleanupFile\Hy@pstringF
12139 \Hy@pstringdef\Hy@pstringF\Hy@pstringF
12140 \Hy@pstringdef\Hy@pstringD{#3}%
12141 \Hy@MakeRemoteAction
12142 \leavevmode
12143 \pdfmark[{#1}]{%
12144 pdfmark=/ANN,%
12145 Subtype=/Link,%
12146 PDFAFlags=4,%
12147 AcroHighlight=\@pdfhighlight,%
12148 Border=\@pdfborder,%
12149 BorderStyle=\@pdfborderstyle,%
12150 linktype=file,%
12151 Color=\@filebordercolor,%
12152 Action={%
12153 <<%
12154 /S/GoToR%
12155 \Hy@SetNewWindow
12156 /F(\Hy@pstringF)%
12157 /D%
12158 \ifx\#3\%
12159 [\Hy@href@page\@pdfremotestartview]%
12160 \else
12161 (\Hy@pstringD)cvn%
12162 \fi
12163 \Hy@href@nextactionraw
12164 >>%
12165 }%
12166 }%
12167 \endgroup
12168 }
12169 \def\@hyper@launch run:#1\#2#3{%
12170 \begingroup
12171 \Hy@pstringdef\Hy@pstringF{#1}%
12172 \Hy@pstringdef\Hy@pstringP{#3}%
12173 \leavevmode
12174 \pdfmark[{#2}]{%
12175 pdfmark=/ANN,%
12176 Subtype=/Link,%
12177 PDFAFlags=4,%
12178 AcroHighlight=\@pdfhighlight,%
12179 Border=\@pdfborder,%
12180 BorderStyle=\@pdfborderstyle,%
12181 linktype=run,%
12182 Color=\@runbordercolor,%
12183 Action={%
12184 <<%

```



```

12185      /S/Launch%
12186      \Hy@SetNewWindow
12187      /F(\Hy@pstringF)%
12188      \ifx\|#3\|%
12189      \else
12190      /Win<</P(\Hy@pstringP)/F(\Hy@pstringF)>>%
12191      \fi
12192      \Hy@href@nextactionraw
12193      >>%
12194      }%
12195      }%
12196      \endgroup
12197      }
12198      </pdfmark>

```

Unfortunately, some parts of the `pdfmark` PostScript code depend on vagaries of the dvi driver. We isolate here all the problems.

47.9 Rokicki's dvips

dvips thinks in 10ths of a big point, its coordinate space is resolution dependent, and its y axis starts at the top of the page. Other drivers can and will be different!

The work is done in `SDict`, because we add in some header definitions in a moment.

```

12199 <*dvips>
12200 \providecommand*\XR@ext}{pdf}
12201 \let\Hy@raisedlink\ltx@empty
12202 \def\literalps@out#1{\special{ps:SDict begin #1 end}}%
12203 \def\headerps@out#1{\special{! #1}}%
12204 \input{pdfmark.def}%
12205 \ifx\@pdfproducer\relax
12206   \def\@pdfproducer{dvips + Distiller}%
12207 \fi
12208 \providecommand*\@pdfborder{0 0 1}
12209 \providecommand*\@pdfborderstyle{}
12210 \providecommand*\@pdfview{XYZ}
12211 \providecommand*\@pdfviewparams{ H.V}
12212 \def\Hy@BorderArrayPatch{BorderArrayPatch}
12213 \g@addto@macro\Hy@FirstPageHook{%
12214   \headerps@out{%

```

Unless I am going mad, this *appears* to be the relationship between the default coordinate system (PDF), and dvips;

```

/DvipsToPDF { .01383701 div Resolution div } def
/PDFToDvips { .01383701 mul Resolution mul } def

```

the latter's coordinates are resolution dependent, but what that .01383701 is, who knows? well, almost everyone except me, I expect...And yes, Maarten Gelderman <mgelderman@econ.vu.nl> points out that its $1/72.27$ (the number of points to an inch, big points to inch is $1/72$). This also suggests that the code would be more understandable (and exact) if `0.013 div` would be replaced by `72.27 mul`, so here we go. If this isn't right, I'll revert it.

```

12215 /DvipsToPDF{72.27 mul Resolution div} def%
12216 /PDFToDvips{72.27 div Resolution mul} def%
12217 /BPToDvips{72 div Resolution mul}def%

```

The values inside the `/Boder` array are not taken literally, but interpreted by ghostscript using the resolution of the dvi driver. I don't know how other distiller programs behaves in this manner.

```

12218 /BorderArrayPatch{%
12219   [exch{%
12220     dup dup type/integertype eq exch type/realtype eq or%
12221     {BPToDvips}if%
12222   }forall]%
12223 }def%
```

The rectangle around the links starts off *exactly* the size of the box; we will to make it slightly bigger, 1 point on all sides.

```

12224 /HyperBorder {1 PDFToDvips} def%
12225 /H.V {pdf@hoff pdf@voff null} def%
12226 /H.B {/Rect[pdf@llx pdf@lly pdf@urx pdf@ury]} def%
```

`H.S` (start of anchor, link, or rect) stores the x and y coordinates of the current point, in PDF coordinates

```

12227 /H.S {%
12228   currentpoint %
12229   HyperBorder add /pdf@lly exch def %
12230   dup DvipsToPDF 72 add /pdf@hoff exch def %
12231   HyperBorder sub /pdf@llx exch def%
12232 } def%
```

The calculation of upper left y is done without raising the point in `TeX`, by simply adding on the current `\baselineskip` to the current y . This is usually too much, so we remove a notional 2 points.

We have to see what the current `baselineskip` is, and convert it to the dvips coordinate system.

Argument: `baselineskip` in pt. The x and y coordinates of the current point, minus the `baselineskip`

```

12233 /H.L {%
12234   2 sub dup%
12235   /HyperBasePt exch def %
12236   PDFToDvips /HyperBaseDvips exch def %
12237   currentpoint %
12238   HyperBaseDvips sub /pdf@ury exch def%
12239   /pdf@urx exch def%
12240 } def%
12241 /H.A {%
12242   H.L %
12243 % |pdf@voff| = the distance from the top of the page to a point
12244 % |\baselineskip| above the current point in PDF coordinates
12245   currentpoint exch pop %
12246   vsize 72 sub exch DvipsToPDF %
12247   HyperBasePt sub % baseline skip
12248   sub /pdf@voff exch def%
12249 } def%
12250 /H.R {%
12251   currentpoint %
12252   HyperBorder sub /pdf@ury exch def %
12253   HyperBorder add /pdf@urx exch def %
12254 % |pdf@voff| = the distance from the top of the page to the current point, in
12255 % PDF coordinates
12256   currentpoint exch pop vsize 72 sub %
12257   exch DvipsToPDF sub /pdf@voff exch def%
12258 } def%
```

```

12259 }%
12260 }
12261 \AtBeginShipoutFirst{%
12262   \ifHy@setpagesize
12263     \begingroup
12264       \@ifundefined{stockwidth}{%
12265         \ifdim\paperwidth>\z@
12266           \ifdim\paperheight>\z@
12267             \special{papersize=\the\paperwidth,\the\paperheight}%
12268           \fi
12269         \fi
12270       }{%
12271         \ifdim\stockwidth>\z@
12272           \ifdim\stockheight>\z@
12273             \special{papersize=\the\stockwidth,\the\stockheight}%
12274           \fi
12275         \fi
12276       }%
12277     \endgroup
12278   \fi
12279   \Hy@DisableOption{setpagesize}%
12280 }
12281 </dvips>

```

47.10 VTeX's vtexpdfmark driver

This part is derived from the dvips (many names reflect this).

The origin seems to be the same as TeX's origin, 1 in from the left and 1 in downwards from the top. The direction of the y axis is downwards, the opposite of the dvips case. Units seems to be pt or bp.

```

12282 (*vtexpdfmark)
12283 \providecommand*\XR@ext}{pdf}
12284 \let\Hy@raisedlink\ltx@empty
12285 \def\literalps@out#1{\special{pS:#1}}%
12286 \def\headerps@out#1{\immediate\special{pS:#1}}%
12287 \input{pdfmark.def}%
12288 \ifx\@pdfproducer\relax
12289   \ifnum\OpMode=\@ne
12290     \def\@pdfproducer{VTeX}%
12291   \else
12292     \def\@pdfproducer{VTeX + Distiller}%
12293   \fi
12294 \fi
12295 \providecommand*\@pdfborder{0 0 1}
12296 \providecommand*\@pdfborderstyle{}
12297 \providecommand*\@pdfview{XYZ}
12298 \providecommand*\@pdfviewparams{ H.V}
12299 \g@addto@macro\Hy@FirstPageHook{%
12300   \headerps@out{%
12301     /vsize {\Hy@pageheight} def%

```

The rectangle around the links starts off *exactly* the size of the box; we will to make it slightly bigger, 1 point on all sides.

```

12302   /HyperBorder {1} def%
12303   /H.V {pdf@hoff pdf@voff null} def%
12304   /H.B {/Rect[pdf@llx pdf@lly pdf@urx pdf@ury]} def%

```

H.S (start of anchor, link, or rect) stores the x and y coordinates of the current point, in PDF coordinates: $\text{pdf@lly} = Y_c - \text{HyperBorder}$, $\text{pdf@hoff} = X_c + 72$, $\text{pdf@llx} = X_c - \text{HyperBorder}$

```

12305 /H.S {%
12306     currentpoint %
12307     HyperBorder sub%
12308     /pdf@lly exch def %
12309     dup 72 add /pdf@hoff exch def %
12310     HyperBorder sub%
12311     /pdf@llx exch def%
12312 } def%

```

The x and y coordinates of the current point, minus the `\baselineskip`: $\text{pdf@ury} = Y_c + \text{HyperBasePt} + \text{HyperBorder}$, $\text{pdf@urx} = X_c + \text{HyperBorder}$

```

12313 /H.L {%
12314     2 sub%
12315     /HyperBasePt exch def %
12316     currentpoint %
12317     HyperBasePt add HyperBorder add%
12318     /pdf@ury exch def %
12319     HyperBorder add%
12320     /pdf@urx exch def%
12321 } def%
12322 /H.A {%
12323     H.L %
12324     currentpoint exch pop %
12325     vsize 72 sub exch %
12326     HyperBasePt add add%
12327     /pdf@voff exch def%
12328 } def%

```

$\text{pdf@ury} = Y_c + \text{HyperBorder}$, $\text{pdf@urx} = X_c + \text{HyperBorder}$

```

12329 /H.R {%
12330     currentpoint %
12331     HyperBorder add%
12332     /pdf@ury exch def %
12333     HyperBorder add%
12334     /pdf@urx exch def %
12335     currentpoint exch pop vsize 72 sub add%
12336     /pdf@voff exch def%
12337 } def%
12338 }%
12339 }
12340 </vtxpdfmark>

```

47.11 Textures

```

12341 <*textures>
12342 \providecommand*\XR@ext\{pdf}

```

At the suggestion of Jacques Distler (distler@golem.ph.utexas.edu), try to derive a suitable driver for Textures. This was initially a copy of dvips, with some guesses about Textures behaviour. Ross Moore (ross@maths.mq.edu.au) has added modifications for better compatibility, and to support use of pdfmark.

Start by defining a macro that expands to the end-of-line character. This will be used to format the appearance of PostScript code, to enhance readability, and avoid excessively long lines which might otherwise become broken to bad places.

`\Hy@ps@CR` The macro `\Hy@ps@CR` contains the end-of-line character.

```

12343 \begingroup
12344 \obeylines %
12345 \gdef\Hy@ps@CR{\noexpand
12346 }%
12347 \endgroup %

```

Textures has two types of `\special` command for inserting PostScript code directly into the dvi output. The ‘postscript’ way preserves TeX’s idea of where on the page the `\special` occurred, but it wraps the contents with a `save-restore` pair, and adjusts the user-space coordinate system for local drawing commands. The ‘rawpostscript’ way simply inserts code, without regard for the location on the page.

Thus, to put arbitrary PostScript coding at a fixed location requires using *both* `\special` constructions. It works by pushing the device-space coordinates onto the operand stack, where they can be used to transform back to the correct user-space coordinates for the whole page, within a ‘rawpostscript’ `\special`.

```

12348 \def\literalps@out#1{%
12349 \special{postscript 0 0 transform}%
12350 \special{rawpostscript itransform moveto\Hy@ps@CR #1}%
12351 }%
12352 %

```

The ‘prepostscript’ is a 3rd kind of `\special`, used for inserting definitions into the dictionaries, before page-building begins. These are to be available for use on all pages.

```

12353 \def\headerps@out#1{%
12354 \special{%
12355 prepostscript TeXdict begin\Hy@ps@CR
12356 #1\Hy@ps@CR
12357 end%
12358 }%
12359 }%
12360 %

```

To correctly support the `pdfmark` method, for embedding PDF definitions with `.ps` files in a non-intrusive way, an appropriate definition needs to be made *before* the file `pdfmark.def` is read. Other parameters are best set afterwards.

```

12361 \g@addto@macro\Hy@FirstPageHook{%
12362 \headerps@out{%
12363 /betterpdfmark {%
12364 systemdict begin %
12365 dup /BP eq%
12366 {cleartomark gsave nulldevice []%
12367 {dup /EP eq%
12368 {cleartomark cleartomark grestore}%
12369 {cleartomark}%
12370 ifelse%
12371 }ifelse %
12372 end%
12373 }def\Hy@ps@CR
12374 ___pdfmark___ not{/pdfmark /betterpdfmark load def}if%
12375 }% end of \headerps@out
12376 }% end of \AtBeginShipoutFirst
12377 %
12378 \input{pdfmark.def}%

```

```

12379 %
12380 \ifx\@pdfproducer\relax
12381 \def\@pdfproducer{Textures + Distiller}%
12382 \fi
12383 \providecommand*\@pdfborder{0 0 1}
12384 \providecommand*\@pdfborderstyle{}
12385 \providecommand*\@pdfview{XYZ}
12386 \providecommand*\@pdfviewparams{ H.V}
12387 %

```

These are called at the start and end of unboxed links; their job is to leave available PS variables called `pdf@llx pdf@lly pdf@urx pdf@ury`, which are the coordinates of the bounding rectangle of the link, and `pdf@hoff pdf@voff` which are the PDF page offsets. The `Rect` pair are called at the LL and UR corners of a box known to \TeX .

```

12388 \Hy@AtBeginDocument{%
12389 \headerps@out{%

```

`Textures` lives in normal points, I think. So conversion from one coordinate system to another involves doing nothing.

```

12390 /vsize {\Hy@pageheight} def%
12391 /DvipsToPDF {} def%
12392 /PDFToDvips {} def%
12393 /BPToDvips {} def%
12394 /HyperBorder { 1 PDFToDvips } def\Hy@ps@CR
12395 /H.V {pdf@hoff pdf@voff null} def\Hy@ps@CR
12396 /H.B {/Rect[pdf@llx pdf@lly pdf@urx pdf@ury]} def\Hy@ps@CR
12397 /H.S {%
12398 currentpoint %
12399 HyperBorder add /pdf@lly exch def %
12400 dup DvipsToPDF 72 add /pdf@hoff exch def %
12401 HyperBorder sub /pdf@llx exch def%
12402 } def\Hy@ps@CR
12403 /H.L {%
12404 2 sub %
12405 PDFToDvips /HyperBase exch def %
12406 currentpoint %
12407 HyperBase sub /pdf@ury exch def%
12408 /pdf@urx exch def%
12409 } def\Hy@ps@CR
12410 /H.A {%
12411 H.L %
12412 currentpoint exch pop %
12413 vsize 72 sub exch DvipsToPDF %
12414 HyperBase sub % baseline skip
12415 sub /pdf@voff exch def%
12416 } def\Hy@ps@CR
12417 /H.R {%
12418 currentpoint %
12419 HyperBorder sub /pdf@ury exch def %
12420 HyperBorder add /pdf@urx exch def %
12421 currentpoint exch pop vsize 72 sub %
12422 exch DvipsToPDF sub /pdf@voff exch def%
12423 } def\Hy@ps@CR
12424 }%
12425 }
12426 \Hy@AtBeginDocument{%

```

```

12427 \ifHy@colorlinks
12428   \headerps@out{/PDFBorder{/Border [0 0 0]}def}%
12429 \fi
12430 }

```

Textures provides built-in support for HyperTeX specials so this part combines code from `hypertex.def` with what is established by loading `pdfmark.def`, or any other driver.

```

12431 \expandafter\let\expandafter\keepPDF@SetupDoc
12432   \csname PDF@SetupDoc\endcsname
12433 \def\PDF@SetupDoc{%
12434   \ifx\@baseurl\@empty
12435   \else
12436     \special{html:<base href="\@baseurl">}%
12437   \fi
12438   \keepPDF@SetupDoc
12439 }
12440 \Hy@WrapperDef\hyper@anchor#1{%
12441   \Hy@SaveLastskip
12442   \Hy@VerboseAnchor{#1}%
12443   \begingroup
12444     \let\protect=\string
12445     \special{html:<a name=%
12446       \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}%
12447   \endgroup
12448   \Hy@activeanchortrue
12449   \Hy@colorlink\@anchorcolor\anchor@spot\Hy@endcolorlink
12450   \special{html:</a>}%
12451   \Hy@activeanchorfalse
12452   \Hy@RestoreLastskip
12453 }
12454 \Hy@WrapperDef\hyper@anchorstart#1{%
12455   \Hy@SaveLastskip
12456   \Hy@VerboseAnchor{#1}%
12457   \begingroup
12458     \hyper@chars
12459     \special{html:<a name=%
12460       \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}%
12461   \endgroup
12462   \Hy@activeanchortrue
12463 }
12464 \def\hyper@anchorend{%
12465   \special{html:</a>}%
12466   \Hy@activeanchorfalse
12467   \Hy@RestoreLastskip
12468 }
12469 \def\@urltype{url}
12470 \def\hyper@linkstart#1#2{%
12471   \Hy@VerboseLinkStart{#1}{#2}%
12472   \expandafter\Hy@colorlink\csname @#1color\endcsname
12473   \def\Hy@tempa{#1}%
12474   \ifx\Hy@tempa\@urltype
12475     \special{html:<a href=\hyper@quote#2\hyper@quote>}%
12476   \else
12477     \begingroup
12478       \hyper@chars
12479       \special{%
12480         html:<a href=%

```

```

12481     \hyper@quote\#\HyperDestNameFilter{#2}\hyper@quote>%
12482 }%
12483 \endgroup
12484 \fi
12485 }
12486 \def\hyper@linkend{%
12487 \special{html:</a>}}%
12488 \Hy@endcolorlink
12489 }
12490 \def\hyper@linkfile#1#2#3{%
12491 \hyper@linkurl{#1}{%
12492 \Hy@linkfileprefix#2\ifx\#3\\\else\##3\fi
12493 }%
12494 }
12495 \def\hyper@linkurl#1#2{%
12496 \leavevmode
12497 \ifHy@raiselinks
12498 \Hy@SaveSpaceFactor
12499 \Hy@SaveSavedSpaceFactor
12500 \sbox\@tempboxa{\Hy@RestoreSpaceFactor#1}%
12501 \Hy@RestoreSavedSpaceFactor
12502 \@linkdim\dp\@tempboxa
12503 \lower\@linkdim\hbox{%
12504 \hyper@chars
12505 \special{html:<a href=\hyper@quote#2\hyper@quote>}}%
12506 }%
12507 \Hy@colorlink\@urlcolor
12508 \Hy@RestoreSpaceFactor
12509 #1\Hy@xspace@end
12510 \Hy@SaveSpaceFactor
12511 \@linkdim\ht\@tempboxa
12512 \advance\@linkdim by -6.5\p@
12513 \raise\@linkdim\hbox{\special{html:</a>}}}%
12514 \Hy@endcolorlink
12515 \Hy@RestoreSpaceFactor
12516 \else
12517 \begingroup
12518 \hyper@chars
12519 \special{html:<a href=\hyper@quote#2\hyper@quote>}}%
12520 \Hy@colorlink\@urlcolor#1\Hy@xspace@end
12521 \special{html:</a>}}%
12522 \Hy@endcolorlink
12523 \endgroup
12524 \fi
12525 }

```

Very poor implementation of \hyper@link without considering #1.

```

12526 \def\hyper@link#1#2#3{%
12527 \Hy@VerboseLinkStart{#1}{#2}%
12528 \hyper@linkurl{#3}{\#\HyperDestNameFilter{#2}}}%
12529 }
12530 \def\hyper@image#1#2{%
12531 \begingroup
12532 \hyper@chars
12533 \special{html:<img src=\hyper@quote#1\hyper@quote>}}%
12534 \endgroup
12535 }
12536 </textures>

```


47.12 dvipsone

```
12537 % \subsection{dvipsone driver}
12538 % Over-ride the default setup macro in pdfmark driver to use Y\&Y
12539 % |\special| commands.
12540 (*dvipsone)
12541 \providecommand*\XR@ext}{pdf}
12542 \let\Hy@raisedlink\ltx@empty
12543 \providecommand*\@pdfborder{0 0 1}
12544 \providecommand*\@pdfborderstyle{}
12545 \def\literalps@out#1{\special{ps:#1}}%
12546 \def\headerps@out#1{\special{headertext=#1}}%
12547 \input{pdfmark.def}%
12548 \ifx\@pdfproducer\relax
12549   \def\@pdfproducer{dvipsone + Distiller}%
12550 \fi
12551 \HyInfo@AddonUnsupportedtrue
12552 \def\PDF@FinishDoc{%
12553   \Hy@UseMaketitleInfos
12554   \HyInfo@TrappedUnsupported
12555   \special{PDF: Keywords \@pdfkeywords}%
12556   \special{PDF: Title \@pdftitle}%
12557   \special{PDF: Creator \@pdfcreator}%
12558   \ifx\@pdfcreationdate\@empty
12559   \else
12560     \special{PDF: CreationDate \@pdfcreationdate}%
12561   \fi
12562   \ifx\@pdfmoddate\@empty
12563   \else
12564     \special{PDF: ModDate \@pdfmoddate}%
12565   \fi
12566   \special{PDF: Author \@pdfauthor}%
12567   \ifx\@pdfproducer\relax
12568   \else
12569     \special{PDF: Producer \@pdfproducer}%
12570   \fi
12571   \special{PDF: Subject \@pdfsubject}%
12572   \Hy@DisableOption{pdfauthor}%
12573   \Hy@DisableOption{pdftitle}%
12574   \Hy@DisableOption{pdfsubject}%
12575   \Hy@DisableOption{pdfcreator}%
12576   \Hy@DisableOption{pdfcreationdate}%
12577   \Hy@DisableOption{pdfmoddate}%
12578   \Hy@DisableOption{pdfproducer}%
12579   \Hy@DisableOption{pdfkeywords}%
12580   \Hy@DisableOption{pdftrapped}%
12581   \Hy@DisableOption{pdfinfo}%
12582 }
12583 \def\PDF@SetupDoc{%
12584   \def\Hy@temp{}%
12585   \ifx\@pdfstartpage\@empty
12586   \else
12587     \ifx\@pdfstartview\@empty
12588     \else
12589       \edef\Hy@temp{%
12590         ,Page=\@pdfstartpage
12591         ,View=\@pdfstartview
12592       }%
```

```

12593 \fi
12594 \fi
12595 \edef\Hy@temp{%
12596 \noexpand\pdfmark{%
12597 pdfmark=/DOCVIEW,%
12598 PageMode=/\@pdfpagemode
12599 \Hy@temp
12600 }%
12601 }%
12602 \Hy@temp
12603 \ifx\@pdfpagescrop\@empty
12604 \else
12605 \pdfmark{pdfmark=/PAGES,CropBox=\@pdfpagescrop}%
12606 \fi
12607 \edef\Hy@temp{%
12608 \ifHy@pdftoolbar\else /HideToolbar true\fi
12609 \ifHy@pdfmenubar\else /HideMenubar true\fi
12610 \ifHy@pdfwindowui\else /HideWindowUI true\fi
12611 \ifHy@pdfwindow /FitWindow true\fi
12612 \ifHy@pdfcenterwindow /CenterWindow true\fi
12613 \ifHy@pdfdisplaydoctitle /DisplayDocTitle true\fi
12614 \Hy@UseNameKey{NonFullScreenPageMode}\@pdfnonfullscreenpagemode
12615 \Hy@UseNameKey{Direction}\@pdfdirection
12616 \Hy@UseNameKey{ViewArea}\@pdfviewarea
12617 \Hy@UseNameKey{ViewClip}\@pdfviewclip
12618 \Hy@UseNameKey{PrintArea}\@pdfprintarea
12619 \Hy@UseNameKey{PrintClip}\@pdfprintclip
12620 \Hy@UseNameKey{PrintScaling}\@pdfprintscaling
12621 \Hy@UseNameKey{Duplex}\@pdfduplex
12622 \ifx\@pdfpicktraybypdfsize\@empty
12623 \else
12624 /PickTrayByPDFSize \@pdfpicktraybypdfsize
12625 \fi
12626 \ifx\@pdfprintpagerange\@empty
12627 \else
12628 /PrintPageRange[\@pdfprintpagerange]%
12629 \fi
12630 \ifx\@pdfnumcopies\@empty
12631 \else
12632 /NumCopies \@pdfnumcopies
12633 \fi
12634 }%
12635 \Hy@pstringdef\Hy@pstringB{\@baseurl}%
12636 \pdfmark{%
12637 pdfmark=/PUT,%
12638 Raw={%
12639 \string{Catalog\string}<<%
12640 \ifx\Hy@temp\@empty
12641 \else
12642 /ViewerPreferences<<\Hy@temp>>%
12643 \fi
12644 \Hy@UseNameKey{PageLayout}\@pdfpagelayout
12645 \ifx\@pdflang\@empty
12646 \else
12647 /Lang(\@pdflang)%
12648 \fi
12649 \ifx\@baseurl\@empty

```

```

12650     \else
12651     /URI<</Base(\Hy@pstringB)>>%
12652     \fi
12653     >>%
12654     }%
12655     }%
12656 }
12657 \providecommand*\@pdfview{XYZ}
12658 \providecommand*\@pdfviewparams{ %
12659     gsave revscl currentpoint grestore %
12660     72 add exch pop null exch null%
12661 }
12662 \def\Hy@BorderArrayPatch{BorderArrayPatch}

```

These are called at the start and end of unboxed links; their job is to leave available PS variables called `pdf@llx pdf@lly pdf@urx pdf@ury`, which are the coordinates of the bounding rectangle of the link, and `pdf@hoff pdf@voff` which are the PDF page offsets. These latter are currently not used in the dvipsone setup. The `Rect` pair are called at the LL and UR corners of a box known to \TeX .

```

12663 \g@addto@macro\Hy@FirstPageHook{%
12664     \headerps@out{%
dvipsone lives in scaled points; does this mean 65536 or 65781?
12665     /DvipsToPDF { 65781 div } def%
12666     /PDFToDvips { 65781 mul } def%
12667     /BPToDvips{65781 mul}def%
12668     /HyperBorder { 1 PDFToDvips } def%
12669     /H.B {/Rect[pdf@llx pdf@lly pdf@urx pdf@ury]} def%

```

The values inside the `/Boder` array are not taken literally, but interpreted by ghostscript using the resolution of the dvi driver. I don't know how other distiller programs behaves in this manner.

```

12670     /BorderArrayPatch{%
12671         [exch{%
12672             dup dup type/integertype eq exch type/realtype eq or%
12673             {BPToDvips}if%
12674             }forall]%
12675         }def%
12676     /H.S {%
12677         currentpoint %
12678         HyperBorder add /pdf@lly exch def %
12679         dup DvipsToPDF 72 add /pdf@hoff exch def %
12680         HyperBorder sub /pdf@llx exch def%
12681     } def%
12682     /H.L {%
12683         2 sub %
12684         PDFToDvips /HyperBase exch def %
12685         currentpoint %
12686         HyperBase sub /pdf@ury exch def%
12687         /pdf@urx exch def%
12688     } def%
12689     /H.A {%
12690         H.L %
12691         currentpoint exch pop %
12692         HyperBase sub % baseline skip
12693         DvipsToPDF /pdf@voff exch def%
12694     } def%
12695     /H.R {%
12696         currentpoint %

```

```

12697   HyperBorder sub /pdf@ury exch def %
12698   HyperBorder add /pdf@urx exch def %
12699   currentpoint exch pop DvipsToPDF /pdf@voff exch def%
12700   } def%
12701 }%
12702 }
12703 </dvipsone>

```

47.13 TeX4ht

```

12704 <{*tex4ht}
12705 \providecommand*{\XR@ext}{html}
12706 \let\Hy@raisedlink\ltx@empty
12707 \@ifpackageloaded{tex4ht}{%
12708   \Hy@InfoNoLine{tex4ht is already loaded}%
12709 }{%
12710   \RequirePackage[hTeX4ht]{tex4ht}%
12711 }
12712 \hyperlinkfileprefix{}
12713 \let\PDF@FinishDoc\ltx@empty
12714 \def\PDF@SetupDoc{%
12715   \ifx\@baseurl\@empty
12716   \else
12717     \special{t4ht=<base href="\@baseurl">}%
12718   \fi
12719 }
12720 \Hy@WrapperDef\hyper@anchor#1{%
12721   \Hy@SaveLastskip
12722   \Hy@VerboseAnchor{#1}%
12723   \begingroup
12724     \let\protect=\string
12725     \special{t4ht=<a name=%
12726       \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}%
12727   \endgroup
12728   \Hy@activeanchortrue
12729   \Hy@colorlink\@anchorcolor\anchor@spot\Hy@endcolorlink
12730   \special{t4ht=</a>}%
12731   \Hy@activeanchorfalse
12732   \Hy@RestoreLastskip
12733 }
12734 \Hy@WrapperDef\hyper@anchorstart#1{%
12735   \Hy@SaveLastskip
12736   \Hy@VerboseAnchor{#1}%
12737   \begingroup
12738     \hyper@chars\special{t4ht=<a name=%
12739       \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}%
12740   \endgroup
12741   \Hy@activeanchortrue
12742 }
12743 \def\hyper@anchorend{%
12744   \special{t4ht=</a>}%
12745   \Hy@activeanchorfalse
12746   \Hy@RestoreLastskip
12747 }
12748 \def\@urltype{url}
12749 \def\hyper@linkstart#1#2{%
12750   \Hy@VerboseLinkStart{#1}{#2}%
12751   \expandafter\Hy@colorlink\csname @#1color\endcsname

```

```

12752 \def\Hy@tempa{#1}%
12753 \ifx\Hy@tempa\@urlltype
12754   \special{t4ht=<a href=\hyper@quote#2\hyper@quote>}%
12755 \else
12756   \begingroup
12757     \hyper@chars
12758     \special{t4ht=<a href=%
12759       \hyper@quote\#\HyperDestNameFilter{#2}\hyper@quote>}%
12760   \endgroup
12761 \fi
12762 }
12763 \def\hyper@linkend{%
12764   \special{t4ht=</a>}%
12765   \Hy@endcolorlink
12766 }
12767 \def\hyper@linkfile#1#2#3{%
12768   \hyper@linkurl{#1}{\Hy@linkfileprefix#2\ifx\\#3\\\else\##3\fi}%
12769 }
12770 \def\hyper@linkurl#1#2{%
12771   \leavevmode
12772   \ifHy@raiselinks
12773     \Hy@SaveSpaceFactor
12774     \Hy@SaveSavedSpaceFactor
12775     \sbox\@tempboxa{\Hy@RestoreSpaceFactor#1}%
12776     \Hy@RestoreSavedSpaceFactor
12777     \@linkdim\dp\@tempboxa
12778     \lower\@linkdim\hbox{%
12779       \begingroup
12780         \hyper@chars
12781         \special{%
12782           t4ht=<a href=\hyper@quote#2\hyper@quote>%
12783         }%
12784       \endgroup
12785     }%
12786     \Hy@colorlink\@urlcolor
12787     \Hy@RestoreSpaceFactor
12788     #1\Hy@xspace@end
12789     \Hy@SaveSpaceFactor
12790     \Hy@endcolorlink
12791     \@linkdim\ht\@tempboxa
12792     \advance\@linkdim by -6.5\p@
12793     \raise\@linkdim\hbox{\special{t4ht=</a>}}%
12794     \Hy@RestoreSpaceFactor
12795   \else
12796     \begingroup
12797       \hyper@chars
12798       \special{t4ht=<a href=\hyper@quote#2\hyper@quote>}%
12799       \Hy@colorlink\@urlcolor
12800       #1\Hy@xspace@end
12801       \Hy@endcolorlink
12802       \special{t4ht=</a>}%
12803     \endgroup
12804 \fi
12805 }

```

Poor implementation of \hyper@link without considering #1.

```

12806 \def\hyper@link#1#2#3{%
12807   \Hy@VerboseLinkStart{#1}{#2}%

```

```

12808 \hyper@linkurl{#3}{\#\HyperDestNameFilter{#2}}%
12809 }
12810 \def\hyper@image#1#2{%
12811 \begingroup
12812 \hyper@chars
12813 \special{t4ht=<img src=\hyper@quote#1\hyper@quote>}%
12814 \endgroup
12815 }
12816 \let\autoref\ref
12817 \ifx \rEFLiNK \UnDef
12818 \def\rEFLiNK #1#2{#2}%
12819 \fi
12820 \let\backref\ltx@gobble

Fix for tex4ht.
12821 \AtBeginDocument{%
12822 \expandafter
12823 \let\expandafter\Hy@OrgMakeLabel\csname Make:Label\endcsname
12824 \expandafter\def\csname Make:Label\endcsname#1#2{%
12825 \ifhmode
12826 \Hy@SaveSpaceFactor
12827 \else
12828 \global\Hy@SavedSpaceFactor=1000 %
12829 \fi
12830 \Hy@OrgMakeLabel{#1}{%
12831 \Hy@RestoreSpaceFactor
12832 #2\Hy@xspace@end%
12833 \Hy@SaveSpaceFactor
12834 }%
12835 \Hy@RestoreSpaceFactor
12836 }%
12837 }
12838 </tex4ht>
12839 <*\tex4htcfg>
12840 \IfFileExists{\jobname.cfg}{\endinput}{\}
12841 \Preamble{html}
12842 \begin{document}%
12843 \EndPreamble
12844 \def\TeX{TeX}
12845 \def\OMEGA{Omega}
12846 \def\LaTeX{LaTeX}
12847 \def\LaTeXe{\LaTeX2e}
12848 \def\eTeX{e-TeX}
12849 \def\MF{Metafont}
12850 \def\MP{MetaPost}
12851 </tex4htcfg>

```

48 Driver-specific form support

48.1 pdfmarks

```

12852 <*\pdfmark>
12853 \long\def\@Form[#1]{%
12854 \g@addto@macro\Hy@FirstPageHook{%
12855 \headerps@out{%
12856 [%
12857 /_objdef{pdfDocEncoding}%
12858 /type/dict%

```

12859 /OBJ pdfmark%
12860 [%
12861 {pdfDocEncoding}%
12862 <<%
12863 /Type/Encoding%
12864 /Differences[%
12865 24/breve/caron/circumflex/dotaccent/hungarumlaut/ogonek/ring%
12866 /tilde %
12867 39/quotesingle %
12868 96/grave %
12869 128/bullet/dagger/daggerdbl/ellipsis/emdash/endash/florin%
12870 /fraction/guilsinglleft/guilsinglright/minus/perthousand%
12871 /quotedblbase/quotedblleft/quotedblright/quoteleft%
12872 /quoteright/quotesinglbase/trademark/fi/fl/Lslash/OE/Scaron%
12873 /Ydieresis/Zcaron/dotlessi/lslash/oe/scaron/zcaron %
12874 164/currency %
12875 166/brokenbar %
12876 168/dieresis/copyright/ordfeminine %
12877 172/logicalnot/.notdef/registered/macron/degree/plusminus%
12878 /twosuperior/threesuperior/acute/mu %
12879 183/periodcentered/cedilla/onesuperior/ordmasculine %
12880 188/onequarter/onehalf/threequarters %
12881 192/Agrave/Aacute/Acircumflex/Atilde/Adieresis/Aring/AE%
12882 /Ccedilla/Egrave/Eacute/Ecircumflex/Edieresis/Igrave%
12883 /Iacute/Icircumflex/Idieresis/Eth/Ntilde/Ograve/Oacute%
12884 /Ocircumflex/Otilde/Odieresis/multiply/Oslash/Ugrave%
12885 /Uacute/Ucircumflex/Udieresis/Yacute/Thorn/germandbls%
12886 /agrave/aacute/acircumflex/atilde/adieresis/aring/ae%
12887 /ccedilla/egrave/eacute/ecircumflex/edieresis/igrave%
12888 /iacute/icircumflex/idieresis/eth/ntilde/ograde/oacute%
12889 /ocircumflex/otilde/odieresis/divide/oslash/ugrave/uacute%
12890 /ucircumflex/udieresis/yacute/thorn/ydieresis%
12891]%
12892 >>%
12893 /PUT pdfmark%
12894 [%
12895 /_objdef{ZaDb}%
12896 /type/dict%
12897 /OBJ pdfmark%
12898 [%
12899 {ZaDb}%
12900 <<%
12901 /Type/Font%
12902 /Subtype/Type1%
12903 /Name/ZaDb%
12904 /BaseFont/ZapfDingbats%
12905 >>%
12906 /PUT pdfmark%
12907 [%
12908 /_objdef{Helv}%
12909 /type/dict%
12910 /OBJ pdfmark%
12911 [%
12912 {Helv}%
12913 <<%
12914 /Type/Font%
12915 /Subtype/Type1%

```

12916 /Name/Helv%
12917 /BaseFont/Helvetica%
12918 /Encoding{pdfDocEncoding}%
12919 >>%
12920 /PUT pdfmark%
12921 [%
12922 /__objdef{aform}%
12923 /type/dict%
12924 /OBJ pdfmark%
12925 [%
12926 /__objdef{afields}%
12927 /type/array%
12928 /OBJ pdfmark%
12929 {%
12930 [%
12931 /BBox[0 0 100 100]%
12932 /__objdef{Check}%
12933 /BP pdfmark %
12934 1 0 0 setrgbcolor%
12935 /ZapfDingbats 80 selectfont %
12936 20 20 moveto%
12937 (4)show%
12938 [/EP pdfmark%
12939 [%
12940 /BBox[0 0 100 100]%
12941 /__objdef{Cross}%
12942 /BP pdfmark %
12943 1 0 0 setrgbcolor%
12944 /ZapfDingbats 80 selectfont %
12945 20 20 moveto%
12946 (8)show%
12947 [/EP pdfmark%
12948 [%
12949 /BBox[0 0 250 100]%
12950 /__objdef{Submit}%
12951 /BP pdfmark %
12952 0.6 setgray %
12953 0 0 250 100 rectfill %
12954 1 setgray %
12955 2 2 moveto %
12956 2 98 lineto %
12957 248 98 lineto %
12958 246 96 lineto %
12959 4 96 lineto %
12960 4 4 lineto %
12961 fill %
12962 0.34 setgray %
12963 248 98 moveto %
12964 248 2 lineto %
12965 2 2 lineto %
12966 4 4 lineto %
12967 246 4 lineto %
12968 246 96 lineto %
12969 fill%
12970 /Helvetica 76 selectfont %
12971 0 setgray %
12972 8 22.5 moveto%

```



```

12973 (Submit)show%
12974 [/EP pdfmark%
12975 [%
12976   /BBox[0 0 250 100]%
12977   /_objdef{SubmitP}%
12978 /BP pdfmark %
12979 0.6 setgray %
12980 0 0 250 100 rectfill %
12981 0.34 setgray %
12982 2 2 moveto %
12983 2 98 lineto %
12984 248 98 lineto %
12985 246 96 lineto %
12986 4 96 lineto %
12987 4 4 lineto %
12988 fill %
12989 1 setgray %
12990 248 98 moveto %
12991 248 2 lineto %
12992 2 2 lineto %
12993 4 4 lineto %
12994 246 4 lineto %
12995 246 96 lineto %
12996 fill%
12997 /Helvetica 76 selectfont %
12998 0 setgray %
12999 10 20.5 moveto%
13000 (Submit)show%
13001 [/EP pdfmark%
13002 } ?pdfmark%
13003 [%
13004 {aform}%
13005 <<%
13006 /Fields{afields}%
13007 /DR<<%
13008 /Font<<%
13009 /ZaDb{ZaDb}%
13010 /Helv{Helv}%
13011 >>%
13012 >>%
13013 /DA(/Helv 10 Tf 0 g)%
13014 /CO{corder}%
13015 \ifHy@pdfa
13016 \else
13017   \ifHyField@NeedAppearances
13018     /NeedAppearances true%
13019   \fi
13020 \fi
13021 >>%
13022 /PUT pdfmark%
13023 [%
13024 {Catalog}%
13025 <<%
13026 /AcroForm{aform}%
13027 >>%
13028 /PUT pdfmark%
13029 [%

```

```

13030 /__objdef{corder}%
13031 /type/array%
13032 /OBJ pdfmark% dps
13033 }}%
13034 \kvsetkeys{Form}{#1}%
13035 }
13036 \let\@endForm\ltx@empty
13037 \def\@Gauge[#1]#2#3#4{% parameters, label, minimum, maximum
13038 \Hy@Message{Sorry, pdfmark drivers do not support FORM gauges}%
13039 }
13040 \edef\Fld@pageobjref{/P/string{ThisPage\string}}
13041 \def\@TextField[#1]#2{% parameters, label
13042 \def\Fld@name{#2}%
13043 \let\Fld@default\ltx@empty
13044 \let\Fld@value\@empty
13045 \def\Fld@width{\DefaultWidthofText}%
13046 \def\Fld@height{%
13047 \ifFld@multiline
13048 \DefaultHeightofTextMultiline
13049 \else
13050 \DefaultHeightofText
13051 \fi
13052 }%
13053 \begingroup
13054 \expandafter\HyField@SetKeys\expandafter{%
13055 \DefaultOptionsofText,#1%
13056 }%
13057 \HyField@FlagsText
13058 \ifFld@hidden\def\Fld@width{1sp}\fi
13059 \ifx\Fld@value\@empty\def\Fld@value{\Fld@default}\fi
13060 \LayoutTextField{#2}{%
13061 \leavevmode
13062 \Hy@escapeform\PDFForm@Text
13063 \pdfmark[\MakeTextField{\Fld@width}{\Fld@height}]{%
13064 pdfmark=/ANN,Raw={\PDFForm@Text}%
13065 }%
13066 }%
13067 \endgroup
13068 }
13069 \def\@ChoiceMenu[#1]#2#3{% parameters, label, choices
13070 \def\Fld@name{#2}%
13071 \let\Fld@default\relax
13072 \let\Fld@value\relax
13073 \def\Fld@width{\DefaultWidthofChoiceMenu}%
13074 \def\Fld@height{\DefaultHeightofChoiceMenu}%
13075 \begingroup
13076 \Fld@menulength=0 %
13077 \@tempdima\z@
13078 \@for\@curropt:=#3\do{%
13079 \expandafter\Fld@checkequals\@curropt==\%
13080 \Hy@StepCount\Fld@menulength
13081 \settowidth{\@tempdimb}{\@currDisplay}%
13082 \ifdim\@tempdimb>\@tempdima\@tempdima\@tempdimb\fi
13083 }%
13084 \advance\@tempdima by 15\p@
13085 \begingroup
13086 \HyField@SetKeys{#1}%

```

```

13087 \edef\x{\endgroup
13088 \noexpand\expandafter
13089 \noexpand\HyField@SetKeys
13090 \noexpand\expandafter{%
13091 \expandafter\noexpand\csname DefaultOptionsof%
13092 \ifFld@radio
13093 Radio%
13094 \else
13095 \ifFld@combo
13096 \ifFld@popdown
13097 PopdownBox%
13098 \else
13099 ComboBox%
13100 \fi
13101 \else
13102 ListBox%
13103 \fi
13104 \fi
13105 \endcsname
13106 }%
13107 }\x
13108 \HyField@SetKeys{#1}%
13109 \ifFld@hidden\def\Fld@width{1sp}\fi
13110 \ifx\Fld@value\relax
13111 \let\Fld@value\Fld@default
13112 \fi
13113 \LayoutChoiceField{#2}{%
13114 \ifFld@radio
13115 \HyField@FlagsRadioButton
13116 \@@Radio{#3}%
13117 \else
13118 \begingroup
13119 \HyField@FlagsChoice
13120 \ifdim\Fld@width<\@tempdima
13121 \ifdim\@tempdima<1cm\@tempdima1cm\fi
13122 \edef\Fld@width{\the\@tempdima}%
13123 \fi
13124 \ifFld@combo
13125 \else
13126 \@tempdima=\the\Fld@menulength\Fld@charsize
13127 \advance\@tempdima by \Fld@borderwidth bp %
13128 \advance\@tempdima by \Fld@borderwidth bp %
13129 \edef\Fld@height{\the\@tempdima}%
13130 \fi
13131 \@@ListBox{#3}%
13132 \endgroup
13133 \fi
13134 }%
13135 \endgroup
13136 }
13137 \def\@@Radio#1{%
13138 \Fld@listcount=0 %
13139 \EdefEscapeName\Fld@default{\Fld@default}%
13140 \@for\@curropt:=#1\do{%
13141 \expandafter\Fld@checkequals\@curropt==\%
13142 \EdefEscapeName\@currValue{\@currValue}%
13143 \Hy@StepCount\Fld@listcount

```

```

13144 \currDisplay\space
13145 \Hy@escapeform\PDFForm@Radio
13146 \pdfmark[\MakeRadioField{\Fld@width}{\Fld@height}]{%
13147 pdfmark=/ANN,%
13148 Raw={%
13149 \PDFForm@Radio /AP <</N <</\currValue\space {Check}>> >>%
13150 }%
13151 } % deliberate space between radio buttons
13152 }%
13153 }
13154 \newcount\Fld@listcount
13155 \def\@@Listbox#1{%
13156 \HyField@PDFChoices{#1}%
13157 \Hy@escapeform\PDFForm@List
13158 \pdfmark[\MakeChoiceField{\Fld@width}{\Fld@height}]{%
13159 pdfmark=/ANN,Raw={\PDFForm@List}%
13160 }%
13161 }
13162 \def\@PushButton[#1]#2{% parameters, label
13163 \def\Fld@name{#2}%
13164 \begingroup
13165 \expandafter\HyField@SetKeys\expandafter{%
13166 \DefaultOptionsofPushButton,#1%
13167 }%
13168 \ifHy@pdfa
13169 \Hy@Error{%
13170 PDF/A: Push button with JavaScript is prohibited%
13171 } \@ehc
13172 \LayoutPushButtonField{%
13173 \leavevmode
13174 \MakeButtonField{#2}%
13175 }%
13176 \else
13177 \HyField@FlagsPushButton
13178 \ifFld@hidden\def\Fld@width{1sp}\fi
13179 \LayoutPushButtonField{%
13180 \leavevmode
13181 \Hy@escapeform\PDFForm@Push
13182 \pdfmark[\MakeButtonField{#2}]{%
13183 pdfmark=/ANN,Raw={\PDFForm@Push}%
13184 }%
13185 }%
13186 \fi
13187 \endgroup
13188 }
13189 \def\@Submit[#1]#2{%
13190 \def\Fld@width{\DefaultWidthofSubmit}%
13191 \def\Fld@height{\DefaultHeightofSubmit}%
13192 \begingroup
13193 \expandafter\HyField@SetKeys\expandafter{%
13194 \DefaultOptionsofSubmit,#1%
13195 }%
13196 \HyField@FlagsPushButton
13197 \HyField@FlagsSubmit
13198 \ifFld@hidden\def\Fld@width{1sp}\fi
13199 \Hy@escapeform\PDFForm@Submit
13200 \pdfmark[\MakeButtonField{#2}]{%

```

```

13201 pdfmark=/ANN,%
13202 Raw={\PDFForm@Submit /AP << /N {Submit} /D {SubmitP} >>}%
13203 }%
13204 \endgroup
13205 }
13206 \def\@Reset[#1]#2{%
13207 \def\Fld@width{\DefaultWidthofReset}%
13208 \def\Fld@height{\DefaultHeightofReset}%
13209 \begingroup
13210 \expandafter\HyField@SetKeys\expandafter{%
13211 \DefaultOptionsofReset,#1%
13212 }%
13213 \leavevmode
13214 \ifHy@pdfa
13215 \Hy@Error{%
13216 PDF/A: Reset action is prohibited%
13217 } \@ehc
13218 \MakeButtonField{#2}%
13219 \else
13220 \HyField@FlagsPushButton
13221 \ifFld@hidden\def\Fld@width{1sp}\fi
13222 \Hy@escapeform\PDFForm@Reset
13223 \pdfmark[\MakeButtonField{#2}]{%
13224 pdfmark=/ANN,Raw={\PDFForm@Reset}%
13225 }%
13226 \fi
13227 \endgroup
13228 }%
13229 \def\@CheckBox[#1]#2{% parameters, label
13230 \def\Fld@name{#2}%
13231 \def\Fld@default{0}%
13232 \begingroup
13233 \def\Fld@width{\DefaultWidthofCheckBox}%
13234 \def\Fld@height{\DefaultHeightofCheckBox}%
13235 \expandafter\HyField@SetKeys\expandafter{%
13236 \DefaultOptionsofCheckBox,#1%
13237 }%
13238 \HyField@FlagsCheckBox
13239 \ifFld@hidden\def\Fld@width{1sp}\fi
13240 \LayoutCheckField{#2}{%
13241 \leavevmode
13242 \Hy@escapeform\PDFForm@Check
13243 \pdfmark[\MakeCheckField{\Fld@width}{\Fld@height}]{%
13244 pdfmark=/ANN,Raw={\PDFForm@Check}%
13245 }%
13246 }%
13247 \endgroup
13248 }
13249 \pdfmark>

```

48.2 HyperTeX

```

13250 \*hypertex>
13251 \def\@Form[#1]{%
13252 \Hy@Message{Sorry, HyperTeX does not support FORMs}%
13253 }
13254 \let\@endForm\tx@empty
13255 \def\@Gauge[#1]#2#3#4{% parameters, label, minimum, maximum

```

```

13256 \Hy@Message{Sorry, HyperTeX does not support FORM gauges}%
13257 }
13258 \def\@TextField[#1]#2{% parameters, label
13259 \Hy@Message{Sorry, HyperTeX does not support FORM text fields}%
13260 }
13261 \def\@CheckBox[#1]#2{% parameters, label
13262 \Hy@Message{Sorry, HyperTeX does not support FORM checkboxes}%
13263 }
13264 \def\@ChoiceMenu[#1]#2#3{% parameters, label, choices
13265 \Hy@Message{Sorry, HyperTeX does not support FORM choice menus}%
13266 }
13267 \def\@PushButton[#1]#2{% parameters, label
13268 \Hy@Message{Sorry, HyperTeX does not support FORM pushbuttons}%
13269 }
13270 \def\@Reset[#1]#2{%
13271 \Hy@Message{Sorry, HyperTeX does not support FORMs}%
13272 }
13273 \def\@Submit[#1]#2{%
13274 \Hy@Message{Sorry, HyperTeX does not support FORMs}%
13275 }
13276 \</hypertex>

```

48.3 TeX4ht

```

13277 (*tex4ht)
13278 \def\@Form[#1]{%
13279 \kvsetkeys{Form}{#1}%
13280 \HCode{<form action="\Form@action" method="\Form@method">}%
13281 }
13282 \def\@endForm{\HCode{</form>}}
13283 \def\@Gauge[#1]#2#3#4{% parameters, label, minimum, maximum
13284 \Hy@Message{Sorry, TeX4ht does not support gauges}%
13285 }
13286 \def\@TextField[#1]#2{% parameters, label
13287 \let\Hy@reserved@a\@empty
13288 \def\Fld@name{#2}%
13289 \let\Fld@default\ltx@empty
13290 \bgroup
13291 \Field@toks={ }%
13292 \kvsetkeys{Field}{#1}%
13293 \HCode{<label for="\Fld@name">#2</label>}%
13294 \ifFld@password
13295 \@@PasswordField
13296 \else
13297 \@@TextField
13298 \fi
13299 \egroup
13300 }
13301 \def\@@PasswordField{%
13302 \HCode{%
13303 <input type="password" %
13304 id="\Fld@name" %
13305 name="\Fld@name" %
13306 \ifFld@hidden type="hidden" \fi
13307 value="\Fld@default" %
13308 \the\Field@toks
13309 >%
13310 }%

```

```

13311 }
13312 \def\@@TextField{%
13313   \ifFld@multiline
13314     \HCode{<textarea %
13315       \ifFld@readonly readonly \fi
13316       id="\Fld@name" %
13317       name="\Fld@name" %
13318       \ifFld@hidden type="hidden" \fi
13319       \the\Field@toks>%
13320   }%
13321   \Fld@default
13322   \HCode{</textarea>}%
13323 \else
13324   \HCode{<input type="text" %
13325     \ifFld@readonly readonly \fi
13326     id="\Fld@name" %
13327     name="\Fld@name" %
13328     \ifFld@hidden type="hidden" \fi
13329     value="\Fld@default" %
13330     \the\Field@toks>%
13331   }%
13332 \fi
13333 }
13334 \def\@ChoiceMenu[#1]#2#3{% parameters, label, choices
13335   \def\Fld@name{#2}%
13336   \let\Fld@default\tx@empty
13337   \let\Hy@reserved@a\relax
13338   \begingroup
13339     \expandafter\Fld@findlength#3\\%
13340     \Field@toks={ }%
13341     \kvsetkeys{Field}{#1}%
13342     #2%
13343     \ifFld@radio
13344       \expandafter\@@Radio#3\\%
13345     \else
13346       \expandafter\@@Menu#3\\%
13347     \fi
13348   \endgroup
13349 }
13350 \def\Fld@findlength#1\\{%
13351   \Fld@menulength=0 %
13352   \@for\@curropt:=#1\do{\Hy@StepCount\Fld@menulength}%
13353 }
13354 \def\@@Menu#1\\{%
13355   \HCode{<select size="\the\Fld@menulength" %
13356     name="\Fld@name" %
13357     \the\Field@toks>%
13358   }%
13359   \@for\@curropt:=#1\do{%
13360     \expandafter\Fld@checkequals\@curropt==\\%
13361     \HCode{<option %
13362       \ifx\@curropt\Fld@default selected \fi
13363       value="\@currValue">\@currDisplay</option>%
13364     }%
13365   }%
13366   \HCode{</select>}%
13367 }

```

```

13368 \def\@@Radio#1\{\%
13369   \@for\@curropt:=#1\do{\%
13370     \expandafter\Fld@checkequals\@curropt==\%
13371     \HCode{<input type="radio" \%
13372       \ifx\@curropt\Fld@default checked \fi
13373       name="\Fld@name" \%
13374       value="\@currValue" \%
13375       \the\Field@toks>\%
13376     }%
13377     \@currDisplay
13378   }%
13379 }
13380 \def\@PushButton[#1]#2{\% parameters, label
13381   \def\Fld@name{#2}%
13382   \bgroup
13383     \Field@toks={ }%
13384     \kvsetkeys{Field}{#1}%
13385     \HCode{<input type="button" \%
13386       name="\Fld@name" \%
13387       value="#2" \%
13388       \the\Field@toks>\%
13389     }%
13390     \HCode{</button>}%
13391   \egroup
13392 }
13393 \def\@Submit[#1]#2{\%
13394   \HCode{<button type="submit">#2</button>}%
13395 }
13396 \def\@Reset[#1]#2{\%
13397   \HCode{<button type="reset">#2</button>}%
13398 }
13399 \def\@CheckBox[#1]#2{\% parameters, label
13400   \let\Hy@reserved@a\@empty
13401   \def\Fld@name{#2}%
13402   \def\Fld@default{0}%
13403   \bgroup
13404     \Field@toks={ }%
13405     \kvsetkeys{Field}{#1}%
13406     \HCode{<input type="checkbox" \%
13407       \ifFld@checked checked \fi
13408       \ifFld@disabled disabled \fi
13409       \ifFld@readonly readonly \fi
13410       name="\Fld@name" \%
13411       \ifFld@hidden type="hidden" \fi
13412       value="\Fld@default" \%
13413       \the\Field@toks>\%
13414     #2%
13415   }%
13416   \egroup
13417 }
13418 </tex4ht>

```

48.4 pdfTeX

```

13419 <*pdfTeX>
13420 \def\@Gauge[#1]#2#3#4{\% parameters, label, minimum, maximum
13421   \Hy@Message{Sorry, pdfTeX does not support FORM gauges}%
13422 }

```



```

13423 \def\MakeFieldObject#1#2{\sbox0{#1}%
13424 \immediate\pdfxform0 %
13425 \expandafter\edef\csname #2Object\endcsname{%
13426 \the\pdfastxform\space 0 R%
13427 }%
13428 % \hbox to 0pt{\hskip-\maxdimen{\pdfrefxform \the\pdfastxform}}%
13429 }%
13430 \let\HyField@afields\ltx@empty
13431 \begingroup\expandafter\expandafter\expandafter\endgroup
13432 \expandafter\ifx\csname pdfastlink\endcsname\relax
13433 \let\HyField@AddToFields\relax
13434 \PackageInfo{hyperref}{%
13435 You need pdfTeX 1.40.0 for setting the /Fields entry.%
13436 \MessageBreak
13437 Adobe Reader/Acrobat accepts an empty /Field array,%
13438 \MessageBreak
13439 but other PDF viewers might complain%
13440 }%
13441 \else
13442 \let\HyField@AuxAddToFields\ltx@gobble
13443 \def\HyField@AfterAuxOpen{\Hy@AtBeginDocument}%
13444 \Hy@AtBeginDocument{%
13445 \if@filesw
13446 \immediate\write\@mainaux{%
13447 \string\providecommand\string\HyField@AuxAddToFields[1]{}%
13448 }%
13449 \fi
13450 \let\HyField@AfterAuxOpen\@firstofone
13451 \def\HyField@AuxAddToFields#1{%
13452 \xdef\HyField@afields{%
13453 \ifx\HyField@afields\@empty
13454 \else
13455 \HyField@afields
13456 \space
13457 \fi
13458 #1 0 R%
13459 }%
13460 }%
13461 }%
13462 \def\HyField@AddToFields{%
13463 \expandafter\HyField@@AddToFields\expandafter{%
13464 \the\pdfastlink
13465 }%
13466 }%
13467 \def\HyField@@AddToFields#1{%
13468 \HyField@AfterAuxOpen{%
13469 \if@filesw
13470 \write\@mainaux{%
13471 \string\HyField@AuxAddToFields{#1}%
13472 }%
13473 \fi
13474 }%
13475 }%
13476 \fi
13477 \def\@Form[#1]{%
13478 \@ifundefined{textcolor}{\let\textcolor\@gobble}{}%
13479 \kvsetkeys{Form}{#1}%

```

```

13480 \pdf@ifdraftmode{}{%
13481 \Hy@FormObjects
13482 \ifnum\pdftexversion>13 %
13483 \pdfrefobj\OBJ@pdfdocencoding
13484 \pdfrefobj\OBJ@ZaDb
13485 \pdfrefobj\OBJ@Helv
13486 \fi
13487 \AtVeryEndDocument{%
13488 \immediate\pdfobj{%
13489 <<%
13490 /Fields[\HyField@afields]%
13491 /DR<<%
13492 /Font<<%
13493 /ZaDb \OBJ@ZaDb\space 0 R%
13494 /Helv \OBJ@Helv\space 0 R%
13495 >>%
13496 >>%
13497 /DA(/Helv 10 Tf 0 g)%
13498 \ifHy@pdfa
13499 \else
13500 \ifHyField@NeedAppearances
13501 /NeedAppearances true%
13502 \fi
13503 \fi
13504 >>%
13505 }%
13506 \edef\OBJ@acroform{\the\pdfflastobj}%
13507 \pdfcatalog{/AcroForm \OBJ@acroform\space 0 R}%
13508 }%
13509 }%
13510 \MakeFieldObject{%

```

Same as \ding{123} of package pifont.

```

13511 \begingroup
13512 \fontfamily{pzd}%
13513 \fontencoding{U}%
13514 \fontseries{m}%
13515 \fontshape{n}%
13516 \selectfont
13517 \char123 %
13518 \endgroup
13519 }{Ding}%
13520 \MakeFieldObject{%
13521 \fbox{\textcolor{yellow}{\textsf{Submit}}}%
13522 }{Submit}%
13523 \MakeFieldObject{%
13524 \fbox{\textcolor{yellow}{\textsf{SubmitP}}}%
13525 }{SubmitP}%
13526 }
13527 \let\@endForm\ltx@empty
13528 \let\HyAnn@AbsPageLabel\ltx@empty
13529 \let\Fld@pageobjref\ltx@empty
13530 \ltx@ifundefined{pdfpageref}{%
13531 }{%
13532 \ltx@ifpackageloaded{zref-abspage}{%
13533 \newcount\HyAnn@Count
13534 \HyAnn@Count=\ltx@zero
13535 \def\HyAnn@AbsPageLabel{%

```

```

13536 \global\advance\HyAnn@Count by\ltx@one
13537 \zref@labelbyprops{HyAnn@\the\HyAnn@Count}{abspage}%
13538 \zref@refused{HyAnn@\the\HyAnn@Count}%
13539 }%
13540 \def\Fld@pageobjref{%
13541 \zref@ifrefundefined{HyAnn@\the\HyAnn@Count}{%
13542 }{%
13543 \zref@ifrefcontainsprop{HyAnn@\the\HyAnn@Count}{abspage}{%
13544 /P \pdfpageref
13545 \zref@extractdefault{HyAnn@\the\HyAnn@Count}{abspage}{1} %
13546 \space 0 R%
13547 }{%
13548 }%
13549 }%
13550 }%
13551 }{%
13552 }%
13553 }

13554 \def\@TextField[#1]#2{% parameters, label
13555 \def\Fld@name{#2}%
13556 \let\Fld@default\ltx@empty
13557 \let\Fld@value\@empty
13558 \def\Fld@width{\DefaultWidthofText}%
13559 \def\Fld@height{%
13560 \ifFld@multiline
13561 \DefaultHeightofTextMultiline
13562 \else
13563 \DefaultHeightofText
13564 \fi
13565 }%
13566 \begingroup
13567 \expandafter\HyField@SetKeys\expandafter{%
13568 \DefaultOptionsofText,#1%
13569 }%
13570 \PDFForm@Name
13571 \HyField@FlagsText
13572 \ifFld@hidden\def\Fld@width{1sp}\fi
13573 \ifx\Fld@value\@empty\def\Fld@value{\Fld@default}\fi
13574 \LayoutTextField{#2}{%
13575 \leavevmode
13576 \HyAnn@AbsPageLabel
13577 \Hy@escapeform\PDFForm@Text
13578 \pdfstartlink user {\PDFForm@Text}\relax
13579 \MakeTextField{\Fld@width}{\Fld@height}\pdfendlink
13580 \HyField@AddToFields
13581 }%
13582 \endgroup
13583 }

13584 \def\@ChoiceMenu[#1]#2#3{% parameters, label, choices
13585 \def\Fld@name{#2}%
13586 \let\Fld@default\relax
13587 \let\Fld@value\relax
13588 \def\Fld@width{\DefaultWidthofChoiceMenu}%
13589 \def\Fld@height{\DefaultHeightofChoiceMenu}%
13590 \begingroup
13591 \Fld@menulength=0 %
13592 \@tempdima\z@

```

```

13593 \@for\@curropt:=#3\do{%
13594 \expandafter\Fld@checkequals\@curropt==\\%
13595 \Hy@StepCount\Fld@menulength
13596 \settowidth{\@tempdimb}{\@currDisplay}%
13597 \ifdim\@tempdimb>\@tempdima\@tempdima\@tempdimb\fi
13598 }%
13599 \advance\@tempdima by 15\p@
13600 \begingroup
13601 \HyField@SetKeys{#1}%
13602 \edef\x{\endgroup
13603 \noexpand\expandafter
13604 \noexpand\HyField@SetKeys
13605 \noexpand\expandafter{%
13606 \expandafter\noexpand\csname DefaultOptionsof%
13607 \ifFld@radio
13608 Radio%
13609 \else
13610 \ifFld@combo
13611 \ifFld@popdown
13612 PopdownBox%
13613 \else
13614 ComboBox%
13615 \fi
13616 \else
13617 ListBox%
13618 \fi
13619 \fi
13620 \endcsname
13621 }%
13622 }\x
13623 \HyField@SetKeys{#1}%
13624 \PDFForm@Name
13625 \ifFld@hidden\def\Fld@width{1sp}\fi
13626 \ifx\Fld@value\relax
13627 \let\Fld@value\Fld@default
13628 \fi
13629 \LayoutChoiceField{#2}{%
13630 \ifFld@radio
13631 \HyField@FlagsRadioButton
13632 \@@Radio{#3}%
13633 \else
13634 \begingroup
13635 \HyField@FlagsChoice
13636 \ifdim\Fld@width<\@tempdima
13637 \ifdim\@tempdima<1cm\@tempdima1cm\fi
13638 \edef\Fld@width{\the\@tempdima}%
13639 \fi
13640 \ifFld@combo
13641 \else
13642 \@tempdima=\the\Fld@menulength\Fld@charsize
13643 \advance\@tempdima by \Fld@borderwidth bp %
13644 \advance\@tempdima by \Fld@borderwidth bp %
13645 \edef\Fld@height{\the\@tempdima}%
13646 \fi
13647 \@@Listbox{#3}%
13648 \endgroup
13649 \fi

```

```

13650 }%
13651 \endgroup
13652 }
13653 \def\@@Radio#1{%
13654 \Fld@listcount=0 %
13655 \EdefEscapeName\Fld@default{\Fld@default}%
13656 \@for\@curropt:=#1\do{%
13657 \expandafter\Fld@checkequals\@curropt==\\%
13658 \EdefEscapeName\@currValue{\@currValue}%
13659 \Hy@StepCount\Fld@listcount
13660 \@currDisplay\space
13661 \leavevmode
13662 \HyAnn@AbsPageLabel
13663 \Hy@escapeform\PDFForm@Radio
13664 \pdfstartlink user {%
13665 \PDFForm@Radio
13666 /AP<<%
13667 /N<<%

```

Laurent.Guillope@math.univ-nantes.fr (Laurent Guillope) persuades me that this was wrong: `/\Fld@name\the\Fld@listcount`. But I leave it here to remind me that it is untested.

```

13668 /\@currValue\space \DingObject
13669 >>%
13670 >>%
13671 }%
13672 \relax
13673 \MakeRadioField{\Fld@width}{\Fld@height}\pdfendlink
13674 \ifnum\Fld@listcount=1 %
13675 \HyField@AddToFields
13676 \fi
13677 \space % deliberate space between radio buttons
13678 }%
13679 }
13680 \newcount\Fld@listcount
13681 \def\@@Listbox#1{%
13682 \HyField@PDFChoices{#1}%
13683 \leavevmode
13684 \HyAnn@AbsPageLabel
13685 \Hy@escapeform\PDFForm@List
13686 \pdfstartlink user {\PDFForm@List}\relax
13687 \MakeChoiceField{\Fld@width}{\Fld@height}%
13688 \pdfendlink
13689 \HyField@AddToFields
13690 }
13691 \def\@PushButton[#1]#2{% parameters, label
13692 \def\Fld@name{#2}%
13693 \begingroup
13694 \expandafter\HyField@SetKeys\expandafter{%
13695 \DefaultOptionsofPushButton,#1%
13696 }%
13697 \PDFForm@Name
13698 \ifHy@pdfa
13699 \Hy@Error{%
13700 PDF/A: Push button with JavaScript is prohibited%
13701 }\@ehc
13702 \LayoutPushButtonField{%
13703 \leavevmode

```

```

13704     \MakeButtonField{#2}%
13705 }%
13706 \else
13707     \HyField@FlagsPushButton
13708     \ifFld@hidden\def\Fld@width{1sp}\fi
13709     \LayoutPushButtonField{%
13710         \leavevmode
13711         \HyAnn@AbsPageLabel
13712         \Hy@escapeform\PDFForm@Push
13713         \pdfstartlink user {\PDFForm@Push}\relax
13714         \MakeButtonField{#2}%
13715         \pdfendlink
13716         \HyField@AddToFields
13717     }%
13718 \fi
13719 \endgroup
13720 }
13721 \def\@Submit[#1]#2{%
13722     \def\Fld@width{\DefaultWidthofSubmit}%
13723     \def\Fld@height{\DefaultHeightofSubmit}%
13724     \begingroup
13725         \expandafter\HyField@SetKeys\expandafter{%
13726             \DefaultOptionsofSubmit,#1%
13727         }%
13728         \HyField@FlagsPushButton
13729         \HyField@FlagsSubmit
13730         \ifFld@hidden\def\Fld@width{1sp}\fi
13731         \leavevmode
13732         \HyAnn@AbsPageLabel
13733         \Hy@escapeform\PDFForm@Submit
13734         \pdfstartlink user {%
13735             \PDFForm@Submit
13736             /AP<</N \SubmitObject/D \SubmitPObject>>%
13737         }%
13738         \relax
13739         \MakeButtonField{#2}%
13740         \pdfendlink
13741         \HyField@AddToFields
13742     \endgroup
13743 }
13744 \def\@Reset[#1]#2{%
13745     \def\Fld@width{\DefaultWidthofReset}%
13746     \def\Fld@height{\DefaultHeightofReset}%
13747     \begingroup
13748         \expandafter\HyField@SetKeys\expandafter{%
13749             \DefaultOptionsofReset,#1%
13750         }%
13751         \leavevmode
13752         \ifHy@pdfa
13753             \Hy@Error{%
13754                 PDF/A: Reset action is prohibited%
13755             }\@ehc
13756             \MakeButtonField{#2}%
13757         \else
13758             \HyField@FlagsPushButton
13759             \ifFld@hidden\def\Fld@width{1sp}\fi
13760             \HyAnn@AbsPageLabel

```

```

13761 \Hy@escapeform\PDFForm@Reset
13762 \pdfstartlink user {\PDFForm@Reset}\relax
13763 \MakeButtonField{#2}%
13764 \pdfendlink
13765 \HyField@AddToFields
13766 \fi
13767 \endgroup
13768 }
13769 \def\@CheckBox[#1]#2{% parameters, label
13770 \def\Fld@name{#2}%
13771 \def\Fld@default{0}%
13772 \begingroup
13773 \def\Fld@width{\DefaultWidthofCheckBox}%
13774 \def\Fld@height{\DefaultHeightofCheckBox}%
13775 \expandafter\HyField@SetKeys\expandafter{%
13776 \DefaultOptionsofCheckBox,#1%
13777 }%
13778 \PDFForm@Name
13779 \HyField@FlagsCheckBox
13780 \ifFld@hidden\def\Fld@width{1sp}\fi
13781 \LayoutCheckField{#2}{%
13782 \leavevmode
13783 \HyAnn@AbsPageLabel
13784 \Hy@escapeform\PDFForm@Check
13785 \pdfstartlink user {\PDFForm@Check}\relax
13786 \MakeCheckField{\Fld@width}{\Fld@height}%
13787 \pdfendlink
13788 \HyField@AddToFields
13789 }%
13790 \endgroup
13791 }
13792 \def\Hy@FormObjects{%
13793 \pdfobj {%
13794 <<%
13795 /Type/Encoding%
13796 /Differences%
13797 24/breve/caron/circumflex/dotaccent/hungarumlaut/ogonek%
13798 /ring/tilde %
13799 39/quotesingle %
13800 96/grave %
13801 128/bullet/dagger/daggerdbl/ellipsis/emdash/endash/florin%
13802 /fraction/guilsinglleft/guilsinglright/minus/perthousand%
13803 /quotedblbase/quotedblleft/quotedblright/quoteleft%
13804 /quoteright/quotesinglbase/trademark/fi/fl/Lslash/OE%
13805 /Scaron/Ydieresis/Zcaron/dotlessi/lslash/oe/scaron/zcaron %
13806 164/currency %
13807 166/brokenbar %
13808 168/dieresis/copyright/ordfeminine %
13809 172/logicalnot/.notdef/registered/macron/degree/plusminus%
13810 /twosuperior/threesuperior/acute/mu %
13811 183/periodcentered/cedilla/onesuperior/ordmasculine %
13812 188/onequarter/onehalf/threequarters %
13813 192/Agrave/Aacute/Acircumflex/Atilde/Adieresis/Aring/AE%
13814 /Ccedilla/Egrave/Eacute/Ecircumflex/Edieresis/Igrave%
13815 /Iacute/Icircumflex/Idieresis/Eth/Ntilde/Ograve/Oacute%
13816 /Ocircumflex/Otilde/Odieresis/multiply/Oslash/Ugrave%
13817 /Uacute/Ucircumflex/Udieresis/Yacute/Thorn/germandbls%

```

```

13818      /grave/aacute/acircumflex/atilde/adieresis/aring/ae%
13819      /cedilla/egrave/eacute/ecircumflex/edieresis/igrave%
13820      /iacute/icircumflex/idieresis/eth/ntilde/ograde/oacute%
13821      /ocircumflex/otilde/odieresis/divide/oshlash/ugrave%
13822      /uacute/ucircumflex/udieresis/yacute/thorn/ydieresis%
13823      ]%
13824      >>%
13825      }%
13826      \xdef\OBJ@pdfdocencoding{\the\pdflastobj}%
13827      \pdfobj{%
13828      <<%
13829      /Type/Font%
13830      /Subtype/Type1%
13831      /Name/ZaDb%
13832      /BaseFont/ZapfDingbats%
13833      >>%
13834      }%
13835      \xdef\OBJ@ZaDb{\the\pdflastobj}%
13836      \pdfobj{%
13837      <<%
13838      /Type/Font%
13839      /Subtype/Type1%
13840      /Name/Helv%
13841      /BaseFont/Helvetica%
13842      /Encoding \OBJ@pdfdocencoding\space 0 R%
13843      >>%
13844      }%
13845      \xdef\OBJ@Helv{\the\pdflastobj}%
13846      \global\let\Hy@FormObjects\relax
13847      }
13848      </pdfTeX>

```

48.5 dvipdfm, xetex

D. P. Story adapted the pdf_TE_X forms part for dvipdfm, of which version 0.12.7b or higher is required because of a bug.

```
13849 <{*dvipdfm | xetex}>
```

\@Gauge

```

13850 \def\@Gauge[#1]#2#3#4{% parameters, label, minimum, maximum
13851   \Hy@Message{Sorry, dvipdfm/XeTeX does not support FORM gauges}%
13852 }

```

\@Form

```

13853 \def\@Form[#1]{%
13854   \@ifundefined{textcolor}{\let\textcolor\@gobble}{}%
13855   \kvsetkeys{Form}{#1}%
13856   \Hy@FormObjects
13857   \@pdfm@mark{obj @afields []}%
13858   \@pdfm@mark{obj @corder []}%
13859   \@pdfm@mark{%
13860     obj @aform <<%
13861     /Fields @afields%
13862     /DR<<%
13863     /Font<<%
13864     /ZaDb @OBJZaDb%
13865     /Helv @OBJHelv%
13866     >>%

```



```

13867    >>%
13868    /DA(/Helv 10 Tf 0 g)%
13869    /CO @corder%
13870    \ifHy@pdfa
13871    \else
13872    \ifHyField@NeedAppearances
13873    /NeedAppearances true%
13874    \fi
13875    \fi
13876    >>%
13877    }%
13878    \@pdfm@mark{put @catalog <</AcroForm @aform>>}%
13879    }

```

\@endForm

```

13880 \let\@endForm\ltx@empty

```

\dvipdfm@setdim \dvipdfm@setdim sets dimensions for ann using \pdfm@box.

```

13881 \def\dvipdfm@setdim{%
13882   height \the\ht\pdfm@box\space
13883   width \the\wd\pdfm@box\space
13884   depth \the\dp\pdfm@box\space
13885 }

```

\HyField@AnnotCount

```

13886 \newcount\HyField@AnnotCount
13887 \HyField@AnnotCount=\z@

```

\HyField@AdvanceAnnotCount

```

13888 \def\HyField@AdvanceAnnotCount{%
13889   \global\advance\HyField@AnnotCount\@ne
13890 }

```

\HyField@TheAnnotCount

```

13891 \def\HyField@TheAnnotCount{%
13892   \the\HyField@AnnotCount
13893 }

```

\Fld@pageobjref

```

13894 \def\Fld@pageobjref{/P @thispage}%

```

\@TextField

```

13895 \def\@TextField[#1]#2{% parameters, label
13896   \def\Fld@name{#2}%
13897   \let\Fld@default\ltx@empty
13898   \let\Fld@value\@empty
13899   \def\Fld@width{\DefaultWidthofText}%
13900   \def\Fld@height{%
13901     \ifFld@multiline
13902       \DefaultHeightofTextMultiline
13903     \else
13904       \DefaultHeightofText
13905     \fi
13906   }%
13907   \begingroup
13908     \expandafter\HyField@SetKeys\expandafter{%

```

```

13909 \DefaultOptionsofText,#1%
13910 }%
13911 \PDFForm@Name
13912 \HyField@FlagsText
13913 \ifFld@hidden\def\Fld@width{1sp}\fi
13914 \ifx\Fld@value\empty\def\Fld@value{\Fld@default}\fi
13915 \setbox\pdfm@box=\hbox{%
13916 \MakeTextField{\Fld@width}{\Fld@height}%
13917 }%
13918 \HyField@AdvanceAnnotCount
13919 \LayoutTextField{#2}{%
13920 \leavevmode
13921 \Hy@escapeform\PDFForm@Text
13922 \@pdfm@mark{%
13923 ann @text\HyField@TheAnnotCount\space
13924 \dvipdfm@setdim << \PDFForm@Text >>%
13925 }%
13926 }%
13927 \unhbox\pdfm@box
13928 \@pdfm@mark{put @afields @text\HyField@TheAnnotCount}%
13929 % record in @afields array
13930 \endgroup
13931 }

```

\@ChoiceMenu

```

13932 \def\@ChoiceMenu[#1]#2#3{% parameters, label, choices
13933 \def\Fld@name{#2}%
13934 \let\Fld@default\relax
13935 \let\Fld@value\relax
13936 \def\Fld@width{\DefaultWidthofChoiceMenu}%
13937 \def\Fld@height{\DefaultHeightofChoiceMenu}%
13938 \begingroup
13939 \Fld@menulength=0 %
13940 \@tempdima\z@
13941 \@for\@curropt:=#3\do{%
13942 \expandafter\Fld@checkequals\@curropt==\%
13943 \Hy@StepCount\Fld@menulength
13944 \settowidth{\@tempdimb}{\@currDisplay}%
13945 \ifdim\@tempdimb>\@tempdima\@tempdima\@tempdimb\fi
13946 }%
13947 \advance\@tempdima by 15\p@
13948 \begingroup
13949 \HyField@SetKeys{#1}%
13950 \edef\x{\endgroup
13951 \noexpand\expandafter
13952 \noexpand\HyField@SetKeys
13953 \noexpand\expandafter{%
13954 \expandafter\noexpand\curname DefaultOptionsof%
13955 \ifFld@radio
13956 Radio%
13957 \else
13958 \ifFld@combo
13959 \ifFld@popdown
13960 PopdownBox%
13961 \else
13962 ComboBox%
13963 \fi
13964 \else

```

```

13965         ListBox%
13966     \fi
13967 \fi
13968 \endcsname
13969 }%
13970 }\x
13971 \HyField@SetKeys{#1}%
13972 \PDFForm@Name
13973 \ifFld@hidden\def\Fld@width{1sp}\fi
13974 \ifx\Fld@value\relax
13975     \let\Fld@value\Fld@default
13976 \fi
13977 \LayoutChoiceField{#2}{%
13978     \ifFld@radio
13979         \HyField@FlagsRadioButton
13980         \@@Radio{#3}%
13981     \else
13982         \begingroup
13983         \HyField@FlagsChoice
13984         \ifdim\Fld@width<\@tempdima
13985             \ifdim\@tempdima<1cm\@tempdima1cm\fi
13986             \edef\Fld@width{\the\@tempdima}%
13987         \fi
13988         \ifFld@combo
13989         \else
13990             \@tempdima=\the\Fld@menulength\Fld@charsize
13991             \advance\@tempdima by \Fld@borderwidth bp %
13992             \advance\@tempdima by \Fld@borderwidth bp %
13993             \edef\Fld@height{\the\@tempdima}%
13994         \fi
13995         \@@ListBox{#3}%
13996     \endgroup
13997 \fi
13998 }%
13999 \endgroup
14000 }

```

\@@Radio

```

14001 \def\@@Radio#1{%
14002     \Fld@listcount=0 %
14003     \EdefEscapeName\Fld@default{\Fld@default}%
14004     \setbox\pdfm@box=\hbox{%
14005         \MakeRadioField{\Fld@width}{\Fld@height}%
14006     }%
14007     \@for\@curropt:=#1\do{%
14008         \expandafter\Fld@checkequals\@curropt==\%
14009         \EdefEscapeName\@currValue{\@currValue}%
14010         \Hy@StepCount\Fld@listcount
14011         \@currDisplay\space
14012         \leavevmode
14013         \Hy@escapeform\PDFForm@Radio
14014         \ifnum\Fld@listcount=1 %
14015             \HyField@AdvanceAnnotCount
14016         \fi
14017         \@pdfm@mark{%
14018             ann %
14019             \ifnum\Fld@listcount=1 %
14020                 @radio\HyField@TheAnnotCount%

```

```

14021     \space
14022     \fi
14023     \dviPDFm@setdim
14024     <<%
14025     \PDFForm@Radio
14026     /AP<</N<</\@currValue /null>>>>%
14027     >>%
14028     }%
14029     \unhcopy\pdfm@box\space% deliberate space between radio buttons
14030     \ifnum\Fld@listcount=1 %
14031     \@pdfm@mark{%
14032         put @afields @radio\HyField@TheAnnotCount
14033     }%
14034     \fi
14035 }%
14036 }

\Fld@listcount
14037 \newcount\Fld@listcount

\@@Listbox
14038 \def\@@Listbox#1{%
14039     \HyField@PDFChoices{#1}%
14040     \setbox\pdfm@box=\hbox{%
14041         \MakeChoiceField{\Fld@width}{\Fld@height}%
14042     }%
14043     \leavevmode
14044     \Hy@escapeform\PDFForm@List
14045     \HyField@AdvanceAnnotCount
14046     \@pdfm@mark{%
14047         ann @list\HyField@TheAnnotCount\space
14048         \dviPDFm@setdim
14049         <<\PDFForm@List>>%
14050     }%
14051     \unhbox\pdfm@box
14052     \@pdfm@mark{put @afields @list\HyField@TheAnnotCount}%
14053 }

\@PushButton
14054 \def\@PushButton[#1]#2{% parameters, label
14055     \def\Fld@name{#2}%
14056     \begingroup
14057     \expandafter\HyField@SetKeys\expandafter{%
14058         \DefaultOptionsofPushButton,#1%
14059     }%
14060     \PDFForm@Name
14061     \ifHy@pdfa
14062         \Hy@Error{%
14063             PDF/A: Push button with JavaScript is prohibited%
14064         }\@ehc
14065     \LayoutPushButtonField{%
14066         \leavevmode
14067         \MakeButtonField{#2}%
14068     }%
14069     \else
14070     \setbox\pdfm@box=\hbox{\MakeButtonField{#2}}%
14071     \HyField@FlagsPushButton

```

```

14072 \ifFld@hidden\def\Fld@width{1sp}\fi
14073 \HyField@AdvanceAnnotCount
14074 \LayoutPushButtonField{%
14075 \leavevmode
14076 \Hy@escapeform\PDFForm@Push
14077 \@pdfm@mark{%
14078 ann @push\HyField@TheAnnotCount\space
14079 \dvipdfm@setdim
14080 <<\PDFForm@Push>>%
14081 }%
14082 }%
14083 \unhbox\pdfm@box
14084 \@pdfm@mark{put @afields @push\HyField@TheAnnotCount}%
14085 \fi
14086 \endgroup
14087 }

```

\@Submit

```

14088 \def\@Submit[#1]#2{%
14089 \def\Fld@width{\DefaultWidthofSubmit}%
14090 \def\Fld@height{\DefaultHeightofSubmit}%
14091 \begingroup
14092 \expandafter\HyField@SetKeys\expandafter{%
14093 \DefaultOptionsofSubmit,#1%
14094 }%
14095 \HyField@FlagsPushButton
14096 \HyField@FlagsSubmit
14097 \ifFld@hidden\def\Fld@width{1sp}\fi
14098 \setbox\pdfm@box=\hbox{\MakeButtonField{#2}}%
14099 \leavevmode
14100 \Hy@escapeform\PDFForm@Submit
14101 \HyField@AdvanceAnnotCount
14102 \@pdfm@mark{%
14103 ann @submit\HyField@TheAnnotCount\space
14104 \dvipdfm@setdim
14105 <<\PDFForm@Submit>>%
14106 }%
14107 \unhbox\pdfm@box%
14108 \@pdfm@mark{put @afields @submit\HyField@TheAnnotCount}%
14109 \endgroup
14110 }

```

\@Reset

```

14111 \def\@Reset[#1]#2{%
14112 \def\Fld@width{\DefaultWidthofReset}%
14113 \def\Fld@height{\DefaultHeightofReset}%
14114 \begingroup
14115 \expandafter\HyField@SetKeys\expandafter{%
14116 \DefaultOptionsofReset,#1%
14117 }%
14118 \leavevmode
14119 \ifHy@pdfa
14120 \Hy@Error{%
14121 PDF/A: Reset action is prohibited%
14122 }\@ehc
14123 \MakeButtonField{#2}%
14124 \else

```

```

14125 \HyField@FlagsPushButton
14126 \ifFld@hidden\def\Fld@width{1sp}\fi
14127 \setbox\pdfm@box=\hbox{\MakeButtonField{#2}}}%
14128 \Hy@escapeform\PDFForm@Reset
14129 \HyField@AdvanceAnnotCount
14130 \@pdfm@mark{%
14131   ann @reset\HyField@TheAnnotCount\space
14132   \dvipdfm@setdim
14133   <<\PDFForm@Reset>>%
14134 }%
14135 \unhbox\pdfm@box
14136 \@pdfm@mark{put @afields @reset\HyField@TheAnnotCount}%
14137 \fi
14138 \endgroup
14139 }

```

\@CheckBox

```

14140 \def\@CheckBox[#1]#2{% parameters, label
14141   \def\Fld@name{#2}%
14142   \def\Fld@default{0}%
14143   \begingroup
14144     \def\Fld@width{\DefaultWidthofCheckBox}%
14145     \def\Fld@height{\DefaultHeightofCheckBox}%
14146     \expandafter\HyField@SetKeys\expandafter{%
14147       \DefaultOptionsofCheckBox,#1%
14148     }%
14149     \PDFForm@Name
14150     \HyField@FlagsCheckBox
14151     \ifFld@hidden\def\Fld@width{1sp}\fi
14152     \setbox\pdfm@box=\hbox{%
14153       \MakeCheckField{\Fld@width}{\Fld@height}%
14154     }%
14155     \HyField@AdvanceAnnotCount
14156     \LayoutCheckField{#2}{%
14157       \leavevmode
14158       \Hy@escapeform\PDFForm@Check
14159       \@pdfm@mark{%
14160         ann @check\HyField@TheAnnotCount\space
14161         \dvipdfm@setdim
14162         <<\PDFForm@Check>>%
14163       }%
14164       \unhbox\pdfm@box
14165       \@pdfm@mark{put @afields @check\HyField@TheAnnotCount}%
14166     }%
14167   \endgroup
14168 }

14169 \def\Hy@FormObjects{%
14170   \@pdfm@mark{obj @OBJpdfdocencoding%
14171     <<%
14172       /Type/Encoding%
14173       /Differences[%
14174         24/breve/caron/circumflex/dotaccent/hungarumlaut/ogonek/ring/tilde %
14175         39/quotesingle %
14176         96/grave %
14177         128/bullet/dagger/daggerdbl/ellipsis/emdash/endash/florin%
14178         /fraction/guilsinglleft/guilsinglright/minus/perthousand%
14179         /quotedblbase/quotedblleft/quotedblright/quoteleft/quoteright%

```

```

14180      /quotesinglbase/trademark/fi/fl/Lslash/OE/Scaron/Ydieresis%
14181      /Zcaron/dotlessi/lslash/oe/scaron/zcaron %
14182      164/currency %
14183      166/brokenbar %
14184      168/dieresis/copyright/ordfeminine %
14185      172/logicalnot/.notdef/registered/macron/degree/plusminus%
14186      /twosuperior/threesuperior/acute/mu %
14187      183/periodcentered/cedilla/onesuperior/ordmasculine %
14188      188/onequarter/onehalf/threequarters %
14189      192/Agrave/Aacute/Acircumflex/Atilde/Adieresis/Aring/AE%
14190      /Ccedilla/Egrave/Eacute/Ecircumflex/Edieresis/Igrave/Iacute%
14191      /Icircumflex/Idieresis/Eth/Ntilde/Ograve/Oacute/Ocircumflex%
14192      /Otilde/Odieresis/multiply/Oslash/Ugrave/Uacute/Ucircumflex%
14193      /Udieresis/Yacute/Thorn/germandbls/agrave/aacute/acircumflex%
14194      /atilde/adieresis/aring/ae/ccedilla/egrave/eacute%
14195      /ecircumflex/edieresis/igrave/iacute/icircumflex/idieresis%
14196      /eth/ntilde/ograde/oacute/ocircumflex/otilde/odieresis%
14197      /divide/oslash/ugrave/uacute/ucircumflex/udieresis/yacute%
14198      /thorn/ydieresis%
14199      ]%
14200      >>%
14201      }%
14202      \@pdfm@mark{obj @OBJZaDb%
14203      <<%
14204      /Type/Font%
14205      /Subtype/Type1%
14206      /Name/ZaDb%
14207      /BaseFont/ZapfDingbats%
14208      >>%
14209      }%
14210      \@pdfm@mark{obj @OBJHelv%
14211      <<%
14212      /Type/Font%
14213      /Subtype/Type1%
14214      /Name/Helv%
14215      /BaseFont/Helvetica%
14216      /Encoding @OBJpdfdocencoding%
14217      >>%
14218      }%
14219      \global\let\Hy@FormObjects\relax
14220      }
14221      </dvipdfm | xetex>

```

48.6 Common forms part

```

14222 (*pdfmform)

\Fld@pageobjref

14223 \providecommand*{\Fld@pageobjref}{\}

\Hy@escapestring

14224 \begingroup\expandafter\expandafter\expandafter\endgroup
14225 \expandafter\ifx\csname pdf@escapestring\endcsname\relax
14226   \let\Hy@escapestring\@firstofone
14227   \def\Hy@escapeform#1{%
14228     \ifHy@pdfescapeform
14229     \def\Hy@escapestring##1{%

```

```

14230     \noexpand\Hy@escapestring{\noexpand##1}%
14231 }%
14232 \edef\Hy@temp{#1}%
14233 \expandafter\Hy@@escapeform\Hy@temp\Hy@escapestring{}\@nil
14234 \def\Hy@escapestring##1{%
14235   \@ifundefined{Hy@esc@\string##1}{%
14236     ##1%
14237     \ThisShouldNotHappen
14238   }{%
14239     \csname Hy@esc@\string##1\endcsname
14240   }%
14241 }%
14242 \else
14243   \let\Hy@escapestring\@firstofone
14244 \fi
14245 }%
14246 \def\Hy@@escapeform#1\Hy@escapestring#2#3\@nil{%
14247   \ifx\#3\%
14248   \else
14249     \expandafter
14250     \Hy@pstringdef\csname Hy@esc@\string#2\endcsname{#2}%
14251     \ltx@ReturnAfterFi{%
14252       \Hy@@escapeform#3\@nil
14253     }%
14254   \fi
14255 }%
14256 \else
14257   \def\Hy@escapeform#1{%
14258     \ifHy@pdfescapeform
14259       \let\Hy@escapestring\pdfescapestring
14260     \else
14261       \let\Hy@escapestring\@firstofone
14262     \fi
14263   }%
14264   \Hy@escapeform{}%
14265 \fi

```

\PDFForm@Name

```

14266 \def\PDFForm@Name{%
14267   \PDFForm@@Name\Fld@name
14268   \ifx\Fld@altname\relax
14269   \else
14270     \PDFForm@@Name\Fld@altname
14271   \fi
14272   \ifx\Fld@mappingname\relax
14273   \else
14274     \PDFForm@@Name\Fld@mappingname
14275   \fi
14276 }

```

\PDFForm@@Name

```

14277 \def\PDFForm@@Name#1{%
14278   \begingroup
14279   \ifnum\Hy@pdfversion<5 % implementation note 117, PDF spec 1.7
14280     \ifHy@unicode
14281       \Hy@unicodedefalse
14282     \fi

```



```

14283 \fi
14284 \HyPsd@XeTeXBigCharstrue
14285 \pdfstringdef\Hy@gtemp#1%
14286 \endgroup
14287 \let#1\Hy@gtemp
14288 }

```

\Fld@additionalactions

```

14289 \def\Fld@@additionalactions{%
K input (keystroke) format
14290 \ifx\Fld@keystroke@code\@empty
14291 \else
14292 /K<</S/JavaScript/JS(\Hy@escapestring{\Fld@keystroke@code})>>%
14293 \fi
F display format
14294 \ifx\Fld@format@code\@empty
14295 \else
14296 /F<</S/JavaScript/JS(\Hy@escapestring{\Fld@format@code})>>%
14297 \fi
V validation
14298 \ifx\Fld@validate@code\@empty
14299 \else
14300 /V<</S/JavaScript/JS(\Hy@escapestring{\Fld@validate@code})>>%
14301 \fi
C calculation
14302 \ifx\Fld@calculate@code\@empty
14303 \else
14304 /C<</S/JavaScript/JS(\Hy@escapestring{\Fld@calculate@code})>>%
14305 \fi
Fo receiving the input focus
14306 \ifx\Fld@onfocus@code\@empty
14307 \else
14308 /Fo<</S/JavaScript/JS(\Hy@escapestring{\Fld@onfocus@code})>>%
14309 \fi
Bl loosing the input focus (blurred)
14310 \ifx\Fld@onblur@code\@empty
14311 \else
14312 /Bl<</S/JavaScript/JS(\Hy@escapestring{\Fld@onblur@code})>>%
14313 \fi
D pressing the mouse button (down)
14314 \ifx\Fld@onmousedown@code\@empty
14315 \else
14316 /D<</S/JavaScript/JS(\Hy@escapestring{\Fld@onmousedown@code})>>%
14317 \fi
U releasing the mouse button (up)
14318 \ifx\Fld@onmouseup@code\@empty
14319 \else
14320 /U<</S/JavaScript/JS(\Hy@escapestring{\Fld@onmouseup@code})>>%
14321 \fi
E cursor enters the annotation's active area.
14322 \ifx\Fld@onenter@code\@empty
14323 \else

```

```

14324 /E<</S/JavaScript/JS(\Hy@escapestring{\Fld@onenter@code})>>%
14325 \fi
X cursor exits the annotation's active area.
14326 \ifx\Fld@onexit@code\@empty
14327 \else
14328 /X<</S/JavaScript/JS(\Hy@escapestring{\Fld@onexit@code})>>%
14329 \fi
14330 }
14331 \def\Fld@additionalactions{%
14332 \if\Fld@@additionalactions-%
14333 \else
14334 \ifHy@pdfa
14335 \else
14336 /AA<<\Fld@@additionalactions>>%
14337 \fi
14338 \fi
14339 }

```

\Fld@annotnames

```

14340 \def\Fld@annotnames{%
14341 /T(\Fld@name)%
14342 \ifx\Fld@altname\relax
14343 \else
14344 /TU(\Fld@altname)%
14345 \fi
14346 \ifx\Fld@mappingname\relax
14347 \else
14348 /TM(\Fld@mappingname)%
14349 \fi
14350 }

```

\PDFForm@Check

```

14351 \def\PDFForm@Check{%
14352 /Subtype/Widget%
14353 \Fld@annotflags
14354 \Fld@pageobjref
14355 \Fld@annotnames
14356 /FT/Btn%
14357 \Fld@flags
14358 /Q \Fld@align
14359 /BS<</W \Fld@borderwidth /S/\Fld@borderstyle>>%
14360 /MK<<%
14361 \ifnum\Fld@rotation=\z@
14362 \else
14363 /R \Fld@rotation
14364 \fi
14365 \ifx\Fld@bordercolor\relax
14366 \else
14367 /BC[\Fld@bordercolor]%
14368 \fi
14369 \ifx\Fld@bcolor\relax
14370 \else
14371 /BG[\Fld@bcolor]%
14372 \fi
14373 /CA(\Hy@escapestring{\Fld@cbsymbol})%
14374 >>%
14375 /DA(/ZaDb \strip@pt\Fld@charsize\space Tf%

```

```

14376     \ifx\Fld@color\@empty\else\space\Fld@color\fi)%
14377 /H/P%
14378 \ifFld@checked /V/Yes/AS/Yes\else /V/Off/AS/Off\fi
14379 \Fld@additionalactions
14380 }

```

\PDFForm@Push

```

14381 \ifHy@pdfa
14382 \else
14383   \def\PDFForm@Push{%
14384     /Subtype/Widget%
14385     \Fld@annotflags
14386     \Fld@pageobjref
14387     \Fld@annotnames
14388     /FT/Btn%
14389     \Fld@flags
14390     /H/P%
14391     /BS<</W \Fld@borderwidth/S/\Fld@borderstyle>>%
14392     \ifcase0\ifnum\Fld@rotation=\z@ \else 1\fi
14393       \ifx\Fld@bordercolor\relax\else 1\fi
14394       \space
14395     \else
14396       /MK<<%
14397       \ifnum\Fld@rotation=\z@
14398       \else
14399       /R \Fld@rotation
14400       \fi
14401       \ifx\Fld@bordercolor\relax
14402       \else
14403       /BC[\Fld@bordercolor]%
14404       \fi
14405       >>%
14406     \fi
14407     /A<</S/JavaScript/JS(\Hy@escapestring{\Fld@onclick@code})>>%
14408     \Fld@additionalactions
14409   }%
14410 \fi

```

\PDFForm@List

```

14411 \def\PDFForm@List{%
14412   /Subtype/Widget%
14413   \Fld@annotflags
14414   \Fld@pageobjref
14415   \Fld@annotnames
14416   /FT/Ch%
14417   \Fld@flags
14418   /Q \Fld@align
14419   /BS<</W \Fld@borderwidth/S/\Fld@borderstyle>>%
14420   \ifcase0\ifnum\Fld@rotation=\z@ \else 1\fi
14421     \ifx\Fld@bordercolor\relax\else 1\fi
14422     \ifx\Fld@bcolor\relax \else 1\fi
14423     \space
14424   \else
14425     /MK<<%
14426     \ifnum\Fld@rotation=\z@
14427     \else
14428     /R \Fld@rotation

```

```

14429 \fi
14430 \ifx\Fld@bordercolor\relax
14431 \else
14432 /BC[\Fld@bordercolor]%
14433 \fi
14434 \ifx\Fld@bcolor\relax
14435 \else
14436 /BG[\Fld@bcolor]%
14437 \fi
14438 >>%
14439 \fi
14440 /DA(/Helv \strip@pt\Fld@charsize\space Tf%
14441 \ifx\Fld@color\@empty\else\space\Fld@color\fi)%
14442 \Fld@choices
14443 \Fld@additionalactions
14444 }

```

\PDFForm@Radio

```

14445 \def\PDFForm@Radio{%
14446 /Subtype/Widget%
14447 \Fld@annotflags
14448 \Fld@pageobjref
14449 \Fld@annotnames
14450 /FT/Btn%
14451 \Fld@flags
14452 /H/P%
14453 /BS<</W \Fld@borderwidth/S/\Fld@borderstyle>>%
14454 /MK<<%
14455 \ifnum\Fld@rotation=\z@
14456 \else
14457 /R \Fld@rotation
14458 \fi
14459 \ifx\Fld@bordercolor\relax
14460 \else
14461 /BC[\Fld@bordercolor]%
14462 \fi
14463 \ifx\Fld@bcolor\relax
14464 \else
14465 /BG[\Fld@bcolor]%
14466 \fi
14467 /CA(\Hy@escapestring{\Fld@radiosymbol})%
14468 >>%
14469 /DA(/ZaDb \strip@pt\Fld@charsize\space Tf%
14470 \ifx\Fld@color\@empty\else\space\Fld@color\fi)%
14471 \ifx\@currValue\Fld@default
14472 /V/\Fld@default
14473 /DV/\Fld@default
14474 \else
14475 /V/Off%
14476 /DV/Off%
14477 \fi
14478 \Fld@additionalactions
14479 }

```

\PDFForm@Text

```

14480 \def\PDFForm@Text{%
14481 /Subtype/Widget%

```

```

14482 \Fld@annotflags
14483 \Fld@pageobjref
14484 \Fld@annotnames
14485 /FT/Tx%
14486 \Fld@flags
14487 /Q \Fld@align
14488 /BS<</W \Fld@borderwidth\space /S /\Fld@borderstyle>>%
14489 \ifcase0\ifnum\Fld@rotation=\z@ \else 1\fi
14490     \ifx\Fld@bordercolor\relax\else 1\fi
14491     \ifx\Fld@bcolor\relax \else 1\fi
14492     \space
14493 \else
14494 /MK<<%
14495     \ifnum\Fld@rotation=\z@
14496     \else
14497     /R \Fld@rotation
14498     \fi
14499     \ifx\Fld@bordercolor\relax
14500     \else
14501     /BC[\Fld@bordercolor]%
14502     \fi
14503     \ifx\Fld@bcolor\relax
14504     \else
14505     /BG[\Fld@bcolor]%
14506     \fi
14507 >>%
14508 \fi
14509 /DA(/Helv \strip@pt\Fld@charsize\space Tf%
14510     \ifx\Fld@color\@empty\else\space\Fld@color\fi)%
14511 /DV(\Hy@escapestring{\Fld@default})%
14512 /V(\Hy@escapestring{\Fld@value})%
14513 \Fld@additionalactions
14514 \ifnum\Fld@maxlen>\z@/MaxLen \Fld@maxlen \fi
14515 }

```

\PDFForm@Submit

```

14516 \def\PDFForm@Submit{%
14517 /Subtype/Widget%
14518 \Fld@annotflags
14519 \Fld@pageobjref
14520 \Fld@annotnames
14521 /FT/Btn%
14522 \Fld@flags
14523 /H/P%
14524 /BS<</W \Fld@borderwidth/S/\Fld@borderstyle>>%
14525 \ifcase0\ifnum\Fld@rotation=\z@ \else 1\fi
14526     \ifx\Fld@bordercolor\relax\else 1\fi
14527     \space
14528 \else
14529 /MK<<%
14530     \ifnum\Fld@rotation=\z@
14531     \else
14532     /R \Fld@rotation
14533     \fi
14534     \ifx\Fld@bordercolor\relax
14535     \else
14536     /BC[\Fld@bordercolor]%
14537     \fi

```

```

14538 >>%
14539 \fi
14540 /A<<%
14541 /S/SubmitForm%
14542 /F<<%
14543 /FS/URL%
14544 /F(\Hy@escapestring{\Form@action})%
14545 >>%
14546 \Fld@submitflags
14547 >>%
14548 \Fld@additionalactions
14549 }

```

\PDFForm@Reset

```

14550 \ifHy@pdfa
14551 \else
14552 \def\PDFForm@Reset{%
14553 /Subtype/Widget%
14554 \Fld@annotflags
14555 \Fld@pageobjref
14556 \Fld@annotnames
14557 /FT/Btn%
14558 \Fld@flags
14559 /H/P%
14560 /DA(/Helv \strip@pt\Fld@charsize\space Tf 0 0 1 rg)%
14561 \ifcase0\ifnum\Fld@rotation=\z@ \else 1\fi
14562 \ifx\Fld@bordercolor\relax\else 1\fi
14563 \space
14564 \else
14565 /MK<<%
14566 \ifnum\Fld@rotation=\z@
14567 \else
14568 /R \Fld@rotation
14569 \fi
14570 \ifx\Fld@bordercolor\relax
14571 \else
14572 /BC[\Fld@bordercolor]%
14573 \fi
14574 % /CA (Clear)
14575 % /AC (Done)
14576 >>%
14577 \fi
14578 /BS<</W \Fld@borderwidth/S/\Fld@borderstyle>>%
14579 /A<</S/ResetForm>>%
14580 \Fld@additionalactions
14581 }%
14582 \fi

14583 </pdfform>
14584 <*package>

```

49 Bookmarks in the PDF file

This was originally developed by Yannis Haralambous (it was the separate `repere.sty`); it needed the `repere` or `makebook.pl` post-processor to work properly. Now redundant, as it is done entirely in \LaTeX macros.

To write out the current section title, and its rationalized number, we have to intercept the `\@sect` command, which is rather dangerous. But how else to see the information we need? We do the *same* for `\@ssect`, giving anchors to unnumbered sections. This allows things like bibliographies to get bookmarks when used with a manual `\addcontentsline`

```

14585 \def\phantomsection{%
14586   \Hy@MakeCurrentHrefAuto{section*}%
14587   \Hy@raisedlink{\hyper@anchorstart{\@currentHref}\hyper@anchorend}%
14588 }
14589 \end{package}

```

49.1 Bookmarks

14590 `*outlines`

This section was written by Heiko Oberdiek; the code replaces an earlier version by David Carlisle.

The first part of bookmark code is in section 6. Further documentation is available as paper and slides of the talk, that Heiko Oberdiek has given at the EuroTeX'99 meeting in Heidelberg. See `paper.pdf` and `slides.pdf` in the `doc` directory of `hyperref`.

When using the right-to-left typesetting based on ε -TeX, the order of the `\BOOKMARK` commands written to the `\@outlinefile` could appear wrong, because of mis-feature of ε -TeX's implementation (that it processes the shipped out lines left-to-right, instead of the order in which they appear in the document). The wrong order will appear when the file contains two bookmarks on the same line typeset right-to-left.

To work around this problem, the `bookmark@seq@number` counter is used to write the bookmark's sequential number into a comment in the `\@outlinefile`, which could be used to post-process it to achieve the proper ordering of `\BOOKMARK` commands in that file.

```

14591 \def\Hy@writebookmark#1#2#3#4#5{%
14592   % section number, text, label, level, file
14593   \ifx\WriteBookmarks\relax%
14594   \else
14595     \ifnum#4>\Hy@bookmarksdepth\relax
14596     \else
14597       \@writetorep{#1}{#2}{#3}{#4}{#5}%
14598     \fi
14599   \fi
14600 }
14601 \def\Hy@currentbookmarklevel{0}
14602 \def\Hy@numberline#1{#1 }
14603 \def\@writetorep#1#2#3#4#5{%
14604   \begingroup
14605     \edef\Hy@tempa{#5}%
14606     \ifx\Hy@tempa\Hy@bookmarkstype
14607       \edef\Hy@level{#4}%
14608       \ifx\Hy@levelcheck Y%
14609         \@tempcnta\Hy@level\relax
14610         \advance\@tempcnta by -1 %
14611         \ifnum\Hy@currentbookmarklevel<\@tempcnta
14612           \advance\@tempcnta by -\Hy@currentbookmarklevel\relax
14613           \advance\@tempcnta by 1 %
14614         \Hy@Warning{%
14615           Difference (\the\@tempcnta) between bookmark levels is %

```

```

14616         greater \MessageBreak than one, level fixed%
14617     }%
14618     \@tempcnta\Hy@currentbookmarklevel
14619     \advance\@tempcnta by 1 %
14620     \edef\Hy@level{\the\@tempcnta}%
14621     \fi
14622 \else
14623     \global\let\Hy@levelcheck Y%
14624     \fi
14625     \global\let\Hy@currentbookmarklevel\Hy@level
14626     \@tempcnta\Hy@level\relax
14627     \expandafter\xdef\csname Parent\Hy@level\endcsname{#3}%
14628     \advance\@tempcnta by -1 %
14629     \edef\Hy@tempa{#3}%
14630     \edef\Hy@tempb{\csname Parent\the\@tempcnta\endcsname}%
14631     \ifx\Hy@tempa\Hy@tempb
14632         \Hy@Warning{%
14633             The anchor of a bookmark and its parent's must not%
14634             \MessageBreak be the same. Added a new anchor%
14635         }%
14636     \phantomsection
14637     \fi
14638     \ifHy@bookmarksnumbered
14639         \let\numberline\Hy@numberline
14640         \let\booknumberline\Hy@numberline
14641         \let\partnumberline\Hy@numberline
14642         \let\chapternumberline\Hy@numberline
14643     \else
14644         \let\numberline\@gobble
14645         \let\booknumberline\@gobble
14646         \let\partnumberline\@gobble
14647         \let\chapternumberline\@gobble
14648     \fi
14649     \HyPsd@XeTeXBigCharstrue
14650     \pdfstringdef\Hy@tempa{#2}%
14651     \HyPsd@SanitizeForOutFile\Hy@tempa
14652     \if@filesw
14653         \stepcounter{bookmark@seq@number}%
14654         \@ifundefined{@outlinefile}{%
14655             {%
14656                 \protected@write\@outlinefile{}{%
14657                     \protect\BOOKMARK
14658                     [\Hy@level][\@bookmarkopenstatus{\Hy@level}]{#3}%
14659                     {\Hy@tempa}{\Hy@tempb}%
14660                     \@percentchar\space\thebookmark@seq@number
14661                 }%
14662             }%
14663         \fi
14664     \fi
14665 \endgroup
14666 }
14667 \newcounter{bookmark@seq@number}

14668 \begingroup
14669 \lccode'('= '{%
14670 \lccode'='='}%
14671 \lccode'1=\z@
14672 \lccode'2=\z@

```



```

14673 \lccode'3=\z@
14674 \lccode'5=\z@
14675 \lccode'7=\z@
14676 \lccode'\#=\z@
14677 \lccode'\'=\z@
14678 \lccode'\{=\z@
14679 \lccode'\}=\z@
14680 \lowercase{%
14681 \endgroup
14682 \def\HyPsd@SanitizeForOutFile#1{%
14683   \@onelevel@sanitize\Hy@tempa
14684   \escapechar'\%
14685   \edef\Hy@tempa{%
14686     \expandafter\HyPsd@SanitizeOut@BraceLeft\Hy@tempa\@nil
14687   }%
14688   \edef\Hy@tempa{%
14689     \expandafter\HyPsd@SanitizeOut@BraceRight\Hy@tempa\@nil
14690   }%
14691 }%
14692 \def\HyPsd@SanitizeOut@BraceLeft#1(#2\@nil{%
14693   #1%
14694   \ifx\#2\%
14695     \expandafter\ltx@gobble
14696   \else
14697     \expandafter\ltx@firstofone
14698   \fi
14699   {%
14700     \string\173%
14701     \HyPsd@SanitizeOut@BraceLeft#2\@nil
14702   }%
14703 }%
14704 \def\HyPsd@SanitizeOut@BraceRight#1)#2\@nil{%
14705   #1%
14706   \ifx\#2\%
14707     \expandafter\ltx@gobble
14708   \else
14709     \expandafter\ltx@firstofone
14710   \fi
14711   {%
14712     \string\175%
14713     \HyPsd@SanitizeOut@BraceRight#2\@nil
14714   }%
14715 }%
14716 }

```

In the call of \BOOKMARK the braces around #4 are omitted, because it is not likely, that the level number contains].

```

14717 \newcommand{\currentpdfbookmark}{%
14718   \pdfbookmark[\Hy@currentbookmarklevel]%
14719 }
14720 \newcommand{\subpdfbookmark}{%
14721   \@tempcnta\Hy@currentbookmarklevel
14722   \Hy@StepCount\@tempcnta
14723   \expandafter\pdfbookmark\expandafter[\the\@tempcnta]%
14724 }
14725 \newcommand{\belowpdfbookmark}[2]{%
14726   \@tempcnta\Hy@currentbookmarklevel
14727   \Hy@StepCount\@tempcnta

```

```

14728 \expandafter\pdfbookmark\expandafter[\the\@tempcnta]{#1}{#2}%
14729 \advance\@tempcnta by -1 %
14730 \xdef\Hy@currentbookmarklevel{\the\@tempcnta}%
14731 }

```

Tobias Oetiker rightly points out that we need a way to force a bookmark entry. So we introduce `\pdfbookmark`, with two parameters, the title, and a symbolic name. By default this is at level 1, but we can reset that with the optional first argument.

```

14732 \renewcommand\pdfbookmark[3][0]{%
14733 \Hy@writebookmark{#2}{#3.#1}{#1}{toc}%
14734 \hyper@anchorstart{#3.#1}\hyper@anchorend
14735 }
14736 \def\BOOKMARK{%
14737 \ifnextchar{\@BOOKMARK}{\@@BOOKMARK[1][-]}%
14738 }
14739 \def\@BOOKMARK[#1]{%
14740 \ifnextchar{\@@BOOKMARK[{#1}]}{\@@BOOKMARK[{#1}][-]}%
14741 }

```

The macros for calculating structure of outlines are derived from those by Petr Olsak used in the `texinfo` macros.

49.1.1 Rerun warning

`\Hy@OutlineRerunCheck`

```

14742 \RequirePackage{rerunfilecheck}[2009/12/10]
14743 \def\Hy@OutlineRerunCheck{%
14744 \RerunFileCheck{\jobname.out}{%
14745 \immediate\closeout\@outlinefile
14746 }{%
14747 Rerun to get outlines right\MessageBreak
14748 or use package 'bookmark'%
14749 }%
14750 }

```

49.1.2 Driver stuff

The VTEX section was written originally by VTEX, but then amended by Denis Girou (denis.girou@idris.fr), then by by Taco Hoekwater (taco.hoekwater@wkap.nl). The problem is that VTEX, with its close integration of the PDF backend, does look at the contents of bookmarks, escaping `\` and the like.

```

14751 <*vtex>
14752 \newcount\@serial@counter\@serial@counter=1\relax

```

`\hv@pdf@char` Plain octal codes doesn't work with versions below 6.50. So for early versions hex numbers have to be used. It would be possible to program this instead of the large `\ifcase`, but I'm too lazy to sort that out now.

```

14753 \begingroup
14754 \catcode'\=12 %
14755 \ifnum\Hy@VTeXversion<650 %
14756 \catcode'\=12 %
14757 \gdef\hv@pdf@char#1#2#3{%
14758 \char
14759 \ifcase'#1#2#3 %
14760 "00\or"01\or"02\or"03\or"04\or"05\or"06\or"07%
14761 \or"08\or"09\or"0A\or"0B\or"0C\or"0D\or"0E\or"0F%
14762 \or"10\or"11\or"12\or"13\or"14\or"15\or"16\or"17%

```

```

14763 \or"18\or"19\or"1A\or"1B\or"1C\or"1D\or"1E\or"1F%
14764 \or"20\or"21\or"22\or"23\or"24\or"25\or"26\or"27%
14765 \or"28\or"29\or"2A\or"2B\or"2C\or"2D\or"2E\or"2F%
14766 \or"30\or"31\or"32\or"33\or"34\or"35\or"36\or"37%
14767 \or"38\or"39\or"3A\or"3B\or"3C\or"3D\or"3E\or"3F%
14768 \or"40\or"41\or"42\or"43\or"44\or"45\or"46\or"47%
14769 \or"48\or"49\or"4A\or"4B\or"4C\or"4D\or"4E\or"4F%
14770 \or"50\or"51\or"52\or"53\or"54\or"55\or"56\or"57%
14771 \or"58\or"59\or"5A\or"5B\or"5C\or"5D\or"5E\or"5F%
14772 \or"60\or"61\or"62\or"63\or"64\or"65\or"66\or"67%
14773 \or"68\or"69\or"6A\or"6B\or"6C\or"6D\or"6E\or"6F%
14774 \or"70\or"71\or"72\or"73\or"74\or"75\or"76\or"77%
14775 \or"78\or"79\or"7A\or"7B\or"7C\or"7D\or"7E\or"7F%
14776 \or"80\or"81\or"82\or"83\or"84\or"85\or"86\or"87%
14777 \or"88\or"89\or"8A\or"8B\or"8C\or"8D\or"8E\or"8F%
14778 \or"90\or"91\or"92\or"93\or"94\or"95\or"96\or"97%
14779 \or"98\or"99\or"9A\or"9B\or"9C\or"9D\or"9E\or"9F%
14780 \or"A0\or"A1\or"A2\or"A3\or"A4\or"A5\or"A6\or"A7%
14781 \or"A8\or"A9\or"AA\or"AB\or"AC\or"AD\or"AE\or"AF%
14782 \or"B0\or"B1\or"B2\or"B3\or"B4\or"B5\or"B6\or"B7%
14783 \or"B8\or"B9\or"BA\or"BB\or"BC\or"BD\or"BE\or"BF%
14784 \or"C0\or"C1\or"C2\or"C3\or"C4\or"C5\or"C6\or"C7%
14785 \or"C8\or"C9\or"CA\or"CB\or"CC\or"CD\or"CE\or"CF%
14786 \or"D0\or"D1\or"D2\or"D3\or"D4\or"D5\or"D6\or"D7%
14787 \or"D8\or"D9\or"DA\or"DB\or"DC\or"DD\or"DE\or"DF%
14788 \or"E0\or"E1\or"E2\or"E3\or"E4\or"E5\or"E6\or"E7%
14789 \or"E8\or"E9\or"EA\or"EB\or"EC\or"ED\or"EE\or"EF%
14790 \or"F0\or"F1\or"F2\or"F3\or"F4\or"F5\or"F6\or"F7%
14791 \or"F8\or"F9\or"FA\or"FB\or"FC\or"FD\or"FE\or"FF%
14792 \fi
14793 }%
14794 \else
14795 \gdef\hv@pdf@char{\char'}%
14796 \fi
14797 \endgroup

```

\@@BOOKMARK

```

14798 \def\@@BOOKMARK[#1][#2]#3#4#5{%
14799 \expandafter\edef\csname @count@#3\endcsname{%
14800 \the\@serial@counter
14801 }%
14802 \edef\@mycount{\the\@serial@counter}%
14803 \Hy@StepCount\@serial@counter
14804 \edef\@parcount{%
14805 \expandafter\ifx\csname @count@#5\endcsname\relax
14806 0%
14807 \else
14808 \csname @count@#5\endcsname
14809 \fi
14810 }%
14811 \immediate\special{%
14812 !outline \HyperDestNameFilter{#3};p=\@parcount,i=\@mycount,%
14813 s=\ifx#2-c\else o\fi,t=#4%
14814 }%
14815 }%

```

\ReadBookmarks

```

14816 \def\ReadBookmarks{%
14817   \begingroup
14818   \def\0{\hv@pdf@char 0}%
14819   \def\1{\hv@pdf@char 1}%
14820   \def\2{\hv@pdf@char 2}%
14821   \def\3{\hv@pdf@char 3}%
14822   \def\({}%
14823   \def\)}%
14824   \def\do##1{%
14825     \ifnum\catcode'##1=\active
14826       \@makeother##1%
14827     \else
14828       \ifnum\catcode'##1=6 %
14829         \@makeother##1%
14830       \fi
14831     \fi
14832   }%
14833   \dospecials
14834   \Hy@safe@activetrue
14835   \InputIfFileExists{jobname.out}{-}{-}%
14836 \endgroup
14837 \ifx\WriteBookmarks\relax
14838 \else
14839   \if@filesw
14840     \newwrite\@outlinefile
14841     \Hy@OutlineRerunCheck
14842     \immediate\openout\@outlinefile=jobname.out\relax
14843     \ifHy@typexml
14844       \immediate\write\@outlinefile{<relaxxml>\relax}%
14845     \fi
14846   \fi
14847 \fi
14848 }

14849 </vtex>
14850 (*!vtex)
14851 \def\ReadBookmarks{%
14852   \pdf@ifdraftmode{-}{-}%
14853   \begingroup
14854   \def\do##1{%
14855     \ifnum\catcode'##1=\active
14856       \@makeother##1%
14857     \else
14858       \ifnum\catcode'##1=6 %
14859         \@makeother##1%
14860       \fi
14861     \fi
14862   }%
14863   \dospecials
14864   \Hy@safe@activetrue
14865   \escapechar='\'%
14866   \def\@@BOOKMARK[##1][##2]##3##4##5{%
14867     \calc@bm@number{##5}%
14868   }%
14869   \InputIfFileExists{jobname.out}{-}{-}%
14870   \ifx\WriteBookmarks\relax
14871     \global\let\WriteBookmarks\relax
14872   \fi

```

```

14873 \def\@@BOOKMARK[##1][##2]###3###4###5{%
14874 \def\Hy@temp{##4}%
14875 (*pdfTeX)
14876 \Hy@pstringdef\Hy@pstringName{\HyperDestNameFilter{##3}}%
14877 \Hy@OutlineName{}\Hy@pstringName{%
14878 ##2\check@bm@number{##3}%
14879 }{%
14880 \expandafter\strip@prefix\meaning\Hy@temp
14881 }%
14882 \pdfTeX)
14883 (*pdfmark)
14884 \pdfmark{%
14885 pdfmark=/OUT,%
14886 Count={##2\check@bm@number{##3}},%
14887 Dest={##3},%
14888 Title=\expandafter\strip@prefix\meaning\Hy@temp
14889 }%
14890 \pdfmark)
14891 (*dvipdfm|xetex)
14892 \Hy@pstringdef\Hy@pstringName{\HyperDestNameFilter{##3}}%
14893 \@pdfm@mark{%
14894 outline \ifHy@DvipdfmxOutlineOpen
14895 [%
14896 \ifnum##21>\z@
14897 \else
14898 -%
14899 \fi
14900 ]%
14901 \fi
14902 ##1<<%
14903 /Title(\expandafter\strip@prefix\meaning\Hy@temp)%
14904 /A<<%
14905 /S/GoTo%
14906 /D(\Hy@pstringName)%
14907 >>%
14908 >>%
14909 }%
14910 \dvipdfm|xetex)
14911 }%
14912 \begingroup
14913 \def\WriteBookmarks{0}%
14914 \InputIfFileExists{jobname.out}{-}{-}%
14915 \endgroup
14916 %{\escapechar\m@ne\InputIfFileExists{jobname.out}{-}{-}}%
14917 \endgroup
14918 }%
14919 \ifx\WriteBookmarks\relax
14920 \else
14921 \if@files
14922 \newwrite\@outlinefile
14923 \Hy@OutlineRerunCheck
14924 \immediate\openout\@outlinefile=jobname.out\relax
14925 \ifHy@typexml
14926 \immediate\write\@outlinefile{<relaxxml>\relax}%
14927 \fi
14928 \fi
14929 \fi

```

```

14930 }
14931 \<*pdfTeX>
14932 \def\Hy@OutlineName#1#2#3#4{%
14933   \pdfoutline goto name{#2}count#3{#4}%
14934 }
14935 \</pdfTeX>
14936 \def\check@bm@number#1{%
14937   \expandafter\ifx\csname B_#1\endcsname\relax
14938     0%
14939   \else
14940     \csname B_#1\endcsname
14941   \fi
14942 }
14943 \def\calc@bm@number#1{%
14944   \@tempcnta=\check@bm@number{#1}\relax
14945   \advance\@tempcnta by 1 %
14946   \expandafter\xdef\csname B_#1\endcsname{\the\@tempcnta}%
14947 }
14948 \</!vTeX>

14949 \ifHy@implicit
14950 \else
14951   \expandafter\endinput
14952 \fi

14953 \</outlines>
14954 \<*outlines | hypertex>

14955 \newlength\Hy@SectionHShift
14956 \def\Hy@SectionAnchorHref#1{%
14957   \ifx\protect\@typeset@protect
14958     \Hy@@SectionAnchor{#1}%
14959   \fi
14960 }
14961 \DeclareRobustCommand*{\Hy@@SectionAnchor}[1]{%
14962   \leavevmode
14963   \hbox to 0pt{%
14964     \kern-\Hy@SectionHShift
14965     \Hy@raisedlink{%
14966       \hyper@anchorstart{#1}\hyper@anchorend
14967     }%
14968     \hss
14969   }%
14970 }
14971 \let\H@old@ssect\@ssect
14972 \def\@ssect#1#2#3#4#5{%
14973   \Hy@MakeCurrentHrefAuto{section*}%
14974   \setlength{\Hy@SectionHShift}{#1}%
14975   \begingroup
14976     \toks@{\H@old@ssect{#1}{#2}{#3}{#4}}%
14977     \toks\tw@\expandafter{%
14978       \expandafter\Hy@SectionAnchorHref\expandafter{\@currentHref}%
14979       #5%
14980     }%
14981   \edef\x{\endgroup
14982     \the\toks@\the\toks\tw@}%
14983   }\x
14984 }
14985 \let\H@old@schapter\@schapter

```

```

14986 \def\@schapter#1{%
14987   \begingroup
14988     \let\@mkboth\@gobbletwo
14989     \Hy@MakeCurrentHrefAuto{\Hy@chapapp*}%
14990     \Hy@raisedlink{%
14991       \hyper@anchorstart{\@currentHref}\hyper@anchorend
14992     }%
14993   \endgroup
14994   \H@old@chapter{#1}%
14995 }

```

If there is no chapter number (`\frontmatter` or `\backmatter`) then the counting by `\refstepcounter{chapter}` is not executed, so there will be no destination for `\ddcontentsline`. So `\@chapter` is overloaded to avoid this:

```

14996 \ltx@ifundefined{@chapter}{-}{%
14997   \let\Hy@org@chapter\@chapter
14998   \def\@chapter{%
14999     \def\Hy@next{%
15000       \Hy@MakeCurrentHrefAuto{\Hy@chapapp*}%
15001       \Hy@raisedlink{%
15002         \hyper@anchorstart{\@currentHref}\hyper@anchorend
15003       }%
15004     }%
15005     \ifnum\c@secnumdepth>\m@ne
15006       \ltx@ifundefined{if@mainmatter}%
15007       \iftrue{\csname if@mainmatter\endcsname}%
15008       \let\Hy@next\relax
15009     \fi
15010     \fi
15011     \Hy@next
15012     \Hy@org@chapter
15013   }%
15014 }

15015 \let\H@old@part\@part
15016 \begingroup\expandafter\expandafter\expandafter\endgroup
15017 \expandafter\ifx\csname chapter\endcsname\relax
15018   \let\Hy@secnum@part\z@
15019 \else
15020   \let\Hy@secnum@part\m@ne
15021 \fi
15022 \def\@part{%
15023   \ifnum\Hy@secnum@part>\c@secnumdepth
15024     \phantomsection
15025     \fi
15026   \H@old@part
15027 }

15028 \let\H@old@spart\@spart
15029 \def\@spart#1{%
15030   \Hy@MakeCurrentHrefAuto{part*}%
15031   \Hy@raisedlink{%
15032     \hyper@anchorstart{\@currentHref}\hyper@anchorend
15033   }%
15034   \H@old@spart{#1}%
15035 }

15036 \let\H@old@sect\@sect
15037 \def\@sect#1#2#3#4#5#6[#7]#8{%
15038   \ifnum #2>\c@secnumdepth

```

```

15039 \expandafter\@firstoftwo
15040 \else
15041 \expandafter\@secondoftwo
15042 \fi
15043 {%
15044 \Hy@MakeCurrentHrefAuto{section*}%
15045 \setlength{\Hy@SectionHShift}{#3}%
15046 \begingroup
15047 \toks@{\H@old@sect{#1}{#2}{#3}{#4}{#5}{#6}{#7}}%
15048 \toks\tw@\expandafter{%
15049 \expandafter\Hy@SectionAnchorHref\expandafter{\@currentHref}%
15050 #8%
15051 }%
15052 \edef\x{\endgroup
15053 \the\toks@\the\toks\tw@}%
15054 }\x
15055 }{%
15056 \H@old@sect{#1}{#2}{#3}{#4}{#5}{#6}{#7}{#8}%
15057 }%
15058 }

15059 </outlines | hypertex>
15060 <*outlines>

15061 \expandafter\def\csname Parent-4\endcsname{}
15062 \expandafter\def\csname Parent-3\endcsname{}
15063 \expandafter\def\csname Parent-2\endcsname{}
15064 \expandafter\def\csname Parent-1\endcsname{}
15065 \expandafter\def\csname Parent0\endcsname{}
15066 \expandafter\def\csname Parent1\endcsname{}
15067 \expandafter\def\csname Parent2\endcsname{}
15068 \expandafter\def\csname Parent3\endcsname{}
15069 \expandafter\def\csname Parent4\endcsname{}

15070 </outlines>

```

50 Compatibility with koma-script classes

```
15071 <*outlines | hypertex>
```

Hard-wire in an unpleasant over-ride of komascript ‘scrbook’ class for Tobias Isenberg (Tobias.Isenberg@gmx.de). With version 6.71b the hack is also applied to ‘scrreprt’ class and is removed for koma-script versions since 2001/01/01, because Markus Kohm supports hyperref in komascript.

```

15072 \def\Hy@tempa{%
15073 \def\@addchap[##1]##2{%
15074 \typeout{##2}%
15075 \if@twoside
15076 \@mkboth{##1}{}%
15077 \else
15078 \@mkboth{}{##1}%
15079 \fi
15080 \addtocontents{lof}{\protect\addvspace{10\p@}}%
15081 \addtocontents{lot}{\protect\addvspace{10\p@}}%
15082 \Hy@MakeCurrentHrefAuto{\Hy@chapapp*}%
15083 \Hy@raisedlink{%
15084 \hyper@anchorstart{\@currentHref}\hyper@anchorend
15085 }%
15086 \if@twocolumn

```



```

15087 \topnewpage[\@makeschapterhead{##2}]%
15088 \else
15089 \@makeschapterhead{##2}%
15090 \@afterheading
15091 \fi
15092 \addcontentsline{toc}{chapter}{##1}%
15093 }%
15094 }
15095 \@ifclassloaded{scrbook}{%
15096 \@ifclasslater{scrbook}{2001/01/01}{%
15097 \let\Hy@tempa\@empty
15098 }{}%
15099 }{%
15100 \@ifclassloaded{scrreprt}{%
15101 \@ifclasslater{scrreprt}{2001/01/01}{%
15102 \let\Hy@tempa\@empty
15103 }{}%
15104 }{%
15105 \let\Hy@tempa\@empty
15106 }%
15107 }%
15108 \Hy@tempa
15109 </outlines | hypertext>

```

51 Encoding definition files for encodings of PDF strings

This was contributed by Heiko Oberdiek.

51.1 PD1 encoding

```

15110 <*pd1enc>
15111 \DeclareFontEncoding{PD1}{}{}

Accents
15112 \DeclareTextAccent{'}{PD1}{\textasciigrave}
15113 \DeclareTextAccent{'}{PD1}{\textacute}
15114 \DeclareTextAccent{^}{PD1}{\textasciicircum}
15115 \DeclareTextAccent{~}{PD1}{\texttilde}
15116 \DeclareTextAccent{"}{PD1}{\textasciidieresis}
15117 \DeclareTextAccent{r}{PD1}{\textstring}
15118 \DeclareTextAccent{v}{PD1}{\textasciicaron}
15119 \DeclareTextAccent{.}{PD1}{\textdotaccent}
15120 \DeclareTextAccent{c}{PD1}{\textcedilla}
15121 \DeclareTextAccent{=}{PD1}{\textasciimacron}
15122 \DeclareTextAccent{b}{PD1}{\textmacronbelow}
15123 \DeclareTextAccent{d}{PD1}{\textdotbelow}
15124 \DeclareTextCompositeCommand{'}{PD1}{\@empty}{\textasciigrave}
15125 \DeclareTextCompositeCommand{'}{PD1}{\@empty}{\textacute}
15126 \DeclareTextCompositeCommand{^}{PD1}{\@empty}{\textasciicircum}
15127 \DeclareTextCompositeCommand{~}{PD1}{\@empty}{\texttilde}
15128 \DeclareTextCompositeCommand{"}{PD1}{\@empty}{\textasciidieresis}
15129 \DeclareTextCompositeCommand{r}{PD1}{\@empty}{\textstring}
15130 \DeclareTextCompositeCommand{v}{PD1}{\@empty}{\textasciicaron}
15131 \DeclareTextCompositeCommand{.}{PD1}{\@empty}{\textdotaccent}
15132 \DeclareTextCompositeCommand{c}{PD1}{\@empty}{\textcedilla}
15133 \DeclareTextCompositeCommand{=}{PD1}{\@empty}{\textasciimacron}

```

```

15134 \DeclareTextCompositeCommand{\b}{PD1}{\@empty}{\textmacronbelow}
15135 \DeclareTextCompositeCommand{\d}{PD1}{\@empty}{\textdotbelow}
15136 \DeclareTextCompositeCommand{\'}{PD1}{\ }{\textasciigrave}
15137 \DeclareTextCompositeCommand{\`}{PD1}{\ }{\textacute}
15138 \DeclareTextCompositeCommand{\^}{PD1}{\ }{\textasciicircum}
15139 \DeclareTextCompositeCommand{\~}{PD1}{\ }{\texttilde}
15140 \DeclareTextCompositeCommand{\"}{PD1}{\ }{\textasciidieresis}
15141 \DeclareTextCompositeCommand{\r}{PD1}{\ }{\textring}
15142 \DeclareTextCompositeCommand{\v}{PD1}{\ }{\textasciicaron}
15143 \DeclareTextCompositeCommand{\.}{PD1}{\ }{\textdotaccent}
15144 \DeclareTextCompositeCommand{\c}{PD1}{\ }{\textcedilla}
15145 \DeclareTextCompositeCommand{\=}{PD1}{\ }{\textasciimacron}
15146 \DeclareTextCompositeCommand{\b}{PD1}{\ }{\textmacronbelow}
15147 \DeclareTextCompositeCommand{\d}{PD1}{\ }{\textdotbelow}
15148 \DeclareTextCommand{\k}{PD1}[1]{\TextSymbolUnavailable{\k{#1}}#1}
15149 \DeclareTextCommand{\t}{PD1}[1]{\TextSymbolUnavailable{\t{#1}}#1}
15150 \DeclareTextCommand{\newtie}{PD1}[1]{%
15151   \TextSymbolUnavailable{\newtie{#1}}#1%
15152 }

```

Special white space escape characters not for use in bookmarks but for other PDF strings.

```

15153 % U+0009 (CHARACTER TABULATION)
15154 \DeclareTextCommand{\textHT}{PD1}{\011}% U+0009
15155 % U+000A (LINE FEED)
15156 \DeclareTextCommand{\textLF}{PD1}{\012}% U+000A
15157 % U+000D (CARRIAGE RETURN)
15158 \DeclareTextCommand{\textCR}{PD1}{\015}% U+000D

```

Accent glyph names

```

15159 % U+02D8 BREVE; breve
15160 \DeclareTextCommand{\textasciibreve}{PD1}{\030}% U+02D8
15161 % U+02C7 CARON; caron
15162 \DeclareTextCommand{\textasciicaron}{PD1}{\031}% U+02C7
15163 % U+02C6 MODIFIER LETTER CIRCUMFLEX ACCENT; circumflex
15164 \DeclareTextCommand{\textcircumflex}{PD1}{\032}% U+02C6
15165 % U+02D9 DOT ABOVE; dotaccent
15166 \DeclareTextCommand{\textdotaccent}{PD1}{\033}% U+02D9
15167 % U+02DD DOUBLE ACUTE ACCENT; hungarumlaut
15168 \DeclareTextCommand{\texthungarumlaut}{PD1}{\034}% U+02DD
15169 % U+02DB OGONEK; ogonek
15170 \DeclareTextCommand{\textogonek}{PD1}{\035}% U+02DB
15171 % U+02DA RING ABOVE; ring
15172 \DeclareTextCommand{\textring}{PD1}{\036}% U+02DA
15173 % U+02DC SMALL TILDE; ilde, *tilde
15174 \DeclareTextCommand{\texttilde}{PD1}{\037}% U+02DC

```

\040: U+0020 SPACE; *space, spacehackarabic

\041: U+0021 EXCLAMATION MARK; exclam

```

15175 % U+0022 QUOTATION MARK; quotedbl
15176 \DeclareTextCommand{\textquotedbl}{PD1}{"}% \042 U+0022
15177 % U+0023 NUMBER SIGN; numbersign
15178 \DeclareTextCommand{\textnumbersign}{PD1}{\043}% U+0023
15179 % U+0024 DOLLAR SIGN; dollar
15180 \DeclareTextCommand{\textdollar}{PD1}{\044}% U+0024
15181 % U+0025 PERCENT SIGN; percent
15182 \DeclareTextCommand{\textpercent}{PD1}{\045}% U+0025
15183 % U+0026 AMPERSAND; ampersand
15184 \DeclareTextCommand{\textampersand}{PD1}{\046}% U+0026

```

\047: U+0027 APOSTROPHE; quotesingle

 15185 % U+0028 LEFT PARENTHESIS; parenleft
 15186 \DeclareTextCommand{\textparenleft}{PD1}{\string\{}% \050 U+0028
 15187 % U+0029 RIGHT PARENTHESIS; parenright
 15188 \DeclareTextCommand{\textparenright}{PD1}{\string\})}% \051 U+0029

 \052: U+002A ASTERISK; asterisk
 \053: U+002B PLUS SIGN; plus
 \054: U+002C COMMA; comma
 \055: U+002D HYPHEN-MINUS; hyphen
 \056: U+002E FULL STOP; period
 15189 % U+002E FULL STOP; period
 15190 \DeclareTextCommand{\textdotbelow}{PD1}{.}% \056 U+002E

 \057: U+002F SOLIDUS; slash
 \060: U+0030 DIGIT ZERO; zero

 ...
 \071: U+0039 DIGIT NINE; nine
 \072: U+003A COLON; colon
 \073: U+003B SEMICOLON; semicolon
 15191 % U+003C LESS-THAN SIGN; less
 15192 \DeclareTextCommand{\textless}{PD1}{<}% \074 U+003C

 \075: U+003D EQUALS SIGN; equal
 15193 % U+003E GREATER-THAN SIGN; greater
 15194 \DeclareTextCommand{\textgreater}{PD1}{>}% \076 U+003E

 \077: U+003F QUESTION MARK; question
 \100: U+0040 COMMERCIAL AT; at
 \101: U+0041 LATIN CAPITAL LETTER A; A

 ...
 \132: U+005A LATIN CAPITAL LETTER Z; Z
 \133: U+005B LEFT SQUARE BRACKET; bracketleft
 15195 % U+005C REVERSE SOLIDUS; backslash
 15196 \DeclareTextCommand{\textbackslash}{PD1}{\134}% U+005C
 15197 % "U+2216 SET MINUS" simulated by "U+005C REVERSE SOLIDUS"
 15198 \DeclareTextCommand{\textsetminus}{PD1}{\textbackslash}

 \135: U+005D RIGHT SQUARE BRACKET; bracketright
 15199 % U+005E CIRCUMFLEX ACCENT; asciicircum
 15200 \DeclareTextCommand{\textasciicircum}{PD1}{\136}% U+005E
 15201 % U+005F LOW LINE; underscore
 15202 \DeclareTextCommand{\textunderscore}{PD1}{\137}% U+005F
 15203 \DeclareTextCommand{\textmacronbelow}{PD1}{\137}% U+005F
 15204 % U+0060 GRAVE ACCENT; grave
 15205 \DeclareTextCommand{\textasciigrave}{PD1}{\140}% U+0060

 \141: U+0061 LATIN SMALL LETTER A; a

 ...
 \150: U+0068 LATIN SMALL LETTER H; h
 15206 % U+0069 LATIN SMALL LETTER I; i
 15207 \DeclareTextCompositeCommand{\.}{PD1}{i}{i}% \151 U+0069

 \152: U+006A LATIN SMALL LETTER J; j

 ...
 \172: U+007A LATIN SMALL LETTER Z; z
 15208 % U+007B LEFT CURLY BRACKET; braceleft
 15209 \DeclareTextCommand{\textbraceleft}{PD1}{\173}% U+007B
 15210 % U+007C VERTICAL LINE; *bar, verticalbar

15211 \DeclareTextCommand{\textbar}{PD1}{|}% U+007C
15212 % U+007D RIGHT CURLY BRACKET; braceright
15213 \DeclareTextCommand{\textbraceright}{PD1}{\175}% U+007D
15214 % U+007E TILDE; asciitilde
15215 \DeclareTextCommand{\textasciitilde}{PD1}{\176}% U+007E
Slot \177 (0x7F) is undefined in PDFDocEncoding.
15216 % U+2022 BULLET; bullet
15217 \DeclareTextCommand{\textbullet}{PD1}{\200}% U+2022
15218 % U+2020 DAGGER; dagger
15219 \DeclareTextCommand{\textdagger}{PD1}{\201}% U+2020
15220 % U+2021 DOUBLE DAGGER; daggerdbl; \ddagger (LaTeX)
15221 \DeclareTextCommand{\textdaggerdbl}{PD1}{\202}% U+2021
15222 \DeclareTextCommand{\textddagger}{PD1}{\textddagger}
15223 % U+2026 HORIZONTAL ELLIPSIS; ellipsis
15224 \DeclareTextCommand{\textellipsis}{PD1}{\203}% U+2026
15225 % U+2014 EM DASH; emdash
15226 \DeclareTextCommand{\textemdash}{PD1}{\204}% U+2014
15227 % U+2013 EN DASH; endash
15228 \DeclareTextCommand{\textendash}{PD1}{\205}% U+2013
15229 % U+0192 LATIN SMALL LETTER F WITH HOOK; florin
15230 \DeclareTextCommand{\textflorin}{PD1}{\206}% U+0192
15231 % U+2044 FRACTION SLASH; fraction
15232 \DeclareTextCommand{\textfractionsolidus}{PD1}{\207}% U+2044
15233 % U+2039 SINGLE LEFT-POINTING ANGLE QUOTATION MARK; guil-
ingleft
15234 \DeclareTextCommand{\guilsingleft}{PD1}{\210}% U+2039
15235 % U+203A SINGLE RIGHT-POINTING ANGLE QUOTATION MARK; guil-
ingright
15236 \DeclareTextCommand{\guilsingright}{PD1}{\211}% U+203A
15237 % U+2212 MINUS SIGN; minus
15238 \DeclareTextCommand{\textminus}{PD1}{\212}% U+2212
15239 % U+2030 PER MILLE SIGN; perthousand
15240 \DeclareTextCommand{\textperthousand}{PD1}{\213}% U+2030
15241 % U+201E DOUBLE LOW-9 QUOTATION MARK; quotedblbase
15242 \DeclareTextCommand{\quotedblbase}{PD1}{\214}% U+201E
15243 % U+201C LEFT DOUBLE QUOTATION MARK; quotedblleft
15244 \DeclareTextCommand{\textquotedblleft}{PD1}{\215}% U+201C
15245 % U+201D RIGHT DOUBLE QUOTATION MARK; quotedblright
15246 \DeclareTextCommand{\textquotedblright}{PD1}{\216}% U+201D
15247 % U+2018 LEFT SINGLE QUOTATION MARK; quoteleft
15248 \DeclareTextCommand{\textquoteleft}{PD1}{\217}% U+2018
15249 % U+2019 RIGHT SINGLE QUOTATION MARK; quoteright
15250 \DeclareTextCommand{\textquoteright}{PD1}{\220}% U+2019
15251 % U+201A SINGLE LOW-9 QUOTATION MARK; quotesinglbase
15252 \DeclareTextCommand{\quotesinglbase}{PD1}{\221}% U+201A
15253 % U+2122 TRADE MARK SIGN; trademark
15254 \DeclareTextCommand{\texttrademark}{PD1}{\222}% U+2122
15255 % U+FB01 LATIN SMALL LIGATURE FI; fi
15256 \DeclareTextCommand{\textfi}{PD1}{\223}% U+FB01
15257 % U+FB02 LATIN SMALL LIGATURE FL; fl
15258 \DeclareTextCommand{\textfl}{PD1}{\224}% U+FB02
15259 % U+0141 LATIN CAPITAL LETTER L WITH STROKE; Lslash
15260 \DeclareTextCommand{\L}{PD1}{\225}% U+0141
15261 % U+0152 LATIN CAPITAL LIGATURE OE; OE
15262 \DeclareTextCommand{\OE}{PD1}{\226}% U+0152
15263 % U+0160 LATIN CAPITAL LETTER S WITH CARON; Scaron
15264 \DeclareTextCompositeCommand{\v}{PD1}{S}{\227}% U+0160

15265 % U+0178 LATIN CAPITAL LETTER Y WITH DIAERESIS; Ydieresis
 15266 \DeclareTextCompositeCommand{"Y}{PD1}{\230}% U+0178
 15267 \DeclareTextCommand{\IJ}{PD1}{IJ}% ligature U+0049 U+004A
 15268 % U+017D LATIN CAPITAL LETTER Z WITH CARON; Zcaron
 15269 \DeclareTextCompositeCommand{\v}{PD1}{Z}{\231}% U+017D
 15270 % U+0131 LATIN SMALL LETTER DOTLESS I; dotlessi
 15271 \DeclareTextCommand{\i}{PD1}{\232}% U+0131
 15272 % U+0142 LATIN SMALL LETTER L WITH STROKE; lslash
 15273 \DeclareTextCommand{\l}{PD1}{\233}% U+0142
 15274 % U+0153 LATIN SMALL LIGATURE OE; oe
 15275 \DeclareTextCommand{\oe}{PD1}{\234}% U+0153
 15276 % U+0161 LATIN SMALL LETTER S WITH CARON; scaron
 15277 \DeclareTextCompositeCommand{\v}{PD1}{s}{\235}% U+0161
 15278 % U+017E LATIN SMALL LETTER Z WITH CARON; zcaron
 15279 \DeclareTextCompositeCommand{\v}{PD1}{z}{\236}% U+017E
 Slot \237 (0x9F) is not defined in PDFDocEncoding.
 The euro \240 is inserted in version 1.3 of the pdf specification.
 15280 % U+20AC EURO SIGN; *Euro, euro
 15281 \DeclareTextCommand{\texteuro}{PD1}{\240}% U+20AC
 15282 % U+00A1 INVERTED EXCLAMATION MARK; exclamdown
 15283 \DeclareTextCommand{\textexclamdown}{PD1}{\241}% U+00A1
 15284 % U+00A2 CENT SIGN; cent
 15285 \DeclareTextCommand{\textcent}{PD1}{\242}% U+00A2
 15286 % U+00A3 POUND SIGN; sterling
 15287 \DeclareTextCommand{\textsterling}{PD1}{\243}% U+00A3
 15288 % U+00A4 CURRENCY SIGN; currency
 15289 \DeclareTextCommand{\textcurrency}{PD1}{\244}% U+00A4
 15290 % U+00A5 YEN SIGN; yen
 15291 \DeclareTextCommand{\textyen}{PD1}{\245}% U+00A5
 15292 % U+00A6 BROKEN BAR; brokenbar
 15293 \DeclareTextCommand{\textbrokenbar}{PD1}{\246}% U+00A6
 15294 % U+00A7 SECTION SIGN; section
 15295 \DeclareTextCommand{\textsection}{PD1}{\247}% U+00A7
 15296 % U+00A8 DIAERESIS; dieresis
 15297 \DeclareTextCommand{\textasciidieresis}{PD1}{\250}% U+00A8
 15298 % U+00A9 COPYRIGHT SIGN; copyright
 15299 \DeclareTextCommand{\textcopyright}{PD1}{\251}% U+00A9
 15300 % U+00AA FEMININE ORDINAL INDICATOR; ordfeminine
 15301 \DeclareTextCommand{\textordfeminine}{PD1}{\252}% U+00AA
 15302 % U+00AB LEFT-POINTING DOUBLE ANGLE QUOTATION MARK; guille-
 motleft
 15303 \DeclareTextCommand{\guillemotleft}{PD1}{\253}% U+00AB
 15304 % U+00AC NOT SIGN; logicalnot
 15305 \DeclareTextCommand{\textlogicalnot}{PD1}{\254}% U+00AC
 15306 \DeclareTextCommand{\textlnot}{PD1}{\254}% logical not
 No glyph \255 in PDFDocEncoding.
 15307 % U+00AE REGISTERED SIGN; registered
 15308 \DeclareTextCommand{\textregistered}{PD1}{\256}% U+00AE
 15309 % U+00AF MACRON; *macron, overscore
 15310 \DeclareTextCommand{\textasciimacron}{PD1}{\257}% U+00AF
 15311 % U+00B0 DEGREE SIGN; degree
 15312 \DeclareTextCommand{\textdegree}{PD1}{\260}% U+00B0
 15313 % U+00B1 PLUS-MINUS SIGN; plusminus
 15314 \DeclareTextCommand{\textplusminus}{PD1}{\261}% U+00B1
 15315 % U+00B2 SUPERSCRIPT TWO; twosuperior
 15316 \DeclareTextCommand{\texttwosuperior}{PD1}{\262}%* U+00B2
 15317 % U+00B3 SUPERSCRIPT THREE; threesuperior

15318 \DeclareTextCommand{\textthreesuperior}{PD1}{\263}%* U+00B3
15319 % U+00B4 ACUTE ACCENT; acute
15320 \DeclareTextCommand{\textacute}{PD1}{\264}% U+00B4
15321 % U+00B5 MICRO SIGN; mu, mul
15322 \DeclareTextCommand{\textmu}{PD1}{\265}% U+00B5
15323 % U+00B6 PILCROW SIGN; paragraph
15324 \DeclareTextCommand{\textparagraph}{PD1}{\266}% U+00B6
15325 % U+00B7 MIDDLE DOT; middot, *periodcentered
15326 \DeclareTextCommand{\textperiodcentered}{PD1}{\267}% U+00B7
15327 % U+00B8 CEDILLA; cedilla
15328 \DeclareTextCommand{\textcedilla}{PD1}{\270}% U+00B8
15329 % U+00B9 SUPERSCRIPT ONE; onesuperior
15330 \DeclareTextCommand{\textonesuperior}{PD1}{\271}%* U+00B9
15331 % U+00BA MASCULINE ORDINAL INDICATOR; ordmasculine
15332 \DeclareTextCommand{\textordmasculine}{PD1}{\272}% U+00BA
15333 % U+00BB RIGHT-POINTING DOUBLE ANGLE QUOTATION MARK; guille-
motright
15334 \DeclareTextCommand{\guillemotright}{PD1}{\273}% U+00BB
15335 % U+00BC VULGAR FRACTION ONE QUARTER; onequarter
15336 \DeclareTextCommand{\textonequarter}{PD1}{\274}% U+00BC
15337 % U+00BD VULGAR FRACTION ONE HALF; onehalf
15338 \DeclareTextCommand{\textonehalf}{PD1}{\275}% U+00BD
15339 % U+00BE VULGAR FRACTION THREE QUARTERS; threequarters
15340 \DeclareTextCommand{\textthreequarters}{PD1}{\276}% U+00BE
15341 % U+00BF INVERTED QUESTION MARK; questiondown
15342 \DeclareTextCommand{\textquestiondown}{PD1}{\277}% U+00BF
15343 % U+00C0 LATIN CAPITAL LETTER A WITH GRAVE; Agrave
15344 \DeclareTextCompositeCommand{\`}{PD1}{A}{\300}% U+00C0
15345 % U+00C1 LATIN CAPITAL LETTER A WITH ACUTE; Aacute
15346 \DeclareTextCompositeCommand{\'}{PD1}{A}{\301}% U+00C1
15347 % U+00C2 LATIN CAPITAL LETTER A WITH CIRCUMFLEX; Acircumflex
15348 \DeclareTextCompositeCommand{\^}{PD1}{A}{\302}% U+00C2
15349 % U+00C3 LATIN CAPITAL LETTER A WITH TILDE; Atilde
15350 \DeclareTextCompositeCommand{\~}{PD1}{A}{\303}% U+00C3
15351 % U+00C4 LATIN CAPITAL LETTER A WITH DIAERESIS; Adieresis
15352 \DeclareTextCompositeCommand{\\"}{PD1}{A}{\304}% U+00C4
15353 % U+00C5 LATIN CAPITAL LETTER A WITH RING ABOVE; Aring
15354 \DeclareTextCompositeCommand{\r}{PD1}{A}{\305}% U+00C5
15355 % U+00C6 LATIN CAPITAL LETTER AE; AE
15356 \DeclareTextCommand{\AE}{PD1}{\306}% U+00C6
15357 % U+00C7 LATIN CAPITAL LETTER C WITH CEDILLA; Ccedilla
15358 \DeclareTextCompositeCommand{\c}{PD1}{C}{\307}% U+00C7
15359 % U+00C8 LATIN CAPITAL LETTER E WITH GRAVE; Egrave
15360 \DeclareTextCompositeCommand{\`}{PD1}{E}{\310}% U+00C8
15361 % U+00C9 LATIN CAPITAL LETTER E WITH ACUTE; Eacute
15362 \DeclareTextCompositeCommand{\'}{PD1}{E}{\311}% U+00C9
15363 % U+00CA LATIN CAPITAL LETTER E WITH CIRCUMFLEX; Ecircumflex
15364 \DeclareTextCompositeCommand{\^}{PD1}{E}{\312}% U+00CA
15365 % U+00CB LATIN CAPITAL LETTER E WITH DIAERESIS; Edieresis
15366 \DeclareTextCompositeCommand{\\"}{PD1}{E}{\313}% U+00CB
15367 % U+00CC LATIN CAPITAL LETTER I WITH GRAVE; Igrave
15368 \DeclareTextCompositeCommand{\`}{PD1}{I}{\314}% U+00CC
15369 % U+00CD LATIN CAPITAL LETTER I WITH ACUTE; Iacute
15370 \DeclareTextCompositeCommand{\'}{PD1}{I}{\315}% U+00CD
15371 % U+00CE LATIN CAPITAL LETTER I WITH CIRCUMFLEX; Icircumflex
15372 \DeclareTextCompositeCommand{\^}{PD1}{I}{\316}% U+00CE
15373 % U+00CF LATIN CAPITAL LETTER I WITH DIAERESIS; Idieresis

15374 \DeclareTextCompositeCommand{"}{PD1}{I}{\317}% U+00CF
15375 % U+00D0 LATIN CAPITAL LETTER ETH; Eth
15376 \DeclareTextCommand{\DH}{PD1}{\320}% U+00D0
15377 \DeclareTextCommand{\DJ}{PD1}{\320}% U+00D0
15378 % U+00D1 LATIN CAPITAL LETTER N WITH TILDE; Ntilde
15379 \DeclareTextCompositeCommand{~}{PD1}{N}{\321}% U+00D1
15380 % U+00D2 LATIN CAPITAL LETTER O WITH GRAVE; Ograve
15381 \DeclareTextCompositeCommand{'}{PD1}{O}{\322}% U+00D2
15382 % U+00D3 LATIN CAPITAL LETTER O WITH ACUTE; Oacute
15383 \DeclareTextCompositeCommand{'}{PD1}{O}{\323}% U+00D3
15384 % U+00D4 LATIN CAPITAL LETTER O WITH CIRCUMFLEX; Ocircumflex
15385 \DeclareTextCompositeCommand{^}{PD1}{O}{\324}% U+00D4
15386 % U+00D5 LATIN CAPITAL LETTER O WITH TILDE; Otilde
15387 \DeclareTextCompositeCommand{~}{PD1}{O}{\325}% U+00D5
15388 % U+00D6 LATIN CAPITAL LETTER O WITH DIAERESIS; Odieresis
15389 \DeclareTextCompositeCommand{"}{PD1}{O}{\326}% U+00D6
15390 % U+00D7 MULTIPLICATION SIGN; multiply
15391 \DeclareTextCommand{\textmultiply}{PD1}{\327}% U+00D7
15392 % U+00D8 LATIN CAPITAL LETTER O WITH STROKE; Oslash
15393 \DeclareTextCommand{\O}{PD1}{\330}% U+00D8
15394 % U+00D9 LATIN CAPITAL LETTER U WITH GRAVE; Ugrave
15395 \DeclareTextCompositeCommand{'}{PD1}{U}{\331}% U+00D9
15396 % U+00DA LATIN CAPITAL LETTER U WITH ACUTE; Uacute
15397 \DeclareTextCompositeCommand{'}{PD1}{U}{\332}% U+00DA
15398 % U+00DB LATIN CAPITAL LETTER U WITH CIRCUMFLEX; Ucircumflex
15399 \DeclareTextCompositeCommand{^}{PD1}{U}{\333}% U+00DB
15400 % U+00DC LATIN CAPITAL LETTER U WITH DIAERESIS; Udieresis
15401 \DeclareTextCompositeCommand{"}{PD1}{U}{\334}% U+00DC
15402 % U+00DD LATIN CAPITAL LETTER Y WITH ACUTE; Yacute
15403 \DeclareTextCompositeCommand{'}{PD1}{Y}{\335}% U+00DD
15404 % U+00DE LATIN CAPITAL LETTER THORN; Thorn; \TH, \Thorn (wasysym)
15405 \DeclareTextCommand{\TH}{PD1}{\336}% U+00DE
15406 \DeclareTextCommand{\textThorn}{PD1}{\336}%* U+00DE
15407 % U+00DF LATIN SMALL LETTER SHARP S; germandbls
15408 \DeclareTextCommand{\ss}{PD1}{\337}% U+00DF
15409 % U+00E0 LATIN SMALL LETTER A WITH GRAVE; agrave
15410 \DeclareTextCompositeCommand{'}{PD1}{a}{\340}% U+00E0
15411 % U+00E1 LATIN SMALL LETTER A WITH ACUTE; aacute
15412 \DeclareTextCompositeCommand{'}{PD1}{a}{\341}% U+00E1
15413 % U+00E2 LATIN SMALL LETTER A WITH CIRCUMFLEX; acircumflex
15414 \DeclareTextCompositeCommand{^}{PD1}{a}{\342}% U+00E2
15415 % U+00E3 LATIN SMALL LETTER A WITH TILDE; atilde
15416 \DeclareTextCompositeCommand{~}{PD1}{a}{\343}% U+00E3
15417 % U+00E4 LATIN SMALL LETTER A WITH DIAERESIS; adieresis
15418 \DeclareTextCompositeCommand{"}{PD1}{a}{\344}% U+00E4
15419 % U+00E5 LATIN SMALL LETTER A WITH RING ABOVE; aring
15420 \DeclareTextCompositeCommand{\r}{PD1}{a}{\345}% U+00E5
15421 % U+00E6 LATIN SMALL LETTER AE; ae
15422 \DeclareTextCommand{\ae}{PD1}{\346}% U+00E6
15423 % U+00E7 LATIN SMALL LETTER C WITH CEDILLA; ccedilla
15424 \DeclareTextCompositeCommand{\c}{PD1}{c}{\347}% U+00E7
15425 % U+00E8 LATIN SMALL LETTER E WITH GRAVE; egrave
15426 \DeclareTextCompositeCommand{'}{PD1}{e}{\350}% U+00E8
15427 % U+00E9 LATIN SMALL LETTER E WITH ACUTE; eacute
15428 \DeclareTextCompositeCommand{'}{PD1}{e}{\351}% U+00E9
15429 % U+00EA LATIN SMALL LETTER E WITH CIRCUMFLEX; ecircumflex
15430 \DeclareTextCompositeCommand{^}{PD1}{e}{\352}% U+00EA

15431 % U+00EB LATIN SMALL LETTER E WITH DIAERESIS; edieresis
15432 \DeclareTextCompositeCommand{"}{PD1}{e}{\353}% U+00EB
15433 % U+00EC LATIN SMALL LETTER I WITH GRAVE; igrave
15434 \DeclareTextCompositeCommand{"}{PD1}{i}{\354}% U+00EC
15435 \DeclareTextCompositeCommand{"}{PD1}{i}{\354}% U+00EC
15436 % U+00ED LATIN SMALL LETTER I WITH ACUTE; iacute
15437 \DeclareTextCompositeCommand{"}{PD1}{i}{\355}% U+00ED
15438 \DeclareTextCompositeCommand{"}{PD1}{i}{\355}% U+00ED
15439 % U+00EE LATIN SMALL LETTER I WITH CIRCUMFLEX; icircumflex
15440 \DeclareTextCompositeCommand{"}{PD1}{i}{\356}% U+00EE
15441 \DeclareTextCompositeCommand{"}{PD1}{i}{\356}% U+00EE
15442 % U+00EF LATIN SMALL LETTER I WITH DIAERESIS; idieresis
15443 \DeclareTextCompositeCommand{"}{PD1}{i}{\357}% U+00EF
15444 \DeclareTextCompositeCommand{"}{PD1}{i}{\357}% U+00EF
15445 % U+00F0 LATIN SMALL LETTER ETH; eth
15446 \DeclareTextCommand{\dh}{PD1}{\360}% U+00F0
15447 % U+00F1 LATIN SMALL LETTER N WITH TILDE; ntilde
15448 \DeclareTextCompositeCommand{"}{PD1}{n}{\361}% U+00F1
15449 % U+00F2 LATIN SMALL LETTER O WITH GRAVE; ograve
15450 \DeclareTextCompositeCommand{"}{PD1}{o}{\362}% U+00F2
15451 % U+00F3 LATIN SMALL LETTER O WITH ACUTE; oacute
15452 \DeclareTextCompositeCommand{"}{PD1}{o}{\363}% U+00F3
15453 % U+00F4 LATIN SMALL LETTER O WITH CIRCUMFLEX; ocircumflex
15454 \DeclareTextCompositeCommand{"}{PD1}{o}{\364}% U+00F4
15455 % U+00F5 LATIN SMALL LETTER O WITH TILDE; otile
15456 \DeclareTextCompositeCommand{"}{PD1}{o}{\365}% U+00F5
15457 % U+00F6 LATIN SMALL LETTER O WITH DIAERESIS; odieresis
15458 \DeclareTextCompositeCommand{"}{PD1}{o}{\366}% U+00F6
15459 % U+00F7 DIVISION SIGN; divide
15460 \DeclareTextCommand{\textdivide}{PD1}{\367}% U+00F7
15461 % U+00F8 LATIN SMALL LETTER O WITH STROKE; oslash
15462 \DeclareTextCommand{\o}{PD1}{\370}% U+00F8
15463 % U+00F9 LATIN SMALL LETTER U WITH GRAVE; ugrave
15464 \DeclareTextCompositeCommand{"}{PD1}{u}{\371}% U+00F9
15465 % U+00FA LATIN SMALL LETTER U WITH ACUTE; uacute
15466 \DeclareTextCompositeCommand{"}{PD1}{u}{\372}% U+00FA
15467 % U+00FB LATIN SMALL LETTER U WITH CIRCUMFLEX; ucircumflex
15468 \DeclareTextCompositeCommand{"}{PD1}{u}{\373}% U+00FB
15469 % U+00FC LATIN SMALL LETTER U WITH DIAERESIS; udieresis
15470 \DeclareTextCompositeCommand{"}{PD1}{u}{\374}% U+00FC
15471 % U+00FD LATIN SMALL LETTER Y WITH ACUTE; yacute
15472 \DeclareTextCompositeCommand{"}{PD1}{y}{\375}% U+00FD
15473 % U+00FE LATIN SMALL LETTER THORN; thorn; \th, \thorn (wasysym)
15474 \DeclareTextCommand{\th}{PD1}{\376}% U+00FE
15475 \DeclareTextCommand{\textthorn}{PD1}{\376}%* U+00FE
15476 % U+00FF LATIN SMALL LETTER Y WITH DIAERESIS; ydieresis
15477 \DeclareTextCompositeCommand{"}{PD1}{y}{\377}% U+00FF
15478 \DeclareTextCommand{\ij}{PD1}{ij}% ligature U+0069 U+006A

Glyphs that consist of several characters.
15479 \DeclareTextCommand{\SS}{PD1}{SS}%
15480 \DeclareTextCommand{\textcelsius}{PD1}{\textdegree C}%

Aliases (german.sty)
15481 \DeclareTextCommand{\textglqq}{PD1}{\quotedblbase}%
15482 \DeclareTextCommand{\textgrqq}{PD1}{\textquotedblleft}%
15483 \DeclareTextCommand{\textglq}{PD1}{\quotesinglbase}%
15484 \DeclareTextCommand{\textgrq}{PD1}{\textquoteleft}%
15485 \DeclareTextCommand{\textflqq}{PD1}{\guillemotleft}%


```

15486 \DeclareTextCommand{\textfrqq}{PD1}{\guillemotright}%
15487 \DeclareTextCommand{\textflq}{PD1}{\guilsinglleft}%
15488 \DeclareTextCommand{\textfrq}{PD1}{\guilsinglright}%
Aliases (math names)
15489 \DeclareTextCommand{\textneg}{PD1}{\textlogicalnot}%
15490 \DeclareTextCommand{\texttimes}{PD1}{\textmultiply}%
15491 \DeclareTextCommand{\textdiv}{PD1}{\textdivide}%
15492 \DeclareTextCommand{\textpm}{PD1}{\textplusminus}%
15493 \DeclareTextCommand{\textcdot}{PD1}{\textperiodcentered}%
15494 \DeclareTextCommand{\textbeta}{PD1}{\ss}%

```

Polish aliases. PDF encoding does not have the characters, but it is useful to Poles to have the plain letters regardless. Requested by Wojciech Myszka (W.Myszka@immt.pwr.wroc.pl).

```

15495 \DeclareTextCompositeCommand{\k}{PD1}{a}{a}% aogonek
15496 \DeclareTextCompositeCommand{\'}{PD1}{c}{c}% cacute
15497 \DeclareTextCompositeCommand{\k}{PD1}{e}{e}% eogonek
15498 \DeclareTextCompositeCommand{\'}{PD1}{n}{n}% nacute
15499 \DeclareTextCompositeCommand{\'}{PD1}{s}{s}% sacute
15500 \DeclareTextCompositeCommand{\'}{PD1}{z}{z}% zacute
15501 \DeclareTextCompositeCommand{\.}{PD1}{z}{z}% zdot
15502 \DeclareTextCompositeCommand{\k}{PD1}{A}{A}% Aogonek
15503 \DeclareTextCompositeCommand{\'}{PD1}{C}{C}% Cacute
15504 \DeclareTextCompositeCommand{\k}{PD1}{E}{E}% Eogonek
15505 \DeclareTextCompositeCommand{\'}{PD1}{N}{N}% Nacute
15506 \DeclareTextCompositeCommand{\'}{PD1}{S}{S}% Sacute
15507 \DeclareTextCompositeCommand{\'}{PD1}{Z}{Z}% Zacute
15508 \DeclareTextCompositeCommand{\.}{PD1}{Z}{Z}% Zdot
15509 \pdlenc)

```

51.2 PU encoding

```

15510 \*puenc)
15511 \DeclareFontEncoding{PU}{-}{-}

```

51.2.1 NFSS2 accents

```

15512 % U+0300 COMBINING GRAVE ACCENT; gravecmb, *gravecomb
15513 \DeclareTextCommand{\`}{PU}[1]{\#1\83\000}% U+0300
15514 % U+0301 COMBINING ACUTE ACCENT; acutecmb, *acutecomb
15515 \DeclareTextCommand{\'}{PU}[1]{\#1\83\001}% U+0301
15516 % U+0302 COMBINING CIRCUMFLEX ACCENT; circumflexcmb
15517 \DeclareTextCommand{\^}{PU}[1]{\#1\83\002}% U+0302
15518 % U+0303 COMBINING TILDE; tildecmb, *tildecmb
15519 \DeclareTextCommand{\~}{PU}[1]{\#1\83\003}% U+0303
15520 % U+0304 COMBINING MACRON; macroncmb
15521 \DeclareTextCommand{\=}{PU}[1]{\#1\83\004}% U+0304
15522 % U+0306 COMBINING BREVE; brevecmb
15523 \DeclareTextCommand{\u}{PU}[1]{\#1\83\006}% U+0306
15524 \DeclareTextCommand{\U}{PU}[1]{\#1\83\006}% U+0306
15525 % U+0307 COMBINING DOT ABOVE; dotaccentcmb
15526 \DeclareTextCommand{\.}{PU}[1]{\#1\83\007}% U+0307
15527 % U+0308 COMBINING DIAERESIS; dieresiscmb
15528 \DeclareTextCommand{\"}{PU}[1]{\#1\83\010}% U+0308
15529 % U+030A COMBINING RING ABOVE; ringcmb
15530 \DeclareTextCommand{\r}{PU}[1]{\#1\83\012}% U+030A
15531 % U+030B COMBINING DOUBLE ACUTE ACCENT; hungarumlautcmb
15532 \DeclareTextCommand{\H}{PU}[1]{\#1\83\013}% U+030B
15533 % U+030C COMBINING CARON; caroncmb

```

```

15534 \DeclareTextCommand{\v}{PU}[1]{#1\83\014}% U+030C
15535 % U+030F COMBINING DOUBLE GRAVE ACCENT; dblgravecmb
15536 \DeclareTextCommand{\G}{PU}[1]{#1\83\017}% U+030F
15537 \DeclareTextCommand{\C}{PU}[1]{#1\83\017}% U+030F
15538 % U+0311 COMBINING INVERTED BREVE; breveinvertedcmb
15539 \DeclareTextCommand{\textinvbreve}{PU}[1]{#1\83\021}% U+0311
15540 % U+0323 COMBINING DOT BELOW; dotbelowcmb, *dotbelowcomb
15541 \DeclareTextCommand{\d}{PU}[1]{#1\83\043}% U+0323
15542 % U+0324 COMBINING DIAERESIS BELOW; dieresisbelowcmb; \textsubum-
    laut (tipa)
15543 \DeclareTextCommand{\textsubumlaut}{PU}[1]{#1\83\044}% U+0324
15544 % U+0325 COMBINING RING BELOW; ringbelowcmb; \textsubring (tipa)
15545 \DeclareTextCommand{\textsubring}{PU}[1]{#1\83\045}% U+0325
15546 % U+0327 COMBINING CEDILLA; cedillacmb
15547 \DeclareTextCommand{\c}{PU}[1]{#1\83\047}% U+0327
15548 % U+0328 COMBINING OGONEK; ogonekcmb
15549 \DeclareTextCommand{\k}{PU}[1]{#1\83\050}% U+0328
15550 % U+032D COMBINING CIRCUMFLEX ACCENT BELOW;
15551 % \textsubcircum (tipa)
15552 \DeclareTextCommand{\textsubcircum}{PU}[1]{#1\83\055}% U+032D
15553 % U+032E COMBINING BREVE BELOW; brevebelowcmb
15554 \DeclareTextCommand{\textsubbreve}{PU}[1]{#1\83\056}% U+032E
15555 % U+0330 COMBINING TILDE BELOW; tildebelowcmb; \textsubtilde (tipa)
15556 \DeclareTextCommand{\textsubtilde}{PU}[1]{#1\83\060}% U+0330
15557 % U+0331 COMBINING MACRON BELOW; macronbelowcmb
15558 \DeclareTextCommand{\b}{PU}[1]{#1\83\061}% U+0331
15559 % U+0361 COMBINING DOUBLE INVERTED BREVE; breveinverteddou-
    blecmb
15560 \DeclareTextCommand{\t}{PU}[1]{#1\83\141}% U+0361
15561 % U+20DD COMBINING ENCLOSING CIRCLE
15562 \DeclareTextCommand{\textcircled}{PU}[1]{#1\9040\335}% U+20DD

```

Double accents.

```

15563 \DeclareTextCommand{\textacutemacron}{PU}[1]{#1\83\001\83\004}% U+0301 U+0304
15564 \DeclareTextCommand{\textgravemacron}{PU}[1]{#1\83\000\83\004}% U+0300 U+0304

```

\@empty is an artefact of the NFSS2 machinery, it gets inserted for empty arguments and spaces.

```

15565 \DeclareTextCompositeCommand{\'}{PU}{\@empty}{\textasciigrave}%
15566 \DeclareTextCompositeCommand{\`}{PU}{\@empty}{\textacute}%
15567 \DeclareTextCompositeCommand{\^}{PU}{\@empty}{\textasciicircum}%
15568 \DeclareTextCompositeCommand{\~}{PU}{\@empty}{\texttilde}%
15569 \DeclareTextCompositeCommand{\"}{PU}{\@empty}{\textasciidieresis}%
15570 \DeclareTextCompositeCommand{\r}{PU}{\@empty}{\textstring}%
15571 \DeclareTextCompositeCommand{\v}{PU}{\@empty}{\textasciicaron}%
15572 \DeclareTextCompositeCommand{\.}{PU}{\@empty}{\textdotaccent}%
15573 \DeclareTextCompositeCommand{\c}{PU}{\@empty}{\textcedilla}%
15574 \DeclareTextCompositeCommand{\u}{PU}{\@empty}{\textasciibreve}%
15575 \DeclareTextCompositeCommand{\G}{PU}{\@empty}{\textdoublegrave}%
15576 \DeclareTextCompositeCommand{\=}{PU}{\@empty}{\textasciimacron}%
15577 \DeclareTextCompositeCommand{\H}{PU}{\@empty}{\texthungarumlaut}%
15578 \DeclareTextCompositeCommand{\k}{PU}{\@empty}{\textogonek}%
15579 \DeclareTextCompositeCommand{\textinvbreve}{PU}{\@empty}{\83\021}% U+0311
15580 \DeclareTextCompositeCommand{\textsubumlaut}{PU}{\@empty}{\83\044}% U+0324
15581 \DeclareTextCompositeCommand{\textsubring}{PU}{\@empty}{\textsubring}%
15582 \DeclareTextCompositeCommand{\textsubcircum}{PU}{\@empty}{\textsubcircum-
    low}%
15583 \DeclareTextCompositeCommand{\textsubbreve}{PU}{\@empty}{\83\056}% U+032E
15584 \DeclareTextCompositeCommand{\textsubtilde}{PU}{\@empty}{\textsubtilde}%

```

```

15585 \DeclareTextCompositeCommand{\b}{PU}{\@empty}{\textmacronbelow}%
15586 \DeclareTextCompositeCommand{\d}{PU}{\@empty}{\textdotbelow}%
15587 \DeclareTextCompositeCommand{\t}{PU}{\@empty}{\texttie}%
15588 \DeclareTextCompositeCommand{\newtie}{PU}{\@empty}{\textnewtie}%
15589 \DeclareTextCompositeCommand{\textcircled}{PU}{\@empty}{\textbigcircle}%
15590 \DeclareTextCompositeCommand{\textacutemacron}{PU}{\@empty}{\{\ \83\001\83\004\}}% U+0301 U
15591 \DeclareTextCompositeCommand{\textgravemacron}{PU}{\@empty}{\{\ \83\000\83\004\}}% U+0300 U
15592 \DeclareTextCompositeCommand{\'}{PU}{\ }{\textasciigrave}%
15593 \DeclareTextCompositeCommand{\`}{PU}{\ }{\textacute}%
15594 \DeclareTextCompositeCommand{\^}{PU}{\ }{\textasciicircum}%
15595 \DeclareTextCompositeCommand{\~}{PU}{\ }{\texttilde}%
15596 \DeclareTextCompositeCommand{\"}{PU}{\ }{\textasciidieresis}%
15597 \DeclareTextCompositeCommand{\r}{PU}{\ }{\textring}%
15598 \DeclareTextCompositeCommand{\v}{PU}{\ }{\textasciicaron}%
15599 \DeclareTextCompositeCommand{\.}{PU}{\ }{\textdotaccent}%
15600 \DeclareTextCompositeCommand{\c}{PU}{\ }{\textcedilla}%
15601 \DeclareTextCompositeCommand{\u}{PU}{\ }{\textasciibreve}%
15602 \DeclareTextCompositeCommand{\G}{PU}{\ }{\textdoublegrave}%
15603 \DeclareTextCompositeCommand{\=}{PU}{\ }{\textasciimacron}%
15604 \DeclareTextCompositeCommand{\H}{PU}{\ }{\texthungarumlaut}%
15605 \DeclareTextCompositeCommand{\k}{PU}{\ }{\textogonek}%
15606 \DeclareTextCompositeCommand{\textinvbreve}{PU}{\ }{\{\ \83\021\}}% U+0311
15607 \DeclareTextCompositeCommand{\textsubumlaut}{PU}{\ }{\{\ \83\044\}}% U+0324
15608 \DeclareTextCompositeCommand{\textsubring}{PU}{\ }{\texttringlow}%
15609 \DeclareTextCompositeCommand{\textsubcircum}{PU}{\ }{\textcircumlow}%
15610 \DeclareTextCompositeCommand{\textsubbreve}{PU}{\ }{\{\ \83\056\}}% U+032E
15611 \DeclareTextCompositeCommand{\textsubtilde}{PU}{\ }{\texttildelow}%
15612 \DeclareTextCompositeCommand{\b}{PU}{\ }{\textmacronbelow}%
15613 \DeclareTextCompositeCommand{\d}{PU}{\ }{\textdotbelow}%
15614 \DeclareTextCompositeCommand{\t}{PU}{\ }{\texttie}%
15615 \DeclareTextCompositeCommand{\newtie}{PU}{\ }{\textnewtie}%
15616 \DeclareTextCompositeCommand{\textcircled}{PU}{\ }{\textbigcircle}%
15617 \DeclareTextCompositeCommand{\textacutemacron}{PU}{\ }{\{\ \83\001\83\004\}}% U+0301 U+0304
15618 \DeclareTextCompositeCommand{\textgravemacron}{PU}{\ }{\{\ \83\000\83\004\}}% U+0300 U+0304

```

Accents for capitals (see encoding TS1)

```

15619 \DeclareTextCommand{\capitalcedilla}{PU}[1]{\c{#1}}%
15620 \DeclareTextCommand{\capitalogonek}{PU}[1]{\k{#1}}%
15621 \DeclareTextCommand{\capitalgrave}{PU}[1]{\`{#1}}%
15622 \DeclareTextCommand{\capitalacute}{PU}[1]{\^{#1}}%
15623 \DeclareTextCommand{\capitalcircumflex}{PU}[1]{\^{#1}}%
15624 \DeclareTextCommand{\capitaltilde}{PU}[1]{\~{#1}}%
15625 \DeclareTextCommand{\capitaldieresis}{PU}[1]{\"}{#1}}%
15626 \DeclareTextCommand{\capitalhungarumlaut}{PU}[1]{\H{#1}}%
15627 \DeclareTextCommand{\capitalring}{PU}[1]{\r{#1}}%
15628 \DeclareTextCommand{\capitalcaron}{PU}[1]{\v{#1}}%
15629 \DeclareTextCommand{\capitalbreve}{PU}[1]{\u{#1}}%
15630 \DeclareTextCommand{\capitalmacron}{PU}[1]{\={#1}}%
15631 \DeclareTextCommand{\capitaldotaccent}{PU}[1]{\.{#1}}%
15632 \DeclareTextCommand{\capitaltie}{PU}[1]{\t{#1}}%
15633 \DeclareTextCommand{\capitalnewtie}{PU}[1]{\newtie{#1}}%

```

51.2.2 Basic Latin: U+0000 to U+007F

Special white space escape characters.

```

15634 % U+0009 (CHARACTER TABULATION)
15635 \DeclareTextCommand{\textHT}{PU}{\80\011}% U+0009
15636 % U+000A (LINE FEED)

```

15637 \DeclareTextCommand{\textLF}{PU}{\80\012}% U+000A
 15638 % U+000D (CARRIAGE RETURN)
 15639 \DeclareTextCommand{\textCR}{PU}{\80\015}% U+000D
 \80\040: U+0020 SPACE; space, spacehackarabic
 \80\041: U+0021 EXCLAMATION MARK; exclam
 15640 % U+0022 QUOTATION MARK; quotedbl
 15641 \DeclareTextCommand{\textquotedbl}{PU}{"}% \80\042 U+0022
 15642 % U+0023 NUMBER SIGN; numbersign
 15643 \DeclareTextCommand{\textnumbersign}{PU}{\80\043}% U+0023
 15644 % U+0024 DOLLAR SIGN; dollar
 15645 \DeclareTextCommand{\textdollar}{PU}{\80\044}% U+0024
 15646 %* \textdollar -> \mathdollar
 15647 %* \textdollar -> \EyesDollar (marvosym)
 15648 % U+0025 PERCENT SIGN; percent
 15649 \DeclareTextCommand{\textpercent}{PU}{\80\045}% U+0025
 15650 % U+0026 AMPERSAND; ampersand
 15651 \DeclareTextCommand{\textampersand}{PU}{\80\046}% U+0026
 15652 %* \textampersand -> \binampersand (stmaryrd)
 15653 %* \textampersand -> \with (cml)
 15654 % U+0027 APOSTROPHE; quotesingle
 15655 \DeclareTextCommand{\textquotesingle}{PU}{\80\047}% U+0027
 15656 % U+0028 LEFT PARENTHESIS; parenleft
 15657 \DeclareTextCommand{\textparenleft}{PU}{\80\050}% U+0028
 15658 % U+0029 RIGHT PARENTHESIS; parenright
 15659 \DeclareTextCommand{\textparenright}{PU}{\80\051}% U+0029
 15660 % U+002A ASTERISK; asterisk; (?)
 15661 \DeclareTextCommand{\textasteriskcentered}{PU}{\80\052}% U+002A
 15662 % U+002B PLUS SIGN; plus; \MVPlus (marvosym)
 15663 \DeclareTextCommand{\textMVPlus}{PU}{\80\053}%* U+002B
 15664 % U+002C COMMA; comma; \MVComma (marvosym)
 15665 \DeclareTextCommand{\textMVComma}{PU}{\80\054}%* U+002C
 15666 % U+002D HYPHEN-MINUS; hyphen; \MVMinus (marvosym)
 15667 \DeclareTextCommand{\textMVMinus}{PU}{\80\055}%* U+002D
 15668 % U+002E FULL STOP; period; \MVPeriod (marvosym)
 15669 \DeclareTextCommand{\textMVPeriod}{PU}{\80\056}%* U+002E
 15670 % U+002F SOLIDUS; slash; \MVDivision (marvosym)
 15671 \DeclareTextCommand{\textMVDivision}{PU}{\80\057}%* U+002F
 15672 % U+0030 DIGIT ZERO; zero; \MVZero (marvosym)
 15673 \DeclareTextCommand{\textMVZero}{PU}{\80\060}%* U+0030
 15674 % U+0031 DIGIT ONE; one; \MVOne (marvosym)
 15675 \DeclareTextCommand{\textMVOne}{PU}{\80\061}%* U+0031
 15676 % U+0032 DIGIT TWO; two; \MVTwo (marvosym)
 15677 \DeclareTextCommand{\textMVTwo}{PU}{\80\062}%* U+0032
 15678 % U+0033 DIGIT THREE; three; \MVThree (marvosym)
 15679 \DeclareTextCommand{\textMVThree}{PU}{\80\063}%* U+0033
 15680 % U+0034 DIGIT FOUR; four; \MVFfour (marvosym)
 15681 \DeclareTextCommand{\textMVFfour}{PU}{\80\064}%* U+0034
 15682 % U+0035 DIGIT FIVE; five; \MVFfive (marvosym)
 15683 \DeclareTextCommand{\textMVFfive}{PU}{\80\065}%* U+0035
 15684 % U+0036 DIGIT SIX; six; \MVSix (marvosym)
 15685 \DeclareTextCommand{\textMVSix}{PU}{\80\066}%* U+0036
 15686 % U+0037 DIGIT SEVEN; seven; \MVSeven (marvosym)
 15687 \DeclareTextCommand{\textMVSeven}{PU}{\80\067}%* U+0037
 15688 % U+0038 DIGIT EIGHT; eight; \MVEight (marvosym)
 15689 \DeclareTextCommand{\textMVEight}{PU}{\80\070}%* U+0038
 15690 % U+0039 DIGIT NINE; nine; \MVNine (marvosym)
 15691 \DeclareTextCommand{\textMVNine}{PU}{\80\071}%* U+0039

$\backslash 80\backslash 072$: U+003A COLON; colon
 $\backslash 80\backslash 073$: U+003B SEMICOLON; semicolon
15692 % U+003C LESS-THAN SIGN; less
15693 $\backslash \text{DeclareTextCommand}\{\backslash \text{textless}\}\{\text{PU}\}\{<\}\%$ $\backslash 80\backslash 074$ U+003C
 $\backslash 80\backslash 075$: U+003D EQUALS SIGN; equal
15694 % U+003E GREATER-THAN SIGN; greater
15695 $\backslash \text{DeclareTextCommand}\{\backslash \text{textgreater}\}\{\text{PU}\}\{>\}\%$ $\backslash 80\backslash 076$ U+003E
 $\backslash 80\backslash 077$: U+003F QUESTION MARK; question
15696 % U+0040 COMMERCIAL AT; at; $\backslash \text{MVAt}$ (marvosym)
15697 $\backslash \text{DeclareTextCommand}\{\backslash \text{textMVAt}\}\{\text{PU}\}\{\backslash 80\backslash 100\}\%$ U+0040
 $\backslash 80\backslash 101$: U+0041 LATIN CAPITAL LETTER A; A
...
 $\backslash 80\backslash 132$: U+005A LATIN CAPITAL LETTER Z; Z
 $\backslash 80\backslash 133$: U+005B LEFT SQUARE BRACKET; bracketleft
15698 % U+005C REVERSE SOLIDUS; backslash
15699 $\backslash \text{DeclareTextCommand}\{\backslash \text{textbackslash}\}\{\text{PU}\}\{\backslash 80\backslash 134\}\%$ U+005C
 $\backslash 80\backslash 135$: U+005D RIGHT SQUARE BRACKET; bracketright
15700 % U+005E CIRCUMFLEX ACCENT; asciicircum
15701 $\backslash \text{DeclareTextCommand}\{\backslash \text{textasciicircum}\}\{\text{PU}\}\{\backslash 80\backslash 136\}\%$ U+005E
15702 % U+005F LOW LINE; underscore
15703 $\backslash \text{DeclareTextCommand}\{\backslash \text{textunderscore}\}\{\text{PU}\}\{\backslash 80\backslash 137\}\%$ U+005F
15704 %* $\backslash \text{textunderscore} \rightarrow \backslash \text{mathunderscore}$ (LaTeX)
15705 % U+0060 GRAVE ACCENT; grave
15706 $\backslash \text{DeclareTextCommand}\{\backslash \text{textasciigrave}\}\{\text{PU}\}\{\backslash 80\backslash 140\}\%$ U+0060
 $\backslash 80\backslash 141$: U+0061 LATIN SMALL LETTER A; a
...
 $\backslash 80\backslash 150$: U+0068 LATIN SMALL LETTER H; h
15707 % U+0069 LATIN SMALL LETTER I; i
15708 $\backslash \text{DeclareTextCompositeCommand}\{\backslash .\}\{\text{PU}\}\{\text{i}\}\{\text{i}\}\%$ $\backslash 80\backslash 151$ U+0069
15709 $\backslash \text{DeclareTextCompositeCommand}\{\backslash .\}\{\text{PU}\}\{\text{i}\}\{\text{i}\}\%$ $\backslash 80\backslash 151$ U+0069
 $\backslash 80\backslash 152$: U+006A LATIN SMALL LETTER J; j
...
 $\backslash 80\backslash 172$: U+007A LATIN SMALL LETTER Z; z
15710 % U+007B LEFT CURLY BRACKET; braceleft
15711 $\backslash \text{DeclareTextCommand}\{\backslash \text{textbraceleft}\}\{\text{PU}\}\{\backslash 80\backslash 173\}\%$ U+007B
15712 % U+007C VERTICAL LINE; *bar, verticalbar
15713 $\backslash \text{DeclareTextCommand}\{\backslash \text{textbar}\}\{\text{PU}\}\{\text{|}\}\%$ $\backslash 80\backslash 174$ U+007C
15714 %* $\backslash \text{textbar} \rightarrow \backslash \text{textvbar}$ (tipa)
15715 % U+007D RIGHT CURLY BRACKET; braceright
15716 $\backslash \text{DeclareTextCommand}\{\backslash \text{textbraceright}\}\{\text{PU}\}\{\backslash 80\backslash 175\}\%$ U+007D
15717 % U+007E TILDE; asciitilde
15718 $\backslash \text{DeclareTextCommand}\{\backslash \text{textasciitilde}\}\{\text{PU}\}\{\backslash 80\backslash 176\}\%$ U+007E

51.2.3 Latin-1 Supplement: U+0080 to U+00FF

$\backslash 80\backslash 240$: U+00A0 NO-BREAK SPACE; nbspace, nonbreakingspace
15719 % U+00A1 INVERTED EXCLAMATION MARK; exclamdown
15720 $\backslash \text{DeclareTextCommand}\{\backslash \text{textexclamdown}\}\{\text{PU}\}\{\backslash 80\backslash 241\}\%$ U+00A1
15721 % U+00A2 CENT SIGN; cent
15722 $\backslash \text{DeclareTextCommand}\{\backslash \text{textcent}\}\{\text{PU}\}\{\backslash 80\backslash 242\}\%$ U+00A2
15723 % U+00A3 POUND SIGN; sterling
15724 $\backslash \text{DeclareTextCommand}\{\backslash \text{textsterling}\}\{\text{PU}\}\{\backslash 80\backslash 243\}\%$ U+00A3
15725 %* $\backslash \text{textsterling} \rightarrow \backslash \text{mathsterling}$ (LaTeX)

15726 %* \textsterling -> \pounds (LaTeX)
 15727 % U+00A4 CURRENCY SIGN; currency
 15728 \DeclareTextCommand{\textcurrency}{PU}{\80\244}% U+00A4
 15729 % U+00A5 YEN SIGN; yen
 15730 \DeclareTextCommand{\textyen}{PU}{\80\245}% U+00A5
 15731 % U+00A6 BROKEN BAR; brokenbar
 15732 \DeclareTextCommand{\textbrokenbar}{PU}{\80\246}% U+00A6
 15733 %* \textbrokenbar -> \brokenvert (wasysym)
 15734 % U+00A7 SECTION SIGN; section
 15735 \DeclareTextCommand{\textsection}{PU}{\80\247}% U+00A7
 15736 %* \textsection -> \mathsection (LaTeX)
 15737 %* \textsection -> \S (LaTeX)
 15738 % U+00A8 DIAERESIS; dieresis
 15739 \DeclareTextCommand{\textasciidieresis}{PU}{\80\250}% U+00A8
 15740 % U+00A9 COPYRIGHT SIGN; copyright
 15741 \DeclareTextCommand{\textcopyright}{PU}{\80\251}%* U+00A9
 15742 % U+00AA FEMININE ORDINAL INDICATOR; ordfeminine
 15743 \DeclareTextCommand{\textordfeminine}{PU}{\80\252}% U+00AA
 15744 % U+00AB LEFT-POINTING DOUBLE ANGLE QUOTATION MARK; guillemotleft
 15745 \DeclareTextCommand{\guillemotleft}{PU}{\80\253}% U+00AB
 15746 % U+00AC NOT SIGN; logicalnot
 15747 \DeclareTextCommand{\textlogicalnot}{PU}{\80\254}% U+00AC
 15748 \DeclareTextCommand{\textlnot}{PU}{\80\254}% U+00AC
 \80\255: U+00AD SOFT HYPHEN; sftthyphen, softthyphen
 15749 % U+00AE REGISTERED SIGN; registered
 15750 \DeclareTextCommand{\textregistered}{PU}{\80\256}% U+00AE
 15751 % U+00AF MACRON; *macron, overscore
 15752 \DeclareTextCommand{\textasciimacron}{PU}{\80\257}% U+00AF
 15753 % U+00B0 DEGREE SIGN; degree
 15754 \DeclareTextCommand{\textdegree}{PU}{\80\260}% U+00B0
 15755 % U+00B1 PLUS-MINUS SIGN; plusminus
 15756 \DeclareTextCommand{\textplusminus}{PU}{\80\261}% U+00B1
 15757 % U+00B2 SUPERSCRIPT TWO; twosuperior
 15758 \DeclareTextCommand{\texttwosuperior}{PU}{\80\262}%* U+00B2
 15759 % U+00B3 SUPERSCRIPT THREE; threesuperior
 15760 \DeclareTextCommand{\textthreesuperior}{PU}{\80\263}%* U+00B3
 15761 % U+00B4 ACUTE ACCENT; acute
 15762 \DeclareTextCommand{\textacute}{PU}{\80\264}% U+00B4
 15763 \DeclareTextCommand{\textasciiacute}{PU}{\80\264}% U+00B4
 15764 % U+00B5 MICRO SIGN; mu, mu1
 15765 \DeclareTextCommand{\textmu}{PU}{\80\265}% U+00B5
 15766 % U+00B6 PILCROW SIGN; paragraph
 15767 \DeclareTextCommand{\textparagraph}{PU}{\80\266}% U+00B6
 15768 %* \textparagraph -> \mathparagraph (LaTeX)
 15769 % U+00B7 MIDDLE DOT; middot, *periodcentered
 15770 \DeclareTextCommand{\textperiodcentered}{PU}{\80\267}% U+00B7
 15771 %* \textperiodcentered -> \MultiplicationDot (marvosym)
 15772 %* \textperiodcentered -> \Squaredot (marvosym)
 15773 % U+00B8 CEDILLA; cedilla
 15774 \DeclareTextCommand{\textcedilla}{PU}{\80\270}% U+00B8
 15775 % U+00B9 SUPERSCRIPT ONE; onesuperior
 15776 \DeclareTextCommand{\textonesuperior}{PU}{\80\271}%* U+00B9
 15777 % U+00BA MASCULINE ORDINAL INDICATOR; ordmasculine
 15778 \DeclareTextCommand{\textordmasculine}{PU}{\80\272}% U+00BA
 15779 % U+00BB RIGHT-POINTING DOUBLE ANGLE QUOTATION MARK; guillemotright

15780 \DeclareTextCommand{\guillemotright}{PU}{\80\273}% U+00BB
15781 % U+00BC VULGAR FRACTION ONE QUARTER; onequarter
15782 \DeclareTextCommand{\textonequarter}{PU}{\80\274}% U+00BC
15783 % U+00BD VULGAR FRACTION ONE HALF; onehalf
15784 \DeclareTextCommand{\textonehalf}{PU}{\80\275}% U+00BD
15785 % U+00BE VULGAR FRACTION THREE QUARTERS; threequarters
15786 \DeclareTextCommand{\textthreequarters}{PU}{\80\276}% U+00BE
15787 % U+00BF INVERTED QUESTION MARK; questiondown
15788 \DeclareTextCommand{\textquestiondown}{PU}{\80\277}% U+00BF
15789 % U+00C0 LATIN CAPITAL LETTER A WITH GRAVE; Agrave
15790 \DeclareTextCompositeCommand{\`}{PU}{A}{\80\300}% U+00C0
15791 % U+00C1 LATIN CAPITAL LETTER A WITH ACUTE; Aacute
15792 \DeclareTextCompositeCommand{\'}{PU}{A}{\80\301}% U+00C1
15793 % U+00C2 LATIN CAPITAL LETTER A WITH CIRCUMFLEX; Acircumflex
15794 \DeclareTextCompositeCommand{\^}{PU}{A}{\80\302}% U+00C2
15795 % U+00C3 LATIN CAPITAL LETTER A WITH TILDE; Atilde
15796 \DeclareTextCompositeCommand{\~}{PU}{A}{\80\303}% U+00C3
15797 % U+00C4 LATIN CAPITAL LETTER A WITH DIAERESIS; Adieresis
15798 \DeclareTextCompositeCommand{\"}{PU}{A}{\80\304}% U+00C4
15799 % U+00C5 LATIN CAPITAL LETTER A WITH RING ABOVE; Aring
15800 \DeclareTextCompositeCommand{\r}{PU}{A}{\80\305}% U+00C5
15801 % U+00C6 LATIN CAPITAL LETTER AE; AE
15802 \DeclareTextCommand{\AE}{PU}{\80\306}% U+00C6
15803 % U+00C7 LATIN CAPITAL LETTER C WITH CEDILLA; Ccedilla
15804 \DeclareTextCompositeCommand{\c}{PU}{C}{\80\307}% U+00C7
15805 % U+00C8 LATIN CAPITAL LETTER E WITH GRAVE; Egrave
15806 \DeclareTextCompositeCommand{\`}{PU}{E}{\80\310}% U+00C8
15807 % U+00C9 LATIN CAPITAL LETTER E WITH ACUTE; Eacute
15808 \DeclareTextCompositeCommand{\'}{PU}{E}{\80\311}% U+00C9
15809 % U+00CA LATIN CAPITAL LETTER E WITH CIRCUMFLEX; Ecircumflex
15810 \DeclareTextCompositeCommand{\^}{PU}{E}{\80\312}% U+00CA
15811 % U+00CB LATIN CAPITAL LETTER E WITH DIAERESIS; Edieresis
15812 \DeclareTextCompositeCommand{\"}{PU}{E}{\80\313}% U+00CB
15813 % U+00CC LATIN CAPITAL LETTER I WITH GRAVE; Igrave
15814 \DeclareTextCompositeCommand{\`}{PU}{I}{\80\314}% U+00CC
15815 % U+00CD LATIN CAPITAL LETTER I WITH ACUTE; Iacute
15816 \DeclareTextCompositeCommand{\'}{PU}{I}{\80\315}% U+00CD
15817 % U+00CE LATIN CAPITAL LETTER I WITH CIRCUMFLEX; Icircumflex
15818 \DeclareTextCompositeCommand{\^}{PU}{I}{\80\316}% U+00CE
15819 % U+00CF LATIN CAPITAL LETTER I WITH DIAERESIS; Idieresis
15820 \DeclareTextCompositeCommand{\"}{PU}{I}{\80\317}% U+00CF
15821 % U+00D0 LATIN CAPITAL LETTER ETH; Eth
15822 \DeclareTextCommand{\DH}{PU}{\80\320}% U+00D0
15823 % U+00D1 LATIN CAPITAL LETTER N WITH TILDE; Ntilde
15824 \DeclareTextCompositeCommand{\~}{PU}{N}{\80\321}% U+00D1
15825 % U+00D2 LATIN CAPITAL LETTER O WITH GRAVE; Ograve
15826 \DeclareTextCompositeCommand{\`}{PU}{O}{\80\322}% U+00D2
15827 % U+00D3 LATIN CAPITAL LETTER O WITH ACUTE; Oacute
15828 \DeclareTextCompositeCommand{\'}{PU}{O}{\80\323}% U+00D3
15829 % U+00D4 LATIN CAPITAL LETTER O WITH CIRCUMFLEX; Ocircumflex
15830 \DeclareTextCompositeCommand{\^}{PU}{O}{\80\324}% U+00D4
15831 % U+00D5 LATIN CAPITAL LETTER O WITH TILDE; Otilde
15832 \DeclareTextCompositeCommand{\~}{PU}{O}{\80\325}% U+00D5
15833 % U+00D6 LATIN CAPITAL LETTER O WITH DIAERESIS; Odieresis
15834 \DeclareTextCompositeCommand{\"}{PU}{O}{\80\326}% U+00D6
15835 % U+00D7 MULTIPLICATION SIGN; multiply
15836 \DeclareTextCommand{\textmultiply}{PU}{\80\327}% U+00D7

15837 %* \textmultiply -> \vartimes (stmaryrd)
15838 %* \textmultiply -> \MVMultiplication (marvosym)
15839 % U+00D8 LATIN CAPITAL LETTER O WITH STROKE; Oslash
15840 \DeclareTextCommand{\O}{PU}{\80\330}% U+00D8
15841 % U+00D9 LATIN CAPITAL LETTER U WITH GRAVE; Ugrave
15842 \DeclareTextCompositeCommand{\'}{PU}{U}{\80\331}% U+00D9
15843 % U+00DA LATIN CAPITAL LETTER U WITH ACUTE; Uacute
15844 \DeclareTextCompositeCommand{\'}{PU}{U}{\80\332}% U+00DA
15845 % U+00DB LATIN CAPITAL LETTER U WITH CIRCUMFLEX; Ucircumflex
15846 \DeclareTextCompositeCommand{\^}{PU}{U}{\80\333}% U+00DB
15847 % U+00DC LATIN CAPITAL LETTER U WITH DIAERESIS; Udieresis
15848 \DeclareTextCompositeCommand{\"}{PU}{U}{\80\334}% U+00DC
15849 % U+00DD LATIN CAPITAL LETTER Y WITH ACUTE; Yacute
15850 \DeclareTextCompositeCommand{\'}{PU}{Y}{\80\335}% U+00DD
15851 % U+00DE LATIN CAPITAL LETTER THORN; Thorn; \TH, \Thorn (wasysym)
15852 \DeclareTextCommand{\TH}{PU}{\80\336}% U+00DE
15853 \DeclareTextCommand{\textThorn}{PU}{\80\336}%* U+00DE
15854 % U+00DF LATIN SMALL LETTER SHARP S; germandbls
15855 \DeclareTextCommand{\ss}{PU}{\80\337}% U+00DF
15856 % U+00E0 LATIN SMALL LETTER A WITH GRAVE; agrave
15857 \DeclareTextCompositeCommand{\'}{PU}{a}{\80\340}% U+00E0
15858 % U+00E1 LATIN SMALL LETTER A WITH ACUTE; aacute
15859 \DeclareTextCompositeCommand{\'}{PU}{a}{\80\341}% U+00E1
15860 % U+00E2 LATIN SMALL LETTER A WITH CIRCUMFLEX; acircumflex
15861 \DeclareTextCompositeCommand{\^}{PU}{a}{\80\342}% U+00E2
15862 % U+00E3 LATIN SMALL LETTER A WITH TILDE; atilde
15863 \DeclareTextCompositeCommand{\~}{PU}{a}{\80\343}% U+00E3
15864 % U+00E4 LATIN SMALL LETTER A WITH DIAERESIS; adieresis
15865 \DeclareTextCompositeCommand{\"}{PU}{a}{\80\344}% U+00E4
15866 % U+00E5 LATIN SMALL LETTER A WITH RING ABOVE; aring
15867 \DeclareTextCompositeCommand{\r}{PU}{a}{\80\345}% U+00E5
15868 % U+00E6 LATIN SMALL LETTER AE; ae
15869 \DeclareTextCommand{\ae}{PU}{\80\346}% U+00E6
15870 % U+00E7 LATIN SMALL LETTER C WITH CEDILLA; ccedilla
15871 \DeclareTextCompositeCommand{\c}{PU}{c}{\80\347}% U+00E7
15872 % U+00E8 LATIN SMALL LETTER E WITH GRAVE; egrave
15873 \DeclareTextCompositeCommand{\'}{PU}{e}{\80\350}% U+00E8
15874 % U+00E9 LATIN SMALL LETTER E WITH ACUTE; eacute
15875 \DeclareTextCompositeCommand{\'}{PU}{e}{\80\351}% U+00E9
15876 % U+00EA LATIN SMALL LETTER E WITH CIRCUMFLEX; ecircumflex
15877 \DeclareTextCompositeCommand{\^}{PU}{e}{\80\352}% U+00EA
15878 % U+00EB LATIN SMALL LETTER E WITH DIAERESIS; edieresis
15879 \DeclareTextCompositeCommand{\"}{PU}{e}{\80\353}% U+00EB
15880 % U+00EC LATIN SMALL LETTER I WITH GRAVE; igrave
15881 \DeclareTextCompositeCommand{\'}{PU}{i}{\80\354}% U+00EC
15882 \DeclareTextCompositeCommand{\'}{PU}{i}{\80\354}% U+00EC
15883 % U+00ED LATIN SMALL LETTER I WITH ACUTE; iacute
15884 \DeclareTextCompositeCommand{\'}{PU}{i}{\80\355}% U+00ED
15885 \DeclareTextCompositeCommand{\'}{PU}{i}{\80\355}% U+00ED
15886 % U+00EE LATIN SMALL LETTER I WITH CIRCUMFLEX; icircumflex
15887 \DeclareTextCompositeCommand{\^}{PU}{i}{\80\356}% U+00EE
15888 \DeclareTextCompositeCommand{\^}{PU}{i}{\80\356}% U+00EE
15889 % U+00EF LATIN SMALL LETTER I WITH DIAERESIS; idieresis
15890 \DeclareTextCompositeCommand{\"}{PU}{i}{\80\357}% U+00EF
15891 \DeclareTextCompositeCommand{\"}{PU}{i}{\80\357}% U+00EF
15892 % U+00F0 LATIN SMALL LETTER ETH; eth
15893 \DeclareTextCommand{\dh}{PU}{\80\360}% U+00F0

15894 %* \dh -> \eth (wsuipa, phonetic)
 15895 % U+00F1 LATIN SMALL LETTER N WITH TILDE; ntilde
 15896 \DeclareTextCompositeCommand{\~}{PU}{n}{\80\361}% U+00F1
 15897 % U+00F2 LATIN SMALL LETTER O WITH GRAVE; ograve
 15898 \DeclareTextCompositeCommand{\`}{PU}{o}{\80\362}% U+00F2
 15899 % U+00F3 LATIN SMALL LETTER O WITH ACUTE; oacute
 15900 \DeclareTextCompositeCommand{\'}{PU}{o}{\80\363}% U+00F3
 15901 % U+00F4 LATIN SMALL LETTER O WITH CIRCUMFLEX; ocircumflex
 15902 \DeclareTextCompositeCommand{\^}{PU}{o}{\80\364}% U+00F4
 15903 % U+00F5 LATIN SMALL LETTER O WITH TILDE; otilde
 15904 \DeclareTextCompositeCommand{\~}{PU}{o}{\80\365}% U+00F5
 15905 % U+00F6 LATIN SMALL LETTER O WITH DIAERESIS; odieresis
 15906 \DeclareTextCompositeCommand{\"}{PU}{o}{\80\366}% U+00F6
 15907 % U+00F7 DIVISION SIGN; divide
 15908 \DeclareTextCommand{\textdivide}{PU}{\80\367}% U+00F7
 15909 % U+00F8 LATIN SMALL LETTER O WITH STROKE; oslash
 15910 \DeclareTextCommand{\o}{PU}{\80\370}% U+00F8
 15911 % U+00F9 LATIN SMALL LETTER U WITH GRAVE; ugrave
 15912 \DeclareTextCompositeCommand{\`}{PU}{u}{\80\371}% U+00F9
 15913 % U+00FA LATIN SMALL LETTER U WITH ACUTE; uacute
 15914 \DeclareTextCompositeCommand{\'}{PU}{u}{\80\372}% U+00FA
 15915 % U+00FB LATIN SMALL LETTER U WITH CIRCUMFLEX; ucircumflex
 15916 \DeclareTextCompositeCommand{\^}{PU}{u}{\80\373}% U+00FB
 15917 % U+00FC LATIN SMALL LETTER U WITH DIAERESIS; udieresis
 15918 \DeclareTextCompositeCommand{\"}{PU}{u}{\80\374}% U+00FC
 15919 % U+00FD LATIN SMALL LETTER Y WITH ACUTE; yacute
 15920 \DeclareTextCompositeCommand{\'}{PU}{y}{\80\375}% U+00FD
 15921 % U+00FE LATIN SMALL LETTER THORN; thorn;
 15922 % \th, \thorn (wasysym), \textthorn (tipa)
 15923 \DeclareTextCommand{\th}{PU}{\80\376}% U+00FE
 15924 \DeclareTextCommand{\textthorn}{PU}{\80\376}%* U+00FE
 15925 % U+00FF LATIN SMALL LETTER Y WITH DIAERESIS; ydieresis
 15926 \DeclareTextCompositeCommand{\"}{PU}{y}{\80\377}% U+00FF

51.2.4 Latin Extended-A: U+0080 to U+017F

15927 % U+0100 LATIN CAPITAL LETTER A WITH MACRON; Amacron
 15928 \DeclareTextCompositeCommand{\=}{PU}{A}{\81\000}% U+0100
 15929 % U+0101 LATIN SMALL LETTER A WITH MACRON; amacron
 15930 \DeclareTextCompositeCommand{\=}{PU}{a}{\81\001}% U+0101
 15931 % U+0102 LATIN CAPITAL LETTER A WITH BREVE; Abreve
 15932 \DeclareTextCompositeCommand{\u}{PU}{A}{\81\002}% U+0102
 15933 % U+0103 LATIN SMALL LETTER A WITH BREVE; abreve
 15934 \DeclareTextCompositeCommand{\u}{PU}{a}{\81\003}% U+0103
 15935 % U+0104 LATIN CAPITAL LETTER A WITH OGONEK; Aogonek
 15936 \DeclareTextCompositeCommand{\k}{PU}{A}{\81\004}% U+0104
 15937 % U+0105 LATIN SMALL LETTER A WITH OGONEK; aogonek
 15938 \DeclareTextCompositeCommand{\k}{PU}{a}{\81\005}% U+0105
 15939 % U+0106 LATIN CAPITAL LETTER C WITH ACUTE; Cacute
 15940 \DeclareTextCompositeCommand{\'}{PU}{C}{\81\006}% U+0106
 15941 % U+0107 LATIN SMALL LETTER C WITH ACUTE; cacute
 15942 \DeclareTextCompositeCommand{\'}{PU}{c}{\81\007}% U+0107
 15943 % U+0108 LATIN CAPITAL LETTER C WITH CIRCUMFLEX; Ccircumflex
 15944 \DeclareTextCompositeCommand{\^}{PU}{C}{\81\010}% U+0108
 15945 % U+0109 LATIN SMALL LETTER C WITH CIRCUMFLEX; ccircumflex
 15946 \DeclareTextCompositeCommand{\^}{PU}{c}{\81\011}% U+0109

15947 % U+010A LATIN CAPITAL LETTER C WITH DOT ABOVE; Cdot, Cdotaccent
15948 \DeclareTextCompositeCommand{\.}{PU}{C}{\81\012}% U+010A
15949 % U+010B LATIN SMALL LETTER C WITH DOT ABOVE; cdot, cdotaccent
15950 \DeclareTextCompositeCommand{\.}{PU}{c}{\81\013}% U+010B
15951 % U+010C LATIN CAPITAL LETTER C WITH CARON; Ccaron
15952 \DeclareTextCompositeCommand{\v}{PU}{C}{\81\014}% U+010C
15953 % U+010D LATIN SMALL LETTER C WITH CARON; ccaron
15954 \DeclareTextCompositeCommand{\v}{PU}{c}{\81\015}% U+010D
15955 % U+010E LATIN CAPITAL LETTER D WITH CARON; Dcaron
15956 \DeclareTextCompositeCommand{\v}{PU}{D}{\81\016}% U+010E
15957 % U+010F LATIN SMALL LETTER D WITH CARON; dcaron
15958 \DeclareTextCompositeCommand{\v}{PU}{d}{\81\017}% U+010F
15959 % U+0110 LATIN CAPITAL LETTER D WITH STROKE; Dcroat, Dslash
15960 \DeclareTextCommand{\DJ}{PU}{\81\020}% U+0110
15961 % U+0111 LATIN SMALL LETTER D WITH STROKE; dcroat, dmacron;
15962 % \textcrd (tipa)
15963 \DeclareTextCommand{\dj}{PU}{\81\021}% U+0111
15964 \DeclareTextCommand{\textcrd}{PU}{\81\021}% U+0111
15965 %* \textcrd -> \crossd (wsuipa)
15966 % An alternate glyph with the stroke through the bowl:
15967 %* \textcrd -> \textbard (tipa)
15968 %* \textcrd -> \bard (wsuipa)
15969 % U+0112 LATIN CAPITAL LETTER E WITH MACRON; Emacron
15970 \DeclareTextCompositeCommand{\=}{PU}{E}{\81\022}% U+0112
15971 % U+0113 LATIN SMALL LETTER E WITH MACRON; emacron
15972 \DeclareTextCompositeCommand{\=}{PU}{e}{\81\023}% U+0113
15973 % U+0114 LATIN CAPITAL LETTER E WITH BREVE; Ebreve
15974 \DeclareTextCompositeCommand{\u}{PU}{E}{\81\024}% U+0114
15975 % U+0115 LATIN SMALL LETTER E WITH BREVE; ebreve
15976 \DeclareTextCompositeCommand{\u}{PU}{e}{\81\025}% U+0115
15977 % U+0116 LATIN CAPITAL LETTER E WITH DOT ABOVE; Edot, Edotaccent
15978 \DeclareTextCompositeCommand{\.}{PU}{E}{\81\026}% U+0116
15979 % U+0117 LATIN SMALL LETTER E WITH DOT ABOVE; edot, edotaccent
15980 \DeclareTextCompositeCommand{\.}{PU}{e}{\81\027}% U+0117
15981 % U+0118 LATIN CAPITAL LETTER E WITH OGONEK; Eogonek
15982 \DeclareTextCompositeCommand{\k}{PU}{E}{\81\030}% U+0118
15983 % U+0119 LATIN SMALL LETTER E WITH OGONEK; eogonek
15984 \DeclareTextCompositeCommand{\k}{PU}{e}{\81\031}% U+0119
15985 % U+011A LATIN CAPITAL LETTER E WITH CARON; Ecaron
15986 \DeclareTextCompositeCommand{\v}{PU}{E}{\81\032}% U+011A
15987 % U+011B LATIN SMALL LETTER E WITH CARON; ecaron
15988 \DeclareTextCompositeCommand{\v}{PU}{e}{\81\033}% U+011B
15989 % U+011C LATIN CAPITAL LETTER G WITH CIRCUMFLEX; Gcircumflex
15990 \DeclareTextCompositeCommand{\^}{PU}{G}{\81\034}% U+011C
15991 % U+011D LATIN SMALL LETTER G WITH CIRCUMFLEX; gcircumflex
15992 \DeclareTextCompositeCommand{\^}{PU}{g}{\81\035}% U+011D
15993 % U+011E LATIN CAPITAL LETTER G WITH BREVE; Gbreve
15994 \DeclareTextCompositeCommand{\u}{PU}{G}{\81\036}% U+011E
15995 % U+011F LATIN SMALL LETTER G WITH BREVE; gbreve
15996 \DeclareTextCompositeCommand{\u}{PU}{g}{\81\037}% U+011F
15997 % U+0120 LATIN CAPITAL LETTER G WITH DOT ABOVE; Gdot, Gdotaccent
15998 \DeclareTextCompositeCommand{\.}{PU}{G}{\81\040}% U+0120
15999 % U+0121 LATIN SMALL LETTER G WITH DOT ABOVE; gdot, gdotaccent
16000 \DeclareTextCompositeCommand{\.}{PU}{g}{\81\041}% U+0121

16001 % U+0122 LATIN CAPITAL LETTER G WITH CEDILLA; Gcedilla, Gcommaaccent
16002 \DeclareTextCompositeCommand{\c}{PU}{G}{\81\042}% U+0122
16003 % U+0123 LATIN SMALL LETTER G WITH CEDILLA; gcedilla, gcommaaccent
16004 \DeclareTextCompositeCommand{\c}{PU}{g}{\81\043}% U+0123
16005 % U+0124 LATIN CAPITAL LETTER H WITH CIRCUMFLEX; Hcircumflex
16006 \DeclareTextCompositeCommand{\^}{PU}{H}{\81\044}% U+0124
16007 % U+0125 LATIN SMALL LETTER H WITH CIRCUMFLEX; hcircumflex
16008 \DeclareTextCompositeCommand{\^}{PU}{h}{\81\045}% U+0125
16009 % U+0126 LATIN CAPITAL LETTER H WITH STROKE; Hbar
16010 \DeclareTextCommand{\textHslash}{PU}{\81\046}% U+0126
16011 % U+0127 LATIN SMALL LETTER H WITH STROKE; hbar; \hbar (AmS)
16012 \DeclareTextCommand{\textthbar}{PU}{\81\047}%* U+0127
16013 %* \textthbar -> \textcrh (tipa)
16014 %* \textthbar -> \crossh (wsuipa)
16015 %* \textthbar -> \planck (phonetic)
16016 % U+0128 LATIN CAPITAL LETTER I WITH TILDE; Itilde
16017 \DeclareTextCompositeCommand{\~}{PU}{I}{\81\050}% U+0128
16018 % U+0129 LATIN SMALL LETTER I WITH TILDE; itilde
16019 \DeclareTextCompositeCommand{\~}{PU}{i}{\81\051}% U+0129
16020 \DeclareTextCompositeCommand{\~}{PU}{\i}{\81\051}% U+0129
16021 % U+012A LATIN CAPITAL LETTER I WITH MACRON; Imacron
16022 \DeclareTextCompositeCommand{\=}{PU}{I}{\81\052}% U+012A
16023 % U+012B LATIN SMALL LETTER I WITH MACRON; imacron
16024 \DeclareTextCompositeCommand{\=}{PU}{i}{\81\053}% U+012B
16025 \DeclareTextCompositeCommand{\=}{PU}{\i}{\81\053}% U+012B
16026 % U+012C LATIN CAPITAL LETTER I WITH BREVE; Ibreve
16027 \DeclareTextCompositeCommand{\u}{PU}{I}{\81\054}% U+012C
16028 % U+012D LATIN SMALL LETTER I WITH BREVE; ibreve
16029 \DeclareTextCompositeCommand{\u}{PU}{i}{\81\055}% U+012D
16030 \DeclareTextCompositeCommand{\u}{PU}{\i}{\81\055}% U+012D
16031 % U+012E LATIN CAPITAL LETTER I WITH OGONEK; Iogonek
16032 \DeclareTextCompositeCommand{\k}{PU}{I}{\81\056}% U+012E
16033 % U+012F LATIN SMALL LETTER I WITH OGONEK; iogonek
16034 \DeclareTextCompositeCommand{\k}{PU}{i}{\81\057}% U+012F
16035 \DeclareTextCompositeCommand{\k}{PU}{\i}{\81\057}% U+012F
16036 % U+0130 LATIN CAPITAL LETTER I WITH DOT ABOVE; Idot, Idotaccent
16037 \DeclareTextCompositeCommand{\.}{PU}{I}{\81\060}% U+0130
16038 % U+0131 LATIN SMALL LETTER DOTLESS I; dotlessi
16039 \DeclareTextCommand{\i}{PU}{\81\061}% U+0131
16040 % U+0132 LATIN CAPITAL LIGATURE IJ; IJ
16041 \DeclareTextCommand{\IJ}{PU}{\81\062}% U+0132
16042 % U+0133 LATIN SMALL LIGATURE IJ; ij
16043 \DeclareTextCommand{\ij}{PU}{\81\063}% U+0133
16044 % U+0134 LATIN CAPITAL LETTER J WITH CIRCUMFLEX; Jcircumflex
16045 \DeclareTextCompositeCommand{\^}{PU}{J}{\81\064}% U+0134
16046 % U+0135 LATIN SMALL LETTER J WITH CIRCUMFLEX; jcircumflex
16047 \DeclareTextCompositeCommand{\^}{PU}{j}{\81\065}% U+0135
16048 \DeclareTextCompositeCommand{\^}{PU}{\j}{\81\065}% U+0135
16049 % U+0136 LATIN CAPITAL LETTER K WITH CEDILLA; Kcedilla, Kcommaaccent
16050 \DeclareTextCompositeCommand{\c}{PU}{K}{\81\066}% U+0136
16051 % U+0137 LATIN SMALL LETTER K WITH CEDILLA; kcedilla, kcommaaccent
16052 \DeclareTextCompositeCommand{\c}{PU}{k}{\81\067}% U+0137

The canonical name of U+0138, small letter kra, would be `\textkgreenlandic`, following the glyph naming convention. However `latex/base/inputenc.dtx` has choosen `\textkra`.

16053 % U+0138 LATIN SMALL LETTER KRA; kgreenlandic
16054 \DeclareTextCommand{\textkra}{PU}{\81\070}% U+0138
16055 % U+0139 LATIN CAPITAL LETTER L WITH ACUTE; Lacute
16056 \DeclareTextCompositeCommand{\'}{PU}{L}{\81\071}% U+0139
16057 % U+013A LATIN SMALL LETTER L WITH ACUTE; lacute
16058 \DeclareTextCompositeCommand{\'}{PU}{l}{\81\072}% U+013A
16059 % U+013B LATIN CAPITAL LETTER L WITH CEDILLA; Lcedilla, Lcommaaccent
16060 \DeclareTextCompositeCommand{\c}{PU}{L}{\81\073}% U+013B
16061 % U+013C LATIN SMALL LETTER L WITH CEDILLA; lcedilla, lcommaaccent
16062 \DeclareTextCompositeCommand{\c}{PU}{l}{\81\074}% U+013C
16063 % U+013D LATIN CAPITAL LETTER L WITH CARON; Lcaron
16064 \DeclareTextCompositeCommand{\v}{PU}{L}{\81\075}% U+013D
16065 % U+013E LATIN SMALL LETTER L WITH CARON; lcaron
16066 \DeclareTextCompositeCommand{\v}{PU}{l}{\81\076}% U+013E

There seems to be no variants of letters ‘L’ and ‘l’ with a dot above (reasonable).
Therefore the \. accent is reused instead of making a separate accent macro
\textmiddledot.

16067 % U+013F LATIN CAPITAL LETTER L WITH MIDDLE DOT; Ldot, Ldotaccent
16068 \DeclareTextCompositeCommand{\.}{PU}{L}{\81\077}% U+013F
16069 % U+0140 LATIN SMALL LETTER L WITH MIDDLE DOT; ldot, ldotaccent
16070 \DeclareTextCompositeCommand{\.}{PU}{l}{\81\100}% U+0140
16071 % U+0141 LATIN CAPITAL LETTER L WITH STROKE; Lslash
16072 \DeclareTextCommand{\L}{PU}{\81\101}% U+0141
16073 % U+0142 LATIN SMALL LETTER L WITH STROKE; lslash
16074 \DeclareTextCommand{\l}{PU}{\81\102}% U+0142
16075 % U+0143 LATIN CAPITAL LETTER N WITH ACUTE; Nacute
16076 \DeclareTextCompositeCommand{\'}{PU}{N}{\81\103}% U+0143
16077 % U+0144 LATIN SMALL LETTER N WITH ACUTE; nacute
16078 \DeclareTextCompositeCommand{\'}{PU}{n}{\81\104}% U+0144
16079 % U+0145 LATIN CAPITAL LETTER N WITH CEDILLA; Ncedilla, Ncommaaccent
16080 \DeclareTextCompositeCommand{\c}{PU}{N}{\81\105}% U+0145
16081 % U+0146 LATIN SMALL LETTER N WITH CEDILLA; ncedilla, ncommaaccent
16082 \DeclareTextCompositeCommand{\c}{PU}{n}{\81\106}% U+0146
16083 % U+0147 LATIN CAPITAL LETTER N WITH CARON; Ncaron
16084 \DeclareTextCompositeCommand{\v}{PU}{N}{\81\107}% U+0147
16085 % U+0148 LATIN SMALL LETTER N WITH CARON; ncaron
16086 \DeclareTextCompositeCommand{\v}{PU}{n}{\81\110}% U+0148
16087 % U+0149 LATIN SMALL LETTER N PRECEDED BY APOSTROPHE; napostrophe, quoterightn
16088 \DeclareTextCommand{\textnapostrophe}{PU}{\81\111}% U+0149
16089 % U+014A LATIN CAPITAL LETTER ENG; Eng
16090 \DeclareTextCommand{\NG}{PU}{\81\112}% U+014A
16091 % U+014B LATIN SMALL LETTER ENG; eng
16092 \DeclareTextCommand{\ng}{PU}{\81\113}% U+014B
16093 %* \ng -> \eng (wsuipa)
16094 %* \ng -> \engma (phonetic)
16095 % U+014C LATIN CAPITAL LETTER O WITH MACRON; Omacron
16096 \DeclareTextCompositeCommand{=} {PU}{O}{\81\114}% U+014C
16097 % U+014D LATIN SMALL LETTER O WITH MACRON; omacron
16098 \DeclareTextCompositeCommand{=} {PU}{o}{\81\115}% U+014D
16099 % U+014E LATIN CAPITAL LETTER O WITH BREVE; Obreve
16100 \DeclareTextCompositeCommand{\u}{PU}{O}{\81\116}% U+014E
16101 % U+014F LATIN SMALL LETTER O WITH BREVE; obreve
16102 \DeclareTextCompositeCommand{\u}{PU}{o}{\81\117}% U+014F

16103 % U+0150 LATIN CAPITAL LETTER O WITH DOUBLE ACUTE; Odblacute, Ohungarumlaut
 16104 \DeclareTextCompositeCommand{\H}{PU}{O}{\81\120}% U+0150
 16105 % U+0151 LATIN SMALL LETTER O WITH DOUBLE ACUTE; odblacute, ohungarumlaut
 16106 \DeclareTextCompositeCommand{\H}{PU}{o}{\81\121}% U+0151
 16107 % U+0152 LATIN CAPITAL LIGATURE OE; OE
 16108 \DeclareTextCommand{\OE}{PU}{\81\122}% U+0152
 16109 % U+0153 LATIN SMALL LIGATURE OE; oe
 16110 \DeclareTextCommand{\oe}{PU}{\81\123}% U+0153
 16111 % U+0154 LATIN CAPITAL LETTER R WITH ACUTE; Racute
 16112 \DeclareTextCompositeCommand{\'}{PU}{R}{\81\124}% U+0154
 16113 % U+0155 LATIN SMALL LETTER R WITH ACUTE; racute
 16114 \DeclareTextCompositeCommand{\'}{PU}{r}{\81\125}% U+0155
 16115 % U+0156 LATIN CAPITAL LETTER R WITH CEDILLA; Rcedilla, Rcommaaccent
 16116 \DeclareTextCompositeCommand{\c}{PU}{R}{\81\126}% U+0156
 16117 % U+0157 LATIN SMALL LETTER R WITH CEDILLA; rcedilla, rcommaaccent
 16118 \DeclareTextCompositeCommand{\c}{PU}{r}{\81\127}% U+0157
 16119 % U+0158 LATIN CAPITAL LETTER R WITH CARON; Rcaron
 16120 \DeclareTextCompositeCommand{\v}{PU}{R}{\81\130}% U+0158
 16121 % U+0159 LATIN SMALL LETTER R WITH CARON; rcaron
 16122 \DeclareTextCompositeCommand{\v}{PU}{r}{\81\131}% U+0159
 16123 % U+015A LATIN CAPITAL LETTER S WITH ACUTE; Sacute
 16124 \DeclareTextCompositeCommand{\'}{PU}{S}{\81\132}% U+015A
 16125 % U+015B LATIN SMALL LETTER S WITH ACUTE; sacute
 16126 \DeclareTextCompositeCommand{\'}{PU}{s}{\81\133}% U+015B
 16127 % U+015C LATIN CAPITAL LETTER S WITH CIRCUMFLEX; Scircumflex
 16128 \DeclareTextCompositeCommand{\^}{PU}{S}{\81\134}% U+015C
 16129 % U+015D LATIN SMALL LETTER S WITH CIRCUMFLEX; scircumflex
 16130 \DeclareTextCompositeCommand{\^}{PU}{s}{\81\135}% U+015D
 16131 % U+015E LATIN CAPITAL LETTER S WITH CEDILLA; Scedilla
 16132 \DeclareTextCompositeCommand{\c}{PU}{S}{\81\136}% U+015E
 16133 % U+015F LATIN SMALL LETTER S WITH CEDILLA; scedilla
 16134 \DeclareTextCompositeCommand{\c}{PU}{s}{\81\137}% U+015F
 16135 % U+0160 LATIN CAPITAL LETTER S WITH CARON; Scaron
 16136 \DeclareTextCompositeCommand{\v}{PU}{S}{\81\140}% U+0160
 16137 % U+0161 LATIN SMALL LETTER S WITH CARON; scaron
 16138 \DeclareTextCompositeCommand{\v}{PU}{s}{\81\141}% U+0161
 16139 % U+0162 LATIN CAPITAL LETTER T WITH CEDILLA; Tcedilla, Tcommaaccent
 16140 \DeclareTextCompositeCommand{\c}{PU}{T}{\81\142}% U+0162
 16141 % U+0163 LATIN SMALL LETTER T WITH CEDILLA; tcedilla, tcommaaccent
 16142 \DeclareTextCompositeCommand{\c}{PU}{t}{\81\143}% U+0163
 16143 % U+0164 LATIN CAPITAL LETTER T WITH CARON; Tcaron
 16144 \DeclareTextCompositeCommand{\v}{PU}{T}{\81\144}% U+0164
 16145 % U+0165 LATIN SMALL LETTER T WITH CARON; tcaron
 16146 \DeclareTextCompositeCommand{\v}{PU}{t}{\81\145}% U+0165
 16147 % U+0166 LATIN CAPITAL LETTER T WITH STROKE; Tbar
 16148 \DeclareTextCommand{\textTslash}{PU}{\81\146}% U+0166
 16149 % U+0167 LATIN SMALL LETTER T WITH STROKE; tbar
 16150 \DeclareTextCommand{\texttslash}{PU}{\81\147}% U+0167
 16151 % U+0168 LATIN CAPITAL LETTER U WITH TILDE; Utilde
 16152 \DeclareTextCompositeCommand{\~}{PU}{U}{\81\150}% U+0168
 16153 % U+0169 LATIN SMALL LETTER U WITH TILDE; utilde
 16154 \DeclareTextCompositeCommand{\~}{PU}{u}{\81\151}% U+0169
 16155 % U+016A LATIN CAPITAL LETTER U WITH MACRON; Umacron

```

16156 \DeclareTextCompositeCommand{\=}{PU}{U}{\81\152}% U+016A
16157 % U+016B LATIN SMALL LETTER U WITH MACRON; umacron
16158 \DeclareTextCompositeCommand{\=}{PU}{u}{\81\153}% U+016B
16159 % U+016C LATIN CAPITAL LETTER U WITH BREVE; Ubreve
16160 \DeclareTextCompositeCommand{\u}{PU}{U}{\81\154}% U+016C
16161 % U+016D LATIN SMALL LETTER U WITH BREVE; ubreve
16162 \DeclareTextCompositeCommand{\u}{PU}{u}{\81\155}% U+016D
16163 % U+016E LATIN CAPITAL LETTER U WITH RING ABOVE; Uring
16164 \DeclareTextCompositeCommand{\r}{PU}{U}{\81\156}% U+016E
16165 % U+016F LATIN SMALL LETTER U WITH RING ABOVE; uring
16166 \DeclareTextCompositeCommand{\r}{PU}{u}{\81\157}% U+016F
16167 % U+0170 LATIN CAPITAL LETTER U WITH DOUBLE ACUTE; Udbla-
cute, Uhungarumlaut
16168 \DeclareTextCompositeCommand{\H}{PU}{U}{\81\160}% U+0170
16169 % U+0171 LATIN SMALL LETTER U WITH DOUBLE ACUTE; udbla-
cute, uhungarumlaut
16170 \DeclareTextCompositeCommand{\H}{PU}{u}{\81\161}% U+0171
16171 % U+0172 LATIN CAPITAL LETTER U WITH OGONEK; Uogonek
16172 \DeclareTextCompositeCommand{\k}{PU}{U}{\81\162}% U+0172
16173 % U+0173 LATIN SMALL LETTER U WITH OGONEK; uogonek
16174 \DeclareTextCompositeCommand{\k}{PU}{u}{\81\163}% U+0173
16175 % U+0174 LATIN CAPITAL LETTER W WITH CIRCUMFLEX; Wcircumflex
16176 \DeclareTextCompositeCommand{\^}{PU}{W}{\81\164}% U+0174
16177 % U+0175 LATIN SMALL LETTER W WITH CIRCUMFLEX; wcircumflex
16178 \DeclareTextCompositeCommand{\^}{PU}{w}{\81\165}% U+0175
16179 % U+0176 LATIN CAPITAL LETTER Y WITH CIRCUMFLEX; Ycircumflex
16180 \DeclareTextCompositeCommand{\^}{PU}{Y}{\81\166}% U+0176
16181 % U+0177 LATIN SMALL LETTER Y WITH CIRCUMFLEX; ycircumflex
16182 \DeclareTextCompositeCommand{\^}{PU}{y}{\81\167}% U+0177
16183 % U+0178 LATIN CAPITAL LETTER Y WITH DIAERESIS; Ydieresis
16184 \DeclareTextCompositeCommand{\"}{PU}{Y}{\81\170}% U+0178
16185 % U+0179 LATIN CAPITAL LETTER Z WITH ACUTE; Zacute
16186 \DeclareTextCompositeCommand{\'}{PU}{Z}{\81\171}% U+0179
16187 % U+017A LATIN SMALL LETTER Z WITH ACUTE; zacute
16188 \DeclareTextCompositeCommand{\'}{PU}{z}{\81\172}% U+017A
16189 % U+017B LATIN CAPITAL LETTER Z WITH DOT ABOVE; Zdot, Zdotaccent
16190 \DeclareTextCompositeCommand{\.}{PU}{Z}{\81\173}% U+017B
16191 % U+017C LATIN SMALL LETTER Z WITH DOT ABOVE; zdot, zdotaccent
16192 \DeclareTextCompositeCommand{\.}{PU}{z}{\81\174}% U+017C
16193 % U+017D LATIN CAPITAL LETTER Z WITH CARON; Zcaron
16194 \DeclareTextCompositeCommand{\v}{PU}{Z}{\81\175}% U+017D
16195 % U+017E LATIN SMALL LETTER Z WITH CARON; zcaron
16196 \DeclareTextCompositeCommand{\v}{PU}{z}{\81\176}% U+017E
16197 % U+017F LATIN SMALL LETTER LONG S; longs, slong
16198 \DeclareTextCommand{\textlongS}{PU}{\81\177}% U+017F

```

51.2.5 Latin Extended-B: U+0180 to U+024F

```

16199 % U+0180 LATIN SMALL LETTER B WITH STROKE; bstroke; \textcrb (tipa)
16200 \DeclareTextCommand{\textcrb}{PU}{\81\200}% U+0180
16201 %* \textcrb -> \crossb (wsuipa)
16202 % An alternate glyph with the stroke through the bowl:
16203 %* \textcrb -> \textbarb (tipa)
16204 %* \textcrb -> \barb (wsuipa)
16205 % U+0181 LATIN CAPITAL LETTER B WITH HOOK; Bhook; \hausab (pho-
netic)
16206 \DeclareTextCommand{\texthausab}{PU}{\81\201}%* U+0181
16207 % U+0188 LATIN SMALL LETTER C WITH HOOK; chook; \texthtc (tipa)

```

16208 \DeclareTextCommand{\texthtc}{PU}{\81\210}% U+0188
16209 % U+018A LATIN CAPITAL LETTER D WITH HOOK; Dhook; \hausad (pho-
netic)
16210 \DeclareTextCommand{\texthausaD}{PU}{\81\212}%* U+018A
16211 % U+018E LATIN CAPITAL LETTER REVERSED E; Ereversed
16212 \DeclareTextCommand{\textEreversed}{PU}{\81\216}% U+018E
16213 \DeclareTextCommand{\textrevE}{PU}{\81\216}% U+018E
16214 % U+0192 LATIN SMALL LETTER F WITH HOOK; florin
16215 \DeclareTextCommand{\textflorin}{PU}{\81\222}% U+0192
16216 %* \textflorin -> \Florin (marvosym)
16217 % U+0195 LATIN SMALL LETTER HV; hv; \texthvlig (tipa)
16218 \DeclareTextCommand{\texthvlig}{PU}{\81\225}% U+0195
16219 %* \texthvlig -> \hv (wsuipa)
16220 % U+0198 LATIN CAPITAL LETTER K WITH HOOK; Khook; \hausak (pho-
netic)
16221 \DeclareTextCommand{\texthausaK}{PU}{\81\230}%* U+0198
16222 % U+0199 LATIN SMALL LETTER K WITH HOOK; khook; \texthtk (tipa)
16223 \DeclareTextCommand{\texthtk}{PU}{\81\231}% U+0199
16224 %* \texthtk -> \hausak (phonetic)
16225 % U+019A LATIN SMALL LETTER L WITH BAR; lbar;
16226 % \textbarl (tipa), \barl (wsuipa)
16227 \DeclareTextCommand{\textbarl}{PU}{\81\232}%* U+019A
16228 % U+019B LATIN SMALL LETTER LAMBDA WITH STROKE/
16229 % LATIN SMALL LETTER BARRED LAMBDA; lambdastroke;
16230 % \textcrlambda (tipa)
16231 \DeclareTextCommand{\textcrlambda}{PU}{\81\233}% U+019B
16232 %* \textcrlambda -> \crossnilambda (wsuipa)
16233 %* \textcrlambda -> \barlambda (phonetic)
16234 %* \textcrlambda -> \lambdabar (txfonts/pxfonts)
16235 %* \textcrlambda -> \lambdaslash (txfonts/pxfonts)
16236 % U+019E LATIN SMALL LETTER N WITH LONG RIGHT LEG; nlegright-
long;
16237 % \textnrleg (tipx)
16238 \DeclareTextCommand{\textPUnrleg}{PU}{\81\236}% U+019E
16239 %* \textPUnrleg -> \textnrleg (tipx)
16240 % U+01A5 LATIN SMALL LETTER P WITH HOOK; phook; \texthtp (tipa)
16241 \DeclareTextCommand{\texthtp}{PU}{\81\245}% U+01A5
16242 % U+01AB LATIN SMALL LETTER T WITH PALATAL HOOK; tpalatalhook;
16243 % \textlhookt (tipa)
16244 \DeclareTextCommand{\textlhookt}{PU}{\81\253}% U+01AB
16245 % U+01AD LATIN SMALL LETTER T WITH HOOK; thook; \texthtt (tipa)
16246 \DeclareTextCommand{\texthtt}{PU}{\81\255}% U+01AD
16247 % U+01B9 LATIN SMALL LETTER EZH REVERSED/
16248 % LATIN SMALL LETTER REVERSED YOGH; \textrevyogh (tipa)
16249 \DeclareTextCommand{\textrevyogh}{PU}{\81\271}% U+01B9
16250 % U+01BB LATIN LETTER TWO WITH STROKE; twostroke; \textcrtwo (tipa)
16251 \DeclareTextCommand{\textcrtwo}{PU}{\81\273}% U+01BB
16252 % U+01BE LATIN LETTER INVERTED GLOTTAL STOP WITH STROKE;
16253 % glottalinvertedstroke; \textcrinvglotstop (tipa)
16254 \DeclareTextCommand{\textcrinvglotstop}{PU}{\81\276}% U+01BE
16255 % U+01BF LATIN LETTER WYNN; wynn; \textwynn (tipa)
16256 \DeclareTextCommand{\textwynn}{PU}{\81\277}% U+01BF
16257 % U+01C0 LATIN LETTER DENTAL CLICK/LATIN LETTER PIPE; clickden-
tal;
16258 % \textpipe (tipa)
16259 \DeclareTextCommand{\textpipe}{PU}{\81\300}% U+01C0
16260 %* \textpipe -> \textpipevar (tipx)

16261 % U+01C1 LATIN LETTER LATERAL CLICK/LATIN LETTER
16262 % DOUBLE PIPE; clicklateral; \textdoublepipe (tipa)
16263 \DeclareTextCommand{\textdoublepipe}{PU}{\81\301}% U+01C1
16264 %* \textdoublepipe -> \textdoublepipevar (tipx)
16265 % U+01C2 LATIN LETTER ALVEOLAR CLICK/LATIN LETTER PIPE DOU-
BLE BAR;
16266 % clickalveolar; \textdoublebarpipe (tipa)
16267 \DeclareTextCommand{\textdoublebarpipe}{PU}{\81\302}% U+01C2
16268 %* \textdoublebarpipe -> \textdoublebarpipevar (tipx)
16269 % U+01CD LATIN CAPITAL LETTER A WITH CARON; Acaron
16270 \DeclareTextCompositeCommand{\v}{PU}{A}{\81\315}% U+01CD
16271 % U+01CE LATIN SMALL LETTER A WITH CARON; acarón
16272 \DeclareTextCompositeCommand{\v}{PU}{a}{\81\316}% U+01CE
16273 % U+01CF LATIN CAPITAL LETTER I WITH CARON; Icaron
16274 \DeclareTextCompositeCommand{\v}{PU}{I}{\81\317}% U+01CF
16275 % U+01D0 LATIN SMALL LETTER I WITH CARON; icarón
16276 \DeclareTextCompositeCommand{\v}{PU}{i}{\81\320}% U+01D0
16277 \DeclareTextCompositeCommand{\v}{PU}{i}{\81\320}% U+01D0
16278 % U+01D1 LATIN CAPITAL LETTER O WITH CARON; Ocaron
16279 \DeclareTextCompositeCommand{\v}{PU}{O}{\81\321}% U+01D1
16280 % U+01D2 LATIN SMALL LETTER O WITH CARON; ocarón
16281 \DeclareTextCompositeCommand{\v}{PU}{o}{\81\322}% U+01D2
16282 % U+01D3 LATIN CAPITAL LETTER U WITH CARON; Ucaron
16283 \DeclareTextCompositeCommand{\v}{PU}{U}{\81\323}% U+01D3
16284 % U+01D4 LATIN SMALL LETTER U WITH CARON; ucarón
16285 \DeclareTextCompositeCommand{\v}{PU}{u}{\81\324}% U+01D4
16286 % U+01DD LATIN SMALL LETTER TURNED E; eturned; \inve (wasysym)
16287 \DeclareTextCommand{\textinve}{PU}{\81\335}%* U+01DD
16288 % U+01E4 LATIN CAPITAL LETTER G WITH STROKE; Gstroke
16289 \DeclareTextCommand{\textGslash}{PU}{\81\344}% U+01E4
16290 % U+01E5 LATIN SMALL LETTER G WITH STROKE; gstroke
16291 \DeclareTextCommand{\textgslash}{PU}{\81\345}% U+01E5
16292 %* \textgslash -> \textcrg (tipa)
16293 % U+01E6 LATIN CAPITAL LETTER G WITH CARON; Gcaron
16294 \DeclareTextCompositeCommand{\v}{PU}{G}{\81\346}% U+01E6
16295 % U+01E7 LATIN SMALL LETTER G WITH CARON; gcaron
16296 \DeclareTextCompositeCommand{\v}{PU}{g}{\81\347}% U+01E7
16297 % U+01E8 LATIN CAPITAL LETTER K WITH CARON; Kcaron
16298 \DeclareTextCompositeCommand{\v}{PU}{K}{\81\350}% U+01E8
16299 % U+01E9 LATIN SMALL LETTER K WITH CARON; kcaron
16300 \DeclareTextCompositeCommand{\v}{PU}{k}{\81\351}% U+01E9
16301 % U+01EA LATIN CAPITAL LETTER O WITH OGONEK; Oogonek
16302 \DeclareTextCompositeCommand{\k}{PU}{O}{\81\352}% U+01EA
16303 % U+01EB LATIN SMALL LETTER O WITH OGONEK; oogonek
16304 \DeclareTextCompositeCommand{\k}{PU}{o}{\81\353}% U+01EB
16305 % U+01F0 LATIN SMALL LETTER J WITH CARON; jcaron
16306 \DeclareTextCompositeCommand{\v}{PU}{j}{\81\360}% U+01F0
16307 \DeclareTextCompositeCommand{\v}{PU}{j}{\81\360}% U+01F0
16308 % U+01F4 LATIN CAPITAL LETTER G WITH ACUTE; Gacute
16309 \DeclareTextCompositeCommand{\'}{PU}{G}{\81\364}% U+01F4
16310 % U+01F5 LATIN SMALL LETTER G WITH ACUTE; gacute
16311 \DeclareTextCompositeCommand{\'}{PU}{g}{\81\365}% U+01F5
16312 % U+01F8 LATIN CAPITAL LETTER N WITH GRAVE
16313 \DeclareTextCompositeCommand{\`}{PU}{N}{\81\370}% U+01F8
16314 % U+01F9 LATIN SMALL LETTER N WITH GRAVE
16315 \DeclareTextCompositeCommand{\`}{PU}{n}{\81\371}% U+01F9
16316 % U+01FC LATIN CAPITAL LETTER AE WITH ACUTE; AEacute

16317 \DeclareTextCompositeCommand{\'}{PU}{\AE}{\81\374}% U+01FC
16318 % U+01FD LATIN SMALL LETTER AE WITH ACUTE; aeacute
16319 \DeclareTextCompositeCommand{\'}{PU}{\ae}{\81\375}% U+01FD
16320 % U+01FE LATIN CAPITAL LETTER O WITH STROKE AND ACUTE;
16321 % *Oslashacute, Ostrokeacut
16322 \DeclareTextCompositeCommand{\'}{PU}{\O}{\81\376}% U+01FE
16323 % U+01FF LATIN SMALL LETTER O WITH STROKE AND ACUTE;
16324 % *oslashacute, ostrokeacute
16325 \DeclareTextCompositeCommand{\'}{PU}{\o}{\81\377}% U+01FF
16326 % U+0200 LATIN CAPITAL LETTER A WITH DOUBLE GRAVE; Adblgrave
16327 \DeclareTextCompositeCommand{\G}{PU}{A}{\82\000}% U+0200
16328 % U+0201 LATIN SMALL LETTER A WITH DOUBLE GRAVE; adblgrave
16329 \DeclareTextCompositeCommand{\G}{PU}{a}{\82\001}% U+0201
16330 % U+0204 LATIN CAPITAL LETTER E WITH DOUBLE GRAVE; Edblgrave
16331 \DeclareTextCompositeCommand{\G}{PU}{E}{\82\004}% U+0204
16332 % U+0205 LATIN SMALL LETTER E WITH DOUBLE GRAVE; edblgrave
16333 \DeclareTextCompositeCommand{\G}{PU}{e}{\82\005}% U+0205
16334 % U+0206 LATIN CAPITAL LETTER E WITH INVERTED BREVE; Einvert-
edbreve
16335 \DeclareTextCompositeCommand{\textinvbreve}{PU}{E}{\82\006}% U+0206
16336 % U+0207 LATIN SMALL LETTER E WITH INVERTED BREVE; einverted-
breve
16337 \DeclareTextCompositeCommand{\textinvbreve}{PU}{e}{\82\007}% U+0207
16338 % U+0208 LATIN CAPITAL LETTER I WITH DOUBLE GRAVE; Idblgrave
16339 \DeclareTextCompositeCommand{\G}{PU}{I}{\82\010}% U+0208
16340 % U+0209 LATIN SMALL LETTER I WITH DOUBLE GRAVE; idblgrave
16341 \DeclareTextCompositeCommand{\G}{PU}{i}{\82\011}% U+0209
16342 \DeclareTextCompositeCommand{\G}{PU}{i}{\82\011}% U+0209
16343 % U+020A LATIN CAPITAL LETTER I WITH INVERTED BREVE; Iinverted-
breve
16344 \DeclareTextCompositeCommand{\textinvbreve}{PU}{I}{\82\012}% U+020A
16345 % U+020B LATIN SMALL LETTER I WITH INVERTED BREVE; iinverted-
breve
16346 \DeclareTextCompositeCommand{\textinvbreve}{PU}{i}{\82\013}% U+020B
16347 \DeclareTextCompositeCommand{\textinvbreve}{PU}{i}{\82\013}% U+020B
16348 % U+020C LATIN CAPITAL LETTER O WITH DOUBLE GRAVE; Odblgrave
16349 \DeclareTextCompositeCommand{\G}{PU}{O}{\82\014}% U+020C
16350 % U+020D LATIN SMALL LETTER O WITH DOUBLE GRAVE; odblgrave
16351 \DeclareTextCompositeCommand{\G}{PU}{o}{\82\015}% U+020D
16352 % U+020E LATIN CAPITAL LETTER O WITH INVERTED BREVE; Oinvert-
edbreve
16353 \DeclareTextCompositeCommand{\textinvbreve}{PU}{O}{\82\016}% U+020E
16354 % U+020F LATIN SMALL LETTER O WITH INVERTED BREVE; oinverted-
breve
16355 \DeclareTextCompositeCommand{\textinvbreve}{PU}{o}{\82\017}% U+020F
16356 % U+0210 LATIN CAPITAL LETTER R WITH DOUBLE GRAVE; Rdblgrave
16357 \DeclareTextCompositeCommand{\G}{PU}{R}{\82\020}% U+0210
16358 % U+0211 LATIN SMALL LETTER R WITH DOUBLE GRAVE; rdblgrave
16359 \DeclareTextCompositeCommand{\G}{PU}{r}{\82\021}% U+0211
16360 % U+0214 LATIN CAPITAL LETTER U WITH DOUBLE GRAVE; Udblgrave
16361 \DeclareTextCompositeCommand{\G}{PU}{U}{\82\024}% U+0214
16362 % U+0215 LATIN SMALL LETTER U WITH DOUBLE GRAVE; udblgrave
16363 \DeclareTextCompositeCommand{\G}{PU}{u}{\82\025}% U+0215
16364 % U+0216 LATIN CAPITAL LETTER U WITH INVERTED BREVE; Uinvert-
edbreve
16365 \DeclareTextCompositeCommand{\textinvbreve}{PU}{U}{\82\026}% U+0216

16366 % U+0217 LATIN SMALL LETTER U WITH INVERTED BREVE; uinverted-breve
16367 \DeclareTextCompositeCommand{\textinvbreve}{PU}{u}{\82\027}% U+0217
16368 % U+021E LATIN CAPITAL LETTER H WITH CARON
16369 \DeclareTextCompositeCommand{\v}{PU}{H}{\82\036}% U+021E
16370 % U+021F LATIN SMALL LETTER H WITH CARON
16371 \DeclareTextCompositeCommand{\v}{PU}{h}{\82\037}% U+021F
16372 % U+0221 LATIN SMALL LETTER D WITH CURL; \textctd (tipa)
16373 \DeclareTextCommand{\textctd}{PU}{\82\041}% U+0221
16374 % U+0225 LATIN SMALL LETTER Z WITH HOOK; \textcommatailz (tipa)
16375 \DeclareTextCommand{\textcommatailz}{PU}{\82\045}% U+0225
16376 % U+0226 LATIN CAPITAL LETTER A WITH DOT ABOVE
16377 \DeclareTextCompositeCommand{\.}{PU}{A}{\82\046}% U+0226
16378 % U+0227 LATIN SMALL LETTER A WITH DOT ABOVE
16379 \DeclareTextCompositeCommand{\.}{PU}{a}{\82\047}% U+0227
16380 % U+0228 LATIN CAPITAL LETTER E WITH CEDILLA
16381 \DeclareTextCompositeCommand{\c}{PU}{E}{\82\050}% U+0228
16382 % U+0229 LATIN SMALL LETTER E WITH CEDILLA
16383 \DeclareTextCompositeCommand{\c}{PU}{e}{\82\051}% U+0229
16384 % U+022E LATIN CAPITAL LETTER O WITH DOT ABOVE
16385 \DeclareTextCompositeCommand{\.}{PU}{O}{\82\056}% U+022E
16386 % U+022F LATIN SMALL LETTER O WITH DOT ABOVE
16387 \DeclareTextCompositeCommand{\.}{PU}{o}{\82\057}% U+022F
16388 % U+0232 LATIN CAPITAL LETTER Y WITH MACRON
16389 \DeclareTextCompositeCommand{\=}{PU}{Y}{\82\062}% U+0232
16390 % U+0233 LATIN SMALL LETTER Y WITH MACRON
16391 \DeclareTextCompositeCommand{\=}{PU}{y}{\82\063}% U+0233
16392 % U+0235 LATIN SMALL LETTER N WITH CURL; \textctn (tipa)
16393 \DeclareTextCommand{\textctn}{PU}{\82\065}% U+0235
16394 % U+0236 LATIN SMALL LETTER T WITH CURL; \textctt (tipa)
16395 \DeclareTextCommand{\textctt}{PU}{\82\066}% U+0236
16396 % U+0237 LATIN SMALL LETTER DOTLESS J
16397 \DeclareTextCommand{\j}{PU}{\82\067}% U+0237
16398 % U+0238 LATIN SMALL LETTER DB DIGRAPH; \textdblig (tipx)
16399 \DeclareTextCommand{\textPUdblig}{PU}{\82\070}% U+0238
16400 %* \textPUdblig -> \textdblig (tipx)
16401 % U+0239 LATIN SMALL LETTER QP DIGRAPH; \textqplig (tipx)
16402 \DeclareTextCommand{\textPUqplig}{PU}{\82\071}% U+0239
16403 %* \textPUqplig -> \textqplig (tipx)
16404 % U+023C LATIN SMALL LETTER C WITH STROKE; \slashc (wsuipa)
16405 \DeclareTextCommand{\textslashc}{PU}{\82\074}%* U+023C
16406 %* \textslashc -> \textcentoldstyle (textcomp)
16407 % With bar instead of stroke:
16408 %* \textslashc -> \textbarc (tipa)

51.2.6 IPA Extensions: U+0250 to U+02AF

16409 % U+0250 LATIN SMALL LETTER TURNED A; aturned; \textturna (tipa)
16410 \DeclareTextCommand{\textturna}{PU}{\82\120}% U+0250
16411 %* \textturna -> \inva (wasysym)
16412 % U+0251 LATIN SMALL LETTER ALPHA/LATIN SMALL LETTER
16413 % SCRIPT A; ascript; \textscripta (tipa), \scripta (wsuipa)
16414 \DeclareTextCommand{\textscripta}{PU}{\82\121}%* U+0251
16415 %* \textscripta -> \vara (phonetic)
16416 % U+0252 LATIN SMALL LETTER TURNED ALPHA; ascriptturned;
16417 % \textturnscripta (tipa)
16418 \DeclareTextCommand{\textturnscripta}{PU}{\82\122}% U+0252
16419 %* \textturnscripta -> \invscripta (wsuipa)

16420 %* \textturnscripta -> \rotvara (phonetic)
 16421 % U+0253 LATIN CAPITAL LETTER B WITH HOOK; bhook; \texthtb (tipa)
 16422 \DeclareTextCommand{\texthtb}{PU}{\82\123}% U+0253
 16423 %* \texthtb -> \hookb (wsuipa)
 16424 %* \texthtb -> \hausab (phonetic)
 16425 % U+0254 LATIN SMALL LETTER OPEN O; oopen;
 16426 % \textopeno (tipa), \openo (wasysym)
 16427 \DeclareTextCommand{\textopeno}{PU}{\82\124}% U+0254
 16428 %* \textopeno -> \varopeno (phonetic)
 16429 % U+0255 LATIN SMALL LETTER C WITH CURL; ccurl; \textctc (tipa)
 16430 \DeclareTextCommand{\textctc}{PU}{\82\125}% U+0255
 16431 %* \textctc -> \curlyc (wsuipa)
 16432 % U+0256 LATIN SMALL LETTER D WITH TAIL; dtail; \textrtaild (tipa)
 16433 \DeclareTextCommand{\textrtaild}{PU}{\82\126}% U+0256
 16434 %* \textrtaild -> \taild (wsuipa)
 16435 % U+0257 LATIN SMALL LETTER D WITH HOOK; dhook; \texthtd (tipa)
 16436 \DeclareTextCommand{\texthtd}{PU}{\82\127}% U+0257
 16437 %* \texthtd -> \hookd (wsuipa)
 16438 %* \texthtd -> \hausad (phonetic)
 16439 % U+0258 LATIN SMALL LETTER REVERSED E; ereversed;
 16440 % \textreve (tipa), \reve (wsuipa)
 16441 \DeclareTextCommand{\textreve}{PU}{\82\130}% U+0258
 16442 % U+0259 LATIN SMALL LETTER SCHWA; schwa;
 16443 % \textschwa (tipa), \schwa (wsuipa, phonetic)
 16444 \DeclareTextCommand{\textschwa}{PU}{\82\131}% U+0259
 16445 % U+025A LATIN SMALL LETTER SCHWA WITH HOOK; schwahook;
 16446 % \textrhookschwa (tipa)
 16447 \DeclareTextCommand{\textrhookschwa}{PU}{\82\132}% U+025A
 16448 %* \textrhookschwa -> \er (wsuipa)
 16449 % U+025B LATIN SMALL LETTER OPEN E/LATIN SMALL LETTER EP-
 SILON; eopen;
 16450 % \niepsilon (wsuipa)
 16451 \DeclareTextCommand{\textniepsilon}{PU}{\82\133}% U+025B
 16452 %* \textniepsilon -> \epsi (phonetic)
 16453 % U+025C LATIN SMALL LETTER REVERSED OPEN E; eopenreversed;
 16454 % \textrevepsilon (tipa), \revepsilon (wsuipa)
 16455 \DeclareTextCommand{\textrevepsilon}{PU}{\82\134}% U+025C
 16456 % U+025D LATIN SMALL LETTER REVERSED OPEN E WITH HOOK; eopen-
 reversedhook;
 16457 % \textrhookrevepsilon (tipa)
 16458 \DeclareTextCommand{\textrhookrevepsilon}{PU}{\82\135}% U+025D
 16459 %* \textrhookrevepsilon -> \hookrevepsilon (wsuipa)
 16460 % U+025E LATIN SMALL LETTER CLOSED REVERSED OPEN E; eopenre-
 versedclosed;
 16461 % \textcloserevepsilon (tipa)
 16462 \DeclareTextCommand{\textcloserevepsilon}{PU}{\82\136}% U+025E
 16463 %* \textcloserevepsilon -> \closedrevepsilon (wsuipa)
 16464 % U+025F LATIN SMALL LETTER DOTLESS J WITH STROKE; jdot-
 lessstroke;
 16465 % \textbardotlessj (tipa)
 16466 \DeclareTextCommand{\textbardotlessj}{PU}{\82\137}% U+025F
 16467 %* \textbardotlessj -> \barj (phonetic)
 16468 % U+0260 LATIN SMALL LETTER G WITH HOOK; ghook; \texthtg (tipa)
 16469 \DeclareTextCommand{\texthtg}{PU}{\82\140}% U+0260
 16470 %* \texthtg -> \hookg (wsuipa)
 16471 % U+0261 LATIN SMALL LETTER SCRIPT G; gscript;
 16472 % \textscriptg (tipa), \scriptg (wsuipa)

16473 \DeclareTextCommand{\textscriptg}{PU}{\82\141}%* U+0261
16474 %* \textscriptg -> \varg (phonetic)
16475 % U+0262 LATIN SMALL LETTER CAPITAL G; \textscg (tipa), \scg (wsuipa)
16476 \DeclareTextCommand{\textscg}{PU}{\82\142}%* U+0262
16477 % U+0263 LATIN SMALL LETTER GAMMA; gammalatinsmall;
16478 % \ipagamma (wsuipa), \vod (phonetic)
16479 \DeclareTextCommand{\textipagamma}{PU}{\82\143}%* U+0263
16480 %* \textipagamma -> \vod (phonetic)
16481 % U+0264 LATIN SMALL LETTER RAMS HORN; ramshorn;
16482 % \babygamma (wsuipa)
16483 \DeclareTextCommand{\textbabygamma}{PU}{\82\144}%* U+0264
16484 % U+0265 LATIN SMALL LETTER TURNED H; hturned; \textturnh (tipa)
16485 \DeclareTextCommand{\textturnh}{PU}{\82\145}% U+0265
16486 %* \textturnh -> \invh (wsuipa)
16487 %* \textturnh -> \udesc (phonetic)
16488 % U+0266 LATIN SMALL LETTER H WITH HOOK; hhook; \texthth (tipa)
16489 \DeclareTextCommand{\texthth}{PU}{\82\146}% U+0266
16490 %* \texthth -> \hookh (wsuipa)
16491 %* \texthth -> \voicedh (phonetic)
16492 % U+0267 LATIN SMALL LETTER HENG WITH HOOK; henghook; \tex-
ththeng (tipa)
16493 \DeclareTextCommand{\texththeng}{PU}{\82\147}% U+0267
16494 %* \texththeng -> \hookheng (wsuipa)
16495 % U+0268 LATIN SMALL LETTER I WITH STROKE;
16496 % \textbari (tipa), \bari (wsuipa)
16497 \DeclareTextCommand{\textbari}{PU}{\82\150}%* U+0268
16498 %* \textbari -> \ibar (phonetic)
16499 % U+0269 LATIN SMALL LETTER IOTA; iotalatin; \niiota (wsuipa)
16500 \DeclareTextCommand{\textniiota}{PU}{\82\151}%* U+0269
16501 %* \textniiota -> \vari (phonetic)
16502 % U+026A LATIN LETTER SMALL CAPITAL I; \textsci (tipa), \sci (wsuipa)
16503 \DeclareTextCommand{\textsci}{PU}{\82\152}%* U+026A
16504 % U+026B LATIN SMALL LETTER L WITH MIDDLE TILDE; lmiddletilde;
16505 % \textltilde (tipa)
16506 \DeclareTextCommand{\textltilde}{PU}{\82\153}% U+026B
16507 %* \textltilde -> \tildel (wsuipa)
16508 % U+026C LATIN SMALL LETTER L WITH BELT; lbelt; \textbeltl (tipa)
16509 \DeclareTextCommand{\textbeltl}{PU}{\82\154}% U+026C
16510 %* \textbeltl -> \latfrc (wsuipa)
16511 % U+026D LATIN SMALL LETTER L WITH RETROFLEX HOOK;
16512 % lhookretroflex; \textrtaill (tipa)
16513 \DeclareTextCommand{\textrtaill}{PU}{\82\155}% U+026D
16514 %* \textrtaill -> \taill (wsuipa)
16515 % U+026E LATIN SMALL LETTER LEZH; lezh; \textlyoghlig (tipa)
16516 \DeclareTextCommand{\textlyoghlig}{PU}{\82\156}% U+026E
16517 %* \textlyoghlig -> \lz (wsuipa)
16518 % U+026F LATIN SMALL LETTER TURNED M; mturned; \textturnm (tipa)
16519 \DeclareTextCommand{\textturnm}{PU}{\82\157}% U+026F
16520 %* \textturnm -> \invm (wsuipa)
16521 %* \textturnm -> \rotm (phonetic)
16522 % U+0270 LATIN SMALL LETTER TURNED M WITH LONG LEG; mlongleg-
turned;
16523 % \textturnmrleg (tipa)
16524 \DeclareTextCommand{\textturnmrleg}{PU}{\82\160}% U+0270
16525 %* \textturnmrleg -> \legm (wsuipa)
16526 % U+0271 LATIN SMALL LETTER M WITH HOOK; mhook; \textltailm (tipa)
16527 \DeclareTextCommand{\textltailm}{PU}{\82\161}% U+0271

16528 %* \textltailm -> \labdentalnas (wsuipa)
 16529 %* \textltailm -> \emgma (phonetic)
 16530 % U+0272 LATIN SMALL LETTER N WITH LEFT HOOK; nhookleft; \textltailn (tipa)
 16531 \DeclareTextCommand{\textltailn}{PU}{\82\162}% U+0272
 16532 %* \textltailn -> \nj (wsuipa)
 16533 %* \textltailn -> \nya (phonetic)
 16534 % U+0273 LATIN SMALL LETTER N WITH RETROFLEX HOOK;
 16535 % nhookretroflex; \textrtailn (tipa)
 16536 \DeclareTextCommand{\textrtailn}{PU}{\82\163}% U+0273
 16537 %* \textrtailn -> \tailn (wsuipa)
 16538 % U+0274 LATIN LETTER SMALL CAPITAL N; \textscn (tipa), \scn (wsuipa)
 16539 \DeclareTextCommand{\textscn}{PU}{\82\164}% U+0274
 16540 % U+0275 LATIN CAPITAL LETTER O WITH MIDDLE TILDE/
 16541 % LATIN CAPITAL LETTER BARRED O; obarred;
 16542 % \textbaro (tipa), \baro (wsuipa)
 16543 % But \baro from stmaryrd is different!
 16544 \DeclareTextCommand{\textbaro}{PU}{\82\165}% U+0275
 16545 % U+0276 LATIN LETTER SMALL CAPITAL OE; \textscelig (tipa)
 16546 \DeclareTextCommand{\textscelig}{PU}{\82\166}% U+0276
 16547 % U+0277 LATIN SMALL LETTER CLOSED OMEGA; omegalatininclosed;
 16548 % \textcloseomega (tipa)
 16549 \DeclareTextCommand{\textcloseomega}{PU}{\82\167}% U+0277
 16550 %* \textcloseomega -> \closedniomega (wsuipa)
 16551 %* \textcloseomega -> \varomega (phonetic)
 16552 % U+0278 LATIN SMALL LETTER PHI; philatin; \nippi (wsuipa)
 16553 \DeclareTextCommand{\textnippi}{PU}{\82\170}% U+0278
 16554 % U+0279 LATIN SMALL LETTER TURNED R; rturned; \textturnr (tipa)
 16555 \DeclareTextCommand{\textturnr}{PU}{\82\171}% U+0279
 16556 %* \textturnr -> \invr (wsuipa)
 16557 %* \textturnr -> \rotr (phonetic)
 16558 % U+027A LATIN SMALL LETTER TURNED R WITH LONG LEG;
 16559 % rlonglegturned; \textturnlongleg (tipa)
 16560 \DeclareTextCommand{\textturnlongleg}{PU}{\82\172}% U+027A
 16561 %* \textturnlongleg -> \invleg (wsuipa)
 16562 % U+027B LATIN SMALL LETTER TURNED R WITH HOOK; rhoorturned;
 16563 % \textturnrrtail (tipa)
 16564 \DeclareTextCommand{\textturnrrtail}{PU}{\82\173}% U+027B
 16565 %* \textturnrrtail -> \tailinvr (wsuipa)
 16566 % U+027C LATIN SMALL LETTER R WITH LONG LEG; rlongleg; \textlongleg (tipa)
 16567 \DeclareTextCommand{\textlongleg}{PU}{\82\174}% U+027C
 16568 %* \textlongleg -> \leg (wsuipa)
 16569 % U+027D LATIN SMALL LETTER R WITH TAIL; rhoortail; \textrtailr (tipa)
 16570 \DeclareTextCommand{\textrtailr}{PU}{\82\175}% U+027D
 16571 %* \textrtailr -> \tailr (wsuipa)
 16572 % U+027E LATIN SMALL LETTER R WITH FISHHOOK; rfishhook;
 16573 % \textfishhookr (tipa)
 16574 \DeclareTextCommand{\textfishhookr}{PU}{\82\176}% U+027E
 16575 %* \textfishhookr -> \flapr (wsuipa)
 16576 %* \textfishhookr -> \flap (phonetic)
 16577 % U+027F LATIN SMALL LETTER REVERSED R WITH FISHHOOK; rfishhookreversed;
 16578 % \textlhtlongi (tipa)
 16579 \DeclareTextCommand{\textlhtlongi}{PU}{\82\177}% U+027F
 16580 % U+0280 LATIN LETTER SMALL CAPITAL R; \textscr (tipa), \scr (wsuipa)
 16581 \DeclareTextCommand{\textscr}{PU}{\82\200}% U+0280

16582 % U+0281 LATIN LETTER SMALL CAPITAL INVERTED R; Rsmallinverted;
16583 % \textinvscr (tipa), \invscr (wsuipa)
16584 \DeclareTextCommand{\textinvscr}{PU}{\82\201}%* U+0281
16585 % U+0282 LATIN SMALL LETTER S WITH HOOK; shook; \textrtails (tipa)
16586 \DeclareTextCommand{\textrtails}{PU}{\82\202}% U+0282
16587 %* \textrtails -> \tails (wsuipa)
16588 % U+0283 LATIN SMALL LETTER ESH; esh; \textesh (tipa), \esh (wsuipa)
16589 \DeclareTextCommand{\textesh}{PU}{\82\203}%* U+0283
16590 % U+0284 LATIN SMALL LETTER DOTLESS J WITH STROKE AND HOOK;
16591 % dotlessjstrokehook; \texthtbardotlessj (tipa)
16592 \DeclareTextCommand{\texthtbardotlessj}{PU}{\82\204}% U+0284
16593 % U+0285 LATIN SMALL LETTER SQUAT REVERSED ESH; eshsquatre-
versed;
16594 % \textvibyi (tipa)
16595 \DeclareTextCommand{\textvibyi}{PU}{\82\205}% U+0285
16596 % U+0286 LATIN SMALL LETTER ESH WITH CURL; eshcurl; \textctesh (tipa)
16597 \DeclareTextCommand{\textctesh}{PU}{\82\206}% U+0286
16598 %* \textctesh -> \curlyesh (wsuipa)
16599 % U+0287 LATIN SMALL LETTER TURNED T; tturned; \textturnt (tipa)
16600 \DeclareTextCommand{\textturnt}{PU}{\82\207}% U+0287
16601 %* \textturnt -> \clickt (wsuipa)
16602 % U+0288 LATIN SMALL LETTER T WITH RETROFLEX HOOK; retroflex-
hook;
16603 % \textrtailt (tipa)
16604 \DeclareTextCommand{\textrtailt}{PU}{\82\210}% U+0288
16605 %* \textrtailt -> \tailt (wsuipa)
16606 % U+0289 LATIN SMALL LETTER U BAR; ubar;
16607 % \textbaru (tipa), \baru (wsuipa)
16608 \DeclareTextCommand{\textbaru}{PU}{\82\211}%* U+0289
16609 %* \textbaru -> \ubar (phonetic)
16610 % U+028A LATIN SMALL LETTER UPSILON; \niupsilon (wsuipa)
16611 \DeclareTextCommand{\textniupsilon}{PU}{\82\212}%* U+028A
16612 %* \textniupsilon -> \rotOmega (phonetic)
16613 % U+028B LATIN SMALL LETTER V WITH HOOK/LATIN SMALL LET-
TER SCRIPT V;
16614 % vhook; \textscriptv (tipa), \scriptv (wsuipa)
16615 \DeclareTextCommand{\textscriptv}{PU}{\82\213}%* U+028B
16616 % U+028C LATIN SMALL LETTER TURNED V; vturned; \textturnv (tipa)
16617 \DeclareTextCommand{\textturnv}{PU}{\82\214}%* U+028C
16618 %* \textturnv -> \invv (wsuipa)
16619 %* \textturnv -> \pwedge (phonetic)
16620 % U+028D LATIN SMALL LETTER TURNED W; wturned; \textturnw (tipa)
16621 \DeclareTextCommand{\textturnw}{PU}{\82\215}%* U+028D
16622 %* \textturnw -> \invw (wsuipa)
16623 %* \textturnw -> \rotw (phonetic)
16624 % U+028E LATIN SMALL LETTER TURNED Y; yturned; \textturny (tipa)
16625 \DeclareTextCommand{\textturny}{PU}{\82\216}%* U+028E
16626 %* \textturny -> \invy (wsuipa)
16627 %* \textturny -> \roty (phonetic)
16628 % U+028F LATIN LETTER SMALL CAPITAL Y; \textscy (tipa), \scy (wsuipa)
16629 \DeclareTextCommand{\textscy}{PU}{\82\217}%* U+028F
16630 % U+0290 LATIN SMALL LETTER Z WITH RETROFLEX HOOK; zretroflex-
hook;
16631 % \textrtailz (tipa)
16632 \DeclareTextCommand{\textrtailz}{PU}{\82\220}% U+0290
16633 %* \textrtailz -> \tailz (wsuipa)
16634 % U+0291 LATIN SMALL LETTER Z WITH CURL; zcurl; \textctz (tipa)

16635 \DeclareTextCommand{\textctz}{PU}{\82\221}% U+0291
16636 %* \textctz -> \curlyz (wsuipa)
16637 % U+0292 LATIN SMALL LETTER EZH/LATIN SMALL LETTER YOGH; ezh;
16638 % \textyogh (tipa), \yogh (wsuipa)
16639 \DeclareTextCommand{\textyogh}{PU}{\82\222}%* U+0292
16640 % U+0293 LATIN SMALL LETTER EZH WITH CURL/LATIN SMALL LETTER YOGH CURL;
16641 % ezhcurl; \textctyogh (tipa)
16642 \DeclareTextCommand{\textctyogh}{PU}{\82\223}% U+0293
16643 %* \textctyogh -> \curlyyogh (wsuipa)
16644 % U+0294 LATIN LETTER GLOTTAL STOP; glottalstop;
16645 % \textglotstop (tipa), \glotstop (wsuipa)
16646 \DeclareTextCommand{\textglotstop}{PU}{\82\224}%* U+0294
16647 %* \textglotstop -> \ejjective (wsuipa)
16648 %* \textglotstop -> \glottal (phonetic)
16649 % U+0295 LATIN LETTER PHARYNGEAL VOICED FRICATIVE/
16650 % LATIN LETTER REVERSED GLOTTAL STOP; glottalstopreversed;
16651 % \textrevglotstop (tipa), \revglotstop (wsuipa)
16652 \DeclareTextCommand{\textrevglotstop}{PU}{\82\225}%* U+0295
16653 %* \textrevglotstop -> \reveject (wsuipa)
16654 % U+0296 LATIN LETTER INVERTED GLOTTAL STOP; glottalstopinverted;
16655 % \textinvglotstop (tipa), \invglotstop (wsuipa)
16656 \DeclareTextCommand{\textinvglotstop}{PU}{\82\226}%* U+0296
16657 % U+0297 LATIN LETTER STRETCHED C; cstretched; \textstretchc (tipa)
16658 \DeclareTextCommand{\textstretchc}{PU}{\82\227}% U+0297
16659 %* \textstretchc -> \clickc (wsuipa)
16660 %* \textstretchc -> \textstretchcvar (tipx)
16661 % U+0298 LATIN LETTER BILABIAL CLICK; bilabialclick;
16662 % \textbullseye (tipa)
16663 \DeclareTextCommand{\textbullseye}{PU}{\82\230}% U+0298
16664 %* \textbullseye -> \clickb (wsuipa)
16665 %* \textbullseye -> \textObullseye (tipx)
16666 % U+0299 LATIN LETTER SMALL CAPITAL B; \textscb (tipa)
16667 \DeclareTextCommand{\textscb}{PU}{\82\231}% U+0299
16668 % U+029A LATIN SMALL LETTER CLOSED OPEN E; eopenclosed;
16669 % \textcloseepsilon (tipa)
16670 \DeclareTextCommand{\textcloseepsilon}{PU}{\82\232}% U+029A
16671 % U+029B LATIN LETTER SMALL CAPITAL G WITH HOOK; Gsmallhook;
16672 % \texthtscg (tipa)
16673 \DeclareTextCommand{\texthtscg}{PU}{\82\233}% U+029B
16674 % U+029C LATIN LETTER SMALL CAPITAL H; \textsch (tipa)
16675 \DeclareTextCommand{\textsch}{PU}{\82\234}% U+029C
16676 % U+029D LATIN SMALL LETTER J WITH CROSSED-TAIL; jcrossetail; \textcdj (tipa)
16677 \DeclareTextCommand{\textctj}{PU}{\82\235}% U+029D
16678 %* \textctj -> \textctjvar (tipx)
16679 % U+029E LATIN SMALL LETTER TURNED K; kturned; \textturnk (tipa)
16680 \DeclareTextCommand{\textturnk}{PU}{\82\236}% U+029E
16681 %* \textturnk -> \textturnsck (tipx)
16682 % U+029F LATIN LETTER SMALL CAPITAL L; \textscL (tipa)
16683 \DeclareTextCommand{\textscL}{PU}{\82\237}% U+029F
16684 % U+02A0 LATIN SMALL LETTER Q WITH HOOK; qhook; \texthtq (tipa)
16685 \DeclareTextCommand{\texthtq}{PU}{\82\240}% U+02A0
16686 % U+02A1 LATIN LETTER GLOTTAL STOP WITH STROKE; glottalstop-stroke;
16687 % \textbarglotstop (tipa)
16688 \DeclareTextCommand{\textbarglotstop}{PU}{\82\241}% U+02A1

16689 % U+02A2 LATIN LETTER REVERSED GLOTTAL STOP WITH STROKE/
 16690 % LATIN LETTER REVERSED GLOTTAL STOP BAR; glottalstopstrokere-
 versed;
 16691 % \textbarrevglotstop (tipa)
 16692 \DeclareTextCommand{\textbarrevglotstop}{PU}{\82\242}% U+02A2
 16693 % U+02A3 LATIN SMALL LETTER DZ DIGRAPH; dzaltone; \textdzlig (tipa)
 16694 \DeclareTextCommand{\textdzlig}{PU}{\82\243}% U+02A3
 16695 %* \textdzlig -> \dz (wsupipa)
 16696 % U+02A4 LATIN SMALL LETTER DEZH DIGRAPH; dezh; \textdyogh-
 lig (tipa)
 16697 \DeclareTextCommand{\textdyoghlig}{PU}{\82\244}% U+02A4
 16698 % U+02A5 LATIN SMALL LETTER DZ DIGRAPH WITH CURL; dzcurl;
 16699 % \textdctzlig (tipa)
 16700 \DeclareTextCommand{\textdctzlig}{PU}{\82\245}% U+02A5
 16701 % U+02A6 LATIN SMALL LETTER TS DIGRAPH; ts; \texttslig (tipa)
 16702 \DeclareTextCommand{\texttslig}{PU}{\82\246}% U+02A6
 16703 % U+02A7 LATIN SMALL LETTER TESH DIGRAPH; tesh; \texttshlig (tipa)
 16704 \DeclareTextCommand{\texttshlig}{PU}{\82\247}% U+02A7
 16705 %* \texttshlig -> \tesh (wsuipa)
 16706 % U+02A8 LATIN SMALL LETTER TC DIGRAPH WITH CURL; tccurl;
 16707 % \texttctclig (tipa)
 16708 \DeclareTextCommand{\texttctclig}{PU}{\82\250}% U+02A8
 16709 % U+02AE LATIN SMALL LETTER TURNED H WITH FISHHOOK;
 16710 % \textlhtlongy (tipa)
 16711 \DeclareTextCommand{\textlhtlongy}{PU}{\82\256}% U+02AE
 16712 % U+02AF LATIN SMALL LETTER TURNED H WITH FISHHOOK AND TAIL;
 16713 % \textvibyy (tipa)
 16714 \DeclareTextCommand{\textvibyy}{PU}{\82\257}% U+02AF

51.2.7 Spacing Modifier Letters: U+02B0 to U+02FF

16715 % U+02BD MODIFIER LETTER REVERSED COMMA;
 16716 % commareversedmod, afi64937; \textrevapostrophe (tipa)
 16717 \DeclareTextCommand{\textrevapostrophe}{PU}{\82\275}% U+02BD
 16718 % U+02C0 MODIFIER LETTER GLOTTAL STOP; glottalstopmod;
 16719 % \textraiseglotstop (tipa)
 16720 \DeclareTextCommand{\textraiseglotstop}{PU}{\82\300}% U+02C0
 16721 % U+02C2 MODIFIER LETTER LEFT ARROWHEAD; arrowheadleftmod;
 16722 % \textlptr (tipa)
 16723 \DeclareTextCommand{\textlptr}{PU}{\82\302}% U+02C2
 16724 % U+02C3 MODIFIER LETTER RIGHT ARROWHEAD; arrowheadrightmod;
 16725 % \textrptr (tipa)
 16726 \DeclareTextCommand{\textrptr}{PU}{\82\303}% U+02C3
 16727 % U+02C7 CARON; caron
 16728 \DeclareTextCommand{\textasciicaron}{PU}{\82\307}% U+02C7
 16729 % U+02C8 MODIFIER LETTER VERTICAL LINE; verticallinemod;
 16730 % \textprimstress (tipa)
 16731 \DeclareTextCommand{\textprimstress}{PU}{\82\310}% U+02C8
 16732 % U+02CC MODIFIER LETTER LOW VERTICAL LINE; verticallinelowmod;
 16733 % \textsecstress (tipa)
 16734 \DeclareTextCommand{\textsecstress}{PU}{\82\314}% U+02CC
 16735 % U+02D0 MODIFIER LETTER TRIANGULAR COLON; colontriangularmod;
 16736 % \textlengthmark (tipa)
 16737 \DeclareTextCommand{\textlengthmark}{PU}{\82\320}% U+02D0
 16738 % U+02D1 MODIFIER LETTER HALF TRIANGULAR COLON; colontriangu-
 larhalfmod;
 16739 % \texthalflength (tipa)
 16740 \DeclareTextCommand{\texthalflength}{PU}{\82\321}% U+02D1

16741 % U+02D8 BREVE; breve
 16742 \DeclareTextCommand{\textasciibreve}{PU}{\82\330}% U+02D8
 16743 % U+02D9 DOT ABOVE; dotaccent
 16744 \DeclareTextCommand{\textdotaccent}{PU}{\82\331}% U+02D9
 16745 % U+02DA RING ABOVE; ring
 16746 \DeclareTextCommand{\textring}{PU}{\82\332}% U+02DA
 16747 % U+02DB OGONEK; ogonek
 16748 \DeclareTextCommand{\textogonek}{PU}{\82\333}% U+02DB
 16749 % U+02DC SMALL TILDE; ilde, *tilde
 16750 \DeclareTextCommand{\texttilde}{PU}{\82\334}% U+02DC
 16751 % U+02DD DOUBLE ACUTE ACCENT; hungarumlaut
 16752 \DeclareTextCommand{\texthungarumlaut}{PU}{\82\335}% U+02DD
 16753 \DeclareTextCommand{\textacutedbl}{PU}{\82\335}% U+02DD
 16754 % U+02F3 MODIFIER LETTER LOW RING
 16755 \DeclareTextCommand{\textringlow}{PU}{\82\363}% U+02F3
 16756 % U+02F5 MODIFIER LETTER MIDDLE DOUBLE GRAVE ACCENT
 16757 \DeclareTextCommand{\textgravedbl}{PU}{\82\365}% U+02F5
 16758 % U+02F7 MODIFIER LETTER LOW TILDE
 16759 \DeclareTextCommand{\texttildelow}{PU}{\82\367}% U+02F7
 16760 % U+02F9 MODIFIER LETTER BEGIN HIGH TONE; \textopencorner (tipa)
 16761 \DeclareTextCommand{\textopencorner}{PU}{\82\371}% U+02F9
 16762 % U+02FA MODIFIER LETTER END HIGH TONE; \textcorner (tipa)
 16763 \DeclareTextCommand{\textcorner}{PU}{\82\372}% U+02FA

51.2.8 Combining Diacritical Marks: U+0300 to U+036F

16764 % U+030F COMBINING DOUBLE GRAVE ACCENT; dblgravecmb
 16765 \DeclareTextCommand{\textdoublegrave}{PU}{\83\017}% U+030F
 16766 % U+0311 COMBINING INVERTED BREVE; breveinvertedcmb
 16767 \DeclareTextCommand{\textnewtie}{PU}{\83\021}% U+0311
 16768 % U+0323 COMBINING DOT BELOW; dotbelowcmb, *dotbelowcomb
 16769 \DeclareTextCommand{\textdotbelow}{PU}{\83\043}% U+0323
 16770 % U+0331 COMBINING MACRON BELOW; macronbelowcmb
 16771 \DeclareTextCommand{\textmacronbelow}{PU}{\83\061}% U+0331
 16772 % U+0361 COMBINING DOUBLE INVERTED BREVE; breveinverteddoublecmb
 16773 \DeclareTextCommand{\texttie}{PU}{\83\141}% U+0361

51.2.9 Greek and Coptic: U+0370 to U+03FF

16774 % U+0374 GREEK NUMERAL SIGN; numeralsigngreek
 16775 \DeclareTextCommand{\textnumeralsigngreek}{PU}{\83\164}% U+0374
 16776 % U+0375 GREEK LOWER NUMERAL SIGN; numeralsignlowergreek
 16777 \DeclareTextCommand{\textnumeralsignlowergreek}{PU}{\83\165}% U+0375
 16778 % U+0386 GREEK CAPITAL LETTER ALPHA WITH TONOS; Alphanos
 16779 \DeclareTextCompositeCommand{\'}{PU}{\textAlpha}{\83\206}% U+0386
 16780 % U+0388 GREEK CAPITAL LETTER EPSILON WITH TONOS; Epsilontonos
 16781 \DeclareTextCompositeCommand{\'}{PU}{\textEpsilon}{\83\210}% U+0388
 16782 % U+0389 GREEK CAPITAL LETTER ETA WITH TONOS; Etatonos
 16783 \DeclareTextCompositeCommand{\'}{PU}{\textEta}{\83\211}% U+0389
 16784 % U+038A GREEK CAPITAL LETTER IOTA WITH TONOS; Iotatonos
 16785 \DeclareTextCompositeCommand{\'}{PU}{\textIota}{\83\212}% U+038A
 16786 % U+038C GREEK CAPITAL LETTER OMICRON WITH TONOS; Omicrontonos
 16787 \DeclareTextCompositeCommand{\'}{PU}{\textOmicron}{\83\214}% U+038C
 16788 % U+038E GREEK CAPITAL LETTER UPSILON WITH TONOS; Upsilononos
 16789 \DeclareTextCompositeCommand{\'}{PU}{\textUpsilon}{\83\216}% U+038E
 16790 % U+038F GREEK CAPITAL LETTER OMEGA WITH TONOS; Omegatonos
 16791 \DeclareTextCompositeCommand{\'}{PU}{\textOmega}{\83\217}% U+038F

16792 % U+0390 GREEK SMALL LETTER IOTA WITH DIALYTIKA AND TONOS;
 16793 % iotadieresis
 16794 \DeclareTextCompositeCommand{\'}{PU}{\textIotadieresis}{\83\220}% U+0390
 16795 % U+0391 GREEK CAPITAL LETTER ALPHA; Alpha
 16796 \DeclareTextCommand{\textAlpha}{PU}{\83\221}% U+0391
 16797 % U+0392 GREEK CAPITAL LETTER BETA; Beta
 16798 \DeclareTextCommand{\textBeta}{PU}{\83\222}% U+0392
 16799 % U+0393 GREEK CAPITAL LETTER GAMMA; Gamma; \Gamma (LaTeX)
 16800 \DeclareTextCommand{\textGamma}{PU}{\83\223}%* U+0393
 16801 % U+0394 GREEK CAPITAL LETTER DELTA; Deltagreek, *Delta; \Delta (LaTeX)
 16802 \DeclareTextCommand{\textDelta}{PU}{\83\224}%* U+0394
 16803 % U+0395 GREEK CAPITAL LETTER EPSILON; Epsilon
 16804 \DeclareTextCommand{\textEpsilon}{PU}{\83\225}% U+0395
 16805 % U+0396 GREEK CAPITAL LETTER ZETA; Zeta
 16806 \DeclareTextCommand{\textZeta}{PU}{\83\226}% U+0396
 16807 % U+0397 GREEK CAPITAL LETTER ETA; Eta
 16808 \DeclareTextCommand{\textEta}{PU}{\83\227}% U+0397
 16809 % U+0398 GREEK CAPITAL LETTER THETA; Theta; \Theta (LaTeX)
 16810 \DeclareTextCommand{\textTheta}{PU}{\83\230}%* U+0398
 16811 % U+0399 GREEK CAPITAL LETTER IOTA; Iota
 16812 \DeclareTextCommand{\textIota}{PU}{\83\231}% U+0399
 16813 % U+039A GREEK CAPITAL LETTER KAPPA; Kappa
 16814 \DeclareTextCommand{\textKappa}{PU}{\83\232}% U+039A
 16815 % U+039B GREEK CAPITAL LETTER LAMDA; Lambda; \Lambda (LaTeX)
 16816 \DeclareTextCommand{\textLambda}{PU}{\83\233}%* U+039B
 16817 % U+039C GREEK CAPITAL LETTER MU; Mu
 16818 \DeclareTextCommand{\textMu}{PU}{\83\234}% U+039C
 16819 % U+039D GREEK CAPITAL LETTER NU; Nu
 16820 \DeclareTextCommand{\textNu}{PU}{\83\235}% U+039D
 16821 % U+039E GREEK CAPITAL LETTER XI; Xi; \Xi (LaTeX)
 16822 \DeclareTextCommand{\textXi}{PU}{\83\236}%* U+039E
 16823 % U+039F GREEK CAPITAL LETTER OMICRON; Omicron
 16824 \DeclareTextCommand{\textOmicron}{PU}{\83\237}% U+039F
 16825 % U+03A0 GREEK CAPITAL LETTER PI; Pi
 16826 \DeclareTextCommand{\textPi}{PU}{\83\240}%* U+03A0
 16827 % U+03A1 GREEK CAPITAL LETTER RHO; Rho
 16828 \DeclareTextCommand{\textRho}{PU}{\83\241}% U+03A1
 16829 % U+03A3 GREEK CAPITAL LETTER SIGMA; Sigma; \Sigma (LaTeX)
 16830 \DeclareTextCommand{\textSigma}{PU}{\83\243}%* U+03A3
 16831 % U+03A4 GREEK CAPITAL LETTER TAU; Tau
 16832 \DeclareTextCommand{\textTau}{PU}{\83\244}% U+03A4
 16833 % U+03A5 GREEK CAPITAL LETTER UPSILON; Upsilon; \Upsilon (LaTeX)
 16834 \DeclareTextCommand{\textUpsilon}{PU}{\83\245}%* U+03A5
 16835 % U+03A6 GREEK CAPITAL LETTER PHI; Phi; \Phi (LaTeX)
 16836 \DeclareTextCommand{\textPhi}{PU}{\83\246}%* U+03A6
 16837 % U+03A7 GREEK CAPITAL LETTER CHI; Chi
 16838 \DeclareTextCommand{\textChi}{PU}{\83\247}% U+03A7
 16839 % U+03A8 GREEK CAPITAL LETTER PSI; Psi; \Psi (LaTeX)
 16840 \DeclareTextCommand{\textPsi}{PU}{\83\250}%* U+03A8
 16841 % U+03A9 GREEK CAPITAL LETTER OMEGA; Omegagreek, *Omega;
 16842 % \Omega (LaTeX)
 16843 \DeclareTextCommand{\textOmega}{PU}{\83\251}%* U+03A9
 16844 % U+03AA GREEK CAPITAL LETTER IOTA WITH DIALYTIKA; Iotadieresis
 16845 \DeclareTextCommand{\textIotadieresis}{PU}{\83\252}% U+03AA
 16846 \DeclareTextCompositeCommand{\"}{PU}{\textIota}{\83\252}% U+03AA

16847 % U+03AB GREEK CAPITAL LETTER UPSILON WITH DIALYTIKA; Up-
 silondieresis
 16848 \DeclareTextCompositeCommand{"}{PU}{\textUpsilon}{\83\253}% U+03AB
 16849 % U+03AC GREEK SMALL LETTER ALPHA WITH TONOS; alphanos
 16850 \DeclareTextCompositeCommand{'}{PU}{\textalpha}{\83\254}%* U+03AC
 16851 % U+03AD GREEK SMALL LETTER EPSILON WITH TONOS; epsilontonos
 16852 \DeclareTextCompositeCommand{'}{PU}{\textepsilon}{\83\255}% U+03AD
 16853 % U+03AE GREEK SMALL LETTER ETA WITH TONOS; etatonos
 16854 \DeclareTextCompositeCommand{'}{PU}{\texteta}{\83\256}% U+03AE
 16855 % U+03AF GREEK SMALL LETTER IOTA WITH TONOS; iotatonos
 16856 \DeclareTextCompositeCommand{'}{PU}{\textiota}{\83\257}% U+03AF
 16857 % U+03B0 GREEK SMALL LETTER UPSILON WITH DIALYTIKA
 16858 % AND TONOS; upsilondieresis
 16859 \DeclareTextCompositeCommand{"}{PU}{\textupsilonacute}{\83\260}% U+03B0
 16860 % U+03B1 GREEK SMALL LETTER ALPHA; alpha; \alpha (LaTeX)
 16861 \DeclareTextCommand{\textalpha}{PU}{\83\261}%* U+03B1
 16862 % U+03B2 GREEK SMALL LETTER BETA; beta; \beta (LaTeX)
 16863 \DeclareTextCommand{\textbeta}{PU}{\83\262}%* U+03B2
 16864 % U+03B3 GREEK SMALL LETTER GAMMA; gamma; \gamma (LaTeX)
 16865 \DeclareTextCommand{\textgamma}{PU}{\83\263}%* U+03B3
 16866 % U+03B4 GREEK SMALL LETTER DELTA; delta; \delta (LaTeX)
 16867 \DeclareTextCommand{\textdelta}{PU}{\83\264}%* U+03B4
 16868 % U+03B5 GREEK SMALL LETTER EPSILON; epsilon; \epsilon (LaTeX)
 16869 \DeclareTextCommand{\textepsilon}{PU}{\83\265}%* U+03B5
 16870 % U+03B6 GREEK SMALL LETTER ZETA; zeta; \zeta (LaTeX)
 16871 \DeclareTextCommand{\textzeta}{PU}{\83\266}%* U+03B6
 16872 % U+03B7 GREEK SMALL LETTER ETA; eta; \eta (LaTeX)
 16873 \DeclareTextCommand{\texteta}{PU}{\83\267}%* U+03B7
 16874 % U+03B8 GREEK SMALL LETTER THETA; theta; \theta (LaTeX)
 16875 \DeclareTextCommand{\texttheta}{PU}{\83\270}%* U+03B8
 16876 % U+03B9 GREEK SMALL LETTER IOTA; iota; \iota (LaTeX)
 16877 \DeclareTextCommand{\textiota}{PU}{\83\271}%* U+03B9
 16878 % U+03BA GREEK SMALL LETTER KAPPA; kappa; \kappa (LaTeX)
 16879 \DeclareTextCommand{\textkappa}{PU}{\83\272}%* U+03BA
 16880 % U+03BB GREEK SMALL LETTER LAMDA; lambda; \lambda (LaTeX)
 16881 \DeclareTextCommand{\textlambda}{PU}{\83\273}%* U+03BB
 16882 % U+03BC GREEK SMALL LETTER MU; mugreek; \mu (LaTeX)
 16883 \DeclareTextCommand{\textmugreek}{PU}{\83\274}%* U+03BC
 16884 % U+03BD GREEK SMALL LETTER NU; nu; \nu (LaTeX)
 16885 \DeclareTextCommand{\textnu}{PU}{\83\275}%* U+03BD
 16886 % U+03BE GREEK SMALL LETTER XI; xi; \xi (LaTeX)
 16887 \DeclareTextCommand{\textxi}{PU}{\83\276}%* U+03BE
 16888 % U+03BF GREEK SMALL LETTER OMICRON; omicron
 16889 \DeclareTextCommand{\textomicron}{PU}{\83\277}% U+03BF
 16890 % U+03C0 GREEK SMALL LETTER PI; pi; \pi (LaTeX)
 16891 \DeclareTextCommand{\textpi}{PU}{\83\300}%* U+03C0
 16892 % U+03C1 GREEK SMALL LETTER RHO; rho; \rho (LaTeX)
 16893 \DeclareTextCommand{\textrho}{PU}{\83\301}%* U+03C1
 16894 % U+03C2 GREEK SMALL LETTER FINAL SIGMA; \sigma1, sigmafinal
 16895 \DeclareTextCommand{\textvarsigma}{PU}{\83\302}%* U+03C2
 16896 % U+03C3 GREEK SMALL LETTER SIGMA; sigma; \sigma (LaTeX)
 16897 \DeclareTextCommand{\textsigma}{PU}{\83\303}%* U+03C3
 16898 % U+03C4 GREEK SMALL LETTER TAU; tau; \tau (LaTeX)
 16899 \DeclareTextCommand{\texttau}{PU}{\83\304}%* U+03C4
 16900 % U+03C5 GREEK SMALL LETTER UPSILON; upsilon; \upsilon (LaTeX)
 16901 \DeclareTextCommand{\textupsilon}{PU}{\83\305}%* U+03C5
 16902 % U+03C6 GREEK SMALL LETTER PHI; phi; \phi (LaTeX)

```

16903 \DeclareTextCommand{\textphi}{PU}{\83\306}%* U+03C6
16904 % U+03C7 GREEK SMALL LETTER CHI; chi; \chi (LaTeX)
16905 \DeclareTextCommand{\textchi}{PU}{\83\307}%* U+03C7
16906 % U+03C8 GREEK SMALL LETTER PSI; psi; \psi (LaTeX)
16907 \DeclareTextCommand{\textpsi}{PU}{\83\310}%* U+03C8
16908 % U+03C9 GREEK SMALL LETTER OMEGA; omega; \omega (LaTeX)
16909 \DeclareTextCommand{\textomega}{PU}{\83\311}%* U+03C9
16910 % U+03CA GREEK SMALL LETTER IOTA WITH DIALYTIKA; iotadieresis
16911 \DeclareTextCompositeCommand{\'}{PU}{\textiota}{\83\312}% U+03CA
16912 % U+03CB GREEK SMALL LETTER UPSILON WITH DIALYTIKA; up-
    silondieresis
16913 \DeclareTextCompositeCommand{\'}{PU}{\textupsilon}{\83\313}% U+03CB
16914 % U+03CC GREEK SMALL LETTER OMICRON WITH TONOS; omicrontonos
16915 \DeclareTextCompositeCommand{\'}{PU}{\textomicron}{\83\314}% U+03CC
16916 % U+03CD GREEK SMALL LETTER UPSILON WITH TONOS; upsilontonos
16917 \DeclareTextCommand{\textupsilonacute}{PU}{\83\315}% U+03CD
16918 \DeclareTextCompositeCommand{\'}{PU}{\textupsilon}{\83\315}% U+03CD
16919 % U+03CE GREEK SMALL LETTER OMEGA WITH TONOS; omegatonos
16920 \DeclareTextCompositeCommand{\'}{PU}{\textomega}{\83\316}% U+03CE
16921 % U+03DA GREEK LETTER STIGMA; Stigmagreek
16922 \DeclareTextCommand{\textStigmagreek}{PU}{\83\332}% U+03DA
16923 % U+03DB GREEK SMALL LETTER STIGMA
16924 \DeclareTextCommand{\textstigmagreek}{PU}{\83\333}% U+03DB
16925 % U+03DC GREEK LETTER DIGAMMA; Digammagreek
16926 \DeclareTextCommand{\textDigammagreek}{PU}{\83\334}% U+03DC
16927 % U+03DD GREEK SMALL LETTER DIGAMMA
16928 \DeclareTextCommand{\textdigammagreek}{PU}{\83\335}% U+03DD
16929 %* \textdigammagreek -> \digamma (AmS)
16930 % U+03DE GREEK LETTER KOPPA; Koppagreek
16931 \DeclareTextCommand{\textKoppagreek}{PU}{\83\336}% U+03DE
16932 % U+03DF GREEK SMALL LETTER KOPPA
16933 \DeclareTextCommand{\textkoppagreek}{PU}{\83\337}% U+03DF
16934 % U+03E0 GREEK LETTER SAMPI; Sampigreek
16935 \DeclareTextCommand{\textSampigreek}{PU}{\83\340}% U+03E0
16936 % U+03E1 GREEK SMALL LETTER SAMPI
16937 \DeclareTextCommand{\textsampigreek}{PU}{\83\341}% U+03E1
16938 % U+03F6 GREEK REVERSED LUNATE EPSILON SYMBOL;
16939 % \backepsilon (AmS)
16940 \DeclareTextCommand{\textbackepsilon}{PU}{\83\366}% U+03F6

```

51.2.10 Cyrillic: U+0400 to U+04FF

Thanks to Vladimir Volovich (vov@vov.vsu.ru) for the help with the Cyrillic glyph names.

```

16941 % U+0400 CYRILLIC CAPITAL LETTER IE WITH GRAVE
16942 \DeclareTextCompositeCommand{\'}{PU}{\CYRE}{\84\000}% U+0400
16943 % U+0401 CYRILLIC CAPITAL LETTER IO; Iocyrrilic, *afi10023
16944 \DeclareTextCommand{\CYRYO}{PU}{\84\001}% U+0401
16945 \DeclareTextCompositeCommand{\'}{PU}{\CYRE}{\84\001}% U+0401
16946 % U+0402 CYRILLIC CAPITAL LETTER DJE; Djecyrillic, *afi10051
16947 \DeclareTextCommand{\CYRDJE}{PU}{\84\002}% U+0402
16948 % U+0403 CYRILLIC CAPITAL LETTER GJE; Gjecyrillic, *afi10052
16949 \DeclareTextCompositeCommand{\'}{PU}{\CYRG}{\84\003}% U+0403
16950 % U+0404 CYRILLIC CAPITAL LETTER UKRAINIAN IE; Ecyrrilic, *afi10053
16951 \DeclareTextCommand{\CYRIE}{PU}{\84\004}% U+0404
16952 % U+0405 CYRILLIC CAPITAL LETTER DZE; Dzecyrillic, *afi10054
16953 \DeclareTextCommand{\CYRDZE}{PU}{\84\005}% U+0405
16954 % U+0406 CYRILLIC CAPITAL LETTER BYELORUSSIAN-UKRAINIAN I;

```

16955 % Icyrillic, *afii10055
 16956 \DeclareTextCommand{\CYRII}{PU}{\84\006}% U+0406
 16957 % U+0407 CYRILLIC CAPITAL LETTER YI; Yicyrillic, *afii10056
 16958 \DeclareTextCommand{\CYRYI}{PU}{\84\007}% U+0407
 16959 \DeclareTextCompositeCommand{\"}{PU}{\CYRII}{\84\007}% U+0407
 16960 % U+0408 CYRILLIC CAPITAL LETTER JE; Jecyrillic, *afii10057
 16961 \DeclareTextCommand{\CYRJE}{PU}{\84\010}% U+0408
 16962 % U+0409 CYRILLIC CAPITAL LETTER LJE; Ljecyrillic, *afii10058
 16963 \DeclareTextCommand{\CYRLJE}{PU}{\84\011}% U+0409
 16964 % U+040A CYRILLIC CAPITAL LETTER NJE; Njecyrillic, *afii10059
 16965 \DeclareTextCommand{\CYRNJE}{PU}{\84\012}% U+040A
 16966 % U+040B CYRILLIC CAPITAL LETTER TSHE; Tshecyrillic, *afii10060
 16967 \DeclareTextCommand{\CYRTSHE}{PU}{\84\013}% U+040B
 16968 % U+040C CYRILLIC CAPITAL LETTER KJE; Kjecyrillic, *afii10061
 16969 \DeclareTextCompositeCommand{\'}{PU}{\CYRK}{\84\014}% U+040C
 16970 % U+040D CYRILLIC CAPITAL LETTER I WITH GRAVE
 16971 \DeclareTextCompositeCommand{\`}{PU}{\CYRI}{\84\015}% U+040D
 16972 % U+040E CYRILLIC CAPITAL LETTER SHORT U; Ushortcyrillic, *afii10062
 16973 \DeclareTextCommand{\CYRUSHRT}{PU}{\84\016}% U+040E
 16974 \DeclareTextCompositeCommand{\U}{PU}{\CYRU}{\84\016}% U+040E
 16975 % U+040F CYRILLIC CAPITAL LETTER DZHE; Dzhecyrillic, *afii10145
 16976 \DeclareTextCommand{\CYRDZHE}{PU}{\84\017}% U+040F
 16977 % U+0410 CYRILLIC CAPITAL LETTER A; Acyrillic, *afii10017
 16978 \DeclareTextCommand{\CYRA}{PU}{\84\020}% U+0410
 16979 % U+0411 CYRILLIC CAPITAL LETTER BE; Becyrillic, *afii10018
 16980 \DeclareTextCommand{\CYRB}{PU}{\84\021}% U+0411
 16981 % U+0412 CYRILLIC CAPITAL LETTER VE; Vecyrillic, *afii10019
 16982 \DeclareTextCommand{\CYRV}{PU}{\84\022}% U+0412
 16983 % U+0413 CYRILLIC CAPITAL LETTER GHE; Gecyrillic, *afii10020
 16984 \DeclareTextCommand{\CYRG}{PU}{\84\023}% U+0413
 16985 % U+0414 CYRILLIC CAPITAL LETTER DE; Decyrillic, *afii10021
 16986 \DeclareTextCommand{\CYRD}{PU}{\84\024}% U+0414
 16987 % U+0415 CYRILLIC CAPITAL LETTER IE; Iecyrillic, *afii10022
 16988 \DeclareTextCommand{\CYRE}{PU}{\84\025}% U+0415
 16989 % U+0416 CYRILLIC CAPITAL LETTER ZHE; Zhecyrillic, *afii10024
 16990 \DeclareTextCommand{\CYRZH}{PU}{\84\026}% U+0416
 16991 % U+0417 CYRILLIC CAPITAL LETTER ZE; Zecyrillic, *afii10025
 16992 \DeclareTextCommand{\CYRZ}{PU}{\84\027}% U+0417
 16993 % U+0418 CYRILLIC CAPITAL LETTER I; Iicyrillic, *afii10026
 16994 \DeclareTextCommand{\CYRI}{PU}{\84\030}% U+0418
 16995 % U+0419 CYRILLIC CAPITAL LETTER SHORT I; Iishortcyrillic, *afii10027
 16996 \DeclareTextCommand{\CYRISHRT}{PU}{\84\031}% U+0419
 16997 \DeclareTextCompositeCommand{\U}{PU}{\CYRI}{\84\031}% U+0419
 16998 % U+041A CYRILLIC CAPITAL LETTER KA; Kacyrillic, *afii10028
 16999 \DeclareTextCommand{\CYRK}{PU}{\84\032}% U+041A
 17000 % U+041B CYRILLIC CAPITAL LETTER EL; Elcyrillic, *afii10029
 17001 \DeclareTextCommand{\CYRL}{PU}{\84\033}% U+041B
 17002 % U+041C CYRILLIC CAPITAL LETTER EM; Emcyrillic, *afii10030
 17003 \DeclareTextCommand{\CYRM}{PU}{\84\034}% U+041C
 17004 % U+041D CYRILLIC CAPITAL LETTER EN; Encyrillic, *afii10031
 17005 \DeclareTextCommand{\CYRN}{PU}{\84\035}% U+041D
 17006 % U+041E CYRILLIC CAPITAL LETTER O; Ocyrillic, *afii10032
 17007 \DeclareTextCommand{\CYRO}{PU}{\84\036}% U+041E
 17008 % U+041F CYRILLIC CAPITAL LETTER PE; Pecyrillic, *afii10033
 17009 \DeclareTextCommand{\CYRP}{PU}{\84\037}% U+041F
 17010 % U+0420 CYRILLIC CAPITAL LETTER ER; Ercyrillic, *afii10034
 17011 \DeclareTextCommand{\CYRR}{PU}{\84\040}% U+0420

17012 % U+0421 CYRILLIC CAPITAL LETTER ES; Escyrillic, *afii10035
17013 \DeclareTextCommand{\CYRS}{PU}{\84\041}% U+0421
17014 % U+0422 CYRILLIC CAPITAL LETTER TE; Tecyrillic, *afii10036
17015 \DeclareTextCommand{\CYRT}{PU}{\84\042}% U+0422
17016 % U+0423 CYRILLIC CAPITAL LETTER U; Ucyrillic, *afii10037
17017 \DeclareTextCommand{\CYRU}{PU}{\84\043}% U+0423
17018 % U+0424 CYRILLIC CAPITAL LETTER EF; Efcyrillic, *afii10038
17019 \DeclareTextCommand{\CYRF}{PU}{\84\044}% U+0424
17020 % U+0425 CYRILLIC CAPITAL LETTER HA; Khacyrillic, *afii10039
17021 \DeclareTextCommand{\CYRH}{PU}{\84\045}% U+0425
17022 % U+0426 CYRILLIC CAPITAL LETTER TSE; Tsecyrillic, *afii10040
17023 \DeclareTextCommand{\CYRC}{PU}{\84\046}% U+0426
17024 % U+0427 CYRILLIC CAPITAL LETTER CHE; Checyrillic, *afii10041
17025 \DeclareTextCommand{\CYRCH}{PU}{\84\047}% U+0427
17026 % U+0428 CYRILLIC CAPITAL LETTER SHA; Shacyrillic, *afii10042
17027 \DeclareTextCommand{\CYRSH}{PU}{\84\050}% U+0428
17028 % U+0429 CYRILLIC CAPITAL LETTER SHCHA; Shchacyrillic, *afii10043
17029 \DeclareTextCommand{\CYRSHCH}{PU}{\84\051}% U+0429
17030 % U+042A CYRILLIC CAPITAL LETTER HARD SIGN;
17031 % Hardsigncyrillic, *afii10044
17032 \DeclareTextCommand{\CYRHRDSN}{PU}{\84\052}% U+042A
17033 % U+042B CYRILLIC CAPITAL LETTER YERU; Yericyrillic, *afii10045
17034 \DeclareTextCommand{\CYRERY}{PU}{\84\053}% U+042B
17035 % U+042C CYRILLIC CAPITAL LETTER SOFT SIGN;
17036 % Softsigncyrillic, *afii10046
17037 \DeclareTextCommand{\CYRSFTSN}{PU}{\84\054}% U+042C
17038 % U+042D CYRILLIC CAPITAL LETTER E; Ereversedcyrillic, *afii10047
17039 \DeclareTextCommand{\CYREREV}{PU}{\84\055}% U+042D
17040 % U+042E CYRILLIC CAPITAL LETTER YU; IUcyrillic, *afii10048
17041 \DeclareTextCommand{\CYRYU}{PU}{\84\056}% U+042E
17042 % U+042F CYRILLIC CAPITAL LETTER YA; IAcyrillic, *afii10049
17043 \DeclareTextCommand{\CYRYA}{PU}{\84\057}% U+042F
17044 % U+0430 CYRILLIC SMALL LETTER A; acyrillic, *afii10065
17045 \DeclareTextCommand{\cyra}{PU}{\84\060}% U+0430
17046 % U+0431 CYRILLIC SMALL LETTER BE; *afii10066, becyrillic
17047 \DeclareTextCommand{\cyrb}{PU}{\84\061}% U+0431
17048 % U+0432 CYRILLIC SMALL LETTER VE; *afii10067, vecyrillic
17049 \DeclareTextCommand{\cyrv}{PU}{\84\062}% U+0432
17050 % U+0433 CYRILLIC SMALL LETTER GHE; *afii10068, gecyrillic
17051 \DeclareTextCommand{\cyrg}{PU}{\84\063}% U+0433
17052 % U+0434 CYRILLIC SMALL LETTER DE; *afii10069, decyrillic
17053 \DeclareTextCommand{\cyrd}{PU}{\84\064}% U+0434
17054 % U+0435 CYRILLIC SMALL LETTER IE; *afii10070, iecyrillic
17055 \DeclareTextCommand{\cyre}{PU}{\84\065}% U+0435
17056 % U+0436 CYRILLIC SMALL LETTER ZHE; *afii10072, zhacyrillic
17057 \DeclareTextCommand{\cyrz}{PU}{\84\066}% U+0436
17058 % U+0437 CYRILLIC SMALL LETTER ZE; *afii10073, zecyrillic
17059 \DeclareTextCommand{\cyrz}{PU}{\84\067}% U+0437
17060 % U+0438 CYRILLIC SMALL LETTER I; *afii10074, iicyrillic
17061 \DeclareTextCommand{\cyri}{PU}{\84\070}% U+0438
17062 % U+0439 CYRILLIC SMALL LETTER SHORT I; *afii10075, iishortcyrillic
17063 \DeclareTextCommand{\cyrishrt}{PU}{\84\071}% U+0439
17064 \DeclareTextCompositeCommand{\U}{PU}{\cyri}{\84\071}% U+0439
17065 % U+043A CYRILLIC SMALL LETTER KA; *afii10076, kacyrillic
17066 \DeclareTextCommand{\cyrk}{PU}{\84\072}% U+043A
17067 % U+043B CYRILLIC SMALL LETTER EL; *afii10077, elcyrillic
17068 \DeclareTextCommand{\cyrl}{PU}{\84\073}% U+043B

17069 % U+043C CYRILLIC SMALL LETTER EM; *afii10078, emcyrillic
17070 \DeclareTextCommand{\cyrm}{PU}{\84\074}% U+043C
17071 % U+043D CYRILLIC SMALL LETTER EN; *afii10079, encyirillic
17072 \DeclareTextCommand{\cyrn}{PU}{\84\075}% U+043D
17073 % U+043E CYRILLIC SMALL LETTER O; *afii10080, ocyrillic
17074 \DeclareTextCommand{\cyro}{PU}{\84\076}% U+043E
17075 % U+043F CYRILLIC SMALL LETTER PE; *afii10081, pecyirillic
17076 \DeclareTextCommand{\cyrp}{PU}{\84\077}% U+043F
17077 % U+0440 CYRILLIC SMALL LETTER ER; *afii10082, ercyirillic
17078 \DeclareTextCommand{\cyrr}{PU}{\84\100}% U+0440
17079 % U+0441 CYRILLIC SMALL LETTER ES; *afii10083, escyirillic
17080 \DeclareTextCommand{\cyrs}{PU}{\84\101}% U+0441
17081 % U+0442 CYRILLIC SMALL LETTER TE; *afii10084, tecyirillic
17082 \DeclareTextCommand{\cyrt}{PU}{\84\102}% U+0442
17083 % U+0443 CYRILLIC SMALL LETTER U; *afii10085, ucyirillic
17084 \DeclareTextCommand{\cyru}{PU}{\84\103}% U+0443
17085 % U+0444 CYRILLIC SMALL LETTER EF; *afii10086, efcyirillic
17086 \DeclareTextCommand{\cyrf}{PU}{\84\104}% U+0444
17087 % U+0445 CYRILLIC SMALL LETTER HA; *afii10087, khacyirillic
17088 \DeclareTextCommand{\cyrh}{PU}{\84\105}% U+0445
17089 % U+0446 CYRILLIC SMALL LETTER TSE; *afii10088, tsecyirillic
17090 \DeclareTextCommand{\cyrc}{PU}{\84\106}% U+0446
17091 % U+0447 CYRILLIC SMALL LETTER CHE; *afii10089, checyirillic
17092 \DeclareTextCommand{\cyrch}{PU}{\84\107}% U+0447
17093 % U+0448 CYRILLIC SMALL LETTER SHA; *afii10090, shacyirillic
17094 \DeclareTextCommand{\cyrsh}{PU}{\84\110}% U+0448
17095 % U+0449 CYRILLIC SMALL LETTER SHCHA; *afii10091, shchacyirillic
17096 \DeclareTextCommand{\cyrshch}{PU}{\84\111}% U+0449
17097 % U+044A CYRILLIC SMALL LETTER HARD SIGN; *afii10092, hardsigncyrillic
17098 \DeclareTextCommand{\cyrhdsn}{PU}{\84\112}% U+044A
17099 %* \cyrhdsn -> \hardsign (tipa)
17100 % U+044B CYRILLIC SMALL LETTER YERU; *afii10093, yericyirillic
17101 \DeclareTextCommand{\cyry}{PU}{\84\113}% U+044B
17102 % U+044C CYRILLIC SMALL LETTER SOFT SIGN; *afii10094, softsigncyirillic
17103 \DeclareTextCommand{\cyrsftsn}{PU}{\84\114}% U+044C
17104 %* \cyrsftsn -> \softsign (tipa)
17105 % U+044D CYRILLIC SMALL LETTER E; *afii10095, ereversedcyirillic
17106 \DeclareTextCommand{\cyrerev}{PU}{\84\115}% U+044D
17107 % U+044E CYRILLIC SMALL LETTER YU; *afii10096, iucyirillic
17108 \DeclareTextCommand{\cyryu}{PU}{\84\116}% U+044E
17109 % U+044F CYRILLIC SMALL LETTER YA; *afii10097, iacyirillic
17110 \DeclareTextCommand{\cyrya}{PU}{\84\117}% U+044F
17111 % U+0450 CYRILLIC SMALL LETTER IE WITH GRAVE
17112 \DeclareTextCompositeCommand{\'}{PU}{\cyre}{\84\120}% U+0450
17113 % U+0451 CYRILLIC SMALL LETTER IO; *afii10071, iocyirillic
17114 \DeclareTextCommand{\cyryo}{PU}{\84\121}% U+0451
17115 \DeclareTextCompositeCommand{\"}{PU}{\cyre}{\84\121}% U+0451
17116 % U+0452 CYRILLIC SMALL LETTER DJE; *afii10099, djecyirillic
17117 \DeclareTextCommand{\cyrdje}{PU}{\84\122}% U+0452
17118 % U+0453 CYRILLIC SMALL LETTER GJE; *afii10100, gjecyirillic
17119 \DeclareTextCompositeCommand{\'}{PU}{\cyrg}{\84\123}% U+0453
17120 % U+0454 CYRILLIC SMALL LETTER UKRAINIAN IE; *afii10101, ecyirillic
17121 \DeclareTextCommand{\cyrie}{PU}{\84\124}% U+0454
17122 % U+0455 CYRILLIC SMALL LETTER DZE; *afii10102, dzecyirillic
17123 \DeclareTextCommand{\cyrdze}{PU}{\84\125}% U+0455
17124 % U+0456 CYRILLIC SMALL LETTER BYELORUSSIAN-UKRAINIAN I;

17125 % *afii10103, icyrillic
17126 \DeclareTextCommand{\cyrii}{PU}{\84\126}% U+0456
17127 % U+0457 CYRILLIC SMALL LETTER YI; *afii10104, yicyrillic
17128 \DeclareTextCommand{\cyryi}{PU}{\84\127}% U+0457
17129 \DeclareTextCompositeCommand{\"}{PU}{\cyrii}{\84\127}% U+0457
17130 % U+0458 CYRILLIC SMALL LETTER JE; *afii10105, jecyrillic
17131 \DeclareTextCommand{\cyrje}{PU}{\84\130}% U+0458
17132 % U+0459 CYRILLIC SMALL LETTER LJE; *afii10106, ljecyrillic
17133 \DeclareTextCommand{\cyrlje}{PU}{\84\131}% U+0459
17134 % U+045A CYRILLIC SMALL LETTER NJE; *afii10107, njecyrillic
17135 \DeclareTextCommand{\cyrnje}{PU}{\84\132}% U+045A
17136 % U+045B CYRILLIC SMALL LETTER TSHE; *afii10108, tshecyrillic
17137 \DeclareTextCommand{\cyrtshe}{PU}{\84\133}% U+045B
17138 % U+045C CYRILLIC SMALL LETTER KJE; *afii10109, kjecyrillic
17139 \DeclareTextCompositeCommand{\'}{PU}{\cyrk}{\84\134}% U+045C
17140 % U+045D CYRILLIC SMALL LETTER I WITH GRAVE
17141 \DeclareTextCompositeCommand{\`}{PU}{\cyri}{\84\135}% U+045D
17142 % U+045E CYRILLIC SMALL LETTER SHORT U; *afii10110, ushortcyrillic
17143 \DeclareTextCommand{\cyrushrt}{PU}{\84\136}% U+045E
17144 \DeclareTextCompositeCommand{\U}{PU}{\curu}{\84\136}% U+045E
17145 % U+045F CYRILLIC SMALL LETTER DZHE; *afii10193, dzhecyrillic
17146 \DeclareTextCommand{\cyrdzhe}{PU}{\84\137}% U+045F
17147 % U+0460 CYRILLIC CAPITAL LETTER OMEGA; Omegacyrillic
17148 \DeclareTextCommand{\CYROMEGA}{PU}{\84\140}% U+0460
17149 % U+0461 CYRILLIC SMALL LETTER OMEGA; omegacyrillic
17150 \DeclareTextCommand{\cyromega}{PU}{\84\141}% U+0461
17151 % U+0462 CYRILLIC CAPITAL LETTER YAT; Yatcyrillic, *afii10146
17152 \DeclareTextCommand{\CYRYAT}{PU}{\84\142}% U+0462
17153 % U+0463 CYRILLIC SMALL LETTER YAT; *afii10194, yatcyrillic
17154 \DeclareTextCommand{\cyryat}{PU}{\84\143}% U+0463
17155 % U+0464 CYRILLIC CAPITAL LETTER IOTIFIED E; Eiotifiedcyrillic
17156 \DeclareTextCommand{\CYRIOTE}{PU}{\84\144}% U+0464
17157 % U+0465 CYRILLIC SMALL LETTER IOTIFIED E; eiotifiedcyrillic
17158 \DeclareTextCommand{\cyriote}{PU}{\84\145}% U+0465
17159 % U+0466 CYRILLIC CAPITAL LETTER LITTLE YUS; Yuslitlecyrillic
17160 \DeclareTextCommand{\CYRLYUS}{PU}{\84\146}% U+0466
17161 % U+0467 CYRILLIC SMALL LETTER LITTLE YUS; yuslitlecyrillic
17162 \DeclareTextCommand{\cyrlyus}{PU}{\84\147}% U+0467
17163 % U+0468 CYRILLIC CAPITAL LETTER IOTIFIED LITTLE YUS; Yuslitlei-
otifiedcyrillic
17164 \DeclareTextCommand{\CYRIOTLYUS}{PU}{\84\150}% U+0468
17165 % U+0469 CYRILLIC SMALL LETTER IOTIFIED LITTLE YUS; yuslitleioti-
fiedcyrillic
17166 \DeclareTextCommand{\cyriotlyus}{PU}{\84\151}% U+0469
17167 % U+046A CYRILLIC CAPITAL LETTER BIG YUS; Yusbigcyrillic
17168 \DeclareTextCommand{\CYRBYUS}{PU}{\84\152}% U+046A
17169 % U+046B CYRILLIC SMALL LETTER BIG YUS; yusbigcyrillic
17170 \DeclareTextCommand{\cyrbyus}{PU}{\84\153}% U+046B
17171 % U+046C CYRILLIC CAPITAL LETTER IOTIFIED BIG YUS; Yusbigiotified-
cyrillic
17172 \DeclareTextCommand{\CYRIOTBYUS}{PU}{\84\154}% U+046C
17173 % U+046D CYRILLIC SMALL LETTER IOTIFIED BIG YUS; yusbigiotified-
cyrillic
17174 \DeclareTextCommand{\cyriotbyus}{PU}{\84\155}% U+046D
17175 % U+046E CYRILLIC CAPITAL LETTER KSI; Ksicyrillic
17176 \DeclareTextCommand{\CYRKSI}{PU}{\84\156}% U+046E
17177 % U+046F CYRILLIC SMALL LETTER KSI; ksicyrillic

17178 \DeclareTextCommand{\cyrksi}{PU}{\84\157}% U+046F
17179 % U+0470 CYRILLIC CAPITAL LETTER PSI; Psicyrillic
17180 \DeclareTextCommand{\CYRPSI}{PU}{\84\160}% U+0470
17181 % U+0471 CYRILLIC SMALL LETTER PSI; psicyrillic
17182 \DeclareTextCommand{\cyrpsi}{PU}{\84\161}% U+0471
17183 % U+0472 CYRILLIC CAPITAL LETTER FITA; Fitacyrillic, *afii10147
17184 \DeclareTextCommand{\CYRFITA}{PU}{\84\162}% U+0472
17185 % U+0473 CYRILLIC SMALL LETTER FITA; *afii10195, fitacyrillic
17186 \DeclareTextCommand{\cyrfita}{PU}{\84\163}% U+0473
17187 % U+0474 CYRILLIC CAPITAL LETTER IZHITSA; Izhitsacyrillic, *afii10148
17188 \DeclareTextCommand{\CYRIZH}{PU}{\84\164}% U+0474
17189 % U+0475 CYRILLIC SMALL LETTER IZHITSA; *afii10196, izhitsacyrillic
17190 \DeclareTextCommand{\cyrizh}{PU}{\84\165}% U+0475
17191 % U+0476 CYRILLIC CAPITAL LETTER IZHITSA WITH DOUBLE
17192 % GRAVE ACCENT; Izhitsadblgravecyrillic
17193 \DeclareTextCompositeCommand{\C}{PU}{\CYRIZH}{\84\166}% U+0476
17194 % U+0477 CYRILLIC SMALL LETTER IZHITSA WITH DOUBLE
17195 % GRAVE ACCENT; izhitsadblgravecyrillic
17196 \DeclareTextCompositeCommand{\C}{PU}{\cyrizh}{\84\167}% U+0477
17197 % U+0478 CYRILLIC CAPITAL LETTER UK; Ukcyrillic
17198 \DeclareTextCommand{\CYRUK}{PU}{\84\170}% U+0478
17199 % U+0479 CYRILLIC SMALL LETTER UK; ukcyrillic
17200 \DeclareTextCommand{\cyruk}{PU}{\84\171}% U+0479
17201 % U+047A CYRILLIC CAPITAL LETTER ROUND OMEGA; Omegaroundcyrillic
17202 \DeclareTextCommand{\CYROMEGARND}{PU}{\84\172}% U+047A
17203 % U+047B CYRILLIC SMALL LETTER ROUND OMEGA; omegaroundcyrillic
17204 \DeclareTextCommand{\cyromegarnd}{PU}{\84\173}% U+047B
17205 % U+047C CYRILLIC CAPITAL LETTER OMEGA WITH TITLO; Omegatitlocyrillic
17206 \DeclareTextCommand{\CYROMEGATITLO}{PU}{\84\174}% U+047C
17207 % U+047D CYRILLIC SMALL LETTER OMEGA WITH TITLO; omegatitlocyrillic
17208 \DeclareTextCommand{\cyromegatitlo}{PU}{\84\175}% U+047D
17209 % U+047E CYRILLIC CAPITAL LETTER OT; Otcyrillic
17210 \DeclareTextCommand{\CYROT}{PU}{\84\176}% U+047E
17211 % U+047F CYRILLIC SMALL LETTER OT; otcyrillic
17212 \DeclareTextCommand{\cyrot}{PU}{\84\177}% U+047F
17213 % U+0480 CYRILLIC CAPITAL LETTER KOPPA; Koppacyrillic
17214 \DeclareTextCommand{\CYRKOPPA}{PU}{\84\200}% U+0480
17215 % U+0481 CYRILLIC SMALL LETTER KOPPA; koppacyrillic
17216 \DeclareTextCommand{\cyrkoppa}{PU}{\84\201}% U+0481
17217 % U+0482 CYRILLIC THOUSANDS SIGN; thousandcyrillic
17218 \DeclareTextCommand{\cyrthousands}{PU}{\84\202}% U+0482
\84\203: U+0483 COMBINING CYRILLIC TITLO; titlocyrilliccmb
\84\204: U+0484 COMBINING CYRILLIC PALATALIZATION; palatalizationcyrilliccmb
\84\205: U+0485 COMBINING CYRILLIC DASIA PNEUMATA; dasiapneumatacyrilliccmb
\84\206: U+0486 COMBINING CYRILLIC PSILI PNEUMATA; psilipneumatacyrilliccmb
\84\207: U+0487 COMBINING CYRILLIC POKRYTIE
\84\210: U+0488 COMBINING CYRILLIC HUNDRED THOUSANDS SIGN
\84\211: U+0489 COMBINING CYRILLIC MILLIONS SIGN
17219 % U+048A CYRILLIC CAPITAL LETTER SHORT I WITH TAIL
17220 \DeclareTextCommand{\CYRISHRTDSC}{PU}{\84\212}% U+048A

17221 % U+048B CYRILLIC SMALL LETTER SHORT I WITH TAIL
 17222 \DeclareTextCommand{\cyrishrtdsc}{PU}{\84\213}% U+048B
 17223 % U+048C CYRILLIC CAPITAL LETTER SEMISOFT SIGN
 17224 \DeclareTextCommand{\CYRSEMISFTSN}{PU}{\84\214}% U+048C
 17225 % U+048D CYRILLIC SMALL LETTER SEMISOFT SIGN
 17226 \DeclareTextCommand{\cyrsemisftsn}{PU}{\84\215}% U+048D
 17227 % U+048E CYRILLIC CAPITAL LETTER ER WITH TICK
 17228 \DeclareTextCommand{\CYRRTICK}{PU}{\84\216}% U+048E
 17229 % U+048F CYRILLIC SMALL LETTER ER WITH TICK
 17230 \DeclareTextCommand{\cyrrtick}{PU}{\84\217}% U+048F
 17231 % U+0490 CYRILLIC CAPITAL LETTER GHE WITH UPTURN; Gheupturn-cyrillic, *afii10050
 17232 \DeclareTextCommand{\CYRGUP}{PU}{\84\220}% U+0490
 17233 % U+0491 CYRILLIC SMALL LETTER GHE WITH UPTURN; *afii10098, gheupturncyrillic
 17234 \DeclareTextCommand{\cyrgup}{PU}{\84\221}% U+0491
 17235 % U+0492 CYRILLIC CAPITAL LETTER GHE WITH STROKE; Ghestroke-cyrillic
 17236 \DeclareTextCommand{\CYRGHCRS}{PU}{\84\222}% U+0492
 17237 % U+0493 CYRILLIC SMALL LETTER GHE WITH STROKE; ghestrokecyrillic
 17238 \DeclareTextCommand{\cyrghcrs}{PU}{\84\223}% U+0493
 17239 % U+0494 CYRILLIC CAPITAL LETTER GHE WITH MIDDLE HOOK;
 17240 % Ghemiddlehookcyrillic
 17241 \DeclareTextCommand{\CYRGHK}{PU}{\84\224}% U+0494
 17242 % U+0495 CYRILLIC SMALL LETTER GHE WITH MIDDLE HOOK;
 17243 % ghemiddlehookcyrillic
 17244 \DeclareTextCommand{\cyrghk}{PU}{\84\225}% U+0495
 17245 % U+0496 CYRILLIC CAPITAL LETTER ZHE WITH DESCENDER;
 17246 % Zhedescendercyrillic
 17247 \DeclareTextCommand{\CYRZHDSC}{PU}{\84\226}% U+0496
 17248 % U+0497 CYRILLIC SMALL LETTER ZHE WITH DESCENDER;
 17249 % zhedescendercyrillic
 17250 \DeclareTextCommand{\cyrzhdsc}{PU}{\84\227}% U+0497
 17251 % U+0498 CYRILLIC CAPITAL LETTER ZE WITH DESCENDER; Zedescendercyrillic
 17252 \DeclareTextCommand{\CYRZDSC}{PU}{\84\230}% U+0498
 17253 \DeclareTextCompositeCommand{\c}{PU}{\CYRZ}{\84\230}% U+0498
 17254 % U+0499 CYRILLIC SMALL LETTER ZE WITH DESCENDER; zedescendercyrillic
 17255 \DeclareTextCommand{\cyrzdsc}{PU}{\84\231}% U+0499
 17256 \DeclareTextCompositeCommand{\c}{PU}{\cyrz}{\84\231}% U+0499
 17257 % U+049A CYRILLIC CAPITAL LETTER KA WITH DESCENDER; Kadescendercyrillic
 17258 \DeclareTextCommand{\CYRKDSC}{PU}{\84\232}% U+049A
 17259 % U+049B CYRILLIC SMALL LETTER KA WITH DESCENDER; kadesendercyrillic
 17260 \DeclareTextCommand{\cyrkdsc}{PU}{\84\233}% U+049B
 17261 % U+049C CYRILLIC CAPITAL LETTER KA WITH VERTICAL STROKE;
 17262 % Kavertikalstrokecyrillic
 17263 \DeclareTextCommand{\CYRKVCRS}{PU}{\84\234}% U+049C
 17264 % U+049D CYRILLIC SMALL LETTER KA WITH VERTICAL STROKE;
 17265 % kavertikalstrokecyrillic
 17266 \DeclareTextCommand{\cyrkvcrs}{PU}{\84\235}% U+049D
 17267 % U+049E CYRILLIC CAPITAL LETTER KA WITH STROKE; Kastrokecyrillic
 17268 \DeclareTextCommand{\CYRKHCRS}{PU}{\84\236}% U+049E
 17269 % U+049F CYRILLIC SMALL LETTER KA WITH STROKE; kastrokecyrillic
 17270 \DeclareTextCommand{\cyrkhcrs}{PU}{\84\237}% U+049F

17271 % U+04A0 CYRILLIC CAPITAL LETTER BASHKIR KA; Kabashkircyrillic
17272 \DeclareTextCommand{\CYRKBEAK}{PU}{\84\240}% U+04A0
17273 % U+04A1 CYRILLIC SMALL LETTER BASHKIR KA; kabashkircyrillic
17274 \DeclareTextCommand{\cyrkbeak}{PU}{\84\241}% U+04A1
17275 % U+04A2 CYRILLIC CAPITAL LETTER EN WITH DESCENDER; Endescen-
dercyrillic
17276 \DeclareTextCommand{\CYRNDSC}{PU}{\84\242}% U+04A2
17277 % U+04A3 CYRILLIC SMALL LETTER EN WITH DESCENDER; endescender-
cyrillic
17278 \DeclareTextCommand{\cyrndsc}{PU}{\84\243}% U+04A3
17279 % U+04A4 CYRILLIC CAPITAL LIGATURE EN GHE; Enghecyrillic
17280 \DeclareTextCommand{\CYRNG}{PU}{\84\244}% U+04A4
17281 % U+04A5 CYRILLIC SMALL LIGATURE EN GHE; enghecyrillic
17282 \DeclareTextCommand{\cyrng}{PU}{\84\245}% U+04A5
17283 % U+04A6 CYRILLIC CAPITAL LETTER PE WITH MIDDLE HOOK; Pemid-
dlehookcyrillic
17284 \DeclareTextCommand{\CYRPHK}{PU}{\84\246}% U+04A6
17285 % U+04A7 CYRILLIC SMALL LETTER PE WITH MIDDLE HOOK; pemiddle-
hookcyrillic
17286 \DeclareTextCommand{\cyrphk}{PU}{\84\247}% U+04A7
17287 % U+04A8 CYRILLIC CAPITAL LETTER ABKHASIAN HA; Haabkhasiancyril-
lic
17288 \DeclareTextCommand{\CYRABHHA}{PU}{\84\250}% U+04A8
17289 % U+04A9 CYRILLIC SMALL LETTER ABKHASIAN HA; haabkhasiancyrillic
17290 \DeclareTextCommand{\cyrabhha}{PU}{\84\251}% U+04A9
17291 % U+04AA CYRILLIC CAPITAL LETTER ES WITH DESCENDER; Esdescen-
dercyrillic
17292 \DeclareTextCommand{\CYRSDSC}{PU}{\84\252}% U+04AA
17293 \DeclareTextCompositeCommand{\CYRSDSC}{PU}{\CYRS}{\84\252}% U+04AA
17294 % U+04AB CYRILLIC SMALL LETTER ES WITH DESCENDER; esdescender-
cyrillic
17295 \DeclareTextCommand{\cyrsdsc}{PU}{\84\253}% U+04AB
17296 \DeclareTextCompositeCommand{\k}{PU}{\cyrs}{\84\253}% U+04AB
17297 % U+04AC CYRILLIC CAPITAL LETTER TE WITH DESCENDER; Tedescen-
dercyrillic
17298 \DeclareTextCommand{\CYRTDSC}{PU}{\84\254}% U+04AC
17299 % U+04AD CYRILLIC SMALL LETTER TE WITH DESCENDER; tedescen-
dercyrillic
17300 \DeclareTextCommand{\cyrtddsc}{PU}{\84\255}% U+04AD
17301 % U+04AE CYRILLIC CAPITAL LETTER STRAIGHT U; Ustraightcyrillic
17302 \DeclareTextCommand{\CYRY}{PU}{\84\256}% U+04AE
17303 % U+04AF CYRILLIC SMALL LETTER STRAIGHT U; ustraightcyrillic
17304 \DeclareTextCommand{\cyry}{PU}{\84\257}% U+04AF
17305 % U+04B0 CYRILLIC CAPITAL LETTER STRAIGHT U WITH STROKE; Us-
traightstrokecyrillic
17306 \DeclareTextCommand{\CYRYHCRS}{PU}{\84\260}% U+04B0
17307 % U+04B1 CYRILLIC SMALL LETTER STRAIGHT U WITH STROKE; us-
traightstrokecyrillic
17308 \DeclareTextCommand{\cyryhcrs}{PU}{\84\261}% U+04B1
17309 % U+04B2 CYRILLIC CAPITAL LETTER HA WITH DESCENDER; Hadescen-
dercyrillic
17310 \DeclareTextCommand{\CYRHDSC}{PU}{\84\262}% U+04B2
17311 % U+04B3 CYRILLIC SMALL LETTER HA WITH DESCENDER; hadescen-
dercyrillic
17312 \DeclareTextCommand{\cyrhdsc}{PU}{\84\263}% U+04B3
17313 % U+04B4 CYRILLIC CAPITAL LIGATURE TE TSE; Tetsecyrillic
17314 \DeclareTextCommand{\CYRTETSE}{PU}{\84\264}% U+04B4

17315 % U+04B5 CYRILLIC SMALL LIGATURE TE TSE; tetsecyrillic
17316 \DeclareTextCommand{\cyrtetse}{PU}{\84\265}% U+04B5
17317 % U+04B6 CYRILLIC CAPITAL LETTER CHE WITH DESCENDER;
17318 % Chedescendercyrillic
17319 \DeclareTextCommand{\CYRCHRDSC}{PU}{\84\266}% U+04B6
17320 % U+04B7 CYRILLIC SMALL LETTER CHE WITH DESCENDER; chedescen-
dercyrillic
17321 \DeclareTextCommand{\cyrchrdsc}{PU}{\84\267}% U+04B7
17322 % U+04B8 CYRILLIC CAPITAL LETTER CHE WITH VERTICAL STROKE;
17323 % Cheverticalstrokecyrillic
17324 \DeclareTextCommand{\CYRCHVCRS}{PU}{\84\270}% U+04B8
17325 % U+04B9 CYRILLIC SMALL LETTER CHE WITH VERTICAL STROKE;
17326 % cheverticalstrokecyrillic
17327 \DeclareTextCommand{\cyrchvcrs}{PU}{\84\271}% U+04B9
17328 % U+04BA CYRILLIC CAPITAL LETTER SHHA; Shhacyrillic
17329 \DeclareTextCommand{\CYRSHHA}{PU}{\84\272}% U+04BA
17330 % U+04BB CYRILLIC SMALL LETTER SHHA; shhacyrillic
17331 \DeclareTextCommand{\cyrshha}{PU}{\84\273}% U+04BB
17332 % U+04BC CYRILLIC CAPITAL LETTER ABKHASIAN CHE; Cheabkhasian-
cyrillic
17333 \DeclareTextCommand{\CYRABHCH}{PU}{\84\274}% U+04BC
17334 % U+04BD CYRILLIC SMALL LETTER ABKHASIAN CHE; cheabkhasiancyril-
lic
17335 \DeclareTextCommand{\cyrabhch}{PU}{\84\275}% U+04BD
17336 % U+04BE CYRILLIC CAPITAL LETTER ABKHASIAN CHE WITH DESCEN-
DER; Chedescenderabkhasiancyrillic
17337 \DeclareTextCommand{\CYRABHCHDSC}{PU}{\84\276}% U+04BE
17338 \DeclareTextCompositeCommand{\k}{PU}{\CYRABHCH}{\84\276}% U+04BE
17339 % U+04BF CYRILLIC SMALL LETTER ABKHASIAN CHE WITH DESCEN-
DER; chedescenderabkhasiancyrillic
17340 \DeclareTextCommand{\cyrabhchdsc}{PU}{\84\277}% U+04BF
17341 \DeclareTextCompositeCommand{\k}{PU}{\cyrabhch}{\84\277}% U+04BF
17342 % U+04C0 CYRILLIC LETTER PALOCHKA; palochkacyrillic
17343 \DeclareTextCommand{\CYRpalochka}{PU}{\84\300}% U+04C0
17344 % U+04C1 CYRILLIC CAPITAL LETTER ZHE WITH BREVE; Zhebrevecyrillic
17345 \DeclareTextCompositeCommand{\U}{PU}{\CYRZH}{\84\301}% U+04C1
17346 % U+04C2 CYRILLIC SMALL LETTER ZHE WITH BREVE; zhebrevecyrillic
17347 \DeclareTextCompositeCommand{\U}{PU}{\cyrzh}{\84\302}% U+04C2
17348 % U+04C3 CYRILLIC CAPITAL LETTER KA WITH HOOK; Kahookcyrillic
17349 \DeclareTextCommand{\CYRKHK}{PU}{\84\303}% U+04C3
17350 % U+04C4 CYRILLIC SMALL LETTER KA WITH HOOK; kahookcyrillic
17351 \DeclareTextCommand{\cyrkhk}{PU}{\84\304}% U+04C4
17352 % U+04C5 CYRILLIC CAPITAL LETTER EL WITH TAIL
17353 \DeclareTextCommand{\CYRLDSC}{PU}{\84\305}% U+04C5
17354 % U+04C6 CYRILLIC SMALL LETTER EL WITH TAIL
17355 \DeclareTextCommand{\cyrldsc}{PU}{\84\306}% U+04C6
17356 % U+04C7 CYRILLIC CAPITAL LETTER EN WITH HOOK; Enhookcyrillic
17357 \DeclareTextCommand{\CYRNHK}{PU}{\84\307}% U+04C7
17358 % U+04C8 CYRILLIC SMALL LETTER EN WITH HOOK; enhookcyrillic
17359 \DeclareTextCommand{\cyrnhk}{PU}{\84\310}% U+04C8
17360 % U+04CB CYRILLIC CAPITAL LETTER KHAKASSIAN CHE; Chekhakas-
siancyrillic
17361 \DeclareTextCommand{\CYRCHLDSC}{PU}{\84\313}% U+04CB
17362 % U+04CC CYRILLIC SMALL LETTER KHAKASSIAN CHE; chekhakassian-
cyrillic
17363 \DeclareTextCommand{\cyrchldsc}{PU}{\84\314}% U+04CC
17364 % U+04CD CYRILLIC CAPITAL LETTER EM WITH TAIL

17365 \DeclareTextCommand{\CYRMDSC}{PU}{\84\315}% U+04CD
17366 % U+04CE CYRILLIC SMALL LETTER EM WITH TAIL
17367 \DeclareTextCommand{\cyrmdsc}{PU}{\84\316}% U+04CE
\84\317: U+04CF CYRILLIC SMALL LETTER PALOCHKA
17368 % U+04D0 CYRILLIC CAPITAL LETTER A WITH BREVE; Abrevecyrillic
17369 \DeclareTextCompositeCommand{\U}{PU}{\CYRA}{\84\320}% U+04D0
17370 % U+04D1 CYRILLIC SMALL LETTER A WITH BREVE; abrevecyrillic
17371 \DeclareTextCompositeCommand{\U}{PU}{\cyra}{\84\321}% U+04D1
17372 % U+04D2 CYRILLIC CAPITAL LETTER A WITH DIAERESIS; Adieresiscyril-
lic
17373 \DeclareTextCompositeCommand{\"}{PU}{\CYRA}{\84\322}% U+04D2
17374 % U+04D3 CYRILLIC SMALL LETTER A WITH DIAERESIS; adieresiscyrillic
17375 \DeclareTextCompositeCommand{\"}{PU}{\cyra}{\84\323}% U+04D3
17376 % U+04D4 CYRILLIC CAPITAL LIGATURE A IE; Aiecyrillic
17377 \DeclareTextCommand{\CYRAE}{PU}{\84\324}% U+04D4
17378 % U+04D5 CYRILLIC SMALL LIGATURE A IE; aiecyrillic
17379 \DeclareTextCommand{\\cyrae}{PU}{\84\325}% U+04D5
17380 % U+04D6 CYRILLIC CAPITAL LETTER IE WITH BREVE; Iebrevocyrillic
17381 \DeclareTextCompositeCommand{\U}{PU}{\CYRE}{\84\326}% U+04D6
17382 % U+04D7 CYRILLIC SMALL LETTER IE WITH BREVE; iebrevocyrillic
17383 \DeclareTextCompositeCommand{\U}{PU}{\cyre}{\84\327}% U+04D7
17384 % U+04D8 CYRILLIC CAPITAL LETTER SCHWA; Schwacyrillic
17385 \DeclareTextCommand{\CYRSCHWA}{PU}{\84\330}% U+04D8
17386 % U+04D9 CYRILLIC SMALL LETTER SCHWA; *afii10846, schwacyrillic
17387 \DeclareTextCommand{\\cyrschwa}{PU}{\84\331}% U+04D9
17388 % U+04DA CYRILLIC CAPITAL LETTER SCHWA WITH DIAERESIS;
17389 % Schwadieresiscyrillic
17390 \DeclareTextCompositeCommand{\"}{PU}{\CYRSCHWA}{\84\332}% U+04DA
17391 % U+04DB CYRILLIC SMALL LETTER SCHWA WITH DIAERESIS;
17392 % schwadieresiscyrillic
17393 \DeclareTextCompositeCommand{\"}{PU}{\cyrschwa}{\84\333}% U+04DB
17394 % U+04DC CYRILLIC CAPITAL LETTER ZHE WITH DIAERESIS; Zhediere-
siscyrillic
17395 \DeclareTextCompositeCommand{\"}{PU}{\CYRZH}{\84\334}% U+04DC
17396 % U+04DD CYRILLIC SMALL LETTER ZHE WITH DIAERESIS; zhedieresis-
cyrillic
17397 \DeclareTextCompositeCommand{\"}{PU}{\cyrz}{\84\335}% U+04DD
17398 % U+04DE CYRILLIC CAPITAL LETTER ZE WITH DIAERESIS; Zedieresis-
cyrillic
17399 \DeclareTextCompositeCommand{\"}{PU}{\CYRZ}{\84\336}% U+04DE
17400 % U+04DF CYRILLIC SMALL LETTER ZE WITH DIAERESIS; zedieresiscyril-
lic
17401 \DeclareTextCompositeCommand{\"}{PU}{\cyrz}{\84\337}% U+04DF
17402 % U+04E0 CYRILLIC CAPITAL LETTER ABKHASIAN DZE; Dzeabkhasian-
cyrillic
17403 \DeclareTextCommand{\CYRABHDZE}{PU}{\84\340}% U+04E0
17404 % U+04E1 CYRILLIC SMALL LETTER ABKHASIAN DZE; dzeabkhasiancyril-
lic
17405 \DeclareTextCommand{\\cyrabhdze}{PU}{\84\341}% U+04E1
17406 % U+04E2 CYRILLIC CAPITAL LETTER I WITH MACRON; Imacroncyrillic
17407 \DeclareTextCompositeCommand{\=}{PU}{\CYRI}{\84\342}% U+04E2
17408 % U+04E3 CYRILLIC SMALL LETTER I WITH MACRON; imacroncyrillic
17409 \DeclareTextCompositeCommand{\=}{PU}{\cyri}{\84\343}% U+04E3
17410 % U+04E4 CYRILLIC CAPITAL LETTER I WITH DIAERESIS; Idieresiscyrillic
17411 \DeclareTextCompositeCommand{\"}{PU}{\CYRI}{\84\344}% U+04E4
17412 % U+04E5 CYRILLIC SMALL LETTER I WITH DIAERESIS; idieresiscyrillic
17413 \DeclareTextCompositeCommand{\"}{PU}{\cyri}{\84\345}% U+04E5

17414 % U+04E6 CYRILLIC CAPITAL LETTER O WITH DIAERESIS; Odieresiscyrillic
 17415 \DeclareTextCompositeCommand{"}{PU}{\CYRO}{\84\346}% U+04E6
 17416 % U+04E7 CYRILLIC SMALL LETTER O WITH DIAERESIS; odieresiscyrillic
 17417 \DeclareTextCompositeCommand{"}{PU}{\cyro}{\84\347}% U+04E7
 17418 % U+04E8 CYRILLIC CAPITAL LETTER BARRED O; Obarredcyrillic
 17419 \DeclareTextCommand{\CYROTLD}{PU}{\84\350}% U+04E8
 17420 % U+04E9 CYRILLIC SMALL LETTER BARRED O; obarredcyrillic
 17421 \DeclareTextCommand{\cyrotld}{PU}{\84\351}% U+04E9
 17422 % U+04EA CYRILLIC CAPITAL LETTER BARRED O WITH DIAERESIS;
 17423 % Obarreddieresiscyrillic
 17424 \DeclareTextCompositeCommand{"}{PU}{\CYROTLD}{\84\352}% U+04EA
 17425 % U+04EB CYRILLIC SMALL LETTER BARRED O WITH DIAERESIS;
 17426 % obarreddieresiscyrillic
 17427 \DeclareTextCompositeCommand{"}{PU}{\cyrotld}{\84\353}% U+04EB
 17428 % U+04EC CYRILLIC CAPITAL LETTER E WITH DIAERESIS
 17429 \DeclareTextCompositeCommand{"}{PU}{\CYREREV}{\84\354}% U+04EC
 17430 % U+04ED CYRILLIC SMALL LETTER E WITH DIAERESIS
 17431 \DeclareTextCompositeCommand{"}{PU}{\cyreref}{\84\355}% U+04ED
 17432 % U+04EE CYRILLIC CAPITAL LETTER U WITH MACRON; Umacroncyrillic
 17433 \DeclareTextCompositeCommand{\=}{PU}{\CYRU}{\84\356}% U+04EE
 17434 % U+04EF CYRILLIC SMALL LETTER U WITH MACRON; umacroncyrillic
 17435 \DeclareTextCompositeCommand{\=}{PU}{\cyru}{\84\357}% U+04EF
 17436 % U+04F0 CYRILLIC CAPITAL LETTER U WITH DIAERESIS; Udieresiscyrillic
 17437 \DeclareTextCompositeCommand{"}{PU}{\CYRU}{\84\360}% U+04F0
 17438 % U+04F1 CYRILLIC SMALL LETTER U WITH DIAERESIS; udieresiscyrillic
 17439 \DeclareTextCompositeCommand{"}{PU}{\cyru}{\84\361}% U+04F1
 17440 % U+04F2 CYRILLIC CAPITAL LETTER U WITH DOUBLE ACUTE; Uhungarumlautcyrillic
 17441 \DeclareTextCompositeCommand{\H}{PU}{\CYRU}{\84\362}% U+04F2
 17442 % U+04F3 CYRILLIC SMALL LETTER U WITH DOUBLE ACUTE; uhungarumlautcyrillic
 17443 \DeclareTextCompositeCommand{\H}{PU}{\cyru}{\84\363}% U+04F3
 17444 % U+04F4 CYRILLIC CAPITAL LETTER CHE WITH DIAERESIS; Chedieresiscyrillic
 17445 \DeclareTextCompositeCommand{"}{PU}{\CYRCH}{\84\364}% U+04F4
 17446 % U+04F5 CYRILLIC SMALL LETTER CHE WITH DIAERESIS; chedieresiscyrillic
 17447 \DeclareTextCompositeCommand{"}{PU}{\cyrch}{\84\365}% U+04F5
 17448 % U+04F6 CYRILLIC CAPITAL LETTER GHE WITH DESCENDER
 17449 \DeclareTextCommand{\CYRGDSC}{PU}{\84\366}% U+04F6
 17450 % U+04F7 CYRILLIC SMALL LETTER GHE WITH DESCENDER
 17451 \DeclareTextCommand{\cyrgdsc}{PU}{\84\367}% U+04F7
 17452 % U+04F8 CYRILLIC CAPITAL LETTER YERU WITH DIAERESIS; Yerudieresiscyrillic
 17453 \DeclareTextCompositeCommand{"}{PU}{\CYRERY}{\84\370}% U+04F8
 17454 % U+04F9 CYRILLIC SMALL LETTER YERU WITH DIAERESIS; yerudieresiscyrillic
 17455 \DeclareTextCompositeCommand{"}{PU}{\cyrery}{\84\371}% U+04F9
 \84\372: U+04FA CYRILLIC CAPITAL LETTER GHE WITH STROKE AND HOOK
 \84\373: U+04FB CYRILLIC SMALL LETTER GHE WITH STROKE AND HOOK
 17456 % U+04FC CYRILLIC CAPITAL LETTER HA WITH HOOK
 17457 \DeclareTextCommand{\CYRHHK}{PU}{\84\374}% U+04FC
 17458 % U+04FD CYRILLIC SMALL LETTER HA WITH HOOK

17459 \DeclareTextCommand{\cyrhhk}{PU}{\84\375}% U+04FD
 \84\376: U+04FE CYRILLIC CAPITAL LETTER HA WITH STROKE
 \84\377: U+04FF CYRILLIC SMALL LETTER HA WITH STROKE

51.2.11 Hebrew: U+0590 to U+05FF

Macro names are taken from he8enc.def.

17460 % U+05C3 HEBREW PUNCTUATION SOF PASUQ
 17461 \DeclareTextCommand{\sofpasuq}{PU}{\85\303}% U+05C3
 17462 % U+05D0 HEBREW LETTER ALEF
 17463 \DeclareTextCommand{\hebalet}{PU}{\85\320}% U+05D0
 17464 % U+05D1 HEBREW LETTER BET
 17465 \DeclareTextCommand{\hebbet}{PU}{\85\321}% U+05D1
 17466 % U+05D2 HEBREW LETTER GIMEL
 17467 \DeclareTextCommand{\hebgimel}{PU}{\85\322}% U+05D2
 17468 % U+05D3 HEBREW LETTER DALET
 17469 \DeclareTextCommand{\hebdalet}{PU}{\85\323}% U+05D3
 17470 % U+05D4 HEBREW LETTER HE
 17471 \DeclareTextCommand{\hebhe}{PU}{\85\324}% U+05D4
 17472 % U+05D5 HEBREW LETTER VAV
 17473 \DeclareTextCommand{\hebvav}{PU}{\85\325}% U+05D5
 17474 % U+05D6 HEBREW LETTER ZAYIN
 17475 \DeclareTextCommand{\hebzayin}{PU}{\85\326}% U+05D6
 17476 % U+05D7 HEBREW LETTER HET
 17477 \DeclareTextCommand{\hebbet}{PU}{\85\327}% U+05D7
 17478 % U+05D8 HEBREW LETTER TET
 17479 \DeclareTextCommand{\hebtet}{PU}{\85\330}% U+05D8
 17480 % U+05D9 HEBREW LETTER YOD
 17481 \DeclareTextCommand{\hebyod}{PU}{\85\331}% U+05D9
 17482 % U+05DA HEBREW LETTER FINAL KAF
 17483 \DeclareTextCommand{\hebfinalkaf}{PU}{\85\332}% U+05DA
 17484 % U+05DB HEBREW LETTER KAF
 17485 \DeclareTextCommand{\hebkaf}{PU}{\85\333}% U+05DB
 17486 % U+05DC HEBREW LETTER LAMED
 17487 \DeclareTextCommand{\heblamed}{PU}{\85\334}% U+05DC
 17488 % U+05DD HEBREW LETTER FINAL MEM
 17489 \DeclareTextCommand{\hebfinalmem}{PU}{\85\335}% U+05DD
 17490 % U+05DE HEBREW LETTER MEM
 17491 \DeclareTextCommand{\hebmam}{PU}{\85\336}% U+05DE
 17492 % U+05DF HEBREW LETTER FINAL NUN
 17493 \DeclareTextCommand{\hebfinalnun}{PU}{\85\337}% U+05DF
 17494 % U+05E0 HEBREW LETTER NUN
 17495 \DeclareTextCommand{\hebnun}{PU}{\85\340}% U+05E0
 17496 % U+05E1 HEBREW LETTER SAMEKH
 17497 \DeclareTextCommand{\hebsamekh}{PU}{\85\341}% U+05E1
 17498 % U+05E2 HEBREW LETTER AYIN
 17499 \DeclareTextCommand{\hebayin}{PU}{\85\342}% U+05E2
 17500 % U+05E3 HEBREW LETTER FINAL PE
 17501 \DeclareTextCommand{\hebfinalpe}{PU}{\85\343}% U+05E3
 17502 % U+05E4 HEBREW LETTER PE
 17503 \DeclareTextCommand{\hebpe}{PU}{\85\344}% U+05E4
 17504 % U+05E5 HEBREW LETTER FINAL TSADI
 17505 \DeclareTextCommand{\hebfinaltsadi}{PU}{\85\345}% U+05E5
 17506 % U+05E6 HEBREW LETTER TSADI
 17507 \DeclareTextCommand{\hebtsadi}{PU}{\85\346}% U+05E6
 17508 % U+05E7 HEBREW LETTER QOF
 17509 \DeclareTextCommand{\hebqof}{PU}{\85\347}% U+05E7

17510 % U+05E8 HEBREW LETTER RESH
 17511 \DeclareTextCommand{\hebresh}{PU}{\85\350}% U+05E8
 17512 % U+05E9 HEBREW LETTER SHIN
 17513 \DeclareTextCommand{\hebshin}{PU}{\85\351}% U+05E9
 17514 %* \hebshin -> \hebsin (he8)
 17515 % U+05EA HEBREW LETTER TAV
 17516 \DeclareTextCommand{\hebtav}{PU}{\85\352}% U+05EA
 17517 % U+05F0 HEBREW LIGATURE YIDDISH DOUBLE VAV
 17518 \DeclareTextCommand{\doublevav}{PU}{\85\360}% U+05F0
 17519 % U+05F1 HEBREW LIGATURE YIDDISH VAV YOD
 17520 \DeclareTextCommand{\vavyod}{PU}{\85\361}% U+05F1
 17521 % U+05F2 HEBREW LIGATURE YIDDISH DOUBLE YOD
 17522 \DeclareTextCommand{\doubleyod}{PU}{\85\362}% U+05F2

51.2.12 Thai: U+0E00 to U+0E7F

17523 % U+0E3F THAI CURRENCY SYMBOL BAHT; bahtthai
 17524 \DeclareTextCommand{\textbaht}{PU}{\9016\077}% U+0E3F

51.2.13 Phonetic Extensions: U+1D00 to U+1D7F

17525 % U+1D00 LATIN LETTER SMALL CAPITAL A; \textscA (tipa)
 17526 \DeclareTextCommand{\textscA}{PU}{\9035\000}% U+1D00
 17527 % U+1D05 LATIN LETTER SMALL CAPITAL D; \scd (wsuipa)
 17528 \DeclareTextCommand{\textscd}{PU}{\9035\005}% U+1D05
 17529 % U+1D07 LATIN LETTER SMALL CAPITAL E; \textscE (tipa)
 17530 \DeclareTextCommand{\textscE}{PU}{\9035\007}% U+1D07
 17531 % U+1D0A LATIN LETTER SMALL CAPITAL J; \textscJ (tipa)
 17532 \DeclareTextCommand{\textscJ}{PU}{\9035\012}% U+1D0A
 17533 % U+1D0B LATIN LETTER SMALL CAPITAL K; \textscK (tipx)
 17534 \DeclareTextCommand{\textPUscK}{PU}{\9035\013}% U+1D0B
 17535 %* \textPUscK -> \textscK (tipx)
 17536 % U+1D0D LATIN LETTER SMALL CAPITAL M; \textscM (tipx)
 17537 \DeclareTextCommand{\textPUscM}{PU}{\9035\015}% U+1D0D
 17538 %* \textPUscM -> \textscM (tipx)
 17539 % U+1D18 LATIN LETTER SMALL CAPITAL P; \textscP (tipx)
 17540 \DeclareTextCommand{\textPUscP}{PU}{\9035\030}% U+1D18
 17541 %* \textPUscP -> \textscP (tipx)
 17542 % U+1D19 LATIN LETTER SMALL CAPITAL REVERSED R; \textrevscr (tipx)
 17543 \DeclareTextCommand{\textPUrevscr}{PU}{\9035\031}% U+1D19
 17544 %* \textPUrevscr -> \textrevscr (tipx)
 17545 % U+1D1C LATIN LETTER SMALL CAPITAL U; \textscU (tipa), \scu (wsuipa)
 17546 \DeclareTextCommand{\textscU}{PU}{\9035\034}% U+1D1C
 17547 % U+1D62 LATIN SUBSCRIPT SMALL LETTER I
 17548 \DeclareTextCommand{\textiinferior}{PU}{\9035\142}% U+1D62
 17549 % U+1D63 LATIN SUBSCRIPT SMALL LETTER R
 17550 \DeclareTextCommand{\textrinferior}{PU}{\9035\143}% U+1D63
 17551 % U+1D64 LATIN SUBSCRIPT SMALL LETTER U
 17552 \DeclareTextCommand{\textuinferior}{PU}{\9035\144}% U+1D64
 17553 % U+1D65 LATIN SUBSCRIPT SMALL LETTER V
 17554 \DeclareTextCommand{\textvinferior}{PU}{\9035\145}% U+1D65
 17555 % U+1D66 GREEK SUBSCRIPT SMALL LETTER BETA
 17556 \DeclareTextCommand{\textbetainferior}{PU}{\9035\146}% U+1D66
 17557 % U+1D67 GREEK SUBSCRIPT SMALL LETTER GAMMA
 17558 \DeclareTextCommand{\textgammainferior}{PU}{\9035\147}% U+1D67
 17559 % U+1D68 GREEK SUBSCRIPT SMALL LETTER RHO
 17560 \DeclareTextCommand{\textrhoinferior}{PU}{\9035\150}% U+1D68
 17561 % U+1D69 GREEK SUBSCRIPT SMALL LETTER PHI

17562 \DeclareTextCommand{\textphiinferior}{PU}{\9035\151}%* U+1D69
 17563 % U+1D6A GREEK SUBSCRIPT SMALL LETTER CHI
 17564 \DeclareTextCommand{\textchiinferior}{PU}{\9035\152}%* U+1D6A
 17565 % U+1D7B LATIN SMALL CAPITAL LETTER I WITH STROKE;
 17566 % \barsci (wsuipa)
 17567 \DeclareTextCommand{\textbarsci}{PU}{\9035\173}%* U+1D7B
 17568 % U+1D7D LATIN SMALL LETTER P WITH STROKE; \barp (wsuipa)
 17569 \DeclareTextCommand{\textbarp}{PU}{\9035\175}%* U+1D7D
 17570 % U+1D7E LATIN SMALL CAPITAL LETTER U WITH STROKE;
 17571 % \barscu (wsuipa)
 17572 \DeclareTextCommand{\textbarscu}{PU}{\9035\176}%* U+1D7E

51.2.14 Phonetic Extensions Supplement: U+1D80 to U+1DBF

17573 % U+1D8F LATIN SMALL LETTER A WITH RETROFLEX HOOK; \tex-
 trhooka (tipx)
 17574 \DeclareTextCommand{\textPUrhooka}{PU}{\9035\217}% U+1D8F
 17575 %* \textPUrhooka -> \textrhooka (tipx)
 17576 % U+1D91 LATIN SMALL LETTER D WITH HOOK AND TAIL; \texthtr-
 taild (tipa)
 17577 \DeclareTextCommand{\texthtrtaild}{PU}{\9035\221}%* U+1D91
 17578 % U+1D92 LATIN SMALL LETTER E WITH RETROFLEX HOOK; \tex-
 trhooke (tipx)
 17579 \DeclareTextCommand{\textPUrhooke}{PU}{\9035\222}% U+1D92
 17580 %* \textPUrhooke -> \textrhooke (tipx)
 17581 % U+1D93 LATIN SMALL LETTER OPEN E WITH RETROFLEX HOOK;
 17582 % \textrhookepsilon (tipx)
 17583 \DeclareTextCommand{\textPUrhookepsilon}{PU}{\9035\223}% U+1D93
 17584 %* \textPUrhookepsilon -> \textrhookepsilon (tipx)
 17585 % U+1D97 LATIN SMALL LETTER OPEN O WITH RETROFLEX HOOK;
 17586 % \textrhookopeno (tipx)
 17587 \DeclareTextCommand{\textPUrhookopeno}{PU}{\9035\227}% U+1D97
 17588 %* \textPUrhookopeno -> \textrhookopeno (tipx)

51.2.15 Latin Extended Additional: U+1E00 to U+1EFF

17589 % U+1E00 LATIN CAPITAL LETTER A WITH RING BELOW; Aringbelow
 17590 \DeclareTextCompositeCommand{\textsubring}{PU}{A}{\9036\000}% U+1E00
 17591 % U+1E01 LATIN SMALL LETTER A WITH RING BELOW; aringbelow
 17592 \DeclareTextCompositeCommand{\textsubring}{PU}{a}{\9036\001}% U+1E01
 17593 % U+1E02 LATIN CAPITAL LETTER B WITH DOT ABOVE; Bdotaccent
 17594 \DeclareTextCompositeCommand{\.}{PU}{B}{\9036\002}% U+1E02
 17595 % U+1E03 LATIN SMALL LETTER B WITH DOT ABOVE; bdotaccent
 17596 \DeclareTextCompositeCommand{\.}{PU}{b}{\9036\003}% U+1E03
 17597 % U+1E04 LATIN CAPITAL LETTER B WITH DOT BELOW; Bdotbelow
 17598 \DeclareTextCompositeCommand{\d}{PU}{B}{\9036\004}% U+1E04
 17599 % U+1E05 LATIN SMALL LETTER B WITH DOT BELOW; bdotbelow
 17600 \DeclareTextCompositeCommand{\d}{PU}{b}{\9036\005}% U+1E05
 17601 % U+1E06 LATIN CAPITAL LETTER B WITH LINE BELOW; Blinebelow
 17602 \DeclareTextCompositeCommand{\b}{PU}{B}{\9036\006}% U+1E06
 17603 % U+1E07 LATIN SMALL LETTER B WITH LINE BELOW; blinebelow
 17604 \DeclareTextCompositeCommand{\b}{PU}{b}{\9036\007}% U+1E07
 17605 % U+1E0A LATIN CAPITAL LETTER D WITH DOT ABOVE; Ddotaccent
 17606 \DeclareTextCompositeCommand{\.}{PU}{D}{\9036\012}% U+1E0A
 17607 % U+1E0B LATIN SMALL LETTER D WITH DOT ABOVE; ddotaccent
 17608 \DeclareTextCompositeCommand{\.}{PU}{d}{\9036\013}% U+1E0B
 17609 % U+1E0C LATIN CAPITAL LETTER D WITH DOT BELOW; Ddotbelow
 17610 \DeclareTextCompositeCommand{\d}{PU}{D}{\9036\014}% U+1E0C
 17611 % U+1E0D LATIN SMALL LETTER D WITH DOT BELOW; ddotbelow

17612 \DeclareTextCompositeCommand{\d}{PU}{d}{\9036\015}% U+1E0D
17613 % U+1E0E LATIN CAPITAL LETTER D WITH LINE BELOW; Dlinebelow
17614 \DeclareTextCompositeCommand{\b}{PU}{D}{\9036\016}% U+1E0E
17615 % U+1E0F LATIN SMALL LETTER D WITH LINE BELOW; dlinebelow
17616 \DeclareTextCompositeCommand{\b}{PU}{d}{\9036\017}% U+1E0F
17617 % U+1E10 LATIN CAPITAL LETTER D WITH CEDILLA; Dcedilla
17618 \DeclareTextCompositeCommand{\c}{PU}{D}{\9036\020}% U+1E10
17619 % U+1E11 LATIN SMALL LETTER D WITH CEDILLA; dcedilla
17620 \DeclareTextCompositeCommand{\c}{PU}{d}{\9036\021}% U+1E11
17621 % U+1E12 LATIN CAPITAL LETTER D WITH CIRCUMFLEX BELOW; Dcir-
cumflexbelow
17622 \DeclareTextCompositeCommand{\textsubcircum}{PU}{D}{\9036\022}% U+1E12
17623 % U+1E13 LATIN SMALL LETTER D WITH CIRCUMFLEX BELOW; dcir-
cumflexbelow
17624 \DeclareTextCompositeCommand{\textsubcircum}{PU}{d}{\9036\023}% U+1E13
17625 % U+1E14 LATIN CAPITAL LETTER E WITH MACRON AND GRAVE;
17626 % Emacrongrave
17627 \DeclareTextCompositeCommand{\textgravemacron}{PU}{E}{\9036\024}% U+1E14
17628 % U+1E15 LATIN SMALL LETTER E WITH MACRON AND GRAVE;
17629 % emacrongrave
17630 \DeclareTextCompositeCommand{\textgravemacron}{PU}{e}{\9036\025}% U+1E15
17631 % U+1E16 LATIN CAPITAL LETTER E WITH MACRON AND ACUTE;
17632 % Emacronacute
17633 \DeclareTextCompositeCommand{\textacutemacron}{PU}{E}{\9036\026}% U+1E16
17634 % U+1E17 LATIN SMALL LETTER E WITH MACRON AND ACUTE;
17635 % emacronacute
17636 \DeclareTextCompositeCommand{\textacutemacron}{PU}{e}{\9036\027}% U+1E17
17637 % U+1E18 LATIN CAPITAL LETTER E WITH CIRCUMFLEX BELOW; Ecir-
cumflexbelow
17638 \DeclareTextCompositeCommand{\textsubcircum}{PU}{E}{\9036\030}% U+1E18
17639 % U+1E19 LATIN SMALL LETTER E WITH CIRCUMFLEX BELOW; ecir-
cumflexbelow
17640 \DeclareTextCompositeCommand{\textsubcircum}{PU}{e}{\9036\031}% U+1E19
17641 % U+1E1A LATIN CAPITAL LETTER E WITH TILDE BELOW; Etildebelow
17642 \DeclareTextCompositeCommand{\textsubtilde}{PU}{E}{\9036\032}% U+1E1A
17643 % U+1E1B LATIN SMALL LETTER E WITH TILDE BELOW; etildebelow
17644 \DeclareTextCompositeCommand{\textsubtilde}{PU}{e}{\9036\033}% U+1E1B
17645 % U+1E1E LATIN CAPITAL LETTER F WITH DOT ABOVE; Fdotaccent
17646 \DeclareTextCompositeCommand{\.}{PU}{F}{\9036\036}% U+1E1E
17647 % U+1E1F LATIN SMALL LETTER F WITH DOT ABOVE; fdotaccent
17648 \DeclareTextCompositeCommand{\.}{PU}{f}{\9036\037}% U+1E1F
17649 % U+1E20 LATIN CAPITAL LETTER G WITH MACRON; Gmacron
17650 \DeclareTextCompositeCommand{\=}{PU}{G}{\9036\040}% U+1E20
17651 % U+1E21 LATIN SMALL LETTER G WITH MACRON; gmacron
17652 \DeclareTextCompositeCommand{\=}{PU}{g}{\9036\041}% U+1E21
17653 % U+1E22 LATIN CAPITAL LETTER H WITH DOT ABOVE; Hdotaccent
17654 \DeclareTextCompositeCommand{\.}{PU}{H}{\9036\042}% U+1E22
17655 % U+1E23 LATIN SMALL LETTER H WITH DOT ABOVE; hdotaccent
17656 \DeclareTextCompositeCommand{\.}{PU}{h}{\9036\043}% U+1E23
17657 % U+1E24 LATIN CAPITAL LETTER H WITH DOT BELOW; Hdotbelow
17658 \DeclareTextCompositeCommand{\d}{PU}{H}{\9036\044}% U+1E24
17659 % U+1E25 LATIN SMALL LETTER H WITH DOT BELOW; hdotbelow
17660 \DeclareTextCompositeCommand{\d}{PU}{h}{\9036\045}% U+1E25
17661 % U+1E26 LATIN CAPITAL LETTER H WITH DIAERESIS; Hdieresis
17662 \DeclareTextCompositeCommand{\"}{PU}{H}{\9036\046}% U+1E26
17663 % U+1E27 LATIN SMALL LETTER H WITH DIAERESIS; hdieresis
17664 \DeclareTextCompositeCommand{\"}{PU}{h}{\9036\047}% U+1E27

17665 % U+1E28 LATIN CAPITAL LETTER H WITH CEDILLA; Hcedilla
17666 \DeclareTextCompositeCommand{\c}{PU}{H}{\9036\050}% U+1E28
17667 % U+1E29 LATIN SMALL LETTER H WITH CEDILLA; hcedilla
17668 \DeclareTextCompositeCommand{\c}{PU}{h}{\9036\051}% U+1E29
17669 % U+1E2A LATIN CAPITAL LETTER H WITH BREVE BELOW; Hbrevebelow
17670 \DeclareTextCompositeCommand{\textsubbreve}{PU}{H}{\9036\052}% U+1E2A
17671 % U+1E2B LATIN SMALL LETTER H WITH BREVE BELOW; hbrevebelow
17672 \DeclareTextCompositeCommand{\textsubbreve}{PU}{h}{\9036\053}% U+1E2B
17673 % U+1E2C LATIN CAPITAL LETTER I WITH TILDE BELOW; Itildebelow
17674 \DeclareTextCompositeCommand{\textsubtilde}{PU}{I}{\9036\054}% U+1E2C
17675 % U+1E2D LATIN SMALL LETTER I WITH TILDE BELOW; itildebelow
17676 \DeclareTextCompositeCommand{\textsubtilde}{PU}{i}{\9036\055}% U+1E2D
17677 % U+1E30 LATIN CAPITAL LETTER K WITH ACUTE; Kacute
17678 \DeclareTextCompositeCommand{\'}{PU}{K}{\9036\060}% U+1E30
17679 % U+1E31 LATIN SMALL LETTER K WITH ACUTE; kacute
17680 \DeclareTextCompositeCommand{\'}{PU}{k}{\9036\061}% U+1E31
17681 % U+1E32 LATIN CAPITAL LETTER K WITH DOT BELOW; Kdotbelow
17682 \DeclareTextCompositeCommand{\d}{PU}{K}{\9036\062}% U+1E32
17683 % U+1E33 LATIN SMALL LETTER K WITH DOT BELOW; kdotbelow
17684 \DeclareTextCompositeCommand{\d}{PU}{k}{\9036\063}% U+1E33
17685 % U+1E34 LATIN CAPITAL LETTER K WITH LINE BELOW; Klinebelow
17686 \DeclareTextCompositeCommand{\b}{PU}{K}{\9036\064}% U+1E34
17687 % U+1E35 LATIN SMALL LETTER K WITH LINE BELOW; klinebelow
17688 \DeclareTextCompositeCommand{\b}{PU}{k}{\9036\065}% U+1E35
17689 % U+1E36 LATIN CAPITAL LETTER L WITH DOT BELOW; Ldotbelow
17690 \DeclareTextCompositeCommand{\d}{PU}{L}{\9036\066}% U+1E36
17691 % U+1E37 LATIN SMALL LETTER L WITH DOT BELOW; ldotbelow
17692 \DeclareTextCompositeCommand{\d}{PU}{l}{\9036\067}% U+1E37
17693 % U+1E3A LATIN CAPITAL LETTER L WITH LINE BELOW; Llinebelow
17694 \DeclareTextCompositeCommand{\b}{PU}{L}{\9036\072}% U+1E3A
17695 % U+1E3B LATIN SMALL LETTER L WITH LINE BELOW; llinebelow
17696 \DeclareTextCompositeCommand{\b}{PU}{l}{\9036\073}% U+1E3B
17697 % U+1E3C LATIN CAPITAL LETTER L WITH CIRCUMFLEX BELOW; Lcir-
cumflexbelow
17698 \DeclareTextCompositeCommand{\textsubcircum}{PU}{L}{\9036\074}% U+1E3C
17699 % U+1E3D LATIN SMALL LETTER L WITH CIRCUMFLEX BELOW; lcir-
cumflexbelow
17700 \DeclareTextCompositeCommand{\textsubcircum}{PU}{l}{\9036\075}% U+1E3D
17701 % U+1E3E LATIN CAPITAL LETTER M WITH ACUTE; Macute
17702 \DeclareTextCompositeCommand{\'}{PU}{M}{\9036\076}% U+1E3E
17703 % U+1E3F LATIN SMALL LETTER M WITH ACUTE; macute
17704 \DeclareTextCompositeCommand{\'}{PU}{m}{\9036\077}% U+1E3F
17705 % U+1E40 LATIN CAPITAL LETTER M WITH DOT ABOVE; Mdotaccent
17706 \DeclareTextCompositeCommand{\.}{PU}{M}{\9036\100}% U+1E40
17707 % U+1E41 LATIN SMALL LETTER M WITH DOT ABOVE; mdotaccent
17708 \DeclareTextCompositeCommand{\.}{PU}{m}{\9036\101}% U+1E41
17709 % U+1E42 LATIN CAPITAL LETTER M WITH DOT BELOW; Mdotbelow
17710 \DeclareTextCompositeCommand{\d}{PU}{M}{\9036\102}% U+1E42
17711 % U+1E43 LATIN SMALL LETTER M WITH DOT BELOW; mdotbelow
17712 \DeclareTextCompositeCommand{\d}{PU}{m}{\9036\103}% U+1E43
17713 % U+1E44 LATIN CAPITAL LETTER N WITH DOT ABOVE; Ndotaccent
17714 \DeclareTextCompositeCommand{\.}{PU}{N}{\9036\104}% U+1E44
17715 % U+1E45 LATIN SMALL LETTER N WITH DOT ABOVE; ndotaccent
17716 \DeclareTextCompositeCommand{\.}{PU}{n}{\9036\105}% U+1E45
17717 % U+1E46 LATIN CAPITAL LETTER N WITH DOT BELOW; Ndotbelow
17718 \DeclareTextCompositeCommand{\d}{PU}{N}{\9036\106}% U+1E46
17719 % U+1E47 LATIN SMALL LETTER N WITH DOT BELOW; ndotbelow

17720 \DeclareTextCompositeCommand{\d}{PU}{n}{\9036\107}% U+1E47
17721 % U+1E48 LATIN CAPITAL LETTER N WITH LINE BELOW; Nlinebelow
17722 \DeclareTextCompositeCommand{\b}{PU}{N}{\9036\110}% U+1E48
17723 % U+1E49 LATIN SMALL LETTER N WITH LINE BELOW; nlinebelow
17724 \DeclareTextCompositeCommand{\b}{PU}{n}{\9036\111}% U+1E49
17725 % U+1E4A LATIN CAPITAL LETTER N WITH CIRCUMFLEX BELOW; Ncir-
cumflexbelow
17726 \DeclareTextCompositeCommand{\textsubcircum}{PU}{N}{\9036\112}% U+1E4A
17727 % U+1E4B LATIN SMALL LETTER N WITH CIRCUMFLEX BELOW; ncir-
cumflexbelow
17728 \DeclareTextCompositeCommand{\textsubcircum}{PU}{n}{\9036\113}% U+1E4B
17729 % U+1E50 LATIN CAPITAL LETTER O WITH MACRON AND GRAVE;
17730 % Omacrongrave
17731 \DeclareTextCompositeCommand{\textgravemacron}{PU}{O}{\9036\120}% U+1E50
17732 % U+1E51 LATIN SMALL LETTER O WITH MACRON AND GRAVE;
17733 % omacrongrave
17734 \DeclareTextCompositeCommand{\textgravemacron}{PU}{o}{\9036\121}% U+1E51
17735 % U+1E52 LATIN CAPITAL LETTER O WITH MACRON AND ACUTE;
17736 % Omacronacute
17737 \DeclareTextCompositeCommand{\textacutemacron}{PU}{O}{\9036\122}% U+1E52
17738 % U+1E53 LATIN SMALL LETTER O WITH MACRON AND ACUTE;
17739 % omacronacute
17740 \DeclareTextCompositeCommand{\textacutemacron}{PU}{o}{\9036\123}% U+1E53
17741 % U+1E54 LATIN CAPITAL LETTER P WITH ACUTE; Pacute
17742 \DeclareTextCompositeCommand{\'}{PU}{P}{\9036\124}% U+1E54
17743 % U+1E55 LATIN SMALL LETTER P WITH ACUTE; pacute
17744 \DeclareTextCompositeCommand{\'}{PU}{p}{\9036\125}% U+1E55
17745 % U+1E56 LATIN CAPITAL LETTER P WITH DOT ABOVE; Pdotaccent
17746 \DeclareTextCompositeCommand{\.}{PU}{P}{\9036\126}% U+1E56
17747 % U+1E57 LATIN SMALL LETTER P WITH DOT ABOVE; pdotaccent
17748 \DeclareTextCompositeCommand{\.}{PU}{p}{\9036\127}% U+1E57
17749 % U+1E58 LATIN CAPITAL LETTER R WITH DOT ABOVE; Rdotaccent
17750 \DeclareTextCompositeCommand{\.}{PU}{R}{\9036\130}% U+1E58
17751 % U+1E59 LATIN SMALL LETTER R WITH DOT ABOVE; rdotaccent
17752 \DeclareTextCompositeCommand{\.}{PU}{r}{\9036\131}% U+1E59
17753 % U+1E5A LATIN CAPITAL LETTER R WITH DOT BELOW; Rdotbelow
17754 \DeclareTextCompositeCommand{\d}{PU}{R}{\9036\132}% U+1E5A
17755 % U+1E5B LATIN SMALL LETTER R WITH DOT BELOW; rdotbelow
17756 \DeclareTextCompositeCommand{\d}{PU}{r}{\9036\133}% U+1E5B
17757 % U+1E5E LATIN CAPITAL LETTER R WITH LINE BELOW; Rlinebelow
17758 \DeclareTextCompositeCommand{\b}{PU}{R}{\9036\136}% U+1E5E
17759 % U+1E5F LATIN SMALL LETTER R WITH LINE BELOW; rlinebelow
17760 \DeclareTextCompositeCommand{\b}{PU}{r}{\9036\137}% U+1E5F
17761 % U+1E60 LATIN CAPITAL LETTER S WITH DOT ABOVE; Sdotaccent
17762 \DeclareTextCompositeCommand{\.}{PU}{S}{\9036\140}% U+1E60
17763 % U+1E61 LATIN SMALL LETTER S WITH DOT ABOVE; sdotaccent
17764 \DeclareTextCompositeCommand{\.}{PU}{s}{\9036\141}% U+1E61
17765 % U+1E62 LATIN CAPITAL LETTER S WITH DOT BELOW; Sdotbelow
17766 \DeclareTextCompositeCommand{\d}{PU}{S}{\9036\142}% U+1E62
17767 % U+1E63 LATIN SMALL LETTER S WITH DOT BELOW; sdotbelow
17768 \DeclareTextCompositeCommand{\d}{PU}{s}{\9036\143}% U+1E63
17769 % U+1E6A LATIN CAPITAL LETTER T WITH DOT ABOVE; Tdotaccent
17770 \DeclareTextCompositeCommand{\.}{PU}{T}{\9036\152}% U+1E6A
17771 % U+1E6B LATIN SMALL LETTER T WITH DOT ABOVE; tdotaccent
17772 \DeclareTextCompositeCommand{\.}{PU}{t}{\9036\153}% U+1E6B
17773 % U+1E6C LATIN CAPITAL LETTER T WITH DOT BELOW; Tdotbelow
17774 \DeclareTextCompositeCommand{\d}{PU}{T}{\9036\154}% U+1E6C

17775 % U+1E6D LATIN SMALL LETTER T WITH DOT BELOW; tdotbelow
17776 \DeclareTextCompositeCommand{\d}{PU}{t}{\9036\155}% U+1E6D
17777 % U+1E6E LATIN CAPITAL LETTER T WITH LINE BELOW; Tlinebelow
17778 \DeclareTextCompositeCommand{\b}{PU}{T}{\9036\156}% U+1E6E
17779 % U+1E6F LATIN SMALL LETTER T WITH LINE BELOW; tlinebelow
17780 \DeclareTextCompositeCommand{\b}{PU}{t}{\9036\157}% U+1E6F
17781 % U+1E70 LATIN CAPITAL LETTER T WITH CIRCUMFLEX BELOW; Tcir-
cumflexbelow
17782 \DeclareTextCompositeCommand{\textsubcircum}{PU}{T}{\9036\160}% U+1E70
17783 % U+1E71 LATIN SMALL LETTER T WITH CIRCUMFLEX BELOW; tcir-
cumflexbelow
17784 \DeclareTextCompositeCommand{\textsubcircum}{PU}{t}{\9036\161}% U+1E71
17785 % U+1E72 LATIN CAPITAL LETTER U WITH DIAERESIS BELOW; Udiere-
sisbelow
17786 \DeclareTextCompositeCommand{\textsubumlaut}{PU}{U}{\9036\162}% U+1E72
17787 % U+1E73 LATIN SMALL LETTER U WITH DIAERESIS BELOW; udiere-
sisbelow
17788 \DeclareTextCompositeCommand{\textsubumlaut}{PU}{u}{\9036\163}% U+1E73
17789 % U+1E74 LATIN CAPITAL LETTER U WITH TILDE BELOW; Utildebelow
17790 \DeclareTextCompositeCommand{\textsubtilde}{PU}{U}{\9036\164}% U+1E74
17791 % U+1E75 LATIN SMALL LETTER U WITH TILDE BELOW; utildebelow
17792 \DeclareTextCompositeCommand{\textsubtilde}{PU}{u}{\9036\165}% U+1E75
17793 % U+1E76 LATIN CAPITAL LETTER U WITH CIRCUMFLEX BELOW; Ucir-
cumflexbelow
17794 \DeclareTextCompositeCommand{\textsubcircum}{PU}{U}{\9036\166}% U+1E76
17795 % U+1E77 LATIN SMALL LETTER U WITH CIRCUMFLEX BELOW; ucir-
cumflexbelow
17796 \DeclareTextCompositeCommand{\textsubcircum}{PU}{u}{\9036\167}% U+1E77
17797 % U+1E7C LATIN CAPITAL LETTER V WITH TILDE; Vtilde
17798 \DeclareTextCompositeCommand{\~}{PU}{V}{\9036\174}% U+1E7C
17799 % U+1E7D LATIN SMALL LETTER V WITH TILDE; vtilde
17800 \DeclareTextCompositeCommand{\~}{PU}{v}{\9036\175}% U+1E7D
17801 % U+1E7E LATIN CAPITAL LETTER V WITH DOT BELOW; Vdotbelow
17802 \DeclareTextCompositeCommand{\d}{PU}{V}{\9036\176}% U+1E7E
17803 % U+1E7F LATIN SMALL LETTER V WITH DOT BELOW; vdotbelow
17804 \DeclareTextCompositeCommand{\d}{PU}{v}{\9036\177}% U+1E7F
17805 % U+1E80 LATIN CAPITAL LETTER W WITH GRAVE; Wgrave
17806 \DeclareTextCompositeCommand{\`}{PU}{W}{\9036\200}% U+1E80
17807 % U+1E81 LATIN SMALL LETTER W WITH GRAVE; wgrave
17808 \DeclareTextCompositeCommand{\`}{PU}{w}{\9036\201}% U+1E81
17809 % U+1E82 LATIN CAPITAL LETTER W WITH ACUTE; Wacute
17810 \DeclareTextCompositeCommand{\'}{PU}{W}{\9036\202}% U+1E82
17811 % U+1E83 LATIN SMALL LETTER W WITH ACUTE; wacute
17812 \DeclareTextCompositeCommand{\'}{PU}{w}{\9036\203}% U+1E83
17813 % U+1E84 LATIN CAPITAL LETTER W WITH DIAERESIS; Wdieresis
17814 \DeclareTextCompositeCommand{\"}{PU}{W}{\9036\204}% U+1E84
17815 % U+1E85 LATIN SMALL LETTER W WITH DIAERESIS; wdieresis
17816 \DeclareTextCompositeCommand{\"}{PU}{w}{\9036\205}% U+1E85
17817 % U+1E86 LATIN CAPITAL LETTER W WITH DOT ABOVE; Wdotaccent
17818 \DeclareTextCompositeCommand{\.}{PU}{W}{\9036\206}% U+1E86
17819 % U+1E87 LATIN SMALL LETTER W WITH DOT ABOVE; wdotaccent
17820 \DeclareTextCompositeCommand{\.}{PU}{w}{\9036\207}% U+1E87
17821 % U+1E88 LATIN CAPITAL LETTER W WITH DOT BELOW; wdotbelow
17822 \DeclareTextCompositeCommand{\d}{PU}{W}{\9036\210}% U+1E88
17823 % U+1E89 LATIN SMALL LETTER W WITH DOT BELOW; wdotbelow
17824 \DeclareTextCompositeCommand{\d}{PU}{w}{\9036\211}% U+1E89
17825 % U+1E8A LATIN CAPITAL LETTER X WITH DOT ABOVE; Xdotaccent

17826 \DeclareTextCompositeCommand{\.}{PU}{X}{\9036\212}% U+1E8A
17827 % U+1E8B LATIN SMALL LETTER X WITH DOT ABOVE; xdotaccent
17828 \DeclareTextCompositeCommand{\.}{PU}{x}{\9036\213}% U+1E8B
17829 % U+1E8C LATIN CAPITAL LETTER X WITH DIAERESIS; Xdieresis
17830 \DeclareTextCompositeCommand{\"}{PU}{X}{\9036\214}% U+1E8C
17831 % U+1E8D LATIN SMALL LETTER X WITH DIAERESIS; xdieresis
17832 \DeclareTextCompositeCommand{\"}{PU}{x}{\9036\215}% U+1E8D
17833 % U+1E8E LATIN CAPITAL LETTER Y WITH DOT ABOVE; Ydotaccent
17834 \DeclareTextCompositeCommand{\.}{PU}{Y}{\9036\216}% U+1E8E
17835 % U+1E8F LATIN SMALL LETTER Y WITH DOT ABOVE; ydotaccent
17836 \DeclareTextCompositeCommand{\.}{PU}{y}{\9036\217}% U+1E8F
17837 % U+1E90 LATIN CAPITAL LETTER Z WITH CIRCUMFLEX; Zcircumflex
17838 \DeclareTextCompositeCommand{^}{PU}{Z}{\9036\220}% U+1E90
17839 % U+1E91 LATIN SMALL LETTER Z WITH CIRCUMFLEX; zcircumflex
17840 \DeclareTextCompositeCommand{^}{PU}{z}{\9036\221}% U+1E91
17841 % U+1E92 LATIN CAPITAL LETTER Z WITH DOT BELOW; Zdotbelow
17842 \DeclareTextCompositeCommand{\d}{PU}{Z}{\9036\222}% U+1E92
17843 % U+1E93 LATIN SMALL LETTER Z WITH DOT BELOW; zdotbelow
17844 \DeclareTextCompositeCommand{\d}{PU}{z}{\9036\223}% U+1E93
17845 % U+1E94 LATIN CAPITAL LETTER Z WITH LINE BELOW; Zlinebelow
17846 \DeclareTextCompositeCommand{\b}{PU}{Z}{\9036\224}% U+1E94
17847 % U+1E95 LATIN SMALL LETTER Z WITH LINE BELOW; zlinebelow
17848 \DeclareTextCompositeCommand{\b}{PU}{z}{\9036\225}% U+1E95
17849 % U+1E96 LATIN SMALL LETTER H WITH LINE BELOW; hlinebelow
17850 \DeclareTextCompositeCommand{\b}{PU}{h}{\9036\226}% U+1E96
17851 % U+1E97 LATIN SMALL LETTER T WITH DIAERESIS; tdieresis
17852 \DeclareTextCompositeCommand{\"}{PU}{t}{\9036\227}% U+1E97
17853 % U+1E98 LATIN SMALL LETTER W WITH RING ABOVE; wring
17854 \DeclareTextCompositeCommand{\r}{PU}{w}{\9036\230}% U+1E98
17855 % U+1E99 LATIN SMALL LETTER Y WITH RING ABOVE; yring
17856 \DeclareTextCompositeCommand{\r}{PU}{y}{\9036\231}% U+1E99
17857 % U+1E9B LATIN SMALL LETTER LONG S WITH DOT ABOVE; slongdo-
taccent
17858 \DeclareTextCompositeCommand{\.}{PU}{\textlongs}{\9036\233}% U+1E9B
17859 % U+1EA0 LATIN CAPITAL LETTER A WITH DOT BELOW; Adotbelow
17860 \DeclareTextCompositeCommand{\d}{PU}{A}{\9036\240}% U+1EA0
17861 % U+1EA1 LATIN SMALL LETTER A WITH DOT BELOW; adotbelow
17862 \DeclareTextCompositeCommand{\d}{PU}{a}{\9036\241}% U+1EA1
17863 % U+1EB8 LATIN CAPITAL LETTER E WITH DOT BELOW; Edotbelow
17864 \DeclareTextCompositeCommand{\d}{PU}{E}{\9036\270}% U+1EB8
17865 % U+1EB9 LATIN SMALL LETTER E WITH DOT BELOW; edotbelow
17866 \DeclareTextCompositeCommand{\d}{PU}{e}{\9036\271}% U+1EB9
17867 % U+1EBC LATIN CAPITAL LETTER E WITH TILDE; Etilde
17868 \DeclareTextCompositeCommand{\~}{PU}{E}{\9036\274}% U+1EBC
17869 % U+1EBD LATIN SMALL LETTER E WITH TILDE; etilde
17870 \DeclareTextCompositeCommand{\~}{PU}{e}{\9036\275}% U+1EBD
17871 % U+1ECA LATIN CAPITAL LETTER I WITH DOT BELOW; Idotbelow
17872 \DeclareTextCompositeCommand{\d}{PU}{I}{\9036\312}% U+1ECA
17873 % U+1ECB LATIN SMALL LETTER I WITH DOT BELOW; idotbelow
17874 \DeclareTextCompositeCommand{\d}{PU}{i}{\9036\313}% U+1ECB
17875 % U+1ECC LATIN CAPITAL LETTER O WITH DOT BELOW; Odotbelow
17876 \DeclareTextCompositeCommand{\d}{PU}{O}{\9036\314}% U+1ECC
17877 % U+1ECD LATIN SMALL LETTER O WITH DOT BELOW; odotbelow
17878 \DeclareTextCompositeCommand{\d}{PU}{o}{\9036\315}% U+1ECD
17879 % U+1EE4 LATIN CAPITAL LETTER U WITH DOT BELOW; Udotbelow
17880 \DeclareTextCompositeCommand{\d}{PU}{U}{\9036\344}% U+1EE4
17881 % U+1EE5 LATIN SMALL LETTER U WITH DOT BELOW; udotbelow

17882 \DeclareTextCompositeCommand{\d}{PU}{u}{\9036\345}% U+1EE5
 17883 % U+1EF2 LATIN CAPITAL LETTER Y WITH GRAVE; Ygrave
 17884 \DeclareTextCompositeCommand{\'}{PU}{Y}{\9036\362}% U+1EF2
 17885 % U+1EF3 LATIN SMALL LETTER Y WITH GRAVE; ygrave
 17886 \DeclareTextCompositeCommand{\'}{PU}{y}{\9036\363}% U+1EF3
 17887 % U+1EF4 LATIN CAPITAL LETTER Y WITH DOT BELOW; Ydotbelow
 17888 \DeclareTextCompositeCommand{\d}{PU}{Y}{\9036\364}% U+1EF4
 17889 % U+1EF5 LATIN SMALL LETTER Y WITH DOT BELOW; ydotbelow
 17890 \DeclareTextCompositeCommand{\d}{PU}{y}{\9036\365}% U+1EF5
 17891 % U+1EF8 LATIN CAPITAL LETTER Y WITH TILDE; Ytilde
 17892 \DeclareTextCompositeCommand{\~}{PU}{Y}{\9036\370}% U+1EF8
 17893 % U+1EF9 LATIN SMALL LETTER Y WITH TILDE; ytilde
 17894 \DeclareTextCompositeCommand{\~}{PU}{y}{\9036\371}% U+1EF9

51.2.16 General Punctuation: U+2000 to U+206F

17895 % U+200C ZERO WIDTH NON-JOINER; *afii61664, zerowidthnonjoiner
 17896 \DeclareTextCommand{\textcompwordmark}{PU}{\9040\014}% U+200C
 17897 % U+2013 EN DASH; endash
 17898 \DeclareTextCommand{\textendash}{PU}{\9040\023}% U+2013
 17899 % U+2014 EM DASH; emdash
 17900 \DeclareTextCommand{\textemdash}{PU}{\9040\024}% U+2014
 17901 % U+2016 DOUBLE VERTICAL LINE; dblverticalbar
 17902 \DeclareTextCommand{\textbardbl}{PU}{\9040\026}% U+2016
 17903 %* \textbardbl -> \textdoublevertline (tipa)
 17904 % U+2018 LEFT SINGLE QUOTATION MARK; quoteleft
 17905 \DeclareTextCommand{\textquoteleft}{PU}{\9040\030}% U+2018
 17906 % U+2019 RIGHT SINGLE QUOTATION MARK; quoteright
 17907 \DeclareTextCommand{\textquoteright}{PU}{\9040\031}% U+2019
 17908 % U+201A SINGLE LOW-9 QUOTATION MARK; quotesinglbase
 17909 \DeclareTextCommand{\quotesinglbase}{PU}{\9040\032}% U+201A
 17910 % U+201C LEFT DOUBLE QUOTATION MARK; quotedblleft
 17911 \DeclareTextCommand{\textquotedblleft}{PU}{\9040\034}% U+201C
 17912 % U+201D RIGHT DOUBLE QUOTATION MARK; quotedblright
 17913 \DeclareTextCommand{\textquotedblright}{PU}{\9040\035}% U+201D
 17914 % U+201E DOUBLE LOW-9 QUOTATION MARK; quotedblbase
 17915 \DeclareTextCommand{\quotedblbase}{PU}{\9040\036}% U+201E
 17916 % U+2020 DAGGER; dagger
 17917 \DeclareTextCommand{\textdagger}{PU}{\9040\040}%* U+2020
 17918 %* \textdagger -> \dag (LaTeX)
 17919 % U+2021 DOUBLE DAGGER; daggerdbl; \ddagger (LaTeX)
 17920 \DeclareTextCommand{\textdaggerdbl}{PU}{\9040\041}% U+2021
 17921 %* \textdaggerdbl -> \ddagger (LaTeX)
 17922 %* \textdaggerdbl -> \dag (LaTeX)
 17923 % U+2022 BULLET; bullet
 17924 \DeclareTextCommand{\textbullet}{PU}{\9040\042}%* U+2022
 17925 % U+2025 TWO DOT LEADER; \hdotfor (MnSymbol)
 17926 \DeclareTextCommand{\texthdotfor}{PU}{\9040\045}%* U+2025
 17927 % U+2026 HORIZONTAL ELLIPSIS; ellipsis
 17928 \DeclareTextCommand{\textellipsis}{PU}{\9040\046}% U+2026
 17929 %* \textellipsis -> \mathellipsis
 17930 % U+2030 PER MILLE SIGN; perthousand
 17931 \DeclareTextCommand{\textperthousand}{PU}{\9040\060}% U+2030
 17932 % U+2031 PER TEN THOUSAND SIGN
 17933 \DeclareTextCommand{\textpertenthousand}{PU}{\9040\061}% U+2031
 17934 % U+2032 PRIME; minute; \prime (MnSymbol)
 17935 \DeclareTextCommand{\textprime}{PU}{\9040\062}%* U+2032
 17936 % U+2033 DOUBLE PRIME; \second (mathabx)

17937 \DeclareTextCommand{\textsecond}{PU}{\9040\063}%* U+2033
 17938 % U+2034 TRIPLE PRIME; \third (mathabx)
 17939 \DeclareTextCommand{\textthird}{PU}{\9040\064}%* U+2034
 17940 % U+2035 REVERSED PRIME; \backprime (AmS)
 17941 \DeclareTextCommand{\textbackprime}{PU}{\9040\065}%* U+2035
 17942 % U+2039 SINGLE LEFT-POINTING ANGLE QUOTATION MARK; guil-
 inglleft
 17943 \DeclareTextCommand{\guilsinglleft}{PU}{\9040\071}% U+2039
 17944 % U+203A SINGLE RIGHT-POINTING ANGLE QUOTATION MARK; guil-
 inglright
 17945 \DeclareTextCommand{\guilsinglright}{PU}{\9040\072}% U+203A
 17946 % U+203B REFERENCE MARK; referencemark
 17947 \DeclareTextCommand{\textreferencemark}{PU}{\9040\073}% U+203B
 17948 % U+203D INTERROBANG
 17949 \DeclareTextCommand{\textinterrobang}{PU}{\9040\075}% U+203D
 17950 % U+2044 FRACTION SLASH; fraction
 17951 \DeclareTextCommand{\textfractionsolidus}{PU}{\9040\104}% U+2044
 17952 % U+2045 LEFT SQUARE BRACKET WITH QUILL
 17953 \DeclareTextCommand{\textlquill}{PU}{\9040\105}% U+2045
 17954 % U+2046 RIGHT SQUARE BRACKET WITH QUILL
 17955 \DeclareTextCommand{\textrquill}{PU}{\9040\106}% U+2046
 17956 % U+2052 COMMERCIAL MINUS SIGN
 17957 \DeclareTextCommand{\textdiscount}{PU}{\9040\122}% U+2052
 17958 % U+2056 THREE DOT PUNCTUATION; \lefttherefore (MnSymbol)
 17959 \DeclareTextCommand{\textlefttherefore}{PU}{\9040\126}%* U+2056
 17960 % U+2057 QUADRUPLE PRIME; \fourth (mathabx)
 17961 \DeclareTextCommand{\textfourth}{PU}{\9040\127}%* U+2057
 17962 % U+2058 FOUR DOT PUNCTUATION; \diamonddots (MnSymbol)
 17963 \DeclareTextCommand{\textdiamonddots}{PU}{\9040\130}%* U+2058

51.2.17 Superscripts and Subscripts: U+2070 to U+209F

17964 % U+2070 SUPERSCRIPT ZERO; zerosuperior
 17965 \DeclareTextCommand{\textzerosuperior}{PU}{\9040\160}%* U+2070
 17966 % U+2071 SUPERSCRIPT LATIN SMALL LETTER I
 17967 \DeclareTextCommand{\textisuperior}{PU}{\9040\161}%* U+2071
 17968 % U+2074 SUPERSCRIPT FOUR; foursuperior
 17969 \DeclareTextCommand{\textfoursuperior}{PU}{\9040\164}%* U+2074
 17970 % U+2075 SUPERSCRIPT FIVE; fivesuperior
 17971 \DeclareTextCommand{\textfivesuperior}{PU}{\9040\165}%* U+2075
 17972 % U+2076 SUPERSCRIPT SIX; sixsuperior
 17973 \DeclareTextCommand{\textsixsuperior}{PU}{\9040\166}%* U+2076
 17974 % U+2077 SUPERSCRIPT SEVEN; sevensuperior
 17975 \DeclareTextCommand{\textsevensuperior}{PU}{\9040\167}%* U+2077
 17976 % U+2078 SUPERSCRIPT EIGHT; eightsuperior
 17977 \DeclareTextCommand{\texteightsuperior}{PU}{\9040\170}%* U+2078
 17978 % U+2079 SUPERSCRIPT NINE; ninesuperior
 17979 \DeclareTextCommand{\textninesuperior}{PU}{\9040\171}%* U+2079
 17980 % U+207A SUPERSCRIPT PLUS SIGN; plussuperior
 17981 \DeclareTextCommand{\textplussuperior}{PU}{\9040\172}%* U+207A
 17982 % U+207B SUPERSCRIPT MINUS
 17983 \DeclareTextCommand{\textminussuperior}{PU}{\9040\173}%* U+207B
 17984 % U+207C SUPERSCRIPT EQUALS SIGN; equalsuperior
 17985 \DeclareTextCommand{\textequalsuperior}{PU}{\9040\174}%* U+207C
 17986 % U+207D SUPERSCRIPT LEFT PARENTHESIS; parenleftsuperior
 17987 \DeclareTextCommand{\textparenleftsuperior}{PU}{\9040\175}%* U+207D
 17988 % U+207E SUPERSCRIPT RIGHT PARENTHESIS; parenrightsuperior
 17989 \DeclareTextCommand{\textparenrightsuperior}{PU}{\9040\176}%* U+207E

17990 % U+207F SUPERSCRIPT LATIN SMALL LETTER N; nsuperior
17991 \DeclareTextCommand{\textnsuperior}{PU}{\9040\177}%* U+207F
17992 % U+2080 SUBSCRIPT ZERO; zeroinferior
17993 \DeclareTextCommand{\textzeroinferior}{PU}{\9040\200}%* U+2080
17994 % U+2081 SUBSCRIPT ONE; oneinferior
17995 \DeclareTextCommand{\textoneinferior}{PU}{\9040\201}%* U+2081
17996 % U+2082 SUBSCRIPT TWO; twoinferior
17997 \DeclareTextCommand{\texttwoinferior}{PU}{\9040\202}%* U+2082
17998 % U+2083 SUBSCRIPT THREE; threeinferior
17999 \DeclareTextCommand{\textthreeinferior}{PU}{\9040\203}%* U+2083
18000 % U+2084 SUBSCRIPT FOUR; fourinferior
18001 \DeclareTextCommand{\textfourinferior}{PU}{\9040\204}%* U+2084
18002 % U+2085 SUBSCRIPT FIVE; fiveinferior
18003 \DeclareTextCommand{\textfiveinferior}{PU}{\9040\205}%* U+2085
18004 % U+2086 SUBSCRIPT SIX; sixinferior
18005 \DeclareTextCommand{\textsixinferior}{PU}{\9040\206}%* U+2086
18006 % U+2087 SUBSCRIPT SEVEN; seveninferior
18007 \DeclareTextCommand{\textseveninferior}{PU}{\9040\207}%* U+2087
18008 % U+2088 SUBSCRIPT EIGHT; eightinferior
18009 \DeclareTextCommand{\texteightinferior}{PU}{\9040\210}%* U+2088
18010 % U+2089 SUBSCRIPT NINE; nineinferior
18011 \DeclareTextCommand{\textnineinferior}{PU}{\9040\211}%* U+2089
18012 % U+208A SUBSCRIPT PLUS SIGN
18013 \DeclareTextCommand{\textplusinferior}{PU}{\9040\212}%* U+208A
18014 % U+208B SUBSCRIPT MINUS
18015 \DeclareTextCommand{\textminusinferior}{PU}{\9040\213}%* U+208B
18016 % U+208C SUBSCRIPT EQUALS SIGN
18017 \DeclareTextCommand{\textequalsinferior}{PU}{\9040\214}%* U+208C
18018 % U+208D SUBSCRIPT LEFT PARENTHESIS; parenleftinferior
18019 \DeclareTextCommand{\textparenleftinferior}{PU}{\9040\215}%* U+208D
18020 % U+208E SUBSCRIPT RIGHT PARENTHESIS; parenrightinferior
18021 \DeclareTextCommand{\textparenrightinferior}{PU}{\9040\216}%* U+208E
18022 % U+2090 LATIN SUBSCRIPT SMALL LETTER A
18023 \DeclareTextCommand{\textainferior}{PU}{\9040\220}%* U+2090
18024 % U+2091 LATIN SUBSCRIPT SMALL LETTER E
18025 \DeclareTextCommand{\texteinferior}{PU}{\9040\221}%* U+2091
18026 % U+2092 LATIN SUBSCRIPT SMALL LETTER O
18027 \DeclareTextCommand{\textoinferior}{PU}{\9040\222}%* U+2092
18028 % U+2093 LATIN SUBSCRIPT SMALL LETTER X
18029 \DeclareTextCommand{\textxinferior}{PU}{\9040\223}%* U+2093
18030 % U+2094 LATIN SUBSCRIPT SMALL LETTER SCHWA
18031 \DeclareTextCommand{\textschwainferior}{PU}{\9040\224}%* U+2094
18032 % U+2095 LATIN SUBSCRIPT SMALL LETTER H
18033 \DeclareTextCommand{\texthinferior}{PU}{\9040\225}%* U+2095
18034 % U+2096 LATIN SUBSCRIPT SMALL LETTER K
18035 \DeclareTextCommand{\textkinferior}{PU}{\9040\226}%* U+2096
18036 % U+2097 LATIN SUBSCRIPT SMALL LETTER L
18037 \DeclareTextCommand{\textlinferior}{PU}{\9040\227}%* U+2097
18038 % U+2098 LATIN SUBSCRIPT SMALL LETTER M
18039 \DeclareTextCommand{\textminferior}{PU}{\9040\230}%* U+2098
18040 % U+2099 LATIN SUBSCRIPT SMALL LETTER N
18041 \DeclareTextCommand{\textninferior}{PU}{\9040\231}%* U+2099
18042 % U+209A LATIN SUBSCRIPT SMALL LETTER P
18043 \DeclareTextCommand{\textpinferior}{PU}{\9040\232}%* U+209A
18044 % U+209B LATIN SUBSCRIPT SMALL LETTER S
18045 \DeclareTextCommand{\textsinferior}{PU}{\9040\233}%* U+209B
18046 % U+209C LATIN SUBSCRIPT SMALL LETTER T

18047 \DeclareTextCommand{\textttinferior}{PU}{\9040\234}%* U+209C

51.2.18 Currency Symbols: U+20A0 to U+20CF

18048 % U+20A1 COLON SIGN; *colonmonetary, colonsign

18049 \DeclareTextCommand{\textcolonmonetary}{PU}{\9040\241}% U+20A1

18050 % U+20A4 LIRA SIGN; afii08941, *lira

18051 \DeclareTextCommand{\textlira}{PU}{\9040\244}% U+20A4

18052 % U+20A6 NAIRA SIGN

18053 \DeclareTextCommand{\textnaira}{PU}{\9040\246}% U+20A6

18054 % U+20A7 PESETA SIGN; peseta

18055 \DeclareTextCommand{\textpeseta}{PU}{\9040\247}% U+20A7

18056 % U+20A9 WON SIGN; won

18057 \DeclareTextCommand{\textwon}{PU}{\9040\251}% U+20A9

18058 % U+20AB DONG SIGN; dong

18059 \DeclareTextCommand{\textdong}{PU}{\9040\253}% U+20AB

18060 % U+20AC EURO SIGN; *Euro, euro

18061 \DeclareTextCommand{\texteuro}{PU}{\9040\254}% U+20AC

18062 %* \texteuro -> \EurDig (marvosym)

18063 %* \texteuro -> \EURdig (marvosym)

18064 %* \texteuro -> \EurHv (marvosym)

18065 %* \texteuro -> \EURhv (marvosym)

18066 %* \texteuro -> \EurCr (marvosym)

18067 %* \texteuro -> \EURcr (marvosym)

18068 %* \texteuro -> \EurTm (marvosym)

18069 %* \texteuro -> \EURtm (marvosym)

18070 %* \texteuro -> \Eur (marvosym)

18071 % U+20B0 GERMAN PENNY SIGN; \Deleatur (marvosym)

18072 \DeclareTextCommand{\textDeleatur}{PU}{\9040\260}%* U+20B0

18073 %* \textDeleatur -> \Denarius (marvosym)

18074 % U+20B1 PESO SIGN

18075 \DeclareTextCommand{\textpeso}{PU}{\9040\261}% U+20B1

18076 % U+20B2 GUARANI SIGN

18077 \DeclareTextCommand{\textguarani}{PU}{\9040\262}% U+20B2

51.2.19 Letterlike Symbols: U+2100 to U+214F

18078 % U+2103 DEGREE CELSIUS; centigrade

18079 \DeclareTextCommand{\textcelsius}{PU}{\9041\003}% U+2103

18080 % U+210F PLANCK CONSTANT OVER TWO PI; \hslash (AmS)

18081 \DeclareTextCommand{\textslash}{PU}{\9041\017}%* U+210F

18082 % U+2111 BLACK-LETTER CAPITAL I (=imaginary part); Ifraktur; \Im (LaTeX)

18083 \DeclareTextCommand{\textIm}{PU}{\9041\021}%* U+2111

18084 % U+2113 SCRIPT SMALL L (=ell, liter); afii61289, lsquare; \ell (LaTeX)

18085 \DeclareTextCommand{\textell}{PU}{\9041\023}%* U+2113

18086 % U+2116 NUMERO SIGN; *afii61352, numero

18087 \DeclareTextCommand{\textnumero}{PU}{\9041\026}% U+2116

18088 % U+2117 SOUND RECORDING COPYRIGHT

18089 \DeclareTextCommand{\textcircledP}{PU}{\9041\027}% U+2117

18090 % U+2118 SCRIPT CAPITAL P (=Weierstrass elliptic function);

18091 % weierstrass; \wp (LaTeX)

18092 \DeclareTextCommand{\textwp}{PU}{\9041\030}%* U+2118

18093 % U+211C BLACK-LETTER CAPITAL R (=real part); Rfraktur; \Re (LaTeX)

18094 \DeclareTextCommand{\textRe}{PU}{\9041\034}%* U+211C

18095 % U+211E PRESCRIPTION TAKE; prescription

18096 \DeclareTextCommand{\textrecipe}{PU}{\9041\036}% U+211E

18097 % U+2120 SERVICE MARK

18098 \DeclareTextCommand{\textservicemark}{PU}{\9041\040}% U+2120

18099 % U+2122 TRADE MARK SIGN; trademark
 18100 \DeclareTextCommand{\texttrademark}{PU}{\9041\042}% U+2122
 18101 % U+2126 OHM SIGN; Ohm, Omega
 18102 \DeclareTextCommand{\textohm}{PU}{\9041\046}% U+2126
 18103 % U+2127 INVERTED OHM SIGN
 18104 \DeclareTextCommand{\textmho}{PU}{\9041\047}%* U+2127
 18105 %* \textmho -> \agemO (wasysym)
 18106 % U+2129 TURNED GREEK SMALL LETTER IOTA; \riota (phonetic)
 18107 \DeclareTextCommand{\textriota}{PU}{\9041\051}%* U+2129
 18108 % U+212B ANGSTROM SIGN; angstrom
 18109 \DeclareTextCommand{\textangstrom}{PU}{\9041\053}% U+212B
 18110 % U+212E ESTIMATED SYMBOL; estimated
 18111 \DeclareTextCommand{\textestimated}{PU}{\9041\056}% U+212E
 18112 %* \textestimated -> \EstimatedSign (marvosym)
 18113 %* \textestimated -> \Ecommerce (marvosym)
 18114 % U+2132 TURNED CAPITAL F; \Finv (AmS)
 18115 \DeclareTextCommand{\textFinv}{PU}{\9041\062}%* U+2132
 18116 % U+2135 ALEF SYMBOL; aleph; \aleph (LaTeX)
 18117 \DeclareTextCommand{\textaleph}{PU}{\9041\065}%* U+2135
 18118 % U+2136 BET SYMBOL; \beth (AmS, MnSymbol)
 18119 \DeclareTextCommand{\textbeth}{PU}{\9041\066}%* U+2136
 18120 % U+2137 GIMEL SYMBOL; \gimel (AmS, MnSymbol)
 18121 \DeclareTextCommand{\textgimel}{PU}{\9041\067}%* U+2137
 18122 % U+2138 DALET SYMBOL; \daleth (AmS, MnSymbol)
 18123 \DeclareTextCommand{\textdaleth}{PU}{\9041\070}%* U+2138
 18124 % U+213B FACSIMILE SIGN; \fax (marvosym)
 18125 \DeclareTextCommand{\textfax}{PU}{\9041\073}%* U+213B
 18126 % U+2141 TURNED SANS-SERIF CAPITAL G (=game); \Game
 18127 \DeclareTextCommand{\textGame}{PU}{\9041\101}%* U+2141
 18128 % U+214B TURNED AMPERSAND; \invamp (txfonts/pxfonts)
 18129 \DeclareTextCommand{\textinvamp}{PU}{\9041\113}% U+214B
 18130 %* \textinvamp -> \bindnasrepma (stmaryrd)
 18131 %* \textinvamp -> \parr (cml)

51.2.20 Number Forms: U+2150 to U+218F

18132 % U+2150 VULGAR FRACTION ONE SEVENTH
 18133 \DeclareTextCommand{\textoneseventh}{PU}{\9041\120}% U+2150
 18134 % U+2151 VULGAR FRACTION ONE NINTH
 18135 \DeclareTextCommand{\textoneninth}{PU}{\9041\121}% U+2151
 18136 % U+2152 VULGAR FRACTION ONE TENTH
 18137 \DeclareTextCommand{\textonetenth}{PU}{\9041\122}% U+2152
 18138 % U+2153 VULGAR FRACTION ONE THIRD; onethird
 18139 \DeclareTextCommand{\textonethird}{PU}{\9041\123}% U+2153
 18140 % U+2154 VULGAR FRACTION TWO THIRDS; twothirds
 18141 \DeclareTextCommand{\texttwothirds}{PU}{\9041\124}% U+2154
 18142 % U+2155 VULGAR FRACTION ONE FIFTH
 18143 \DeclareTextCommand{\textonefifth}{PU}{\9041\125}% U+2155
 18144 % U+2156 VULGAR FRACTION TWO FIFTHS
 18145 \DeclareTextCommand{\texttwofifths}{PU}{\9041\126}% U+2156
 18146 % U+2157 VULGAR FRACTION THREE FIFTHS
 18147 \DeclareTextCommand{\textthreelfths}{PU}{\9041\127}% U+2157
 18148 % U+2158 VULGAR FRACTION FOUR FIFTHS
 18149 \DeclareTextCommand{\textfourfifths}{PU}{\9041\130}% U+2158
 18150 % U+2159 VULGAR FRACTION ONE SIXTH
 18151 \DeclareTextCommand{\textonesixth}{PU}{\9041\131}% U+2159
 18152 % U+215A VULGAR FRACTION FIVE SIXTHS
 18153 \DeclareTextCommand{\textfivesixths}{PU}{\9041\132}% U+215A

18154 % U+215B VULGAR FRACTION ONE EIGHTH; oneeighth
 18155 \DeclareTextCommand{\textoneeighth}{PU}{\9041\133}% U+215B
 18156 % U+215C VULGAR FRACTION THREE EIGHTHS; threeeighths
 18157 \DeclareTextCommand{\textthreeeighths}{PU}{\9041\134}% U+215C
 18158 % U+215D VULGAR FRACTION FIVE EIGHTHS; fiveeighths
 18159 \DeclareTextCommand{\textfiveeighths}{PU}{\9041\135}% U+215D
 18160 % U+215E VULGAR FRACTION SEVEN EIGHTHS; seveneighths
 18161 \DeclareTextCommand{\textseveneighths}{PU}{\9041\136}% U+215E
 18162 % U+2184 LATIN SMALL LETTER REVERSED C
 18163 \DeclareTextCommand{\textrevc}{PU}{\9041\204}% U+2184
 18164 % U+2189 VULGAR FRACTION ZERO THIRDS
 18165 \DeclareTextCommand{\textzer thirds}{PU}{\9041\211}% U+2189

51.2.21 Arrows: U+2190 to U+21FF

18166 % U+2190 LEFTWARDS ARROW; arrowleft
 18167 \DeclareTextCommand{\textleftarrow}{PU}{\9041\220}%* U+2190
 18168 % U+2191 UPWARDS ARROW; arrowup
 18169 \DeclareTextCommand{\textuparrow}{PU}{\9041\221}%* U+2191
 18170 % U+2192 RIGHTWARDS ARROW; arrowright
 18171 \DeclareTextCommand{\textrightarrow}{PU}{\9041\222}%* U+2192
 18172 %* \textrightarrow -> \MVRightArrow (marvosym)
 18173 %* \textrightarrow -> \MVRightarrow (marvosym)
 18174 % U+2193 DOWNWARDS ARROW; arrowdown
 18175 \DeclareTextCommand{\textdownarrow}{PU}{\9041\223}%* U+2193
 18176 %* \textdownarrow -> \MVarrowDown (marvosym)
 18177 %* \textdownarrow -> \Force (marvosym)
 18178 % U+2194 LEFT RIGHT ARROW; arrowboth; \leftrightarrow (LaTeX)
 18179 \DeclareTextCommand{\textleftrightarrow}{PU}{\9041\224}%* U+2194
 18180 % U+2195 UP DOWN ARROW; arrowupdn; \updownarrow (LaTeX)
 18181 \DeclareTextCommand{\textupdownarrow}{PU}{\9041\225}%* U+2195
 18182 % U+2196 NORTH WEST ARROW; arrowupleft; \nwarrow (LaTeX)
 18183 \DeclareTextCommand{\textnwarrow}{PU}{\9041\226}%* U+2196
 18184 % U+2197 NORTH EAST ARROW; arrowupright; \nearrow (LaTeX)
 18185 \DeclareTextCommand{\textnearrow}{PU}{\9041\227}%* U+2197
 18186 %* \textnearrow -> \textglobrise (tipa)
 18187 % U+2198 SOUTH EAST ARROW; arrowdownright; \searrow (LaTeX)
 18188 \DeclareTextCommand{\textsearrow}{PU}{\9041\230}%* U+2198
 18189 %* \textsearrow -> \textglobfall (tipa)
 18190 % U+2199 SOUTH WEST ARROW; arrowdownleft; \swarrow (LaTeX)
 18191 \DeclareTextCommand{\textswarrow}{PU}{\9041\231}%* U+2199
 18192 % U+219A LEFTWARDS ARROW WITH STROKE; \leftarrow (AmS)
 18193 \DeclareTextCommand{\textnleftarrow}{PU}{\9041\232}%* U+219A
 18194 % U+219B RIGHTWARDS ARROW WITH STROKE; \rightarrow (AmS)
 18195 \DeclareTextCommand{\textnrightarrow}{PU}{\9041\233}%* U+219B
 18196 % U+219E LEFTWARDS TWO HEADED ARROW; \twoheadleftarrow (AmS)
 18197 \DeclareTextCommand{\texttwoheadleftarrow}{PU}{\9041\236}%* U+219E
 18198 % \twoheadleftarrow (txfonts/pxfonts)
 18199 \DeclareTextCommand{\textntwoheadleftarrow}{PU}{\9041\236\83\070}%* U+219E U+0338
 18200 % U+219F UPWARDS TWO HEADED ARROW; \twoheaduparrow (MnSymbol)
 18201 \DeclareTextCommand{\texttwoheaduparrow}{PU}{\9041\237}%* U+219F
 18202 % U+21A0 RIGHTWARDS TWO HEADED ARROW;
 18203 % \twoheadrightarrow (AmS)
 18204 \DeclareTextCommand{\texttwoheadrightarrow}{PU}{\9041\240}%* U+21A0
 18205 % \twoheadrightarrow (txfonts/pxfonts)
 18206 \DeclareTextCommand{\textntwoheadrightarrow}{PU}{\9041\240\83\070}%* U+21A0 U+0338
 18207 % U+21A1 DOWNWARDS TWO HEADED ARROW; \twoheaddownarrow (Mn-
 Symbol)

```

18208 \DeclareTextCommand{\texttwoheaddownarrow}{PU}{\9041\241}%* U+21A1
18209 % U+21A2 LEFTWARDS ARROW WITH TAIL; \leftarrowtail (AmS)
18210 \DeclareTextCommand{\textleftarrowtail}{PU}{\9041\242}%* U+21A2
18211 % U+21A3 RIGHTWARDS ARROW WITH TAIL; \rightarrowtail (AmS)
18212 \DeclareTextCommand{\textrightarrowtail}{PU}{\9041\243}%* U+21A3
18213 % U+21A6 RIGHTWARDS ARROW FROM BAR; \mapsto (LaTeX)
18214 \DeclareTextCommand{\textmapsto}{PU}{\9041\246}%* U+21A6
18215 % U+21A9 LEFTWARDS ARROW WITH HOOK; \hookleftarrow (LaTeX)
18216 \DeclareTextCommand{\texthookleftarrow}{PU}{\9041\251}%* U+21A9
18217 % U+21AA RIGHTWARDS ARROW WITH HOOK; \hookrightarrow (LaTeX)
18218 \DeclareTextCommand{\texthookrightarrow}{PU}{\9041\252}%* U+21AA
18219 % U+21AB LEFTWARDS ARROW WITH LOOP; \looparrowleft (AmS)
18220 \DeclareTextCommand{\textlooparrowleft}{PU}{\9041\253}%* U+21AB
18221 % U+21AC RIGHTWARDS ARROW WITH LOOP; \looparrowright (AmS)
18222 \DeclareTextCommand{\textlooparrowright}{PU}{\9041\254}%* U+21AC
18223 % U+21AE LEFT RIGHT ARROW WITH STROKE; \leftrightharpoonup (AmS)
18224 \DeclareTextCommand{\textleftrightharpoonup}{PU}{\9041\256}%* U+21AE
18225 % U+21AF DOWNWARDS ZIGZAG ARROW; \lightning (stmaryrd)
18226 \DeclareTextCommand{\textlightning}{PU}{\9041\257}%* U+21AF
18227 %* \textlightning -> \Lightning (marvosym)
18228 % U+21B5 DOWNWARDS ARROW WITH CORNER LEFTWARDS;
18229 % \dsh (mathabx)
18230 \DeclareTextCommand{\textdsh}{PU}{\9041\265}%* U+21B5
18231 % U+21B6 ANTICLOCKWISE TOP SEMICIRCLE ARROW;
18232 % \curvearrowleft (AmS)
18233 \DeclareTextCommand{\textcurvearrowleft}{PU}{\9041\266}%* U+21B6
18234 % U+21B7 CLOCKWISE TOP SEMICIRCLE ARROW; \curvearrowright (AmS)
18235 \DeclareTextCommand{\textcurvearrowright}{PU}{\9041\267}%* U+21B7
18236 % U+21BC LEFTWARDS HARPOON WITH BARB UPWARDS; harpoonleft-
    barbut;
18237 % \leftharpoonup (LaTeX)
18238 \DeclareTextCommand{\textleftharpoonup}{PU}{\9041\274}%* U+21BC
18239 % U+21BD LEFTWARDS HARPOON WITH BARB DOWNWARDS;
18240 % \leftharpoondown (LaTeX)
18241 \DeclareTextCommand{\textleftharpoondown}{PU}{\9041\275}%* U+21BD
18242 % U+21BE UPWARDS HARPOON WITH BARB RIGHTWARDS;
18243 % \upharpoonright (AmS)
18244 \DeclareTextCommand{\textupharpoonright}{PU}{\9041\276}%* U+21BE
18245 % U+21BF UPWARDS HARPOON WITH BARB LEFTWARDS;
18246 % \upharpoonleft (AmS)
18247 \DeclareTextCommand{\textupharpoonleft}{PU}{\9041\277}%* U+21BF
18248 % U+21C0 RIGHTWARDS HARPOON WITH BARB UPWARDS; harpoonright-
    barbut
18249 % \rightharpoonup (LaTeX)
18250 \DeclareTextCommand{\textrightharpoonup}{PU}{\9041\300}%* U+21C0
18251 % U+21C1 RIGHTWARDS HARPOON WITH BARB DOWNWARDS;
18252 % \rightharpoondown (LaTeX)
18253 \DeclareTextCommand{\textrightharpoondown}{PU}{\9041\301}%* U+21C1
18254 % U+21C2 DOWNWARDS HARPOON WITH BARB RIGHTWARDS;
18255 % \downharpoonright (AmS)
18256 \DeclareTextCommand{\textdownharpoonright}{PU}{\9041\302}%* U+21C2
18257 % U+21C3 DOWNWARDS HARPOON WITH BARB LEFTWARDS;
18258 % \downharpoonleft (AmS)
18259 \DeclareTextCommand{\textdownharpoonleft}{PU}{\9041\303}%* U+21C3
18260 % U+21C4 RIGHTWARDS ARROW OVER LEFTWARDS ARROW;
18261 % \rightarrowoverleft; \rightleftarrows (MnSymbol)
18262 \DeclareTextCommand{\textrightleftarrows}{PU}{\9041\304}%* U+21C4

```

```

18263 % U+21C5 UPWARDS ARROW LEFTWARDS OF DOWNWARDS ARROW; ar-
rowupleftofdown;
18264 % \updownarrows (MnSymbol)
18265 \DeclareTextCommand{\textupdownarrows}{PU}{\9041\305}%* U+21C5
18266 % U+21C6 LEFTWARDS ARROW OVER RIGHTWARDS ARROW; arrowleft-
overright;
18267 % \leftrightarrows (AmS)
18268 \DeclareTextCommand{\textleftrightarrows}{PU}{\9041\306}%* U+21C6
18269 % U+21C7 LEFTWARDS PAIRED ARROWS; \leftleftarrows (AmS)
18270 \DeclareTextCommand{\textleftleftarrows}{PU}{\9041\307}%* U+21C7
18271 % U+21C8 UPWARDS PAIRED ARROWS; \upuparrows (AmS)
18272 \DeclareTextCommand{\textupuparrows}{PU}{\9041\310}%* U+21C8
18273 % U+21C9 RIGHTWARDS PAIRED ARROWS; \rightrightarrows (AmS)
18274 \DeclareTextCommand{\textrightarrows}{PU}{\9041\311}%* U+21C9
18275 % U+21CA DOWNWARDS PAIRED ARROWS; \downdownarrows (AmS)
18276 \DeclareTextCommand{\textdownarrows}{PU}{\9041\312}%* U+21CA
18277 % U+21CB LEFTWARDS HARPOON OVER RIGHTWARDS HARPOON;
18278 % \leftrightharpoons (AmS);
18279 \DeclareTextCommand{\textleftrightharpoons}{PU}{\9041\313}%* U+21CB
18280 % U+21CC RIGHTWARDS HARPOON OVER LEFTWARDS HARPOON;
18281 % \rightleftharpoons (LaTeX, AmS)
18282 \DeclareTextCommand{\textrightleftharpoons}{PU}{\9041\314}%* U+21CC
18283 % U+21CD LEFTWARDS DOUBLE ARROW WITH STROKE; arrowleftd-
blstroke;
18284 % \nLeftarrow (AmS)
18285 \DeclareTextCommand{\textnLeftarrow}{PU}{\9041\315}%* U+21CD
18286 % U+21CE LEFT RIGHT DOUBLE ARROW WITH STROKE; \nLeftrightarrow (AmS)
18287 \DeclareTextCommand{\textnLeftrightarrow}{PU}{\9041\316}%* U+21CE
18288 % U+21CF RIGHTWARDS DOUBLE ARROW WITH STROKE; arrowrightd-
blstroke;
18289 % \nRightarrow (AmS)
18290 \DeclareTextCommand{\textnRightarrow}{PU}{\9041\317}%* U+21CF
18291 % U+21D0 LEFTWARDS DOUBLE ARROW; arrowdblleft, arrowleftdbl;
18292 % \Leftarrow (LaTeX)
18293 \DeclareTextCommand{\textLeftarrow}{PU}{\9041\320}%* U+21D0
18294 % U+21D1 UPWARDS DOUBLE ARROW; arrowdblup; \Uparrow (LaTeX)
18295 \DeclareTextCommand{\textUparrow}{PU}{\9041\321}%* U+21D1
18296 % U+21D2 RIGHTWARDS DOUBLE ARROW; arrowdblright, dblarrowright;
18297 % \Rightarrow (LaTeX)
18298 \DeclareTextCommand{\textRightarrow}{PU}{\9041\322}%* U+21D2
18299 %* \textRightarrow -> \Conclusion (marvosym)
18300 % U+21D3 DOWNWARDS DOUBLE ARROW; arrowdbl down; \Downarrow (La-
TeX)
18301 \DeclareTextCommand{\textDownarrow}{PU}{\9041\323}%* U+21D3
18302 % U+21D4 LEFT RIGHT DOUBLE ARROW; arrowdblboth;
18303 % \Leftrightarrow (LaTeX)
18304 \DeclareTextCommand{\textLeftrightarrow}{PU}{\9041\324}%* U+21D4
18305 %* \textLeftrightarrow -> \Equivalence (marvosym)
18306 % U+21D5 UP DOWN DOUBLE ARROW; \Updownarrow (LaTeX)
18307 \DeclareTextCommand{\textUpdownarrow}{PU}{\9041\325}%* U+21D5
18308 % U+21D6 NORTH WEST DOUBLE ARROW; \Nwarrow (MnSymbol)
18309 \DeclareTextCommand{\textNwarrow}{PU}{\9041\326}%* U+21D6
18310 % U+21D7 NORTH EAST DOUBLE ARROW; \Nearrow (MnSymbol)
18311 \DeclareTextCommand{\textNearrow}{PU}{\9041\327}%* U+21D7
18312 % U+21D8 SOUTH EAST DOUBLE ARROW; \Searrow (MnSymbol)
18313 \DeclareTextCommand{\textSearrow}{PU}{\9041\330}%* U+21D8

```

```

18314 % U+21D9 SOUTH WEST DOUBLE ARROW; \Swarrow (MnSymbol)
18315 \DeclareTextCommand{\textSwarrow}{PU}{\9041\331}%* U+21D9
18316 % U+21DA LEFTWARDS TRIPLE ARROW; \Lleftarrow (AmS)
18317 \DeclareTextCommand{\textLleftarrow}{PU}{\9041\332}%* U+21DA
18318 % U+21DB RIGHTWARDS TRIPLE ARROW; \Rrightarrow (MnSymbol)
18319 \DeclareTextCommand{\textRrightarrow}{PU}{\9041\333}%* U+21DB
18320 % U+21DC LEFTWARDS SQUIGGLE ARROW; \leftsquigarrow (mathabx)
18321 \DeclareTextCommand{\textleftsquigarrow}{PU}{\9041\334}%* U+21DC
18322 % U+21DD RIGHTWARDS SQUIGGLE ARROW; \rightsquigarrow (mathabx)
18323 \DeclareTextCommand{\textright squigarrow}{PU}{\9041\335}%* U+21DD
18324 % U+21E0 LEFTWARDS DASHED ARROW; arrowdashleft;
18325 % \dashleftarrow (AmS)
18326 \DeclareTextCommand{\texdashleftarrow}{PU}{\9041\340}%* U+21E0
18327 %* \texdashleftarrow -> \dashedleftarrow (MnSymbol)
18328 % U+21E1 UPWARDS DASHED ARROW; arrowdashup; \dasheduparrow (Mn-
Symbol)
18329 \DeclareTextCommand{\texdasheduparrow}{PU}{\9041\341}%* U+21E1
18330 % U+21E2 RIGHTWARDS DASHED ARROW; arrowdashright; \dashrightar-
row (AmS)
18331 \DeclareTextCommand{\texdashrightarrow}{PU}{\9041\342}%* U+21E2
18332 %* \texdashrightarrow -> \dashedrightarrow (MnSymbol)
18333 % U+21E3 DOWNWARDS DASHED ARROW; arrowdashdown; \dasheddownar-
row (MnSymbol)
18334 \DeclareTextCommand{\texdasheddownarrow}{PU}{\9041\343}%* U+21E3
18335 % U+21E8 RIGHTWARDS WHITE ARROW; \pointer (wasysym)
18336 \DeclareTextCommand{\textpointer}{PU}{\9041\350}%* U+21E8
18337 % U+21F5 DOWNWARDS ARROW LEFTWARDS OF UPWARDS ARROW;
18338 % \downuparrows (MnSymbol)
18339 \DeclareTextCommand{\texdownuparrows}{PU}{\9041\365}%* U+21F5
18340 % U+21FD LEFTWARDS OPEN-HEADED ARROW; \leftarrowtriangle (stmaryrd)
18341 \DeclareTextCommand{\textleftarrowtriangle}{PU}{\9041\375}%* U+21FD
18342 % U+21FE RIGHTWARDS OPEN-HEADED ARROW; \rightarrowtriangle (stmaryrd)
18343 \DeclareTextCommand{\textrightarrowtriangle}{PU}{\9041\376}%* U+21FE
18344 % U+21FF LEFT RIGHT OPEN-HEADED ARROW; \leftrightharrowtrian-
gle (stmaryrd)
18345 \DeclareTextCommand{\textleftrightharrowtriangle}{PU}{\9041\377}%* U+21FF

```

51.2.22 Mathematical Operators: U+2200 to U+22FF

```

18346 % U+2200 FOR ALL; forall; \forall (LaTeX)
18347 \DeclareTextCommand{\textforall}{PU}{\9042\000}%* U+2200
18348 % U+2201 COMPLEMENT; \complement (AmS)
18349 \DeclareTextCommand{\textcomplement}{PU}{\9042\001}%* U+2201
18350 % U+2202 PARTIAL DIFFERENTIAL; partialdiff; \partial (LaTeX)
18351 \DeclareTextCommand{\textpartial}{PU}{\9042\002}%* U+2202
18352 % U+2203 THERE EXISTS; existential; \exists (LaTeX)
18353 \DeclareTextCommand{\textexists}{PU}{\9042\003}%* U+2203
18354 % U+2204 THERE DOES NOT EXIST; \nexists (AmS)
18355 \DeclareTextCommand{\textnexists}{PU}{\9042\004}%* U+2204
18356 % U+2205 EMPTY SET; emptyset; \emptyset (LaTeX), \varnothing (AmS)
18357 \DeclareTextCommand{\textemptyset}{PU}{\9042\005}%* U+2205
18358 %* \textemptyset -> \varnothing (AmS)
18359 % U+2206 INCREMENT; increment, Deta; \triangle (LaTeX)
18360 \DeclareTextCommand{\texttriangle}{PU}{\9042\006}%* U+2206
18361 % U+2207 NABLA; nabla, gradient; \nabla (LaTeX)
18362 \DeclareTextCommand{\textnabla}{PU}{\9042\007}%* U+2207
18363 % U+2208 ELEMENT OF; element; \in (LaTeX)
18364 \DeclareTextCommand{\textin}{PU}{\9042\010}%* U+2208

```

18365 % U+2209 NOT AN ELEMENT OF; notelement, notelementof; \notin (LaTeX)
18366 \DeclareTextCommand{\textnotin}{PU}{\9042\011}%* U+2209
18367 % U+220A SMALL ELEMENT OF; \smallin (mathdesign)
18368 \DeclareTextCommand{\textsmallin}{PU}{\9042\012}%* U+220A
18369 % U+220B CONTAINS AS MEMBER; suchthat; \ni (LaTeX)
18370 \DeclareTextCommand{\textni}{PU}{\9042\013}%* U+220B
18371 %* \textni -> \owns (mathabx)
18372 % U+220C DOES NOT CONTAIN AS MEMBER; \notowner (mathabx)
18373 \DeclareTextCommand{\textnotowner}{PU}{\9042\014}%* U+220C
18374 %* \textnotowner -> \notni (txfonts/pxfonts)
18375 % U+220D SMALL CONTAINS AS MEMBER; \smallowns (mathdesign)
18376 \DeclareTextCommand{\textsmallowns}{PU}{\9042\015}%* U+220D
18377 % U+220F N-ARY PRODUCT; \prod (LaTeX)
18378 \DeclareTextCommand{\textprod}{PU}{\9042\017}%* U+220F
18379 % U+2210 N-ARY COPRODUCT; \amalg (LaTeX)
18380 \DeclareTextCommand{\textamalg}{PU}{\9042\020}%* U+2210
18381 % U+2211 N-ARY SUMMATION; summation; \sum (LaTeX)
18382 \DeclareTextCommand{\textsum}{PU}{\9042\021}%* U+2211
18383 % U+2212 MINUS SIGN; minus
18384 \DeclareTextCommand{\textminus}{PU}{\9042\022}% U+2212
18385 % U+2213 MINUS-OR-PLUS SIGN; minusplus; \mp (LaTeX)
18386 \DeclareTextCommand{\textmp}{PU}{\9042\023}%* U+2213
18387 % U+2214 DOT PLUS; \dotplus (AmS)
18388 \DeclareTextCommand{\textdotplus}{PU}{\9042\024}%* U+2214
18389 % U+2215 DIVISION SLASH; divisionslash; \Divides (marvosym)
18390 \DeclareTextCommand{\textDivides}{PU}{\9042\025}%* U+2215
18391 % \DividesNot (marvosym)
18392 \DeclareTextCommand{\textDividesNot}{PU}{\9042\025\9040\322}%* U+2215 U+20D2
18393 % U+2216 SET MINUS; \setminus (LaTeX)
18394 \DeclareTextCommand{\textsetminus}{PU}{\9042\026}%* U+2216
18395 % U+2217 ASTERISK OPERATOR; asteriskmath; \ast (LaTeX)
18396 \DeclareTextCommand{\textast}{PU}{\9042\027}%* U+2217
18397 % U+2218 RING OPERATOR; \circ (LaTeX)
18398 \DeclareTextCommand{\textcirc}{PU}{\9042\030}%* U+2218
18399 % U+2219 BULLET OPERATOR; bulletoperator; \bullet (LaTeX)
18400 \DeclareTextCommand{\textbulletoperator}{PU}{\9042\031}% U+2219
18401 % U+221A SQUARE ROOT; radical
18402 \DeclareTextCommand{\textsqrt}{PU}{\9042\032}%* U+221A
18403 % U+221D PROPORTIONAL TO; proportional; \propto (LaTeX)
18404 \DeclareTextCommand{\textpropto}{PU}{\9042\035}%* U+221D
18405 %* \textpropto -> \varprop (wasysym)
18406 % U+221E INFINITY; infinity; \infty (LaTeX)
18407 \DeclareTextCommand{\textinfty}{PU}{\9042\036}%* U+221E
18408 % U+2220 ANGLE; angle; \angle (LaTeX)
18409 \DeclareTextCommand{\textangle}{PU}{\9042\040}%* U+2220
18410 % U+2221 MEASURED ANGLE; \measuredangle (mathabx, MnSymbol)
18411 \DeclareTextCommand{\textmeasuredangle}{PU}{\9042\041}%* U+2221
18412 % U+2222 SPHERICAL ANGLE; \sphericalangle (AmS)
18413 \DeclareTextCommand{\textsphericalangle}{PU}{\9042\042}%* U+2222
18414 %* \textsphericalangle -> \varangle (wasysym)
18415 %* \textsphericalangle -> \Anglesign (marvosym)
18416 %* \textsphericalangle -> \AngleSign (marvosym)
18417 % U+2223 DIVIDES; divides; \mid (LaTeX)
18418 \DeclareTextCommand{\textmid}{PU}{\9042\043}%* U+2223
18419 % U+2224 DOES NOT DIVIDE; \nmid (AmS)
18420 \DeclareTextCommand{\textnmid}{PU}{\9042\044}%* U+2224
18421 %* \textnmid -> \notdivides (mathabx)

18422 % U+2225 PARALLEL TO; parallel; \parallel (LaTeX)
18423 \DeclareTextCommand{\textparallel}{PU}{\9042\045}%* U+2225
18424 % U+2226 NOT PARALLEL TO; notparallel; \nparallel (AmS)
18425 \DeclareTextCommand{\textnparallel}{PU}{\9042\046}%* U+2226
18426 %* \textnparallel -> nUpdownline (MnSymbol)
18427 % U+2227 LOGICAL AND; logicaland; \wedge (LaTeX)
18428 \DeclareTextCommand{\textwedge}{PU}{\9042\047}%* U+2227
18429 % \owedge (stmaryrd)
18430 \DeclareTextCommand{\textowedge}{PU}{\9042\047\9040\335}%* U+2227 U+20DD
18431 %* \textowedge -> \varowedge (stmaryrd)
18432 % U+2228 LOGICAL OR; logicalor; \vee (LaTeX)
18433 \DeclareTextCommand{\textvee}{PU}{\9042\050}%* U+2228
18434 % \ovee (stmaryrd)
18435 \DeclareTextCommand{\textovee}{PU}{\9042\050\9040\335}%* U+2228 U+20DD
18436 %* \textovee -> \varovee (stmaryrd)
18437 % U+2229 INTERSECTION; intersection; \cap (LaTeX)
18438 \DeclareTextCommand{\textcap}{PU}{\9042\051}%* U+2229
18439 % U+222A UNION; union; \cup (LaTeX)
18440 \DeclareTextCommand{\textcup}{PU}{\9042\052}%* U+222A
18441 % U+222B INTEGRAL; integral; \int (LaTeX)
18442 \DeclareTextCommand{\textint}{PU}{\9042\053}%* U+222B
18443 %* \textint -> \varint (wasysym)
18444 % U+222C DOUBLE INTEGRAL; dblintegral; \iint (AmS)
18445 \DeclareTextCommand{\textiint}{PU}{\9042\054}%* U+222C
18446 % U+222D TRIPLE INTEGRAL; \iiint (AmS)
18447 \DeclareTextCommand{\textiiint}{PU}{\9042\055}%* U+222D
18448 % U+222E CONTOUR INTEGRAL; contourintegral; \oint (LaTeX)
18449 \DeclareTextCommand{\textoint}{PU}{\9042\056}%* U+222E
18450 %* \textoint -> \varoint (wasysym)
18451 % U+222F SURFACE INTEGRAL; \oiint (wasysym)
18452 \DeclareTextCommand{\textoiint}{PU}{\9042\057}%* U+222F
18453 % U+2232 CLOCKWISE CONTOUR INTEGRAL;
18454 % \ointclockwise (txfonts/pxfonts)
18455 \DeclareTextCommand{\textointclockwise}{PU}{\9042\062}%* U+2232
18456 % U+2233 ANTICLOCKWISE CONTOUR INTEGRAL; \ointctrackwise (tx-
font/pxfonts)
18457 \DeclareTextCommand{\textointctrackwise}{PU}{\9042\063}%* U+2233
18458 % U+2234 THEREFORE; therefore; \therefore (AmS)
18459 \DeclareTextCommand{\texttherefore}{PU}{\9042\064}%* U+2234
18460 %* \texttherefore -> uptherefore (MnSymbol)
18461 % U+2235 BECAUSE; because; \because (AmS)
18462 \DeclareTextCommand{\textbecause}{PU}{\9042\065}%* U+2235
18463 %* \textbecause -> \downtherefore (MnSymbol)
18464 % U+2236 RATIO; \vdotdot (MnSymbol)
18465 \DeclareTextCommand{\textvdotdot}{PU}{\9042\066}%* U+2236
18466 % U+2237 PROPORTION; \squaredots (MnSymbol)
18467 \DeclareTextCommand{\textsquaredots}{PU}{\9042\067}%* U+2237
18468 % U+2238 DOT MINUS; \dotminus (MnSymbol)
18469 \DeclareTextCommand{\textdotminus}{PU}{\9042\070}%* U+2238
18470 %* \textdotminus -> \textdotdiv (mathabx)
18471 % U+2239 EXCESS; \eqcolon (txfonts/pxfonts)
18472 \DeclareTextCommand{\texteqcolon}{PU}{\9042\071}%* U+2239
18473 % U+223C TILDE OPERATOR; similar; \sim (LaTeX)
18474 \DeclareTextCommand{\textsim}{PU}{\9042\074}%* U+223C
18475 %* \textsim -> \AC (wasysym)
18476 % U+223D REVERSED TILDE; reversedtilde; \backsim (AmS)
18477 \DeclareTextCommand{\textbacksim}{PU}{\9042\075}%* U+223D

18478 % \nbacksim (txfonts/pxfonts)
18479 \DeclareTextCommand{\textnbacksim}{PU}{\9042\075\83\070}%* U+223D U+0338
18480 % U+2240 WREATH PRODUCT; \wr (LaTeX)
18481 \DeclareTextCommand{\textwr}{PU}{\9042\100}%* U+2240
18482 %* \textwr -> \wreath (MnSymbol)
18483 % U+2241 NOT TILDE; \nsim (AmS)
18484 \DeclareTextCommand{\textnsim}{PU}{\9042\101}%* U+2241
18485 % U+2242 MINUS TILDE; \eqsim (MnSymbol)
18486 \DeclareTextCommand{\texteqsim}{PU}{\9042\102}%* U+2242
18487 % \neqsim (MnSymbol)
18488 \DeclareTextCommand{\textneqsim}{PU}{\9042\102\83\070}%* U+2242 U+0338
18489 % U+2243 ASYMPTOTICALLY EQUAL TO; asymptoticallyequal; \simeq (LaTeX)
18490 \DeclareTextCommand{\textsimeq}{PU}{\9042\103}%* U+2243
18491 % U+2244 NOT ASYMPTOTICALLY EQUAL TO; \nsimeq (txfonts/pxfonts)
18492 \DeclareTextCommand{\textnsimeq}{PU}{\9042\104}%* U+2244
18493 % U+2245 APPROXIMATELY EQUAL TO; approximatelyequal; \cong (LaTeX)
18494 \DeclareTextCommand{\textcong}{PU}{\9042\105}%* U+2245
18495 % U+2247 NEITHER APPROXIMATELY NOR ACTUALLY EQUAL TO;
18496 % \ncong (AmS)
18497 \DeclareTextCommand{\textncong}{PU}{\9042\107}%* U+2247
18498 % U+2248 ALMOST EQUAL TO; approxequal; \approx (LaTeX)
18499 \DeclareTextCommand{\textapprox}{PU}{\9042\110}%* U+2248
18500 % U+2249 NOT ALMOST EQUAL TO; \napprox (txfonts/pxfonts)
18501 \DeclareTextCommand{\textnapprox}{PU}{\9042\111}%* U+2249
18502 %* \textnapprox -> \nthickapprox (txfonts/pxfonts)
18503 % U+224A ALMOST EQUAL OR EQUAL TO; \approxeq (AmS)
18504 \DeclareTextCommand{\textapproxeq}{PU}{\9042\112}%* U+224A
18505 % \napproxeq (txfonts/pxfonts)
18506 \DeclareTextCommand{\textnapproxeq}{PU}{\9042\112\83\070}%* U+224A U+0338
18507 % U+224B TRIPLE TILDE; \triplesim (MnSymbol)
18508 \DeclareTextCommand{\texttriplesim}{PU}{\9042\113}%* U+224B
18509 %* \texttriplesim -> \VHF (wasysym)
18510 % \ntriplesim (MnSymbol)
18511 \DeclareTextCommand{\textntriplesim}{PU}{\9042\113\83\070}%* U+224B U+0338
18512 % U+224C ALL EQUAL TO; allequal; \backcong (MnSymbol)
18513 \DeclareTextCommand{\textbackcong}{PU}{\9042\114}%* U+224C
18514 % \nbackcong (MnSymbol)
18515 \DeclareTextCommand{\textnbackcong}{PU}{\9042\114\83\070}%* U+224C U+0338
18516 % U+224D EQUIVALENT TO; \asymp (LaTeX)
18517 \DeclareTextCommand{\textasymp}{PU}{\9042\115}%* U+224D
18518 % \nasymp (txfonts/pxfonts)
18519 \DeclareTextCommand{\textnasymp}{PU}{\9042\115\83\070}%* U+224D U+0338
18520 %* \textnasymp -> \notasympt (mathabx)
18521 % U+224E GEOMETRICALLY EQUIVALENT TO; \Bumpeq (AmS)
18522 \DeclareTextCommand{\textBumpeq}{PU}{\9042\116}%* U+224E
18523 % \nBumpeq (txfonts/pxfonts)
18524 \DeclareTextCommand{\textnBumpeq}{PU}{\9042\116\83\070}%* U+224E U+0338
18525 % U+224F DIFFERENCE BETWEEN; \bumpeq (AmS)
18526 \DeclareTextCommand{\textbumpeq}{PU}{\9042\117}%* U+224F
18527 % \nbumpeq (txfonts/pxfonts)
18528 \DeclareTextCommand{\textnbumpeq}{PU}{\9042\117\83\070}%* U+224F U+0338
18529 % U+2250 APPROACHES THE LIMIT; approaches; \doteq (LaTeX)
18530 \DeclareTextCommand{\textdoteq}{PU}{\9042\120}%* U+2250
18531 % \ndoteq (MnSymbol)
18532 \DeclareTextCommand{\textndoteq}{PU}{\9042\120\83\070}%* U+2250 U+0338
18533 % U+2251 GEOMETRICALLY EQUAL TO; geometricallyequal;

```

18534 % \doteqdot (AmS)
18535 \DeclareTextCommand{\textdoteqdot}{PU}{\9042\121}%* U+2251
18536 %* \textdoteqdot -> \Doteq (MnSymbol)
18537 % \nDoteq (MnSymbol)
18538 \DeclareTextCommand{\textnDoteq}{PU}{\9042\121\83\070}%* U+2251 U+0338
18539 % U+2252 APPROXIMATELY EQUAL TO OR THE IMAGE OF; approx-
qualorimage;
18540 % \fallingdotseq (AmS)
18541 \DeclareTextCommand{\textfallingdotseq}{PU}{\9042\122}%* U+2252
18542 % \nfallingdotseq (MnSymbol)
18543 \DeclareTextCommand{\textnfallingdotseq}{PU}{\9042\122\83\070}%* U+2252 U+0338
18544 % U+2253 IMAGE OF OR APPROXIMATELY EQUAL TO; imageorapprox-
imatelyequal;
18545 % \risingdotseq (AmS)
18546 \DeclareTextCommand{\textrisingdotseq}{PU}{\9042\123}%* U+2253
18547 % \nrisingdotseq (MnSymbol)
18548 \DeclareTextCommand{\textnrisingdotseq}{PU}{\9042\123\83\070}%* U+2253 U+0338
18549 % U+2254 COLON EQUALS; \colonequals (colonequals)
18550 \DeclareTextCommand{\textcolonequals}{PU}{\9042\124}%* U+2254
18551 % U+2255 EQUALS COLON; \equalscolon (colonequals)
18552 \DeclareTextCommand{\textequalscolon}{PU}{\9042\125}%* U+2255
18553 % U+2256 RING IN EQUAL TO; \eqcirc (AmS)
18554 \DeclareTextCommand{\texteqcirc}{PU}{\9042\126}%* U+2256
18555 % \neqcirc (MnSymbol)
18556 \DeclareTextCommand{\textneqcirc}{PU}{\9042\126\83\070}%* U+2256 U+0338
18557 % U+2257 RING EQUAL TO; \circeq (AmS)
18558 \DeclareTextCommand{\textcirceq}{PU}{\9042\127}%* U+2257
18559 % \ncirceq (MnSymbol)
18560 \DeclareTextCommand{\textncirceq}{PU}{\9042\127\83\070}%* U+2257 U+0338
18561 % U+2259 ESTIMATES; \hateq (MnSymbol)
18562 \DeclareTextCommand{\texthateq}{PU}{\9042\131}%* U+2259
18563 %* \texthateq -> \corresponds (mathabx)
18564 %* \texthateq -> \Corresponds (marvosym)
18565 % \nhateq (MnSymbol)
18566 \DeclareTextCommand{\textnhateq}{PU}{\9042\131\83\070}%* U+2259 U+0338
18567 % U+225C DELTA EQUAL TO; \triangleeq (AmS)
18568 \DeclareTextCommand{\texttriangleeq}{PU}{\9042\134}%* U+225C
18569 % U+2260 NOT EQUAL TO; notequal; \ne (LaTeX), \neq (LaTeX)
18570 \DeclareTextCommand{\textneq}{PU}{\9042\140}%* U+2260
18571 \DeclareTextCommand{\textne}{PU}{\9042\140}%* U+2260
18572 %* \textneq -> \nequal (MnSymbol)
18573 % U+2261 IDENTICAL TO; equivalence; \equiv (LaTeX)
18574 \DeclareTextCommand{\textequiv}{PU}{\9042\141}%* U+2261
18575 %* \textequiv -> \Congruent (marvosym)
18576 % U+2262 NOT IDENTICAL TO; notidentical; \nequiv (txfonts/pxfonts)
18577 \DeclareTextCommand{\textnequiv}{PU}{\9042\142}%* U+2262
18578 %* \textnequiv -> \NotCongruent (marvosym)
18579 %* \textnequiv -> \notequiv (mathabx)
18580 % U+2264 LESS-THAN OR EQUAL TO; lessequal; \le (LaTeX), \leq (LaTeX)
18581 \DeclareTextCommand{\textleq}{PU}{\9042\144}%* U+2264
18582 \DeclareTextCommand{\textle}{PU}{\9042\144}%* U+2264
18583 %* \textleq -> \LessOrEqual (marvosym)
18584 % U+2265 GREATER-THAN OR EQUAL TO; greaterequal;
18585 % \ge (LaTeX), \geq (LaTeX)
18586 \DeclareTextCommand{\textgeq}{PU}{\9042\145}%* U+2265
18587 \DeclareTextCommand{\textge}{PU}{\9042\145}%* U+2265
18588 %* \textgeq -> \LargerOrEqual (marvosym)

```

18589 % U+2266 LESS-THAN OVER EQUAL TO; lessorequal; \leqq (AmS)
18590 \DeclareTextCommand{\textleqq}{PU}{\9042\146}%* U+2266
18591 % \leqq (txfonts/pxfonts)
18592 \DeclareTextCommand{\textnleqq}{PU}{\9042\146\83\070}%* U+2266 U+0338
18593 % U+2267 GREATER-THAN OVER EQUAL TO; greaterorequal; \geqq (AmS)
18594 \DeclareTextCommand{\textgeqq}{PU}{\9042\147}%* U+2267
18595 % \ngeqq (txfonts/pxfonts)
18596 \DeclareTextCommand{\textngeqq}{PU}{\9042\147\83\070}%* U+2267 U+0338
18597 % U+2268 LESS-THAN BUT NOT EQUAL TO; \lneqq (AmS)
18598 \DeclareTextCommand{\textlneqq}{PU}{\9042\150}%* U+2268
18599 % U+2269 GREATER-THAN BUT NOT EQUAL TO; \gneqq (AmS)
18600 \DeclareTextCommand{\textgneqq}{PU}{\9042\151}%* U+2269
18601 % U+226A MUCH LESS-THAN; muchless; \ll (LaTeX)
18602 \DeclareTextCommand{\textll}{PU}{\9042\152}%* U+226A
18603 % \ll (txfonts/pxfonts)
18604 \DeclareTextCommand{\textnll}{PU}{\9042\152\83\070}%* U+226A U+0338
18605 % U+226B MUCH GREATER-THAN; muchgreater; \gg (LaTeX)
18606 \DeclareTextCommand{\textgg}{PU}{\9042\153}%* U+226B
18607 % \ngg (txfonts/pxfonts)
18608 \DeclareTextCommand{\textngg}{PU}{\9042\153\83\070}%* U+226B U+0338
18609 % U+226C BETWEEN; \between (AmS)
18610 \DeclareTextCommand{\textbetween}{PU}{\9042\154}%* U+226C
18611 % U+226E NOT LESS-THAN; notless; \nless (AmS)
18612 \DeclareTextCommand{\textnless}{PU}{\9042\156}%* U+226E
18613 % U+226F NOT GREATER-THAN; notgreater; \ngtr (AmS)
18614 \DeclareTextCommand{\textngtr}{PU}{\9042\157}%* U+226F
18615 % U+2270 NEITHER LESS-THAN NOR EQUAL TO; notlessnorequal;
18616 % \nleq (AmS)
18617 \DeclareTextCommand{\textnleq}{PU}{\9042\160}%* U+2270
18618 % U+2271 NEITHER GREATER-THAN NOR EQUAL TO; notgreaternorequal;
18619 \DeclareTextCommand{\textngeq}{PU}{\9042\161}%* U+2271
18620 % U+2272 LESS-THAN OR EQUIVALENT TO; lessorequivalent; \lessim (AmS)
18621 \DeclareTextCommand{\textlessim}{PU}{\9042\162}%* U+2272
18622 %* \textlessim -> \apprle (wasysym)
18623 % U+2273 GREATER-THAN OR EQUIVALENT TO; greaterorequivalent; \gtrsim (AmS)
18624 \DeclareTextCommand{\textgtrsim}{PU}{\9042\163}%* U+2273
18625 %* \textgtrsim -> \apprge (wasysym)
18626 % U+2274 NEITHER LESS-THAN NOR EQUIVALENT TO; \nlessim (txfonts/pxfonts)
18627 \DeclareTextCommand{\textnlessim}{PU}{\9042\164}%* U+2274
18628 % U+2275 NEITHER GREATER-THAN NOR EQUIVALENT TO; \ngtrsim (txfonts/pxfonts)
18629 \DeclareTextCommand{\textngtrsim}{PU}{\9042\165}%* U+2275
18630 % U+2276 LESS-THAN OR GREATER-THAN; lessorgreater; \lessgtr (AmS)
18631 \DeclareTextCommand{\textlessgtr}{PU}{\9042\166}%* U+2276
18632 % U+2277 GREATER-THAN OR LESS-THAN; greaterorless; \gtrless (AmS)
18633 \DeclareTextCommand{\textgtrless}{PU}{\9042\167}%* U+2277
18634 % U+2278 NEITHER LESS-THAN NOR GREATER-THAN; \ngtrless (txfonts/pxfonts)
18635 \DeclareTextCommand{\textngtrless}{PU}{\9042\170}%* U+2278
18636 % U+2279 NEITHER GREATER-THAN NOR LESS-THAN; \nlessgtr (txfonts/pxfonts)
18637 \DeclareTextCommand{\textnlessgtr}{PU}{\9042\171}%* U+2279
18638 % U+227A PRECEDES; precedes; \prec (LaTeX)
18639 \DeclareTextCommand{\textprec}{PU}{\9042\172}%* U+227A

18640 % U+227B SUCCEEDS; succeeds; \succ (LaTeX)
18641 \DeclareTextCommand{\textsucc}{PU}{\9042\173}%* U+227B
18642 % U+227C PRECEDES OR EQUAL TO; \preccurlyeq (AmS)
18643 \DeclareTextCommand{\textpreccurlyeq}{PU}{\9042\174}%* U+227C
18644 % U+227D SUCCEEDS OR EQUAL TO; \succcurlyeq (AmS)
18645 \DeclareTextCommand{\textsucccurlyeq}{PU}{\9042\175}%* U+227D
18646 % U+227E PRECEDES OR EQUIVALENT TO; \precsim (AmS)
18647 \DeclareTextCommand{\textprecsim}{PU}{\9042\176}%* U+227E
18648 % \nprecsim (txfonts/pxfonts)
18649 \DeclareTextCommand{\textnprecsim}{PU}{\9042\176\83\070}%* U+227E U+0338
18650 % U+227F SUCCEEDS OR EQUIVALENT TO; \succsim (AmS)
18651 \DeclareTextCommand{\textsuccsim}{PU}{\9042\177}%* U+227F
18652 % \nsuccsim (txfonts/pxfonts)
18653 \DeclareTextCommand{\textnsuccsim}{PU}{\9042\177\83\070}%* U+227F U+0338
18654 % U+2280 DOES NOT PRECEDE; notprecedes; \nprec (AmS)
18655 \DeclareTextCommand{\textnprec}{PU}{\9042\200}%* U+2280
18656 % U+2281 DOES NOT SUCCEED; notsucceds; \nsucc (AmS)
18657 \DeclareTextCommand{\textnsucc}{PU}{\9042\201}%* U+2281
18658 % U+2282 SUBSET OF; propersubset; \subset (LaTeX)
18659 \DeclareTextCommand{\textsubset}{PU}{\9042\202}%* U+2282
18660 % U+2283 SUPERSET OF; propersuperset; \supset (LaTeX)
18661 \DeclareTextCommand{\textsupset}{PU}{\9042\203}%* U+2283
18662 % U+2284 NOT A SUBSET OF; notsubset; \nsubset (mathabx)
18663 \DeclareTextCommand{\textnsubset}{PU}{\9042\204}%* U+2284
18664 % U+2285 NOT A SUPERSET OF; notsuperset; \nsupset (mathabx)
18665 \DeclareTextCommand{\textnsupset}{PU}{\9042\205}%* U+2285
18666 % U+2286 SUBSET OF OR EQUAL TO; reflexsubset; \subsetq (LaTeX)
18667 \DeclareTextCommand{\textsubsetq}{PU}{\9042\206}%* U+2286
18668 % U+2287 SUPERSET OF OR EQUAL TO; reflexsuperset; \supsetq (LaTeX)
18669 \DeclareTextCommand{\textsupsetq}{PU}{\9042\207}%* U+2287
18670 % U+2288 NEITHER A SUBSET OF NOR EQUAL TO; \nsubsetq (AmS)
18671 \DeclareTextCommand{\textnsubsetq}{PU}{\9042\210}%* U+2288
18672 % U+2289 NEITHER A SUPERSET OF NOR EQUAL TO; \nsupsetq (AmS)
18673 \DeclareTextCommand{\textnsupsetq}{PU}{\9042\211}%* U+2289
18674 % U+228A SUBSET OF WITH NOT EQUAL TO; subsetnotequal; \subset-
neq (AmS)
18675 \DeclareTextCommand{\textsubsetneq}{PU}{\9042\212}%* U+228A
18676 % U+228B SUPERSET OF WITH NOT EQUAL TO; supersetnotequal; \supset-
neq (AmS)
18677 \DeclareTextCommand{\textsupsetneq}{PU}{\9042\213}%* U+228B
18678 % U+228D MULTISSET MULTIPLICATION; \cupdot (MnSymbol)
18679 \DeclareTextCommand{\textcupdot}{PU}{\9042\215}%* U+228D
18680 % U+228E MULTISSET UNION; \cupplus (MnSymbol)
18681 \DeclareTextCommand{\textcupplus}{PU}{\9042\216}%* U+228E
18682 % U+228F SQUARE IMAGE OF; \sqsubset (latexsym, ...)
18683 \DeclareTextCommand{\textsqsubset}{PU}{\9042\217}%* U+228F
18684 % \nsqsubset (txfonts/pxfonts)
18685 \DeclareTextCommand{\textnsqsubset}{PU}{\9042\217\83\070}%* U+228F U+0338
18686 % U+2290 SQUARE ORIGINAL OF; \sqsupset (latexsym, ...)
18687 \DeclareTextCommand{\textsqsupset}{PU}{\9042\220}%* U+2290
18688 % \nsqsupset (txfonts/pxfonts)
18689 \DeclareTextCommand{\textnsqsupset}{PU}{\9042\220\83\070}%* U+2290 U+0338
18690 % U+2291 SQUARE IMAGE OF OR EQUAL TO; \sqsubsetq (LaTeX)
18691 \DeclareTextCommand{\textsqsubsetq}{PU}{\9042\221}%* U+2291
18692 % \nsqsubsetq (txfonts/pxfonts)
18693 \DeclareTextCommand{\textnsqsubsetq}{PU}{\9042\221\83\070}%* U+2291 U+0338
18694 % U+2292 SQUARE ORIGINAL OF OR EQUAL TO; \sqsupsetq (LaTeX)

```

18695 \DeclareTextCommand{\textsqsupseteq}{PU}{\9042\222}%* U+2292
18696 % \nsqsupseteq (txfonts/pxfonts)
18697 \DeclareTextCommand{\textnsqsupseteq}{PU}{\9042\222\83\070}%* U+2292 U+0338
18698 % U+2293 SQUARE CAP; \sqcap (LaTeX)
18699 \DeclareTextCommand{\textsqcap}{PU}{\9042\223}%* U+2293
18700 % U+2294 SQUARE CUP; \sqcup (LaTeX)
18701 \DeclareTextCommand{\textsqcup}{PU}{\9042\224}%* U+2294
18702 % U+2295 CIRCLED PLUS; circleplus; \oplus (LaTeX)
18703 \DeclareTextCommand{\textoplus}{PU}{\9042\225}%* U+2295
18704 %* \textoplus -> \varoplus (stmaryrd)
18705 % U+2296 CIRCLED MINUS; minuscircle; \ominus (LaTeX)
18706 \DeclareTextCommand{\textominus}{PU}{\9042\226}%* U+2296
18707 %* \textominus -> \varominus (stmaryrd)
18708 % U+2297 CIRCLED TIMES; circlemultiply; \otimes (LaTeX)
18709 \DeclareTextCommand{\textotimes}{PU}{\9042\227}%* U+2297
18710 %* \textotimes -> \varotimes (stmaryrd)
18711 % U+2298 CIRCLED DIVISION SLASH; \oslash (LaTeX)
18712 \DeclareTextCommand{\textoslash}{PU}{\9042\230}%* U+2298
18713 %* \textoslash -> \varoslash (stmaryrd)
18714 % U+2299 CIRCLED DOT OPERATOR; circle(d?)ot; \odot (LaTeX)
18715 \DeclareTextCommand{\textodot}{PU}{\9042\231}%* U+2299
18716 %* \textodot -> \varodot (stmaryrd)
18717 % U+229A CIRCLED RING OPERATOR; \circledcirc (AmS)
18718 \DeclareTextCommand{\textcircledcirc}{PU}{\9042\232}%* U+229A
18719 %* \textcircledcirc -> \ocirc (mathabx)
18720 %* \textcircledcirc -> \varocircle (stmaryrd)
18721 % U+229B CIRCLED ASTERISK OPERATOR; \circledast (AmS)
18722 \DeclareTextCommand{\textcircledast}{PU}{\9042\233}%* U+229B
18723 %* \textcircledast -> \varoast (stmaryrd)
18724 %* \textcircledast -> \oasterisk (mathabx)
18725 % U+229D CIRCLED DASH; \circleddash (AmS)
18726 \DeclareTextCommand{\textcircleddash}{PU}{\9042\235}%* U+229D
18727 % U+229E SQUARED PLUS; \boxplus (AmS)
18728 \DeclareTextCommand{\textboxplus}{PU}{\9042\236}%* U+229E
18729 % U+229F SQUARED MINUS; \boxminus (AmS)
18730 \DeclareTextCommand{\textboxminus}{PU}{\9042\237}%* U+229F
18731 % U+22A0 SQUARED TIMES; \boxtimes (AmS)
18732 \DeclareTextCommand{\textboxtimes}{PU}{\9042\240}%* U+22A0
18733 % U+22A1 SQUARED DOT OPERATOR; \boxdot (AmS)
18734 \DeclareTextCommand{\textboxdot}{PU}{\9042\241}%* U+22A1
18735 % U+22A2 RIGHT TACK; \vdash (LaTeX)
18736 \DeclareTextCommand{\textvdash}{PU}{\9042\242}%* U+22A2
18737 %* \textvdash -> \rightvdash (MnSymbol)
18738 % U+22A3 LEFT TACK; \dashv (LaTeX)
18739 \DeclareTextCommand{\textdashv}{PU}{\9042\243}%* U+22A3
18740 %* \textdashv -> \leftvdash (MnSymbol)
18741 %* \ndashv (mathabx)
18742 \DeclareTextCommand{\textndashv}{PU}{\9042\243\83\070}%* U+22A3 U+0338
18743 %* \textndashv -> \nleftvdash (MnSymbol)
18744 % U+22A4 DOWN TACK (=top); tackdown; \top (LaTeX)
18745 \DeclareTextCommand{\texttop}{PU}{\9042\244}%* U+22A4
18746 %* \texttop -> \downvdash (MnSymbol)
18747 %* \ndownvdash (MnSymbol)
18748 \DeclareTextCommand{\textndownvdash}{PU}{\9042\244\83\070}%* U+22A4 U+0338
18749 % U+22A5 UP TACK (=base, bottom); \bot (LaTeX)
18750 \DeclareTextCommand{\textbot}{PU}{\9042\245}%* U+22A5
18751 %* \textbot -> \upvdash (MnSymbol)

```

```

18752 % \nupvdash (MnSymbol)
18753 \DeclareTextCommand{\textnupvdash}{PU}{\9042\245\83\070}%* U+22A5 U+0338
18754 %* \textnupvdash -> \nperp (MnSymbol)
18755 % U+22A8 TRUE; \vDash (AmS)
18756 \DeclareTextCommand{\textvDash}{PU}{\9042\250}%* U+22A8
18757 %* \textvDash -> \models (LaTeX)
18758 %* \textvDash -> \rightmodels (MnSymbol)
18759 % U+22A9 FORCES; \Vdash (AmS)
18760 \DeclareTextCommand{\textVdash}{PU}{\9042\251}%* U+22A9
18761 %* \textVdash -> \rightVdash (MnSymbol)
18762 % U+22AA TRIPLE VERTICAL BAR RIGHT TURNSTILE; \Vvdash (AmS)
18763 \DeclareTextCommand{\textVvdash}{PU}{\9042\252}%* U+22AA
18764 % \nVdash (mathabx)
18765 \DeclareTextCommand{\textnVdash}{PU}{\9042\252\83\070}%* U+22AA U+0338
18766 % U+22AB DOUBLE VERTICAL BAR DOUBLE RIGHT TURNSTILE;
18767 % \VDash (mathabx)
18768 \DeclareTextCommand{\textVDash}{PU}{\9042\253}%* U+22AB
18769 %* \textVDash -> \rightModels (MnSymbol)
18770 % U+22AC DOES NOT PROVE; \nvdash (AmS)
18771 \DeclareTextCommand{\textnvdash}{PU}{\9042\254}%* U+22AC
18772 %* \textnvdash -> \nrighvdash (MnSymbol)
18773 % U+22AD NOT TRUE; \nVDash (AmS)
18774 \DeclareTextCommand{\textnVDash}{PU}{\9042\255}%* U+22AD
18775 %* \textnVDash -> \nrighmodels (MnSymbol)
18776 %* \textnVDash -> \nmodels (MnSymbol)
18777 % U+22AE DOES NOT FORCE; \nVdash (txfonts/pxfonts)
18778 \DeclareTextCommand{\textnVdash}{PU}{\9042\256}%* U+22AE
18779 %* \textnVdash -> \nrighVdash (MnSymbol)
18780 % U+22AF NEGATED DOUBLE VERTICAL BAR DOUBLE RIGHT TURN-
      STILE; \nVDash (AmS)
18781 \DeclareTextCommand{\textnVDash}{PU}{\9042\257}%* U+22AF
18782 %* \textnVDash -> \nrighModels (MnSymbol)
18783 % U+22B2 NORMAL SUBGROUP OF; \lhd (latexsym, ...)
18784 \DeclareTextCommand{\textlhd}{PU}{\9042\262}%* U+22B2
18785 %* \textlhd -> \lessclosed (MnSymbol)
18786 % U+22B3 CONTAINS AS NORMAL SUBGROUP; \rhd (latexsym, ...)
18787 \DeclareTextCommand{\textrhd}{PU}{\9042\263}%* U+22B3
18788 %* \textrhd -> \gtrclosed (MnSymbol)
18789 % U+22B4 NORMAL SUBGROUP OF OR EQUAL TO; \unlhd (latexsym, ...)
18790 \DeclareTextCommand{\textunlhd}{PU}{\9042\264}%* U+22B4
18791 %* \textunlhd -> \leqclosed (MnSymbol)
18792 %* \textunlhd -> \trianglelefteq (MnSymbol)
18793 % U+22B5 CONTAINS AS NORMAL SUBGROUP OR EQUAL TO; \unrhd (la-
      texsym, ...)
18794 \DeclareTextCommand{\textunrhd}{PU}{\9042\265}%* U+22B5
18795 %* \textunrhd -> \geqclosed (MnSymbol)
18796 %* \textunrhd -> \trianglerighteq (MnSymbol)
18797 % U+22B6 ORIGINAL OF; \multimapdotbothA (txfonts/pxfonts)
18798 \DeclareTextCommand{\textmultimapdotbothA}{PU}{\9042\266}%* U+22B6
18799 % U+22B7 IMAGE OF; \multimapdotbothB (txfonts/pxfonts)
18800 \DeclareTextCommand{\textmultimapdotbothB}{PU}{\9042\267}%* U+22B7
18801 % U+22B8 MULTIMAP; \multimap (AmS, txfonts/pxfonts)
18802 \DeclareTextCommand{\textmultimap}{PU}{\9042\270}%* U+22B8
18803 % U+22BB XOR; \veebar (AmS)
18804 \DeclareTextCommand{\textveebar}{PU}{\9042\273}%* U+22BB
18805 % U+22BC NAND; \barwedge (mathabx)
18806 \DeclareTextCommand{\textbarwedge}{PU}{\9042\274}%* U+22BC

```

18807 % U+22C6 STAR OPERATOR; \star (LaTeX)
18808 \DeclareTextCommand{\textstar}{PU}{\9042\306}%* U+22C6
18809 % U+22C7 DIVISION TIMES; \divideontimes (AmS)
18810 \DeclareTextCommand{\textdivideontimes}{PU}{\9042\307}%* U+22C7
18811 % U+22C8 BOWTIE; \bowtie (LaTeX)
18812 \DeclareTextCommand{\textbowtie}{PU}{\9042\310}%* U+22C8
18813 %* \textbowtie -> \Bowtie (wasysym)
18814 % U+22C9 LEFT NORMAL FACTOR SEMIDIRECT PRODUCT; \ltimes (AmS)
18815 \DeclareTextCommand{\textltimes}{PU}{\9042\311}%* U+22C9
18816 % U+22CA RIGHT NORMAL FACTOR SEMIDIRECT PRODUCT;
18817 % \rtimes (AmS)
18818 \DeclareTextCommand{\textrtimes}{PU}{\9042\312}%* U+22CA
18819 % U+22CB LEFT SEMIDIRECT PRODUCT; \leftthreetimes (AmS)
18820 \DeclareTextCommand{\textleftthreetimes}{PU}{\9042\313}%* U+22CB
18821 % U+22CC RIGHT SEMIDIRECT PRODUCT; \rightthreetimes (AmS)
18822 \DeclareTextCommand{\textrightthreetimes}{PU}{\9042\314}%* U+22CC
18823 % U+22CD REVERSED TILDE EQUALS; \backsimeq (AmS)
18824 \DeclareTextCommand{\textbacksimeq}{PU}{\9042\315}%* U+22CD
18825 % \nbacksimeq (txfonts/pxfonts)
18826 \DeclareTextCommand{\textnbacksimeq}{PU}{\9042\315\83\070}%* U+22CD U+0338
18827 % U+22CE CURLY LOGICAL OR; curlyor; \curlyvee (AmS)
18828 \DeclareTextCommand{\textcurlyvee}{PU}{\9042\316}%* U+22CE
18829 %* \textcurlyvee -> \varcurlyvee (stmaryrd)
18830 % U+22CF CURLY LOGICAL AND; curlyand; \curlywedge (AmS)
18831 \DeclareTextCommand{\textcurlywedge}{PU}{\9042\317}%* U+22CF
18832 %* \textcurlywedge -> \varcurlywedge (stmaryrd)
18833 % U+22D0 DOUBLE SUBSET; \Subset (AmS)
18834 \DeclareTextCommand{\textSubset}{PU}{\9042\320}%* U+22D0
18835 % \nSubset (txfonts/pxfonts)
18836 \DeclareTextCommand{\textnSubset}{PU}{\9042\320\83\070}%* U+22D0 U+0338
18837 % U+22D1 DOUBLE SUPERSET; \Supset (AmS)
18838 \DeclareTextCommand{\textSupset}{PU}{\9042\321}%* U+22D1
18839 % \nSupset (txfonts/pxfonts)
18840 \DeclareTextCommand{\textnSupset}{PU}{\9042\321\83\070}%* U+22D1 U+0338
18841 % U+22D2 DOUBLE INTERSECTION; \Cap (AmS)
18842 \DeclareTextCommand{\textCap}{PU}{\9042\322}%* U+22D2
18843 %* \textCap -> \doublecap (mathabx)
18844 % U+22D3 DOUBLE UNION; \Cup (AmS)
18845 \DeclareTextCommand{\textCup}{PU}{\9042\323}%* U+22D3
18846 %* \textCup -> \doublecup (mathabx)
18847 % U+22D4 PITCHFORK; \pitchfork (mathabx)
18848 \DeclareTextCommand{\textpitchfork}{PU}{\9042\324}%* U+22D4
18849 % U+22D6 LESS-THAN WITH DOT; \lessdot (AmS)
18850 \DeclareTextCommand{\textlessdot}{PU}{\9042\326}%* U+22D6
18851 % U+22D7 GREATER-THAN WITH DOT; \gtrdot (AmS)
18852 \DeclareTextCommand{\textgtrdot}{PU}{\9042\327}%* U+22D7
18853 % U+22D8 VERY MUCH LESS-THAN; \lll (AmS)
18854 \DeclareTextCommand{\textlll}{PU}{\9042\330}%* U+22D8
18855 % U+22D9 VERY MUCH GREATER-THAN; \ggg (AmS)
18856 \DeclareTextCommand{\textggg}{PU}{\9042\331}%* U+22D9
18857 % U+22DA LESS-THAN EQUAL TO OR GREATER-THAN; lessequalorgreater;
18858 % \lesseqgtr (AmS)
18859 \DeclareTextCommand{\textlesseqgtr}{PU}{\9042\332}%* U+22DA
18860 % U+22DB GREATER-THAN EQUAL TO OR LESS-THAN; greaterqualorless;
18861 % \gtreqless (AmS)
18862 \DeclareTextCommand{\textgtreqless}{PU}{\9042\333}%* U+22DB
18863 % U+22DE EQUAL TO OR PRECEDES; \curlyeqprec (MnSymbol)


```

18864 \DeclareTextCommand{\textcurlyeqprec}{PU}{\9042\336}%* U+22DE
18865 % \ncurlyeqprec (mathabx)
18866 \DeclareTextCommand{\textncurlyeqprec}{PU}{\9042\336\83\070}%* U+22DE U+0338
18867 % U+22DF EQUAL TO OR SUCCEEDS; \curlyeqsucc (MnSymbol)
18868 \DeclareTextCommand{\textcurlyeqsucc}{PU}{\9042\337}%* U+22DF
18869 % \ncurlyeqsucc (mathabx)
18870 \DeclareTextCommand{\textncurlyeqsucc}{PU}{\9042\337\83\070}%* U+22DF U+0338
18871 % U+22E0 DOES NOT PRECEDE OR EQUAL; \npreccurlyeq (txfonts/pxfonts)
18872 \DeclareTextCommand{\textnpreccurlyeq}{PU}{\9042\340}%* U+22E0
18873 % U+22E1 DOES NOT SUCCEED OR EQUAL; \nsucccurlyeq (txfonts/pxfonts)
18874 \DeclareTextCommand{\textnsucccurlyeq}{PU}{\9042\341}%* U+22E1
18875 % U+22E2 NOT SQUARE IMAGE OF OR EQUAL TO; \nsqsubseteq (tx-
    fonts/pxfonts)
18876 \DeclareTextCommand{\textnqsubseteq}{PU}{\9042\342}%* U+22E2
18877 % U+22E3 NOT SQUARE ORIGINAL OF OR EQUAL TO; \nsqsupseteq (tx-
    fonts/pxfonts)
18878 \DeclareTextCommand{\textnqsupseteq}{PU}{\9042\343}%* U+22E3
18879 % U+22E4 SQUARE IMAGE OF OR NOT EQUAL TO; \sqsubsetneq (mathabx)
18880 \DeclareTextCommand{\textsqsubsetneq}{PU}{\9042\344}%* U+22E4
18881 %* \textsqsubsetneq -> \varsqsubsetneq (mathabx)
18882 % U+22E5 SQUARE ORIGINAL OF OR NOT EQUAL TO; \sqsupsetneq (math-
    abx)
18883 \DeclareTextCommand{\textsqsupsetneq}{PU}{\9042\345}%* U+22E5
18884 %* \textsqsupsetneq -> \varsqsupsetneq (mathabx)
18885 % U+22E6 LESS-THAN BUT NOT EQUIVALENT TO; \lnsim (AmS)
18886 \DeclareTextCommand{\textlnsim}{PU}{\9042\346}%* U+22E6
18887 % U+22E7 GREATER-THAN BUT NOT EQUIVALENT TO; \gnsim (AmS)
18888 \DeclareTextCommand{\textgnsim}{PU}{\9042\347}%* U+22E7
18889 % U+22E8 PRECEDES BUT NOT EQUIVALENT TO; \precnsim (AmS)
18890 \DeclareTextCommand{\textprecnsim}{PU}{\9042\350}%* U+22E8
18891 % U+22E9 SUCCEEDS BUT NOT EQUIVALENT TO; \succnsim (AmS)
18892 \DeclareTextCommand{\textsuccnsim}{PU}{\9042\351}%* U+22E9
18893 % U+22EA NOT NORMAL SUBGROUP OF; \ntriangleleft (AmS)
18894 \DeclareTextCommand{\textntriangleleft}{PU}{\9042\352}%* U+22EA
18895 %* \textntriangleleft -> \nlessclosed (MnSymbol)
18896 % U+22EB DOES NOT CONTAIN AS NORMAL SUBGROUP; \ntriangleright
    (AmS)
18897 \DeclareTextCommand{\textntriangleright}{PU}{\9042\353}%* U+22EB
18898 %* \textntriangleright -> \ngtrclosed (MnSymbol)
18899 % U+22EC NOT NORMAL SUBGROUP OF OR EQUAL TO;
18900 % \ntrianglelefteq (AmS)
18901 \DeclareTextCommand{\textntrianglelefteq}{PU}{\9042\354}%* U+22EC
18902 % U+22ED DOES NOT CONTAIN AS NORMAL SUBGROUP OR EQUAL;
18903 % \ntrianglerighteq (AmS)
18904 \DeclareTextCommand{\textntrianglerighteq}{PU}{\9042\355}%* U+22ED
18905 %* \textntrianglerighteq -> \textngeqclosed
18906 % U+22EE VERTICAL ELLIPSIS; ellipsisvertical; \vdots (LaTeX)
18907 \DeclareTextCommand{\textvdots}{PU}{\9042\356}%* U+22EE
18908 % U+22EF MIDLINE HORIZONTAL ELLIPSIS; \cdots (LaTeX)
18909 \DeclareTextCommand{\textcdots}{PU}{\9042\357}%* U+22EF
18910 % U+22F0 UP RIGHT DIAGONAL ELLIPSIS; \udots (MnSymbol)
18911 \DeclareTextCommand{\textudots}{PU}{\9042\360}%* U+22F0
18912 % U+22F1 DOWN RIGHT DIAGONAL ELLIPSIS; \ddots (LaTeX)
18913 \DeclareTextCommand{\textddots}{PU}{\9042\361}%* U+22F1
18914 % U+22F6 ELEMENT OF WITH OVERBAR; \barin (mathabx)
18915 \DeclareTextCommand{\textbarin}{PU}{\9042\366}%* U+22F6

```

51.2.23 Miscellaneous Technical: U+2300 to U+23FF

```

18916 % U+2300 DIAMETER SIGN; \diameter (mathabx,wasysym)
18917 \DeclareTextCommand{\textdiameter}{PU}{\9043\000}%* U+2300
18918 % U+2310 REVERSED NOT SIGN; \backneg (MnSymbol)
18919 \DeclareTextCommand{\textbackneg}{PU}{\9043\020}%* U+2310
18920 % U+2311 SQUARE LOZENGE; \wasylozenge (wasysym)
18921 \DeclareTextCommand{\textwasylozenge}{PU}{\9043\021}%* U+2311
18922 % U+2319 TURNED NOT SIGN; \invbackneg (MnSymbol)
18923 \DeclareTextCommand{\textinvbackneg}{PU}{\9043\031}%* U+2319
18924 % U+231A WATCH; \clock (wasysym)
18925 \DeclareTextCommand{\textclock}{PU}{\9043\032}%* U+231A
18926 %* \textclock -> \Clocklogo (marvosym)
18927 %* \textclock -> \ClockLogo (marvosym)
18928 % U+231C TOP LEFT CORNER; \ulcorner (AmS)
18929 \DeclareTextCommand{\textulcorner}{PU}{\9043\034}%* U+231C
18930 % U+231D TOP RIGHT CORNER; \urcorner (AmS)
18931 \DeclareTextCommand{\texturcorner}{PU}{\9043\035}%* U+231D
18932 % U+231E BOTTOM LEFT CORNER; \llcorner (AmS)
18933 \DeclareTextCommand{\textllcorner}{PU}{\9043\036}%* U+231E
18934 % U+231F BOTTOM RIGHT CORNER; \lrcorner (AmS)
18935 \DeclareTextCommand{\textlrcorner}{PU}{\9043\037}%* U+231F
18936 % U+2322 FROWN; \frown (LaTeX)
18937 \DeclareTextCommand{\textfrown}{PU}{\9043\042}%* U+2322
18938 % U+2323 SMILE; \smile (LaTeX)
18939 \DeclareTextCommand{\textsmile}{PU}{\9043\043}%* U+2323
18940 % U+2328 KEYBOARD; \Keyboard (marvosym)
18941 \DeclareTextCommand{\textKeyboard}{PU}{\9043\050}%* U+2328
18942 % U+2329 LEFT-POINTING ANGLE BRACKET; \angleleft; \angle (LaTeX)
18943 \DeclareTextCommand{\textlangle}{PU}{\9043\051}%* U+2329
18944 % U+232A RIGHT-POINTING ANGLE BRACKET; \angleright; \rangle (LaTeX)
18945 \DeclareTextCommand{\textrangle}{PU}{\9043\052}%* U+232A
18946 % U+2339 APL FUNCTIONAL SYMBOL QUAD DIVIDE; \APLinv (wasysym)
18947 \DeclareTextCommand{\textAPLinv}{PU}{\9043\071}%* U+2339
18948 % U+233C APL FUNCTIONAL SYMBOL QUAD CIRCLE; \Tumbler (marvosym)
18949 \DeclareTextCommand{\textTumbler}{PU}{\9043\074}%* U+233C
18950 % U+233D APL FUNCTIONAL SYMBOL CIRCLE STILE; \baro (stmaryrd)
18951 \DeclareTextCommand{\textstmaryrdbaro}{PU}{\9043\075}%* U+233D
18952 %* \textstmaryrdbaro -> \baro (stmaryrd)
18953 % U+233F APL FUNCTIONAL SYMBOL SLASH BAR; \notslash (wasysym)
18954 \DeclareTextCommand{\textnotslash}{PU}{\9043\077}%* U+233F
18955 % U+2340 APL FUNCTIONAL SYMBOL BACKSLASH BAR;
18956 % \notbackslash (wasysym)
18957 \DeclareTextCommand{\textnotbackslash}{PU}{\9043\100}%* U+2340
18958 % U+2342 APL FUNCTIONAL SYMBOL QUAD BACKSLASH; \boxbackslash (mathabx)
18959 \DeclareTextCommand{\textboxbackslash}{PU}{\9043\102}%* U+2342
18960 % U+2347 APL FUNCTIONAL SYMBOL QUAD LEFTWARDS ARROW;
18961 % \APLleftarrowbox (wasysym)
18962 \DeclareTextCommand{\textAPLleftarrowbox}{PU}{\9043\107}%* U+2347
18963 % U+2348 APL FUNCTIONAL SYMBOL QUAD RIGHTWARDS ARROW;
18964 % \APLrightarrowbox (wasysym)
18965 \DeclareTextCommand{\textAPLrightarrowbox}{PU}{\9043\110}%* U+2348
18966 % U+2350 APL FUNCTIONAL SYMBOL QUAD UPWARDS ARROW; \APLuparrowbox (wasysym)
18967 \DeclareTextCommand{\textAPLuparrowbox}{PU}{\9043\120}%* U+2350
18968 % U+2357 APL FUNCTIONAL SYMBOL QUAD DOWNWARDS ARROW;

```

18969 % \APLdownarrowbox (wasysym)
18970 \DeclareTextCommand{\textAPLdownarrowbox}{PU}{\9043\127}%* U+2357
18971 % U+235E APL FUNCTIONAL SYMBOL QUOTE QUAD;
18972 % \APLinput (wasysym)
18973 \DeclareTextCommand{\textAPLinput}{PU}{\9043\136}%* U+235E
18974 % U+2370 APL FUNCTIONAL SYMBOL QUAD QUESTION; \Request (china2e)
18975 \DeclareTextCommand{\textRequest}{PU}{\9043\160}%* U+2370
18976 % U+2393 DIRECT CURRENT SYMBOL FORM TWO; \Beam (marvosym)
18977 \DeclareTextCommand{\textBeam}{PU}{\9043\223}%* U+2393
18978 % U+2394 SOFTWARE-FUNCTION SYMBOL; \hexagon (wasysym)
18979 \DeclareTextCommand{\texthexagon}{PU}{\9043\224}%* U+2394
18980 % U+2395 APL FUNCTIONAL SYMBOL QUAD; \APLbox (wasysym)
18981 \DeclareTextCommand{\textAPLbox}{PU}{\9043\225}%* U+2395
18982 % U+23ED BLACK RIGHT-POINTING DOUBLE TRIANGLE WITH VERTI-
CAL BAR;
18983 % \ForwardToIndex (marvosym)
18984 \DeclareTextCommand{\textForwardToIndex}{PU}{\9043\355}%* U+23ED
18985 % U+23EE BLACK LEFT-POINTING DOUBLE TRIANGLE WITH VERTI-
CAL BAR;
18986 % \RewindToIndex (marvosym)
18987 \DeclareTextCommand{\textRewindToIndex}{PU}{\9043\356}%* U+23EE

51.2.24 Control Pictures: U+2400 to U+243F

18988 % U+2422 BLANK SYMBOL
18989 \DeclareTextCommand{\textblank}{PU}{\9044\042}% U+2422
18990 % U+2423 OPEN BOX; blank
18991 \DeclareTextCommand{\textvisiblespace}{PU}{\9044\043}% U+2423

51.2.25 Optical Character Recognition: U+2440 to U+245F

18992 % U+244A OCR DOUBLE BACKSLASH; \bbslash (stmaryrd)
18993 \DeclareTextCommand{\textbbslash}{PU}{\9044\112}%* U+244A
18994 %* \textbbslash -> \varparalelinv (txfonts/pxfonts)

51.2.26 Enclosed Alphanumerics: U+2460 to U+24FF

18995 % U+2460 CIRCLED DIGIT ONE; onecircle
18996 \DeclareTextCompositeCommand{\textcircled}{PU}{1}{\9044\140}% U+2460
18997 % U+2461 CIRCLED DIGIT TWO; twocircle
18998 \DeclareTextCompositeCommand{\textcircled}{PU}{2}{\9044\141}% U+2461
18999 % U+2462 CIRCLED DIGIT THREE; threecircle
19000 \DeclareTextCompositeCommand{\textcircled}{PU}{3}{\9044\142}% U+2462
19001 % U+2463 CIRCLED DIGIT FOUR; fourcircle
19002 \DeclareTextCompositeCommand{\textcircled}{PU}{4}{\9044\143}% U+2463
19003 % U+2464 CIRCLED DIGIT FIVE; fivecircle
19004 \DeclareTextCompositeCommand{\textcircled}{PU}{5}{\9044\144}% U+2464
19005 % U+2465 CIRCLED DIGIT SIX; sixcircle
19006 \DeclareTextCompositeCommand{\textcircled}{PU}{6}{\9044\145}% U+2465
19007 % U+2466 CIRCLED DIGIT SEVEN; sevendcircle
19008 \DeclareTextCompositeCommand{\textcircled}{PU}{7}{\9044\146}% U+2466
19009 % U+2467 CIRCLED DIGIT EIGHT; eightcircle
19010 \DeclareTextCompositeCommand{\textcircled}{PU}{8}{\9044\147}% U+2467
19011 % U+2468 CIRCLED DIGIT NINE; ninecircle
19012 \DeclareTextCompositeCommand{\textcircled}{PU}{9}{\9044\150}% U+2468
19013 % U+2469 CIRCLED NUMBER TEN; tencircle
19014 \DeclareTextCompositeCommand{\textcircled}{PU}{10}{\9044\151}% U+2469
19015 % U+246A CIRCLED NUMBER ELEVEN; elevencircle
19016 \DeclareTextCompositeCommand{\textcircled}{PU}{11}{\9044\152}% U+246A
19017 % U+246B CIRCLED NUMBER TWELVE; twelvecircle

19018 \DeclareTextCompositeCommand{\textcircled}{PU}{12}{\9044\153}% U+246B
19019 % U+246C CIRCLED NUMBER THIRTEEN; thirteencircle
19020 \DeclareTextCompositeCommand{\textcircled}{PU}{13}{\9044\154}% U+246C
19021 % U+246D CIRCLED NUMBER FOURTEEN; fourteencircle
19022 \DeclareTextCompositeCommand{\textcircled}{PU}{14}{\9044\155}% U+246D
19023 % U+246E CIRCLED NUMBER FIFTEEN; fifteencircle
19024 \DeclareTextCompositeCommand{\textcircled}{PU}{15}{\9044\156}% U+246E
19025 % U+246F CIRCLED NUMBER SIXTEEN; sixteencircle
19026 \DeclareTextCompositeCommand{\textcircled}{PU}{16}{\9044\157}% U+246F
19027 % U+2470 CIRCLED NUMBER SEVENTEEN; seventeencircle
19028 \DeclareTextCompositeCommand{\textcircled}{PU}{17}{\9044\160}% U+2470
19029 % U+2471 CIRCLED NUMBER EIGHTEEN; eighteencircle
19030 \DeclareTextCompositeCommand{\textcircled}{PU}{18}{\9044\161}% U+2471
19031 % U+2472 CIRCLED NUMBER NINETEEN; nineteencircle
19032 \DeclareTextCompositeCommand{\textcircled}{PU}{19}{\9044\162}% U+2472
19033 % U+2473 CIRCLED NUMBER TWENTY; twentycircle
19034 \DeclareTextCompositeCommand{\textcircled}{PU}{20}{\9044\163}% U+2473
19035 % U+24B6 CIRCLED LATIN CAPITAL LETTER A; Acircle
19036 \DeclareTextCompositeCommand{\textcircled}{PU}{A}{\9044\266}% U+24B6
19037 % \CircledA (marvosym)
19038 \DeclareTextCommand{\textCircledA}{PU}{\9044\266}%* U+24B6
19039 %* \textCircledA -> \CleaningA
19040 % U+24B7 CIRCLED LATIN CAPITAL LETTER B; Bcircle
19041 \DeclareTextCompositeCommand{\textcircled}{PU}{B}{\9044\267}% U+24B7
19042 % U+24B8 CIRCLED LATIN CAPITAL LETTER C; Ccircle
19043 \DeclareTextCompositeCommand{\textcircled}{PU}{C}{\9044\270}% U+24B8
19044 % U+24B9 CIRCLED LATIN CAPITAL LETTER D; Dcircle
19045 \DeclareTextCompositeCommand{\textcircled}{PU}{D}{\9044\271}% U+24B9
19046 % U+24BA CIRCLED LATIN CAPITAL LETTER E; Ecircle
19047 \DeclareTextCompositeCommand{\textcircled}{PU}{E}{\9044\272}% U+24BA
19048 % U+24BB CIRCLED LATIN CAPITAL LETTER F; Fcircle
19049 \DeclareTextCompositeCommand{\textcircled}{PU}{F}{\9044\273}% U+24BB
19050 % \CleaningF (marvosym)
19051 \DeclareTextCommand{\textCleaningF}{PU}{\9044\273}%* U+24BB
19052 % \CleaningFF (marvosym)
19053 \DeclareTextCommand{\textCleaningFF}{PU}{\9044\273\83\062}%* U+24BB U+0332
19054 % U+24BC CIRCLED LATIN CAPITAL LETTER G; Gcircle
19055 \DeclareTextCompositeCommand{\textcircled}{PU}{G}{\9044\274}% U+24BC
19056 % U+24BD CIRCLED LATIN CAPITAL LETTER H; Hcircle
19057 \DeclareTextCompositeCommand{\textcircled}{PU}{H}{\9044\275}% U+24BD
19058 % U+24BE CIRCLED LATIN CAPITAL LETTER I; Icircle
19059 \DeclareTextCompositeCommand{\textcircled}{PU}{I}{\9044\276}% U+24BE
19060 % U+24BF CIRCLED LATIN CAPITAL LETTER J; Jcircle
19061 \DeclareTextCompositeCommand{\textcircled}{PU}{J}{\9044\277}% U+24BF
19062 % U+24C0 CIRCLED LATIN CAPITAL LETTER K; Kcircle
19063 \DeclareTextCompositeCommand{\textcircled}{PU}{K}{\9044\300}% U+24C0
19064 % U+24C1 CIRCLED LATIN CAPITAL LETTER L; Lcircle
19065 \DeclareTextCompositeCommand{\textcircled}{PU}{L}{\9044\301}% U+24C1
19066 % U+24C2 CIRCLED LATIN CAPITAL LETTER M; Mcircle
19067 \DeclareTextCompositeCommand{\textcircled}{PU}{M}{\9044\302}% U+24C2
19068 % U+24C3 CIRCLED LATIN CAPITAL LETTER N; Ncircle
19069 \DeclareTextCompositeCommand{\textcircled}{PU}{N}{\9044\303}% U+24C3
19070 % U+24C4 CIRCLED LATIN CAPITAL LETTER O; Ocircle
19071 \DeclareTextCompositeCommand{\textcircled}{PU}{O}{\9044\304}% U+24C4
19072 % U+24C5 CIRCLED LATIN CAPITAL LETTER P; Pcircle
19073 \DeclareTextCompositeCommand{\textcircled}{PU}{P}{\9044\305}% U+24C5
19074 % \CleaningP (marvosym)

19075 \DeclareTextCommand{\textCleaningP}{PU}{\9044\305}%* U+24C5
 19076 % \CleaningPP (marvosym)
 19077 \DeclareTextCommand{\textCleaningPP}{PU}{\9044\305\83\062}%* U+24C5 U+0332
 19078 % U+24C6 CIRCLED LATIN CAPITAL LETTER Q; Qcircle
 19079 \DeclareTextCompositeCommand{\textcircled}{PU}{Q}{\9044\306}% U+24C6
 19080 % U+24C7 CIRCLED LATIN CAPITAL LETTER R; Rcircle
 19081 \DeclareTextCompositeCommand{\textcircled}{PU}{R}{\9044\307}% U+24C7
 19082 % U+24C8 CIRCLED LATIN CAPITAL LETTER S; Scircle
 19083 \DeclareTextCompositeCommand{\textcircled}{PU}{S}{\9044\310}% U+24C8
 19084 % U+24C9 CIRCLED LATIN CAPITAL LETTER T; Tcircle
 19085 \DeclareTextCompositeCommand{\textcircled}{PU}{T}{\9044\311}% U+24C9
 19086 % U+24CA CIRCLED LATIN CAPITAL LETTER U; Ucircle
 19087 \DeclareTextCompositeCommand{\textcircled}{PU}{U}{\9044\312}% U+24CA
 19088 % U+24CB CIRCLED LATIN CAPITAL LETTER V; Vcircle
 19089 \DeclareTextCompositeCommand{\textcircled}{PU}{V}{\9044\313}% U+24CB
 19090 % U+24CC CIRCLED LATIN CAPITAL LETTER W; Wcircle
 19091 \DeclareTextCompositeCommand{\textcircled}{PU}{W}{\9044\314}% U+24CC
 19092 % U+24CD CIRCLED LATIN CAPITAL LETTER X; Xcircle
 19093 \DeclareTextCompositeCommand{\textcircled}{PU}{X}{\9044\315}% U+24CD
 19094 % U+24CE CIRCLED LATIN CAPITAL LETTER Y; Ycircle
 19095 \DeclareTextCompositeCommand{\textcircled}{PU}{Y}{\9044\316}% U+24CE
 19096 % U+24CF CIRCLED LATIN CAPITAL LETTER Z; Zcircle
 19097 \DeclareTextCompositeCommand{\textcircled}{PU}{Z}{\9044\317}% U+24CF
 19098 % U+24D0 CIRCLED LATIN SMALL LETTER A; acircle
 19099 \DeclareTextCompositeCommand{\textcircled}{PU}{a}{\9044\320}% U+24D0
 19100 % U+24D1 CIRCLED LATIN SMALL LETTER B; bcircle
 19101 \DeclareTextCompositeCommand{\textcircled}{PU}{b}{\9044\321}% U+24D1
 19102 % U+24D2 CIRCLED LATIN SMALL LETTER C; ccircle
 19103 \DeclareTextCompositeCommand{\textcircled}{PU}{c}{\9044\322}% U+24D2
 19104 % U+24D3 CIRCLED LATIN SMALL LETTER D; dcircle
 19105 \DeclareTextCompositeCommand{\textcircled}{PU}{d}{\9044\323}% U+24D3
 19106 % U+24D4 CIRCLED LATIN SMALL LETTER E; ecircle
 19107 \DeclareTextCompositeCommand{\textcircled}{PU}{e}{\9044\324}% U+24D4
 19108 % U+24D5 CIRCLED LATIN SMALL LETTER F; fcircle
 19109 \DeclareTextCompositeCommand{\textcircled}{PU}{f}{\9044\325}% U+24D5
 19110 % U+24D6 CIRCLED LATIN SMALL LETTER G; gcircle
 19111 \DeclareTextCompositeCommand{\textcircled}{PU}{g}{\9044\326}% U+24D6
 19112 % U+24D7 CIRCLED LATIN SMALL LETTER H; hcircle
 19113 \DeclareTextCompositeCommand{\textcircled}{PU}{h}{\9044\327}% U+24D7
 19114 % U+24D8 CIRCLED LATIN SMALL LETTER I; icircle
 19115 \DeclareTextCompositeCommand{\textcircled}{PU}{i}{\9044\330}% U+24D8
 19116 % U+24D9 CIRCLED LATIN SMALL LETTER J; jcircle
 19117 \DeclareTextCompositeCommand{\textcircled}{PU}{j}{\9044\331}% U+24D9
 19118 % U+24DA CIRCLED LATIN SMALL LETTER K; kcircle
 19119 \DeclareTextCompositeCommand{\textcircled}{PU}{k}{\9044\332}% U+24DA
 19120 % U+24DB CIRCLED LATIN SMALL LETTER L; lcircle
 19121 \DeclareTextCompositeCommand{\textcircled}{PU}{l}{\9044\333}% U+24DB
 19122 % U+24DC CIRCLED LATIN SMALL LETTER M; mcircle
 19123 \DeclareTextCompositeCommand{\textcircled}{PU}{m}{\9044\334}% U+24DC
 19124 % U+24DD CIRCLED LATIN SMALL LETTER N; ncircle
 19125 \DeclareTextCompositeCommand{\textcircled}{PU}{n}{\9044\335}% U+24DD
 19126 % U+24DE CIRCLED LATIN SMALL LETTER O; ocircle
 19127 \DeclareTextCompositeCommand{\textcircled}{PU}{o}{\9044\336}% U+24DE
 19128 % U+24DF CIRCLED LATIN SMALL LETTER P; pcircle
 19129 \DeclareTextCompositeCommand{\textcircled}{PU}{p}{\9044\337}% U+24DF
 19130 % U+24E0 CIRCLED LATIN SMALL LETTER Q; qcircle
 19131 \DeclareTextCompositeCommand{\textcircled}{PU}{q}{\9044\340}% U+24E0

```

19132 % U+24E1 CIRCLED LATIN SMALL LETTER R; rcircle
19133 \DeclareTextCompositeCommand{\textcircled}{PU}{r}{\9044\341}% U+24E1
19134 % U+24E2 CIRCLED LATIN SMALL LETTER S; scircle
19135 \DeclareTextCompositeCommand{\textcircled}{PU}{s}{\9044\342}% U+24E2
19136 % U+24E3 CIRCLED LATIN SMALL LETTER T; tcircle
19137 \DeclareTextCompositeCommand{\textcircled}{PU}{t}{\9044\343}% U+24E3
19138 % U+24E4 CIRCLED LATIN SMALL LETTER U; ucircle
19139 \DeclareTextCompositeCommand{\textcircled}{PU}{u}{\9044\344}% U+24E4
19140 % U+24E5 CIRCLED LATIN SMALL LETTER V; vcircle
19141 \DeclareTextCompositeCommand{\textcircled}{PU}{v}{\9044\345}% U+24E5
19142 % U+24E6 CIRCLED LATIN SMALL LETTER W; wcircle
19143 \DeclareTextCompositeCommand{\textcircled}{PU}{w}{\9044\346}% U+24E6
19144 % U+24E7 CIRCLED LATIN SMALL LETTER X; xcircle
19145 \DeclareTextCompositeCommand{\textcircled}{PU}{x}{\9044\347}% U+24E7
19146 % U+24E8 CIRCLED LATIN SMALL LETTER Y; ycircle
19147 \DeclareTextCompositeCommand{\textcircled}{PU}{y}{\9044\350}% U+24E8
19148 % U+24E9 CIRCLED LATIN SMALL LETTER Z; zcircle
19149 \DeclareTextCompositeCommand{\textcircled}{PU}{z}{\9044\351}% U+24E9
19150 % U+24EA CIRCLED DIGIT ZERO
19151 \DeclareTextCompositeCommand{\textcircled}{PU}{0}{\9044\352}% U+24EA

```

51.2.27 Box Drawing: U+2500 to 257F

```

19152 % U+2504 BOX DRAWINGS LIGHT TRIPLE DASH HORIZONTAL; \Cutting-
      Line (marvosym)
19153 \DeclareTextCommand{\textCuttingLine}{PU}{\9045\004}%* U+2504
19154 %* \textCuttingLine -> \Kutline (marvosym)
19155 %* \textCuttingLine -> \CutLine (marvosym)
19156 %* \textCuttingLine -> \Cutline (marvosym)

```

51.2.28 Geometric Shapes: U+25A0 to U+25FF

```

19157 % U+25B2 BLACK UP-POINTING TRIANGLE; \UParrow (wasysym)
19158 \DeclareTextCommand{\textUParrow}{PU}{\9045\262}%* U+25B2
19159 %* \textUParrow -> \MoveUp (marvosym)
19160 % U+25B3 WHITE UP-POINTING TRIANGLE; whiteuppointingtriangle;
19161 % \bigtriangleup (LaTeX)
19162 \DeclareTextCommand{\textbigtriangleup}{PU}{\9045\263}%* U+25B3
19163 %* \textbigtriangleup -> \APLup (wasysym)
19164 %* \textbigtriangleup -> \Bleech (marvosym)
19165 % U+25B6 BLACK RIGHT-POINTING TRIANGLE; \Forward (marvosym)
19166 \DeclareTextCommand{\textForward}{PU}{\9045\266}%* U+25B6
19167 % U+25B7 WHITE RIGHT-POINTING TRIANGLE (= z notation range restric-
      tion);
19168 % whiterightpointingtriangle; \triangleright (LaTeX)
19169 \DeclareTextCommand{\texttriangleright}{PU}{\9045\267}%* U+25B7
19170 % U+25BA BLACK RIGHT-POINTING POINTER; \RHD (wasysym)
19171 \DeclareTextCommand{\textRHD}{PU}{\9045\272}%* U+25BA
19172 % U+25BC BLACK DOWN-POINTING TRIANGLE; \DOWNarrow (wasysym)
19173 \DeclareTextCommand{\textDOWNarrow}{PU}{\9045\274}%* U+25BC
19174 %* \textDOWNarrow -> \MoveDown (marvosym)
19175 % U+25BD WHITE DOWN-POINTING TRIANGLE; whitedownpointingtri-
      angle;
19176 % \bigtriangledown (LaTeX)
19177 \DeclareTextCommand{\textbigtriangledown}{PU}{\9045\275}%* U+25BD
19178 %* \textbigtriangledown -> \APLdown (wasysym)
19179 % U+25C0 BLACK LEFT-POINTING TRIANGLE; \Rewind (marvosym)
19180 \DeclareTextCommand{\textRewind}{PU}{\9045\300}%* U+25C0

```

19181 % U+25C1 WHITE RIGHT-POINTING TRIANGLE (= z notation domain restriction);
 19182 % whiteleftpointingtriangle; \triangleleft (LaTeX)
 19183 \DeclareTextCommand{\texttriangleleft}{PU}{\9045\301}%* U+25C1
 19184 % U+25C4 BLACK LEFT-POINTING POINTER; \LHD (wasysym)
 19185 \DeclareTextCommand{\textLHD}{PU}{\9045\304}%* U+25C4
 19186 % U+25C7 WHITE DIAMOND; whitediamond; \diamond (LaTeX)
 19187 \DeclareTextCommand{\textdiamond}{PU}{\9045\307}%* U+25C7
 19188 %* \textdiamond -> \Diamond (wasysym)
 19189 % U+25CA LOZENGE; lozenge; \lozenge (AmS)
 19190 \DeclareTextCommand{\textlozenge}{PU}{\9045\312}%* U+25CA
 19191 % U+25D6 LEFT HALF BLACK CIRCLE; \LEFTCIRCLE (wasysym)
 19192 \DeclareTextCommand{\textLEFTCIRCLE}{PU}{\9045\326}%* U+25D6
 19193 % U+25D7 RIGHT HALF BLACK CIRCLE; \RIGHTCIRCLE (wasysym)
 19194 \DeclareTextCommand{\textRIGHTCIRCLE}{PU}{\9045\327}%* U+25D7
 19195 % U+25E6 WHITE BULLET; *openbullet, whitebullet
 19196 \DeclareTextCommand{\textopenbullet}{PU}{\9045\346}%* U+25E6
 19197 % U+25EB WHITE SQUARE WITH VERTICAL BISECTING LINE;
 19198 % \boxbar (stmaryrd)
 19199 \DeclareTextCommand{\textboxbar}{PU}{\9045\353}%* U+25EB
 19200 % U+25EF LARGE CIRCLE; largecircle
 19201 \DeclareTextCommand{\textbigcircle}{PU}{\9045\357}%* U+25EF
 19202 %* \textbigcircle -> \varbigcirc (stmaryrd)
 19203 %

51.2.29 Miscellaneous Symbols: U+2600 to U+26FF

19204 % U+2601 CLOUD; \Cloud (ifsym)
 19205 \DeclareTextCommand{\textCloud}{PU}{\9046\001}%* U+2601
 19206 % U+2605 BLACK STAR; \FiveStar (bbding)
 19207 \DeclareTextCommand{\textFiveStar}{PU}{\9046\005}%* U+2605
 19208 % U+2606 WHITE STAR; \FiveStarOpen (bbding)
 19209 \DeclareTextCommand{\textFiveStarOpen}{PU}{\9046\006}%* U+2606
 19210 % U+260E BLACK TELEPHONE; telephoneblack; \Phone (bbding)
 19211 \DeclareTextCommand{\textPhone}{PU}{\9046\016}%* U+260E
 19212 %* \textPhone -> \Telefon (marvosym)
 19213 % U+2610 BALLOT BOX; \boxempty (stmaryrd)
 19214 \DeclareTextCommand{\textboxempty}{PU}{\9046\020}%* U+2610
 19215 %* \textboxempty -> \Box (wasysym)
 19216 % U+2611 BALLOT BOX WITH CHECK; \Checkedbox (marvosym)
 19217 \DeclareTextCommand{\textCheckedbox}{PU}{\9046\021}%* U+2611
 19218 %* \textCheckedbox -> \CheckedBox (marvosym)
 19219 % U+2612 BALLOT BOX WITH X; \Crossedbox (marvosym)
 19220 \DeclareTextCommand{\textCrossedbox}{PU}{\9046\022}%* U+2612
 19221 %* \textCrossedbox -> \XBox (wasysym)
 19222 %* \textCrossedbox -> \CrossedBox (marvosym)
 19223 % U+2615 HOT BEVERAGE; \Coffeecup (marvosym)
 19224 \DeclareTextCommand{\textCoffeecup}{PU}{\9046\025}%* U+2615
 19225 % U+261A BLACK LEFT POINTING INDEX; \HandCuffLeft (bbding)
 19226 \DeclareTextCommand{\textHandCuffLeft}{PU}{\9046\032}%* U+261A
 19227 % U+261B BLACK RIGHT POINTING INDEX; \HandCuffRight (bbding)
 19228 \DeclareTextCommand{\textHandCuffRight}{PU}{\9046\033}%* U+261B
 19229 % U+261C WHITE LEFT POINTING INDEX; \HandLeft (bbding)
 19230 \DeclareTextCommand{\textHandLeft}{PU}{\9046\034}%* U+261C
 19231 %* \textHandLeft -> \rightpointleft (fourier)
 19232 % U+261E WHITE RIGHT POINTING INDEX; \HandRight (bbding)
 19233 \DeclareTextCommand{\textHandRight}{PU}{\9046\036}%* U+261E
 19234 %* \textHandRight -> \leftpointright (fourier)

19235 %* \textHandRight -> \PointingHand (marvosym)
19236 %* \textHandRight -> \Pointinghand (marvosym)
19237 % U+2622 RADIOACTIVE SIGN; \Radioactivity (marvosym)
19238 \DeclareTextCommand{\textRadioactivity}{PU}{\9046\042}%* U+2622
19239 %* \textRadioactivity -> \Radiation (ifsym)
19240 % U+2623 BIOHAZARD SIGN; \Biohazard (marvosym)
19241 \DeclareTextCommand{\textBiohazard}{PU}{\9046\043}%* U+2623
19242 % U+2625 ANKH; \Ankh (marvosym)
19243 \DeclareTextCommand{\textAnkh}{PU}{\9046\045}%* U+2625
19244 % U+262F YIN YANG; \YinYang (marvosym)
19245 \DeclareTextCommand{\textYinYang}{PU}{\9046\057}%* U+262F
19246 %* \textYinYang -> \Yinyang (marvosym)
19247 %* \textYinYang -> \YingYang (marvosym)
19248 %* \textYinYang -> \Yingyang (marvosym)
19249 % U+2639 WHITE FROWNING FACE; \frownie (wasysym)
19250 \DeclareTextCommand{\textfrownie}{PU}{\9046\071}%* U+2639
19251 %* \textfrownie -> \Frowny (marvosym)
19252 % U+263A WHITE SMILING FACE; \smiley (wasysym)
19253 \DeclareTextCommand{\textsmiley}{PU}{\9046\072}%* U+263A
19254 %* \textsmiley -> \Smiley (marvosym)
19255 % U+263B BLACK SMILING FACE; \blacksmiley (wasysym)
19256 \DeclareTextCommand{\textblacksmiley}{PU}{\9046\073}%* U+263B
19257 % U+263C WHITE SUN WITH RAYS; \sun (wasysym)
19258 \DeclareTextCommand{\textsun}{PU}{\9046\074}%* U+263C
19259 %* \textsun -> \Sun (marvosym)
19260 % U+263D FIRST QUARTER MOON; \leftmoon (wasysym, mathabx)
19261 \DeclareTextCommand{\textleftmoon}{PU}{\9046\075}%* U+263D
19262 % U+263E LAST QUARTER MOON; \rightmoon (wasysym, mathabx)
19263 \DeclareTextCommand{\textrightmoon}{PU}{\9046\076}%* U+263E
19264 % U+263F MERCURY; \mercury (wasysym)
19265 \DeclareTextCommand{\textmercury}{PU}{\9046\077}%* U+263F
19266 %* \textmercury -> \Mercury (marvosym)
19267 % U+2640 FEMALE SIGN; female; \female (wasysym)
19268 \DeclareTextCommand{\textPUfemale}{PU}{\9046\100}% U+2640
19269 %* \textPUfemale -> \textfemale (tipx)
19270 %* \textPUfemale -> \female (wasysym)
19271 %* \textPUfemale -> \venus (wasysym)
19272 %* \textPUfemale -> \Venus (marvosym)
19273 %* \textPUfemale -> \Female (marvosym)
19274 % U+2641 EARTH; \earth (wasysym)
19275 \DeclareTextCommand{\textearth}{PU}{\9046\101}%* U+2641
19276 %* \textearth -> \Earth (marvosym)
19277 % U+2642 MALE SIGN; male, mars; \male (wasysym)
19278 \DeclareTextCommand{\textmale}{PU}{\9046\102}%* U+2642
19279 %* \textmale -> \mars (wasysym)
19280 %* \textmale -> \Mars (marvosym)
19281 %* \textmale -> \Male (marvosym)
19282 % U+2643 JUPITER; \jupiter (wasysym)
19283 \DeclareTextCommand{\textjupiter}{PU}{\9046\103}%* U+2643
19284 %* \textjupiter -> \Jupiter (marvosym)
19285 % U+2644 SATURN; \saturn (wasysym)
19286 \DeclareTextCommand{\textsaturn}{PU}{\9046\104}%* U+2644
19287 %* \textsaturn -> \Saturn (marvosym)
19288 % U+2645 URANUS; \uranus (wasysym)
19289 \DeclareTextCommand{\texturanus}{PU}{\9046\105}%* U+2645
19290 %* \texturanus -> \Uranus (marvosym)
19291 % U+2646 NEPTUNE; \neptune (wasysym)


```

19292 \DeclareTextCommand{\textneptune}{PU}{\9046\106}%* U+2646
19293 %* \textneptune -> \Neptune (marvosym)
19294 % U+2647 PLUTO; \pluto (wasysym)
19295 \DeclareTextCommand{\textpluto}{PU}{\9046\107}%* U+2647
19296 %* \textpluto -> \Pluto (marvosym)
19297 % U+2648 ARIES; \aries (wasysym)
19298 \DeclareTextCommand{\textaries}{PU}{\9046\110}%* U+2648
19299 %* \textaries -> \Aries (marvosym)
19300 % U+2649 TAURUS; \taurus (wasysym)
19301 \DeclareTextCommand{\texttaurus}{PU}{\9046\111}%* U+2649
19302 %* \texttaurus -> \Taurus (marvosym)
19303 % U+264A GEMINI; \gemini (wasysym)
19304 \DeclareTextCommand{\textgemini}{PU}{\9046\112}%* U+264A
19305 %* \textgemini -> \Gemini (marvosym)
19306 % U+264B CANCER; \cancer (wasysym)
19307 \DeclareTextCommand{\textcancer}{PU}{\9046\113}%* U+264B
19308 %* \textcancer -> \Cancer (marvosym)
19309 % U+264C LEO; \leo (wasysym)
19310 \DeclareTextCommand{\textleo}{PU}{\9046\114}%* U+264C
19311 %* \textleo -> \Leo (marvosym)
19312 % U+264D VIRGO; \virgo (wasysym)
19313 \DeclareTextCommand{\textvirgo}{PU}{\9046\115}%* U+264D
19314 %* \textvirgo -> \Virgo (marvosym)
19315 % U+264E LIBRA; \libra (wasysym)
19316 \DeclareTextCommand{\textlibra}{PU}{\9046\116}%* U+264E
19317 %* \textlibra -> \Libra (marvosym)
19318 % U+264F SCORPIO; \scorpio (wasysym)
19319 \DeclareTextCommand{\textscorpio}{PU}{\9046\117}%* U+264F
19320 %* \textscorpio -> \Scorpio (marvosym)
19321 % U+2650 SAGITTARIUS; \sagittarius (wasysym)
19322 \DeclareTextCommand{\textsagittarius}{PU}{\9046\120}%* U+2650
19323 %* \textsagittarius -> \Sagittarius (marvosym)
19324 % U+2651 CAPRICORN; \capricornus (wasysym)
19325 \DeclareTextCommand{\textcapricornus}{PU}{\9046\121}%* U+2651
19326 %* \textcapricornus -> \Capricorn (marvosym)
19327 % U+2652 AQUARIUS; \aquarius (wasysym)
19328 \DeclareTextCommand{\textaquarius}{PU}{\9046\122}%* U+2652
19329 %* \textaquarius -> \Aquarius (marvosym)
19330 % U+2653 PISCES; \pisces (wasysym)
19331 \DeclareTextCommand{\textpisces}{PU}{\9046\123}%* U+2653
19332 %* \textpisces -> \Pisces (marvosym)
19333 % U+2660 BLACK SPADE SUIT; spade, spadesuitblack; \spadesuit (LaTeX)
19334 \DeclareTextCommand{\textspadesuitblack}{PU}{\9046\140}% U+2660
19335 %* \textspadesuitblack -> \spadesuit (MnSymbol)
19336 % U+2661 WHITE HEART SUIT; heartsuitwhite; \heartsuit (LaTeX)
19337 \DeclareTextCommand{\textheartsuitwhite}{PU}{\9046\141}% U+2661
19338 %* \textheartsuitwhite -> \Heart (marvosym)
19339 %* \textheartsuitwhite -> \heartsuit (MnSymbol)
19340 % U+2662 WHITE DIAMOND SUIT; diamondsuitwhite; \diamondsuit (LaTeX)
19341 \DeclareTextCommand{\textdiamondsuitwhite}{PU}{\9046\142}% U+2662
19342 %* \textdiamondsuitwhite -> \diamondsuit (MnSymbol)
19343 % U+2663 BLACK CLUB SUIT; club, clubsuitblack; \clubsuit (LaTeX)
19344 \DeclareTextCommand{\textclubsuitblack}{PU}{\9046\143}% U+2663
19345 %* \textclubsuitblack -> \clubsuit (MnSymbol)
19346 % U+2664 WHITE SPADE SUIT; spadesuitwhite
19347 \DeclareTextCommand{\textspadesuitwhite}{PU}{\9046\144}% U+2664
19348 % U+2665 BLACK HEART SUIT; heartsuitblack, heart

```

19349 \DeclareTextCommand{\textheartsuitblack}{PU}{\9046\145}% U+2665
 19350 % U+2666 BLACK DIAMOND SUIT; diamond
 19351 \DeclareTextCommand{\textdiamondsuitblack}{PU}{\9046\146}% U+2666
 19352 % U+2667 WHITE CLUB SUIT; clubsuitwhite
 19353 \DeclareTextCommand{\textclubsuitwhite}{PU}{\9046\147}% U+2667
 19354 % U+2669 QUARTER NOTE; quarternote; \quarternote (wasysym, arev)
 19355 \DeclareTextCommand{\textquarternote}{PU}{\9046\151}%* U+2669
 19356 % U+266A EIGHTH NOTE; musicalnote; \textmusicalnote (textcomp)
 19357 \DeclareTextCommand{\textmusicalnote}{PU}{\9046\152}% U+266A
 19358 %* \textmusicalnote -> \eighthnote (wasysym, arev)
 19359 % U+266B BEAMED EIGHTH NOTES; eighthnotebeamed; \twonotes (wasysym)
 19360 \DeclareTextCommand{\texttwonotes}{PU}{\9046\153}%* U+266B
 19361 % U+266C BEAMED SIXTEENTH NOTES; beamedsixteenthnotes; \sixteenth-
 note (arev)
 19362 \DeclareTextCommand{\textsixteenthnote}{PU}{\9046\154}%* U+266C
 19363 % U+266D MUSIC FLAT SIGN; musicflatsign; \flat (LaTeX)
 19364 \DeclareTextCommand{\textflat}{PU}{\9046\155}%* U+266D
 19365 % U+266E MUSIC NATURAL SIGN; \natural (LaTeX)
 19366 \DeclareTextCommand{\textnatural}{PU}{\9046\156}%* U+266E
 19367 % U+266F MUSIC SHARP SIGN; musicsharpsign; \sharp (LaTeX)
 19368 \DeclareTextCommand{\textsharp}{PU}{\9046\157}%* U+266F
 19369 % U+2672 UNIVERSAL RECYCLING SYMBOL; \recycle (recycle)
 19370 \DeclareTextCommand{\textrecycle}{PU}{\9046\162}%* U+2672
 19371 %* \textrecycle -> \Recycling (marvosym)
 19372 % U+267F WHEELCHAIR SYMBOL; \Wheelchair (marvosym)
 19373 \DeclareTextCommand{\textWheelchair}{PU}{\9046\177}%* U+267F
 19374 % U+2691 BLACK FLAG; \Flag (ifsym)
 19375 \DeclareTextCommand{\textFlag}{PU}{\9046\221}%* U+2691
 19376 %* \textFlag -> \VarFlag (ifsym)
 19377 % U+2692 HAMMER AND PICK; \MineSign (marvosym)
 19378 \DeclareTextCommand{\textMineSign}{PU}{\9046\222}%* U+2692
 19379 % U+2694 CROSSED SWORDS; \dsmilitary (dictsym)
 19380 \DeclareTextCommand{\textdsmilitary}{PU}{\9046\224}%* U+2694
 19381 %* \textdsmilitary -> \textxswup (fourier)
 19382 % U+2695 STAFF OF AESCULAPIUS; \dsmedical (dictsym)
 19383 \DeclareTextCommand{\textdsmedical}{PU}{\9046\225}%* U+2695
 19384 % U+2696 SCALES; \dsjuridical (dictsym)
 19385 \DeclareTextCommand{\textdsjuridical}{PU}{\9046\226}%* U+2696
 19386 % U+2697 ALEMBIC; \dschemical (dictsym)
 19387 \DeclareTextCommand{\textdschemical}{PU}{\9046\227}%* U+2697
 19388 % U+2698 FLOWER; \dsbiological (dictsym)
 19389 \DeclareTextCommand{\textdsbiological}{PU}{\9046\230}%* U+2698
 19390 % U+269A STAFF OF HERMES; \dscommercial (dictsym)
 19391 \DeclareTextCommand{\textdscommercial}{PU}{\9046\232}%* U+269A
 19392 % U+269D OUTLINED WHITE STAR; \manstar (manfnt)
 19393 \DeclareTextCommand{\textmanstar}{PU}{\9046\235}%* U+269D
 19394 % U+26A0 WARNING SIGN; \danger (fourier)
 19395 \DeclareTextCommand{\textdanger}{PU}{\9046\240}%* U+26A0
 19396 % U+26A2 DOUBLED FEMALE SIGN; \FemaleFemale (marvosym)
 19397 \DeclareTextCommand{\textFemaleFemale}{PU}{\9046\242}%* U+26A2
 19398 % U+26A3 DOUBLED MALE SIGN; \MaleMale (marvosym)
 19399 \DeclareTextCommand{\textMaleMale}{PU}{\9046\243}%* U+26A3
 19400 % U+26A4 INTERLOCKED FEMALE AND MALE SIGN; \FemaleMale (mar-
 vosym)
 19401 \DeclareTextCommand{\textFemaleMale}{PU}{\9046\244}%* U+26A4
 19402 % U+26A5 MALE AND FEMALE SIGN; \Hermaphrodite (marvosym)
 19403 \DeclareTextCommand{\textHermaphrodite}{PU}{\9046\245}%* U+26A5

19404 % U+26AA MEDIUM WHITE CIRCLE; \Neural (marvosym)
 19405 \DeclareTextCommand{\textNeutral}{PU}{\9046\252}%* U+26AA
 19406 % U+26AD MARRIAGE SYMBOL
 19407 \DeclareTextCommand{\textmarried}{PU}{\9046\255}% U+26AD
 19408 % U+26AE DIVORCE SYMBOL
 19409 \DeclareTextCommand{\textdivorced}{PU}{\9046\256}% U+26AE
 19410 % U+26B2 NEUTER; \textuncrfemale (tipx)
 19411 \DeclareTextCommand{\textPUuncrfemale}{PU}{\9046\262}% U+26B2
 19412 %* \textPUuncrfemale -> \textuncrfemale (tipx)
 19413 % U+26B9 SEXTILE; \hexstar (wasysym)
 19414 \DeclareTextCommand{\texthexstar}{PU}{\9046\271}%* U+26B9
 19415 % U+26BD SOCCER BALL; \Football (marvosym)
 19416 \DeclareTextCommand{\textSoccerBall}{PU}{\9046\275}% U+26BD
 19417 %* \textSoccerBall -> \Football (marvosym)
 19418 % U+26C5 SUN BEHIND CLOUD; \SunCloud (ifsym)
 19419 \DeclareTextCommand{\textSunCloud}{PU}{\9046\305}%* U+26C5
 19420 % U+26C6 RAIN; \Rain (ifsym)
 19421 \DeclareTextCommand{\textRain}{PU}{\9046\306}%* U+26C6
 19422 % U+26D4 NO ENTRY; \noway (fourier)
 19423 \DeclareTextCommand{\textnoway}{PU}{\9046\324}%* U+26D4
 19424 % U+26F0 MOUNTAIN; \Mountain (ifsym)
 19425 \DeclareTextCommand{\textMountain}{PU}{\9046\360}%* U+26F0
 19426 % U+26FA TENT; \Tent (ifsym)
 19427 \DeclareTextCommand{\textTent}{PU}{\9046\372}%* U+26FA

51.2.30 Dingbats: U+2700 to U+27BF

19428 % U+2701 UPPER BLADE SCISSORS; \ScissorRightBrokenBottom (bbding)
 19429 \DeclareTextCommand{\textScissorRightBrokenBottom}{PU}{\9047\001}% U+2701
 19430 %* \textScissorRightBrokenBottom -> \CutLeft (marvosym)
 19431 %* \textScissorRightBrokenBottom -> \Cutright (marvosym)
 19432 % U+2702 BLACK SCISSORS; \ScissorRight (bbding)
 19433 \DeclareTextCommand{\textScissorRight}{PU}{\9047\002}%* U+2702
 19434 %* \textScissorRight -> \RightScissors (marvosym)
 19435 %* \textScissorRight -> \Leftscissors (marvosym)
 19436 % U+2703 LOWER BLADE SCISSORS; \ScissorRightBrokenTop (bbding)
 19437 \DeclareTextCommand{\textScissorRightBrokenTop}{PU}{\9047\003}%* U+2703
 19438 % U+2704 WHITE SCISSORS; \ScissorHollowRight (bbding)
 19439 \DeclareTextCommand{\textScissorHollowRight}{PU}{\9047\004}%* U+2704
 19440 % U+2706 TELEPHONE LOCATION SIGN; \PhoneHandset (bbding)
 19441 \DeclareTextCommand{\textPhoneHandset}{PU}{\9047\006}%* U+2706
 19442 % U+2707 TAPE DRIVE; \Tape (bbding)
 19443 \DeclareTextCommand{\textTape}{PU}{\9047\007}%* U+2707
 19444 % U+2708 AIRPLANE; \Plane (bbding)
 19445 \DeclareTextCommand{\textPlane}{PU}{\9047\010}%* U+2708
 19446 % U+2709 ENVELOPE; \Envelope (bbding),
 19447 \DeclareTextCommand{\textEnvelope}{PU}{\9047\011}%* U+2709
 19448 %* \textEnvelope -> \Letter (marvosym)
 19449 % U+270C VICTORY HAND; \Peace (bbding)
 19450 \DeclareTextCommand{\textPeace}{PU}{\9047\014}%* U+270C
 19451 % U+270D WRITING HAND; \WritingHand (marvosym)
 19452 \DeclareTextCommand{\textWritingHand}{PU}{\9047\015}%* U+270D
 19453 %* \textWritingHand -> \Writinghand (marvosym)
 19454 % U+270E LOWER RIGHT PENCIL; \PencilRightDown (bbding)
 19455 \DeclareTextCommand{\textPencilRightDown}{PU}{\9047\016}%* U+270E
 19456 % U+270F PENCIL; \PencilRight (bbding)
 19457 \DeclareTextCommand{\textPencilRight}{PU}{\9047\017}%* U+270F
 19458 % U+2710 UPPER RIGHT PENCIL; \PencilRightUp (bbding)

19459 \DeclareTextCommand{\textPencilRightUp}{PU}{\9047\020}%* U+2710
 19460 % U+2711 WHITE NIB; \NibRight (bbling)
 19461 \DeclareTextCommand{\textNibRight}{PU}{\9047\021}%* U+2711
 19462 % U+2712 BLACK NIB; \NibSolidRight (bbling)
 19463 \DeclareTextCommand{\textNibSolidRight}{PU}{\9047\022}%* U+2712
 19464 % U+2713 CHECK MARK; checkmark; \Checkmark (bbling)
 19465 \DeclareTextCommand{\textCheckmark}{PU}{\9047\023}%* U+2713
 19466 %* \textCheckmark -> \checkmark (MnSymbol)
 19467 % U+2714 HEAVY CHECK MARK; \CheckmarkBold (bbling)
 19468 \DeclareTextCommand{\textCheckmarkBold}{PU}{\9047\024}%* U+2714
 19469 % U+2715 MULTIPLICATION X; \XSolid (bbling)
 19470 \DeclareTextCommand{\textXSolid}{PU}{\9047\025}%* U+2715
 19471 % U+2716 HEAVY MULTIPLICATION X; \XSolidBold (bbling)
 19472 \DeclareTextCommand{\textXSolidBold}{PU}{\9047\026}%* U+2716
 19473 % U+2717 BALLOT X; \XSolidBrush (bbling)
 19474 \DeclareTextCommand{\textXSolidBrush}{PU}{\9047\027}%* U+2717
 19475 % U+2719 OUTLINED GREEK CROSS; \PlusOutline (bbling)
 19476 \DeclareTextCommand{\textPlusOutline}{PU}{\9047\031}%* U+2719
 19477 % U+271A HEAVY GREEK CROSS; \Plus (bbling)
 19478 \DeclareTextCommand{\textPlus}{PU}{\9047\032}%* U+271A
 19479 % U+271B OPEN CENTRE CROSS; \PlusThinCenterOpen (bbling)
 19480 \DeclareTextCommand{\textPlusThinCenterOpen}{PU}{\9047\033}%* U+271B
 19481 % U+271C HEAVY OPEN CENTRE CROSS; \PlusCenterOpen (bbling)
 19482 \DeclareTextCommand{\textPlusCenterOpen}{PU}{\9047\034}%* U+271C
 19483 % U+271D LATIN CROSS; \Cross (bbling)
 19484 \DeclareTextCommand{\textCross}{PU}{\9047\035}%* U+271D
 19485 % U+271E SHADOWED WHITE LATIN CROSS; \CrossOpenShadow (bbling)
 19486 \DeclareTextCommand{\textCrossOpenShadow}{PU}{\9047\036}%* U+271E
 19487 % U+271F OUTLINED LATIN CROSS; \CrossOutline (bbling)
 19488 \DeclareTextCommand{\textCrossOutline}{PU}{\9047\037}%* U+271F
 19489 % U+2720 MALTESE CROSS; \CrossMaltese (bbling)
 19490 \DeclareTextCommand{\textCrossMaltese}{PU}{\9047\040}%* U+2720
 19491 % U+2721 STAR OF DAVID; \DavidStar (bbling)
 19492 \DeclareTextCommand{\textDavidStar}{PU}{\9047\041}%* U+2721
 19493 %* \textDavidStar -> \davidstar (wasysym)
 19494 % U+2722 FOUR TEARDROP-SPOKED ASTERISK; \FourAsterisk (bbling)
 19495 \DeclareTextCommand{\textFourAsterisk}{PU}{\9047\042}%* U+2722
 19496 % U+2723 FOUR BALLOON-SPOKED ASTERISK; \JackStar (bbling)
 19497 \DeclareTextCommand{\textJackStar}{PU}{\9047\043}%* U+2723
 19498 % U+2724 HEAVY FOUR BALLOON-SPOKED ASTERISK; \JackStarBold (bbling)
 19499 \DeclareTextCommand{\textJackStarBold}{PU}{\9047\044}%* U+2724
 19500 % U+2725 FOUR CLUB-SPOKED ASTERISK; \CrossClowerTips (bbling)
 19501 \DeclareTextCommand{\textClowerTips}{PU}{\9047\045}%* U+2725
 19502 % U+2726 BLACK FOUR POINTED STAR; \FourStar (bbling)
 19503 \DeclareTextCommand{\textFourStar}{PU}{\9047\046}%* U+2726
 19504 % U+2727 WHITE FOUR POINTED STAR; \FourStarOpen (bbling)
 19505 \DeclareTextCommand{\textFourStarOpen}{PU}{\9047\047}%* U+2727
 19506 % U+272A CIRCLED WHITE STAR; \FiveStarOpenCircled (bbling)
 19507 \DeclareTextCommand{\textFiveStarOpenCircled}{PU}{\9047\052}%* U+272A
 19508 % U+272B OPEN CENTRE BLACK STAR; \FiveStarCenterOpen (bbling)
 19509 \DeclareTextCommand{\textFiveStarCenterOpen}{PU}{\9047\053}%* U+272B
 19510 % U+272C BLACK CENTRE WHITE STAR; \FiveStarOpenDotted (bbling)
 19511 \DeclareTextCommand{\textFiveStarOpenDotted}{PU}{\9047\054}%* U+272C
 19512 % U+272D OUTLINED BLACK STAR; \FiveStarOutline (bbling)
 19513 \DeclareTextCommand{\textFiveStarOutline}{PU}{\9047\055}%* U+272D
 19514 % U+272E HEAVY OUTLINED BLACK STAR; \FiveStarOutlineHeavy (bbling)

19515 \DeclareTextCommand{\textFiveStarOutlineHeavy}{PU}{\9047\056}%* U+272E
19516 % U+272F PINWHEEL STAR; \FiveStarConvex (bding)
19517 \DeclareTextCommand{\textFiveStarConvex}{PU}{\9047\057}%* U+272F
19518 % U+2730 SHADOWED WHITE STAR; \FiveStarShadow (bding)
19519 \DeclareTextCommand{\textFiveStarShadow}{PU}{\9047\060}%* U+2730
19520 % U+2731 HEAVY ASTERISK; \AsteriskBold (bding)
19521 \DeclareTextCommand{\textAsteriskBold}{PU}{\9047\061}%* U+2731
19522 % U+2732 OPEN CENTRE ASTERISK; \AsteriskCenterOpen (bding)
19523 \DeclareTextCommand{\textAsteriskCenterOpen}{PU}{\9047\062}%* U+2732
19524 % U+2734 EIGHT POINTED BLACK STAR; \EightStarTaper (bding)
19525 \DeclareTextCommand{\textEightStarTaper}{PU}{\9047\064}%* U+2734
19526 % U+2735 EIGHT POINTED PINWHEEL STAR; \EightStarConvex (bding)
19527 \DeclareTextCommand{\textEightStarConvex}{PU}{\9047\065}%* U+2735
19528 % U+2736 SIX POINTED BLACK STAR; \SixStar (bding)
19529 \DeclareTextCommand{\textSixStar}{PU}{\9047\066}%* U+2736
19530 % U+2737 EIGHT POINTED RECTILINEAR BLACK STAR; \EightStar (bding)
19531 \DeclareTextCommand{\textEightStar}{PU}{\9047\067}%* U+2737
19532 % U+2738 HEAVY EIGHT POINTED RECTILINEAR BLACK STAR; \EightStarBold (bding)
19533 \DeclareTextCommand{\textEightStarBold}{PU}{\9047\070}%* U+2738
19534 % U+2739 TWELVE POINTED BLACK STAR; \TwelveStar (bding)
19535 \DeclareTextCommand{\textTwelveStar}{PU}{\9047\071}%* U+2739
19536 % U+273A SIXTEEN POINTED ASTERISK; \SixteenStarLight (bding)
19537 \DeclareTextCommand{\textSixteenStarLight}{PU}{\9047\072}%* U+273A
19538 % U+273B TEARDROP-SPOKED ASTERISK; \SixFlowerPetalRemoved (bding)
19539 \DeclareTextCommand{\textSixFlowerPetalRemoved}{PU}{\9047\073}%* U+273B
19540 % U+273C OPEN CENTRE TEARDROP-SPOKED ASTERISK;
19541 % \SixFlowerOpenCenter (bding)
19542 \DeclareTextCommand{\textSixFlowerOpenCenter}{PU}{\9047\074}%* U+273C
19543 % U+273D HEAVY TEARDROP-SPOKED ASTERISK; \Asterisk (bding)
19544 \DeclareTextCommand{\textAsterisk}{PU}{\9047\075}%* U+273D
19545 % U+273E SIX PETALLED BLACK AND WHITE FLORETTE; \SixFlowerAlternate (bding)
19546 \DeclareTextCommand{\textSixFlowerAlternate}{PU}{\9047\076}%* U+273E
19547 % U+273F BLACK FLORETTE; \FiveFlowerPetal (bding)
19548 \DeclareTextCommand{\textFiveFlowerPetal}{PU}{\9047\077}%* U+273F
19549 % U+2740 WHITE FLORETTE; \FiveFlowerOpen (bding)
19550 \DeclareTextCommand{\textFiveFlowerOpen}{PU}{\9047\100}%* U+2740
19551 % U+2741 EIGHT PETALLED OUTLINED BLACK FLORETTE; \EightFlowerPetal (bding)
19552 \DeclareTextCommand{\textEightFlowerPetal}{PU}{\9047\101}%* U+2741
19553 % U+2742 CIRCLED OPEN CENTRE EIGHT POINTED STAR; \SunshineOpenCircled (bding)
19554 \DeclareTextCommand{\textSunshineOpenCircled}{PU}{\9047\102}%* U+2742
19555 % U+2743 HEAVY TEARDROP-SPOKED PINWHEEL ASTERISK; \SixFlowerAltPetal (bding)
19556 \DeclareTextCommand{\textSixFlowerAltPetal}{PU}{\9047\103}%* U+2743
19557 % U+2744 SNOWFLAKE; \SnowflakeChevron (bding)
19558 \DeclareTextCommand{\textSnowflakeChevron}{PU}{\9047\104}%* U+2744
19559 % U+2745 TIGHT TRIFOLIATE SNOWFLAKE; \Snowflake (bding)
19560 \DeclareTextCommand{\textSnowflake}{PU}{\9047\105}%* U+2745
19561 % U+2746 HEAVY CHEVRON SNOWFLAKE; \SnowflakeChevronBold (bding)
19562 \DeclareTextCommand{\textSnowflakeChevronBold}{PU}{\9047\106}%* U+2746
19563 % U+2747 SPARKLE; \Sparkle (bding)
19564 \DeclareTextCommand{\textSparkle}{PU}{\9047\107}%* U+2747

19565 % U+2748 HEAVY SPARKLE; \SparkleBold (bding)
 19566 \DeclareTextCommand{\textSparkleBold}{PU}{\9047\110}%* U+2748
 19567 % U+2749 BALLOON-SPOKED ASTERISK; \AsteriskRoundedEnds (bding)
 19568 \DeclareTextCommand{\textAsteriskRoundedEnds}{PU}{\9047\111}%* U+2749
 19569 % U+274A EIGHT TEARDROP-SPOKED PROPELLER ASTERISK;
 19570 % \EightFlowerPetalRemoved (bding)
 19571 \DeclareTextCommand{\textEightFlowerPetalRemoved}{PU}{\9047\112}%* U+274A
 19572 % U+274B HEAVY EIGHT TEARDROP-SPOKED PROPELLER ASTERISK;
 19573 % \EightAsterisk (bding)
 19574 \DeclareTextCommand{\textEightAsterisk}{PU}{\9047\113}%* U+274B
 19575 % U+274D SHADOWED WHITE CIRCLE; \CircleShadow (bding)
 19576 \DeclareTextCommand{\textCircleShadow}{PU}{\9047\115}%* U+274D
 19577 % U+274F LOWER RIGHT DROP-SHADOWED WHITE SQUARE;
 19578 % \SquareShadowBottomRight (bding)
 19579 \DeclareTextCommand{\textSquareShadowBottomRight}{PU}{\9047\117}%* U+274F
 19580 % U+2750 UPPER RIGHT DROP-SHADOWED WHITE SQUARE;
 19581 % \SquareShadowTopRight (bding)
 19582 \DeclareTextCommand{\textSquareTopRight}{PU}{\9047\120}%* U+2750
 19583 % U+2751 LOWER RIGHT SHADOWED WHITE SQUARE;
 19584 % \SquareCastShadowBottomRight (bding)
 19585 \DeclareTextCommand{\textSquareCastShadowBottomRight}{PU}{\9047\121}%* U+2751
 19586 % U+2752 UPPER RIGHT SHADOWED WHITE SQUARE;
 19587 % \SquareCastShadowTopRight (bding)
 19588 \DeclareTextCommand{\textSquareCastShadowTopRight}{PU}{\9047\122}%* U+2752
 19589 % U+2756 BLACK DIAMOND MINUS WHITE X; \OrnamentDiamandSolid (bding)
 19590 \DeclareTextCommand{\textDiamandSolid}{PU}{\9047\126}%* U+2756
 19591 % U+2758 LIGHT VERTICAL BAR; \RectangleThin (bding)
 19592 \DeclareTextCommand{\textRectangleThin}{PU}{\9047\130}%* U+2758
 19593 % U+2759 MEDIUM VERTICAL BAR; \Rectangle (bding)
 19594 \DeclareTextCommand{\textRectangle}{PU}{\9047\131}%* U+2759
 19595 % U+275A HEAVY VERTICAL BAR; \RectangleBold (bding)
 19596 \DeclareTextCommand{\textRectangleBold}{PU}{\9047\132}%* U+275A

51.2.31 Miscellaneous Mathematical Symbols-A: U+27C0 to U+27EF

19597 % U+27C2 PERPENDICULAR; perpendicular; \perp (LaTeX)
 19598 \DeclareTextCommand{\textperp}{PU}{\9047\302}%* U+27C2
 19599 % \notperp (mathabx)
 19600 \DeclareTextCommand{\textnotperp}{PU}{\9047\302\83\070}%* U+27C2 U+0338
 19601 % U+27C7 OR WITH DOT INSIDE; \veedot (MnSymbol)
 19602 \DeclareTextCommand{\textveedot}{PU}{\9047\307}%* U+27C7
 19603 % U+27D1 AND WITH DOT; \wedgedot (MnSymbol)
 19604 \DeclareTextCommand{\textwedgedot}{PU}{\9047\321}%* U+27D1
 19605 % U+27DC LEFT MULTIMAP; \leftspoon (MnSymbol)
 19606 \DeclareTextCommand{\textleftspoon}{PU}{\9047\334}%* U+27DC
 19607 % U+27E6 MATHEMATICAL LEFT WHITE SQUARE BRACKET
 19608 \DeclareTextCommand{\textlbrackdbl}{PU}{\9047\346}%* U+27E6
 19609 %* \textlbrackdbl -> \lbracket (stmaryrd)
 19610 % U+27E7 MATHEMATICAL RIGHT WHITE SQUARE BRACKET
 19611 \DeclareTextCommand{\textrbrackdbl}{PU}{\9047\347}%* U+27E7
 19612 %* \textrbrackdbl -> \rrbracket (stmaryrd)

51.2.32 Supplemental Arrows-A: U+27F0 to U+27FF

19613 % U+27F2 ANTICLOCKWISE GAPPED CIRCLE ARROW;
 19614 % \circlearrowleft (AmS)
 19615 \DeclareTextCommand{\textcirclearrowleft}{PU}{\9047\362}%* U+27F2
 19616 % U+27F3 CLOCKWISE GAPPED CIRCLE ARROW; \circlearrowright (AmS)

19617 \DeclareTextCommand{\textcirclearrowright}{PU}{\9047\363}%* U+27F3
 19618 % U+27F5 LONG LEFTWARDS ARROW; \longleftarrow (AmS)
 19619 \DeclareTextCommand{\textlongleftarrow}{PU}{\9047\365}%* U+27F5
 19620 % U+27F6 LONG RIGHTWARDS ARROW; \longrightarrow (AmS)
 19621 \DeclareTextCommand{\textlongrightarrow}{PU}{\9047\366}%* U+27F6
 19622 % U+27F7 LONG LEFT RIGHT ARROW; \longlefttrightarrow (AmS)
 19623 \DeclareTextCommand{\textlongleftrightarrow}{PU}{\9047\367}%* U+27F7
 19624 % U+27F8 LONG LEFTWARDS DOUBLE ARROW; \Longleftarrow (AmS)
 19625 \DeclareTextCommand{\textLongleftarrow}{PU}{\9047\370}%* U+27F8
 19626 % U+27F9 LONG RIGHTWARDS DOUBLE ARROW; \Longrightarrow (AmS)
 19627 \DeclareTextCommand{\textLongrightarrow}{PU}{\9047\371}%* U+27F9
 19628 % U+27FA LONG LEFT RIGHT DOUBLE ARROW; \Longleftrightarrow (AmS)
 19629 \DeclareTextCommand{\textLongleftrightarrow}{PU}{\9047\372}%* U+27FA
 19630 % U+27FC LONG RIGHTWARDS ARROW FROM BAR; \longmapsto (AmS)
 19631 \DeclareTextCommand{\textlongmapsto}{PU}{\9047\374}%* U+27FC
 19632 % U+27FD LONG LEFTWARDS DOUBLE ARROW FROM BAR; \Longmaps-
 from (stmaryrd)
 19633 \DeclareTextCommand{\textLongmapsfrom}{PU}{\9047\375}%* U+27FD
 19634 % U+27FE LONG RIGHTWARDS DOUBLE ARROW FROM BAR; \Longmap-
 sto (stmaryrd)
 19635 \DeclareTextCommand{\textLongmapsto}{PU}{\9047\376}%* U+27FE

51.2.33 Supplemental Arrows-B: U+2900 to U+297F

19636 % U+2921 NORTH WEST AND SOUTH EAST ARROW; \nwsearrow (MnSym-
 bol)
 19637 \DeclareTextCommand{\textnwsearrow}{PU}{\9051\041}%* U+2921
 19638 % U+2922 NORTH EAST AND SOUTH WEST ARROW; \neswarrow (MnSym-
 bol)
 19639 \DeclareTextCommand{\textneswarrow}{PU}{\9051\042}%* U+2922
 19640 % U+2923 NORTH WEST ARROW WITH HOOK; \hooknwarrow (MnSymbol)
 19641 \DeclareTextCommand{\textlhooknwarrow}{PU}{\9051\043}%* U+2923
 19642 % U+2924 NORTH EAST ARROW WITH HOOK; \rhooknearrow (MnSymbol)
 19643 \DeclareTextCommand{\textrhooknearrow}{PU}{\9051\044}%* U+2924
 19644 % U+2925 SOUTH EAST ARROW WITH HOOK; \hooksearrow (MnSymbol)
 19645 \DeclareTextCommand{\textlhooksearrow}{PU}{\9051\045}%* U+2925
 19646 % U+2926 SOUTH WEST ARROW WITH HOOK; \rhookswarrow (MnSymbol)
 19647 \DeclareTextCommand{\textrhookswarrow}{PU}{\9051\046}%* U+2926
 19648 % U+2933 WAVE ARROW POINTING DIRECTLY RIGHT; \leadsto (wasysym)
 19649 \DeclareTextCommand{\textleadsto}{PU}{\9051\063}%* U+2933
 19650 % U+2934 ARROW POINTING RIGHTWARDS THEN CURVING UPWARDS;
 19651 % \rcurvearrowne (MnSymbol)
 19652 \DeclareTextCommand{\textrcurvearrowne}{PU}{\9051\064}%* U+2934
 19653 % U+2935 ARROW POINTING RIGHTWARDS THEN CURVING DOWN-
 WARDS;
 19654 % \lcurvearrowse (MnSymbol)
 19655 \DeclareTextCommand{\textlcurvearrowse}{PU}{\9051\065}%* U+2935
 19656 % U+2936 ARROW POINTING DOWNWARDS THEN CURVING LEFT-
 WARDS;
 19657 % \lcurvearrowsw (MnSymbol)
 19658 \DeclareTextCommand{\textlcurvearrowsw}{PU}{\9051\066}%* U+2936
 19659 % U+2937 ARROW POINTING DOWNWARDS THEN CURVING RIGHT-
 WARDS;
 19660 % \rcurvearrowse (MnSymbol)
 19661 \DeclareTextCommand{\textrcurvearrowse}{PU}{\9051\067}%* U+2937
 19662 % U+2938 RIGHT-SIDE ARC CLOCKWISE ARROW; \lcurvearrowdown (Mn-
 Symbol)
 19663 \DeclareTextCommand{\textlcurvearrowdown}{PU}{\9051\070}%* U+2938

19664 %* \textlcurvearrowdown -> \RightTorque (marvosym)
 19665 %* \textlcurvearrowdown -> \Righttorque (marvosym)
 19666 % U+2939 LEFT-SIDE ARC ANTICLOCKWISE ARROW;
 19667 % \rcurvearrowdown (MnSymbol)
 19668 \DeclareTextCommand{\textrcurvearrowdown}{PU}{\9051\071}%* U+2939
 19669 %* \textrcurvearrowdown -> \LeftTorque (marvosym)
 19670 %* \textrcurvearrowdown -> \Lefttorque (marvosym)
 19671 % U+293A TOP ARC ANTICLOCKWISE ARROW; \rcurvearrowleft (MnSymbol)
 19672 \DeclareTextCommand{\textrcurvearrowleft}{PU}{\9051\072}%* U+293A
 19673 % U+293B BOTTOM ARC ANTICLOCKWISE ARROW;
 19674 % \rcurvearrowright (MnSymbol)
 19675 \DeclareTextCommand{\textrcurvearrowright}{PU}{\9051\073}%* U+293B
 19676 % U+294A LEFT BARB UP RIGHT BARB DOWN HARPOON; \leftrightharpoon (mathabx)
 19677 \DeclareTextCommand{\textleftrightharpoon}{PU}{\9051\112}%* U+294A
 19678 % U+294B LEFT BARB DOWN RIGHT BARB UP HARPOON; \rightleftharpoon (mathabx)
 19679 \DeclareTextCommand{\textrightleftharpoon}{PU}{\9051\113}%* U+294B
 19680 % U+294C UP BARB RIGHT DOWN BARB LEFT HARPOON;
 19681 % \updownharpoonrightleft (MnSymbol)
 19682 \DeclareTextCommand{\textupdownharpoonrightleft}{PU}{\9051\114}%* U+294C
 19683 % U+294D UP BARB LEFT DOWN BARB RIGHT HARPOON;
 19684 % \updownharpoonleftright (MnSymbol)
 19685 \DeclareTextCommand{\textupdownharpoonleftright}{PU}{\9051\115}%* U+294D
 19686 % U+2962 LEFTWARDS HARPOON WITH BARB UP ABOVE LEFTWARDS
 19687 % HARPOON WITH BARB DOWN; \leftleftharpoons (mathabx)
 19688 \DeclareTextCommand{\textleftleftharpoons}{PU}{\9051\142}%* U+2962
 19689 % U+2963 UPWARDS HARPOON WITH BARB LEFT BESIDE UPWARDS
 19690 % HARPOON WITH BARB RIGHT; \upupharpoons (mathabx)
 19691 \DeclareTextCommand{\textupupharpoons}{PU}{\9051\143}%* U+2963
 19692 % U+2964 RIGHTWARDS HARPOON WITH BARB UP ABOVE RIGHTWARDS HARPOON
 19693 % WITH BARB DOWN; \rightrightarpoons (mathabx)
 19694 \DeclareTextCommand{\textrightarpoons}{PU}{\9051\144}%* U+2964
 19695 % U+2965 DOWNWARDS HARPOON WITH BARB LEFT BESIDE DOWNWARDS HARPOON
 19696 % WITH BARB RIGHT; \downdownharpoons (mathabx)
 19697 \DeclareTextCommand{\textdowndownharpoons}{PU}{\9051\145}%* U+2965
 19698 % U+296A LEFTWARDS HARPOON WITH BARB UP ABOVE LONG DASH;
 19699 % \leftbarharpoon (mathabx)
 19700 \DeclareTextCommand{\textleftbarharpoon}{PU}{\9051\152}%* U+296A
 19701 % U+296B LEFTWARDS HARPOON WITH BARB DOWN BELOW
 19702 % LONG DASH; \barleftharpoon (mathabx)
 19703 \DeclareTextCommand{\textbarleftharpoon}{PU}{\9051\153}%* U+296B
 19704 % U+296C RIGHTWARDS HARPOON WITH BARB UP ABOVE
 19705 % LONG DASH; \rightbarharpoon (mathabx)
 19706 \DeclareTextCommand{\textrightbarharpoon}{PU}{\9051\154}%* U+296C
 19707 % U+296D RIGHTWARDS HARPOON WITH BARB DOWN BELOW
 19708 % LONG DASH; \barrightharpoon (mathabx)
 19709 \DeclareTextCommand{\textbarrightharpoon}{PU}{\9051\155}%* U+296D
 19710 % U+296E UPWARDS HARPOON WITH BARB LEFT BESIDE DOWNWARDS HARPOON
 19711 % WITH BARB RIGHT; \updownharpoons (mathabx)
 19712 \DeclareTextCommand{\textupdownharpoons}{PU}{\9051\156}%* U+296E
 19713 % U+296F DOWNWARDS HARPOON WITH BARB LEFT BESIDE UPWARDS HARPOON

19714 % WITH BARB RIGHT; \downupharpoons (mathabx)
 19715 \DeclareTextCommand{\textdownupharpoons}{PU}{\9051\157}%* U+296F
 19716 % U+297F DOWN FISH TAIL
 19717 \DeclareTextCommand{\textmoo}{PU}{\9051\177\83\066}%* U+297F U+0336

51.2.34 Miscellaneous Mathematical Symbols-B: U+2980 to U+29FF

19718 % U+2987 Z NOTATION LEFT IMAGE BRACKET; \lparenthesis (stmaryrd)
 19719 \DeclareTextCommand{\textllparenthesis}{PU}{\9051\207}%* U+2987
 19720 % U+2988 Z NOTATION RIGHT IMAGE BRACKET; \rrparenthesis (stmaryrd)
 19721 \DeclareTextCommand{\textrrparenthesis}{PU}{\9051\210}%* U+2988
 19722 % U+29B0 REVERSED EMPTY SET; \invdiameter (wasysym)
 19723 \DeclareTextCommand{\textinvdiameter}{PU}{\9051\260}%* U+29B0
 19724 % U+29B6 CIRCLED VERTICAL BAR; \obar (stmaryrd)
 19725 \DeclareTextCommand{\textobar}{PU}{\9051\266}%* U+29B6
 19726 %* \textobar -> \textvarobar (stmaryrd)
 19727 % U+29B8 CIRCLED REVERSE SOLIDUS; \obslash (stmaryrd)
 19728 \DeclareTextCommand{\textobslash}{PU}{\9051\270}%* U+29B8
 19729 %* \textobslash -> \circledbslash (txfonts/pxfonts)
 19730 %* \textobslash -> \obackslash (mathabx)
 19731 %* \textobslash -> \varobslash (stmaryrd)
 19732 % U+29BA CIRCLE DIVIDED BY HORIZONTAL BAR AND TOP HALF
 19733 % DIVIDED BY VERTICAL BAR; \obot (mathabx)
 19734 \DeclareTextCommand{\textobot}{PU}{\9051\272}%* U+29BA
 19735 %* \textobot -> \odplus (ulsy)
 19736 % U+29BB CIRCLE WITH SUPERIMPOSED X; \NoChemicalCleaning (marvosym)
 19737 \DeclareTextCommand{\textNoChemicalCleaning}{PU}{\9051\273}%* U+29BB
 19738 % U+29C0 CIRCLED LESS-THAN; \olessthan (stmaryrd)
 19739 \DeclareTextCommand{\textolessthan}{PU}{\9051\300}%* U+29C0
 19740 %* \textolessthan -> \varolessthan (stmaryrd)
 19741 % U+29C1 CIRCLED GREATER-THAN; \ogreaterthan (stmaryrd)
 19742 \DeclareTextCommand{\textogreaterthan}{PU}{\9051\301}%* U+29C1
 19743 %* \textogreaterthan -> \varogreaterthan (stmaryrd)
 19744 % U+29C4 SQUARED RISING DIAGONAL SLASH; \boxslash (mathabx, stmaryrd)
 19745 \DeclareTextCommand{\textboxslash}{PU}{\9051\304}%* U+29C4
 19746 % U+29C5 SQUARED FALLING DIAGONAL SLASH; \boxbslash (stmaryrd)
 19747 \DeclareTextCommand{\textboxbslash}{PU}{\9051\305}%* U+29C5
 19748 % U+29C6 SQUARED ASTERISK; \boxast (stmaryrd)
 19749 \DeclareTextCommand{\textboxast}{PU}{\9051\306}%* U+29C6
 19750 % U+29C7 SQUARED SMALL CIRCLE; \boxcircle (stmaryrd)
 19751 \DeclareTextCommand{\textboxcircle}{PU}{\9051\307}%* U+29C7
 19752 % U+29C8 SQUARED SQUARE; \boxbox (stmaryrd)
 19753 \DeclareTextCommand{\textboxbox}{PU}{\9051\310}%* U+29C8
 19754 % U+29D3 BLACK BOWTIE; \Valve (marvosym)
 19755 \DeclareTextCommand{\textValve}{PU}{\9051\323}%* U+29D3
 19756 % U+29DF DOUBLE-ENDED MULTIMAP; \multimapboth (txfonts/pxfonts)
 19757 \DeclareTextCommand{\textmultimapboth}{PU}{\9051\337}%* U+29DF
 19758 % U+29E2 SHUFFLE PRODUCT; \shuffle (shuffle)
 19759 \DeclareTextCommand{\textshuffle}{PU}{\9051\342}%* U+29E2

51.2.35 Supplemental Mathematical Operators: U+2A00 to U+2AFF

19760 % U+2A04 N-ARY UNION OPERATOR WITH PLUS; \uplus (LaTeX)
 19761 \DeclareTextCommand{\textuplus}{PU}{\9052\004}%* U+2A04
 19762 % U+2A07 TWO LOGICAL AND OPERATOR; \bigdoublewedge (MnSymbol)
 19763 \DeclareTextCommand{\textbigdoublewedge}{PU}{\9052\007}%* U+2A07
 19764 % U+2A08 TWO LOGICAL OR OPERATOR; \bigdoublevee (MnSymbol)
 19765 \DeclareTextCommand{\textbigdoublevee}{PU}{\9052\010}%* U+2A08

```

19766 % U+2A1D JOIN; \Join (latexsym, amsfonts, amssymb, mathabx, txfonts,
19767 %   pxfonts, wasysym)
19768 \DeclareTextCommand{\textJoin}{PU}{\9052\035}%* U+2A1D
19769 % U+2A1F Z NOTATION SCHEMA COMPOSITION; \fatsemi (stmaryrd)
19770 \DeclareTextCommand{\textfatsemi}{PU}{\9052\037}%* U+2A1F
19771 % U+2A22 PLUS SIGN WITH SMALL CIRCLE ABOVE; \circplus (mathabx)
19772 \DeclareTextCommand{\textcircplus}{PU}{\9052\042}%* U+2A22
19773 % U+2A2A MINUS SIGN WITH DOT BELOW; \minusdot (MnSymbol)
19774 \DeclareTextCommand{\textminusdot}{PU}{\9052\052}%* U+2A2A
19775 %* \textminusdot -> \divdot (mathabx)
19776 % U+2A30 MULTIPLICATION SIGN WITH DOT ABOVE; \dottimes (math-
19777 %   abx)
19777 \DeclareTextCommand{\textdottimes}{PU}{\9052\060}%* U+2A30
19778 % U+2A32 SEMIDIRECT PRODUCT WITH BOTTOM CLOSED;
19779 %   \dtimes (mathdesign)
19780 \DeclareTextCommand{\textdtimes}{PU}{\9052\062}%* U+2A32
19781 % U+2A38 CIRCLED DIVISION SIGN; \odiv (mathabx)
19782 \DeclareTextCommand{\textodiv}{PU}{\9052\070}%* U+2A38
19783 % U+2A3C INTERIOR PRODUCT; \invneg (MnSymbol)
19784 \DeclareTextCommand{\textinvneg}{PU}{\9052\074}%* U+2A3C
19785 % U+2A4E DOUBLE SQUARE INTERSECTION; \sqdoublecap (mathabx)
19786 \DeclareTextCommand{\textsqdoublecap}{PU}{\9052\116}%* U+2A4E
19787 %* \textsqdoublecap -> \doublesqcap (MnSymbol)
19788 % U+2A40 INTERSECTION WITH DOT; \capdot (MnSymbol)
19789 \DeclareTextCommand{\textcapdot}{PU}{\9052\100}%* U+2A40
19790 % U+2A4F DOUBLE SQUARE UNION; \sqdoublecup (mathabx)
19791 \DeclareTextCommand{\textsqdoublecup}{PU}{\9052\117}%* U+2A4F
19792 %* \textsqdoublecup -> \doublesqcup (MnSymbol)
19793 % U+2A55 TWO INTERSECTING LOGICAL AND; \doublewedge (MnSymbol)
19794 \DeclareTextCommand{\textdoublewedge}{PU}{\9052\125}%* U+2A55
19795 % U+2A56 TWO INTERSECTING LOGICAL OR; \doublevee (MnSymbol)
19796 \DeclareTextCommand{\textdoublevee}{PU}{\9052\126}%* U+2A56
19797 %* \textdoublevee -> \merge (stmaryrd)
19798 % U+2A5E LOGICAL AND WITH DOUBLE OVERBAR;
19799 %   \doublebarwedge (AmS)
19800 \DeclareTextCommand{\textdoublebarwedge}{PU}{\9052\136}%* U+2A5E
19801 % U+2A63 LOGICAL OR WITH DOUBLE UNDERBAR;
19802 %   \veedoublebar (mahtabx)
19803 \DeclareTextCommand{\textveedoublebar}{PU}{\9052\143}%* U+2A63
19804 % U+2A66 EQUALS SIGN WITH DOT BELOW; \eqdot (MnSymbol)
19805 \DeclareTextCommand{\texteqdot}{PU}{\9052\146}%* U+2A66
19806 % \neqdot (MnSymbol)
19807 \DeclareTextCommand{\textneqdot}{PU}{\9052\146\83\070}%* U+2A66 U+0338
19808 % U+2A74 DOUBLE COLON EQUAL; \coloncolonequals (colonequals)
19809 \DeclareTextCommand{\textcoloncolonequals}{PU}{\9052\164}%* U+2A74
19810 % U+2A7D LESS-THAN OR SLANTED EQUAL TO; \leqslant (AmS)
19811 \DeclareTextCommand{\textleqslant}{PU}{\9052\175}%* U+2A7D
19812 % \nleqslant (txfonts/pxfonts)
19813 \DeclareTextCommand{\textnleqslant}{PU}{\9052\175\83\070}%* U+2A7D U+0338
19814 % U+2A7E GREATER-THAN OR SLANTED EQUAL TO; \geqslant (AmS)
19815 \DeclareTextCommand{\textgeqslant}{PU}{\9052\176}%* U+2A7E
19816 % \ngeqslant (txfonts/pxfonts)
19817 \DeclareTextCommand{\textngeqslant}{PU}{\9052\176\83\070}%* U+2A7E U+0338
19818 % U+2A85 LESS-THAN OR APPROXIMATE; \lessapprox (AmS)
19819 \DeclareTextCommand{\textlessapprox}{PU}{\9052\205}%* U+2A85
19820 % \nlessapprox (txfonts/pxfonts)
19821 \DeclareTextCommand{\textnlessapprox}{PU}{\9052\205\83\070}%* U+2A85 U+0338

```

19822 % U+2A86 GREATER-THAN OR APPROXIMATE; \gtrapprox (AmS)
 19823 \DeclareTextCommand{\textgtrapprox}{PU}{\9052\206}%* U+2A86
 19824 % \ngtrapprox (txfonts/pxfonts)
 19825 \DeclareTextCommand{\textngtrapprox}{PU}{\9052\206\83\070}%* U+2A86 U+0338
 19826 % U+2A87 LESS-THAN AND SINGLE-LINE NOT EQUAL TO; \lneq (AmS)
 19827 \DeclareTextCommand{\textlneq}{PU}{\9052\207}%* U+2A87
 19828 % U+2A88 GREATER-THAN AND SINGLE-LINE NOT EQUAL TO;
 19829 % \gneq (AmS)
 19830 \DeclareTextCommand{\textgneq}{PU}{\9052\210}%* U+2A88
 19831 % U+2A89 LESS-THAN AND NOT APPROXIMATE; \lnapprox (AmS)
 19832 \DeclareTextCommand{\textlnapprox}{PU}{\9052\211}%* U+2A89
 19833 % U+2A8A GREATER-THAN AND NOT APPROXIMATE; \gnapprox (AmS)
 19834 \DeclareTextCommand{\textgnapprox}{PU}{\9052\212}%* U+2A8A
 19835 % U+2A8B LESS-THAN ABOVE DOUBLE-LINE EQUAL ABOVE GREATER-THAN;
 19836 % \lesseqgtr (AmS)
 19837 \DeclareTextCommand{\textlesseqgtr}{PU}{\9052\213}%* U+2A8B
 19838 % U+2A8C GREATER-THAN ABOVE DOUBLE-LINE EQUAL ABOVE LESS-THAN;
 19839 % \gtreqless (AmS)
 19840 \DeclareTextCommand{\textgtreqless}{PU}{\9052\214}%* U+2A8C
 19841 % U+2A95 SLANTED EQUAL TO OR LESS-THAN; \eqslantless (AmS)
 19842 \DeclareTextCommand{\texteqslantless}{PU}{\9052\225}%* U+2A95
 19843 % U+2A96 SLANTED EQUAL TO OR GREATER-THAN; \eqslantgtr (AmS)
 19844 \DeclareTextCommand{\texteqslantgtr}{PU}{\9052\226}%* U+2A96
 19845 % U+2AA6 LESS-THAN CLOSED BY CURVE; \leftslice (stmaryrd)
 19846 \DeclareTextCommand{\textleftslice}{PU}{\9052\246}%* U+2AA6
 19847 % U+2AA7 GREATER-THAN CLOSED BY CURVE; \rightslice (stmaryrd)
 19848 \DeclareTextCommand{\textright slice}{PU}{\9052\247}%* U+2AA7
 19849 % U+2AAF PRECEDES ABOVE SINGLE-LINE EQUALS SIGN; \preceq (Mn-Symbol)
 19850 \DeclareTextCommand{\textpreceq}{PU}{\9052\257}%* U+2AAF
 19851 % \npreceq (txfonts/pxfonts)
 19852 \DeclareTextCommand{\textnpreceq}{PU}{\9052\257\83\070}%* U+2AAF U+0338
 19853 % U+2AB0 SUCCEEDS ABOVE SINGLE-LINE EQUALS SIGN; \succeq (Mn-Symbol)
 19854 \DeclareTextCommand{\textsucceq}{PU}{\9052\260}%* U+2AB0
 19855 % \nsucceq (txfonts/pxfonts)
 19856 \DeclareTextCommand{\textnsucceq}{PU}{\9052\260\83\070}%* U+2AB0 U+0338
 19857 % U+2AB1 PRECEDES ABOVE SINGLE-LINE NOT EQUAL TO; \precneq (mathabx)
 19858 \DeclareTextCommand{\textprecneq}{PU}{\9052\261}%* U+2AB1
 19859 % U+2AB2 SUCCEEDS ABOVE SINGLE-LINE NOT EQUAL TO; \succneq (mathabx)
 19860 \DeclareTextCommand{\textsuccneq}{PU}{\9052\262}%* U+2AB2
 19861 % U+2AB3 PRECEDES ABOVE EQUALS SIGN; \preceqq (txfonts/pxfonts)
 19862 \DeclareTextCommand{\textpreceqq}{PU}{\9052\263}%* U+2AB3
 19863 % \npreceqq (txfonts/pxfonts)
 19864 \DeclareTextCommand{\textnpreceqq}{PU}{\9052\263\83\070}%* U+2AB3 U+0338
 19865 % U+2AB4 SUCCEEDS ABOVE EQUALS SIGN; \succeqq (txfonts/pxfonts)
 19866 \DeclareTextCommand{\textsucceqq}{PU}{\9052\264}%* U+2AB4
 19867 % \nsucceqq (txfonts/pxfonts)
 19868 \DeclareTextCommand{\textnsucceqq}{PU}{\9052\264\83\070}%* U+2AB4 U+0338
 19869 % U+2AB5 PRECEDES ABOVE NOT EQUAL TO; \precneqq (txfonts/pxfonts)
 19870 \DeclareTextCommand{\textprecneqq}{PU}{\9052\265}%* U+2AB5
 19871 % U+2AB6 SUCCEEDS ABOVE NOT EQUAL TO; \succneqq (txfonts/pxfonts)
 19872 \DeclareTextCommand{\textsuccneqq}{PU}{\9052\266}%* U+2AB6
 19873 % U+2AB7 PRECEDES ABOVE ALMOST EQUAL TO; \precapprox (AmS)
 19874 \DeclareTextCommand{\textprecapprox}{PU}{\9052\267}%* U+2AB7

```

19875 % \nprecapprox (txfonts/pxfonts)
19876 \DeclareTextCommand{\textnprecapprox}{PU}{\9052\267\83\070}%* U+2AB7 U+0338
19877 % U+2AB8 SUCCEEDS ABOVE ALMOST EQUAL TO; \succapprox (AmS)
19878 \DeclareTextCommand{\textsuccapprox}{PU}{\9052\270}%* U+2AB8
19879 % \nsuccapprox (txfonts/pxfonts)
19880 \DeclareTextCommand{\textnsuccapprox}{PU}{\9052\270\83\070}%* U+2AB8 U+0338
19881 % U+2AB9 PRECEDES ABOVE NOT ALMOST EQUAL TO; \precnapprox (AmS)
19882 \DeclareTextCommand{\textprecnapprox}{PU}{\9052\271}%* U+2AB9
19883 % U+2ABA SUCCEEDS ABOVE NOT ALMOST EQUAL TO; \succnapprox (AmS)
19884 \DeclareTextCommand{\textsuccnapprox}{PU}{\9052\272}%* U+2ABA
19885 % U+2AC5 SUBSET OF ABOVE EQUALS SIGN; \subseteqq (AmS)
19886 \DeclareTextCommand{\textsubseteqq}{PU}{\9052\305}%* U+2AC5
19887 % \nsubseteqq (txfonts/pxfonts, mathabx)
19888 \DeclareTextCommand{\textnsubseteqq}{PU}{\9052\305\83\070}%* U+2AC5 U+0338
19889 % U+2AC6 SUPERSET OF ABOVE EQUALS SIGN; \supseteqq (AmS)
19890 \DeclareTextCommand{\textsupseteqq}{PU}{\9052\306}%* U+2AC6
19891 % \nsupseteqq (mathabx)
19892 \DeclareTextCommand{\textnsupseteqq}{PU}{\9052\306\83\070}%* U+2AC6 U+0338
19893 % U+2AE3 DOUBLE VERTICAL BAR LEFT TURNSTILE
19894 \DeclareTextCommand{\textdashV}{PU}{\9052\343}%* U+2AE3
19895 %* \textdashV -> \leftVdash (MnSymbol)
19896 % \ndashV (mathabx)
19897 \DeclareTextCommand{\textndashV}{PU}{\9052\343\83\070}%* U+2AE3 U+0338
19898 %* \textndashV -> \nleftVdash (MnSymbol)
19899 % U+2AE4 VERTICAL BAR DOUBLE LEFT TURNSTILE; \Dashv (mathabx)
19900 \DeclareTextCommand{\textDashv}{PU}{\9052\344}%* U+2AE4
19901 %* \textDashv -> \leftmodels (MnSymbol)
19902 % \nDashv (mathabx)
19903 \DeclareTextCommand{\textnDashv}{PU}{\9052\344\83\070}%* U+2AE4 U+0338
19904 %* \textnDashv -> \nleftmodels (MnSymbol)
19905 % U+2AE5 DOUBLE VERTICAL BAR DOUBLE LEFT TURNSTILE;
19906 % \DashV (mathabx)
19907 \DeclareTextCommand{\textDashV}{PU}{\9052\345}%* U+2AE5
19908 %* \textDashV -> \leftModels (MnSymbol)
19909 % \nDashV (mathabx)
19910 \DeclareTextCommand{\textnDashV}{PU}{\9052\345\83\070}%* U+2AE5 U+0338
19911 %* \textnDashV -> \nleftModels (MnSymbol)
19912 % U+2AEA DOUBLE DOWN TACK; \downmodels (MnSymbol)
19913 \DeclareTextCommand{\textdownmodels}{PU}{\9052\352}%* U+2AEA
19914 % \ndownmodels (MnSymbol)
19915 \DeclareTextCommand{\textndownmodels}{PU}{\9052\352\83\070}%* U+2AEA U+0338
19916 % U+2AEB DOUBLE UP TACK; \upmodels (MnSymbol)
19917 \DeclareTextCommand{\textupmodels}{PU}{\9052\353}%* U+2AEB
19918 % \nupmodels (MnSymbol)
19919 \DeclareTextCommand{\textnupmodels}{PU}{\9052\353\83\070}%* U+2AEB U+0338
19920 % U+2AEF VERTICAL LINE WITH CIRCLE ABOVE; \upspoon (MnSymbol)
19921 \DeclareTextCommand{\textupspoon}{PU}{\9052\357}%* U+2AEF
19922 % U+2AF4 TRIPLE VERTICAL BAR BINARY RELATION;
19923 % \interleave (stmaryrd)
19924 \DeclareTextCommand{\textinterleave}{PU}{\9052\364}%* U+2AF4
19925 % U+2AFD DOUBLE SOLIDUS OPERATOR; \sslash (stmaryrd)
19926 \DeclareTextCommand{\textsslash}{PU}{\9052\375}%* U+2AFD
19927 %* \textsslash -> \varparallel (txfonts/pxfonts)

```

51.2.36 Miscellaneous Symbols and Arrows: U+2B00 to U+2BFF

19928 % U+2B20 WHITE PENTAGON; \pentagon (wasysym)
 19929 \DeclareTextCommand{\textpentagon}{PU}{\9053\040}%* U+2B20
 19930 % U+2B21 WHITE HEXAGON; \varhexagon (wasysym)
 19931 \DeclareTextCommand{\textvarhexagon}{PU}{\9053\041}%* U+2B21

51.2.37 Latin Extended-C: U+2C60 to U+2C7F

19932 % U+2C7C LATIN SUBSCRIPT SMALL LETTER J
 19933 \DeclareTextCommand{\textjinferior}{PU}{\9054\174}%* U+2C7C

51.2.38 Supplemental Punctuation: U+2E00 to U+2E7F

19934 % U+2E13 DOTTED OBELOS; \slashdiv (MnSymbol)
 19935 \DeclareTextCommand{\textslashdiv}{PU}{\9056\023}%* U+2E13
 19936 % U+2E18 INVERTED INTERROBANG; \textinterrobangdown (textcomp)
 19937 \DeclareTextCommand{\textinterrobangdown}{PU}{\9056\030}% U+2E18
 19938 % U+2E2D FIVE DOT MARK; \fivedots (MnSymbol)
 19939 \DeclareTextCommand{\textfivedots}{PU}{\9056\055}%* U+2E2D

51.2.39 Modifier Tone Letters: U+A700 to U+A71F

19940 % U+A71B MODIFIER LETTER RAISED UP ARROW; \textupstep (tipa)
 19941 \DeclareTextCommand{\textupstep}{PU}{\9247\033}% U+A71B
 19942 % U+A71C MODIFIER LETTER RAISED DOWN ARROW;
 19943 % \textdownstep (tipa)
 19944 \DeclareTextCommand{\textdownstep}{PU}{\9247\034}% U+A71C

51.2.40 Latin Extended-D: U+A720 to U+A7FF

19945 % U+A727 LATIN SMALL LETTER HENG; \textheng (tipx)
 19946 \DeclareTextCommand{\textPUheng}{PU}{\9247\047}% U+A727
 19947 %* \textPUheng -> \textheng (tipx)
 19948 % U+A72C LATIN CAPITAL LETTER CUATRILLO; \textlhookfour (tipx)
 19949 \DeclareTextCommand{\textPULhookfour}{PU}{\9247\054}% U+A72C
 19950 %* \textPULhookfour -> \textlhookfour (tipx)
 19951 % U+A730 LATIN LETTER SMALL CAPITAL F; \textscf (tipx)
 19952 \DeclareTextCommand{\textPUscf}{PU}{\9247\060}% U+A730
 19953 %* \textPUscf -> \textscf (tipx)
 19954 % U+A735 LATIN SMALL LETTER AO; \textao lig (tipx)
 19955 \DeclareTextCommand{\textPUaolig}{PU}{\9247\065}% U+A735
 19956 %* \textPUaolig -> \textao lig (tipx)
 19957 % U+A74F LATIN SMALL LETTER OO; \oo (wsuipa)
 19958 \DeclareTextCommand{\textoo}{PU}{\9247\117}%* U+A74F
 19959 % U+A788 MODIFIER LETTER LOW CIRCUMFLEX ACCENT
 19960 \DeclareTextCommand{\textcircumlow}{PU}{\9247\210}% U+A788

51.2.41 Alphabetic Presentation Forms: U+FB00 to U+FB4F

19961 % U+FB01 LATIN SMALL LIGATURE FI; fi
 19962 \DeclareTextCommand{\textfi}{PU}{\9373\001}% U+FB01
 19963 % U+FB02 LATIN SMALL LIGATURE FL; fl
 19964 \DeclareTextCommand{\textfl}{PU}{\9373\002}% U+FB02

51.2.42 Musical Symbols: U+1D100 to U+1D1FF

19965 % U+1D13B MUSICAL SYMBOL WHOLE REST; \GaPa (harmony)
 19966 \DeclareTextCommand{\textGaPa}{PU}{\9330\064\9335\073}%* U+1D13B
 19967 % U+1D13C MUSICAL SYMBOL HALF REST; \HaPa (harmony)
 19968 \DeclareTextCommand{\textHaPa}{PU}{\9330\064\9335\074}%* U+1D13C
 19969 % U+1D13D MUSICAL SYMBOL QUARTER REST; \ViPa (harmony)
 19970 \DeclareTextCommand{\textViPa}{PU}{\9330\064\9335\075}%* U+1D13D
 19971 % U+1D13E MUSICAL SYMBOL EIGHTH REST; \AcPa (harmony)
 19972 \DeclareTextCommand{\textAcPa}{PU}{\9330\064\9335\076}%* U+1D13E

19973 % U+1D13F MUSICAL SYMBOL SIXTEENTH REST; \SePa (harmony)
 19974 \DeclareTextCommand{\textSePa}{PU}{\9330\064\9335\077}%* U+1D13F
 19975 % U+1D140 MUSICAL SYMBOL THIRTY-SECOND REST; \ZwPa (harmony)
 19976 \DeclareTextCommand{\textZwPa}{PU}{\9330\064\9335\100}%* U+1D140
 19977 % U+1D15D MUSICAL SYMBOL WHOLE NOTE; \fullnote (wasysym)
 19978 \DeclareTextCommand{\textfullnote}{PU}{\9330\064\9335\135}%* U+1D15D
 19979 %* \textfullnote -> \Ganz (harmony)
 19980 % U+1D15E MUSICAL SYMBOL HALF NOTE; \halfnote (wasysym)
 19981 \DeclareTextCommand{\texthalfnote}{PU}{\9330\064\9335\136}%* U+1D15E
 19982 %* \texthalfnote -> \Halb (harmony)
 19983 % U+1D15F MUSICAL SYMBOL QUARTER NOTE; \Vier (harmony)
 19984 \DeclareTextCommand{\textVier}{PU}{\9330\064\9335\137}%* U+1D15F
 19985 % U+1D160 MUSICAL SYMBOL EIGHTH NOTE; \Acht (harmony)
 19986 \DeclareTextCommand{\textAcht}{PU}{\9330\064\9335\140}%* U+1D160
 19987 % U+1D161 MUSICAL SYMBOL SIXTEENTH NOTE; \Sech (harmony)
 19988 \DeclareTextCommand{\textSech}{PU}{\9330\064\9335\141}%* U+1D161
 19989 % U+1D162 MUSICAL SYMBOL THIRTY-SECOND NOTE; \Zwdr (harmony)
 19990 \DeclareTextCommand{\textZwdr}{PU}{\9330\064\9335\142}%* U+1D162

51.2.43 Miscellaneous Symbols and Pictographs: U+1F300 to U+1F5FF

19991 % U+1F30D EARTH GLOBE EUROPE-AFRICA; \Mundus (marvosym)
 19992 \DeclareTextCommand{\textMundus}{PU}{\9330\074\9337\015}%* U+1F30D
 19993 % U+1F319 CRESCENT MOON; \Moon (marvosym)
 19994 \DeclareTextCommand{\textMoon}{PU}{\9330\074\9337\031}%* U+1F319
 19995 % U+1F468 MAN; \ManFace (marvosym)
 19996 \DeclareTextCommand{\textManFace}{PU}{\9330\075\9334\150}%* U+1F468
 19997 % U+1F469 WOMAN; \WomanFace (marvosym)
 19998 \DeclareTextCommand{\textWomanFace}{PU}{\9330\075\9334\151}%* U+1F469
 19999 %* \textWomanFace -> \Womanface (marvosym)
 20000 % U+1F4E0 FAX MACHINE; \Fax (marvosym)
 20001 \DeclareTextCommand{\textFax}{PU}{\9330\075\9334\340}%* U+1F4E0
 20002 %* \textFax -> \Faxmachine (marvosym)
 20003 % U+1F525 FIRE; \Fire (ifsym)
 20004 \DeclareTextCommand{\textFire}{PU}{\9330\075\9335\045}%* U+1F525

51.2.44 Transport and Map Symbols: U+1F680 to U+1F6FF

20005 % U+1F6B2 BICYCLE; \Bicycle (marvosym)
 20006 \DeclareTextCommand{\textBicycle}{PU}{\9330\075\9336\262}%* U+1F6B2
 20007 % U+1F6B9 MENS SYMBOL; \Gentsroom (marvosym)
 20008 \DeclareTextCommand{\textGentsroom}{PU}{\9330\075\9336\271}%* U+1F6B9
 20009 % U+1F6BA WOMENS SYMBOL; \Ladiesroom (marvosym)
 20010 \DeclareTextCommand{\textLadiesroom}{PU}{\9330\075\9336\272}%* U+1F6BA

51.2.45 Miscellaneous

20011 \DeclareTextCommand{\SS}{PU}{SS}%
 20012 % \textcopyleft (textcomp)
 20013 \DeclareTextCommand{\textcopyleft}{PU}{\9041\204\9040\335}% U+2184 U+20DD
 20014 % \ccnc (ccllicenses)
 20015 \DeclareTextCommand{\textccnc}{PU}{\80\044\9040\340}%* U+0024 U+20E0
 20016 % \ccnd (ccllicenses)
 20017 \DeclareTextCommand{\textccnd}{PU}{=\9040\335}%* U+003D U+20DD
 20018 % \ccsa (ccllicenses)
 20019 \DeclareTextCommand{\textccsa}{PU}{\9047\362\9040\335}%* U+27F2 U+20DD
 20020 % \Info (marvosym, china2e)
 20021 \DeclareTextCommand{\textInfo}{PU}{\9330\065\9334\042\9040\336}%* U+1D422 U+20DE
 20022 % \CESign (marvosym)
 20023 \DeclareTextCommand{\textCESign}{PU}{\80\103\80\105}%* U+0043 U+0045

20024 %* \textCESign -> \CESign (marvosym)

51.2.46 Aliases

Aliases (german.sty)

```
20025 \DeclareTextCommand{\textglqq}{PU}{\quotedblbase}%
20026 \DeclareTextCommand{\textgrqq}{PU}{\textquotedblleft}%
20027 \DeclareTextCommand{\textglq}{PU}{\quotesinglbase}%
20028 \DeclareTextCommand{\textgrq}{PU}{\textquoteleft}%
20029 \DeclareTextCommand{\textflqq}{PU}{\guillemotleft}%
20030 \DeclareTextCommand{\textfrqq}{PU}{\guillemotright}%
20031 \DeclareTextCommand{\textflq}{PU}{\guilsinglleft}%
20032 \DeclareTextCommand{\textfrq}{PU}{\guilsinglright}%

```

Aliases (math names)

```
20033 \DeclareTextCommand{\textneg}{PU}{\textlogicalnot}%*
20034 \DeclareTextCommand{\texttimes}{PU}{\textmultiply}%*
20035 \DeclareTextCommand{\textdiv}{PU}{\textdivide}%*
20036 \DeclareTextCommand{\textpm}{PU}{\textplusminus}%*
20037 \DeclareTextCommand{\textcdot}{PU}{\textperiodcentered}%*
20038 </puenc>

```

51.3 PU encoding, additions for VnTeX

This file is provided by Han The Thanh.

```
20039 <*puvnenc>
20040 \DeclareTextCommand{\abreve}{PU}{\81\003}% U+0103
20041 \DeclareTextCommand{\acircumflex}{PU}{\80\342}% U+00E2
20042 \DeclareTextCommand{\ecircumflex}{PU}{\80\352}% U+00EA
20043 \DeclareTextCommand{\ocircumflex}{PU}{\80\364}% U+00F4
20044 \DeclareTextCommand{\ohorn}{PU}{\81\241}% U+01A1
20045 \DeclareTextCommand{\uhorn}{PU}{\81\260}% U+01B0
20046 \DeclareTextCommand{\ABREVE}{PU}{\81\002}% U+0102
20047 \DeclareTextCommand{\ACIRCUMFLEX}{PU}{\80\302}% U+00C2
20048 \DeclareTextCommand{\ECIRCUMFLEX}{PU}{\80\312}% U+00CA
20049 \DeclareTextCommand{\OCIRCUMFLEX}{PU}{\80\324}% U+00D4
20050 \DeclareTextCommand{\OHORN}{PU}{\81\240}% U+01A0
20051 \DeclareTextCommand{\UHORN}{PU}{\81\257}% U+01AF
20052 \DeclareTextCompositeCommand{\'}{PU}{a}{\80\341}% U+00E1
20053 \DeclareTextCompositeCommand{\d}{PU}{a}{\9036\241}% U+1EA1
20054 \DeclareTextCompositeCommand{\'}{PU}{a}{\80\340}% U+00E0
20055 \DeclareTextCompositeCommand{\h}{PU}{a}{\9036\243}% U+1EA3
20056 \DeclareTextCompositeCommand{\~}{PU}{a}{\80\343}% U+00E3
20057 \DeclareTextCompositeCommand{\'}{PU}{\abreve}{\9036\257}% U+1EAF
20058 \DeclareTextCompositeCommand{\d}{PU}{\abreve}{\9036\267}% U+1EB7
20059 \DeclareTextCompositeCommand{\'}{PU}{\abreve}{\9036\261}% U+1EB1
20060 \DeclareTextCompositeCommand{\h}{PU}{\abreve}{\9036\263}% U+1EB3
20061 \DeclareTextCompositeCommand{\~}{PU}{\abreve}{\9036\265}% U+1EB5
20062 \DeclareTextCompositeCommand{\'}{PU}{\acircumflex}{\9036\245}% U+1EA5
20063 \DeclareTextCompositeCommand{\d}{PU}{\acircumflex}{\9036\255}% U+1EAD
20064 \DeclareTextCompositeCommand{\'}{PU}{\acircumflex}{\9036\247}% U+1EA7
20065 \DeclareTextCompositeCommand{\h}{PU}{\acircumflex}{\9036\251}% U+1EA9
20066 \DeclareTextCompositeCommand{\~}{PU}{\acircumflex}{\9036\253}% U+1EAB
20067 \DeclareTextCompositeCommand{\'}{PU}{e}{\80\351}% U+00E9
20068 \DeclareTextCompositeCommand{\d}{PU}{e}{\9036\271}% U+1EB9
20069 \DeclareTextCompositeCommand{\'}{PU}{e}{\80\350}% U+00E8

```

20070 \DeclareTextCompositeCommand{\h}{PU}{e}{\9036\273}% U+1EBB
 20071 \DeclareTextCompositeCommand{\~}{PU}{e}{\9036\275}% U+1EBD
 20072 \DeclareTextCompositeCommand{\'}{PU}{\ecircumflex}{\9036\277}% U+1EBF
 20073 \DeclareTextCompositeCommand{\d}{PU}{\ecircumflex}{\9036\307}% U+1EC7
 20074 \DeclareTextCompositeCommand{\'}{PU}{\ecircumflex}{\9036\301}% U+1EC1
 20075 \DeclareTextCompositeCommand{\h}{PU}{\ecircumflex}{\9036\303}% U+1EC3
 20076 \DeclareTextCompositeCommand{\~}{PU}{\ecircumflex}{\9036\305}% U+1EC5
 20077 \DeclareTextCompositeCommand{\'}{PU}{i}{\80\355}% U+00ED
 20078 \DeclareTextCompositeCommand{\d}{PU}{i}{\9036\313}% U+1ECB
 20079 \DeclareTextCompositeCommand{\'}{PU}{i}{\80\354}% U+00EC
 20080 \DeclareTextCompositeCommand{\h}{PU}{i}{\9036\311}% U+1EC9
 20081 \DeclareTextCompositeCommand{\~}{PU}{i}{\81\051}% U+0129
 20082 \DeclareTextCompositeCommand{\'}{PU}{o}{\80\363}% U+00F3
 20083 \DeclareTextCompositeCommand{\d}{PU}{o}{\9036\315}% U+1ECD
 20084 \DeclareTextCompositeCommand{\'}{PU}{o}{\80\362}% U+00F2
 20085 \DeclareTextCompositeCommand{\h}{PU}{o}{\9036\317}% U+1ECF
 20086 \DeclareTextCompositeCommand{\~}{PU}{o}{\80\365}% U+00F5
 20087 \DeclareTextCompositeCommand{\'}{PU}{\ocircumflex}{\9036\321}% U+1ED1
 20088 \DeclareTextCompositeCommand{\d}{PU}{\ocircumflex}{\9036\331}% U+1ED9
 20089 \DeclareTextCompositeCommand{\'}{PU}{\ocircumflex}{\9036\323}% U+1ED3
 20090 \DeclareTextCompositeCommand{\h}{PU}{\ocircumflex}{\9036\325}% U+1ED5
 20091 \DeclareTextCompositeCommand{\~}{PU}{\ocircumflex}{\9036\327}% U+1ED7
 20092 \DeclareTextCompositeCommand{\'}{PU}{\ohorn}{\9036\333}% U+1EDB
 20093 \DeclareTextCompositeCommand{\d}{PU}{\ohorn}{\9036\343}% U+1EE3
 20094 \DeclareTextCompositeCommand{\'}{PU}{\ohorn}{\9036\335}% U+1EDD
 20095 \DeclareTextCompositeCommand{\h}{PU}{\ohorn}{\9036\337}% U+1EDF
 20096 \DeclareTextCompositeCommand{\~}{PU}{\ohorn}{\9036\341}% U+1EE1
 20097 \DeclareTextCompositeCommand{\'}{PU}{u}{\80\372}% U+00FA
 20098 \DeclareTextCompositeCommand{\d}{PU}{u}{\9036\345}% U+1EE5
 20099 \DeclareTextCompositeCommand{\'}{PU}{u}{\80\371}% U+00F9
 20100 \DeclareTextCompositeCommand{\h}{PU}{u}{\9036\347}% U+1EE7
 20101 \DeclareTextCompositeCommand{\~}{PU}{u}{\81\151}% U+0169
 20102 \DeclareTextCompositeCommand{\'}{PU}{\uhorn}{\9036\351}% U+1EE9
 20103 \DeclareTextCompositeCommand{\d}{PU}{\uhorn}{\9036\361}% U+1EF1
 20104 \DeclareTextCompositeCommand{\'}{PU}{\uhorn}{\9036\353}% U+1EEB
 20105 \DeclareTextCompositeCommand{\h}{PU}{\uhorn}{\9036\355}% U+1EED
 20106 \DeclareTextCompositeCommand{\~}{PU}{\uhorn}{\9036\357}% U+1EEF
 20107 \DeclareTextCompositeCommand{\'}{PU}{y}{\80\375}% U+00FD
 20108 \DeclareTextCompositeCommand{\d}{PU}{y}{\9036\365}% U+1EF5
 20109 \DeclareTextCompositeCommand{\'}{PU}{y}{\9036\363}% U+1EF3
 20110 \DeclareTextCompositeCommand{\h}{PU}{y}{\9036\367}% U+1EF7
 20111 \DeclareTextCompositeCommand{\~}{PU}{y}{\9036\371}% U+1EF9
 20112 \DeclareTextCompositeCommand{\'}{PU}{A}{\80\301}% U+00C1
 20113 \DeclareTextCompositeCommand{\d}{PU}{A}{\9036\240}% U+1EA0
 20114 \DeclareTextCompositeCommand{\'}{PU}{A}{\80\300}% U+00C0
 20115 \DeclareTextCompositeCommand{\h}{PU}{A}{\9036\242}% U+1EA2
 20116 \DeclareTextCompositeCommand{\~}{PU}{A}{\80\303}% U+00C3
 20117 \DeclareTextCompositeCommand{\'}{PU}{\ABREVE}{\9036\256}% U+1EAE
 20118 \DeclareTextCompositeCommand{\d}{PU}{\ABREVE}{\9036\266}% U+1EB6
 20119 \DeclareTextCompositeCommand{\'}{PU}{\ABREVE}{\9036\260}% U+1EB0
 20120 \DeclareTextCompositeCommand{\h}{PU}{\ABREVE}{\9036\262}% U+1EB2
 20121 \DeclareTextCompositeCommand{\~}{PU}{\ABREVE}{\9036\264}% U+1EB4
 20122 \DeclareTextCompositeCommand{\'}{PU}{\ACIRCUMFLEX}{\9036\244}% U+1EA4
 20123 \DeclareTextCompositeCommand{\d}{PU}{\ACIRCUMFLEX}{\9036\254}% U+1EAC
 20124 \DeclareTextCompositeCommand{\'}{PU}{\ACIRCUMFLEX}{\9036\246}% U+1EA6
 20125 \DeclareTextCompositeCommand{\h}{PU}{\ACIRCUMFLEX}{\9036\250}% U+1EA8
 20126 \DeclareTextCompositeCommand{\~}{PU}{\ACIRCUMFLEX}{\9036\252}% U+1EAA


```

20127 \DeclareTextCompositeCommand{\'}{PU}{E}{\80\311}% U+00C9
20128 \DeclareTextCompositeCommand{\d}{PU}{E}{\9036\270}% U+1EB8
20129 \DeclareTextCompositeCommand{\'}{PU}{E}{\80\310}% U+00C8
20130 \DeclareTextCompositeCommand{\h}{PU}{E}{\9036\272}% U+1EBA
20131 \DeclareTextCompositeCommand{\~}{PU}{E}{\9036\274}% U+1EBC
20132 \DeclareTextCompositeCommand{\'}{PU}{\ECIRCUMFLEX}{\9036\276}% U+1EBE
20133 \DeclareTextCompositeCommand{\d}{PU}{\ECIRCUMFLEX}{\9036\306}% U+1EC6
20134 \DeclareTextCompositeCommand{\'}{PU}{\ECIRCUMFLEX}{\9036\300}% U+1EC0
20135 \DeclareTextCompositeCommand{\h}{PU}{\ECIRCUMFLEX}{\9036\302}% U+1EC2
20136 \DeclareTextCompositeCommand{\~}{PU}{\ECIRCUMFLEX}{\9036\304}% U+1EC4
20137 \DeclareTextCompositeCommand{\'}{PU}{I}{\80\315}% U+00CD
20138 \DeclareTextCompositeCommand{\d}{PU}{I}{\9036\312}% U+1ECA
20139 \DeclareTextCompositeCommand{\'}{PU}{I}{\80\314}% U+00CC
20140 \DeclareTextCompositeCommand{\h}{PU}{I}{\9036\310}% U+1EC8
20141 \DeclareTextCompositeCommand{\~}{PU}{I}{\81\050}% U+0128
20142 \DeclareTextCompositeCommand{\'}{PU}{O}{\80\323}% U+00D3
20143 \DeclareTextCompositeCommand{\d}{PU}{O}{\9036\314}% U+1ECC
20144 \DeclareTextCompositeCommand{\'}{PU}{O}{\80\322}% U+00D2
20145 \DeclareTextCompositeCommand{\h}{PU}{O}{\9036\316}% U+1ECE
20146 \DeclareTextCompositeCommand{\~}{PU}{O}{\80\325}% U+00D5
20147 \DeclareTextCompositeCommand{\'}{PU}{\OCIRCUMFLEX}{\9036\320}% U+1ED0
20148 \DeclareTextCompositeCommand{\d}{PU}{\OCIRCUMFLEX}{\9036\330}% U+1ED8
20149 \DeclareTextCompositeCommand{\'}{PU}{\OCIRCUMFLEX}{\9036\322}% U+1ED2
20150 \DeclareTextCompositeCommand{\h}{PU}{\OCIRCUMFLEX}{\9036\324}% U+1ED4
20151 \DeclareTextCompositeCommand{\~}{PU}{\OCIRCUMFLEX}{\9036\326}% U+1ED6
20152 \DeclareTextCompositeCommand{\'}{PU}{\OHORN}{\9036\332}% U+1EDA
20153 \DeclareTextCompositeCommand{\d}{PU}{\OHORN}{\9036\342}% U+1EE2
20154 \DeclareTextCompositeCommand{\'}{PU}{\OHORN}{\9036\334}% U+1EDC
20155 \DeclareTextCompositeCommand{\h}{PU}{\OHORN}{\9036\336}% U+1EDE
20156 \DeclareTextCompositeCommand{\~}{PU}{\OHORN}{\9036\340}% U+1EE0
20157 \DeclareTextCompositeCommand{\'}{PU}{U}{\80\332}% U+00DA
20158 \DeclareTextCompositeCommand{\d}{PU}{U}{\9036\344}% U+1EE4
20159 \DeclareTextCompositeCommand{\'}{PU}{U}{\80\331}% U+00D9
20160 \DeclareTextCompositeCommand{\h}{PU}{U}{\9036\346}% U+1EE6
20161 \DeclareTextCompositeCommand{\~}{PU}{U}{\81\150}% U+0168
20162 \DeclareTextCompositeCommand{\'}{PU}{\UHORN}{\9036\350}% U+1EE8
20163 \DeclareTextCompositeCommand{\d}{PU}{\UHORN}{\9036\360}% U+1EF0
20164 \DeclareTextCompositeCommand{\'}{PU}{\UHORN}{\9036\352}% U+1EEA
20165 \DeclareTextCompositeCommand{\h}{PU}{\UHORN}{\9036\354}% U+1EEC
20166 \DeclareTextCompositeCommand{\~}{PU}{\UHORN}{\9036\356}% U+1EEE
20167 \DeclareTextCompositeCommand{\'}{PU}{Y}{\80\335}% U+00DD
20168 \DeclareTextCompositeCommand{\d}{PU}{Y}{\9036\364}% U+1EF4
20169 \DeclareTextCompositeCommand{\'}{PU}{Y}{\9036\362}% U+1EF2
20170 \DeclareTextCompositeCommand{\h}{PU}{Y}{\9036\366}% U+1EF6
20171 \DeclareTextCompositeCommand{\~}{PU}{Y}{\9036\370}% U+1EF8
20172 </p>

```

51.4 PU encoding, additions for Arabi

This file is provided and maintained by Youssef Jabri.

```

20173 < *puarenc >
20174 % U+0621;afii57409;ARABIC LETTER HAMZA
20175 \DeclareTextCommand{\hamza}{PU}{\86\041}% U+0621
20176 % U+0622;afii57410;ARABIC LETTER ALEF WITH MADDA ABOVE
20177 \DeclareTextCommand{\alefmadda}{PU}{\86\042}% U+0622
20178 % U+0623;afii57411;ARABIC LETTER ALEF WITH HAMZA ABOVE

```

20179 \DeclareTextCommand{\alefhamza}{PU}{\86\043}% U+0623
 20180 % U+0624;afii57412;ARABIC LETTER WAW WITH HAMZA ABOVE
 20181 \DeclareTextCommand{\wawhamza}{PU}{\86\044}% U+0624
 20182 % U+0625;afii57413;ARABIC LETTER ALEF WITH HAMZA BELOW
 20183 \DeclareTextCommand{\aleflowerhamza}{PU}{\86\045}% U+0625
 20184 % U+0626;afii57414;ARABIC LETTER YEH WITH HAMZA ABOVE
 20185 \DeclareTextCommand{\yahamza}{PU}{\86\046}% U+0626
 20186 % U+0627;afii57415;ARABIC LETTER ALEF
 20187 \DeclareTextCommand{\alef}{PU}{\86\047}% U+0627
 20188 % U+0628;afii57416;ARABIC LETTER BEH
 20189 \DeclareTextCommand{\baa}{PU}{\86\050}% U+0628
 20190 % U+0629;afii57417;ARABIC LETTER TEH MARBUTA
 20191 \DeclareTextCommand{\T}{PU}{\86\051}% U+0629
 20192 % U+062A;afii57418;ARABIC LETTER TEH
 20193 \DeclareTextCommand{\taa}{PU}{\86\052}% U+062A
 20194 % U+062B;afii57419;ARABIC LETTER THEH
 20195 \DeclareTextCommand{\thaa}{PU}{\86\053}% U+062B
 20196 % U+062C;afii57420;ARABIC LETTER JEEM
 20197 \DeclareTextCommand{\jeem}{PU}{\86\054}% U+062C
 20198 % U+062D;afii57421;ARABIC LETTER HAH
 20199 \DeclareTextCommand{\Haa}{PU}{\86\055}% U+062D
 20200 % U+062E;afii57422;ARABIC LETTER KHAH
 20201 \DeclareTextCommand{\kha}{PU}{\86\056}% U+062E
 20202 % U+062F;afii57423;ARABIC LETTER DAL
 20203 \DeclareTextCommand{\dal}{PU}{\86\057}% U+062F
 20204 % U+0630;afii57424;ARABIC LETTER THAL
 20205 \DeclareTextCommand{\dhal}{PU}{\86\060}% U+0630
 20206 % U+0631;afii57425;ARABIC LETTER REH
 20207 \DeclareTextCommand{\ra}{PU}{\86\061}% U+0631
 20208 % U+0632;afii57426;ARABIC LETTER ZAIN
 20209 \DeclareTextCommand{\zay}{PU}{\86\062}% U+0632
 20210 % U+0633;afii57427;ARABIC LETTER SEEN
 20211 \DeclareTextCommand{\seen}{PU}{\86\063}% U+0633
 20212 % U+0634;afii57428;ARABIC LETTER SHEEN
 20213 \DeclareTextCommand{\sheen}{PU}{\86\064}% U+0634
 20214 % U+0635;afii57429;ARABIC LETTER SAD
 20215 \DeclareTextCommand{\sad}{PU}{\86\065}% U+0635
 20216 % U+0636;afii57430;ARABIC LETTER DAD
 20217 \DeclareTextCommand{\dad}{PU}{\86\066}% U+0636
 20218 % U+0637;afii57431;ARABIC LETTER TAH
 20219 \DeclareTextCommand{\Ta}{PU}{\86\067}% U+0637
 20220 % U+0638;afii57432;ARABIC LETTER ZAH
 20221 \DeclareTextCommand{\za}{PU}{\86\070}% U+0638
 20222 % U+0639;afii57433;ARABIC LETTER AIN
 20223 \DeclareTextCommand{\ayn}{PU}{\86\071}% U+0639
 20224 % U+063A;afii57434;ARABIC LETTER GHAIN
 20225 \DeclareTextCommand{\ghayn}{PU}{\86\072}% U+063A
 20226 % U+0640;afii57440;ARABIC TATWEEL
 20227 \DeclareTextCommand{\tatweel}{PU}{\86\100}% U+0640
 20228 % U+0641;afii57441;ARABIC LETTER FEH
 20229 \DeclareTextCommand{\fa}{PU}{\86\101}% U+0641
 20230 % U+0642;afii57442;ARABIC LETTER QAF
 20231 \DeclareTextCommand{\qaf}{PU}{\86\102}% U+0642
 20232 % U+0643;afii57443;ARABIC LETTER KAF
 20233 \DeclareTextCommand{\kaf}{PU}{\86\103}% U+0643
 20234 % U+0644;afii57444;ARABIC LETTER LAM
 20235 \DeclareTextCommand{\lam}{PU}{\86\104}% U+0644

20236 % U+0645;afi57445;ARABIC LETTER MEEM
 20237 \DeclareTextCommand{\meem}{PU}{\86\105}% U+0645
 20238 % U+0646;afi57446;ARABIC LETTER NOON
 20239 \DeclareTextCommand{\nun}{PU}{\86\106}% U+0646
 20240 % U+0647;afi57470;ARABIC LETTER HEH
 20241 \DeclareTextCommand{\ha}{PU}{\86\107}% U+0647
 20242 % U+0648;afi57448;ARABIC LETTER WAW
 20243 \DeclareTextCommand{\waw}{PU}{\86\110}% U+0648
 20244 % U+0649;afi57449;ARABIC LETTER ALEF MAKSURA
 20245 \DeclareTextCommand{\alefmaqsura}{PU}{\86\111}% U+0649
 20246 % U+064A;afi57450;ARABIC LETTER YEH
 20247 \DeclareTextCommand{\ya}{PU}{\86\112}% U+064A

 20248 % U+064B;afi57451;ARABIC FATHATAN
 20249 \DeclareTextCommand{\nasb}{PU}{\86\113}% U+064B
 20250 % U+064C;afi57452;ARABIC DAMMATAN
 20251 \DeclareTextCommand{\raff}{PU}{\86\114}% U+064C
 20252 % U+064D;afi57453;ARABIC KASRATAN
 20253 \DeclareTextCommand{\jarr}{PU}{\86\115}% U+064D
 20254 % U+064E;afi57454;ARABIC FATHA
 20255 \DeclareTextCommand{\fatha}{PU}{\86\116}% U+064E
 20256 % U+064F;afi57455;ARABIC DAMMA
 20257 \DeclareTextCommand{\damma}{PU}{\86\117}% U+064F
 20258 % U+0650;afi57456;ARABIC KASRA
 20259 \DeclareTextCommand{\kasra}{PU}{\86\120}% U+0650
 20260 % U+0651;afi57457;ARABIC SHADDA
 20261 \DeclareTextCommand{\shadda}{PU}{\86\121}% U+0651
 20262 % U+0652;afi57458;ARABIC SUKUN
 20263 \DeclareTextCommand{\sukun}{PU}{\86\122}% U+0652

 Farsi
 20264 % U+067E ARABIC LETTER PEH; afi57506
 20265 \DeclareTextCommand{\peh}{PU}{\86\176}% U+067E
 20266 % U+0686 ARABIC LETTER TCHEH; afi57507
 20267 \DeclareTextCommand{\tch eh}{PU}{\86\206}% U+0686
 20268 % U+0698 ARABIC LETTER JEH; afi57508
 20269 \DeclareTextCommand{\jeh}{PU}{\86\230}% U+0698
 20270 % U+06A9 ARABIC LETTER KEHEH
 20271 \DeclareTextCommand{\farsikaf}{PU}{\86\251}% U+06A9
 20272 % U+06AF ARABIC LETTER GAF; afi57509
 20273 \DeclareTextCommand{\gaf}{PU}{\86\257}% U+06AF
 20274 % U+06CC ARABIC LETTER FARSI YEH
 20275 \DeclareTextCommand{\farsiya}{PU}{\86\314}% U+06CC

 20276 % U+200C ZERO WIDTH NON-JOINER; afi61664
 20277 \DeclareTextCommand{\ZWNJ}{PU}{\9040\014}% U+200C
 20278 % U+200D ZERO WIDTH JOINER; afi301
 20279 \DeclareTextCommand{\noboundary}{PU}{\9040\015}% U+200D

 20280 (/puarenc)
 20281 (*psdextra)
 20282 \Hy@VersionCheck{psdextra.def}
 20283 \newcommand*{\psdmapshortnames}{%
 20284 \let\MVPlus\textMVPlus
 20285 \let\MVComma\textMVComma
 20286 \let\MVMinus\textMVMinus
 20287 \let\MVPeriod\textMVPeriod
 20288 \let\MVDivision\textMVDivision
 20289 \let\MVZero\textMVZero

20290 \let\MVOne\textMVOne
 20291 \let\MVTwo\textMVTwo
 20292 \let\MVThree\textMVThree
 20293 \let\MVFour\textMVFour
 20294 \let\MVFive\textMVFive
 20295 \let\MVSix\textMVSix
 20296 \let\MVSeven\textMVSeven
 20297 \let\MVEight\textMVEight
 20298 \let\MVNine\textMVNine
 20299 \let\MVAt\textMVAt
 20300 \let\copyright\textcopyright
 20301 \let\twosuperior\texttwosuperior
 20302 \let\threesuperior\textthreesuperior
 20303 \let\onesuperior\textonesuperior
 20304 \let\Thorn\textThorn
 20305 \let\thorn\textthorn
 20306 \let\hbar\texthbar
 20307 \let\hausA\texthausA
 20308 \let\hausD\texthausD
 20309 \let\hausK\texthausK
 20310 \let\barl\textbarl
 20311 \let\inve\textinve
 20312 \let\slashc\textslashc
 20313 \let\scripta\textscripta
 20314 \let\openo\textopeno
 20315 \let\rtaild\textrtaild
 20316 \let\reve\textreve
 20317 \let\schwa\textschwa
 20318 \let\niepsilon\textniepsilon
 20319 \let\repsilon\textrepsilon
 20320 \let\rhookrepsilon\text\rhookrepsilon
 20321 \let\scriptg\textscriptg
 20322 \let\scg\textscg
 20323 \let\ipagamma\textipagamma
 20324 \let\babygamma\textbabygamma
 20325 \let\bari\textbari
 20326 \let\niota\textniota
 20327 \let\sci\textsci
 20328 \let\scn\textscn
 20329 \let\niphi\textniphi
 20330 \let\longlegr\textlonglegr
 20331 \let\scr\textscr
 20332 \let\invscr\textinvscr
 20333 \let\esh\textesh
 20334 \let\baru\textbaru
 20335 \let\niupsilon\textniupsilon
 20336 \let\scriptv\textscriptv
 20337 \let\turnv\textturnv
 20338 \let\turnw\textturnw
 20339 \let\turny\textturny
 20340 \let\scy\textscy
 20341 \let\yogh\textyogh
 20342 \let\glotstop\textglotstop
 20343 \let\revglotstop\textrevglotstop
 20344 \let\invglotstop\textinvglotstop
 20345 \let\Gamma\textGamma
 20346 \let\Delta\textDelta

20347 \let\Theta\textTheta
 20348 \let\Lambda\textLambda
 20349 \let\Xi\textXi
 20350 \let\Pi\textPi
 20351 \let\Sigma\textSigma
 20352 \let\Upsilon\textUpsilon
 20353 \let\Phi\textPhi
 20354 \let\Psi\textPsi
 20355 \let\Omega\textOmega
 20356 \let\alpha\textalpha
 20357 \let\beta\textbeta
 20358 \let\gamma\textgamma
 20359 \let\delta\textdelta
 20360 \let\epsilon\textepsilon
 20361 \let\zeta\textzeta
 20362 \let\eta\texteta
 20363 \let\theta\texttheta
 20364 \let\iota\textiota
 20365 \let\kappa\textkappa
 20366 \let\lambda\textlambda
 20367 \let\mugreek\textmugreek
 20368 \let\nu\textnu
 20369 \let\xi\textxi
 20370 \let\pi\textpi
 20371 \let\rho\textrho
 20372 \let\varsigma\textvarsigma
 20373 \let\sigma\textsigma
 20374 \let\tau\texttau
 20375 \let\upsilon\textupsilon
 20376 \let\phi\textphi
 20377 \let\chi\textchi
 20378 \let\psi\textpsi
 20379 \let\omega\textomega
 20380 \let\scd\textscd
 20381 \let\scu\textscu
 20382 \let\iinferior\textiinferior
 20383 \let\rinferior\textrinferior
 20384 \let\uinferior\textuinferior
 20385 \let\vinferior\textvinferior
 20386 \let\betainferior\textbetainferior
 20387 \let\gammainferior\textgammainferior
 20388 \let\rhoinferior\textrhoinferior
 20389 \let\phiinferior\textphiinferior
 20390 \let\chiinferior\textchiinferior
 20391 \let\barsci\textbarsci
 20392 \let\barp\textbarp
 20393 \let\barscu\textbarscu
 20394 \let\htrtaild\texthtrtaild
 20395 \let\dagger\textdagger
 20396 \let\bullet\textbullet
 20397 \let\hdotfor\texthdotfor
 20398 \let\prime\textprime
 20399 \let\second\textsecond
 20400 \let\third\textthird
 20401 \let\backprime\textbackprime
 20402 \let\lefttherefore\textlefttherefore
 20403 \let\fourth\textfourth

20404 \let\diamonddots\textdiamonddots
 20405 \let\zerosuperior\textzerosuperior
 20406 \let\isuperior\textisuperior
 20407 \let\foursuperior\textfoursuperior
 20408 \let\fivesuperior\textfivesuperior
 20409 \let\sixsuperior\textsixsuperior
 20410 \let\sevensuperior\textsevensuperior
 20411 \let\eightsuperior\texteightsuperior
 20412 \let\ninesuperior\textninesuperior
 20413 \let\plussuperior\textplussuperior
 20414 \let\minussuperior\textminussuperior
 20415 \let>equalsuperior\textequalsuperior
 20416 \let\parenleftsuperior\textparenleftsuperior
 20417 \let\parenrightsuperior\textparenrightsuperior
 20418 \let\nsuperior\textnsuperior
 20419 \let\zeroinferior\textzeroinferior
 20420 \let\oneinferior\textoneinferior
 20421 \let\twoinferior\texttwoinferior
 20422 \let\threeinferior\textthreeinferior
 20423 \let\fourinferior\textfourinferior
 20424 \let\fiveinferior\textfiveinferior
 20425 \let\sixinferior\textsixinferior
 20426 \let\seveninferior\textseveninferior
 20427 \let\eightinferior\texteightinferior
 20428 \let\nineinferior\textnineinferior
 20429 \let\plusinferior\textplusinferior
 20430 \let\minusinferior\textminusinferior
 20431 \let>equalsinferior\textequalsinferior
 20432 \let\parenleftinferior\textparenleftinferior
 20433 \let\parenrightinferior\textparenrightinferior
 20434 \let\ainferior\textainferior
 20435 \let\eginferior\texteginferior
 20436 \let\oinferior\textoinferior
 20437 \let\xinferior\textxinferior
 20438 \let\schwainferior\textschwainferior
 20439 \let\hinferior\texthinferior
 20440 \let\kinferior\textkinferior
 20441 \let\linferior\textlinferior
 20442 \let\minferior\textminferior
 20443 \let\ninferior\textninferior
 20444 \let\pinferior\textpinferior
 20445 \let\sinferior\textsinferior
 20446 \let\tinferior\texttinferior
 20447 \let\Deleatur\textDeleatur
 20448 \let\hslash\texthslash
 20449 \let\Im\textIm
 20450 \let\ell\textell
 20451 \let\wp\textwp
 20452 \let\Re\textRe
 20453 \let\mho\textmho
 20454 \let\riota\textriota
 20455 \let\Finv\textFinv
 20456 \let\aleph\textaleph
 20457 \let\beth\textbeth
 20458 \let\gimel\textgimel
 20459 \let\daleth\textdaleth
 20460 \let\xfax\textfax

20461 \let\Game\textGame
 20462 \let\leftarrow\textleftarrow
 20463 \let\uparrow\textuparrow
 20464 \let\rightarrow\textrightarrow
 20465 \let\downarrow\textdownarrow
 20466 \let\leftrightarrow\textleftrightarrow
 20467 \let\updownarrow\textupdownarrow
 20468 \let\nwarrow\textnwarrow
 20469 \let\nearrow\textnearrow
 20470 \let\searrow\textsearrow
 20471 \let\swarrow\textswarrow
 20472 \let\nleftarrow\textnleftarrow
 20473 \let\nrightarrow\textnrightarrow
 20474 \let\twoheadleftarrow\texttwoheadleftarrow
 20475 \let\ntwoheadleftarrow\textntwoheadleftarrow
 20476 \let\twoheaduparrow\texttwoheaduparrow
 20477 \let\twoheadrightarrow\texttwoheadrightarrow
 20478 \let\ntwoheadrightarrow\textntwoheadrightarrow
 20479 \let\twoheaddownarrow\texttwoheaddownarrow
 20480 \let\leftarrowtail\textleftarrowtail
 20481 \let\rightarrowtail\textrightarrowtail
 20482 \let\mapsto\textmapsto
 20483 \let\hookleftarrow\texthookleftarrow
 20484 \let\hookrightarrow\texthookrightarrow
 20485 \let\looparrowleft\textlooparrowleft
 20486 \let\looparrowright\textlooparrowright
 20487 \let\leftrightharpoonup\textleftrightharpoonup
 20488 \let\lightning\textlightning
 20489 \let\dlsh\textdlsh
 20490 \let\curvearrowleft\textcurvearrowleft
 20491 \let\curvearrowright\textcurvearrowright
 20492 \let\leftharpoonup\textleftharpoonup
 20493 \let\leftharpoondown\textleftharpoondown
 20494 \let\upharpoonright\textupharpoonright
 20495 \let\upharpoonleft\textupharpoonleft
 20496 \let\rightarpoonup\textrightarpoonup
 20497 \let\rightarpoondown\textrightarpoondown
 20498 \let\downharpoonright\textdownharpoonright
 20499 \let\downharpoonleft\textdownharpoonleft
 20500 \let\rightleftarrows\textrightleftarrows
 20501 \let\updownarrows\textupdownarrows
 20502 \let\leftrightarrows\textleftrightarrows
 20503 \let\leftleftarrows\textleftleftarrows
 20504 \let\upuparrows\textupuparrows
 20505 \let\righttrightarrows\textrighttrightarrows
 20506 \let\downdownarrows\textdowndownarrows
 20507 \let\leftrightharpoons\textleftrightharpoons
 20508 \let\rightleftharpoons\textrightleftharpoons
 20509 \let\nLeftarrow\textnLeftarrow
 20510 \let\nLeftrightarrow\textnLeftrightarrow
 20511 \let\nRightarrow\textnRightarrow
 20512 \let\Leftarrow\textLeftarrow
 20513 \let\Uparrow\textUparrow
 20514 \let\Rightarrow\textRightarrow
 20515 \let\Downarrow\textDownarrow
 20516 \let\Leftrightarrow\textLeftrightarrow
 20517 \let\Updownarrow\textUpdownarrow

20518 $\backslash\text{let}\backslash\text{Nwarrow}\backslash\text{textNwarrow}$
 20519 $\backslash\text{let}\backslash\text{Nearrow}\backslash\text{textNearrow}$
 20520 $\backslash\text{let}\backslash\text{Searrow}\backslash\text{textSearrow}$
 20521 $\backslash\text{let}\backslash\text{Swarrow}\backslash\text{textSwarrow}$
 20522 $\backslash\text{let}\backslash\text{Lleftarrow}\backslash\text{textLleftarrow}$
 20523 $\backslash\text{let}\backslash\text{Rrightarrow}\backslash\text{textRrightarrow}$
 20524 $\backslash\text{let}\backslash\text{leftsquigarrow}\backslash\text{textleftsquigarrow}$
 20525 $\backslash\text{let}\backslash\text{rightsquigarrow}\backslash\text{textrightsquigarrow}$
 20526 $\backslash\text{let}\backslash\text{dashleftarrow}\backslash\text{texdashleftarrow}$
 20527 $\backslash\text{let}\backslash\text{dasheduparrow}\backslash\text{texdasheduparrow}$
 20528 $\backslash\text{let}\backslash\text{dashrightarrow}\backslash\text{texdashrightarrow}$
 20529 $\backslash\text{let}\backslash\text{dasheddownarrow}\backslash\text{texdasheddownarrow}$
 20530 $\backslash\text{let}\backslash\text{pointer}\backslash\text{textpointer}$
 20531 $\backslash\text{let}\backslash\text{downuparrows}\backslash\text{texdownuparrows}$
 20532 $\backslash\text{let}\backslash\text{leftarrowtriangle}\backslash\text{textleftarrowtriangle}$
 20533 $\backslash\text{let}\backslash\text{rightarrowtriangle}\backslash\text{textrightarrowtriangle}$
 20534 $\backslash\text{let}\backslash\text{leftrightarrowtriangle}\backslash\text{textleftrightarrowtriangle}$
 20535 $\backslash\text{let}\backslash\text{forall}\backslash\text{textforall}$
 20536 $\backslash\text{let}\backslash\text{complement}\backslash\text{textcomplement}$
 20537 $\backslash\text{let}\backslash\text{partial}\backslash\text{textpartial}$
 20538 $\backslash\text{let}\backslash\text{exists}\backslash\text{textexists}$
 20539 $\backslash\text{let}\backslash\text{nexists}\backslash\text{textnexists}$
 20540 $\backslash\text{let}\backslash\text{emptyset}\backslash\text{textemptyset}$
 20541 $\backslash\text{let}\backslash\text{triangle}\backslash\text{texttriangle}$
 20542 $\backslash\text{let}\backslash\text{nabla}\backslash\text{textnabla}$
 20543 $\backslash\text{let}\backslash\text{in}\backslash\text{textin}$
 20544 $\backslash\text{let}\backslash\text{notin}\backslash\text{textnotin}$
 20545 $\backslash\text{let}\backslash\text{smallin}\backslash\text{textsmallin}$
 20546 $\backslash\text{let}\backslash\text{ni}\backslash\text{textni}$
 20547 $\backslash\text{let}\backslash\text{notowner}\backslash\text{textnotowner}$
 20548 $\backslash\text{let}\backslash\text{smallowns}\backslash\text{textsmallowns}$
 20549 $\backslash\text{let}\backslash\text{prod}\backslash\text{textprod}$
 20550 $\backslash\text{let}\backslash\text{amalg}\backslash\text{textamalg}$
 20551 $\backslash\text{let}\backslash\text{sum}\backslash\text{textsum}$
 20552 $\backslash\text{let}\backslash\text{mp}\backslash\text{textmp}$
 20553 $\backslash\text{let}\backslash\text{dotplus}\backslash\text{texdotplus}$
 20554 $\backslash\text{let}\backslash\text{Divides}\backslash\text{textDivides}$
 20555 $\backslash\text{let}\backslash\text{DividesNot}\backslash\text{textDividesNot}$
 20556 $\backslash\text{let}\backslash\text{setminus}\backslash\text{textsetminus}$
 20557 $\backslash\text{let}\backslash\text{ast}\backslash\text{textast}$
 20558 $\backslash\text{let}\backslash\text{circ}\backslash\text{textcirc}$
 20559 $\backslash\text{let}\backslash\text{surd}\backslash\text{textsurd}$
 20560 $\backslash\text{let}\backslash\text{propto}\backslash\text{textpropto}$
 20561 $\backslash\text{let}\backslash\text{infty}\backslash\text{textinfty}$
 20562 $\backslash\text{let}\backslash\text{angle}\backslash\text{textangle}$
 20563 $\backslash\text{let}\backslash\text{measuredangle}\backslash\text{textmeasuredangle}$
 20564 $\backslash\text{let}\backslash\text{sphericalangle}\backslash\text{textsphericalangle}$
 20565 $\backslash\text{let}\backslash\text{mid}\backslash\text{textmid}$
 20566 $\backslash\text{let}\backslash\text{nmid}\backslash\text{textnmid}$
 20567 $\backslash\text{let}\backslash\text{parallel}\backslash\text{textparallel}$
 20568 $\backslash\text{let}\backslash\text{nparallel}\backslash\text{textnparallel}$
 20569 $\backslash\text{let}\backslash\text{wedge}\backslash\text{textwedge}$
 20570 $\backslash\text{let}\backslash\text{owedge}\backslash\text{textowedge}$
 20571 $\backslash\text{let}\backslash\text{vee}\backslash\text{textvee}$
 20572 $\backslash\text{let}\backslash\text{ovee}\backslash\text{textovee}$
 20573 $\backslash\text{let}\backslash\text{cap}\backslash\text{textcap}$
 20574 $\backslash\text{let}\backslash\text{cup}\backslash\text{textcup}$

20575 `\let\int\textint`
 20576 `\let\iint\textiint`
 20577 `\let\iiint\textiiint`
 20578 `\let\oint\textoint`
 20579 `\let\oiint\textoiint`
 20580 `\let\ointclockwise\textointclockwise`
 20581 `\let\ointctrlockwise\textointctrlockwise`
 20582 `\let\therefore\texttherefore`
 20583 `\let\because\textbecause`
 20584 `\let\vdotdot\textvdotdot`
 20585 `\let\squaredots\textsquaredots`
 20586 `\let\dotminus\textdotminus`
 20587 `\let\eqcolon\texteqcolon`
 20588 `\let\sim\textsim`
 20589 `\let\backsim\textbacksim`
 20590 `\let\backsim\textnbacksim`
 20591 `\let\wr\textwr`
 20592 `\let\sim\textnsim`
 20593 `\let\eqsim\texteqsim`
 20594 `\let\neqsim\textneqsim`
 20595 `\let\simeq\textsimeq`
 20596 `\let\sim\textnsimeq`
 20597 `\let\cong\textcong`
 20598 `\let\cong\textncong`
 20599 `\let\approx\textapprox`
 20600 `\let\approx\textnapprox`
 20601 `\let\approx\textapprox`
 20602 `\let\approx\textnapprox`
 20603 `\let\triplesim\texttriplesim`
 20604 `\let\triplesim\textntriplesim`
 20605 `\let\backcong\textbackcong`
 20606 `\let\backcong\textnbackcong`
 20607 `\let\asympt\textasympt`
 20608 `\let\asympt\textnasympt`
 20609 `\let\Bumpeq\textBumpeq`
 20610 `\let\Bumpeq\textnBumpeq`
 20611 `\let\bumpeq\textbumpeq`
 20612 `\let\bumpeq\textnbumpeq`
 20613 `\let\doteq\textdoteq`
 20614 `\let\ndoteq\textndoteq`
 20615 `\let\doteqdot\textdoteqdot`
 20616 `\let\ndoteq\textndoteq`
 20617 `\let\fallingdoteq\textfallingdoteq`
 20618 `\let\fallingdoteq\textnfallingdoteq`
 20619 `\let\risingdoteq\textrisingdoteq`
 20620 `\let\risingdoteq\textnrisingdoteq`
 20621 `\let\colonequals\textcolonequals`
 20622 `\let\equalscolon\textequalscolon`
 20623 `\let\eqcirc\texteqcirc`
 20624 `\let\neqcirc\textneqcirc`
 20625 `\let\circeq\textcirceq`
 20626 `\let\ncirceq\textncirceq`
 20627 `\let\hateq\texthateq`
 20628 `\let\hateq\textnhateq`
 20629 `\let\triangleeq\texttriangleeq`
 20630 `\let\neq\textneq`
 20631 `\let\neq\textne`

20632 \let\equiv\textequiv
 20633 \let\nequiv\textnequiv
 20634 \let\leq\textleq
 20635 \let\le\textle
 20636 \let\geq\textgeq
 20637 \let\ge\textge
 20638 \let\leqq\textleqq
 20639 \let\leqq\textleqq
 20640 \let\geqq\textgeqq
 20641 \let\geqq\textgeqq
 20642 \let\lneqq\textlneqq
 20643 \let\gneqq\textgneqq
 20644 \let\ll\textll
 20645 \let\nll\textnll
 20646 \let\gg\textgg
 20647 \let\ngg\textngg
 20648 \let\between\textbetween
 20649 \let\nless\textnless
 20650 \let\ngtr\textngtr
 20651 \let\lneq\textlneq
 20652 \let\ngeq\textngeq
 20653 \let\lesssim\textlessssim
 20654 \let\gtrsim\textgtrsim
 20655 \let\nlesssim\textnlesssim
 20656 \let\ngtrsim\textngtrsim
 20657 \let\lessgtr\textlessgtr
 20658 \let\gtrless\textgtrless
 20659 \let\ngtrless\textngtrless
 20660 \let\nlessgtr\textnlessgtr
 20661 \let\prec\textprec
 20662 \let\succ\textsucc
 20663 \let\preccurlyeq\textpreccurlyeq
 20664 \let\succcurlyeq\textsucccurlyeq
 20665 \let\prec\textprec
 20666 \let\prec\textprec
 20667 \let\succsim\textsuccsim
 20668 \let\nsuccsim\textnsuccsim
 20669 \let\prec\textprec
 20670 \let\succ\textsucc
 20671 \let\subset\textsubset
 20672 \let\supset\textsupset
 20673 \let\nsubset\textnsubset
 20674 \let\nsupset\textnsupset
 20675 \let\subse\textsubse
 20676 \let\supseteq\textsupseteq
 20677 \let\nsubse\textnsubse
 20678 \let\nsupseteq\textnsupseteq
 20679 \let\subsetneq\textsubsetneq
 20680 \let\supsetneq\textsupsetneq
 20681 \let\cupdot\textcupdot
 20682 \let\cupplus\textcupplus
 20683 \let\sqs\textsqsubset
 20684 \let\nsqsubset\textnsqsubset
 20685 \let\sqs\textsqsupset
 20686 \let\nsqsupset\textnsqsupset
 20687 \let\sqs\textsqsubse
 20688 \let\nsqsubse\textnsqsubse

20689 $\backslash\mathrm{sqsupseteq}\backslash\mathrm{textsqsupseteq}$
 20690 $\backslash\mathrm{nsqsupseteq}\backslash\mathrm{textnsqsupseteq}$
 20691 $\backslash\mathrm{sqcap}\backslash\mathrm{textsqcap}$
 20692 $\backslash\mathrm{sqcup}\backslash\mathrm{textsqcup}$
 20693 $\backslash\mathrm{oplus}\backslash\mathrm{textoplus}$
 20694 $\backslash\mathrm{ominus}\backslash\mathrm{textominus}$
 20695 $\backslash\mathrm{otimes}\backslash\mathrm{textotimes}$
 20696 $\backslash\mathrm{oslash}\backslash\mathrm{textoslash}$
 20697 $\backslash\mathrm{odot}\backslash\mathrm{textodot}$
 20698 $\backslash\mathrm{circledcirc}\backslash\mathrm{textcircledcirc}$
 20699 $\backslash\mathrm{circledast}\backslash\mathrm{textcircledast}$
 20700 $\backslash\mathrm{circleddash}\backslash\mathrm{textcircleddash}$
 20701 $\backslash\mathrm{boxplus}\backslash\mathrm{textboxplus}$
 20702 $\backslash\mathrm{boxminus}\backslash\mathrm{textboxminus}$
 20703 $\backslash\mathrm{boxtimes}\backslash\mathrm{textboxtimes}$
 20704 $\backslash\mathrm{boxdot}\backslash\mathrm{textboxdot}$
 20705 $\backslash\mathrm{vdash}\backslash\mathrm{textvdash}$
 20706 $\backslash\mathrm{dashv}\backslash\mathrm{textdashv}$
 20707 $\backslash\mathrm{ndashv}\backslash\mathrm{textndashv}$
 20708 $\backslash\mathrm{top}\backslash\mathrm{texttop}$
 20709 $\backslash\mathrm{ndownvdash}\backslash\mathrm{textndownvdash}$
 20710 $\backslash\mathrm{bot}\backslash\mathrm{textbot}$
 20711 $\backslash\mathrm{nupvdash}\backslash\mathrm{textnupvdash}$
 20712 $\backslash\mathrm{vDash}\backslash\mathrm{textvDash}$
 20713 $\backslash\mathrm{VDash}\backslash\mathrm{textVDash}$
 20714 $\backslash\mathrm{Vvdash}\backslash\mathrm{textVvdash}$
 20715 $\backslash\mathrm{nVdash}\backslash\mathrm{textnVdash}$
 20716 $\backslash\mathrm{VDash}\backslash\mathrm{textVDash}$
 20717 $\backslash\mathrm{nvDash}\backslash\mathrm{textnvDash}$
 20718 $\backslash\mathrm{nvDash}\backslash\mathrm{textnvDash}$
 20719 $\backslash\mathrm{nVdash}\backslash\mathrm{textnVdash}$
 20720 $\backslash\mathrm{nVDash}\backslash\mathrm{textnVDash}$
 20721 $\backslash\mathrm{lhs}\backslash\mathrm{textrhs}$
 20722 $\backslash\mathrm{rhd}\backslash\mathrm{textrhd}$
 20723 $\backslash\mathrm{unlhd}\backslash\mathrm{textunlhd}$
 20724 $\backslash\mathrm{unrhd}\backslash\mathrm{textunrhd}$
 20725 $\backslash\mathrm{multimapdotbothA}\backslash\mathrm{textmultimapdotbothA}$
 20726 $\backslash\mathrm{multimapdotbothB}\backslash\mathrm{textmultimapdotbothB}$
 20727 $\backslash\mathrm{multimap}\backslash\mathrm{textmultimap}$
 20728 $\backslash\mathrm{veebar}\backslash\mathrm{textveebar}$
 20729 $\backslash\mathrm{barwedge}\backslash\mathrm{textbarwedge}$
 20730 $\backslash\mathrm{star}\backslash\mathrm{textstar}$
 20731 $\backslash\mathrm{divideontimes}\backslash\mathrm{textdivideontimes}$
 20732 $\backslash\mathrm{bowtie}\backslash\mathrm{textbowtie}$
 20733 $\backslash\mathrm{ltimes}\backslash\mathrm{textltimes}$
 20734 $\backslash\mathrm{rtimes}\backslash\mathrm{textrtimes}$
 20735 $\backslash\mathrm{leftthreetimes}\backslash\mathrm{textleftthreetimes}$
 20736 $\backslash\mathrm{rightthreetimes}\backslash\mathrm{textrightthreetimes}$
 20737 $\backslash\mathrm{backsimeq}\backslash\mathrm{textbacksimeq}$
 20738 $\backslash\mathrm{nbacksimeq}\backslash\mathrm{textnbacksimeq}$
 20739 $\backslash\mathrm{curlyvee}\backslash\mathrm{textcurlyvee}$
 20740 $\backslash\mathrm{curlywedge}\backslash\mathrm{textcurlywedge}$
 20741 $\backslash\mathrm{Subset}\backslash\mathrm{textSubset}$
 20742 $\backslash\mathrm{nSubset}\backslash\mathrm{textnSubset}$
 20743 $\backslash\mathrm{Supset}\backslash\mathrm{textSupset}$
 20744 $\backslash\mathrm{nSupset}\backslash\mathrm{textnSupset}$
 20745 $\backslash\mathrm{Cap}\backslash\mathrm{textCap}$

20746 $\backslash\text{let}\backslash\text{Cup}\backslash\text{textCup}$
 20747 $\backslash\text{let}\backslash\text{pitchfork}\backslash\text{textpitchfork}$
 20748 $\backslash\text{let}\backslash\text{lessdot}\backslash\text{textlessdot}$
 20749 $\backslash\text{let}\backslash\text{gtrdot}\backslash\text{textgtrdot}$
 20750 $\backslash\text{let}\backslash\text{lll}\backslash\text{textlll}$
 20751 $\backslash\text{let}\backslash\text{ggg}\backslash\text{textggg}$
 20752 $\backslash\text{let}\backslash\text{lesseqgtr}\backslash\text{textlesseqgtr}$
 20753 $\backslash\text{let}\backslash\text{gtreqless}\backslash\text{textgtreqless}$
 20754 $\backslash\text{let}\backslash\text{curlyeqprec}\backslash\text{textcurlyeqprec}$
 20755 $\backslash\text{let}\backslash\text{ncurlyeqprec}\backslash\text{textncurlyeqprec}$
 20756 $\backslash\text{let}\backslash\text{curlyeqsucc}\backslash\text{textcurlyeqsucc}$
 20757 $\backslash\text{let}\backslash\text{ncurlyeqsucc}\backslash\text{textncurlyeqsucc}$
 20758 $\backslash\text{let}\backslash\text{npreccurlyeq}\backslash\text{textnpreccurlyeq}$
 20759 $\backslash\text{let}\backslash\text{nsucccurlyeq}\backslash\text{textnsucccurlyeq}$
 20760 $\backslash\text{let}\backslash\text{nqsubseteq}\backslash\text{textnqsubseteq}$
 20761 $\backslash\text{let}\backslash\text{nqsupseteq}\backslash\text{textnqsupseteq}$
 20762 $\backslash\text{let}\backslash\text{sqsubsetneq}\backslash\text{textsqsubsetneq}$
 20763 $\backslash\text{let}\backslash\text{sqsupsetneq}\backslash\text{textsqsupsetneq}$
 20764 $\backslash\text{let}\backslash\text{lnsim}\backslash\text{textlnsim}$
 20765 $\backslash\text{let}\backslash\text{gnsim}\backslash\text{textgnsim}$
 20766 $\backslash\text{let}\backslash\text{precnsim}\backslash\text{textprecnsim}$
 20767 $\backslash\text{let}\backslash\text{succnsim}\backslash\text{textsuccnsim}$
 20768 $\backslash\text{let}\backslash\text{ntriangleleft}\backslash\text{textntriangleleft}$
 20769 $\backslash\text{let}\backslash\text{ntriangleright}\backslash\text{textntriangleright}$
 20770 $\backslash\text{let}\backslash\text{ntrianglelefteq}\backslash\text{textntrianglelefteq}$
 20771 $\backslash\text{let}\backslash\text{ntrianglerighteq}\backslash\text{textntrianglerighteq}$
 20772 $\backslash\text{let}\backslash\text{vdots}\backslash\text{textvdots}$
 20773 $\backslash\text{let}\backslash\text{cdots}\backslash\text{textcdots}$
 20774 $\backslash\text{let}\backslash\text{udots}\backslash\text{textudots}$
 20775 $\backslash\text{let}\backslash\text{ddots}\backslash\text{textddots}$
 20776 $\backslash\text{let}\backslash\text{barin}\backslash\text{textbarin}$
 20777 $\backslash\text{let}\backslash\text{diameter}\backslash\text{textdiameter}$
 20778 $\backslash\text{let}\backslash\text{backneg}\backslash\text{textbackneg}$
 20779 $\backslash\text{let}\backslash\text{wasylounge}\backslash\text{textwasylounge}$
 20780 $\backslash\text{let}\backslash\text{invbackneg}\backslash\text{textinvbackneg}$
 20781 $\backslash\text{let}\backslash\text{clock}\backslash\text{textclock}$
 20782 $\backslash\text{let}\backslash\text{ulcorner}\backslash\text{textulcorner}$
 20783 $\backslash\text{let}\backslash\text{urcorner}\backslash\text{texturcorner}$
 20784 $\backslash\text{let}\backslash\text{llcorner}\backslash\text{textllcorner}$
 20785 $\backslash\text{let}\backslash\text{lrcorner}\backslash\text{textlrcorner}$
 20786 $\backslash\text{let}\backslash\text{frown}\backslash\text{textfrown}$
 20787 $\backslash\text{let}\backslash\text{smile}\backslash\text{textsmile}$
 20788 $\backslash\text{let}\backslash\text{Keyboard}\backslash\text{textKeyboard}$
 20789 $\backslash\text{let}\backslash\text{langle}\backslash\text{textlangle}$
 20790 $\backslash\text{let}\backslash\text{rangle}\backslash\text{textrangle}$
 20791 $\backslash\text{let}\backslash\text{APLinv}\backslash\text{textAPLinv}$
 20792 $\backslash\text{let}\backslash\text{Tumbler}\backslash\text{textTumbler}$
 20793 $\backslash\text{let}\backslash\text{notslash}\backslash\text{textnotslash}$
 20794 $\backslash\text{let}\backslash\text{notbackslash}\backslash\text{textnotbackslash}$
 20795 $\backslash\text{let}\backslash\text{boxbackslash}\backslash\text{textboxbackslash}$
 20796 $\backslash\text{let}\backslash\text{APLleftarrowbox}\backslash\text{textAPLleftarrowbox}$
 20797 $\backslash\text{let}\backslash\text{APLrightarrowbox}\backslash\text{textAPLrightarrowbox}$
 20798 $\backslash\text{let}\backslash\text{APLuparrowbox}\backslash\text{textAPLuparrowbox}$
 20799 $\backslash\text{let}\backslash\text{APLdownarrowbox}\backslash\text{textAPLdownarrowbox}$
 20800 $\backslash\text{let}\backslash\text{APLinput}\backslash\text{textAPLinput}$
 20801 $\backslash\text{let}\backslash\text{Request}\backslash\text{textRequest}$
 20802 $\backslash\text{let}\backslash\text{Beam}\backslash\text{textBeam}$

20803 \let\hexagon\texthexagon
 20804 \let\APLbox\textAPLbox
 20805 \let\ForwardToIndex\textForwardToIndex
 20806 \let\RewindToIndex\textRewindToIndex
 20807 \let\bbslash\textbbslash
 20808 \let\CircledA\textCircledA
 20809 \let\CleaningF\textCleaningF
 20810 \let\CleaningFF\textCleaningFF
 20811 \let\CleaningP\textCleaningP
 20812 \let\CleaningPP\textCleaningPP
 20813 \let\CuttingLine\textCuttingLine
 20814 \let\UParrow\textUParrow
 20815 \let\bigtriangleup\textbigtriangleup
 20816 \let\Forward\textForward
 20817 \let\triangleright\texttriangleright
 20818 \let\RHD\textRHD
 20819 \let\DOWNarrow\textDOWNarrow
 20820 \let\bigtriangledown\textbigtriangledown
 20821 \let\Rewind\textRewind
 20822 \let\triangleleft\texttriangleleft
 20823 \let\LHD\textLHD
 20824 \let\diamond\textdiamond
 20825 \let\lozenge\textlozenge
 20826 \let\LEFTCIRCLE\textLEFTCIRCLE
 20827 \let\RIGHTCIRCLE\textRIGHTCIRCLE
 20828 \let\openbullet\textopenbullet
 20829 \let\boxbar\textboxbar
 20830 \let\bigcircle\textbigcircle
 20831 \let\Cloud\textCloud
 20832 \let\FiveStar\textFiveStar
 20833 \let\FiveStarOpen\textFiveStarOpen
 20834 \let\Phone\textPhone
 20835 \let\boxempty\textboxempty
 20836 \let\Checkedbox\textCheckedbox
 20837 \let\Crossedbox\textCrossedbox
 20838 \let\Coffeecup\textCoffeecup
 20839 \let\HandCuffLeft\textHandCuffLeft
 20840 \let\HandCuffRight\textHandCuffRight
 20841 \let\HandLeft\textHandLeft
 20842 \let\HandRight\textHandRight
 20843 \let\Radioactivity\textRadioactivity
 20844 \let\Biohazard\textBiohazard
 20845 \let\Ankh\textAnkh
 20846 \let\YinYang\textYinYang
 20847 \let\frownie\textfrownie
 20848 \let\smiley\textsmiley
 20849 \let\blacksmiley\textblacksmiley
 20850 \let\sun\textsun
 20851 \let\leftmoon\textleftmoon
 20852 \let\rightmoon\textrightmoon
 20853 \let\mercury\textmercury
 20854 \let\earth\textearth
 20855 \let\male\textmale
 20856 \let\jupiter\textjupiter
 20857 \let\saturn\textsaturn
 20858 \let\uranus\texturanus
 20859 \let\neptune\textneptune

20860 \let\pluto\textpluto
 20861 \let\aries\textaries
 20862 \let\taurus\texttaurus
 20863 \let\gemini\textgemini
 20864 \let\cancer\textcancer
 20865 \let\leo\textleo
 20866 \let\virgo\textvirgo
 20867 \let\libra\textlibra
 20868 \let\scorpio\textscorpio
 20869 \let\sagittarius\textsagittarius
 20870 \let\capricornus\textcapricornus
 20871 \let\aquarius\textaquarius
 20872 \let\pisces\textpisces
 20873 \let\quarternote\textquarternote
 20874 \let\twonotes\texttwonotes
 20875 \let\sixteenthnote\textsixteenthnote
 20876 \let\flat\textflat
 20877 \let\natural\textnatural
 20878 \let\sharp\textsharp
 20879 \let\recycle\textrecycle
 20880 \let\Wheelchair\textWheelchair
 20881 \let\Flag\textFlag
 20882 \let\MineSign\textMineSign
 20883 \let\ds\textds
 20884 \let\dsmedical\textdsmedical
 20885 \let\dsjuridical\textdsjuridical
 20886 \let\dschemical\textdschemical
 20887 \let\dsbiological\textdsbiological
 20888 \let\dscommercial\textdscommercial
 20889 \let\manstar\textmanstar
 20890 \let\danger\textdanger
 20891 \let\FemaleFemale\textFemaleFemale
 20892 \let\MaleMale\textMaleMale
 20893 \let\FemaleMale\textFemaleMale
 20894 \let\Hermaphrodite\textHermaphrodite
 20895 \let\Neutral\textNeutral
 20896 \let\hexstar\texthexstar
 20897 \let\SunCloud\textSunCloud
 20898 \let\Rain\textRain
 20899 \let\noway\textnoway
 20900 \let\Mountain\textMountain
 20901 \let\Tent\textTent
 20902 \let\ScissorRight\textScissorRight
 20903 \let\ScissorRightBrokenTop\textScissorRightBrokenTop
 20904 \let\ScissorHollowRight\textScissorHollowRight
 20905 \let\PhoneHandset\textPhoneHandset
 20906 \let\Tape\textTape
 20907 \let\Plane\textPlane
 20908 \let\Envelope\textEnvelope
 20909 \let\Peace\textPeace
 20910 \let\WritingHand\textWritingHand
 20911 \let\PencilRightDown\textPencilRightDown
 20912 \let\PencilRight\textPencilRight
 20913 \let\PencilRightUp\textPencilRightUp
 20914 \let\NibRight\textNibRight
 20915 \let\NibSolidRight\textNibSolidRight
 20916 \let\Checkmark\textCheckmark

20917 \let\CheckmarkBold\textCheckmarkBold
 20918 \let\XSolid\textXSolid
 20919 \let\XSolidBold\textXSolidBold
 20920 \let\XSolidBrush\textXSolidBrush
 20921 \let\PlusOutline\textPlusOutline
 20922 \let\Plus\textPlus
 20923 \let\PlusThinCenterOpen\textPlusThinCenterOpen
 20924 \let\PlusCenterOpen\textPlusCenterOpen
 20925 \let\Cross\textCross
 20926 \let\CrossOpenShadow\textCrossOpenShadow
 20927 \let\CrossOutline\textCrossOutline
 20928 \let\CrossMaltese\textCrossMaltese
 20929 \let\DavidStar\textDavidStar
 20930 \let\FourAsterisk\textFourAsterisk
 20931 \let\JackStar\textJackStar
 20932 \let\JackStarBold\textJackStarBold
 20933 \let\ClowerTips\textClowerTips
 20934 \let\FourStar\textFourStar
 20935 \let\FourStarOpen\textFourStarOpen
 20936 \let\FiveStarOpenCircled\textFiveStarOpenCircled
 20937 \let\FiveStarCenterOpen\textFiveStarCenterOpen
 20938 \let\FiveStarOpenDotted\textFiveStarOpenDotted
 20939 \let\FiveStarOutline\textFiveStarOutline
 20940 \let\FiveStarOutlineHeavy\textFiveStarOutlineHeavy
 20941 \let\FiveStarConvex\textFiveStarConvex
 20942 \let\FiveStarShadow\textFiveStarShadow
 20943 \let\AsteriskBold\textAsteriskBold
 20944 \let\AsteriskCenterOpen\textAsteriskCenterOpen
 20945 \let\EightStarTaper\textEightStarTaper
 20946 \let\EightStarConvex\textEightStarConvex
 20947 \let\SixStar\textSixStar
 20948 \let\EightStar\textEightStar
 20949 \let\EightStarBold\textEightStarBold
 20950 \let\TwelveStar\textTwelveStar
 20951 \let\SixteenStarLight\textSixteenStarLight
 20952 \let\SixFlowerPetalRemoved\textSixFlowerPetalRemoved
 20953 \let\SixFlowerOpenCenter\textSixFlowerOpenCenter
 20954 \let\Asterisk\textAsterisk
 20955 \let\SixFlowerAlternate\textSixFlowerAlternate
 20956 \let\FiveFlowerPetal\textFiveFlowerPetal
 20957 \let\FiveFlowerOpen\textFiveFlowerOpen
 20958 \let\EightFlowerPetal\textEightFlowerPetal
 20959 \let\SunshineOpenCircled\textSunshineOpenCircled
 20960 \let\SixFlowerAltPetal\textSixFlowerAltPetal
 20961 \let\SnowflakeChevron\textSnowflakeChevron
 20962 \let\Snowflake\textSnowflake
 20963 \let\SnowflakeChevronBold\textSnowflakeChevronBold
 20964 \let\Sparkle\textSparkle
 20965 \let\SparkleBold\textSparkleBold
 20966 \let\AsteriskRoundedEnds\textAsteriskRoundedEnds
 20967 \let\EightFlowerPetalRemoved\textEightFlowerPetalRemoved
 20968 \let\EightAsterisk\textEightAsterisk
 20969 \let\CircleShadow\textCircleShadow
 20970 \let\SquareShadowBottomRight\textSquareShadowBottomRight
 20971 \let\SquareTopRight\textSquareTopRight
 20972 \let\SquareCastShadowBottomRight\textSquareCastShadowBottomRight
 20973 \let\SquareCastShadowTopRight\textSquareCastShadowTopRight

20974 `\let\DiamondSolid\textDiamondSolid`
 20975 `\let\RectangleThin\textRectangleThin`
 20976 `\let\Rectangle\textRectangle`
 20977 `\let\RectangleBold\textRectangleBold`
 20978 `\let\perp\textperp`
 20979 `\let\notperp\textnotperp`
 20980 `\let\veedot\textveedot`
 20981 `\let\wedgedot\textwedgedot`
 20982 `\let\leftspoon\textleftspoon`
 20983 `\let\lbrackdbl\textlbrackdbl`
 20984 `\let\rbrackdbl\textrbrackdbl`
 20985 `\let\circlearrowleft\textcirclearrowleft`
 20986 `\let\circlearrowright\textcirclearrowright`
 20987 `\let\longleftarrow\textlongleftarrow`
 20988 `\let\longrightarrow\textlongrightarrow`
 20989 `\let\longleftarrow\textlongleftarrow`
 20990 `\let\Longleftarrow\textLongleftarrow`
 20991 `\let\Longrightarrow\textLongrightarrow`
 20992 `\let\Longleftarrow\textLongleftarrow`
 20993 `\let\longmapsto\textlongmapsto`
 20994 `\let\Longmapsfrom\textLongmapsfrom`
 20995 `\let\Longmapsto\textLongmapsto`
 20996 `\let\nwsearrow\textnwsearrow`
 20997 `\let\neswarrow\textneswarrow`
 20998 `\let\hookrightarrow\texthookrightarrow`
 20999 `\let\rhookrightarrow\text\rhookrightarrow`
 21000 `\let\hookrightarrow\texthookrightarrow`
 21001 `\let\rhookrightarrow\text\rhookrightarrow`
 21002 `\let\leadsto\textleadsto`
 21003 `\let\rcurvesearrow\textrcurvesearrow`
 21004 `\let\lcurvesearrow\textlcurvesearrow`
 21005 `\let\lcurvesearrowsw\textlcurvesearrowsw`
 21006 `\let\rcurvesearrowse\textrcurvesearrowse`
 21007 `\let\lcurvesearrowdown\textlcurvesearrowdown`
 21008 `\let\rcurvesearrowdown\textrcurvesearrowdown`
 21009 `\let\rcurvesearrowleft\textrcurvesearrowleft`
 21010 `\let\rcurvesearrowright\textrcurvesearrowright`
 21011 `\let\leftrightharpoon\textleftrightharpoon`
 21012 `\let\rightrightharpoon\text\rightrightharpoon`
 21013 `\let\updownharpoonrightleft\textupdownharpoonrightleft`
 21014 `\let\updownharpoonleftright\textupdownharpoonleftright`
 21015 `\let\leftleftharpoons\textleftleftharpoons`
 21016 `\let\upupharpoons\textupupharpoons`
 21017 `\let\rightrightharpoons\text\rightrightharpoons`
 21018 `\let\downdownharpoons\textdowndownharpoons`
 21019 `\let\leftbarharpoon\textleftbarharpoon`
 21020 `\let\barleftharpoon\textbarleftharpoon`
 21021 `\let\rightbarharpoon\textrightbarharpoon`
 21022 `\let\barrightharpoon\textbarrightharpoon`
 21023 `\let\updownharpoons\textupdownharpoons`
 21024 `\let\downupharpoons\textdownupharpoons`
 21025 `\let\moo\textmoo`
 21026 `\let\llparenthesis\textllparenthesis`
 21027 `\let\rrparenthesis\textrrparenthesis`
 21028 `\let\invdiameter\textinvdiameter`
 21029 `\let\obar\textobar`
 21030 `\let\obslash\textobslash`

21031 $\backslash\text{let}\backslash\text{obot}\backslash\text{textobot}$
 21032 $\backslash\text{let}\backslash\text{NoChemicalCleaning}\backslash\text{textNoChemicalCleaning}$
 21033 $\backslash\text{let}\backslash\text{olessthan}\backslash\text{textolessthan}$
 21034 $\backslash\text{let}\backslash\text{ogreaterthan}\backslash\text{textogreaterthan}$
 21035 $\backslash\text{let}\backslash\text{boxslash}\backslash\text{textboxslash}$
 21036 $\backslash\text{let}\backslash\text{boxbslash}\backslash\text{textboxbslash}$
 21037 $\backslash\text{let}\backslash\text{boxast}\backslash\text{textboxast}$
 21038 $\backslash\text{let}\backslash\text{boxcircle}\backslash\text{textboxcircle}$
 21039 $\backslash\text{let}\backslash\text{boxbox}\backslash\text{textboxbox}$
 21040 $\backslash\text{let}\backslash\text{Valve}\backslash\text{textValve}$
 21041 $\backslash\text{let}\backslash\text{multimapboth}\backslash\text{textmultimapboth}$
 21042 $\backslash\text{let}\backslash\text{shuffle}\backslash\text{textshuffle}$
 21043 $\backslash\text{let}\backslash\text{uplus}\backslash\text{textuplus}$
 21044 $\backslash\text{let}\backslash\text{bigdoublewedge}\backslash\text{textbigdoublewedge}$
 21045 $\backslash\text{let}\backslash\text{bigdoublevee}\backslash\text{textbigdoublevee}$
 21046 $\backslash\text{let}\backslash\text{Join}\backslash\text{textJoin}$
 21047 $\backslash\text{let}\backslash\text{fatsemi}\backslash\text{textfatsemi}$
 21048 $\backslash\text{let}\backslash\text{circplus}\backslash\text{textcircplus}$
 21049 $\backslash\text{let}\backslash\text{minusdot}\backslash\text{textminusdot}$
 21050 $\backslash\text{let}\backslash\text{dottimes}\backslash\text{textdottimes}$
 21051 $\backslash\text{let}\backslash\text{dtimes}\backslash\text{texdtimes}$
 21052 $\backslash\text{let}\backslash\text{odiv}\backslash\text{textodiv}$
 21053 $\backslash\text{let}\backslash\text{invneg}\backslash\text{textinvneg}$
 21054 $\backslash\text{let}\backslash\text{sqdoublecap}\backslash\text{textsquaddoublecap}$
 21055 $\backslash\text{let}\backslash\text{capdot}\backslash\text{textcapdot}$
 21056 $\backslash\text{let}\backslash\text{sqdoublecup}\backslash\text{textsquaddoublecup}$
 21057 $\backslash\text{let}\backslash\text{doublewedge}\backslash\text{textdoublewedge}$
 21058 $\backslash\text{let}\backslash\text{doublevee}\backslash\text{textdoublevee}$
 21059 $\backslash\text{let}\backslash\text{doublebarwedge}\backslash\text{textdoublebarwedge}$
 21060 $\backslash\text{let}\backslash\text{veedoublebar}\backslash\text{textveedoublebar}$
 21061 $\backslash\text{let}\backslash\text{eqdot}\backslash\text{texteqdot}$
 21062 $\backslash\text{let}\backslash\text{neqdot}\backslash\text{textneqdot}$
 21063 $\backslash\text{let}\backslash\text{coloncolonequals}\backslash\text{textcoloncolonequals}$
 21064 $\backslash\text{let}\backslash\text{leqslant}\backslash\text{textleqslant}$
 21065 $\backslash\text{let}\backslash\text{nleqslant}\backslash\text{textnleqslant}$
 21066 $\backslash\text{let}\backslash\text{geqslant}\backslash\text{textgeqslant}$
 21067 $\backslash\text{let}\backslash\text{ngeqslant}\backslash\text{textngeqslant}$
 21068 $\backslash\text{let}\backslash\text{lessapprox}\backslash\text{textlessapprox}$
 21069 $\backslash\text{let}\backslash\text{nlessapprox}\backslash\text{textnlessapprox}$
 21070 $\backslash\text{let}\backslash\text{gtrapprox}\backslash\text{textgtrapprox}$
 21071 $\backslash\text{let}\backslash\text{ngtrapprox}\backslash\text{textngtrapprox}$
 21072 $\backslash\text{let}\backslash\text{lneq}\backslash\text{textlneq}$
 21073 $\backslash\text{let}\backslash\text{gneq}\backslash\text{textgneq}$
 21074 $\backslash\text{let}\backslash\text{lnapprox}\backslash\text{textlnapprox}$
 21075 $\backslash\text{let}\backslash\text{gnapprox}\backslash\text{textgnapprox}$
 21076 $\backslash\text{let}\backslash\text{lesseqgtr}\backslash\text{textlesseqgtr}$
 21077 $\backslash\text{let}\backslash\text{gtreqqlless}\backslash\text{textgtreqqlless}$
 21078 $\backslash\text{let}\backslash\text{eqslantless}\backslash\text{texteqslantless}$
 21079 $\backslash\text{let}\backslash\text{eqslantgtr}\backslash\text{texteqslantgtr}$
 21080 $\backslash\text{let}\backslash\text{leftslice}\backslash\text{textleftslice}$
 21081 $\backslash\text{let}\backslash\text{rightslice}\backslash\text{textrightslice}$
 21082 $\backslash\text{let}\backslash\text{preceq}\backslash\text{textpreceq}$
 21083 $\backslash\text{let}\backslash\text{npreceq}\backslash\text{textnpreceq}$
 21084 $\backslash\text{let}\backslash\text{succeq}\backslash\text{textsucceq}$
 21085 $\backslash\text{let}\backslash\text{nsucceq}\backslash\text{textnsucceq}$
 21086 $\backslash\text{let}\backslash\text{precneq}\backslash\text{textprecneq}$
 21087 $\backslash\text{let}\backslash\text{succneq}\backslash\text{textsuccneq}$

21088 \let\preceqq\textpreceqq
 21089 \let\npreceqq\textnpreceqq
 21090 \let\succeqq\textsucceqq
 21091 \let\nsucceqq\textnsucceqq
 21092 \let\precneqq\textprecneqq
 21093 \let\succneqq\textsuccneqq
 21094 \let\precapprox\textprecapprox
 21095 \let\nprecapprox\textnprecapprox
 21096 \let\succapprox\textsuccapprox
 21097 \let\nsuccapprox\textnsuccapprox
 21098 \let\precnapprox\textprecnapprox
 21099 \let\succnapprox\textsuccnapprox
 21100 \let\subseteqq\textsubseteqq
 21101 \let\nsubseteqq\textnsubseteqq
 21102 \let\supseteqq\textsupteqq
 21103 \let\nsupseteqq\textnsupseteqq
 21104 \let\dashV\textdashV
 21105 \let\ndashV\textndashV
 21106 \let\Dashv\textDashv
 21107 \let\ndashv\textndashv
 21108 \let\DashV\textDashV
 21109 \let\ndashV\textndashV
 21110 \let\downmodels\textdownmodels
 21111 \let\ndownmodels\textndownmodels
 21112 \let\upmodels\textupmodels
 21113 \let\nupmodels\textnupmodels
 21114 \let\upspoon\textupspoon
 21115 \let\interleave\textinterleave
 21116 \let\slash\textslash
 21117 \let\pentagon\textpentagon
 21118 \let\varhexagon\textvarhexagon
 21119 \let\jinferior\textjinferior
 21120 \let\slashdiv\textslashdiv
 21121 \let\fivedots\textfivedots
 21122 \let\oo\textoo
 21123 \let\GaPa\textGaPa
 21124 \let\HaPa\textHaPa
 21125 \let\ViPa\textViPa
 21126 \let\AcPa\textAcPa
 21127 \let\SePa\textSePa
 21128 \let\ZwPa\textZwPa
 21129 \let\fullnote\textfullnote
 21130 \let\halfnote\texthalfnote
 21131 \let\Vier\textVier
 21132 \let\Acht\textAcht
 21133 \let\Sech\textSech
 21134 \let\Zwdr\textZwdr
 21135 \let\Mundus\textMundus
 21136 \let\Moon\textMoon
 21137 \let\ManFace\textManFace
 21138 \let\WomanFace\textWomanFace
 21139 \let\Fax\textFax
 21140 \let\Fire\textFire
 21141 \let\Bicycle\textBicycle
 21142 \let\Gentsroom\textGentsroom
 21143 \let\Ladiesroom\textLadiesroom
 21144 \let\ccnc\textccnc

```

21145 \let\ccsa\textccsa
21146 \let\Info\textInfo
21147 \let\CESign\textCESign
21148 \let\neg\textneg
21149 \let\times\texttimes
21150 \let\div\textdiv
21151 \let\pm\textpm
21152 \let\cdot\textcdot
21153 }% \psdmapshortnames
21154 \newcommand*{\psdaliasnames}{%
21155 \let\epsdice\HyPsd@DieFace
21156 \let\fcdice\HyPsd@DieFace
21157 \let\MoonPha\HyPsd@MoonPha
21158 \let\mathdollar\textdollar
21159 \let\EyesDollar\textdollar
21160 \let\binampersand\textampersand
21161 \let\with\textampersand
21162 \let\mathunderscore\textunderscore
21163 \let\textvertline\textbar
21164 \let\mathsterling\textsterling
21165 \let\pounds\textsterling
21166 \let\brokenvert\textbrokenbar
21167 \let\mathsection\textsection
21168 \let\S\textsection
21169 \let\mathparagraph\textparagraph
21170 \let\MultiplicationDot\textperiodcentered
21171 \let\Squaredot\textperiodcentered
21172 \let\var times\textmultiply
21173 \let\MVMultiplication\textmultiply
21174 \let\eth\dh
21175 \let\crossd\textcrd
21176 \let\textbard\textcrd
21177 \let\bard\textcrd
21178 \let\textcrh\texthbar
21179 \let\crossh\texthbar
21180 \let\planck\texthbar
21181 \let\eng\ng
21182 \let\engma\ng
21183 \let\crossb\textcrb
21184 \let\textbarb\textcrb
21185 \let\barb\textcrb
21186 \let\Florin\textflorin
21187 \let\hv\texthvligh
21188 \let\hausak\texthtk
21189 \let\crossnilambda\textcrlambda
21190 \let\barlambda\textcrlambda
21191 \let\lambdabar\textcrlambda
21192 \let\lambdaslash\textcrlambda
21193 \let\textnrleg\textPUnrleg
21194 \let\textpipevar\textpipe
21195 \let\textdoublepipevar\textdoublepipe
21196 \let\textdoublebarpipevar\textdoublebarpipe
21197 \let\textcrg\textgslash
21198 \let\textdblig\textPUdblig
21199 \let\textqplig\textPUqplig
21200 \let\textcentoldstyle\textslashc
21201 \let\textbarc\textslashc

```

21202 \let\inva\textturna
 21203 \let\vara\textscripta
 21204 \let\invscripta\textturnscripta
 21205 \let\rotvara\textturnscripta
 21206 \let\hookb\texthtb
 21207 \let\hausab\texthtb
 21208 \let\varopeno\textopeno
 21209 \let\curlyc\textctc
 21210 \let\taild\textrtaild
 21211 \let\hookd\texthtd
 21212 \let\hausad\texthtd
 21213 \let\er\textrhookschwa
 21214 \let\epsi\textniepsilon
 21215 \let\hookrevepsilon\texthookrevepsilon
 21216 \let\closedrevepsilon\textcloserevepsilon
 21217 \let\barj\textbardotlessj
 21218 \let\hookg\texthtg
 21219 \let\varg\textscriptg
 21220 \let\vod\textipagamma
 21221 \let\invh\textturnh
 21222 \let\udesc\textturnh
 21223 \let\hookh\texthth
 21224 \let\voicedh\texthth
 21225 \let\hookheng\texththeng
 21226 \let\ibar\textbari
 21227 \let\vari\textniota
 21228 \let\tildel\textltilde
 21229 \let\latfric\textbeltl
 21230 \let\tail\textrtail
 21231 \let\lz\textlyoghlig
 21232 \let\invm\textturnm
 21233 \let\rotm\textturnm
 21234 \let\legm\textturnmrleg
 21235 \let\labdentalnas\textltailm
 21236 \let\emgma\textltailm
 21237 \let\nj\textltailn
 21238 \let\enya\textltailn
 21239 \let\tailn\textrtailn
 21240 \let\closedniomega\textcloseomega
 21241 \let\varomega\textcloseomega
 21242 \let\invr\textturnr
 21243 \let\rotr\textturnr
 21244 \let\invlegr\textturnlonglegr
 21245 \let\tailinvr\textturnrrtail
 21246 \let\legr\textlonglegr
 21247 \let\tailr\textrtailr
 21248 \let\flapr\textfishhookr
 21249 \let\flap\textfishhookr
 21250 \let\tails\textrtails
 21251 \let\curlyesh\textctesh
 21252 \let\clickt\textturnt
 21253 \let\tailt\textrtailt
 21254 \let\ubar\textbaru
 21255 \let\rotOmega\textniupsilon
 21256 \let\invv\textturnv
 21257 \let\pwedge\textturnv
 21258 \let\invw\textturnw

21259 \let\rotw\textturnw
 21260 \let\invy\textturny
 21261 \let\roty\textturny
 21262 \let\tailz\texttrtailz
 21263 \let\curlyz\textctz
 21264 \let\curlyyogh\textctyogh
 21265 \let\ejective\textglotstop
 21266 \let\glottal\textglotstop
 21267 \let\reveject\textrevglotstop
 21268 \let\clickc\textstretchc
 21269 \let\textstretchcvar\textstretchc
 21270 \let\clickb\textbullseye
 21271 \let\textObullseye\textbullseye
 21272 \let\textctjvar\textctj
 21273 \let\textturnsck\textturnk
 21274 \let\dz\textdzlig
 21275 \let\tesh\textteshlig
 21276 \let\digamma\textdigammagreek
 21277 \let\hardsign\cyrhrdsn
 21278 \let\softsign\cyrsoftsn
 21279 \let\hebsin\hebshin
 21280 \let\textsck\textPUscK
 21281 \let\textscm\textPUscm
 21282 \let\textscp\textPUscp
 21283 \let\textrevscr\textPUrevscr
 21284 \let\textrhoKa\textPURhooka
 21285 \let\textrhoKe\textPURhooke
 21286 \let\textrhoKepsilon\textPURhookepsilon
 21287 \let\textrhoKopeno\textPURhookopeno
 21288 \let\textdoublevertline\textbardbl
 21289 \let\dag\textdagger
 21290 \let\ddagger\textdaggerdbl
 21291 \let\ddag\textdaggerdbl
 21292 \let\mathellipsis\textellipsis
 21293 \let\EurDig\texteuro
 21294 \let\EURdig\texteuro
 21295 \let\EurHv\texteuro
 21296 \let\EURhv\texteuro
 21297 \let\EurCr\texteuro
 21298 \let\EURcr\texteuro
 21299 \let\EurTm\texteuro
 21300 \let\EURtm\texteuro
 21301 \let\Eur\texteuro
 21302 \let\Denarius\textDeleatur
 21303 \let\agemO\textmho
 21304 \let\EstimatedSign\textestimated
 21305 \let\Ecommerce\textestimated
 21306 \let\bindnasrepma\textinvamp
 21307 \let\parr\textinvamp
 21308 \let\MVRightArrow\textrightarrow
 21309 \let\MVRightarrow\textrightarrow
 21310 \let\MArrowDown\textdownarrow
 21311 \let\Force\textdownarrow
 21312 \let\textglobrise\textnearrow
 21313 \let\textglobfall\textsearrow
 21314 \let\Lightning\textlightning
 21315 \let\Conclusion\textRightarrow

21316 \let\dashedleftarrow\textdashleftarrow
 21317 \let\dashedrightarrow\textdashrightarrow
 21318 \let\varnothing\textemptyset
 21319 \let\owns\textni
 21320 \let\notni\textnotowner
 21321 \let\varprop\textpropto
 21322 \let\varangle\textsphericalangle
 21323 \let\Anglesign\textsphericalangle
 21324 \let\AngleSign\textsphericalangle
 21325 \let\notdivides\textnmid
 21326 \let\varowedge\textowedge
 21327 \let\varovee\textovee
 21328 \let\varint\textint
 21329 \let\varoint\textoint
 21330 \let\downtherefore\textbecause
 21331 \let\textdotdiv\textdotminus
 21332 \let\AC\textsim
 21333 \let\wreath\textwr
 21334 \let\nthickapprox\textnapprox
 21335 \let\VHF\texttriplesim
 21336 \let\notasymp\textnasymp
 21337 \let\Doteq\textdoteqdot
 21338 \let\corresponds\texthateq
 21339 \let\Corresponds\texthateq
 21340 \let\nequal\textneq
 21341 \let\Congruent\textequiv
 21342 \let\NotCongruent\textnequiv
 21343 \let\notequiv\textnequiv
 21344 \let\LessOrEqual\textleq
 21345 \let\LargerOrEqual\textgeq
 21346 \let\apprle\textless sim
 21347 \let\apprge\textgtr sim
 21348 \let\varoplus\textoplus
 21349 \let\varominus\textominus
 21350 \let\varotimes\textotimes
 21351 \let\varoslash\textoslash
 21352 \let\varodot\textodot
 21353 \let\ocirc\textcircledcirc
 21354 \let\varocircle\textcircledcirc
 21355 \let\varoast\textcircledast
 21356 \let\oasterisk\textcircledast
 21357 \let\rightvdash\textvdash
 21358 \let\leftvdash\textdashv
 21359 \let\nleftvdash\textndashv
 21360 \let\downvdash\texttop
 21361 \let\upvdash\textbot
 21362 \let\nperp\textnupvdash
 21363 \let\models\textvDash
 21364 \let\rightmodels\textvDash
 21365 \let\rightVdash\textVdash
 21366 \let\rightModels\textVDash
 21367 \let\nrightvdash\textnvDash
 21368 \let\nrightmodels\textnvDash
 21369 \let\nmodels\textnvDash
 21370 \let\nrightVdash\textnVdash
 21371 \let\nrightModels\textnVDash
 21372 \let\lessclosed\textlhd

21373 \let\gtrclosed\texttrhd
 21374 \let\leqclosed\textunlhd
 21375 \let\trianglelefteq\textunlhd
 21376 \let\geqclosed\textunrhd
 21377 \let\trianglerighteq\textunrhd
 21378 \let\Bowtie\textbowtie
 21379 \let\varcurlyvee\textcurlyvee
 21380 \let\varcurlywedge\textcurlywedge
 21381 \let\doublecap\textCap
 21382 \let\doublecup\textCup
 21383 \let\varsqsubsetneq\textsqsubsetneq
 21384 \let\varsqsupsetneq\textsqsupsetneq
 21385 \let\nlessclosed\textntriangleleft
 21386 \let\ngtrclosed\textntriangleright
 21387 \let\Clocklogo\textclock
 21388 \let\ClockLogo\textclock
 21389 \let\baro\textstmaryrdbaro
 21390 \let\varparallelinv\textbbslash
 21391 \let\CleaningA\textCircledA
 21392 \let\Kutline\textCuttingLine
 21393 \let\CutLine\textCuttingLine
 21394 \let\Cutline\textCuttingLine
 21395 \let\MoveUp\textUParrow
 21396 \let\APLup\textbigtriangleup
 21397 \let\Bleech\textbigtriangleup
 21398 \let\MoveDown\textDOWNarrow
 21399 \let\APLdown\textbigtriangledown
 21400 \let\Diamond\textdiamond
 21401 \let\varbigcirc\textbigcircle
 21402 \let\Telefon\textPhone
 21403 \let\Box\textboxempty
 21404 \let\CheckedBox\textCheckedbox
 21405 \let\XBox\textCrossedbox
 21406 \let\CrossedBox\textCrossedbox
 21407 \let\rightpointleft\textHandLeft
 21408 \let\leftpointright\textHandRight
 21409 \let\PointingHand\textHandRight
 21410 \let\Pointinghand\textHandRight
 21411 \let\Radiation\textRadioactivity
 21412 \let\Yinyang\textYinYang
 21413 \let\YingYang\textYinYang
 21414 \let\Yingyang\textYinYang
 21415 \let\Frowny\textfrownie
 21416 \let\Smiley\textsmiley
 21417 \let\Sun\textsun
 21418 \let\Mercury\textmercury
 21419 \let\textfemale\textPUfemale
 21420 \let\female\textPUfemale
 21421 \let\venus\textPUfemale
 21422 \let\Venus\textPUfemale
 21423 \let\Female\textPUfemale
 21424 \let\Earth\textearth
 21425 \let\mars\textmale
 21426 \let\Mars\textmale
 21427 \let\Male\textmale
 21428 \let\Jupiter\textjupiter
 21429 \let\Saturn\textsaturn

21430 \let\Uranus\texturanus
 21431 \let\Neptune\textneptune
 21432 \let\Pluto\textpluto
 21433 \let\Aries\textaries
 21434 \let\Taurus\texttaurus
 21435 \let\Gemini\textgemini
 21436 \let\Cancer\textcancer
 21437 \let\Leo\textleo
 21438 \let\Virgo\textvirgo
 21439 \let\Libra\textlibra
 21440 \let\Scorpio\textscorpio
 21441 \let\Sagittarius\textsagittarius
 21442 \let\Capricorn\textcapricornus
 21443 \let\Aquarius\textaquarius
 21444 \let\Pisces\textpisces
 21445 \let\spadesuit\textspadesuitblack
 21446 \let\Heart\textheartsuitwhite
 21447 \let\heartsuit\textheartsuitwhite
 21448 \let\diamondsuit\textdiamondsuitwhite
 21449 \let\clubsuit\textclubsuitblack
 21450 \let\eighthnote\textmusicalnote
 21451 \let\Recycling\textrecycle
 21452 \let\VarFlag\textFlag
 21453 \let\textxswup\textdsmilitary
 21454 \let\textuncrfemale\textPUuncrfemale
 21455 \let\Football\textSoccerBall
 21456 \let\CutLeft\textScissorRightBrokenBottom
 21457 \let\Cutright\textScissorRightBrokenBottom
 21458 \let\RightScissors\textScissorRight
 21459 \let\Leftscissors\textScissorRight
 21460 \let\Letter\textEnvelope
 21461 \let\Writinghand\textWritingHand
 21462 \let\checkmark\textCheckmark
 21463 \let\davidstar\textDavidStar
 21464 \let\llbracket\textlbrackdbl
 21465 \let\rrbracket\textrrbrackdbl
 21466 \let\RightTorque\textlcurvearrowdown
 21467 \let\Righttorque\textlcurvearrowdown
 21468 \let\LeftTorque\textrcurvearrowdown
 21469 \let\Lefttorque\textrcurvearrowdown
 21470 \let\textvarobar\textobar
 21471 \let\circledbslash\textobslash
 21472 \let\obackslash\textobslash
 21473 \let\varobslash\textobslash
 21474 \let\odplus\textobot
 21475 \let\varolessthan\textolessthan
 21476 \let\varogreaterthan\textogreaterthan
 21477 \let\divdot\textminusdot
 21478 \let\doublesqcap\textsqdoublecap
 21479 \let\doublesqcup\textsqdoublecup
 21480 \let\merge\textdoublevee
 21481 \let\leftVdash\textdashV
 21482 \let\nleftVdash\textndashV
 21483 \let\leftmodels\textDashv
 21484 \let\nleftmodels\textnDashv
 21485 \let\leftModels\textDashV
 21486 \let\nleftModels\textnDashV


```

21487 \let\varparallel\textsslash
21488 \let\textheng\textPUheng
21489 \let\textlhookfour\textPUlhookfour
21490 \let\textscf\textPUscf
21491 \let\textaoig\textPUaoig
21492 \let\Ganz\textfullnote
21493 \let\Halb\texthalfnote
21494 \let\Womanface\textWomanFace
21495 \let\Faxmachine\textFax
21496 \let\CEsign\textCESign
21497 }% \psdaliasnames
21498 </psdextra>

```

52 End of file hyccheck.tex

```

21499 <*check>
21500 \typeout{}
21501 \begin{document}
21502 \end{document}
21503 </check>

```

53 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols			
\!	195, 220, 2167	16126, 16186, 16188, 16309,	\@ 3403
\”	202, 227, 3412, 14756, 15116, 15128, 15140, 15266, 15352, 15366, 15374, 15389, 15401, 15418, 15432, 15443, 15444, 15458, 15470, 15477, 15528, 15569, 15596, 15625, 15798, 15812, 15820, 15834, 15848, 15865, 15879, 15890, 15891, 15906, 15918, 15926, 16184, 16846, 16848, 16859, 16911, 16913, 16945, 16959, 17115, 17129, 17373, 17375, 17390, 17393, 17395, 17397, 17399, 17401, 17411, 17413, 17415, 17417, 17424, 17427, 17429, 17431, 17437, 17439, 17445, 17447, 17453, 17455, 17662, 17664, 17814, 17816, 17830, 17832, 17852	16311, 16317, 16319, 16322, 16325, 16779, 16781, 16783, 16785, 16787, 16789, 16791, 16794, 16850, 16852, 16854, 16856, 16915, 16918, 16920, 16949, 16969, 17119, 17139, 17678, 17680, 17702, 17704, 17742, 17744, 17810, 17812, 20052, 20057, 20062, 20067, 20072, 20077, 20082, 20087, 20092, 20097, 20102, 20107, 20112, 20117, 20122, 20127, 20132, 20137, 20142, 20147, 20152, 20157, 20162, 20167	\@@@ 2608 \@@BOOKMARK 14737, 14740, <u>14798</u> , 14866, 14873 \@@ListBox 13131, 13155, 13647, 13681, 13995, <u>14038</u> \@@Menu 13346, 13354 \@@PasswordField . 13295, 13301 \@@Radio . 13116, 13137, 13344 13368, 13632, 13653, 13980, <u>14001</u> \@@TextField 13297, 13312 \@@commahyperpage 8642, 8643 \@@hyper@readexternallink 5236, 5238 \@@hyperref 5090, 5091 \@@latextohtmlX . . . 3220, 5453 \@@wrindex 8570, 8571 \@@writetorep 14597, 14603 \@Alph 7147, 7149 \@BIBLABEL . 7990, 7996, 8002 \@BOOKMARK . . 14737, 14739 \@CITE 8067, 8075 \@CITEX 8069 \@CheckBox 6250, 10942, 13229, <u>13261</u> , 13399, 13769, <u>14140</u> \@ChoiceMenu 6247, 10945, 13069, 13264, 13334, 13584, <u>13932</u> \@Form 5911, 10932, 12853, <u>13251</u> , 13278, 13477, <u>13853</u> \@Gauge . . . 6256, 10936, 13037, <u>13255</u> , 13283, 13420, <u>13850</u> \@Localurlfalse 10885 \@Localurltrue 10882 \@M . . . 1218, 2665, 4974, 7602 \@MM 7752 \@PackageError 264 \@PackageInfo 267 \@PackageInfoNoLine 268 \@PackageWarning 265 \@PackageWarningNoLine . . 266 \@PushButton 6253, 10948, <u>13162</u> , 13267, 13380, 13691, <u>14054</u> \@Refstar 8946, 8953 \@Reset 6262, 10951, 13206, <u>13270</u> , 13396, 13744, <u>14111</u> \@Roman 657 \@SCTR 8690, 8742 \@SetMaxRnhefLabel 8064
\# .	562, 2252, 2253, 4867, 4878, 4880, 4896, 4928, 4988, 9137, 9139, 9992, 10001, 10036, 10877, 12481, 12492, 12528, 12759, 12768, 12808, 14676	\(. 190, 215, 333, 783, 786, 788, 2169, 14822, 15186 \) . 191, 216, 334, 755, 761, 764, 2170, 14823, 15188 * 336 \+ 200, 225, 337 \- 201, 226 \. 198, 223, 330, 1312, 3754, 4181, 15119, 15131, 15143, 15207, 15501, 15508, 15526, 15572, 15599, 15631, 15708, 15709, 15948, 15950, 15978, 15980, 15998, 16000, 16037, 16068, 16070, 16190, 16192, 16377, 16379, 16385, 16387, 17594, 17596, 17606, 17608, 17646, 17648, 17654, 17656, 17706, 17708, 17714, 17716, 17746, 17748, 17750, 17752, 17762, 17764, 17770, 17772, 17818, 17820, 17826, 17828, 17834, 17836, 17858 \/. 194, 219, 696, 697, 698, 766, 1936, 8535 \: 189, 214 \; 199, 224, 8831 \< 196, 221 \= . . . 167, 173, 180, 183, 15121, 15133, 15145, 15521, 15576, 15603, 15630, 15928, 15930, 15970, 15972, 16022, 16024, 16025, 16096, 16098, 16156, 16158, 16389, 16391, 17407, 17409, 17433, 17435, 17650, 17652 \> 197, 222 \? 338	
\\$	184, 209, 332, 563, 4869, 4987		
\%	564, 2167, 2227, 2228, 4866, 4875, 4877, 4929, 9139		
\& . . .	185, 210, 565, 4870, 4881, 4883, 12538		
\’ . . .	203, 228, 3352, 3366, 3407, 3409, 3410, 3411, 3412, 3417, 3418, 3420, 3425, 3431, 3435, 3436, 3439, 3482, 3483, 3488, 3489, 3490, 3491, 3492, 3493, 3494, 3495, 3497, 3501, 3514, 14754, 15113, 15125, 15137, 15346, 15362, 15370, 15383, 15397, 15403, 15412, 15428, 15437, 15438, 15452, 15466, 15472, 15496, 15498, 15499, 15500, 15503, 15505, 15506, 15507, 15515, 15566, 15593, 15622, 15792, 15808, 15816, 15828, 15844, 15850, 15859, 15875, 15884, 15885, 15900, 15914, 15920, 15940, 15942, 16056, 16058, 16076, 16078, 16112, 16114, 16124,		

<code>\@Submit</code> . . . 6259, 10954, 13189, 13273, 13393, 13721, 14088	<code>\@citedatax@opt</code> . . . 8209, 8215	<code>\@extra@b@citeb</code>
<code>\@TextField</code> . 6244, 10939, 13041, 13258, 13286, 13554, 13895	<code>\@citeseppen</code> 8194, 8200	. . . 7975, 7978, 7995, 8000, 8020, 8068, 8090, 8106, 8113
<code>\@addchap</code> 15073	<code>\@citex</code> 8096	<code>\@extra@b@info</code> . 7974, 7977, 7981
<code>\@addtoreset</code> . 8464, 8465, 8479, 8687	<code>\@clubpenalty</code> 7604	<code>\@fifthoffive</code> . . 4368, 4806, 5124, 8897, 9016
<code>\@afterheading</code> 15090	<code>\@commahyperpage</code> . 8637, 8642	<code>\@filebordercolor</code> 3797, 4270, 9540, 9542, 10566, 10568, 11085, 11087, 12151
<code>\@alph</code> 7143, 7145	<code>\@ctrerr</code> 7120, 7129	<code>\@filecolor</code> . . . 3723, 3735, 9561, 10175, 10192, 10584, 11091
<code>\@anchorcolor</code> 3733, 9961, 10056, 10999, 12449, 12729	<code>\@currDisplay</code> 5999, 13081, 13144, 13363, 13377, 13596, 13660, 13944, 14011	<code>\@firstoffive</code> . . 4802, 4811, 8936, 9021
<code>\@arabic</code> 1188, 1193, 1197, 7055, 7071, 7142	<code>\@currValue</code> . . 6001, 6003, 13142, 13149, 13363, 13374, 13658, 13668, 14009, 14026, 14471	<code>\@firstofone</code> 593, 594, 595, 596, 597, 598, 599, 600, 601, 602, 603, 646, 683, 839, 1054, 1065, 1298, 1302, 1306, 1644, 4159, 4693, 5877, 5883, 6149, 6951, 7140, 7152, 7219, 7856, 7938, 8079, 8102, 8284, 8525, 9849, 13450, 14226, 14243, 14261
<code>\@auxout</code> 2602, 5137, 5400, 6470, 6472, 7232, 7260, 8010, 8025, 8041, 8051, 8081, 8104, 8130, 8136, 8160	<code>\@currentHlabel</code> 7193	<code>\@firstoftwo</code> . . . 666, 1012, 1180, 1852, 6440, 15039
<code>\@backslashchar</code> 879, 882, 885, 1442, 2129, 2133, 2136, 2274, 2291, 2297, 2301, 2309, 4891, 9152, 9162	<code>\@currentHref</code> 2610, 5429, 6352, 7036, 7173, 7175, 7184, 7186, 7193, 7274, 7276, 7286, 7337, 7348, 7350, 7389, 7408, 7412, 7421, 7447, 7539, 7570, 7595, 7668, 7678, 7680, 7681, 7737, 7765, 7863, 7889, 7893, 7920, 7922, 8139, 8323, 8346, 8359, 8366, 8434, 8458, 8460, 14587, 14978, 14991, 15002, 15032, 15049, 15084	<code>\@fnsymbol</code> 7141
<code>\@baseurl</code> 3740, 3742, 5294, 9673, 9676, 9946, 9948, 10234, 10236, 10754, 10764, 10850, 10852, 11388, 11390, 11780, 11794, 12434, 12436, 12635, 12649, 12715, 12717	<code>\@currentlabel</code> 7316, 7755, 8132, 8139, 8439, 8446, 8696, 8748	<code>\@footnotemark</code> 7611, 7674, 7692, 7774, 7786, 7788, 7800, 7801, 7831, 7833
<code>\@begintheorem</code> 7504, 7508, 7534, 7541, 7565, 7572	<code>\@currentlabelname</code> . 2600, 7669, 7738, 7766, 7868	<code>\@footnotetext</code> 7610, 7617, 7651, 7691, 7787, 7789, 7803, 7804, 7824
<code>\@bibitem</code> 8017, 8048	<code>\@currentlabstr</code> 2599, 2607	<code>\@for</code> . . . 3773, 5519, 8076, 8099, 13078, 13140, 13352, 13359, 13369, 13593, 13656, 13941, 14007
<code>\@biblabel</code> 7990, 8037	<code>\@curropt</code> . 13078, 13079, 13140, 13141, 13352, 13359, 13360, 13362, 13369, 13370, 13372, 13593, 13594, 13656, 13657, 13941, 13942, 14007, 14008	<code>\@fourthoffive</code> 4805, 5125, 9011, 9018
<code>\@bookmarkopenstatus</code> . . 4691, 4708, 14658	<code>\@dblarg</code> 7858, 7940	<code>\@gobble</code> 49, 56, 117, 586, 587, 588, 589, 626, 627, 628, 629, 669, 670, 671, 680, 682, 843, 1019, 1052, 1063, 1204, 1208, 1211, 1581, 1642, 1661, 1674, 1678, 1741, 1804, 1805, 1812, 1817, 1831, 1836, 2455, 2637, 2910, 2922, 4147, 4356, 4411, 4857, 5862, 6139, 6405, 6409, 6426, 6428, 6444, 6445, 6448, 6449, 6451, 6925, 6945, 6949, 7493, 7521, 7554, 7845, 7935, 8322, 9076, 9851, 11268, 11271, 13478, 13854, 14644, 14645, 14646, 14647
<code>\@bookmarkopenlevel</code> . . 3694, 3696, 4694	<code>\@definecounter</code> 8419, 8420	<code>\@gobblefour</code> . . . 592, 706, 1338,
<code>\@bsphack</code> 2595, 5130, 8134	<code>\@ehc</code> . . 2963, 3078, 3103, 3136, 3174, 3181, 3192, 3198, 4409, 5036, 5258, 5623, 5747, 5943, 5976, 6186, 6235, 13171, 13217, 13701, 13755, 14064, 14122	
<code>\@capstartfalse</code> 7883	<code>\@ehd</code> . . 63, 283, 289, 313, 7844, 7934	
<code>\@caption</code> 7848, 7860, 7903, 7940, 7942	<code>\@elt</code> . . . 7043, 7045, 7046, 7051	
<code>\@capter</code> 2604, 7843, 7847, 7851, 7858, 7865, 7919, 7933, 7937, 7940	<code>\@endForm</code> . 5912, 10935, 13036, 13254, 13282, 13527, 13880	
<code>\@car</code> . . . 1724, 1740, 1758, 1778, 3673, 5529, 9625, 9636	<code>\@endparent</code> . . 7502, 7530, 7561	
<code>\@cdr</code> 9626, 9637	<code>\@eqnqr</code> 7431	
<code>\@chapter</code> 14997, 14998	<code>\@eqnstarfalse</code> 7403, 7434	
<code>\@cite</code> . . 8067, 8098, 8195, 8201	<code>\@eqnstartrue</code> 7431	
<code>\@cite@opt</code> 8196, 8202, 8206, 8216	<code>\@eqnswtrue</code> 7364, 7373	
<code>\@citea</code> . 8070, 8077, 8078, 8097, 8100, 8101	<code>\@esphack</code> 2616, 5141, 8144, 8582	
<code>\@citeb</code> . 8076, 8079, 8081, 8083, 8087, 8090, 8099, 8102, 8104, 8106, 8110, 8113		
<code>\@citebordercolor</code> . . 3796, 4272		
<code>\@citecolor</code> 3734		
<code>\@citedata@opt</code> 8197, 8203, 8205		
<code>\@citedatax</code> 8212, 8217		

1339, 1340, 3950, 8811	8499, 9195, 10826, 11468,	2579, 2580, 2581, 2582,
\@gobbleopt 6451, 6453	11469, 12264, 13478, 13854,	2583, 2584, 2585, 2586,
\@gobbletwo 590, 673, 699, 707,	14235, 14654	2732, 3043, 3044, 3045,
708, 856, 1337, 1759, 1836,	\@indexfile . . . 8574, 8589, 8597,	3046, 3047, 3048, 3049,
1840, 2795, 3948, 3949,	8601, 8606	3050, 3541, 3553, 5629,
4360, 5808, 6430, 6439,	\@inlabeledfalse 7583	5630, 5631, 5632, 5954,
6447, 6451, 8999, 14988	\@inmathwarn 556, 557	5955, 7205, 7430, 7433,
\@harvarditem 8149, 8151	\@inpenc@undefined@ 2329	8124, 8125, 8126, 8127
\@hyper@C@anchor . . 5344, 5345	\@labels 7599	\@namerefstar 4844, 8941
\@hyper@itemfalse . . 6981, 6999,	\@latex@ 6555, 6556	\@nameuse 2604, 3040, 5635, 5946
7013	\@latex@error 7844, 7934	\@ne 1187, 2982, 3124, 4679, 5006,
\@hyper@itemtrue 6982	\@latex@warning . . . 5117, 8086,	10498, 10503, 11367, 12289,
\@hyper@launch . . . 5264, 5273,	8109, 8872, 8892, 8909, 9027	13889
9565, 10589, 11160, 12169	\@libibitem 7991, 8036	\@newctr 8424, 8425
\@hyper@linkfile . . . 5245, 5248,	\@linkbordercolor . . 3798, 4267,	\@newl@bel . . . 5383, 6518, 7977
5252, 5284	9489, 10989	\@newlistfalse 7580
\@hyper@readexternallink 5239,	\@linkcolor 3732, 11827	\@nil 294, 321, 501, 505, 510, 514,
5243	\@linkdim . . . 484, 10010, 10011,	529, 1636, 1639, 1647, 1724,
\@hyperdef 5098, 5099	10019, 10020, 10021, 10090,	1742, 1760, 1776, 1778,
\@hyperpage 8634, 8635	10091, 10103, 10104, 10105,	1781, 1784, 1787, 2338,
\@hyperref 5079, 5090	10127, 10128, 10141, 10142,	2340, 2356, 2358, 3673,
\@ifclasslater 15096, 15101	10143, 10167, 10168, 10181,	4913, 4917, 4922, 5311,
\@ifclassloaded 2587, 4833, 7204,	10182, 10183, 12502, 12503,	5319, 5325, 5327, 5529,
7241, 8059, 8670, 8674,	12511, 12512, 12513, 12777,	6130, 6133, 6152, 6543,
9854, 15095, 15100	12778, 12791, 12792, 12793	6546, 6553, 6555, 6556,
\@ifnextchar . . 12, 88, 103, 123,	\@listctr 8026, 8052	6668, 6716, 6717, 6719,
700, 4981, 5079, 5098, 5199,	\@m . . . 1201, 8078, 8101, 11315	6742, 6759, 6813, 6815,
5911, 6244, 6247, 6250,	\@mainaux . . 6468, 6469, 6908,	7332, 7341, 7343, 7355,
6253, 6256, 6259, 6262,	6916, 13446, 13470	8621, 8623, 8630, 8653,
6451, 6524, 6533, 7790,	\@makecaption 7884, 7886, 7953	8656, 8666, 8876, 8879,
7808, 8149, 8207, 11805,	\@makefnmark 7683, 7836	9035, 9066, 9148, 9154,
12080, 12094, 14737, 14740	\@makefnstext 7756	9158, 9164, 9625, 9626,
\@ifpackagelater 238, 1074, 2618,	\@makeother 166, 167,	9636, 9637, 11233, 11235,
7195, 8489	179, 180, 182, 183, 188, 189,	14233, 14246, 14252, 14686,
\@ifpackageloaded 515,	190, 191, 192, 193, 194, 195,	14689, 14692, 14701, 14704,
909, 1073, 2590, 3015, 3650,	196, 197, 198, 199, 200, 201,	14713
3654, 4328, 4514, 7022,	202, 203, 4881, 9124, 14826,	\@nobeckfalse 6515, 7602
7194, 7207, 7269, 7302,	14829, 14856, 14859	\@nocnterr 8478, 8492
7306, 7326, 7360, 7487,	\@makeschapterhead 15087,	\@nocounterr 8477, 8491
7688, 7704, 7744, 7916,	15089	\@noparitemfalse 7581
8119, 8192, 8431, 8488,	\@mem@titleref 4840	\@number 7140, 7219, 8284
8530, 8531, 8532, 8680,	\@mem@titleref@nolink 4840	\@onx . . . 8481, 8495, 8498, 8500
8945, 9089, 9093, 12707	\@menubordercolor . 3799, 4269,	\@onelevel@sanitize . 2788, 2792,
\@ifpackagewith 3532, 4329, 8454	9911, 9913, 10660, 10662,	2997, 3672, 4386, 4416,
\@ifstar . . . 66, 4828, 4831, 4840,	11198, 11200, 12073	4437, 4947, 5306, 5309,
4844, 6387, 6391, 6457,	\@menucolor . 3737, 9926, 10671,	5322, 5336, 5619, 5855,
6461, 8953, 8979, 8999	11204	5939, 6769, 6771, 7180,
\@ifundefined 34, 372, 976,	\@minipagefalse 7579	8352, 8922, 10355, 14683
986, 1015, 1018, 2884, 3033,	\@mkboth . . . 673, 8793, 14988,	\@oparg . 7504, 7508, 7534, 7541,
3550, 3586, 3594, 3601,	15076, 15078	7565, 7572
3623, 3671, 4296, 5618,	\@mpfn 7614, 7809, 7821	\@outlinefile 14656, 14745, 14840,
5938, 6878, 6991, 7026,	\@mpfootnotetext . . 7617, 7630,	14842, 14844, 14922, 14924,
7041, 7308, 7329, 7330,	7631, 7693	14926
7383, 7414, 7442, 7479,	\@mycount 14802, 14812	\@pagerefstar . . 4831, 8938, 8969
7849, 7867, 7984, 8067,	\@namedef 1318, 2558, 2560, 2562,	\@pagesetref 8888
8083, 8106, 8428, 8469,	2564, 2566, 2568, 2570,	\@parboxrestore 7754, 7876, 7948
8477, 8478, 8491, 8492,	2572, 2574, 2576, 2578,	\@parcount 14804, 14812

\@part	15015, 15022	9743, 10212, 10214, 10697,	12159
\@pdfauthor .	3966, 4275, 9733,	10699, 11685, 11689, 12562,	\@pdfstartpage 4168, 4170, 4286,
10216, 10701, 11441, 11706,	12566	12564	9681, 9685, 10242, 10247,
\@pdfborder		\@pdfnonfullscreenpagemode . . .	10757, 10761, 11380, 11384,
. . .	3615, 3811, 3812, 3813,	9695, 10271, 10733, 11399,	11730, 11735, 12585, 12590
3820, 3824, 3847, 3849,		11759, 12614	\@pdfstartview 4175, 4177, 4284,
4774, 9419, 10373, 10987,		\@pdfnumcopies . . .	9683, 9685, 10244, 10248,
11572, 11667, 12071, 12084,		10287, 10289, 10749, 10751,	10759, 10761, 11382, 11732,
12099, 12120, 12148, 12179,		11415, 11417, 11775, 11777,	11736, 12587, 12591
12208, 12295, 12383, 12543		12630, 12632	\@pdfsubject .
\@pdfborderstyle		\@pdfpageduration .	4012, 4280, 9735,
. . .	3616, 3828, 3829, 3830,	9797, 9802, 10799, 10801,	10221, 10691, 11443, 11704,
3839, 3843, 3851, 3853,		10804, 11324, 11326, 11329,	12571
4775, 6101, 9420, 10374,		11611, 11613, 11621	\@pdftempa . . .
10988, 11573, 11668, 12072,		\@pdfpagelayout . .	5250, 5251, 5254
12085, 12100, 12121, 12149,		9721, 10299,	\@pdftempwordfile .
12180, 12209, 12296, 12384,		10773, 11420, 11422, 11789,	5241, 5251
12544		12644	\@pdftempwordrun .
\@pdfcreationdate . .	3999, 4278,	\@pdfpagemode	5242, 5254
9737, 9739, 10208, 10210,		. . .	\@pdftitle . . .
10693, 10695, 11681, 11683,		. . .	3960, 4274, 9734,
12558, 12560		. . .	10206, 10690, 11442, 11703,
\@pdfcreator .	3994, 4277, 9736,	. . .	12556
10207, 10692, 11444, 11705,		. . .	\@pdftrapped 4023, 4026, 4029,
12557		. . .	4038, 4047, 4282, 9750,
\@pdfdirection	9696, 10272,	. . .	9752, 10707, 10709, 11708
10734, 11400, 11760, 12615		\@pdfpagescrop 4213, 4283, 9660,	\@pdfview . . .
\@pdfduplex 9702, 10278, 10740,		9664, 10238, 10239, 10260,	4149, 9401, 9409,
11406, 11766, 12621		10262, 10780, 10782, 11376,	10323, 10327, 10331, 10335,
\@pdfhighlight		11378, 11748, 11750, 12603,	10339, 10343, 10344, 10347,
. . .	3803, 4273, 9439, 9441,	12605	10348, 10351, 10355, 10357,
9500, 9536, 9538, 9573,		\@pdfpagetransition .	10372, 10986, 10996, 11008,
9575, 9907, 9909, 11571,		3746, 9769,	11509, 11529, 12210, 12297,
11666, 12070, 12119, 12147,		9773, 9778, 10788, 10790,	12385, 12657
12178		10793, 11213, 11215, 11217,	\@pdfviewarea . . .
\@pdfhighlight	9498	11594, 11596, 11604	9697, 10273,
\@pdfkeywords 4018, 4281, 9749,		\@pdfpicktraybypdfsize . .	10735, 11401, 11761, 12616
10205, 10706, 11449, 11707,		9703,	\@pdfviewclip 9698, 10274, 10736,
12555		9705, 10279, 10281, 10741,	11402, 11762, 12617
\@pdflang 4259, 4288, 9722, 9724,		10743, 11407, 11409, 11767,	\@pdfviewparams . .
10300, 10302, 10774, 10776,		11769, 12622, 12624	4151, 4153,
11790, 11792, 12645, 12647		\@pdfprintarea . . .	11509, 11529, 12211, 12298,
\@pdfm@dest 10317, 10376, 10380		9699, 10275,	12386, 12658
\@pdfm@mark	6896, 10316,	10737, 11403, 11763, 12618	\@percentchar 4876, 4877, 4929,
10368, 10388, 10402, 10404,		\@pdfprintclip	14660
10418, 10420, 10425, 10426,		9700, 10276,	\@processme .
10456, 10480, 10482, 10487,		10738, 11404, 11764, 12619	5987, 5988, 9775,
10505, 10528, 10560, 10594,		\@pdfprintpagerange 3918, 4287,	9781, 9799, 9805, 9821,
10625, 10654, 10688, 10755,		9707, 9709, 10283, 10285,	9827, 11808, 11809, 11920,
10782, 13857, 13858, 13859,		10745, 10747, 11411, 11413,	11921, 11924, 11925
13878, 13922, 13928, 14017,		11771, 11773, 12626, 12628	\@protected@testopt
14031, 14046, 14052, 14077,		\@pdfprintscaling .	703
14084, 14102, 14108, 14130,		9701, 10277,	\@protected@testopt@xargs .
14136, 14159, 14165, 14170,		10739, 11405, 11765, 12620	704
14202, 14210, 14893		\@pdfproducer 3972, 4276, 9601,	\@refstar
\@pdfmoddate 4005, 4279, 9741,		9745, 9747, 10198, 10199,	4828, 8935
		10217, 10219, 10677, 10678,	\@runbordercolor . . .
		10682, 10702, 10704, 11344,	3800, 4271,
		11345, 11349, 11352, 11353,	9577, 9579, 10600, 10602,
		11445, 11447, 11692, 11696,	11179, 11181, 12182
		12205, 12206, 12288, 12290,	\@runcolor . . .
		12292, 12380, 12381, 12548,	3738, 9597, 10616,
		12549, 12567, 12569	11185
		\@pdfremotestartview	\@safe@activesfalse . .
		. . .	655, 4808
		. . .	\@safe@activestrue . . .
		4185, 4187, 4188, 4189,	654, 4807
		4200, 4204, 4206, 4207,	\@savsf
		4209, 4285, 9553, 10575,	9404, 9412
			\@schapter
			14985, 14986
			\@secondoffive 4369, 4803, 4816,
			8898, 8899, 8939
			\@secondoftwo
			636,
			645, 1010, 1183, 1710, 1850,

4368, 4369, 15041		
\@sect	15036, 15037	
\@seqnctr	7431	
\@serial@counter	14752, 14800, 14802, 14803	
\@seteqlabel	8455, 8456	
\@setminipage	7878, 7950	
\@setref	4811, 4816, 8867, 8868, 8905	
\@sharp	7332, 7338	
\@skiphyperreffalse	7000, 8006, 8018	
\@skiphyperreftrue	7992, 8018	
\@spaces	271	
\@spart	15028, 15029	
\@ssect	14971, 14972	
\@startlos	8805, 8812, 8861	
\@starttoc	6502	
\@tempa	7503, 7504, 7507, 7511, 7533, 7540, 7544, 7564, 7571, 7575, 7706, 7710, 7713, 7725	
\@tempb	7459, 7463	
\@tempboxa	10008, 10010, 10019, 10088, 10090, 10093, 10094, 10103, 10109, 10110, 10125, 10127, 10130, 10131, 10141, 10147, 10148, 10165, 10167, 10170, 10171, 10181, 10187, 10188, 12500, 12502, 12511, 12775, 12777, 12791	
\@tempcnta	14609, 14610, 14611, 14612, 14613, 14615, 14618, 14619, 14620, 14626, 14628, 14630, 14721, 14722, 14723, 14726, 14727, 14728, 14729, 14730, 14944, 14945, 14946	
\@tempdima	2668, 6284, 6285, 6286, 6287, 6288, 6289, 6290, 6291, 9394, 13077, 13082, 13084, 13120, 13121, 13122, 13126, 13127, 13128, 13129, 13592, 13597, 13599, 13636, 13637, 13638, 13642, 13643, 13644, 13645, 13940, 13945, 13947, 13984, 13985, 13986, 13990, 13991, 13992, 13993	
\@tempdimb	13081, 13082, 13596, 13597, 13944, 13945	
\@tempswafalse	8211	
\@tempswattrue	8181, 8184, 8187, 8208	
\@temptokena	3519, 3524, 3527, 3529	
\@tfor	7460	
\@the@H@page	8251, 8287, 8289, 8290	
\@thefnmark	7615, 7626, 7717, 7755, 7772, 7779, 7810, 7822, 7829	
\@thirdoffive	4804, 8942	
\@thm	7513, 7514, 7547	
\@topnewpage	15087	
\@topsep	7501, 7529, 7560	
\@topsepadd	7502, 7530, 7561	
\@typeset@protect	14957	
\@undefined	385, 388, 709, 3523, 6441, 6476, 6489, 6501, 6731, 6749, 6794, 7843, 7907, 7912, 7918, 7933, 8930, 9392, 9605, 9614, 10959, 11355, 11369	
\@undottedtocline	8857	
\@unprocessedoptions	4652	
\@urlbordercolor	3801, 4268, 9502, 9504, 10631, 10633, 11111, 11113, 12122	
\@urlcolor	3736, 9521, 10015, 10028, 10135, 10152, 10645, 11117, 12507, 12520, 12786, 12799	
\@urltype	9981, 9986, 10855, 10881, 11016, 11030, 12469, 12474, 12748, 12753	
\@vpageref	8963	
\@whilenum	1354	
\@wrindex	8538, 8539, 8570	
\@writefile	8137	
\@x@sf	7676, 7685, 7835, 7837	
\@xfootnote	7808	
\@xfootnotemark	7623, 7826	
\@xfootnotenext	7612, 7819	
\@xp	8445, 8480, 8481, 8494, 8495, 8497, 8498	
\@xxxii	5155	
\[.	192, 217, 331, 3817, 3835, 5048	
\{	339, 361, 559, 2169, 11500, 14678	
\}	340, 366, 560, 2170, 11500, 14679	
\]	193, 218	
\^	186, 211, 329, 2267, 2268, 3430, 4864, 4865, 4873, 15114, 15126, 15138, 15348, 15364, 15372, 15385, 15399, 15414, 15430, 15440, 15441, 15454, 15468, 15517, 15567, 15594, 15623, 15794, 15810, 15818, 15830, 15846, 15861, 15877, 15887, 15888, 15902, 15916, 15944, 15946, 15990, 15992, 16006,	
	16008, 16045, 16047, 16048, 16128, 16130, 16176, 16178, 16180, 16182, 17838, 17840	
_	187, 212, 567, 4868, 4885, 4886	
\'	166, 172, 179, 182, 3366, 3500, 3503, 3505, 3513, 14677, 15112, 15124, 15136, 15344, 15360, 15368, 15381, 15395, 15410, 15426, 15434, 15435, 15450, 15464, 15513, 15565, 15592, 15621, 15790, 15806, 15814, 15826, 15842, 15857, 15873, 15881, 15882, 15898, 15912, 16313, 16315, 16942, 16971, 17112, 17141, 17806, 17808, 17884, 17886, 20054, 20059, 20064, 20069, 20074, 20079, 20084, 20089, 20094, 20099, 20104, 20109, 20114, 20119, 20124, 20129, 20134, 20139, 20144, 20149, 20154, 20159, 20164, 20169	
\ 	188, 213, 335, 2075, 2168, 2209, 3312, 4311, 8534, 9123, 9133	
\~	566, 1356, 2317, 3424, 3432, 3433, 3434, 4430, 4889, 15115, 15127, 15139, 15350, 15379, 15387, 15416, 15448, 15456, 15519, 15568, 15595, 15624, 15796, 15824, 15832, 15863, 15896, 15904, 16017, 16019, 16020, 16152, 16154, 17798, 17800, 17868, 17870, 17892, 17894, 20056, 20061, 20066, 20071, 20076, 20081, 20086, 20091, 20096, 20101, 20106, 20111, 20116, 20121, 20126, 20131, 20136, 20141, 20146, 20151, 20156, 20161, 20166, 20171	
Numbers		
\3	543, 1400, 1401, 1402, 1403, 1404, 1405, 1406, 1407, 1516, 1517, 1518, 1519, 1520, 1521, 1522, 1523, 2431, 2568, 2576, 2578, 14821, 15344, 15346, 15348, 15350, 15352, 15354, 15356, 15358, 15360, 15362, 15364, 15366, 15368, 15370, 15372, 15374, 15376, 15377, 15379, 15381, 15383, 15385, 15387, 15389, 15391, 15393, 15395, 15397, 15399, 15401, 15403, 15405, 15406, 15408,	

15410, 15412, 15414, 15416,
 15418, 15420, 15422, 15424,
 15426, 15428, 15430, 15432,
 15434, 15435, 15437, 15438,
 15440, 15441, 15443, 15444,
 15446, 15448, 15450, 15452,
 15454, 15456, 15458, 15460,
 15462, 15464, 15466, 15468,
 15470, 15472, 15474, 15475,
 15477, 15562, 15790, 15792,
 15794, 15796, 15798, 15800,
 15802, 15804, 15806, 15808,
 15810, 15812, 15814, 15816,
 15818, 15820, 15822, 15824,
 15826, 15828, 15830, 15832,
 15834, 15836, 15840, 15842,
 15844, 15846, 15848, 15850,
 15852, 15853, 15855, 15857,
 15859, 15861, 15863, 15865,
 15867, 15869, 15871, 15873,
 15875, 15877, 15879, 15881,
 15882, 15884, 15885, 15887,
 15888, 15890, 15891, 15893,
 15896, 15898, 15900, 15902,
 15904, 15906, 15908, 15910,
 15912, 15914, 15916, 15918,
 15920, 15923, 15924, 15926,
 16259, 16263, 16267, 16270,
 16272, 16274, 16276, 16277,
 16279, 16281, 16283, 16285,
 16287, 16289, 16291, 16294,
 16296, 16298, 16300, 16302,
 16304, 16306, 16307, 16309,
 16311, 16313, 16315, 16317,
 16319, 16322, 16325, 16720,
 16723, 16726, 16728, 16731,
 16734, 16737, 16740, 16742,
 16744, 16746, 16748, 16750,
 16752, 16753, 16755, 16757,
 16759, 16761, 16763, 16891,
 16893, 16895, 16897, 16899,
 16901, 16903, 16905, 16907,
 16909, 16911, 16913, 16915,
 16917, 16918, 16920, 16922,
 16924, 16926, 16928, 16931,
 16933, 16935, 16937, 16940,
 17343, 17345, 17347, 17349,
 17351, 17353, 17355, 17357,
 17359, 17361, 17363, 17365,
 17367, 17369, 17371, 17373,
 17375, 17377, 17379, 17381,
 17383, 17385, 17387, 17390,
 17393, 17395, 17397, 17399,
 17401, 17403, 17405, 17407,
 17409, 17411, 17413, 17415,
 17417, 17419, 17421, 17424,
 17427, 17429, 17431, 17433,

17435, 17437, 17439, 17441,
 17443, 17445, 17447, 17449,
 17451, 17453, 17455, 17457,
 17459, 17461, 17463, 17465,
 17467, 17469, 17471, 17473,
 17475, 17477, 17479, 17481,
 17483, 17485, 17487, 17489,
 17491, 17493, 17495, 17497,
 17499, 17501, 17503, 17505,
 17507, 17509, 17511, 17513,
 17516, 17518, 17520, 17522,
 17872, 17874, 17876, 17878,
 17880, 17882, 17884, 17886,
 17888, 17890, 17892, 17894,
 18250, 18253, 18256, 18259,
 18262, 18265, 18268, 18270,
 18272, 18274, 18276, 18279,
 18282, 18285, 18287, 18290,
 18293, 18295, 18298, 18301,
 18304, 18307, 18309, 18311,
 18313, 18315, 18317, 18319,
 18321, 18323, 18326, 18329,
 18331, 18334, 18336, 18339,
 18341, 18343, 18345, 18392,
 18430, 18435, 18808, 18810,
 18812, 18815, 18818, 18820,
 18822, 18824, 18826, 18828,
 18831, 18834, 18836, 18838,
 18840, 18842, 18845, 18848,
 18850, 18852, 18854, 18856,
 18859, 18862, 18864, 18866,
 18868, 18870, 18872, 18874,
 18876, 18878, 18880, 18883,
 18886, 18888, 18890, 18892,
 18894, 18897, 18901, 18904,
 18907, 18909, 18911, 18913,
 18915, 18984, 18987, 19063,
 19065, 19067, 19069, 19071,
 19073, 19075, 19077, 19079,
 19081, 19083, 19085, 19087,
 19089, 19091, 19093, 19095,
 19097, 19099, 19101, 19103,
 19105, 19107, 19109, 19111,
 19113, 19115, 19117, 19119,
 19121, 19123, 19125, 19127,
 19129, 19131, 19133, 19135,
 19137, 19139, 19141, 19143,
 19145, 19147, 19149, 19151,
 19180, 19183, 19185, 19187,
 19190, 19192, 19194, 19196,
 19199, 19201, 19419, 19421,
 19423, 19425, 19427, 19598,
 19600, 19602, 19604, 19606,
 19608, 19611, 19615, 19617,
 19619, 19621, 19623, 19625,
 19627, 19629, 19631, 19633,
 19635, 19739, 19742, 19745,

19747, 19749, 19751, 19753,
 19755, 19757, 19759, 19886,
 19888, 19890, 19892, 19894,
 19897, 19900, 19903, 19907,
 19910, 19913, 19915, 19917,
 19919, 19921, 19924, 19926,
 20001, 20013, 20015, 20017,
 20019, 20021, 20041, 20042,
 20043, 20047, 20048, 20049,
 20052, 20054, 20056, 20067,
 20069, 20073, 20074, 20075,
 20076, 20077, 20078, 20079,
 20080, 20082, 20083, 20084,
 20085, 20086, 20087, 20088,
 20089, 20090, 20091, 20092,
 20093, 20094, 20095, 20096,
 20097, 20098, 20099, 20100,
 20102, 20103, 20104, 20105,
 20106, 20107, 20108, 20109,
 20110, 20111, 20112, 20114,
 20116, 20127, 20129, 20133,
 20134, 20135, 20136, 20137,
 20138, 20139, 20140, 20142,
 20143, 20144, 20145, 20146,
 20147, 20148, 20149, 20150,
 20151, 20152, 20153, 20154,
 20155, 20156, 20157, 20158,
 20159, 20160, 20162, 20163,
 20164, 20165, 20166, 20167,
 20168, 20169, 20170, 20171,
 20275

\9 . 546, 1420, 1423, 1454, 2359,
 2374, 2383, 2411, 2431,
 2468, 2472, 2486, 2490,
 2498, 2503, 2506, 2540,
 2544, 2547, 2550, 2560,
 2562, 2564, 2566, 2568,
 2570, 2572, 2574, 2576,
 2578, 15562, 17524, 17526,
 17528, 17530, 17532, 17534,
 17537, 17540, 17543, 17546,
 17548, 17550, 17552, 17554,
 17556, 17558, 17560, 17562,
 17564, 17567, 17569, 17572,
 17574, 17577, 17579, 17583,
 17587, 17590, 17592, 17594,
 17596, 17598, 17600, 17602,
 17604, 17606, 17608, 17610,
 17612, 17614, 17616, 17618,
 17620, 17622, 17624, 17627,
 17630, 17633, 17636, 17638,
 17640, 17642, 17644, 17646,
 17648, 17650, 17652, 17654,
 17656, 17658, 17660, 17662,
 17664, 17666, 17668, 17670,
 17672, 17674, 17676, 17678,
 17680, 17682, 17684, 17686,

17688, 17690, 17692, 17694,
17696, 17698, 17700, 17702,
17704, 17706, 17708, 17710,
17712, 17714, 17716, 17718,
17720, 17722, 17724, 17726,
17728, 17731, 17734, 17737,
17740, 17742, 17744, 17746,
17748, 17750, 17752, 17754,
17756, 17758, 17760, 17762,
17764, 17766, 17768, 17770,
17772, 17774, 17776, 17778,
17780, 17782, 17784, 17786,
17788, 17790, 17792, 17794,
17796, 17798, 17800, 17802,
17804, 17806, 17808, 17810,
17812, 17814, 17816, 17818,
17820, 17822, 17824, 17826,
17828, 17830, 17832, 17834,
17836, 17838, 17840, 17842,
17844, 17846, 17848, 17850,
17852, 17854, 17856, 17858,
17860, 17862, 17864, 17866,
17868, 17870, 17872, 17874,
17876, 17878, 17880, 17882,
17884, 17886, 17888, 17890,
17892, 17894, 17896, 17898,
17900, 17902, 17905, 17907,
17909, 17911, 17913, 17915,
17917, 17920, 17924, 17926,
17928, 17931, 17933, 17935,
17937, 17939, 17941, 17943,
17945, 17947, 17949, 17951,
17953, 17955, 17957, 17959,
17961, 17963, 17965, 17967,
17969, 17971, 17973, 17975,
17977, 17979, 17981, 17983,
17985, 17987, 17989, 17991,
17993, 17995, 17997, 17999,
18001, 18003, 18005, 18007,
18009, 18011, 18013, 18015,
18017, 18019, 18021, 18023,
18025, 18027, 18029, 18031,
18033, 18035, 18037, 18039,
18041, 18043, 18045, 18047,
18049, 18051, 18053, 18055,
18057, 18059, 18061, 18072,
18075, 18077, 18079, 18081,
18083, 18085, 18087, 18089,
18092, 18094, 18096, 18098,
18100, 18102, 18104, 18107,
18109, 18111, 18115, 18117,
18119, 18121, 18123, 18125,
18127, 18129, 18133, 18135,
18137, 18139, 18141, 18143,
18145, 18147, 18149, 18151,
18153, 18155, 18157, 18159,
18161, 18163, 18165, 18167,

18169, 18171, 18175, 18179,
18181, 18183, 18185, 18188,
18191, 18193, 18195, 18197,
18199, 18201, 18204, 18206,
18208, 18210, 18212, 18214,
18216, 18218, 18220, 18222,
18224, 18226, 18230, 18233,
18235, 18238, 18241, 18244,
18247, 18250, 18253, 18256,
18259, 18262, 18265, 18268,
18270, 18272, 18274, 18276,
18279, 18282, 18285, 18287,
18290, 18293, 18295, 18298,
18301, 18304, 18307, 18309,
18311, 18313, 18315, 18317,
18319, 18321, 18323, 18326,
18329, 18331, 18334, 18336,
18339, 18341, 18343, 18345,
18347, 18349, 18351, 18353,
18355, 18357, 18360, 18362,
18364, 18366, 18368, 18370,
18373, 18376, 18378, 18380,
18382, 18384, 18386, 18388,
18390, 18392, 18394, 18396,
18398, 18400, 18402, 18404,
18407, 18409, 18411, 18413,
18418, 18420, 18423, 18425,
18428, 18430, 18433, 18435,
18438, 18440, 18442, 18445,
18447, 18449, 18452, 18455,
18457, 18459, 18462, 18465,
18467, 18469, 18472, 18474,
18477, 18479, 18481, 18484,
18486, 18488, 18490, 18492,
18494, 18497, 18499, 18501,
18504, 18506, 18508, 18511,
18513, 18515, 18517, 18519,
18522, 18524, 18526, 18528,
18530, 18532, 18535, 18538,
18541, 18543, 18546, 18548,
18550, 18552, 18554, 18556,
18558, 18560, 18562, 18566,
18568, 18570, 18571, 18574,
18577, 18581, 18582, 18586,
18587, 18590, 18592, 18594,
18596, 18598, 18600, 18602,
18604, 18606, 18608, 18610,
18612, 18614, 18617, 18619,
18621, 18624, 18627, 18629,
18631, 18633, 18635, 18637,
18639, 18641, 18643, 18645,
18647, 18649, 18651, 18653,
18655, 18657, 18659, 18661,
18663, 18665, 18667, 18669,
18671, 18673, 18675, 18677,
18679, 18681, 18683, 18685,
18687, 18689, 18691, 18693,

18695, 18697, 18699, 18701,
18703, 18706, 18709, 18712,
18715, 18718, 18722, 18726,
18728, 18730, 18732, 18734,
18736, 18739, 18742, 18745,
18748, 18750, 18753, 18756,
18760, 18763, 18765, 18768,
18771, 18774, 18778, 18781,
18784, 18787, 18790, 18794,
18798, 18800, 18802, 18804,
18806, 18808, 18810, 18812,
18815, 18818, 18820, 18822,
18824, 18826, 18828, 18831,
18834, 18836, 18838, 18840,
18842, 18845, 18848, 18850,
18852, 18854, 18856, 18859,
18862, 18864, 18866, 18868,
18870, 18872, 18874, 18876,
18878, 18880, 18883, 18886,
18888, 18890, 18892, 18894,
18897, 18901, 18904, 18907,
18909, 18911, 18913, 18915,
18917, 18919, 18921, 18923,
18925, 18929, 18931, 18933,
18935, 18937, 18939, 18941,
18943, 18945, 18947, 18949,
18951, 18954, 18957, 18959,
18962, 18965, 18967, 18970,
18973, 18975, 18977, 18979,
18981, 18984, 18987, 18989,
18991, 18993, 18996, 18998,
19000, 19002, 19004, 19006,
19008, 19010, 19012, 19014,
19016, 19018, 19020, 19022,
19024, 19026, 19028, 19030,
19032, 19034, 19036, 19038,
19041, 19043, 19045, 19047,
19049, 19051, 19053, 19055,
19057, 19059, 19061, 19063,
19065, 19067, 19069, 19071,
19073, 19075, 19077, 19079,
19081, 19083, 19085, 19087,
19089, 19091, 19093, 19095,
19097, 19099, 19101, 19103,
19105, 19107, 19109, 19111,
19113, 19115, 19117, 19119,
19121, 19123, 19125, 19127,
19129, 19131, 19133, 19135,
19137, 19139, 19141, 19143,
19145, 19147, 19149, 19151,
19153, 19158, 19162, 19166,
19169, 19171, 19173, 19177,
19180, 19183, 19185, 19187,
19190, 19192, 19194, 19196,
19199, 19201, 19205, 19207,
19209, 19211, 19214, 19217,
19220, 19224, 19226, 19228,

19230, 19233, 19238, 19241,
 19243, 19245, 19250, 19253,
 19256, 19258, 19261, 19263,
 19265, 19268, 19275, 19278,
 19283, 19286, 19289, 19292,
 19295, 19298, 19301, 19304,
 19307, 19310, 19313, 19316,
 19319, 19322, 19325, 19328,
 19331, 19334, 19337, 19341,
 19344, 19347, 19349, 19351,
 19353, 19355, 19357, 19360,
 19362, 19364, 19366, 19368,
 19370, 19373, 19375, 19378,
 19380, 19383, 19385, 19387,
 19389, 19391, 19393, 19395,
 19397, 19399, 19401, 19403,
 19405, 19407, 19409, 19411,
 19414, 19416, 19419, 19421,
 19423, 19425, 19427, 19429,
 19433, 19437, 19439, 19441,
 19443, 19445, 19447, 19450,
 19452, 19455, 19457, 19459,
 19461, 19463, 19465, 19468,
 19470, 19472, 19474, 19476,
 19478, 19480, 19482, 19484,
 19486, 19488, 19490, 19492,
 19495, 19497, 19499, 19501,
 19503, 19505, 19507, 19509,
 19511, 19513, 19515, 19517,
 19519, 19521, 19523, 19525,
 19527, 19529, 19531, 19533,
 19535, 19537, 19539, 19542,
 19544, 19546, 19548, 19550,
 19552, 19554, 19556, 19558,
 19560, 19562, 19564, 19566,
 19568, 19571, 19574, 19576,
 19579, 19582, 19585, 19588,
 19590, 19592, 19594, 19596,
 19598, 19600, 19602, 19604,
 19606, 19608, 19611, 19615,
 19617, 19619, 19621, 19623,
 19625, 19627, 19629, 19631,
 19633, 19635, 19637, 19639,
 19641, 19643, 19645, 19647,
 19649, 19652, 19655, 19658,
 19661, 19663, 19668, 19672,
 19675, 19677, 19679, 19682,
 19685, 19688, 19691, 19694,
 19697, 19700, 19703, 19706,
 19709, 19712, 19715, 19717,
 19719, 19721, 19723, 19725,
 19728, 19734, 19737, 19739,
 19742, 19745, 19747, 19749,
 19751, 19753, 19755, 19757,
 19759, 19761, 19763, 19765,
 19768, 19770, 19772, 19774,
 19777, 19780, 19782, 19784,

19786, 19789, 19791, 19794,
 19796, 19800, 19803, 19805,
 19807, 19809, 19811, 19813,
 19815, 19817, 19819, 19821,
 19823, 19825, 19827, 19830,
 19832, 19834, 19837, 19840,
 19842, 19844, 19846, 19848,
 19850, 19852, 19854, 19856,
 19858, 19860, 19862, 19864,
 19866, 19868, 19870, 19872,
 19874, 19876, 19878, 19880,
 19882, 19884, 19886, 19888,
 19890, 19892, 19894, 19897,
 19900, 19903, 19907, 19910,
 19913, 19915, 19917, 19919,
 19921, 19924, 19926, 19929,
 19931, 19933, 19935, 19937,
 19939, 19941, 19944, 19946,
 19949, 19952, 19955, 19958,
 19960, 19962, 19964, 19966,
 19968, 19970, 19972, 19974,
 19976, 19978, 19981, 19984,
 19986, 19988, 19990, 19992,
 19994, 19996, 19998, 20001,
 20004, 20006, 20008, 20010,
 20013, 20015, 20017, 20019,
 20021, 20053, 20055, 20057,
 20058, 20059, 20060, 20061,
 20062, 20063, 20064, 20065,
 20066, 20068, 20070, 20071,
 20072, 20073, 20074, 20075,
 20076, 20078, 20080, 20083,
 20085, 20087, 20088, 20089,
 20090, 20091, 20092, 20093,
 20094, 20095, 20096, 20098,
 20100, 20102, 20103, 20104,
 20105, 20106, 20108, 20109,
 20110, 20111, 20113, 20115,
 20117, 20118, 20119, 20120,
 20121, 20122, 20123, 20124,
 20125, 20126, 20128, 20130,
 20131, 20132, 20133, 20134,
 20135, 20136, 20138, 20140,
 20143, 20145, 20147, 20148,
 20149, 20150, 20151, 20152,
 20153, 20154, 20155, 20156,
 20158, 20160, 20162, 20163,
 20164, 20165, 20166, 20168,
 20169, 20170, 20171, 20277,
 20279

_ 342, 688, 945,
 965, 3447, 3450, 4181, 8078,
 8101, 15136, 15137, 15138,
 15139, 15140, 15141, 15142,
 15143, 15144, 15145, 15146,
 15147, 15592, 15593, 15594,

15595, 15596, 15597, 15598,
 15599, 15600, 15601, 15602,
 15603, 15604, 15605, 15606,
 15607, 15608, 15609, 15610,
 15611, 15612, 15613, 15614,
 15615, 15616, 15617, 15618

A

\a 300, 302, 306, 312
 \ABREVE . 20046, 20117, 20118,
 20119, 20120, 20121
 \abreve . . . 20040, 20057, 20058,
 20059, 20060, 20061
 \AC 18475, 21332
 \AccFancyVerbLineautorefname .
 3474
 \Accfootnoteautorefname . . 3454
 \Acctheoremautorefname . . 3478
 \Acht 19985, 21132
 \ACIRCUMFLEX 20047, 20122,
 20123, 20124, 20125, 20126
 \acircumflex 3505, 20041, 20062,
 20063, 20064, 20065, 20066
 \AcPa 19971, 21126
 \Acrobatmenu 2639, 4365, 6438,
 9900, 10650, 11190, 12064
 \active . . 1334, 1341, 1946, 4865,
 4866, 4867, 4868, 4869,
 4870, 4873, 4875, 4878,
 4886, 14825, 14855
 \add@accent 558
 \addcontentsline . . . 7872, 7944,
 8320, 8325, 8413, 15092
 \AddLineBeginAux 5444
 \addtocontents 8365, 8414, 8688,
 8740, 15080, 15081
 \addtocounter 7216, 7239, 7248,
 7259, 7263, 7481, 10507
 \addvspace 15080, 15081
 \adl@LT@array 7330
 \advance 482,
 483, 1355, 5014, 5164, 5177,
 5479, 5807, 5853, 6285,
 6286, 6289, 6290, 6641,
 6649, 6686, 8223, 8233,
 8236, 8250, 9650, 10020,
 10104, 10142, 10182, 11351,
 12512, 12792, 13084, 13127,
 13128, 13536, 13599, 13643,
 13644, 13889, 13947, 13991,
 13992, 14610, 14612, 14613,
 14619, 14628, 14729, 14945
 \AE 15356, 15802, 16317
 \ae 15422, 15869, 16319
 \afterassignment . . . 1955, 1961,
 1967, 6062
 \AfterBeginDocument . 372, 386
 \aftergroup 7759

<code>\agemO</code>	18105, 21303	<code>\AsteriskRoundedEnds</code> . .	19567, 20966	<code>\baru</code>	16607, 20334
<code>\ainferior</code>	20434	<code>\asymp</code>	18516, 20607	<code>\barwedge</code>	18805, 20729
<code>\alef</code>	20187	<code>\AtBeginDocument</code> . .	373, 5412, 5416, 6474, 7320, 12821	<code>\baselineskip</code>	2642, 6298, 6299, 6300, 6301, 6302, 6303, 10075, 11525, 11557, 12244
<code>\alefhamza</code>	20179	<code>\AtBeginShipout</code> . . .	6587, 6599, 9939, 10453	<code>\bbl@cite@choice</code>	7985
<code>\aleflowerhamza</code>	20183	<code>\AtBeginShipoutBox</code>	6591, 6594, 9932, 9933, 10454, 10455	<code>\bbslash</code>	18992, 20807
<code>\alefmadda</code>	20177	<code>\AtBeginShipoutFirst</code> . . .	6604, 10823, 12261, 12376	<code>\Beam</code>	18976, 20802
<code>\alefmaqsura</code>	20245	<code>\AtEndDocument</code>	6488	<code>\because</code>	18461, 20583
<code>\aleph</code>	18116, 20456	<code>\AtEndOfPackage</code>	383	<code>\BeforeTeXIVht</code>	3085
<code>\Alph</code>	6735, 7100	<code>\AtVeryEndDocument</code> . . .	6834, 13487	<code>\begin</code>	634, 12842, 21501
<code>\alph</code>	6736, 7452, 7483	<code>\author</code>	6523, 6533	<code>\belowpdfbookmark</code>	14725
<code>\alpha</code>	16860, 20356	<code>\autopageref</code>	4501, 8978	<code>\beta</code>	16862, 20357
<code>\amalg</code>	18379, 20550	<code>\autoref</code>	677, 4500, 8997, 12816	<code>\betainferior</code>	20386
<code>\AMSautorefname</code>	9098	<code>\ayn</code>	20223	<code>\beth</code>	18118, 20457
<code>\anchor@spot</code>	5349, 5362, 5369, 5375, 5377, 9459, 9961, 10056, 10927, 10999, 11506, 11852, 11855, 12449, 12729			<code>\between</code>	18609, 20648
<code>\angle</code>	18408, 20562			<code>\bfseries</code>	608, 8084, 8107, 8871, 8891, 8908, 9026
<code>\AngleSign</code>	18416, 21324			<code>\bgroup</code>	697, 4981, 7746, 7758, 9366, 10471, 10927, 11546, 13290, 13382, 13403
<code>\Anglesign</code>	18415, 21323			<code>\biblecite</code>	7976, 7982, 7986, 8011, 8026, 8042, 8052
<code>\Ankh</code>	19242, 20845			<code>\Bicycle</code>	20005, 21141
<code>\APLbox</code>	18980, 20804			<code>\bigcircle</code>	20830
<code>\APLdown</code>	19178, 21399			<code>\bigdoublevee</code>	19764, 21045
<code>\APLdownarrowbox</code>	18969, 20799			<code>\bigdoublewedge</code>	19762, 21044
<code>\APLinput</code>	18972, 20800			<code>\bigtriangledown</code>	19176, 20820
<code>\APLinv</code>	18946, 20791			<code>\bigtriangleup</code>	19161, 20815
<code>\APLleftarrowbox</code> .	18961, 20796			<code>\binampersand</code>	15652, 21160
<code>\APLrightarrowbox</code>	18964, 20797			<code>\bindnasrepma</code>	18130, 21306
<code>\APLup</code>	19163, 21396			<code>\Biohazard</code>	19240, 20844
<code>\APLuparrowbox</code> . .	18966, 20798			<code>\bitsetGetDec</code>	5531, 5664, 5682, 5696, 5709, 5725, 5757, 5782
<code>\appendix</code>	7092, 7104			<code>\bitsetGetHex</code>	5532
<code>\appendixautorefname</code>	3322, 3340, 3358, 3376, 3394, 3412, 3430, 3462, 3463, 3488, 3506, 9108			<code>\bitsetGetSetBitList</code>	5520
<code>\apprge</code>	18625, 21347			<code>\bitsetIsEmpty</code>	5661, 5679, 5693, 5706, 5722, 5754, 5779
<code>\apprle</code>	18622, 21346			<code>\bitsetReset</code>	5634, 5668, 5687, 5701, 5714, 5730, 5762
<code>\approx</code>	18498, 20599			<code>\bitsetSetValue</code>	5500, 5510
<code>\approxseq</code>	18503, 20601			<code>\blacksmiley</code>	19255, 20849
<code>\Aquarius</code>	19329, 21443			<code>\Bleech</code>	19164, 21397
<code>\aquarius</code>	19327, 20871			<code>\BOOKMARK</code>	14657, 14736
<code>\arabic</code>	6732, 6956, 6959, 6962, 6963, 6964, 6966, 6967, 6968, 6969, 6971, 6972, 6973, 6974, 6975, 6976, 6979, 6989, 6990, 7223, 8422, 8428, 8476, 8490, 8676, 8681, 8683			<code>\booknumberline</code>	14640, 14645
<code>\Aries</code>	19299, 21433			<code>\bot</code>	18749, 20710
<code>\aries</code>	19297, 20861			<code>\Bowtie</code>	18813, 21378
<code>\ast</code>	18395, 20557			<code>\bowtie</code>	18811, 20732
<code>\Asterisk</code>	19543, 20954			<code>\Box</code>	19215, 21403
<code>\AsteriskBold</code>	19520, 20943			<code>\box</code>	6292, 6594, 9380, 10485, 11899, 11902
<code>\AsteriskCenterOpen</code>	19522, 20944			<code>\boxast</code>	19748, 21037
				<code>\boxbackslash</code>	18958, 20795
				<code>\boxbar</code>	19198, 20829
				<code>\boxbox</code>	19752, 21039
				<code>\boxbslash</code>	19746, 21036

\boxcircle	19750, 21038	\capitalgrave	15621	\checklatex	4, 7818, 7931, 8035, 8412, 8904
\boxdot	18733, 20704	\capitalhungarumlaut	15626	\Checkmark	19464, 20916
\boxempty	19213, 20835	\capitalmacron	15630	\checkmark	19466, 21462
\boxminus	18729, 20702	\capitalnewtie	15633	\CheckmarkBold	19467, 20917
\boxplus	18727, 20701	\capitalogonek	15620	\checkpackage	9, 7257, 8475
\boxslash	19744, 21035	\capitalring	15627	\chi	16904, 20377
\boxtimes	18731, 20703	\capitaltie	15632	\chiinferior	20390
\brokenvert	15733, 21166	\capitaltilde	15624	\ChoiceBox	5857
\bullet	8823, 8831, 8841, 8849, 18399, 20396	\Capricorn	19326, 21442	\ChoiceMenu	6246
\Bumpeq	18521, 20609	\capricornus	19324, 20870	\circ	18397, 20558
\bumpeq	18525, 20611	\caption	7842, 7844, 7932, 7934	\circeq	18557, 20625
C					
\C	15537, 17193, 17196	\catcode	172, 173, 184, 185, 186, 187, 206, 836, 837, 931, 932, 933, 934, 935, 936, 937, 938, 939, 940, 941, 942, 943, 944, 945, 946, 947, 948, 949, 952, 953, 954, 955, 956, 957, 958, 959, 960, 961, 962, 963, 964, 965, 966, 967, 968, 969, 1034, 1334, 1341, 1946, 2075, 2076, 2209, 2210, 2266, 2267, 2268, 4724, 4726, 4864, 4865, 4866, 4867, 4868, 4869, 4870, 4873, 4875, 4878, 4886, 4896, 4987, 4988, 9123, 11587, 11588, 14754, 14756, 14825, 14828, 14855, 14858	\circlearrowleft	19614, 20985
\c	911, 915, 921, 3424, 3432, 3433, 3434, 6546, 6553, 15120, 15132, 15144, 15358, 15424, 15547, 15573, 15600, 15619, 15804, 15871, 16002, 16004, 16050, 16052, 16060, 16062, 16080, 16082, 16116, 16118, 16132, 16134, 16140, 16142, 16381, 16383, 17253, 17256, 17618, 17620, 17666, 17668	\ccnc	20014, 21144	\circlearrowright	19616, 20986
\c@footnote	7625, 7708, 7716, 7828	\ccnd	20016	\CircledA	19037, 20808
\c@Hy@tempcnt	4999, 5000, 5006, 5014	\ccsa	20018, 21145	\circledast	18721, 20699
\c@note	8226	\cdot	21152	\circledbslash	19729, 21471
\c@overlay	8226	\cdots	18908, 20773	\circledcirc	18717, 20698
\c@page	6641, 6649, 6666, 6686, 6687, 6691, 6703, 6705, 6710, 6717, 6719, 6721, 6750, 8223, 8227, 8229, 8233, 8236, 8237, 8250, 8280	\CESign	20022, 21147	\circleddash	18725, 20700
\c@secnumdepth	15005, 15023, 15038	\CEsign	20024, 21496	\CircleShadow	19575, 20969
\c@slide	8226	\cf@encoding	1659	\circplus	19771, 21048
\c@slidesection	8689, 8817, 8818	\chapterautorefname	3323, 3341, 3359, 3377, 3395, 3413, 3431, 3460, 3489, 3507, 9109	\citation	8081, 8104, 8130
\c@slidesubsection	8741	\chapternumberline	14642, 14647	\citeauthoryear	8196, 8202
\c@tocdepth	3664, 3669	\char	13517, 14758, 14795	\citeN	8193
\calc@bm@number	14867, 14943	\chardef	276, 319, 2874, 2875, 2876, 2877, 3124, 3126, 4647, 4679, 11847, 11850, 11856	\CJK@char	1337
\calculate@pdfview	4145, 4148	\check@bm@number	14878, 14886, 14936, 14944	\CJK@charx	1338
\Cancer	19308, 21436	\CheckBox	6249	\CJK@CJK	1326
\cancer	19306, 20864	\CheckCommand	7705	\CJK@eight	1537, 1540, 1654
\Cap	18841, 20745	\checkcommand	42, 7258, 7819, 7826, 7833, 7932, 7942, 8036, 8048, 8413, 8416, 8476, 8905	\CJK@five	1537, 1539, 1654
\cap	18437, 20573	\CheckedBox	19218, 21404	\CJK@four	1536, 1539, 1653
\capdot	19788, 21055	\Checkedbox	19216, 20836	\CJK@hundred	1603
\capitalacute	15622			\CJK@hundredmillion	1566
\capitalbreve	15629			\CJK@ignorespaces	1336
\capitalcaron	15628			\CJK@kern	1324
\capitalcedilla	15619			\CJK@minus	1528
\capitalcircumflex	15623			\CJK@nine	1537, 1541, 1654
\capitaldieresis	15625			\CJK@null	1630
\capitaldotaccent	15631			\CJK@one	1536, 1538, 1653
				\CJK@punctchar	1339
				\CJK@punctcharx	1340
				\CJK@seven	1537, 1540, 1654
				\CJK@six	1537, 1540, 1654
				\CJK@ten	1538, 1539, 1540, 1541, 1618
				\CJK@tenthousand	1551, 1572
				\CJK@thousand	1588
				\CJK@three	1536, 1539, 1653
				\CJK@two	1536, 1538, 1653
				\CJK@zero	1536, 1554, 1571, 1575, 1591, 1606, 1628
				\CJKdigits	1413
				\CJKkern	1325
				\CJKnumber	1412
				\cl@@ckpt	7050
				\CleaningA	19039, 21391
				\CleaningF	19050, 20809
				\CleaningFF	19052, 20810

\CleaningP	19074, 20811	\Cube	631	\cyrch	3450, 3451, 3459, 17092, 17447
\CleaningPP	19076, 20812	\Cup	18844, 20746	\CYRCHLDSC	17361
\clickb	16664, 21270	\cup	18439, 20574	\cyrchldsc	17363
\clickc	16659, 21268	\cupdot	18678, 20681	\CYRCHRDSC	17319
\clickt	16601, 21252	\cupplus	18680, 20682	\cyrchrdsc	17321
\clock	18924, 20781	\curlyc	16431, 21209	\CYRCHVCRS	17324
\ClockLogo	18927, 21388	\curlyeqprec	18863, 20754	\cyrchvcrs	17327
\Clocklogo	18926, 21387	\curlyeqsucc	18867, 20756	\CYRD	16986
\close@pdfink	9453, 9478, 9487, 9522, 9562, 9598, 9927	\curlyesh	16598, 21251	\cyrd	3447, 3450, 3461, 3466, 3467, 17053
\closedniomega	16550, 21240	\curlyvesh	18827, 20739	\CYRDJE	16947
\closedreveysion	16463, 21216	\curlywedge	18830, 20740	\cyrdje	17117
\closeout	6468, 14745	\curlyyogh	16643, 21264	\CYRDZE	16953
\Cloud	19204, 20831	\curlyz	16636, 21263	\cyrdze	17123
\ClowerTips	20933	\CurrentBorderColor		\CYRDZHE	16976
\clubpenalty	7602, 7604	9443, 9445, 9472, 9474, 9482, 9484, 9489, 10989, 11023, 11025, 11041, 11043, 11062, 11064, 11126, 11128, 11145, 11147	\cyrdzhe	17146
\clubsuit	19343, 19345, 21449	\currentpdfbookmark	14717	\CYRE	16942, 16945, 16988, 17381
\codeof	8160	\curu	17144	\cyre	3444, 3450, 3451, 3464, 3476, 3477, 3478, 17055, 17112, 17115, 17383
\Coffeecup	19223, 20838	\curvearrowleft	18232, 20490	\cyreref	17431
\coloncolonequals	19808, 21063	\curvearrowright	18234, 20491	\CYREREV	17039, 17429
\colonequals	18549, 20621	\CutLeft	19430, 21456	\cyrerev	17106
\color@begingroup	9366, 10471	\CutLine	19155, 21393	\CYRERY	17034, 17453
\color@endgroup	9373, 10478	\Cutline	19156, 21394	\cyrery	3442, 3444, 17101, 17455
\columnwidth	7753	\Cutright	19431, 21457	\CYRF	17019
\comma@entry	5848, 5855, 5857	\CuttingLine	19152, 20813	\cyrf	17086
\comma@parse	5847	\cyr	656, 3442, 3444, 3447, 3450, 3453, 3454, 3455, 3456, 3457, 3458, 3459, 3460, 3461, 3462, 3464, 3466, 3467, 3468, 3469, 3470, 3471, 3472, 3473, 3474, 3475, 3476, 3477, 3478, 3479	\CYRFITA	17184
\complement	18348, 20536	\CYRA	16978, 17369, 17373	\cyrfit	17186
\Conclusion	18299, 21315	\cyra	3444, 3451, 3453, 3458, 3461, 3466, 3467, 3473, 3477, 17045, 17371, 17375	\CYRG	16949, 16984
\cong	18493, 20597	\CYRABHCH	17333, 17338	\cyr	3460, 17051, 17119
\Congruent	18575, 21341	\cyrabhch	17335, 17341	\CYRGDSC	17449
\contentsline	6477, 6478, 6490, 8366, 8370, 8414, 8416	\CYRABHCHDSC	17337	\cyr	17451
\copy	5173, 5175, 5186, 5194, 9376, 9933, 10455, 10481	\cyrabhchdsc	17340	\CYRGHCRC	17236
\copyright	20300	\CYRABHDZE	17403	\cyrghcrs	17238
\Corresponds	18564, 21339	\cyrabhdze	17405	\CYRGHK	17241
\corresponds	18563, 21338	\CYRABHHA	17288	\cyrghk	17244
\count@	875, 877, 878, 881, 884, 887, 890, 1353, 1354, 1355, 1356, 1956, 3680, 3681, 3686, 3687, 5478, 5479, 5494, 5790, 5805, 5807, 5831, 5853, 5869, 9645, 9646, 9647, 9648, 9649, 9650, 9653, 11347, 11348, 11349, 11350, 11351, 11354	\cyrabhha	17290	\CYRGUP	17232
\Cross	19483, 20925	\CYRAE	17377	\cyr	17234
\crossb	16201, 21183	\cyrae	17379	\CYRH	17021
\CrossClowerTips	19500	\CYRB	16980	\cyrh	17088
\crossd	15965, 21175	\cyrb	3458, 17047	\CYRHDSC	17310
\CrossedBox	19222, 21406	\CYRBYUS	17168	\cyrhdsc	17312
\Crossedbox	19219, 20837	\cyrbyus	17170	\CYRHHK	17457
\crossh	16014, 21179	\CYRC	17023	\cyrh	17459
\CrossMaltese	19489, 20928	\cyr	17090	\CYRHRDSN	17032
\crossnilambda	16232, 21189	\CYRCH	17025, 17445	\cyrhrdsn	17098, 17099, 21277
\CrossOpenShadow	19485, 20926			\CYRI	16971, 16994, 16997, 17407, 17411
\CrossOutline	19487, 20927			\cyri	3444, 3447, 3451, 3457, 3462, 3464, 17061, 17064, 17141, 17409, 17413
				\CYRIE	16951
				\cyrie	17121
				\CYRII	16956, 16959

\cyrii	17126, 17129	\CYRNJE	16965	\cyrtdsc	17300
\CYRIOTBYUS	17172	\cyrnje	17135	\CYRTETSE	17314
\cyrriotbyus	17174	\CYRO	17007, 17415	\cyrttetse	17316
\CYRIOTE	17156	\cyro	3447, 3450, 3453, 3454, 3464, 3473, 3474, 3476, 3477, 3478, 17074, 17417	\cyrthousands	17218
\cyrriote	17158	\CYROMEGA	17148	\CYRTSHE	16967
\CYRIOTLYUS	17164	\cyromega	17150	\cyrtshe	17137
\cyrriotlyus	17166	\CYROMEGARND	17202	\CYRU	16974, 17017, 17433, 17437, 17441
\CYRISHRT	16996	\cyromegarnd	17204	\cyr	3454, 3456, 3470, 3471, 3474, 3478, 17084, 17435, 17439, 17443
\cyrishrt	17063	\CYROMEGATITLO	17206	\CYRUK	17198
\CYRISHRTDSC	17220	\cyromegatitlo	17208	\cyruk	17200
\cyrishrtdsc	17222	\CYROT	17210	\CYRUSHRT	16973
\CYRIZH	17188, 17193	\cyrot	17212	\cyrushrt	17143
\cyrizh	17190, 17196	\CYROTLD	17419, 17424	\CYRV	16982
\CYRJE	16961	\cyrotld	17421, 17427	\cyrv	3442, 3444, 17049
\cyrje	17131	\CYRP	17009	\CYRY	17302
\CYRK	16969, 16999	\cyrp	3447, 3450, 3451, 3455, 3456, 3462, 3464, 3468, 3469, 3470, 3471, 17076	\cyr	17304
\cyrk	3453, 3454, 3456, 3470, 3471, 3473, 3474, 3475, 17066, 17139	\CYRpalochka	17343	\CYRYA	17043
\CYRKBEAK	17272	\CYRPHK	17284	\cyr	17110
\cyrkbeak	17274	\cyrphk	17286	\CYRYAT	17152
\CYRKDSC	17258	\CYRPSI	17180	\cyr	17154
\cyrkdsc	17260	\cyrpsi	17182	\CYRYHCRS	17306
\CYRKHCRS	17268	\CYRR	17011	\cyr	17308
\cyrkhcrs	17270	\cyr	3442, 3444, 3447, 3450, 3451, 3457, 3461, 3462, 3464, 3466, 3467, 3472, 3473, 3474, 3475, 3476, 3477, 3478, 17078	\CYRYI	16958
\CYRKHK	17349	\CYRRICK	17228	\cyr	17128
\cyrkhk	17351	\cyr	17230	\CYRYO	16944
\CYRKOPPA	17214	\CYRS	17013, 17293	\cyr	17114
\cyrkoppa	17216	\cyr	3447, 3450, 3453, 3454, 3457, 3472, 3473, 3474, 3475, 3479, 17080, 17296	\CYRYU	17041
\CYRKSI	17176	\CYRSCHWA	17385, 17390	\cyr	17108
\cyrksi	17178	\cyr	17387, 17393	\CYRZ	16992, 17253, 17399
\CYRKVCRS	17263	\CYRSDSC	17292, 17293	\cyr	3461, 3466, 3467, 17059, 17256, 17401
\cyrkvcrs	17266	\cyr	17295	\CYRZDSC	17252
\CYRL	17001	\CYRSEMISFTSN	17224	\cyr	17255
\cyr	3458, 3460, 3462, 3464, 17068	\cyrsemisftsn	17226	\CYRZH	16990, 17345, 17395
\CYRLDSC	17353	\CYRSFTSN	17037	\cyr	3444, 3464, 17057, 17347, 17397
\cyrldsc	17355	\cyr	17103, 17104, 21278	\CYRZHDSC	17247
\CYRLJE	16963	\CYRSH	17027	\cyr	17250
\cyr	17133	\cyrsh	17094		
\CYRLYUS	17160	\CYRSHCH	17029		
\cyrlyus	17162	\cyrshch	17096		
\CYRM	17003	\CYRSHHA	17329		
\cyr	3447, 3451, 3477, 3478, 17070	\cyrshha	17331		
\CYRMDSC	17365	\CYRT	17015		
\cyrmdsc	17367	\cyr	3447, 3450, 3456, 3458, 3470, 3471, 3472, 3473, 3474, 3475, 3476, 3477, 3478, 17082		
\CYRN	17005	\CYRTDSC	17298		
\cyr	3444, 3450, 3451, 3453, 3454, 3456, 3464, 3470, 3471, 17072				
\CYRNDSC	17276				
\cyrndsc	17278				
\CYRNG	17280				
\cyrng	17282				
\CYRNHK	17357				
\cyrnhk	17359				

D

\d	912, 916, 922, 3502, 3506, 3508, 3509, 3510, 3511, 3512, 3514, 15123, 15135, 15147, 15541, 15586, 15613, 17598, 17600, 17610, 17612, 17658, 17660, 17682, 17684, 17690, 17692, 17710, 17712, 17718, 17720, 17754, 17756, 17766, 17768, 17774, 17776, 17802, 17804, 17822, 17824, 17842, 17844, 17860, 17862, 17864, 17866, 17872, 17874, 17876, 17878, 17880, 17882, 17888, 17890, 20053, 20058, 20063,
----	--

20068, 20073, 20078, 20083, 20088, 20093, 20098, 20103, 20108, 20113, 20118, 20123, 20128, 20133, 20138, 20143, 20148, 20153, 20158, 20163, 20168	3116, 3129, 3139, 3144, 3149, 3155, 3184, 3201, 3208, 3213, 3218, 3223, 3583, 3591, 3599, 3609	3803, 3810, 3827, 3917, 3926, 3956, 3962, 3968, 3990, 3996, 4002, 4008, 4014, 4020, 4053, 4060, 4094, 4145, 4146, 4166, 4173, 4183, 4213, 4214, 4217, 4220, 4223, 4226, 4229, 4232, 4235, 4258, 4261, 4264, 4995, 5024, 5030, 5042, 5472, 5560, 5616, 5918, 5923, 5936, 5964, 6006, 6009, 6012, 6016, 6019, 6023, 6026, 6030, 6034, 6038, 6041, 6045, 6048, 6051, 6054, 6057, 6094, 6110, 6113, 6116, 6119, 6122, 6125, 6155, 6158, 6161, 6164, 6183, 6189, 6204, 6210, 6227, 6232, 6238, 6847, 6858, 11426, 11432, 11931, 11933, 11936, 11938, 11940, 11949, 11957, 11964, 11966, 11968, 11970, 11972, 11974, 11983, 11993, 11995, 11997, 11998, 12004, 12013, 12015, 12017, 12019, 12021, 12023, 12025, 12027, 12029, 12031, 12033, 12035, 12037, 12039, 12041, 12043, 12044, 12045, 12046, 12047, 12048, 12049, 12050, 12051, 12052, 12053, 12054
\dad 20217	\DefaultHeightofCheckBox 6298, 13234, 13774, 14145	\Deleatur 18071, 20447
\dag 17918, 21289	\DefaultHeightofChoiceMenu ... 6300, 13074, 13589, 13937	\Delta 16801, 20346
\dagger 20395	\DefaultHeightofReset ... 6296, 13208, 13746, 14113	\delta 16866, 20359
\dal 20203	\DefaultHeightofSubmit . 6294, 13191, 13723, 14090	\Denarius 18073, 21302
\daleth 18122, 20459	\DefaultHeightofText 6302, 13050, 13563, 13904	\dest@name 5392
\damma 20257	\DefaultHeightofTextMultiline .. 6303, 13048, 13561, 13902	\df@tag 8437, 8443
\danger 19394, 20890	\DefaultOptionsofCheckBox 6308, 13236, 13776, 14147	\DH 15376, 15822
\dasheddownarrow 18333, 20529	\DefaultOptionsofComboBox 6311	\dh . 15446, 15893, 15894, 21174
\dashedleftarrow . 18327, 21316	\DefaultOptionsofListBox . 6310	\dhal 20205
\dashedrightarrow . 18332, 21317	\DefaultOptionsofPopdownBox 6312	\DiamandSolid 20974
\dasheduparrow ... 18328, 20527	\DefaultOptionsofPushButton .. 6307, 13166, 13695, 14058	\diameter 18916, 20777
\dashleftarrow ... 18325, 20526	\DefaultOptionsofRadio ... 6313	\Diamond 19188, 21400
\dashrightarrow ... 18330, 20528	\DefaultOptionsofReset .. 6306, 13211, 13749, 14116	\diamond 19186, 20824
\DashV 19906, 21108	\DefaultOptionsofSubmit 6305, 13194, 13726, 14093	\diamonddots 17962, 20404
\Dashv 19899, 21106	\DefaultOptionsofText .. 6309, 13055, 13568, 13909	\diamondsuit 19340, 19342, 21448
\dashV 21104	\DefaultWidthofCheckBox 6299, 13233, 13773, 14144	\digamma 16929, 21276
\dashv 18738, 20706	\DefaultWidthofChoiceMenu ... 6301, 13073, 13588, 13936	\dimen@ 521, 522, 526, 1962, 2039, 2040, 2043, 2045, 4297, 4298, 4300, 4307, 4308, 5163, 5164, 5167, 5176, 5177, 5181, 6063, 6072, 6075, 6088, 11314, 11315, 11317, 11889, 11904, 11907
\DavidStar 19491, 20929	\DefaultWidthofReset ... 6297, 13207, 13745, 14112	
\davidstar 19493, 21463	\DefaultWidthofSubmit .. 6295, 13190, 13722, 14089	
\ddag 17922, 21291	\DefaultWidthofText 6304, 13045, 13558, 13899	
\ddagger .. 15220, 17919, 17921, 21290	\define@key .. 2773, 2775, 2818, 2833, 2836, 2839, 2847, 2850, 2860, 2863, 2866, 2883, 2895, 2897, 2900, 2903, 2920, 2924, 2927, 2930, 2933, 2936, 2939, 2942, 2945, 2970, 3026, 3032, 3121, 3229, 3241, 3251, 3254, 3261, 3290, 3309, 3312, 3549, 3606, 3618, 3633, 3658, 3661, 3665, 3693, 3698, 3702, 3705, 3712, 3724, 3731, 3741, 3744, 3747, 3751, 3766, 3775, 3785, 3792,	
\ddots 18912, 20775		
\declare@shorthand 1088, 1089, 1094, 1095, 1100, 1110, 1111, 1112, 1117, 1118, 1123, 1124, 1129, 1134, 1135, 1140, 1145, 1146, 1147, 1148, 1149, 1150, 1155, 1156, 1161, 1162, 1167, 1168		
\DeclareFontEncoding ... 15111, 15511		
\DeclareFontFamily ... 982, 992		
\DeclareFontShape ... 983, 993		
\DeclareFontSubstitution .. 984, 994		
\DeclareLocalOptions 4325		
\DeclareRobustCommand 4827, 4830, 4839, 4843, 4978, 5065, 5067, 5069, 5078, 6243, 6246, 6249, 6252, 6255, 6258, 6261, 6386, 6390, 6456, 6460, 8952, 8978, 8997, 14961		
\DeclareTextAccent 15112, 15113, 15114, 15115, 15116, 15117, 15118, 15119, 15120, 15121, 15122, 15123		
\DeclareVoidOption 3082, 3096, 3106, 3111,		

<code>\dimexpr</code> . 533, 2335, 2337, 2345, 2350, 2353, 2355, 2369, 2371, 2374, 2375, 2382, 2385, 2388, 2389, 2390, 2391, 2401, 2406, 2414, 2418, 2423, 2433, 2436, 2441, 2444, 2449, 2450, 6088	<code>\Downarrow</code> 18300, 20515	<code>\EightStarConvex</code> . 19526, 20946
<code>\ding</code> 630, 6130, 6133	<code>\downarrow</code> 20465	<code>\EightStarTaper</code> . . 19524, 20945
<code>\DingObject</code> 13668	<code>\downdownarrows</code> . 18275, 20506	<code>\eightsuperior</code> 20411
<code>\discretionary</code> 699	<code>\downdownharpoons</code> 19696, 21018	<code>\einferior</code> 20435
<code>\div</code> 21150	<code>\downharpoonleft</code> . 18258, 20499	<code>\ejective</code> 16647, 21265
<code>\divdot</code> 19775, 21477	<code>\downharpoonright</code> 18255, 20498	<code>\ell</code> 18084, 20450
<code>\divide</code> 9646, 11348	<code>\downmodels</code> 19912, 21110	<code>\em</code> 614
<code>\divideontimes</code> . . 18809, 20731	<code>\downtherefore</code> . . 18463, 21330	<code>\emgma</code> 16529, 21236
<code>\Divides</code> 18389, 20554	<code>\downuparrows</code> . . 18338, 20531	<code>\emph</code> 593
<code>\DividesNot</code> 18391, 20555	<code>\downupharpoons</code> . 19714, 21024	<code>\empty</code> 1336, 3668
<code>\DJ</code> 3514, 15377, 15960	<code>\downvdash</code> 18746, 21360	<code>\emptyset</code> 18356, 20540
<code>\dj</code> 3511, 3512, 15963	<code>\dp</code> 5163, 5171, 5184, 6288, 6291, 7751, 10010, 10090, 10127, 10167, 11890, 11893, 12502, 12777, 13884	<code>\enc@html</code> 5922, 5925
<code>\dls</code> 18229, 20489	<code>\dsbiological</code> 19388, 20887	<code>\enc@update</code> 555
<code>\do</code> 1354, 2790, 2795, 2800, 3773, 3805, 3806, 3807, 3808, 3857, 3858, 3859, 3860, 3861, 3862, 3865, 3866, 3867, 3868, 3869, 3870, 3873, 3874, 3877, 3878, 3879, 3880, 3881, 3884, 3885, 3886, 3887, 3888, 3891, 3892, 3893, 3894, 3895, 3898, 3899, 3900, 3901, 3902, 3905, 3906, 3909, 3910, 3911, 3914, 3915, 3921, 3922, 3923, 3924, 4251, 4252, 4253, 4254, 4255, 4256, 5520, 7463, 8076, 8099, 13078, 13140, 13352, 13359, 13369, 13593, 13656, 13941, 14007, 14824, 14854	<code>\dschemical</code> 19386, 20886	<code>\END</code> . . 1684, 1685, 1711, 1712, 1727, 1728, 1745, 1746, 1763, 1764, 2148, 2154, 2159, 2261, 2263, 9772, 9785, 9789, 9796, 9809, 9813, 9819, 9831, 9835
<code>\documentclass</code> 2, 9252	<code>\dscommercial</code> 19390, 20888	<code>\end</code> 635, 21502
<code>\dospecials</code> 14833, 14863	<code>\dsjuridical</code> 19384, 20885	<code>\endeqnarray</code> . . 7405, 7427, 7434
<code>\Doteq</code> 18536, 21337	<code>\dsmedical</code> 19382, 20884	<code>\endequation</code> 7359, 7393
<code>\doteq</code> 18529, 20613	<code>\dsmilitary</code> 19379, 20883	<code>\endForm</code> 5912
<code>\doteqdot</code> 18534, 20615	<code>\dth@counter</code> . 7531, 7532, 7562, 7563, 7590	<code>\endinput</code> . 64, 3093, 3168, 4497, 4603, 8865, 11515, 12840, 14951
<code>\dotminus</code> 18468, 20586	<code>\dth@everypar</code> 7578	<code>\endlinechar</code> 930, 951, 4863
<code>\dotplus</code> 18387, 20553	<code>\dtimes</code> 19779, 21051	<code>\endNoHyper</code> 6420
<code>\dots</code> 570	<code>\dvipdfm@setdim</code> 13881, 13924, 14023, 14048, 14079, 14104, 14132, 14161	<code>\EndPreamble</code> 12843
<code>\dottimes</code> 19776, 21050	<code>\dz</code> 16695, 21274	<code>\endsubeqnarray</code> . . . 7438, 7449
<code>\doublebarwedge</code> . . 19799, 21059	E	
<code>\doublecap</code> 18843, 21381	<code>\Earth</code> 19276, 21424	<code>\eng</code> 16093, 21181
<code>\doublecup</code> 18846, 21382	<code>\earth</code> 19274, 20854	<code>\engma</code> 16094, 21182
<code>\doublesqcap</code> 19787, 21478	<code>\ECIRCUMFLEX</code> 20048, 20132, 20133, 20134, 20135, 20136	<code>\ensuremath</code> 683
<code>\doublesqcup</code> 19792, 21479	<code>\ecircumflex</code> 20042, 20072, 20073, 20074, 20075, 20076	<code>\Envelope</code> 19446, 20908
<code>\doublevav</code> 17518	<code>\Ecommerce</code> 18113, 21305	<code>\enya</code> 16533, 21238
<code>\doublevee</code> 19795, 21058	<code>\EdefEscapeHex</code> 855	<code>\epsdice</code> 632, 21155
<code>\doublewedge</code> 19793, 21057	<code>\EdefEscapeName</code> . . 4084, 4128, 9903, 10653, 11191, 12065, 13139, 13142, 13655, 13658, 14003, 14009	<code>\epsi</code> 16452, 21214
<code>\doubleyod</code> 17522	<code>\EdefEscapeString</code> 809, 819	<code>\epsilon</code> 16868, 20360
<code>\DOWNarrow</code> 19172, 20819	<code>\EdefUnescapeName</code> 4085	<code>\eqcirc</code> 18553, 20623
	<code>\EdefUnescapeString</code> . 804, 8289	<code>\eqcolon</code> 18471, 20587
	<code>\egroup</code> 698, 9373, 10478, 10927, 11582, 13299, 13391, 13416	<code>\eqdot</code> 19804, 21061
	<code>\EightAsterisk</code> 19573, 20968	<code>\eqnarray</code> 7404, 7406, 7431
	<code>\EightFlowerPetal</code> . 19551, 20958	<code>\eqsim</code> 18485, 20593
	<code>\EightFlowerPetalRemoved</code> 19570, 20967	<code>\eqslantgtr</code> 19843, 21079
	<code>\eighthnote</code> 19358, 21450	<code>\eqslantless</code> 19841, 21078
	<code>\eighthinferior</code> 20427	<code>\equal</code> 8157
	<code>\EightStar</code> 19530, 20948	<code>\equalscolon</code> 18551, 20622
	<code>\EightStarBold</code> . . . 19532, 20949	<code>\equalsinferior</code> 20431
		<code>\equalsuperior</code> 20415
		<code>\equation</code> 7358, 7367, 7371, 7380
		<code>\equationautorefname</code> 3316, 3334, 3352, 3370, 3388, 3406, 3424, 3442, 3443, 3482, 3500, 9098, 9102
		<code>\equiv</code> 18573, 20632
		<code>\Equivalence</code> 18305
		<code>\er</code> 16448, 21213

<code>\errmessage</code>	3546	<code>\Field@toks</code>	5984, 5985, 5987, 13291, 13308, 13319, 13330, 13340, 13357, 13375, 13383, 13388, 13404, 13413	<code>\fid@bcolor</code>	14422
<code>\es@roman</code>	657	<code>\Field@Width</code>	5897, 6043	<code>\Fld@bordercolor</code>	5904, 6162, 14365, 14367, 14393, 14401, 14403, 14421, 14430, 14432, 14459, 14461, 14490, 14499, 14501, 14526, 14534, 14536, 14562, 14570, 14572
<code>\es@save@dot</code>	1312	<code>\figureautorefname</code>	3319, 3337, 3355, 3373, 3391, 3409, 3427, 3457, 3485, 3503, 9105	<code>\Fld@bordersep</code>	5905, 6111
<code>\escapechar</code> 539, 860, 4444, 7456, 14684, 14865, 14916		<code>\filename@area</code>	5290	<code>\Fld@borderstyle</code>	5907, 6095, 6096, 6097, 6107, 14359, 14391, 14419, 14453, 14488, 14524, 14578
<code>\esh</code>	16588, 20333	<code>\filename@base</code>	5290	<code>\Fld@borderwidth</code>	5906, 6058, 6282, 6285, 6286, 6289, 6290, 13127, 13128, 13643, 13644, 13991, 13992, 14359, 14391, 14419, 14453, 14488, 14524, 14578
<code>\EstimatedSign</code>	18112, 21304	<code>\filename@ext</code> 5287, 5288, 5290, 5291		<code>\Fld@calculate@code</code> 6170, 14302, 14304	
<code>\eta</code>	16872, 20362	<code>\filename@parse</code>	5286	<code>\Fld@cbsymbol</code> 5908, 6123, 14373	
<code>\eTeX</code>	579, 12848	<code>\find@pdfink</code>	9422, 9476, 9486	<code>\Fld@charsize</code> 5898, 5899, 6055, 13126, 13642, 13990, 14375, 14440, 14469, 14509, 14560	
<code>\etex@unexpanded</code>	1887, 1894	<code>\Finv</code>	18114, 20455	<code>\Fld@checkedfalse</code>	5894
<code>\eTeXversion</code>	9605, 9607, 9609	<code>\Fire</code>	20003, 21140	<code>\Fld@checkequals</code>	5998, 13079, 13141, 13360, 13370, 13594, 13657, 13942, 14008
<code>\eth</code>	15894, 21174	<code>\fivedots</code>	19938, 21121	<code>\Fld@choices</code>	5787, 5795, 5797, 5801, 5810, 5818, 5823, 5871, 5873, 5881, 5882, 14442
<code>\Eur</code>	18070, 21301	<code>\FiveFlowerOpen</code>	19549, 20957	<code>\Fld@color</code>	5902, 6165, 14376, 14441, 14470, 14510
<code>\EURcr</code>	18067, 21298	<code>\FiveFlowerPetal</code>	19547, 20956	<code>\Fld@default</code>	5812, 5815, 5817, 6114, 13043, 13059, 13071, 13111, 13139, 13231, 13289, 13307, 13321, 13329, 13336, 13362, 13372, 13402, 13412, 13556, 13573, 13586, 13627, 13655, 13771, 13897, 13914, 13934, 13975, 14003, 14142, 14471, 14472, 14473, 14511
<code>\EurCr</code>	18066, 21297	<code>\fiveinferior</code>	20424	<code>\Fld@DingDef</code>	6123, 6126, 6128
<code>\EURdig</code>	18063, 21294	<code>\FiveStar</code>	19206, 20832	<code>\Fld@disabledfalse</code>	5895
<code>\EurDig</code>	18062, 21293	<code>\FiveStarCenterOpen</code>	19508, 20937	<code>\Fld@export</code>	5625, 5628, 5635, 5927
<code>\EURhV</code>	18065, 21296	<code>\FiveStarConvex</code>	19516, 20941	<code>\Fld@findlength</code>	13339, 13350
<code>\EurHv</code>	18064, 21295	<code>\FiveStarOpen</code>	19208, 20833	<code>\Fld@flags</code> 5694, 5696, 5707, 5709, 5723, 5725, 5755, 5757, 5780, 5782, 14357, 14389, 14417, 14451, 14486, 14522, 14558	
<code>\EURtm</code>	18069, 21300	<code>\FiveStarOpenCircled</code>	19506, 20936	<code>\Fld@format@code</code>	6168, 14294, 14296
<code>\EurTm</code>	18068, 21299	<code>\FiveStarOpenDotted</code>	19510, 20938	<code>\Fld@getmethodfalse</code>	5947
<code>\evensidemargin</code>	8307	<code>\FiveStarOutline</code>	19512, 20939	<code>\Fld@getmethodtrue</code>	5949
<code>\everypar</code>	7604	<code>\FiveStarOutlineHeavy</code>	19514, 20940		
<code>\ExecuteOptions</code> 4312, 4313, 4317		<code>\FiveStarShadow</code>	19518, 20942		
<code>\exists</code>	18352, 20538	<code>\fivesuperior</code>	20408		
<code>\ext@figure</code>	8672	<code>\Flag</code>	19374, 20881		
<code>\ext@table</code>	8671	<code>\flap</code>	16576, 21249		
<code>\extra@b@citeb</code>	8083	<code>\flap*</code>	16575, 21248		
<code>\extravietnam</code>	3592	<code>\flat</code>	19363, 20876		
<code>\extravietnamese</code>	3584	<code>\Fld@@additionalactions</code>	14289, 14332, 14336		
<code>\EyesDollar</code>	15647, 21159	<code>\Fld@@DingDef</code> 6130, 6133, 6152			
		<code>\Fld@additionalactions</code>	14289, 14379, 14408, 14443, 14478, 14513, 14548, 14580		
F		<code>\Fld@align</code>	5901, 6117, 14358, 14418, 14487		
<code>\fa</code>	20229	<code>\Fld@altname</code> 6033, 6035, 14268, 14270, 14342, 14344			
<code>\fallingdoteq</code>	20617	<code>\Fld@annotflags</code>	5680, 5682, 14353, 14385, 14413, 14447, 14482, 14518, 14554		
<code>\fallingdotseq</code>	18540	<code>\Fld@annotnames</code> 14340, 14355, 14387, 14415, 14449, 14484, 14520, 14556			
<code>\FancyVerbLineautorefname</code>	3329, 3347, 3365, 3383, 3401, 3419, 3437, 3472, 3475, 3495, 3513, 9115	<code>\Fld@bcolor</code>	5903, 6159, 14369, 14371, 14434, 14436, 14463, 14465, 14491, 14503, 14505		
<code>\farsikaf</code>	20271				
<code>\farsiya</code>	20275				
<code>\fatha</code>	20255				
<code>\fatsemi</code>	19769, 21047				
<code>\Fax</code>	20000, 21139				
<code>\fax</code>	18124, 20460				
<code>\Faxmachine</code>	20002, 21495				
<code>\fbox</code>	13521, 13524				
<code>\fcdice</code>	633, 21156				
<code>\Female</code>	19273, 21423				
<code>\female</code>	19267, 19270, 21420				
<code>\FemaleFemale</code>	19396, 20891				
<code>\FemaleMale</code>	19400, 20893				
<code>\Field@addtoks</code> 5986, 6017, 6020, 6205, 6228					
<code>\Field@boolkey</code> 5473, 5561, 5980, 6010, 6013					

\Fld@height . 6052, 13046, 13063,
13074, 13129, 13146, 13158,
13191, 13208, 13234, 13243,
13559, 13579, 13589, 13645,
13673, 13687, 13723, 13746,
13774, 13786, 13900, 13916,
13937, 13993, 14005, 14041,
14090, 14113, 14145, 14153
\Fld@hiddenfalse 5583
\Fld@hiddentrue 5584
\Fld@invisiblefalse 5579
\Fld@invisibletrue 5580
\Fld@keystroke@code 6171,
14290, 14292
\Fld@listcount . . . 13138, 13143,
13154, 13654, 13659, 13674,
13680, 14002, 14010, 14014,
14019, 14030, 14037
\Fld@loc 6007
\Fld@mappingname . 6037, 6039,
14272, 14274, 14346, 14348
\Fld@maxlen . 5900, 6046, 14514
\Fld@menulength . . 5896, 6049,
13076, 13080, 13126, 13351,
13352, 13355, 13591, 13595,
13642, 13939, 13943, 13990
\Fld@name . 6031, 13042, 13070,
13163, 13230, 13288, 13293,
13304, 13305, 13316, 13317,
13326, 13327, 13335, 13356,
13373, 13381, 13386, 13401,
13410, 13555, 13585, 13692,
13770, 13896, 13933, 14055,
14141, 14267, 14341
\Fld@norotatefalse 5596
\Fld@norotatetrue 5595
\Fld@noviewfalse 5599
\Fld@noviewtrue 5600
\Fld@nozoomfalse 5592
\Fld@nozoomtrue 5591
\Fld@onblur@code . 6173, 14310,
14312
\Fld@onclick@code . 6167, 6239,
14407
\Fld@onenter@code 6176, 14322,
14324
\Fld@onexit@code . 6177, 14326,
14328
\Fld@onfocus@code 6172, 14306,
14308
\Fld@onmousedown@code 6174,
14314, 14316
\Fld@onmouseup@code . . 6175,
14318, 14320
\Fld@pageobjref . 13040, 13529,
13540, 13894, 14223, 14354,
14386, 14414, 14448, 14483,
14519, 14555
\Fld@printfalse 5588
\Fld@printrue 5587
\Fld@radiosymbol . . 5909, 6126,
14467
\Fld@rotation 5910, 6156, 14361,
14363, 14392, 14397, 14399,
14420, 14426, 14428, 14455,
14457, 14489, 14495, 14497,
14525, 14530, 14532, 14561,
14566, 14568
\Fld@submitflags . . . 5662, 5664,
14546
\Fld@temp . . 6129, 6131, 6134,
6135, 6144, 6145
\Fld@validate@code 6169, 14298,
14300
\Fld@value 5813, 5820, 5822, 6120,
13044, 13059, 13072, 13110,
13111, 13557, 13573, 13587,
13626, 13627, 13898, 13914,
13935, 13974, 13975, 14512
\Fld@width . 6042, 13045, 13058,
13063, 13073, 13109, 13120,
13122, 13146, 13158, 13178,
13190, 13198, 13207, 13221,
13233, 13239, 13243, 13558,
13572, 13579, 13588, 13625,
13636, 13638, 13673, 13687,
13708, 13722, 13730, 13745,
13759, 13773, 13780, 13786,
13899, 13913, 13916, 13936,
13973, 13984, 13986, 14005,
14041, 14072, 14089, 14097,
14112, 14126, 14144, 14151,
14153
\float@caption 7852, 7924
\float@makebox 7926, 7927
\floatingpenalty 7752
\Florin 16216, 21186
\fiq 664
\fiqq 662
\fmtname 7
\fmtversion 7
\font 5151
\fontencoding . . . 547, 551, 586,
13513
\fontfamily 587, 13512
\fontseries 588, 7496, 7524, 7555,
13514
\fontshape 589, 4790, 13515
\fontsize 590
\Football . . 19415, 19417, 21455
\footins 7746
\footnote 5449
\footnoteautorefname
. . 3317, 3335, 3353, 3371,
3389, 3407, 3425, 3446,
3449, 3483, 3501, 9099, 9103
\footnotesep 7750, 7757
\footnotesize 619, 7748
\footnotetext 7708
\footref 7776, 7777
\forall 18346, 20535
\Force 18177, 21311
\foreignlanguage 645
\Form 5911
\Form@action 5921, 13280, 14544
\Form@boolkey 5915
\Form@htmlfalse . . . 5914, 5933
\Form@htmltrue 5926
\Form@method 5945, 5953, 13280
\Foward 19165, 20816
\FowardToIndex . . 18983, 20805
\FourAsterisk 19494, 20930
\fourinferior 20423
\FourStar 19502, 20934
\FourStarOpen . . . 19504, 20935
\foursuperior 20407
\fourth 17960, 20403
\frown 18936, 20786
\frownie 19249, 20847
\Frowny 19251, 21415
\frq 665
\frqq 663
\fullnote 19977, 21129
\futurelet 718, 1678
\FV@SetLineNo 7197
\FV@StepLineNo . . . 7196, 7198,
7199
G
\G . . 15536, 15575, 15602, 16327,
16329, 16331, 16333, 16339,
16341, 16342, 16349, 16351,
16357, 16359, 16361, 16363
\g@addto@macro . . . 6608, 6780,
7985, 8262, 8265, 8268,
8317, 9839, 10816, 11338,
11638, 12213, 12299, 12361,
12663, 12854
\G@refundefinedtrue 5116, 8085,
8108, 8870, 8890, 8907, 9025
\gaf 20273
\Game 18126, 20461
\Gamma 16799, 20345
\gamma 16864, 20358
\gammainferior 20387
\Ganz 19979, 21492
\GaPa 19965, 21123
\Gauge 6255
\ge 18585, 20637

\Gemini	19305, 21435	20150, 20155, 20160, 20165, 20170	6277, 6278, 6279, 8113, 8302, 9366, 9932, 10011, 10021, 10091, 10105, 10128, 10143, 10168, 10183, 10454, 10471, 11546, 11893, 11907, 12503, 12513, 12778, 12793, 13428, 13915, 14004, 14040, 14070, 14098, 14127, 14152, 14963
\gemini	19303, 20863		\hc@currentHref 7863
\GenericError	706, 3950	\H@footnotemark 7611, 7628, 7692, 7781, 7788, 7800, 7811	\HCode 13280, 13282, 13293, 13302, 13314, 13322, 13324, 13355, 13361, 13366, 13371, 13385, 13390, 13394, 13397, 13406
\GenericInfo	708, 3948	\H@footnotetext	\hdotfor 17925, 20397
\GenericWarning	270, 707, 3949	7610, 7620, 7652, 7691, 7730, 7789, 7803, 7811	\headerps@out 6881, 12203, 12214, 12286, 12300, 12353, 12362, 12375, 12389, 12428, 12546, 12664, 12855
\Gentsroom	20007, 21142	\H@mpfootnotetext 7618, 7630, 7632, 7693	\Heart 19338, 21446
\geq	18585, 20636	\H@definecounter 8419, 8421	\heartsuit 19336, 19339, 21447
\geqclosed	18795, 21376	\H@endeqnarray 7405, 7428	\hebalef 17463
\geqq	18593, 20640	\H@endequation 7359, 7399	\hebayin 17499
\geqslant	19814, 21066	\H@endsubeqnarray 7438, 7450	\hebbet 17465
\getpagerefnumber	7311	\H@eqnarray 7404, 7409	\hebdalet 17469
\getrefbykeydefault	7267, 7268	\H@equation 7358, 7382	\hebfinalkaf 17483
\gexmode	11369, 11370, 11470	\H@item 6977, 6983, 7993, 8018	\hebfinalmem 17489
\gg	18605, 20646	\H@newctr 8424, 8426	\hebfinalnun 17493
\ggg	18855, 20751	\H@old@part 15015, 15026	\hebfinalpe 17501
\ghayn	20225	\H@old@chapter 14985, 14994	\hebfinaltsadi 17505
\gimel	18120, 20458	\H@old@sect 15036, 15047, 15056	\hebgimel 17467
\Gin@setfile	8514, 8515	\H@old@spart 15028, 15034	\hebhe 17471
\glossary	671	\H@old@ssect 14971, 14976	\hebhet 17477
\glotstop	16645, 20342	\H@refstepcounter 6994, 7004, 7198, 7322, 7335, 7381, 7537, 7568, 7847, 8686, 8739	\hebkafe 17485
\glottal	16648, 21266	\H@seteqlabel 8455, 8457	\heblamed 17487
\glq	660	\H@subeqnarray 7437, 7441	\hebmam 17491
\glqq	658	\ha 20241	\hebnun 17495
\gnapprox	19833, 21075	\Haa 20199	\hebpe 17503
\gneq	19829, 21073	\Halb 19982, 21493	\hebpqf 17509
\gneqq	18599, 20643	\halfnote 19980, 21130	\hebresh 17511
\gnsim	18887, 20765	\halign 680	\hebsamekh 17497
\Greeknumeral	1176	\hamza 20175	\hebsin 17513, 17514, 21279
\greeknumeral	1175	\HandCuffLeft 19225, 20839	\hebtav 17516
\grq	661	\HandCuffRight 19227, 20840	\hebtet 17479
\grqq	659	\HandLeft 19229, 20841	\hebtsadi 17507
\gtrapprox	19822, 21070	\HandRight 19232, 20842	\hebvav 17473
\gtrclosed	18788, 21373	\HaPa 19967, 21124	\hebyod 17481
\gtrdot	18851, 20749	\HAR@checkcitations 8173	\hebzayin 17475
\gtreqless	18861, 20753	\HAR@citetoaux 8129	\Hermaphrodite 19402, 20894
\gtreqqlless	19839, 21077	\HAR@tempa 8174, 8175, 8176, 8177, 8178, 8179	\hexagon 18978, 20803
\gtrless	18632, 20658	\hardsign 17099, 21277	\hexstar 19413, 20896
\gtrsim	18623, 20654	\harvardcite 8123, 8160	\hfill 6276, 6277, 6278, 6279, 8004, 8037
\guill@spacing	1105	\harvarditem 8148	\Hfootnoteautorefname 9099
\guillemotleft	1145, 15303, 15485, 15745, 20029	\hateq 18561, 20627	\hhypperref 5454
\guillemotright	1146, 15334, 15486, 15780, 20030	\hausab 16205, 20307	
\guilsinglleft	15234, 15487, 17943, 20031	\hausab 16424, 21207	
\guilsinglright	15236, 15488, 17945, 20032	\hausad 16209, 20308	
		\hausad 16438, 21212	
		\hausak 16220, 20309	
		\hausak 16224, 21188	
		\hb@xt@ 5166, 5179	
		\hbar 16011, 20306	
		\hbox 1954, 1960, 1966, 2672, 3679, 3685, 5167, 5181, 5325, 5327, 6043, 6276,	

<code>\hinferior</code>	20439	<code>\hvtex@parse@trans</code> 11217, 11239	<code>\Hy@appendixstring</code> 7088, 7110
<code>\hoffset</code>	8303	<code>\hvtex@produce@trans</code> . . . 11278, 11284	<code>\Hy@AtBeginDocument</code>
<code>\hookb</code>	16423, 21206	<code>\hvtex@token</code> . . . 11236, 11247, 11253, 11260, 11265, 11268, 11271, 11273	. . . 375, 1084, 2954, 3014, 3089, 3164, 3220, 3621, 4294, 4337, 4354, 4493, 4499, 4599, 4758, 4848, 6354, 6465, 6914, 7203, 8120, 8944, 9092, 9361, 9847, 10466, 10981, 12388, 12426, 13443, 13444
<code>\hookd</code>	16437, 21211	<code>\hvtex@trans@code</code> 11221, 11222, 11223, 11224, 11225, 11226, 11227, 11240, 11286, 11287, 11289, 11291, 11293, 11295, 11297, 11299, 11301, 11302, 11303, 11304, 11305, 11307	<code>\Hy@AtBeginDocumentHook</code> 376, 381, 387, 388
<code>\hookg</code>	16470, 21218	<code>\hvtex@trans@effect@Blinds</code> 11221	<code>\Hy@AtEndOfPackage</code> 378, 918, 2588, 3585, 3593, 3600, 4481, 4507, 4513, 4710
<code>\hookh</code>	16490, 21223	<code>\hvtex@trans@effect@Box</code> 11222	<code>\Hy@AtEndOfPackageHook</code> 379, 382, 384, 385
<code>\hookheng</code>	16494, 21225	<code>\hvtex@trans@effect@Dissolve</code> 11223	<code>\Hy@author</code> 6535, 6539
<code>\hookleftarrow</code> 18215, 20483		<code>\hvtex@trans@effect@Glitter</code> 11224	<code>\Hy@babelnormalise</code> 5079, 5081
<code>\hookrelepsilon</code> . . . 16459, 21215		<code>\hvtex@trans@effect@R</code> . . 11227	<code>\Hy@backout</code> . 4857, 6405, 6409, 7959
<code>\hookrightarrow</code> . . 18217, 20484		<code>\hvtex@trans@effect@Split</code> 11225	<code>\Hy@backreffalse</code> 443, 3281, 3303, 4505
<code>\hphantom</code>	629	<code>\hvtex@trans@effect@Wipe</code> 11226	<code>\Hy@backreftrue</code> 3274, 3278, 3300
<code>\href</code> 672, 4978, 5448, 5449, 6446		<code>\hvtex@trans@par</code> 11260, 11264, 11266, 11269, 11272	<code>\Hy@BeginAnnot</code> . 10496, 10513, 10554, 10591, 10623, 10652
<code>\href@</code>	4981, 4984, 4989	<code>\hvtex@trans@params</code> . . . 11254, 11256, 11280	<code>\Hy@bibcite</code> 7982, 7986
<code>\href@split</code>	4989, 4990	<code>\Hy@@@CleanupFile</code> . 5325, 5327	<code>\Hy@bookmarksdepth</code> . . . 3664, 3669, 3681, 3687, 14595
<code>\hsize</code>	7753	<code>\Hy@@@DefNameKey</code> . 2815, 2817	<code>\Hy@bookmarksnumberedfalse</code> 444
<code>\hskip</code> . . 1965, 2052, 2713, 2714, 4975, 6282, 13428		<code>\Hy@@@Escapeform</code> 14233, 14246, 14252	<code>\Hy@bookmarksopenfalse</code> . . 445
<code>\hslash</code>	18080, 20448	<code>\Hy@@@SectionAnchor</code> 14958, 14961	<code>\Hy@bookmarkstrue</code> 446
<code>\hspace</code>	668, 8163, 8164	<code>\Hy@@@temp</code> . . 3709, 3711, 6179, 6181	<code>\Hy@bookmarkstype</code> 3699, 3701, 8333, 14606
<code>\hss</code>	5168, 5180, 8311, 14968	<code>\Hy@@@VersionCheck</code> . . 292, 321	<code>\Hy@boolkey</code> . 2742, 2834, 2837, 2840, 2861, 2864, 2867, 2898, 2901, 2904, 2921, 2925, 2928, 2931, 2934, 2937, 2940, 2943, 2946, 3027, 3252, 3255, 3310, 3607, 3619, 3634, 3659, 3662, 3703, 3706, 3767, 3927, 4215, 4218, 4221, 4224, 4227, 4230, 4233, 4241, 4262, 4265, 6848
<code>\ht</code> 5172, 5176, 5185, 6284, 6287, 10019, 10094, 10103, 10110, 10131, 10141, 10148, 10171, 10181, 10188, 11889, 12511, 12791, 13882		<code>\Hy@Cabspace</code> . 6628, 6714, 6830, 6907	<code>\Hy@BorderArrayPatch</code> . . 11944, 11947, 12212, 12662
<code>\htmladdimg</code>	5447	<code>\Hy@Acrobatmenu</code> . . 4382, 4423, 9901, 10651, 11192, 12066	<code>\Hy@breaklinks@unsupported</code> 2909, 11498
<code>\htmladdnormallink</code>	5448	<code>\Hy@activeanchorfalse</code> 4861, 9467, 9963, 9978, 10057, 10067, 10383, 10912, 10929, 11000, 11013, 11532, 12451, 12466, 12731, 12745	<code>\Hy@breaklinksfalse</code> 447
<code>\htmladdnormallinkfoot</code> . . . 5449		<code>\Hy@activeanchortrue</code> 9463, 9960, 9974, 10055, 10064, 10379, 10908, 10926, 10998, 11010, 11522, 12448, 12462, 12728, 12741	<code>\Hy@breaklinksunhbox</code> . . 11843, 11897
<code>\htmlref</code>	5450	<code>\Hy@ActiveCarriageReturn</code> 4897, 4900	<code>\Hy@CatcodeWrapper</code> . . . 4719, 4778, 4822, 4851
<code>\htrtaild</code>	20394	<code>\Hy@AllowHyphens</code> 4971, 11520, 11552, 11876	<code>\Hy@chapapp</code> 7089, 7110, 7137, 14989, 15000, 15082
<code>\Huge</code>	616	<code>\Hy@AlphNoErr</code> 7093, 7106, 7108	
<code>\huge</code>	620	<code>\Hy@AnchorName</code>	
<code>\Hurl</code>	5064, 5066, 5068	. . 5101, 5103, 5106, 5108, 5132, 5134, 5138, 5143, 5145	
<code>\hv</code>	16219, 21187		
<code>\hv@pdf@char</code> . . . 14753, 14818, 14819, 14820, 14821			
<code>\hvtex@buffer</code> . . . 11233, 11237, 11245, 11248, 11257, 11261, 11277			
<code>\hvtex@gettoken</code> . 11232, 11246, 11250, 11259, 11263			
<code>\hvtex@gettoken@</code> . 11233, 11235			
<code>\hvtex@par@dimension</code> . . 11228, 11269			
<code>\hvtex@par@direction</code> . . . 11229, 11272			
<code>\hvtex@par@duration</code> 11230, 11264			
<code>\hvtex@par@motion</code> 11231, 11266			
<code>\hvtex@param@dimension</code> 11241, 11270, 11288, 11291			
<code>\hvtex@param@direction</code> . 11242, 11273, 11299, 11307			
<code>\hvtex@param@duration</code> . 11243, 11265, 11312, 11314			
<code>\hvtex@param@motion</code> . . 11244, 11267, 11288, 11295			

\Hy@chapterstring . . . 7084, 7086, 7089, 7136	6371, 6372, 6373, 6374, 6375, 6376, 6377, 6378, 6379, 6380, 6381, 6559, 6782, 7815, 8519, 8617, 8618, 9285, 9389, 9757, 9758, 9759, 9760, 9761, 9762, 9763, 9764, 9765, 9766, 9896, 10222, 10223, 10224, 10225, 10226, 10227, 10228, 10229, 10230, 10231, 10494, 10714, 10715, 10716, 10717, 10718, 10719, 10720, 10721, 10722, 10723, 10841, 10983, 11450, 11451, 11452, 11453, 11454, 11455, 11456, 11457, 11458, 11459, 11717, 11718, 11719, 11720, 11721, 11722, 11723, 11724, 11725, 11726, 12279, 12572, 12573, 12574, 12575, 12576, 12577, 12578, 12579, 12580, 12581	\Hy@EndWrap 4720, 4722, 4723, 4756
\Hy@CheckOptionValue . . 2785, 2822	\Hy@DistillerDestFix 8276, 11463, 11465	\Hy@Error 264, 280, 286, 309, 2958, 3075, 3100, 3133, 3171, 3178, 3189, 3195, 4407, 5032, 5256, 5620, 5744, 5940, 5972, 6184, 6233, 13169, 13215, 13699, 13753, 14062, 14120
\Hy@CJKbookmarksfalse . . . 449	\Hy@draftfalse 405	\Hy@escapeform . . 13062, 13145, 13157, 13181, 13199, 13222, 13242, 13577, 13663, 13685, 13712, 13733, 13761, 13784, 13921, 14013, 14044, 14076, 14100, 14128, 14158, 14227, 14257, 14264
\Hy@cjkp 1347, 1349, 1370	\Hy@drafttrue 406	\Hy@escapestring 14224, 14292, 14296, 14300, 14304, 14308, 14312, 14316, 14320, 14324, 14328, 14373, 14407, 14467, 14511, 14512, 14544
\Hy@CleanupFile . . . 5323, 9528, 10556, 11077, 12138	\Hy@driver 485, 2914, 3086, 3098, 3108, 3113, 3118, 3131, 3141, 3146, 3151, 3158, 3161, 3187, 3203, 3210, 3215, 3225, 3981, 4515, 4518, 4522, 4525, 4529, 4532, 4534, 4538, 4544, 4548, 4551, 4555, 4560, 4564, 4567, 4571, 4574, 4576, 4580, 4586, 4590, 4593, 4596, 4607, 4610, 4613, 4622, 4623, 4634, 4636, 4644, 4646, 4648, 4650	\Hy@EveryPageAnchor . . 8275, 8318
\Hy@colorlink 3613, 4782, 4790, 4794, 9362, 9448, 9521, 9561, 9597, 9926, 9961, 9984, 10015, 10028, 10056, 10072, 10097, 10113, 10135, 10152, 10175, 10192, 10467, 10545, 10584, 10616, 10645, 10671, 10999, 11021, 11091, 11117, 11152, 11185, 11204, 11550, 11827, 11829, 12449, 12472, 12507, 12520, 12729, 12751, 12786, 12799	\Hy@DviErrMsg . . . 3053, 3055, 3058, 3064, 3077	\Hy@EveryPageBoxHook 6585, 6589, 6593, 8317, 10816, 11338, 11638
\Hy@colorlinksfalse 3610	\Hy@dth@currentHref 7539, 7570, 7595	\Hy@EveryPageHook 6584, 6588, 6780, 9839
\Hy@ColorList 3772, 3773	\Hy@DviModetrue . . 3062, 3067	\Hy@ExchangeLeftParenthesis 9148, 9154
\Hy@CounterExists . . 6942, 6955, 6958	\Hy@DvipdfmxOutlineOpentrue 4680, 4687	\Hy@ExchangeRightParenthesis 9158, 9164
\Hy@currentbookmarklevel 14601, 14611, 14612, 14618, 14625, 14718, 14721, 14726, 14730	\Hy@EndAnnot . . 10502, 10548, 10587, 10619, 10648, 10674	\Hy@false 2636, 2752, 3266, 3302, 5969
\Hy@debugfalse 439	\Hy@endcolorlink . . 3614, 4786, 4791, 4795, 9371, 9454, 9961, 9998, 10022, 10030, 10056, 10080, 10101, 10115, 10139, 10154, 10179, 10194, 10476, 10504, 10999, 11072, 11093, 11119, 11154, 11187, 11206, 11577, 11836, 12449, 12488, 12514, 12522, 12729, 12765, 12790, 12801	\Hy@finalfalse 406
\Hy@debugtrue 438		\Hy@finaltrue 405
\Hy@defaultbp 6058, 6060		\Hy@FirstPage 4393
\Hy@defaultbpAux . . 6062, 6067, 6081		\Hy@FirstPageHook 6586, 6600, 6601, 6605, 6608, 6879, 6880, 12213, 12299, 12361, 12663, 12854
\Hy@defaultdriver . . 4588, 4613, 4623, 4634		\Hy@FixNotFirstPage 9930, 9931, 9939
\Hy@DefFormAction 5919, 5921		\Hy@float@caption . . 7853, 7903, 7917
\Hy@DefNameKey . . 2814, 3804, 3856, 3864, 3872, 3876, 3883, 3890, 3897, 3904, 3908, 3913, 3920, 4250		\Hy@float@currentHref . . 7907, 7910, 7912, 7918, 7920, 7922
\Hy@DEST 11844, 11911		\Hy@footnote@currentHref 6353, 7640, 7645, 7660, 7665, 7668, 7680, 7682, 7721, 7762, 7765
\Hy@destlabelfalse 450		\Hy@FormObjects 13481, 13792, 13846, 13856, 14169, 14219
\Hy@DestName 9409, 9416		\Hy@frenchlinksfalse 3612
\Hy@DestRename . . 5388, 5413, 5417		\Hy@Gin@setfile . . . 8514, 8516
\Hy@DisableOption 2771, 4374, 4375, 4376, 4378, 4381, 4486, 4512, 4654, 4655, 4656, 4657, 4658, 4659, 4660, 4661, 4662, 4663, 4664, 4665, 4666, 4667, 4668, 4669, 4670, 4671, 4672, 4673, 4718, 4771, 4799, 4800, 4859, 4860, 5443, 6358, 6359, 6360, 6361, 6362, 6363, 6364, 6365, 6366, 6367, 6368, 6369, 6370,		\Hy@GlobalStepCount 483, 6714, 7167, 7190, 8293, 8728, 8779

\Hy@temp	833, 834, 4445, 4451, 4453, 5817, 5818, 5822, 5823, 5834, 5848, 7697, 7702, 9172, 9174, 14285, 14287	\Hy@linktoc@section	2871, 2875, 2881	\Hy@OutlineRerunCheck	14742, 14841, 14923
\Hy@href	4981, 4983	\Hy@linktocpagefalse	458	\Hy@PageAnchorSlide	8235, 8273, 8286
\Hy@href@nextactionraw	5018, 5041, 5043, 5044, 5046, 5051, 5055, 5057, 9517, 9557, 9593, 9922, 10541, 10580, 10612, 10641, 10667, 11036, 11106, 11174, 12163, 12192	\Hy@localanchornamfalse	459	\Hy@PageAnchorSlidesPlain	8222, 8272, 8281
\Hy@href@page	4996, 4998, 5002, 5003, 5005, 5012, 5015, 9553, 10575, 12159	\Hy@LT@currentHref	7337, 7348	\Hy@pageanchortrue	465
\Hy@hyperfiguresfalse	452	\Hy@LT@footnotetext	7720, 7729	\Hy@pagecounter	488, 490, 7229, 8293, 8295
\Hy@hyperfootnotetrue	454	\Hy@make@anchor	8432, 8438, 8444	\Hy@pageheight	4308, 12301, 12390
\Hy@hyperindextrue	455	\Hy@make@cdf@tag@@	8436, 8451	\Hy@param	7135, 7136, 7137, 7164, 7168
\Hy@hypertextnamesfalse	2592	\Hy@make@cdf@tag@@@	8442, 8452	\Hy@pdfafalse	481
\Hy@hypertextnametrue	456	\Hy@MakeCurrentHref	7178, 7191	\Hy@pdfcenterwindowfalse	448
\Hy@ifStringEndsWith	5291, 5303	\Hy@MakeCurrentHrefAuto	7189, 7271, 8433, 14586, 14973, 14989, 15000, 15030, 15044, 15082	\Hy@pdfdisplaydoctitlefalse	480
\Hy@implittrue	457	\Hy@MakeRemoteAction	5001, 9531, 10559, 12141	\Hy@pdfencoding@pdfdoc	3009
\Hy@info	267, 2760, 4456, 4458, 4461, 4463, 4466, 4468, 4471, 4473, 4476, 4478, 4703, 4709, 4787, 4792, 4796, 4940, 4967, 5527, 6315, 6317, 6320, 6322, 6325, 6327, 6330, 6332, 6335, 6337, 6340, 6342, 6345, 6347, 8060, 8121, 8338, 8355	\Hy@maketitle@end	7792, 7797, 7799	\Hy@pdfescapeformfalse	451
\Hy@isNotEmpty	5395, 5396, 5419	\Hy@maketitle@optarg	7790, 7795	\Hy@pdffitwindowfalse	453
\Hy@lastPage	4396	\Hy@match	325, 327, 3232, 3753, 3813, 3830, 4189, 5046, 6097	\Hy@pdfmarkerrorfalse	11807
\Hy@level	14607, 14609, 14620, 14625, 14626, 14627, 14658	\Hy@MaybeStopNow	3154, 4318, 4321	\Hy@pdfmarkerrortrue	11977, 11986
\Hy@levelcheck	14608, 14623	\Hy@message	269, 3088, 3163, 4492, 4598, 4646, 10933, 10937, 10940, 10943, 10946, 10949, 10952, 10955, 13038, 13252, 13256, 13259, 13262, 13265, 13268, 13271, 13274, 13284, 13421, 13851	\Hy@pdfmenubartrue	460
\Hy@linkcounter	487, 489, 7167, 7168, 7190, 7191, 8458, 8728, 8729, 8733, 8779, 8780, 8784	\Hy@naturalnamesfalse	461	\Hy@pdfminorversion	9184, 9190, 9193, 9201, 9220, 9243, 9264, 9279, 9283
\Hy@linkfileprefix	3743, 5275, 10001, 10877, 12492, 12768	\Hy@nestingfalse	462	\Hy@pdfnewwindowfalse	464
\Hy@linkmath	11541, 11543, 11548, 11580, 11868, 11870, 11875, 11877, 11883, 11885	\Hy@newline@author	6578	\Hy@pdfnewwindowsetfalse	463, 4238
\Hy@linktoc	2869, 2871, 2879, 2881, 2891, 8379	\Hy@newline@title	6577	\Hy@pdfnewwindowsettrue	4240, 5020
\Hy@linktoc@all	2877	\Hy@next	6730, 6740, 6745, 14999, 15008, 15011	\Hy@pdfnewwindowtrue	5021
\Hy@linktoc@none	2874	\Hy@nextfalse	4425, 8529	\Hy@pdfpagehiddenfalse	467
\Hy@linktoc@page	2869, 2876, 2879	\Hy@nextpage	4387	\Hy@pdfpagelabelsfalse	6615
		\Hy@nexttrue	4426, 4427, 4428, 8530, 8531, 8532	\Hy@pdfpagelabelstrue	466
		\Hy@number	4158, 4162, 4170	\Hy@pdfstringdef	832, 5792, 5800
		\Hy@numberline	14602, 14639, 14640, 14641, 14642	\Hy@pdfstringfalse	468, 6383
		\Hy@obsoletePaperOption	2843, 2851	\Hy@pdfstringtrue	685, 6355
		\Hy@ocgcolor	9365, 9379, 10470, 10484	\Hy@pdftoolbartrue	474
		\Hy@ocgcolorlinksfalse	3611, 4766	\Hy@pdfusetitlefalse	477
		\Hy@org@chapter	14997, 15012	\Hy@pdfversion	3040, 3051, 5794, 9206, 9214, 9220, 9243, 9246, 9264, 9266, 9280, 9283, 14279
		\Hy@orgMakeLabel	12823, 12830	\Hy@pdfwindowuitrue	479
		\Hy@outlineName	14877, 14932	\Hy@plainpagesfalse	469
				\Hy@PrevPage	4390
				\Hy@ProvideTheHCounter	7040
				\Hy@ps@CR	12343, 12350, 12355, 12356, 12373, 12394, 12395, 12396, 12402, 12409, 12416, 12423
				\Hy@psdextrafalse	473
				\Hy@pstringB	9673, 9678, 10754, 10766, 11780, 11796, 12635, 12651

\Hy@pstringD 9530, 9555, 10558, 10577, 12140, 12161	10370, 10913, 10930, 11001, 11014, 11513, 11533, 12452, 12467, 12732, 12746	\Hy@scanoptauthor . 6533, 6534
\Hy@pstringdef 9119, 9408, 9432, 9492, 9529, 9530, 9567, 9568, 9673, 10321, 10522, 10557, 10558, 10592, 10593, 10624, 10754, 11020, 11098, 11161, 11162, 11780, 11975, 11984, 12113, 12139, 12140, 12171, 12172, 12635, 14250, 14876, 14892	\Hy@RestoreSavedSpaceFactor . 2656, 10009, 10089, 10126, 10166, 12501, 12776	\Hy@scanopttitle . . . 6524, 6525
\Hy@pstringDest . . . 9408, 9409, 10321, 10368, 11975, 11976, 11980, 11984, 11985, 11989	\Hy@RestoreSpaceFactor . 2647, 2673, 2678, 10008, 10016, 10023, 10088, 10098, 10106, 10125, 10136, 10144, 10165, 10176, 10184, 11547, 11583, 11874, 11882, 11909, 12500, 12508, 12515, 12775, 12787, 12794, 12831, 12835	\Hy@secnum@part 15018, 15020, 15023
\Hy@pstringF 9527, 9528, 9529, 9549, 9567, 9586, 9591, 10555, 10556, 10557, 10572, 10592, 10605, 10610, 11076, 11077, 11081, 11161, 11168, 11172, 12137, 12138, 12139, 12156, 12171, 12187, 12190	\Hy@ReturnAfterElseFiFiEnd 493, 1921	\Hy@SectionAnchorHref . . 682, 14956, 14978, 15049
\Hy@pstringName 14876, 14877, 14892, 14906	\Hy@ReturnAfterFiFiEnd . 492, 1913, 1927, 2020, 2027	\Hy@SectionHShift 14955, 14964, 14974, 15045
\Hy@pstringP 9568, 9591, 10593, 10610, 11162, 11172, 12172, 12190	\Hy@ReturnEnd . 491, 492, 493, 1933, 2032	\Hy@seminarslidesfalse . . . 8678
\Hy@pstringURI . . . 9492, 9513, 10624, 10637, 11020, 11032, 11098, 11102, 12113, 12125	\Hy@Safe@activesfalse 494, 4812, 4817, 5224, 9014	\Hy@seminarssidetrue . . . 8675
\Hy@PutCatalog 6776, 6784, 6896	\Hy@Safe@activetrue 494, 4434, 4810, 4815, 4893, 4930, 4938, 4966, 5083, 5223, 5381, 5391, 7134, 8372, 8920, 9003, 14834, 14864	\Hy@setbreaklinks . . 2906, 2910, 2922, 9180, 10311
\Hy@Raisedlink 2660, 7035, 7273, 7294, 7295, 7296, 7299, 7349, 7389, 7394, 7397, 7420, 7592, 7643, 7663, 7734, 7760, 7891, 7970, 7994, 7999, 8019, 8434, 8459, 12201, 12284, 12542, 12706, 14587, 14965, 14990, 15001, 15031, 15083	\Hy@SaveCatcodeSettings . 928, 977, 987, 1001	\Hy@SetCatcodes 181, 231, 4316
\Hy@raiselinksfalse . . 470, 8122	\Hy@saved@currentHref . . 7678, 7681	\Hy@SetNewWindow 4244, 9551, 9588, 10579, 10607, 11169, 12155, 12186
\Hy@RemoveDurPageAttr 9796, 9809	\Hy@saved@footnotemark 7786, 7801	\Hy@setouterhbox . 11842, 11873
\Hy@RemoveHidPageAttr 9819, 9831	\Hy@saved@footnotetext . 7787, 7804	\Hy@setpagesizetrue 471
\Hy@RemovePercentCr . . 4913, 4917, 4922	\Hy@saved@hook . . . 6563, 6573	\Hy@setpdfborder 3846, 9438, 9497, 9535, 9572, 9906, 10533, 10565, 10599, 10630, 10659, 11040, 11061, 11084, 11110, 11144, 11178, 11197
\Hy@RemoveTransPageAttr 9771, 9785	\Hy@saved@refstepcounter 7021, 7323	\Hy@setpdfversiontrue . . . 3039
\Hy@reserved@a 5198, 7407, 7440, 13287, 13337, 13400	\Hy@SavedSpaceFactor 2643, 2645, 2650, 2651, 2657, 12828	\Hy@setref@link . . . 8876, 8879
\Hy@RestoreCatcodes 205, 4314, 4653	\Hy@SaveLastskip . . 2681, 9406, 9952, 9967, 10049, 10061, 10318, 10900, 10916, 10991, 11004, 11503, 11517, 12441, 12455, 12721, 12735	\Hy@SlidesFormatOptionalPage . 6644, 8221, 8240, 8244
\Hy@RestoreCatcodeSettings 972, 979, 989, 1003	\Hy@SaveSavedSpaceFactor 2655, 10007, 10087, 10124, 10164, 12499, 12774	\Hy@SlidesPage 6651, 8254, 8255, 8261, 8263, 8266, 8269
\Hy@RestoreLastskip 2681, 9410, 9964, 9979, 10058, 10068,	\Hy@SaveSpaceFactor 2644, 2664, 2675, 10006, 10018, 10086, 10100, 10123, 10138, 10163, 10178, 11545, 11581, 11866, 11878, 11886, 12498, 12510, 12773, 12789, 12826, 12833	\Hy@slidetitle 8705, 8707, 8714, 8722, 8732, 8756, 8758, 8765, 8773, 8783
	\Hy@scanauthor . . . 6533, 6538	\Hy@StartlinkName . 9436, 9450
		\Hy@StepCount 482, 6691, 13080, 13143, 13352, 13595, 13659, 13943, 14010, 14722, 14727, 14803
		\Hy@stoppedearlyfalse 4323, 6941
		\Hy@stoppedearlytrue 4320, 6938
		\Hy@StringLocalhost 5321, 5322, 5337
		\Hy@tabularx@hook 7690, 7698
		\Hy@temp 713, 720, 836, 908, 1072, 1075, 1083, 1084, 2849, 2854, 2855, 2856, 2857, 2858, 2859, 3708, 3717, 3718, 3719, 3720, 3721, 3722, 3723, 3773, 3774, 3775, 3778, 3780, 3783, 3793, 3796, 3797, 3798, 3799, 3800, 3801, 3811, 3824, 3828, 3843, 3980, 3981, 4021, 4022, 4025, 4028, 4031, 4056, 4064, 4065, 4066, 4067,

4068, 4069, 4070, 4071, 4072, 4236, 4237, 4414, 4418, 4419, 4420, 4421, 4520, 4522, 4527, 4529, 4532, 4546, 4548, 4553, 4555, 4562, 4564, 4569, 4571, 4574, 4635, 4636, 5517, 5521, 5522, 5533, 5617, 5618, 5619, 5621, 5625, 5937, 5938, 5939, 5941, 5945, 5946, 6095, 6107, 6178, 6194, 6195, 6196, 6197, 6198, 6199, 6200, 6201, 6203, 6209, 6215, 6216, 6217, 6218, 6219, 6220, 6221, 6222, 6223, 6224, 6225, 6671, 6674, 6683, 6685, 6689, 6693, 6737, 6739, 7043, 7044, 7065, 7223, 7226, 7229, 7235, 7361, 7367, 7488, 7513, 7770, 7776, 8386, 8387, 8395, 8396, 8626, 8627, 9222, 9225, 9226, 9242, 9260, 9688, 9717, 9719, 10241, 10246, 10252, 10256, 10259, 10264, 10295, 10297, 10726, 10769, 10771, 11680, 11683, 11687, 11688, 11694, 11695, 11701, 11729, 11734, 11740, 11744, 11747, 11752, 11785, 11787, 11848, 11849, 11853, 11941, 11942, 11950, 11951, 12055, 12056, 12584, 12589, 12595, 12599, 12602, 12607, 12640, 12642, 14232, 14233, 14874, 14880, 14888, 14903	3291, 3293, 3295, 3296, 3298, 3302, 4899, 4900, 4911, 4915, 5084, 5088, 5210, 5212, 5924, 5925, 5965, 5966, 5969, 5973, 6720, 6722, 6760, 6762, 6907, 6909, 7458, 7460, 7461, 7464, 7465, 7466, 7848, 7853, 7858, 8332, 8333, 8351, 8352, 8358, 8692, 8693, 8744, 8745, 9985, 9986, 10881, 11029, 11030, 12473, 12474, 12752, 12753, 14605, 14606, 14629, 14631, 14650, 14651, 14659, 14683, 14685, 14686, 14688, 14689, 15072, 15097, 15102, 15105, 15108	\Hy@UseMaketitleInfos . . 6579, 9730, 10203, 10686, 11439, 11678, 12553 \Hy@UseMaketitleString . 6560, 6580, 6581 \Hy@UseNameKey 2827, 9695, 9696, 9697, 9698, 9699, 9700, 9701, 9702, 9721, 10271, 10272, 10273, 10274, 10275, 10276, 10277, 10278, 10299, 10733, 10734, 10735, 10736, 10737, 10738, 10739, 10740, 10773, 11399, 11400, 11401, 11402, 11403, 11404, 11405, 11406, 11759, 11760, 11761, 11762, 11763, 11764, 11765, 11766, 11789, 12614, 12615, 12616, 12617, 12618, 12619, 12620, 12621, 12644 \Hy@varioref@crefstepcounter 7314, 7321 \Hy@varioref@undefined . 7305, 7309, 9009 \Hy@VerboseAnchor 4963, 9407, 9953, 9968, 10050, 10062, 10319, 10901, 10917, 10992, 11005, 11504, 11518, 12442, 12456, 12722, 12736 \Hy@verbosefalse 439, 478 \Hy@VerboseGlobalTemp 4939, 4940, 4941, 4942, 4946 \Hy@VerboseLinkInfo 4946, 4947, 4950, 4957 \Hy@VerboseLinkStart 4935, 9470, 9480, 9983, 10035, 10071, 10083, 10511, 10857, 10880, 11019, 11124, 11536, 11648, 12471, 12527, 12750, 12807 \Hy@VerboseLinkStop 4951, 9455 \Hy@verbostrue 438 \Hy@VersionCheck . . 277, 4650, 20282 \Hy@VersionChecked . . 276, 319, 4647, 4649 \Hy@vt@PutCatalog 6813, 6815 \Hy@VTeXversion . . 6793, 6805, 11080, 11210, 11346, 14755 \Hy@WarnHTMLFieldOption . . . 5991, 6024, 6027, 6211 \Hy@Warning 265, 350, 516, 1845, 2765, 2780, 2805, 2885, 2993, 2998, 3245, 3625, 3677, 3756, 3819, 3838, 3974, 3982, 4033, 4080, 4088, 4199, 4762,
\Hy@temp@A 745, 746, 1905, 1907, 1918, 1920, 1925, 1926, 1929, 4057, 4059, 7060, 7063, 7064, 7065, 7066, 8548, 8549, 8550, 8557, 8585, 8586, 8587, 8596, 9223, 9234, 9235, 9236, 9237, 9240, 9245, 9248, 9274 \Hy@temp@B 1906, 1907 \Hy@temp@menu . . . 9903, 9921, 10653, 10666, 11191, 11194, 12065, 12074 \Hy@tempa 2743, 2745, 2747, 2748, 2750, 2752, 2754, 2757, 2760, 2761, 3262, 3263, 3264, 3266, 3267, 3269, 3270, 3272, 3276, 3280,	\Hy@tempb 5211, 5227, 6721, 6722, 6761, 6762, 14630, 14631, 14659 \Hy@tempcolor . . 11559, 11561, 11574, 11650, 11652, 11664 \Hy@TempPageAnchor . . 8224, 8280, 8290, 8294, 8310 \Hy@Test@Alph 7123, 7147 \Hy@Test@alph 7114, 7143 \Hy@testname 9424, 9425, 9430, 9432, 9433, 9447, 10514, 10515, 10520, 10522, 10524, 10540, 11048, 11049, 11054, 11058, 11131, 11132, 11137, 11141, 11655, 11656, 11661, 11672 \Hy@texhtfalse 472 \Hy@texhttrue 3083, 4516 \Hy@TheSlideOptionalPage 8239, 8243, 8248, 8257 \Hy@title 6526, 6530 \Hy@tocdestname . . 8374, 8376, 8383, 8391, 8398, 8402, 8404 \Hy@toclevel . . 8343, 8347, 8360 \Hy@true 2635, 2748, 2750, 3296, 3298, 5966 \Hy@typexmlfalse 475 \Hy@undefinedname 9421, 9428, 9430, 10509, 10518, 10520, 11017, 11052, 11054, 11135, 11137, 11646, 11659, 11661 \Hy@unicodfalse 476, 812, 822, 2965, 2966, 2974, 3998, 4004, 7225, 8285, 14281 \Hy@unicodetrue . . . 2966, 6841, 6855 \Hy@usehidkeyfalse 3765 \Hy@usehidkeytrue 3769	

5007, 5050, 5207, 5347,
 5574, 5929, 5992, 6100,
 6851, 6866, 8324, 8989,
 9039, 9426, 10352, 10356,
 10516, 11050, 11133, 11427,
 11433, 11657, 11978, 11987,
 14614, 14632
 \Hy@WarningNoLine 266,
 303, 2844, 2912, 3019, 3728,
 3789, 3933, 4049, 4301,
 4372, 4524, 4533, 4550,
 4566, 4575, 6507, 6616,
 6807, 6921, 7210, 8334,
 8506, 9256, 11815
 \Hy@WarningPageBorderColor .
 . . . 3786, 3788, 3790
 \Hy@WarningPageColor . 3725,
 3727, 3729
 \Hy@WarnOptionDisabled 2777,
 2779
 \Hy@WarnOptionValue . . 2758,
 2764, 3283, 3305
 \Hy@wrapper@babel 4432, 4450
 \Hy@WrapperDef . . 4442, 9402,
 9951, 9966, 10048, 10060,
 10317, 10899, 10915, 10990,
 11003, 11502, 11516, 12440,
 12454, 12720, 12734
 \Hy@writebookmark 2640, 8344,
 8712, 8720, 8730, 8763,
 8771, 8781, 14591, 14733
 \Hy@xspace@end
 . . 4335, 4340, 4344, 4349,
 4352, 4357, 4358, 4359,
 4361, 4362, 4363, 4364,
 4365, 6394, 6395, 6397,
 6400, 6402, 6403, 6404,
 6408, 6411, 6414, 6416,
 6417, 6418, 9486, 9521,
 9561, 9597, 10028, 10099,
 10114, 10137, 10153, 10177,
 10193, 10550, 10586, 10618,
 10647, 10673, 10861, 10871,
 11092, 11118, 11153, 11186,
 11205, 11876, 11884, 12509,
 12520, 12788, 12800, 12832
 \HyAnn@AbsPageLabel . . 13528,
 13535, 13576, 13662, 13684,
 13711, 13732, 13760, 13783
 \HyAnn@Count . . 13533, 13534,
 13536, 13537, 13538, 13541,
 13543, 13545
 \HyC@cmd 87, 109, 122
 \HyC@check 68, 71, 74
 \HyC@checkcommand 50, 57, 59
 \HyC@checkFailed 146, 157
 \HyC@checkItem . 132, 133, 134,
 135, 138
 \HyC@checklong 45, 53
 \HyC@checkOk 144, 154
 \HyC@checkPackage . 12, 16, 18
 \HyC@cmd . 62, 75, 87, 95, 118,
 131
 \HyC@date . . . 11, 15, 23, 29, 31
 \HyC@DeclareRobustCommand
 114
 \HyC@def 125
 \HyC@defcmd 47, 54, 93
 \HyC@doCheck 99, 130
 \HyC@edef 125
 \HyC@getDate 12, 14
 \HyC@meaning 152, 160
 \HyC@nc@default . . . 103, 105
 \HyC@nc@noopt 88, 91, 103, 112,
 123, 127
 \HyC@nc@opt 88, 101, 123
 \HyC@newcommand 86
 \HyC@next 48, 55, 60, 83
 \HyC@noValue 80, 81, 82, 85, 139
 \HyC@optcmd 107, 111
 \HyC@org@cmd 76
 \HyC@org@optcmd 80, 111
 \HyC@org@robustcmd . . 81, 120
 \HyC@org@robustoptcmd . . 82
 \HyC@package 10, 22, 28, 34, 37,
 38
 \HyC@param 78, 96, 102
 \HyC@robustcmd 115, 120, 121,
 122
 \HyC@star 67, 70, 94
 \HyC@string . 131, 152, 155, 158
 \HyC@Toks . 79, 90, 96, 106, 126
 \HyCal@do 510, 514
 \HyCal@scan 501, 505, 529
 \HyCnt@LookForParentCounter
 7047, 7059
 \HyCnt@ProvideTheHCounter . .
 7031, 7040
 \HyColor@FieldBColor . . 6159,
 6162
 \HyColor@FieldColor 6165
 \HyColor@HyperrefBorderColor
 3776, 3794
 \HyColor@HyperrefColor
 . . 3713, 3732, 3733, 3734,
 3735, 3736, 3737, 3738
 \HyColor@UseColor . 4784, 9368,
 9379, 10473, 10484
 \HyField@@AddToFields . 13463,
 13467
 \HyField@@PDFChoices . 5812,
 5813, 5828
 \HyField@@SetFlag . 5507, 5509
 \HyField@@UseFlag . 5497, 5499
 \HyField@AddToFields . . 13433,
 13462, 13580, 13675, 13689,
 13716, 13741, 13765, 13788
 \HyField@AdvanceAnnotCount .
 13888, 13918, 14015,
 14045, 14073, 14101, 14129,
 14155
 \HyField@afields . 13430, 13452,
 13453, 13455, 13490
 \HyField@AfterAuxOpen . 13443,
 13450, 13468
 \HyField@AnnotCount . . 13886,
 13889, 13892
 \HyField@AuxAddToFields
 13442, 13447, 13451, 13471
 \HyField@FlagsAnnot 5667, 5686,
 5700, 5713, 5729, 5761
 \HyField@FlagsCheckBox 5699,
 13238, 13779, 14150
 \HyField@FlagsChoice . . 5760,
 13119, 13635, 13983
 \HyField@FlagsPushButton 5685,
 13177, 13196, 13220, 13707,
 13728, 13758, 14071, 14095,
 14125
 \HyField@FlagsRadioButton . . .
 5712, 13115, 13631, 13979
 \HyField@FlagsSubmit . . 5633,
 13197, 13729, 14096
 \HyField@FlagsText 5728, 13057,
 13571, 13912
 \HyField@NeedAppearancesfalse
 5957, 5970
 \HyField@NeedAppearancetrue
 . . . 5960, 5963, 5967
 \HyField@NewBitsetFlag . 5465,
 5468, 5476
 \HyField@NewFlag . 5463, 5539,
 5540, 5541, 5542, 5543,
 5544, 5545, 5546, 5547,
 5548, 5549, 5550, 5551,
 5552, 5553, 5554, 5555,
 5556, 5557, 5558, 5563,
 5564, 5565, 5566, 5567,
 5568, 5569, 5570, 5571,
 5604, 5606, 5607, 5609,
 5610, 5612, 5613, 5614, 5615
 \HyField@NewFlagOnly . 5467,
 5605, 5608, 5611
 \HyField@NewOption 5464, 5470
 \HyField@PDFAFlagWarning . .
 . . 5573, 5581, 5585, 5589,
 5593, 5597, 5601
 \HyField@PDFChoices . . 5785,
 13156, 13682, 14039

\HyField@PrintFlags	\HyInfo@AddonUnsupportedtrue	\HyOrg@appendix
.. 5514, 5660, 5678, 5692,	.. 10201, 11425, 12551	\HyOrg@author 6523, 6536, 6540
5705, 5721, 5753, 5778	\HyInfo@do 4077, 4104, 4127	\HyOrg@elt 7045, 7051
\HyField@SetFlag 5506, 5646,	\HyInfo@GenerateAddons 4121,	\HyOrg@float@makebox 7905,
5652, 5657, 5691, 5719	9731, 10687, 11679	7926
\HyField@SetKeys 5889, 13054,	\HyInfo@Key	\HyOrg@hyperpage 8524, 8526,
13086, 13089, 13108, 13165,	.. 4085, 4086, 4094, 4099,	8527
13193, 13210, 13235, 13567,	4104, 4107, 4114, 4128, 4132	\HyOrg@languageshorthands
13601, 13604, 13623, 13694,	\HyInfo@KeyEscaped 4084, 4085	. 1043, 1057, 1068, 1078
13725, 13748, 13775, 13908,	\HyInfo@trapped@false 4025,	\HyOrg@make@df@tag@@ 8449
13949, 13952, 13971, 14057,	4044	\HyOrg@make@df@tag@@@ 8450
14092, 14115, 14146	\HyInfo@trapped@true 4022, 4043	\HyOrg@maketitle 7784, 7791,
\HyField@TheAnnotCount 13891,	\HyInfo@trapped@unknown 4028,	7796
13923, 13928, 14020, 14032,	4045	\HyOrg@subequations 7475, 7482
14047, 14052, 14078, 14084,	\HyInfo@TrappedUnsupported	\HyOrg@title 6522, 6527, 6531
14103, 14108, 14131, 14136,	. 4046, 4050, 10204, 11440,	\HyOrg@TX@endtabularx 7689
14160, 14165	12554	\HyOrg@url 5063
\HyField@UseFlag	\HyInfo@Value 4098, 4100	\HyPat@NonNegativeReal
.. 5496, 5637, 5638, 5639,	\HyLang@addto 3517, 3533, 3551,	.. 3814, 3815, 3816, 3817,
5640, 5641, 5642, 5643,	3584, 3592	3833, 3835, 4180, 4190,
5644, 5647, 5648, 5649,	\HyLang@afrikaans 3315	4191, 4192, 4194, 4195, 4196
5650, 5653, 5654, 5655,	\HyLang@DeclareLang	\HyPat@ObjRef 5047, 5048, 5061,
5658, 5669, 5670, 5671,	.. 3531, 3560, 3561, 3562,	9181, 10312, 11499
5672, 5673, 5674, 5675,	3563, 3564, 3565, 3566,	\hyper@@@anchor 4356, 5073, 5075,
5676, 5677, 5688, 5689,	3567, 3568, 3569, 3570,	5106, 5108, 5143, 5145,
5690, 5702, 5703, 5704,	3571, 3572, 3573, 3574,	5344, 6395, 6410, 6426,
5715, 5716, 5717, 5718,	3575, 3576, 3577, 3578,	7639, 7644, 7659, 7664,
5720, 5731, 5732, 5733,	3579, 3580, 3581, 3582	7732, 7735, 7761, 7889,
5734, 5735, 5736, 5737,	\HyLang@english 3333	7892, 7909, 8225, 8280,
5738, 5749, 5752, 5763,	\HyLang@french 3351	8290, 8295, 8711, 8719,
5764, 5765, 5766, 5768,	\HyLang@german 3369	8729, 8762, 8770, 8780
5770, 5771, 5774, 5777	\HyLang@italian 3387	\hyper@Qlink 4933, 4991, 5096,
\HyInd@@@wrindex 8544, 8547,	\HyLang@magyar 3405	5124, 5198, 7978, 8124,
8578, 8584	\HyLang@portuges 3423	8125, 8126, 8174, 8176,
\HyInd@@hyperpage 8624, 8634	\HyLang@russian 3441	8178, 8881, 8896, 8999
\HyInd@@wrindex 8539, 8540	\HyLang@spanish 3481	\hyper@@normalise 4902, 4906,
\HyInd@EncapChar 3313, 4311,	\HyLang@vietnamese 3499, 3584,	4910
8534	3592	\hyper@anchor
\HyInd@hyperpage 8621, 8623,	\HyLinguex@OrgB 910, 914	.. 5371, 6398, 6412, 6476,
8630	\HyLinguex@OrgC 911, 915	6489, 9458, 9951, 10048,
\HyInd@org@wrindex 8538, 8542,	\HyLinguex@OrgD 912, 916	10375, 10915, 10990, 11502,
8552, 8558, 8560, 8563	\HyLinguex@Restore 913, 926,	12440, 12720
\HyInd@pagelink 8639, 8645,	980, 990	\hyper@anchorend 4344, 4352,
8647, 8650	\HyNew@float@makebox 7904,	4359, 6382, 6400, 6414,
\HyInd@ParenLeft 8521, 8549,	7927	6429, 7036, 7275, 7350,
8586	\HyOpt@CheckDvi	7395, 7397, 7421, 7447,
\HyInd@ParenRight 8522, 8550,	.. 3071, 3107, 3112, 3117,	7596, 7972, 7997, 8000,
8557, 8587, 8596	3140, 3145, 3150, 3202,	8020, 8153, 8434, 8460,
\HyInd@removespaces 8653, 8656,	3209, 3214, 3219, 3224	9465, 9976, 10066, 10382,
8666	\HyOpt@CustomDriver 301,	10910, 11012, 11524, 12464,
\HyInfo@AddonHandler 4075,	3240, 3243, 4585, 4644	12743, 14587, 14734, 14966,
4078	\HyOpt@DriverFallback 3228,	14991, 15002, 15032, 15084
\HyInfo@AddonList 4102, 4103,	3231, 3232, 3236, 4612, 4617	\hyper@anchorstart
4137, 4144	\HyOpt@DriverType 4584, 4587,	.. 4358, 6382, 6399, 6413,
\HyInfo@Addons 4123, 4139,	4614, 4624, 4626, 4643, 4646	6428, 7036, 7274, 7350,
9754, 10711, 11710, 11714	\HyOrg@addtoreset 8464, 8466,	7389, 7421, 7447, 7593,
	8493	7970, 7995, 8000, 8020,

8153, 8434, 8460, 9461,
 9966, 10060, 10378, 10899,
 11003, 11516, 12454, 12734,
 14587, 14734, 14966, 14991,
 15002, 15032, 15084
 \hyper@chars . 4927, 9493, 9956,
 9970, 9990, 10012, 10026,
 10040, 10120, 10160, 10866,
 10887, 10903, 10920, 10995,
 11007, 11099, 12114, 12458,
 12478, 12504, 12518, 12532,
 12738, 12757, 12780, 12797,
 12812
 \hyper@currentanchor . . 11521,
 11530, 11553, 11570
 \hyper@currentlinktype . . 11554,
 11558, 11562
 \hyper@destlabel@hook . . 5387,
 5394
 \hyper@hash . 4879, 4880, 4928,
 5267, 5279, 5296, 5299,
 6349, 10860
 \hyper@image 5069, 5070, 10038,
 11157, 11643, 12530, 12810
 \hyper@last 6496, 6501
 \hyper@link . . 4357, 5215, 6396,
 6397, 6411, 6421, 6427,
 9479, 10034, 10082, 10549,
 10856, 11123, 11647, 12526,
 12806
 \hyper@link@ . 4364, 5199, 5205,
 6394, 6408, 6434
 \hyper@linkend 4344, 4352, 4361,
 6402, 6416, 6431, 7684,
 7964, 7967, 8383, 8391,
 8398, 8402, 8404, 9478,
 9996, 10079, 10548, 10550,
 10892, 11070, 11556, 12486,
 12763
 \hyper@linkfile
 . . 4363, 5292, 6404, 6418,
 6433, 9525, 10000, 10158,
 10552, 10876, 11074, 12135,
 12490, 12767
 \hyper@linkstart
 . . 4360, 6401, 6415, 6430,
 7682, 7960, 7967, 8383,
 8391, 8398, 8402, 8404,
 9469, 9982, 10070, 10510,
 10550, 10879, 11018, 11535,
 12470, 12749
 \hyper@linkurl
 . . 4362, 5068, 5267, 5274,
 5295, 5299, 6403, 6417,
 6432, 9490, 10001, 10003,
 10036, 10118, 10621, 10864,
 10877, 11096, 11158, 11644,
 12111, 12491, 12495, 12528,
 12768, 12770, 12808
 \hyper@livelink 6396, 6421
 \hyper@makecurrent 7032, 7132,
 7336, 7387, 7418, 7446,
 7538, 7569, 7679, 7865, 7919
 \hyper@n@rmalise . . 4894, 4898
 \hyper@nat@current 7961
 \hyper@nat@anchorend . . . 7972
 \hyper@nat@anchorstart . . 7969
 \hyper@nat@linkbreak 7966
 \hyper@nat@linkend 7963
 \hyper@nat@linkstart 7958
 \hyper@newdestlabel 5379, 5401,
 5440, 5445
 \hyper@normalise . . 4312, 4317,
 4871, 4981, 4984, 5065,
 5067, 5069, 5090, 5919
 \hyper@pageduration 9792, 9841,
 10798, 10818, 11323, 11340,
 11610, 11640
 \hyper@pagehidden . 9816, 9842,
 10809, 10819, 11333, 11341,
 11627, 11641
 \hyper@pagetransition 9768, 9840,
 10787, 10817, 11212, 11339,
 11593, 11639
 \hyper@quote 6351, 9958, 9972,
 9987, 9992, 10013, 10027,
 10041, 10860, 10870, 10883,
 10906, 10924, 12446, 12460,
 12475, 12481, 12505, 12519,
 12533, 12726, 12739, 12754,
 12759, 12782, 12798, 12813
 \hyper@readexternallink . 5220,
 5232
 \hyper@refstepcounter . . . 7012,
 7015, 7023
 \hyper@tilde . 4888, 4889, 4890,
 6350
 \hyperbaseurl . 3740, 3741, 6445
 \hypercalcbp 496, 496
 \hypercalcbpdef . 498, 535, 4177,
 4187
 \hyperdef 5098, 6447
 \HyperDestLabelReplace . 5431,
 5438, 5441
 \HyperDestNameFilter
 4293, 4967, 5438,
 9408, 9433, 9958, 9972,
 9992, 10036, 10321, 10523,
 10860, 10870, 10888, 10906,
 10924, 10996, 11008, 11057,
 11140, 11975, 11984, 12446,
 12460, 12481, 12528, 12726,
 12739, 12759, 12808, 14812,
 14876, 14892
 \HyperDestRename . 5411, 5429,
 5442
 \HyperFirstAtBeginDocument . .
 . 6473, 6475, 6497, 6500
 \hypergetpageref 7268
 \hypergetref 7267
 \HyperGlobalCurrentHref 7153,
 7155, 7163, 7164, 7168,
 7171, 7175, 7181, 7182, 7186
 \hyperimage . . 5069, 5447, 8516
 \hyperindexformat 8523
 \hyperlink . . . 4932, 6448, 8662,
 8801, 8809, 8824, 8832,
 8842, 8850, 8857
 \hyperlinkfileprefix . 3743, 3744,
 3745, 12712
 \HyperLocalCurrentHref
 . . 7171, 7173, 7179, 7180,
 7181, 7182, 7184
 \hyperpage . . 6454, 8524, 8525,
 8527, 8620
 \HyperRaiseLinkDefault . 2642,
 2669
 \HyperRaiseLinkHook 2641, 2670
 \HyperRaiseLinkLength . . 2668,
 2669, 2672
 \hyperref 5078, 5454, 5455, 6450,
 8956, 8960, 8970, 8984
 \hypersetup . . 2986, 3030, 3569,
 4061, 4313, 6444
 \hypertarget 5071, 6449
 \HyPL@@@CheckThePage 6741,
 6759
 \HyPL@@CheckThePage . 6717,
 6719
 \HyPL@Alph 6636
 \HyPL@alph 6637
 \HyPL@arabic 6633
 \HyPL@CheckThePage . . 6668,
 6716
 \HyPL@Entry 6909, 6917, 6925,
 6927
 \HyPL@EveryPage . 6656, 6780
 \HyPL@Format 6732, 6733, 6734,
 6735, 6736, 6748
 \HyPL@found 6731, 6738, 6742,
 6749, 6759, 6761
 \HyPL@Labels 6627, 6771, 6772,
 6774, 6776, 6827, 6828,
 6920, 6928, 6929
 \HyPL@LastNumber 6631, 6687,
 6710
 \HyPL@LastPrefix . . 6632, 6681,
 6712
 \HyPL@LastType . . 6630, 6672,
 6711

\HyPL@page . 6650, 6659, 6662, 6668, 6677
\HyPL@Prefix 6677, 6679, 6681, 6695, 6698, 6700, 6712, 6726, 6764
\HyPL@Roman 6634
\HyPL@roman 6635
\HyPL@SetPageLabels . . . 6770, 6835, 6923
\HyPL@SlidesOptionalPage 6643, 6647, 6652
\HyPL@SlidesSetPage 6638, 6640, 6660, 6667
\HyPL@StorePageLabel . . 6695, 6697, 6767, 6825, 6904
\HyPL@thisLabel . . 6624, 6626, 6658, 6662, 6663
\HyPL@Type . 6665, 6672, 6676, 6694, 6702, 6711, 6725, 6763
\HyPL@Useless 6768, 6774
\HyPsd@@@autoref . 1766, 1768, 1771
\HyPsd@@@CJKdigits . . . 1636, 1639, 1647
\HyPsd@@@nameref 1748, 1750, 1753
\HyPsd@@@pageref . 1730, 1732, 1735
\HyPsd@@@ref . 1714, 1716, 1719
\HyPsd@@@UTFviii@four 2384, 2387
\HyPsd@@AppendItalcorr . 1935
\HyPsd@@autoref . . 1763, 1764
\HyPsd@@autorefname . . 1784, 1787
\HyPsd@@CJKdigits 1628, 1630, 1633
\HyPsd@@CJKnumber 1529, 1531, 1534, 1587, 1602, 1615, 1617, 1621
\HyPsd@@ConvertToUnicode 2263
\HyPsd@@ding 2522, 2526, 2537
\HyPsd@@GetNextTwoTokens 2261
\HyPsd@@GlyphProcessWarning 2121, 2124
\HyPsd@@GreekNum 1191, 1200, 1299, 1303, 1307
\HyPsd@@hspace . . . 1684, 1685
\HyPsd@@LetCommand . 1808, 1829
\HyPsd@@nameref . . 1745, 1746
\HyPsd@@pageref . . 1727, 1728
\HyPsd@@ProtectSpacesFi 1857, 1861, 1879, 1885, 1890
\HyPsd@@ref 1711, 1712
\HyPsd@@RemoveBraces . . 1903
\HyPsd@@RemoveBracesFi 1900, 1903
\HyPsd@@RemoveCmdPrefix 2078, 2081
\HyPsd@@ReplaceFi 2148, 2154, 2159
\HyPsd@@UTFviii@four . . 2368, 2373
\HyPsd@add@accent . 558, 1673
\HyPsd@AfterCountRemove 1955, 2035
\HyPsd@AfterDimenRemove 1961, 2038
\HyPsd@AfterSkipRemove 1967, 2050
\HyPsd@AMScsclassfix . 667, 1694, 1696
\HyPsd@AppendItalcorr . 1919, 1926, 1935
\HyPsd@autoref 677, 1763
\HyPsd@autorefname 1775, 1781
\HyPsd@babel@danish . . . 1087
\HyPsd@babel@dutch . . . 1093
\HyPsd@babel@finnish . . . 1099
\HyPsd@babel@frenchb . . . 1104
\HyPsd@babel@german . . . 1109
\HyPsd@babel@macedonian 1116
\HyPsd@babel@ngerman . . 1122
\HyPsd@babel@portuges . . 1128
\HyPsd@babel@russian . . . 1133
\HyPsd@babel@slovene . . . 1139
\HyPsd@babel@spanish . . . 1144
\HyPsd@babel@swedish . . . 1154
\HyPsd@babel@ukrainian . . 1160
\HyPsd@babel@usorbian . . 1166
\HyPsd@BabelPatch . 653, 1042, 1077
\HyPsd@CatcodeWarning 1971, 1995, 1998, 2001, 2004, 2062
\HyPsd@Char 2265
\HyPsd@CharOctByte . . . 2285, 2287, 2290, 2299, 2304
\HyPsd@CharSurrogate . . 2279, 2296
\HyPsd@CharTwoByte . . 2277, 2284
\HyPsd@CheckCatcodes . . 731, 1945
\HyPsd@CJK@Unicode . . 1411, 1415
\HyPsd@CJKActiveChars 1351, 1366
\HyPsd@CJKdigit . . 1640, 1650
\HyPsd@CJKdigits . 1413, 1626
\HyPsd@CJKhook . . . 684, 1322, 1333
\HyPsd@CJKhook@bookmarks 1328, 1362
\HyPsd@CJKhook@unicode 1330, 1410
\HyPsd@CJKnumber 1412, 1526
\HyPsd@CJKnumberFour 1544, 1548, 1552, 1565, 1569, 1573, 1579
\HyPsd@CJKnumberLarge 1557, 1564
\HyPsd@CJKnumberThree 1585, 1589, 1595
\HyPsd@CJKnumberTwo 1600, 1604, 1610
\HyPsd@ConvertToUnicode 800, 2211
\HyPsd@DecimalToOctal . 1343, 1374
\HyPsd@DecimalToOctalFirst 1417, 1453
\HyPsd@DecimalToOctalSecond 1418, 1427, 1490, 2541, 2547, 2550
\HyPsd@DefCommand 714, 715, 716, 717, 1797
\HyPsd@DieFace . 631, 632, 633, 2462, 21155, 21156
\HyPsd@DieFaceLarge 2470, 2479
\HyPsd@ding 630, 2512
\HyPsd@DisableCommands 1024, 1026
\HyPsd@DoConvert . 2213, 2223
\HyPsd@DoEscape 2237
\HyPsd@doxspace . . . 772, 2184
\HyPsd@empty . . 757, 759, 763, 764, 766, 774, 781
\HyPsd@end 731, 735, 1858, 1861, 1864, 1867, 1870, 1883, 1893, 1900, 1903, 1948, 1956, 1962, 1968, 2021, 2028, 2035, 2038, 2050
\HyPsd@endWithElse 1663, 1672
\HyPsd@EscapeTeX . . 811, 821, 2166
\HyPsd@fi 1875, 1881, 1885, 1891
\HyPsd@GetNextTwoTokens 2261
\HyPsd@GetOneByte 2256
\HyPsd@GetTwoBytes . . . 2252
\HyPsd@GLYPHERR 737, 1660, 1674, 1681
\HyPsd@GlyphProcess 739, 2109, 2122
\HyPsd@GlyphProcessWarning 2116, 2120
\HyPsd@GobbleFiFi 1665, 1671

\HyPsd@GreekNum . 1180, 1183, 1185	\HyPsd@pdfencoding@unicode . . . 2976, 3008, 6842, 6860	\HyPsd@tocsection 1697, 1698, 1699, 1700, 1701, 1702, 1703, 1705
\HyPsd@Greeknumeral . . 1176, 1182	\HyPsd@PrerenderUnicode 3943, 3959, 3965, 3971, 3993, 4011, 4017, 4097	\HyPsd@UnescapedString . 806, 855, 856, 862
\HyPsd@greeknumeral 1175, 1179	\HyPsd@protected@testopt 703, 704, 1838	\HyPsd@UnexpandableSpace 1680, 1866, 1890, 2041, 2053
\HyPsd@GreekNumI 1203, 1229, 1272, 1298	\HyPsd@ProtectSpaces 724, 1855, 1876, 1925	\HyPsd@unichar . . . 2326, 2393, 2399, 2404
\HyPsd@GreekNumII 1207, 1251, 1295, 1302	\HyPsd@ref 674, 1711	\HyPsd@unichar@first@byte 2412, 2432
\HyPsd@GreekNumIII . . . 1210, 1274, 1306	\HyPsd@RemoveBraces . . . 726, 1897, 1914, 1922, 1928	\HyPsd@unichar@octtwo . 2434, 2442, 2448
\HyPsd@GreekNumIV 1219, 1297	\HyPsd@RemoveCmdPrefix 2071, 2077	\HyPsd@unichar@second@byte 2420, 2440
\HyPsd@GreekNumV 1222, 1301	\HyPsd@RemoveMask 734, 1864, 1870, 1883, 1893	\HyPsd@UnicodeReplace- mentCharacter 2396, 2431, 2465, 2495, 2500, 2508, 2515, 2518, 2528, 2586
\HyPsd@GreekNumVI 1224, 1305	\HyPsd@RemoveSpaceWarning 2045, 2057, 2083	\HyPsd@utf@viii@undeferr . 554, 2454
\HyPsd@GreekPatch . 650, 1172, 1174	\HyPsd@ReplaceSpaceWarning 2040, 2052, 2096	\HyPsd@UTFviii 548, 2314, 2319
\HyPsd@HighA 1421, 1430	\HyPsd@Rest 1949, 2017, 2025, 2028, 2036, 2041, 2047, 2053, 2059	\HyPsd@UTFviii@@three . 2349, 2358
\HyPsd@HighB 1431, 1436	\HyPsd@RussianPatch 652, 1315	\HyPsd@UTFviii@@two . . 2334, 2340
\HyPsd@HighC 1437, 1440	\HyPsd@SanitizeForOutFile 14651, 14682	\HyPsd@UTFviii@ccxliv@def 2324, 2330
\HyPsd@HighD 1433, 1445	\HyPsd@SanitizeOut@BraceLeft . . . 14686, 14692, 14701	\HyPsd@UTFviii@ccxliv@undef 2323, 2329
\HyPsd@href 672, 1710	\HyPsd@SanitizeOut@BraceRight . . . 14689, 14704, 14713	\HyPsd@UTFviii@four 2322, 2367
\HyPsd@hspace 668, 1684	\HyPsd@SPACEOPTI . 728, 744, 745, 747, 749, 751, 752, 791, 793, 1991, 2195	\HyPsd@UTFviii@three . . 2321, 2348
\HyPsd@hspacetest . 1687, 1689, 1692	\HyPsd@spaceopti . . . 793, 2140	\HyPsd@UTFviii@two 2320, 2333
\HyPsd@ifnextchar 700, 701, 702, 1834	\HyPsd@SpanishPatch 651, 1309	\HyPsd@Warning . . 1842, 2063, 2084, 2097, 2126, 2132
\HyPsd@ignorespaces 681, 1033	\HyPsd@String 725, 727, 730, 732, 738, 740, 1908, 1909, 1919, 1979, 1981, 1985, 1986, 1990, 1991, 2006, 2007, 2039, 2051, 2110, 2111	\HyPsd@XeTeXBigCharsfalse 828, 842, 847
\HyPsd@inmathwarn . 557, 1657	\HyPsd@StringSubst . . 741, 743, 749, 755, 758, 761, 764, 783, 786, 788, 2163	\HyPsd@XeTeXBigCharstrue 841, 850, 3958, 3964, 3970, 3992, 4010, 4016, 4096, 14284, 14649
\HyPsd@ITALCORR . . 692, 696, 1681	\HyPsd@Subst 737, 746, 750, 756, 762, 766, 770, 775, 776, 777, 778, 779, 780, 784, 787, 2147, 2164, 2179, 2180, 2181	\HyPsd@XSPACE 694, 771, 1681
\HyPsd@langshort@system 1048, 1051	\HyPsd@temp 804, 806, 807, 809, 810, 817, 819, 820, 2971, 2972, 2973, 2976, 2979, 2985, 2997, 3001, 6859, 6860, 6861, 6863, 6864, 6869	\HyPsd@xspace . . 769, 771, 772
\HyPsd@LanguageShorthands 1044, 1049, 1061	\HyPsd@ToBigChar 861, 862, 871	\HyRef@@StarSetRef 8924, 8929
\HyPsd@LetCommand 718, 719, 1797	\HyPsd@ToBigChars . . 814, 853	\HyRef@autopageref 8981, 8983
\HyPsd@LetUnexpandableSpace . 687, 688, 689, 690, 1677, 1680		\HyRef@autopagerefname 8980, 8984, 8986
\HyPsd@LoadExtra . . . 995, 998, 3028		\HyRef@autoref . . . 8999, 9001
\HyPsd@LoadStringEnc . . 2990, 3010, 3012, 3016, 3018, 6846		\HyRef@autosetref . . 9004, 9007
\HyPsd@LoadUnicode 985, 2949, 2955, 2957, 2964, 6840		\HyRef@CaseStar . . 9068, 9074
\HyPsd@MoonPha . . 2493, 2511, 21157		\HyRef@currentHtag 9020, 9038, 9041, 9047, 9054, 9060, 9075
\HyPsd@nameref 676, 1745		\HyRef@MakeUppercaseFirstOf- Five 8947, 8949
\HyPsd@pageref 675, 1727		
\HyPsd@pdfencoding 801, 2948, 2951, 2973, 2985, 2988, 2989, 2994, 3009, 6842, 6844, 6861, 6864		
\HyPsd@pdfencoding@auto 801, 2979, 2989, 3006, 6844, 6863		
\HyPsd@pdfencoding@pdfdoc 2972, 2994, 3007		

`\HyRef@name` 9036, 9037, 9042, 9049, 9067, 9068, 9069, 9071
`\HyRef@Ref` 8953, 8955
`\HyRef@ShowKeysInit` . . . 9077, 9090, 9094
`\HyRef@ShowKeysRef` 9008, 9076
`\HyRef@StarSetRef` . 8918, 8936, 8939, 8942, 8947
`\HyRef@StripStar` . . 9035, 9066
`\HyRef@testrestype` . 9013, 9032
`\HyRef@thisref` 9010, 9013
`\HyTmp@found` 5839, 5849, 5852
`\HyTmp@key` 5833, 5834
`\HyTmp@optitem` . . 5789, 5805, 5832, 5837, 5843, 5864, 5875
`\HyTmp@optlist`
. . 5788, 5803, 5804, 5835, 5836, 5841, 5842, 5850, 5851, 5871, 5873, 5880, 5883
`\HyXeTeX@CheckUnicode` 3929, 3940, 3957, 3963, 3969, 3991, 4009, 4015, 4095, 6874

I

`\i` . . . 15271, 15435, 15438, 15441, 15444, 15708, 15882, 15885, 15888, 15891, 16020, 16025, 16030, 16035, 16039, 16276, 16341, 16347
`\ibar` 16498, 21226
`\if` 1706, 2629, 6685, 6693, 7464, 7465, 11286, 11289, 11293, 11297, 11301, 11303, 11305, 14332
`\if@eqnstar` 7402, 7410
`\if@filesw` 2597, 5136, 5399, 6466, 6511, 6905, 6915, 7217, 8007, 8022, 8038, 8050, 8080, 8103, 8130, 8135, 8154, 8572, 13445, 13469, 14652, 14839, 14921
`\if@hyper@item` 6997, 7010
`\if@inlabel` 7582
`\if@Localurl` 10847, 10893
`\if@mid@expandable` 666
`\if@minipage` 7877, 7949
`\if@nmbrlist` 6982
`\if@nobreak` 7601
`\if@skiphyperref` . . . 6998, 7008
`\if@twocolumn` 15086
`\if@twoside` 15075
`\ifcase` 343, 1236, 1258, 1281, 1375, 1424, 1446, 1449, 1455, 1491, 1535, 1651, 2362, 2494, 2976, 3674, 4649, 5635, 5740, 5869, 5946, 7115, 7124, 8379, 8549, 8586, 8816, 9009, 11359, 11861, 14392, 14420, 14489, 14525, 14561, 14759
`\ifcat` 1950, 1977, 1984, 1989, 1994, 1997, 2000, 2003, 5355, 5357
`\ifdim` . . 1692, 2039, 2043, 2051, 2055, 2684, 2703, 4298, 4677, 9860, 9864, 9869, 9873, 9880, 9883, 9887, 9890, 10827, 10828, 10833, 10834, 10966, 10969, 10973, 10976, 11890, 11904, 12265, 12266, 12271, 12272, 13082, 13120, 13121, 13597, 13636, 13637, 13945, 13984, 13985
`\ifetex@unexpanded` 1849
`\iffalse` 848, 5958
`\ifFileExists` . . 232, 3242, 6506, 9247, 12840
`\ifFld@checked` . . . 5892, 13407, 14378
`\ifFld@comb` 5739
`\ifFld@combo` 5767, 5772, 13095, 13124, 13610, 13640, 13958, 13988
`\ifFld@disabled` 5893, 13408
`\ifFld@edit` 5773
`\ifFld@fileselect` 5742
`\ifFld@hidden` . . . 13058, 13109, 13178, 13198, 13221, 13239, 13306, 13318, 13328, 13411, 13572, 13625, 13708, 13730, 13759, 13780, 13913, 13973, 14072, 14097, 14126, 14151
`\ifFld@multiline` . . . 5740, 13047, 13313, 13560, 13901
`\ifFld@multiselect` 5811
`\ifFld@password` . . . 5741, 13294
`\ifFld@popdown` . . 5559, 13096, 13611, 13959
`\ifFld@radio` 13092, 13114, 13343, 13607, 13630, 13955, 13978
`\ifFld@readonly` . . 13315, 13325, 13409
`\ifForm@html` 5913
`\ifhmode` 2645, 2649, 2702, 2711, 4973, 7489, 7515, 7548, 7676, 7685, 7835, 7837, 9403, 9411, 11896, 12825
`\ifHy@activeanchor` . . 394, 5368
`\ifHy@backref` . 395, 4475, 4854, 6329, 8131, 8167
`\ifHy@bookmarks` . . . 396, 4702
`\ifHy@bookmarksnumbered` 397, 8704, 8755, 14638
`\ifHy@bookmarksopen` 398, 4692
`\ifHy@breaklinks` 399, 2911, 11537, 11578, 11872, 11895
`\ifHy@CJKbookmarks` 401, 1327
`\ifHy@colorlinks` 402, 4773, 6334, 12427
`\ifHy@destlabel` 403, 5378
`\ifHy@draft` 404, 4355
`\ifHy@dviMode` 3052, 3072, 3230
`\ifHy@dviPDFmxOutlineOpen` 4675, 14894
`\ifHy@frenchlinks` . . . 410, 4789
`\ifHy@href@ismap` . . 5029, 9514, 10638, 11033, 11103, 12126
`\ifHy@hyperfigures` . . 408, 4455, 6314, 8513
`\ifHy@hyperfootnotes` 411, 7608
`\ifHy@hyperindex` . . . 412, 4465, 6324, 8520
`\ifHy@hypertexnames` 413, 7139, 7221, 8278, 8709, 8760
`\ifHy@implicit` . 414, 4487, 14949
`\ifHy@linktocpage` . . . 415, 2868, 2878
`\ifHy@localanchorname` . . . 416, 7172, 7183
`\ifHy@naturalnames` . 418, 7151, 8710, 8761
`\ifHy@nesting` . 419, 4460, 5072, 5105, 5142, 5353, 6319, 7633, 7653, 7731, 7888
`\ifHy@next` . . . 1085, 4429, 8537
`\ifHy@ocgcolorlinks`
. . . 422, 3624, 4759, 4769, 6339, 9200, 9286, 9364, 9372, 10386, 10469, 10477
`\ifHy@pageanchor` . . . 423, 7208, 7220, 7235, 8277
`\ifHy@pdfa` 442, 4379, 4761, 5255, 5572, 6182, 6231, 6344, 9437, 9509, 9547, 9584, 9918, 10532, 10564, 10598, 10629, 10658, 11039, 11060, 11083, 11109, 11143, 11177, 11196, 11999, 13015, 13168, 13214, 13498, 13698, 13752, 13870, 14061, 14119, 14334, 14381, 14550
`\ifHy@pdfcenterwindow` . . . 400, 9693, 10269, 10731, 11397, 11757, 12612
`\ifHy@pdfdisplaydoctitle` . . 441, 9694, 10270, 10732, 11398, 11758, 12613
`\ifHy@pdfescapeform` 407, 14228, 14258
`\ifHy@pdffitwindow` . . 409, 9692, 10268, 10730, 11396, 11756,

12611		
\ifHy@pdfmarkerror	11804, 11812	
\ifHy@pdfmenubar	417, 9690, 10266, 10728, 11394, 11754, 12609	
\ifHy@pdfnewwindow	421, 4247, 11080	
\ifHy@pdfnewwindowset	420, 4245	
\ifHy@pdfpagehidden	425, 3768, 9820, 10812, 11335, 11633	
\ifHy@pdfpagelabels	424, 6612, 6825, 6903	
\ifHy@pdfstring	426, 1009, 7002	
\ifHy@pdftoolbar	434, 9689, 10265, 10727, 11393, 11753, 12608	
\ifHy@pdfusetitle	436, 6521	
\ifHy@pdfwindowui	440, 9691, 10267, 10729, 11395, 11755, 12610	
\ifHy@plainpages	427, 4470, 7222, 8279	
\ifHy@psdextra	433, 639, 999	
\ifHy@psize	428	
\ifHy@raiselinks	429, 10005, 10085, 10122, 10162, 12497, 12772	
\ifHy@seminarslides	430	
\ifHy@setpagesize	431, 9848, 10824, 10963, 12262	
\ifHy@setpdfversion	3031, 9205	
\ifHy@stoppedearly	392	
\ifHy@texht	432, 4542, 4801, 4849, 5983, 6015, 6202, 6226, 6382, 8864	
\ifHy@typexml	393, 4480, 4776, 4820, 6467, 14843, 14925	
\ifHy@unicode	435, 544, 577, 580, 640, 742, 754, 782, 790, 799, 1186, 1346, 2065, 2086, 2099, 2128, 2134, 2394, 2463, 2513, 2947, 2987, 3931, 6849, 14280	
\ifHy@useHidKey	3764, 9817, 10810, 11334, 11628	
\ifHy@verbose	437, 4936, 4952, 4964, 5515, 8349, 9209	
\ifHyField@NeedAppearances	5956, 5958, 5961, 13017, 13500, 13872	
\ifHyInfo@AddonUnsupported	4073, 4087, 4122	
\IfHyperBoolean	2733	
\IfHyperBooleanExists	2727, 2734	
\ifHyPsd@XeTeXBigChars	846, 848, 851, 854	
\ifin@	7067	
\ifmeasuring@	7022, 7033	
\ifmmode	11540, 11867	
\ifnum	244, 878, 881, 884, 887, 890, 1062, 1187, 1190, 1201, 1202, 1206, 1214, 1218, 1221, 1231, 1253, 1276, 1416, 1527, 1543, 1547, 1567, 1580, 1583, 1596, 1598, 1611, 1613, 1619, 2273, 2276, 2352, 2395, 2398, 2410, 2464, 2467, 2480, 2514, 2517, 2520, 2524, 2539, 2543, 2546, 2650, 3157, 3160, 3186, 3675, 3676, 4686, 4693, 5006, 5794, 5865, 5876, 6642, 6666, 6687, 6703, 6805, 7094, 7097, 8227, 8237, 8818, 8856, 9201, 9206, 9220, 9224, 9229, 9246, 9266, 9609, 9616, 9622, 9630, 10498, 10503, 11080, 11210, 11346, 11354, 11356, 11357, 11367, 11370, 11468, 11470, 11590, 12289, 13482, 13674, 14014, 14019, 14030, 14279, 14361, 14392, 14397, 14420, 14426, 14455, 14489, 14495, 14514, 14525, 14530, 14561, 14566, 14595, 14611, 14755, 14825, 14828, 14855, 14858, 14896, 15005, 15023, 15038	
\ifodd	2376, 2381, 8304	
\ifpdf	242, 3054, 3097, 4521, 4589	
\ifpdfstringunicode	549, 552	
\ifportrait	9859	
\ifthenelse	8157	
\iftrue	851, 1856, 1878, 2158, 5961, 15007	
\ifvmode	2661, 2683, 2692	
\ifvoid	7343, 7347, 7586	
\ifvtex	3060, 3156, 3185	
\ifvtexdvi	3061	
\ifvtexhtml	4563, 4595	
\ifvtexpdf	4606	
\ifvtexps	4609	
\ifxetex	805, 838, 3057, 3130, 3930, 3973, 4547, 4592, 4676, 5150	
\ignorespaces	681, 7303, 7484, 7767, 7873, 7884, 7887, 7945, 7953, 8015, 8030, 8046, 8055, 8165, 8689, 8741	
\iint	18446, 20577	
\inferior	20382	
\iint	18444, 20576	
\IJ	15267, 16041	
\ij	15478, 16043	
\Im	18082, 20449	
\immediate	6468, 6469, 6470, 6472, 6513, 6818, 6908, 6916, 7232, 7260, 8010, 8025, 8041, 8051, 8081, 8104, 8130, 8160, 9288, 9303, 9318, 11473, 12286, 13424, 13446, 13488, 14745, 14811, 14842, 14844, 14924, 14926	
\in	18363, 20543	
\in@	7065	
\incr@eqnum	7362, 7375	
\indent	7494, 7522	
\index	670	
\indexentry	8575, 8590, 8598, 8602, 8607	
\Info	20020, 21146	
\infty	18406, 20561	
\input	978, 988, 1002, 3587, 3595, 3602, 4648, 12204, 12287, 12378, 12547	
\InputIfFileExists	4315, 14835, 14869, 14914, 14916	
\inputlineno	4943, 5360	
\insert	7746	
\int	18441, 20575	
\IntCalcAdd	2302	
\IntCalcDec	1438, 2490	
\intcalcDec	2472	
\IntCalcDiv	1432, 1441, 1446, 1549, 1558, 1570, 1587, 1602, 1617, 2286, 2292, 2298	
\intcalcDiv	1422, 2293, 2300, 2303	
\IntCalcMod	1434, 1443, 1449, 1553, 1559, 1574, 1590, 1605, 1619, 1621, 2288, 2293, 2294, 2300, 2303, 2305	
\intcalcMod	1424	
\intcalcNum	2494, 2522, 2526	
\IntCalcSub	2488, 2541, 2544, 2547, 2550	
\intcalcSub	2280, 2470	
\interfootnotelinepenalty	7749	
\interleave	19923, 21115	
\interlinepenalty	7749	
\inva	16411, 21202	
\invamp	18128	
\invbackneg	18922, 20780	
\invdiameter	19722, 21028	
\inve	16286, 20311	
\invglotstop	16655, 20344	
\invh	16486, 21221	

`\invlegr` 16561, 21244
`\invm` 16520, 21232
`\invneg` 19783, 21053
`\invr` 16556, 21242
`\invscr` 16583, 20332
`\invscripta` 16419, 21204
`\invv` 16618, 21256
`\invw` 16622, 21258
`\invy` 16626, 21260
`\iota` 16876, 20364
`\ipagamma` 16478, 20323
`\isuperior` 20406
`\item` ... 6977, 6980, 8037, 8049, 8152
`\Itemautorefname` 9100
`\itemautorefname` .. 3318, 3336, 3354, 3372, 3390, 3408, 3426, 3455, 3456, 3484, 3502, 9100, 9101, 9104
`\itemindent` 7587
`\itshape` 610

J

`\j` 16048, 16306, 16397
`\JackStar` 19496, 20931
`\JackStarBold` 19498, 20932
`\jarr` 20253
`\jeem` 20197
`\jeh` 20269
`\jinferior` 21119
`\jobname` 6469, 6506, 6513, 12840, 14744, 14835, 14842, 14869, 14914, 14916, 14924
`\Join` 19766, 21046
`\Jupiter` 19284, 21428
`\jupiter` 19282, 20856

K

`\k` .. 15148, 15495, 15497, 15502, 15504, 15549, 15578, 15605, 15620, 15936, 15938, 15982, 15984, 16032, 16034, 16035, 16172, 16174, 16302, 16304, 17296, 17338, 17341
`\kaf` 20233
`\kappa` 16878, 20365
`\kasra` 20259
`\keepPDF@SetupDoc` ... 12431, 12438
`\kern` ... 1959, 2040, 2045, 2057, 7587, 8299, 8300, 8301, 8303, 8304, 8309, 14964
`\kernel@ifnextchar` 701
`\Keyboard` 18940, 20788
`\kha` 20201
`\kinferior` 20440
`\Kutline` 19154, 21392
`\KV@href@pdfnewwindow` . 5027

`\KV@href@pdfnewwindow@de-fault` 5028
`\KV@Hyp@draft` 2842
`\KV@Hyp@nolinks` 2842
`\KV@Hyp@pdfnewwindow` . 5027
`\KV@Hyp@pdfnewwindow@de-fault` 5028
`\kv@key` 4081, 4084, 4091, 5792, 5795, 5797, 5801, 5805
`\kv@parse` 5791
`\kv@parse@normalized` 4106, 4113
`\kv@processor@default` 4109, 4116
`\kv@set@family@handler` .. 4074
`\kv@value` 4079, 5793, 5800, 5801
`\kvsetkeys` 3030, 3084, 3204, 3937, 4054, 4380, 4619, 4637, 4760, 5890, 9202, 11811, 13034, 13279, 13292, 13341, 13384, 13405, 13479, 13855

L

`\L` 15260, 16072
`\l` 15273, 16074
`\l@slide` . 8689, 8799, 8804, 8808, 8815
`\l@subslide` 8741, 8804, 8811, 8855
`\labdentalnas` 16528, 21235
`\label` 669, 8322
`\label@C@hyperref` ... 5112, 5114
`\label@hook` 5428
`\label@hyperdef` 5098, 5128
`\label@hyperref` 5079, 5111, 5451
`\label@name` .. 5393, 5403, 5429
`\labelsep` 8164
`\labelwidth` 8163
`\Ladiesroom` 20009, 21143
`\lam` 20235
`\Lambda` 16815, 20348
`\lambda` 16880, 20366
`\lambdabar` 16234, 21191
`\lambdashash` 16235, 21192
`\langle` 18942, 20789
`\language@group` 648
`\languageshorthands` 1043, 1044, 1078
`\LARGE` 617
`\Large` 618
`\large` 621, 8821, 8829, 8839, 8847
`\LargerOrEqual` ... 18588, 21345
`\lastbox` 7585
`\lastpage@putlabel` 7203
`\lastskip` 2684, 2688, 2695, 2703, 2707, 2714
`\LaTeX` . 574, 576, 12846, 12847
`\LaTeXe` 575, 12847
`\latfric` 16510, 21229
`\LayoutCheckField` 6270, 13240, 13781, 14156

`\LayoutChoiceField` 6267, 13113, 13629, 13977
`\LayoutPushButtonField` . 6273, 13172, 13179, 13702, 13709, 14065, 14074
`\LayoutTextField` . 6264, 13060, 13574, 13919
`\lbrackdbl` 20983
`\lccode` 361, 366, 877, 1356, 2167, 2168, 2169, 2170, 2171, 2172, 2173, 2174, 2175, 2176, 2317, 6142, 8534, 8535, 14669, 14670, 14671, 14672, 14673, 14674, 14675, 14676, 14677, 14678, 14679
`\lcurvearrowdown` . 19662, 21007
`\lcurvearrowse` 19654, 21004
`\lcurvearrowsw` ... 19657, 21005
`\ldots` 569
`\le` 18580, 20635
`\leadsto` 19648, 21002
`\leavevmode` 678, 2639, 4365, 4383, 4423, 5160, 5192, 5260, 6438, 7675, 7834, 8071, 8959, 8967, 8998, 9423, 9494, 9532, 9569, 9902, 10004, 10084, 10121, 10161, 10512, 10553, 10590, 10622, 10858, 10867, 10921, 11075, 11100, 11130, 11163, 11539, 11865, 12115, 12142, 12173, 12496, 12771, 13061, 13173, 13180, 13213, 13241, 13575, 13661, 13683, 13703, 13710, 13731, 13751, 13782, 13920, 14012, 14043, 14066, 14075, 14099, 14118, 14157, 14962
`\Leftarrow` 18292, 20512
`\leftarrow` 20462
`\leftarrowtail` 18209, 20480
`\leftarrowtriangle` . 18340, 20532
`\leftbarharpoon` ... 19699, 21019
`\LEFTCIRCLE` ... 19191, 20826
`\leftharpoondown` . 18240, 20493
`\leftharpoonup` ... 18237, 20492
`\leftleftarrows` 18269, 20503
`\leftleftharpoons` ... 19687, 21015
`\leftModels` 19908, 21485
`\leftmodels` 19901, 21483
`\leftmoon` 19260, 20851
`\leftpointright` 19234, 21408
`\Leftrightarrow` ... 18303, 20516
`\leftrightharrow` ... 18178, 20466
`\leftrightharrows` ... 18267, 20502

<code>\leftrightharpoonup</code>	18344, 20534	<code>\llparentthesis</code>	19718, 21026	9944, 10848, 10935, 11543,	
<code>\leftrightharpoonup</code>	19676, 21011	<code>\lnapprox</code>	19831, 21074	11849, 11870, 12201, 12284,	
<code>\leftrightharpoons</code>	18278, 20507	<code>\lneq</code>	19826, 21072	12542, 12706, 12713, 13036,	
<code>\Leftscissors</code>	19435, 21459	<code>\lneqq</code>	18597, 20642	13043, 13254, 13289, 13336,	
<code>\leftslice</code>	19845, 21080	<code>\lnsim</code>	18885, 20764	13430, 13527, 13528, 13529,	
<code>\leftspoon</code>	19605, 20982	<code>\Longleftarrow</code>	19624, 20990	13556, 13880, 13897	
<code>\leftsquigarrow</code>	18320, 20524	<code>\longleftarrow</code>	19618, 20987	<code>\ltx@ifirstofone</code>	3073, 5424, 5441,
<code>\lefttherefore</code>	17958, 20402	<code>\Longleftrightarrow</code>	19628, 20992	6500, 14697, 14709	
<code>\leftthreetimes</code>	18819, 20735	<code>\longleftrightarrow</code>	19622, 20989	<code>\ltx@ifirstoftwo</code>	245, 348,
<code>\LeftTorque</code>	19669, 21468	<code>\longleg</code>	20330	356, 2481, 2729, 2736, 4835,	
<code>\Lefttorque</code>	19670, 21469	<code>\Longmapsfrom</code>	19632, 20994	5316, 7634, 7654	
<code>\leftVdash</code>	19895, 21481	<code>\Longmapsto</code>	19634, 20995	<code>\ltx@GlobalAppendToMacro</code>	1027, 5428
<code>\leftvdash</code>	18740, 21358	<code>\longmapsto</code>	19630, 20993	<code>\ltx@gobble</code>	273, 3079, 4341, 4350,
<code>\legm</code>	16525, 21234	<code>\Longrightarrow</code>	19626, 20991	4708, 5420, 5422, 6398,	
<code>\legr</code>	16568, 21246	<code>\longrightarrow</code>	19620, 20988	6399, 6410, 6412, 6413,	
<code>\Leo</code>	19311, 21437	<code>\looparrowleft</code>	18219, 20485	6786, 12820, 13442, 14695,	
<code>\leo</code>	19309, 20865	<code>\looparrowright</code>	18221, 20486	14707	
<code>\leq</code>	18580, 20634	<code>\lower</code>	5167, 10011, 10091, 10128,	<code>\ltx@gobblefour</code>	325
<code>\leqclosed</code>	18791, 21374		10168, 11893, 12503, 12778	<code>\ltx@gobblethree</code>	8259
<code>\leqq</code>	18589, 20638	<code>\lowercase</code>	362, 367,	<code>\ltx@gobbletwo</code>	5440, 6401, 6415
<code>\leqslant</code>	19810, 21064		897, 1357, 2177, 2318, 2744,	<code>\ltx@ifclassloaded</code>	6639, 8220
<code>\lessapprox</code>	19818, 21068		3262, 3292, 4021, 4057,	<code>\ltx@ifempty</code>	5206
<code>\lessclosed</code>	18785, 21372		5464, 5465, 5468, 5473,	<code>\ltx@iffileloaded</code>	1000, 6598
<code>\lessdot</code>	18849, 20748		5497, 5507, 5561, 5617,	<code>\ltx@ifpackagelater</code>	359, 9937
<code>\lesseqgtr</code>	18858, 20752		5937, 6010, 6013, 6143,	<code>\ltx@ifpackageloaded</code>	1323, 6505,
<code>\lesseqqgtr</code>	19836, 21076		8536, 11589, 14680	13532	
<code>\lessgtr</code>	18630, 20657	<code>\lozenge</code>	19189, 20825	<code>\ltx@ifUndefined</code>	239, 279, 285,
<code>\LessOrEqual</code>	18583, 21344	<code>\lrcorner</code>	18934, 20785	324, 647, 691, 767, 802, 920,	
<code>\lesssim</code>	18620, 20653	<code>\slide@flag</code>	8816, 8819, 8837,	921, 922, 1086, 1092, 1098,	
<code>\LetLtxMacro</code>	6385, 6389, 6455,		8856, 8860	1103, 1108, 1115, 1121,	
6459		<code>\LT@array</code>	7328	1127, 1132, 1138, 1143,	
<code>\Letter</code>	19448, 21460	<code>\LT@foot</code>	7343, 7347	1153, 1159, 1165, 1171,	
<code>\LHD</code>	19184, 20823	<code>\LT@p@ftn</code>	7707, 7710, 7714, 7724	1310, 1316, 1693, 1788,	
<code>\lhd</code>	18783, 20721	<code>\LT@p@ftntext</code>	7705, 7712	1789, 1941, 2591, 2624,	
<code>\hooknwarrow</code>	19640, 20998	<code>\LT@start</code>	7345, 7355	4336, 4338, 4426, 4427,	
<code>\hooksearrow</code>	19644, 21000	<code>\ltimes</code>	18814, 20733	4428, 4834, 4835, 5031,	
<code>\Libra</code>	19317, 21439	<code>\ltx@backslashchar</code>	329, 330, 331,	5389, 5420, 6561, 6961,	
<code>\libra</code>	19315, 20867		332, 333, 334, 335, 336, 337,	7061, 7068, 7090, 7105,	
<code>\Lightning</code>	18227, 21314		338, 339, 341	7436, 7973, 8238, 8987,	
<code>\lightning</code>	18225, 20488	<code>\ltx@empty</code>	381, 382,	8988, 9033, 9034, 9036,	
<code>\limits</code>	4919		485, 1947, 3053, 3228, 3236,	9037, 9207, 9238, 9471,	
<code>\linferior</code>	20441		3240, 3616, 3761, 4144,	9481, 9879, 10965, 11022,	
<code>\listofslides</code>	8790		4168, 4175, 4274, 4275,	11125, 11515, 11558, 11649,	
<code>\listslidenam</code>	8789, 8792, 8794,		4278, 4279, 4280, 4281,	11826, 13530, 14996, 15006	
8796			4282, 4283, 4287, 4288,	<code>\ltx@ifundefined</code>	2538, 2728, 2729,
<code>\literalps@out</code>	2637, 11462, 11467,		4584, 4585, 4612, 4622,	2772, 5432, 7594, 8254, 9267	
11519, 11525, 11551, 11557,			4720, 5212, 5377, 5398,	<code>\ltx@leftbracechar</code>	339, 363
11822, 11833, 11862, 11863,			5421, 5662, 5680, 5694,	<code>\ltx@LocalAppendToMacro</code>	376,
11891, 11893, 11905, 11907,			5707, 5723, 5755, 5780,	379, 7053, 7069, 7074	
12202, 12285, 12348, 12545			5787, 5788, 6129, 6167,	<code>\ltx@one</code>	244, 6641, 6642, 6649,
<code>\ll</code>	18601, 20644		6168, 6169, 6170, 6171,	8223, 8227, 8233, 8236,	
<code>\llap</code>	5165		6172, 6173, 6174, 6175,	8237, 8250, 9229, 13536	
<code>\llbracket</code>	19609, 21464		6176, 6177, 6584, 6585,	<code>\ltx@onelevel@sanitize</code>	7044, 7063
<code>\llcorner</code>	18932, 20784		6586, 6589, 6601, 6610,	<code>\ltx@ReturnAfterElseFi</code>	4901
<code>\Lleftarrow</code>	18316, 20522		6627, 6632, 6638, 6647,	<code>\ltx@ReturnAfterFi</code>	509, 2115, 4905, 4921, 8629,
<code>\lll</code>	18853, 20750		6667, 7394, 8376, 8387,		
			8396, 9222, 9242, 9245,		

8665, 9153, 9163, 14251
`\ltx@rightbracechar` . . . 340, 368
`\ltx@secondoftwo` . 240, 247, 251,
345, 2483, 2728, 2729, 2738,
2740, 4834, 4835, 4837,
5314, 7636, 7656
`\ltx@space` 342, 1844
`\ltx@zero` 2171, 2172, 2173, 2174,
2175, 2176, 9217, 9224,
13534
`\luatexrevision` 9653
`\luatexversion` 9645, 9650
`\lz` 16517, 21231

M

`\m@ne` . . 4444, 4955, 5014, 5479,
7248, 7456, 10507, 14916,
15005, 15020
`\make@df@tag@` . . . 8449, 8451
`\make@df@tag@@` . 8450, 8452
`\make@stripped@name` . . 7027,
7384, 7415, 7443, 7454
`\makeatletter` 3, 970, 1023, 6504
`\MakeButtonField` . 6280, 13174,
13182, 13200, 13218, 13223,
13704, 13714, 13739, 13756,
13763, 14067, 14070, 14098,
14123, 14127
`\MakeCheckField` . 6277, 13243,
13786, 14153
`\MakeChoiceField` . 6279, 13158,
13687, 14041
`\MakeFieldObject` 13423, 13510,
13520, 13523
`\MakeLowercase` 638
`\MakeLowercaseUnsupportedIn-`
`PdfStrings` 638
`\MakeRadioField` . . 6276, 13146,
13673, 14005
`\makeslideheading` 8699
`\makeslidesubheading` 8751
`\maketag@@@` 8438
`\MakeTextField` . . . 6278, 13063,
13579, 13916
`\maketitle` 7784, 7785
`\MakeUppercase` 637, 8794, 8796,
8950
`\MakeUppercaseUnsupportedIn-`
`PdfStrings` 637
`\Male` 19281, 21427
`\male` 19277, 20855
`\MaleMale` 19398, 20892
`\ManFace` 19995, 21137
`\manstar` 19392, 20889
`\mapsto` 18213, 20482
`\Mars` 19280, 21426
`\mars` 19279, 21425

`\MathBSuppress` . . 10868, 10872
`\mathclose` 7397
`\mathdisplay` 7365, 7374
`\mathdisplay@push` . 7363, 7372
`\mathdollar` 15646, 21158
`\mathellipsis` 17929, 21292
`\mathopen` 7388, 7419
`\mathparagraph` . . 15768, 21169
`\mathsection` 15736, 21167
`\mathsterling` 15725, 21164
`\mathunderscore` . . 15704, 21162
`\mathversion` 626
`\maxdimen` 3696, 13428
`\MaybeStopEarly` 486, 3087, 3162,
4491, 4597, 6936, 6939
`\mbox` . . . 679, 8084, 8107, 9374,
10479
`\mddefault` . . . 7496, 7524, 7555
`\mdseries` 609
`\meaning` 62, 153,
159, 2600, 6545, 7164, 7461,
14880, 14888, 14903
`\measuredangle` . . . 18410, 20563
`\measuring@false` 7022
`\mediaheight` 10959, 10961,
10967, 10974
`\mediawidth` 10970, 10977
`\meem` 20237
`\Mercury` 19266, 21418
`\mercury` 19264, 20853
`\merge` 19797, 21480
`\message` 8817
`\MessageBreak` 281, 287,
304, 305, 310, 311, 351, 352,
517, 2071, 2092, 2105, 2128,
2133, 2135, 2766, 2767,
2781, 2803, 2806, 2808,
2886, 2887, 2913, 2914,
2959, 2960, 2961, 2999,
3000, 3020, 3035, 3076,
3101, 3134, 3172, 3179,
3190, 3196, 3246, 3284,
3626, 3757, 3758, 3820,
3821, 3839, 3840, 3934,
3976, 3984, 4034, 4089,
4090, 4200, 4201, 4303,
4525, 4526, 4534, 4535,
4551, 4552, 4567, 4568,
4576, 4577, 4763, 5008,
5009, 5033, 5034, 5050,
5051, 5518, 5523, 5532,
5575, 5621, 5745, 5858,
5930, 5941, 5973, 5974,
5993, 6101, 6102, 6103,
6104, 6617, 6852, 6867,
6868, 7211, 8326, 8356,
8357, 8358, 8359, 8360,

8508, 9212, 9230, 9249,
9251, 9257, 9259, 9262,
9269, 9427, 10517, 11051,
11134, 11428, 11434, 11658,
13436, 13438, 14616, 14634,
14747
`\MF` 584, 12849
`\mho` 20453
`\mid` 18417, 20565
`\MineSign` 19377, 20882
`\mininferior` 20442
`\minusdot` 19773, 21049
`\minusinferior` 20430
`\minussuperior` 20414
`\models` 18757, 21363
`\moo` 21025
`\Moon` 19993, 21136
`\MoonPha` . . . 2497, 2502, 2505,
2511, 21157
`\Mountain` 19424, 20900
`\MoveDown` 19174, 21398
`\MoveUp` 19159, 21395
`\MP` 585, 12850
`\mp` 18385, 20552
`\mu` 16882
`\mugreek` 20367
`\multimap` 18801, 20727
`\multimapboth` . . . 19756, 21041
`\multimapdotbothA` 18797, 20725
`\multimapdotbothB` 18799, 20726
`\MultiplicationDot` 15771, 21170
`\multiply` . . . 9649, 11315, 11350
`\Mundus` 19991, 21135
`\MVArrowDown` . . 18176, 21310
`\MVAt` 15696, 20299
`\MVComma` 15664, 20285
`\MVDivision` 15670, 20288
`\MVEight` 15688, 20297
`\MVFive` 15682, 20294
`\MVFour` 15680, 20293
`\MVMinus` 15666, 20286
`\MVMultiplication` 15838, 21173
`\MVNine` 15690, 20298
`\MVOne` 15674, 20290
`\MVPeriod` 15668, 20287
`\MVPlus` 15662, 20284
`\MVRightArrow` . . 18172, 21308
`\MVRightarrow` . . . 18173, 21309
`\MVSeven` 15686, 20296
`\MVSix` 15684, 20295
`\MVThree` 15678, 20292
`\MVTwo` 15676, 20291
`\MVZero` 15672, 20289

N

`\n` 888
`\nabla` 18361, 20542

<code>\name@of@Eq</code>	6995, 7025	<code>\newif</code>	392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 435, 436, 437, 440, 441, 442, 846, 1085, 3031, 3052, 3764, 4073, 4675, 5029, 5471, 5559, 5892, 5893, 5913, 5956, 6997, 6998, 7022, 7402, 10847, 11804	<code>\nLeftarrow</code>	18284, 20509		
<code>\name@of@slide</code>	6996, 7006	<code>\newlabel</code> 2603, 5138, 6482, 6483, 6491, 6518, 7233, 7261	<code>\nleftarrow</code>	18192, 20472			
<code>\nameref</code>	676, 4839, 4843	<code>\newlabelxx</code>	6484, 6485	<code>\nleftModels</code>	19911, 21486		
<code>\napprox</code>	18500, 20600	<code>\newlength</code>	14955	<code>\nleftmodels</code>	19904, 21484		
<code>\napproxseq</code>	18505, 20602	<code>\newline</code>	572, 6566	<code>\nLeftrightarrow</code>	18286, 20510		
<code>\nasb</code>	20249	<code>\newname</code> 7028, 7385, 7416, 7444, 7457, 7466	<code>\nleq</code>	<code>\nletrightarrow</code>	18223, 20487		
<code>\nasymp</code>	18518, 20608	<code>\newsavebox</code>	10315, 11841	<code>\nleftVdash</code>	19898, 21482		
<code>\natural</code>	19365, 20877	<code>\newtie</code>	15150, 15151, 15588, 15615, 15633	<code>\nleftvdash</code>	18743, 21359		
<code>\nbackcong</code>	18514, 20606	<code>\newtoks</code> 90, 5984, 11676, 11916, 11917	<code>\nleqq</code>	<code>\nless</code>	18611, 20649		
<code>\nbacksim</code>	18478, 20590	<code>\newwrite</code>	6512, 14840, 14922	<code>\nlessapprox</code>	19820, 21069		
<code>\nbacksimeq</code>	18825, 20738	<code>\nexists</code>	18354, 20539	<code>\nlessclosed</code>	18895, 21385		
<code>\nBumpeq</code>	18523, 20610	<code>\next</code>	8158, 8159, 8160, 11278, 11280, 11282	<code>\nlessgtr</code>	18636, 20660		
<code>\nbumpeq</code>	18527, 20612	<code>\nfallingdoteq</code>	20618	<code>\nlesssim</code>	18626, 20655		
<code>\ncirceq</code>	18559, 20626	<code>\nfallingdotseq</code>	18542	<code>\nll</code>	18603, 20645		
<code>\ncong</code>	18496, 20598	<code>\nfss@text</code> 8871, 8891, 8908, 9026	<code>\NG</code>	<code>\nmid</code>	18419, 20566		
<code>\ncurlyeqprec</code>	18865, 20755	<code>\ng</code>	16092, 16093, 16094, 21181, 21182	<code>\nmodels</code>	18776, 21369		
<code>\ncurlyeqsucc</code>	18869, 20757	<code>\ngeq</code>	18618, 20652	<code>\noboundary</code>	20279		
<code>\nDashV</code>	19909, 21109	<code>\ngeqq</code>	18595, 20641	<code>\nobreak</code> 2685, 2693, 2704, 2712, 7676, 7835			
<code>\nDashv</code>	19902, 21107	<code>\ngeqslang</code>	19816	<code>\nobreakspace</code>	690, 8962, 8991, 8994		
<code>\ndashV</code>	19896, 21105	<code>\ngeqslant</code>	21067	<code>\NoChemicalCleaning</code>	19736, 21032		
<code>\ndashv</code>	18741, 20707	<code>\ngg</code>	18607, 20647	<code>\noexpand</code>	22, 93, 95, 108, 116, 169, 171, 172, 173, 176, 206, 866, 1031, 1370, 1803, 1820, 1950, 1977, 2331, 2691, 2692, 2693, 2696, 2710, 2711, 2712, 2715, 3545, 3547, 3549, 3550, 3551, 3553, 3569, 3775, 3776, 3778, 4139, 4446, 4450, 4451, 4619, 4913, 5086, 5355, 5357, 5383, 5527, 6074, 6087, 6741, 6742, 6751, 6753, 6756, 6881, 7047, 7048, 7065, 7245, 7246, 7248, 7273, 7274, 7275, 7276, 7277, 7285, 7286, 7287, 7460, 7698, 7708, 7716, 7717, 7718, 7720, 7844, 7934, 8009, 8024, 8040, 8225, 8374, 8468, 8470, 8924, 8925, 9042, 9043, 9048, 9050, 9055, 9056, 9061, 9062, 9652, 10253, 11741, 11808, 12345, 12596, 13088, 13089, 13090, 13091, 13603, 13604, 13605, 13606, 13951, 13952, 13953, 13954, 14230		
<code>\nDoteq</code>	18537, 20616	<code>\ngtr</code>	18613, 20650	<code>\noexpandQ</code>	1977		
<code>\ndoteq</code>	18531, 20614	<code>\ngtrapprox</code>	19824, 21071	<code>\nofrenchguillemets</code>	709, 711		
<code>\ndownmodels</code>	19914, 21111	<code>\ngtrclosed</code>	18898, 21386				
<code>\ndownvdash</code>	18747, 20709	<code>\ngtrless</code>	18634, 20659				
<code>\ne</code>	18569, 20631	<code>\ngtrsim</code>	18628, 20656				
<code>\Narrow</code>	18310, 20519	<code>\nhateq</code>	18565, 20628				
<code>\narrow</code>	18184, 20469	<code>\ni</code>	18369, 20546				
<code>\neg</code>	21148	<code>\NibRight</code>	19460, 20914				
<code>\Neptune</code>	19293, 21431	<code>\NibSolidRight</code>	19462, 20915				
<code>\neptune</code>	19291, 20859	<code>\niepsilon</code>	16450, 20318				
<code>\neq</code>	18569, 20630	<code>\niiota</code>	16499, 20326				
<code>\neqcirc</code>	18555, 20624	<code>\nineinferior</code>	20428				
<code>\neqdot</code>	19806, 21062	<code>\ninesuperior</code>	20412				
<code>\neqsim</code>	18487, 20594	<code>\ninferior</code>	20443				
<code>\nequal</code>	18572, 21340	<code>\nipi</code>	16552, 20329				
<code>\nequiv</code>	18576, 20633	<code>\niupilon</code>	16610, 20335				
<code>\neswarrow</code>	19638, 20997	<code>\nj</code>	16532, 21237				
<code>\netscape</code>	10047						
<code>\Neural</code>	19404						
<code>\Neutral</code>	20895						
<code>\new@ifnextchar</code>	702						
<code>\new@pdfink</code>	9402, 9459, 9462						
<code>\new@refstepcounter</code>	7357, 7391						
<code>\newblock</code>	8168						
<code>\newcommand</code>	4, 9, 42, 2638, 5152, 5158, 5190, 5388, 5411, 6442, 6446, 7904, 8476, 14717, 14720, 14725, 20283, 21154						
<code>\newcount</code>	487, 488, 2643, 4999, 5896, 6628, 13154, 13533, 13680, 13886, 14037, 14752						
<code>\newcounter</code>	6978, 7609, 10385, 14667						
<code>\newdimen</code>	484, 5148, 5897, 5898						

<code>\NoHy@OrgPageRef</code>	6389, 6391, 6459, 6461	<code>\nsuccapprox</code>	19879, 21097	<code>\nVdash</code>	18777, 20719
<code>\NoHy@OrgRef</code>	6385, 6387, 6455, 6457	<code>\nsucccurlyeq</code>	18873, 20759	<code>\nvDash</code>	18773, 20718
<code>\NoHyper</code>	6393	<code>\nsucceq</code>	19855, 21085	<code>\nvDash</code>	18770, 20717
<code>\nohyperpage</code>	6437, 8619, 8621, 8623	<code>\nsucceqq</code>	19867, 21091	<code>\nVdash</code>	18764, 20715
<code>\nolinkurl</code>	5065	<code>\nsuccsim</code>	18652, 20668	<code>\Nwarrow</code>	18308, 20518
<code>\nolinkurl@</code>	5065, 5066	<code>\nsuperior</code>	20418	<code>\nwarrow</code>	18182, 20468
<code>\NomFancyVerbLineautorefname</code>	3473	<code>\nSupset</code>	18839, 20744	<code>\nwsearrow</code>	19636, 20996
<code>\Nomfootnoteautorefname</code>	3453	<code>\nsubset</code>	18664, 20674	O	
<code>\Nomtheoremautorefname</code>	3477	<code>\nsubseteq</code>	18672, 20678	<code>\O</code>	15393, 15840, 16322
<code>\nonumber</code>	7431, 7434	<code>\nsubseteqq</code>	19891, 21103	<code>\o</code>	15462, 15910, 16325
<code>\normalfont</code>	604, 7490, 7518, 7551	<code>\nthickapprox</code>	18502, 21334	<code>\oasterisk</code>	18724, 21356
<code>\normalsize</code>	622, 7880, 7952	<code>\ntriangleleft</code>	18893, 20768	<code>\obackslash</code>	19730, 21472
<code>\notasymp</code>	18520, 21336	<code>\ntrianglelefteq</code>	18900, 20770	<code>\obar</code>	19724, 21029
<code>\notbackslash</code>	18956, 20794	<code>\ntriangleright</code>	18896, 20769	<code>\obeylines</code>	12344
<code>\NotCongruent</code>	18578, 21342	<code>\ntrianglerighteq</code>	18903, 20771	<code>\OBJ@acroform</code>	13506, 13507
<code>\notdivides</code>	18421, 21325	<code>\ntriplesim</code>	18510, 20604	<code>\OBJ@Helv</code>	13485, 13494, 13845
<code>\note</code>	8268	<code>\ntwoheadleftarrow</code>	18198, 20475	<code>\OBJ@OCG@print</code>	9317, 9320, 9328, 9355, 10403, 10405, 10418, 10422, 10431, 10460
<code>\notequiv</code>	18579, 21343	<code>\ntwoheadrightarrow</code>	18205, 20478	<code>\OBJ@OCG@view</code>	9302, 9320, 9354, 10387, 10389, 10402, 10422, 10459
<code>\notin</code>	18365, 20544	<code>\nu</code>	16884, 20368	<code>\OBJ@OCGs</code>	9323, 9326, 9332, 9337, 9342, 10419, 10421, 10425, 10429, 10435, 10440, 10445
<code>\notni</code>	18374, 21320	<code>\null</code>	8149, 8157, 8913, 9022	<code>\OBJ@pdfdocencoding</code>	13483, 13826, 13842
<code>\notowner</code>	18372, 20547	<code>\number</code>	1204, 1208, 1211, 1219, 1222, 1224, 1529, 1531, 1558, 1559, 2277, 2335, 2336, 2337, 2338, 2342, 2343, 2344, 2345, 2346, 2350, 2351, 2352, 2353, 2354, 2355, 2356, 2360, 2361, 2362, 2363, 2364, 2365, 2368, 2370, 2374, 2375, 2377, 2379, 2381, 2384, 2388, 2389, 2390, 2391, 2400, 2401, 2405, 2406, 2413, 2414, 2418, 2421, 2422, 2423, 2433, 2435, 2436, 2441, 2443, 2444, 2449, 2450, 4159, 4677, 4694, 5485, 7095, 7098, 7141, 7142, 7145, 7149, 9280, 9283, 10075, 10093, 10094, 10109, 10110, 10130, 10131, 10147, 10148, 10170, 10171, 10187, 10188	<code>\OBJ@ZaDb</code>	13484, 13493, 13835
<code>\notperp</code>	19599, 20979	<code>\numberline</code>	7873, 7945, 14639, 14644	<code>\obot</code>	19733, 21031
<code>\notslash</code>	18953, 20793	<code>\numberwithin</code>	8473	<code>\obslash</code>	19727, 21030
<code>\noway</code>	19422, 20899	<code>\numexpr</code>	2342, 2343, 2344, 2346, 2352, 2360, 2361, 2362, 2363, 2364, 2365, 2369, 2371, 2375, 2377, 2379, 2381, 2385, 2388, 2389, 2391, 2400, 2405, 2422, 2436, 2444, 2450, 4163	<code>\ocirc</code>	18719, 21353
<code>\nparallel</code>	18424, 20568	<code>\nun</code>	20239	<code>\OCIRCUMFLEX</code>	20049, 20147, 20148, 20149, 20150, 20151
<code>\nperp</code>	18754, 21362	<code>\nupmodels</code>	19918, 21113	<code>\ocircumflex</code>	20043, 20087, 20088, 20089, 20090, 20091
<code>\nprec</code>	18654, 20669	<code>\nupvdash</code>	18752, 20711	<code>\oddsidemargin</code>	8305
<code>\nprecapprox</code>	19875, 21095	<code>\nVDash</code>	18780, 20720	<code>\odiv</code>	19781, 21052
<code>\npreccurlyeq</code>	18871, 20758			<code>\odot</code>	18714, 20697
<code>\npreceq</code>	19851, 21083			<code>\odplus</code>	19735, 21474
<code>\npreceqq</code>	19863, 21089			<code>\OE</code>	15262, 16108
<code>\nprecsim</code>	18648, 20666			<code>\oe</code>	15275, 16110
<code>\nqsubseteq</code>	20760			<code>\offinterlineskip</code>	6592
<code>\nqsupseteq</code>	20761			<code>\ogreaterthan</code>	19741, 21034
<code>\NR@getttitle</code>	7870			<code>\OHORN</code>	20050, 20152, 20153, 20154, 20155, 20156
<code>\nRightarrow</code>	18289, 20511			<code>\ohorn</code>	3500, 3507, 20044, 20092, 20093, 20094, 20095, 20096
<code>\nrightarrow</code>	18194, 20473			<code>\oiint</code>	18451, 20579
<code>\nrightModels</code>	18782, 21371			<code>\oinferior</code>	20436
<code>\nrightModels</code>	18775, 21368			<code>\oint</code>	18448, 20578
<code>\nrightVdash</code>	18779, 21370			<code>\ointclockwise</code>	18454, 20580
<code>\nrightvdash</code>	18772, 21367			<code>\ointctrclockwise</code>	18456, 20581
<code>\nrisingdoteq</code>	18547, 20620			<code>\oldb</code>	920
<code>\nsim</code>	18483, 20592			<code>\oldc</code>	921
<code>\nsimeq</code>	18491, 20596			<code>\oldcontentsline</code>	6477, 6480, 6490
<code>\nsqsubset</code>	18684, 20684				
<code>\nsqsubseteq</code>	18692, 18875, 20688				
<code>\nsqsupset</code>	18688, 20686				
<code>\nsqsupseteq</code>	18696, 18877, 20690				
<code>\nSubset</code>	18835, 20742				
<code>\nsubset</code>	18662, 20673				
<code>\nsubseteq</code>	18670, 20677				
<code>\nsubseteqqq</code>	19887, 21101				
<code>\nsucc</code>	18656, 20670				

`\oldd` 922
`\oldnewlabel` .. 6482, 6487, 6491
`\olessthan` 19738, 21033
`\OMEGA` 12845
`\Omega` 16842, 20355
`\omega` 16908, 20379
`\ominus` 18705, 20694
`\on@line` 8353, 8354
`\oneinferior` 20420
`\onesuperior` 20303
`\oo` 19957, 21122
`\openbullet` 20828
`\openo` 16426, 20314
`\openout` 6469, 6513, 14842, 14924
`\oplus` 18702, 20693
`\OpMode` 3157, 3160, 3173, 3186, 3191, 11367, 11470, 12289
`\or` 346, 1238, 1239, 1240, 1241, 1242, 1243, 1244, 1245, 1246, 1260, 1261, 1262, 1263, 1264, 1265, 1266, 1267, 1268, 1283, 1284, 1285, 1286, 1287, 1288, 1289, 1290, 1291, 1376, 1377, 1378, 1379, 1380, 1381, 1382, 1383, 1384, 1385, 1386, 1387, 1388, 1389, 1390, 1391, 1392, 1393, 1394, 1395, 1396, 1397, 1398, 1399, 1400, 1401, 1402, 1403, 1404, 1405, 1406, 1407, 1425, 1447, 1450, 1456, 1457, 1458, 1459, 1460, 1461, 1462, 1463, 1464, 1465, 1466, 1467, 1468, 1469, 1470, 1471, 1472, 1473, 1474, 1475, 1476, 1477, 1478, 1479, 1480, 1481, 1482, 1483, 1484, 1485, 1486, 1487, 1492, 1493, 1494, 1495, 1496, 1497, 1498, 1499, 1500, 1501, 1502, 1503, 1504, 1505, 1506, 1507, 1508, 1509, 1510, 1511, 1512, 1513, 1514, 1515, 1516, 1517, 1518, 1519, 1520, 1521, 1522, 1523, 1536, 1537, 1538, 1539, 1540, 1652, 1653, 1654, 2496, 2499, 2501, 2504, 5645, 5651, 5656, 5870, 7115, 7116, 7117, 7118, 7124, 7125, 7126, 7127, 8381, 8385, 8836, 8845, 11360, 14760,

14761, 14762, 14763, 14764, 14765, 14766, 14767, 14768, 14769, 14770, 14771, 14772, 14773, 14774, 14775, 14776, 14777, 14778, 14779, 14780, 14781, 14782, 14783, 14784, 14785, 14786, 14787, 14788, 14789, 14790, 14791
`\OrnamentDiamandSolid` . 19589
`\oslash` 18711, 20696
`\otimes` 18708, 20695
`\ovee` 18434, 20572
`\overlay` 8265
`\owedge` 18429, 20570
`\owns` 18371, 21319

P

`\P` 568
`\p@` 2401, 2406, 5899, 5905, 7498, 7526, 7557, 10020, 10104, 10142, 10182, 11314, 12512, 12792, 13084, 13599, 13947, 15080, 15081
`\p@equation` 8445
`\PackageError` 61
`\PackageInfo` . 9196, 9278, 13434
`\PackageWarning` .. 3034, 5856
`\pageautorefname`
... 3331, 3349, 3367, 3385, 3403, 3421, 3439, 3479, 3497, 3515, 8994, 9117
`\pagename` 8991
`\pageref`
675, 4501, 4830, 6389, 6390, 6459, 6460, 7211, 8980, 8984
`\paperheight`
... 4296, 9864, 9866, 9869, 9871, 9883, 9884, 10828, 10829, 10966, 10967, 10969, 12266, 12267
`\paperwidth`
... 9860, 9862, 9873, 9875, 9880, 9881, 10827, 10829, 10970, 12265, 12267
`\par` 7489, 7516, 7549, 7872, 7900, 7943, 7953, 8151, 8171
`\paragraphautorefname`
... 3327, 3345, 3363, 3381, 3399, 3417, 3435, 3468, 3470, 3493, 3511, 9113
`\parallel` 18422, 20567
`\parenleftinferior` 20432
`\parenleftsuperior` 20416
`\parenrightinferior` 20433
`\parenrightsuperior` 20417
`\parr` 18131, 21307
`\parskip` 6505

`\partautorefname` .. 3321, 3339, 3357, 3375, 3393, 3411, 3429, 3459, 3487, 3505, 9107
`\partial` 18350, 20537
`\partnumberline` .. 14641, 14646
`\PassOptionsToPackage` .. 3205, 3273, 3277, 3299, 4330, 4638
`\pdf@addtoks` 11919, 11938, 11944, 11953, 11960, 11964, 11966, 11968, 11970, 11972, 11980, 11989, 11993, 11995, 11997, 12000, 12009, 12013, 12015, 12017, 12019, 12021, 12023, 12025, 12027, 12029, 12031, 12033, 12035, 12037, 12039, 12041, 12043, 12044, 12045, 12046, 12047, 12048, 12049, 12050, 12051, 12052, 12053, 12058
`\pdf@addtoksx` .. 11913, 11923, 11936
`\pdf@box` .. 11841, 11873, 11881, 11889, 11890, 11893, 11897, 11899, 11902
`\pdf@defaulttoks` . 11808, 11917, 11918, 11928
`\pdf@docset` 11676
`\pdf@endanchor` 9415, 9459, 9466
`\pdf@escapestring` 9172
`\PDF@FinishDoc`
... 3090, 3091, 3165, 3166, 4290, 4367, 4494, 4495, 4600, 4601, 6436, 6609, 6610, 9728, 9944, 10202, 10685, 10848, 11438, 11677, 12552, 12713
`\pdf@ifdraftmode` 240, 243, 251, 6785, 9287, 9729, 9838, 13480, 14852
`\pdf@linktype` 11826, 11830, 11933, 11934
`\pdf@rect` . 11818, 11832, 11845
`\PDF@SetupDoc`
... 4289, 4366, 6356, 6357, 6435, 9659, 9945, 10233, 10725, 10849, 11375, 11728, 12433, 12583, 12714
`\PDF@SetupDox` 9659
`\pdf@strcmp` 1062
`\pdf@toks` . 11808, 11823, 11834, 11916, 11920, 11924
`\pdf@type` . 11810, 11814, 11823, 11834, 11911, 11931
`\pdfannotlink` 9393
`\pdfbookmark` 2638, 6441, 6442, 14718, 14723, 14728, 14732

\pdfcatalog . . . 6788, 9324, 9674, 9716, 13507	11781, 11805, 12067, 12082, 12097, 12109, 12116, 12143, 12174, 12596, 12605, 12636, 13063, 13146, 13158, 13182, 13200, 13223, 13243, 14884	\Peace 19449, 20909
\PDFdefaults 11927	\pdfmark@ 11805, 11806	\peh 20265
\pdfdest 9417	\pdfmatch 343	\penalty 1953, 2665, 4974, 8078, 8101
\pdfdraftmode 244	\pdfminorversion 9193	\PencilRight 19456, 20912
\pdfendlink . 9456, 13579, 13673, 13688, 13715, 13740, 13764, 13787	\PDFNextPage 12080	\PencilRightDown . 19454, 20911
\pdfescapestring 14259	\PDFNextPage@ . . 12080, 12081	\PencilRightUp . . . 19458, 20913
\pdfform 9395	\pdfobj 9288, 9303, 9318, 13488, 13793, 13827, 13836	\pentagon 19928, 21117
\PDFForm@Name 14267, 14270, 14274, 14277	\pdfobjcompresslevel 9217, 9271	\perp 19597, 20978
\PDFForm@Check 13242, 13244, 13784, 13785, 14158, 14162, 14351	\PDFOpen 12108	\phantom 627
\PDFForm@List . 13157, 13159, 13685, 13686, 14044, 14049, 14411	\pdfoptionpdfminorversion 9190	\phantomsection . . . 4291, 6443, 8328, 14585, 14636, 15024
\PDFForm@Name 13570, 13624, 13697, 13778, 13911, 13972, 14060, 14149, 14266	\pdfoutline 14933	\Phi 16835, 20353
\PDFForm@Push . 13181, 13183, 13712, 13713, 14076, 14080, 14381	\pdfpageattr . 9772, 9776, 9777, 9787, 9796, 9800, 9801, 9811, 9819, 9822, 9823, 9833	\phi 16902, 20376
\PDFForm@Radio 13145, 13149, 13663, 13665, 14013, 14025, 14445	\pdfpageheight 9866, 9875, 9884, 9891	\phiinferior 20389
\PDFForm@Reset 13222, 13224, 13761, 13762, 14128, 14133, 14550	\pdfpageref 13544	\Phone 19210, 20834
\PDFForm@Submit 13199, 13202, 13733, 13735, 14100, 14105, 14516	\pdfpageresources . . 9351, 9352	\PhoneHandset . . . 19440, 20905
\PDFForm@Text . 13062, 13064, 13577, 13578, 13921, 13924, 14480	\pdfpagesattr . 9663, 9665, 9667	\Pi 20350
\pdfhorigin 9856	\pdfpagewidth 9862, 9871, 9881, 9888	\pi 16890, 20370
\pdfinfo 9732	\PDFPreviousPage 12093	\pinferior 20444
\pdflastannot 9237	\PDFPreviousPage@ . . . 12094, 12096	\Pisces 19332, 21444
\pdflastform 9396	\pdfrefform 9397	\pisces 19330, 20872
\pdflastlink 9240, 13464	\pdfrefobj . 13483, 13484, 13485	\pitchfork 18847, 20747
\pdflastobj 9234, 9302, 9317, 9323, 13506, 13826, 13835, 13845	\pdfrefxform 9397, 13428	\planck 16015, 21180
\pdflastxform 9235, 9396, 13426, 13428	\pdfstartlink 9392, 9393, 9451, 9495, 9533, 9570, 9904, 13578, 13664, 13686, 13713, 13734, 13762, 13785	\Plane 19444, 20907
\pdflastximage 9236	\pdfstringdef 537, 833, 3960, 3966, 3972, 3994, 3999, 4005, 4012, 4018, 4098, 5817, 5822, 5848, 6569, 6677, 6679, 7226, 8251, 8287, 14285, 14650	\Plus 19477, 20922
\pdflinkmargin 9391, 9394, 9399	\pdfstringdefDisableCommands . . . 919, 1021, 6439, 6564	\PlusCenterOpen . 19481, 20924
\pdfliteral 9375, 9377, 9382	\pdfstringdefPostHook 829, 1015	\plusinferior 20429
\pdfm@box 10315, 13882, 13883, 13884, 13915, 13927, 14004, 14029, 14040, 14051, 14070, 14083, 14098, 14107, 14127, 14135, 14152, 14164	\pdfstringdefPreHook 686, 1015, 1027, 6563, 6573	\PlusOutline 19475, 20921
\pdfmark . . . 6899, 10253, 10262, 10292, 11506, 11526, 11565, 11600, 11617, 11629, 11663, 11700, 11712, 11741, 11750,	\pdfstringdefWarn 571, 572, 680, 1030, 1811, 1816, 1835, 1839	\plussuperior 20413
	\pdftexrevision 9619, 9627, 9638	\PlusThinCenterOpen . . . 19479, 20923
	\pdftexversion 9614, 9616, 9619, 9622, 9625, 9626, 9630, 9636, 9637, 13482	\Pluto 19296, 21432
	\pdfvorigin 9857	\pluto 19294, 20860
	\pdfxform 9395, 13424	\pm 21151
		\pointer 18335, 20530
		\PointingHand 19235, 21409
		\Pointinghand 19236, 21410
		\pounds 15726, 21165
		\Preamble 12841
		\prec 18638, 20661
		\precapprox 19873, 21094
		\preccurlyeq 18642, 20663
		\preceq 19849, 21082
		\preceqq 19861, 21088
		\precnapprox 19881, 21098
		\precneq 19857, 21086
		\precneqq 19869, 21092
		\precnsim 18889, 20766
		\precsim 18646, 20665
		\PrerenderUnicode 3951
		\prime 17934, 20398
		\process@me . 6543, 6555, 6556, 9662, 9671
		\ProcessKeyvalOptions . . . 4334
		\prod 18377, 20549
		\propto 18403, 20560

<code>\protect</code>	1951, 5116, 7873, 7945, 8009, 8024, 8040, 8156, 8163, 8164, 8366, 8414, 8689, 8741, 8870, 8890, 8896, 8907, 9025, 9955, 10052, 10919, 10994, 12444, 12724, 14657, 14957, 15080, 15081	<code>\quotedblbase</code> . . .	15242, 15481, 17915, 20025	<code>\RerunFileCheck</code>	14744
<code>\protected@edef</code>	5210, 6643, 6737, 7316, 7458, 7478, 8239, 8243, 9424, 10514, 11048, 11131, 11655	<code>\quotesinglbase</code> . .	15252, 15483, 17909, 20027	<code>\Reset</code>	6261
<code>\protected@write</code> . . .	2602, 5137, 5400, 8136, 8574, 8589, 8597, 8601, 8606, 14656	R		<code>\reset@font</code>	8084, 8107, 8871, 8891, 8908, 9026
<code>\protected@xdef</code> . . .	7717, 7810	<code>\r</code>	891, 15117, 15129, 15141, 15354, 15420, 15530, 15570, 15597, 15627, 15800, 15867, 16164, 16166, 17854, 17856	<code>\reve</code>	16440, 20316
<code>\providecommand</code>	2619, 2620, 3651, 3652, 3655, 3656, 4588, 4807, 4808, 4927, 5070, 5387, 5445, 6473, 6767, 6792, 6917, 6956, 6959, 6962, 6963, 6964, 6966, 6967, 6968, 6969, 6971, 6972, 6973, 6974, 6975, 6976, 6985, 6986, 6987, 6988, 6989, 6990, 7452, 7974, 7975, 7990, 8068, 8671, 8672, 8676, 8681, 8682, 8789, 9098, 9099, 9100, 9101, 9102, 9103, 9104, 9105, 9106, 9107, 9108, 9109, 9110, 9111, 9112, 9113, 9114, 9115, 9116, 9117, 9179, 9401, 9419, 9420, 9943, 10046, 10047, 10310, 10372, 10373, 10374, 10845, 10964, 10986, 10987, 10988, 11463, 11842, 11843, 12200, 12208, 12209, 12210, 12211, 12283, 12295, 12296, 12297, 12298, 12342, 12383, 12384, 12385, 12386, 12541, 12543, 12544, 12657, 12658, 12705, 13447, 14223	<code>\ra</code>	20207	<code>\Rewind</code>	19179, 20821
<code>\psdaliasnames</code> . . .	21154, 21497	<code>\Radiation</code>	19239, 21411	<code>\RewindToIndex</code> . .	18986, 20806
<code>\psdmapshortnames</code>	20283, 21153	<code>\Radioactivity</code>	19237, 20843	<code>\RHD</code>	19170, 20818
<code>\Psi</code>	16839, 20354	<code>\raff</code>	20251	<code>\rhd</code>	18786, 20722
<code>\psi</code>	16906, 20378	<code>\Rain</code>	19420, 20898	<code>\rho</code>	16892, 20371
<code>\PushButton</code>	6252	<code>\raise</code>	2672, 5181, 10021, 10105, 10143, 10183, 11907, 12513, 12793	<code>\rhoinferior</code>	20388
<code>\put@me@back</code>	5350, 5363, 5373	<code>\rangle</code>	18944, 20790	<code>\rhohooknearrow</code>	19642, 20999
<code>\pwedge</code>	16619, 21257	<code>\rbrackdbl</code>	20984	<code>\rhohookswarrow</code> . . .	19646, 21001
<code>\pxfonts</code>	19927	<code>\rcurvearrowdown</code> . .	19667, 21008	<code>\Rightarrow</code>	8823, 18297, 20514
Q		<code>\rcurvearrowleft</code> . . .	19671, 21009	<code>\rightarrow</code>	20464
<code>\Q</code>	1946	<code>\rcurvearrowne</code> . . .	19651, 21003	<code>\rightarrowtail</code>	18211, 20481
<code>\qaf</code>	20231	<code>\rcurvearrowright</code> . .	19674, 21010	<code>\rightarrowtriangle</code>	18342, 20533
<code>\quarternote</code>	19354, 20873	<code>\rcurvearrowse</code> . . .	19660, 21006	<code>\rightbarharpoon</code> . .	19705, 21021
		<code>\Re</code>	18093, 20452	<code>\RIGHTCIRCLE</code> . . .	19193, 20827
		<code>\ReadBookmarks</code>	4333, 4370, 4508, 4711, 4851, 14816, 14851	<code>\rightharpoondown</code>	18252, 20497
		<code>\real@setref</code>	8867, 8933	<code>\rightharpoonup</code> . . .	18249, 20496
		<code>\realfootnote</code>	7807	<code>\rightleftarrows</code> . . .	18261, 20500
		<code>\Rectangle</code>	19593, 20976	<code>\rightleftharpoon</code> . .	19678, 21012
		<code>\RectangleBold</code> . . .	19595, 20977	<code>\rightleftharpoons</code> . .	18281, 20508
		<code>\RectangleThin</code> . . .	19591, 20975	<code>\rightModels</code>	18769, 21366
		<code>\recycle</code>	19369, 20879	<code>\rightmoon</code>	19262, 20852
		<code>\Recycling</code>	19371, 21451	<code>\rightpointleft</code> . . .	19231, 21407
		<code>\Ref</code>	8952, 8956, 8961	<code>\rightrightarrows</code> . .	18273, 20505
		<code>\ref</code>	674, 4500, 4827, 5459, 6385, 6386, 6455, 6456, 7772, 7779, 8971, 12816	<code>\rightrightharpoons</code>	19693, 21017
		<code>\ref@one</code>	5092, 5093	<code>\RightScissors</code> . . .	19434, 21458
		<code>\rEfLiNK</code>	12817, 12818	<code>\rightslice</code>	19847, 21081
		<code>\refstepcounter</code>	6994, 7001, 7021, 7298, 7321, 7322, 7323, 7332, 7357, 7381, 7391, 7506, 7937	<code>\rightsquigarrow</code> . .	18322, 20525
		<code>\rem@ptetc</code>	11590, 11592	<code>\rightthreetimes</code> . .	18821, 20736
		<code>\renewcommand</code>	2594, 8490, 14732	<code>\RightTorque</code>	19664, 21466
		<code>\Request</code>	18974, 20801	<code>\Righttorque</code>	19665, 21467
		<code>\RequirePackage</code>	22, 233, 235, 236, 237, 255, 256, 257, 258, 259, 260, 261, 262, 263, 391, 1321, 1848, 2588, 3011, 3085, 4482, 4483, 4779, 4823, 4855, 5062, 5462, 6425, 6583, 6833, 9250, 10846, 12710, 14742	<code>\rightVdash</code>	18761, 21365
				<code>\rightvdash</code>	18737, 21357
				<code>\rinferior</code>	20383
				<code>\riota</code>	18106, 20454
				<code>\risingdoteq</code>	20619
				<code>\risingdotseq</code>	18545
				<code>\rlap</code>	5178, 9376, 10481
				<code>\rm</code>	615
				<code>\rmfamily</code>	605
				<code>\Roman</code>	6733
				<code>\roman</code>	6734
				<code>\romannumeral</code>	1037, 1038
				<code>\rotm</code>	16521, 21233
				<code>\rotOmega</code>	16612, 21255
				<code>\rotr</code>	16557, 21243
				<code>\rotvara</code>	16420, 21205

`\rotw` 16623, 21259
`\roty` 16627, 21261
`\rrbracket` 19612, 21465
`\Rrightarrow` 18318, 20523
`\rrparenthesis` 19720, 21027
`\rtaild` 20315
`\rtimes` 18817, 20734
`\rule` 7757

S

`\S` 15737, 21168
`\sad` 20215
`\Sagittarius` 19323, 21441
`\sagittarius` 19321, 20869
`\Saturn` 19287, 21429
`\saturn` 19285, 20857
`\sbox` ... 3947, 5161, 5193, 6281,
10008, 10088, 10125, 10165,
11842, 11881, 12500, 12775,
13423
`\scd` 17527, 20380
`\scg` 16475, 20322
`\schwa` 16443, 20317
`\schwainferior` 20438
`\sci` 16502, 20327
`\ScissorHollowRight` 19438, 20904
`\ScissorRight` 19432, 20902
`\ScissorRightBrokenBottom` ...
..... 19428
`\ScissorRightBrokenTop` . 19436,
20903
`\scn` 16538, 20328
`\Scorpio` 19320, 21440
`\scorpio` 19318, 20868
`\scr` 16580, 20331
`\scr@LT@array` 7331
`\scripta` 16413, 20313
`\scriptg` 16472, 20321
`\scriptsize` 623
`\scriptstyle` 8074
`\scriptv` 16614, 20336
`\scrollmode` .. 1863, 1888, 1898,
1911, 2018, 2151
`\scshape` 611, 7495, 7523
`\scu` 17545, 20381
`\scy` 16628, 20340
`\Searrow` 18312, 20520
`\searrow` 18187, 20470
`\Sech` 19987, 21133
`\second` 17936, 20399
`\section` 8791
`\sectionautorefname` 3324, 3342,
3360, 3378, 3396, 3414,
3432, 3461, 3490, 3508, 9110
`\seen` 20211
`\selectfont` 591, 4790, 13516
`\SePa` 19973, 21127

`\set@display@protect` 4435
`\setbox` 1954, 1960, 1966,
3679, 3685, 5165, 5178,
6043, 6591, 7585, 9366,
9932, 10454, 10471, 13915,
14004, 14040, 14070, 14098,
14127, 14152
`\setcounter` 5005
`\setkeys` 4980, 5025
`\setlength` 521,
522, 2669, 5149, 6055, 9856,
9857, 9862, 9866, 9871,
9875, 9881, 9884, 9888,
9891, 10967, 10970, 10974,
10977, 11314, 14974, 15045
`\setminus` 18393, 20556
`\setpdfinkmargin` .. 4146, 4147,
9391
`\settowidth` 13081, 13596, 13944
`\SetupKeyvalOptions` 2723, 4324
`\seveninferior` 20426
`\sevensuperior` 20410
`\sffamily` 606
`\shadda` 20261
`\sharp` 19367, 20878
`\sheen` 20213
`\shortciteN` 8199
`\shuffle` 19758, 21042
`\Sigma` 16829, 20351
`\sigma` 16896, 20373
`\sim` 18473, 20588
`\simeq` 18489, 20595
`\sinferior` 20445
`\SixFlowerAlternate` 19545, 20955
`\SixFlowerAltPetal` 19555, 20960
`\SixFlowerOpenCenter` .. 19541,
20953
`\SixFlowerPetalRemoved` . 19538,
20952
`\sixinferior` 20425
`\SixStar` 19528, 20947
`\sixsuperior` 20409
`\SixteenStarLight` . 19536, 20951
`\sixteenthnote` 19361, 20875
`\SK@` 9084
`\SK@ref` 9084
`\SK@ref` 9081
`\skip@` .. 1968, 2051, 2052, 2055,
2057, 2688, 2694, 2707, 2713
`\slashc` 16404, 20312
`\slashdiv` 19934, 21120
`\slide` 8262
`\slide@ccline` .. 8809, 8822, 8830,
8840, 8848
`\Slide@contents` 8814
`\slide@contents` 8807
`\slide@heading` 8685

`\slide@subheading` 8738
`\slide@undottedcline` 8800
`\slidenumberline` ... 8801, 8809,
8823, 8831, 8841, 8849
`\SliTeX` 583
`\slshape` 612
`\small` 624
`\smallin` 18367, 20545
`\smallowns` 18375, 20548
`\smash` 2666
`\smile` 18938, 20787
`\Smiley` 19254, 21416
`\smiley` 19252, 20848
`\Snowflake` 19559, 20962
`\SnowflakeChevron` 19557, 20961
`\SnowflakeChevronBold` .. 19561,
20963
`\sofpasuq` 17461
`\softsign` 17104, 21278
`\spacefactor` .. 2645, 2651, 7676,
7685, 7835, 7837, 9404, 9412
`\spadesuit` . 19333, 19335, 21445
`\Sparkle` 19563, 20964
`\SparkleBold` 19565, 20965
`\special@paper` 4292
`\SpecialDvipdfmxOutlineOpen` .
. 3124, 3126, 4679, 4686
`\sphericalangle` ... 18412, 20564
`\splitmaxdepth` 7751
`\splittopskip` 7750
`\sqcap` 18698, 20691
`\sqcup` 18700, 20692
`\sqdoublecap` 19785, 21054
`\sqdoublecup` 19790, 21056
`\sqsubset` 18682, 20683
`\sqsubseteq` 18690, 20687
`\sqsubsetneq` 18879, 20762
`\sqsupset` 18686, 20685
`\sqsupseteq` 18694, 20689
`\sqsupsetneq` 18882, 20763
`\SquareCastShadowBottomRight`
..... 19584, 20972
`\SquareCastShadowTopRight` ..
..... 19587, 20973
`\Squaredot` 15772, 21171
`\squaredots` 18466, 20585
`\SquareShadowBottomRight` ...
..... 19578, 20970
`\SquareShadowTopRight` . 19581
`\SquareTopRight` 20971
`\SS` 15479, 20011
`\ss` ... 3371, 15408, 15494, 15855
`\sslash` 19925, 21116
`\st@rredfalse` 7364, 7373
`\star` 18807, 20730

<code>\stepcounter</code>	<code>\succnsim</code>	<code>\textacutedbl</code>
7011, 7246, 7315, 7477, 7677, 7809, 10497, 14653	18891, 20767	16753
<code>\stockheight</code> .. 4296, 9890, 9891, 10834, 10835, 10973, 10974, 12272, 12273	<code>\succsim</code>	<code>\textacutemacron</code> 15563, 15590, 15617, 17633, 17636, 17737, 17740
<code>\stockwidth</code> .. 9887, 9888, 10833, 10835, 10976, 10977, 12271, 12273	<code>\sukun</code>	<code>\textainferior</code>
<code>\stop@hyper</code>	18381, 20551	18023, 20434
<code>\StringEncodingConvertTest</code> 807, 817	<code>\Sun</code>	<code>\textaleph</code>
<code>\strip@period</code>	19259, 21417	18117, 20456
<code>\strip@prefix</code> 62, 2600, 6545, 7164, 7461, 14880, 14888, 14903	<code>\sun</code>	<code>\textAlpha</code> .. 1238, 16779, 16796
<code>\strip@pt</code>	19257, 20850	<code>\textalpha</code> .. 1238, 16850, 16861, 20356
526, 533, 4308, 6075, 6088, 9862, 9866, 9871, 9875, 11317, 14375, 14440, 14469, 14509, 14560	<code>\SunCloud</code>	<code>\textamalg</code>
<code>\strip@pt@and@otherjunk</code> 11525, 11557, 11592	<code>\SunCloud</code>	18380, 20550
<code>\strutbox</code>	<code>\SunshineOpenCircled</code> ... 19553, 20959	<code>\textampersand</code> 565, 15184, 15651, 15652, 15653, 21160, 21161
<code>\sub@label</code>	<code>\Supset</code>	<code>\textangle</code>
2594	18837, 20743	18409, 20562
<code>\subeqnarray</code>	<code>\supset</code>	<code>\textangstrom</code>
7437, 7439	18660, 20672	18109
<code>\subequations</code>	<code>\supseteq</code>	<code>\textAnkh</code>
7475, 7476	18668, 20676	19243, 20845
<code>\subfig@oldlabel</code>	<code>\supseteqq</code>	<code>\textaoilig</code> .. 19954, 19956, 21491
2596	19889, 21102	<code>\textAPLbox</code> 18981, 20804
<code>\Submit</code>	<code>\supsetneq</code>	<code>\textAPLdownarrowbox</code> . 18970, 20799
6258	18676, 20680	<code>\textAPLinput</code> ... 18973, 20800
<code>\SubmitObject</code>	<code>\surd</code>	<code>\textAPLinv</code> 18947, 20791
13736	8831, 20559	<code>\textAPLleftarrowbox</code> ... 18962, 20796
<code>\SubmitPObject</code>	<code>\Swarrow</code>	<code>\textAPLrightarrowbox</code> .. 18965, 20797
13736	18314, 20521	<code>\textAPLuparrowbox</code> ... 18967, 20798
<code>\subparagraphautorefname</code> 3328, 3346, 3364, 3382, 3400, 3418, 3436, 3469, 3471, 3494, 3512, 9114	<code>\swarrow</code>	<code>\textapprox</code>
14720	18190, 20471	18499, 20599
<code>\subsection</code>	T	<code>\textapproxeq</code> 18504, 20601
12537	<code>\T</code>	<code>\textaquarius</code> 19328, 19329, 20871, 21443
<code>\subsectionautorefname</code>	20191	<code>\textaries</code> .. 19298, 19299, 20861, 21433
.. 3325, 3343, 3361, 3379, 3397, 3415, 3433, 3466, 3491, 3509, 9111	<code>\t</code> .. 15149, 15560, 15587, 15614, 15632	<code>\textasciicute</code>
<code>\Subset</code>	<code>\T@nameref</code>	15763
18833, 20741	4844	<code>\textasciibreve</code> ... 15160, 15574, 15601, 16742
<code>\subset</code>	<code>\T@pageref</code> ... 4814, 4831, 8969	<code>\textasciicaron</code> ... 15118, 15130, 15142, 15162, 15571, 15598, 16728
18658, 20671	<code>\T@ref</code>	<code>\textasciicircum</code> .. 15114, 15126, 15138, 15200, 15567, 15594, 15701
<code>\subseteq</code>	4809, 4828	<code>\textasciidieresis</code> . 15116, 15128, 15140, 15297, 15569, 15596, 15739
18666, 20675	<code>\T@temp</code>	<code>\textasciigrave</code> ... 15112, 15124, 15136, 15205, 15565, 15592, 15706
<code>\subseteqq</code>	<code>\Ta</code>	<code>\textasciimacron</code> . 15121, 15133, 15145, 15310, 15576, 15603, 15752
19885, 21100	<code>\taa</code>	<code>\textasciitilde</code> 566, 4890, 15215, 15718
<code>\subsetneq</code>	<code>\tableautorefname</code> .. 3320, 3338, 3356, 3374, 3392, 3410, 3428, 3458, 3486, 3504, 9106	<code>\textast</code>
18674, 20679	<code>\tagform@</code>	18396, 20557
<code>\subsubsectionautorefname</code> 3326, 3344, 3362, 3380, 3398, 3416, 3434, 3467, 3492, 3510, 9112	<code>\taild</code>	<code>\textAsterisk</code> 19544, 20954
<code>\succ</code>	16434, 21210	<code>\textAsteriskBold</code> . 19521, 20943
18640, 20662	<code>\tailnvr</code>	
<code>\succapprox</code>	16565, 21245	
19877, 21096	<code>\taill</code>	
<code>\succcurlyeq</code>	16514, 21230	
18644, 20664	<code>\tailn</code>	
<code>\succeq</code>	16537, 21239	
19853, 21084	<code>\tailr</code>	
<code>\succeqq</code>	16571, 21247	
19865, 21090	<code>\tails</code>	
<code>\succnapprox</code> 19883, 21099	<code>\tailt</code>	
<code>\succneq</code>	16587, 21250	
19859, 21087	<code>\tailz</code>	
<code>\succneqq</code>	16605, 21253	
19871, 21093	<code>\tailz</code>	
	16633, 21262	
	<code>\Tape</code>	
	19442, 20906	
	<code>\tatweel</code>	
	20227	
	<code>\tau</code>	
	16898, 20374	
	<code>\Taurus</code>	
	19302, 21434	
	<code>\taurus</code>	
	19300, 20862	
	<code>\tchek</code>	
	20267	
	<code>\Telefon</code>	
	19212, 21402	
	<code>\temp@online</code> 8353, 8356	
	<code>\Tent</code>	
	19426, 20901	
	<code>\tesh</code>	
	16705, 21275	
	<code>\TeX</code> .. 573, 574, 581, 583, 12844, 12846, 12848	
	<code>\texorpdfstring</code> 1008, 6440	
	<code>\textAcht</code>	
	19986, 21132	
	<code>\textAcPa</code>	
	19972, 21126	
	<code>\textacute</code> .. 15113, 15125, 15137, 15320, 15566, 15593, 15762	

<code>\textasteriskcentered</code>	15661	<code>\textbigdoublevee</code> .	19765, 21045	<code>\textcentoldstyle</code> . .	16406, 21200	
<code>\textAsteriskCenterOpen</code> .	19523, 20944	<code>\textbigdoublewedge</code>	19763, 21044	<code>\textCESign</code> 20023, 20024, 21147, 21496		
<code>\textAsteriskRoundedEnds</code>	19568, 20966	<code>\textbigtriangledown</code>	19177, 19178, 20820, 21399	<code>\textCheckedbox</code> .	19217, 19218, 20836, 21404	
<code>\textasympt</code>	18517, 20607	<code>\textbigtriangleup</code> 19162, 19163, 19164, 20815, 21396, 21397		<code>\textCheckmark</code> .	19465, 19466, 20916, 21462	
<code>\textbabygamma</code> . .	16483, 20324	<code>\textBiohazard</code> . . .	19241, 20844	<code>\textCheckmarkBold</code>	19468, 20917	
<code>\textbackcong</code>	18513, 20605	<code>\textblacksmiley</code> . .	19256, 20849	<code>\textChi</code>	1288, 16838	
<code>\textbackepsilon</code>	16940	<code>\textblank</code>	18989	<code>\textchi</code>	1288, 16905, 20377	
<code>\textbackneg</code>	18919, 20778	<code>\textbot</code> . .	18750, 18751, 20710, 21361	<code>\textchiinferior</code> . . .	17564, 20390	
<code>\textbackprime</code> . . .	17941, 20401	<code>\textbowtie</code> 18812, 18813, 20732, 21378		<code>\textcirc</code>	18398, 20558	
<code>\textbacksim</code>	18477, 20589	<code>\textboxast</code>	19749, 21037	<code>\textcirceq</code>	18558, 20625	
<code>\textbacksimeq</code> . . .	18824, 20737	<code>\textboxbackslash</code> .	18959, 20795	<code>\textcirclearrowleft</code>	19615, 20985	
<code>\textbackslash</code> . .	561, 741, 2457, 15196, 15198, 15699	<code>\textboxbar</code>	19199, 20829	<code>\textcirclearrowright</code>	19617, 20986	
<code>\textbaht</code>	17524	<code>\textboxbox</code>	19753, 21039	<code>\textcircled</code> 15562, 15589, 15616, 18996, 18998, 19000, 19002, 19004, 19006, 19008, 19010, 19012, 19014, 19016, 19018, 19020, 19022, 19024, 19026, 19028, 19030, 19032, 19034, 19036, 19041, 19043, 19045, 19047, 19049, 19055, 19057, 19059, 19061, 19063, 19065, 19067, 19069, 19071, 19073, 19079, 19081, 19083, 19085, 19087, 19089, 19091, 19093, 19095, 19097, 19099, 19101, 19103, 19105, 19107, 19109, 19111, 19113, 19115, 19117, 19119, 19121, 19123, 19125, 19127, 19129, 19131, 19133, 19135, 19137, 19139, 19141, 19143, 19145, 19147, 19149, 19151		
<code>\textbar</code> . .	15211, 15713, 15714, 21163	<code>\textboxbslash</code>	19747, 21036	<code>\textCircledA</code> . . .	19038, 19039, 20808, 21391	
<code>\textbarb</code>	16203, 21184	<code>\textboxcircle</code>	19751, 21038	<code>\textcircledast</code> . . .	18722, 18723, 18724, 20699, 21355, 21356	
<code>\textbarc</code>	16408, 21201	<code>\textboxdot</code>	18734, 20704	<code>\textcircledcirc</code> . .	18718, 18719, 18720, 20698, 21353, 21354	
<code>\textbard</code>	15967, 21176	<code>\textboxempty</code> . .	19214, 19215, 20835, 21403	<code>\textcircledddash</code> . .	18726, 20700	
<code>\textbardbl</code> 17902, 17903, 21288		<code>\textboxminus</code>	18730, 20702	<code>\textcircledP</code>	18089	
<code>\textbardotlessj</code> . .	16465, 16466, 16467, 21217	<code>\textboxplus</code>	18728, 20701	<code>\textCircleShadow</code> .	19576, 20969	
<code>\textbarglotstop</code> . .	16687, 16688	<code>\textboxslash</code>	19745, 21035	<code>\textcirccircplus</code>	19772, 21048	
<code>\textbari</code> . .	16496, 16497, 16498, 20325, 21226	<code>\textboxtimes</code>	18732, 20703	<code>\textcirccircumflex</code>	15164	
<code>\textbarin</code>	18915, 20776	<code>\textbraceleft</code> 559, 2458, 15209, 15711		<code>\textcirccircumlow</code> . .	15582, 15609, 19960	
<code>\textbarl</code> . .	16226, 16227, 20310	<code>\textbraceright</code> 560, 2458, 15213, 15716		<code>\textCleaningF</code> . . .	19051, 20809	
<code>\textbarleftharpoon</code>	19703, 21020	<code>\textbrokenbar</code> . .	15293, 15732, 15733, 21166	<code>\textCleaningFF</code> . .	19053, 20810	
<code>\textbaro</code>	16542, 16544	<code>\textbullet</code> .	15217, 17924, 20396	<code>\textCleaningP</code> . . .	19075, 20811	
<code>\textbarp</code>	17569, 20392	<code>\textbulletoperator</code>	18400	<code>\textCleaningPP</code> . .	19077, 20812	
<code>\textbarrevglotstop</code>	16691, 16692	<code>\textbullseye</code>	16662, 16663, 16664, 16665, 21270, 21271	<code>\textclock</code> .	18925, 18926, 18927, 20781, 21387, 21388	
<code>\textbarrightharpoon</code>	19709, 21022	<code>\textBumpeq</code>	18522, 20609	<code>\textclosepsilon</code> . .	16669, 16670	
<code>\textbarsci</code>	17567, 20391	<code>\textbumpeq</code>	18526, 20611			
<code>\textbarscu</code>	17572, 20393	<code>\textcancer</code> 19307, 19308, 20864, 21436				
<code>\textbaru</code> . .	16607, 16608, 16609, 20334, 21254	<code>\textCap</code> . .	18842, 18843, 20745, 21381			
<code>\textbarwedge</code>	18806, 20729	<code>\textcap</code>	18438, 20573			
<code>\textbbslash</code> 18993, 18994, 20807, 21390		<code>\textcapdot</code>	19789, 21055			
<code>\textBeam</code>	18977, 20802	<code>\textcapricornus</code> .	19325, 19326, 20870, 21442			
<code>\textbecause</code> 18462, 18463, 20583, 21330		<code>\textccnc</code>	20015, 21144			
<code>\textbeltl</code> . .	16508, 16509, 16510, 21229	<code>\textccnd</code>	20017			
<code>\textBeta</code>	1239, 16798	<code>\textccsa</code>	20019, 21145			
<code>\textbeta</code> . . .	1239, 15494, 16863, 20357	<code>\textcdj</code>	16676			
<code>\textbetainferior</code> . .	17556, 20386	<code>\textcdot</code> . .	15493, 20037, 21152			
<code>\textbeth</code>	18119, 20457	<code>\textcdots</code>	18909, 20773			
<code>\textbetween</code>	18610, 20648	<code>\textcedilla</code> 15120, 15132, 15144, 15328, 15573, 15600, 15774				
<code>\textbf</code>	598	<code>\textcelsius</code>	15480, 18079			
<code>\textBicycle</code>	20006, 21141	<code>\textcent</code>	15285, 15722			
<code>\textbigcircle</code>	15589, 15616, 19201, 19202, 20830, 21401					

<code>\textcloseomega</code> . . .	16548, 16549, 16550, 16551, 21240, 21241
<code>\textcloserevepsilon</code> . . .	16461, 16462, 16463, 21216
<code>\textCloud</code>	19205, 20831
<code>\textClowerTips</code> . . .	19501, 20933
<code>\textclubsuitblack</code> . . .	2579, 19344, 19345, 21449
<code>\textclubsuitwhite</code>	19353
<code>\textCoffeecup</code>	19224, 20838
<code>\textcoloncolonequals</code> . . .	19809, 21063
<code>\textcolonequals</code> . . .	18550, 20621
<code>\textcolonmonetary</code>	18049
<code>\textcolor</code>	636, 13478, 13521, 13524, 13854
<code>\textcommatailz</code>	16374, 16375
<code>\textcomplement</code>	18349, 20536
<code>\textcompwordmark</code>	17896
<code>\textcong</code>	18494, 20597
<code>\textcopyleft</code>	20012, 20013
<code>\textcopyright</code>	15299, 15741, 20300
<code>\textcorner</code>	16762, 16763
<code>\textCR</code>	15158, 15639
<code>\textcrb</code>	16199, 16200, 16201, 16203, 16204, 21183, 21184, 21185
<code>\textcrd</code>	15962, 15964, 15965, 15967, 15968, 21175, 21176, 21177
<code>\textcrg</code>	16292, 21197
<code>\textcrh</code>	16013, 21178
<code>\textcrinvglotstop</code> . . .	16253, 16254
<code>\textcrlambda</code>	16230, 16231, 16232, 16233, 16234, 16235, 21189, 21190, 21191, 21192
<code>\textCross</code>	19484, 20925
<code>\textCrossedbox</code>	19220, 19221, 19222, 20837, 21405, 21406
<code>\textCrossMaltese</code> . . .	19490, 20928
<code>\textCrossOpenShadow</code> . .	19486, 20926
<code>\textCrossOutline</code> . . .	19488, 20927
<code>\textcrtwo</code>	16250, 16251
<code>\textctc</code>	16429, 16430, 16431, 21209
<code>\textctd</code>	16372, 16373
<code>\textctesh</code>	16596, 16597, 16598, 21251
<code>\textctj</code>	16677, 16678, 21272
<code>\textctjvar</code>	16678, 21272
<code>\textctn</code>	16392, 16393
<code>\textctt</code>	16394, 16395
<code>\textctyogh</code>	16641, 16642, 16643, 21264
<code>\textctz</code>	16634, 16635, 16636, 21263
<code>\textCup</code>	18845, 18846, 20746, 21382
<code>\textcup</code>	18440, 20574
<code>\textcupdot</code>	18679, 20681
<code>\textcupplus</code>	18681, 20682
<code>\textcurlyeqprec</code>	18864, 20754
<code>\textcurlyeqsucc</code>	18868, 20756
<code>\textcurlyvee</code>	18828, 18829, 20739, 21379
<code>\textcurlywedge</code>	18831, 18832, 20740, 21380
<code>\textcurrency</code>	15289, 15728
<code>\textcurvearrowleft</code>	18233, 20490
<code>\textcurvearrowright</code>	18235, 20491
<code>\textCuttingLine</code>	19153, 19154, 19155, 19156, 20813, 21392, 21393, 21394
<code>\textdagger</code>	15219, 17917, 17918, 20395, 21289
<code>\textdaggerdbl</code>	15221, 17920, 17921, 17922, 21290, 21291
<code>\textdaleth</code>	18123, 20459
<code>\textdanger</code>	19395, 20890
<code>\textdasheddownarrow</code> . . .	18334, 20529
<code>\textdasheduparrow</code>	18329, 20527
<code>\textdashleftarrow</code>	18326, 18327, 20526, 21316
<code>\textdashrightarrow</code>	18331, 18332, 20528, 21317
<code>\textDashV</code>	19907, 19908, 21108, 21485
<code>\textDashv</code>	19900, 19901, 21106, 21483
<code>\textdashV</code>	19894, 19895, 21104, 21481
<code>\textdashv</code>	18739, 18740, 20706, 21358
<code>\textDavidStar</code>	19492, 19493, 20929, 21463
<code>\textdblig</code>	16398, 16400, 21198
<code>\textdctzlig</code>	16699, 16700
<code>\textddagger</code>	15222
<code>\textddots</code>	18913, 20775
<code>\textdegree</code>	15312, 15480, 15754
<code>\textDeleatur</code>	18072, 18073, 20447, 21302
<code>\textDelta</code>	1241, 16802, 20346
<code>\textdelta</code>	1241, 16867, 20359
<code>\textDiamondSolid</code>	19590, 20974
<code>\textdiameter</code>	18917, 20777
<code>\textdiamond</code>	19187, 19188, 20824, 21400
<code>\textdiamonddots</code>	17963, 20404
<code>\textdiamondsuitblack</code> . . .	2580, 19351
<code>\textdiamondsuitwhite</code> . . .	19341, 19342, 21448
<code>\textDigammagreek</code>	16926
<code>\textdigammagreek</code>	16928, 16929, 21276
<code>\textdiscount</code>	17957
<code>\textdiv</code>	15491, 20035, 21150
<code>\textdivide</code>	15460, 15491, 15908, 20035
<code>\textdivideontimes</code>	18810, 20731
<code>\textDivides</code>	18390, 20554
<code>\textDividesNot</code>	18392, 20555
<code>\textdivorced</code>	19409
<code>\textdlsh</code>	18230, 20489
<code>\textdollar</code>	563, 15180, 15645, 15646, 15647, 21158, 21159
<code>\textdong</code>	18059
<code>\textdotaccent</code>	15119, 15131, 15143, 15166, 15572, 15599, 16744
<code>\textdotbelow</code>	15123, 15135, 15147, 15190, 15586, 15613, 16769
<code>\textdotdiv</code>	18470, 21331
<code>\textdoteq</code>	18530, 20613
<code>\textdoteqdot</code>	18535, 18536, 20615, 21337
<code>\textdotminus</code>	18469, 18470, 20586, 21331
<code>\textdotplus</code>	18388, 20553
<code>\textdottimes</code>	19777, 21050
<code>\textdoublebarpipe</code>	16266, 16267, 16268, 21196
<code>\textdoublebarpipevar</code> . . .	16268, 21196
<code>\textdoublebarwedge</code>	19800, 21059
<code>\textdoublegrave</code>	15575, 15602, 16765
<code>\textdoublepipe</code>	16262, 16263, 16264, 21195
<code>\textdoublepipevar</code>	16264, 21195
<code>\textdoublevee</code>	19796, 19797, 21058, 21480
<code>\textdoublevertline</code>	17903, 21288
<code>\textdoublewedge</code>	19794, 21057
<code>\textDOWNarrow</code>	19173, 19174, 20819, 21398
<code>\textDownarrow</code>	18301, 20515
<code>\textdownarrow</code>	18175, 18176, 18177, 20465, 21310, 21311
<code>\textdownarrowdownarrows</code> . . .	18276, 20506
<code>\textdownarrowdownharpoons</code> .	19697, 21018

<code>\textdownharpoonleft</code> . . . 18259, 20499	<code>\textequiv</code> . 18574, 18575, 20632, 21341	<code>\textfl</code> 778, 15258, 19964
<code>\textdownharpoonright</code> . . 18256, 20498	<code>\textEreversed</code> 16212	<code>\textFlag</code> . . 19375, 19376, 20881, 21452
<code>\textdownmodels</code> . . 19913, 21110	<code>\textesh</code> . . . 16588, 16589, 20333	<code>\textflat</code> 19364, 20876
<code>\textdownstep</code> 19943, 19944	<code>\textestimated</code> . . . 18111, 18112, 18113, 21304, 21305	<code>\textflorin</code> . 15230, 16215, 16216, 21186
<code>\textdownuparrows</code> 18339, 20531	<code>\textEta</code> . . . 1245, 16783, 16808	<code>\textflq</code> 664, 15487, 20031
<code>\textdownupharpoons</code> . . . 19715, 21024	<code>\texteta</code> 1245, 16854, 16873, 20362	<code>\textflqq</code> 662, 15485, 20029
<code>\textdsbiological</code> . . 19389, 20887	<code>\texteuro</code> . . 15281, 18061, 18062, 18063, 18064, 18065, 18066, 18067, 18068, 18069, 18070, 21293, 21294, 21295, 21296, 21297, 21298, 21299, 21300, 21301	<code>\textforall</code> 18347, 20535
<code>\textdschemical</code> . . . 19387, 20886	<code>\textexclamdown</code> 779, 1149, 15283, 15720	<code>\textForward</code> 19166, 20816
<code>\textdscommercial</code> . 19391, 20888	<code>\textexists</code> 18353, 20538	<code>\textForwardToIndex</code> 18984, 20805
<code>\textdsjuridical</code> . . . 19385, 20885	<code>\textfallingdoteq</code> . . 18541, 20617	<code>\textFourAsterisk</code> . 19495, 20930
<code>\textdsmedical</code> 19383, 20884	<code>\textfatsemi</code> 19770, 21047	<code>\textfourfifths</code> 18149
<code>\textdsmilitary</code> . . 19380, 19381, 20883, 21453	<code>\textFax</code> . . 20001, 20002, 21139, 21495	<code>\textfourinferior</code> . . 18001, 20423
<code>\textdstimes</code> 19780, 21051	<code>\textfax</code> 18125, 20460	<code>\textFourStar</code> 19503, 20934
<code>\textdyoghlig</code> 16696, 16697	<code>\textfemale</code> 19269, 21419	<code>\textFourStarOpen</code> 19505, 20935
<code>\textdzlig</code> . 16693, 16694, 16695, 21274	<code>\textFemaleFemale</code> 19397, 20891	<code>\textfoursuperior</code> . . 17969, 20407
<code>\textearth</code> . 19275, 19276, 20854, 21424	<code>\textFemaleMale</code> . . 19401, 20893	<code>\textfourth</code> 17961, 20403
<code>\textEightAsterisk</code> . 19574, 20968	<code>\textfi</code> 777, 15256, 19962	<code>\textfractionsolidus</code> 15232, 17951
<code>\textEightFlowerPetal</code> . . . 19552, 20958	<code>\textField</code> 6243	<code>\textfrown</code> 18937, 20786
<code>\textEightFlowerPetalRemoved</code> 19571, 20967	<code>\textFinv</code> 18115, 20455	<code>\textfrownie</code> 19250, 19251, 20847, 21415
<code>\texteightinferior</code> . . 18009, 20427	<code>\textFire</code> 20004, 21140	<code>\textfrq</code> 665, 15488, 20032
<code>\textEightStar</code> 19531, 20948	<code>\textfishhookr</code> . . . 16573, 16574, 16575, 16576, 21248, 21249	<code>\textfrqq</code> 663, 15486, 20030
<code>\textEightStarBold</code> 19533, 20949	<code>\textfivedots</code> 19939, 21121	<code>\textfullnote</code> 19978, 19979, 21129, 21492
<code>\textEightStarConvex</code> . . . 19527, 20946	<code>\textfiveeighths</code> 18159	<code>\textGame</code> 18127, 20461
<code>\textEightStarTaper</code> 19525, 20945	<code>\textFiveFlowerOpen</code> . . . 19550, 20957	<code>\textGamma</code> 1240, 16800, 20345
<code>\texteightsuperior</code> . 17977, 20411	<code>\textFiveFlowerPetal</code> 19548, 20956	<code>\textgamma</code> . 1240, 16865, 20358
<code>\texteinferior</code> 18025, 20435	<code>\textfiveinferior</code> . . . 18003, 20424	<code>\textgammainferior</code> 17558, 20387
<code>\textell</code> 18085, 20450	<code>\textfivesixths</code> 18153	<code>\textGaPa</code> 19966, 21123
<code>\textellipsis</code> . . . 569, 570, 15224, 17928, 17929, 21292	<code>\textFiveStar</code> 19207, 20832	<code>\textge</code> 18587, 20637
<code>\textemdash</code> . 775, 15226, 17900	<code>\textFiveStarCenterOpen</code> 19509, 20937	<code>\textgemini</code> 19304, 19305, 20863, 21435
<code>\textemptyset</code> . . . 18357, 18358, 20540, 21318	<code>\textFiveStarConvex</code> 19517, 20941	<code>\textGentsroom</code> . . . 20008, 21142
<code>\textendash</code> . . 776, 15228, 17898	<code>\textFiveStarOpen</code> 19209, 20833	<code>\textgeq</code> . . 18586, 18588, 20636, 21345
<code>\textEnvelope</code> . . . 19447, 19448, 20908, 21460	<code>\textFiveStarOpenCircled</code> 19507, 20936	<code>\textgeqq</code> 18594, 20640
<code>\textEpsilon</code> 1242, 16781, 16804	<code>\textFiveStarOpenDotted</code> 19511, 20938	<code>\textgeqslant</code> 19815, 21066
<code>\textepsilon</code> 577, 580, 1242, 16852, 16869, 20360	<code>\textFiveStarOutline</code> 19513, 20939	<code>\textgg</code> 18606, 20646
<code>\texteqcirc</code> 18554, 20623	<code>\textFiveStarOutlineHeavy</code> 19515, 20940	<code>\textggg</code> 18856, 20751
<code>\texteqcolon</code> 18472, 20587	<code>\textFiveStarShadow</code> 19519, 20942	<code>\textgimel</code> 18121, 20458
<code>\texteqdot</code> 19805, 21061	<code>\textfivesuperior</code> . . 17971, 20408	<code>\textglobfall</code> 18189, 21313
<code>\texteqsim</code> 18486, 20593		<code>\textglobrise</code> 18186, 21312
<code>\texteqslantgtr</code> . . . 19844, 21079		<code>\textglotstop</code> 16645, 16646, 16647, 16648, 20342, 21265, 21266
<code>\texteqslantless</code> . . . 19842, 21078		<code>\textglq</code> 660, 15483, 20027
<code>\textequalscolon</code> . . 18552, 20622		<code>\textglqq</code> 658, 15481, 20025
<code>\textequalsinferior</code> . 18017, 20431		<code>\textgnapprox</code> 19834, 21075
<code>\textequalsuperior</code> . 17985, 20415		<code>\textgneq</code> 19830, 21073
		<code>\textgneqq</code> 18600, 20643
		<code>\textgnsim</code> 18888, 20765
		<code>\textgravedbl</code> 16757

<code>\textgravemacron</code>	15564, 15591, 15618, 17627, 17630, 17731, 17734	<code>\texthth</code>	16488, 16489, 16490, 16491, 21223, 21224	<code>\textkappa</code>	1261, 16879, 20365
<code>\textgreater</code>	15194, 15695	<code>\texththeng</code>	16492, 16493, 16494, 21225	<code>\textKeyboard</code>	18941, 20788
<code>\textgrq</code>	661, 15484, 20028	<code>\texthtk</code>	16222, 16223, 16224, 21188	<code>\textkinferior</code>	18035, 20440
<code>\textgrqq</code>	659, 15482, 20026	<code>\texthtp</code>	16240, 16241	<code>\textkoppagreek</code>	1268, 16931
<code>\textGslash</code>	16289	<code>\texthtq</code>	16684, 16685	<code>\textkoppagreek</code>	1268, 16933
<code>\textgslash</code>	16291, 16292, 21197	<code>\texthtrtaild</code>	17576, 17577, 20394	<code>\textkra</code>	16054
<code>\textgtrapprox</code>	19823, 21070	<code>\texhtscg</code>	16672, 16673	<code>\textLadiesroom</code>	20010, 21143
<code>\textgtrdot</code>	18852, 20749	<code>\texhtt</code>	16245, 16246	<code>\textLambda</code>	1262, 16816, 20348
<code>\textgtreqless</code>	18862, 20753	<code>\texthungarumlaut</code>	15168, 15577, 15604, 16752	<code>\textlambda</code>	1262, 16881, 20366
<code>\textgtreqqlless</code>	19840, 21077	<code>\texthvlig</code>	16217, 16218, 16219, 21187	<code>\textlangle</code>	18943, 20789
<code>\textgtrless</code>	18633, 20658	<code>\textiint</code>	18447, 20577	<code>\textlatin</code>	646, 7152
<code>\textgtrsims</code>	18624, 18625, 20654, 21347	<code>\textiinferior</code>	17548, 20382	<code>\textlbrackdbl</code>	19608, 19609, 20983, 21464
<code>\textguarani</code>	18077	<code>\textiint</code>	18445, 20576	<code>\textlcurvearrowdown</code>	19663, 19664, 19665, 21007, 21466, 21467
<code>\texthalflength</code>	16739, 16740	<code>\textIm</code>	18083, 20449	<code>\textlcurvearrowse</code>	19655, 21004
<code>\texthalfnote</code>	19981, 19982, 21130, 21493	<code>\textin</code>	18364, 20543	<code>\textlcurvearrowsw</code>	19658, 21005
<code>\textHandCuffLeft</code>	19226, 20839	<code>\textInfo</code>	20021, 21146	<code>\textle</code>	18582, 20635
<code>\textHandCuffRight</code>	19228, 20840	<code>\textinfo</code>	18407, 20561	<code>\textleadsto</code>	19649, 21002
<code>\textHandLeft</code>	19230, 19231, 20841, 21407	<code>\textint</code>	18442, 18443, 20575, 21328	<code>\textLeftarrow</code>	18293, 20512
<code>\textHandRight</code>	19233, 19234, 19235, 19236, 20842, 21408, 21409, 21410	<code>\textinterleave</code>	19924, 21115	<code>\textleftarrow</code>	18167, 20462
<code>\textHaPa</code>	19968, 21124	<code>\textinterrobang</code>	17949	<code>\textleftarrowtail</code>	18210, 20480
<code>\texthateq</code>	18562, 18563, 18564, 20627, 21338, 21339	<code>\textinterrobangdown</code>	19936, 19937	<code>\textleftarrowtriangle</code>	18341, 20532
<code>\texthausaB</code>	16206, 20307	<code>\textinvamp</code>	18129, 18130, 18131, 21306, 21307	<code>\textleftbarharpoon</code>	19700, 21019
<code>\texthausaD</code>	16210, 20308	<code>\textinvbackneg</code>	18923, 20780	<code>\textLEFTCIRCLE</code>	19192, 20826
<code>\texthausaK</code>	16221, 20309	<code>\textinvbreve</code>	15539, 15579, 15606, 16335, 16337, 16344, 16346, 16347, 16353, 16355, 16365, 16367	<code>\textleftharpoondown</code>	18241, 20493
<code>\texthbar</code>	16012, 16013, 16014, 16015, 20306, 21178, 21179, 21180	<code>\textinvdiameter</code>	19723, 21028	<code>\textleftharpoonup</code>	18238, 20492
<code>\texthdotfor</code>	17926, 20397	<code>\textinve</code>	16287, 20311	<code>\textleftleftarrows</code>	18270, 20503
<code>\textheartsuitblack</code>	2581, 19349	<code>\textinvglotstop</code>	16655, 16656, 20344	<code>\textleftleftharpoons</code>	19688, 21015
<code>\textheartsuitwhite</code>	19337, 19338, 19339, 21446, 21447	<code>\textinvneg</code>	19784, 21053	<code>\textleftmoon</code>	19261, 20851
<code>\textheng</code>	19945, 19947, 21488	<code>\textinvsc</code>	16583, 16584, 20332	<code>\textLeftrightarrow</code>	18304, 20516
<code>\textHermaphrodite</code>	19403, 20894	<code>\textIota</code>	1260, 16785, 16812, 16846	<code>\textleftrightharpoon</code>	2584, 18179, 20466
<code>\texthexagon</code>	18979, 20803	<code>\textiota</code>	1260, 16856, 16877, 16911, 20364	<code>\textleftrightharpoons</code>	18268, 20502
<code>\texthexstar</code>	19414, 20896	<code>\textlotadieresis</code>	16794, 16845	<code>\textleftrightharpoontriangle</code>	18345, 20534
<code>\texthinferior</code>	18033, 20439	<code>\texttipagamma</code>	16479, 16480, 20323, 21220	<code>\textleftrightharpoon</code>	19677, 21011
<code>\texthookleftarrow</code>	18216, 20483	<code>\textisuperior</code>	17967, 20406	<code>\textleftrightharpoons</code>	18279, 20507
<code>\texthookrightarrow</code>	18218, 20484	<code>\textit</code>	600	<code>\textleftslice</code>	19846, 21080
<code>\textHslash</code>	16010	<code>\textJackStar</code>	19497, 20931	<code>\textleftspoon</code>	19606, 20982
<code>\texthslash</code>	18081, 20448	<code>\textJackStarBold</code>	19499, 20932	<code>\textleftsquigarrow</code>	18321, 20524
<code>\textHT</code>	15154, 15635	<code>\textjinferior</code>	19933, 21119	<code>\textlefttherefore</code>	17959, 20402
<code>\texthtb</code>	16421, 16422, 16423, 16424, 21206, 21207	<code>\textJoin</code>	19768, 21046	<code>\textleftthreetimes</code>	18820, 20735
<code>\texthtbardotlessj</code>	16591, 16592	<code>\textjupiter</code>	19283, 19284, 20856, 21428	<code>\textlengthmark</code>	16736, 16737
<code>\texthtc</code>	16207, 16208	<code>\textKappa</code>	1261, 16814	<code>\textleo</code>	19310, 19311, 20865, 21437
<code>\texthtd</code>	16435, 16436, 16437, 16438, 21211, 21212			<code>\textleq</code>	18581, 18583, 20634, 21344
<code>\texthtg</code>	16468, 16469, 16470, 21218			<code>\textleqq</code>	18590, 20638
				<code>\textleqslant</code>	19811, 21064
				<code>\textless</code>	15192, 15693

<code>\textlessapprox</code> . . .	19819, 21068	<code>\textltailm</code> .	16526, 16527, 16528, 16529, 21235, 21236	<code>\textMVFive</code>	15683, 20294
<code>\textlessdot</code>	18850, 20748	<code>\textltailn</code> .	16530, 16531, 16532, 16533, 21237, 21238	<code>\textMVFfour</code>	15681, 20293
<code>\textlesseqgtr</code>	18859, 20752	<code>\textltild</code> .	16505, 16506, 16507, 21228	<code>\textMVMinus</code>	15667, 20286
<code>\textlesseqqgtr</code> . . .	19837, 21076	<code>\textltimes</code>	18815, 20733	<code>\textMVNine</code>	15691, 20298
<code>\textlessgtr</code>	18631, 20657	<code>\textlyoghlig</code> .	16515, 16516, 16517, 21231	<code>\textMVOne</code>	15675, 20290
<code>\textlesssim</code>	18621, 18622, 20653, 21346	<code>\textmacronbelow</code> .	15122, 15134, 15146, 15203, 15585, 15612, 16771	<code>\textMVPeriod</code> . . .	15669, 20287
<code>\textLF</code>	15156, 15637	<code>\textmale</code> .	19278, 19279, 19280, 19281, 20855, 21425, 21426, 21427	<code>\textMVPlus</code>	15663, 20284
<code>\textLHD</code>	19185, 20823	<code>\textMaleMale</code>	19399, 20892	<code>\textMVSeven</code>	15687, 20296
<code>\textlhd</code>	18784, 18785, 20721, 21372	<code>\textManFace</code>	19996, 21137	<code>\textMVSix</code>	15685, 20295
<code>\textlhookfour</code> . . .	19948, 19950, 21489	<code>\textmanstar</code>	19393, 20889	<code>\textMVThree</code>	15679, 20292
<code>\textlhooknarrow</code> .	19641, 20998	<code>\textmapsto</code>	18214, 20482	<code>\textMVTwo</code>	15677, 20291
<code>\textlhooksearrow</code> .	19645, 21000	<code>\textmarried</code>	19407	<code>\textMVZero</code>	15673, 20289
<code>\textlhookt</code>	16243, 16244	<code>\textmd</code>	599	<code>\textnabla</code>	18362, 20542
<code>\textlhtlongi</code>	16578, 16579	<code>\textmeasuredangle</code> .	18411, 20563	<code>\textnaira</code>	18053
<code>\textlhtlongy</code>	16710, 16711	<code>\textmercury</code>	19265, 19266, 20853, 21418	<code>\textnapostrophe</code>	16088
<code>\textlibra</code>	19316, 19317, 20867, 21439	<code>\textmho</code>	18104, 18105, 20453, 21303	<code>\textnapprox</code>	18501, 18502, 20600, 21334
<code>\textlightning</code> . . .	18226, 18227, 20488, 21314	<code>\textmid</code>	18418, 20565	<code>\textnapproxeq</code> . . .	18506, 20602
<code>\textlinferior</code>	18037, 20441	<code>\textMineSign</code>	19378, 20882	<code>\textnasymp</code>	18519, 18520, 20608, 21336
<code>\textlira</code>	18051	<code>\textminferior</code>	18039, 20442	<code>\textnatural</code>	19366, 20877
<code>\textll</code>	18602, 20644	<code>\textminus</code>	15238, 18384	<code>\textnbackcong</code> . . .	18515, 20606
<code>\textllcorner</code>	18933, 20784	<code>\textminusdot</code>	19774, 19775, 21049, 21477	<code>\textnbacksim</code>	18479, 20590
<code>\textLleftarrow</code>	18317, 20522	<code>\textminusinferior</code> .	18015, 20430	<code>\textnbacksimeq</code> . .	18826, 20738
<code>\textlll</code>	18854, 20750	<code>\textminussuperior</code> .	17983, 20414	<code>\textnbumpeq</code>	18524, 20610
<code>\textllparentthesis</code> .	19719, 21026	<code>\textmoo</code>	19717, 21025	<code>\textnbumpeq</code>	18528, 20612
<code>\textlnapprox</code>	19832, 21074	<code>\textMoon</code>	19994, 21136	<code>\textncirceq</code>	18560, 20626
<code>\textlneq</code>	19827, 21072	<code>\textMountain</code>	19425, 20900	<code>\textncong</code>	18497, 20598
<code>\textlneqq</code>	18598, 20642	<code>\texttmp</code>	18386, 20552	<code>\textncurlyeqprec</code> .	18866, 20755
<code>\textlnot</code>	15306, 15748	<code>\textMu</code>	1263, 16818	<code>\textncurlyeqsucc</code> .	18870, 20757
<code>\textlnsim</code>	18886, 20764	<code>\textmu</code>	1263, 15322, 15765	<code>\textnDashV</code>	19910, 19911, 21109, 21486
<code>\textlogicalnot</code> . . .	15305, 15489, 15747, 20033	<code>\textmugreek</code>	16883, 20367	<code>\textnDashv</code>	19903, 19904, 21107, 21484
<code>\textLongleftarrow</code> .	19625, 20990	<code>\textmultimap</code>	18802, 20727	<code>\textndashV</code>	19897, 19898, 21105, 21482
<code>\textLongleftarrow</code> .	19619, 20987	<code>\textmultimapboth</code> .	19757, 21041	<code>\textndashv</code>	18742, 18743, 20707, 21359
<code>\textLongleftarrow</code> . .	19629, 20992	<code>\textmultimapdotbothA</code> .	18798, 20725	<code>\textnDoteq</code>	18538, 20616
<code>\textLongleftarrow</code> . .	19623, 20989	<code>\textmultimapdotbothB</code> .	18800, 20726	<code>\textndoteq</code>	18532, 20614
<code>\textlongleg</code>	16566, 16567, 16568, 20330, 21246	<code>\textmultiply</code>	15391, 15490, 15836, 15837, 15838, 20034, 21172, 21173	<code>\textndownmodels</code> .	19915, 21111
<code>\textLongmapsfrom</code> .	19633, 20994	<code>\textMundus</code>	19992, 21135	<code>\textndownvdash</code> . .	18748, 20709
<code>\textLongmapsto</code> . .	19635, 20995	<code>\textmusicalnote</code> .	19356, 19357, 19358, 21450	<code>\textne</code>	18571, 20631
<code>\textLongmapsto</code> . .	19631, 20993	<code>\textMVAt</code>	15697, 20299	<code>\textNearrow</code>	18311, 20519
<code>\textLongrightarrow</code> .	19627, 20991	<code>\textMVComma</code>	15665, 20285	<code>\textnearrow</code>	18185, 18186, 20469, 21312
<code>\textLongrightarrow</code> .	19621, 20988	<code>\textMVDivision</code> . .	15671, 20288	<code>\textneg</code>	15489, 20033, 21148
<code>\textlong</code>	16198, 17858	<code>\textMVEight</code>	15689, 20297	<code>\textneptune</code>	19292, 19293, 20859, 21431
<code>\textlooparrowleft</code> .	18220, 20485			<code>\textneq</code>	18570, 18572, 20630, 21340
<code>\textlooparrowright</code> .	18222, 20486			<code>\textneqcirc</code>	18556, 20624
<code>\textlozenge</code>	19190, 20825			<code>\textneqdot</code>	19807, 21062
<code>\textlptr</code>	16722, 16723			<code>\textneqsim</code>	18488, 20594
<code>\textlquill</code>	17953			<code>\textnequiv</code>	18577, 18578, 18579, 20633, 21342, 21343
<code>\textlrcorner</code>	18935, 20785			<code>\textneswarrow</code> . . .	19639, 20997

<code>\textNeutral</code>	19405, 20895	<code>\textnpreceqq</code>	19864, 21089	<code>\textnvDash</code> 18774, 18775, 18776,	
<code>\textnewtie</code> 15588, 15615, 16767		<code>\textnprecsim</code>	18649, 20666	20718, 21368, 21369	
<code>\textnexists</code>	18355, 20539	<code>\textnqsubseteq</code> . . .	18876, 20760	<code>\textnvdash</code> 18771, 18772, 20717,	
<code>\textnfallingdoteq</code> .	18543, 20618	<code>\textnqsupseteq</code> . . .	18878, 20761	21367	
<code>\textngeq</code>	18619, 20652	<code>\textnRightarrow</code> .	18290, 20511	<code>\textnVdash</code>	18765, 20715
<code>\textngeqq</code>	18596, 20641	<code>\textnrightarrow</code> .	18195, 20473	<code>\textnWarrow</code>	18309, 20518
<code>\textngeqslant</code>	19817, 21067	<code>\textnrisingdoteq</code> .	18548, 20620	<code>\textnwarrow</code>	18183, 20468
<code>\textngg</code>	18608, 20647	<code>\textnrleg</code> . 16237, 16239, 21193		<code>\textnwsearrow</code> . . .	19637, 20996
<code>\textngtr</code>	18614, 20650	<code>\textnsim</code>	18484, 20592	<code>\textobar</code> . . 19725, 19726, 21029,	
<code>\textngtrapprox</code> . . .	19825, 21071	<code>\textnsimeq</code>	18492, 20596	21470	
<code>\textngtrless</code>	18635, 20659	<code>\textnsqsubset</code>	18685, 20684	<code>\textobot</code> . . 19734, 19735, 21031,	
<code>\textngtrsim</code>	18629, 20656	<code>\textnsqsubseq</code> . . .	18693, 20688	21474	
<code>\textnhateq</code>	18566, 20628	<code>\textnsqsupset</code>	18689, 20686	<code>\textobslash</code> 19728, 19729, 19730,	
<code>\textni</code> 18370, 18371, 20546,		<code>\textnsqsupseteq</code> . .	18697, 20690	19731, 21030, 21471, 21472,	
21319		<code>\textnSubset</code>	18836, 20742	21473	
<code>\textNibRight</code>	19461, 20914	<code>\textnsubset</code>	18663, 20673	<code>\textObullseye</code>	16665, 21271
<code>\textNibSolidRight</code> 19463, 20915		<code>\textnsubseq</code>	18671, 20677	<code>\textodiv</code>	19782, 21052
<code>\textniepsilon</code>	16451, 16452,	<code>\textnsubseqeq</code> . . .	19888, 21101	<code>\textodot</code> . . . 18715, 18716, 20697,	
20318, 21214		<code>\textnsucc</code>	18657, 20670	21352	
<code>\textniiota</code> . 16500, 16501, 20326,		<code>\textnsuccapprox</code> . .	19880, 21097	<code>\textogonek</code> 15170, 15578, 15605,	
21227		<code>\textnsuccurlyeq</code> .	18874, 20759	16748	
<code>\textnineinferior</code> . .	18011, 20428	<code>\textnsucceq</code>	19856, 21085	<code>\textogreaterthan</code> 19742, 19743,	
<code>\textninesuperior</code> . .	17979, 20412	<code>\textnsucceqq</code>	19868, 21091	21034, 21476	
<code>\textninferior</code>	18041, 20443	<code>\textnsuccsim</code>	18653, 20668	<code>\textohm</code>	18102
<code>\textnippi</code>	16553, 20329	<code>\textnsuperior</code>	17991, 20418	<code>\textoiint</code>	18452, 20579
<code>\textniupsilon</code> . . .	16611, 16612,	<code>\textnSupset</code>	18840, 20744	<code>\textoinferior</code>	18027, 20436
20335, 21255		<code>\textnSupset</code>	18665, 20674	<code>\textoint</code> . . 18449, 18450, 20578,	
<code>\textnLeftarrow</code>	18285, 20509	<code>\textnSupseteq</code>	18673, 20678	21329	
<code>\textnleftarrow</code>	18193, 20472	<code>\textnSupseteqq</code> . . .	19892, 21103	<code>\textointclockwise</code> .	18455, 20580
<code>\textnLefttrightharrow</code>	18287,	<code>\textntriangleleft</code> .	18894, 18895,	<code>\textointctrclockwise</code>	18457,
20510		20768, 21385		20581	
<code>\textnleftrightharrow</code> 18224, 20487		<code>\textntriangleleftteq</code> 18901, 20770		<code>\textolessthan</code>	19739, 19740,
<code>\textnleq</code>	18617, 20651	<code>\textntriangleright</code> 18897, 18898,		21033, 21475	
<code>\textnleqq</code>	18592, 20639	20769, 21386		<code>\textOmega</code> . 1290, 16791, 16843,	
<code>\textnleqslant</code>	19813, 21065	<code>\textntrianglerighteq</code>	18904,	20355	
<code>\textnless</code>	18612, 20649	18905, 20771		<code>\textomega</code> . 1290, 16909, 16920,	
<code>\textnlessapprox</code> . .	19821, 21069	<code>\textntriplesim</code> . . .	18511, 20604	20379	
<code>\textnlessgtr</code>	18637, 20660	<code>\textntwoheadleftarrow</code> . .	18199,	<code>\textOmicron</code> 1266, 16787, 16824	
<code>\textnlesssim</code>	18627, 20655	20475		<code>\textomicron</code> 1266, 16889, 16915	
<code>\textnll</code>	18604, 20645	<code>\textntwoheadrightarrow</code> .	18206,	<code>\textominus</code> 18706, 18707, 20694,	
<code>\textnmid</code> . 18420, 18421, 20566,		20478		21349	
21325		<code>\textNu</code>	1264, 16820	<code>\textoneeighth</code>	18155
<code>\textNoChemicalCleaning</code> 19737,		<code>\textnu</code> 1264, 16885, 20368		<code>\textonefifth</code>	18143
21032		<code>\textnumbersign</code> . . .	562, 15178,	<code>\textonehalf</code>	15338, 15784
<code>\textnormal</code>	594	15643		<code>\textoneinferior</code> . . .	17995, 20420
<code>\textnotbackslash</code> .	18957, 20794	<code>\textnumeralsigngreek</code> . . .	1215,	<code>\textoneninth</code>	18135
<code>\textnotin</code>	18366, 20544	16775		<code>\textonequarter</code> . . .	15336, 15782
<code>\textnotowner</code> . . .	18373, 18374,	<code>\textnumeralsignlowergreek</code> 1232,		<code>\textoneseventh</code>	18133
20547, 21320		1254, 1277, 16777		<code>\textonesixth</code>	18151
<code>\textnotperp</code>	19600, 20979	<code>\textnumero</code>	18087	<code>\textonesuperior</code> .	15330, 15776,
<code>\textnotslash</code>	18954, 20793	<code>\textnupmodels</code> . . .	19919, 21113	20303	
<code>\textnoway</code>	19423, 20899	<code>\textnupvdash</code> . . .	18753, 18754,	<code>\textonetenth</code>	18137
<code>\textnparallel</code> 18425, 18426, 20568		20711, 21362		<code>\textonethird</code>	18139
<code>\textnprec</code>	18655, 20669	<code>\textnVDash</code> 18781, 18782, 20720,		<code>\textoo</code>	19958, 21122
<code>\textnprecapprox</code> . .	19876, 21095	21371		<code>\textopenbullet</code> . . .	19196, 20828
<code>\textnprecurllyeq</code> .	18872, 20758	<code>\textnVdash</code> 18778, 18779, 20719,		<code>\textopencorner</code> . . .	16760, 16761
<code>\textnpreceq</code>	19852, 21083	21370			

<code>\textopeno</code> 16426, 16427, 16428, 20314, 21208	<code>\textpisces</code> . 19331, 19332, 20872, 21444	<code>\textPUscm</code> 17534, 17535, 21280
<code>\textoplus</code> . 18703, 18704, 20693, 21348	<code>\textpitchfork</code> 18848, 20747	<code>\textPUscm</code> 17537, 17538, 21281
<code>\textordfeminine</code> .. 15301, 15743	<code>\textPlane</code> 19445, 20907	<code>\textPUscp</code> 17540, 17541, 21282
<code>\textordmasculine</code> . 15332, 15778	<code>\textPlus</code> 19478, 20922	<code>\textPUuncrfemale</code> 19411, 19412, 21454
<code>\textoslash</code> 18712, 18713, 20696, 21351	<code>\textPlusCenterOpen</code> ... 19482, 20924	<code>\textqplig</code> . 16401, 16403, 21199
<code>\textotimes</code> 18709, 18710, 20695, 21350	<code>\textplusinferior</code> .. 18013, 20429	<code>\textquaternote</code> .. 19355, 20873
<code>\textovee</code> .. 18435, 18436, 20572, 21327	<code>\textplusminus</code> .. 15314, 15492, 15756, 20036	<code>\textquestiondown</code> ... 780, 1150, 15342, 15788
<code>\textowedge</code> 18430, 18431, 20570, 21326	<code>\textPlusOutline</code> .. 19476, 20921	<code>\textquotedbl</code> 15176, 15641
<code>\textparagraph</code> 568, 15324, 15767, 15768, 21169	<code>\textplussuperior</code> .. 17981, 20413	<code>\textquotedblleft</code> . 15244, 15482, 17911, 20026
<code>\textparallel</code> 18423, 20567	<code>\textPlusThinCenterOpen</code> 19480, 20923	<code>\textquotedblright</code> . 15246, 17913
<code>\textparenleft</code> . 783, 784, 15186, 15657	<code>\textpluto</code> . 19295, 19296, 20860, 21432	<code>\textquoteleft</code> ... 15248, 15484, 17905, 20028
<code>\textparenleftinferior</code> 18019, 20432	<code>\texttpm</code> ... 15492, 20036, 21151	<code>\textquoteright</code> ... 15250, 17907
<code>\textparenleftsuperior</code> ... 17987, 20416	<code>\texttpointer</code> 18336, 20530	<code>\textquotesingle</code> 15655
<code>\textparenright</code> ... 15188, 15659	<code>\texttprec</code> 18639, 20661	<code>\textRadioactivity</code> 19238, 19239, 20843, 21411
<code>\textparenrightinferior</code> ... 18021, 20433	<code>\texttprecapprox</code> ... 19874, 21094	<code>\textRain</code> 19421, 20898
<code>\textparenrightsuperior</code> .. 17989, 20417	<code>\texttpreccurlyeq</code> .. 18643, 20663	<code>\textraiseglotstop</code> . 16719, 16720
<code>\textpartial</code> 18351, 20537	<code>\texttpreceq</code> 19850, 21082	<code>\texttriangle</code> 18945, 20790
<code>\textPeace</code> 19450, 20909	<code>\texttpreceqq</code> 19862, 21088	<code>\texttrbrackdbl</code> ... 19611, 19612, 20984, 21465
<code>\textPencilRight</code> .. 19457, 20912	<code>\texttprecnapprox</code> .. 19882, 21098	<code>\texttrcurvearrowdown</code> ... 19668, 19669, 19670, 21008, 21468, 21469
<code>\textPencilRightDown</code> ... 19455, 20911	<code>\texttprecneq</code> 19858, 21086	<code>\texttrcurvearrowleft</code> 19672, 21009
<code>\textPencilRightUp</code> 19459, 20913	<code>\texttprecneqq</code> 19870, 21092	<code>\texttrcurvearrowne</code> 19652, 21003
<code>\textpentagon</code> 19929, 21117	<code>\texttprecnsim</code> 18890, 20766	<code>\texttrcurvearrowright</code> ... 19675, 21010
<code>\textpercent</code> . 564, 15182, 15649	<code>\texttprecsim</code> 18647, 20665	<code>\texttrcurvearrowse</code> 19661, 21006
<code>\textperiodcentered</code> 15326, 15493, 15770, 15771, 15772, 20037, 21170, 21171	<code>\texttpriem</code> 17935, 20398	<code>\textRe</code> 18094, 20452
<code>\textperp</code> 19598, 20978	<code>\texttpriestress</code> ... 16730, 16731	<code>\textrecipe</code> 18096
<code>\textpertenthousand</code> 17933	<code>\texttprod</code> 18378, 20549	<code>\textRectangle</code> 19594, 20976
<code>\textperthousand</code> .. 15240, 17931	<code>\texttpropto</code> 18404, 18405, 20560, 21321	<code>\textRectangleBold</code> 19596, 20977
<code>\textpeseta</code> 18055	<code>\textPsi</code> 1289, 16840, 20354	<code>\textRectangleThin</code> 19592, 20975
<code>\textpeso</code> 18075	<code>\texttpsi</code> 1289, 16907, 20378	<code>\textrecycle</code> 19370, 19371, 20879, 21451
<code>\textPhi</code> ... 1287, 16836, 20353	<code>\textPUaolig</code> 19955, 19956, 21491	<code>\textreferencemark</code> 17947
<code>\textphi</code> 1287, 16903, 20376	<code>\textPUdblig</code> 16399, 16400, 21198	<code>\textregistered</code> 15308, 15750
<code>\textphiinferior</code> ... 17562, 20389	<code>\textPUfemale</code> ... 19268, 19269, 19270, 19271, 19272, 19273, 21419, 21420, 21421, 21422, 21423	<code>\textRequest</code> 18975, 20801
<code>\textPhone</code> 19211, 19212, 20834, 21402	<code>\textPUheng</code> 19946, 19947, 21488	<code>\textrevapostrophe</code> 16716, 16717
<code>\textPhoneHandset</code> 19441, 20905	<code>\textPUhookfour</code> 19949, 19950, 21489	<code>\textrevc</code> 18163
<code>\textPi</code> 1267, 16826, 20350	<code>\textPUnrleg</code> 16238, 16239, 21193	<code>\textrevE</code> 16213
<code>\textpi</code> 1267, 16891, 20370	<code>\textPUqplig</code> 16402, 16403, 21199	<code>\textreve</code> .. 16440, 16441, 20316
<code>\textpinferior</code> 18043, 20444	<code>\textPUrevscr</code> ... 17543, 17544, 21283	<code>\textreveysilon</code> .. 16454, 16455, 20319
<code>\textpipe</code> .. 16258, 16259, 16260, 21194	<code>\textPUrhooka</code> .. 17574, 17575, 21284	<code>\textrevglotstop</code> . 16651, 16652, 16653, 20343, 21267
<code>\textpipevar</code> 16260, 21194	<code>\textPUrhooko</code> .. 17579, 17580, 21285	<code>\textrevscr</code> 17542, 17544, 21283
	<code>\textPUrhookepsilon</code> 17583, 17584, 21286	<code>\textrevyogh</code> 16248, 16249
	<code>\textPUrhookopeno</code> 17587, 17588, 21287	<code>\textRewind</code> 19180, 20821
	<code>\textPUScf</code> . 19952, 19953, 21490	<code>\textRewindToIndex</code> 18987, 20806
		<code>\textRHD</code> 19171, 20818

<code>\textrhd</code> . . . 18787, 18788, 20722, 21373	<code>\textrtaild</code> . 16432, 16433, 16434, 20315, 21210	<code>\textscy</code> . . . 16628, 16629, 20340
<code>\textRho</code> 1283, 16828	<code>\textrtaill</code> . 16512, 16513, 16514, 21230	<code>\textSearrow</code> 18313, 20520
<code>\textrho</code> 1283, 16893, 20371	<code>\textrtailn</code> . 16535, 16536, 16537, 21239	<code>\textsearrow</code> 18188, 18189, 20470, 21313
<code>\textrhoinferior</code> . . . 17560, 20388	<code>\textrtailr</code> . 16569, 16570, 16571, 21247	<code>\textSech</code> 19988, 21133
<code>\textrhooka</code> 17573, 17575, 21284	<code>\textrtails</code> . 16585, 16586, 16587, 21250	<code>\textsecond</code> 17937, 20399
<code>\textrhooke</code> 17578, 17580, 21285	<code>\textrtailt</code> . 16603, 16604, 16605, 21253	<code>\textsecstress</code> 16733, 16734
<code>\textrhookepsilon</code> 17582, 17584, 21286	<code>\textrtailz</code> . 16631, 16632, 16633, 21262	<code>\textsection</code> 15295, 15735, 15736, 15737, 21167, 21168
<code>\textrhooknearrow</code> . 19643, 20999	<code>\textrtimes</code> 18818, 20734	<code>\textSePa</code> 19974, 21127
<code>\textrhookopeno</code> . 17586, 17588, 21287	<code>\textssagittarius</code> . . 19322, 19323, 20869, 21441	<code>\textservicemark</code> 18098
<code>\textrhookrepsilon</code> 16457, 16458, 16459, 20320, 21215	<code>\textSampigreek</code> . . . 1291, 16935	<code>\textsetminus</code> . . . 15198, 18394, 20556
<code>\textrhookschwa</code> . 16446, 16447, 16448, 21213	<code>\textsampigreek</code> 1291, 16937	<code>\textseveneighths</code> 18161
<code>\textrhookswarrow</code> 19647, 21001	<code>\textsaturn</code> 19286, 19287, 20857, 21429	<code>\textseveninferior</code> . 18007, 20426
<code>\textRightarrow</code> . 18298, 18299, 20514, 21315	<code>\textsc</code> 601	<code>\textsevensuperior</code> . 17975, 20410
<code>\textrightarrow</code> . . . 2583, 18171, 18172, 18173, 20464, 21308, 21309	<code>\textscsca</code> 17525, 17526	<code>\textsf</code> 596, 13521, 13524
<code>\textrightarrowtail</code> . 18212, 20481	<code>\textscsb</code> 16666, 16667	<code>\textsharp</code> 19368, 20878
<code>\textrightarrowtriangle</code> . . 18343, 20533	<code>\textscsd</code> 17528, 20380	<code>\textshuffle</code> 19759, 21042
<code>\textrightbarharpoon</code> 19706, 21021	<code>\textscse</code> 17529, 17530	<code>\textSigma</code> . 1284, 16830, 20351
<code>\textRIGHTCIRCLE</code> 19194, 20827	<code>\textscf</code> . . . 19951, 19953, 21490	<code>\textsigma</code> . . 1284, 16897, 20373
<code>\textrightbarpoondown</code> . . 18253, 20497	<code>\textscg</code> . . . 16475, 16476, 20322	<code>\textsim</code> . . 18474, 18475, 20588, 21332
<code>\textrightbarpoonup</code> 18250, 20496	<code>\textsch</code> 16674, 16675	<code>\textsimeq</code> 18490, 20595
<code>\textrightleftarrows</code> 18262, 20500	<code>\textschwa</code> . 16443, 16444, 20317	<code>\textsinferior</code> 18045, 20445
<code>\textrightleftharpoon</code> 19679, 21012	<code>\textschwainferior</code> . 18031, 20438	<code>\textSixFlowerAlternate</code> . 19546, 20955
<code>\textrightleftharpoons</code> . . . 18282, 20508	<code>\textsci</code> . . . 16502, 16503, 20327	<code>\textSixFlowerAltPetal</code> . . 19556, 20960
<code>\textrightmoon</code> . . . 19263, 20852	<code>\textScissorHollowRight</code> . 19439, 20904	<code>\textSixFlowerOpenCenter</code> 19542, 20953
<code>\textrighttrigharrows</code> 18274, 20505	<code>\textScissorRight</code> . 19433, 19434, 19435, 20902, 21458, 21459	<code>\textSixFlowerPetalRemoved</code> 19539, 20952
<code>\textrighttrigharpoons</code> . . 19694, 21017	<code>\textScissorRightBrokenBottom</code> 19429, 19430, 19431, 21456, 21457	<code>\textsixinferior</code> . . . 18005, 20425
<code>\textrightlslice</code> 19848, 21081	<code>\textScissorRightBrokenTop</code> 19437, 20903	<code>\textSixStar</code> 19529, 20947
<code>\textrightlsquigarrow</code> 18323, 20525	<code>\textscj</code> 17531, 17532	<code>\textsixsuperior</code> . . . 17973, 20409
<code>\textrightthreetimes</code> 18822, 20736	<code>\textscck</code> 17533, 17535, 21280	<code>\textSixteenStarLight</code> . . . 19537, 20951
<code>\textrinferior</code> 17550, 20383	<code>\textsccl</code> 16682, 16683	<code>\textsixteenthnote</code> . 19362, 20875
<code>\textring</code> . . 15117, 15129, 15141, 15172, 15570, 15597, 16746	<code>\textscm</code> . . 17536, 17538, 21281	<code>\textsl</code> 602
<code>\textringlow</code> 15581, 15608, 16755	<code>\textscn</code> . . . 16538, 16539, 20328	<code>\textslashc</code> . 16405, 16406, 16408, 20312, 21200, 21201
<code>\textriota</code> 18107, 20454	<code>\textscscn</code> . . . 16538, 16539, 20328	<code>\textslashdiv</code> 19935, 21120
<code>\textringdoteq</code> . . . 18546, 20619	<code>\textscscoelig</code> 16545, 16546	<code>\textsmallin</code> 18368, 20545
<code>\textrm</code> 595	<code>\textscscorpio</code> 19319, 19320, 20868, 21440	<code>\textsmallowns</code> . . . 18376, 20548
<code>\textrprtr</code> 16725, 16726	<code>\textscsp</code> . . . 17539, 17541, 21282	<code>\textsmile</code> 18939, 20787
<code>\textrquill</code> 17955	<code>\textscr</code> . . . 16580, 16581, 20331	<code>\textsmiley</code> 19253, 19254, 20848, 21416
<code>\textRrightarrow</code> . . 18319, 20523	<code>\textscripta</code> 16413, 16414, 16415, 20313, 21203	<code>\textSnowflake</code> . . . 19560, 20962
<code>\textrrparenthesis</code> . 19721, 21027	<code>\textscriptg</code> 16472, 16473, 16474, 20321, 21219	<code>\textSnowflakeChevron</code> . . 19558, 20961
	<code>\textscriptv</code> 16614, 16615, 20336	<code>\textSnowflakeChevronBold</code> 19562, 20963
	<code>\textscu</code> . . . 17545, 17546, 20381	<code>\textSoccerBall</code> . . 19416, 19417, 21455
		<code>\textspadesuitblack</code> 2582, 19334, 19335, 21445

<code>\textspadesuitwhite</code>	19347	<code>\textsubtilde</code>	15555, 15556, 15584, 15611, 17642, 17644, 17674, 17676, 17790, 17792	<code>\texttilde</code>	4430, 15115, 15127, 15139, 15174, 15568, 15595, 16750
<code>\textSparkle</code>	19564, 20964	<code>\textsubumlaut</code>	15542, 15543, 15580, 15607, 17786, 17788	<code>\texttildebelow</code>	15584, 15611, 16759
<code>\textSparkleBold</code>	19566, 20965	<code>\textsucc</code>	18641, 20662	<code>\textttimes</code>	15490, 20034, 21149
<code>\textssphericalangle</code>	18413, 18414, 18415, 18416, 20564, 21322, 21323, 21324	<code>\textsuccapprox</code>	19878, 21096	<code>\textttinferior</code>	18047, 20446
<code>\textsqcap</code>	18699, 20691	<code>\textsucccurlyeq</code>	18645, 20664	<code>\textttop</code>	18745, 18746, 20708, 21360
<code>\textsqcup</code>	18701, 20692	<code>\textsucceq</code>	19854, 21084	<code>\texttrademark</code>	15254, 18100
<code>\textsqdoublecap</code>	19786, 19787, 21054, 21478	<code>\textsucceqq</code>	19866, 21090	<code>\texttriangle</code>	18360, 20541
<code>\textsqdoublecup</code>	19791, 19792, 21056, 21479	<code>\textsuccnapprox</code>	19884, 21099	<code>\texttriangleleeq</code>	18568, 20629
<code>\textsqsubset</code>	18683, 20683	<code>\textsuccneq</code>	19860, 21087	<code>\texttriangleleft</code>	19183, 20822
<code>\textsqsubseteq</code>	18691, 20687	<code>\textsuccneqq</code>	19872, 21093	<code>\texttriangleright</code>	19169, 20817
<code>\textsqsubsetneq</code>	18880, 18881, 20762, 21383	<code>\textsuccnsim</code>	18892, 20767	<code>\texttriplesim</code>	18508, 18509, 20603, 21335
<code>\textsqsupset</code>	18687, 20685	<code>\textsuccsim</code>	18651, 20667	<code>\textTslash</code>	16148
<code>\textsqsupseteq</code>	18695, 20689	<code>\textsum</code>	18382, 20551	<code>\textttslash</code>	16150
<code>\textsqsupsetneq</code>	18883, 18884, 20763, 21384	<code>\textsun</code>	19258, 19259, 20850, 21417	<code>\textttslig</code>	16701, 16702
<code>\textSquareCastShadowBottom- Right</code>	19585, 20972	<code>\textSunCloud</code>	19419, 20897	<code>\textttt</code>	597
<code>\textSquareCastShadowTopRight</code>	19588, 20973	<code>\textSunshineOpenCircled</code>	19554, 20959	<code>\textTumbler</code>	18949, 20792
<code>\textssquaredots</code>	18467, 20585	<code>\textSupset</code>	18838, 20743	<code>\textturna</code>	16409, 16410, 16411, 21202
<code>\textSquareShadowBottomRight</code>	19579, 20970	<code>\textsupset</code>	18661, 20672	<code>\textturnh</code>	16484, 16485, 16486, 16487, 21221, 21222
<code>\textSquareTopRight</code>	19582, 20971	<code>\textsupseteq</code>	18669, 20676	<code>\textturnk</code>	16679, 16680, 16681, 21273
<code>\textsslash</code>	19926, 19927, 21116, 21487	<code>\textsupseteqq</code>	19890, 21102	<code>\textturnlonglegr</code>	16559, 16560, 16561, 21244
<code>\textstar</code>	18808, 20730	<code>\textsupsetneq</code>	18677, 20680	<code>\textturnm</code>	16518, 16519, 16520, 16521, 21232, 21233
<code>\textsterling</code>	15287, 15724, 15725, 15726, 21164, 21165	<code>\textsurd</code>	18402, 20559	<code>\textturnmrleg</code>	16523, 16524, 16525, 21234
<code>\textStigmagreek</code>	1243, 16922	<code>\textswarrow</code>	18315, 20521	<code>\textturnr</code>	16554, 16555, 16556, 16557, 21242, 21243
<code>\textstigmagreek</code>	1243, 16924	<code>\textswarrow</code>	18191, 20471	<code>\textturnrrtail</code>	16563, 16564, 16565, 21245
<code>\textstmaryrdbaro</code>	18951, 18952, 21389	<code>\textSymbolUnavailable</code>	15148, 15149, 15151	<code>\textturnsck</code>	16681, 21273
<code>\textstretchc</code>	16657, 16658, 16659, 16660, 21268, 21269	<code>\textTape</code>	19443, 20906	<code>\textturnscripta</code>	16417, 16418, 16419, 16420, 21204, 21205
<code>\textstretchcvar</code>	16660, 21269	<code>\textTau</code>	1285, 16832	<code>\textturnt</code>	16599, 16600, 16601, 21252
<code>\textsubbreve</code>	15554, 15583, 15610, 17670, 17672	<code>\textttau</code>	1285, 16899, 20374	<code>\textturnv</code>	16616, 16617, 16618, 16619, 20337, 21256, 21257
<code>\textsubcircum</code>	15551, 15552, 15582, 15609, 17622, 17624, 17638, 17640, 17698, 17700, 17726, 17728, 17782, 17784, 17794, 17796	<code>\texttaurus</code>	19301, 19302, 20862, 21434	<code>\textturnw</code>	16620, 16621, 16622, 16623, 20338, 21258, 21259
<code>\textsubring</code>	15544, 15545, 15581, 15608, 17590, 17592	<code>\texttctclig</code>	16707, 16708	<code>\textturny</code>	16624, 16625, 16626, 16627, 20339, 21260, 21261
<code>\textSubset</code>	18834, 20741	<code>\textTent</code>	19427, 20901	<code>\textTwelveStar</code>	19535, 20950
<code>\textsubset</code>	18659, 20671	<code>\texttshlig</code>	16703, 16704, 16705, 21275	<code>\texttwofifths</code>	18145
<code>\textsubseteq</code>	18667, 20675	<code>\texttherefore</code>	18459, 18460, 20582	<code>\texttwoheaddownarrow</code>	18208, 20479
<code>\textsubseteqq</code>	19886, 21100	<code>\textTheta</code>	1246, 16810, 20347	<code>\texttwoheadleftarrow</code>	18197, 20474
<code>\textsubsetneq</code>	18675, 20679	<code>\texttheta</code>	1246, 16875, 20363	<code>\texttwoheadrightarrow</code>	18204, 20477
		<code>\textthird</code>	17939, 20400	<code>\texttwoheaduparrow</code>	18201, 20476
		<code>\textThorn</code>	15406, 15853, 20304		
		<code>\textthorn</code>	15475, 15922, 15924, 20305		
		<code>\textthreethirds</code>	18157		
		<code>\textthreefifths</code>	18147		
		<code>\textthreeinferior</code>	17999, 20422		
		<code>\textthreequarters</code>	15340, 15786		
		<code>\textthreesuperior</code>	15318, 15760, 20302		
		<code>\texttie</code>	15587, 15614, 16773		

<code>\texttwoinferior</code> . . .	17997, 20421	<code>\textvDash</code> 18756, 18757, 18758,	20712, 21363, 21364	<code>\theequation</code> . 7027, 7384, 7415,	7443, 7479
<code>\texttwoones</code>	19360, 20874	<code>\textvdash</code> . 18736, 18737, 20705,	21357	<code>\thefootnote</code>	7626, 7829
<code>\texttwosuperior</code> . 15316, 15758,	20301	<code>\textvdotdot</code>	18465, 20584	<code>\theHchapter</code> . 6966, 6967, 6968,	6969, 7108
<code>\texttwothirds</code>	18141	<code>\textvdots</code>	18907, 20772	<code>\theHenumi</code>	6985
<code>\textudots</code>	18911, 20774	<code>\textvee</code>	18433, 20571	<code>\theHenumii</code>	6986
<code>\textuinferior</code>	17552, 20384	<code>\textveebar</code>	18804, 20728	<code>\theHenumiii</code>	6987
<code>\textulcorner</code>	18929, 20782	<code>\textveedot</code>	19602, 20980	<code>\theHenumiv</code>	6988
<code>\textuncrfemale</code> . . 19410, 19412,	21454	<code>\textveedoublebar</code> . 19803, 21060		<code>\theHequation</code> 6956, 7028, 7385,	7416, 7444, 7452, 7479, 7483
<code>\textunderscore</code> 567, 4884, 4885,	4887, 15202, 15703, 15704,	<code>\textvline</code>	15714, 21163	<code>\theHfigure</code>	6963, 6967
	21162	<code>\textvibyi</code>	16594, 16595	<code>\theHHfootnote</code>	6989, 6992
<code>\textunlhd</code> . 18790, 18791, 18792,	20723, 21374, 21375	<code>\textvibyy</code>	16713, 16714	<code>\theHHmpfootnote</code>	6992
<code>\textunrhd</code> 18794, 18795, 18796,	20724, 21376, 21377	<code>\textVier</code>	19984, 21131	<code>\theHItem</code> . . . 6979, 6985, 6986,	6987, 6988
<code>\textup</code>	603	<code>\textViPa</code>	19970, 21125	<code>\theHlisting</code>	3655
<code>\textUParrow</code> . . . 19158, 19159,	20814, 21395	<code>\textvirgo</code> . 19313, 19314, 20866,	21438	<code>\theHlstlisting</code>	3651
<code>\textUparrow</code> 18295, 20513		<code>\textvisiblespace</code>	18991	<code>\theHmpfootnote</code>	6990
<code>\textuparrow</code>	18169, 20463	<code>\textVvdash</code>	18763, 20714	<code>\theHpage</code>	8244
<code>\textUpdownarrow</code> 18307, 20517		<code>\textwasylounge</code> . . 18921, 20779		<code>\theHparagraph</code>	6973, 6974
<code>\textupdownarrow</code> . 2585, 18181,	20467	<code>\textwedge</code>	18428, 20569	<code>\theHparentequation</code> 7478, 7483	
<code>\textupdownarrows</code> 18265, 20501		<code>\textwedgedot</code> . . . 19604, 20981		<code>\theHpart</code>	6959
<code>\textupdownharpoonleftright</code> 19685, 21014	<code>\textWheelchair</code> . . 19373, 20880		<code>\theHsection</code> . 6956, 6962, 6969,	6971, 6975, 6976, 7106
<code>\textupdownharpoonrightleft</code> 19682, 21013	<code>\textWomanFace</code> . 19998, 19999,	21138, 21494	<code>\theHslide</code>	8676
<code>\textupdownharpoons</code> . . . 19712,	21023	<code>\textwon</code>	18057	<code>\theHslidesection</code> . . . 8681, 8683,	8719, 8723
<code>\textupharpoonleft</code> 18247, 20495		<code>\textwtr</code> . . . 18481, 18482, 20591,	21333	<code>\theHslidesubsection</code> 8682, 8770,	8774
<code>\textupharpoonright</code> 18244,	20494	<code>\textWritingHand</code> 19452, 19453,	20910, 21461	<code>\theHsubequation</code>	7452
<code>\textupplus</code>	19761, 21043	<code>\textwynn</code>	16255, 16256	<code>\theHsubparagraph</code>	6974
<code>\textupmodels</code>	19917, 21112	<code>\textXi</code>	1265, 16822, 20349	<code>\theHsubsection</code> . . . 6971, 6972	
<code>\textUpsilon</code> 1286, 16789, 16834,	16848, 20352	<code>\textxi</code>	1265, 16887, 20369	<code>\theHsubsubsection</code> . 6972, 6973	
<code>\textupsilon</code> . 1286, 16901, 16913,	16918, 20375	<code>\textxinferior</code> 18029, 20437		<code>\theHtable</code>	6964, 6968
<code>\textupsilonacute</code> . 16859, 16917		<code>\textXSolid</code>	19470, 20918	<code>\theHtheorem</code>	6975
<code>\textupspoon</code>	19921, 21114	<code>\textXSolidBold</code> . . 19472, 20919		<code>\theHthm</code>	6976
<code>\textupstep</code>	19940, 19941	<code>\textXSolidBrush</code> . 19474, 20920		<code>\theHy@tempcnt</code> 5000, 5008, 5015	
<code>\textupuparrows</code> . . 18272, 20504		<code>\textxswup</code>	19381, 21453	<code>\thelisting</code>	3655
<code>\textupupharpoons</code> 19691, 21016		<code>\texttyen</code>	15291, 15730	<code>\thelstlisting</code>	3651
<code>\texturanus</code> 19289, 19290, 20858,	21430	<code>\textYinYang</code> . . . 19245, 19246,	19247, 19248, 20846, 21412,	<code>\thempfn</code> 7615, 7718, 7810, 7822	
			21413, 21414	<code>\theoremautorefname</code> 3330, 3348,	3366, 3384, 3402, 3420,
<code>\texturcorner</code>	18931, 20783	<code>\textyogh</code> . 16638, 16639, 20341			3438, 3476, 3496, 3514, 9116
<code>\textValve</code>	19755, 21040	<code>\textzeroinferior</code> . . 17993, 20419		<code>\thepage</code> 2605, 5118, 6618, 6644,	6659, 7226, 7234, 7261,
<code>\textvarhexagon</code> . . 19931, 21118		<code>\textzerosuperior</code> . . 17965, 20405			8087, 8110, 8139, 8240,
<code>\textvarobar</code>	19726, 21470	<code>\textzerothirds</code>	18165		8287, 8366, 8414, 8575,
<code>\textvarsigma</code> 16895, 20372		<code>\textZeta</code>	1244, 16806		8592, 8598, 8602, 8609,
<code>\textVDash</code> 18768, 18769, 20716,	21366	<code>\textzeta</code> . . . 1244, 16871, 20361			8873, 8893, 8910, 9028
<code>\textVdash</code> 18760, 18761, 20713,	21365	<code>\textZwdr</code>	19990, 21134	<code>\therefore</code>	18458, 20582
		<code>\textZwPa</code>	19976, 21128	<code>\theslideheading</code>	8702
		<code>\TH</code> . 15404, 15405, 15851, 15852		<code>\theslidesection</code> 8690, 8697, 8705,	8711, 8713, 8715, 8721, 8731
		<code>\th</code> . 15473, 15474, 15922, 15923		<code>\theslidesubheading</code> . 8703, 8754	
		<code>\thaa</code>	20195		
		<code>\thebookmark@seq@number</code> 14660		

<code>\theslidesubsection</code>	<code>\tocsubsection</code> 1701	<code>\TX@endtabularx</code> . . 7689, 7696, 7702
.. 8742, 8749, 8756, 8762, 8764, 8766, 8772, 8782	<code>\tocsubsubsection</code> 1702	<code>\typeout</code> 5, 6, 7, 19, 26, 27, 36, 131, 155, 158, 159, 160, 5359, 15074, 21500
<code>\Theta</code> 16809, 20347	<code>\toks</code> . . 8881, 8882, 8884, 14977, 14982, 15048, 15053	
<code>\theta</code> 16874, 20363	<code>\toks@</code> 171, 208, 500, 503, 506, 524, 525, 859, 866, 898, 899, 1335, 1358, 1361, 1363, 1871, 1872, 3526, 3527, 3529, 4126, 4130, 4131, 4139, 4438, 4439, 4617, 4619, 5213, 5218, 5225, 5226, 5229, 5329, 5334, 5338, 5342, 6739, 6741, 6827, 6829, 6879, 6891, 7243, 7247, 7283, 7288, 7696, 7699, 8445, 8446, 8652, 8657, 8659, 8662, 14976, 14982, 15047, 15053	
<code>\third</code> 17938, 20400	<code>\top</code> 18744, 20708	
<code>\This@name</code> . 7005, 7006, 7024, 7025	<code>\topmargin</code> 8300	
<code>\thispdfpagelabel</code> 6623	<code>\triangle</code> 18359, 20541	
<code>\ThisShouldNotHappen</code> . . 14237	<code>\triangleeq</code> 18567, 20629	
<code>\thm@headfont</code> 7495, 7523	<code>\triangleleft</code> 19182, 20822	
<code>\thm@headpunct</code> . . . 7497, 7525, 7556	<code>\trianglelefteq</code> 18792, 21375	
<code>\thm@headsep</code> . 7498, 7526, 7557	<code>\triangleright</code> 19168, 20817	
<code>\thm@indent</code> 7494, 7522	<code>\trianglerighteq</code> 18796, 21377	
<code>\thm@notefont</code> 7496, 7524, 7555	<code>\triplesim</code> 18507, 20603	
<code>\thm@notskip</code> 7502, 7530, 7561	<code>\trivlist</code> 7491, 7519, 7552	
<code>\thm@preskip</code> . 7501, 7529, 7560	<code>\tryhyper@link</code> 5093, 5095	
<code>\thm@space@setup</code> . 7499, 7527, 7558	<code>\ttfamily</code> 607	
<code>\thm@swap</code> . . . 7493, 7521, 7554	<code>\ttl@b</code> 7294, 7299	
<code>\thmheadnl</code> . . . 7492, 7520, 7553	<code>\ttl@gobblecontents</code> 7303	
<code>\Thorn</code> . . . 15404, 15851, 20304	<code>\ttl@Hy@PatchSaveWrite</code> . 7277, 7281	
<code>\thorn</code> . . . 15473, 15922, 20305	<code>\ttl@Hy@refstepcounter</code> . . . 7293	
<code>\threeinferior</code> 20422	<code>\ttl@Hy@saveanchor</code> 7272, 7296	
<code>\threesuperior</code> 20302	<code>\ttl@Hy@SavedCurrentHref</code> 7276, 7287	
<code>\tildel</code> 16507, 21228	<code>\ttl@Hy@steplink</code> 7270	
<code>\times</code> 21149	<code>\ttl@savewrite</code> 7283, 7285	
<code>\tinferior</code> 20446	<code>\Tumbler</code> 18948, 20792	
<code>\tiny</code> 625	<code>\turnv</code> 20337	
<code>\title</code> 6522, 6524	<code>\turnw</code> 20338	
<code>\TMP@EnsureCode</code>	<code>\turny</code> 20339	
.. 4721, 4728, 4729, 4730, 4731, 4732, 4733, 4734, 4735, 4736, 4737, 4738, 4739, 4740, 4741, 4742, 4743, 4744, 4745, 4746, 4747, 4748, 4749, 4750, 4751, 4752, 4753, 4754	<code>\tw@</code> 5165, 5171, 5172, 5173, 5178, 5184, 5185, 5186, 14977, 14982, 15048, 15053	
<code>\tocappendix</code> 1699	<code>\TwelveStar</code> 19534, 20950	
<code>\tocchapter</code> 1698	<code>\twoheaddownarrow</code> 18207, 20479	
<code>\toclevel@chapter</code> 3642	<code>\twoheadleftarrow</code> . 18196, 20474	
<code>\toclevel@figure</code> 3648	<code>\twoheadrightarrow</code> 18203, 20477	
<code>\toclevel@listing</code> 3656	<code>\twoheaduparrow</code> . . 18200, 20476	
<code>\toclevel@lstlisting</code> 3652	<code>\twoinferior</code> 20421	
<code>\toclevel@paragraph</code> 3646	<code>\twonotes</code> 19359, 20874	
<code>\toclevel@part</code> 3638, 3640	<code>\twosuperior</code> 20301	
<code>\toclevel@section</code> 3643		
<code>\toclevel@subfigure</code> 2619		
<code>\toclevel@subparagraph</code> . . . 3647		
<code>\toclevel@subsection</code> 3644		
<code>\toclevel@subsubsection</code> . . . 3645		
<code>\toclevel@subtable</code> 2620		
<code>\toclevel@table</code> 3649		
<code>\tocparagraph</code> 1703		
<code>\tocpart</code> 1697		
<code>\tocsection</code> 1700		

U	
<code>\U</code> . . 15524, 16974, 16997, 17064, 17144, 17345, 17347, 17369, 17371, 17381, 17383	
<code>\u</code> . . 15523, 15574, 15601, 15629, 15932, 15934, 15974, 15976, 15994, 15996, 16027, 16029, 16030, 16100, 16102, 16160, 16162	
<code>\ubar</code> 16609, 21254	
<code>\udesc</code> 16487, 21222	
<code>\udots</code> 18910, 20774	
<code>\UHORN</code> . . 20051, 20162, 20163, 20164, 20165, 20166	
<code>\uhorn</code> 3500, 3507, 20045, 20102, 20103, 20104, 20105, 20106	
<code>\uinferior</code> 20384	
<code>\ulcorner</code> 18928, 20782	
<code>\UnDef</code> 12817	
<code>\unhbox</code> . . . 7599, 11843, 13927, 14051, 14083, 14107, 14135, 14164	
<code>\unhcopy</code> 14029	
<code>\unichar</code> 2326	
<code>\Unicode</code> 1411	
<code>\unlhd</code> 18789, 20723	
<code>\unrestored@protected@xdef</code> 7615, 7626, 7772, 7779, 7822, 7829	
<code>\unrhd</code> 18793, 20724	
<code>\unskip</code> . 7489, 7516, 7549, 8072, 8959, 8963, 8967, 8972	
<code>\UParrow</code> 19157, 20814	
<code>\Uparrow</code> 18294, 20513	
<code>\uparrow</code> 20463	
<code>\Updownarrow</code> . . . 18306, 20517	
<code>\updownarrow</code> . . . 18180, 20467	
<code>\updownarrows</code> . . . 18264, 20501	
<code>\updownharpoonleftright</code> . 19684, 21014	
<code>\updownharpoonrightleft</code> . 19681, 21013	
<code>\updownharpoons</code> . 19711, 21023	
<code>\upharpoonleft</code> . . . 18246, 20495	
<code>\upharpoonright</code> . . 18243, 20494	
<code>\uplus</code> 19760, 21043	
<code>\upmodels</code> 19916, 21112	
<code>\upshape</code> . 613, 7496, 7524, 7555	
<code>\Upsilon</code> 16833, 20352	
<code>\upsilon</code> 16900, 20375	
<code>\upspoon</code> 19920, 21114	
<code>\upuparrows</code> 18271, 20504	

`\upupharpoons` . . . 19690, 21016
`\upvdash` 18751, 21361
`\Uranus` 19290, 21430
`\uranus` 19288, 20858
`\urcorner` 18930, 20783
`\Url` 5064
`\url` 5063, 5067
`\url@` 5067, 5068
`\use@file` 5290, 5292, 5299
`\usefont` 592
`\utf@viii@undeferr` 554
`\UTFviii@four@octets` 2322, 2331
`\UTFviii@three@octets` . . . 2321
`\UTFviii@two@octets` 2320

V

`\v` . . 15118, 15130, 15142, 15264,
15269, 15277, 15279, 15534,
15571, 15598, 15628, 15952,
15954, 15956, 15958, 15986,
15988, 16064, 16066, 16084,
16086, 16120, 16122, 16136,
16138, 16144, 16146, 16194,
16196, 16270, 16272, 16274,
16276, 16277, 16279, 16281,
16283, 16285, 16294, 16296,
16298, 16300, 16306, 16307,
16369, 16371
`\V@@@footnotetext` 7759
`\V@@footnotetext` 7745
`\value` . . 6642, 7094, 7095, 7097,
7098, 8026, 8052, 8304,
8470, 10498, 10503
`\Valve` 19754, 21040
`\vara` 16415, 21203
`\varangle` 18414, 21322
`\varbigcirc` 19202, 21401
`\varcurlyvee` 18829, 21379
`\varcurlywedge` . . . 18832, 21380
`\VarFlag` 19376, 21452
`\varg` 16474, 21219
`\varhexagon` 19930, 21118
`\vari` 16501, 21227
`\varint` 18443, 21328
`\varnothing` 18356, 18358, 21318
`\varoast` 18723, 21355
`\varobslash` 19731, 21473
`\varocircle` 18720, 21354
`\varodot` 18716, 21352
`\varogreaterthan` . . 19743, 21476
`\varoint` 18450, 21329
`\varolessthan` 19740, 21475
`\varomega` 16551, 21241
`\varominus` 18707, 21349
`\varopeno` 16428, 21208
`\varoplus` 18704, 21348
`\varoslash` 18713, 21351

`\varotimes` 18710, 21350
`\varovee` 18436, 21327
`\varowedge` 18431, 21326
`\varparallel` 19927, 21487
`\varparallelinv` 18994, 21390
`\varprop` 18405, 21321
`\varsigma` 20372
`\varsqsubsetneq` . . . 18881, 21383
`\varsqsupsetneq` . . . 18884, 21384
`\vartimes` 15837, 21172
`\vavyod` 17520
`\vbox` . . 6276, 6277, 6278, 6279,
6591, 8298

`\VDash` 18767, 20716
`\Vdash` 18759, 20713
`\vDash` 18755, 20712
`\vdash` 18735, 20705
`\vdots` 18464, 20584
`\vdots` 18906, 20772
`\vee` 18432, 20571
`\veebar` 18803, 20728
`\veedot` 19601, 20980
`\veedoublebar` 19802, 21060
`\Venus` 19272, 21422
`\venus` 19271, 21421
`\vfill` . . . 6276, 6277, 6278, 6279
`\VHF` 18509, 21335
`\Vier` 19983, 21131
`\vinferior` 20385
`\ViPa` 19969, 21125
`\Virgo` 19314, 21438
`\virgo` 19312, 20866
`\vod` 16478, 16480, 21220
`\voffset` 8299
`\voicedh` 16491, 21224
`\vpageref` 8972
`\vphantom` 628
`\Vr@f` 8958
`\vr@f` 8966
`\vref@pagenum` 7307
`\vref@space` . . . 8959, 8962, 8967
`\vskip` 2694, 2695
`\vss` 8313
`\vtex@trans@special` 11285,
11287, 11290, 11294, 11298,
11302, 11304, 11306, 11310,
11316, 11317, 11320
`\VTeXInitMediaSize` 10964, 10981
`\VTeXOS` . 11355, 11356, 11357,
11359
`\VTeXversion` 6794, 6797, 6800,
11347, 11351
`\Vvdash` 18762, 20714

W

`\wasylounge` 18920, 20779
`\waw` 20243

`\wawhamza` 20181
`\wd` . 10093, 10109, 10130, 10147,
10170, 10187, 13883
`\wedge` 18427, 20569
`\wedgedot` 19603, 20981
`\Wheelchair` 19372, 20880
`\with` 15653, 21161
`\WomanFace` 19997, 21138
`\Womanface` 19999, 21494
`\wp` 18091, 20451
`\wr` 18480, 20591
`\wreath` 18482, 21333
`\write` . . 4955, 6470, 6472, 6908,
6916, 7232, 7260, 8010,
8025, 8041, 8051, 8081,
8104, 8130, 8160, 13446,
13470, 14844, 14926

`\WriteBookmarks` . . 4371, 4509,
4690, 4712, 14593, 14837,
14870, 14871, 14913, 14919
`\WritingHand` 19451, 20910
`\Writinghand` 19453, 21461
`\wwwbrowser` . . . 10047, 10132,
10149

X

`\x` 21, 25,
92, 98, 168, 169, 176, 178,
206, 209, 210, 211, 212, 213,
214, 215, 216, 217, 218, 219,
220, 221, 222, 223, 224, 225,
226, 227, 228, 291, 296, 297,
523, 528, 861, 864, 868, 873,
905, 1035, 1041, 1798, 1826,
2269, 2271, 2689, 2699,
2708, 2718, 2787, 2788,
2793, 2809, 3537, 3540,
3544, 3557, 3667, 3668,
3671, 3672, 3673, 3677,
3680, 3686, 4129, 4135,
4138, 4141, 4296, 4297,
4302, 4303, 4385, 4386,
4387, 4390, 4393, 4396,
4436, 4437, 4439, 4440,
4618, 4621, 4954, 4960,
5305, 5306, 5307, 5319,
5330, 5331, 5332, 5333,
5336, 5337, 5382, 5385,
5480, 5494, 5519, 5523,
5526, 5536, 6073, 6077,
6086, 6090, 6544, 6545,
6550, 7244, 7251, 7284,
7291, 7332, 7341, 7343,
7355, 8373, 8375, 8659,
8660, 8883, 8886, 8921,
8922, 8923, 8925, 8927,
9350, 9359, 9647, 9648,
9651, 9653, 9656, 10322,

10323, 10324, 10326, 10327,
 10328, 10330, 10331, 10332,
 10334, 10335, 10336, 10338,
 10339, 10340, 10342, 10343,
 10344, 10346, 10347, 10348,
 10350, 10351, 10353, 10359,
 10368, 11467, 11472, 11476,
 11847, 11850, 11856, 11861,
 12006, 12007, 13087, 13107,
 13602, 13622, 13950, 13970,
 14981, 14983, 15052, 15054
 \XBox 19221, 21405
 \XeTeXLink@font . . 5151, 5154
 \XeTeXLink@space . 5152, 5167,
 5181
 \XeTeXLinkBox . . . 5158, 5190
 \XeTeXLinkMargin . 5148, 5149,
 5164, 5166, 5177, 5179
 \XeTeXrevision 4677, 10682
 \XeTeXversion 4677, 10682
 \Xi 16821, 20349
 \xi 16886, 20369
 \xinferior 20437
 \XR@cdURL 2626, 2627
 \XR@addURL 2626
 \XR@ext 2895, 2896, 5288, 5291,
 6792, 9179, 9943, 10046,
 10310, 10845, 12200, 12283,
 12342, 12541, 12705
 \XR@URL 2631
 \XSolid 19469, 20918
 \XSolidBold 19471, 20919

\XSolidBrush 19473, 20920
 \xspace 692, 694
 \xspaceaddeceptions 4343, 4352

Y

\y 296, 298, 305, 311,
 876, 879, 882, 885, 888, 891,
 900, 2789, 2794, 2799, 3673,
 3674, 3675, 3676, 4388,
 4391, 4394, 4397, 4399,
 4405, 5308, 5309, 5310,
 5311, 5319, 6545, 6553,
 7328, 7330, 7331, 7334,
 7341, 11852, 11853, 11854,
 11855
 \ya 20247
 \yahamza 20185
 \YingYang 19247, 21413
 \Yingyang 19248, 21414
 \YinYang 19244, 20846
 \Yinyang 19246, 21412
 \yogh 16638, 20341

Z

\z 297, 298, 306, 312, 2791, 2792,
 2793, 5311, 5319
 \z@ 837,
 877, 1062, 1214, 1231, 1253,
 1276, 1527, 1567, 1580,
 1596, 1611, 1619, 1692,
 1954, 1960, 1966, 2039,
 2043, 2051, 2055, 2645,
 2650, 2684, 2703, 2977,

2980, 3126, 3679,
 4298, 4686, 5161,
 5171, 5172, 5175,
 5184, 5185, 5193,
 6505, 6795, 6798,
 7586, 7757, 9860,
 9869, 9873, 9880,
 9887, 9890, 10827,
 10833, 10834, 11346,
 11590, 11890, 11904,
 12266, 12271, 12272,
 13592, 13887, 13940,
 14392, 14397, 14420,
 14455, 14489, 14495,
 14525, 14530, 14561,
 14671, 14672, 14673,
 14675, 14676, 14677,
 14679, 14896, 15018

\z@skip
 \za
 \zay
 \zeroinferior
 \zerosuperior
 \zeta 16870,
 \zref@extractdefault
 \zref@ifrefcontainsprop . .
 \zref@ifrefundefined
 \zref@labelbyprops
 \zref@refused
 \Zwdr 19989,
 \ZW NJ
 \ZwPa 19975,