

TravelCCM

0.5.3

Generated by Doxygen 1.8.1.2

Thu Aug 16 2012 09:53:37

Contents

1	TravelCCM Documentation	2
1.1	Getting Started	2
1.2	TravelCCM at SourceForge	2
1.3	TravelCCM Development	2
1.4	External Libraries	2
1.5	Support TravelCCM	3
1.6	About TravelCCM	3
2	TravelCCM People	3
2.1	Project Admins	3
2.2	Developers	3
2.3	Retired Developers	3
2.4	Contributors	4
2.5	Distribution Maintainers	4
3	Coding Rules	4
3.1	Default Naming Rules for Variables	4
3.2	Default Naming Rules for Files	4
3.3	Default Naming Rules for Functions	5
3.4	Default Naming Rules for Classes and Structures	5
3.5	Default Functionality of Classes	5
4	Copyright and License	5
4.1	GNU LESSER GENERAL PUBLIC LICENSE	5
4.1.1	Version 2.1, February 1999	5
4.2	Preamble	5
4.3	TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION	7
4.3.1	NO WARRANTY	10
4.3.2	END OF TERMS AND CONDITIONS	11
4.4	How to Apply These Terms to Your New Programs	11
5	Documentation Rules	11
5.1	General Rules	11
5.2	File Header	12
5.3	Grouping Various Parts	13
6	Main features of TravelCCM	13
6.1	Customer-Choice features	13
6.2	Other features	13
7	Make a Difference	14

8	Make a new release	14
8.1	Introduction	14
8.2	Initialisation	15
8.3	Release branch maintenance	15
8.4	Commit and publish the release branch	15
8.5	Create source packages (tar-balls)	15
8.6	Upload the HTML documentation to SourceForge	16
8.7	Generate the RPM packages	16
8.8	Update distributed change log	16
8.9	Create the binary package, including the documentation	16
8.10	Upload the files to SourceForge	17
8.11	Make a new post	17
8.12	Send an email on the announcement mailing-list	17
9	Installation	17
9.1	Table of Contents	17
9.2	Fedora/RedHat Linux distributions	17
9.3	TravelCCM Requirements	18
9.4	Basic Installation	18
9.5	Compilers and Options	19
9.6	Compiling For Multiple Architectures	19
9.7	Installation Names	20
9.8	Optional Features	20
9.9	Particular systems	21
9.10	Specifying the System Type	21
9.11	Sharing Defaults	22
9.12	Defining Variables	22
9.13	'cmake' Invocation	22
10	Linking with TravelCCM	26
10.1	Table of Contents	26
10.2	Introduction	26
10.3	Dependencies	26
10.3.1	StdAir	26
10.4	Using the pkg-config command	27
10.5	Using the travelccm-config script	27
10.6	M4 macro for the GNU Autotools	28
10.7	Using TravelCCM with dynamic linking	28
11	Test Rules	28
11.1	The Test File	28

11.2 The Reference File	28
11.3 Testing IT++ Library	28
12 Users Guide	29
12.1 Table of Contents	29
12.2 Introduction	29
12.3 Get Started	29
12.3.1 Get the TravelCCM library	29
12.3.2 Build the TravelCCM project	29
12.3.3 Build and Run the Tests	30
12.3.4 Install the TravelCCM Project (Binaries, Documentation)	30
12.4 Input file of TravelCCM Project	30
12.5 The schedule BOM Tree	31
12.5.1 Build of the schedule BOM tree	32
12.5.2 Display of the schedule BOM tree	32
12.6 Exploring the Predefined BOM Tree	75
12.6.1 Airline Network BOM Tree	75
12.6.2 Airline Schedule BOM Tree	75
12.7 Extending the BOM Tree	76
12.8 The travel solution calculation procedure	76
13 TRAVELCCM Supported Systems	76
13.1 Table of Contents	76
13.2 Introduction	76
13.3 TRAVELCCM 3.10.x	77
13.3.1 Linux Systems	77
13.3.2 Windows Systems	80
13.3.3 Unix Systems	83
14 TRAVELCCM Supported Systems (Previous Releases)	83
14.1 TRAVELCCM 3.9.1	83
14.2 TRAVELCCM 3.9.0	83
14.3 TRAVELCCM 3.8.1	83
15 Tutorials	83
15.1 Table of Contents	83
15.2 Preparing the TravelCCM Project for Development	84
15.3 Your first networkBuilde	84
15.3.1 Summary of the different steps	84
15.3.2 Result of the Batch Program	84
15.4 Network building with an input file	85

15.4.1	How to build a network input file?	85
15.4.2	Building the BOM tree with an input file	86
15.4.3	Result of the Batch Program	86
16	Command-Line Test to Demonstrate How To Test the Travel CCM Project	87
17	Namespace Index	88
17.1	Namespace List	88
18	Class Index	88
18.1	Class Hierarchy	88
19	Class Index	89
19.1	Class List	89
20	File Index	90
20.1	File List	90
21	Namespace Documentation	91
21.1	stdair Namespace Reference	91
21.1.1	Detailed Description	91
21.2	TRAVELCCM Namespace Reference	91
21.2.1	Typedef Documentation	91
22	Class Documentation	91
22.1	TRAVELCCM::ChoiceManager Class Reference	91
22.1.1	Detailed Description	92
22.1.2	Member Function Documentation	92
22.2	TRAVELCCM::CmdAbstract Class Reference	92
22.2.1	Detailed Description	92
22.3	TRAVELCCM::CustomerChoiceException Class Reference	92
22.3.1	Detailed Description	93
22.3.2	Constructor & Destructor Documentation	93
22.4	FacServiceAbstract Class Reference	93
22.5	TRAVELCCM::FacTRAVELCCMSERVICECONTEXT Class Reference	93
22.5.1	Detailed Description	94
22.5.2	Constructor & Destructor Documentation	94
22.5.3	Member Function Documentation	94
22.6	TRAVELCCM::FileMgr Class Reference	95
22.6.1	Detailed Description	95
22.7	TRAVELCCM::PriceOrientedModel Class Reference	95
22.7.1	Detailed Description	95
22.7.2	Member Function Documentation	95

22.8	RootException Class Reference	95
22.9	ServiceAbstract Class Reference	96
22.10	TestFixture Class Reference	96
22.11	TRAVELCCM::TRAVELCCM_Service Class Reference	96
22.11.1	Detailed Description	97
22.11.2	Constructor & Destructor Documentation	97
22.11.3	Member Function Documentation	98
22.12	TRAVELCCM::TRAVELCCM_ServiceContext Class Reference	99
22.12.1	Detailed Description	100
22.12.2	Friends And Related Function Documentation	100
22.13	TravelChoiceTestSuite Class Reference	100
22.13.1	Detailed Description	101
22.13.2	Constructor & Destructor Documentation	101
22.13.3	Member Function Documentation	101
22.13.4	Member Data Documentation	101
23	File Documentation	101
23.1	doc/local/authors.doc File Reference	101
23.2	doc/local/codingrules.doc File Reference	101
23.3	doc/local/copyright.doc File Reference	101
23.4	doc/local/documentation.doc File Reference	101
23.5	doc/local/features.doc File Reference	101
23.6	doc/local/help_wanted.doc File Reference	101
23.7	doc/local/howto_release.doc File Reference	101
23.8	doc/local/index.doc File Reference	101
23.9	doc/local/installation.doc File Reference	101
23.10	doc/local/linking.doc File Reference	101
23.11	doc/local/test.doc File Reference	102
23.12	doc/local/users_guide.doc File Reference	102
23.13	doc/local/verification.doc File Reference	102
23.14	doc/tutorial/tutorial.doc File Reference	102
23.15	test/travelccm/TravelChoiceTestSuite.cpp File Reference	102
23.16	TravelChoiceTestSuite.cpp	102
23.17	test/travelccm/TravelChoiceTestSuite.hpp File Reference	103
23.17.1	Function Documentation	103
23.18	TravelChoiceTestSuite.hpp	104
23.19	travelccm/basic/BasConst.cpp File Reference	104
23.20	BasConst.cpp	104
23.21	travelccm/basic/BasConst_General.hpp File Reference	104
23.22	BasConst_General.hpp	104

23.23travelccm/batches/travelccm.cpp File Reference	105
23.24travelccm.cpp	105
23.25travelccm/bom/PriceOrientedModel.cpp File Reference	107
23.26PriceOrientedModel.cpp	108
23.27travelccm/bom/PriceOrientedModel.hpp File Reference	109
23.28PriceOrientedModel.hpp	109
23.29travelccm/command/ChoiceManager.cpp File Reference	109
23.30ChoiceManager.cpp	110
23.31travelccm/command/ChoiceManager.hpp File Reference	110
23.32ChoiceManager.hpp	110
23.33travelccm/command/CmdAbstract.cpp File Reference	111
23.34CmdAbstract.cpp	111
23.35travelccm/command/CmdAbstract.hpp File Reference	111
23.36CmdAbstract.hpp	111
23.37travelccm/command/FileMgr.cpp File Reference	112
23.38FileMgr.cpp	112
23.39travelccm/command/FileMgr.hpp File Reference	112
23.40FileMgr.hpp	112
23.41travelccm/config/travelccm-paths.hpp File Reference	113
23.41.1 Macro Definition Documentation	113
23.42travelccm-paths.hpp	114
23.43travelccm/config/travelccm-paths.hpp.in File Reference	115
23.43.1 Macro Definition Documentation	115
23.44travelccm-paths.hpp.in	116
23.45travelccm/factory/FacTRAVELCCMSERVICECONTEXT.cpp File Reference	117
23.46FacTRAVELCCMSERVICECONTEXT.cpp	117
23.47travelccm/factory/FacTRAVELCCMSERVICECONTEXT.hpp File Reference	118
23.48FacTRAVELCCMSERVICECONTEXT.hpp	118
23.49travelccm/service/TRAVELCCM_Service.cpp File Reference	119
23.50TRAVELCCM_Service.cpp	119
23.51travelccm/service/TRAVELCCM_ServiceContext.cpp File Reference	123
23.52TRAVELCCM_ServiceContext.cpp	123
23.53travelccm/service/TRAVELCCM_ServiceContext.hpp File Reference	124
23.54TRAVELCCM_ServiceContext.hpp	124
23.55travelccm/TRAVELCCM_Service.hpp File Reference	125
23.56TRAVELCCM_Service.hpp	125
23.57travelccm/TRAVELCCM_Types.hpp File Reference	126
23.58TRAVELCCM_Types.hpp	127

1 TravelCCM Documentation

1.1 Getting Started

- [Main features of TravelCCM](#)
- [Installation](#)
- [Linking with TravelCCM](#)
- [Users Guide](#)
- [Tutorials](#)
- [Copyright and License](#)
- [Make a Difference](#)
- [Make a new release](#)
- [TravelCCM People](#)

1.2 TravelCCM at SourceForge

- [Project page](#)
- [Download TravelCCM](#)
- [Open a ticket for a bug or feature](#)
- [Mailing lists](#)
- [Forums](#)
 - [Discuss about Development issues](#)
 - [Ask for Help](#)
 - [Discuss TravelCCM](#)

1.3 TravelCCM Development

- [Git Repository](#) (Subversion is deprecated)
- [coding_rules](#)
- [Documentation Rules](#)
- [Test Rules](#)

1.4 External Libraries

- [Boost](#) (C++ STL extensions)
- [Python](#)
- [MySQL client](#)
- [SOI](#) (C++ DB API)

1.5 Support TravelCCM

1.6 About TravelCCM

TravelCCM aims at providing a clean API, and the corresponding C++ implementation, for choosing one item among a set of travel solutions, given demand-related characteristics (e.g., Willingness-To-Pay, preferred airline, preferred cabin, etc.). [N](#)

The TravelCCM C++ library implements some simple Customer Choice Models (CCM), as referenced in the literature (PhD dissertations at MIT, for instance: <http://dspace.mit.edu>).

The TravelCCM C++ library exposes a simple, clean and object-oriented, API. For instance, the `choose()` method takes, as input, both a structure representing the travel request (e.g., from Washington, DC, US, to Beijing, China, on the 25th of May) and a list of travel solutions (as provided by the Airline Schedule Manager project: <http://sourceforge.net/projects/air-sched>), and yields, as output, the chosen item.

The output can then be used by other systems, for instance to book the corresponding travel or to visualise it on a map and calendar and to share it with others.

TravelCCM makes an extensive use of existing open-source libraries for increased functionality, speed and accuracy. In particular **Boost** (*C++ STL Extensions*) library is used.

The TravelCCM project originates from the department of Operational Research and Innovation at **Amadeus**, Sophia Antipolis, France. TravelCCM is released under the terms of the **GNU Lesser General Public License** (LGPLv2.1) for you to enjoy.

TravelCCM should work on **GNU/Linux**, **Sun Solaris**, Microsoft Windows (with **Cygwin**, **MinGW/MSYS**, or **Microsoft Visual C++ .NET**) and **Mac OS X** operating systems.

Note

(N) - The TravelCCM library is **NOT** intended, in any way, to be used by airlines for production systems. If you want to report issue, bug or feature request, or if you just want to give feedback, have a look on the right-hand side of this page for the preferred reporting methods. In any case, please do not contact Amadeus directly for any matter related to TravelCCM.

2 TravelCCM People

2.1 Project Admins

- Denis Arnaud denis_arnaud@users.sourceforge.net ([N](#))
- Anh Quan Nguyen quannaus@users.sourceforge.net ([N](#))

2.2 Developers

- Anh Quan Nguyen quannaus@users.sourceforge.net ([N](#))
- Denis Arnaud denis_arnaud@users.sourceforge.net ([N](#))
- Gabrielle Sabatier gsabatier@users.sourceforge.net ([N](#))

2.3 Retired Developers

- Benoit Lardeux benlardeux@users.sourceforge.net ([N](#))
- Mehdi Ayouni mehdi.ayouni@gmail.com
- Alexandre Point apoint@users.sourceforge.net

2.4 Contributors

- Dongkyoung Choe dchoe@users.sourceforge.net (N)
- Emmanuel Bastien ebastien@users.sourceforge.net (N)
- Christophe Lacombe ddtof@users.sourceforge.net (N)

2.5 Distribution Maintainers

- **Fedora/RedHat**: Denis Arnaud denis_arnaud@users.sourceforge.net (N)
- **Debian**: Emmanuel Bastien ebastien@users.sourceforge.net (N)

Note

(N) - **Amadeus** employees.

3 Coding Rules

In the following sections we describe the naming conventions which are used for files, classes, structures, local variables, and global variables.

3.1 Default Naming Rules for Variables

Variables are named using lower-case letters and words are separated using under-score. Abbreviations, when used in variable names, are also written with lower-case letters. Examples:

- `'fft_size'`
- `'nrof_paths'`
- `'my_variable_name'`

Some variable names or parts of variable names are commonly used in several different functions and files to denote the same thing. For instance the following common names and prefixes should be used:

- `'rows'` - number of rows in a matrix
- `'cols'` - number of columns in a matrix
- `'nrof_'` - number of ...

3.2 Default Naming Rules for Files

Files are named using lower-case letters and words are separated using under-score. Abbreviations, when used in file names, are also written with lower-case letters.

Source files are named using `' .cpp'` suffix, whereas header files end with `' .h'` extension. Examples:

- `'my_file.h'`
- `'my_file.cpp'`

3.3 Default Naming Rules for Functions

Function names are named using lower-case letters and words are separated using under-score. Abbreviations, when used in function names, are also written with lower-case letters. This rule applies both to stand-alone functions as well as to member functions of classes. Example:

- `int my_function_name(int a, int b)`

3.4 Default Naming Rules for Classes and Structures

Each new word in a class or structure name should always start with a capital letter and the words should be separated with an under-score. Abbreviations are written with capital letters. Examples:

- `'My_Class_Name'`
- `'My_Struct_Name'`
- `'OFDM'`

3.5 Default Functionality of Classes

All classes that are configured by input parameters should include:

- default empty constructor
- one or more additional constructor(s) that takes input parameters and initializes the class instance
- setup function, preferably named `'setup'` or `'set_parameters'`

Explicit destructor functions are not required, unless they are needed. It shall not be possible to use any of the other member functions unless the class has been properly initiated with the input parameters.

4 Copyright and License

4.1 GNU LESSER GENERAL PUBLIC LICENSE

4.1.1 Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

4.2 Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software—to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages—typically libraries—of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest

you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

4.3 TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

1. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

1. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

1. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

1. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

1. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the work with the complete corresponding

machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

1. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

1. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

1. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

1. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.
1. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

1. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.
1. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

1. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

4.3.1 NO WARRANTY

1. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

1. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

4.3.2 END OF TERMS AND CONDITIONS

4.4 How to Apply These Terms to Your New Programs

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>
```

```
This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.
```

```
This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.
```

```
You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
```

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the
library 'Frob' (a library for tweaking knobs) written by James Random Hacker.
```

```
<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice
```

That's all there is to it!

Source

5 Documentation Rules

5.1 General Rules

All classes in IT++ should be properly documented with Doxygen comments in include ('.h') files. Source ('.cpp') files should be documented according to a normal standard for well documented C++ code.

An example of how the interface of a class shall be documented in IT++ is shown here:

```

/*!
 * \brief Brief description of My_Class here
 *
 * Detailed description of My_Class here. With example code if needed.
 */
class My_Class {

public:

    //! Default constructor
    My_Class(void) { setup_done = false; }

    /*!
     * \brief Constructor that initializes the class with parameters
     *
     * Detailed description of the constructor here if needed
     *
     * \param[in] param1 Description of \a param1 here
     * \param[in] param2 Description of \a param2 here
     */
    My_Class(TYPE1 param1, TYPE2 param2) { setup(param1, param2); }

    /*!
     * \brief Setup function for My_Class
     *
     * Detailed description of the setup function here if needed
     *
     * \param[in] param1 Description of \a param1 here
     * \param[in] param2 Description of \a param2 here
     */
    void setup(TYPE1 param1, TYPE2 param2);

    /*!
     * \brief Brief description of member_function1
     *
     * Detailed description of member_function1 here if needed
     *
     * \param[in] param1 Description of \a param1 here
     * \param[in] param2 Description of \a param2 here
     * \param[in,out] param3 Description of \a param3 here
     * \return Description of the return value here
     */
    TYPE4 member_function1(TYPE1 param1, TYPE2 param2, TYPE3 &param3);

private:

    bool setup_done;          /*!< Variable that checks if the class is properly
                               initialized with parameters */
    TYPE1 private_variable1; /*!< Short description of private_variable1 here
    TYPE2 private_variable2; /*!< Short description of private_variable2 here
};

```

5.2 File Header

All files should start with the following header, which include Doxygen's `\file`, `\brief` and `\author` tags, `$Date$` and `$Revisions$` CVS tags, and a common copyright note:

```

/*!
 * \file
 * \brief Brief description of the file here
 * \author Names of the authors who contributed to this code
 *
 * Detailed description of the file here if needed.
 *
 * $Date: 2005-12-13 12:27:39 +0100 (mar, 13 déc 2005) $
 * $Revision: 93 $
 *
 * -----
 *
 * IT++ - C++ library of mathematical, signal processing, speech processing,
 * and communications classes and functions

```

```

*
* Copyright (C) 1995-2005 (see AUTHORS file for a list of contributors)
*
* This program is free software; you can redistribute it and/or modify
* it under the terms of the GNU General Public License as published by
* the Free Software Foundation; either version 2 of the License, or
* (at your option) any later version.
*
* This program is distributed in the hope that it will be useful,
* but WITHOUT ANY WARRANTY; without even the implied warranty of
* MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
* GNU General Public License for more details.
*
* You should have received a copy of the GNU General Public License
* along with this program; if not, write to the Free Software
* Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
*
* -----
*/

```

5.3 Grouping Various Parts

All functions must be added to a Doxygen group in order to appear in the documentation. The following code example defines the group `'my_group'`:

```

/*!
 * \defgroup my_group Brief description of the group here
 *
 * Detailed description of the group here
 */

```

The following example shows how to document the function `'my_function'` and how to add it to the group `'my_group'`:

```

/*!
 * \brief Brief description of my_function here
 * \ingroup my_group
 *
 * Detailed description of my_function here
 *
 * \param[in] param1 Description of \a param1 here
 * \param[in] param2 Description of \a param2 here
 * \return Description of the return value here
 */
TYPE3 my_function(TYPE1 param1, TYPE2 &param2);

```

6 Main features of TravelCCM

A short list of the main features of TravelCCM is given below sorted in different categories. Some more features and functions exist and for these we refer to the reference documentation.

6.1 Customer-Choice features

- Customer-Choice Model (CCM)

6.2 Other features

- CSV input file parsing

7 Make a Difference

Do not ask what TravelCCM can do for you. Ask what you can do for TravelCCM.

You can help us to develop the TravelCCM library. There are always a lot of things you can do:

- Start using TravelCCM
- Tell your friends about TravelCCM and help them to get started using it
- If you find a bug, report it to us. Without your help we can never hope to produce a bug free code.
- Help us to improve the documentation by providing information about documentation bugs
- Answer support requests in the TravelCCM discussion forums on SourceForge. If you know the answer to a question, help others to overcome their TravelCCM problems.
- Help us to improve our algorithms. If you know of a better way (e.g. that is faster or requires less memory) to implement some of our algorithms, then let us know.
- Help us to port TravelCCM to new platforms. If you manage to compile TravelCCM on a new platform, then tell us how you did it.
- Send us your code. If you have a good TravelCCM compatible code, which you can release under the LGPLv2.1, and you think it should be included in TravelCCM, then send it to us.
- Become an TravelCCM developer. Send us an e-mail and tell what you can do for TravelCCM.

8 Make a new release

8.1 Introduction

This document describes briefly the recommended procedure of releasing a new version of TravelCCM using a Linux development machine and the SourceForge project site.

The following steps are required to make a release of the distribution package.

- [Initialisation](#)
- [Release branch maintenance](#)
- [Commit and publish the release branch](#)
- [Create source packages \(tar-balls\)](#)
- [Upload the HTML documentation to SourceForge](#)
- [Generate the RPM packages](#)
- [Update distributed change log](#)
- [Create the binary package, including the documentation](#)
- [Upload the files to SourceForge](#)
- [Make a new post](#)
- [Send an email on the announcement mailing-list](#)

8.2 Initialisation

Clone locally the full [Git project](#):

```
cd ~
mkdir -p dev/sim
cd ~/dev/sim
git clone git://travel-ccm.git.sourceforge.net/gitroot/travel-ccm/travel-ccm travelccmgit
cd travelccmgit
git checkout trunk
```

8.3 Release branch maintenance

Switch to the release branch, on your local clone, and merge the latest updates from the trunk. Decide about the new version to be released.

```
cd ~/dev/sim/travelccmgit
git checkout releases
git merge trunk
```

Update the version in the various build system files, replacing the old version numbers by the correct ones:

```
vi CMakeLists.txt
vi autogen.sh
vi README
```

Update the version, add some news in the NEWS file, add a change-log in the ChangeLog file and in the RPM specification files:

```
vi NEWS
vi ChangeLog
vi travelccm.spec
```

8.4 Commit and publish the release branch

Commit the new release:

```
cd ~/dev/sim/travelccmgit
git add -A
git commit -m "[Release 0.5.0] Release of the 0.5.0 version of TravelCCM."
git push
```

8.5 Create source packages (tar-balls)

Create the distribution packages using the following command:

```
cd ~/dev/sim/travelccmgit
git checkout releases
rm -rf build && mkdir -p build
cd build
export INSTALL_BASEDIR=/home/user/dev/deliveries
export LIBSUFFIX_4_CMAKE="-DLIB_SUFFIX=64"
cmake -DCMAKE_INSTALL_PREFIX=${INSTALL_BASEDIR}/travelccm-0.5.0 \
  -DWITH_STDAIR_PREFIX=${INSTALL_BASEDIR}/stdair-stable \
  -DWITH_AIRAC_PREFIX=${INSTALL_BASEDIR}/airsched-stable \
  -DWITH_AIRAC_PREFIX=${INSTALL_BASEDIR}/airrac-stable \
  -DWITH_TravelCCM_PREFIX=${INSTALL_BASEDIR}/travelccm-stable \
  -DWITH_TravelCCM_PREFIX=${INSTALL_BASEDIR}/airinv-stable \
  -DWITH_TravelCCM_PREFIX=${INSTALL_BASEDIR}/simfqt-stable \
  -DCMAKE_BUILD_TYPE:String=Debug -DINSTALL_DOC:BOOL=ON \
  ${LIBSUFFIX_4_CMAKE} ..
make check && make dist
make install
```

This will configure, compile and check the package. The output packages will be named, for instance, `travelccm-0.5.0.tar.gz` and `travelccm-0.5.0.tar.bz2`.

8.6 Upload the HTML documentation to SourceForge

In order to update the Web site files, either:

- **synchronise them with rsync and SSH:** Upload the just generated HTML (and PDF) documentation onto the **SourceForge Web site**.

```
cd ~/dev/sim/travelccmgit/build
git checkout releases
rsync -aiv ${INSTALL_BASEDIR}/travelccm-0.5.0/share/doc/travelccm-0.5.0/html/ \
  your_sf_user,travel-ccm@web.sourceforge.net:htdocs/
```

where `-aiv` options mean:

- `-a`: archive/mirror mode; equals `-rlptgoD` (no `-H`, `-A`, `-X`)
- `-v`: increase verbosity
- `-i`: output a change-summary for all updates
- Note the trailing slashes (/) at the end of both the source and target directories. It means that the content of the source directory (`doc/html`), rather than the directory itself, has to be copied into the content of the target directory.

- or use the **SourceForge Shell service**.

8.7 Generate the RPM packages

Optionally, generate the RPM package (for instance, for **Fedora/RedHat**):

```
cd ~/dev/sim/travelccmgit/build
git checkout releases
make dist
```

To perform this step, `rpm-build`, `rpmlint` and `rpmdevtools` have to be available on the system.

```
cp ../travelccm.spec ~/dev/packages/SPECS \
  && cp travelccm-0.5.0.tar.bz2 ~/dev/packages/SOURCES
cd ~/dev/packages/SPECS
rpmbuild -ba travelccm.spec
cd ~/dev/packages
rpmlint -i SPECS/travelccm.spec SRPMS/travelccm-0.5.0-1.fc16.src.rpm \
  RPMS/noarch/travelccm-* RPMS/i686/travelccm-*
```

8.8 Update distributed change log

Update the `NEWS` and `ChangeLog` files with appropriate information, including what has changed since the previous release. Then commit and push the changes into the **TravelCCM's Git repository**.

8.9 Create the binary package, including the documentation

Create the binary package, which includes HTML and PDF documentation, using the following command:

```
cd ~/dev/sim/travelccmgit/build
git checkout releases
make package
```

The output binary package will be named, for instance, `travelccm-0.5.0-Linux.tar.bz2`. That package contains both the HTML and PDF documentation. The binary package contains also the executables and shared libraries, as well as C++ header files, but all of those do not interest us for now.

8.10 Upload the files to SourceForge

Upload the distribution and documentation packages to the SourceForge server. Check [SourceForge help page on uploading software](#).

8.11 Make a new post

- submit a new entry in the [SourceForge project-related news feed](#)
- make a new post on the [SourceForge hosted WordPress blog](#)
- and update, if necessary, [Trac tickets](#).

8.12 Send an email on the announcement mailing-list

Finally, you should send an announcement to travelccm-announce@lists.sourceforge.net (see <https://lists.sourceforge.net/lists/listinfo/travelccm-announce> for the archives)

9 Installation

9.1 Table of Contents

- [Fedora/RedHat Linux distributions](#)
- [TravelCCM Requirements](#)
- [Basic Installation](#)
- [Compilers and Options](#)
- [Compiling For Multiple Architectures](#)
- [Installation Names](#)
- [Optional Features](#)
- [Particular systems](#)
- [Specifying the System Type](#)
- [Sharing Defaults](#)
- [Defining Variables](#)
- ['cmake' Invocation](#)

9.2 Fedora/RedHat Linux distributions

Note that on [Fedora/RedHat](#) Linux distributions, RPM packages are available and can be installed with your usual package manager. For instance:

```
yum -y install travelccm-devel travelccm-doc
```

RPM packages can also be available on the [SourceForge download site](#).

9.3 TravelCCM Requirements

TravelCCM should compile without errors or warnings on most GNU/Linux systems, on UNIX systems like Solaris SunOS, and on POSIX based environments for Microsoft Windows like Cygwin or MinGW with MSYS. It can be also built on Microsoft Windows NT/2000/XP/Vista/7 using Microsoft's Visual C++ .NET, but our support for this compiler is limited. For GNU/Linux, SunOS, Cygwin and MinGW we assume that you have at least the following GNU software installed on your computer:

- GNU Autotools:
 - `autoconf`,
 - `automake`,
 - `libtool`,
 - `make`, version 3.72.1 or later (check version with ``make --version``)
- `GCC` - GNU C++ Compiler (g++), version 4.3.x or later (check version with ``gcc --version``)
- `Boost` - C++ STL extensions, version 1.35 or later (check version with ``grep "define BOOST_LIB_VERSION" /usr/include/boost/version.hpp``)
- `MySQL` - Database client libraries, version 5.0 or later (check version with ``mysql --version``)
- `SOCI` - C++ database client library wrapper, version 3.0.0 or later (check version with ``soci-config --version``)

Optionally, you might need a few additional programs: `Doxygen`, `LaTeX`, `Dvips` and `Ghostscript`, to generate the HTML and PDF documentation.

We strongly recommend that you use recent stable releases of the GCC, if possible. We do not actively work on supporting older versions of the GCC, and they may therefore (without prior notice) become unsupported in future releases of TravelCCM.

9.4 Basic Installation

Briefly, the shell commands `./cmake .. && make install` should configure, build, and install this package. The following more-detailed instructions are generic; see the `'README'` file for instructions specific to this package. Some packages provide this `'INSTALL'` file but do not implement all of the features documented below. The lack of an optional feature in a given package is not necessarily a bug. More recommendations for GNU packages can be found in the info page corresponding to "Makefile Conventions: (standards)Makefile Conventions".

The `'cmake'` shell script attempts to guess correct values for various system-dependent variables used during compilation. It uses those values to create a `'Makefile'` in each directory of the package. It may also create one or more ``.h'` files containing system-dependent definitions. Finally, it creates a `'CMakeCache.txt'` cache file that you can refer to in the future to recreate the current configuration, and a file `'CMakeFiles'` containing compiler output (useful mainly for debugging `'cmake'`).

It can also use an optional file (typically called `'config.cache'` and enabled with `'-cache-file=config.cache'` or simply `'-C'`) that saves the results of its tests to speed up reconfiguring. Caching is disabled by default to prevent problems with accidental use of stale cache files.

If you need to do unusual things to compile the package, please try to figure out how `'configure'` could check whether to do them, and mail diffs or instructions to the address given in the `'README'` so they can be considered for the next release. If you are using the cache, and at some point `'config.cache'` contains results you don't want to keep, you may remove or edit it.

The file `'CMakeLists.txt'` is used to create the `'CMakefile'`

files.

The simplest way to compile this package is:

1. `'cd'` to the directory containing the package's source code and type `'./cmake ..'` to configure the package for your system. Running `'cmake'` is generally fast. While running, it prints some messages telling which features it is checking for.
2. Type `'make'` to compile the package.
3. Optionally, type `'make check'` to run any self-tests that come with the package, generally using the just-built uninstalled binaries.
4. Type `'make install'` to install the programs and any data files and documentation. When installing into a prefix owned by root, it is recommended that the package be configured and built as a regular user, and only the `'make install'` phase executed with root privileges.
5. You can remove the program binaries and object files from the source code directory by typing `'make clean'`. To also remove the files that `'configure'` created (so you can compile the package for a different kind of computer), type `'make distclean'`. There is also a `'make maintainer-clean'` target, but that is intended mainly for the package's developers. If you use it, you may have to get all sorts of other programs in order to regenerate files that came with the distribution.
6. Often, you can also type `'make uninstall'` to remove the installed files again. In practice, not all packages have tested that uninstallation works correctly, even though it is required by the GNU Coding Standards.

9.5 Compilers and Options

Some systems require unusual options for compilation or linking that the `'cmake'` script does not know about. Run `'./cmake -help'` for details on some of the pertinent environment variables.

You can give `'cmake'` initial values for configuration parameters by setting variables in the command line or in the environment. Here is an example:

```
./cmake CC=c99 CFLAGS=-g LIBS=-lposix
```

See Also

[Defining Variables](#) for more details.

9.6 Compiling For Multiple Architectures

You can compile the package for more than one kind of computer at the same time, by placing the object files for each architecture in their own directory. To do this, you can use GNU `'make'`. `'cd'` to the directory where you want the object files and executables to go and run the `'configure'` script. `'configure'` automatically checks for the source code in the directory that `'configure'` is in and in `'../'`. This is known as a "VPATH" build.

With a non-GNU `'make'`, it is safer to compile the package for one architecture at a time in the source code directory. After you have installed the package for one architecture, use `'make distclean'` before reconfiguring for another architecture.

On MacOS X 10.5 and later systems, you can create libraries and executables that work on multiple system types-known as "fat" or "universal" binaries-by specifying multiple `'-arch'` options to the compiler but only a single `'-arch'` option to the preprocessor. Like this:

```
./configure CC="gcc -arch i386 -arch x86_64 -arch ppc -arch ppc64" \
           CXX="g++ -arch i386 -arch x86_64 -arch ppc -arch ppc64" \
           CPP="gcc -E" CXXCPP="g++ -E"
```

This is not guaranteed to produce working output in all cases, you may have to build one architecture at a time and combine the results using the 'lipo' tool if you have problems.

9.7 Installation Names

By default, 'make install' installs the package's commands under '/usr/local/bin', include files under '/usr/local/include', etc. You can specify an installation prefix other than '/usr/local' by giving 'configure' the option '-prefix=PREFIX', where PREFIX must be an absolute file name.

You can specify separate installation prefixes for architecture-specific files and architecture-independent files. If you pass the option '-exec-prefix=PREFIX' to 'configure', the package uses PREFIX as the prefix for installing programs and libraries. Documentation and other data files still use the regular prefix.

In addition, if you use an unusual directory layout you can give options like '-bindir=DIR' to specify different values for particular kinds of files. Run 'configure -help' for a list of the directories you can set and what kinds of files go in them. In general, the default for these options is expressed in terms of '\${prefix}', so that specifying just '-prefix' will affect all of the other directory specifications that were not explicitly provided.

The most portable way to affect installation locations is to pass the correct locations to 'configure'; however, many packages provide one or both of the following shortcuts of passing variable assignments to the 'make install' command line to change installation locations without having to reconfigure or recompile.

The first method involves providing an override variable for each affected directory. For example, 'make install prefix=/alternate/directory' will choose an alternate location for all directory configuration variables that were expressed in terms of '\${prefix}'. Any directories that were specified during 'configure', but not in terms of '\${prefix}', must each be overridden at install time for the entire installation to be relocated. The approach of makefile variable overrides for each directory variable is required by the GNU Coding Standards, and ideally causes no recompilation. However, some platforms have known limitations with the semantics of shared libraries that end up requiring recompilation when using this method, particularly noticeable in packages that use GNU Libtool.

The second method involves providing the 'DESTDIR' variable. For example, 'make install DESTDIR=/alternate/directory' will prepend '/alternate/directory' before all installation names. The approach of 'DESTDIR' overrides is not required by the GNU Coding Standards, and does not work on platforms that have drive letters. On the other hand, it does better at avoiding recompilation issues, and works well even when some directory options were not specified in terms of '\${prefix}' at 'configure' time.

9.8 Optional Features

If the package supports it, you can cause programs to be installed with an extra prefix or suffix on their names by giving 'cmake' the option '-program-prefix=PREFIX' or '-program-suffix=SUFFIX'.

Some packages pay attention to `'-enable-FEATURE'` options to `'configure'`, where `FEATURE` indicates an optional part of the package. They may also pay attention to `'-with-PACKAGE'` options, where `PACKAGE` is something like `'gnu-as'` or `'x'` (for the X Window System). The `'README'` should mention any `'-enable-'` and `'-with-'` options that the package recognizes.

For packages that use the X Window System, `'configure'` can usually find the X include and library files automatically, but if it doesn't, you can use the `'configure'` options `'-x-includes=DIR'` and `'-x-libraries=DIR'` to specify their locations.

Some packages offer the ability to configure how verbose the execution of `'make'` will be. For these packages, running `'./configure -enable-silent-rules'` sets the default to minimal output, which can be overridden with `'make V=1'`; while running `'./configure -disable-silent-rules'` sets the default to verbose, which can be overridden with `'make V=0'`.

9.9 Particular systems

On HP-UX, the default C compiler is not ANSI C compatible. If GNU CC is not installed, it is recommended to use the following options in order to use an ANSI C compiler:

```
./configure CC="cc -Ae -D_XOPEN_SOURCE=500"
```

and if that doesn't work, install pre-built binaries of GCC for HP-UX.

On OSF/1 a.k.a. Tru64, some versions of the default C compiler cannot parse its `<wchar.h>` header file. The option `'-nodtk'` can be used as a workaround. If GNU CC is not installed, it is therefore recommended to try

```
./configure CC="cc"
```

and if that doesn't work, try

```
./configure CC="cc -nodtk"
```

On Solaris, don't put `'/usr/ucb'` early in your `'PATH'`. This directory contains several dysfunctional programs; working variants of these programs are available in `'/usr/bin'`. So, if you need `'/usr/ucb'` in your `'PATH'`, put it *after* `'/usr/bin'`.

On Haiku, software installed for all users goes in `'/boot/common'`, not `'/usr/local'`. It is recommended to use the following options:

```
./cmake -DCMAKE_INSTALL_PREFIX=/boot/common
```

9.10 Specifying the System Type

There may be some features `'configure'` cannot figure out automatically, but needs to determine by the type of machine the package will run on. Usually, assuming the package is built to be run on the *same* architectures, `'configure'` can figure that out, but if it prints a message saying it cannot guess the machine type, give it the `'-build=TYPE'` option. `TYPE` can either be a short name for the system type, such as `'sun4'`, or a canonical name which has the form `CPU-COMPANY-SYSTEM`

where `SYSTEM` can have one of these forms:

- OS
- KERNEL-OS

See the file `'config.sub'` for the possible values of each field. If `'config.sub'` isn't included in this package, then this package doesn't need to know the machine type.

If you are *building* compiler tools for cross-compiling, you should use the option `'-target=TYPE'` to select the type of system they will produce code for.

If you want to use a cross compiler, that generates code for a platform different from the build platform, you should specify the "host" platform (i.e., that on which the generated programs will eventually be run) with `'-host=TYPE'`.

9.11 Sharing Defaults

If you want to set default values for `'configure'` scripts to share, you can create a site shell script called `'config.site'` that gives default values for variables like `'CC'`, `'cache_file'`, and `'prefix'`. `'configure'` looks for `'PREFIX/share/config.site'` if it exists, then `'PREFIX/etc/config.site'` if it exists. Or, you can set the `'CONFIG_SITE'` environment variable to the location of the site script. A warning: not all `'configure'` scripts look for a site script.

9.12 Defining Variables

Variables not defined in a site shell script can be set in the environment passed to `'configure'`. However, some packages may run `configure` again during the build, and the customized values of these variables may be lost. In order to avoid this problem, you should set them in the `'configure'` command line, using `'VAR=value'`. For example:

```
./configure CC=/usr/local2/bin/gcc
```

causes the specified `'gcc'` to be used as the C compiler (unless it is overridden in the site shell script).

Unfortunately, this technique does not work for `'CONFIG_SHELL'` due to an Autoconf bug. Until the bug is fixed you can use this workaround:

```
CONFIG_SHELL=/bin/bash /bin/bash ./configure CONFIG_SHELL=/bin/bash
```

9.13 'cmake' Invocation

`'cmake'` recognizes the following options to control how it operates.

- `'-help'`, `'-h'` print a summary of all of the options to `'cmake'`, and exit.
- `'-help=short'`, `'-help=recursive'` print a summary of the options unique to this package's `'configure'`, and exit. The `'short'` variant lists options used only in the top level, while the `'recursive'` variant lists options also present in any nested packages.
- `'-version'`, `'-V'` print the version of Autoconf used to generate the `'configure'` script, and exit.

- '-cache-file=FILE' enable the cache: use and save the results of the tests in FILE, traditionally 'config.cache'. FILE defaults to '/dev/null' to disable caching.
- '-config-cache', '-C' alias for '-cache-file=config.cache'.
- '-quiet', '-silent', '-q' do not print messages saying which checks are being made. To suppress all normal output, redirect it to '/dev/null' (any error messages will still be shown).
- '-srcdir=DIR' look for the package's source code in directory DIR. Usually 'configure' can determine that directory automatically.
- '-prefix=DIR' use DIR as the installation prefix.

See Also

[Installation Names](#) for more details, including other options available for fine-tuning the installation locations.

- '-no-create', '-n' run the configure checks, but stop before creating any output files.

'cmake' also accepts some other, not widely useful, options. Run 'cmake' -help' for more details.

The 'cmake' script produces an output like this:

```
-- Requires Git without specifying any version
cmake -DCMAKE_INSTALL_PREFIX=/home/user/dev/deliveries/travelccm-99.99.99 -DLIB_SUFFIX=64 -DCMAKE_BUILD_TYPE:S
-- The C compiler identification is GNU
-- The CXX compiler identification is GNU
-- Check for working C compiler: /usr/lib64/ccache/gcc
-- Check for working C compiler: /usr/lib64/ccache/gcc -- works
-- Detecting C compiler ABI info
-- Detecting C compiler ABI info - done
-- Check for working CXX compiler: /usr/lib64/ccache/c++
-- Check for working CXX compiler: /usr/lib64/ccache/c++ -- works
-- Detecting CXX compiler ABI info
-- Detecting CXX compiler ABI info - done
-- Requires Git without specifying any version
-- Current Git revision name: dbedfae29cd555c176034d09ecff12e80f28e915 trunk
-- Requires Boost-1.41
-- Boost version: 1.46.0
-- Found the following Boost libraries:
--   regex
--   program_options
--   date_time
--   iostreams
--   serialization
--   filesystem
--   unit_test_framework
--   python
-- Found Boost version: 1.46.0
-- Found BoostWrapper: /usr/include (Required is at least version "1.41")
-- Requires MySQL without specifying any version
-- Using mysql-config: /usr/bin/mysql_config
-- Found MySQL: /usr/lib64/mysql/libmysqlclient.so
-- Found MySQL version: 5.5.14
-- Requires SOCI-3.0
-- Using soci-config: /usr/bin/soci-config
-- SOCI headers are buried
-- Found SOCI: /usr/lib64/libsoci_core.so (Required is at least version "3.0")
-- Found SOCIMySQL: /usr/lib64/libsoci_mysql.so (Required is at least version "3.0")
-- Found SOCI with MySQL back-end support version: 3.0.0
-- Requires StdAir-0.35
-- Found StdAir version: 0.38.0
-- Requires Doxygen without specifying any version
-- Found Doxygen: /usr/bin/doxygen
-- Found DoxygenWrapper: /usr/bin/doxygen
```

```

-- Found Doxygen version: 1.7.4
-- Had to set the linker language for 'travelccmlib' to CXX
-- Test 'TravelChoiceTestSuite' to be built with 'TravelChoiceTestSuite.cpp'
--
-- =====
-- -----
-- ---      Project Information      ---
-- -----
-- PROJECT_NAME ..... : travelccm
-- PACKAGE_PRETTY_NAME ..... : TravelCCM
-- PACKAGE ..... : travelccm
-- PACKAGE_NAME ..... : TRAVELCCM
-- PACKAGE_BRIEF ..... : C++ Travel Customer Choice Model Library
-- PACKAGE_VERSION ..... : 99.99.99
-- GENERIC_LIB_VERSION ..... : 99.99.99
-- GENERIC_LIB_SOVERSION ..... : 99.99
--
-- -----
-- ---      Build Configuration      ---
-- -----
-- Modules to build ..... : travelccm
-- Libraries to build/install ..... : travelccmlib
-- Binaries to build/install ..... : travelccm
-- Modules to test ..... : travelccm
-- Binaries to test ..... : TravelChoiceTestSuitetst
--
-- * Module ..... : travelccm
--   + Layers to build ..... : .;basic;bom;factory;command;service
--   + Dependencies on other layers :
--   + Libraries to build/install . : travelccmlib
--   + Executables to build/install : travelccm
--   + Tests to perform ..... : TravelChoiceTestSuitetst
--
-- BUILD_SHARED_LIBS ..... : ON
-- CMAKE_BUILD_TYPE ..... : Debug
-- * CMAKE_C_FLAGS ..... :
-- * CMAKE_CXX_FLAGS ..... : -Wall -Werror
-- * BUILD_FLAGS ..... :
-- * COMPILE_FLAGS ..... :
-- CMAKE_MODULE_PATH ..... : /home/user/dev/sim/travelccm/travelccmgithub/config/
-- CMAKE_INSTALL_PREFIX ..... : /home/user/dev/deliveries/travelccm-99.99.99
--
-- * Doxygen:
--   - DOXYGEN_VERSION ..... : 1.7.4
--   - DOXYGEN_EXECUTABLE ..... : /usr/bin/doxygen
--   - DOXYGEN_DOT_EXECUTABLE ..... : /usr/bin/dot
--   - DOXYGEN_DOT_PATH ..... : /usr/bin
--
-- -----
-- ---      Installation Configuration      ---
-- -----
-- INSTALL_LIB_DIR ..... : /home/user/dev/deliveries/travelccm-99.99.99/lib64
-- INSTALL_BIN_DIR ..... : /home/user/dev/deliveries/travelccm-99.99.99/bin
-- INSTALL_INCLUDE_DIR ..... : /home/user/dev/deliveries/travelccm-99.99.99/include
-- INSTALL_DATA_DIR ..... : /home/user/dev/deliveries/travelccm-99.99.99/share
-- INSTALL_SAMPLE_DIR ..... : /home/user/dev/deliveries/travelccm-99.99.99/share/travelccm/samples
-- INSTALL_DOC ..... : ON
--
-- -----
-- ---      Packaging Configuration      ---
-- -----
-- CPACK_PACKAGE_CONTACT ..... : Denis Arnaud <denis_arnaud - at - users dot sourceforge dot net>
-- CPACK_PACKAGE_VENDOR ..... : Denis Arnaud
-- CPACK_PACKAGE_VERSION ..... : 99.99.99
-- CPACK_PACKAGE_DESCRIPTION_FILE . : /home/user/dev/sim/travelccm/travelccmgithub/README
-- CPACK_RESOURCE_FILE_LICENSE .... : /home/user/dev/sim/travelccm/travelccmgithub/COPYING
-- CPACK_GENERATOR ..... : TBZ2
-- CPACK_DEBIAN_PACKAGE_DEPENDS ... :
-- CPACK_SOURCE_GENERATOR ..... : TBZ2;TGZ
-- CPACK_SOURCE_PACKAGE_FILE_NAME . : travelccm-99.99.99
--
-- -----
-- ---      External libraries      ---

```

```

-- -----
--
-- * Boost:
--   - Boost_VERSION ..... : 104600
--   - Boost_LIB_VERSION ..... : 1_46
--   - Boost_HUMAN_VERSION ..... : 1.46.0
--   - Boost_INCLUDE_DIRS ..... : /usr/include
--   - Boost required components .. : regex;program_options;date_time;iostreams;serialization;filesystem;unit_
--   - Boost required libraries ... : optimized;/usr/lib64/libboost_regex-mt.so;debug;/usr/lib64/libboost_rege
--
-- * MySQL:
--   - MYSQL_VERSION ..... : 5.5.14
--   - MYSQL_INCLUDE_DIR ..... : /usr/include/mysql
--   - MYSQL_LIBRARIES ..... : /usr/lib64/mysql/libmysqlclient.so
--
-- * SOCI:
--   - SOCI_VERSION ..... : 3.0.0
--   - SOCI_INCLUDE_DIR ..... : /usr/include/soci
--   - SOCI_MYSQL_INCLUDE_DIR ..... : /usr/include/soci
--   - SOCI_LIBRARIES ..... : /usr/lib64/libsoci_core.so
--   - SOCI_MYSQL_LIBRARIES ..... : /usr/lib64/libsoci_mysql.so
--
-- * StdAir:
--   - STDAIR_VERSION ..... : 0.38.0
--   - STDAIR_BINARY_DIRS ..... : /home/user/dev/deliveries/stdair-0.38.0/bin
--   - STDAIR_EXECUTABLES ..... : stdair
--   - STDAIR_LIBRARY_DIRS ..... : /home/user/dev/deliveries/stdair-0.38.0/lib64
--   - STDAIR_LIBRARIES ..... : stdairlib;stdairuiclib
--   - STDAIR_INCLUDE_DIRS ..... : /home/user/dev/deliveries/stdair-0.38.0/include
--   - STDAIR_SAMPLE_DIR ..... : /home/user/dev/deliveries/stdair-0.38.0/share/stdair/samples
--
-- Change a value with: cmake -D<Variable>=<Value>
-- =====
--
-- Configuring done
-- Generating done
-- Build files have been written to: /home/user/dev/sim/travelccm/travelccmgithub/build

```

It is recommended that you check if your library has been compiled and linked properly and works as expected. To do so, you should execute the testing process 'make check'. As a result, you should obtain a similar report:

```

[ 0%] Built target hdr_cfg_travelccm
[ 88%] Built target travelccmlib
[100%] Built target TravelChoiceTestSuitetst
Scanning dependencies of target check_travelccmtst
Test project /home/user/dev/sim/travelccm/travelccmgithub/build/test/travelccm
  Start 1: TravelChoiceTestSuitetst
1/1 Test #1: TravelChoiceTestSuitetst ..... Passed    0.02 sec

100% tests passed, 0 tests failed out of 1

Total Test time (real) = 0.30 sec
[100%] Built target check_travelccmtst
Scanning dependencies of target check
[100%] Built target check

```

Check if all the executed tests PASSED. If not, please contact us by filling a [bug-report](#).

Finally, you should install the compiled and linked library, include files and (optionally) HTML and PDF documentation by typing:

```
make install
```

Depending on the PREFIX settings during configuration, you might need the root (administrator) access to perform this step.

Eventually, you might invoke the following command

```
make clean
```

to remove all files created during compilation process, or even

```
cd ~/dev/sim/travelccmgit
rm -rf build && mkdir build
cd build
```

to remove everything.

10 Linking with TravelCCM

10.1 Table of Contents

- [Introduction](#)
- [Dependencies](#)
- [Using the pkg-config command](#)
- [Using the travelccm-config script](#)
- [M4 macro for the GNU Autotools](#)
- [Using TravelCCM with dynamic linking](#)

10.2 Introduction

There are two convenient methods of linking your programs with the TravelCCM library. The first one employs the `'pkg-config'` command (see <http://pkgconfig.freedesktop.org/>), whereas the second one uses `'travelccm-config'` script. These methods are shortly described below.

10.3 Dependencies

The TravelCCM library depends on several other C++ components.

10.3.1 StdAir

Among them, as for now, only StdAir has been packaged. The support for StdAir is taken in charge by a dedicated M4 macro file (namely, `'stdair.m4'`), from the configuration script (generated thanks to `'configure.ac'`).




Figure 1: TravelCCM Dependencies

10.4 Using the pkg-config command

'pkg-config' is a helper tool used when compiling applications and libraries. It helps you insert the correct compiler and linker options. The syntax of the 'pkg-config' is as follows:

```
pkg-config <options> <library_name>
```

For instance, assuming that you need to compile an TravelCCM based program 'my_prog.cpp', you should use the following command:

```
g++ `pkg-config --cflags travelccm` -o my_prog my_prog.cpp `pkg-config --libs travelccm`
```

For more information see the 'pkg-config' man pages.

10.5 Using the travelccm-config script

TravelCCM provides a shell script called `travelccm-config`, which is installed by default in '\$prefix/bin' ('/usr/local/bin') directory. It can be used to simplify compilation and linking of TravelCCM based programs. The usage of this script is quite similar to the usage of the 'pkg-config' command.

Assuming that you need to compile the program 'my_prog.cpp' you can now do that with the following command:

```
g++ `travelccm-config --cflags` -o my_prog_opt my_prog.cpp `travelccm-config --libs`
```

A list of 'travelccm-config' options can be obtained by typing:

```
travelccm-config --help
```

If the 'travelccm-config' command is not found by your shell, you should add its location '\$prefix/bin' to the PATH environment variable, e.g.:

```
export PATH=/usr/local/bin:$PATH
```

10.6 M4 macro for the GNU Autotools

A M4 macro file is delivered with TravelCCM, namely 'travelccm.m4', which can be found in, e.g., '/usr/share/aclocal'. When used by a 'configure' script, thanks to the 'AM_PATH_TravelCCM' macro (specified in the M4 macro file), the following Makefile variables are then defined:

- 'TravelCCM_VERSION' (e.g., defined to 0.23.0)
- 'TravelCCM_CFLAGS' (e.g., defined to '-I\${prefix}/include')
- 'TravelCCM_LIBS' (e.g., defined to '-L\${prefix}/lib -ltravelccm')

10.7 Using TravelCCM with dynamic linking

When using static linking some of the library routines in TravelCCM are copied into your executable program. This can lead to unnecessary large executables. To avoid having too large executable files you may use dynamic linking instead. Dynamic linking means that the actual linking is performed when the program is executed. This requires that the system is able to locate the shared TravelCCM library file during your program execution. If you install the TravelCCM library using a non-standard prefix, the 'LD_LIBRARY_PATH' environment variable might be used to inform the linker of the dynamic library location, e.g.:

```
export LD_LIBRARY_PATH=<TravelCCM installation prefix>/lib:$LD_LIBRARY_PATH
```

11 Test Rules

This section describes rules how the functionality of the IT++ library should be verified. In the 'tests' subdirectory test files are provided. All functionality should be tested using these test files.

11.1 The Test File

Each new IT++ module/class should be accompanied with a test file. The test file is an implementation in C++ that tests the functionality of a function/class or a group of functions/classes called modules. The test file should test relevant parameter settings and input/output relations to guarantee correct functionality of the corresponding classes/functions. The test files should be maintained using version control and updated whenever new functionality is added to the IT++ library.

The test file should print relevant data to a standard output that can be used to verify the functionality. All relevant parameter settings should be tested.

The test file should be placed in the 'tests' subdirectory and should have a name ending with '_test.cpp'.

11.2 The Reference File

Consider a test file named 'module_test.cpp'. A reference file named 'module_test.ref' should accompany the test file. The reference file contains a reference printout of the standard output generated when running the test program. The reference file should be maintained using version control and updated according to the test file.

11.3 Testing IT++ Library

One can compile and execute all test programs from 'tests' subdirectory by typing

```
% make check
```

after successful compilation of the IT++ library.

12 Users Guide

12.1 Table of Contents

- [Introduction](#)
- [Get Started](#)
 - [Get the TravelCCM library](#)
 - [Build the TravelCCM project](#)
 - [Build and Run the Tests](#)
 - [Install the TravelCCM Project \(Binaries, Documentation\)](#)
- [Input file of TravelCCM Project](#)
- [The schedule BOM Tree](#)
 - [Build of the schedule BOM tree](#)
 - [Display of the schedule BOM tree](#)
- [Exploring the Predefined BOM Tree](#)
 - [Airline Network BOM Tree](#)
 - [Airline Schedule BOM Tree](#)
- [Extending the BOM Tree](#)
- [The travel solution calculation procedure](#)

12.2 Introduction

The `TravelCCM` library contains classes for airline business management. This document does not cover all the aspects of the `TravelCCM` library. It does however explain the most important things you need to know in order to start using `TravelCCM`.

12.3 Get Started

12.3.1 Get the TravelCCM library

Clone locally the full [Git project](#):

```
cd ~
mkdir -p dev/sim
cd ~/dev/sim
git clone git://travel-ccm.git.sourceforge.net/gitroot/travel-ccm/travel-ccm travelccmgit
cd travelccmgit
git checkout trunk
```

12.3.2 Build the TravelCCM project

Link with `StdAir`, create the distribution package (say, 0.5.0) and compile using the following commands:

```
cd ~/dev/sim/travelccmgit
rm -rf build && mkdir -p build
cd build
cmake -DCMAKE_INSTALL_PREFIX=~/dev/deliveries/travelccm-0.5.0 \
-DWITH_STDAIR_PREFIX=~/dev/deliveries/stdair-stable \
-DMAKE_BUILD_TYPE:STRING=Debug -DINSTALL_DOC:BOOL=ON ..
make
```

12.3.3 Build and Run the Tests

After building the TravelCCM project, the following commands run the tests:

```
cd ~/dev/sim/travelccmgit
cd build
make check
```

As a result, you should obtain a similar report:

```
[ 0%] Built target hdr_cfg_travelccm
[ 96%] Built target travelccmlib
[100%] Built target AirlineScheduleTestSuitetst
Scanning dependencies of target check_travelccmtst
Test project /home/user/dev/sim/travelccm/travelccmgithub/build/test/travelccm
  Start 1: AirlineScheduleTestSuitetst
1/1 Test #1: AirlineScheduleTestSuitetst ..... Passed    0.15 sec

100% tests passed, 0 tests failed out of 1

Total Test time (real) = 0.40 sec
[100%] Built target check_travelccmtst
Scanning dependencies of target check
[100%] Built target check
```

12.3.4 Install the TravelCCM Project (Binaries, Documentation)

After the step [Build the TravelCCM project](#), to install the library and its header files, type:

```
cd ~/dev/sim/travelccmgit
cd build
make install
```

You can check that the executables and other required files have been copied into the given final directory:

```
cd ~/dev/deliveries/travelccm-0.5.0
```

To generate the TravelCCM project documentation, the commands are:

```
cd ~/dev/sim/travelccmgit
cd build
make doc
```

The TravelCCM project documentation is available in the following formats: HTML, LaTeX. Those documents are available in a subdirectory:

```
cd ~/dev/sim/travelccmgit
cd build
cd doc
```

12.4 Input file of TravelCCM Project

The schedule input file structure should look like the following sample:

Each line, beyond the header, represents a schedule entry, i.e., the specification of a given flight-period (see `TRAVELCCM::FlightPeriodStruct`). The fields are as follows:

- Flights section

- AirlineCode (e.g., BA)
- FlightNumber (e.g., 9)
- Start of the flight departure period (e.g., 2007-04-20)
- End of the flight departure period (e.g., 2007-06-30)
- Day-Of-the-Week for the flight departure period (DOW) (e.g., 0000011)
- Leg section
- Segment section
- Leg section
 - BoardPoint (e.g., LHR)
 - OffPoint (e.g., BKK)
 - BoardTime (e.g., 22:00)
 - ArrivalTime (e.g., 15:15)
 - ArrivalDateOffset (e.g., +1)
 - ElapsedTime (e.g., 11:15)
 - Leg-cabin section
- Leg-cabin section
 - Cabin code (e.g., F, J, W or Y)
 - Capacity (e.g., respectively 5, 12, 20 or 300)
- Segment section
 - Specificity flag:
 - * 0 means that all the segments behave the same way, i.e., have got the same dressing (distribution and order of the booking classes per cabin)
 - * 1 means that each segment behave differently. The full specification of each of those segments must therefore be given.
 - Segment-cabin section
 - Fare family section
- Segment-cabin section
 - Cabin code (e.g., F, J, W or Y)
 - List of (one-letter-code) booking classes for the cabin (e.g, respectively FA, JC DI, WT or YBHKMLSQ)
- Fare family section
 - Fare family code (e.g., 1)
 - List of (one-letter-code) booking classes for the fare family (e.g, respectively FA, JC DI, WT or YBHKMLSQ)

Some fare input examples (including the example above named `schedule03.csv`) are given in the `StdAir project`.

12.5 The schedule BOM Tree

The schedule-related Business Object Model (BOM) tree is a structure allowing to store all the `TRAVELCCM: : - FlightPeriodStruct` objects of the simulation. That is why parsing an input file, containing the specification for all the flight-periods, is more convenient (

See Also

the previous section [Input file of TravelCCM Project](#)).

As it may be time consuming, and it for sure requires some know-how, to first build such a schedule input file, a small sample BOM tree is provided by default when needed.

12.5.1 Build of the schedule BOM tree

First, a BOM root object (i.e., a root for all the classes in the project) is instantiated by the `stdair::STDAIR_ServiceContext` context object, when the `stdair::STDAIR_Service` is itself instantiated (during the instantiation of the `TRAVELCCM::TRAVELCCM_Service` object).

The corresponding type (class) `stdair::BomRoot` is defined in the `StdAir` library.

Then, the BOM root can be either constructed thanks to the `TRAVELCCM::TRAVELCCM_Service::buildSampleBom()` method:

```
void buildSampleBom();
```

or can be constructed using the schedule input file described above thanks to the `TRAVELCCM::TRAVELCCM_Service::parseAndLoad (const stdair::Filename_T&)` method:

12.5.2 Display of the schedule BOM tree

Note

That feature (of BOM tree display) has not been implemented yet. Do not hesitate to [open a ticket](#) if you would like to have it implemented more quickly.

The schedule BOM tree can be displayed as done in the `batches::travelccm.cpp` program:

When the default BOM tree is used (`-b/-builtin` option of the main program `travelccm.cpp`), the schedule BOM tree display (for now, corresponding to `schedule01.csv` parsed by `TRAVELCCM::travelccm`) should look like:

```
=====
BomRoot:  -- ROOT --
=====
+++++
Inventory: SQ
+++++
*****
FlightDate: SQ11, 2010-Jan-15
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
          Elapsed, Distance, Capacity,
SQ11 2010-Jan-15, SIN-BKK, 2010-Jan-15, 08:20:00, 2010-Jan-15, 11:00:00, 07:40:
          00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
          CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-15, SIN-BKK 2010-Jan-15, Y, 300, 300, 0, 0, 0, 0, 0, 0, 2, 298
          , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-15, SIN-BKK 2010-Jan-15, Y, 1, 0, 0, 0, 2, 298, 0,
SQ11 2010-Jan-15, SIN-BKK 2010-Jan-15, Y, 2, 0, 0, 0, 2, 298, 0,
*****
```

```
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
    GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-15, SIN-BKK 2010-Jan-15, Y, 1, Y, 300 (0), 0, 0, 0, 2, 0 (0), 0,
    0, 0, 0, 0, 0,
SQ11 2010-Jan-15, SIN-BKK 2010-Jan-15, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-16
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
    Elapsed, Distance, Capacity,
SQ11 2010-Jan-16, SIN-BKK, 2010-Jan-16, 08:20:00, 2010-Jan-16, 11:00:00, 07:40:
    00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
    CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-16, SIN-BKK 2010-Jan-16, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
    , 9, 1.83244e-319, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-16, SIN-BKK 2010-Jan-16, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-16, SIN-BKK 2010-Jan-16, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
    GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-16, SIN-BKK 2010-Jan-16, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
SQ11 2010-Jan-16, SIN-BKK 2010-Jan-16, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-17
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
    Elapsed, Distance, Capacity,
SQ11 2010-Jan-17, SIN-BKK, 2010-Jan-17, 08:20:00, 2010-Jan-17, 11:00:00, 07:40:
    00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
    CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-17, SIN-BKK 2010-Jan-17, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
    , 9, 1.58896e-319, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-17, SIN-BKK 2010-Jan-17, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-17, SIN-BKK 2010-Jan-17, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
    GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
```

```

SQ11 2010-Jan-17, SIN-BKK 2010-Jan-17, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Jan-17, SIN-BKK 2010-Jan-17, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-18
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Jan-18, SIN-BKK, 2010-Jan-18, 08:20:00, 2010-Jan-18, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-18, SIN-BKK 2010-Jan-18, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-18, SIN-BKK 2010-Jan-18, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-18, SIN-BKK 2010-Jan-18, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-18, SIN-BKK 2010-Jan-18, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Jan-18, SIN-BKK 2010-Jan-18, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-19
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Jan-19, SIN-BKK, 2010-Jan-19, 08:20:00, 2010-Jan-19, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-19, SIN-BKK 2010-Jan-19, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-19, SIN-BKK 2010-Jan-19, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-19, SIN-BKK 2010-Jan-19, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-19, SIN-BKK 2010-Jan-19, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Jan-19, SIN-BKK 2010-Jan-19, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****

```



```

*****
FlightDate: SQ11, 2010-Jan-20
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Jan-20, SIN-BKK, 2010-Jan-20, 08:20:00, 2010-Jan-20, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-20, SIN-BKK 2010-Jan-20, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-20, SIN-BKK 2010-Jan-20, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-20, SIN-BKK 2010-Jan-20, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-20, SIN-BKK 2010-Jan-20, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Jan-20, SIN-BKK 2010-Jan-20, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-21
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Jan-21, SIN-BKK, 2010-Jan-21, 08:20:00, 2010-Jan-21, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-21, SIN-BKK 2010-Jan-21, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-21, SIN-BKK 2010-Jan-21, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Jan-21, SIN-BKK 2010-Jan-21, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-22
*****
*****
Leg-Dates:

```

```
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Jan-22, SIN-BKK, 2010-Jan-22, 08:20:00, 2010-Jan-22, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-22, SIN-BKK 2010-Jan-22, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-22, SIN-BKK 2010-Jan-22, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-22, SIN-BKK 2010-Jan-22, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-22, SIN-BKK 2010-Jan-22, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Jan-22, SIN-BKK 2010-Jan-22, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-23
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Jan-23, SIN-BKK, 2010-Jan-23, 08:20:00, 2010-Jan-23, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-23, SIN-BKK 2010-Jan-23, Y, 300, 300, 0, 0, 0, 0, 0, 6.64029e-
319, 0, 300, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-23, SIN-BKK 2010-Jan-23, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-23, SIN-BKK 2010-Jan-23, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-23, SIN-BKK 2010-Jan-23, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Jan-23, SIN-BKK 2010-Jan-23, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-24
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Jan-24, SIN-BKK, 2010-Jan-24, 08:20:00, 2010-Jan-24, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
```

```
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-24, SIN-BKK 2010-Jan-24, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-24, SIN-BKK 2010-Jan-24, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-24, SIN-BKK 2010-Jan-24, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-24, SIN-BKK 2010-Jan-24, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Jan-24, SIN-BKK 2010-Jan-24, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-25
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Jan-25, SIN-BKK, 2010-Jan-25, 08:20:00, 2010-Jan-25, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-25, SIN-BKK 2010-Jan-25, Y, 300, 300, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-25, SIN-BKK 2010-Jan-25, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-25, SIN-BKK 2010-Jan-25, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-25, SIN-BKK 2010-Jan-25, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Jan-25, SIN-BKK 2010-Jan-25, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-26
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Jan-26, SIN-BKK, 2010-Jan-26, 08:20:00, 2010-Jan-26, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
```

```
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-26, SIN-BKK 2010-Jan-26, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-26, SIN-BKK 2010-Jan-26, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-26, SIN-BKK 2010-Jan-26, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-26, SIN-BKK 2010-Jan-26, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Jan-26, SIN-BKK 2010-Jan-26, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-27
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Jan-27, SIN-BKK, 2010-Jan-27, 08:20:00, 2010-Jan-27, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-27, SIN-BKK 2010-Jan-27, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-27, SIN-BKK 2010-Jan-27, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-27, SIN-BKK 2010-Jan-27, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-27, SIN-BKK 2010-Jan-27, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Jan-27, SIN-BKK 2010-Jan-27, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-28
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Jan-28, SIN-BKK, 2010-Jan-28, 08:20:00, 2010-Jan-28, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-28, SIN-BKK 2010-Jan-28, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
```

```
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-28, SIN-BKK 2010-Jan-28, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-28, SIN-BKK 2010-Jan-28, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-28, SIN-BKK 2010-Jan-28, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQ11 2010-Jan-28, SIN-BKK 2010-Jan-28, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-29
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
  Elapsed, Distance, Capacity,
SQ11 2010-Jan-29, SIN-BKK, 2010-Jan-29, 08:20:00, 2010-Jan-29, 11:00:00, 07:40:
  00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
  CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-29, SIN-BKK 2010-Jan-29, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
  , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-29, SIN-BKK 2010-Jan-29, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-29, SIN-BKK 2010-Jan-29, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-29, SIN-BKK 2010-Jan-29, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQ11 2010-Jan-29, SIN-BKK 2010-Jan-29, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-30
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
  Elapsed, Distance, Capacity,
SQ11 2010-Jan-30, SIN-BKK, 2010-Jan-30, 08:20:00, 2010-Jan-30, 11:00:00, 07:40:
  00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
  CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-30, SIN-BKK 2010-Jan-30, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
  , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
```

```
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-30, SIN-BKK 2010-Jan-30, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-30, SIN-BKK 2010-Jan-30, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-30, SIN-BKK 2010-Jan-30, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ11 2010-Jan-30, SIN-BKK 2010-Jan-30, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Jan-31
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ11 2010-Jan-31, SIN-BKK, 2010-Jan-31, 08:20:00, 2010-Jan-31, 11:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Jan-31, SIN-BKK 2010-Jan-31, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Jan-31, SIN-BKK 2010-Jan-31, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Jan-31, SIN-BKK 2010-Jan-31, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Jan-31, SIN-BKK 2010-Jan-31, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ11 2010-Jan-31, SIN-BKK 2010-Jan-31, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-01
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ11 2010-Feb-01, SIN-BKK, 2010-Feb-01, 08:20:00, 2010-Feb-01, 11:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-01, SIN-BKK 2010-Feb-01, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-01, SIN-BKK 2010-Feb-01, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-01, SIN-BKK 2010-Feb-01, Y, 2, 0, 0, 0, 0, 300, 0,
```

```

*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
    GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-01, SIN-BKK 2010-Feb-01, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
SQ11 2010-Feb-01, SIN-BKK 2010-Feb-01, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-02
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
    Elapsed, Distance, Capacity,
SQ11 2010-Feb-02, SIN-BKK, 2010-Feb-02, 08:20:00, 2010-Feb-02, 11:00:00, 07:40:
    00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
    CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-02, SIN-BKK 2010-Feb-02, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
    , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-02, SIN-BKK 2010-Feb-02, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-02, SIN-BKK 2010-Feb-02, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
    GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-02, SIN-BKK 2010-Feb-02, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
SQ11 2010-Feb-02, SIN-BKK 2010-Feb-02, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-03
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
    Elapsed, Distance, Capacity,
SQ11 2010-Feb-03, SIN-BKK, 2010-Feb-03, 08:20:00, 2010-Feb-03, 11:00:00, 07:40:
    00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
    CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-03, SIN-BKK 2010-Feb-03, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
    , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-03, SIN-BKK 2010-Feb-03, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-03, SIN-BKK 2010-Feb-03, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,

```

```

      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-03, SIN-BKK 2010-Feb-03, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ11 2010-Feb-03, SIN-BKK 2010-Feb-03, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-04
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ11 2010-Feb-04, SIN-BKK, 2010-Feb-04, 08:20:00, 2010-Feb-04, 11:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-04, SIN-BKK 2010-Feb-04, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-04, SIN-BKK 2010-Feb-04, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-04, SIN-BKK 2010-Feb-04, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-04, SIN-BKK 2010-Feb-04, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ11 2010-Feb-04, SIN-BKK 2010-Feb-04, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-05
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ11 2010-Feb-05, SIN-BKK, 2010-Feb-05, 08:20:00, 2010-Feb-05, 11:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-05, SIN-BKK 2010-Feb-05, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-05, SIN-BKK 2010-Feb-05, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ11 2010-Feb-05, SIN-BKK 2010-Feb-05, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****

```



```
*****
*****
FlightDate: SQ11, 2010-Feb-06
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-06, SIN-BKK, 2010-Feb-06, 08:20:00, 2010-Feb-06, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-06, SIN-BKK 2010-Feb-06, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-06, SIN-BKK 2010-Feb-06, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-06, SIN-BKK 2010-Feb-06, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-06, SIN-BKK 2010-Feb-06, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Feb-06, SIN-BKK 2010-Feb-06, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-07
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-07, SIN-BKK, 2010-Feb-07, 08:20:00, 2010-Feb-07, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-07, SIN-BKK 2010-Feb-07, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-07, SIN-BKK 2010-Feb-07, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-07, SIN-BKK 2010-Feb-07, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-07, SIN-BKK 2010-Feb-07, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Feb-07, SIN-BKK 2010-Feb-07, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-08
*****
*****
```

```
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-08, SIN-BKK, 2010-Feb-08, 08:20:00, 2010-Feb-08, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-08, SIN-BKK 2010-Feb-08, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-08, SIN-BKK 2010-Feb-08, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-08, SIN-BKK 2010-Feb-08, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-08, SIN-BKK 2010-Feb-08, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Feb-08, SIN-BKK 2010-Feb-08, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-09
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-09, SIN-BKK, 2010-Feb-09, 08:20:00, 2010-Feb-09, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-09, SIN-BKK 2010-Feb-09, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-09, SIN-BKK 2010-Feb-09, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-09, SIN-BKK 2010-Feb-09, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-09, SIN-BKK 2010-Feb-09, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Feb-09, SIN-BKK 2010-Feb-09, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-10
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-10, SIN-BKK, 2010-Feb-10, 08:20:00, 2010-Feb-10, 11:00:00, 07:40:
```

```

00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-10, SIN-BKK 2010-Feb-10, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-10, SIN-BKK 2010-Feb-10, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-10, SIN-BKK 2010-Feb-10, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-10, SIN-BKK 2010-Feb-10, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Feb-10, SIN-BKK 2010-Feb-10, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-11
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-11, SIN-BKK 2010-Feb-11, 08:20:00, 2010-Feb-11, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-11, SIN-BKK 2010-Feb-11, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-11, SIN-BKK 2010-Feb-11, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-11, SIN-BKK 2010-Feb-11, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-11, SIN-BKK 2010-Feb-11, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Feb-11, SIN-BKK 2010-Feb-11, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-12
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-12, SIN-BKK 2010-Feb-12, 08:20:00, 2010-Feb-12, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----

```

```
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-12, SIN-BKK 2010-Feb-12, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-12, SIN-BKK 2010-Feb-12, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-12, SIN-BKK 2010-Feb-12, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-12, SIN-BKK 2010-Feb-12, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Feb-12, SIN-BKK 2010-Feb-12, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-13
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-13, SIN-BKK, 2010-Feb-13, 08:20:00, 2010-Feb-13, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-13, SIN-BKK 2010-Feb-13, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-13, SIN-BKK 2010-Feb-13, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-13, SIN-BKK 2010-Feb-13, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-13, SIN-BKK 2010-Feb-13, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Feb-13, SIN-BKK 2010-Feb-13, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-14
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-14, SIN-BKK, 2010-Feb-14, 08:20:00, 2010-Feb-14, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-14, SIN-BKK 2010-Feb-14, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
```

```
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQL1 2010-Feb-14, SIN-BKK 2010-Feb-14, Y, 1, 0, 0, 0, 0, 300, 0,
SQL1 2010-Feb-14, SIN-BKK 2010-Feb-14, Y, 2, 0, 0, 0, 0, 300, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQL1 2010-Feb-14, SIN-BKK 2010-Feb-14, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQL1 2010-Feb-14, SIN-BKK 2010-Feb-14, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQL1, 2010-Feb-15
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQL1 2010-Feb-15, SIN-BKK, 2010-Feb-15, 08:20:00, 2010-Feb-15, 11:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQL1 2010-Feb-15, SIN-BKK 2010-Feb-15, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQL1 2010-Feb-15, SIN-BKK 2010-Feb-15, Y, 1, 0, 0, 0, 0, 300, 0,
SQL1 2010-Feb-15, SIN-BKK 2010-Feb-15, Y, 2, 0, 0, 0, 0, 300, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQL1 2010-Feb-15, SIN-BKK 2010-Feb-15, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQL1 2010-Feb-15, SIN-BKK 2010-Feb-15, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQL1, 2010-Feb-16
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQL1 2010-Feb-16, SIN-BKK, 2010-Feb-16, 08:20:00, 2010-Feb-16, 11:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQL1 2010-Feb-16, SIN-BKK 2010-Feb-16, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
```

```

*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-16, SIN-BKK 2010-Feb-16, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-16, SIN-BKK 2010-Feb-16, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-16, SIN-BKK 2010-Feb-16, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ11 2010-Feb-16, SIN-BKK 2010-Feb-16, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-17
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ11 2010-Feb-17, SIN-BKK, 2010-Feb-17, 08:20:00, 2010-Feb-17, 11:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-17, SIN-BKK 2010-Feb-17, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-17, SIN-BKK 2010-Feb-17, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-17, SIN-BKK 2010-Feb-17, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-17, SIN-BKK 2010-Feb-17, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ11 2010-Feb-17, SIN-BKK 2010-Feb-17, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-18
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ11 2010-Feb-18, SIN-BKK, 2010-Feb-18, 08:20:00, 2010-Feb-18, 11:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-18, SIN-BKK 2010-Feb-18, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-18, SIN-BKK 2010-Feb-18, Y, 1, 0, 0, 0, 0, 300, 0,

```

```
SQL1 2010-Feb-18, SIN-BKK 2010-Feb-18, Y, 2, 0, 0, 0, 0, 300, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQL1 2010-Feb-18, SIN-BKK 2010-Feb-18, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQL1 2010-Feb-18, SIN-BKK 2010-Feb-18, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
*****
*****
FlightDate: SQL1, 2010-Feb-19
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
  Elapsed, Distance, Capacity,
SQL1 2010-Feb-19, SIN-BKK 2010-Feb-19, 08:20:00, 2010-Feb-19, 11:00:00, 07:40:
  00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
  CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQL1 2010-Feb-19, SIN-BKK 2010-Feb-19, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
  , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQL1 2010-Feb-19, SIN-BKK 2010-Feb-19, Y, 1, 0, 0, 0, 0, 300, 0,
SQL1 2010-Feb-19, SIN-BKK 2010-Feb-19, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQL1 2010-Feb-19, SIN-BKK 2010-Feb-19, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQL1 2010-Feb-19, SIN-BKK 2010-Feb-19, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
*****
*****
FlightDate: SQL1, 2010-Feb-20
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
  Elapsed, Distance, Capacity,
SQL1 2010-Feb-20, SIN-BKK 2010-Feb-20, 08:20:00, 2010-Feb-20, 11:00:00, 07:40:
  00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
  CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQL1 2010-Feb-20, SIN-BKK 2010-Feb-20, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
  , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQL1 2010-Feb-20, SIN-BKK 2010-Feb-20, Y, 1, 0, 0, 0, 0, 300, 0,
SQL1 2010-Feb-20, SIN-BKK 2010-Feb-20, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
```

```
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-20, SIN-BKK 2010-Feb-20, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQ11 2010-Feb-20, SIN-BKK 2010-Feb-20, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-21
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
  Elapsed, Distance, Capacity,
SQ11 2010-Feb-21, SIN-BKK, 2010-Feb-21, 08:20:00, 2010-Feb-21, 11:00:00, 07:40:
  00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
  CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-21, SIN-BKK 2010-Feb-21, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
  , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-21, SIN-BKK 2010-Feb-21, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-21, SIN-BKK 2010-Feb-21, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-21, SIN-BKK 2010-Feb-21, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQ11 2010-Feb-21, SIN-BKK 2010-Feb-21, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-22
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
  Elapsed, Distance, Capacity,
SQ11 2010-Feb-22, SIN-BKK, 2010-Feb-22, 08:20:00, 2010-Feb-22, 11:00:00, 07:40:
  00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
  CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-22, SIN-BKK 2010-Feb-22, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
  , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-22, SIN-BKK 2010-Feb-22, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-22, SIN-BKK 2010-Feb-22, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-22, SIN-BKK 2010-Feb-22, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQ11 2010-Feb-22, SIN-BKK 2010-Feb-22, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
```



```

0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-23
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-23, SIN-BKK, 2010-Feb-23, 08:20:00, 2010-Feb-23, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-23, SIN-BKK 2010-Feb-23, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-23, SIN-BKK 2010-Feb-23, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-23, SIN-BKK 2010-Feb-23, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-23, SIN-BKK 2010-Feb-23, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Feb-23, SIN-BKK 2010-Feb-23, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-24
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-24, SIN-BKK, 2010-Feb-24, 08:20:00, 2010-Feb-24, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-24, SIN-BKK 2010-Feb-24, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-24, SIN-BKK 2010-Feb-24, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-24, SIN-BKK 2010-Feb-24, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-24, SIN-BKK 2010-Feb-24, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Feb-24, SIN-BKK 2010-Feb-24, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-25
*****
*****

```

```
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-25, SIN-BKK, 2010-Feb-25, 08:20:00, 2010-Feb-25, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-25, SIN-BKK 2010-Feb-25, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-25, SIN-BKK 2010-Feb-25, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-25, SIN-BKK 2010-Feb-25, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-25, SIN-BKK 2010-Feb-25, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Feb-25, SIN-BKK 2010-Feb-25, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-26
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ11 2010-Feb-26, SIN-BKK, 2010-Feb-26, 08:20:00, 2010-Feb-26, 11:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-26, SIN-BKK 2010-Feb-26, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 0, 300
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-26, SIN-BKK 2010-Feb-26, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-26, SIN-BKK 2010-Feb-26, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-26, SIN-BKK 2010-Feb-26, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ11 2010-Feb-26, SIN-BKK 2010-Feb-26, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-27
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
```

```

SQ11 2010-Feb-27, SIN-BKK, 2010-Feb-27, 08:20:00, 2010-Feb-27, 11:00:00, 07:40:
    00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
    CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-27, SIN-BKK 2010-Feb-27, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
    , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-27, SIN-BKK 2010-Feb-27, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-27, SIN-BKK 2010-Feb-27, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
    GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-27, SIN-BKK 2010-Feb-27, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
SQ11 2010-Feb-27, SIN-BKK 2010-Feb-27, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ11, 2010-Feb-28
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
    Elapsed, Distance, Capacity,
SQ11 2010-Feb-28, SIN-BKK, 2010-Feb-28, 08:20:00, 2010-Feb-28, 11:00:00, 07:40:
    00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
    CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ11 2010-Feb-28, SIN-BKK 2010-Feb-28, Y, 300, 300, 0, 0, 0, 0, 0, 0, 0, 300
    , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ11 2010-Feb-28, SIN-BKK 2010-Feb-28, Y, 1, 0, 0, 0, 0, 300, 0,
SQ11 2010-Feb-28, SIN-BKK 2010-Feb-28, Y, 2, 0, 0, 0, 0, 300, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
    GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ11 2010-Feb-28, SIN-BKK 2010-Feb-28, Y, 1, Y, 300 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
SQ11 2010-Feb-28, SIN-BKK 2010-Feb-28, Y, 2, M, 300 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Jan-15
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
    Elapsed, Distance, Capacity,
SQ12 2010-Jan-15, SIN-HND, 2010-Jan-15, 09:20:00, 2010-Jan-15, 12:00:00, 07:40:
    00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:

```

```

-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-15, SIN-HND 2010-Jan-15, Y, 200, 200, 2.082e+121, 5.53287e-48, 5.
20268e-90, 0, 1.31346e-47, 1.05119e-153, 2.78986e+179, 0, 200, 9, 3.66962e-62, 1
.0854e-71, 6.74783e-67, 6.9835e-77, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-15, SIN-HND 2010-Jan-15, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-15, SIN-HND 2010-Jan-15, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-15, SIN-HND 2010-Jan-15, Y, 1, Y13856, 200 (0), 0, 0, 0, 0, 0 (0)
, 0, 0, 0, 0, 0, 0,
SQ12 2010-Jan-15, SIN-HND 2010-Jan-15, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Jan-16
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Jan-16, SIN-HND, 2010-Jan-16, 09:20:00, 2010-Jan-16, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-16, SIN-HND 2010-Jan-16, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 2.63638e-319, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-16, SIN-HND 2010-Jan-16, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-16, SIN-HND 2010-Jan-16, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-16, SIN-HND 2010-Jan-16, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Jan-16, SIN-HND 2010-Jan-16, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Jan-17
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Jan-17, SIN-HND, 2010-Jan-17, 09:20:00, 2010-Jan-17, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-17, SIN-HND 2010-Jan-17, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200

```

```

, 9, 2.39291e-319, 0, 0, 0, 0,
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-17, SIN-HND 2010-Jan-17, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-17, SIN-HND 2010-Jan-17, Y, 2, 0, 0, 0, 0, 200, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-17, SIN-HND 2010-Jan-17, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQ12 2010-Jan-17, SIN-HND 2010-Jan-17, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
*****
FlightDate: SQ12, 2010-Jan-18
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
  Elapsed, Distance, Capacity,
SQ12 2010-Jan-18, SIN-HND, 2010-Jan-18, 09:20:00, 2010-Jan-18, 12:00:00, 07:40:
  00, 0, -05:00:00, 6300, 0,
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
  CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-18, SIN-HND 2010-Jan-18, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
  , 9, 2.14469e-319, 0, 0, 0, 0,
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-18, SIN-HND 2010-Jan-18, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-18, SIN-HND 2010-Jan-18, Y, 2, 0, 0, 0, 0, 200, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-18, SIN-HND 2010-Jan-18, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQ12 2010-Jan-18, SIN-HND 2010-Jan-18, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
*****
FlightDate: SQ12, 2010-Jan-19
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
  Elapsed, Distance, Capacity,
SQ12 2010-Jan-19, SIN-HND, 2010-Jan-19, 09:20:00, 2010-Jan-19, 12:00:00, 07:40:
  00, 0, -05:00:00, 6300, 0,
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
  CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-19, SIN-HND 2010-Jan-19, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
  , 9, 0, 0, 0, 0, 0,
*****
Buckets:
-----

```

```
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-19, SIN-HND 2010-Jan-19, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-19, SIN-HND 2010-Jan-19, Y, 2, 0, 0, 0, 0, 200, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-19, SIN-HND 2010-Jan-19, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ12 2010-Jan-19, SIN-HND 2010-Jan-19, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
FlightDate: SQ12, 2010-Jan-20
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ12 2010-Jan-20, SIN-HND, 2010-Jan-20, 09:20:00, 2010-Jan-20, 12:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-20, SIN-HND 2010-Jan-20, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
      , 9, 0, 0, 0, 0, 0,
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-20, SIN-HND 2010-Jan-20, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-20, SIN-HND 2010-Jan-20, Y, 2, 0, 0, 0, 0, 200, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-20, SIN-HND 2010-Jan-20, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ12 2010-Jan-20, SIN-HND 2010-Jan-20, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
FlightDate: SQ12, 2010-Jan-21
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ12 2010-Jan-21, SIN-HND, 2010-Jan-21, 09:20:00, 2010-Jan-21, 12:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-21, SIN-HND 2010-Jan-21, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
      , 9, 0, 0, 0, 0, 0,
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
```

```
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-21, SIN-HND 2010-Jan-21, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-21, SIN-HND 2010-Jan-21, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-21, SIN-HND 2010-Jan-21, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ12 2010-Jan-21, SIN-HND 2010-Jan-21, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Jan-22
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ12 2010-Jan-22, SIN-HND, 2010-Jan-22, 09:20:00, 2010-Jan-22, 12:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-22, SIN-HND 2010-Jan-22, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-22, SIN-HND 2010-Jan-22, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-22, SIN-HND 2010-Jan-22, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-22, SIN-HND 2010-Jan-22, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ12 2010-Jan-22, SIN-HND 2010-Jan-22, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Jan-23
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ12 2010-Jan-23, SIN-HND, 2010-Jan-23, 09:20:00, 2010-Jan-23, 12:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-23, SIN-HND 2010-Jan-23, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-23, SIN-HND 2010-Jan-23, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-23, SIN-HND 2010-Jan-23, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
```

```
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-23, SIN-HND 2010-Jan-23, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQ12 2010-Jan-23, SIN-HND 2010-Jan-23, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Jan-24
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
  Elapsed, Distance, Capacity,
SQ12 2010-Jan-24, SIN-HND, 2010-Jan-24, 09:20:00, 2010-Jan-24, 12:00:00, 07:40:
  00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
  CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-24, SIN-HND 2010-Jan-24, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
  , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-24, SIN-HND 2010-Jan-24, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-24, SIN-HND 2010-Jan-24, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-24, SIN-HND 2010-Jan-24, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQ12 2010-Jan-24, SIN-HND 2010-Jan-24, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Jan-25
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
  Elapsed, Distance, Capacity,
SQ12 2010-Jan-25, SIN-HND, 2010-Jan-25, 09:20:00, 2010-Jan-25, 12:00:00, 07:40:
  00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
  CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-25, SIN-HND 2010-Jan-25, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
  , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-25, SIN-HND 2010-Jan-25, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-25, SIN-HND 2010-Jan-25, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-25, SIN-HND 2010-Jan-25, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
```



```

0, 0, 0, 0, 0,
SQ12 2010-Jan-25, SIN-HND 2010-Jan-25, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Jan-26
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Jan-26, SIN-HND, 2010-Jan-26, 09:20:00, 2010-Jan-26, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-26, SIN-HND 2010-Jan-26, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-26, SIN-HND 2010-Jan-26, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-26, SIN-HND 2010-Jan-26, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-26, SIN-HND 2010-Jan-26, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Jan-26, SIN-HND 2010-Jan-26, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Jan-27
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Jan-27, SIN-HND, 2010-Jan-27, 09:20:00, 2010-Jan-27, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-27, SIN-HND 2010-Jan-27, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-27, SIN-HND 2010-Jan-27, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-27, SIN-HND 2010-Jan-27, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-27, SIN-HND 2010-Jan-27, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Jan-27, SIN-HND 2010-Jan-27, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****

```

```
FlightDate: SQ12, 2010-Jan-28
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Jan-28, SIN-HND, 2010-Jan-28, 09:20:00, 2010-Jan-28, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-28, SIN-HND 2010-Jan-28, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-28, SIN-HND 2010-Jan-28, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-28, SIN-HND 2010-Jan-28, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-28, SIN-HND 2010-Jan-28, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Jan-28, SIN-HND 2010-Jan-28, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Jan-29
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Jan-29, SIN-HND, 2010-Jan-29, 09:20:00, 2010-Jan-29, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-29, SIN-HND 2010-Jan-29, Y, 200, 200, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-29, SIN-HND 2010-Jan-29, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-29, SIN-HND 2010-Jan-29, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-29, SIN-HND 2010-Jan-29, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Jan-29, SIN-HND 2010-Jan-29, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Jan-30
*****
*****
Leg-Dates:
-----
```

```
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Jan-30, SIN-HND, 2010-Jan-30, 09:20:00, 2010-Jan-30, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-30, SIN-HND 2010-Jan-30, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-30, SIN-HND 2010-Jan-30, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-30, SIN-HND 2010-Jan-30, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-30, SIN-HND 2010-Jan-30, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Jan-30, SIN-HND 2010-Jan-30, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Jan-31
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Jan-31, SIN-HND, 2010-Jan-31, 09:20:00, 2010-Jan-31, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Jan-31, SIN-HND 2010-Jan-31, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Jan-31, SIN-HND 2010-Jan-31, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Jan-31, SIN-HND 2010-Jan-31, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Jan-31, SIN-HND 2010-Jan-31, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Jan-31, SIN-HND 2010-Jan-31, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-01
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-01, SIN-HND, 2010-Feb-01, 09:20:00, 2010-Feb-01, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
```

```

*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-01, SIN-HND 2010-Feb-01, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-01, SIN-HND 2010-Feb-01, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-01, SIN-HND 2010-Feb-01, Y, 2, 0, 0, 0, 0, 200, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-01, SIN-HND 2010-Feb-01, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-01, SIN-HND 2010-Feb-01, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
FlightDate: SQ12, 2010-Feb-02
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-02, SIN-HND, 2010-Feb-02, 09:20:00, 2010-Feb-02, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-02, SIN-HND 2010-Feb-02, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-02, SIN-HND 2010-Feb-02, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-02, SIN-HND 2010-Feb-02, Y, 2, 0, 0, 0, 0, 200, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-02, SIN-HND 2010-Feb-02, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-02, SIN-HND 2010-Feb-02, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
FlightDate: SQ12, 2010-Feb-03
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-03, SIN-HND, 2010-Feb-03, 09:20:00, 2010-Feb-03, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,

```

```
SQL12 2010-Feb-03, SIN-HND 2010-Feb-03, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQL12 2010-Feb-03, SIN-HND 2010-Feb-03, Y, 1, 0, 0, 0, 0, 200, 0,
SQL12 2010-Feb-03, SIN-HND 2010-Feb-03, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQL12 2010-Feb-03, SIN-HND 2010-Feb-03, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQL12 2010-Feb-03, SIN-HND 2010-Feb-03, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQL12, 2010-Feb-04
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQL12 2010-Feb-04, SIN-HND, 2010-Feb-04, 09:20:00, 2010-Feb-04, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQL12 2010-Feb-04, SIN-HND 2010-Feb-04, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQL12 2010-Feb-04, SIN-HND 2010-Feb-04, Y, 1, 0, 0, 0, 0, 200, 0,
SQL12 2010-Feb-04, SIN-HND 2010-Feb-04, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQL12 2010-Feb-04, SIN-HND 2010-Feb-04, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQL12 2010-Feb-04, SIN-HND 2010-Feb-04, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQL12, 2010-Feb-05
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQL12 2010-Feb-05, SIN-HND, 2010-Feb-05, 09:20:00, 2010-Feb-05, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQL12 2010-Feb-05, SIN-HND 2010-Feb-05, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
```

```
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-05, SIN-HND 2010-Feb-05, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-05, SIN-HND 2010-Feb-05, Y, 2, 0, 0, 0, 0, 200, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-05, SIN-HND 2010-Feb-05, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ12 2010-Feb-05, SIN-HND 2010-Feb-05, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
FlightDate: SQ12, 2010-Feb-06
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ12 2010-Feb-06, SIN-HND, 2010-Feb-06, 09:20:00, 2010-Feb-06, 12:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-06, SIN-HND 2010-Feb-06, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
      , 9, 0, 0, 0, 0, 0,
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-06, SIN-HND 2010-Feb-06, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-06, SIN-HND 2010-Feb-06, Y, 2, 0, 0, 0, 0, 200, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-06, SIN-HND 2010-Feb-06, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ12 2010-Feb-06, SIN-HND 2010-Feb-06, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
FlightDate: SQ12, 2010-Feb-07
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ12 2010-Feb-07, SIN-HND, 2010-Feb-07, 09:20:00, 2010-Feb-07, 12:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-07, SIN-HND 2010-Feb-07, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
      , 9, 0, 0, 0, 0, 0,
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
```

```
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-07, SIN-HND 2010-Feb-07, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-07, SIN-HND 2010-Feb-07, Y, 2, 0, 0, 0, 0, 200, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-07, SIN-HND 2010-Feb-07, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-07, SIN-HND 2010-Feb-07, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
FlightDate: SQ12, 2010-Feb-08
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-08, SIN-HND, 2010-Feb-08, 09:20:00, 2010-Feb-08, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-08, SIN-HND 2010-Feb-08, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-08, SIN-HND 2010-Feb-08, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-08, SIN-HND 2010-Feb-08, Y, 2, 0, 0, 0, 0, 200, 0,
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-08, SIN-HND 2010-Feb-08, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-08, SIN-HND 2010-Feb-08, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
FlightDate: SQ12, 2010-Feb-09
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-09, SIN-HND, 2010-Feb-09, 09:20:00, 2010-Feb-09, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-09, SIN-HND 2010-Feb-09, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-09, SIN-HND 2010-Feb-09, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-09, SIN-HND 2010-Feb-09, Y, 2, 0, 0, 0, 0, 200, 0,
*****
```

```
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
    GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-09, SIN-HND 2010-Feb-09, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
SQ12 2010-Feb-09, SIN-HND 2010-Feb-09, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-10
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
    Elapsed, Distance, Capacity,
SQ12 2010-Feb-10, SIN-HND, 2010-Feb-10, 09:20:00, 2010-Feb-10, 12:00:00, 07:40:
    00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
    CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-10, SIN-HND 2010-Feb-10, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
    , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-10, SIN-HND 2010-Feb-10, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-10, SIN-HND 2010-Feb-10, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
    GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-10, SIN-HND 2010-Feb-10, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
SQ12 2010-Feb-10, SIN-HND 2010-Feb-10, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
    0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-11
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
    Elapsed, Distance, Capacity,
SQ12 2010-Feb-11, SIN-HND, 2010-Feb-11, 09:20:00, 2010-Feb-11, 12:00:00, 07:40:
    00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
    CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-11, SIN-HND 2010-Feb-11, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
    , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-11, SIN-HND 2010-Feb-11, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-11, SIN-HND 2010-Feb-11, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
    GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
```



```
SQL12 2010-Feb-11, SIN-HND 2010-Feb-11, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQL12 2010-Feb-11, SIN-HND 2010-Feb-11, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQL12, 2010-Feb-12
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQL12 2010-Feb-12, SIN-HND, 2010-Feb-12, 09:20:00, 2010-Feb-12, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQL12 2010-Feb-12, SIN-HND 2010-Feb-12, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQL12 2010-Feb-12, SIN-HND 2010-Feb-12, Y, 1, 0, 0, 0, 0, 200, 0,
SQL12 2010-Feb-12, SIN-HND 2010-Feb-12, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQL12 2010-Feb-12, SIN-HND 2010-Feb-12, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQL12 2010-Feb-12, SIN-HND 2010-Feb-12, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQL12, 2010-Feb-13
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQL12 2010-Feb-13, SIN-HND, 2010-Feb-13, 09:20:00, 2010-Feb-13, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQL12 2010-Feb-13, SIN-HND 2010-Feb-13, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQL12 2010-Feb-13, SIN-HND 2010-Feb-13, Y, 1, 0, 0, 0, 0, 200, 0,
SQL12 2010-Feb-13, SIN-HND 2010-Feb-13, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQL12 2010-Feb-13, SIN-HND 2010-Feb-13, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQL12 2010-Feb-13, SIN-HND 2010-Feb-13, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
```

```
*****
FlightDate: SQ12, 2010-Feb-14
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-14, SIN-HND, 2010-Feb-14, 09:20:00, 2010-Feb-14, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-14, SIN-HND 2010-Feb-14, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-14, SIN-HND 2010-Feb-14, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-14, SIN-HND 2010-Feb-14, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-14, SIN-HND 2010-Feb-14, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-14, SIN-HND 2010-Feb-14, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-15
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-15, SIN-HND, 2010-Feb-15, 09:20:00, 2010-Feb-15, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-15, SIN-HND 2010-Feb-15, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-15, SIN-HND 2010-Feb-15, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-15, SIN-HND 2010-Feb-15, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-16
*****
*****
Leg-Dates:
```

```

-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-16, SIN-HND, 2010-Feb-16, 09:20:00, 2010-Feb-16, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-16, SIN-HND 2010-Feb-16, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-16, SIN-HND 2010-Feb-16, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-16, SIN-HND 2010-Feb-16, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-16, SIN-HND 2010-Feb-16, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-16, SIN-HND 2010-Feb-16, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-17
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-17, SIN-HND, 2010-Feb-17, 09:20:00, 2010-Feb-17, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-17, SIN-HND 2010-Feb-17, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-17, SIN-HND 2010-Feb-17, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-17, SIN-HND 2010-Feb-17, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-17, SIN-HND 2010-Feb-17, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-17, SIN-HND 2010-Feb-17, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-18
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-18, SIN-HND, 2010-Feb-18, 09:20:00, 2010-Feb-18, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,

```

```
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-18, SIN-HND 2010-Feb-18, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-18, SIN-HND 2010-Feb-18, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-18, SIN-HND 2010-Feb-18, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-18, SIN-HND 2010-Feb-18, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-18, SIN-HND 2010-Feb-18, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-19
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-19, SIN-HND, 2010-Feb-19, 09:20:00, 2010-Feb-19, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-19, SIN-HND 2010-Feb-19, Y, 200, 200, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-19, SIN-HND 2010-Feb-19, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-19, SIN-HND 2010-Feb-19, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-19, SIN-HND 2010-Feb-19, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-19, SIN-HND 2010-Feb-19, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-20
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-20, SIN-HND, 2010-Feb-20, 09:20:00, 2010-Feb-20, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
```

```

CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-20, SIN-HND 2010-Feb-20, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-20, SIN-HND 2010-Feb-20, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-20, SIN-HND 2010-Feb-20, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-20, SIN-HND 2010-Feb-20, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-20, SIN-HND 2010-Feb-20, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-21
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-21, SIN-HND, 2010-Feb-21, 09:20:00, 2010-Feb-21, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-21, SIN-HND 2010-Feb-21, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-21, SIN-HND 2010-Feb-21, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-21, SIN-HND 2010-Feb-21, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-21, SIN-HND 2010-Feb-21, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-21, SIN-HND 2010-Feb-21, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-22
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
Elapsed, Distance, Capacity,
SQ12 2010-Feb-22, SIN-HND, 2010-Feb-22, 09:20:00, 2010-Feb-22, 12:00:00, 07:40:
00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-22, SIN-HND 2010-Feb-22, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
, 9, 0, 0, 0, 0, 0,
*****
*****

```

```
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-22, SIN-HND 2010-Feb-22, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-22, SIN-HND 2010-Feb-22, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-22, SIN-HND 2010-Feb-22, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQ12 2010-Feb-22, SIN-HND 2010-Feb-22, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-23
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
  Elapsed, Distance, Capacity,
SQ12 2010-Feb-23, SIN-HND, 2010-Feb-23, 09:20:00, 2010-Feb-23, 12:00:00, 07:40:
  00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
  CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-23, SIN-HND 2010-Feb-23, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
  , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-23, SIN-HND 2010-Feb-23, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-23, SIN-HND 2010-Feb-23, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
  GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-23, SIN-HND 2010-Feb-23, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
SQ12 2010-Feb-23, SIN-HND 2010-Feb-23, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
  0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-24
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
  Elapsed, Distance, Capacity,
SQ12 2010-Feb-24, SIN-HND, 2010-Feb-24, 09:20:00, 2010-Feb-24, 12:00:00, 07:40:
  00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
  CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-24, SIN-HND 2010-Feb-24, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
  , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
```

```

SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-24, SIN-HND 2010-Feb-24, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-24, SIN-HND 2010-Feb-24, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-24, SIN-HND 2010-Feb-24, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ12 2010-Feb-24, SIN-HND 2010-Feb-24, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-25
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ12 2010-Feb-25, SIN-HND, 2010-Feb-25, 09:20:00, 2010-Feb-25, 12:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-25, SIN-HND 2010-Feb-25, Y, 200, 200, 0, 0, 0, 0, 0, 0, 200
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-25, SIN-HND 2010-Feb-25, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-25, SIN-HND 2010-Feb-25, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-25, SIN-HND 2010-Feb-25, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ12 2010-Feb-25, SIN-HND 2010-Feb-25, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-26
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ12 2010-Feb-26, SIN-HND, 2010-Feb-26, 09:20:00, 2010-Feb-26, 12:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhycAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-26, SIN-HND 2010-Feb-26, Y, 200, 200, 0, 0, 0, 0, 0, 0, 200
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-26, SIN-HND 2010-Feb-26, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-26, SIN-HND 2010-Feb-26, Y, 2, 0, 0, 0, 0, 200, 0,

```

```
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-26, SIN-HND 2010-Feb-26, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ12 2010-Feb-26, SIN-HND 2010-Feb-26, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-27
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ12 2010-Feb-27, SIN-HND, 2010-Feb-27, 09:20:00, 2010-Feb-27, 12:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-27, SIN-HND 2010-Feb-27, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 0, 200
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-27, SIN-HND 2010-Feb-27, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-27, SIN-HND 2010-Feb-27, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
      GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-27, SIN-HND 2010-Feb-27, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
SQ12 2010-Feb-27, SIN-HND 2010-Feb-27, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
      0, 0, 0, 0, 0,
*****
*****
FlightDate: SQ12, 2010-Feb-28
*****
*****
Leg-Dates:
-----
Flight, Leg, BoardDate, BoardTime, OffDate, OffTime, Date Offset, Time Offset,
      Elapsed, Distance, Capacity,
SQ12 2010-Feb-28, SIN-HND, 2010-Feb-28, 09:20:00, 2010-Feb-28, 12:00:00, 07:40:
      00, 0, -05:00:00, 6300, 0,
*****
*****
LegCabins:
-----
Flight, Leg, Cabin, OffedCAP, PhyCAP, RgdADJ, AU, UPR, SS, Staff, WL, Group,
      CommSpace, AvPool, Avl, NAV, GAV, ACP, ETB, BidPrice,
SQ12 2010-Feb-28, SIN-HND 2010-Feb-28, Y, 200, 200, 0, 0, 0, 0, 0, 0, 0, 200
      , 9, 0, 0, 0, 0, 0,
*****
*****
Buckets:
-----
Flight, Leg, Cabin, Yield, AU/SI, SS, AV,
*****
*****
SegmentCabins:
-----
Flight, Segment, Cabin, FF, Bkgs, MIN, UPR, CommSpace, AvPool, BP,
SQ12 2010-Feb-28, SIN-HND 2010-Feb-28, Y, 1, 0, 0, 0, 0, 200, 0,
SQ12 2010-Feb-28, SIN-HND 2010-Feb-28, Y, 2, 0, 0, 0, 0, 200, 0,
*****
*****
Subclasses:
-----
Flight, Segment, Cabin, FF, Subclass, MIN/AU (Prot), Nego, NS%, OB%, Bkgs,
```



```

GrpBks (pdg), StfBkgs, WLBkgs, ETB, ClassAvl, RevAvl, SegAvl,
SQ12 2010-Feb-28, SIN-HND 2010-Feb-28, Y, 1, Y, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
SQ12 2010-Feb-28, SIN-HND 2010-Feb-28, Y, 2, M, 200 (0), 0, 0, 0, 0, 0 (0), 0,
0, 0, 0, 0, 0,
*****

```

12.6 Exploring the Predefined BOM Tree




Figure 2: TravelCCM BOM tree

TravelCCM predefines a BOM (Business Object Model) tree specific to the airline IT arena.

12.6.1 Airline Network BOM Tree

- TRAVELCCM::ReachableUniverse
- TRAVELCCM::OriginDestinationSet
- TRAVELCCM::SegmentPathPeriod

12.6.2 Airline Schedule BOM Tree

- stdair::Inventory
- stdair::FlightPeriod
- stdair::SegmentPeriod
- stdair::OnDPeriod

12.7 Extending the BOM Tree

12.8 The travel solution calculation procedure

The project TravelCCM aims at calculating a list of `travel solutions` for every incoming `booking request`.

13 TRAVELCCM Supported Systems

13.1 Table of Contents

- [Introduction](#)
- [TRAVELCCM 3.10.x](#)
 - [Linux Systems](#)
 - * [Fedora Core 4 with ATLAS](#)
 - * [Gentoo Linux with ACML](#)
 - * [Gentoo Linux with ATLAS](#)
 - * [Gentoo Linux with MKL](#)
 - * [Gentoo Linux with NetLib's BLAS and LAPACK](#)
 - * [Red Hat Enterprise Linux with TRAVELCCM External](#)
 - * [SUSE Linux 10.0 with NetLib's BLAS and LAPACK](#)
 - * [SUSE Linux 10.0 with MKL](#)
 - [Windows Systems](#)
 - * [Microsoft Windows XP with Cygwin](#)
 - * [Microsoft Windows XP with Cygwin and ATLAS](#)
 - * [Microsoft Windows XP with Cygwin and ACML](#)
 - * [Microsoft Windows XP with MinGW, MSYS and ACML](#)
 - * [Microsoft Windows XP with MinGW, MSYS and TRAVELCCM External](#)
 - * [Microsoft Windows XP with MS Visual C++ and Intel MKL](#)
 - [Unix Systems](#)
 - * [SunOS 5.9 with TRAVELCCM External](#)
- [TRAVELCCM 3.9.1](#)
- [TRAVELCCM 3.9.0](#)
- [TRAVELCCM 3.8.1](#)

13.2 Introduction

This page is intended to provide a list of [TRAVELCCM](#) supported systems, i.e. the systems on which configuration, installation and testing process of the [TRAVELCCM](#) library has been successful. Results are grouped based on minor release number. Therefore, only the latest tests for bug-fix releases are included. Besides, the information on this page is divided into sections dependent on the operating system.

Where necessary, some extra information is given for each tested configuration, e.g. external libraries installed, configuration commands used, etc.

If you manage to compile, install and test the [TRAVELCCM](#) library on a system not mentioned below, please let us know, so we could update this database.

13.3 TRAVELCCM 3.10.x

13.3.1 Linux Systems

13.3.1.1 Fedora Core 4 with ATLAS

- **Platform:** Intel Pentium 4
- **Operating System:** Fedora Core 4 (x86)
- **Compiler:** g++ (GCC) 4.0.2 20051125
- **TRAVELCCM release:** 3.10.0
- **External Libraries:** From FC4 distribution:
 - `fftw3.i386-3.0.1-3`
 - `fftw3-devel.i386-3.0.1-3`
 - `atlas-sse2.i386-3.6.0-8.fc4`
 - `atlas-sse2-devel.i386-3.6.0-8.fc4`
 - `blas.i386-3.0-35.fc4`
 - `lapack.i386-3.0-35.fc4`
- **Tests Status:** All tests PASSED
- **Comments:** TRAVELCCM configured with:


```
% CXXFLAGS="-O3 -pipe -march=pentium4" ./configure
```
- **Date:** March 7, 2006
- **Tester:** Tony Ottosson

13.3.1.2 Gentoo Linux with ACML

- **Platform:** AMD Sempron 3000+
- **Operating System:** Gentoo Linux 2006.0 (x86 arch)
- **Compiler(s):** g++ (GCC) 3.4.5
- **TRAVELCCM release:** 3.10.1
- **External Libraries:** Compiled and installed from portage tree:
 - `sci-libs/acml-3.0.0`
- **Tests Status:** All tests PASSED
- **Comments:** BLAS and LAPACK libs set by using the following system commands:


```
% eselect blas set ACML
% eselect lapack set ACML
```

TRAVELCCM configured with:

```
% export CPPFLAGS="-I/usr/include/acml"
% ./configure --with-blas="-lblas"
```
- **Date:** March 31, 2006
- **Tester:** Adam Piatyszek (ediap)

13.3.1.3 Gentoo Linux with ATLAS

- **Platform:** Intel Pentium M Centrino
- **Operating System:** Gentoo Linux 2006.0 (x86)
- **Compiler:** g++ (GCC) 3.4.5
- **TRAVELCCM release:** 3.10.1
- **External Libraries:** Compiled and installed from portage tree:
 - sci-libs/fftw-3.1
 - sci-libs/blas-atlas-3.6.0-r1
 - sci-libs/lapack-atlas-3.6.0
- **Tests Status:** All tests PASSED
- **Comments:** BLAS and LAPACK libs set by using the following system commands:

```
% eselect blas set ATLAS
% eselect lapack set ATLAS
```

TRAVELCCM configured with:

```
% ./configure --with-blas="-lblas"
```

- **Date:** March 31, 2006
- **Tester:** Adam Piatyszek (ediap)

13.3.1.4 Gentoo Linux with MKL

- **Platform:** Intel Pentium M Centrino
- **Operating System:** Gentoo Linux 2006.0 (x86 arch)
- **Compiler:** g++ (GCC) 3.4.5
- **TRAVELCCM release:** 3.10.0
- **External Libraries:** Intel Math Kernel Library (MKL) 8.0.1 installed manually in the following directory:
/opt/intel/mkl/8.0.1
- **Tests Status:** All tests PASSED
- **Comments:** TRAVELCCM configured using the following commands:

```
% export LDFLAGS="-L/opt/intel/mkl/8.0.1/lib/32"
% export CPPFLAGS="-I/opt/intel/mkl/8.0.1/include"
% ./configure
```

- **Date:** February 28, 2006
- **Tester:** Adam Piatyszek (ediap)

13.3.1.5 Gentoo Linux with NetLib's BLAS and LAPACK

- **Platform:** Intel Pentium M Centrino
- **Operating System:** Gentoo Linux 2006.0 (x86)
- **Compiler:** g++ (GCC) 3.4.5
- **TRAVELCCM release:** 3.10.1
- **External Libraries:** Compiled and installed from portage tree:
 - sci-libs/fftw-3.1
 - sci-libs/blas-reference-19940131-r2
 - sci-libs/cblas-reference-20030223
 - sci-libs/lapack-reference-3.0-r2
- **Tests Status:** All tests PASSED
- **Comments:** BLAS and LAPACK libs set by using the following system commands:

```
% blas-config reference
% lapack-config reference
```

TRAVELCCM configured with:

```
% ./configure --with-blas="-lblas"
```

- **Date:** March 31, 2006
- **Tester:** Adam Piatyszek (ediap)

13.3.1.6 Red Hat Enterprise Linux with TRAVELCCM External

- **Platform:** Intel Pentium 4
- **Operating System:** Red Hat Enterprise Linux AS release 4 (Nahant Update 2)
- **Compiler:** g++ (GCC) 3.4.4 20050721 (Red Hat 3.4.4-2)
- **TRAVELCCM release:** 3.10.0
- **External Libraries:** BLAS, CBLAS, LAPACK and FFTW libraries from TRAVELCCM External 2.1.1 package
- **Tests Status:** All tests PASSED
- **Date:** March 7, 2006
- **Tester:** Erik G. Larsson

13.3.1.7 SUSE Linux 10.0 with NetLib's BLAS and LAPACK

- **Platform:** Intel Pentium 4 CPU 3.20GHz (64-bit)
- **Operating System:** SUSE Linux 10.0 (x86_64)
- **Compiler(s):** g++ (GCC) 4.0.2
- **TRAVELCCM release:** 3.10.0
- **External Libraries:** BLAS, LAPACK and FFTW libraries installed from OpenSuse 10.0 RPM repository:
 - blas-3.0-926
 - lapack-3.0-926
 - fftw3-3.0.1-114

- fftw3-threads-3.0.1-114
- fftw3-devel-3.0.1-114

- **Tests Status:** All tests PASSED
- **Comments:** TRAVELCCM configured with:

```
% export CXXFLAGS="-m64 -march=nocona -O3 -pipe"
% ./configure --with-lapack="/usr/lib64/liblapack.so.3"
```

- **Date:** March 1, 2006
- **Tester:** Adam Piatyszek (ediap)

13.3.1.8 SUSE Linux 10.0 with MKL

- **Platform:** Intel Pentium 4 CPU 3.20GHz (64-bit)
- **Operating System:** SUSE Linux 10.0 (x86_64)
- **Compiler(s):** g++ (GCC) 4.0.2
- **TRAVELCCM release:** 3.10.0
- **External Libraries:** Intel Math Kernel Library (MKL) 8.0.1 installed manually in the following directory:
/opt/intel/mkl/8.0.1
- **Tests Status:** All tests PASSED
- **Comments:** TRAVELCCM configured with:

```
% export CXXFLAGS="-m64 -march=nocona -O3 -pipe"
% export LDFLAGS="-L/opt/intel/mkl/8.0.1/lib/em64t"
% export CPPFLAGS="-I/opt/intel/mkl/8.0.1/include"
% ./configure
```

- **Date:** March 1, 2006
- **Tester:** Adam Piatyszek (ediap)

13.3.2 Windows Systems

13.3.2.1 Microsoft Windows XP with Cygwin

- **Platform:** AMD Sempron 3000+
- **Operating System:** Microsoft Windows XP SP2, Cygwin 1.5.19-4
- **Compiler(s):** g++ (GCC) 3.4.4 (cygming special)
- **TRAVELCCM release:** 3.10.1
- **External Libraries:** Installed from Cygwin's repository:
 - fftw-3.0.1-2
 - fftw-dev-3.0.1-1
 - lapack-3.0-4
- **Tests Status:** All tests PASSED
- **Comments:** Only static library can be built. TRAVELCCM configured with:

```
% ./configure
```

- **Date:** March 31, 2006
- **Tester:** Adam Piatyszek (ediap)

13.3.2.2 Microsoft Windows XP with Cygwin and ATLAS

- **Platform:** AMD Sempron 3000+
- **Operating System:** Microsoft Windows XP SP2, Cygwin 1.5.19-4
- **Compiler(s):** g++ (GCC) 3.4.4 (cygming special)
- **TRAVELCCM release:** 3.10.1
- **External Libraries:** Installed from Cygwin's repository:
 - fftw-3.0.1-2
 - fftw-dev-3.0.1-1

ATLAS BLAS and LAPACK libraries from [TRAVELCCM](#) External 2.1.1 package configured using:

```
% ./configure --enable-atlas --disable-fftw
```

- **Tests Status:** All tests PASSED
- **Comments:** Only static library can be built. [TRAVELCCM](#) configured with:

```
% export LDFLAGS="-L/usr/local/lib"
% ./configure
```

- **Date:** March 31, 2006
- **Tester:** Adam Piatyszek (ediap)

13.3.2.3 Microsoft Windows XP with Cygwin and ACML

- **Platform:** AMD Sempron 3000+
- **Operating System:** Microsoft Windows XP SP2, Cygwin 1.5.19-4
- **Compiler(s):** g++ (GCC) 3.4.4 (cygming special)
- **TRAVELCCM release:** 3.10.2
- **External Libraries:** ACML version 3.1.0 (acml3.1.0-32-win32-g77.exe) installed into a default directory, i.e. "c:\Program Files\AMD\acml3.1.0"
- **Tests Status:** All tests PASSED
- **Comments:** Only static library can be built. [TRAVELCCM](#) configured with:

```
% export LDFLAGS="-L/cygdrive/c/Progra~1/AMD/acml3.1.0/gnu32/lib"
% export CPPFLAGS="-I/cygdrive/c/Progra~1/AMD/acml3.1.0/gnu32/include"
% ./configure --enable-debug
```

- **Date:** May 15, 2006
- **Tester:** Adam Piatyszek (ediap)

13.3.2.4 Microsoft Windows XP with MinGW, MSYS and ACML

- **Platform:** AMD Sempron 3000+
- **Operating System:** Microsoft Windows XP SP2, MinGW 5.0.2, MSYS 1.0.10
- **Compiler(s):** g++ (GCC) 3.4.4 (mingw special)
- **TRAVELCCM release:** 3.10.2
- **External Libraries:** ACML version 3.1.0 (acml3.1.0-32-win32-g77.exe) installed into a default directory, i.e. "c:\Program Files\AMD\acml3.1.0"
- **Tests Status:** All tests PASSED
- **Comments:** Only static library can be built. TRAVELCCM configured with:


```
% export LDFLAGS="-L/c/Progra~1/AMD/acml3.1.0/gnu32/lib"
% export CPPFLAGS="-I/c/Progra~1/AMD/acml3.1.0/gnu32/include"
% ./configure --enable-debug
```
- **Date:** May 15, 2006
- **Tester:** Adam Piatyszek (ediap)

13.3.2.5 Microsoft Windows XP with MinGW, MSYS and TRAVELCCM External

- **Platform:** AMD Sempron 3000+
- **Operating System:** Microsoft Windows XP SP2, MinGW 5.0.2, MSYS 1.0.10
- **Compiler(s):** g++ (GCC) 3.4.4 (mingw special)
- **TRAVELCCM release:** 3.10.5
- **External Libraries:** BLAS, CBLAS, LAPACK and FFTW libraries from TRAVELCCM External 2.2.0 package
- **Tests Status:** All tests PASSED
- **Comments:** Only static library can be built. TRAVELCCM configured with:


```
% export LDFLAGS="-L/usr/local/lib"
% export CPPFLAGS="-I/usr/local/include"
% export CXXFLAGS="-Wall -O3 -march=athlon-tbird -pipe"
% ./configure --disable-html-doc
```
- **Date:** August 11, 2006
- **Tester:** Adam Piatyszek (ediap)

13.3.2.6 Microsoft Windows XP with MS Visual C++ and Intel MKL

- **Platform:** AMD Sempron 3000+
- **Operating System:** Microsoft Windows XP SP2
- **Compiler(s):** Microsoft Visual C++ 2005 .NET
- **TRAVELCCM release:** 3.10.5
- **External Libraries:** Intel Math Kernel Library (MKL) 8.1 installed manually in the following directory: "C:\Program Files\Intel\MKL\8.1"
- **Tests Status:** Not fully tested. Some TRAVELCCM based programs compiled and run with success.
- **Comments:** Only static library can be built. TRAVELCCM built by opening the "win32\travelccm.-vcproj" project file in MSVC++ and executing "Build -> Build Solution" command from menu.
- **Date:** August 11, 2006
- **Tester:** Adam Piatyszek (ediap)

13.3.3 Unix Systems

13.3.3.1 SunOS 5.9 with TRAVELCCM External

- **Platform:** SUNW, Sun-Blade-100 (SPARC)
- **Operating System:** SunOS 5.9 Generic_112233-10
- **Compiler(s):** g++ (GCC) 3.4.5
- **TRAVELCCM release:** 3.10.2
- **External Libraries:** BLAS, CBLAS, LAPACK and FFTW libraries from [TRAVELCCM External 2.1.1](#) package. The following configuration command has been used:

```
% export CFLAGS="-mcpu=ultrasparc -O2 -pipe -funroll-all-loops"  
% ./configure
```

- **Tests Status:** All tests PASSED
- **Comments:** [TRAVELCCM](#) configured with:

```
% export LDFLAGS="-L/usr/local/lib"  
% export CPPFLAGS="-I/usr/local/include"  
% export CXXFLAGS="-mcpu=ultrasparc -O2 -pipe"  
% ./configure --enable-debug
```

- **Date:** May 15, 2006
- **Tester:** Adam Piatyszek (ediap)

14 TRAVELCCM Supported Systems (Previous Releases)

14.1 TRAVELCCM 3.9.1

14.2 TRAVELCCM 3.9.0

14.3 TRAVELCCM 3.8.1

15 Tutorials

15.1 Table of Contents

- [Preparing the TravelCCM Project for Development](#)
- [Your first networkBuilde](#)
 - [Summary of the different steps](#)
 - [Result of the Batch Program](#)
- [Network building with an input file](#)
 - [How to build a network input file?](#)
 - [Building the BOM tree with an input file](#)
 - [Result of the Batch Program](#)

15.2 Preparing the TravelCCM Project for Development

The source code for these examples can be found in the `batches` and `test/travelccm` directories. They are compiled along with the rest of the `TravelCCM` project. See the [Users Guide](#) for more details on how to build the `TravelCCM` project.

15.3 Your first networkBuild

15.3.1 Summary of the different steps

All the steps below can be found in the same order in the batch `TravelCCM.cpp` program.

First, we instantiate the `TRAVELCCM_Service` object:

Then, we construct a default sample list of travel solutions and a default booking request (as mentioned in `ug_procedure_bookingrequest` and `ug_procedure_travelsolution` parts):

```
stdair::TravelSolutionList_T lTSList;
```

For basic use, the default BOM tree can be built using:

The main step is the network building (see [The travel solution calculation procedure](#)):

15.3.2 Result of the Batch Program

When the `TravelCCM.cpp` program is run (with the `-b` option), the log output file should look like:

What is interesting is to compare the travel solution list (here reduced to a single travel solution) displayed before:

and after the network building:

Between the two groups of dashes, we can see that a network option structure has been added by the network builder: the price is 450 EUR for the Y class, the ticket is refundable but there are exchange fees and the customer must stay over on Saturday night.

Let's return to our default BOM tree display: the only network rule stored was a match for the travel solution into consideration (same origin airport, same destination airport, flight date included in the network rule date range, same airline "BA", ...).

By looking at the network rule trip type "RT", we can guess we face a round trip network: that means the price given in the default bom tree construction in `stdair::CmdBomManager.hpp` has been divided by 2 because we are considering either an inbound trip or an outbound one.

15.4 Network building with an input file

15.4.1 How to build a network input file?

The objective here is to build a network input file to network build the default travel solution list built using:

This travel solution list, reduced to a singleton, can be displayed as done before:

We deduce:

- we need a network rule whose origin-destination couple is "LHR, SYD".
- the date range must include the date "2011-06-10".
- the time range must include the time "21:45".
- the airline operating is "BA", so it must be the airline pricing.

We can deduce a part of our network rule file :

```
// Fares: fare ID; OriginCity; DestinationCity; TripType; DateRangeStart;
    DateRangeEnd; DepartureTimeRangeStart; DepartureTimeRangeEnd; POS; CabinCode;
    Channel; AdvancePurchase; SaturdayNight; ChangeFees; NonRefundable; MinimumStay; Price;
    nb Segments
// Segment: AirlineCode; Class;
1; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; ???; ?; ??; ?; ?; ?; ?;
    ?; ???; BA; ?;
```

We have no information about stay duration and advance purchase (such information are contained into the booking request): so let us put "0" to embrace all the requests possible.

No information for the point-of-sale and the channel too: let us consider all the channels ("IN", "DN", "IF" and "DF") and all the points of sale (the origin "LHR", the destination "SYD" and the rest-of-the-world "ROW") existing. To access this information, we could look into the default booking request.

The input file is now:

```
// Fares: fare ID; OriginCity; DestinationCity; TripType; DateRangeStart;
    DateRangeEnd; DepartureTimeRangeStart; DepartureTimeRangeEnd; POS; CabinCode;
    Channel; AdvancePurchase; SaturdayNight; ChangeFees; NonRefundable; MinimumStay; Price;
    nb Segments
// Segment: AirlineCode; Class;
1; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; LHR; ?; IN; 0; ?; ?; ?;
    0; ???; BA; ?;
2; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; LHR; ?; IF; 0; ?; ?; ?;
    0; ???; BA; ?;
3; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; LHR; ?; DN; 0; ?; ?; ?;
    0; ???; BA; ?;
4; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; LHR; ?; DF; 0; ?; ?; ?;
    0; ???; BA; ?;
5; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; SYD; ?; IN; 0; ?; ?; ?;
    0; ???; BA; ?;
6; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; SYD; ?; IF; 0; ?; ?; ?;
    0; ???; BA; ?;
7; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; SYD; ?; DN; 0; ?; ?; ?;
    0; ???; BA; ?;
8; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; SYD; ?; DF; 0; ?; ?; ?;
    0; ???; BA; ?;
9; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; ROW; ?; IN; 0; ?; ?; ?;
    0; ???; BA; ?;
10; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; ROW; ?; IF; 0; ?; ?; ?;
    0; ???; BA; ?;
11; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; ROW; ?; DN; 0; ?; ?; ?;
    0; ???; BA; ?;
12; LHR; SYD; ??; 2011-01-01; 2011-12-31; 00:00; 23:59; ROW; ?; DF; 0; ?; ?; ?;
    0; ???; BA; ?;
```

Let us say we have just the Economy cabin "Y" and British Airways prices ticket for class "Y".

No information about the trip type, so we duplicate all the network rules for both type: one-way "OW" and round-trip "RT" (to access this information, we could look to the default booking request).

The network options are all set to a default value "T" (meaning true) and the network values are chosen to be all distinct.

We obtain:

```
// Fares: fare ID; OriginCity; DestinationCity; TripType; DateRangeStart;
//         DateRangeEnd; DepartureTimeRangeStart; DepartureTimeRangeEnd; POS; CabinCode;
//         Channel; AdvancePurchase; SaturdayNight; ChangeFees; NonRefundable; MinimumStay; Price;
// nb Segments
// Segment: AirlineCode; Class;
1; LHR; SYD; OW; 2011-01-01; 2011-12-31; 00:00; 23:59; LHR; Y; IN; 0; T; T; T;
0; 50; BA; Y;
2; LHR; SYD; OW; 2011-01-01; 2011-12-31; 00:00; 23:59; LHR; Y; IF; 0; T; T; T;
0; 150; BA; Y;
3; LHR; SYD; OW; 2011-01-01; 2011-12-31; 00:00; 23:59; LHR; Y; DN; 0; T; T; T;
0; 250; BA; Y;
4; LHR; SYD; OW; 2011-01-01; 2011-12-31; 00:00; 23:59; LHR; Y; DF; 0; T; T; T;
0; 350; BA; Y;
5; LHR; SYD; OW; 2011-01-01; 2011-12-31; 00:00; 23:59; SYD; Y; IN; 0; T; T; T;
0; 450; BA; Y;
6; LHR; SYD; OW; 2011-01-01; 2011-12-31; 00:00; 23:59; SYD; Y; IF; 0; T; T; T;
0; 550; BA; Y;
7; LHR; SYD; OW; 2011-01-01; 2011-12-31; 00:00; 23:59; SYD; Y; DN; 0; T; T; T;
0; 650; BA; Y;
8; LHR; SYD; OW; 2011-01-01; 2011-12-31; 00:00; 23:59; SYD; Y; DF; 0; T; T; T;
0; 750; BA; Y;
9; LHR; SYD; OW; 2011-01-01; 2011-12-31; 00:00; 23:59; ROW; Y; IN; 0; T; T; T;
0; 850; BA; Y;
10; LHR; SYD; OW; 2011-01-01; 2011-12-31; 00:00; 23:59; ROW; Y; IF; 0; T; T; T;
0; 950; BA; Y;
11; LHR; SYD; OW; 2011-01-01; 2011-12-31; 00:00; 23:59; ROW; Y; DN; 0; T; T; T;
0; 1050; BA; Y;
12; LHR; SYD; OW; 2011-01-01; 2011-12-31; 00:00; 23:59; ROW; Y; DF; 0; T; T; T;
0; 1150; BA; Y;
13; LHR; SYD; RT; 2011-01-01; 2011-12-31; 00:00; 23:59; LHR; Y; IN; 0; T; T; T;
0; 90; BA; Y;
14; LHR; SYD; RT; 2011-01-01; 2011-12-31; 00:00; 23:59; LHR; Y; IF; 0; T; T; T;
0; 190; BA; Y;
15; LHR; SYD; RT; 2011-01-01; 2011-12-31; 00:00; 23:59; LHR; Y; DN; 0; T; T; T;
0; 290; BA; Y;
16; LHR; SYD; RT; 2011-01-01; 2011-12-31; 00:00; 23:59; LHR; Y; DF; 0; T; T; T;
0; 390; BA; Y;
17; LHR; SYD; RT; 2011-01-01; 2011-12-31; 00:00; 23:59; SYD; Y; IN; 0; T; T; T;
0; 490; BA; Y;
18; LHR; SYD; RT; 2011-01-01; 2011-12-31; 00:00; 23:59; SYD; Y; IF; 0; T; T; T;
0; 590; BA; Y;
19; LHR; SYD; RT; 2011-01-01; 2011-12-31; 00:00; 23:59; SYD; Y; DN; 0; T; T; T;
0; 690; BA; Y;
20; LHR; SYD; RT; 2011-01-01; 2011-12-31; 00:00; 23:59; SYD; Y; DF; 0; T; T; T;
0; 790; BA; Y;
21; LHR; SYD; RT; 2011-01-01; 2011-12-31; 00:00; 23:59; ROW; Y; IN; 0; T; T; T;
0; 890; BA; Y;
22; LHR; SYD; RT; 2011-01-01; 2011-12-31; 00:00; 23:59; ROW; Y; IF; 0; T; T; T;
0; 990; BA; Y;
23; LHR; SYD; RT; 2011-01-01; 2011-12-31; 00:00; 23:59; ROW; Y; DN; 0; T; T; T;
0; 1090; BA; Y;
24; LHR; SYD; RT; 2011-01-01; 2011-12-31; 00:00; 23:59; ROW; Y; DF; 0; T; T; T;
0; 1190; BA; Y;
```

15.4.2 Building the BOM tree with an input file

The steps are the same as before [Summary of the different steps](#) except the bom tree must be built using the network input file :

15.4.3 Result of the Batch Program

When the TravelCCM.cpp program is run with the -f option linking with the file built just above:

```
~/TravelCCM -f ~/<YourFileName>.csv
```

the last lines of the log output should look like:

```
[D]~/TravelCCMgit/TravelCCM/batches/TravelCCM.cpp:223: Travel solutions:
[0] [0] BA, 9, 2011-06-10, LHR, SYD, 21:45 --- Y, 145, 1 1 1 ---
```

We have just one network option added to the travel solution. We can deduce from the price value 145 that the network builder used the network rule number 15 to price the travel solution. We have an inbound or outbound trip of a round trip: the total price 290 has been divided by 2.

16 Command-Line Test to Demonstrate How To Test the Travel CCM Project

```
*/
// //////////////////////////////////////
// Import section
// //////////////////////////////////////
// STL
#include <sstream>
#include <fstream>
#include <string>
// Boost Unit Test Framework (UTF)
#define BOOST_TEST_DYN_LINK
#define BOOST_TEST_MAIN
#define BOOST_TEST_MODULE TravelCCMTest
#include <boost/test/unit_test.hpp>
// StdAir
#include <stdair/basic/BasLogParams.hpp>
#include <stdair/basic/BasDBParams.hpp>
#include <stdair/basic/BasFileMgr.hpp>
#include <stdair/bom/TravelSolutionStruct.hpp>
#include <stdair/bom/BookingRequestStruct.hpp>
#include <stdair/service/Logger.hpp>
// TravelCCM
#include <travelccm/TRAVELCCM_Service.hpp>
#include <travelccm/config/travelccm-paths.hpp>
>

namespace boost_utf = boost::unit_test;

// (Boost) Unit Test XML Report
std::ofstream utfReportStream ("TravelChoiceTestSuite_utfresults.xml");

struct UnitTestConfig {
    UnitTestConfig() {
        boost_utf::unit_test_log.set_stream (utfReportStream);
        boost_utf::unit_test_log.set_format (boost_utf::XML);
        boost_utf::unit_test_log.set_threshold_level (boost_utf::log_test_units);
        //boost_utf::unit_test_log.set_threshold_level
        (boost_utf::log_successful_tests);
    }
    ~UnitTestConfig() {
    }
};

// ////////////////////////////////// Main: Unit Test Suite //////////////////////////////////

// Set the UTF configuration (re-direct the output to a specific file)
BOOST_GLOBAL_FIXTURE (UnitTestConfig);

// Start the test suite
BOOST_AUTO_TEST_SUITE (master_test_suite)

BOOST_AUTO_TEST_CASE (simple_simulation_test) {

    // Input file name
    /*
        const stdair::Filename_T inputFileName (STDAIR_SAMPLE_DIR "/ccm_02.csv");

    // Check that the file path given as input corresponds to an actual file
    const bool doesExistAndIsReadable =
        stdair::BasFileMgr::doesExistAndIsReadable (lInputFilename);
    BOOST_CHECK_MESSAGE (doesExistAndIsReadable == true,
        "The '" << lInputFilename
        << "' input file can not be open and read");
    */

    // Output log File
    const stdair::Filename_T lLogFilename ("TravelChoiceTestSuite.log");
```

```

// Set the log parameters
std::ofstream logOutputFile;
// Open and clean the log outputfile
logOutputFile.open (lLogFilename.c_str());
logOutputFile.clear();

// Initialise the service context
const stdair::BasLogParams lLogParams (stdair::LOG::DEBUG, logOutputFile);

// Build the BOM tree
TRAVELCCM::TRAVELCCM_Service travelccmService (
    lLogParams);

// DEBUG
STDAIR_LOG_DEBUG ("Welcome to TravelCCM");

// Build a list of travel solutions
const stdair::BookingRequestStruct& lBookingRequest =
    travelccmService.buildSampleBookingRequest();

// DEBUG
STDAIR_LOG_DEBUG ("Booking request: " << lBookingRequest.display());

// Build the sample BOM tree
stdair::TravelSolutionList_T lTSList;
travelccmService.buildSampleTravelSolutions (lTSList);

// DEBUG: Display the list of travel solutions
const std::string& lCSVDump = travelccmService.csvDisplay (lTSList);
STDAIR_LOG_DEBUG (lCSVDump);

// Choose a travel solution
const stdair::TravelSolutionStruct* lTS_ptr =
    travelccmService.chooseTravelSolution (lTSList, lBookingRequest);

// Check that a solution has been found
BOOST_REQUIRE_MESSAGE (lTS_ptr != NULL,
    "No travel solution can be found for "
    << lBookingRequest.display()
    << " within the following list of travel solutions. "
    << lCSVDump);

// Close the log file
logOutputFile.close();
}

// End the test suite
BOOST_AUTO_TEST_SUITE_END()

/*!

```

17 Namespace Index

17.1 Namespace List

Here is a list of all namespaces with brief descriptions:

stdair	
Forward declarations	91
TRAVELCCM	91

18 Class Index

18.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

```

std::basic_fstream< char >
std::basic_fstream< wchar_t >
std::basic_ifstream< char >
std::basic_ifstream< wchar_t >

```

std::basic_ios< char >	
std::basic_ios< wchar_t >	
std::basic_iostream< char >	
std::basic_iostream< wchar_t >	
std::basic_istream< char >	
std::basic_istream< wchar_t >	
std::basic_istreamstream< char >	
std::basic_istreamstream< wchar_t >	
std::basic_ofstream< char >	
std::basic_ofstream< wchar_t >	
std::basic_ostream< char >	
std::basic_ostream< wchar_t >	
std::basic_ostreamstream< char >	
std::basic_ostreamstream< wchar_t >	
std::basic_string< char >	
std::basic_string< wchar_t >	
std::basic_stringstream< char >	
std::basic_stringstream< wchar_t >	
TRAVELCCM::ChoiceManager	91
TRAVELCCM::CmdAbstract	92
FacServiceAbstract	93
TRAVELCCM::FacTRAVELCCMServiceContext	93
TRAVELCCM::FileMgr	95
TRAVELCCM::PriceOrientedModel	95
RootException	95
TRAVELCCM::CustomerChoiceException	92
ServiceAbstract	96
TRAVELCCM::TRAVELCCM_ServiceContext	99
TestFixture	96
TravelChoiceTestSuite	100
TRAVELCCM::TRAVELCCM Service	96

19 Class Index

19.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

TRAVELCCM::ChoiceManager	91
TRAVELCCM::CmdAbstract	92
TRAVELCCM::CustomerChoiceException	92
FacServiceAbstract	93

TRAVELCCM::FacTRAVELCCMServiceContext	93
TRAVELCCM::FileMgr	95
TRAVELCCM::PriceOrientedModel	95
RootException	95
ServiceAbstract	96
TestFixture	96
TRAVELCCM::TRAVELCCM_Service	96
TRAVELCCM::TRAVELCCM_ServiceContext Inner class holding the context for the TravelCCM Service object	99
TravelChoiceTestSuite	100

20 File Index

20.1 File List

Here is a list of all files with brief descriptions:

test/travelccm/TravelChoiceTestSuite.cpp	102
test/travelccm/TravelChoiceTestSuite.hpp	104
travelccm/TRAVELCCM_Service.hpp	125
travelccm/TRAVELCCM_Types.hpp	127
travelccm/basic/BasConst.cpp	104
travelccm/basic/BasConst_General.hpp	104
travelccm/batches/travelccm.cpp	105
travelccm/bom/PriceOrientedModel.cpp	108
travelccm/bom/PriceOrientedModel.hpp	109
travelccm/command/ChoiceManager.cpp	110
travelccm/command/ChoiceManager.hpp	110
travelccm/command/CmdAbstract.cpp	111
travelccm/command/CmdAbstract.hpp	111
travelccm/command/FileMgr.cpp	112
travelccm/command/FileMgr.hpp	112
travelccm/config/travelccm-paths.hpp	114
travelccm/config/travelccm-paths.hpp.in	116
travelccm/factory/FacTRAVELCCMServiceContext.cpp	117

travelccm/factory/FacTRAVELCCMServiceContext.hpp	118
travelccm/service/TRAVELCCM_Service.cpp	119
travelccm/service/TRAVELCCM_ServiceContext.cpp	123
travelccm/service/TRAVELCCM_ServiceContext.hpp	124

21 Namespace Documentation

21.1 stdair Namespace Reference

Forward declarations.

21.1.1 Detailed Description

Forward declarations.

21.2 TRAVELCCM Namespace Reference

Classes

- class [PriceOrientedModel](#)
- class [ChoiceManager](#)
- class [CmdAbstract](#)
- class [FileMgr](#)
- class [FacTRAVELCCMServiceContext](#)
- class [TRAVELCCM_ServiceContext](#)
 - Inner class holding the context for the TravelCCM Service object.*
- class [TRAVELCCM_Service](#)
- class [CustomerChoiceException](#)

Typedefs

- typedef boost::shared_ptr
< [TRAVELCCM_Service](#) > [TRAVELCCM_ServicePtr_T](#)

21.2.1 Typedef Documentation

21.2.1.1 typedef boost::shared_ptr<[TRAVELCCM_Service](#)> [TRAVELCCM::TRAVELCCM_ServicePtr_T](#)

Pointer on the [TRAVELCCM](#) Service handler.

Definition at line 38 of file [TRAVELCCM_Types.hpp](#).

22 Class Documentation

22.1 TRAVELCCM::ChoiceManager Class Reference

```
#include <travelccm/command/ChoiceManager.hpp>
```

Static Public Member Functions

- static const
stdair::TravelSolutionStruct * [chooseTravelSolution](#) (stdair::TravelSolutionList_T &, const stdair::BookingRequestStruct &)

22.1.1 Detailed Description

Class managing the customer choice model/algorithm.

Definition at line 21 of file [ChoiceManager.hpp](#).

22.1.2 Member Function Documentation

22.1.2.1 const stdair::TravelSolutionStruct * TRAVELCCM::ChoiceManager::chooseTravelSolution (stdair::TravelSolutionList_T & *ioTravelSolutionList*, const stdair::BookingRequestStruct & *iBookingRequest*) [static]

Choose the travel solution and the fare option within the given list of travel solutions.

The returned pointer will be NULL if no travel solution is chosen (e.g. Willingness-To-Pay too low).

Definition at line 17 of file [ChoiceManager.cpp](#).

The documentation for this class was generated from the following files:

- travelccm/command/[ChoiceManager.hpp](#)
- travelccm/command/[ChoiceManager.cpp](#)

22.2 TRAVELCCM::CmdAbstract Class Reference

```
#include <travelccm/command/CmdAbstract.hpp>
```

22.2.1 Detailed Description

Base class for the Command layer.

Definition at line 11 of file [CmdAbstract.hpp](#).


The documentation for this class was generated from the following file:

- travelccm/command/[CmdAbstract.hpp](#)

22.3 TRAVELCCM::CustomerChoiceException Class Reference

```
#include <travelccm/TRAVELCCM_Types.hpp>
```

Inheritance diagram for TRAVELCCM::CustomerChoiceException:



Public Member Functions

- [CustomerChoiceException](#) (const std::string &iWhat)

22.3.1 Detailed Description

TravelCCM specific root exception.

Definition at line 24 of file [TRAVELCCM_Types.hpp](#).

22.3.2 Constructor & Destructor Documentation

22.3.2.1 TRAVELCCM::CustomerChoiceException::CustomerChoiceException (const std::string & *iWhat*) [inline]

Constructor.


Definition at line 29 of file [TRAVELCCM_Types.hpp](#).

The documentation for this class was generated from the following file:

- [travelccm/TRAVELCCM_Types.hpp](#)

22.4 FacServiceAbstract Class Reference

Inheritance diagram for FacServiceAbstract:




The documentation for this class was generated from the following file:

- [travelccm/factory/FacTRAVELCCMServiceContext.hpp](#)

22.5 TRAVELCCM::FacTRAVELCCMServiceContext Class Reference

```
#include <travelccm/factory/FacTRAVELCCMServiceContext.hpp>
```

Inheritance diagram for TRAVELCCM::FacTRAVELCCMServiceContext:



Public Member Functions

- [~FacTRAVELCCMServiceContext \(\)](#)
- [TRAVELCCM_ServiceContext & create \(\)](#)

Static Public Member Functions

- static [FacTRAVELCCMServiceContext & instance \(\)](#)

Protected Member Functions

- [FacTRAVELCCMServiceContext](#) ()

22.5.1 Detailed Description

Factory for Bucket.

Definition at line 18 of file [FacTRAVELCCMServiceContext.hpp](#).

22.5.2 Constructor & Destructor Documentation

22.5.2.1 TRAVELCCM::FacTRAVELCCMServiceContext::~~FacTRAVELCCMServiceContext ()

Destructor.

The Destruction put the `_instance` to NULL in order to be clean for the next [FacTRAVELCCMServiceContext::instance\(\)](#).

Definition at line 17 of file [FacTRAVELCCMServiceContext.cpp](#).

22.5.2.2 TRAVELCCM::FacTRAVELCCMServiceContext::FacTRAVELCCMServiceContext () [inline],
[protected]

Default Constructor.

This constructor is protected in order to ensure the singleton pattern.

Definition at line 42 of file [FacTRAVELCCMServiceContext.hpp](#).

Referenced by [instance\(\)](#).

22.5.3 Member Function Documentation

22.5.3.1 FacTRAVELCCMServiceContext & TRAVELCCM::FacTRAVELCCMServiceContext::instance () [static]

Provide the unique instance.

The singleton is instantiated when first used

Returns

[FacTRAVELCCMServiceContext&](#)

Definition at line 22 of file [FacTRAVELCCMServiceContext.cpp](#).

References [FacTRAVELCCMServiceContext\(\)](#).

22.5.3.2 TRAVELCCM_ServiceContext & TRAVELCCM::FacTRAVELCCMServiceContext::create ()

Create a new [TRAVELCCM_ServiceContext](#) object.

This new object is added to the list of instantiated objects.

Returns

[TRAVELCCM_ServiceContext&](#) The newly created object.

Definition at line 34 of file [FacTRAVELCCMServiceContext.cpp](#).

The documentation for this class was generated from the following files:

- `travelccm/factory/FacTRAVELCCMServiceContext.hpp`
- `travelccm/factory/FacTRAVELCCMServiceContext.cpp`

22.6 TRAVELCCM::FileMgr Class Reference

```
#include <travelccm/command/FileMgr.hpp>
```

22.6.1 Detailed Description

Class filling the TravelSolutionHolder structure (representing a list of classes/travelSolutions) from a given input file.

Definition at line 15 of file [FileMgr.hpp](#).

The documentation for this class was generated from the following file:

- [travelccm/command/FileMgr.hpp](#)

22.7 TRAVELCCM::PriceOrientedModel Class Reference

```
#include <travelccm/bom/PriceOrientedModel.hpp>
```

Static Public Member Functions

- static const
stdair::TravelSolutionStruct * [chooseTravelSolution](#) (stdair::TravelSolutionList_T &, const stdair::BookingRequestStruct &)

22.7.1 Detailed Description

Class implementing the customer choice of cheapest solution.

Definition at line 21 of file [PriceOrientedModel.hpp](#).

22.7.2 Member Function Documentation

22.7.2.1 `const stdair::TravelSolutionStruct * TRAVELCCM::PriceOrientedModel::chooseTravelSolution (stdair::TravelSolutionList_T & ioTSList, const stdair::BookingRequestStruct & iBookingRequest) [static]`

Choose the cheapest travel solution and the fare option within the given list of travel solutions.

The returned pointer will be NULL if no travel solution is chosen (e.g. Willingness-To-Pay too low).


Definition at line 21 of file [PriceOrientedModel.cpp](#).

The documentation for this class was generated from the following files:

- [travelccm/bom/PriceOrientedModel.hpp](#)
- [travelccm/bom/PriceOrientedModel.cpp](#)

22.8 RootException Class Reference

Inheritance diagram for RootException:




The documentation for this class was generated from the following file:

- [travelccm/TRAVELCCM_Types.hpp](#)

22.9 ServiceAbstract Class Reference

Inheritance diagram for ServiceAbstract:




The documentation for this class was generated from the following file:

- [travelccm/service/TRAVELCCM_ServiceContext.hpp](#)

22.10 TestFixture Class Reference

Inheritance diagram for TestFixture:



The documentation for this class was generated from the following file:

- [test/travelccm/TravelChoiceTestSuite.hpp](#)

22.11 TRAVELCCM::TRAVELCCM_Service Class Reference

```
#include <travelccm/TRAVELCCM_Service.hpp>
```

Public Member Functions

- [TRAVELCCM_Service](#) (const stdair::BasLogParams &, const stdair::BasDBParams &)
- [TRAVELCCM_Service](#) (const stdair::BasLogParams &)
- [TRAVELCCM_Service](#) (stdair::STDAIR_ServicePtr_T)
- [~TRAVELCCM_Service](#) ()
- void [buildSampleBom](#) ()
- void [buildSampleTravelSolutions](#) (stdair::TravelSolutionList_T &)
- stdair::BookingRequestStruct [buildSampleBookingRequest](#) (const bool isForCRS=false)
- const
stdair::TravelSolutionStruct * [chooseTravelSolution](#) (stdair::TravelSolutionList_T &, const stdair::BookingRequestStruct &)
- std::string [csvDisplay](#) () const
- std::string [csvDisplay](#) (const stdair::TravelSolutionList_T &) const

22.11.1 Detailed Description

Interface for the [TRAVELCCM](#) Services.

Definition at line 31 of file [TRAVELCCM_Service.hpp](#).

22.11.2 Constructor & Destructor Documentation

22.11.2.1 TRAVELCCM::TRAVELCCM_Service::TRAVELCCM_Service (const stdair::BasLogParams & *iLogParams*, const stdair::BasDBParams & *iDBParams*)

Constructor.

The init() method is called; see the corresponding documentation for more details.

A reference on an output stream is given, so that log outputs can be directed onto that stream.

Moreover, database connection parameters are given, so that a session can be created on the corresponding database.

Parameters

<i>const</i>	stdair::BasLogParams& Parameters for the output log stream.
<i>const</i>	stdair::BasDBParams& Parameters for the database access.

Definition at line 36 of file [TRAVELCCM_Service.cpp](#).

22.11.2.2 TRAVELCCM::TRAVELCCM_Service::TRAVELCCM_Service (const stdair::BasLogParams & *iLogParams*)

Constructor.

The init() method is called; see the corresponding documentation for more details.

A reference on an output stream is given, so that log outputs can be directed onto that stream.

Parameters

<i>const</i>	stdair::BasLogParams& Parameters for the output log stream.
--------------	---

Definition at line 57 of file [TRAVELCCM_Service.cpp](#).

22.11.2.3 TRAVELCCM::TRAVELCCM_Service::TRAVELCCM_Service (stdair::STDAIR_ServicePtr_T *ioSTDAIR_Service_ptr*)

Constructor.

The init() method is called; see the corresponding documentation for more details.

Moreover, as no reference on any output stream is given, it is assumed that the StdAir log service has already been initialised with the proper log output stream by some other methods in the calling chain (for instance, when the [TRAVELCCM_Service](#) is itself being initialised by another library service such as [DSIM_Service](#)).

Parameters

<i>stdair::STDAIR_ServicePtr_T</i>	Reference on the STDAIR service.
------------------------------------	----------------------------------

Definition at line 78 of file [TRAVELCCM_Service.cpp](#).

22.11.2.4 TRAVELCCM::TRAVELCCM_Service::~~TRAVELCCM_Service ()

Destructor.

Definition at line 94 of file [TRAVELCCM_Service.cpp](#).

22.11.3 Member Function Documentation

22.11.3.1 void TRAVELCCM::TRAVELCCM_Service::buildSampleBom ()

Build a sample BOM tree, and attach it to the BomRoot instance.

Definition at line 170 of file [TRAVELCCM_Service.cpp](#).

22.11.3.2 void TRAVELCCM::TRAVELCCM_Service::buildSampleTravelSolutions (stdair::TravelSolutionList_T & ioTSList)

Build a sample list of travel solutions.

As of now (March 2011), that list is made of the following travel solutions:

- BA9
- LHR-SYD
- 2011-06-10
- Q
- WTP: 900
- Change fee: 20; Non refundable; Saturday night stay

Parameters

<i>stdair::TravelSolutionList_T &</i>	Sample list of travel solution structures. It should be given empty. It is altered with the returned sample.
---	--

Definition at line 217 of file [TRAVELCCM_Service.cpp](#).

22.11.3.3 stdair::BookingRequestStruct TRAVELCCM::TRAVELCCM_Service::buildSampleBookingRequest (const bool isForCRS = false)

Build a sample booking request structure.

As of now (March 2011), the sample booking request is made of the following parameters:

- Return trip (inbound): LHR-SYD (POS: LHR, Channel: DN),
- Departing 10-JUN-2011 around 8:00, staying 7 days
- Requested on 15-MAY-2011 at 10:00
- Economy cabin, 3 persons, FF member
- WTP: 1000.0 EUR
- Dis-utility: 100.0 EUR/hour

As of now (March 2011), the CRS-related booking request is made of the following parameters:

- Return trip (inbound): SIN-BKK (POS: SIN, Channel: IN),
- Departing 30-JAN-2010 around 10:00, staying 7 days
- Requested on 22-JAN-2010 at 10:00
- Economy cabin, 3 persons, FF member
- WTP: 1000.0 EUR
- Dis-utility: 100.0 EUR/hour

Parameters

<i>const</i>	bool isForCRS Whether the sample booking request is for CRS.
--------------	--

Returns

BookingRequestStruct& Sample booking request structure.

Definition at line 239 of file [TRAVELCCM_Service.cpp](#).

22.11.3.4 `const stdair::TravelSolutionStruct * TRAVELCCM::TRAVELCCM_Service::chooseTravelSolution (stdair::TravelSolutionList_T & ioTravelSolutionList, const stdair::BookingRequestStruct & iBookingRequest)`

Choose the travel solution and the fare option within the given list of travel solutions.

The returned pointer will be NULL if no travel solution is chosen (e.g., when the Willingness-To-Pay is too low).

Parameters

<i>stdair::TravelSolutionList_T&</i>	The list of travel solution to choose among.
<i>const</i>	stdair::BookingRequestStruct& The booking request and its context.

Returns

stdair::TravelSolutionStruct* The chosen travel solution. NULL when not found.

Definition at line 303 of file [TRAVELCCM_Service.cpp](#).

22.11.3.5 `std::string TRAVELCCM::TRAVELCCM_Service::csvDisplay () const`

Recursively display (dump in the returned string) the objects of the BOM tree.

Returns

std::string Output string in which the BOM tree is logged/dumped.

Definition at line 260 of file [TRAVELCCM_Service.cpp](#).

22.11.3.6 `std::string TRAVELCCM::TRAVELCCM_Service::csvDisplay (const stdair::TravelSolutionList_T & iTravelSolutionList) const`

Display (dump in the returned string) the full list of travel solution structures.

Returns

std::string Output string in which the list of travel solutions is logged/dumped.

Definition at line 282 of file [TRAVELCCM_Service.cpp](#).

The documentation for this class was generated from the following files:


- [travelccm/TRAVELCCM_Service.hpp](#)
- [travelccm/service/TRAVELCCM_Service.cpp](#)

22.12 TRAVELCCM::TRAVELCCM_ServiceContext Class Reference

Inner class holding the context for the TravelCCM Service object.

```
#include <travelccm/service/TRAVELCCM_ServiceContext.hpp>
```

Inheritance diagram for TRAVELCCM::TRAVELCCM_ServiceContext:



Friends

- class [TRAVELCCM_Service](#)
- class [FacTRAVELCCMServiceContext](#)

22.12.1 Detailed Description

Inner class holding the context for the TravelCCM Service object.

Definition at line 23 of file [TRAVELCCM_ServiceContext.hpp](#).

22.12.2 Friends And Related Function Documentation

22.12.2.1 friend class TRAVELCCM_Service [friend]

The [TRAVELCCM_Service](#) class should be the sole class to get access to ServiceContext content: general users do not want to bother with a context interface.

Definition at line 29 of file [TRAVELCCM_ServiceContext.hpp](#).

22.12.2.2 friend class FacTRAVELCCMServiceContext [friend]

Definition at line 30 of file [TRAVELCCM_ServiceContext.hpp](#).


The documentation for this class was generated from the following files:

- [travelccm/service/TRAVELCCM_ServiceContext.hpp](#)
- [travelccm/service/TRAVELCCM_ServiceContext.cpp](#)

22.13 TravelChoiceTestSuite Class Reference

```
#include <test/travelccm/TravelChoiceTestSuite.hpp>
```

Inheritance diagram for TravelChoiceTestSuite:



Public Member Functions

- void [testTravelChoice](#) ()
- [TravelChoiceTestSuite](#) ()

Protected Attributes

- `std::stringstream _describeKey`

22.13.1 Detailed Description

Definition at line 6 of file [TravelChoiceTestSuite.hpp](#).

22.13.2 Constructor & Destructor Documentation

22.13.2.1 `TravelChoiceTestSuite::TravelChoiceTestSuite ()`

Test some error detection functionalities. Constructor.

22.13.3 Member Function Documentation

22.13.3.1 `void TravelChoiceTestSuite::testTravelChoice ()`

Test the Optimisation functionality.

22.13.4 Member Data Documentation

22.13.4.1 `std::stringstream TravelChoiceTestSuite::_describeKey` `[protected]`

Definition at line 23 of file [TravelChoiceTestSuite.hpp](#).

The documentation for this class was generated from the following file:

- `test/travelccm/TravelChoiceTestSuite.hpp`

23 File Documentation

23.1 `doc/local/authors.doc` File Reference

23.2 `doc/local/codingrules.doc` File Reference

23.3 `doc/local/copyright.doc` File Reference

23.4 `doc/local/documentation.doc` File Reference

23.5 `doc/local/features.doc` File Reference

23.6 `doc/local/help_wanted.doc` File Reference

23.7 `doc/local/howto_release.doc` File Reference

23.8 `doc/local/index.doc` File Reference

23.9 `doc/local/installation.doc` File Reference

23.10 `doc/local/linking.doc` File Reference

23.11 doc/local/test.doc File Reference

23.12 doc/local/users_guide.doc File Reference

23.13 doc/local/verification.doc File Reference

23.14 doc/tutorial/tutorial.doc File Reference

23.15 test/travelccm/TravelChoiceTestSuite.cpp File Reference

23.16 TravelChoiceTestSuite.cpp

```

00001
00005 // //////////////////////////////////////
00006 // Import section
00007 // //////////////////////////////////////
00008 // STL
00009 #include <sstream>
00010 #include <fstream>
00011 #include <string>
00012 // Boost Unit Test Framework (UTF)
00013 #define BOOST_TEST_DYN_LINK
00014 #define BOOST_TEST_MAIN
00015 #define BOOST_TEST_MODULE TravelCCMTest
00016 #include <boost/test/unit_test.hpp>
00017 // StdAir
00018 #include <stdair/basic/BasLogParams.hpp>
00019 #include <stdair/basic/BasDBParams.hpp>
00020 #include <stdair/basic/BasFileMgr.hpp>
00021 #include <stdair/bom/TravelSolutionStruct.hpp>
00022 #include <stdair/bom/BookingRequestStruct.hpp>
00023 #include <stdair/service/Logger.hpp>
00024 // TravelCCM
00025 #include <travelccm/TRAVELCCM_Service.hpp>
00026 #include <travelccm/config/travelccm-paths.hpp>
00027 >
00028 namespace boost_utf = boost::unit_test;
00029
00030 // (Boost) Unit Test XML Report
00031 std::ofstream utfReportStream ("TravelChoiceTestSuite_utfresults.xml");
00032
00033 struct UnitTestConfig {
00034     UnitTestConfig() {
00035         boost_utf::unit_test_log.set_stream (utfReportStream);
00036         boost_utf::unit_test_log.set_format (boost_utf::XML);
00037         boost_utf::unit_test_log.set_threshold_level (boost_utf::log_test_units);
00038         //boost_utf::unit_test_log.set_threshold_level
00039         (boost_utf::log_successful_tests);
00040     }
00041     ~UnitTestConfig() {
00042     }
00043 };
00044
00045 // ////////////////////////////////// Main: Unit Test Suite //////////////////////////////////
00046
00047 // Set the UTF configuration (re-direct the output to a specific file)
00048 BOOST_GLOBAL_FIXTURE (UnitTestConfig);
00049
00050 // Start the test suite
00051 BOOST_AUTO_TEST_SUITE (master_test_suite)
00052
00053 BOOST_AUTO_TEST_CASE (simple_simulation_test) {
00054
00055     // Input file name
00056     /*
00057     const stdair::Filename_T inputFileName (STDAIR_SAMPLE_DIR "/ccm_02.csv");
00058
00059     // Check that the file path given as input corresponds to an actual file
00060     const bool doesExistAndIsReadable =
00061         stdair::BasFileMgr::doesExistAndIsReadable (lInputFilename);
00062     BOOST_CHECK_MESSAGE (doesExistAndIsReadable == true,
00063         "The '" << lInputFilename
00064         << "' input file can not be open and read");
00065     */
00066
00067     // Output log File
00068     const stdair::Filename_T lLogFilename ("TravelChoiceTestSuite.log");

```

```

00077
00078 // Set the log parameters
00079 std::ofstream logOutputFile;
00080 // Open and clean the log outputfile
00081 logOutputFile.open (lLogFilename.c_str());
00082 logOutputFile.clear();
00083
00084 // Initialise the service context
00085 const stdair::BasLogParams lLogParams (stdair::LOG::DEBUG, logOutputFile);
00086
00087 // Build the BOM tree
00088 TRAVELCCM::TRAVELCCM_Service travelccmService (
lLogParams);
00089
00090 // DEBUG
00091 STDAIR_LOG_DEBUG ("Welcome to TravelCCM");
00092
00093 // Build a list of travel solutions
00094 const stdair::BookingRequestStruct& lBookingRequest =
00095     travelccmService.buildSampleBookingRequest();
00096
00097 // DEBUG
00098 STDAIR_LOG_DEBUG ("Booking request: " << lBookingRequest.display());
00099
00100 // Build the sample BOM tree
00101 stdair::TravelSolutionList_T lTSList;
00102 travelccmService.buildSampleTravelSolutions (lTSList);
00103
00104 // DEBUG: Display the list of travel solutions
00105 const std::string& lCSVDump = travelccmService.csvDisplay (lTSList);
00106 STDAIR_LOG_DEBUG (lCSVDump);
00107
00108 // Choose a travel solution
00109 const stdair::TravelSolutionStruct* lTS_ptr =
00110     travelccmService.chooseTravelSolution (lTSList, lBookingRequest);
00111
00112 // Check that a solution has been found
00113 BOOST_REQUIRE_MESSAGE (lTS_ptr != NULL,
00114     "No travel solution can be found for "
00115     << lBookingRequest.display()
00116     << " within the following list of travel solutions. "
00117     << lCSVDump);
00118
00119 // Close the log file
00120 logOutputFile.close();
00121 }
00122
00123 // End the test suite
00124 BOOST_AUTO_TEST_SUITE_END()
00125
00126

```

23.17 test/travelccm/TravelChoiceTestSuite.hpp File Reference

```

#include <sstream>
#include <cppunit/extensions/HelperMacros.h>

```

Classes

- class [TravelChoiceTestSuite](#)

Functions

- [CPPUNIT_TEST_SUITE_REGISTRATION](#) ([TravelChoiceTestSuite](#))

23.17.1 Function Documentation

23.17.1.1 CPPUNIT_TEST_SUITE_REGISTRATION ([TravelChoiceTestSuite](#))

23.18 TravelChoiceTestSuite.hpp

```

00001 // STL
00002 #include <sstream>
00003 // CPPUNIT
00004 #include <cppunit/extensions/HelperMacros.h>
00005
00006 class TravelChoiceTestSuite : public CppUnit::TestFixture
00007 {
00008     CPPUNIT_TEST_SUITE (TravelChoiceTestSuite);
00009     CPPUNIT_TEST (testTravelChoice);
00010     // CPPUNIT_TEST (errorCase);
00011     CPPUNIT_TEST_SUITE_END ();
00012 public:
00013     void testTravelChoice ();
00014     // void errorCase ();
00015     TravelChoiceTestSuite ();
00016 protected:
00017     std::stringstream _describeKey;
00018 };
00019 CPPUNIT_TEST_SUITE_REGISTRATION (
00020     TravelChoiceTestSuite);

```

23.19 travelccm/basic/BasConst.cpp File Reference

```
#include <travelccm/basic/BasConst_General.hpp>
```

Namespaces

- namespace [TRAVELCCM](#)

23.20 BasConst.cpp

```

00001 // //////////////////////////////////////
00002 // Import section
00003 // //////////////////////////////////////
00004 #include <travelccm/basic/BasConst_General.hpp>
00005 >
00006 namespace TRAVELCCM {
00007
00008 }

```

23.21 travelccm/basic/BasConst_General.hpp File Reference

Namespaces

- namespace [TRAVELCCM](#)

23.22 BasConst_General.hpp

```

00001 #ifndef __TRAVELCCM_BAS_BASCONST_GENERAL_HPP
00002 #define __TRAVELCCM_BAS_BASCONST_GENERAL_HPP
00003
00004 // //////////////////////////////////////
00005 // Import section
00006 // //////////////////////////////////////
00007
00008 namespace TRAVELCCM {
00009
00010 }
00011 #endif // __TRAVELCCM_BAS_BASCONST_GENERAL_HPP

```

23.23 travelccm/batches/travelccm.cpp File Reference

23.24 travelccm.cpp

```

00001
00005 // STL
00006 #include <cassert>
00007 #include <iostream>
00008 #include <sstream>
00009 #include <fstream>
00010 #include <string>
00011 // Boost (Extended STL)
00012 #include <boost/program_options.hpp>
00013 // StdAir
00014 #include <stdair/basic/BasLogParams.hpp>
00015 #include <stdair/basic/BasDBParams.hpp>
00016 #include <stdair/bom/BookingRequestStruct.hpp>
00017 #include <stdair/bom/TravelSolutionStruct.hpp>
00018 #include <stdair/service/Logger.hpp>
00019 // TravelCCM
00020 #include <travelccm/TRAVELCCM_Service.hpp>
00021 #include <travelccm/config/travelccm-paths.hpp>
00022 >
00023 // ////////// Constants //////////
00027 const std::string K_TRAVELCCM_DEFAULT_LOG_FILENAME ("travelccm.log");
00028
00032 const std::string K_TRAVELCCM_DEFAULT_INPUT_FILENAME (STDAIR_SAMPLE_DIR
00033                                                         "/ccm_01.csv");
00034
00039 const bool K_TRAVELCCM_DEFAULT_BUILT_IN_INPUT = false;
00040
00044 const int K_TRAVELCCM_EARLY_RETURN_STATUS = 99;
00045
00046
00047 // ////////// Parsing of Options & Configuration //////////
00048 // A helper function to simplify the main part.
00049 template<class T> std::ostream& operator<< (std::ostream& os,
00050                                           const std::vector<T>& v) {
00051     std::copy (v.begin(), v.end(), std::ostream_iterator<T> (std::cout, " "));
00052     return os;
00053 }
00054
00058 int readConfiguration (int argc, char* argv[], bool& ioIsBuiltin,
00059                       stdair::Filename_T& lInputFilename,
00060                       stdair::Filename_T& lLogFilename) {
00061
00062     // Default for the built-in input
00063     ioIsBuiltin = K_TRAVELCCM_DEFAULT_BUILT_IN_INPUT;
00064
00065     // Declare a group of options that will be allowed only on command line
00066     boost::program_options::options_description generic ("Generic options");
00067     generic.add_options()
00068         ("prefix", "print installation prefix")
00069         ("version,v", "print version string")
00070         ("help,h", "produce help message");
00071
00072     // Declare a group of options that will be allowed both on command
00073     // line and in config file
00074     boost::program_options::options_description config ("Configuration");
00075     config.add_options()
00076         ("builtin,b",
00077          "The sample BOM tree can be either built-in or parsed from an input file.
00078          That latter must then be given with the -i/--input option")
00079         ("input,i",
00080          boost::program_options::value< std::string >(&lInputFilename)->
00081          default_value(K_TRAVELCCM_DEFAULT_INPUT_FILENAME),
00082          "(CSV) input file for the customer choice rule sets")
00083         ("log,l",
00084          boost::program_options::value< std::string >(&lLogFilename)->default_value
00085          (K_TRAVELCCM_DEFAULT_LOG_FILENAME),
00086          "Filename for the logs")
00087         ;
00088
00089     // Hidden options, will be allowed both on command line and
00090     // in config file, but will not be shown to the user.
00091     boost::program_options::options_description hidden ("Hidden options");
00092     hidden.add_options()
00093         ("copyright",
00094          boost::program_options::value< std::vector<std::string> >(),
00095          "Show the copyright (license)");
00096
00097     boost::program_options::options_description cmdline_options;
00098     cmdline_options.add(generic).add(config).add(hidden);

```

```

00097 boost::program_options::options_description config_file_options;
00098 config_file_options.add(config).add(hidden);
00099
00100 boost::program_options::options_description visible ("Allowed options");
00101 visible.add(generic).add(config);
00102
00103 boost::program_options::positional_options_description p;
00104 p.add ("copyright", -1);
00105
00106 boost::program_options::variables_map vm;
00107 boost::program_options::
00108     store (boost::program_options::command_line_parser (argc, argv).
00109         options (cmdline_options).positional(p).run(), vm);
00110
00111 std::ifstream ifs ("travelccm.cfg");
00112 boost::program_options::store (parse_config_file (ifs, config_file_options),
00113     vm);
00114 boost::program_options::notify (vm);
00115
00116 if (vm.count ("help")) {
00117     std::cout << visible << std::endl;
00118     return K_TRAVELCCM_EARLY_RETURN_STATUS;
00119 }
00120
00121 if (vm.count ("version")) {
00122     std::cout << PACKAGE_NAME << ", version " << PACKAGE_VERSION
00123 << std::endl;
00124     return K_TRAVELCCM_EARLY_RETURN_STATUS;
00125 }
00126 if (vm.count ("prefix")) {
00127     std::cout << "Installation prefix: " << PREFIXDIR << std::endl;
00128     return K_TRAVELCCM_EARLY_RETURN_STATUS;
00129 }
00130
00131 if (vm.count ("builtin")) {
00132     ioIsBuiltin = true;
00133 }
00134 const std::string isBuiltinStr = (ioIsBuiltin == true)?"yes":"no";
00135 std::cout << "The BOM should be built-in? " << isBuiltinStr << std::endl;
00136
00137 if (ioIsBuiltin == false) {
00138     // The BOM tree should be built from parsing a customer-choice rule file
00139     if (vm.count ("input")) {
00140         lInputFilename = vm["input"].as< std::string >();
00141         std::cout << "Input filename is: " << lInputFilename << std::endl;
00142     } else {
00143         // The built-in option is not selected. However, no demand input file
00144         // is specified
00145         std::cerr << "Either one among the -b/--builtin and -i/--input "
00146             << "options must be specified" << std::endl;
00147     }
00148 }
00149
00150 if (vm.count ("log")) {
00151     lLogFilename = vm["log"].as< std::string >();
00152     std::cout << "Log filename is: " << lLogFilename << std::endl;
00153 }
00154
00155 return 0;
00156 }
00157
00158 // ////////////////////////////////// M A I N //////////////////////////////////
00159 int main (int argc, char* argv[]) {
00160
00161     // State whether the BOM tree should be built-in or parsed from an input file
00162     bool isBuiltin;
00163
00164     // Input file name
00165     stdair::Filename_T lInputFilename;
00166
00167     // Output log File
00168     stdair::Filename_T lLogFilename;
00169
00170     // Call the command-line option parser
00171     const int lOptionParserStatus =
00172         readConfiguration (argc, argv, isBuiltin, lInputFilename, lLogFilename);
00173
00174     if (lOptionParserStatus == K_TRAVELCCM_EARLY_RETURN_STATUS) {
00175         return 0;
00176     }
00177
00178     // Set the log parameters
00179     std::ofstream logOutputFile;

```



```

00183 // Open and clean the log outputfile
00184 logOutputFile.open (lLogFilename.c_str());
00185 logOutputFile.clear();
00186
00187 // Initialise the service context
00188 const stdair::BasLogParams lLogParams (stdair::LOG::DEBUG, logOutputFile);
00189
00190 // Build the BOM tree
00191 TRAVELCCM::TRAVELCCM_Service travelccmService (
    lLogParams);
00192
00193 // DEBUG
00194 STDAIR_LOG_DEBUG ("Welcome to TravelCCM");
00195
00196 // Check whether or not a (CSV) input file should be read
00197 if (isBuiltin == true) {
00198     // Create a sample Customer-Choice rule object, and insert it
00199     // within the BOM tree
00200     travelccmService.buildSampleBom();
00201 }
00202 } else {
00203     // travelccmService.parseAndLoad (lInputFilename);
00204 }
00205
00206 // Build a list of travel solutions
00207 const stdair::BookingRequestStruct& lBookingRequest =
00208     travelccmService.buildSampleBookingRequest();
00209
00210 // DEBUG
00211 STDAIR_LOG_DEBUG ("Booking request: " << lBookingRequest.display());
00212
00213 // Build the sample BOM tree
00214 stdair::TravelSolutionList_T lTSList;
00215 travelccmService.buildSampleTravelSolutions (lTSList);
00216
00217 // DEBUG: Display the list of travel solutions
00218 const std::string& lCSVDump = travelccmService.csvDisplay (lTSList);
00219 STDAIR_LOG_DEBUG (lCSVDump);
00220
00221 // Choose a travel solution
00222 const stdair::TravelSolutionStruct* lTS_ptr =
00223     travelccmService.chooseTravelSolution (lTSList, lBookingRequest);
00224
00225 if (lTS_ptr != NULL) {
00226     // DEBUG
00227     STDAIR_LOG_DEBUG ("Chosen travel solution: " << lTS_ptr->display());
00228 }
00229 } else {
00230     // DEBUG
00231     STDAIR_LOG_DEBUG ("No travel solution can be found for "
00232         << lBookingRequest.display()
00233         << " within the following list of travel solutions");
00234     STDAIR_LOG_DEBUG (lCSVDump);
00235 }
00236
00237 // Close the Log outputfile
00238 logOutputFile.close();
00239
00240 return 0;
00241 }

```

23.25 travelccm/bom/PriceOrientedModel.cpp File Reference

```

#include <cassert>
#include <sstream>
#include <stdair/bom/BomKeyManager.hpp>
#include <stdair/bom/BookingClassKey.hpp>
#include <stdair/bom/BookingRequestStruct.hpp>
#include <stdair/bom/TravelSolutionStruct.hpp>
#include <stdair/bom/FareOptionStruct.hpp>
#include <stdair/service/Logger.hpp>
#include <travelccm/bom/PriceOrientedModel.hpp>

```

Namespaces

- namespace TRAVELCCM

23.26 PriceOrientedModel.cpp

```

00001 // //////////////////////////////////////
00002 // Import section
00003 // //////////////////////////////////////
00004 // STL
00005 #include <cassert>
00006 #include <sstream>
00007 // StdAir
00008 #include <stdair/bom/BomKeyManager.hpp>
00009 #include <stdair/bom/BookingClassKey.hpp>
00010 #include <stdair/bom/BookingRequestStruct.hpp>
00011 #include <stdair/bom/TravelSolutionStruct.hpp>
00012 #include <stdair/bom/FareOptionStruct.hpp>
00013 #include <stdair/service/Logger.hpp>
00014 // TravelCCM
00015 #include <travelccm/bom/PriceOrientedModel.hpp>
00016 >
00017 namespace TRAVELCCM {
00018
00019     // //////////////////////////////////////
00020     const stdair::TravelSolutionStruct* PriceOrientedModel::
00021     chooseTravelSolution (stdair::TravelSolutionList_T&
00022     ioTSList,
00023     const stdair::BookingRequestStruct& iBookingRequest) {
00024     stdair::TravelSolutionStruct* oChosenTS_ptr = NULL;
00025
00026     // Retrieve the number of passengers
00027     const stdair::NbOfSeats_T& lPartySize = iBookingRequest.getPartySize();
00028
00029     // Retrieve the Willingness-to-Pay (WTP) of the customer
00030     const stdair::WTP_T& lWTP = iBookingRequest.getWTP();
00031
00032     // Browse the travel solution list and choose the cheapest one
00033     stdair::Fare_T lLowestFare = std::numeric_limits<stdair::Fare_T>::max();
00034     for (stdair::TravelSolutionList_T::iterator itTS = ioTSList.begin();
00035          itTS != ioTSList.end(); ++itTS) {
00036         stdair::TravelSolutionStruct& lTS = *itTS;
00037
00038         // Browse the fare options
00039         const stdair::FareOptionList_T& lFOList = lTS.getFareOptionList();
00040         for (stdair::FareOptionList_T::const_iterator itFO = lFOList.begin();
00041              itFO != lFOList.end(); ++itFO) {
00042             const stdair::FareOptionStruct& lFO = *itFO;
00043
00044             // Choose the current fare option and the current solution
00045             // if the current fare is lower than the current lowest fare.
00046             const stdair::Fare_T& lFOFare = lFO.getFare();
00047             const stdair::Availability_T& lFOAvl = lFO.getAvailability();
00048
00049             if (lFOFare < lLowestFare && lFOFare <= lWTP && lFOAvl >= lPartySize) {
00050                 // DEBUG
00051                 /*
00052                 STDAIR_LOG_DEBUG ("The travel solution (TS) '" << lTS
00053                 << "' is chosen because its fare (" << lFOFare
00054                 << ") is lower than the lowest fare (" <<
00055                 lLowestFare
00056                 << ") and than the WTP (" << lWTP
00057                 << "), and because the party size (" << lPartySize
00058                 << ") is lower than the availability (" << lFOAvl
00059                 << ")");
00060                 */
00061                 lLowestFare = lFOFare;
00062                 oChosenTS_ptr = &lTS;
00063                 oChosenTS_ptr->setChosenFareOption (lFO);
00064             } else {
00065                 // DEBUG
00066                 /*
00067                 STDAIR_LOG_DEBUG ("The travel solution (TS) '" << lTS
00068                 << "' is not chosen because either its fare ("
00069                 << lFOFare << ") is greater than the lowest fare ("
00070                 << lLowestFare << ") or than the WTP (" << lWTP
00071                 << "), or because the party size (" << lPartySize
00072                 << ") is greater than the availability (" << lFOAvl
00073                 << ")");
00074                 */

```

```

00075         */
00076     }
00077 }
00078 }
00079
00080     return oChosenTS_ptr;
00081 }
00082
00083 }
```

23.27 travelccm/bom/PriceOrientedModel.hpp File Reference

```

#include <stdair/stdair_service_types.hpp>
#include <stdair/bom/TravelSolutionTypes.hpp>
```

Classes

- class [TRAVELCCM::PriceOrientedModel](#)

Namespaces

- namespace [stdair](#)
Forward declarations.
- namespace [TRAVELCCM](#)

23.28 PriceOrientedModel.hpp

```

00001 #ifndef __TRAVELCCM_BOM_PRICEORIENTEDMODEL_HPP
00002 #define __TRAVELCCM_BOM_PRICEORIENTEDMODEL_HPP
00003
00004 // //////////////////////////////////////
00005 // Import section
00006 // //////////////////////////////////////
00007 // StdAir
00008 #include <stdair/stdair_service_types.hpp>
00009 #include <stdair/bom/TravelSolutionTypes.hpp>
00010
00012 namespace stdair {
00013     struct BookingRequestStruct;
00014 }
00015
00016 namespace TRAVELCCM {
00017
00021     class PriceOrientedModel {
00022     public:
00030         static const stdair::TravelSolutionStruct*
00031         chooseTravelSolution (stdair::TravelSolutionList_T&,
00032                             const stdair::BookingRequestStruct&);
00033     };
00034 }
00035 #endif // __TRAVELCCM_BOM_PRICEORIENTEDMODEL_HPP
```

23.29 travelccm/command/ChoiceManager.cpp File Reference

```

#include <cassert>
#include <stdair/bom/TravelSolutionStruct.hpp>
#include <stdair/bom/BookingRequestStruct.hpp>
#include <travelccm/bom/PriceOrientedModel.hpp>
#include <travelccm/command/ChoiceManager.hpp>
```

Namespaces

- namespace [TRAVELCCM](#)

23.30 ChoiceManager.cpp

```

00001 // //////////////////////////////////////
00002 // Import section
00003 // //////////////////////////////////////
00004 // STL
00005 #include <cassert>
00006 // StdAir
00007 #include <stdair/bom/TravelSolutionStruct.hpp>
00008 #include <stdair/bom/BookingRequestStruct.hpp>
00009 // TravelCCM
00010 #include <travelccm/bom/PriceOrientedModel.hpp>
00011 #include <travelccm/command/ChoiceManager.hpp>
00012
00013 namespace TRAVELCCM {
00014
00015     // //////////////////////////////////////
00016     const stdair::TravelSolutionStruct* ChoiceManager::
00017     chooseTravelSolution (stdair::TravelSolutionList_T&
00018     ioTravelSolutionList,
00019     const stdair::BookingRequestStruct& iBookingRequest) {
00020         // Return the cheapest solution.
00021         const stdair::TravelSolutionStruct* oTravelSolution_ptr =
00022         PriceOrientedModel::chooseTravelSolution
00023         (ioTravelSolutionList,
00024         iBookingRequest);
00025         return oTravelSolution_ptr;
00026     }
00027 }

```

23.31 travelccm/command/ChoiceManager.hpp File Reference

```

#include <stdair/stdair_service_types.hpp>
#include <stdair/bom/TravelSolutionTypes.hpp>

```

Classes

- class [TRAVELCCM::ChoiceManager](#)

Namespaces

- namespace [stdair](#)
Forward declarations.
- namespace [TRAVELCCM](#)

23.32 ChoiceManager.hpp

```

00001 #ifndef __TRAVELCCM_CMD_CHOICEMANAGER_HPP
00002 #define __TRAVELCCM_CMD_CHOICEMANAGER_HPP
00003
00004 // //////////////////////////////////////
00005 // Import section
00006 // //////////////////////////////////////
00007 // StdAir
00008 #include <stdair/stdair_service_types.hpp>
00009 #include <stdair/bom/TravelSolutionTypes.hpp>
00010
00011 namespace stdair {
00012     struct BookingRequestStruct;
00013 }
00014
00015

```

```

00016 namespace TRAVELCCM {
00017
00021     class ChoiceManager {
00022     public:
00030         static const stdair::TravelSolutionStruct*
00031         chooseTravelSolution (stdair::TravelSolutionList_T&,
00032                             const stdair::BookingRequestStruct&);
00033     };
00034 }
00035 #endif // __TRAVELCCM_CMD_CHOICEMANAGER_HPP

```

23.33 travelccm/command/CmdAbstract.cpp File Reference

```
#include <travelccm/command/CmdAbstract.hpp>
```

Namespaces

- namespace [TRAVELCCM](#)

23.34 CmdAbstract.cpp

```

00001 // //////////////////////////////////////
00002 // Import section
00003 // //////////////////////////////////////
00004 // TRAVELCCM
00005 #include <travelccm/command/CmdAbstract.hpp>
00006
00007 namespace TRAVELCCM {
00008
00009 }

```

23.35 travelccm/command/CmdAbstract.hpp File Reference

Classes

- class [TRAVELCCM::CmdAbstract](#)

Namespaces

- namespace [TRAVELCCM](#)

23.36 CmdAbstract.hpp

```

00001 #ifndef __TRAVELCCM_CMD_CMDABSTRACT_HPP
00002 #define __TRAVELCCM_CMD_CMDABSTRACT_HPP
00003
00004 // //////////////////////////////////////
00005 // Import section
00006 // //////////////////////////////////////
00007
00008 namespace TRAVELCCM {
00009
00011     class CmdAbstract {
00012     public:
00013
00014     };
00015
00016 }
00017 #endif // __TRAVELCCM_CMD_CMDABSTRACT_HPP

```

23.37 travelccm/command/FileMgr.cpp File Reference

```
#include <cassert>
#include <fstream>
#include <stdair/service/Logger.hpp>
#include <travelccm/command/FileMgr.hpp>
```

Namespaces

- namespace [TRAVELCCM](#)

23.38 FileMgr.cpp

```
00001 // //////////////////////////////////////
00002 // Import section
00003 // //////////////////////////////////////
00004 // STL
00005 #include <cassert>
00006 #include <fstream>
00007 // StdAir
00008 #include <stdair/service/Logger.hpp>
00009 // TRAVEL-CCM
00010 #include <travelccm/command/FileMgr.hpp>
00011
00012 namespace TRAVELCCM {
00013
00014 }
```

23.39 travelccm/command/FileMgr.hpp File Reference

```
#include <string>
```

Classes

- class [TRAVELCCM::FileMgr](#)

Namespaces

- namespace [TRAVELCCM](#)

23.40 FileMgr.hpp

```
00001 #ifndef __TRAVELCCM_CMD_FILEMGR_HPP
00002 #define __TRAVELCCM_CMD_FILEMGR_HPP
00003
00004 // //////////////////////////////////////
00005 // Import section
00006 // //////////////////////////////////////
00007 #include <string>
00008
00009 namespace TRAVELCCM {
00010
00011     class TravelSolutionHolder;
00012
00015     class FileMgr {
00016     public:
00017
00018     };
00019 }
00020 #endif // __TRAVELCCM_CMD_FILEMGR_HPP
```

23.41 travelccm/config/travelccm-paths.hpp File Reference

Macros

- `#define PACKAGE "travelccm"`
- `#define PACKAGE_NAME "TRAVELCCM"`
- `#define PACKAGE_VERSION "0.5.3"`
- `#define PREFIXDIR "/usr"`
- `#define EXEC_PREFIX "/usr"`
- `#define BINDIR "/usr/bin"`
- `#define LIBDIR "/usr/lib"`
- `#define LIBEXECDIR "/usr/libexec"`
- `#define SBINDIR "/usr/sbin"`
- `#define SYSCONFDIR "/usr/etc"`
- `#define INCLUDEDIR "/usr/include"`
- `#define DATAROOTDIR "/usr/share"`
- `#define DATADIR "/usr/share"`
- `#define DOCDIR "/usr/share/doc/travelccm-0.5.3"`
- `#define MANDIR "/usr/share/man"`
- `#define INFODIR "/usr/share/info"`
- `#define HTMLDIR "/usr/share/doc/travelccm-0.5.3/html"`
- `#define PDFDIR "/usr/share/doc/travelccm-0.5.3/html"`
- `#define STDAIR_SAMPLE_DIR "/usr/share/stdair/samples"`

23.41.1 Macro Definition Documentation

23.41.1.1 `#define PACKAGE "travelccm"`

Definition at line 4 of file [travelccm-paths.hpp](#).

23.41.1.2 `#define PACKAGE_NAME "TRAVELCCM"`

Definition at line 5 of file [travelccm-paths.hpp](#).

23.41.1.3 `#define PACKAGE_VERSION "0.5.3"`

Definition at line 6 of file [travelccm-paths.hpp](#).

23.41.1.4 `#define PREFIXDIR "/usr"`

Definition at line 7 of file [travelccm-paths.hpp](#).

23.41.1.5 `#define EXEC_PREFIX "/usr"`

Definition at line 8 of file [travelccm-paths.hpp](#).

23.41.1.6 `#define BINDIR "/usr/bin"`

Definition at line 9 of file [travelccm-paths.hpp](#).

23.41.1.7 `#define LIBDIR "/usr/lib"`

Definition at line 10 of file [travelccm-paths.hpp](#).

23.41.1.8 `#define LIBEXECDIR "/usr/libexec"`

Definition at line 11 of file [travelccm-paths.hpp](#).

23.41.1.9 `#define SBINDIR "/usr/sbin"`

Definition at line 12 of file [travelccm-paths.hpp](#).

23.41.1.10 `#define SYSCONFDIR "/usr/etc"`

Definition at line 13 of file [travelccm-paths.hpp](#).

23.41.1.11 `#define INCLUDEDIR "/usr/include"`

Definition at line 14 of file [travelccm-paths.hpp](#).

23.41.1.12 `#define DATAROOTDIR "/usr/share"`

Definition at line 15 of file [travelccm-paths.hpp](#).

23.41.1.13 `#define DATADIR "/usr/share"`

Definition at line 16 of file [travelccm-paths.hpp](#).

23.41.1.14 `#define DOCDIR "/usr/share/doc/travelccm-0.5.3"`

Definition at line 17 of file [travelccm-paths.hpp](#).

23.41.1.15 `#define MANDIR "/usr/share/man"`

Definition at line 18 of file [travelccm-paths.hpp](#).

23.41.1.16 `#define INFODIR "/usr/share/info"`

Definition at line 19 of file [travelccm-paths.hpp](#).

23.41.1.17 `#define HTMLDIR "/usr/share/doc/travelccm-0.5.3/html"`

Definition at line 20 of file [travelccm-paths.hpp](#).

23.41.1.18 `#define PDFDIR "/usr/share/doc/travelccm-0.5.3/html"`

Definition at line 21 of file [travelccm-paths.hpp](#).

23.41.1.19 `#define STDAIR_SAMPLE_DIR "/usr/share/stdair/samples"`

Definition at line 22 of file [travelccm-paths.hpp](#).

23.42 travelccm-paths.hpp

```
00001 #ifndef __TRAVELCCM_PATHS_HPP__
00002 #define __TRAVELCCM_PATHS_HPP__
00003
00004 #define PACKAGE "travelccm"
00005 #define PACKAGE_NAME "TRAVELCCM"
00006 #define PACKAGE_VERSION "0.5.3"
00007 #define PREFIXDIR "/usr"
00008 #define EXEC_PREFIX "/usr"
00009 #define BINDIR "/usr/bin"
00010 #define LIBDIR "/usr/lib"
00011 #define LIBEXECDIR "/usr/libexec"
00012 #define SBINDIR "/usr/sbin"
00013 #define SYSCONFDIR "/usr/etc"
00014 #define INCLUDEDIR "/usr/include"
00015 #define DATAROOTDIR "/usr/share"
00016 #define DATADIR "/usr/share"
00017 #define DOCDIR "/usr/share/doc/travelccm-0.5.3"
00018 #define MANDIR "/usr/share/man"
00019 #define INFODIR "/usr/share/info"
00020 #define HTMLDIR "/usr/share/doc/travelccm-0.5.3/html"
00021 #define PDFDIR "/usr/share/doc/travelccm-0.5.3/html"
```



```
00022 #define STDAIR_SAMPLE_DIR "/usr/share/stdair/samples"
00023
00024 #endif // __TRAVELCCM_PATHS_HPP__
```

23.43 travelccm/config/travelccm-paths.hpp.in File Reference

Macros

- #define [__TRAVELCCM_PATHS_HPP__](#)
- #define [PACKAGE](#) "@PACKAGE@"
- #define [PACKAGE_NAME](#) "@PACKAGE_NAME@"
- #define [PACKAGE_VERSION](#) "@PACKAGE_VERSION@"
- #define [PREFIXDIR](#) "@prefix@"
- #define [EXEC_PREFIX](#) "@exec_prefix@"
- #define [BINDIR](#) "@bindir@"
- #define [LIBDIR](#) "@libdir@"
- #define [LIBEXECDIR](#) "@libexecdir@"
- #define [SBINDIR](#) "@sbindir@"
- #define [SYSCONFDIR](#) "@sysconfdir@"
- #define [INCLUDEDIR](#) "@includedir@"
- #define [DATAROOTDIR](#) "@datarootdir@"
- #define [DATADIR](#) "@datadir@"
- #define [DOCDIR](#) "@docdir@"
- #define [MANDIR](#) "@mandir@"
- #define [INFODIR](#) "@infodir@"
- #define [HTMLDIR](#) "@htmldir@"
- #define [PDFDIR](#) "@pdfdir@"
- #define [STDAIR_SAMPLE_DIR](#) "@sampledir@"

23.43.1 Macro Definition Documentation

23.43.1.1 #define [__TRAVELCCM_PATHS_HPP__](#)

Definition at line 2 of file [travelccm-paths.hpp.in](#).

23.43.1.2 #define [PACKAGE](#) "@PACKAGE@"

Definition at line 4 of file [travelccm-paths.hpp.in](#).

23.43.1.3 #define [PACKAGE_NAME](#) "@PACKAGE_NAME@"

Definition at line 5 of file [travelccm-paths.hpp.in](#).

23.43.1.4 #define [PACKAGE_VERSION](#) "@PACKAGE_VERSION@"

Definition at line 6 of file [travelccm-paths.hpp.in](#).

23.43.1.5 #define [PREFIXDIR](#) "@prefix@"

Definition at line 7 of file [travelccm-paths.hpp.in](#).

23.43.1.6 #define [EXEC_PREFIX](#) "@exec_prefix@"

Definition at line 8 of file [travelccm-paths.hpp.in](#).

23.43.1.7 #define [BINDIR](#) "@bindir@"

Definition at line 9 of file [travelccm-paths.hpp.in](#).

23.43.1.8 `#define LIBDIR "@libdir@"`

Definition at line 10 of file [travelccm-paths.hpp.in](#).

23.43.1.9 `#define LIBEXECDIR "@libexecdir@"`

Definition at line 11 of file [travelccm-paths.hpp.in](#).

23.43.1.10 `#define SBINDIR "@sbindir@"`

Definition at line 12 of file [travelccm-paths.hpp.in](#).

23.43.1.11 `#define SYSCONFDIR "@sysconfdir@"`

Definition at line 13 of file [travelccm-paths.hpp.in](#).

23.43.1.12 `#define INCLUDEDIR "@includedir@"`

Definition at line 14 of file [travelccm-paths.hpp.in](#).

23.43.1.13 `#define DATAROOTDIR "@datarootdir@"`

Definition at line 15 of file [travelccm-paths.hpp.in](#).

23.43.1.14 `#define DATADIR "@datadir@"`

Definition at line 16 of file [travelccm-paths.hpp.in](#).

23.43.1.15 `#define DOCDIR "@docdir@"`

Definition at line 17 of file [travelccm-paths.hpp.in](#).

23.43.1.16 `#define MANDIR "@mandir@"`

Definition at line 18 of file [travelccm-paths.hpp.in](#).

23.43.1.17 `#define INFODIR "@infodir@"`

Definition at line 19 of file [travelccm-paths.hpp.in](#).

23.43.1.18 `#define HTMLDIR "@htmldir@"`

Definition at line 20 of file [travelccm-paths.hpp.in](#).

23.43.1.19 `#define PDFDIR "@pdfdir@"`

Definition at line 21 of file [travelccm-paths.hpp.in](#).

23.43.1.20 `#define STDAIR_SAMPLE_DIR "@sampledir@"`

Definition at line 22 of file [travelccm-paths.hpp.in](#).

23.44 travelccm-paths.hpp.in

```
00001 #ifndef __TRAVELCCM_PATHS_HPP__
00002 #define __TRAVELCCM_PATHS_HPP__
00003
00004 #define PACKAGE "@PACKAGE@"
00005 #define PACKAGE_NAME "@PACKAGE_NAME@"
00006 #define PACKAGE_VERSION "@PACKAGE_VERSION@"
00007 #define PREFIXDIR "@prefix@"
00008 #define EXEC_PREFIX "@exec_prefix@"
00009 #define BINDIR "@bindir@"
00010 #define LIBDIR "@libdir@"
```

```

00011 #define LIBEXECDIR "@libexecdir@"
00012 #define SBINDIR "@sbindir@"
00013 #define SYSCONFDIR "@sysconfdir@"
00014 #define INCLUDEDIR "@includedir@"
00015 #define DATAROOTDIR "@datarootdir@"
00016 #define DATADIR "@datadir@"
00017 #define DOCDIR "@docdir@"
00018 #define MANDIR "@mandir@"
00019 #define INFODIR "@infodir@"
00020 #define HTMLEDIR "@htmldir@"
00021 #define PDFDIR "@pdfdir@"
00022 #define STDAIR_SAMPLE_DIR "@sampledir@"
00023
00024 #endif // __TRAVELCCM_PATHS_HPP__

```

23.45 travelccm/factory/FacTRAVELCCMServiceContext.cpp File Reference

```

#include <cassert>
#include <stdair/service/FacSupervisor.hpp>
#include <travelccm/factory/FacTRAVELCCMServiceContext.hpp>
#include <travelccm/service/TRAVELCCM_ServiceContext.hpp>

```

Namespaces

- namespace [TRAVELCCM](#)

23.46 FacTRAVELCCMServiceContext.cpp

```

00001 // //////////////////////////////////////
00002 // Import section
00003 // //////////////////////////////////////
00004 // STL
00005 #include <cassert>
00006 // StdAir
00007 #include <stdair/service/FacSupervisor.hpp>
00008 // TravelCCM
00009 #include <travelccm/factory/FacTRAVELCCMServiceContext.hpp>
00010 #include <travelccm/service/TRAVELCCM_ServiceContext.hpp>
00011
00012 namespace TRAVELCCM {
00013
00014     FacTRAVELCCMServiceContext* FacTRAVELCCMServiceContext::_instance = NULL;
00015
00016     // //////////////////////////////////////
00017     FacTRAVELCCMServiceContext::~FacTRAVELCCMServiceContext
00018     () {
00019         _instance = NULL;
00020     }
00021
00022     // //////////////////////////////////////
00023     FacTRAVELCCMServiceContext&
00024     FacTRAVELCCMServiceContext::instance () {
00025
00026         if (_instance == NULL) {
00027             _instance = new FacTRAVELCCMServiceContext();
00028             assert (_instance != NULL);
00029
00030             stdair::FacSupervisor::instance().
00031             registerServiceFactory (_instance);
00032         }
00033         return *_instance;
00034     }
00035
00036     // //////////////////////////////////////
00037     TRAVELCCM_ServiceContext&
00038     FacTRAVELCCMServiceContext::create () {
00039         TRAVELCCM_ServiceContext* aServiceContext_ptr =
00040         NULL;
00041
00042         aServiceContext_ptr = new TRAVELCCM_ServiceContext
00043         ();
00044         assert (aServiceContext_ptr != NULL);
00045     }

```

```

00040     // The new object is added to the Bom pool
00041     _pool.push_back (aServiceContext_ptr);
00042
00043     return *aServiceContext_ptr;
00044 }
00045
00046 }

```

23.47 travelccm/factory/FacTRAVELCCMSERVICECONTEXT.hpp File Reference

```

#include <stdair/service/FacServiceAbstract.hpp>
#include <travelccm/TRAVELCCM_Types.hpp>

```

Classes

- class [TRAVELCCM::FacTRAVELCCMSERVICECONTEXT](#)

Namespaces

- namespace [TRAVELCCM](#)

23.48 FacTRAVELCCMSERVICECONTEXT.hpp

```

00001 #ifndef __TRAVELCCM_FAC_FACTRAVELCCMSERVICECONTEXT_HPP
00002 #define __TRAVELCCM_FAC_FACTRAVELCCMSERVICECONTEXT_HPP
00003
00004 // //////////////////////////////////////
00005 // Import section
00006 // //////////////////////////////////////
00007 // StdAir
00008 #include <stdair/service/FacServiceAbstract.hpp>
00009 // TravelCCM
00010 #include <travelccm/TRAVELCCM_Types.hpp>
00011
00012 namespace TRAVELCCM {
00013
00014     class TRAVELCCM_ServiceContext;
00015
00016     class FacTRAVELCCMSERVICECONTEXT : public
00017         stdair::FacServiceAbstract {
00018     public:
00019
00020         static FacTRAVELCCMSERVICECONTEXT& instance
00021         ();
00022
00023         ~FacTRAVELCCMSERVICECONTEXT ();
00024
00025         TRAVELCCM_ServiceContext& create ();
00026
00027     protected:
00028         FacTRAVELCCMSERVICECONTEXT () {}
00029
00030     private:
00031         static FacTRAVELCCMSERVICECONTEXT* _instance;
00032     };
00033 }
00034
00035 #endif // __TRAVELCCM_FAC_FACTRAVELCCMSERVICECONTEXT_HPP

```

23.49 travelccm/service/TRAVELCCM_Service.cpp File Reference

```

#include <cassert>
#include <boost/make_shared.hpp>
#include <stdair/basic/BasChronometer.hpp>
#include <stdair/basic/BasFileMgr.hpp>
#include <stdair/bom/BomManager.hpp>
#include <stdair/bom/BookingRequestStruct.hpp>
#include <stdair/factory/FacBomManager.hpp>
#include <stdair/service/Logger.hpp>
#include <stdair/STDAIR_Service.hpp>
#include <travelccm/factory/FacTRAVELCCMSERVICEContext.hpp>
#include <travelccm/command/ChoiceManager.hpp>
#include <travelccm/service/TRAVELCCM_ServiceContext.hpp>
#include <travelccm/TRAVELCCM_Service.hpp>

```

Namespaces

- namespace [TRAVELCCM](#)

23.50 TRAVELCCM_Service.cpp

```

00001 // //////////////////////////////////////
00002 // Import section
00003 // //////////////////////////////////////
00004 // STL
00005 #include <cassert>
00006 // Boost
00007 #include <boost/make_shared.hpp>
00008 // StdAir
00009 #include <stdair/basic/BasChronometer.hpp>
00010 #include <stdair/basic/BasFileMgr.hpp>
00011 #include <stdair/bom/BomManager.hpp>
00012 #include <stdair/bom/BookingRequestStruct.hpp>
00013 #include <stdair/factory/FacBomManager.hpp>
00014 #include <stdair/service/Logger.hpp>
00015 #include <stdair/STDAIR_Service.hpp>
00016 // TravelCCM
00017 #include <travelccm/factory/FacTRAVELCCMSERVICEContext.hpp>
00018 >
00018 #include <travelccm/command/ChoiceManager.hpp>
00019 >
00019 #include <travelccm/service/TRAVELCCM_ServiceContext.hpp>
00020 >
00020 #include <travelccm/TRAVELCCM_Service.hpp>
00021
00022 namespace TRAVELCCM {
00023
00024 // //////////////////////////////////////
00025 TRAVELCCM_Service::TRAVELCCM_Service() : _travelccmServiceContext (NULL) {
00026     assert (false);
00027 }
00028
00029 // //////////////////////////////////////
00030 TRAVELCCM_Service::TRAVELCCM_Service (const TRAVELCCM_Service& iService)
00031 : _travelccmServiceContext (NULL) {
00032     assert (false);
00033 }
00034
00035 // //////////////////////////////////////
00036 TRAVELCCM_Service::TRAVELCCM_Service (const stdair::BasLogParams& iLogParams,
00037                                         const stdair::BasDBParams& iDBParams)
00038 : _travelccmServiceContext (NULL) {
00039
00040     // Initialise the STDAIR service handler
00041     stdair::STDAIR_ServicePtr_T lSTDAIR_Service_ptr =
00042         initStdAirService (iLogParams, iDBParams);
00043
00044     // Initialise the service context
00045     initServiceContext();
00046
00047     // Add the StdAir service context to the AIRINV service context
00048     // \note AIRINV owns the STDAIR service resources here.

```

```

00049     const bool ownStdairService = true;
00050     addStdAirService (lSTDAIR_Service_ptr, ownStdairService);
00051
00052     // Initialise the (remaining of the) context
00053     initTravelCCMService();
00054 }
00055
00056 // //////////////////////////////////////
00057 TRAVELCCM_Service::TRAVELCCM_Service (const stdair::BasLogParams& iLogParams)
00058     : _travelccmServiceContext (NULL) {
00059
00060     // Initialise the STDAIR service handler
00061     stdair::STDAIR_ServicePtr_T lSTDAIR_Service_ptr =
00062         initStdAirService (iLogParams);
00063
00064     // Initialise the service context
00065     initServiceContext();
00066
00067     // Add the StdAir service context to the AIRINV service context
00068     // \note AIRINV owns the STDAIR service resources here.
00069     const bool ownStdairService = true;
00070     addStdAirService (lSTDAIR_Service_ptr, ownStdairService);
00071
00072     // Initialise the (remaining of the) context
00073     initTravelCCMService();
00074 }
00075
00076 // //////////////////////////////////////
00077 TRAVELCCM_Service::
00078 TRAVELCCM_Service (stdair::STDAIR_ServicePtr_T ioSTDAIR_Service_ptr)
00079     : _travelccmServiceContext (NULL) {
00080
00081     // Initialise the service context
00082     initServiceContext();
00083
00084     // Store the STDAIR service object within the (AIRINV) service context
00085     // \note AirInv does not own the STDAIR service resources here.
00086     const bool doesNotOwnStdairService = false;
00087     addStdAirService (ioSTDAIR_Service_ptr, doesNotOwnStdairService);
00088
00089     // Initialise the (remaining of the) context
00090     initTravelCCMService();
00091 }
00092
00093 // //////////////////////////////////////
00094 TRAVELCCM_Service::~TRAVELCCM_Service()
00095 {
00096     // Delete/Clean all the objects from memory
00097     finalise();
00098 }
00099
00100 // //////////////////////////////////////
00101 void TRAVELCCM_Service::finalise() {
00102     assert (_travelccmServiceContext != NULL);
00103     // Reset the (Boost.)Smart pointer pointing on the STDAIR_Service object.
00104     _travelccmServiceContext->reset();
00105 }
00106
00107 // //////////////////////////////////////
00108 void TRAVELCCM_Service::initServiceContext() {
00109     // Initialise the context
00110     TRAVELCCM_ServiceContext& lTRAVELCCM_ServiceContext =
00111         FacTRAVELCCMServiceContext::instance(
00112         ).create();
00113     _travelccmServiceContext = &lTRAVELCCM_ServiceContext;
00114 }
00115
00116 // //////////////////////////////////////
00117 void TRAVELCCM_Service::
00118 addStdAirService (stdair::STDAIR_ServicePtr_T ioSTDAIR_Service_ptr,
00119                 const bool iOwnStdairService) {
00120     // Retrieve the Travelccm service context
00121     assert (_travelccmServiceContext != NULL);
00122     TRAVELCCM_ServiceContext& lTRAVELCCM_ServiceContext =
00123         *_travelccmServiceContext;
00124
00125     // Store the STDAIR service object within the (TRAVELCCM) service context
00126     lTRAVELCCM_ServiceContext.setSTDAIR_Service (ioSTDAIR_Service_ptr,
00127                                                  iOwnStdairService);
00128 }
00129
00130 // //////////////////////////////////////
00131 stdair::STDAIR_ServicePtr_T TRAVELCCM_Service::
00132 initStdAirService (const stdair::BasLogParams& iLogParams,
00133                  const stdair::BasDBParams& iDBParams) {
00134     stdair::STDAIR_ServicePtr_T oSTDAIR_Service_ptr =

```

```

00140         boost::make_shared<stdair::STDAIR_Service> (iLogParams, iDBParams);
00141         assert (oSTDAIR_Service_ptr != NULL);
00142
00143         return oSTDAIR_Service_ptr;
00144     }
00145
00146     // //////////////////////////////////////
00147     stdair::STDAIR_ServicePtr_T TRAVELCCM_Service::
00148     initStdAirService (const stdair::BasLogParams& iLogParams) {
00149
00150         stdair::STDAIR_ServicePtr_T oSTDAIR_Service_ptr =
00151             boost::make_shared<stdair::STDAIR_Service> (iLogParams);
00152         assert (oSTDAIR_Service_ptr != NULL);
00153
00154         return oSTDAIR_Service_ptr;
00155     }
00156
00157     // //////////////////////////////////////
00158     void TRAVELCCM_Service::initTravelCCMService() {
00159         // Do nothing at this stage. A sample BOM tree may be built by
00160         // calling the buildSampleBom() method
00161     }
00162
00163     // //////////////////////////////////////
00164     void TRAVELCCM_Service::buildSampleBom() {
00165         // Retrieve the TravelCCM service context
00166         if (_travelccmServiceContext == NULL) {
00167             throw stdair::NonInitialisedServiceException ("The TravelCCM service has
00168 "
00169 "not been initialised");
00170         }
00171         assert (_travelccmServiceContext != NULL);
00172
00173         // Retrieve the TravelCCM service context and whether it owns the Stdair
00174         // service
00175         TRAVELCCM_ServiceContext& lTRAVELCCM_ServiceContext
00176         =
00177             *_travelccmServiceContext;
00178         const bool doesOwnStdairService =
00179             lTRAVELCCM_ServiceContext.getOwnStdairServiceFlag();
00180
00181         // Retrieve the StdAir service object from the (TravelCCM) service context
00182         stdair::STDAIR_Service& lSTDAIR_Service =
00183             lTRAVELCCM_ServiceContext.getSTDAIR_Service();
00184
00185         if (doesOwnStdairService == true) {
00186             //
00187             lSTDAIR_Service.buildSampleBom();
00188         }
00189     }
00190
00191     // //////////////////////////////////////
00192     void TRAVELCCM_Service::
00193     buildSampleTravelSolutions (
00194         stdair::TravelSolutionList_T& ioTSList) {
00195
00196         // Retrieve the TRAVELCCM service context
00197         if (_travelccmServiceContext == NULL) {
00198             throw stdair::NonInitialisedServiceException ("The Travelccm service has
00199 "
00200 "not been initialised");
00201         }
00202         assert (_travelccmServiceContext != NULL);
00203
00204         TRAVELCCM_ServiceContext& lTRAVELCCM_ServiceContext
00205         =
00206             *_travelccmServiceContext;
00207
00208         // Retrieve the STDAIR service object from the (TRAVELCCM) service context
00209         stdair::STDAIR_Service& lSTDAIR_Service =
00210             lTRAVELCCM_ServiceContext.getSTDAIR_Service();
00211
00212         // Delegate the BOM building to the dedicated service
00213         lSTDAIR_Service.buildSampleTravelSolutions (ioTSList);
00214     }
00215
00216     // //////////////////////////////////////
00217     stdair::BookingRequestStruct TRAVELCCM_Service::
00218     buildSampleBookingRequest (const bool isForCRS) {
00219
00220         // Retrieve the TRAVELCCM service context
00221         if (_travelccmServiceContext == NULL) {
00222             throw stdair::NonInitialisedServiceException ("The Travelccm service has
00223 "
00224 "not been initialised");

```

```

00245     }
00246     assert (_travelccmServiceContext != NULL);
00247
00248     TRAVELCCM_ServiceContext& lTRAVELCCM_ServiceContext
00249 =
00250     *_travelccmServiceContext;
00251
00252     // Retrieve the STDAIR service object from the (TRAVELCCM) service context
00253     stdair::STDAIR_Service& lSTDAIR_Service =
00254     lTRAVELCCM_ServiceContext.getSTDAIR_Service();
00255
00256     // Delegate the BOM building to the dedicated service
00257     return lSTDAIR_Service.buildSampleBookingRequest (isForCRS);
00258 }
00259
00260 // //////////////////////////////////////
00261 std::string TRAVELCCM_Service::csvDisplay()
00262 const {
00263     // Retrieve the TRAVELCCM service context
00264     if (_travelccmServiceContext == NULL) {
00265         throw stdair::NonInitialisedServiceException ("The TravelccmMaster
00266 service"
00267 " has not been initialised"
00268 );
00269     }
00270     assert (_travelccmServiceContext != NULL);
00271
00272     TRAVELCCM_ServiceContext& lTRAVELCCM_ServiceContext
00273 =
00274     *_travelccmServiceContext;
00275
00276     // Retrieve the STDAIR service object from the (TRAVELCCM) service context
00277     stdair::STDAIR_Service& lSTDAIR_Service =
00278     lTRAVELCCM_ServiceContext.getSTDAIR_Service();
00279
00280     // Delegate the BOM building to the dedicated service
00281     return lSTDAIR_Service.csvDisplay();
00282 }
00283
00284 // //////////////////////////////////////
00285 std::string TRAVELCCM_Service::
00286 csvDisplay (const stdair::TravelSolutionList_T&
00287 iTravelSolutionList) const {
00288     // Retrieve the TRAVELCCM service context
00289     if (_travelccmServiceContext == NULL) {
00290         throw stdair::NonInitialisedServiceException ("The TravelccmMaster
00291 service"
00292 " has not been initialised"
00293 );
00294     }
00295     assert (_travelccmServiceContext != NULL);
00296
00297     TRAVELCCM_ServiceContext& lTRAVELCCM_ServiceContext
00298 =
00299     *_travelccmServiceContext;
00300
00301     // Retrieve the STDAIR service object from the (TRAVELCCM) service context
00302     stdair::STDAIR_Service& lSTDAIR_Service =
00303     lTRAVELCCM_ServiceContext.getSTDAIR_Service();
00304
00305     // Delegate the BOM building to the dedicated service
00306     return lSTDAIR_Service.csvDisplay (iTravelSolutionList);
00307 }
00308
00309 // //////////////////////////////////////
00310 const stdair::TravelSolutionStruct* TRAVELCCM_Service::
00311 chooseTravelSolution (stdair::TravelSolutionList_T&
00312 iTravelSolutionList,
00313 const stdair::BookingRequestStruct& iBookingRequest) {
00314     const stdair::TravelSolutionStruct* oTravelSolution_ptr =
00315     ChoiceManager::chooseTravelSolution (
00316 iTravelSolutionList,
00317 iBookingRequest);
00318     return oTravelSolution_ptr;
00319 }
00320 }

```


23.51 travelccm/service/TRAVELCCM_ServiceContext.cpp File Reference

```
#include <cassert>
#include <sstream>
#include <travelccm/service/TRAVELCCM_ServiceContext.hpp>
```

Namespaces

- namespace [TRAVELCCM](#)

23.52 TRAVELCCM_ServiceContext.cpp

```
00001 // //////////////////////////////////////
00002 // Import section
00003 // //////////////////////////////////////
00004 // STL
00005 #include <cassert>
00006 #include <sstream>
00007 // TravelCCM Basic
00008 #include <travelccm/service/TRAVELCCM_ServiceContext.hpp>
00009
00010 namespace TRAVELCCM {
00011
00012 // //////////////////////////////////////
00013 TRAVELCCM_ServiceContext::TRAVELCCM_ServiceContext()
00014 : _ownStdairService (false) {
00015 }
00016
00017 // //////////////////////////////////////
00018 TRAVELCCM_ServiceContext::
00019 TRAVELCCM_ServiceContext (const TRAVELCCM_ServiceContext&) {
00020     assert (false);
00021 }
00022
00023 // //////////////////////////////////////
00024 TRAVELCCM_ServiceContext::~TRAVELCCM_ServiceContext() {
00025 }
00026
00027 // //////////////////////////////////////
00028 const std::string TRAVELCCM_ServiceContext::shortDisplay() const {
00029     std::ostringstream ostr;
00030     ostr << "TRAVELCCM_ServiceContext -- Owns StdAir service: "
00031         << _ownStdairService;
00032     return ostr.str();
00033 }
00034
00035 // //////////////////////////////////////
00036 const std::string TRAVELCCM_ServiceContext::display() const {
00037     std::ostringstream ostr;
00038     ostr << shortDisplay();
00039     return ostr.str();
00040 }
00041
00042 // //////////////////////////////////////
00043 const std::string TRAVELCCM_ServiceContext::describe() const {
00044     return shortDisplay();
00045 }
00046
00047 // //////////////////////////////////////
00048 void TRAVELCCM_ServiceContext::reset() {
00049     if (_ownStdairService == true) {
00050         _stdairService.reset();
00051     }
00052 }
00053
00054 }
```

23.53 travelccm/service/TRAVELCCM_ServiceContext.hpp File Reference

```
#include <string>
#include <boost/shared_ptr.hpp>
#include <stdair/stdair_service_types.hpp>
#include <stdair/service/ServiceAbstract.hpp>
#include <travelccm/TRAVELCCM_Types.hpp>
```

Classes

- class [TRAVELCCM::TRAVELCCM_ServiceContext](#)
Inner class holding the context for the TravelCCM Service object.

Namespaces

- namespace [TRAVELCCM](#)

23.54 TRAVELCCM_ServiceContext.hpp

```
00001 #ifndef __TRAVELCCM_SVC_TRAVELCCM_SERVICE_CONTEXT_HPP
00002 #define __TRAVELCCM_SVC_TRAVELCCM_SERVICE_CONTEXT_HPP
00003
00004 // //////////////////////////////////////
00005 // Import section
00006 // //////////////////////////////////////
00007 // STL
00008 #include <string>
00009 // Boost
00010 #include <boost/shared_ptr.hpp>
00011 // StdAir
00012 #include <stdair/stdair_service_types.hpp>
00013 #include <stdair/service/ServiceAbstract.hpp>
00014 // TravelCCM
00015 #include <travelccm/TRAVELCCM_Types.hpp>
00016
00017 namespace TRAVELCCM {
00018
00023     class TRAVELCCM_ServiceContext : public
stdair::ServiceAbstract {
00029         friend class TRAVELCCM_Service;
00030         friend class FacTRAVELCCMServiceContext;
00031
00032     private:
00033         // ////////////////////////////////////// Getters //////////////////////////////////////
00037         stdair::STDAIR_ServicePtr_T getSTDAIR_ServicePtr() const {
00038             return _stdairService;
00039         }
00040
00044         stdair::STDAIR_Service& getSTDAIR_Service() const {
00045             assert (_stdairService != NULL);
00046             return *_stdairService;
00047         }
00048
00052         const bool getOwnStdairServiceFlag() const {
00053             return _ownStdairService;
00054         }
00055
00056
00057         // ////////////////////////////////////// Setters //////////////////////////////////////
00061         void setSTDAIR_Service (stdair::STDAIR_ServicePtr_T ioSTDAIR_ServicePtr,
00062                                 const bool iOwnStdairService) {
00063             _stdairService = ioSTDAIR_ServicePtr;
00064             _ownStdairService = iOwnStdairService;
00065         }
00066
00067     private:
00069         // ////////////////////////////////////// Display Methods //////////////////////////////////////
00073         const std::string shortDisplay() const;
00074
00078         const std::string display() const;
00079
00083         const std::string describe() const;
```

```

00084
00085
00086     private:
00087
00088
00091         TRAVELCCM_ServiceContext();
00095         TRAVELCCM_ServiceContext (const TRAVELCCM_ServiceContext&);
00096
00100         ~TRAVELCCM_ServiceContext();
00101
00105         void reset();
00106
00107
00108     private:
00109         // //////////// Children ////////////
00113         stdair::STDAIR_ServicePtr_T _stdairService;
00114
00118         bool _ownStdairService;
00119     };
00120
00121 }
00122 #endif // __TRAVELCCM_SVC_TRAVELCCM_SERVICE_CONTEXT_HPP

```

23.55 travelccm/TRAVELCCM_Service.hpp File Reference

```

#include <stdair/stdair_basic_types.hpp>
#include <stdair/stdair_service_types.hpp>
#include <stdair/bom/TravelSolutionTypes.hpp>
#include <travelccm/TRAVELCCM_Types.hpp>

```

Classes

- class [TRAVELCCM::TRAVELCCM_Service](#)

Namespaces

- namespace [stdair](#)
Forward declarations.
- namespace [TRAVELCCM](#)

23.56 TRAVELCCM_Service.hpp

```

00001 #ifndef __TRAVELCCM_SVC_TRAVELCCM_SERVICE_HPP
00002 #define __TRAVELCCM_SVC_TRAVELCCM_SERVICE_HPP
00003
00004 // //////////////////////////////////////
00005 // Import section
00006 // //////////////////////////////////////
00007 // StdAir
00008 #include <stdair/stdair_basic_types.hpp>
00009 #include <stdair/stdair_service_types.hpp>
00010 #include <stdair/bom/TravelSolutionTypes.hpp>
00011 // TravelCCM
00012 #include <travelccm/TRAVELCCM_Types.hpp>
00013
00015 namespace stdair {
00016     class STDAIR_Service;
00017     struct BasLogParams;
00018     struct BasDBParams;
00019     struct BookingRequestStruct;
00020 }
00021
00022 namespace TRAVELCCM {
00023
00025     class TRAVELCCM_ServiceContext;
00026
00027
00031     class TRAVELCCM_Service {
00032     public:
00033         // //////////// Constructors and destructors ////////////
00049         TRAVELCCM_Service (const stdair::BasLogParams&, const

```

```

stdair::BasDBParams&);
00050
00062     TRAVELCCM_Service (const stdair::BasLogParams&);
00063
00079     TRAVELCCM_Service (stdair::STDAIR_ServicePtr_T);
00080
00084     ~TRAVELCCM_Service();
00085
00086
00087 public:
00088     // ////////// Business methods //////////
00092     void buildSampleBom();
00093
00112     void buildSampleTravelSolutions (
stdair::TravelSolutionList_T&);
00113
00142     stdair::BookingRequestStruct
00143     buildSampleBookingRequest (const bool isForCRS =
false);
00144
00159     const stdair::TravelSolutionStruct*
00160     chooseTravelSolution (stdair::TravelSolutionList_T&,
00161                          const stdair::BookingRequestStruct&);
00162
00163
00164 public:
00165     // ////////// Display support methods //////////
00173     std::string csvDisplay() const;
00174
00182     std::string csvDisplay (const stdair::TravelSolutionList_T&)
const;
00183
00184
00185 private:
00186     // ////////// Construction and Destruction helper methods //////////
00190     TRAVELCCM_Service();
00194     TRAVELCCM_Service (const TRAVELCCM_Service
&);
00195
00205     stdair::STDAIR_ServicePtr_T initStdAirService (const stdair::BasLogParams&,
00206                                                    const stdair::BasDBParams&);
00207
00216     stdair::STDAIR_ServicePtr_T initStdAirService (const stdair::BasLogParams&)
;
00217
00226     void addStdAirService (stdair::STDAIR_ServicePtr_T ioSTDAIR_ServicePtr,
00227                          const bool iOwnStdairService);
00228
00233     void initServiceContext();
00234
00241     void initTravelCCMService();
00242
00246     void finalise();
00247
00248 private:
00249     // ////////// Service Context //////////
00253     TRAVELCCM_ServiceContext* _travelccmServiceContext;
00254 };
00255 }
00256 #endif // __TRAVELCCM_SVC_TRAVELCCM_SERVICE_HPP

```

23.57 travelccm/TRAVELCCM_Types.hpp File Reference

```

#include <string>
#include <boost/shared_ptr.hpp>
#include <stdair/stdair_exceptions.hpp>

```

Classes

- class [TRAVELCCM::CustomerChoiceException](#)

Namespaces

- namespace [TRAVELCCM](#)

Typedefs

- typedef boost::shared_ptr
 < TRAVELCCM_Service > TRAVELCCM::TRAVELCCM_ServicePtr_T

23.58 TRAVELCCM_Types.hpp

```

00001 #ifndef __TRAVELCCM_TRAVELCCM_TYPES_HPP
00002 #define __TRAVELCCM_TRAVELCCM_TYPES_HPP
00003
00004 // //////////////////////////////////////
00005 // Import section
00006 // //////////////////////////////////////
00007 // STL
00008 #include <string>
00009 // Boost
00010 #include <boost/shared_ptr.hpp>
00011 // StdAir
00012 #include <stdair/stdair_exceptions.hpp>
00013
00014 namespace TRAVELCCM {
00015
00016     class TRAVELCCM_Service;
00017
00018
00019
00020     // /////////// Exceptions ///////////
00024     class CustomerChoiceException : public
stdair::RootException {
00025     public:
00029         CustomerChoiceException (const std::string& iWhat)
00030             : stdair::RootException (iWhat) {}
00031     };
00032
00033
00034     // /////////// Type definitions ///////////
00038     typedef boost::shared_ptr<TRAVELCCM_Service> TRAVELCCM_ServicePtr_T
;
00039
00040 }
00041 #endif // __TRAVELCCM_TRAVELCCM_TYPES_HPP

```

Index

- [_describeKey](#)
 - [TravelChoiceTestSuite](#), [101](#)
- [BINDIR](#)
 - [travelccm-paths.hpp](#), [113](#)
 - [travelccm-paths.hpp.in](#), [115](#)
- [buildSampleBom](#)
 - [TRAVELCCM::TRAVELCCM_Service](#), [98](#)
- [buildSampleBookingRequest](#)
 - [TRAVELCCM::TRAVELCCM_Service](#), [98](#)
- [buildSampleTravelSolutions](#)
 - [TRAVELCCM::TRAVELCCM_Service](#), [98](#)
- [chooseTravelSolution](#)
 - [TRAVELCCM::ChoiceManager](#), [92](#)
 - [TRAVELCCM::PriceOrientedModel](#), [95](#)
 - [TRAVELCCM::TRAVELCCM_Service](#), [99](#)
- [create](#)
 - [TRAVELCCM::FacTRAVELCCMServiceContext](#), [94](#)
- [csvDisplay](#)
 - [TRAVELCCM::TRAVELCCM_Service](#), [99](#)
- [CustomerChoiceException](#)
 - [TRAVELCCM::CustomerChoiceException](#), [93](#)
- [DATADIR](#)
 - [travelccm-paths.hpp](#), [114](#)
 - [travelccm-paths.hpp.in](#), [116](#)
- [DATAROOTDIR](#)
 - [travelccm-paths.hpp](#), [114](#)
 - [travelccm-paths.hpp.in](#), [116](#)
- [DOCDIR](#)
 - [travelccm-paths.hpp](#), [114](#)
 - [travelccm-paths.hpp.in](#), [116](#)
- [doc/local/authors.doc](#), [101](#)
- [doc/local/codingrules.doc](#), [101](#)
- [doc/local/copyright.doc](#), [101](#)
- [doc/local/documentation.doc](#), [101](#)
- [doc/local/features.doc](#), [101](#)
- [doc/local/help_wanted.doc](#), [101](#)
- [doc/local/howto_release.doc](#), [101](#)
- [doc/local/index.doc](#), [101](#)
- [doc/local/installation.doc](#), [101](#)
- [doc/local/linking.doc](#), [101](#)
- [doc/local/test.doc](#), [102](#)
- [doc/local/users_guide.doc](#), [102](#)
- [doc/local/verification.doc](#), [102](#)
- [doc/tutorial/tutorial.doc](#), [102](#)
- [EXEC_PREFIX](#)
 - [travelccm-paths.hpp](#), [113](#)
 - [travelccm-paths.hpp.in](#), [115](#)
- [FacServiceAbstract](#), [93](#)
- [HTMLDIR](#)
 - [travelccm-paths.hpp](#), [114](#)
- [travelccm-paths.hpp.in](#), [116](#)
- [INCLUDEDIR](#)
 - [travelccm-paths.hpp](#), [114](#)
 - [travelccm-paths.hpp.in](#), [116](#)
- [INFODIR](#)
 - [travelccm-paths.hpp](#), [114](#)
 - [travelccm-paths.hpp.in](#), [116](#)
- [instance](#)
 - [TRAVELCCM::FacTRAVELCCMServiceContext](#), [94](#)
- [LIBDIR](#)
 - [travelccm-paths.hpp](#), [113](#)
 - [travelccm-paths.hpp.in](#), [115](#)
- [LIBEXECDIR](#)
 - [travelccm-paths.hpp](#), [113](#)
 - [travelccm-paths.hpp.in](#), [116](#)
- [MANDIR](#)
 - [travelccm-paths.hpp](#), [114](#)
 - [travelccm-paths.hpp.in](#), [116](#)
- [PACKAGE](#)
 - [travelccm-paths.hpp](#), [113](#)
 - [travelccm-paths.hpp.in](#), [115](#)
- [PACKAGE_NAME](#)
 - [travelccm-paths.hpp](#), [113](#)
 - [travelccm-paths.hpp.in](#), [115](#)
- [PACKAGE_VERSION](#)
 - [travelccm-paths.hpp](#), [113](#)
 - [travelccm-paths.hpp.in](#), [115](#)
- [PDFDIR](#)
 - [travelccm-paths.hpp](#), [114](#)
 - [travelccm-paths.hpp.in](#), [116](#)
- [PREFIXDIR](#)
 - [travelccm-paths.hpp](#), [113](#)
 - [travelccm-paths.hpp.in](#), [115](#)
- [RootException](#), [95](#)
- [SBINDIR](#)
 - [travelccm-paths.hpp](#), [113](#)
 - [travelccm-paths.hpp.in](#), [116](#)
- [STDAIR_SAMPLE_DIR](#)
 - [travelccm-paths.hpp](#), [114](#)
 - [travelccm-paths.hpp.in](#), [116](#)
- [SYSCONFDIR](#)
 - [travelccm-paths.hpp](#), [114](#)
 - [travelccm-paths.hpp.in](#), [116](#)
- [ServiceAbstract](#), [96](#)
- [stdair](#), [91](#)
- [TRAVELCCM](#), [91](#)
- [TRAVELCCM::ChoiceManager](#), [91](#)
 - [chooseTravelSolution](#), [92](#)
- [TRAVELCCM::CmdAbstract](#), [92](#)

TRAVELCCM::CustomerChoiceException, 92
 CustomerChoiceException, 93
TRAVELCCM::FacTRAVELCCMServiceContext, 93
TRAVELCCM::FileMgr, 95
TRAVELCCM::PriceOrientedModel, 95
 chooseTravelSolution, 95
TRAVELCCM::TRAVELCCM_Service, 96
TRAVELCCM_ServicePtr_T
 TRAVELCCM, 91
test/travelccm/TravelChoiceTestSuite.cpp, 102
test/travelccm/TravelChoiceTestSuite.hpp, 103, 104
TestFixture, 96
testTravelChoice
 TravelChoiceTestSuite, 101
TravelChoiceTestSuite, 100
 _describeKey, 101
 testTravelChoice, 101
 TravelChoiceTestSuite, 101
 TravelChoiceTestSuite, 101
travelccm-paths.hpp
 BINDIR, 113
 DATADIR, 114
 DATAROOTDIR, 114
 DOCDIR, 114
 EXEC_PREFIX, 113
 HTMLDIR, 114
 INCLUDEDIR, 114
 INFODIR, 114
 LIBDIR, 113
 LIBEXECDIR, 113
 MANDIR, 114
 PACKAGE, 113
 PACKAGE_NAME, 113
 PACKAGE_VERSION, 113
 PDFDIR, 114
 PREFIXDIR, 113
 SBINDIR, 113
 STDAIR_SAMPLE_DIR, 114
 SYSCONFDIR, 114
travelccm-paths.hpp.in
 BINDIR, 115
 DATADIR, 116
 DATAROOTDIR, 116
 DOCDIR, 116
 EXEC_PREFIX, 115
 HTMLDIR, 116
 INCLUDEDIR, 116
 INFODIR, 116
 LIBDIR, 115
 LIBEXECDIR, 116
 MANDIR, 116
 PACKAGE, 115
 PACKAGE_NAME, 115
 PACKAGE_VERSION, 115
 PDFDIR, 116
 PREFIXDIR, 115
 SBINDIR, 116
 STDAIR_SAMPLE_DIR, 116
SYSCONFDIR, 116
travelccm/TRAVELCCM_Service.hpp, 125
travelccm/TRAVELCCM_Types.hpp, 126, 127
travelccm/basic/BasConst.cpp, 104
travelccm/basic/BasConst_General.hpp, 104
travelccm/batches/travelccm.cpp, 105
travelccm/bom/PriceOrientedModel.cpp, 107, 108
travelccm/bom/PriceOrientedModel.hpp, 109
travelccm/command/ChoiceManager.cpp, 109, 110
travelccm/command/ChoiceManager.hpp, 110
travelccm/command/CmdAbstract.cpp, 111
travelccm/command/CmdAbstract.hpp, 111
travelccm/command/FileMgr.cpp, 112
travelccm/command/FileMgr.hpp, 112
travelccm/config/travelccm-paths.hpp, 113, 114
travelccm/config/travelccm-paths.hpp.in, 115, 116
travelccm/factory/FacTRAVELCCMServiceContext.cpp, 117
travelccm/factory/FacTRAVELCCMServiceContext.hpp, 118
travelccm/service/TRAVELCCM_Service.cpp, 119
travelccm/service/TRAVELCCM_ServiceContext.cpp, 123
travelccm/service/TRAVELCCM_ServiceContext.hpp, 124