

M4RIE

0.20130416

Generated by Doxygen 1.8.3.1

Thu May 9 2013 13:25:28

Contents

1	Main Page	1
2	Todo List	1
3	Module Documentation	2
3.1	Type definitions	2
3.1.1	Detailed Description	2
3.2	Constructions	3
3.2.1	Detailed Description	3
3.2.2	Function Documentation	3
3.3	Assignment and basic manipulation	8
3.3.1	Detailed Description	8
3.3.2	Function Documentation	8
3.4	Operations on rows	12
3.4.1	Detailed Description	13
3.4.2	Function Documentation	13
3.5	String conversions and I/O	19
3.5.1	Detailed Description	19
3.5.2	Function Documentation	19
3.6	Addition and subtraction	20
3.6.1	Detailed Description	20
3.6.2	Macro Definition Documentation	20
3.6.3	Function Documentation	21
3.7	Multiplication	23
3.7.1	Detailed Description	24
3.7.2	Function Documentation	24
3.8	PLE and PLUQ decomposition	33
3.8.1	Detailed Description	33
3.8.2	Function Documentation	33
3.9	Echelon forms	36
3.9.1	Detailed Description	36
3.9.2	Macro Definition Documentation	36
3.9.3	Function Documentation	36
3.10	Triangular matrices	38
3.10.1	Detailed Description	38
3.10.2	Function Documentation	38

4	Data Structure Documentation	42
4.1	gf2e_struct Struct Reference	42
4.1.1	Detailed Description	42
4.1.2	Field Documentation	42
4.2	mzd_poly_t Struct Reference	43
4.2.1	Field Documentation	43
4.3	mzd_slice_t Struct Reference	43
4.3.1	Detailed Description	44
4.3.2	Field Documentation	44
4.4	mzed_t Struct Reference	44
4.4.1	Detailed Description	45
4.4.2	Field Documentation	45
4.5	njt_mzed_t Struct Reference	45
4.5.1	Detailed Description	45
4.5.2	Field Documentation	45
5	File Documentation	46
5.1	conversion.h File Reference	46
5.1.1	Detailed Description	47
5.1.2	Function Documentation	47
5.2	echelonform.h File Reference	49
5.2.1	Detailed Description	50
5.3	gf2e.h File Reference	50
5.3.1	Detailed Description	51
5.3.2	Function Documentation	51
5.4	gf2x.h File Reference	52
5.4.1	Detailed Description	53
5.4.2	Macro Definition Documentation	53
5.4.3	Function Documentation	53
5.5	m4rie.h File Reference	53
5.5.1	Detailed Description	54
5.6	mzd_slice.h File Reference	54
5.6.1	Detailed Description	56
5.6.2	Function Documentation	57
5.7	mzed.h File Reference	58
5.7.1	Detailed Description	60
5.7.2	Function Documentation	60

5.8	newton_john.h File Reference	61
5.8.1	Detailed Description	62
5.8.2	Function Documentation	62
5.9	permutation.h File Reference	63
5.9.1	Detailed Description	64
5.9.2	Function Documentation	64
5.10	ple.h File Reference	66
5.10.1	Detailed Description	66
5.10.2	Macro Definition Documentation	66
5.11	strassen.h File Reference	66
5.11.1	Detailed Description	67
5.12	trsm.h File Reference	67
5.12.1	Detailed Description	68
5.12.2	Macro Definition Documentation	68
6	Example Documentation	68
6.1	tests/test_elimination.cc	68

Index

70

1 Main Page

M4RIE is a library to do fast computations with dense matrices over \mathbb{F}_{2^e} for small e . M4RIE is available under the GPLv2+.

The two fundamental data types of this library are [mzed_t](#) and [mzd_slice_t](#). For big matrices, i.e., those which do not fit into L2 cache, it is recommended to use [mzd_slice_t](#) and for smaller matrices [mzed_t](#) will be slightly faster and use less memory.

Function names follow the pattern

```
[_]_[type]_[what]_[algorithm]
```

Function names beginning with an underscore perform less consistency checks (matching dimensions, matching fields) than those without, e.g., [_mzed_ple\(\)](#) is called by [mzed_ple\(\)](#) after some checks were performed.

For both data types almost all functions are the same, e.g., there is a function [mzd_slice_add\(\)](#) and there also should be a function [mzed_add\(\)](#) with the same signature except for the matrix type.

Functions which do not specify an algorithm choose the best available algorithm (based on some heuristic), e.g., [mzed_ple\(\)](#) might call [mzed_ple_newton_john\(\)](#).

2 Todo List

Global [_mzd_slice_mul_karatsuba8](#) ([mzd_slice_t](#) *C, const [mzd_slice_t](#) *A, const [mzd_slice_t](#) *B)

reduce memory requirements by writing formula explicitly

Global `gf2e_t16_init` (`const gf2e *ff, const word a`)

: this is a bit of overkill, we could do better

Global `mzd_poly_randomize` (`mzd_poly_t *A`)

Allow the user to provide a RNG callback.

Global `mzd_slice_add_elem` (`mzd_slice_t *A, const rci_t row, const rci_t col, word elem`)

This function is considerably slower than it needs to be.

Global `mzd_slice_randomize` (`mzd_slice_t *A`)

Allow the user to provide a RNG callback.

Global `mzd_slice_read_elem` (`const mzd_slice_t *A, const rci_t row, const rci_t col`)

This function is considerably slower than it needs to be.

Global `mzd_slice_write_elem` (`mzd_slice_t *A, const rci_t row, const rci_t col, word elem`)

This function is considerably slower than it needs to be.

Global `mzed_echelonize_newton_john` (`mzed_t *A, int full`)

we don't really compute the upper triangular form yet, we need to implement `_mzed_gauss_submatrix()` and a better table creation for that.

Global `mzed_randomize` (`mzed_t *A`)

Allow the user to provide a RNG callback.

3 Module Documentation

3.1 Type definitions

Data Structures

- struct `mzd_slice_t`
Dense matrices over \mathbb{F}_{2^e} represented as slices of matrices over \mathbb{F}_2 .
- struct `mzed_t`
Dense matrices over \mathbb{F}_{2^e} represented as packed matrices.

3.1.1 Detailed Description

3.2 Constructions

Functions

- `mzed_t * mzed_cling (mzed_t *A, const mzd_slice_t *Z)`
Pack a bitslice matrix into a packed representation.
- `mzd_slice_t * mzed_slice (mzd_slice_t *A, const mzed_t *Z)`
Unpack the matrix Z into bitslice representation.
- `static mzd_slice_t * mzd_slice_init (const gf2e *ff, const rci_t m, const rci_t n)`
Create a new matrix of dimension $m \times n$ over ff.
- `static void mzd_slice_free (mzd_slice_t *A)`
Free a matrix created with `mzd_slice_init()`.
- `static mzd_slice_t * mzd_slice_concat (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
Concatenate B to A and write the result to C.
- `static mzd_slice_t * mzd_slice_stack (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
Stack A on top of B and write the result to C.
- `static mzd_slice_t * mzd_slice_submatrix (mzd_slice_t *S, const mzd_slice_t *A, const size_t lowr, const size_t lowc, const size_t highr, const size_t highc)`
Copy a submatrix.
- `static mzd_slice_t * mzd_slice_init_window (const mzd_slice_t *A, const size_t lowr, const size_t lowc, const size_t highr, const size_t highc)`
Create a window/view into the matrix M.
- `static void mzd_slice_free_window (mzd_slice_t *A)`
Free a matrix window created with `mzd_slice_init_window()`.
- `mzed_t * mzed_init (const gf2e *ff, const rci_t m, const rci_t n)`
Create a new matrix of dimension $m \times n$ over ff.
- `void mzed_free (mzed_t *A)`
Free a matrix created with `mzed_init()`.
- `static mzed_t * mzed_concat (mzed_t *C, const mzed_t *A, const mzed_t *B)`
Concatenate B to A and write the result to C.
- `static mzed_t * mzed_stack (mzed_t *C, const mzed_t *A, const mzed_t *B)`
Stack A on top of B and write the result to C.
- `static mzed_t * mzed_submatrix (mzed_t *S, const mzed_t *M, const rci_t lowr, const rci_t lowc, const rci_t highr, const rci_t highc)`
Copy a submatrix.
- `static mzed_t * mzed_init_window (const mzed_t *A, const rci_t lowr, const rci_t lowc, const rci_t highr, const rci_t highc)`
Create a window/view into the matrix A.
- `static void mzed_free_window (mzed_t *A)`
Free a matrix window created with `mzed_init_window()`.

3.2.1 Detailed Description

3.2.2 Function Documentation

3.2.2.1 `static mzd_slice_t * mzd_slice_concat (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`
`[inline], [static]`

Concatenate B to A and write the result to C.

That is,

$$[A], [B] \rightarrow [A \ B] = C$$

The inputs are not modified but a new matrix is created.

Parameters

<i>C</i>	Matrix, may be NULL for automatic creation.
<i>A</i>	Matrix.
<i>B</i>	Matrix.

Note

This is sometimes called augment.

3.2.2.2 `static void mzd_slice_free (mzd_slice_t * A)` `[inline], [static]`

Free a matrix created with [mzd_slice_init\(\)](#).

Parameters

<i>A</i>	Matrix.
----------	---------

3.2.2.3 `static void mzd_slice_free_window (mzd_slice_t * A)` `[inline], [static]`

Free a matrix window created with [mzd_slice_init_window\(\)](#).

Parameters

<i>A</i>	Matrix
----------	--------

3.2.2.4 `static mzd_slice_t* mzd_slice_init (const gf2e * ff, const rci_t m, const rci_t n)` `[inline], [static]`

Create a new matrix of dimension $m \times n$ over ff.

Use [mzd_slice_free\(\)](#) to free it.

Parameters

<i>ff</i>	Finite field
<i>m</i>	Number of rows
<i>n</i>	Number of columns

3.2.2.5 `static mzd_slice_t* mzd_slice_init_window (const mzd_slice_t * A, const size_t lowr, const size_t lowc, const size_t highr, const size_t highc)` `[inline], [static]`

Create a window/view into the matrix M.

A matrix window for M is a meta structure on the matrix M. It is setup to point into the matrix so M *must not* be freed while the matrix window is used.

This function puts the restriction on the provided parameters that all parameters must be within range for M which is not currently enforced.

Use [mzd_slice_free_window\(\)](#) to free the window.

Parameters

<i>A</i>	Matrix
<i>lowr</i>	Starting row (inclusive)
<i>lowc</i>	Starting column (inclusive)
<i>highr</i>	End row (exclusive)
<i>highc</i>	End column (exclusive)

3.2.2.6 `static mzd_slice_t* mzd_slice_stack (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`
`[inline], [static]`

Stack A on top of B and write the result to C.

That is,

$$\begin{bmatrix} A \\ B \end{bmatrix} \rightarrow \begin{bmatrix} A \\ B \end{bmatrix} = C$$

The inputs are not modified but a new matrix is created.

Parameters

<i>C</i>	Matrix, may be NULL for automatic creation
<i>A</i>	Matrix
<i>B</i>	Matrix

3.2.2.7 `static mzd_slice_t* mzd_slice_submatrix (mzd_slice_t * S, const mzd_slice_t * A, const size_t lowr, const size_t lowc, const size_t highr, const size_t highc)` `[inline], [static]`

Copy a submatrix.

Parameters

<i>S</i>	Preallocated space for submatrix, may be NULL for automatic creation.
<i>A</i>	Matrix
<i>lowr</i>	start rows
<i>lowc</i>	start column
<i>highr</i>	stop row (this row is <i>not</i> included)
<i>highc</i>	stop column (this column is <i>not</i> included)

3.2.2.8 `mzed_t* mzed_cling (mzed_t * A, const mzd_slice_t * Z)`

Pack a bitslice matrix into a packed representation.

Parameters

<i>A</i>	Matrix over \mathbb{F}_{2^e} or NULL
<i>Z</i>	Bitslice matrix over \mathbb{F}_{2^e}

3.2.2.9 `static mzed_t* mzed_concat (mzed_t * C, const mzed_t * A, const mzed_t * B)` `[inline], [static]`

Concatenate B to A and write the result to C.

That is,

$$\begin{bmatrix} A \\ B \end{bmatrix} \rightarrow \begin{bmatrix} A & B \end{bmatrix} = C$$

The inputs are not modified but a new matrix is created.

Parameters

<i>C</i>	Matrix, may be NULL for automatic creation
<i>A</i>	Matrix
<i>B</i>	Matrix

Note

This is sometimes called augment.

3.2.2.10 void mzed_free (mzed_t * A)

Free a matrix created with [mzed_init\(\)](#).

Parameters

<i>A</i>	Matrix
----------	--------

3.2.2.11 static void mzed_free_window (mzed_t * A) [inline],[static]

Free a matrix window created with [mzed_init_window\(\)](#).

Parameters

<i>A</i>	Matrix
----------	--------

3.2.2.12 mzed_t* mzed_init (const gf2e * ff, const rci_t m, const rci_t n)

Create a new matrix of dimension m x n over ff.

Use [mzed_free\(\)](#) to kill it.

Parameters

<i>ff</i>	Finite field
<i>m</i>	Number of rows
<i>n</i>	Number of columns

3.2.2.13 static mzed_t* mzed_init_window (const mzed_t * A, const rci_t lowr, const rci_t lowc, const rci_t highr, const rci_t highc) [inline],[static]

Create a window/view into the matrix A.

A matrix window for A is a meta structure on the matrix A. It is setup to point into the matrix so M *must not* be freed while the matrix window is used.

This function puts the restriction on the provided parameters that all parameters must be within range for A which is not currently enforced.

Use [mzed_free_window\(\)](#) to free the window.

Parameters

<i>A</i>	Matrix
<i>lowr</i>	Starting row (inclusive)
<i>lowc</i>	Starting column (inclusive)
<i>highr</i>	End row (exclusive)
<i>highc</i>	End column (exclusive)

3.2.2.14 `mzd_slice_t* mzed_slice (mzd_slice_t * A, const mzed_t * Z)`

Unpack the matrix Z into bitslice representation.

Parameters

<i>A</i>	Bitslice matrix or NULL
<i>Z</i>	Input matrix

3.2.2.15 `static mzed_t* mzed_stack (mzed_t * C, const mzed_t * A, const mzed_t * B) [inline],[static]`

Stack A on top of B and write the result to C.

That is,

$$\begin{bmatrix} A \\ B \end{bmatrix}, \begin{bmatrix} B \end{bmatrix} \rightarrow \begin{bmatrix} A \\ B \end{bmatrix} = C$$

The inputs are not modified but a new matrix is created.

Parameters

<i>C</i>	Matrix, may be NULL for automatic creation
<i>A</i>	Matrix
<i>B</i>	Matrix

3.2.2.16 `static mzed_t* mzed_submatrix (mzed_t * S, const mzed_t * M, const rci_t lowr, const rci_t lowc, const rci_t highr, const rci_t highc) [inline],[static]`

Copy a submatrix.

Note that the upper bounds are not included.

Parameters

<i>S</i>	Preallocated space for submatrix, may be NULL for automatic creation.
<i>M</i>	Matrix
<i>lowr</i>	start rows
<i>lowc</i>	start column
<i>highr</i>	stop row (this row is <i>not</i> included)
<i>highc</i>	stop column (this column is <i>not</i> included)

3.3 Assignment and basic manipulation

Functions

- static void `mzd_poly_randomize (mzd_poly_t *A)`
Fill matrix A with random elements.
- void `mzd_slice_set_ui (mzd_slice_t *A, word value)`
Return diagonal matrix with value on the diagonal.
- static void `mzd_slice_randomize (mzd_slice_t *A)`
Fill matrix A with random elements.
- static `mzd_slice_t * mzd_slice_copy (mzd_slice_t *B, const mzd_slice_t *A)`
Copy matrix A to B.
- static word `mzd_slice_read_elem (const mzd_slice_t *A, const rci_t row, const rci_t col)`
Get the element at position (row,col) from the matrix A.
- static void `mzd_slice_add_elem (mzd_slice_t *A, const rci_t row, const rci_t col, word elem)`
At the element elem to the element at position (row,col) in the matrix A.
- static void `mzd_slice_write_elem (mzd_slice_t *A, const rci_t row, const rci_t col, word elem)`
Write the element elem to the position (row,col) in the matrix A.
- void `mzed_randomize (mzed_t *A)`
Fill matrix A with random elements.
- `mzed_t * mzed_copy (mzed_t *B, const mzed_t *A)`
Copy matrix A to B.
- void `mzed_set_ui (mzed_t *A, word value)`
Return diagonal matrix with value on the diagonal.
- static word `mzed_read_elem (const mzed_t *A, const rci_t row, const rci_t col)`
Get the element at position (row,col) from the matrix A.
- static void `mzed_add_elem (mzed_t *A, const rci_t row, const rci_t col, const word elem)`
At the element elem to the element at position (row,col) in the matrix A.
- static void `mzed_write_elem (mzed_t *A, const rci_t row, const rci_t col, const word elem)`
Write the element elem to the position (row,col) in the matrix A.

3.3.1 Detailed Description

3.3.2 Function Documentation

3.3.2.1 static void mzd_poly_randomize (mzd_poly_t * A) [inline],[static]

Fill matrix A with random elements.

Parameters

A	Matrix
---	--------

Todo Allow the user to provide a RNG callback.

3.3.2.2 static void mzd_slice_add_elem (mzd_slice_t * A, const rci_t row, const rci_t col, word elem) [inline],[static]

At the element elem to the element at position (row,col) in the matrix A.

Parameters

<i>A</i>	Target matrix.
<i>row</i>	Starting row.
<i>col</i>	Starting column.
<i>elem</i>	finite field element.

Todo This function is considerably slower than it needs to be.

3.3.2.3 `static mzd_slice_t* mzd_slice_copy (mzd_slice_t * B, const mzd_slice_t * A)` `[inline]`, `[static]`

Copy matrix A to B.

Parameters

<i>B</i>	May be NULL for automatic creation.
<i>A</i>	Source matrix.

3.3.2.4 `static void mzd_slice_randomize (mzd_slice_t * A)` `[inline]`, `[static]`

Fill matrix A with random elements.

Parameters

<i>A</i>	Matrix
----------	--------

Todo Allow the user to provide a RNG callback.

3.3.2.5 `static word mzd_slice_read_elem (const mzd_slice_t * A, const rci_t row, const rci_t col)` `[inline]`, `[static]`

Get the element at position (row,col) from the matrix A.

Parameters

<i>A</i>	Source matrix.
<i>row</i>	Starting row.
<i>col</i>	Starting column.

Todo This function is considerably slower than it needs to be.

3.3.2.6 `void mzd_slice_set_ui (mzd_slice_t * A, word value)`

Return diagonal matrix with value on the diagonal.

If the matrix is not square then the largest possible square submatrix is used.

Parameters

<i>A</i>	Matrix.
<i>value</i>	Finite Field element.

3.3.2.7 `static void mzd_slice_write_elem (mzd_slice_t * A, const rci_t row, const rci_t col, word elem) [inline], [static]`

Write the element `elem` to the position `(row,col)` in the matrix `A`.

Parameters

<code>A</code>	Target matrix.
<code>row</code>	Starting row.
<code>col</code>	Starting column.
<code>elem</code>	finite field element.

Todo This function is considerably slower than it needs to be.

3.3.2.8 `static void mzed_add_elem (mzed_t * A, const rci_t row, const rci_t col, const word elem) [inline], [static]`

Add the element `elem` to the element at position `(row,col)` in the matrix `A`.

Parameters

<code>A</code>	Target matrix.
<code>row</code>	Starting row.
<code>col</code>	Starting column.
<code>elem</code>	finite field element.

3.3.2.9 `mzed_t * mzed_copy (mzed_t * B, const mzed_t * A)`

Copy matrix `A` to `B`.

Parameters

<code>B</code>	May be NULL for automatic creation.
<code>A</code>	Source matrix.

3.3.2.10 `void mzed_randomize (mzed_t * A)`

Fill matrix `A` with random elements.

Parameters

<code>A</code>	Matrix
----------------	--------

Todo Allow the user to provide a RNG callback.

3.3.2.11 `static word mzed_read_elem (const mzed_t * A, const rci_t row, const rci_t col) [inline], [static]`

Get the element at position `(row,col)` from the matrix `A`.

Parameters

<code>A</code>	Source matrix.
<code>row</code>	Starting row.
<code>col</code>	Starting column.

3.3.2.12 `void mzed_set_ui (mzed_t * A, word value)`

Return diagonal matrix with value on the diagonal.

If the matrix is not square then the largest possible square submatrix is used.

Parameters

<i>A</i>	Matrix
<i>value</i>	Finite Field element

3.3.2.13 `static void mzed_write_elem (mzed_t * A, const rci_t row, const rci_t col, const word elem)` `[inline]`,
`[static]`

Write the element elem to the position (row,col) in the matrix A.

Parameters

<i>A</i>	Target matrix.
<i>row</i>	Starting row.
<i>col</i>	Starting column.
<i>elem</i>	finite field element.

3.4 Operations on rows

Functions

- static void `mzd_slice_rescale_row` (`mzd_slice_t` *A, `rci_t` r, `rci_t` c, word x)
Rescale the row r in A by X starting c.
- static void `mzd_slice_row_swap` (`mzd_slice_t` *A, const `rci_t` rowa, const `rci_t` rowb)
Swap the two rows rowa and rowb.
- static void `mzd_slice_copy_row` (`mzd_slice_t` *B, `size_t` i, const `mzd_slice_t` *A, `size_t` j)
copy row j from A to row i from B.
- static void `mzd_slice_col_swap` (`mzd_slice_t` *A, const `rci_t` cola, const `rci_t` colb)
Swap the two columns cola and colb.
- static void `mzd_slice_row_add` (`mzd_slice_t` *A, const `rci_t` sourcerow, const `rci_t` destrow)
Add the rows sourcerow and destrow and stores the total in the row destrow.
- static void `mzd_slice_row_clear_offset` (`mzd_slice_t` *A, const `rci_t` row, const `rci_t` coloffset)
Clear the given row, but only begins at the column coloffset.
- void `mzed_add_multiple_of_row` (`mzed_t` *A, `rci_t` ar, const `mzed_t` *B, `rci_t` br, word x, `rci_t` start_col)
- static void `mzed_add_row` (`mzed_t` *A, `rci_t` ar, const `mzed_t` *B, `rci_t` br, `rci_t` start_col)
- static void `mzed_rescale_row` (`mzed_t` *A, `rci_t` r, `rci_t` start_col, const word x)
Rescale the row r in A by X starting c.
- static void `mzed_row_swap` (`mzed_t` *M, const `rci_t` rowa, const `rci_t` rowb)
Swap the two rows rowa and rowb.
- static void `mzed_copy_row` (`mzed_t` *B, `rci_t` i, const `mzed_t` *A, `rci_t` j)
copy row j from A to row i from B.
- static void `mzed_col_swap` (`mzed_t` *M, const `rci_t` cola, const `rci_t` colb)
Swap the two columns cola and colb.
- static void `mzed_col_swap_in_rows` (`mzed_t` *A, const `rci_t` cola, const `rci_t` colb, const `rci_t` start_row, `rci_t` stop_row)
Swap the two columns cola and colb but only between start_row and stop_row.
- static void `mzed_row_add` (`mzed_t` *M, const `rci_t` sourcerow, const `rci_t` destrow)
Add the rows sourcerow and destrow and stores the total in the row destrow.
- static `rci_t` `mzed_first_zero_row` (`mzed_t` *A)
Return the first row with all zero entries.
- static void `mzed_row_clear_offset` (`mzed_t` *M, const `rci_t` row, const `rci_t` coloffset)
Clear the given row, but only begins at the column coloffset.
- static void `mzed_process_rows` (`mzed_t` *M, const `rci_t` startrow, const `rci_t` endrow, `rci_t` startcol, const `njt_mzed_t` *T)
The function looks up 6 entries from position i,startcol in each row and adds the appropriate row from T to the row i.
- static void `mzed_process_rows2` (`mzed_t` *M, const `rci_t` startrow, const `rci_t` endrow, const `rci_t` startcol, const `njt_mzed_t` *T0, const `njt_mzed_t` *T1)
Same as mzed_process_rows but works with two Newton-John tables in parallel.
- static void `mzed_process_rows3` (`mzed_t` *M, const `rci_t` startrow, const `rci_t` endrow, const `rci_t` startcol, const `njt_mzed_t` *T0, const `njt_mzed_t` *T1, const `njt_mzed_t` *T2)
Same as mzed_process_rows but works with three Newton-John tables in parallel.
- static void `mzed_process_rows4` (`mzed_t` *M, const `rci_t` startrow, const `rci_t` endrow, const `rci_t` startcol, const `njt_mzed_t` *T0, const `njt_mzed_t` *T1, const `njt_mzed_t` *T2, const `njt_mzed_t` *T3)
Same as mzed_process_rows but works with four Newton-John tables in parallel.
- static void `mzed_process_rows5` (`mzed_t` *M, const `rci_t` startrow, const `rci_t` endrow, const `rci_t` startcol, const `njt_mzed_t` *T0, const `njt_mzed_t` *T1, const `njt_mzed_t` *T2, const `njt_mzed_t` *T3, const `njt_mzed_t` *T4)

Same as `mzed_process_rows` but works with five Newton-John tables in parallel.

- static void `mzed_process_rows6` (`mzed_t` *M, const `rci_t` startrow, const `rci_t` endrow, const `rci_t` startcol, const `njt_mzed_t` *T0, const `njt_mzed_t` *T1, const `njt_mzed_t` *T2, const `njt_mzed_t` *T3, const `njt_mzed_t` *T4, const `njt_mzed_t` *T5)

Same as `mzed_process_rows` but works with six Newton-John tables in parallel.

3.4.1 Detailed Description

3.4.2 Function Documentation

3.4.2.1 static void `mzd_slice_col_swap` (`mzd_slice_t` *A, const `rci_t` cola, const `rci_t` colb) [inline],[static]

Swap the two columns cola and colb.

Parameters

A	Matrix.
cola	Column index.
colb	Column index.

3.4.2.2 static void `mzd_slice_copy_row` (`mzd_slice_t` *B, size_t i, const `mzd_slice_t` *A, size_t j) [inline],[static]

copy row j from A to row i from B.

The offsets of A and B must match and the number of columns of A must be less than or equal to the number of columns of B.

Parameters

B	Target matrix.
i	Target row index.
A	Source matrix.
j	Source row index.

3.4.2.3 static void `mzd_slice_rescale_row` (`mzd_slice_t` *A, `rci_t` r, `rci_t` c, word x) [inline],[static]

Recalc the row r in A by X starting c.

Parameters

A	Matrix
r	Row index.
c	Column index.
x	Multiplier

3.4.2.4 static void `mzd_slice_row_add` (`mzd_slice_t` *A, const `rci_t` sourcerow, const `rci_t` destrow) [inline],[static]

Add the rows sourcerow and destrow and stores the total in the row destrow.

Parameters

<i>A</i>	Matrix
<i>sourcerow</i>	Index of source row
<i>destrow</i>	Index of target row

Note

this can be done much faster with `mzd_combine`.

3.4.2.5 `static void mzd_slice_row_clear_offset (mzd_slice_t * A, const rci_t row, const rci_t coloffset) [inline], [static]`

Clear the given row, but only begins at the column coloffset.

Parameters

<i>A</i>	Matrix
<i>row</i>	Index of row
<i>coloffset</i>	Column offset

3.4.2.6 `static void mzd_slice_row_swap (mzd_slice_t * A, const rci_t rowa, const rci_t rowb) [inline], [static]`

Swap the two rows rowa and rowb.

Parameters

<i>A</i>	Matrix
<i>rowa</i>	Row index.
<i>rowb</i>	Row index.

3.4.2.7 `void mzed_add_multiple_of_row (mzed_t * A, rci_t ar, const mzed_t * B, rci_t br, word x, rci_t start_col)`

$A[ar,c] = A[ar,c] + x \cdot B[br,c]$ for all $c \geq \text{startcol}$.

Parameters

<i>A</i>	Matrix.
<i>ar</i>	Row index in A.
<i>B</i>	Matrix.
<i>br</i>	Row index in B.
<i>x</i>	Finite field element.
<i>start_col</i>	Column index.

3.4.2.8 `static void mzed_add_row (mzed_t * A, rci_t ar, const mzed_t * B, rci_t br, rci_t start_col) [inline], [static]`

$A[ar,c] = A[ar,c] + B[br,c]$ for all $c \geq \text{startcol}$.

Parameters

<i>A</i>	Matrix.
<i>ar</i>	Row index in A.
<i>B</i>	Matrix.
<i>br</i>	Row index in B.
<i>start_col</i>	Column index.

3.4.2.9 `static void mzed_col_swap (mzed_t * M, const rci_t cola, const rci_t colb)` `[inline],[static]`

Swap the two columns *cola* and *colb*.

Parameters

<i>M</i>	Matrix.
<i>cola</i>	Column index.
<i>colb</i>	Column index.

3.4.2.10 `static void mzed_col_swap_in_rows (mzed_t * A, const rci_t cola, const rci_t colb, const rci_t start_row, rci_t stop_row)` `[inline],[static]`

Swap the two columns *cola* and *colb* but only between *start_row* and *stop_row*.

Parameters

<i>A</i>	Matrix.
<i>cola</i>	Column index.
<i>colb</i>	Column index.
<i>start_row</i>	Row index.
<i>stop_row</i>	Row index (exclusive).

3.4.2.11 `static void mzed_copy_row (mzed_t * B, rci_t i, const mzed_t * A, rci_t j)` `[inline],[static]`

copy row *j* from *A* to row *i* from *B*.

The offsets of *A* and *B* must match and the number of columns of *A* must be less than or equal to the number of columns of *B*.

Parameters

<i>B</i>	Target matrix.
<i>i</i>	Target row index.
<i>A</i>	Source matrix.
<i>j</i>	Source row index.

3.4.2.12 `static rci_t mzed_first_zero_row (mzed_t * A)` `[inline],[static]`

Return the first row with all zero entries.

If no such row can be found returns *nrows*.

Parameters

<i>A</i>	Matrix
----------	--------

3.4.2.13 `static void mzed_process_rows (mzed_t * M, const rci_t startrow, const rci_t endrow, rci_t startcol, const njt_mzed_t * T)` `[inline],[static]`

The function looks up 6 entries from position *i*,*startcol* in each row and adds the appropriate row from *T* to the row *i*.

This process is iterated for *i* from *startrow* to *stoprow* (exclusive).

Parameters

<i>M</i>	Matrix to operate on
<i>startrow</i>	top row which is operated on
<i>endrow</i>	bottom row which is operated on
<i>startcol</i>	Starting column for addition
<i>T</i>	Newton-John table

3.4.2.14 `static void mzed_process_rows2 (mzed_t * M, const rci_t startrow, const rci_t endrow, const rci_t startcol, const njt_mzed_t * T0, const njt_mzed_t * T1) [inline],[static]`

Same as `mzed_process_rows` but works with two Newton-John tables in parallel.

Parameters

<i>M</i>	Matrix to operate on
<i>startrow</i>	top row which is operated on
<i>endrow</i>	bottom row which is operated on
<i>startcol</i>	Starting column for addition
<i>T0</i>	Newton-John table
<i>T1</i>	Newton-John table

3.4.2.15 `static void mzed_process_rows3 (mzed_t * M, const rci_t startrow, const rci_t endrow, const rci_t startcol, const njt_mzed_t * T0, const njt_mzed_t * T1, const njt_mzed_t * T2) [inline],[static]`

Same as `mzed_process_rows` but works with three Newton-John tables in parallel.

Parameters

<i>M</i>	Matrix to operate on
<i>startrow</i>	top row which is operated on
<i>endrow</i>	bottom row which is operated on
<i>startcol</i>	Starting column for addition
<i>T0</i>	Newton-John table
<i>T1</i>	Newton-John table
<i>T2</i>	Newton-John table

3.4.2.16 `static void mzed_process_rows4 (mzed_t * M, const rci_t startrow, const rci_t endrow, const rci_t startcol, const njt_mzed_t * T0, const njt_mzed_t * T1, const njt_mzed_t * T2, const njt_mzed_t * T3) [inline],[static]`

Same as `mzed_process_rows` but works with four Newton-John tables in parallel.

Parameters

<i>M</i>	Matrix to operate on
<i>startrow</i>	top row which is operated on
<i>endrow</i>	bottom row which is operated on
<i>startcol</i>	Starting column for addition
<i>T0</i>	Newton-John table
<i>T1</i>	Newton-John table
<i>T2</i>	Newton-John table
<i>T3</i>	Newton-John table

3.4.2.17 `static void mzed_process_rows5 (mzed_t * M, const rci_t startrow, const rci_t endrow, const rci_t startcol, const njt_mzed_t * T0, const njt_mzed_t * T1, const njt_mzed_t * T2, const njt_mzed_t * T3, const njt_mzed_t * T4) [inline],[static]`

Same as `mzed_process_rows` but works with five Newton-John tables in parallel.

Parameters

<i>M</i>	Matrix to operate on
<i>startrow</i>	top row which is operated on
<i>endrow</i>	bottom row which is operated on
<i>startcol</i>	Starting column for addition
<i>T0</i>	Newton-John table
<i>T1</i>	Newton-John table
<i>T2</i>	Newton-John table
<i>T3</i>	Newton-John table
<i>T4</i>	Newton-John table

3.4.2.18 `static void mzed_process_rows6 (mzed_t * M, const rci_t startrow, const rci_t endrow, const rci_t startcol, const njt_mzed_t * T0, const njt_mzed_t * T1, const njt_mzed_t * T2, const njt_mzed_t * T3, const njt_mzed_t * T4, const njt_mzed_t * T5) [inline],[static]`

Same as `mzed_process_rows` but works with six Newton-John tables in parallel.

Parameters

<i>M</i>	Matrix to operate on
<i>startrow</i>	top row which is operated on
<i>endrow</i>	bottom row which is operated on
<i>startcol</i>	Starting column for addition
<i>T0</i>	Newton-John table
<i>T1</i>	Newton-John table
<i>T2</i>	Newton-John table
<i>T3</i>	Newton-John table
<i>T4</i>	Newton-John table
<i>T5</i>	Newton-John table

3.4.2.19 `static void mzed_rescale_row (mzed_t * A, rci_t r, rci_t start_col, const word x) [inline],[static]`

Rescale the row *r* in *A* by *X* starting *c*.

Parameters

<i>A</i>	Matrix
<i>r</i>	Row index.
<i>start_col</i>	Column index.
<i>x</i>	Multiplier

3.4.2.20 `static void mzed_row_add (mzed_t * M, const rci_t sourcerow, const rci_t destrow) [inline],[static]`

Add the rows *sourcerow* and *destrow* and stores the total in the row *destrow*.

Parameters

<i>M</i>	Matrix
<i>sourcerow</i>	Index of source row
<i>destrow</i>	Index of target row

Note

this can be done much faster with `mzed_combine`.

3.4.2.21 `static void mzed_row_clear_offset (mzed_t * M, const rci_t row, const rci_t coloffset)` `[inline], [static]`

Clear the given row, but only begins at the column coloffset.

Parameters

<i>M</i>	Matrix
<i>row</i>	Index of row
<i>coloffset</i>	Column offset

3.4.2.22 `static void mzed_row_swap (mzed_t * M, const rci_t rowa, const rci_t rowb)` `[inline], [static]`

Swap the two rows rowa and rowb.

Parameters

<i>M</i>	Matrix
<i>rowa</i>	Row index.
<i>rowb</i>	Row index.

3.5 String conversions and I/O

Functions

- void [mzd_slice_print](#) (const [mzd_slice_t](#) *A)
Print a matrix to stdout.
- void [mzed_print](#) (const [mzed_t](#) *M)
Print a matrix to stdout.

3.5.1 Detailed Description

3.5.2 Function Documentation

3.5.2.1 void [mzd_slice_print](#) (const [mzd_slice_t](#) * A)

Print a matrix to stdout.

Parameters

<i>A</i>	Matrix
----------	--------

3.5.2.2 void [mzed_print](#) (const [mzed_t](#) * M)

Print a matrix to stdout.

Parameters

<i>M</i>	Matrix
----------	--------

3.6 Addition and subtraction

Macros

- `#define mzd_slice_sub mzd_slice_add`
 $C = A + B.$
- `#define _mzd_slice_sub _mzd_slice_add`
 $C = A + B.$
- `#define mzed_sub mzed_add`
 $C = A + B.$
- `#define _mzed_sub _mzed_add`
 $C = A + B.$

Functions

- `static mzd_slice_t * _mzd_slice_add (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = A + B.$
- `static mzd_slice_t * mzd_slice_add (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = A + B.$
- `mzed_t * mzed_add (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = A + B.$
- `mzed_t * _mzed_add (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = A + B.$

3.6.1 Detailed Description

3.6.2 Macro Definition Documentation

3.6.2.1 `#define mzd_slice_sub _mzd_slice_add`

$C = A + B.$

Parameters

C	Preallocated sum matrix, may be NULL for automatic creation.
A	Matrix
B	Matrix

3.6.2.2 `#define mzed_sub _mzed_add`

$C = A + B.$

Parameters

C	Preallocated difference matrix, may be NULL for automatic creation.
A	Matrix
B	Matrix

3.6.2.3 #define mzd_slice_sub mzd_slice_add

$$C = A + B.$$

C is also returned. If C is NULL then a new matrix is created which must be freed by [mzd_slice_free\(\)](#).

Parameters

<i>C</i>	Preallocated sum matrix, may be NULL for automatic creation.
<i>A</i>	Matrix
<i>B</i>	Matrix

3.6.2.4 #define mzed_sub mzed_add

$$C = A + B.$$

Parameters

<i>C</i>	Preallocated difference matrix, may be NULL for automatic creation.
<i>A</i>	Matrix
<i>B</i>	Matrix

3.6.3 Function Documentation

3.6.3.1 `static mzd_slice_t* _mzd_slice_add (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`
`[inline], [static]`

$$C = A + B.$$

Parameters

<i>C</i>	Preallocated sum matrix, may be NULL for automatic creation.
<i>A</i>	Matrix
<i>B</i>	Matrix

3.6.3.2 `mzed_t* _mzed_add (mzed_t * C, const mzed_t * A, const mzed_t * B)`

$$C = A + B.$$

Parameters

<i>C</i>	Preallocated sum matrix, may be NULL for automatic creation.
<i>A</i>	Matrix
<i>B</i>	Matrix

3.6.3.3 `static mzd_slice_t* mzd_slice_add (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`
`[inline], [static]`

$$C = A + B.$$

C is also returned. If C is NULL then a new matrix is created which must be freed by [mzd_slice_free\(\)](#).

Parameters

<i>C</i>	Preallocated sum matrix, may be NULL for automatic creation.
<i>A</i>	Matrix

<i>B</i>	Matrix
----------	--------

3.6.3.4 `mzed_t* mzed_add (mzed_t * C, const mzed_t * A, const mzed_t * B)`

$C = A + B$.

C is also returned. If C is NULL then a new matrix is created which must be freed by [mzed_free\(\)](#).

Parameters

<i>C</i>	Preallocated sum matrix, may be NULL for automatic creation.
<i>A</i>	Matrix
<i>B</i>	Matrix

3.7 Multiplication

Functions

- `mzd_slice_t * _mzd_slice_mul_naive (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = A \cdot B$ using quadratic polynomial multiplication with matrix coefficients.
- `mzd_slice_t * _mzd_slice_mul_karatsuba2 (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = A \cdot B$ over \mathbb{F}_2 using 3 multiplications over \mathbb{F}_2 and 2 temporary \mathbb{F}_2 matrices..
- `mzd_slice_t * _mzd_slice_mul_karatsuba3 (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = A \cdot B$ over \mathbb{F}_2 using 6 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices..
- `mzd_slice_t * _mzd_slice_mul_karatsuba4 (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = A \cdot B$ over \mathbb{F}_2 using 9 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices..
- `mzd_slice_t * _mzd_slice_mul_karatsuba5 (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = A \cdot B$ over \mathbb{F}_2 using 13 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices..
- `mzd_slice_t * _mzd_slice_mul_karatsuba6 (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = A \cdot B$ over \mathbb{F}_2 using 17 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices..
- `mzd_slice_t * _mzd_slice_mul_karatsuba7 (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = A \cdot B$ over \mathbb{F}_2 using 22 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices..
- `mzd_slice_t * _mzd_slice_mul_karatsuba8 (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = A \cdot B$ over \mathbb{F}_2 using 27 multiplications over \mathbb{F}_2 and 15 temporary \mathbb{F}_2 matrices..
- `static mzd_slice_t * _mzd_slice_mul_karatsuba (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = C + A \cdot B$ using Karatsuba multiplication of polynomials over matrices over \mathbb{F}_2 .
- `static mzd_slice_t * mzd_slice_mul_karatsuba (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = A \cdot B$ using Karatsuba multiplication of polynomials over matrices over \mathbb{F}_2 .
- `static mzd_slice_t * mzd_slice_addmul_karatsuba (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = C + A \cdot B$ using Karatsuba multiplication of polynomials over matrices over \mathbb{F}_2 .
- `mzd_slice_t * mzd_slice_mul_scalar (mzd_slice_t *C, const word a, const mzd_slice_t *B)`
 $C = a \cdot B$.
- `mzd_slice_t * mzd_slice_addmul_scalar (mzd_slice_t *C, const word a, const mzd_slice_t *B)`
 $C += a \cdot B$.
- `static mzd_slice_t * mzd_slice_mul (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = A \cdot B$.
- `static mzd_slice_t * mzd_slice_addmul (mzd_slice_t *C, const mzd_slice_t *A, const mzd_slice_t *B)`
 $C = C + A \cdot B$.
- `mzed_t * mzed_mul (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = A \cdot B$.
- `mzed_t * mzed_addmul (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = C + A \cdot B$.
- `mzed_t * _mzed_mul (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = A \cdot B$.
- `mzed_t * _mzed_addmul (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = C + A \cdot B$.
- `mzed_t * mzed_addmul_naive (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = C + A \cdot B$ using naive cubic multiplication.
- `mzed_t * mzed_mul_naive (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = A \cdot B$ using naive cubic multiplication.
- `mzed_t * _mzed_mul_naive (mzed_t *C, const mzed_t *A, const mzed_t *B)`

- $C = C + A \cdot B$ using naive cubic multiplication.
- `mzed_t * mzed_mul_scalar (mzed_t *C, const word a, const mzed_t *B)`
 $C = a \cdot B$.
- `mzed_t * mzed_mul_newton_john (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = A \cdot B$ using Newton-John tables.
- `mzed_t * mzed_addmul_newton_john (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = C + A \cdot B$ using Newton-John tables.
- `mzed_t * _mzed_mul_newton_john0 (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = C + A \cdot B$ using Newton-John tables.
- `mzed_t * _mzed_mul_newton_john (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = C + A \cdot B$ using Newton-John tables.
- `mzed_t * mzed_mul_strassen (mzed_t *C, const mzed_t *A, const mzed_t *B, int cutoff)`
 $C = A \cdot B$ using Strassen-Winograd.
- `mzed_t * mzed_addmul_strassen (mzed_t *C, const mzed_t *A, const mzed_t *B, int cutoff)`
 $C = C + A \cdot B$ using Strassen-Winograd.
- `mzed_t * _mzed_mul_strassen (mzed_t *C, const mzed_t *A, const mzed_t *B, int cutoff)`
 $C = A \cdot B$ using Strassen-Winograd.
- `mzed_t * _mzed_addmul_strassen (mzed_t *C, const mzed_t *A, const mzed_t *B, int cutoff)`
 $C = C + A \cdot B$ using Strassen-Winograd.
- `rci_t _mzed_strassen_cutoff (const mzed_t *C, const mzed_t *A, const mzed_t *B)`
Return heuristic choice for crossover parameter for Strassen-Winograd multiplication given A, B and C.

3.7.1 Detailed Description

3.7.2 Function Documentation

3.7.2.1 `static mzd_slice_t* _mzd_slice_mul_karatsuba (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`
`[inline], [static]`

$C = C + A \cdot B$ using Karatsuba multiplication of polynomials over matrices over \mathbb{F}_2 .

This function reduces matrix multiplication over \mathbb{F}_{2^e} to matrix multiplication over \mathbb{F}_2 .

As an example consider \mathbb{F}_4 . The minimal polynomial is $x^2 + x + 1$. The matrix A can be represented as $A0 \cdot x + A1$ and the matrix B can be represented as $B0 \cdot x + B1$. Their product C is

$$A0 \cdot B0 \cdot x^2 + (A0 \cdot B1 + A1 \cdot B0) \cdot x + A1 \cdot B1.$$

Reduction modulo $x^2 + x + 1$ gives

$$(A0 \cdot B0 + A0 \cdot B1 + A1 \cdot B0) \cdot x + A1 \cdot B1 + A0 \cdot B0.$$

This can be re-written as

$$((A0 + A1) \cdot (B0 + B1) + A1 \cdot B1) \cdot x + A1 \cdot B1 + A0 \cdot B0$$

and thus this multiplication costs 3 matrix multiplications over \mathbb{F}_2 and 4 matrix additions over \mathbb{F}_2 .

This technique was proposed in Tomas J. Boothby and Robert W. Bradshaw; Bitslicing and the Method of Four Russians Over Larger Finite Fields; 2009; <http://arxiv.org/abs/0901.1413>

Parameters

<i>C</i>	Preallocated return matrix, may be NULL for automatic creation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

See Also

[mzed_mul\(\)](#) [mzd_slice_mul\(\)](#) [mzd_slice_mul_karatsuba\(\)](#)

3.7.2.2 `mzd_slice_t* mzd_slice_mul_karatsuba2 (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`

$C = A \cdot B$ over \mathbb{F}_{2^2} using 3 multiplications over \mathbb{F}_2 and 2 temporary \mathbb{F}_2 matrices..

Parameters

<i>C</i>	Preallocated return matrix, may be NULL for automatic creation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba\(\)](#)

3.7.2.3 `mzd_slice_t* mzd_slice_mul_karatsuba3 (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`

$C = A \cdot B$ over \mathbb{F}_{2^3} using 6 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices..

The formula was taken from Peter L. Montgomery. "Five, Six, and Seven-Term Karatsuba-Like Formulae" in IEEE TRANSACTIONS ON COMPUTERS, VOL. 54, NO. 3, MARCH 2005/

Parameters

<i>C</i>	Preallocated return matrix, may be NULL for automatic creation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba\(\)](#)

3.7.2.4 `mzd_slice_t* mzd_slice_mul_karatsuba4 (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`

$C = A \cdot B$ over \mathbb{F}_{2^4} using 9 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices..

Parameters

<i>C</i>	Preallocated return matrix, may be NULL for automatic creation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba\(\)](#)

3.7.2.5 `mzd_slice_t* mzd_slice_mul_karatsuba5 (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`

$C = A \cdot B$ over \mathbb{F}_{2^5} using 13 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices..

The formula was taken from Peter L. Montgomery. "Five, Six, and Seven-Term Karatsuba-Like Formulae" in IEEE TRANSACTIONS ON COMPUTERS, VOL. 54, NO. 3, MARCH 2005/

Parameters

C	Preallocated return matrix, may be NULL for automatic creation.
A	Input matrix A.
B	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba\(\)](#)

3.7.2.6 `mzd_slice_t* _mzd_slice_mul_karatsuba6 (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`

$C = A \cdot B$ over \mathbb{F}_{2^6} using 17 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices.

The formula was taken from Peter L. Montgomery. "Five, Six, and Seven-Term Karatsuba-Like Formulae" in IEEE TRANSACTIONS ON COMPUTERS, VOL. 54, NO. 3, MARCH 2005/

Parameters

C	Preallocated return matrix, may be NULL for automatic creation.
A	Input matrix A.
B	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba\(\)](#)

3.7.2.7 `mzd_slice_t* _mzd_slice_mul_karatsuba7 (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`

$C = A \cdot B$ over \mathbb{F}_{2^7} using 22 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices.

The formula was taken from Peter L. Montgomery. "Five, Six, and Seven-Term Karatsuba-Like Formulae" in IEEE TRANSACTIONS ON COMPUTERS, VOL. 54, NO. 3, MARCH 2005/

Parameters

C	Preallocated return matrix, may be NULL for automatic creation.
A	Input matrix A.
B	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba\(\)](#)

3.7.2.8 `mzd_slice_t* _mzd_slice_mul_karatsuba8 (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`

$C = A \cdot B$ over \mathbb{F}_{2^8} using 27 multiplications over \mathbb{F}_2 and 15 temporary \mathbb{F}_2 matrices.

Parameters

C	Preallocated return matrix, may be NULL for automatic creation.
A	Input matrix A.
B	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba\(\)](#)

8 + 7 temporaries

Todo reduce memory requirements by writing formula explicitly

3.7.2.9 `mzd_slice_t* _mzd_slice_mul_naive (mzd_slice_t* C, const mzd_slice_t* A, const mzd_slice_t* B)`

$C = A \cdot B$ using quadratic polynomial multiplication with matrix coefficients.

Parameters

<i>C</i>	Preallocated return matrix, may be NULL for automatic creation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

3.7.2.10 `mzed_t* _mzed_addmul (mzed_t* C, const mzed_t* A, const mzed_t* B)`

$C = C + A \cdot B$.

Parameters

<i>C</i>	Preallocated product matrix.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

3.7.2.11 `mzed_t* _mzed_addmul_strassen (mzed_t* C, const mzed_t* A, const mzed_t* B, int cutoff)`

$C = A \cdot B$ using Strassen-Winograd.

This function uses Strassen-Winograd multiplication (Bodrato variant) recursively until it reaches the cutoff, where it switches to Newton-John table based multiplication or naive multiplication.

Parameters

<i>C</i>	Preallocated product matrix.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.
<i>cutoff</i>	Crossover to basecase dimension > 64

Note

See Marco Bodrato; "A Strassen-like Matrix Multiplication Suited for Squaring and Highest Power Computation"; <http://bodrato.it/papres/#CIVV2008> for reference on the used sequence of operations.

3.7.2.12 `mzed_t* _mzed_mul (mzed_t* C, const mzed_t* A, const mzed_t* B)`

$C = A \cdot B$.

Parameters

<i>C</i>	Preallocated product matrix.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

3.7.2.13 `mzed_t* _mzed_mul_naive (mzed_t* C, const mzed_t* A, const mzed_t* B)`

$C = C + A \cdot B$ using naive cubic multiplication.

Parameters

<i>C</i>	Preallocated product matrix.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

3.7.2.14 `mzed_t* _mzed_mul_newton_john (mzed_t* C, const mzed_t* A, const mzed_t* B)`

$C = C + A \cdot B$ using Newton-John tables.

This is an optimised implementation.

Parameters

<i>C</i>	Preallocated product matrix.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

See Also

[mzed_mul\(\)](#)

3.7.2.15 `mzed_t* _mzed_mul_newton_john0 (mzed_t* C, const mzed_t* A, const mzed_t* B)`

$C = C + A \cdot B$ using Newton-John tables.

This is a simple implementation for clarity of presentation. Do not call, it is slow.

Parameters

<i>C</i>	Preallocated product matrix.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

See Also

[mzed_mul_newton_john\(\)](#) [mzed_mul\(\)](#)

3.7.2.16 `mzed_t* _mzed_mul_strassen (mzed_t* C, const mzed_t* A, const mzed_t* B, int cutoff)`

$C = A \cdot B$ using Strassen-Winograd.

This function uses Strassen-Winograd multiplication (Bodrato variant) recursively until it reaches the cutoff, where it switches to Newton-John table based multiplication or naive multiplication.

Parameters

<i>C</i>	Preallocated product matrix.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.
<i>cutoff</i>	Crossover to basecase dimension > 64

Note

See Marco Bodrato; "A Strassen-like Matrix Multiplication Suited for Squaring and Highest Power Computation"; <http://bodrato.it/papres/#CIVV2008> for reference on the used sequence of operations.

3.7.2.17 `rci_t mzed_strassen_cutoff (const mzed_t * C, const mzed_t * A, const mzed_t * B)`

Return heuristic choice for crossover parameter for Strassen-Winograd multiplication given A, B and C.

Parameters

<i>C</i>	Matrix (ignored)
<i>A</i>	Matrix
<i>B</i>	Matrix (ignored)

3.7.2.18 `static mzd_slice_t* mzd_slice_addmul (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`
[inline], [static]

$C = C + A \cdot B$.

Parameters

<i>C</i>	Preallocated return matrix.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba\(\)](#)

3.7.2.19 `static mzd_slice_t* mzd_slice_addmul_karatsuba (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)` [inline], [static]

$C = C + A \cdot B$ using Karatsuba multiplication of polynomials over matrices over \mathbb{F}_2 .

Parameters

<i>C</i>	Preallocated return matrix.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba\(\)](#)

3.7.2.20 `mzd_slice_t* mzd_slice_addmul_scalar (mzd_slice_t * C, const word a, const mzd_slice_t * B)`

$C+ = a \cdot B$.

Parameters

<i>C</i>	Preallocated product matrix.
<i>a</i>	finite field element.
<i>B</i>	Input matrix B.

3.7.2.21 `static mzd_slice_t* mzd_slice_mul (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`
`[inline], [static]`

$$C = A \cdot B.$$

Parameters

<i>C</i>	Preallocated return matrix, may be NULL for automatic creation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba\(\)](#)

3.7.2.22 `static mzd_slice_t* mzd_slice_mul_karatsuba (mzd_slice_t * C, const mzd_slice_t * A, const mzd_slice_t * B)`
`[inline], [static]`

$$C = A \cdot B \text{ using Karatsuba multiplication of polynomials over matrices over } \mathbb{F}_2.$$

Parameters

<i>C</i>	Preallocated return matrix, may be NULL for automatic creation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba\(\)](#)

3.7.2.23 `mzd_slice_t* mzd_slice_mul_scalar (mzd_slice_t * C, const word a, const mzd_slice_t * B)`

$$C = a \cdot B.$$

Parameters

<i>C</i>	Preallocated product matrix or NULL.
<i>a</i>	finite field element.
<i>B</i>	Input matrix B.

3.7.2.24 `mzed_t* mzed_addmul (mzed_t * C, const mzed_t * A, const mzed_t * B)`

$$C = C + A \cdot B.$$

Parameters

<i>C</i>	Preallocated product matrix, may be NULL for automatic creation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

3.7.2.25 `mzed_t* mzed_addmul_naive (mzed_t * C, const mzed_t * A, const mzed_t * B)`

$$C = C + A \cdot B \text{ using naive cubic multiplication.}$$

Parameters

<i>C</i>	Preallocated product matrix.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

Note

There is no reason to call this function except for checking the correctness of other algorithms. It is very slow.

3.7.2.26 `mzed_t* mzed_addmul_newton_john (mzed_t * C, const mzed_t * A, const mzed_t * B)`

$C = C + A \cdot B$ using Newton-John tables.

Parameters

<i>C</i>	Preallocated product matrix, may be NULL for automatic creation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

See Also

[_mzed_mul_newton_john\(\)](#) [mzed_mul\(\)](#)

3.7.2.27 `mzed_t* mzed_addmul_strassen (mzed_t * C, const mzed_t * A, const mzed_t * B, int cutoff)`

$C = C + A \cdot B$ using Strassen-Winograd.

This function uses Strassen-Winograd multiplication (Bodrato variant) recursively until it reaches the cutoff, where it switches to Newton-John table based multiplication or naive multiplication.

Parameters

<i>C</i>	Preallocated product matrix, may be NULL for allocation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.
<i>cutoff</i>	Crossover to basecase dimension > 64 or 0 for heuristic choice.

3.7.2.28 `mzed_t* mzed_mul (mzed_t * C, const mzed_t * A, const mzed_t * B)`

$C = A \cdot B$.

Parameters

<i>C</i>	Preallocated return matrix, may be NULL for automatic creation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

3.7.2.29 `mzed_t* mzed_mul_naive (mzed_t * C, const mzed_t * A, const mzed_t * B)`

$C = A \cdot B$ using naive cubic multiplication.

Parameters

<i>C</i>	Preallocated product matrix, may be NULL for automatic creation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

Note

There is no reason to call this function except for checking the correctness of other algorithms. It is very slow.

3.7.2.30 `mzed_t* mzed_mul_newton_john (mzed_t * C, const mzed_t * A, const mzed_t * B)`

$C = A \cdot B$ using Newton-John tables.

Parameters

<i>C</i>	Preallocated return matrix, may be NULL for automatic creation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.

See Also

[mzed_mul_mzed_mul_newton_john0\(\)](#)

3.7.2.31 `mzed_t* mzed_mul_scalar (mzed_t * C, const word a, const mzed_t * B)`

$C = a \cdot B$.

Parameters

<i>C</i>	Preallocated product matrix or NULL.
<i>a</i>	finite field element.
<i>B</i>	Input matrix B.

The algorithm proceeds as follows:

0) If a direct approach would need less lookups we use that.

1) We generate a lookup table of 16-bit wide entries

2) We use that lookup table to do 4 lookups per word

3.7.2.32 `mzed_t* mzed_mul_strassen (mzed_t * C, const mzed_t * A, const mzed_t * B, int cutoff)`

$C = A \cdot B$ using Strassen-Winograd.

This function uses Strassen-Winograd multiplication (Bodrato variant) recursively until it reaches the cutoff, where it switches to Newton-John table based multiplication or naive multiplication.

Parameters

<i>C</i>	Preallocated product matrix, may be NULL for allocation.
<i>A</i>	Input matrix A.
<i>B</i>	Input matrix B.
<i>cutoff</i>	Crossover to basecase dimension > 64 or 0 for heuristic choice

3.8 PLE and PLUQ decomposition

Functions

- `rci_t mzed_ple_newton_john (mzed_t *A, mzp_t *P, mzp_t *Q)`
PLE decomposition: $L \cdot E = P \cdot A$ using Newton-John tables.
- `rci_t mzed_ple_naive (mzed_t *A, mzp_t *P, mzp_t *Q)`
PLE decomposition: $L \cdot E = P \cdot A$.
- `rci_t _mzd_slice_ple (mzd_slice_t *A, mzp_t *P, mzp_t *Q, rci_t cutoff)`
PLE decomposition: $L \cdot E = P \cdot A$.
- `static rci_t mzd_slice_ple (mzd_slice_t *A, mzp_t *P, mzp_t *Q)`
PLE decomposition: $L \cdot E = P \cdot A$.
- `rci_t _mzd_slice_pluq (mzd_slice_t *A, mzp_t *P, mzp_t *Q, rci_t cutoff)`
PLUQ decomposition: $L \cdot U \cdot Q = P \cdot A$.
- `static rci_t mzd_slice_pluq (mzd_slice_t *A, mzp_t *P, mzp_t *Q)`
PLUQ decomposition: $L \cdot U \cdot Q = P \cdot A$.
- `rci_t _mzed_ple (mzed_t *A, mzp_t *P, mzp_t *Q, rci_t cutoff)`
PLE decomposition: $L \cdot E = P \cdot A$.
- `static rci_t mzed_ple (mzed_t *A, mzp_t *P, mzp_t *Q)`
PLE decomposition: $L \cdot E = P \cdot A$.

3.8.1 Detailed Description

3.8.2 Function Documentation

3.8.2.1 `rci_t _mzd_slice_ple (mzd_slice_t * A, mzp_t * P, mzp_t * Q, rci_t cutoff)`

PLE decomposition: $L \cdot E = P \cdot A$.

Modifies A in place to store lower triangular L below (and on) the main diagonal and E – an echelon form of A – above the main diagonal (pivots are stored in Q). P and Q are updated with row and column permutations respectively.

This function uses either asymptotically fast PLE decomposition by reducing it to matrix multiplication or naive cubic PLE decomposition depending on the size of the underlying field. If asymptotically fast PLE decomposition is used, then the algorithm switches to `mzed_ple_newton_john` if $e * ncols * nrows$ is \leq cutoff where e is the exponent of the finite field.

Parameters

<i>A</i>	Matrix
<i>P</i>	Permutation vector of length A->nrows
<i>Q</i>	Permutation vector of length A->ncols
<i>cutoff</i>	Integer

See Also

[mzed_ple_naive\(\)](#) [mzed_ple_newton_john\(\)](#) [mzed_ple\(\)](#)

3.8.2.2 `rci_t _mzd_slice_pluq (mzd_slice_t * A, mzp_t * P, mzp_t * Q, rci_t cutoff)`

PLUQ decomposition: $L \cdot U \cdot Q = P \cdot A$.

This function implements asymptotically fast PLE decomposition by reducing it to matrix multiplication. From PLE the PLUQ decomposition is then obtained.

Parameters

<i>A</i>	Matrix
<i>P</i>	Permutation vector of length A->nrows
<i>Q</i>	Permutation vector of length A->ncols
<i>cutoff</i>	Crossover to base case if <code>mzed_t::w * mzed_t::ncols * mzed_t::nrows < cutoff</code> .

3.8.2.3 `rci_t mzed_ple (mzed_t * A, mzp_t * P, mzp_t * Q, rci_t cutoff)`

PLE decomposition: $L \cdot E = P \cdot A$.

Modifies A in place to store lower triangular L below (and on) the main diagonal and E – an echelon form of A – above the main diagonal (pivots are stored in Q). P and Q are updated with row and column permutations respectively.

This function uses either asymptotically fast PLE decomposition by reducing it to matrix multiplication or naive cubic PLE decomposition depending on the size of the underlying field. If asymptotically fast PLE decomposition is used, then the algorithm switches to `mzed_ple_newton_john` if $e * ncols * nrows$ is \leq cutoff where e is the exponent of the finite field.

Parameters

<i>A</i>	Matrix
<i>P</i>	Permutation vector of length A->nrows
<i>Q</i>	Permutation vector of length A->ncols
<i>cutoff</i>	Integer ≥ 0

See Also

[mzed_ple_naive\(\)](#) [mzed_ple_newton_john\(\)](#) [_mzed_ple\(\)](#)

3.8.2.4 `static rci_t mzd_slice_ple (mzd_slice_t * A, mzp_t * P, mzp_t * Q) [inline], [static]`

PLE decomposition: $L \cdot E = P \cdot A$.

Modifies A in place to store lower triangular L below (and on) the main diagonal and E – an echelon form of A – above the main diagonal (pivots are stored in Q). P and Q are updated with row and column permutations respectively.

This function implements asymptotically fast PLE decomposition by reducing it to matrix multiplication.

Parameters

<i>A</i>	Matrix
<i>P</i>	Permutation vector of length A->nrows
<i>Q</i>	Permutation vector of length A->ncols

See Also

[mzed_ple_naive\(\)](#) [mzed_ple_newton_john\(\)](#) [_mzd_slice_ple\(\)](#)

3.8.2.5 `static rci_t mzd_slice_pluq (mzd_slice_t * A, mzp_t * P, mzp_t * Q) [inline], [static]`

PLUQ decomposition: $L \cdot U \cdot Q = P \cdot A$.

This function implements asymptotically fast PLE decomposition by reducing it to matrix multiplication. From PLE the PLUQ decomposition is then obtained.

Parameters

A	Matrix
P	Permutation vector of length $A \rightarrow \text{nrows}$
Q	Permutation vector of length $A \rightarrow \text{ncols}$

3.8.2.6 `static rci_t mzed_ple (mzed_t * A , mzp_t * P , mzp_t * Q)` `[inline], [static]`

PLE decomposition: $L \cdot E = P \cdot A$.

Modifies A in place to store lower triangular L below (and on) the main diagonal and E – an echelon form of A – above the main diagonal (pivots are stored in Q). P and Q are updated with row and column permutations respectively.

This function uses either asymptotically fast PLE decomposition by reducing it to matrix multiplication or naive cubic PLE decomposition depending on the size of the underlying field.

Parameters

A	Matrix
P	Permutation vector of length $A \rightarrow \text{nrows}$
Q	Permutation vector of length $A \rightarrow \text{ncols}$

See Also

[mzed_ple_naive\(\)](#) [mzed_ple_newton_john\(\)](#) [_mzed_ple\(\)](#)

3.8.2.7 `rci_t mzed_ple_naive (mzed_t * A , mzp_t * P , mzp_t * Q)`

PLE decomposition: $L \cdot E = P \cdot A$.

Modifies A in place to store lower triangular L below (and on) the main diagonal and E – an echelon form of A – above the main diagonal (pivots are stored in Q). P and Q are updated with row and column permutations respectively.

This function uses naive cubic PLE decomposition depending on the size of the underlying field.

Parameters

A	Matrix
P	Permutation vector of length $A \rightarrow \text{nrows}$
Q	Permutation vector of length $A \rightarrow \text{ncols}$

See Also

[mzed_ple_newton_john\(\)](#) [mzed_ple\(\)](#)

3.9 Echelon forms

Macros

- `#define mzd_slice_echelonize mzd_slice_echelonize_ple`
Compute row echelon forms.

Functions

- `rci_t mzd_slice_echelonize_ple (mzd_slice_t *A, int full)`
Compute row echelon forms using PLE decomposition.
- `static rci_t mzed_echelonize_ple (mzed_t *A, int full)`
Compute row echelon forms using PLE decomposition.
- `rci_t mzed_echelonize (mzed_t *A, int full)`
Compute row echelon forms.
- `rci_t mzed_echelonize_naive (mzed_t *A, int full)`
Gaussian elimination.
- `rci_t mzed_echelonize_newton_john (mzed_t *A, int full)`
Reduce matrix A to row echelon form using Gauss-Newton-John elimination.

3.9.1 Detailed Description

3.9.2 Macro Definition Documentation

3.9.2.1 `#define mzd_slice_echelonize mzd_slice_echelonize_ple`

Compute row echelon forms.

Compute the (reduced) row echelon form of the matrix A. If full=0, then return the reduced REF.

Parameters

<i>A</i>	Matrix
<i>full</i>	REF or RREF.

3.9.3 Function Documentation

3.9.3.1 `rci_t mzd_slice_echelonize_ple (mzd_slice_t * A, int full)`

Compute row echelon forms using PLE decomposition.

Compute the (reduced) row echelon form of the matrix A. If full=0, then return the reduced row echelon. This function reduces echelon forms to PLE (or PLUQ) decomposition.

Parameters

<i>A</i>	Matrix
<i>full</i>	REF or RREF.

3.9.3.2 `rci_t mzed_echelonize (mzed_t * A, int full)`

Compute row echelon forms.

Compute the (reduced) row echelon form of the matrix A. If full=0, then return the reduced row echelon form.

Parameters

<i>A</i>	Matrix
<i>full</i>	REF or RREF.

3.9.3.3 `rci.t mzed_echelonize_naive (mzed_t * A, int full)`

Gaussian elimination.

Perform Gaussian elimination on the matrix A. If full=0, then it will do triangular style elimination, and if full=1, it will do Gauss-Jordan style, or full elimination.

Parameters

<i>A</i>	Matrix
<i>full</i>	Gauss-Jordan style or upper unit-triangular form only.

3.9.3.4 `rci.t mzed_echelonize_newton_john (mzed_t * A, int full)`

Reduce matrix A to row echelon form using Gauss-Newton-John elimination.

Parameters

<i>A</i>	Matrix to be reduced.
<i>full</i>	If set to true, the reduced row echelon form will be computed.

Todo we don't really compute the upper triangular form yet, we need to implement `_mzed_gauss_submatrix()` and a better table creation for that.

3.9.3.5 `static rci.t mzed_echelonize_ple (mzed_t * A, int full) [inline],[static]`

Compute row echelon forms using PLE decomposition.

Compute the (reduced) row echelon form of the matrix A. If full=0, then return the reduced REF. This function reduces echelon forms to PLE (or PLUQ) decomposition.

Parameters

<i>A</i>	Matrix
<i>full</i>	REF or RREF.

Note

This function converts A to bitslice representation and back. Hence, it uses more memory than using `mzed_echelonize_newton_john()` or `mzd_slice_echelonize_ple()`

Examples:

[tests/test_elimination.cc](#).

3.10 Triangular matrices

Functions

- void `mzed_trsm_lower_left_newton_john` (const `mzed_t` **L*, `mzed_t` **B*)
 $B = L^{-1} \cdot B$ using Newton-John tables.
- void `mzd_slice_trsm_lower_left_newton_john` (const `mzd_slice_t` **L*, `mzd_slice_t` **B*)
 $B = L^{-1} \cdot B$ using Newton-John tables.
- void `mzed_trsm_upper_left_newton_john` (const `mzed_t` **U*, `mzed_t` **B*)
 $B = U^{-1} \cdot B$ using Newton-John tables.
- void `mzd_slice_trsm_upper_left_newton_john` (const `mzd_slice_t` **U*, `mzd_slice_t` **B*)
 $B = U^{-1} \cdot B$ using Newton-John tables.
- void `_mzed_trsm_upper_left` (const `mzed_t` **U*, `mzed_t` **B*, const `rci_t` cutoff)
 $B = U^{-1} \cdot B$
- void `mzed_trsm_upper_left_naive` (const `mzed_t` **U*, `mzed_t` **B*)
 $B = U^{-1} \cdot B$
- static void `mzed_trsm_upper_left` (const `mzed_t` **U*, `mzed_t` **B*)
 $B = U^{-1} \cdot B$
- void `_mzd_slice_trsm_upper_left` (const `mzd_slice_t` **U*, `mzd_slice_t` **B*, const `rci_t` cutoff)
 $B = U^{-1} \cdot B$
- void `mzd_slice_trsm_upper_left_naive` (const `mzd_slice_t` **U*, `mzd_slice_t` **B*)
 $B = U^{-1} \cdot B$
- static void `mzd_slice_trsm_upper_left` (const `mzd_slice_t` **U*, `mzd_slice_t` **B*)
 $B = U^{-1} \cdot B$
- void `_mzed_trsm_lower_left` (const `mzed_t` **L*, `mzed_t` **B*, const `rci_t` cutoff)
 $B = L^{-1} \cdot B$
- void `mzed_trsm_lower_left_naive` (const `mzed_t` **L*, `mzed_t` **B*)
 $B = L^{-1} \cdot B$
- static void `mzed_trsm_lower_left` (const `mzed_t` **L*, `mzed_t` **B*)
 $B = L^{-1} \cdot B$
- void `_mzd_slice_trsm_lower_left` (const `mzd_slice_t` **L*, `mzd_slice_t` **B*, const `rci_t` cutoff)
 $B = L^{-1} \cdot B$
- void `mzd_slice_trsm_lower_left_naive` (const `mzd_slice_t` **L*, `mzd_slice_t` **B*)
 $B = L^{-1} \cdot B$
- static void `mzd_slice_trsm_lower_left` (const `mzd_slice_t` **L*, `mzd_slice_t` **B*)
 $B = L^{-1} \cdot B$

3.10.1 Detailed Description

3.10.2 Function Documentation

3.10.2.1 void `_mzd_slice_trsm_lower_left` (const `mzd_slice_t` * *L*, `mzd_slice_t` * *B*, const `rci_t` *cutoff*)

$$B = L^{-1} \cdot B$$

Parameters

<i>L</i>	Lower-triangular matrix (other entries are ignored).
<i>B</i>	Matrix.
<i>cutoff</i>	Crossover dimension to base case.

3.10.2.2 `void _mzd_slice_trsm_upper_left (const mzd_slice_t * U, mzd_slice_t * B, const rci_t cutoff)`

$$B = U^{-1} \cdot B$$

Parameters

<i>U</i>	Upper-triangular matrix (other entries are ignored).
<i>B</i>	Matrix.
<i>cutoff</i>	Crossover dimension to base case.

3.10.2.3 `void _mzed_trsm_lower_left (const mzed_t * L, mzed_t * B, const rci_t cutoff)`

$$B = L^{-1} \cdot B$$

Parameters

<i>L</i>	Lower-triangular matrix (other entries are ignored).
<i>B</i>	Matrix.
<i>cutoff</i>	Crossover dimension to base case.

3.10.2.4 `void _mzed_trsm_upper_left (const mzed_t * U, mzed_t * B, const rci_t cutoff)`

$$B = U^{-1} \cdot B$$

Parameters

<i>U</i>	Upper-triangular matrix (other entries are ignored).
<i>B</i>	Matrix.
<i>cutoff</i>	Crossover dimension to base case.

3.10.2.5 `static void mzd_slice_trsm_lower_left (const mzd_slice_t * L, mzd_slice_t * B) [inline], [static]`

$$B = L^{-1} \cdot B$$

Parameters

<i>L</i>	Lower-triangular matrix (other entries are ignored).
<i>B</i>	Matrix.

3.10.2.6 `void mzd_slice_trsm_lower_left_naive (const mzd_slice_t * L, mzd_slice_t * B)`

$$B = L^{-1} \cdot B$$

Parameters

<i>L</i>	Lower-triangular matrix (other entries are ignored).
<i>B</i>	Matrix.

3.10.2.7 `void mzd_slice_trsm_lower_left_newton_john (const mzd_slice_t * L, mzd_slice_t * B)`

$$B = L^{-1} \cdot B \text{ using Newton-John tables.}$$

Parameters

L	Lower-triangular matrix (other entries are ignored).
B	Matrix.

3.10.2.8 `static void mzd_slice_trsm_upper_left (const mzd_slice_t * U , mzd_slice_t * B)` `[inline],[static]`

$$B = U^{-1} \cdot B$$

Parameters

U	Upper-triangular matrix (other entries are ignored).
B	Matrix.

3.10.2.9 `void mzd_slice_trsm_upper_left_naive (const mzd_slice_t * U , mzd_slice_t * B)`

$$B = U^{-1} \cdot B$$

Parameters

U	Upper-triangular matrix (other entries are ignored).
B	Matrix.

3.10.2.10 `void mzd_slice_trsm_upper_left_newton_john (const mzd_slice_t * U , mzd_slice_t * B)`

$$B = U^{-1} \cdot B \text{ using Newton-John tables.}$$

Parameters

U	Upper-triangular matrix (other entries are ignored).
B	Matrix.

3.10.2.11 `static void mzed_trsm_lower_left (const mzed_t * L , mzed_t * B)` `[inline],[static]`

$$B = L^{-1} \cdot B$$

Parameters

L	Lower-triangular matrix (other entries are ignored).
B	Matrix.

3.10.2.12 `void mzed_trsm_lower_left_naive (const mzed_t * L , mzed_t * B)`

$$B = L^{-1} \cdot B$$

Parameters

L	Lower-triangular matrix (other entries are ignored).
B	Matrix.

3.10.2.13 `void mzed_trsm_lower_left_newton_john (const mzed_t * L , mzed_t * B)`

$$B = L^{-1} \cdot B \text{ using Newton-John tables.}$$

Parameters

L	Lower-triangular matrix (other entries are ignored).
B	Matrix.

3.10.2.14 `static void mzed_trsm_upper_left (const mzed_t * U , mzed_t * B)` `[inline], [static]`

$$B = U^{-1} \cdot B$$

Parameters

U	Upper-triangular matrix (other entries are ignored).
B	Matrix.

3.10.2.15 `void mzed_trsm_upper_left_naive (const mzed_t * U , mzed_t * B)`

$$B = U^{-1} \cdot B$$

Parameters

U	Upper-triangular matrix (other entries are ignored).
B	Matrix.

3.10.2.16 `void mzed_trsm_upper_left_newton_john (const mzed_t * U , mzed_t * B)`

$$B = U^{-1} \cdot B \text{ using Newton-John tables.}$$

Parameters

U	Upper-triangular matrix (other entries are ignored).
B	Matrix.

4 Data Structure Documentation

4.1 gf2e_struct Struct Reference

Data Fields

- unsigned int `degree`
- word `minpoly`
- word * `pow_gen`
- word * `red`
- word ** `_mul`
- word(* `inv`)(const `gf2e` *ff, const word a)
- word(* `mul`)(const `gf2e` *ff, const word a, const word b)

4.1.1 Detailed Description

Examples:

[tests/test_elimination.cc](#).

4.1.2 Field Documentation

4.1.2.1 word** gf2e_struct::_mul

`mul[a][b]` holds $a \cdot b$ for small fields.

4.1.2.2 unsigned int gf2e_struct::degree

The degree e .

Examples:

[tests/test_elimination.cc](#).

4.1.2.3 word(* gf2e_struct::inv)(const gf2e *ff, const word a)

implements a^{-1} for a in \mathbb{F}_{2^e}

4.1.2.4 word gf2e_struct::minpoly

Irreducible polynomial of degree e .

Examples:

[tests/test_elimination.cc](#).

4.1.2.5 word(* gf2e_struct::mul)(const gf2e *ff, const word a, const word b)

implements $a \cdot b$ for a in \mathbb{F}_{2^e}

4.1.2.6 word* gf2e_struct::pow_gen

`pow_gen[i]` holds $a^i / \langle f \rangle$ for a a generator of this field.

4.1.2.7 word* gf2e_struct::red

red[i] holds precomputed reducers for the minpoly.

The documentation for this struct was generated from the following file:

- [gf2e.h](#)

4.2 mzd_poly_t Struct Reference

Data Fields

- mzd_t ** **x**
- rci_t [nrows](#)
- rci_t [ncols](#)
- deg_t [depth](#)

4.2.1 Field Documentation

4.2.1.1 deg_t mzd_poly_t::depth

Degree +1

4.2.1.2 rci_t mzd_poly_t::ncols

Number of columns.

4.2.1.3 rci_t mzd_poly_t::nrows

Number of rows.

The documentation for this struct was generated from the following file:

- [mzd_poly.h](#)

4.3 mzd_slice_t Struct Reference

Dense matrices over \mathbb{F}_{2^e} represented as slices of matrices over \mathbb{F}_2 .

```
#include <mzd_slice.h>
```

Data Fields

- mzd_t * **x** [16]
- rci_t [nrows](#)
- rci_t [ncols](#)
- unsigned int [depth](#)
- const [gf2e](#) * [finite_field](#)

4.3.1 Detailed Description

Dense matrices over \mathbb{F}_{2^e} represented as slices of matrices over \mathbb{F}_2 .

This is one of two fundamental data types of this library, the other being [mzed_t](#). For large matrices ($m \times n \times e > L2$) it is advisable to use this data type because multiplication is faster in this representation. Hence, compared to [mzed_t](#) one saves the time to convert between representations and - more importantly - memory.

4.3.2 Field Documentation

4.3.2.1 unsigned int mzd_slice_t::depth

Number of slices *

Note

This value may be greater than `finite_field->degree` in some situations

4.3.2.2 const gf2e* mzd_slice_t::finite_field

A finite field \mathbb{F}_{2^e} .

4.3.2.3 rci_t mzd_slice_t::ncols

Number of columns.

4.3.2.4 rci_t mzd_slice_t::nrows

Number of rows.

4.3.2.5 mzd_t* mzd_slice_t::x[16]

[mzd_slice_t::x\[e\]\[i,j\]](#) is the e -th bit of the entry $A[i,j]$.

The documentation for this struct was generated from the following file:

- [mzd_slice.h](#)

4.4 mzed_t Struct Reference

Dense matrices over \mathbb{F}_{2^e} represented as packed matrices.

```
#include <mzed.h>
```

Data Fields

- `mzd_t * x`
- `const gf2e * finite_field`
- `rci_t nrows`
- `rci_t ncols`
- `wi_t w`

4.4.1 Detailed Description

Dense matrices over \mathbb{F}_{2^e} represented as packed matrices.

Examples:

[tests/test_elimination.cc](#).

4.4.2 Field Documentation

4.4.2.1 `const gf2e* mzed_t::finite_field`

A finite field \mathbb{F}_{2^e} .

4.4.2.2 `rci_t mzed_t::ncols`

Number of columns.

4.4.2.3 `rci_t mzed_t::nrows`

Number of rows.

4.4.2.4 `wi_t mzed_t::w`

The internal width of elements (must divide 64).

4.4.2.5 `mzd_t* mzed_t::x`

$m \times n$ matrices over \mathbb{F}_{2^e} are represented as $m \times (en)$ matrices over \mathbb{F}_2 .

The documentation for this struct was generated from the following file:

- [mzed.h](#)

4.5 njt_mzed_t Struct Reference

Newton-John table.

```
#include <newton_john.h>
```

Data Fields

- `rci_t * L`
- `mzed_t * M`
- `mzed_t * T`

4.5.1 Detailed Description

Newton-John table.

4.5.2 Field Documentation

4.5.2.1 `rci_t* njt_mzed_t::L`

A map such that `L[a]` points to the row where the first entry is `a`.

4.5.2.2 `mzed_t* njt_mzed_t::M`

Table of length e with multiples of the input s.t. a^i is the first entry of row i .

4.5.2.3 `mzed_t* njt_mzed_t::T`

Actual table of length 2^e of all linear combinations of `T`.

The documentation for this struct was generated from the following file:

- [newton_john.h](#)

5 File Documentation

5.1 conversion.h File Reference

Conversion between `mzed_t` and `mzd_slice_t`.

```
#include <m4ri/m4ri.h>
#include <m4rie/mzed.h>
#include <m4rie/mzd_slice.h>
```

Functions

- `mzed_t* mzed_cling(mzed_t*A, const mzd_slice_t*Z)`
Pack a bitslice matrix into a packed representation.
- `mzd_slice_t* mzed_slice(mzd_slice_t*A, const mzed_t*Z)`
Unpack the matrix Z into bitslice representation.
- `mzd_slice_t* _mzed_slice2(mzd_slice_t*A, const mzed_t*Z)`
Unpack the matrix Z over $GF(2^2)$ into bitslice representation.
- `mzd_slice_t* _mzed_slice4(mzd_slice_t*A, const mzed_t*Z)`
Unpack the matrix Z over \mathbb{F}_{2^e} into bitslice representation.
- `mzd_slice_t* _mzed_slice8(mzd_slice_t*A, const mzed_t*Z)`
Unpack the matrix Z over \mathbb{F}_{2^e} into bitslice representation.
- `mzd_slice_t* _mzed_slice16(mzd_slice_t*A, const mzed_t*Z)`
Unpack the matrix Z over \mathbb{F}_{2^e} into bitslice representation.
- `mzed_t* _mzed_cling2(mzed_t*A, const mzd_slice_t*Z)`
Pack a bitslice matrix into a classical representation over $GF(2^2)$.
- `mzed_t* _mzed_cling4(mzed_t*A, const mzd_slice_t*Z)`
Pack a bitslice matrix into a classical representation over \mathbb{F}_{2^e} for $2 < e \leq 4$.
- `mzed_t* _mzed_cling8(mzed_t*A, const mzd_slice_t*Z)`
Pack a bitslice matrix into a classical representation over \mathbb{F}_{2^e} for $4 < e \leq 8$.
- `mzed_t* _mzed_cling16(mzed_t*A, const mzd_slice_t*Z)`
Pack a bitslice matrix into a classical representation over \mathbb{F}_{2^e} for $8 < e \leq 16$.
- `static mzed_t* _mzed_mul_karatsuba(mzed_t*C, const mzed_t*A, const mzed_t*B)`

*Compute $C \leftarrow A * B$ using Karatsuba multiplication of polynomials over $GF(2)$.*

- static `mzed_t * mzed_mul_karatsuba (mzed_t *C, const mzed_t *A, const mzed_t *B)`

*Compute $C = A * B$.*

- static `mzed_t * mzed_addmul_karatsuba (mzed_t *C, const mzed_t *A, const mzed_t *B)`

*Compute $C \leftarrow A * B$.*

- static void `mzd_slice_rescale_row (mzd_slice_t *A, rci_t r, rci_t c, word x)`

Rescale the row r in A by X starting c .

Variables

- static const word `x80008000` = 0x8000800080008000ULL
- static const word `x80808080` = 0x8080808080808080ULL
- static const word `x88888888` = 0x8888888888888888ULL
- static const word `xaaaaaaaa` = 0aaaaaaaaaaaaaaaaaULL
- static const word `xc0c0c0c0` = 0xc0c0c0c0c0c0c0c0ULL
- static const word `xc0c0c0c0` = 0xc0c0c0c0c0c0c0c0ULL
- static const word `xf0f0f0f0` = 0xf0f0f0f0f0f0f0f0ULL
- static const word `xff00ff00` = 0xff00ff00ff00ff00ULL
- static const word `xffff0000` = 0xffff0000ffff0000ULL
- static const word `ffffff00` = 0xffffffff00000000ULL
- static const word `x__left04` = 0xf000000000000000ULL
- static const word `x__left08` = 0xff00000000000000ULL
- static const word `x__left16` = 0xffff000000000000ULL
- static const word `x__left32` = 0xffffffff00000000ULL

5.1.1 Detailed Description

Conversion between `mzed_t` and `mzd_slice_t`.

Author

Martin Albrecht martinralbrecht@googlemail.com

5.1.2 Function Documentation

5.1.2.1 `mzed_t * mzed_cling16 (mzed_t * A, const mzd_slice_t * Z)`

Pack a bitslice matrix into a classical representation over \mathbb{F}_{2^e} for $8 < e \leq 16$.

Parameters

<code>A</code>	Matrix over \mathbb{F}_{2^e} , must be zero
<code>Z</code>	Bitslice matrix over \mathbb{F}_{2^e}

5.1.2.2 `mzed_t * mzed_cling2 (mzed_t * A, const mzd_slice_t * Z)`

Pack a bitslice matrix into a classical representation over $GF(2^2)$.

Elements in $GF(2^2)$ can be represented as $c_1 * a + c_0$ where a is a root of $x^2 + x + 1$. `A1` contains the coefficients for `c_1` while `A0` contains the coefficients for `c_0`.

Parameters

A	Matrix over $\text{GF}(2^2)$, must be zero
Z	Bitslice matrix over $\text{GF}(2^2)$

5.1.2.3 `mzed_t* _mzed_cling4 (mzed_t * A, const mzd_slice_t * Z)`

Pack a bitslice matrix into a classical representation over \mathbb{F}_{2^e} for $2 < e \leq 4$.

Parameters

A	Matrix over \mathbb{F}_{2^e} , must be zero
Z	Bitslice matrix over \mathbb{F}_{2^e}

5.1.2.4 `mzed_t* _mzed_cling8 (mzed_t * A, const mzd_slice_t * Z)`

Pack a bitslice matrix into a classical representation over \mathbb{F}_{2^e} for $4 < e \leq 8$.

Parameters

A	Matrix over \mathbb{F}_{2^e} , must be zero
Z	Bitslice matrix over \mathbb{F}_{2^e}

5.1.2.5 `static mzed_t* _mzed_mul_karatsuba (mzed_t * C, const mzed_t * A, const mzed_t * B) [inline], [static]`

Compute $C += A*B$ using Karatsuba multiplication of polynomials over $\text{GF}(2)$.

Parameters

C	Preallocated return matrix, may be NULL for automatic creation.
A	Input matrix A.
B	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba](#)

5.1.2.6 `mzd_slice_t* _mzed_slice16 (mzd_slice_t * A, const mzed_t * Z)`

Unpack the matrix Z over \mathbb{F}_{2^e} into bitslice representation.

Parameters

A	Zero bitslice matrix over \mathbb{F}_{2^e}
Z	Matrix over \mathbb{F}_{2^e}

5.1.2.7 `mzd_slice_t* _mzed_slice2 (mzd_slice_t * A, const mzed_t * Z)`

Unpack the matrix Z over $\text{GF}(2^2)$ into bitslice representation.

Elements in $\text{GF}(2^2)$ can be represented as $x*a + y$ where a is a root of $x^2 + x + 1$. A0 contains the coefficients for x while A1 contains the coefficients for y .

Parameters

A	Zero bitslice matrix over $\text{GF}(2^2)$
Z	Matrix over $\text{GF}(2^2)$

5.1.2.8 `mzd_slice_t* _mzed_slice4 (mzd_slice_t * A, const mzed_t * Z)`

Unpack the matrix Z over \mathbb{F}_{2^e} into bitslice representation.

Parameters

A	Zero bitslice matrix over \mathbb{F}_{2^e}
Z	Matrix over \mathbb{F}_{2^e}

5.1.2.9 `mzd_slice_t* _mzed_slice8 (mzd_slice_t * A, const mzed_t * Z)`

Unpack the matrix Z over \mathbb{F}_{2^e} into bitslice representation.

Parameters

A	Zero bitslice matrix over \mathbb{F}_{2^e}
Z	Matrix over \mathbb{F}_{2^e}

5.1.2.10 `static mzed_t* mzed_addmul_karatsuba (mzed_t * C, const mzed_t * A, const mzed_t * B) [inline], [static]`

Compute $C += A*B$.

Parameters

C	Preallocated return matrix.
A	Input matrix A.
B	Input matrix B.

5.1.2.11 `static mzed_t* mzed_mul_karatsuba (mzed_t * C, const mzed_t * A, const mzed_t * B) [inline], [static]`

Compute $C = A*B$.

Parameters

C	Preallocated return matrix, may be NULL for automatic creation.
A	Input matrix A.
B	Input matrix B.

See Also

[_mzd_slice_mul_karatsuba](#)

5.2 echelonform.h File Reference

Echelon forms.

```
#include <m4rie/mzed.h>
#include <m4rie/mzd_slice.h>
#include <m4rie/conversion.h>
```

Macros

- `#define mzd_slice_echelonize mzd_slice_echelonize_ple`
Compute row echelon forms.

Functions

- `rci_t mzd_slice_echelonize_ple (mzd_slice_t *A, int full)`
Compute row echelon forms using PLE decomposition.
- `static rci_t mzed_echelonize_ple (mzed_t *A, int full)`
Compute row echelon forms using PLE decomposition.
- `rci_t mzed_echelonize (mzed_t *A, int full)`
Compute row echelon forms.

5.2.1 Detailed Description

Echelon forms.

Author

Martin Albrecht martinralbrecht@googlemail.com

5.3 gf2e.h File Reference

\mathbb{F}_{2^e}

```
#include <m4rie/m4rie.h>
#include <m4rie/gf2x.h>
```

Data Structures

- struct `gf2e_struct`

Macros

- `#define M4RIE_MAX_DEGREE 16`

Typedefs

- typedef struct `gf2e_struct` `gf2e`
 \mathbb{F}_{2^e}

Functions

- `gf2e * gf2e_init` (const word minpoly)
- void `gf2e_free` (gf2e *ff)
- static word `gf2e_inv` (const gf2e *ff, word a)
 $a^{(-1)} \% \text{minpoly}$
- static word `_gf2e_mul_table` (const gf2e *ff, const word a, const word b)
 $a*b$ in \mathbb{F}_{2^e} using a table lookups.
- static word `_gf2e_mul_arith` (const gf2e *ff, const word a, const word b)
 $a*b$ in \mathbb{F}_{2^e} using a `gf2x_mul()` lookups.
- static word `gf2e_mul` (const gf2e *ff, const word a, const word b)
 $a*b$ in \mathbb{F}_{2^e} .
- static size_t `gf2e_degree_to_w` (const gf2e *ff)
- static word * `gf2e_t16_init` (const gf2e *ff, const word a)
- static void `gf2e_t16_free` (word *mul)
Free multiplication table.

Variables

- const word * `irreducible_polynomials` [17]

5.3.1 Detailed Description

 \mathbb{F}_{2^e}

Author

Martin Albrecht martinralbrecht@googlemail.com

5.3.2 Function Documentation

5.3.2.1 static size_t gf2e_degree_to_w (const gf2e * ff) [inline],[static]

Return the width used for storing elements of ff

Parameters

<code>ff</code>	Finite field.
-----------------	---------------

5.3.2.2 void gf2e_free (gf2e * ff)

Free ff

Parameters

<code>ff</code>	Finite field.
-----------------	---------------

Examples:

[tests/test_elimination.cc](#).

5.3.2.3 gf2e* gf2e_init (const word minpoly)

Create finite field from minimal polynomial

Parameters

<i>minpoly</i>	Polynomial represented as series of bits.
----------------	---

red

pow_gen: X^i

mul tables

Examples:

[tests/test_elimination.cc](#).

5.3.2.4 static void gf2e.t16_free (word * mul) [inline],[static]

Free multiplication table.

Parameters

<i>mul</i>	Multiplication table
------------	----------------------

5.3.2.5 static word* gf2e.t16_init (const gf2e * ff, const word a) [inline],[static]

Compute all multiples by a of vectors fitting into 16 bits.

Parameters

<i>ff</i>	Finite field.
<i>a</i>	Finite field element.

Todo : this is a bit of overkill, we could do better

5.4 gf2x.h File Reference

\mathbb{F}_{2^x} for degrees < 64

```
#include <m4ri/m4ri.h>
```

Macros

- `#define __M4RIE_1tF(X) ~((X)-1)`

Functions

- static word `gf2x_mul` (const word a, const word b, unsigned int d)
 $a * b$ in \mathbb{F}_{2^x} with $\deg(a)$ and $\deg(b) < d$.
- static int `gf2x_deg` (word a)

- $\deg(a)$ in \mathbb{F}_{2^x} .
- static word `gf2x_div` (word a, word b)
 a / b in \mathbb{F}_{2^x} .
- static word `gf2x_mod` (word a, word b)
 $a \bmod b$ in \mathbb{F}_{2^x} .
- static word `gf2x_divmod` (word a, word b, word *rem)
 a / b and $a \bmod b$ in \mathbb{F}_{2^x} .
- static word `gf2x_invmod` (word a, word b, unsigned int d)
 $a^{-1} \bmod b$ with $\deg(a), \deg(b) \leq d$.

5.4.1 Detailed Description

\mathbb{F}_{2^x} for degrees < 64

Author

Martin Albrecht martinralbrecht@googlemail.com

Warning

Do not rely on these functions for high performance, they are not fully optimised.

5.4.2 Macro Definition Documentation

5.4.2.1 `#define __M4RIE_1tF(X) ~((X)-1)`

Maps 1 to word with all ones and 0 to 0.

5.4.3 Function Documentation

5.4.3.1 `static int gf2x_deg (word a) [inline], [static]`

$\deg(a)$ in \mathbb{F}_{2^x} .

Parameters

<i>a</i>	Polynomial of degree ≤ 64 .
----------	----------------------------------

5.5 m4rie.h File Reference

Main include file for the M4RIE library.


```
#include <m4rie/gf2e.h>
#include <m4rie/mzed.h>
#include <m4rie/newton_john.h>
#include <m4rie/echelonform.h>
#include <m4rie/strassen.h>
#include <m4rie/mzd_slice.h>
#include <m4rie/trsm.h>
#include <m4rie/ple.h>
#include <m4rie/conversion.h>
#include <m4rie/permutation.h>
#include <m4rie/mzd_poly.h>
```

5.5.1 Detailed Description

Main include file for the M4RIE library.

Author

Martin Albrecht martinralbrecht@googlemail.com

5.6 mzd_slice.h File Reference

Matrices using a bitsliced representation.

```
#include <m4ri/m4ri.h>
#include <m4rie/mzd_poly.h>
#include <m4rie/mzed.h>
```

Data Structures

- struct [mzd_slice_t](#)
Dense matrices over \mathbb{F}_{2^e} represented as slices of matrices over \mathbb{F}_2 .

Macros

- #define [mzd_slice_sub mzd_slice_add](#)
 $C = A + B.$
- #define [_mzd_slice_sub _mzd_slice_add](#)
 $C = A + B.$

Functions

- static [mzd_slice_t * mzd_slice_init](#) (const [gf2e](#) *ff, const rci_t m, const rci_t n)
Create a new matrix of dimension $m \times n$ over ff.
- void [mzd_slice_set_ui](#) ([mzd_slice_t](#) *A, word value)
Return diagonal matrix with value on the diagonal.
- static [mzd_slice_t * _mzd_slice_adapt_depth](#) ([mzd_slice_t](#) *A, const unsigned int new_depth)
Extend or truncate the depth of A to depth new_depth.

- static void `mzd_slice_free` (`mzd_slice_t` *A)
Free a matrix created with `mzd_slice_init()`.
- static `mzd_slice_t` * `mzd_slice_concat` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
Concatenate B to A and write the result to C.
- static `mzd_slice_t` * `mzd_slice_stack` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
Stack A on top of B and write the result to C.
- static `mzd_slice_t` * `mzd_slice_submatrix` (`mzd_slice_t` *S, const `mzd_slice_t` *A, const size_t lowr, const size_t lowc, const size_t highr, const size_t highc)
Copy a submatrix.
- static `mzd_slice_t` * `mzd_slice_init_window` (const `mzd_slice_t` *A, const size_t lowr, const size_t lowc, const size_t highr, const size_t highc)
Create a window/view into the matrix M.
- static void `mzd_slice_free_window` (`mzd_slice_t` *A)
Free a matrix window created with `mzd_slice_init_window()`.
- static `mzd_slice_t` * `_mzd_slice_add` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = A + B$.
- static `mzd_slice_t` * `mzd_slice_add` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = A + B$.
- `mzd_slice_t` * `_mzd_slice_mul_naive` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = A \cdot B$ using quadratic polynomial multiplication with matrix coefficients.
- `mzd_slice_t` * `_mzd_slice_mul_karatsuba2` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = A \cdot B$ over \mathbb{F}_{2^2} using 3 multiplications over \mathbb{F}_2 and 2 temporary \mathbb{F}_2 matrices..
- `mzd_slice_t` * `_mzd_slice_mul_karatsuba3` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = A \cdot B$ over \mathbb{F}_{2^3} using 6 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices..
- `mzd_slice_t` * `_mzd_slice_mul_karatsuba4` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = A \cdot B$ over \mathbb{F}_{2^4} using 9 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices..
- `mzd_slice_t` * `_mzd_slice_mul_karatsuba5` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = A \cdot B$ over \mathbb{F}_{2^5} using 13 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices..
- `mzd_slice_t` * `_mzd_slice_mul_karatsuba6` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = A \cdot B$ over \mathbb{F}_{2^6} using 17 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices.
- `mzd_slice_t` * `_mzd_slice_mul_karatsuba7` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = A \cdot B$ over \mathbb{F}_{2^7} using 22 multiplications over \mathbb{F}_2 and 3 temporary \mathbb{F}_2 matrices.
- `mzd_slice_t` * `_mzd_slice_mul_karatsuba8` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = A \cdot B$ over \mathbb{F}_{2^8} using 27 multiplications over \mathbb{F}_2 and 15 temporary \mathbb{F}_2 matrices.
- static `mzd_slice_t` * `_mzd_slice_mul_karatsuba` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = C + A \cdot B$ using Karatsuba multiplication of polynomials over matrices over \mathbb{F}_2 .
- static `mzd_slice_t` * `mzd_slice_mul_karatsuba` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = A \cdot B$ using Karatsuba multiplication of polynomials over matrices over \mathbb{F}_2 .
- static `mzd_slice_t` * `mzd_slice_addmul_karatsuba` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = C + A \cdot B$ using Karatsuba multiplication of polynomials over matrices over \mathbb{F}_2 .
- `mzd_slice_t` * `mzd_slice_mul_scalar` (`mzd_slice_t` *C, const word a, const `mzd_slice_t` *B)
 $C = a \cdot B$.
- `mzd_slice_t` * `mzd_slice_addmul_scalar` (`mzd_slice_t` *C, const word a, const `mzd_slice_t` *B)
 $C += a \cdot B$.
- static `mzd_slice_t` * `mzd_slice_mul` (`mzd_slice_t` *C, const `mzd_slice_t` *A, const `mzd_slice_t` *B)
 $C = A \cdot B$.

- static `mzd_slice_t * mzd_slice_addmul` (`mzd_slice_t *C`, const `mzd_slice_t *A`, const `mzd_slice_t *B`)
 $C = C + A \cdot B$.
- static void `mzd_slice_randomize` (`mzd_slice_t *A`)
Fill matrix A with random elements.
- static `mzd_slice_t * mzd_slice_copy` (`mzd_slice_t *B`, const `mzd_slice_t *A`)
Copy matrix A to B.
- static word `mzd_slice_read_elem` (const `mzd_slice_t *A`, const `rci_t` row, const `rci_t` col)
Get the element at position (row,col) from the matrix A.
- static void `mzd_slice_add_elem` (`mzd_slice_t *A`, const `rci_t` row, const `rci_t` col, word elem)
Add the element elem to the element at position (row,col) in the matrix A.
- static void `mzd_slice_write_elem` (`mzd_slice_t *A`, const `rci_t` row, const `rci_t` col, word elem)
Write the element elem to the position (row,col) in the matrix A.
- static int `mzd_slice_cmp` (`mzd_slice_t *A`, `mzd_slice_t *B`)
Return -1,0,1 if if $A < B$, $A == B$ or $A > B$ respectively.
- static int `mzd_slice_is_zero` (const `mzd_slice_t *A`)
Zero test for matrix.
- static void `mzd_slice_row_swap` (`mzd_slice_t *A`, const `rci_t` rowa, const `rci_t` rowb)
Swap the two rows rowa and rowb.
- static void `mzd_slice_copy_row` (`mzd_slice_t *B`, `size_t` i, const `mzd_slice_t *A`, `size_t` j)
Copy row j from A to row i from B.
- static void `mzd_slice_col_swap` (`mzd_slice_t *A`, const `rci_t` cola, const `rci_t` colb)
Swap the two columns cola and colb.
- static void `mzd_slice_col_swap_in_rows` (`mzd_slice_t *A`, const `rci_t` cola, const `rci_t` colb, const `rci_t` start_row, `rci_t` stop_row)
Swap the two columns cola and colb but only between start_row and stop_row.
- static void `mzd_slice_row_add` (`mzd_slice_t *A`, const `rci_t` sourcerow, const `rci_t` destrow)
Add the rows sourcerow and destrow and stores the total in the row destrow.
- static void `mzd_slice_row_clear_offset` (`mzd_slice_t *A`, const `rci_t` row, const `rci_t` coloffset)
Clear the given row, but only begins at the column coloffset.
- void `mzd_slice_print` (const `mzd_slice_t *A`)
Print a matrix to stdout.
- static void `_mzd_slice_compress_l` (`mzd_slice_t *A`, const `rci_t` r1, const `rci_t` n1, const `rci_t` r2)
Move the submatrix L of rank r2 starting at column n1 to the left to column r1.

5.6.1 Detailed Description

Matrices using a bitsliced representation. Matrices over \mathbb{F}_{2^e} can be represented as polynomials with matrix coefficients where the matrices are in \mathbb{F}_2 .

In this file, matrices over \mathbb{F}_{2^e} are implemented as e slices of matrices over \mathbb{F}_2 where each slice holds the coefficients of one degree when viewing elements of \mathbb{F}_{2^e} as polynomials over \mathbb{F}_2 .

Author

Martin Albrecht martinralbrecht@googlemail.com

5.6.2 Function Documentation

5.6.2.1 `static mzd_slice_t* _mzd_slice_adapt_depth (mzd_slice_t* A, const unsigned int new_depth) [inline], [static]`

Extend or truncate the depth of A to depth new_depth.

We may think of `mzd_slice_t` as polynomials over matrices over \mathbb{F}_2 . This function then truncates/extends these polynomials to degree new_depth-1. In case of extension, all newly created coefficients are zero, hence the mathematical content of A is not changed. In case of truncation higher degree terms are simply deleted and A's mathematical content modified.

Parameters

<i>A</i>	Matrix, modified in place.
<i>new_depth</i>	Integer \geq <code>mzd_slice_t::finite_field::degree</code> .

5.6.2.2 `static void _mzd_slice_compress_l (mzd_slice_t* A, const rci_t r1, const rci_t n1, const rci_t r2) [inline], [static]`

Move the submatrix L of rank r2 starting at column n1 to the left to column r1.

Parameters

<i>A</i>	Matrix
<i>r1</i>	Integer $< n1$
<i>n1</i>	Integer $> r1$
<i>r2</i>	Integer $\leq A->ncols - n1$

5.6.2.3 `static int mzd_slice_cmp (mzd_slice_t* A, mzd_slice_t* B) [inline], [static]`

Return -1,0,1 if $A < B$, $A == B$ or $A > B$ respectively.

Parameters

<i>A</i>	Matrix.
<i>B</i>	Matrix.

Note

This comparison is not well defined (except for $k=0$) mathematically and relatively arbitrary since elements of $G-F(2^k)$ don't have an ordering.

5.6.2.4 `static void mzd_slice_col_swap_in_rows (mzd_slice_t* A, const rci_t cola, const rci_t colb, const rci_t start_row, rci_t stop_row) [inline], [static]`

Swap the two columns cola and colb but only between start_row and stop_row.

Parameters

<i>A</i>	Matrix.
<i>cola</i>	Column index.
<i>colb</i>	Column index.
<i>start_row</i>	Row index.
<i>stop_row</i>	Row index (exclusive).

5.6.2.5 static int mzd_slice.is_zero (const mzd_slice_t * A) [inline], [static]

Zero test for matrix.

Parameters

A	Input matrix.
---	---------------

5.7 mzed.h File Reference

Dense matrices over \mathbb{F}_{2^e} represented as packed matrices.

```
#include <m4ri/m4ri.h>
#include <m4rie/gf2e.h>
#include <m4rie/m4ri_functions.h>
```

Data Structures

- struct [mzed_t](#)
Dense matrices over \mathbb{F}_{2^e} represented as packed matrices.

Macros

- #define [mzed_sub mzed_add](#)
 $C = A + B.$
- #define [_mzed_sub _mzed_add](#)
 $C = A + B.$

Functions

- [mzed_t * mzed_init](#) (const [gf2e](#) *ff, const rci_t m, const rci_t n)
Create a new matrix of dimension $m \times n$ over ff.
- void [mzed_free](#) ([mzed_t](#) *A)
Free a matrix created with [mzed_init\(\)](#).
- static [mzed_t * mzed_concat](#) ([mzed_t](#) *C, const [mzed_t](#) *A, const [mzed_t](#) *B)
Concatenate B to A and write the result to C.
- static [mzed_t * mzed_stack](#) ([mzed_t](#) *C, const [mzed_t](#) *A, const [mzed_t](#) *B)
Stack A on top of B and write the result to C.
- static [mzed_t * mzed_submatrix](#) ([mzed_t](#) *S, const [mzed_t](#) *M, const rci_t lowr, const rci_t lowc, const rci_t highr, const rci_t highc)
Copy a submatrix.
- static [mzed_t * mzed_init_window](#) (const [mzed_t](#) *A, const rci_t lowr, const rci_t lowc, const rci_t highr, const rci_t highc)
Create a window/view into the matrix A.
- static void [mzed_free_window](#) ([mzed_t](#) *A)
Free a matrix window created with [mzed_init_window\(\)](#).
- [mzed_t * mzed_add](#) ([mzed_t](#) *C, const [mzed_t](#) *A, const [mzed_t](#) *B)
 $C = A + B.$

- `mzed_t * _mzed_add (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = A + B.$
- `mzed_t * mzed_mul (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = A \cdot B.$
- `mzed_t * mzed_addmul (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = C + A \cdot B.$
- `mzed_t * _mzed_mul (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = A \cdot B.$
- `mzed_t * _mzed_addmul (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = C + A \cdot B.$
- `mzed_t * mzed_addmul_naive (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = C + A \cdot B$ using naive cubic multiplication.
- `mzed_t * mzed_mul_naive (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = A \cdot B$ using naive cubic multiplication.
- `mzed_t * _mzed_mul_naive (mzed_t *C, const mzed_t *A, const mzed_t *B)`
 $C = C + A \cdot B$ using naive cubic multiplication.
- `mzed_t * mzed_mul_scalar (mzed_t *C, const word a, const mzed_t *B)`
 $C = a \cdot B.$
- `mzed_t * _mzed_mul_init (mzed_t *C, const mzed_t *A, const mzed_t *B, int clear)`
- `void mzed_randomize (mzed_t *A)`
Fill matrix A with random elements.
- `mzed_t * mzed_copy (mzed_t *B, const mzed_t *A)`
Copy matrix A to B.
- `void mzed_set_ui (mzed_t *A, word value)`
Return diagonal matrix with value on the diagonal.
- `static word mzed_read_elem (const mzed_t *A, const rci_t row, const rci_t col)`
Get the element at position (row,col) from the matrix A.
- `static void mzed_add_elem (mzed_t *A, const rci_t row, const rci_t col, const word elem)`
Add the element elem to the element at position (row,col) in the matrix A.
- `static void mzed_write_elem (mzed_t *A, const rci_t row, const rci_t col, const word elem)`
Write the element elem to the position (row,col) in the matrix A.
- `static int mzed_cmp (mzed_t *A, mzed_t *B)`
Return -1,0,1 if if $A < B$, $A == B$ or $A > B$ respectively.
- `static int mzed_is_zero (const mzed_t *A)`
Zero test for matrix.
- `void mzed_add_multiple_of_row (mzed_t *A, rci_t ar, const mzed_t *B, rci_t br, word x, rci_t start_col)`
- `static void mzed_add_row (mzed_t *A, rci_t ar, const mzed_t *B, rci_t br, rci_t start_col)`
- `static void mzed_rescale_row (mzed_t *A, rci_t r, rci_t start_col, const word x)`
Rescale the row r in A by X starting c.
- `static void mzed_row_swap (mzed_t *M, const rci_t rowa, const rci_t rowb)`
Swap the two rows rowa and rowb.
- `static void mzed_copy_row (mzed_t *B, rci_t i, const mzed_t *A, rci_t j)`
copy row j from A to row i from B.
- `static void mzed_col_swap (mzed_t *M, const rci_t cola, const rci_t colb)`
Swap the two columns cola and colb.
- `static void mzed_col_swap_in_rows (mzed_t *A, const rci_t cola, const rci_t colb, const rci_t start_row, rci_t stop_row)`

- Swap the two columns cola and colb but only between start_row and stop_row.*
- static void `mzed_row_add` (`mzed_t` *M, const `rci_t` sourcerow, const `rci_t` destrow)
Add the rows sourcerow and destrow and stores the total in the row destrow.
- static `rci_t` `mzed_first_zero_row` (`mzed_t` *A)
Return the first row with all zero entries.
- static void `mzed_row_clear_offset` (`mzed_t` *M, const `rci_t` row, const `rci_t` coloffset)
Clear the given row, but only begins at the column coloffset.
- `rci_t` `mzed_echelonize_naive` (`mzed_t` *A, int full)
Gaussian elimination.
- void `mzed_print` (const `mzed_t` *M)
Print a matrix to stdout.

5.7.1 Detailed Description

Dense matrices over \mathbb{F}_{2^e} represented as packed matrices. This file implements the data type `mzed_t`. That is, matrices over \mathbb{F}_{2^e} in row major representation.

For example, let $a = \sum a_i x_i / \langle f \rangle$ and $b = \sum b_i x_i / \langle f \rangle$ be elements in \mathbb{F}_{2^6} with minimal polynomial f . Then, the 1×2 matrix [b a] would be stored as

```
[...| 0 0 b5 b4 b3 b2 b1 b0 | 0 0 a5 a4 a3 a2 a1 a0]
```

Internally M4RI matrices are used to store bits with allows to re-use existing M4RI methods (such as `mzd_add`) when implementing functions for `mzed_t`.

This data type is preferable when Newton-John tables ought be used or when the matrix is small ($m \times n \times e < L2$).

Author

Martin Albrecht martinralbrecht@googlemail.com

5.7.2 Function Documentation

5.7.2.1 `mzed_t* mzed_mul_init (mzed_t* C, const mzed_t* A, const mzed_t* B, int clear)`

Check whether C, A and B match in sizes and fields for multiplication

Parameters

<i>C</i>	Output matrix, if NULL a new matrix is created.
<i>A</i>	Input matrix.
<i>B</i>	Input matrix.
<i>clear</i>	Write zeros to C or not.

5.7.2.2 `static int mzed_cmp (mzed_t* A, mzed_t* B)` `[inline]`, `[static]`

Return -1,0,1 if if $A < B$, $A == B$ or $A > B$ respectively.

Parameters

<i>A</i>	Matrix.
<i>B</i>	Matrix.

Note

This comparison is not well defined mathematically and relatively arbitrary since elements of \mathbb{F}_{2^e} don't have an ordering.

Examples:

[tests/test_elimination.cc](#).

5.7.2.3 static int mzed_is_zero (const mzed_t * A) [inline],[static]

Zero test for matrix.

Parameters

A	Input matrix.
---	---------------

5.8 newton_john.h File Reference

Newton-John table based algorithms.

```
#include <m4rie/gf2e.h>
#include <m4rie/mzed.h>
#include <m4rie/mzd_slice.h>
```

Data Structures

- struct [njt_mzed_t](#)
Newton-John table.

Functions

- [njt_mzed_t](#) * [njt_mzed_init](#) (const [gf2e](#) *ff, const rci_t ncols)
*Allocate Newton-John table of dimension [gf2e::degree](#) < 1 * ncols.*
- void [njt_mzed_free](#) ([njt_mzed_t](#) *t)
Free Newton-John table.
- [njt_mzed_t](#) * [mzed_make_table](#) ([njt_mzed_t](#) *T, const [mzed_t](#) *A, const rci_t r, const rci_t c)
Construct Newton-John table T for row r of A, and element A[r,c].
- [mzed_t](#) * [mzed_mul_newton_john](#) ([mzed_t](#) *C, const [mzed_t](#) *A, const [mzed_t](#) *B)
C = A · B using Newton-John tables.
- [mzed_t](#) * [mzed_addmul_newton_john](#) ([mzed_t](#) *C, const [mzed_t](#) *A, const [mzed_t](#) *B)
C = C + A · B using Newton-John tables.
- [mzed_t](#) * [_mzed_mul_newton_john0](#) ([mzed_t](#) *C, const [mzed_t](#) *A, const [mzed_t](#) *B)
C = C + A · B using Newton-John tables.
- [mzed_t](#) * [_mzed_mul_newton_john](#) ([mzed_t](#) *C, const [mzed_t](#) *A, const [mzed_t](#) *B)
C = C + A · B using Newton-John tables.
- rci_t [mzed_echelonize_newton_john](#) ([mzed_t](#) *A, int full)
Reduce matrix A to row echelon form using Gauss-Newton-John elimination.
- [mzed_t](#) * [mzed_invert_newton_john](#) ([mzed_t](#) *B, const [mzed_t](#) *A)
Invert the matrix A using Gauss-Newton-John elimination.

- void `mzed_trsm_lower_left_newton_john` (const `mzed_t` *L, `mzed_t` *B)
 $B = L^{-1} \cdot B$ using Newton-John tables.
- void `mzd_slice_trsm_lower_left_newton_john` (const `mzd_slice_t` *L, `mzd_slice_t` *B)
 $B = L^{-1} \cdot B$ using Newton-John tables.
- void `mzed_trsm_upper_left_newton_john` (const `mzed_t` *U, `mzed_t` *B)
 $B = U^{-1} \cdot B$ using Newton-John tables.
- void `mzd_slice_trsm_upper_left_newton_john` (const `mzd_slice_t` *U, `mzd_slice_t` *B)
 $B = U^{-1} \cdot B$ using Newton-John tables.
- `rci_t` `mzed_ple_newton_john` (`mzed_t` *A, `mzp_t` *P, `mzp_t` *Q)
PLE decomposition: $L \cdot E = P \cdot A$ using Newton-John tables.
- static void `mzed_process_rows` (`mzed_t` *M, const `rci_t` startrow, const `rci_t` endrow, `rci_t` startcol, const `njt_mzed_t` *T)
The function looks up 6 entries from position *i*, startcol in each row and adds the appropriate row from T to the row *i*.
- static void `mzed_process_rows2` (`mzed_t` *M, const `rci_t` startrow, const `rci_t` endrow, const `rci_t` startcol, const `njt_mzed_t` *T0, const `njt_mzed_t` *T1)
Same as `mzed_process_rows` but works with two Newton-John tables in parallel.
- static void `mzed_process_rows3` (`mzed_t` *M, const `rci_t` startrow, const `rci_t` endrow, const `rci_t` startcol, const `njt_mzed_t` *T0, const `njt_mzed_t` *T1, const `njt_mzed_t` *T2)
Same as `mzed_process_rows` but works with three Newton-John tables in parallel.
- static void `mzed_process_rows4` (`mzed_t` *M, const `rci_t` startrow, const `rci_t` endrow, const `rci_t` startcol, const `njt_mzed_t` *T0, const `njt_mzed_t` *T1, const `njt_mzed_t` *T2, const `njt_mzed_t` *T3)
Same as `mzed_process_rows` but works with four Newton-John tables in parallel.
- static void `mzed_process_rows5` (`mzed_t` *M, const `rci_t` startrow, const `rci_t` endrow, const `rci_t` startcol, const `njt_mzed_t` *T0, const `njt_mzed_t` *T1, const `njt_mzed_t` *T2, const `njt_mzed_t` *T3, const `njt_mzed_t` *T4)
Same as `mzed_process_rows` but works with five Newton-John tables in parallel.
- static void `mzed_process_rows6` (`mzed_t` *M, const `rci_t` startrow, const `rci_t` endrow, const `rci_t` startcol, const `njt_mzed_t` *T0, const `njt_mzed_t` *T1, const `njt_mzed_t` *T2, const `njt_mzed_t` *T3, const `njt_mzed_t` *T4, const `njt_mzed_t` *T5)
Same as `mzed_process_rows` but works with six Newton-John tables in parallel.

5.8.1 Detailed Description

Newton-John table based algorithms.

Note

These tables were formally known as Travolta tables.

Author

Martin Albrecht martinralbrecht@googlemail.com

5.8.2 Function Documentation

5.8.2.1 `mzed_t`* `mzed_invert_newton_john` (`mzed_t` * B, const `mzed_t` * A)

Invert the matrix A using Gauss-Newton-John elimination.

Parameters

<i>B</i>	Preallocated space for inversion matrix, may be NULL for automatic creation.
<i>A</i>	Matrix to be inverted.

5.8.2.2 `njt_mzed_t* mzed_make_table (njt_mzed_t * T, const mzed_t * A, const rci_t r, const rci_t c)`

Construct Newton-John table *T* for row *r* of *A*, and element *A*[*r*,*c*].

Parameters

<i>T</i>	Preallocated Newton-John table or NULL.
<i>A</i>	Matrix.
<i>r</i>	Row index.
<i>c</i>	Column index.

5.8.2.3 `void njt_mzed_free (njt_mzed_t * t)`

Free Newton-John table.

Parameters

<i>t</i>	Table
----------	-------

5.8.2.4 `njt_mzed_t* njt_mzed_init (const gf2e * ff, const rci_t ncols)`

Allocate Newton-John table of dimension `gf2e::degree` < 1 * *ncols*.

Parameters

<i>ff</i>	Finite field.
<i>ncols</i>	Integer > 0.

5.9 permutation.h File Reference

Permutation matrices.

```
#include <m4ri/mzp.h>
#include <m4rie/mzed.h>
#include <m4rie/mzd_slice.h>
```

Functions

- static void `mzed_apply_p_left` (mzed_t **A*, mzp_t const **P*)
- static void `mzed_apply_p_left_trans` (mzed_t **A*, mzp_t const **P*)
- static void `mzed_apply_p_right` (mzed_t **A*, mzp_t const **P*)
- static void `mzed_apply_p_right_trans` (mzed_t **A*, mzp_t const **P*)
- static void `mzd_slice_apply_p_left` (mzd_slice_t **A*, mzp_t const **P*)
- static void `mzd_slice_apply_p_left_trans` (mzd_slice_t **A*, mzp_t const **P*)
- static void `mzd_slice_apply_p_right` (mzd_slice_t **A*, mzp_t const **P*)
- static void `mzd_slice_apply_p_right_trans` (mzd_slice_t **A*, mzp_t const **P*)
- static void `mzd_slice_apply_p_right_trans_tri` (mzd_slice_t **A*, mzp_t const **P*)

5.9.1 Detailed Description

Permutation matrices.

Author

Martin Albrecht martinralbrecht@googlemail.com

5.9.2 Function Documentation

5.9.2.1 `static void mzd_slice_apply_p_left (mzd_slice_t * A, mzp_t const * P)` `[inline]`, `[static]`

Apply the permutation P to A from the left.

This is equivalent to row swaps walking from 0 to length-1.

Parameters

<i>A</i>	Matrix.
<i>P</i>	Permutation.

5.9.2.2 `static void mzd_slice_apply_p_left_trans (mzd_slice_t * A, mzp_t const * P)` `[inline]`, `[static]`

Apply the permutation P to A from the left but transpose P before.

This is equivalent to row swaps walking from length-1 to 0.

Parameters

<i>A</i>	Matrix.
<i>P</i>	Permutation.

5.9.2.3 `static void mzd_slice_apply_p_right (mzd_slice_t * A, mzp_t const * P)` `[inline]`, `[static]`

Apply the permutation P to A from the right.

This is equivalent to column swaps walking from length-1 to 0.

Parameters

<i>A</i>	Matrix.
<i>P</i>	Permutation.

5.9.2.4 `static void mzd_slice_apply_p_right_trans (mzd_slice_t * A, mzp_t const * P)` `[inline]`, `[static]`

Apply the permutation P to A from the right but transpose P before.

This is equivalent to column swaps walking from 0 to length-1.

Parameters

<i>A</i>	Matrix.
<i>P</i>	Permutation.

5.9.2.5 `static void mzd_slice_apply_p_right_trans_tri (mzd_slice_t * A, mzp_t const * P) [inline],[static]`

Apply the permutation P to A from the right, but only on the upper the matrix A above the main diagonal.

This is equivalent to column swaps walking from 0 to length-1 and is used to compress PLE to PLUQ.

Parameters

<i>A</i>	Matrix.
<i>P</i>	Permutation.

5.9.2.6 `static void mzed_apply_p_left (mzed_t * A, mzp_t const * P) [inline],[static]`

Apply the permutation P to A from the left.

This is equivalent to row swaps walking from 0 to length-1.

Parameters

<i>A</i>	Matrix.
<i>P</i>	Permutation.

5.9.2.7 `static void mzed_apply_p_left_trans (mzed_t * A, mzp_t const * P) [inline],[static]`

Apply the permutation P to A from the left but transpose P before.

This is equivalent to row swaps walking from length-1 to 0.

Parameters

<i>A</i>	Matrix.
<i>P</i>	Permutation.

5.9.2.8 `static void mzed_apply_p_right (mzed_t * A, mzp_t const * P) [inline],[static]`

Apply the permutation P to A from the right.

This is equivalent to column swaps walking from length-1 to 0.

Parameters

<i>A</i>	Matrix.
<i>P</i>	Permutation.

5.9.2.9 `static void mzed_apply_p_right_trans (mzed_t * A, mzp_t const * P) [inline],[static]`

Apply the permutation P to A from the right but transpose P before.

This is equivalent to column swaps walking from 0 to length-1.

Parameters

<i>A</i>	Matrix.
<i>P</i>	Permutation.

5.10 ple.h File Reference

PLE decomposition: $L \cdot E = P \cdot A$.

```
#include <m4ri/m4ri.h>
#include <m4rie/mzed.h>
#include <m4rie/mzd_slice.h>
#include <m4rie/conversion.h>
```

Macros

- `#define __M4RIE_PLE_CUTOFF (__M4RI_CPU_L2_CACHE<<2)`

Functions

- `rci_t mzed_ple_naive (mzed_t *A, mzp_t *P, mzp_t *Q)`
PLE decomposition: $L \cdot E = P \cdot A$.
- `rci_t _mzd_slice_ple (mzd_slice_t *A, mzp_t *P, mzp_t *Q, rci_t cutoff)`
PLE decomposition: $L \cdot E = P \cdot A$.
- `static rci_t mzd_slice_ple (mzd_slice_t *A, mzp_t *P, mzp_t *Q)`
PLE decomposition: $L \cdot E = P \cdot A$.
- `rci_t _mzd_slice_pluq (mzd_slice_t *A, mzp_t *P, mzp_t *Q, rci_t cutoff)`
PLUQ decomposition: $L \cdot U \cdot Q = P \cdot A$.
- `static rci_t mzd_slice_pluq (mzd_slice_t *A, mzp_t *P, mzp_t *Q)`
PLUQ decomposition: $L \cdot U \cdot Q = P \cdot A$.
- `rci_t _mzed_ple (mzed_t *A, mzp_t *P, mzp_t *Q, rci_t cutoff)`
PLE decomposition: $L \cdot E = P \cdot A$.
- `static rci_t mzed_ple (mzed_t *A, mzp_t *P, mzp_t *Q)`
PLE decomposition: $L \cdot E = P \cdot A$.

5.10.1 Detailed Description

PLE decomposition: $L \cdot E = P \cdot A$.

Author

Martin Albrecht martinralbrecht@googlemail.com

5.10.2 Macro Definition Documentation

5.10.2.1 `#define __M4RIE_PLE_CUTOFF (__M4RI_CPU_L2_CACHE<<2)`

Default crossover to PLE base case (Newton-John based).

5.11 strassen.h File Reference

Strassen-Winograd multiplication for `mzed_t`.

Functions

- `mzed_t * mzed_mul_strassen` (`mzed_t *C`, `const mzed_t *A`, `const mzed_t *B`, `int cutoff`)
 $C = A \cdot B$ using Strassen-Winograd.
- `mzed_t * mzed_addmul_strassen` (`mzed_t *C`, `const mzed_t *A`, `const mzed_t *B`, `int cutoff`)
 $C = C + A \cdot B$ using Strassen-Winograd.
- `mzed_t * _mzed_mul_strassen` (`mzed_t *C`, `const mzed_t *A`, `const mzed_t *B`, `int cutoff`)
 $C = A \cdot B$ using Strassen-Winograd.
- `mzed_t * _mzed_addmul_strassen` (`mzed_t *C`, `const mzed_t *A`, `const mzed_t *B`, `int cutoff`)
 $C = A \cdot B$ using Strassen-Winograd.
- `rci_t _mzed_strassen_cutoff` (`const mzed_t *C`, `const mzed_t *A`, `const mzed_t *B`)
Return heuristic choice for crossover parameter for Strassen-Winograd multiplication given A , B and C .

5.11.1 Detailed Description

Strassen-Winograd multiplication for `mzed_t`.

Author

Martin Albrecht martinralbrecht@googlemail.com

5.12 trsm.h File Reference

Triangular System Solving with Matrices (TRSM).

```
#include <m4rie/mzed.h>
#include <m4rie/mzd_slice.h>
```

Macros

- `#define MZED_TRSM_CUTOFF` 512

Functions

- `void _mzed_trsm_upper_left` (`const mzed_t *U`, `mzed_t *B`, `const rci_t cutoff`)
 $B = U^{-1} \cdot B$
- `void mzed_trsm_upper_left_naive` (`const mzed_t *U`, `mzed_t *B`)
 $B = U^{-1} \cdot B$
- `static void mzed_trsm_upper_left` (`const mzed_t *U`, `mzed_t *B`)
 $B = U^{-1} \cdot B$
- `void _mzd_slice_trsm_upper_left` (`const mzd_slice_t *U`, `mzd_slice_t *B`, `const rci_t cutoff`)
 $B = U^{-1} \cdot B$
- `void mzd_slice_trsm_upper_left_naive` (`const mzd_slice_t *U`, `mzd_slice_t *B`)
 $B = U^{-1} \cdot B$
- `static void mzd_slice_trsm_upper_left` (`const mzd_slice_t *U`, `mzd_slice_t *B`)
 $B = U^{-1} \cdot B$
- `void _mzed_trsm_lower_left` (`const mzed_t *L`, `mzed_t *B`, `const rci_t cutoff`)
 $B = L^{-1} \cdot B$

- void `mzed_trsm_lower_left_naive` (const `mzed_t` *L, `mzed_t` *B)

$$B = L^{-1} \cdot B$$
- static void `mzed_trsm_lower_left` (const `mzed_t` *L, `mzed_t` *B)

$$B = L^{-1} \cdot B$$
- void `_mzd_slice_trsm_lower_left` (const `mzd_slice_t` *L, `mzd_slice_t` *B, const `rci_t` cutoff)

$$B = L^{-1} \cdot B$$
- void `mzd_slice_trsm_lower_left_naive` (const `mzd_slice_t` *L, `mzd_slice_t` *B)

$$B = L^{-1} \cdot B$$
- static void `mzd_slice_trsm_lower_left` (const `mzd_slice_t` *L, `mzd_slice_t` *B)

$$B = L^{-1} \cdot B$$

5.12.1 Detailed Description

Triangular System Solving with Matrices (TRSM).

Author

Martin Albrecht martinralbrecht@googlemail.com

5.12.2 Macro Definition Documentation

5.12.2.1 #define MZED_TRSM_CUTOFF 512

Crossover dimension to TRSM base cases

6 Example Documentation

6.1 tests/test_elimination.cc

tests/test_multiplication.cc

```

/*****
 *
 *      M4RIE: Linear Algebra over GF(2^e)
 *
 *      Copyright (C) 2010-2012 Martin Albrecht <martinralbrecht@googlemail.com>
 *
 *      Distributed under the terms of the GNU General Public License (GPL)
 *      version 2 or higher.
 *
 *      This code is distributed in the hope that it will be useful,
 *      but WITHOUT ANY WARRANTY; without even the implied warranty of
 *      MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
 *      General Public License for more details.
 *
 *      The full text of the GPL is available at:
 *
 *      http://www.gnu.org/licenses/
 *****/

#include "testing.h"

int test_equality(gf2e *ff, rci_t m, rci_t n) {
    int fail_ret = 0;
    mzed_t *A0 = random_mzed_t(ff, m, n);
    mzed_t *A1 = mzed_copy(NULL, A0);
    mzed_t *A2 = mzed_copy(NULL, A0);
    mzed_t *A3 = mzed_copy(NULL, A0);

```

```

mzed_set_canary(A1);
mzed_set_canary(A2);
mzed_set_canary(A3);

const rci_t r0 = mzed_echelonize_newton_john(A0,1);
const rci_t r1 = mzed_echelonize_naive(A1,1);
const rci_t r2 = mzed_echelonize(A2,1);
const rci_t r3 = mzed_echelonize_ple(A3,1);

m4rie_check( r0 == r1);
m4rie_check( mzed_cmp(A0, A1) == 0);

m4rie_check( r1 == r2);
m4rie_check( mzed_cmp(A1, A2) == 0);

m4rie_check( r2 == r3);
m4rie_check( mzed_cmp(A2, A3) == 0);
m4rie_check( r3 == r0);
m4rie_check( mzed_cmp(A3, A0) == 0);

m4rie_check( mzed_canary_is_alive(A0) );
m4rie_check( mzed_canary_is_alive(A1) );
m4rie_check( mzed_canary_is_alive(A2) );
m4rie_check( mzed_canary_is_alive(A3) );

mzed_free(A0);
mzed_free(A1);
mzed_free(A2);
mzed_free(A3);

return fail_ret;
}

int test_batch(gf2e *ff, rci_t m, rci_t n) {
    int fail_ret = 0;
    printf("elim: k: %2d, minpoly: 0x%05x m: %5d, n: %5d ",(int)ff->degree, (unsigned int)ff->
        minpoly, (int)m, (int)n);

    if(m == n) {
        m4rie_check( test_equality(ff, m, n) == 0); printf("."); fflush(0);
        printf(" ");
    } else {
        m4rie_check( test_equality(ff, m, n) == 0); printf("."); fflush(0);
        m4rie_check( test_equality(ff, n, m) == 0); printf("."); fflush(0);
    }

    if (fail_ret == 0)
        printf(" passed\n");
    else
        printf(" FAILED\n");

    return fail_ret;
}

int main(int argc, char **argv) {
    srandom(17);

    int runlong = parse_parameters(argc, argv);

    gf2e *ff;
    int fail_ret = 0;

    for(int k=2; k<=16; k++) {
        ff = gf2e_init(irreducible_polynomials[k][1]);

        fail_ret += test_batch(ff, 2, 5);
        fail_ret += test_batch(ff, 5, 10);
        fail_ret += test_batch(ff, 1, 1);
        fail_ret += test_batch(ff, 1, 2);
        fail_ret += test_batch(ff, 11, 12);
        fail_ret += test_batch(ff, 21, 22);
        fail_ret += test_batch(ff, 13, 2);
        fail_ret += test_batch(ff, 32, 33);
        fail_ret += test_batch(ff, 63, 64);
        if (k <= 12 || runlong) {
            fail_ret += test_batch(ff, 127, 128);
            fail_ret += test_batch(ff, 200, 20);
        }
        fail_ret += test_batch(ff, 1, 1);
        fail_ret += test_batch(ff, 1, 3);
    }

```



```
fail_ret += test_batch(ff, 11, 13);
fail_ret += test_batch(ff, 21, 23);
fail_ret += test_batch(ff, 13, 90);
fail_ret += test_batch(ff, 32, 34);
fail_ret += test_batch(ff, 63, 65);
if (k <= 12 || runlong) {
    fail_ret += test_batch(ff, 127, 129);
    fail_ret += test_batch(ff, 200, 112);
    fail_ret += test_batch(ff, 10, 200);
}
gf2e_free(ff);
}

return fail_ret;
}
```

Index

- `__M4RIE_1tF`
 - `gf2x.h`, [53](#)
- `__M4RIE_PLE_CUTOFF`
 - `ple.h`, [66](#)
- `_mul`
 - `gf2e_struct`, [42](#)
- `_mzd_slice_adapt_depth`
 - `mzd_slice.h`, [57](#)
- `_mzd_slice_add`
 - Addition and subtraction, [21](#)
- `_mzd_slice_compress_l`
 - `mzd_slice.h`, [57](#)
- `_mzd_slice_mul_karatsuba`
 - Multiplication, [24](#)
- `_mzd_slice_mul_karatsuba2`
 - Multiplication, [25](#)
- `_mzd_slice_mul_karatsuba3`
 - Multiplication, [25](#)
- `_mzd_slice_mul_karatsuba4`
 - Multiplication, [25](#)
- `_mzd_slice_mul_karatsuba5`
 - Multiplication, [25](#)
- `_mzd_slice_mul_karatsuba6`
 - Multiplication, [26](#)
- `_mzd_slice_mul_karatsuba7`
 - Multiplication, [26](#)
- `_mzd_slice_mul_karatsuba8`
 - Multiplication, [26](#)
- `_mzd_slice_mul_naive`
 - Multiplication, [27](#)
- `_mzd_slice_ple`
 - PLE and PLUQ decomposition, [33](#)
- `_mzd_slice_pluq`
 - PLE and PLUQ decomposition, [33](#)
- `_mzd_slice_sub`
 - Addition and subtraction, [20](#)
- `_mzd_slice_trsm_lower_left`
 - Triangular matrices, [38](#)
- `_mzd_slice_trsm_upper_left`
 - Triangular matrices, [39](#)
- `_mzed_add`
 - Addition and subtraction, [21](#)
- `_mzed_addmul`
 - Multiplication, [27](#)
- `_mzed_addmul_strassen`
 - Multiplication, [27](#)
- `_mzed_cling16`
 - `conversion.h`, [47](#)
- `_mzed_cling2`
 - `conversion.h`, [47](#)
- `_mzed_cling4`
 - `conversion.h`, [48](#)
- `_mzed_cling8`
 - `conversion.h`, [48](#)
- `_mzed_mul`
 - Multiplication, [27](#)
- `_mzed_mul_init`
 - `mzed.h`, [60](#)
- `_mzed_mul_karatsuba`
 - `conversion.h`, [48](#)
- `_mzed_mul_naive`
 - Multiplication, [28](#)
- `_mzed_mul_newton_john`
 - Multiplication, [28](#)
- `_mzed_mul_newton_john0`
 - Multiplication, [28](#)
- `_mzed_mul_strassen`
 - Multiplication, [28](#)
- `_mzed_ple`
 - PLE and PLUQ decomposition, [34](#)
- `_mzed_slice16`
 - `conversion.h`, [48](#)
- `_mzed_slice2`
 - `conversion.h`, [48](#)
- `_mzed_slice4`
 - `conversion.h`, [49](#)
- `_mzed_slice8`
 - `conversion.h`, [49](#)
- `_mzed_strassen_cutoff`
 - Multiplication, [29](#)
- `_mzed_sub`
 - Addition and subtraction, [20](#)
- `_mzed_trsm_lower_left`
 - Triangular matrices, [39](#)
- `_mzed_trsm_upper_left`
 - Triangular matrices, [39](#)
- Addition and subtraction, [20](#)
 - `_mzd_slice_add`, [21](#)
 - `_mzd_slice_sub`, [20](#)
 - `_mzed_add`, [21](#)
 - `_mzed_sub`, [20](#)
 - `mzd_slice_add`, [21](#)
 - `mzd_slice_sub`, [20](#)
 - `mzed_add`, [22](#)
 - `mzed_sub`, [21](#)
- Assignment and basic manipulation, [8](#)
 - `mzd_poly_randomize`, [8](#)
 - `mzd_slice_add_elem`, [8](#)
 - `mzd_slice_copy`, [9](#)
 - `mzd_slice_randomize`, [9](#)
 - `mzd_slice_read_elem`, [9](#)

- mzd_slice_set_ui, 9
- mzd_slice_write_elem, 9
- mzed_add_elem, 10
- mzed_copy, 10
- mzed_randomize, 10
- mzed_read_elem, 10
- mzed_set_ui, 10
- mzed_write_elem, 11
- Constructions, 3
 - mzd_slice_concat, 3
 - mzd_slice_free, 4
 - mzd_slice_free_window, 4
 - mzd_slice_init, 4
 - mzd_slice_init_window, 4
 - mzd_slice_stack, 5
 - mzd_slice_submatrix, 5
 - mzed_cling, 5
 - mzed_concat, 5
 - mzed_free, 6
 - mzed_free_window, 6
 - mzed_init, 6
 - mzed_init_window, 6
 - mzed_slice, 7
 - mzed_stack, 7
 - mzed_submatrix, 7
- conversion.h, 46
 - _mzed_cling16, 47
 - _mzed_cling2, 47
 - _mzed_cling4, 48
 - _mzed_cling8, 48
 - _mzed_mul_karatsuba, 48
 - _mzed_slice16, 48
 - _mzed_slice2, 48
 - _mzed_slice4, 49
 - _mzed_slice8, 49
 - mzed_addmul_karatsuba, 49
 - mzed_mul_karatsuba, 49
- degree
 - gf2e_struct, 42
- depth
 - mzd_poly_t, 43
 - mzd_slice_t, 44
- Echelon forms, 36
 - mzd_slice_echelonize, 36
 - mzd_slice_echelonize_ple, 36
 - mzed_echelonize, 36
 - mzed_echelonize_naive, 37
 - mzed_echelonize_newton_john, 37
 - mzed_echelonize_ple, 37
- echelonform.h, 49
- finite_field
 - mzd_slice_t, 44
 - mzed_t, 45
- gf2e.h, 50
 - gf2e_degree_to_w, 51
 - gf2e_free, 51
 - gf2e_init, 51
 - gf2e_t16_free, 52
 - gf2e_t16_init, 52
- gf2e_degree_to_w
 - gf2e.h, 51
- gf2e_free
 - gf2e.h, 51
- gf2e_init
 - gf2e.h, 51
- gf2e_struct, 42
 - _mul, 42
 - degree, 42
 - inv, 42
 - minpoly, 42
 - mul, 42
 - pow_gen, 42
 - red, 42
- gf2e_t16_free
 - gf2e.h, 52
- gf2e_t16_init
 - gf2e.h, 52
- gf2x.h, 52
 - __M4RIE_1tF, 53
 - gf2x_deg, 53
- gf2x_deg
 - gf2x.h, 53
- inv
 - gf2e_struct, 42
- L
 - njt_mzed_t, 45
- M
 - njt_mzed_t, 46
- m4rie.h, 53
- MZED_TRSM_CUTOFF
 - trsm.h, 68
- minpoly
 - gf2e_struct, 42
- mul
 - gf2e_struct, 42
- Multiplication, 23
 - _mzd_slice_mul_karatsuba, 24
 - _mzd_slice_mul_karatsuba2, 25
 - _mzd_slice_mul_karatsuba3, 25
 - _mzd_slice_mul_karatsuba4, 25
 - _mzd_slice_mul_karatsuba5, 25
 - _mzd_slice_mul_karatsuba6, 26

- [_mzd_slice_mul_karatsuba7](#), [26](#)
- [_mzd_slice_mul_karatsuba8](#), [26](#)
- [_mzd_slice_mul_naive](#), [27](#)
- [_mzed_addmul](#), [27](#)
- [_mzed_addmul_strassen](#), [27](#)
- [_mzed_mul](#), [27](#)
- [_mzed_mul_naive](#), [28](#)
- [_mzed_mul_newton_john](#), [28](#)
- [_mzed_mul_newton_john0](#), [28](#)
- [_mzed_mul_strassen](#), [28](#)
- [_mzed_strassen_cutoff](#), [29](#)
- [mzd_slice_addmul](#), [29](#)
- [mzd_slice_addmul_karatsuba](#), [29](#)
- [mzd_slice_addmul_scalar](#), [29](#)
- [mzd_slice_mul](#), [30](#)
- [mzd_slice_mul_karatsuba](#), [30](#)
- [mzd_slice_mul_scalar](#), [30](#)
- [mzed_addmul](#), [30](#)
- [mzed_addmul_naive](#), [30](#)
- [mzed_addmul_newton_john](#), [31](#)
- [mzed_addmul_strassen](#), [31](#)
- [mzed_mul](#), [31](#)
- [mzed_mul_naive](#), [31](#)
- [mzed_mul_newton_john](#), [32](#)
- [mzed_mul_scalar](#), [32](#)
- [mzed_mul_strassen](#), [32](#)
- [mzd_poly_randomize](#)
 - Assignment and basic manipulation, [8](#)
- [mzd_poly_t](#), [43](#)
 - [depth](#), [43](#)
 - [ncols](#), [43](#)
 - [nrows](#), [43](#)
- [mzd_slice.h](#), [54](#)
 - [_mzd_slice_adapt_depth](#), [57](#)
 - [_mzd_slice_compress_l](#), [57](#)
 - [mzd_slice_cmp](#), [57](#)
 - [mzd_slice_col_swap_in_rows](#), [57](#)
 - [mzd_slice_is_zero](#), [58](#)
- [mzd_slice_add](#)
 - Addition and subtraction, [21](#)
- [mzd_slice_add_elem](#)
 - Assignment and basic manipulation, [8](#)
- [mzd_slice_addmul](#)
 - Multiplication, [29](#)
- [mzd_slice_addmul_karatsuba](#)
 - Multiplication, [29](#)
- [mzd_slice_addmul_scalar](#)
 - Multiplication, [29](#)
- [mzd_slice_apply_p_left](#)
 - [permutation.h](#), [64](#)
- [mzd_slice_apply_p_left_trans](#)
 - [permutation.h](#), [64](#)
- [mzd_slice_apply_p_right](#)
 - [permutation.h](#), [64](#)
- [mzd_slice_apply_p_right_trans](#)
 - [permutation.h](#), [64](#)
- [mzd_slice_apply_p_right_trans_tri](#)
 - [permutation.h](#), [64](#)
- [mzd_slice_cmp](#)
 - [mzd_slice.h](#), [57](#)
- [mzd_slice_col_swap](#)
 - Operations on rows, [13](#)
- [mzd_slice_col_swap_in_rows](#)
 - [mzd_slice.h](#), [57](#)
- [mzd_slice_concat](#)
 - Constructions, [3](#)
- [mzd_slice_copy](#)
 - Assignment and basic manipulation, [9](#)
- [mzd_slice_copy_row](#)
 - Operations on rows, [13](#)
- [mzd_slice_echelonize](#)
 - Echelon forms, [36](#)
- [mzd_slice_echelonize_ple](#)
 - Echelon forms, [36](#)
- [mzd_slice_free](#)
 - Constructions, [4](#)
- [mzd_slice_free_window](#)
 - Constructions, [4](#)
- [mzd_slice_init](#)
 - Constructions, [4](#)
- [mzd_slice_init_window](#)
 - Constructions, [4](#)
- [mzd_slice_is_zero](#)
 - [mzd_slice.h](#), [58](#)
- [mzd_slice_mul](#)
 - Multiplication, [30](#)
- [mzd_slice_mul_karatsuba](#)
 - Multiplication, [30](#)
- [mzd_slice_mul_scalar](#)
 - Multiplication, [30](#)
- [mzd_slice_ple](#)
 - PLE and PLUQ decomposition, [34](#)
- [mzd_slice_pluq](#)
 - PLE and PLUQ decomposition, [34](#)
- [mzd_slice_print](#)
 - String conversions and I/O, [19](#)
- [mzd_slice_randomize](#)
 - Assignment and basic manipulation, [9](#)
- [mzd_slice_read_elem](#)
 - Assignment and basic manipulation, [9](#)
- [mzd_slice_rescale_row](#)
 - Operations on rows, [13](#)
- [mzd_slice_row_add](#)
 - Operations on rows, [13](#)
- [mzd_slice_row_clear_offset](#)
 - Operations on rows, [14](#)
- [mzd_slice_row_swap](#)
 - Operations on rows, [14](#)

- mzd_slice_set_ui
 - Assignment and basic manipulation, 9
- mzd_slice_stack
 - Constructions, 5
- mzd_slice_sub
 - Addition and subtraction, 20
- mzd_slice_submatrix
 - Constructions, 5
- mzd_slice_t, 43
 - depth, 44
 - finite_field, 44
 - ncols, 44
 - nrows, 44
 - x, 44
- mzd_slice_trsm_lower_left
 - Triangular matrices, 39
- mzd_slice_trsm_lower_left_naive
 - Triangular matrices, 39
- mzd_slice_trsm_lower_left_newton_john
 - Triangular matrices, 39
- mzd_slice_trsm_upper_left
 - Triangular matrices, 40
- mzd_slice_trsm_upper_left_naive
 - Triangular matrices, 40
- mzd_slice_trsm_upper_left_newton_john
 - Triangular matrices, 40
- mzd_slice_write_elem
 - Assignment and basic manipulation, 9
- mzed.h, 58
 - _mzed_mul_init, 60
 - mzed_cmp, 60
 - mzed_is_zero, 61
- mzed_add
 - Addition and subtraction, 22
- mzed_add_elem
 - Assignment and basic manipulation, 10
- mzed_add_multiple_of_row
 - Operations on rows, 14
- mzed_add_row
 - Operations on rows, 14
- mzed_addmul
 - Multiplication, 30
- mzed_addmul_karatsuba
 - conversion.h, 49
- mzed_addmul_naive
 - Multiplication, 30
- mzed_addmul_newton_john
 - Multiplication, 31
- mzed_addmul_strassen
 - Multiplication, 31
- mzed_apply_p_left
 - permutation.h, 65
- mzed_apply_p_left_trans
 - permutation.h, 65
- mzed_apply_p_right
 - permutation.h, 65
- mzed_apply_p_right_trans
 - permutation.h, 65
- mzed_cling
 - Constructions, 5
- mzed_cmp
 - mzed.h, 60
- mzed_col_swap
 - Operations on rows, 15
- mzed_col_swap_in_rows
 - Operations on rows, 15
- mzed_concat
 - Constructions, 5
- mzed_copy
 - Assignment and basic manipulation, 10
- mzed_copy_row
 - Operations on rows, 15
- mzed_echelonize
 - Echelon forms, 36
- mzed_echelonize_naive
 - Echelon forms, 37
- mzed_echelonize_newton_john
 - Echelon forms, 37
- mzed_echelonize_ple
 - Echelon forms, 37
- mzed_first_zero_row
 - Operations on rows, 15
- mzed_free
 - Constructions, 6
- mzed_free_window
 - Constructions, 6
- mzed_init
 - Constructions, 6
- mzed_init_window
 - Constructions, 6
- mzed_invert_newton_john
 - newton_john.h, 62
- mzed_is_zero
 - mzed.h, 61
- mzed_make_table
 - newton_john.h, 63
- mzed_mul
 - Multiplication, 31
- mzed_mul_karatsuba
 - conversion.h, 49
- mzed_mul_naive
 - Multiplication, 31
- mzed_mul_newton_john
 - Multiplication, 32
- mzed_mul_scalar
 - Multiplication, 32
- mzed_mul_strassen
 - Multiplication, 32

- mzed_ple
 - PLE and PLUQ decomposition, 35
- mzed_ple_naive
 - PLE and PLUQ decomposition, 35
- mzed_print
 - String conversions and I/O, 19
- mzed_process_rows
 - Operations on rows, 15
- mzed_process_rows2
 - Operations on rows, 16
- mzed_process_rows3
 - Operations on rows, 16
- mzed_process_rows4
 - Operations on rows, 16
- mzed_process_rows5
 - Operations on rows, 16
- mzed_process_rows6
 - Operations on rows, 17
- mzed_randomize
 - Assignment and basic manipulation, 10
- mzed_read_elem
 - Assignment and basic manipulation, 10
- mzed_rescale_row
 - Operations on rows, 17
- mzed_row_add
 - Operations on rows, 17
- mzed_row_clear_offset
 - Operations on rows, 18
- mzed_row_swap
 - Operations on rows, 18
- mzed_set_ui
 - Assignment and basic manipulation, 10
- mzed_slice
 - Constructions, 7
- mzed_stack
 - Constructions, 7
- mzed_sub
 - Addition and subtraction, 21
- mzed_submatrix
 - Constructions, 7
- mzed_t, 44
 - finite_field, 45
 - ncols, 45
 - nrows, 45
 - w, 45
 - x, 45
- mzed_trsm_lower_left
 - Triangular matrices, 40
- mzed_trsm_lower_left_naive
 - Triangular matrices, 40
- mzed_trsm_lower_left_newton_john
 - Triangular matrices, 40
- mzed_trsm_upper_left
 - Triangular matrices, 41
- mzed_trsm_upper_left_naive
 - Triangular matrices, 41
- mzed_trsm_upper_left_newton_john
 - Triangular matrices, 41
- mzed_write_elem
 - Assignment and basic manipulation, 11
- ncols
 - mzd_poly_t, 43
 - mzd_slice_t, 44
 - mzed_t, 45
- newton_john.h, 61
 - mzed_invert_newton_john, 62
 - mzed_make_table, 63
 - njt_mzed_free, 63
 - njt_mzed_init, 63
- njt_mzed_free
 - newton_john.h, 63
- njt_mzed_init
 - newton_john.h, 63
- njt_mzed_t, 45
 - L, 45
 - M, 46
 - T, 46
- nrows
 - mzd_poly_t, 43
 - mzd_slice_t, 44
 - mzed_t, 45
- Operations on rows, 12
 - mzd_slice_col_swap, 13
 - mzd_slice_copy_row, 13
 - mzd_slice_rescale_row, 13
 - mzd_slice_row_add, 13
 - mzd_slice_row_clear_offset, 14
 - mzd_slice_row_swap, 14
 - mzed_add_multiple_of_row, 14
 - mzed_add_row, 14
 - mzed_col_swap, 15
 - mzed_col_swap_in_rows, 15
 - mzed_copy_row, 15
 - mzed_first_zero_row, 15
 - mzed_process_rows, 15
 - mzed_process_rows2, 16
 - mzed_process_rows3, 16
 - mzed_process_rows4, 16
 - mzed_process_rows5, 16
 - mzed_process_rows6, 17
 - mzed_rescale_row, 17
 - mzed_row_add, 17
 - mzed_row_clear_offset, 18
 - mzed_row_swap, 18
- PLE and PLUQ decomposition, 33
 - _mzd_slice_ple, 33

- [_mzd_slice_pluq](#), [33](#)
 - [_mzed_ple](#), [34](#)
 - [mzd_slice_ple](#), [34](#)
 - [mzd_slice_pluq](#), [34](#)
 - [mzed_ple](#), [35](#)
 - [mzed_ple_naive](#), [35](#)
- [permutation.h](#), [63](#)
 - [mzd_slice_apply_p_left](#), [64](#)
 - [mzd_slice_apply_p_left_trans](#), [64](#)
 - [mzd_slice_apply_p_right](#), [64](#)
 - [mzd_slice_apply_p_right_trans](#), [64](#)
 - [mzd_slice_apply_p_right_trans_tri](#), [64](#)
 - [mzed_apply_p_left](#), [65](#)
 - [mzed_apply_p_left_trans](#), [65](#)
 - [mzed_apply_p_right](#), [65](#)
 - [mzed_apply_p_right_trans](#), [65](#)
- [ple.h](#), [66](#)
- [pow_gen](#)
 - [gf2e_struct](#), [42](#)
- [red](#)
 - [gf2e_struct](#), [42](#)
- [strassen.h](#), [66](#)
- [String conversions and I/O](#), [19](#)
 - [mzd_slice_print](#), [19](#)
 - [mzed_print](#), [19](#)
- [T](#)
 - [njt_mzed_t](#), [46](#)
- [Triangular matrices](#), [38](#)
 - [_mzd_slice_trsm_lower_left](#), [38](#)
 - [_mzd_slice_trsm_upper_left](#), [39](#)
 - [_mzed_trsm_lower_left](#), [39](#)
 - [_mzed_trsm_upper_left](#), [39](#)
 - [mzd_slice_trsm_lower_left](#), [39](#)
 - [mzd_slice_trsm_lower_left_naive](#), [39](#)
 - [mzd_slice_trsm_lower_left_newton_john](#), [39](#)
 - [mzd_slice_trsm_upper_left](#), [40](#)
 - [mzd_slice_trsm_upper_left_naive](#), [40](#)
 - [mzd_slice_trsm_upper_left_newton_john](#), [40](#)
 - [mzed_trsm_lower_left](#), [40](#)
 - [mzed_trsm_lower_left_naive](#), [40](#)
 - [mzed_trsm_lower_left_newton_john](#), [40](#)
 - [mzed_trsm_upper_left](#), [41](#)
 - [mzed_trsm_upper_left_naive](#), [41](#)
 - [mzed_trsm_upper_left_newton_john](#), [41](#)
- [trsm.h](#), [67](#)
 - [MZED_TRSM_CUTOFF](#), [68](#)
- [Type definitions](#), [2](#)
- [w](#)
 - [mzed_t](#), [45](#)
- [x](#)