

smallantimagmas

**A library of antiassociative magmas of
small order**

0.6.0

5 July 2026

**Kamil Zabielski
Ryszard Mazurek**

Kamil Zabielski

Address: Department of Theoretical Computer Science
Białystok University of Technology
Wiejska 45A
15-325 Białystok
Poland

Ryszard Mazurek

Address: Department of Theoretical Computer Science
Białystok University of Technology
Wiejska 45A
15-325 Białystok
Poland

Copyright

© 2024 by Kamil Zabielski

smallantimagmas package is free software; you can redistribute it and/or modify it under the terms of the [GNU General Public License](#) as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

Acknowledgements

We appreciate very much all past and future comments, suggestions and contributions to this package and its documentation provided by **GAP** users and developers.

Contents

1	smallantimagmas automatic generated documentation	4
1.1	smallantimagmas automatic generated documentation of properties	4
1.2	smallantimagmas automatic generated documentation of attributes	7
1.3	smallantimagmas automatic generated documentation of global functions	9
1.4	smallantimagmas automatic generated documentation of methods	13
Index		14

Chapter 1

smallantimagmas automatic generated documentation

1.1 smallantimagmas automatic generated documentation of properties

1.1.1 IsAntiassociative (for IsMagma)

▷ `IsAntiassociative( $M$ )` (property)

Returns: true or false

identifies whether magma M is antiassociative.

Example

```
gap> IsAntiassociative(OneSmallGroup(16));
false
gap> IsAntiassociative(OneSmallAntimagma(2));
true
gap> IsAntiassociative(OneSmallAntimagma(3));
true
```

1.1.2 IsLeftCyclic (for IsMagma)

▷ `IsLeftCyclic( $M$ )` (property)

Returns: true or false

if magma is left cyclic m .

1.1.3 IsRightCyclic (for IsMagma)

▷ `IsRightCyclic( $M$ )` (property)

Returns: true or false

if magma is left cyclic m .

1.1.4 IsLeftDistributive (for IsMagma)

▷ `IsLeftDistributive( $M$ )` (property)

Returns: true or false

if magma is left distributive m .

Example

```
gap> List(AllSmallAntimagnas(3), M -> IsLeftDistributive(M));
[ true, false, false, false, false, false, false, false, true ]
```

1.1.5 IsRightDistributive (for IsMagma)

▷ IsRightDistributive(M) (property)

Returns: true or false
if magma is right distributive m .

Example

```
gap> List(AllSmallAntimagnas(3), M -> IsRightDistributive(M));
[ false, false, false, false, true, false, false, false, true, false ]
```

1.1.6 IsLeftCancellative (for IsMagma)

▷ IsLeftCancellative(M) (property)

Returns: true or false
if magma is left cancellative m .

Example

```
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> Display(MultiplicationTable(M));
[ [ 2, 1 ],
  [ 2, 1 ] ]
gap> IsRightCancellative(M);
false
gap> IsLeftCancellative(M);
true
gap> List(AllSmallAntimagnas(2), M -> IsLeftCancellative(M));
[ true, false ]
```

1.1.7 IsRightCancellative (for IsMagma)

▷ IsRightCancellative(M) (property)

Returns: true or false
if magma is right cancellative m .

Example

```
gap> List(AllSmallAntimagnas(2), M -> IsRightCancellative(M));
[ false, true ]
```

1.1.8 IsCancellative (for IsMagma)

▷ IsCancellative(M) (property)

Returns: true or false
if magma is cancellative m .

Example

```
gap> List(AllSmallAntimagnas(2), M -> IsCancellative(M));
[ false, false ]
```

1.1.9 IsLeftFPFInducted (for IsMagma)

▷ IsLeftFPFInducted(M) (property)

Returns: true or false

is a left-hand sided fixed-point free inducted m .

Example

```
gap> Display(MultiplicationTable(SmallAntimagma(2, 2)));
[ [ 2, 2 ],
  [ 1, 1 ] ]
gap> IsLeftFPFInducted(SmallAntimagma(2, 2));
true
```

1.1.10 IsRightFPFInducted (for IsMagma)

▷ IsRightFPFInducted(M) (property)

Returns: true or false

is a right-hand sided fixed-point free inducted m .

Example

```
gap> Display(MultiplicationTable(SmallAntimagma(2, 1)));
[ [ 2, 1 ],
  [ 2, 1 ] ]
gap> IsRightFPFInducted(SmallAntimagma(2, 1));
true
```

1.1.11 IsLeftDerangementInducted (for IsMagma)

▷ IsLeftDerangementInducted(M) (property)

Returns: true or false

is a left-hand sided derangement inducted m .

Example

```
gap> M := SmallAntimagma(2, 2);
<magma with 2 generators>
gap> IsLeftFPFInducted(M);
true
gap> IsRightFPFInducted(M);
false
gap> IsRightDerangementInducted(M);
false
```

1.1.12 IsRightDerangementInducted (for IsMagma)

▷ IsRightDerangementInducted(M) (property)

Returns: true or false

is a right-hand sided derangement inducted m .

Example

```
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> IsLeftFPFInducted(M);
false
```

```
gap> IsRightFPFInducted(M);
true
gap> IsRightDerangementInducted(M);
true
```

1.1.13 IsLeftAlternative (for IsMagma)

- ▷ IsLeftAlternative(M) (property)
Returns: true or false
 is a left-alternative magma M .

Example

1.1.14 IsRightAlternative (for IsMagma)

- ▷ IsRightAlternative(M) (property)
Returns: true or false
 is a right-alternative magma M .

Example

1.2 smallantimagmas automatic generated documentation of attributes

1.2.1 AssociativityIndex (for IsMagma)

- ▷ AssociativityIndex(M) (attribute)
 identifies associativity index of M .

Example

```
gap> OneSmallAntimagma(2);
<magma with 2 generators>
gap> AssociativityIndex(OneSmallAntimagma(2));
0
gap> OneSmallGroup(4);
<pc group of size 4 with 2 generators>
gap> AssociativityIndex(OneSmallGroup(4));
64
gap> AssociativityIndex(OneSmallGroup(4)) = 4 ^ 3;
true
```

1.2.2 DiagonalOfMultiplicationTable (for IsMagma)

- ▷ DiagonalOfMultiplicationTable(M) (attribute)
 computes diagonal of multiplication table of M .

Example

```
gap> List(AllSmallAntimagmas(3), M -> DiagonalOfMultiplicationTable((M)));
[ [ 2, 1, 1 ], [ 2, 1, 1 ],
  [ 2, 3, 2 ], [ 2, 1, 1 ],
```

```
[ [ 2, 1, 1 ], [ 2, 1, 2 ],
  [ 2, 3, 2 ], [ 2, 1, 2 ],
  [ 2, 3, 1 ], [ 2, 3, 1 ]
]
```

1.2.3 CommutativityIndex (for IsMagma)

▷ `CommutativityIndex( $M$ )` (attribute)

identifies commutativity index of M .

Example

1.2.4 AnticommutativityIndex (for IsMagma)

▷ `AnticommutativityIndex( $M$ )` (attribute)

calculates anticommutativity index of M .

Example

1.2.5 SquaresIndex (for IsMagma)

▷ `SquaresIndex( $M$ )` (attribute)

computes squares index of M so the order of $\{m^2 | m \in M\}$.

Example

```
gap> List(AllSmallAntimagnas(2), M -> List(M, m -> m * m));
[ [ m2, m1 ], [ m2, m1 ] ]
gap> List(AllSmallAntimagnas(2), M -> SquaresIndex(M));
[ 2, 2 ]
gap> List(AllSmallAntimagnas(3), M -> SquaresIndex(M));
[ 2, 2, 2, 2, 2, 2, 2, 2, 3, 3 ]
```

1.2.6 IdSmallAntimagma (for IsMagma)

▷ `IdSmallAntimagma( $M$ )` (attribute)

identifies class of antiassociative magma M .

Example

```
gap> IsAntiassociative(OneSmallGroup(16));
false
gap> IsAntiassociative(OneSmallAntimagma(2));
true
gap> IsAntiassociative(OneSmallAntimagma(3));
true
```

1.2.7 LeftOrder (for IsExtLElement)

▷ `LeftOrder([m])` (attribute)

returns a left order of element m .

1.2.8 RightOrder (for IsExtRElement)

▷ `RightOrder([m])` (attribute)

returns a right order of element m .

1.2.9 LeftOrdersOfElements (for IsMagma)

▷ `LeftOrdersOfElements([m])` (attribute)

returns a left order of element m .

1.2.10 RightOrdersOfElements (for IsMagma)

▷ `RightOrdersOfElements([m])` (attribute)

returns a left order of element m .

1.2.11 DigraphOfDiagonal (for IsMagma)

▷ `DigraphOfDiagonal(M)` (attribute)

builds a digraph from the diagonal of M .

Example

1.3 smallantimagnas automatic generated documentation of global functions

1.3.1 AllSubmagnas

▷ `AllSubmagnas(M)` (function)

builds a collection of non-isomorphic submagnas of M .

Example

```
gap> AllSmallAntimagnas(2);
[ <magma with 2 generators>, <magma with 2 generators> ]
gap> List(AllSmallAntimagnas(2), M -> AllSubmagnas(M));
[ [ <magma with 1 generator> ], [ <magma with 1 generator> ] ]
```

1.3.2 MagmaIsomorphismInvariantsMatch

▷ MagmaIsomorphismInvariantsMatch(M) (function)

computes isomorphism invariants of M .

1.3.3 IsMagmaIsomorphic

▷ IsMagmaIsomorphic(M, N) (function)

identifies whether magmas M, N are isomorphic.

Example

```
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> N := SmallAntimagma(2, 2);
<magma with 2 generators>
gap> T := MagmaByMultiplicationTable([[2, 1], [2, 1]]);
<magma with 2 generators>
gap> IsMagmaIsomorphic(M, M);
true
gap> IsMagmaIsomorphic(M, T);
true
gap> IsMagmaIsomorphic(M, N);
false
```

1.3.4 IsMagmaAntiisomorphic

▷ IsMagmaAntiisomorphic($[M, N]$) (function)

identifies whether magmas M, N are antiisomorphic.

Example

```
gap> N := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> N := SmallAntimagma(2, 2);
<magma with 2 generators>
gap> IsMagmaAntiisomorphic(M, M);
false
gap> IsMagmaAntiisomorphic(M, N);
true
gap> IsMagmaAntiisomorphic(M, TransposedMagma(M));
true
```

1.3.5 TransposedMagma

▷ TransposedMagma($[M]$) (function)

generates transposed magma M .

Example

```

gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> IsMagmaAntiisomorphic(M, TransposedMagma(M));
true
gap> IsMagmaIsomorphic(M, TransposedMagma(TransposedMagma(M)));
true
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> Display(MultiplicationTable(M));
[ [ 2, 1 ],
  [ 2, 1 ] ]
gap> Display(MultiplicationTable(TransposedMagma(M)));
[ [ 2, 2 ],
  [ 1, 1 ] ]

```

1.3.6 LeftPower

▷ LeftPower($[m, k]$) (function)

returns a left k -power of element m .

1.3.7 RightPower

▷ RightPower($[m, k]$) (function)

returns a right k -power of element m .

1.3.8 AllSmallAntimagmas

▷ AllSmallAntimagmas(n) (function)

returns all antiassociative magmas of specified size n (a number)

Example

```

gap> AllSmallAntimagmas(2);
[ <magma with 2 generators>, <magma with 2 generators> ]
gap> AllSmallAntimagmas(3);
[
  <magma with 3 generators>, <magma with 3 generators>, <magma with 3 generators>,
  <magma with 3 generators>, <magma with 3 generators>, <magma with 3 generators>,
  <magma with 3 generators>, <magma with 3 generators>,
  <magma with 3 generators>, <magma with 3 generators>
]

```

1.3.9 NrSmallAntimagmas

▷ NrSmallAntimagmas(n) (function)

counts number of antiassociative magmas of specified size n (a number).

Example

```
gap> NrSmallAntimagnas(2);
2
gap> NrSmallAntimagnas(3);
10
gap> NrSmallAntimagnas(4);
17780
```

1.3.10 SmallAntimagma

▷ `SmallAntimagma([n, i])` (function)

returns antiassociative magma of id $[n, i]$.

Example

```
gap> SmallAntimagma(2, 1);
<magma with 2 generators>
gap> SmallAntimagma(4, 5);
<magma with 4 generators>
gap> SmallAntimagma([4, 5]);
<magma with 4 generators>
```

1.3.11 OneSmallAntimagma

▷ `OneSmallAntimagma(n)` (function)

returns a random antiassociative magma of size n .

Example

```
gap> OneSmallAntimagma(2);
<magma with 2 generators>

gap> OneSmallAntimagma(3);
<magma with 3 generators>
```

1.3.12 ReallyAllSmallAntimagnas

▷ `ReallyAllSmallAntimagnas(n)` (function)

returns really-all antiassociative magnas, isomorphic, of specified size n (a number)

Example

```
gap> ReallyAllSmallAntimagnas(2);
[ <magma with 2 generators>, <magma with 2 generators> ]
```

1.3.13 ReallyNrSmallAntimagnas

▷ `ReallyNrSmallAntimagnas(n)` (function)

counts number of antiassociative magnas of specified size n (a number)

Example

```
gap> ReallyNrSmallAntimagmas(3);
52
```

1.4 smallantimagmas automatic generated documentation of methods

1.4.1 MagmaIsomorphism (for IsMagma, IsMagma)

▷ MagmaIsomorphism(M , N) (operation)

computes an isomorphism between magmas M , N .

Example

```
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> N := MagmaByMultiplicationTable([[2, 1], [2, 1]]);
<magma with 2 generators>
gap> MagmaIsomorphism(M, N);
<general mapping: Domain([ m1, m2 ]) -> Domain([ m1, m2 ]) >
```

1.4.2 MagmaAntiisomorphism (for IsMagma, IsMagma)

▷ MagmaAntiisomorphism(M , N) (operation)

creates an antiisomorphism between magmas M , N .

Example

```
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> N := SmallAntimagma(2, 2);
<magma with 2 generators>
gap> MagmaAntiisomorphism(M, N);
<mapping: Domain([ m1, m2 ]) -> Domain([ m1, m2 ]) >
```

Index

AllSmallAntimagmas, [11](#)
AllSubmagmas, [9](#)
AnticommutativityIndex
 for IsMagma, [8](#)
AssociativityIndex
 for IsMagma, [7](#)

CommutativityIndex
 for IsMagma, [8](#)

DiagonalOfMultiplicationTable
 for IsMagma, [7](#)
DigraphOfDiagonal
 for IsMagma, [9](#)

IdSmallAntimagma
 for IsMagma, [8](#)
IsAntiassociative
 for IsMagma, [4](#)
IsCancellative
 for IsMagma, [5](#)
IsLeftAlternative
 for IsMagma, [7](#)
IsLeftCancellative
 for IsMagma, [5](#)
IsLeftCyclic
 for IsMagma, [4](#)
IsLeftDerangementInducted
 for IsMagma, [6](#)
IsLeftDistributive
 for IsMagma, [4](#)
IsLeftFPFInducted
 for IsMagma, [6](#)
IsMagmaAntiisomorphic, [10](#)
IsMagmaIsomorphic, [10](#)
IsRightAlternative
 for IsMagma, [7](#)
IsRightCancellative
 for IsMagma, [5](#)
IsRightCyclic
 for IsMagma, [4](#)
IsRightDerangementInducted
 for IsMagma, [6](#)
IsRightDistributive
 for IsMagma, [5](#)
IsRightFPFInducted
 for IsMagma, [6](#)

LeftOrder
 for IsExtLElement, [9](#)
LeftOrdersOfElements
 for IsMagma, [9](#)
LeftPower, [11](#)
License, [2](#)

MagmaAntiisomorphism
 for IsMagma, IsMagma, [13](#)
MagmaIsomorphism
 for IsMagma, IsMagma, [13](#)
MagmaIsomorphismInvariantsMatch, [10](#)

NrSmallAntimagmas, [11](#)

OneSmallAntimagma, [12](#)

ReallyAllSmallAntimagmas, [12](#)
ReallyNrSmallAntimagmas, [12](#)
RightOrder
 for IsExtRElement, [9](#)
RightOrdersOfElements
 for IsMagma, [9](#)
RightPower, [11](#)

SmallAntimagma, [12](#)
SquaresIndex
 for IsMagma, [8](#)

TransposedMagma, [10](#)